Stress-testing Road Networks and Access to Medical Care

Hannah Schuster^{*a,b,*,1*}, Axel Polleres^{*a,b*} and Johannes Wachs^{*c,d,a,**}

^aComplexity Science Hub Vienna, Josefstädterstraße, Vienna, AT-1080, Austria

^bVienna University of Economics and Business, Welthandelsplatz, Vienna, AT-1020, Austria

^cCorvinus University of Budapest, Fővám Tér 8, Budapest, 1093, Hungary

^d Centre for Economic and Regional Studies, Eötvös Loránd Research Network, Tóth Kálmán u. 4., Budapest, 1097, Hungary

ARTICLE INFO

Keywords: arXiv:2307.02250v1 [cs.SI] 5 Jul 202 Road networks Health Care Stress-test Simulation

ABSTRACT

This research studies how populations depend on road networks for access to health care during crises or natural disasters. So far, most researchers rather studied the accessibility of the whole network or the cost of network disruptions in general, rather than as a function of the accessibility of specific priority destinations like hospitals. Even short delays in accessing healthcare can have significant adverse consequences. We carry out a comprehensive stress test of the entire Austrian road network from this perspective. We simplify the whole network into one consisting of what we call accessibility corridors, deleting single corridors to evaluate the change in accessibility of populations to healthcare. The data created by our stress test was used to generate an importance ranking of the corridors. The findings suggest that certain road segments and corridors are orders of magnitude more important in terms of access to hospitals than the typical one. Our method also highlights vulnerable municipalities and hospitals who may experience demand surges as populations are cut off from their usual nearest hospitals. Even though the skewed importance of some corridors highlights vulnerabilities, they provide policymakers with a clear agenda.

1. Introduction

Our dependence on road networks to access emergency medical care increases in two important ways during crises. Crisis events, such as natural disasters, can create increased demands for access to medical services by causing injuries directly. Additionally, these can also disrupt the functionality of these networks themselves, increasing the time it takes to get to a hospital. In acute cases, we know that delays can cause markedly worse medical outcomes for patients [Murata and Matsuda, 2013, Jena et al., 2017]. As climate change increases the frequency of severe weather events [Mukherji et al., 2023], which can extensively disrupt road networks, we need to better understand not only the abstract resilience of infrastructure such as road networks [Antoniou and Tsompa, 2008] but also the specific weaknesses of these systems in terms of access to medical care.

Indeed, we can expect such weaknesses in road networks: especially in geographically rugged terrain, transportation infrastructure is expensive and highly constrained by physical barriers [Rodrigue et al., 2020]. Road networks are rightfully built with cost efficiency as a priority alongside robustness to periodic maintenance and disturbances. At the same time, these growing networks, like other complex systems, are known to be highly vulnerable to unanticipated shocks [Doyle, 2002]. Much like the banking sector, in which an unexpected financial insolvency can cause cascades of bankruptcies [Battiston et al., 2016, Diem et al., 2020], local problems in road networks impact transportation through the whole system [Hackl, 2019, Goldbeck et al., 2019]. Hospitals also face critical "tipping-points" - above a certain capacity they deliver significantly worse care Kuntz et al. [2015]. Likewise, macro-scale medical care systems can also break down in the face of unexpected shocks [Lo Sardo et al., 2019, Kaleta et al., 2022]. Policymakers in all three domains: finance, transport infrastructure, and medical care are increasingly turning to stress tests to analyze their systems and pinpoint weaknesses.

Yet to date, little work has been done on how stresses and problems in one system can impact provision of services in another. Whatever the cause of a disruption, the complexity of these networks makes it difficult to predict the effect of one disruption on the functioning of the whole system. Given the significant potential coupling of risks in road transportation networks and access to and provision of medical care, we propose to develop a suitable stress test to examine how road network disruptions impact access to medical care. The aim of such a stress test is to highlight

^{*} The authors acknowledge support from an Austrian Applied Research Agency (FFG) grant: CRISP (FFG No 887554).

[🖄] schuster@csh.ac.at (H. Schuster); johannes.wachs@uni-corvinus.hu (J. Wachs)

ORCID(s): xx (H. Schuster)

critical road segments or corridors that provide access to medical care, population centers at risk of being cut off from care, and hospitals that may see sudden surges in demand during crises.

We implement this stress test by applying simulation analysis to data on road and healthcare infrastructure in Austria. Simulation analysis has proven an effective tool in modeling relative risks and the importance of components of complex systems [Liu et al., 2022, Hackl et al., 2018, van Ginkel et al., 2022]. Elements of these systems highlighted by stress tests are natural candidates for resources and attention from planners.

Our stress test of road networks and their provision of access to medical care presents three novel aspects. First, we develop a measure to quantify access from population centers to medical care. Most quantitative work on the resilience of transportation systems to date focuses on the impact of disruptions by determining the cost of disruption or by measuring the change of accessibility of the whole system during specific scenarios. However, during a disaster, changes in global accessibility or costs may be of minor concern compared to the specifics of which roads are used in the provision of essential services like healthcare or fire protection. We know that small differences in travel time to emergency care can have a significant impact on mortality and other patient outcomes [Murata and Matsuda, 2013]. To this end, we modify an existing measure of accessibility in road networks [Martín et al., 2021] in order to classify the importance of links in a network relating to the accessibility of municipalities to the closest hospitals.

A second challenge in stress testing the resilience of road networks at the scale of a whole country is their size, which can make an exhaustive calculation and comparison of outages and their consequences intractable. We, therefore, introduce and stress test a coarse-grained simplification of the road system: we merge road segments connecting municipalities to create a backbone representation of the Austrian road network. We can stress test this network more extensively and show that derived insights can be transferred to the more realistic fine-grained system.

A third contribution of our approach is that we quantify the impact of our stress tests along three orthogonal dimensions. We measure how road network disruptions limit people's access to hospitals, suggesting vulnerability of population centers. We quantify road importance by observing the effects of their disruption. Finally, we measure the vulnerability of hospitals to sudden surges in the population they are the first point of care for. Thus our framework provides multi-level insight. We note that our approach can be applied and generalised to both other countries (depending on data availability) or to the provision of other services in crisis situations (for instance, firefighting facilities).

In the remainder of this paper, we first review the related literature on road network resilience and access to emergency medical care (Section 2). We then introduce the case of the Austrian road network and relevant datasets, and describe the methods and measures used to study (Section 3). We present and interpret the results of our stress tests in Section 4. Finally, we conclude by discussing our method, including its limitations and avenues for future work in Section 5.

2. Literature Review

During crisis events impacting entire regions, the accessibility of medical care is crucial, given its potential to influence patient outcomes. Indeed, there is ample evidence of a direct effect of the travel distance to a hospital and the mortality of patients. A study using a national database in Japan concluded that the ambulance distance to hospitals significantly correlates with macro-regional mortality risks for particula acute diseases such as acute myocardial infarction and brain infarction [Murata and Matsuda, 2013]. Consequently, also Planned road closures and infrastructure disruptions result in worse mortality outcomes: for instance, previous work found a sharp increase in acute myocardial infarction or cardiac arrest hospitalizations among Medicare beneficiaries in 11 U.S. cities during major marathons [Jena et al., 2017].

In summary, the accessibility of emergency medical care depends crucially on road networks, which are also especially vulnerable to environmental perturbations such as extreme weather events [Bíl et al., 2015]. Therefore, as numerous studies have shown that events like heatwaves, heavy rainfall, droughts, and tropical weather cyclones have become more frequent and intense globally since the 1950s [Mukherji et al., 2023], the vulnerability of road networks is likely to increase. In addition, the problem of transportation networks and accessibility is especially salient in geographic areas with rugged terrain [Rodrigue et al., 2020] (as we face it for instance in alpine regions in Austria), since such conditions limit possible cost-efficient redundancies that would make such networks more robust.

More generally, growing systems like road networks are known to be vulnerable to unanticipated shocks [Doyle, 2002]. Indeed, there is a whole literature analyzing the resilience of networks that tend to function well in "normal" times but can fail catastrophically during unexpected disruptions. Researchers have begun to stress test these systems

to analyze their weak points, where simulation analysis has demonstrated its efficacy in modeling relative risks and the importance of components of complex systems [Liu et al., 2022, Mattsson and Jenelius, 2015]. Particular applications of these methods include financial markets [Battiston et al., 2016], food suppliers [Schueller et al., 2022], regional economies [Tóth et al., 2022], ride-sharing systems [Bokányi and Hannák, 2020], and software systems [Schueller and Wachs, 2022]. Here, the resilience of a network is generally determined by monitoring the response of systems to the cumulative elimination of sections according to random order, deterministic order of criticality, and deterministic order in areas at high risk [Martín et al., 2021]. Insights gained through stress tests can be used to help guide planning resources and areas of attention, in order to improve the robustness of diverse networks while their functionality remains unchanged [Schneider et al., 2011, Lin et al., 2023].

Methodological approaches to measuring resilience of road networks, in particular, vary from quantifying the travel cost of a disruption [Jenelius et al., 2006, Xie et al., 2023] to quantifying the risk to the overall network [Hackl et al., 2018]. The healthcare system has specifically been studied from this perspective, especially since the Covid-19 Pandemic: the additional stress of the pandemic shed light on the various problems of healthcare systems. Stress tests of hospital networks and networks of doctors have demonstrated that macro-scale medical care systems can also breakdown in the face of unexpected shocks [Lo Sardo et al., 2019, Kaleta et al., 2022], manifesting, for instance, in a sudden surge in patients which may overwhelm individual hospitals Kuntz et al. [2015].

Despite the apparent interest, little work has been done to understand how the infrastructure that provides access to care is vulnerable to shocks. Therefore in the present paper, we concentrate on how road closures change patient flows and volumes to hospitals. While previous work has studied how transport infrastructure ensures the provision of essential goods to communities [Wiśniewski et al., 2020, Anderson et al., 2022], to the best of our knowledge, access to healthcare has not been considered from this perspective thus far.

3. Data and Methods

We now outline the data and methods we will use to stress test the Austrian road system. Our aim is to evaluate the importance of specific parts of the network in terms of the population's access to healthcare at hospitals. We first describe how we create an abstracted network representation of the road system. We call the edges or links in this resulting network *corridors* and define measures of corridor importance. We then outline the methodology of two kinds of stress tests we will apply to this network. Finally, we describe how to measure the impact of these tests on hospitals.

3.1. Constructing a network of corridors

There are many possible ways to represent a nationwide transport network. Our goal is to create a representation of the Austrian road network that is simplified enough so that extensive stress tests are computationally feasible and still fine-grained enough to capture important details. We begin with data from GIP (Graphenintegrations-Plattform)¹ - an extensive open data source of Austrian transportation infrastructure segments, from hiking trails to highways and railroads. As we are interested in emergency response, we focus on roads that can be accessed via automobile.

We first create a network of all roads, in which nodes are intersections of road segments and edges are roads. This is a very fine-grained representation of the system: with close to 1.5 million links and about 1.3 million nodes. Obviously, such a fine-grained representation presents a computational problem for network analysis and simulation: as we aim to simulate the removal of road segments and measure the impact on shortest paths to hospitals many times over, we therefore derive a coarse-grained abstraction of this network to keep shortest path calculations tractable while maintaining its core features. In the derived network nodes are *municipalities* connected by an edge if there is a road segment ending in both municipalities. In other words: two municipalities are connected in the network if there is a direct path between them. We call these edges **accessibility corridors** or corridors for short, as they represent an abstraction of road connections between municipalities. We also record how many real-world roads between the municipalities are combined in a single corridor. This information is later used in the analysis section to emphasize the importance of the corridor in a real-world context. The resulting network representation of Austria is visualized in Figure 1, with municipalities hosting a hospital highlighted.

¹https://www.gip.gv.at/



Figure 1: A coarse-grained representation of the Austrian road transportation system as a network. Nodes are municipalities and edges are accessibility corridors connecting them. Municipalities are colored and marked with a green cross if they contain a hospital.

3.2. Measures of corridor importance

Given our network representation of the Austrian road transportation network, we would like to quantify the importance of specific access corridors. The literature presents several ways to measure the importance of corridors and the impact of their closure on the movement of people, in general [Jenelius et al., 2006, Xie et al., 2023, Hackl et al., 2018, Wiśniewski et al., 2020, Anderson et al., 2022]. Our research introduces a new method by taking the accessibility of critical infrastructure into account when measuring importance. Specifically, we observe the impact of corridor closures on the accessibility of a municipality to its *closest* hospital. Whether a corridor's closure causes a population to take a longer, indirect path to a hospital or forces them to go to a different hospital, we infer corridor importance from increases in travel times upon their removal weighted by the impacted population numbers. The changes in the accessibility measurement are used to implement a ranking of corridors, henceforth referred to as the Accessibility Corridor Impact Score (ACIS).

The ACIS can be used to assess the impact of the initial stress test on the accessibility corridor network by estimating how a deletion impacts the distance to the closest hospital weighted by the impacted people. To determine the ACIS, we start by calculating the integral of the cumulative population with respect to the distance for the baseline case and the stress-tested situation, using the trapezoid rule. Subsequently, the ACIS can be determined by computing the difference between the baseline integral and the stressed integral, which can be expressed by the following formula:

$$ACIS = \int_0^{dist_{max}} P_{base}(x) \, dx - \int_0^{dist_{max}} P_{stress}(x) \, dx,\tag{1}$$

where $dist_{max}$ stands for the maximum distance between a hospital and a municipality in the original situation and the population functions $P_{base}(x)$ and $P_{stress}(x)$ characterize how many people have a hospital reachable within x km.

Alternative Measures As an alternative to the Accessibility Corridor Impact Score we also calculated a measure based on Martín et al. [2021], where the authors introduce a measurement of a municipality's access to a full network of destinations based on the population distribution and the minimal distance to each node in the network. In our case, we modify this measure by switching the target variable to its closest hospital instead of all the other municipalities in the network given our focus on access to healthcare. The following equation represents our version of the accessibility

measure, which we call the Hospital Accessibility of a municipality (HA_m) :

$$HA_m = max_{h \in H} \left(\frac{P_m}{d(m,h)}\right),\tag{2}$$

where we measure the accessibility HA_m of a municipality *m* to the closest hospital by finding the maximum of the ratio of the population of the municipality P_m divided by its distance *d* to hospitals *h* in Austria. The municipality's population is included to give greater weight to those municipalities with more people because the probability of someone needing a hospital increases with increasing population.

To calculate an overall, aggregated accessibility measure for the entire country, which we call its Hospital Accessibility HA, we use the following formula:

$$HA = \sum_{m \in M \setminus H} \frac{(HA_m * P_m)}{P_{M \setminus H}},$$
(3)

where we calculate the sum of HA_m over all municipalities *m* in Austria, except for municipalities with a hospital, and then normalize each summand by a population factor $\frac{P_m}{P_{M\setminus H}}$, which takes the population $P_{M\setminus H}$ of all Austrian municipalities without a hospital into account. This measure captures the overall efficiency of the corridor network in terms of how well it gets people from population centers to hospitals.

To rank the importance of the different corridors, we calculated the difference between the baseline accessibility score and the overall accessibility after stress testing the network. Specifically, if we remove corridor k, we define its impact HA(k) as follows:

$$HA(k) = \frac{HA_{baseline} - HA_{\backslash k}}{HA_{baseline}} * 100,$$
(4)

where $HA_{baseline}$ is the accessibility in the original situation and HA_{k} is the overall hospital accessibility after accessibility corridor k was deleted from the network.

As a third alternative besides the ACIS and *HA* measures of corridor importance, we also considered a popular way of ranking edges in networks called *edge betweenness centrality*. In our context, this defines the importance of a corridor as follows:

$$c_B(\text{corridor } e) = \sum_{s \in M, t \in H; d(s,t) \le 100 km} \frac{\sigma(s,t|e)}{\sigma(s,t)},$$
(5)

where the betweenness centrality c_B of a corridor e is the sum of fractions of all shortest paths between a municipality $s \in M$ and a hospital $t \in H$ that use the corridor e, divided by the number of all shortest paths between them (denoted by $\sigma(s, t)$). In plain words, this measures calculates how often corridors appear on the shortest paths between all pairs of municipalities and hospitals in the country at most 100km apart from one another.

3.3. Stress testing corridor networks

In an effort to establish a ranking of the accessibility corridors based on their importance to hospital accessibility, we conducted two distinct stress tests of the Austrian accessibility corridor network. The first kind of test tracks the reaction of the system to the deletion of a single accessibility corridor. Specifically, we remove one link from the network and calculate the accessibility of each municipality to its closest hospital post-deletion. The ranking of the corridors was based on the resulting ACIS for each deletion: the higher the ACIS score a corridor receives, the higher its ranking.

We show a concrete example of such a corridor deletion in Figure 2. On the left, we color municipalities by how long they must travel to reach a hospital when the network is functioning undisturbed. Following the removal of the focal corridor, visualized on the right, people in several municipalities must travel significantly farther to reach healthcare. This would be reflected in a large ACIS score for this corridor.

While the results of the first stress test serve as a fine approximation for the topological importance of corridors, real world events often impact roads across wider geographic areas. For instance a weather event like a snow storm could impact roads across entire regions. Even when a single corridor or road may be closed, resulting congestion may cause significant delays for travelers on nearby alternatives.

The second stress test thus introduces neighborhood outages of roads. It measures the system's functionality after the deletion of a corridor and its neighboring corridors. This idea was initially sparked by the observation that severe



Figure 2: Here we observe how the deletion of a single corridor, highlighted in the white box, significantly impacts the hospital access of the surrounding municipalities (adapted from Schuster et al. [2022]).

weather conditions often have a widespread impact across geographic space rather than being confined to a single location. To increase the potential volatility of the stress test, we first delete the focal corridor, then with a fixed probability p remove each of its immediate neighbors. This fixed probability p was chosen to simulate the decreasing severity of a weather event with increasing distance from its core, which is assumed to be at the focal corridor. In particular, we ran 100 simulations for each corridor and its neighborhood with $p \in [0.1, 0.25, 0.5, 0.75]$. In each simulation, the hospital accessibility of the network and the distance to the closest hospital for each municipality were calculated, and the same impact measures were calculated as for the single corridor removal stress test.

3.4. Measuring hospital vulnerability

While assessing the resilience of infrastructure networks and the accessibility changes caused by disturbances has been studied in previous research [Jenelius et al., 2006, Xie et al., 2023, Wiśniewski et al., 2020, Anderson et al., 2022], less attention has been paid to how transportation infrastructure disturbances impact potential flows to healthcare centers. For instance, a key road closure could greatly increase the number of people going to a specific hospital as closest point of care.

Therefore we also explored an alternative approach to measuring the impact of corridor deletions in terms of their impact on hospital catchment areas. In particular, we look for which hospitals become responsible for a significantly larger population as their closest point of care when specific corridors are closed. This allows us to measure the strain on hospitals resulting from corridor closures. To quantify this impact on hospitals, we assess how many people have to move from one hospital to another for each stress test, which can be mathematically written as:

$$P_{affected} = \sum_{M \in Change} P_M,\tag{6}$$

where we calculate the total affected Population $P_{affected}$ by summing over all $M \in Change$, which is the portion of municipalities that have a new closest hospital after the simulated deletion of a corridor, and P_M stands for the population of municipality M. From this calculation, we are also able to calculate the new number of patients per hospital. Besides this, we use the different stress test results to calculate how often a hospital experiences a changing inflow due to a corridor deletion.

Through the application of these measurements, we can better understand how hospital catchment areas change due to the alteration of the accessibility corridor network. For instance, a corridor closure may change the closest hospital for a significant number of people. The changing size of the hospital catchment area thus either causes a growth or reduction in the patient flow to specific hospitals, straining or relaxing those hospitals' capacity, respectively. By examining the effect of corridor deletions on hospital catchment areas, we can derive a map of redundancy relationships between hospitals. This map allows us to report hospitals that could be more prone to sudden patient influx during crisis events which lead to corridor closures.

4. Results

In this section, we present the results of our analyses. We first focus on the single corridor deletion stress test. We find that according to the ACIS measure, the impact of such deletions is highly heterogeneous: some corridors are

significantly more important than the average one. We show a significant correlation between the ACIS measure and the *HA* measure of corridor importance in this scenario. We investigate the relationship between corridor ACIS score and the number of roads in a corridor, finding highly important corridors containing very few roads. We also analyze changes in travel times. We then analyze the results of the corridor neighborhood stress test. Finally, we present two case studies in which hospitals are often or significantly impacted by corridor closures.

4.1. Single Corridor stress test

First, we found that most accessibility corridors closures have a low impact on the population, see Figure 3a. In this figure we plot the complementary cumulative density function (CCDF) of the Accessibility Corridor Impact Score score of each corridor. In general, the closure of any given corridor is a minor nuisance in terms of getting to a hospital. However, there are a few accessibility corridors which have a tremendous impact on the system if closed, observed in the right tail of this figure. Furthermore, the results of the neighborhood deletion stress test, see Figure 3b, suggest that locally correlated corridor closures can have an even greater impact. This is our first important result: as a few corridors are much more important than the typical one, policymakers can focus their attention on just a few parts of the (abstracted) road network. Improvements to the resilience at these key points can make a significant difference in its resilience.

100





(a) The CCDF of the Accessibility Corridor Impact Score scores under the single accessibility corridor deletion stress test. This stress test can be used to simulate the failure of a single corridor due to weather events with geographically limited impacts, i.e., avalanche or mudflow.

(b) The CCDF of the 90th percentile from 100 simulation of the Accessibility Corridor Impact Score scores of neighborhood accessibility corridor deletion stress test, with a deletion probability $p \in [10\%, 25\%, 50\%, 75\%]$ for the neighboring streets. This stress test is used to simulate a simplified weather event, where we assume that the impact on the road network decreases with increasing distance from the core located at the focal street.

Figure 3: The CCDF of the Accessibility Corridor Impact Score scores calculated from the deletion of Accessibility Corridors under different stress tests. In general, we observe that most corridors are not critical in providing access to hospitals but that a few are orders of magnitude more important.

A comprehensive representation of the simulation results using the Accessibility Corridor Impact Score (ACIS) of the single corridor stress test can be found in Figure 4. To provide context for these findings, we now interpret which corridors play a crucial role according to this first stress test. In the map, we see that the highlighted corridors seem to function as connectors to otherwise isolated dead-ends to the network or as critical connectors reducing travel time between different regions. Another category of highlighted corridors are short-cuts directly connected to a hospital.

As corridors are abstractions that bundle together any number of roads between two neighboring municipalities, we look more closely at the relationship between the ACIS ranking and the number of roads within a corridor in the inset of Figure 4. We find that there are many examples of corridors containing just a few roads and having a high ACIS. These corridors are perhaps the most important ones to focus on: they are both systemically important and contain few local redundancies. This is especially relevant when the topography of Austria is considered as many valleys in the

= 10 %



Figure 4: The top 100 most important corridors based on ACIS under the single corridor deletion stress test. Inset: the relationship between the number of roads in a corridor and its ACIS score. We observe critically important corridors containing few roads.

Alps are only connected to the rest of Austria by a single corridor. If a road like that is blocked, the access to a hospital of the municipalities in the valley is cut off.

What about the other measures of corridor importance? Under the single deletion stress test scenario, ACIS and HA(k) are highly correlated (Spearman's $\rho = 0.83$). Edge betweenness centrality on the other hand is not significantly correlated (Spearman's $\rho = 0.09$) with the ACIS measure, nor with the HA(k) measure (Spearman's $\rho = 0.098$). As edge betweenness centrality evaluates corridor importance in terms of access to multiple hospitals, we focus on the other measures as they capture access to the closest point of care.

Upon closer examination, we found that ACIS and HA(k) do deviate significantly from each other in the most important cases. If we consider the top 100 corridors according to either ranking, this correlation turns negative (Spearman's $\rho = -0.26$). This means that the two rankings significantly diverge in terms of which corridors they consider most important. In Figure 5, we plot the map of Austria with important corridors according to the HA(k)measure highlighted. We observe that the HA(k) measure tends to rank the last corridors leading directly to hospitals as the most important, while the ACIS measure tends to emphasize corridors that appear to bridge regions. Among the top 100 HA(k) ranked corridors, the average corridor contains 14 roads, while the top 100 ACIS ranked corridors contain on average only 11 roads. This suggests that the ACIS is ranking highly those corridors that bridge regions and are highly vulnerable due to their dependence on fewer road segments. In the rest of the paper, we therefore focus on the ACIS measure.

To make the analysis more concrete, we report changes in driving times experienced by people following the single deletion stress test in Figure 6a. Specifically, we examine the number of additional individuals who would need to drive at least 15, 30, or 60 minutes, assuming a tempo limit of 50km/h, following a corridor deletion. We observe that a significant number of people would have to drive more than 15 minutes following such a deletion. As before, it is worth focusing on the extreme cases: some corridors cause thousands of people to have to drive over 60 minutes to get to a hospital. We report specific examples in Table 6b: the deletion of the corridor reported in the first row, which contains a single road, causes a nearly 20-minute increase in driving time for over 10,000 people. Such delays can make a significant difference in critical care outcomes. To that end we report those corridors whose deletion increases average travel time by at least five minutes in Table 1. Such a difference has been shown to cause statistically observable higher 30-day mortality rate in critical cases, cf. Jena et al. [2017]. For example, the deletion of the corridor in the first row of this Table 1 leads to a mean increase of approximately 7 minutes for more than 40,000 people.



Figure 5: The top 100 most important corridors based on the accessibility corridor importance factor HA(k) under the single corridor deletion stress test. Inset: the relationship between the number of roads in a corridor and its HA(k) score. We observe critically important corridors containing few roads.



minutes in total to the nearest hospital.

Figure 6a: How many accessibility corridors cause Table 6b: Impact of the deletion of an accessibility corridor on the minimum through their deletion y people to drive more than x travel time sorted by affected population, including the number of real roads in an accessibility corridor.

4.2. Corridor Neighborhood stress test

We now discuss the results of our second stress test, where we simulated the deletion of corridor neighborhoods to see the network's reaction to more significant alterations. To recapitulate, the main idea of the second stress test extend the first stress by introducing local geographic correlations in road closures, reflecting for example the broader impacts of extreme weather. Besides ranking the corridor neighborhoods, we will also compare the rankings to the initial stress test to see if the same areas are impacted.

Each instance of the second stress test also focuses on a single focal corridor. It additionally considers all neighboring corridors, removing them from the system with a probability p. For each focal corridor we ran 100

Deleted Corridor		Travel Time			affected	affected	Roade	
From	То	Old	Delta	New	Population	Municipalties	TOaus	
AT41743	AT41746	18.48	7.29	25.77	42656	14	24	
AT70926	AT70921	31.33	7.89	39.19	30791	21	6	
AT70332	AT70331	25.45	6.56	32.07	27080	15	7	
AT61045	AT61053	13.98	8.8	22.78	26548	8	37	
AT70921	AT70910	34.83	6.68	41.47	26260	18	2	
AT70331	AT70350	27.01	6.5	33.57	24850	14	4	
AT70910	AT70935	36.28	6.28	42.52	24824	17	2	
AT70935	AT70923	37.58	9.53	47.13	22987	16	8	
AT70413	AT70416	17.0	7.63	24.6	21291	6	4	
AT31839	AT31818	19.58	7.82	27.38	18747	4	12	
AT61114	AT61108	23.3	9.65	32.92	18027	4	9	
AT20923	AT20913	24.25	10.45	34.7	17898	4	50	
AT10706	AT10724	37.1	6.03	43.1	17543	7	5	
AT20101	AT20402	27.3	6.18	33.45	16737	6	19	
AT40101	AT41624	13.55	6.7	20.25	16731	4	9	

Stress-testing Road Networks

Table 1

Impact of the deletion of an accessibility corridor (Top 15) on the travel time with a focus on the time difference. We include the number of roads in each accessibility corridor and the affected population and report the largest impacted populations thresholded by five minutes.

simulations for each $p \in [0.1, 0.25, 0.5, 0.75]$. This approach yields a distribution of impact scores for each corridor. For each focal corridor and p we considered the mean and the 90th percentile of the ACIS of this distribution of results.

For low values of p, i.e. 0.1, the Spearman correlation between ACIS of the single corridor deletion stress test and the neighborhood deletion stress test are high: 0.57 for the mean and 0.41 for the 90th percentile result. However, this correlation quickly drops as we consider higher likelihoods of correlated corridor failures. At p = 0.75, the correlations drop to 0.08 for the mean and 0.03 for the 90th percentile. We may conclude this implies that when corridors are failing in a larger geographic area, as is often the case, the impact on hospital access is very different from the situation in which a single corridor is removed.

Indeed, in Figure 7, we observe that the top 100 most important corridors according to the neighborhood deletion stress test are quite different from those under the single corridor deletion stress test when the deletion probability is increased. Calculating the overlap of the top 100 most impactful corridors of the single ACIS with the ACIS ranking considering a probability of 25% for neighborhood deletions shows that only 15% of the corridors are ranked in the top 100. This overlap is even lower for higher probabilities. Furthermore, it is apparent from this visualization that in many cases, important corridors are directly connected to a hospital forming small clusters, indirectly highlighting vulnerable neighborhoods within the corridor network as a whole.

4.3. Hospital vulnerability

In this section, we will study the vulnerability of hospitals based on the single corridor removal stress test. By closely examining the relations between accessibility corridor deletions and hospital catchment area shifts, we are able to derive a map of redundancies between hospitals, and to quantify which hospitals are at risk of suddenly becoming responsible for a significantly greater number of patients due to road closures. The resulting map provides detailed insight into the dynamics of patient flow between the hospitals caused by the alteration of the corridor network.

The map and scatter plot inset in Figure 8 offers a compelling portrayal of the frequency and magnitude of impacts that hospitals experience during the different stress tests. To delve deeper into the analysis, we have selected two illuminating cases that exemplify two kinds of vulnerable hospitals. Our first example, located in Kalwang, is a hospital



Figure 7: The Top 100 most important corridors based on ACIS under the neighborhood corridor deletion stress test with a deletion probability of 25% for the neighboring streets. We observe that there is a notable presence of corridors directly connected to hospitals among the Top 100.

People per Bed		Change per Bed		Accessibility Corridor		Affected
Initial	After Deletion	in %	People	Deleted Corridor	# Roads	Population
183.56	203.40	10.81	19.83	(AT41743, AT41746)	24	9 787
183.56	196.04	6.80	12.48	(AT41426, AT41402)	3	5 203
183.56	195.31	6.40	11.74	(AT40419, AT40418)	5	4 897
183.56	195.28	6.38	11.71	(AT41716, AT41743)	2	4 884
183.56	195.28	6.38	11.71	(AT41716, AT41709)	15	4 884
183.56	193.96	5.66	10.39	(AT40830, AT40808)	4	4 334
183.56	191.69	4.42	8.12	(AT41711, AT41743)	8	3 387
183.56	191.69	4.42	8.12	(AT41747, AT41711)	9	3 387
183.56	190.07	3.54	6.50	(AT41422, AT41418)	15	2 712

Table 2

The ten cases in this table exemplify the significant impact on the hospital in Ried im Innkreis, Oberösterreich, with a focus on the change of people per bed.

that is only impacted by a few specific corridor closures. However, when those corridors close, the impact is extreme: with a 250% increase in the number of people in its catchment area per bed, see Table 3. These corridors would otherwise provide access to hospitals in Rottenmann (162 beds) or Leoben (408 beds). In other words, closures of nearby corridors can lead to dramatic surges at this hospital, with a capacity of only 72 beds.

The second example, located in Ried im Innkreis, is rather potentially impacted by many corridor closures, but to a smaller degree. Over 20 different corridors can impact its catchment area, but they increase the population to bed ratio by less than 10%. In other words, this hospital will likely often see small increases in the population for which it is the first point of service. Such small increases can nevertheless be the source of significant volatility over time in hospital admittances.

Even though the latter is an extreme case where the closure of accessibility corridors blocks the way to big hospitals and puts a lot of strain on a small hospital, it shows how small changes can have big effects. Both cases show how our developed method can be used to refine the analysis and offer another perspective to the stress test.



Figure 8: Exploring the impact of corridor deletions on the hospitals in the network: comparing the probability a hospital is affected to the stress tests' impact on the hospital. In this illustration, a comparison is made between a high-probability case with a moderate impact and a low probability with a high impact.

People per Bed		Change per Bed		Accessibility Corridor		Affected
Initial	After Deletion	in %	People	Deleted Corridor	# Roads	Population
83.32	298.23	257.96	214.92	(AT61114, AT61108)	9	15 689
83.32	298.23	257.96	214.92	(AT61114, AT61120)	16	15 689
83.32	134.27	61.16	50.96	(AT61263, AT61247)	10	3 720

Table 3

The following cases exemplify the significant impact on the hospital in Kalwang, Steiermark, with a focus on the change of people per bed.

5. Conclusion and Future Research

In this paper, we show the resilience of a population's access to healthcare can be meaningfully analyzed and quantified based on stress tests of road-based transportation networks. These stress tests can provide meaningful insights into the dependencies between different systems, in this case of the transportation system and hospitals. By ranking corridors based on their importance in terms of hospital access, we can identify corridors of interest for policymakers seeking to allocate limited resources. In particular, we show that there are high impact corridors containing few roads which provide access to emergency care for many people. We also show that some hospitals are vulnerable to sudden surges of people they are responsible for.

Based on these results further investigations can be conducted, for instance by including the area around the corridors of interest. This would lead to guidelines to improve the underlying network's resilience and general access to health care. Analyzing the corridors' neighborhoods is another step from the abstract model to real-world scenarios where natural disasters impact whole regions.

Our results show that certain road segments and corridors play a pivotal role in access to hospitals in Austria. The disruption of these roads during crisis scenarios can have a significant impact on travel time to hospitals for large numbers of people. Specific municipalities are especially vulnerable to the closure of specific road corridors. Hospitals can also be affected: a road closure can change which hospital is closest for large numbers of people. The skewed importance of some corridors highlights vulnerabilities but also gives policymakers something to focus on.

Compared to previous work, we focus on the specific problem of accessibility of hospitals in our stress test, using a generated measurement as well as adapting an appropriate accessibility measure [Martín et al., 2021]. As we are

interested in hospital accessibility, which is a local network problem, this derived measure of road importance is more appropriate than a global measure such as edge betweenness centrality. Further comparison shows that the measurement generated in this paper is a better fit for our problem since the accessibility measure from [Martín et al., 2021] overemphasizes city size for our application. In the scenario described in the paper, the size of a hospital doesn't add to its attractiveness, and the focus is solely on the accessibility of medical care. If the size of the target is important to the simulation, for example, the size of a city or the number of hospital beds, an adaptation of [Martín et al., 2021] is more practical. However, in this simulation, we assume that fast access to health care is crucial and not influenced by the size of the hospital.

Our work also has policy implications for the healthcare sector. Past research has demonstrated that hospital capacity has a tipping-point in terms of care quality: when occupancy exceeds a critical level of capacity, mortality outcomes worsen significantly Kuntz et al. [2015]. Our work shows that such surges can occur due to the outcomes in another complex system. Flexible staffing and pooled capacity across hospitals, effective policies recommended in this previous work, should take into account how exogeneous shocks influencing transport networks can create surges and limit the effectiveness of these interventions.

Rather than vulnerability to specific events (i.e., floods [van Ginkel et al., 2022]), we consider abstract road closures. By coarse-graining the Austrian road network, we can run a more thorough stress test on a country-wide network. Both of these simplifications enable us to easily identify network sections of interest. More fine-grained versions of these sections can be further investigated in future work using more realistic stress tests. This would be especially tractable if policymakers wished to zoom in on a specific region or part of the country.

Our study has several limitations. Roads in different parts of the country may be more or less vulnerable to closure, given factors like local weather and altitude. Future work should consider historical weather patterns and their correlation with road closures. More realistic stress tests can be developed in this way. Some but not all of the road corridors we highlight pass through extremely rugged terrain (i.e. the Alps). Creating redundancies in this context may be very expensive. In such areas it may be more useful to create redundancies at highly impact hospitals.

Furthermore, our results show that overlaying the ACIS measurement with the number of real-world roads in a corridor can help to understand the implications of a corridor closure better. Therefore, we propose to update the introduce ACIS method by including a factor that takes the number of real-world roads into account.

More generally, our approach to stress-testing road networks can be applied in a variety of contexts. For example, rather than measuring the accessibility of hospitals from population centers, we may measure accessibility of population centers from firefighting stations. Indeed, many critical services rely on the functionality of transportation systems like the road network. Social, demographic, and environmental factors suggest that these systems will only experience greater strain in the coming decades. Whether due to climate change, large-scale migration, or the aging of the population, resilience and robustness of these services as a function of the systems they depend on will merit increasing scrutiny. Integrating various forms of data, for example, in a knowledge graph designed for crisis management Anjomshoaa et al. [2023], can greatly expand the potential scope of our simulations. The knowledge graph can be used in future works to determine additional risk factors for roads due to overlapping networks, e.g., river networks which can increase the risk to a road located close by or crossing the river. By adding these risk factors to the simplified network, the simulation can be adapted by updating the probabilities, and consequently, the relevance of the findings to real-world situations can be improved.

References

- M. J. Anderson, D. A. F. Kiddle, and T. M. Logan. The underestimated role of the transportation network: Improving disaster & community resilience. *Transportation Research Part D: Transport and Environment*, 106:103218, 2022. ISSN 1361-9209. doi: 10.1016/j.trd.2022.103218. URL https://www.sciencedirect.com/science/article/pii/S1361920922000487.
- Amin Anjomshoaa, Hannah Schuster, Johannes Wachs, and Axel Polleres. Towards crisis response and intervention using knowledge graphs-crisp case study. In *International Conference on Advanced Information Systems Engineering*, pages 67–73. Springer, 2023.

I. E. Antoniou and E. T. Tsompa. Statistical analysis of weighted networks. Discrete Dynamics in Nature and Society, 2008:1–16, 2008. ISSN 1026-0226, 1607-887X. doi: 10.1155/2008/375452. URL http://www.hindawi.com/journals/ddns/2008/375452/.

Stefano Battiston, J Doyne Farmer, Andreas Flache, Diego Garlaschelli, Andrew G Haldane, Hans Heesterbeek, Cars Hommes, Carlo Jaeger, Robert May, and Marten Scheffer. Complexity theory and financial regulation. *Science*, 351(6275):818–819, 2016.

Eszter Bokányi and Anikó Hannák. Understanding inequalities in ride-hailing services through simulations. Scientific reports, 10(1):6500, 2020.

Michal Bíl, Rostislav Vodák, Jan Kubeček, Martina Bílová, and Jiří Sedoník. Evaluating road network damage caused by natural disasters in the czech republic between 1997 and 2010. *Transportation Research Part A: Policy and Practice*, 80:90–103, 2015. ISSN 0965-8564. doi: https://doi.org/10.1016/j.tra.2015.07.006. URL https://www.sciencedirect.com/science/article/pii/S0965856415001883.

- Christian Diem, Anton Pichler, and Stefan Thurner. What is the minimal systemic risk in financial exposure networks? *Journal of Economic Dynamics and Control*, 116:103900, 2020.
- John Doyle. Complexity and robustness. Proceedings of the national academy of sciences, 99(suppl_1):2538-2545, 2002.
- Nils Goldbeck, Panagiotis Angeloudis, and Washington Y. Ochieng. Resilience assessment for interdependent urban infrastructure systems using dynamic network flow models. *Reliability Engineering & System Safety*, 188:62–79, 2019. ISSN 0951-8320. doi: 10.1016/j.ress.2019.03.007. URL https://www.sciencedirect.com/science/article/pii/S0951832018308937.
- Jürgen Hackl. Risk Assessments of Complex Infrastructure Systems Considering Spatial and Temporal Aspects. phdthesis, ETH Zurich, 2019. URL http://hdl.handle.net/20.500.11850/345378. Artwork Size: 251 p. Medium: application/pdf Pages: 251 p.
- Jürgen Hackl, Juan Carlos Lam, Magnus Heitzler, Bryan T. Adey, and Lorenz Hurni. Estimating network related risks: A methodology and an application in the transport sector. *Natural Hazards and Earth System Sciences*, 18(8):2273–2293, 2018. ISSN 1684-9981. doi: 10.5194/nhess-18-2273-2018. URL https://nhess.copernicus.org/articles/18/2273/2018/.
- Anupam B. Jena, N. Clay Mann, Leia N. Wedlund, and Andrew Olenski. Delays in Emergency Care and Mortality during Major U.S. Marathons. *New England Journal of Medicine*, 376(15):1441–1450, 04 2017. ISSN 0028-4793, 1533-4406. doi: 10.1056/NEJMsa1614073. URL http://www.nejm.org/doi/10.1056/NEJMsa1614073.
- Erik Jenelius, Tom Petersen, and Lars-Göran Mattsson. Importance and exposure in road network vulnerability analysis. *Transportation Research Part A: Policy and Practice*, 40(7):537–560, 2006. ISSN 09658564. doi: 10.1016/j.tra.2005.11.003. URL https://linkinghub.elsevier. com/retrieve/pii/S096585640500162X.
- Michaela Kaleta, Jana Lasser, Elma Dervic, Liuhuaying Yang, Johannes Sorger, D Ruggiero Lo Sardo, Stefan Thurner, Alexandra Kautzky-Willer, and Peter Klimek. Stress-testing the resilience of the Austrian healthcare system using agent-based simulation. *Nature Communications*, 13(1): 4259, 2022.
- Ludwig Kuntz, Roman Mennicken, and Stefan Scholtes. Stress on the ward: Evidence of safety tipping points in hospitals. *Management Science*, 61(4):754–771, 2015.
- Hongzhi Lin, Min Xu, and Chi Xie. Location and capacity planning for preventive healthcare facilities with congestion effects. *Journal of Industrial* and Management Optimization, 19(4):3044–3059, 2023. ISSN 1547-5816. doi: 10.3934/jimo.2022076. URL https://www.aimsciences. org/en/article/doi/10.3934/jimo.2022076. Publisher: Journal of Industrial and Management Optimization.
- Xueming Liu, Daqing Li, Manqing Ma, Boleslaw K. Szymanski, H Eugene Stanley, and Jianxi Gao. Network resilience. *Physics Reports*, 971:1–108, 2022. ISSN 03701573. doi: 10.1016/j.physrep.2022.04.002. URL https://linkinghub.elsevier.com/retrieve/pii/ S0370157322001211.
- Donald Ruggiero Lo Sardo, Stefan Thurner, Johannes Sorger, Georg Duftschmid, Gottfried Endel, and Peter Klimek. Quantification of the resilience of primary care networks by stress testing the health care system. *Proceedings of the National Academy of Sciences*, 116(48):23930–23935, 2019.
- Belén Martín, Emilio Ortega, Rodrigo Cuevas-Wizner, Antonio Ledda, and Andrea De Montis. Assessing road network resilience: An accessibility comparative analysis. *Transportation Research Part D: Transport and Environment*, 95:102851, 2021. ISSN 1361-9209. doi: 10.1016/j.trd. 2021.102851. URL https://www.sciencedirect.com/science/article/pii/S1361920921001541.
- Lars-Göran Mattsson and Erik Jenelius. Vulnerability and resilience of transport systems a discussion of recent research. *Transportation Research Part A: Policy and Practice*, 81:16–34, 2015. ISSN 0965-8564. doi: https://doi.org/10.1016/j.tra.2015.06.002. URL https://www.sciencedirect.com/science/article/pii/S0965856415001603. Resilience of Networks.
- Aditi Mukherji, Peter Thorne, William W L Cheung, Sarah L Connors, Matthias Garschagen, Oliver Geden, Bronwyn Hayward, Nicholas P Simpson, Edmond Totin, Kornelis Blok, Siri Eriksen, Erich Fischer, Gregory Garner, Céline Guivarch, Marjolijn Haasnoot, Tim Hermans, Debora Ley, Jared Lewis, Zebedee Nicholls, Leila Niamir, Sophie Szopa, Blair Trewin, Mark Howden, Carlos Méndez, Joy Pereira, Ramón Pichs, Steven K Rose, Yamina Saheb, Roberto Sánchez, Cunde Xiao, and Noureddine Yassaa. SYNTHESIS REPORT OF THE IPCC SIXTH ASSESSMENT REPORT (AR6), 2023. URL https://www.ipcc.ch/report/sixth-assessment-report-cycle/.
- Atsuhiko Murata and Shinya Matsuda. Association Between Ambulance Distance to Hospitals and Mortality from Acute Diseases in Japan: National Database Analysis. *Journal of Public Health Management and Practice*, 19(5):E23–E28, 2013. ISSN 1078-4659. doi: 10.1097/PHH.0b013e31828b7150. URL https://journals.lww.com/00124784-201309000-00023.
- Jean-Paul Rodrigue, Brian Slack, Claude Comtois, William Anderson, John Bowen, Cesar Ducruet, Theo Notteboom, and Shih-Lung Shaw. Transportation and geography. In Jean-Paul Rodrigue, editor, *The Geography of Transport Systems*, chapter 1. Hofstra University, Department of Global Studies & Geography, https://transportgeography.org, 2020.
- Christian M. Schneider, André A. Moreira, José S. Andrade, Shlomo Havlin, and Hans J. Herrmann. Mitigation of malicious attacks on networks. *Proceedings of the National Academy of Sciences*, 108(10):3838–3841, 2011. doi: 10.1073/pnas.1009440108. URL https://www.pnas.org/doi/full/10.1073/pnas.1009440108. Publisher: Proceedings of the National Academy of Sciences.
- Willam Schueller and Johannes Wachs. Modeling interconnected social and technical risks in open source software ecosystems. *arXiv preprint arXiv:2205.04268*, 2022.
- William Schueller, Christian Diem, Melanie Hinterplattner, Johannes Stangl, Beate Conrady, Markus Gerschberger, and Stefan Thurner. Propagation of disruptions in supply networks of essential goods: A population-centered perspective of systemic risk, 2022. URL https://papers.ssrn.com/abstract=4022513.
- Hannah Schuster, Johannes Wachs, and Axel Polleres. Municipality access to hospitals via road networks. In *Konferenzband der Disaster Research Days 2022*, pages 53–58. Disaster Competence Network Austria, 2022. ISBN: 978-3-900397-04-3.
- Gergő Tóth, Zoltán Elekes, Adam Whittle, Changjun Lee, and Dieter F Kogler. Technology network structure conditions the economic resilience of regions. *Economic Geography*, 98(4):355–378, 2022.
- Kees C.H. van Ginkel, Elco E. Koks, Frederique de Groen, Viet Dung Nguyen, and Lorenzo Alfieri. Will river floods 'tip' european road networks? a robustness assessment. *Transportation Research Part D: Transport and Environment*, 108:103332, 2022. ISSN 13619209. doi: 10.1016/j.trd.2022.103332. URL https://linkinghub.elsevier.com/retrieve/pii/S1361920922001602.

- Szymon Wiśniewski, Marta Borowska-Stefańska, Michał Kowalski, and Paulina Sapińska. Vulnerability of the accessibility to grocery shopping in the event of flooding. *Transportation Research Part D: Transport and Environment*, 87:102510, 2020. ISSN 1361-9209. doi: https://doi.org/10.1016/j.trd.2020.102510. URL https://www.sciencedirect.com/science/article/pii/S1361920920306970.
- Chi Xie, Zhaoyao Bao, and Anthony Chen. Disrupted transportation networks under different information availability and stochasticity situations. *Transportation Research Part C: Emerging Technologies*, 150:104097, 2023. ISSN 0968-090X. doi: 10.1016/j.trc.2023.104097. URL https://www.sciencedirect.com/science/article/pii/S0968090X23000864.