Best-Subset Selection in Generalized Linear Models: A Fast and Consistent Algorithm via Splicing Technique

Junxian Zhu^{*1}, Jin Zhu^{*2}, Borui Tang⁴, Xuanyu Chen², Hongmei Lin^{†3}, and Xueqin Wang^{†4}

¹Saw Swee Hock School of Public Health, National University of Singapore

²Southern China Center for Statistical Science, Department of Statistical Science, School of Mathematics, Sun Yat-Sen University

³School of Statistics and Information, Shanghai University of International Business and Economics , hmlin@suibe.edu.cn

⁴Department of Statistics and Finance/International Institute of Finance, School of Management, University of Science and Technology of China, wangxq20@ustc.edu.cn

Abstract

In high-dimensional generalized linear models, it is crucial to identify a sparse model that adequately accounts for response variation. Although the best subset section has been widely regarded as the Holy Grail of problems of this type, achieving either computational efficiency or statistical guarantees is challenging. In this article, we intend to surmount this obstacle by utilizing a fast algorithm to select the best subset with high certainty. We proposed and illustrated an algorithm for best subset recovery in regularity conditions. Under mild conditions, the computational complexity of our algorithm scales polynomially with sample size and dimension. In addition to demonstrating the statistical properties of our method, extensive numerical experiments reveal that it outperforms existing methods for variable selection and coefficient estimation. The runtime analysis shows that our implementation achieves approximately a fourfold speedup compared to popular variable selection toolkits like glmnet and ncvreg.

Key words : Best-Subset Selection, Generalized Linear Models, Splicing Technique, Support Recovery Consistency, Polynomial Complexity

^{*}Equal contribution

[†]Corresponding author

1 Introduction

Generalized linear models [GLMs, McCullagh and Nelder, 1989] can model a family of continuous or discrete responses with a set of predictors. It generalizes linear regression by assuming responses follow an exponential distribution with a mean determined by a linear combination of predictors. Specifically, let $\{(\boldsymbol{x}_i, y_i)\}_{i=1}^n$ be a dataset with *n* observations in which y_i is a response and $\boldsymbol{x}_i = (x_{i1}, \ldots, x_{ip})^{\top}$ is a *p*-dimensional predictor vector. GLMs assume the density function of y_i given \boldsymbol{x}_i is: $f(y_i; \boldsymbol{x}_i^{\top}\boldsymbol{\beta}, \phi) = \exp\{y_i\boldsymbol{x}_i^{\top}\boldsymbol{\beta} - b(\boldsymbol{x}_i^{\top}\boldsymbol{\beta}) + c(y_i, \phi)\}$, where $\boldsymbol{\beta} \in \mathbb{R}^p$ is a regression coefficient vector, $b(\cdot)$ and $c(\cdot)$ are some suitably chosen known functions such that $b'(\boldsymbol{x}_i^{\top}\boldsymbol{\beta}) = \mathbb{E}[y_i|\boldsymbol{x}_i]$. It is worth noting that $b(\cdot)$ is the critical component in determining the distribution of y_i ; for instance, let $\boldsymbol{\theta} = \boldsymbol{x}_i^{\top}\boldsymbol{\beta}$, taking $b(\boldsymbol{\theta}) = \frac{1}{2}\boldsymbol{\theta}^2$ results in the ordinary linear model $y_i = \boldsymbol{x}_i^{\top}\boldsymbol{\beta} + \epsilon_i$, where $\epsilon_i \sim \mathcal{N}(0, 1)$. Due to their flexibility, GLMs include many frequently-used models like logistic regression, Poisson regression, gamma regression, etc. Therefore, GLMs adapt to various scientific and engineering disciplines, including economics, biology, and geography.

Scientific research and data analysis in the modern era frequently collect a large number of predictors for GLMs in order to model responses, i.e., p is large in comparison to n. It is critical to select a minimally adequate subset of predictors to fit responses accurately, as this results in a sparse GLM that is accurate and interpretable. Besides, when $p \approx O(n)$ or $p \gg O(n)$, minimizing the negative log-likelihood function for β ,

$$l_n(\boldsymbol{\beta}) = -\sum_{i=1}^n \{ y_i \boldsymbol{x}_i^\top \boldsymbol{\beta} - b(\boldsymbol{x}_i^\top \boldsymbol{\beta}) + c(y_i, \phi) \},\$$

yields an estimated coefficient with significant fluctuation or even no unique solution. At this time, pursuing a sparse regression coefficient vector is indispensable. We seek an efficient algorithm to solve the following best-subset selection problem:

$$\hat{\boldsymbol{\beta}} \leftarrow \arg\min_{\boldsymbol{\beta}} l_n(\boldsymbol{\beta}), \text{ subject to: } \|\boldsymbol{\beta}\|_0 \le s,$$
 (1)

where $\|\boldsymbol{\beta}\|_0 = \sum_{j=1}^p I(\beta_j \neq 0)$ and $I(\cdot)$ is the indicator function. Since the cardinality constraint on $\boldsymbol{\beta}$ is non-convex, finding such an algorithm is not trivial.

To this end, the mathematical and statistical communities have spent decades studying how to select the best subset. One of the most well-known methods is exhaustive enumeration in conjunction with the Akaike/Bayesian information criterion [Hocking and Leslie, 1967, Akaike, 1998, Schwarz, 1978, Anderson and Burnham, 2020]. The branch-and-bound algorithm improves exhaustive searching by rejecting suboptimal subsets without direct evaluation [LaMotte and Hocking, 1970, Narendra and Fukunaga, 1977]. Unfortunately, this method continues to impose a sharp increase in computational cost when p grows, as determining the exact best subset is NP-hard, even for linear regression [Natarajan, 1995]. Empirical evidence is that a widely used software implementing this algorithm [Calcagno and de Mazancourt, 2010] is limited to datasets with no more than 50 variables [Wen et al., 2020].

Numerous researchers have attempted to circumvent the NP-hardness. One important direction is to develop statistical relaxation methods that take advantage of continuous penalties that promote sparsity. The well-known relaxation methods are the least absolute shrinkage and selection operator [LASSO, Tibshirani, 1996], elastic net [Zou and Hastie, 2005], Dantzig selector [Candes and Tao, 2007], smoothly clipped absolute deviation [SCAD, Fan and Li, 2001], minimax concave penalty [MCP, Zhang, 2010], and truncated ℓ_1 penalty [Shen et al., 2012]. The proposed penalty functions have been extended to GLMs [Park and Hastie, 2007, James and Radchenko, 2009, Fan and Lv, 2011]. While the majority of relaxation methods can be solved in polynomial time, some of them (for example, the LASSO) lack desirable statistical properties due to the resulting biased estimations [Zhang and Huang, 2008].

Another primary direction is the development of algorithms for approximating the best-subset solutions. A well-known approximation strategy is forward stepwise model selection — iteratively adding a variable that is highly correlated with the current residuals, referring to the orthogonal matching pursuit in the machine learning community [Mallat and Zhang, 1993, Lozano et al., 2011. Many researchers believe this procedure is excessively greedy and results in an unsatisfactory solution [Weisberg, 2005, Friedman et al., 2009]. To improve the adaptiveness of forward selection, Blumensath [2013] extend the iterative hard thresholding algorithm under linear models [Blumensath and Davies, 2009] to nonlinear objective functions. Bahmani et al. [2013] propose a gradient support pursuit method for best-subset selection under logistic regression. Wen et al. [2020] develop a primal-dual active set algorithm for logistic regression that builds on the algorithm developed for linear models [Huang et al., 2018]. We refer readers to Zhou et al. [2021] for an excellent review of these methods. Although ℓ_0 -penalized GLM learning problems are not equivalent to the problem (1), some literature designs algorithms starting with ℓ_0 -penalized GLM learning. For example, Beck and Eldar [2013], Dedieu et al. [2021] develop coordinate descent algorithms for computing the coordinate-wise minimizer of ℓ_0 -penalized regression. Unfortunately, the methods above have not been demonstrated to be both statistically recovery-guaranteed and computationally efficient for the best-subset selection under GLMs. For example, the coordinate-wise minimizer cannot guarantee the recovery of the best subset. At the same time, the primal-dual active set algorithm may sink into periodic iteration even for linear models [Foucart, 2011].

1.1 Our Proposal and Contributions

Our primary objective is to contribute a reliable, certifiably efficient, best-subset selection algorithm for GLM. To accomplish this, our algorithm promotes the *s*-cardinality selected

subset by excluding "irrelevant" variables, including the same amount of "crucial" variables, both of which are defined by low-cost computational criteria. The inclusion-and-exclusion iteration continues until the model can sufficiently fit the data. This iterative algorithm avoids the tedious task of enumerating all possible fixed-size subsets. More impressively, our theoretical analysis ensures the correct selection of the best subset after a few iterations. The computational efficiency of our algorithm is also reflected by its effortless convergence. At the same time, the other best subset approximated methods require additional assumptions to ensure convergence to the fixed points of sparsity-pursuit operators. We then design an information criterion to determine the optimal s in a data-driven manner. The information criterion evaluates the solutions with different cardinality and chooses the one that makes a reasonable trade-off between model complexity and accuracy. Theoretical analysis demonstrates that the underlying true subset can be identified in polynomial time with high probability by integrating the information criterion.

This section concludes with the following summary of our contributions:

- We propose a new fast algorithm for solving the problem of best-subset selection in GLMs based on the following: (i) an efficient technique for iteratively improving the quality of selected subset and (ii) an information criterion for choosing the size of the selected subset. A toolkit abess implementing our algorithm is freely available on CRAN at: https://cran.r-project.org/web/packages/abess.
- We theoretically demonstrate that the new algorithm is high-speed. To put it another way, a few steps of algorithmic iterations reach a stable solution with great certainty. Additionally, its computational complexity is proportional to the sample size and the number of variables, comparable to the most widely used variable selection method for GLMs—the LASSO.
- We rigorously establish our proposed algorithm's best-subset-recovery property with a high probability in GLMs, which extends the theoretical guarantees for linear models [Zhu et al., 2020]. This extension is not trivial because adapting GLMs to various supervised learning tasks complicates log-likelihood analysis with complex forms.
- Our simulation studies provide compelling evidence that our method surpasses state-ofthe-art methods in terms of subset selection and parameter estimation across various regression models, including logistic regression, Poisson regression, and multipleresponse regression. Furthermore, our method exhibits exceptional performance by achieving a remarkable fourfold speedup compared to the LASSO algorithm.

1.2 Organization and Notations

The rest of the paper is organized as follows. In Section 2, we propose a novel technique for improving the selected subset in GLMs and design a new iterative best-subset selection algorithm upon this technique. Section 3 establishes our algorithm's theoretical properties, accompanied by high-level proofs. In Section 4, we describe the implementation details for the fast computing of our proposal. Section 5 evaluates the proposed method's empirical performance using artificial datasets. The paper concludes with a few remarks in Section 6. Due to space constraints, we relegate the detailed proofs of primary theoretical results and additional numerical experiments to Supplementary Material.

Below, we define a few useful notations for the content. For any vector $\boldsymbol{\beta} = (\beta_1, \ldots, \beta_p)^\top \in \mathbb{R}^p$, the ℓ_0 -norm of $\boldsymbol{\beta}$ is defined as $\|\boldsymbol{\beta}\|_0 = \sum_{j=1}^p I(\beta_j \neq 0)$ where $I(\cdot)$ is the indicator function, and we define the ℓ_q -norm of $\boldsymbol{\beta}$ by $\|\boldsymbol{\beta}\|_q = (\sum_{j=1}^p |\beta_j|^q)^{1/q}$, where $q \in [1, \infty)$. Let $\mathcal{F} = \{1, \ldots, p\}$, for any set $\mathcal{A} \subseteq \mathcal{F}$, denote $|\mathcal{A}|$ as its cardinality, $\mathcal{A}^c = \mathcal{F} \setminus \mathcal{A}$ as the complement of \mathcal{A} and $\boldsymbol{\beta}_{\mathcal{A}} = (\beta_j, j \in \mathcal{A}) \in \mathbb{R}^{|\mathcal{A}|}$. The support set for the vector $\boldsymbol{\beta}$ is defined as $\operatorname{supp}(\boldsymbol{\beta}) = \{j : \beta_j \neq 0\}$. For a matrix $\mathbf{X} \in \mathbb{R}^{n \times p}$, define $\mathbf{X}_{\mathcal{A}} = (\mathbf{X}_j, j \in \mathcal{A}) \in \mathbb{R}^{n \times |\mathcal{A}|}$, where \mathbf{X}_j is the *j*-th column of \mathbf{X} . For any vector $\boldsymbol{t} \in \mathbb{R}^p$ and index set \mathcal{A} , we define $\boldsymbol{t}|_{\mathcal{A}}$ as a *p*-dimensional vector whose the *j*-th entry $(\boldsymbol{t}|_{\mathcal{A}})_j$ is equal to t_j if $j \in \mathcal{A}$ and zero otherwise. For example, $\boldsymbol{t}|_{\{j\}}$ denotes the vector whose the *j*-th entry is t_j and zero otherwise. We also simplify $\boldsymbol{t}|_{\{j\}}$ as $\boldsymbol{t}|_j$ for notational convenience. Denote the true sparse regression coefficient as $\boldsymbol{\beta}^*$ and its support set as \mathcal{A}^* (also known as a best subset or true active set) with size $s^* := |\mathcal{A}^*|$, where $\mathbb{E}[y_i|\boldsymbol{x}_i] = b'(\boldsymbol{x}_i^\top \boldsymbol{\beta}^*)$.

2 Algorithm

In this section, we present our fast and consistent best-subset selection algorithm. Firstly, we introduce an algorithm for selecting the best subset when the support size is known. Subsequently, we address the scenario where the knowledge of the support size is unavailable and introduce a novel information criterion to determine the optimal support size.

2.1 Splicing Method For GLM

Imagine we begin with an arbitrary guess $\mathcal{A} \subseteq \{1, \ldots, p\}$ for the best subset with cardinality $|\mathcal{A}| = s$. Let $\mathcal{I} = \mathcal{A}^c$, and we shall refer to \mathcal{A} and \mathcal{I} as the active set and inactive set, respectively. The coefficient estimator under \mathcal{A} is:

$$\hat{\boldsymbol{\beta}} = \arg\min_{\boldsymbol{\beta}_{\mathcal{I}}=0} l_n(\boldsymbol{\beta}).$$

As follows, define the gradient of $l_n(\beta)$ at $\hat{\beta}$ as:

$$\hat{oldsymbol{d}} = \left. rac{\partial l_n(oldsymbol{eta})}{\partial oldsymbol{eta}}
ight|_{oldsymbol{eta} = \hat{oldsymbol{eta}}}$$

Following that, we will introduce two critical concepts for deriving our algorithm.

• Backward sacrifice: the magnitude of discarding the *j*-th variable in \mathcal{A} , i.e.,

$$\xi_j^* = l_n(\hat{\boldsymbol{\beta}}|_{\mathcal{A}\setminus\{j\}}) - l_n(\hat{\boldsymbol{\beta}}).$$
⁽²⁾

Intuitively, the *j*-th variable in \mathcal{A} associated with a larger ξ_j^* is more relevant to the response.

• Forward sacrifice: the magnitude of adding the *j*-th variable in \mathcal{I} into \mathcal{A} , i.e.,

$$\zeta_j^* = l_n(\hat{\boldsymbol{\beta}}) - l_n(\hat{\boldsymbol{\beta}} + \hat{\boldsymbol{t}}|_j), \qquad (3)$$

where $\hat{t} = \arg\min_{t} l_n(\hat{\beta} + t|_j)$. As with the backward sacrifice, a larger ζ_j^* indicates that the *j*-th variable in \mathcal{I} is more critical for modeling the response.

However, it is worth noting that the two sacrifices are incomparable due to their association with different support sets.

The computation of forward sacrifices is time-consuming because an iterative algorithm is needed to minimize $l_n(\hat{\beta} + t|_j)$ for all $j \in \mathcal{I}$. We introduce the following approximations to mitigate this. According to the definition of \hat{t}_j and the Taylor's expansion, we have

$$\hat{t}_j = -\left(\left.\frac{\partial^2 l_n(\boldsymbol{\beta})}{(\partial\beta_j)^2}\right|_{\boldsymbol{\beta}=\bar{\boldsymbol{\beta}}}\right)^{-1} \left.\frac{\partial l_n(\boldsymbol{\beta})}{\partial\beta_j}\right|_{\boldsymbol{\beta}=\hat{\boldsymbol{\beta}}},$$

where $\bar{\boldsymbol{\beta}} = \hat{\boldsymbol{\beta}} + (1-a)\boldsymbol{t}|_j$ (0 < a < 1). Additionally, using Taylor's expansion and simple algebra, for any $j \in \mathcal{I}$, the forward sacrifice (2) can be expressed as follows:

$$\zeta_j^* = -\left.\frac{\partial l_n(\boldsymbol{\beta})}{\partial \beta_j}\right|_{\boldsymbol{\beta}=\hat{\boldsymbol{\beta}}} \hat{t}_j - \frac{1}{2} \left.\frac{\partial^2 l_n(\boldsymbol{\beta})}{(\partial \beta_j)^2}\right|_{\boldsymbol{\beta}=\bar{\boldsymbol{\beta}}} (\hat{t}_j)^2 \approx \frac{1}{2} \left(\left.\frac{\partial^2 l_n(\boldsymbol{\beta})}{(\partial \beta_j)^2}\right|_{\boldsymbol{\beta}=\hat{\boldsymbol{\beta}}}\right)^{-1} (\hat{\boldsymbol{d}}_j)^2.$$

Similarly, for any $j \in \mathcal{A}$, the backward sacrifice (3) can be approximated by

$$\xi_j^* = -\left. \frac{\partial l_n(\boldsymbol{\beta})}{\partial \beta_j} \right|_{\boldsymbol{\beta} = \hat{\boldsymbol{\beta}}} \hat{\beta}_j + \frac{1}{2} \left. \frac{\partial^2 l_n(\boldsymbol{\beta})}{(\partial \beta_j)^2} \right|_{\boldsymbol{\beta} = \bar{\boldsymbol{\beta}}} (\hat{\beta}_j)^2 \approx \frac{1}{2} \left. \frac{\partial^2 l_n(\boldsymbol{\beta})}{(\partial \beta_j)^2} \right|_{\boldsymbol{\beta} = \hat{\boldsymbol{\beta}}} (\hat{\boldsymbol{\beta}}_j)^2,$$

where $\bar{\hat{\beta}} = \hat{\beta}|_{\mathcal{A}\setminus\{j\}} + a'\hat{\beta}|_j$ (0 < a' < 1). We can see that the sacrifices ξ_j^* and ζ_j^* can be approximated by the weighted squared values of $\hat{\beta}_j$ and \hat{d}_j , respectively.

Our algorithm's central idea is to swap "irrelevant" variables in \mathcal{A} for "important" variables in \mathcal{I} , which may result in a higher-quality solution. This intuitive idea is referred

to as the "splicing" technique. Specifically, denote

$$\xi_{j} \coloneqq \left. \frac{\partial^{2} l_{n}(\boldsymbol{\beta})}{(\partial \beta_{j})^{2}} \right|_{\boldsymbol{\beta} = \hat{\boldsymbol{\beta}}} (\hat{\boldsymbol{\beta}}_{j})^{2} \text{ (for } j \in \mathcal{A}),$$

$$\zeta_{j} \coloneqq \left(\left. \frac{\partial^{2} l_{n}(\boldsymbol{\beta})}{(\partial \beta_{j})^{2}} \right|_{\boldsymbol{\beta} = \hat{\boldsymbol{\beta}}} \right)^{-1} (\hat{\boldsymbol{d}}_{j})^{2} \text{ (for } j \in \mathcal{I}),$$
(4)

given any splicing size $k \leq s$, and

$$\mathcal{S}_{k,1} = \{ j \in \mathcal{A} : \sum_{i \in \mathcal{A}} \mathrm{I}(\xi_j \ge \xi_i) \le k \}, \ \mathcal{S}_{k,2} = \{ j \in \mathcal{I} : \sum_{i \in \mathcal{I}} \mathrm{I}(\zeta_j \le \zeta_i) \le k \},$$
(5)

splicing \mathcal{A} and \mathcal{I} by swapping $\mathcal{S}_{k,1}$ and $\mathcal{S}_{k,2}$, resulting in a candidate active set $\tilde{\mathcal{A}} = (\mathcal{A} \setminus \mathcal{S}_{k,1}) \cup \mathcal{S}_{k,2}$. Denote $\tilde{\mathcal{I}} = (\tilde{\mathcal{A}})^c$ and $\tilde{\boldsymbol{\beta}} = \arg\min_{\boldsymbol{\beta}_{\tilde{\mathcal{I}}}=0} l_n(\boldsymbol{\beta})$. If $l_n(\tilde{\boldsymbol{\beta}})$ is significantly smaller than $l_n(\hat{\boldsymbol{\beta}})$, then we believe $\tilde{\mathcal{A}}$ surpasses \mathcal{A} , and we should update the active set: $\mathcal{A} \leftarrow \tilde{\mathcal{A}}$. The active set can be iteratively updated using the splicing technique until no visible reduction in loss is possible. The above argument is summarized in Algorithm 1.

Algorithm 1 Best-Subset Selection for \underline{GLM} given support size s (BESS-GLM)

Require: A dataset $\{(\boldsymbol{x}_i, y_i)\}_{i=1}^n$, an initial active set \mathcal{A}^0 with *s* elements, the maximum splicing size $k_{\max}(\leq s)$, and a threshold τ_s .

1: Initialize: $q \leftarrow -1, \mathcal{I}^0 \leftarrow (\mathcal{A}^0)^c, \beta^0 \leftarrow \arg \min_{\beta_{\mathcal{I}^0}=0} l_n(\beta), \text{ and } \mathbf{d}^0 \leftarrow \frac{\partial l_n(\beta)}{\partial \beta}\Big|_{\beta=\beta^0}.$

2: repeat

3:
$$q \leftarrow q+1$$
, and $L \leftarrow l_n(\boldsymbol{\beta}^q)$.

4: **for** $k = 1, ..., k_{\max}$ **do**

5:
$$\xi_j \leftarrow \frac{\partial^2 l_n(\boldsymbol{\beta})}{(\partial \beta_j)^2}\Big|_{\boldsymbol{\beta} = \boldsymbol{\beta}^q} (\boldsymbol{\beta}_j^q)^2, j \in \mathcal{A}^q, \text{ and } \zeta_j \leftarrow \left(\left. \frac{\partial^2 l_n(\boldsymbol{\beta})}{(\partial \beta_j)^2} \right|_{\boldsymbol{\beta} = \boldsymbol{\beta}^q} \right)^{-1} (\boldsymbol{d}_j^q)^2, j \in \mathcal{I}^q.$$

6: Update the candidate active set via splicing: $\hat{\mathcal{A}} \leftarrow (\mathcal{A}^q \setminus \mathcal{S}_{k,1}) \cup \mathcal{S}_{k,2}$, where

$$\mathcal{S}_{k,1} = \{ j \in \mathcal{A}^q : \sum_{i \in \mathcal{A}^q} \mathrm{I}(\xi_j \ge \xi_i) \le k \}, \ \mathcal{S}_{k,2} = \{ j \in \mathcal{I}^q : \sum_{i \in \mathcal{I}^q} \mathrm{I}(\zeta_j \le \zeta_i) \le k \}.$$

7: Let
$$\tilde{\mathcal{I}} \leftarrow (\tilde{\mathcal{A}})^c$$
, solve $\tilde{\boldsymbol{\beta}} \leftarrow \arg \min_{\boldsymbol{\beta}_{\tilde{\mathcal{I}}}=0} l_n(\boldsymbol{\beta})$ and compute $\tilde{\boldsymbol{d}} \leftarrow \left. \frac{\partial l_n(\boldsymbol{\beta})}{\partial \boldsymbol{\beta}} \right|_{\boldsymbol{\beta}=\tilde{\boldsymbol{\beta}}}$

8: **if** $L - l_n(\boldsymbol{\beta}) > \tau_s$ **then** 9: $L \leftarrow l_n(\boldsymbol{\tilde{\beta}}), (\boldsymbol{\mathcal{A}}^{q+1}, \boldsymbol{\mathcal{I}}^{q+1}, \boldsymbol{\beta}^{q+1}, \boldsymbol{d}^{q+1}) \leftarrow (\boldsymbol{\tilde{\mathcal{A}}}, \boldsymbol{\tilde{\mathcal{I}}}, \boldsymbol{\tilde{\beta}}, \boldsymbol{\tilde{d}}),$ and break from the **for** loop. 10: **end if** 11: **end for**

12: until $\mathcal{A}^{q+1} = \mathcal{A}^q$ Ensure: $(\mathcal{B}^q, \mathcal{A}^q, \mathbf{d}^q)$.

Remark 1 Algorithm 1 necessitates repeated splicing until the active set converges. A

good initial guess for the active set \mathcal{A}_0 would accelerate the convergence of Algorithm 1. The output of sure independent screening for GLMs [Fan and Song, 2010] provides an intuitive setting for the initial active set \mathcal{A}_0 . To be more precise, we perform predictor-wise regression:

$$\hat{\beta}_j^M \leftarrow \arg\min_{\beta} - \sum_{i=1}^n \{y_i x_{ij}\beta - b(x_{ij}\beta) + c(y_i, \phi)\}, \text{ for } j = 1, \dots, p.$$

The initial set \mathcal{A}_0 is then set as $\left\{1 \leq j \leq p_n : |\hat{\beta}_j^M| \geq \gamma_s\right\}$, with γ_s being the s-th largest value among $\{|\hat{\beta}_1^M|, \ldots, |\hat{\beta}_p^M|\}$.

Remark 2 When $s > s^*$, after the algorithm has covered the true active set, further splicing of irrelevant variables reduces the loss slightly but has no effect on subset selection. The threshold τ_s is used to prevent such unnecessary splicing. We choose $\tau_s = 0.01s \log p \log \log n$ in our implementation based on Assumption (A6) in Section 3.1.

Remark 3 The maximum splicing size is specified by k_{max} . Our numerical results indicate that k_{max} generally has a negligible effect on identifying the relevant variables. However, k_{max} makes a tradeoff between the computational time required by the **repeat-until** loop and the for loop. More precisely, a larger k_{max} considers more possible active sets in a single for loop but may result in less execution of the **repeat-until** loop. On the other hand, a smaller k_{max} consumes less time in a single for loop but may result in more times of repetitions. Our numerical experience suggests $k_{max} = 2$ or 5 is a reasonable choice.

Remark 4 Algorithm 1 naturally terminates since the loss monotonously decreases. More importantly, it runs extremely fast. It is clear that the computational complexity of Algorithm 1 is dominated by computing the following: (i) regression coefficients with fixed support sets; (ii) the gradient of loss function at the estimated coefficients; and (iii) the diagonal elements of the Hessian matrix of the loss function. For (i), the standard GLM textbook's iterative reweighted least squares algorithm can solve it in $O(ns^2)$ loops. According to (ii), the gradient elements are $\{\sum_{i=1}^{n} x_{ij}(y_i - b'(\mathbf{x}_i^{\top}\boldsymbol{\beta}))\}_{j=1}^{p}$, and thus can be computed in O(np) loops. For (iii), the diagonal elements equal to $\{\sum_{i=1}^{n} b''(\mathbf{x}_i^{\top}\boldsymbol{\beta})x_{ij}^2\}_{j=1}^{p}$, and can be computed using O(np) loops. When combined with the analysis for the number of iterations within the **repeat-until** loop in Theorem 2, the computational complexity of Algorithm 1 is roughly controlled by $O(n(p+s^2))$. On the other hand, searching all possible subsets requires $O(ns^2p^s)$ loops.

We conclude this section by discussing the rationale for leveraging the splicing concept. Splicing has been demonstrated to be a novel technique for solving the best-subset selection problem under a linear model in polynomial time (in terms of n and p) and with a high

probability [Zhu et al., 2020]. Empirical evidence indicates that splicing can produce high-quality solutions for best-subset regression problems. Indeed, when dimensionality $p = O(10^5)$ and sample size $n = O(10^3)$, it can effectively solve best-subset selection in half a minute and produce sparse coefficient estimation with desirable predictive power [Zhu et al., 2021]. However, the algorithm is not a straightforward generalization because theoretical validation of the splicing concept is significantly more complicated than Zhu et al. [2020] for two reasons. To begin, because the approximations for the sacrifices (2) and (3) serve as the splicing criteria, it cannot be deduced directly that splicing results in a higher quality subset selection estimation. The second difficulty level stems from the adaptability and potential complexity of the loss function's form. Our rigorous analysis eliminates both difficulties and establishes statistical properties for Algorithm 1 in Lemma 1.

2.2 Adaptive Best-Subset Selection

In this part, we design a data-driven procedure to determine the optimal support size s. Model selection methods such as cross-validation and information criteria are widely used techniques. Recently, Fan and Tang [2013] explored generalized information criterion (GIC) in tuning parameter selection for penalized likelihood methods under GLMs. In particular, we introduce a GIC-type information criterion to recovery support size, which is defined as follows:

$$F(\hat{\boldsymbol{\beta}}) = l_n(\hat{\boldsymbol{\beta}}) + |\operatorname{supp}(\hat{\boldsymbol{\beta}})| \log(p) \log\log n.$$
(6)

Intuitively speaking, the model complexity penalty term $|\operatorname{supp}(\hat{\beta})| \log p \log \log n$ in (6) is set to prevent over-fitting, the term $\log \log n$ with a slow diverging rate is used to prevent underfitting. Combining the Algorithm 1 with GIC, we select the support size that minimizes the $F(\hat{\beta})$. Specifically, we consider a series of candidate support sizes, then we conduct Algorithm 1 for each fixed candidate support size and compute the corresponding GIC via E.q. (6). The support size that minimizes the GIC is chosen. The procedure above is detailed in Algorithm 2. According to Theorem 1, Algorithm 2 guarantees consistent best-subset selection with high probability.

Algorithm 2 Adaptive Best-Subset Selection for GLM (ABESS)

Require: A dataset set $\{(\boldsymbol{x}_i, y_i)\}_{i=1}^n$ and the maximum support size s_{\max} . 1: $\mathcal{A}^0 \leftarrow \{\arg\max_j | (\frac{\partial l_n(\beta)}{\partial \beta}|_{\beta=0})_j | \}$ 2: for $s = 1, \ldots, s_{\max}$ do 3: $(\hat{\boldsymbol{\beta}}_s, \hat{\mathcal{A}}_s, \hat{\boldsymbol{d}}_s) \leftarrow \text{BESS-GLM} (\{(\boldsymbol{x}_i, y_i)\}_{i=1}^n, \mathcal{A}^0, k_{\max}, \tau_s).$ 4: $\mathcal{A}^0 \leftarrow \hat{\mathcal{A}}_s \cup \{\arg\max_j | (\hat{\boldsymbol{d}}_s)_j | \}.$ 5: end for 6: Compute the size of the support set that minimizes GIC: $\hat{s} \leftarrow \arg\min_s F(\hat{\boldsymbol{\beta}}_s).$

Ensure: $(\hat{\boldsymbol{\beta}}_{\hat{s}}, \hat{\mathcal{A}}_{\hat{s}})$.

Remark 5 According to Condition (A7) in Section 3.1, a reasonable choice for s_{\max} is $s_{\max} = \left[\left(\frac{n}{\log p}\right)^{\frac{1}{4}}\right]$, where [a] returns the nearest integer of a.

Remark 6 In Algorithm 2, Algorithm 1 is run on different support sizes, from a small to a large one. Fortunately, it allows exploiting the latest output of Algorithm 1 to construct a better active set to help Algorithm 1 reach convergence with less splicing iteration. Precisely, in Step 4 of Algorithm 2, we combine the selected best subset returned by Algorithm 1 together with the variable with the most significant forward sacrifice and set it as an initial active set for the following support size. It is the so-called "warm starts initialization". Both theory and numerical experiments suggest such initialization is remarkably efficient [Barut et al., 2016, Friedman et al., 2010].

3 Theoretical Guarantees

This section starts by presenting assumptions for the theoretical analysis. The statistical performance guarantees and convergence analysis of our algorithm are depicted in Sections 3.2 and 3.3, respectively; followed by high-level proofs in Sections 3.4. Unless otherwise specified, detailed proofs are relegated to Supplementary Materials. Without loss of generality, assume that the design matrix $\mathbf{X} = (\mathbf{x}_1, \ldots, \mathbf{x}_n)^{\top}$ has \sqrt{n} -normalized columns, i.e., $\mathbf{X}_j^{\top} \mathbf{X}_j = n, \ j = 1, 2, \ldots, p$.

3.1 Assumptions

We present assumptions below to establish the theoretical properties of our algorithm.

(A1) There exists a constant $c_0 \in (0, 1]$ such that, the function $b(\theta)$ is three times differentiable with $c_0 \leq b''(\theta) \leq (c_0)^{-1}$ and $|b'''(\theta)| \leq (c_0)^{-1}$ in its domain.

Assumption (A1) avoids infinitely large or small variances of the response [Rigollet, 2012] as well as to ensure the existence of the Fisher information for statistical inference [Fan and Tang, 2013]. This assumption is valid for several commonly used GLMs, such as linear regression, logistic regression, and Poisson regression, where the coefficient estimation at any active set \mathcal{A} should be bounded for the latter two.

(A2) For the model error $W_i = y_i - \mathbb{E}[y_i]$ $(i = 1, ..., n), W_1, ..., W_n$ follow a sub-Gaussian distribution, i.e., there exist universal positive constants c_1, c_2 such that $\mathbb{P}(|W_i| \ge t) \le c_1 \exp\{-c_2 t^2\}$ for any t > 0.

Assumption (A2) is usually assumed in GLMs [Negahban et al., 2012]. This assumption holds when the response comes from Gaussian, Bernoulli, or other distributions with bound support (e.g., the gamma distribution). Before presenting the following assumption, we introduce the spectrum-restricted condition (SRC). A matrix **M** enjoying the SRC with order s and spectrum bound $\{m_s, M_s\}$ means:

$$0 < m_s \leq \frac{\|\mathbf{M}_{\mathcal{A}}\mathbf{u}\|_2^2}{n\|\mathbf{u}\|_2^2} \leq M_s < \infty, \forall \mathbf{u} \neq 0, \mathbf{u} \in \mathbb{R}^{|\mathcal{A}|}, \text{ with } \mathcal{A} \subset \mathcal{F} \text{ and } |\mathcal{A}| \leq s.$$

(A3) **X** fulfills the SRC with order 2s and spectrum bound $\{m_{2s}, M_{2s}\}$.

Assumption (A3) is a widely used identifiability condition in the literature on highdimensional GLMs [Shi et al., 2019] and was used to investigate the theory of LASSO and MCP [Zhang and Huang, 2008, Zhang, 2010]. (A3) implies that the spectrum of the off-diagonal sub-matrices of $\mathbf{X}^{\top}\mathbf{X}$ is bounded by a constant ν_s that is defined as the smallest value such that

$$\nu_s \geq \frac{\|\mathbf{X}_{\mathcal{A}}^{\top}\mathbf{X}_{\mathcal{A}'}\mathbf{u}\|_2}{n\|\mathbf{u}\|_2}, \forall \mathbf{u} \neq 0, \mathbf{u} \in \mathbb{R}^{|\mathcal{A}'|} \text{ with } \mathcal{A}, \mathcal{A}' \subset \mathcal{F}, |\mathcal{A}| \leq s, |\mathcal{A}'| \leq s \text{ and } \mathcal{A} \cap \mathcal{A}' = \varnothing.$$

(A4) Let
$$C_1 := \frac{1}{c_0^2} \left(\frac{M_s}{2c_0} + \frac{\nu_s^2}{m_s c_0^3} + \frac{M_s v_s^2}{2m_s^2 c_0^5} \right) \left[(2 + \Delta + \frac{2\nu_s}{m_s c_0^2})^2 + (2 + \Delta)^2 \right] \left(\frac{\nu_s}{m_s c_0^2} \right)^2$$
 and $C_2 := \frac{m_s c_0}{2} - \frac{\nu_s^2}{m_s c_0^3} - \frac{M_s v_s^2}{2m_s^2 c_0^5}$, there exists a constant $\Delta > 0$ such that $\gamma_s := \frac{C_1}{(1 - \Delta)C_2} < 1$.

(A4) is a technical assumption. Roughly speaking, we expect ν_s to be reasonably small for its establishment. Here we derive sufficient conditions in a simpler form for (A4). By (A3) and Lemma 20 in Huang et al. [2018], we have $\nu_s \leq \kappa_s := \max\{1 - m_{2s}, M_{2s} - 1\}$. As a result, it suffices to have $f(c_0, \kappa_s) > 0$, where

$$f(c_0, \kappa_s) \coloneqq \frac{(1-\kappa_s)c_0}{2} - \frac{\kappa_s^2}{(1-\kappa_s)c_0^3} - \frac{(1+\kappa_s)\kappa_s^2}{2(1-\kappa_s)^2 c_0^5} - \frac{1}{c_0^2} \left(\frac{1+\kappa_s}{2c_0} + \frac{\kappa_s^2}{(1-\kappa_s)c_0^3} + \frac{(1+\kappa_s)\kappa_s^2}{2(1-\kappa_s)^2 c_0^5}\right) \left[\left(2 + \frac{2\kappa_s}{(1-\kappa_s)c_0^2}\right)^2 + 4 \right] \frac{\kappa_s^2}{(1-\kappa_s)^2 c_0^4}.$$

It holds if sufficient assumptions are made, such as $\{c_0 \ge 0.9, \kappa_s \le 0.1\}$ or $\{c_0 = 1, \kappa_s \le 0.183\}$. The latter, in particular, corresponds to the case of linear models, and the sufficient assumption $\kappa_s \le 0.183$ is identical to its counterpart in Remark 2 in Zhu et al. [2020].

(A5)
$$\frac{1}{\min_{j \in \mathcal{A}^*} |\beta_j^*|^2} = o\left(\frac{n}{s \log p \log \log n}\right)$$

(A6)
$$\tau_s = \Theta\left(s \log p \log \log n\right)$$

Assumption (A5) sets a minimal magnitude of the regression coefficient and is a commonly employed assumption for variable selection in GLMs [Fan and Tang, 2013]. Assumption (A6) ensures that the threshold τ_s can control random errors and prevent unnecessary splicing iterations that reduce loss negligibly. (A7) $s_{\max} = O\left(\left(\frac{n}{\log p}\right)^{\frac{1}{4}}\right).$

(A8) There exists a constant c_3 such that $\max_{1 \le i \le n} \max_{1 \le j \le p} |x_{ij}| \le c_3$.

Remark 7 Assumption (A7) controls the growing rate of s_{max} , which ensures that our algorithm avoids selecting an excessively large support size. When establishing model selection consistency on over-fitted models, the Assumption (A7) controls the log-likelihood function's third and higher order derivatives. A stronger assumption is presented in Theorem 2 of Fan and Tang [2013], where $s_{max} = O(\min\{n^{1/6}(\log p)^{-1/3}, n^{1/8}(\log p)^{-3/8}\})$ is assumed for the case of bounded responses. Assumption (A8) is a common assumption in high-dimensional GLMs [see, e.g., Fei and Li, 2021], which requires that the predictors are uniformly bounded. This assumption is reasonable since preprocessing can be employed to normalize the predictor matrix **X**.

3.2 Statistical Guarantees: Support Recovery

The statistical properties of the support set $\hat{\mathcal{A}}$ returned by Algorithm 1 are presented in the following.

Lemma 1 When $s^* \leq s$, under Assumptions (A1)-(A6), we have

$$\mathbb{P}(\hat{\mathcal{A}} \supseteq \mathcal{A}^*) \ge 1 - \delta_1 - \delta_2 - \delta_3,$$

where $\delta_i = O\left(\exp\left\{\log p - K_i \frac{n}{s} \min_{j \in \mathcal{A}^*} |\mathcal{\beta}_j^*|^2\right\}\right)$ for some constant $K_i > 0$ $(i = 1, 2, 3).$

Lemma 1 indicates that our algorithm has screening property — the estimated support set can cover the true support with high probability. Furthermore, Assumption (A5) ensures that δ_1 , δ_2 , $\delta_3 \rightarrow 0$ as $n \rightarrow \infty$, which leads to the following asymptotic result in Corollary 1. Corollary 1 guarantees Algorithm 1 covers the true support set with probability 1 when the sample size is sufficiently large, which can be witnessed by the numerical results displayed in Figure 1.

Corollary 1 If assumptions in Lemma 1 hold and $s = s^*$, we have

$$\mathbb{P}(\hat{\mathcal{A}} = \mathcal{A}^*) \to 1$$
, as $n \to \infty$.

The establishment of support recovery relies on the idea that, if some elements of the true active set are omitted, the splicing procedure improves the quality of the active set and thus reduce the value of the loss function. We rigorously prove this statement via proof by contradiction shown in Supplementary Materials. Our idea discriminates from other approaches that design the sparse-pursuit operators such that its corresponding the fixed point is the true active set [Li et al., 2017, Yuan et al., 2018, Huang et al., 2022]. Their

proposal has yet to leverage the information of loss function to decide convergence, and thus, some additional assumptions are to be imposed. Furthermore, the following theorem guarantees Algorithm 2 enjoys the consistency of best-subset recovery property, i.e., it can recover the true active set with high probability.

Theorem 1 (Consistency of Best-Subset Recovery) Suppose Assumptions (A1)-(A8) hold, then for some positive constant $\alpha > 0$ and sufficient large n, Algorithm 2 identifies the true active set (i.e., $\hat{\mathcal{A}}_{\hat{s}} = \mathcal{A}^*$), with probability at least $1 - O(p^{-\alpha})$.

3.3 Computational Properties

Denote (β^q, \mathcal{A}^q) as the output of the q-th iteration of Algorithm 1. The following theorem characterizes the total number of iterations needed for screening support.

Theorem 2 Suppose Assumptions (A1)-(A6) hold and $s^* \leq s$. Then, with probability at least $1 - \delta_1 - \delta_2 - \delta_3$, we have $\mathcal{A}^* \subseteq \mathcal{A}^q$ if

$$q > \log_{\frac{1}{\gamma_s}} \left[\frac{l_n(\mathbf{0}) + l_n(\boldsymbol{\beta}^*)}{(1 - \Delta)C_2 n \min_{j \in \mathcal{A}^*} |\boldsymbol{\beta}_j^*|^2} \right],$$

where δ_1 , δ_2 , δ_3 are defined in Lemma 1.

Theorem 2 shows that, within a few number of iterations, the splicing technique leads to an active set that covers the true active set (see Proof of Theorem 2 in Supplementary Material). Particularly, a large magnitude of the minimum coefficient lessens the number of iterations covering the true active set.

From Theorem 2, Algorithm 1 converges with a few iteration. As such, the proposed Algorithm 2 can achieve a polynomial computational time complexity with high probability.

Theorem 3 Suppose Assumptions (A1)-(A8) hold and Algorithm 2 successfully select the true model, i.e., $\hat{\mathcal{A}} = \mathcal{A}^*$ (by Theorem 1, this event is true with a large probability for sufficiently large sample size n), then the computational complexity of Algorithm 2 for a given $s_{\max} \geq s^*$ is

$$O\Big(\Big(s_{\max}^2 \log_{\frac{1}{\gamma_{s_{\max}}}} \left[\frac{l_n(\mathbf{0}) + l_n(\boldsymbol{\beta}^*)}{s^* \log p \log \log n}\right] + \frac{l_n(\mathbf{0}) + l_n(\boldsymbol{\beta}^*)}{\log p \log \log n}\Big)\Big(k_{\max}ns_{\max} + k_{\max}p\Big)\Big)$$

From Theorem 3, the proposed Algorithm 2 achieves a polynomial computational complexity with high probability— roughly speaking, the complexity is controlled by the sample size n, the dimensionality p, the square of sparsity level s, and logarithmic terms of them. As such, Algorithm 1 has competitive computational properties for other state-of-the-art variable selection methods such as the LASSO. The numerical results presented in Figure 5 certify the competitive computational advantage. Finally, we present a theorem demonstrating the gap between estimating the coefficients at the q-th iteration and the true coefficients.

Theorem 4 Under Assumptions (A1)-(A6), if $|\mathcal{A}^*| \leq s$, the ℓ_2 -error of parameter estimation is upper bounded by

$$\|\boldsymbol{\beta}^{q} - \boldsymbol{\beta}^{*}\|_{2} \leq \frac{[l_{n}(\boldsymbol{0}) + l_{n}(\boldsymbol{\beta}^{*})]\left(\frac{\nu_{s}}{m_{s}c_{0}^{2}} + 1\right)}{(1 - \Delta)C_{2}n}\gamma_{s}^{q} + \frac{t}{m_{s}c_{0}}$$

with probability at least $1 - \delta_1 - \delta_2 - \delta_3 - \delta_4(t)$, where $\delta_4(t) \coloneqq O\left(\exp\left\{\log p - K_4 \frac{nt^2}{s}\right\}\right)$ for any t > 0.

Theorem 4 depicts our estimator's ℓ_2 error bound. Li et al. [2017] derive an similar parameter estimation error bound in ℓ_2 norm with order $O(\sqrt{\frac{s\log p}{n}})$. In fact, for any constant $\delta_4 > 0$, there exists a constant $K(\delta_4) > 0$ (depending only on δ_4) such that if we set $t = K(\delta_4)\sqrt{\frac{n}{s\log p}}$, then with probability at least $1 - \delta_1 - \delta_2 - \delta_3 - \delta_4$, our ℓ_2 error bound attains the same order as that in Li et al. [2017] when $q \ge \log_{\frac{1}{\gamma_s}} \left(\sqrt{\frac{n}{s\log p}} \frac{[l_n(\mathbf{0}) + l_n(\boldsymbol{\beta}^*)]\left(\frac{\nu_s}{m_s c_0^2} + 1\right)}{(1 - \Delta)C_2 n}\right)$.

3.4 A Sketch of the Proofs

Here we give a brief high-level description of proofs of the lemma and the four main theorems, pointing out their main ideas and essential ingredients and where the assumptions are used.

To prove Lemma 1, we show by contradiction that with a high probability, any support which fails to cover the true support will not be the output of Algorithm 1 — there exists a splicing iteration that can sufficiently decrease the loss function and thus continue the splicing procedure. Specifically, let $\mathcal{I}_1 := \hat{\mathcal{I}} \cap \mathcal{A}^*$ be the indices of relevant variables that are excluded from the estimated support, we suppose Algorithm 1 fails in support recovery, i.e., $\mathcal{I}_1 \neq \emptyset$. On one hand, using Assumptions (A1) and (A3), the loss under $\hat{\mathcal{J}}$ output by Algorithm 1 satisfies:

$$l_n(\hat{\boldsymbol{\beta}}) - l_n(\boldsymbol{\beta}^*) \ge nC_2 \|\boldsymbol{\beta}_{\mathcal{I}_1}^*\|_2^2 - \varepsilon(\hat{\mathcal{A}}), \tag{7}$$

where C_2 is defined in Assumption (A4) and $\varepsilon(\cdot)$ represents error terms converge in probability to 0 with a convergence rate specified by the sub-Gaussian assumption (A2). On the other hand, with a well-chosen splicing size k_0 , we denote the active set obtained after the splicing iteration by $\tilde{\mathcal{A}} = (\hat{\mathcal{A}} \setminus S_{k_0,1}) \cup S_{k_0,2}$. By the rules of the splicing procedure and again using Assumptions (A1) and (A3), we can obtain that

$$l_n(\tilde{\boldsymbol{\beta}}) - l_n(\boldsymbol{\beta}^*) \le nC_1 \|\boldsymbol{\beta}_{\mathcal{I}_1}^*\|_2^2 + \varepsilon(\tilde{\mathcal{A}}), \tag{8}$$

where $\tilde{\boldsymbol{\beta}}$ is the minimizer of $l_n(\boldsymbol{\beta})$ under the constraint $\boldsymbol{\beta}_{\tilde{\mathcal{A}}^c} = \mathbf{0}$ and C_1 is defined in Assumption (A4). Intuitively, (7) and (8) indicate that $l_n(\hat{\boldsymbol{\beta}}) - l_n(\boldsymbol{\beta}^*)$ and $l_n(\tilde{\boldsymbol{\beta}}) - l_n(\boldsymbol{\beta}^*)$ can be roughly approximated by a term proportional to $\|\boldsymbol{\beta}_{\mathcal{I}_1}^*\|_2$ — the magnitude of true coefficients that are excluded from the estimated ones. Combining (7), (8) and Assumptions (A4)-(A6), we derive that, with high probability, there will be a contradiction, which completes the proof of Lemma 1.

When $s < s^*$, it can be shown that the difference $l_n(\hat{\beta}^s) - l_n(\hat{\beta}^*)$ dominates the penalty term of GIC, i.e. $F(\hat{\beta}^s) > F(\hat{\beta}^*)$, where $\hat{\beta}^s$ is the output of Algorithm 1 given support size s. On the other hand, when $s > s^*$, the penalty term of GIC plays the leading role, i.e., $F(\hat{\beta}^s) > F(\hat{\beta}^*)$. Combining these two aspects, the GIC attains its minimum at the support size s^* .

The proofs of Theorems 2 and 4 rely heavily on intermediate results in the proof of Lemma 1. A crucial inequality on which we spend much effort establishing is

$$l_n(\boldsymbol{\beta}^q) - l_n(\boldsymbol{\beta}^*) \le \gamma_s \Big[l_n(\boldsymbol{\beta}^{q-1}) - l_n(\boldsymbol{\beta}^*) \Big] + R_1, \tag{9}$$

where $\gamma_s < 1$ is a constant defined in Assumption (A4) and R_1 is some small remainder term to be controlled. Applying (9) recurrently and using

$$l_n(\boldsymbol{\beta}^q) - l_n(\boldsymbol{\beta}^*) \ge nC_2 \|\boldsymbol{\beta}^*_{\mathcal{I}_1}\|_2^2 - \varepsilon(\mathcal{A}^q)$$
(10)

which is essentially identical to (7), we can obtain the bound of the number of iterations described in Theorem 2. From Theorem 2, the loss function decreases drastically as iterations when $s \ge s^*$. When $s < s^*$, the iterations of Algorithm 2 can be determined by thresholding to exclude useless splicing. Thus, the computational complexity of Algorithm 2 is presented in Theorem 3. Finally, using the above inequalities involving $l_n(\beta)$ for certain β and Assumption (A3) that characterizes the curvature of l_n , we can naturally derive the upper bound for $\|\beta^q - \beta^*\|_2$ stated in Theorem 4.

4 Efficient Implementation: Details

We implement the proposed algorithm in a highly efficient **abess** library with both Python and R interfaces. As can be seen from the numerical experiments below, **abess** can have competitive or even less running times compared with other well-known sparse learning software like **glmnet**. **abess** achieves extreme efficiency by leveraging efficient implementation to reduce the time consumption on computing forward and backward sacrifices. In the following, we provide a detailed description of the efficient implementation.

4.1 Simplified Convex Optimization and Early Stopping

In Algorithm 1, we need to solve convex optimization problems: $\tilde{\boldsymbol{\beta}} \leftarrow \arg\min_{\boldsymbol{\beta}_{\mathcal{I}}=0} l_n(\boldsymbol{\beta})$. Directly solving it via a convex optimization solver would consume a large time. To leverage the sparsity nature of this problem, we can turn to solve a simplified problem:

$$\tilde{\boldsymbol{\beta}}_{\mathcal{A}} \leftarrow \arg\min_{\boldsymbol{\beta}_{\mathcal{A}}} - \sum_{i=1}^{n} \{ y_i \boldsymbol{\beta}_{\mathcal{A}}^{\top}(\boldsymbol{x}_i)_{\mathcal{A}} - b(\boldsymbol{\beta}_{\mathcal{A}}^{\top}(\boldsymbol{x}_i)_{\mathcal{A}}) + c(y_i, \phi) \}$$

and pad zero entries to obtain $\tilde{\beta}$. The simplified problem solves the regression coefficient on a much smaller dataset, and thus it is computationally appealing. Since the simplified problem has no closed-form solution, we must perform iterative algorithms to solve it. The Newton method is one of the most popular methods to solve this problem. More precisely, we conduct Newton's updates until $\|\beta_{\mathcal{A}}^{m+1} - \beta_{\mathcal{A}}^m\|_2 \leq \epsilon$ or m > k, where ϵ is convergence tolerance and k is the maximal number of Newton's updates. Generally, setting $\epsilon = 10^{-6}$ and k = 80 returns a desirable coefficient estimation.

Notice that not all of the candidate active sets considered in Algorithm 1 associate with a better solution such that $L - l_n(\tilde{\beta}) > \tau_s$, This inspires us to stop Newton's updates on these active candidates early sets to reduce unnecessary Newton's updates. More precise, after each Newton's update, we check whether the heuristic criterion $l_1 - (k-m) \times (l_2 - l_1) > L - \tau_s$ holds, where $l_1 = l_n(\beta_A^m), l_2 = l_n(\beta_A^{m+1})$. If so, it implies the remaining k - m times Newton update can potentially lead to a lower loss, and thus, it has no reason to stop Newton's updates; otherwise, we can stop Newton's updates. The heuristic criterion is designed based on the fact that the convergence rate of Newton's iterative method is quadratic [Nocedal and Wright, 1999]. It considerably improves the efficiency of computing forward sacrifices and retain the high quality of coefficient estimations.

4.2 Importance-Priority Splicing

Considerable speedup is achieved in a high-dimensional regime by employing an importance-priority splicing procedure, which is motivated by an active set update for the Lasso [Tibshirani et al., 2012]. Specifically, a heavy computational burden comes up when computing forward sacrifices for p - s variables in the inactive set, especially since p is very large. To alleviate this burden, after completing forward and backward sacrifices through all the variables, we perform the splicing iteration on a small but essential subset: the union of the selected variables and $d \ll p$ variables with the more significant forward sacrifices. Once the splicing iteration converges, we re-compute sacrifices for all the variables and update the important subset. If the updated important subset is the same as the previous one, Algorithm 1 is done. Otherwise, the above procedure is repeated. From our numerical experience, the procedure mentioned above can save lots of time; meantime, it keeps Algorithm 1 enjoying the statistical properties presented in Section 3.

5 Simulation Studies

In this section, we are mainly interested in the empirical performance of the ABESS algorithm on logistic regression and Poisson regression. Logistic regression is widely used for classification tasks, and Poisson regression is appropriate when the response is a count. In "Additional Simulation" of Supplementary Material, we also consider the performance of ABESS algorithm on multi-response linear regression (a.k.a., multi-task learning). Before formally analyzing the simulation results, we illustrate our simulation settings in Section 5.1.

5.1 Setup

To synthesize a dataset, we generate multivariate Gaussian realizations $\boldsymbol{x}_1, \ldots, \boldsymbol{x}_n \overset{i.i.d.}{\sim} \mathcal{MVN}(0, \Sigma)$, where Σ is a *p*-by-*p* covariance matrix. We consider two covariance structures for Σ : the independent structure (Σ is an identity matrix) and the constant structure ($\Sigma_{ij} = \rho^{I(i \neq j)}$ for some positive constant ρ). The value of ρ and p will be specified later. We set the true regression coefficient $\boldsymbol{\beta}^*$ as a sparse vector with k non-zero entries that have equi-spaced indices in $\{1, \ldots, p\}$. Finally, given a design matrix $\mathbf{X} = (\boldsymbol{x}_1, \ldots, \boldsymbol{x}_n)^{\top}$ and $\boldsymbol{\beta}^*$, we draw response realizations $\{y_i\}_{i=1}^n$ according to the GLMs.

We assess our proposal via the following criteria. First, to measure the performance of subset selection, we consider the probabilities of covering true active and inactive sets: $\mathbb{P}(\mathcal{A}^* \subseteq \hat{\mathcal{A}})$ and $\mathbb{P}(\mathcal{I}^* \subseteq \hat{\mathcal{I}})$ (here, $\mathcal{I}^* = (\mathcal{A}^*)^c$). We also consider exact support recover probability as $\mathbb{P}(\mathcal{A}^* = \hat{\mathcal{A}})$. Since the probability is unknown, we empirically examine the proportion of recovery for the active set, inactive set, and exact recovery in 200 replications for instead. As for parameter estimation performance, we examine relative error (ReErr) on parameter estimations: $\|\hat{\mathcal{A}} - \mathcal{A}^*\|_2 / \|\mathcal{A}^*\|_2$. Finally, computational efficiency is directly measured by the runtime.

In addition to our proposed algorithms, we compare classical variable selection methods: LASSO [Tibshirani, 1996], SCAD [Fan and Li, 2001], and MCP [Zhang, 2010]. For all these methods, we apply 10-fold cross-validation (CV) and the GIC to select the tuning parameter, respectively. The software for these methods is available at R CRAN (https://cran.r-project.org). The software of all methods is summarized in Table 1. All experiments are carried out on an R environment in a Linux platform with Intel(R) Xeon(R) Gold 6248 CPU @ 2.50GHz.

Table 1: Software for all methods. The values in the parentheses indicate the version number of R packages. The tuning parameter within the MCP/SCAD penalty is fixed at 3/3.7.

Method	ABESS	LASSO	SCAD	MCP
Software Tuning	abess (0.4.0) sparsity s	glmnet (4.1-3) ℓ_1 penalty	ncvreg $(3.13.0)$ λ	ncvreg $(3.13.0)$ λ

5.2 Logistic Regression

The dimension p is fixed as 500 for the logistic regression model. For the constant correlation case, we set $\rho = 0.4$. The non-zero coefficients $\beta_{\mathcal{A}^*}^*$ are set to be $(2, 2, 8, 8, 8, 10, 10, 10, 10)^{\top}$. Now we compare methods listed in Table 1. Figures 1 and 2 present the results on subset selection and parameter estimation when the sample size increases. Out of clarity, we omit the CV results here and defer these results to the Additional Figures in Supplementary Material.



Figure 1: Performance on subset selection under logistic regression when covariates have independent correlation structure (Upper) and constant correlation structure (Lower), measured by three kinds probabilities: $\mathbb{P}(\mathcal{A}^* \subseteq \hat{\mathcal{A}})$, $\mathbb{P}(\mathcal{I}^* \subseteq \hat{\mathcal{I}})$, and $\mathbb{P}(\mathcal{A}^* = \hat{\mathcal{A}})$ that are presented in Left, Middle and Right panels, respectively.

As depicted in the left panel of Figure 1, the probability $\mathbb{P}(\mathcal{A}^* \subseteq \hat{\mathcal{A}})$ approaches 1 as the sample size increases, indicating that all methods, except LASSO in the high correlation setting, can provide a no-false-exclusion estimator when the sample size is sufficiently large. However, when considering $\mathbb{P}(\mathcal{I}^* \subseteq \hat{\mathcal{I}})$, as observed in the middle panel of Figure 1, the LASSO estimator consistently exhibits false inclusions, and the SCAD/MCP estimator shows false inclusions when the covariates are highly correlated. In contrast, only ABESS guarantees that $\mathbb{P}(\mathcal{I}^* \subseteq \hat{\mathcal{I}})$ approaches 1 for large sample sizes.

Furthermore, as evident from the right panel of Figure 1, ABESS accurately recovers the true subset under both correlation settings. While SCAD and MCP can also achieve exact support recovery given a sufficient sample size, ABESS demonstrates support recovery consistency with the smallest sample size, particularly when variables are correlated. It is important to note that although our theory imposes restrictions on the correlation among a small subset of variables (see Assumption (A4)), our algorithm still performs effectively



Figure 2: Performance on parameter estimation under logistic regression models when covariance matrices have independent correlation structure (Left) and exponential correlation structure (Right). The *y*-axis is the median of ReErr in a log scale.

in the constant correlation setting. This setting (i.e., $\rho = 0.4$) violates Assumption (A4) as the correlation between any two variables exceeds 0.183, which is the maximum acceptable pairwise correlation satisfying Assumption (A4).

Moving on to Figure 2, it illustrates the superiority of ABESS in parameter estimation. ABESS visibly outperforms other methods in the small sample size regime and maintains highly competitive performance as the sample size increases. This superiority in parameter estimation is not surprising, as ABESS yields an oracle estimator when the support set is correctly identified. Although SCAD and MCP do not provide algorithmic guarantees for finding the local minimum, they exhibit competitive parameter estimation performance due to their asymptotic unbiasedness. Conversely, the LASSO estimator is biased and performs the worst among all the methods.

5.3 Poisson Regression

For the Poisson regression model, we consider a fixed p value of 500, and set $\rho = 0.2$ for the constant correlation case. The non-zero coefficients $\beta_{\mathcal{A}^*}^*$ are specified as $(1, 1, 1)^{\top}$. Figures 3-4 present the evaluation of subset selection and parameter estimation quality. Examining Figures 3, we observe that for ABESS/SCAD/MCP, the probabilities $\mathbb{P}(\mathcal{A}^* \subseteq \hat{\mathcal{A}})$, $\mathbb{P}(\mathcal{I}^* \subseteq \hat{\mathcal{I}})$, and $\mathbb{P}(\mathcal{A}^* = \hat{\mathcal{A}})$ gradually approach 1 as the sample size n increases. In contrary, the LASSO, regardless of the highest inclusion probability for \mathcal{A}^* , still has a chance of including ineffective variables, especially when variables are correlated. Comparing ABESS, SCAD, and MCP, it is evident that ABESS achieves the highest exact selection probability, followed by SCAD and MCP. Similar to the results in logistic regression, ABESS achieves exact selection of the effective variables with the smallest sample size under the constant correlation structure. Regarding the quality of parameter estimation, the ReErr of all methods reasonably decreases as the sample size n increases. Again, ABESS exhibits the least estimation error in terms of the ℓ_2 -norm, which coincides with the results on logistic regression. It is worth noting that our method demonstrates consistency and polynomial complexity under Poisson regression, even though it violates the sub-Gaussian assumption. This is because the current framework of proofs allows for the relaxation of Assumption (A2) to a sub-exponential distribution assumption, enabling the establishment of similar theoretical properties.



Figure 3: Performance on subset selection under Poisson regression when covariates have independent correlation structure (Upper) and constant correlation structure (Lower), measured by three kinds probabilities: $\mathbb{P}(\mathcal{A}^* \subseteq \hat{\mathcal{A}})$, $\mathbb{P}(\mathcal{I}^* \subseteq \hat{\mathcal{I}})$, and $\mathbb{P}(\mathcal{A}^* = \hat{\mathcal{A}})$ that are presented in Left, Middle and Right panels, respectively.

5.4 Computational analysis

We compare the runtime of different methods in Table 1 for the logistic regression and Poisson regression models in Sections 5.2 to 5.3. The runtime results are summarized in Figure 5, indicating that ABESS demonstrates superior computational efficiency compared to state-of-the-art variable selection methods. For instance, when n = 3000, ABESS is at least four times faster than its competitors in logistic regression under an independent correlation structure. Furthermore, regardless of logistic regression or Poisson regression, ABESS exhibits similar computational performance, while other competitors run much faster when the pairwise correlation is higher. Lastly, it is important to note that the runtime of ABESS scales polynomially with sample sizes, aligning with the complexity presented in Theorem 3.



Figure 4: Performance on parameter estimation under Poisson regression models when covariance matrices have independent correlation structure (Left) and exponential correlation structure (Right). The y-axis is the median of ReErr in a log scale.



Figure 5: Average runtime (measured in seconds) on logistic regression (Upper panel) and Poisson regression (Lower panel). The results on two types of covariances matrix Σ , the independent correlation structure and constant correlation structure, are presented in the left and right panels, respectively. The error bars represent two times the standard errors.

6 Conclusion and Discussion

In this paper, we look for algorithms for the best-subset selection problem in GLM that will be useful to statisticians and practitioners. We devise novel algorithms to pursue high-quality sparse solutions iteratively, and thus, circumvent the enumeration of all possible subsets. More importantly, under mild assumptions, we establish best-subset-screening guarantees and polynomial computational complexity for our algorithms in a high-probability sense. Our research on logistic regression, Poisson regression, and multi-response regression shows that, equipped with efficient implementation, the ABESS algorithm has excellent computational and statistical properties. The ABESS algorithms are packaged in an openly shared R/Python package abess [Zhu et al., 2021] that can be used by data scientists worldwide.

Several intriguing directions should be investigated further. One of our future directions is to apply our algorithmic ideas to a broader range of convex optimization problems such as the GLMs with latent variables [Zheng et al., 2021]. The application of our proposal to causal inference is another intriguing topic [Lin et al., 2015].

References

- Peter McCullagh and John Nelder. *Generalized Linear Models, Second Edition*. Chapman & Hall, 1989.
- Ronald R Hocking and RN Leslie. Selection of the best subset in regression analysis. *Technometrics*, 9(4):531–540, 1967.
- Hirotogu Akaike. Information theory and an extension of the maximum likelihood principle. In *Selected papers of hirotugu akaike*, pages 199–213. Springer, 1998.
- Gideon Schwarz. Estimating the dimension of a model. *The Annals of Statistics*, 6(2): 461–464, 1978.
- David R. Anderson and Kenneth P. Burnham. *Model selection and multi-model inference*. NY: Springer-Verlag, 2020.
- LR LaMotte and Ronald R Hocking. Computational efficiency in the selection of regression variables. *Technometrics*, 12(1):83–93, 1970.
- Patrenahalli M. Narendra and Keinosuke Fukunaga. A branch and bound algorithm for feature subset selection. *IEEE Transactions on computers*, 26(09):917–922, 1977.
- Balas Kausik Natarajan. Sparse approximate solutions to linear systems. SIAM Journal on Computing, 24(2):227–234, 1995.

- Vincent Calcagno and Claire de Mazancourt. glmulti: An r package for easy automated model selection with (generalized) linear models. *Journal of Statistical Software*, 34(12): 1–29, May 2010. doi:10.18637/jss.v034.i12.
- Canhong Wen, Aijun Zhang, Shijie Quan, and Xueqin Wang. Bess: An r package for best subset selection in linear, logistic and cox proportional hazards models. *Journal of Statistical Software*, (4):1–24, 2020. doi:10.18637/jss.v094.i04.
- Robert Tibshirani. Regression shrinkage and selection via the lasso. Journal of the Royal Statistical Society. Series B (Methodological), pages 267–288, 1996.
- Hui Zou and Trevor Hastie. Regularization and variable selection via the elastic net. Journal of the Royal Statistical Society: Series B (Statistical Methodology), 67(2):301–320, 2005.
- Emmanuel Candes and Terence Tao. The Dantzig selector: Statistical estimation when p is much larger than n. *The Annals of Statistics*, 35(6):2313–2351, December 2007. doi:10.1214/009053606000001523.
- Jianqing Fan and Runze Li. Variable selection via nonconcave penalized likelihood and its oracle properties. Journal of the American statistical Association, 96(456):1348–1360, 2001.
- Cunhui Zhang. Nearly unbiased variable selection under minimax concave penalty. *The* Annals of Statistics, 38(2):894–942, 2010.
- Xiaotong Shen, Wei Pan, and Yunzhang Zhu. Likelihood-based selection and sharp parameter estimation. *Journal of the American Statistical Association*, 107(497):223–232, 2012. doi:10.1080/01621459.2011.645783.
- Mee Young Park and Trevor Hastie. L1-regularization path algorithm for generalized linear models. Journal of the Royal Statistical Society: Series B (Statistical Methodology), 69 (4):659–677, September 2007. ISSN 1369-7412. doi:10.1111/j.1467-9868.2007.00607.x.
- Gareth M. James and Peter Radchenko. A generalized Dantzig selector with shrinkage tuning. *Biometrika*, 96(2):323–337, June 2009. doi:10.1093/biomet/asp013.
- Jianqing Fan and Jinchi Lv. Nonconcave penalized likelihood with npdimensionality. *IEEE Transactions on Information Theory*, 57(8):5467–5484, 2011. doi:10.1109/TIT.2011.2158486.
- Cunhui Zhang and Jian Huang. The sparsity and bias of the lasso selection in highdimensional linear regression. *The Annals of Statistics*, 36(4):1567–1594, 2008.
- S.G. Mallat and Zhifeng Zhang. Matching pursuits with time-frequency dictionaries. *IEEE Transactions on Signal Processing*, 41(12):3397–3415, 1993. doi:10.1109/78.258082.

- Aurelie Lozano, Grzegorz Swirszcz, and Naoki Abe. Group orthogonal matching pursuit for logistic regression. In Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics, volume 15, pages 452–460, Fort Lauderdale, FL, USA, 11–13 Apr 2011.
- Sanford Weisberg. Applied linear regression, volume 528. John Wiley & Sons, 2005.
- Jerome Friedman, Trevor Hastie, and Robert Tibshirani. *The elements of statistical learning: data mining, inference, and prediction.* Springer Science & Business Media, 2009.
- Thomas Blumensath. Compressed sensing with nonlinear observations and related nonlinear optimization problems. *IEEE Transactions on Information Theory*, 59(6):3466–3474, June 2013. doi:10.1109/TIT.2013.2245716.
- Thomas Blumensath and Mike E. Davies. Iterative hard thresholding for compressed sensing. *Applied and Computational Harmonic Analysis*, 27(3):265–274, November 2009. doi:10.1016/j.acha.2009.04.002.
- Sohail Bahmani, Bhiksha Raj, and Petros T Boufounos. Greedy sparsity-constrained optimization. Journal of Machine Learning Research, 14(1):807–841, 2013.
- Jian Huang, Yuling Jiao, Yanyan Liu, and Xiliang Lu. A constructive approach to ℓ_0 penalized regression. Journal of Machine Learning Research, 19(10):1–37, 2018.
- Shenglong Zhou, Naihua Xiu, and Houduo Qi. Global and quadratic convergence of Newton hard-thresholding pursuit. *Journal of Machine Learning Research*, 22(12):1–45, 2021.
- Amir Beck and Yonina C Eldar. Sparsity constrained nonlinear optimization: Optimality conditions and algorithms. *SIAM Journal on Optimization*, 23(3):1480–1509, 2013.
- Antoine Dedieu, Hussein Hazimeh, and Rahul Mazumder. Learning sparse classifiers: Continuous and mixed integer optimization perspectives. Journal of Machine Learning Research, 22(135):1–47, 2021.
- Simon Foucart. Hard thresholding pursuit: an algorithm for compressive sensing. SIAM Journal on numerical analysis, 49(6):2543–2563, 2011. ISSN 0036-1429.
- Junxian Zhu, Canhong Wen, Jin Zhu, Heping Zhang, and Xueqin Wang. A polynomial algorithm for best-subset selection problem. *Proceedings of the National Academy of Sciences*, 117(52):33117–33123, 2020.
- Jianqing Fan and Rui Song. Sure independence screening in generalized linear models with NP-dimensionality. The Annals of Statistics, 38(6):3567–3604, December 2010. doi:10.1214/10-AOS798.

- Jin Zhu, Liyuan Hu, Junhao Huang, Kangkang Jiang, Yanhang Zhang, Shiyun Lin, Junxian Zhu, and Xueqin Wang. abess: A fast best subset selection library in python and r. arXiv:2110.09697, 2021.
- Yingying Fan and Cheng Yong Tang. Tuning parameter selection in high dimensional penalized likelihood. Journal of the Royal Statistical Society: Series B (Statistical Methodology), 75(3):531–552, 2013.
- Emre Barut, Jianqing Fan, and Anneleen Verhasselt. Conditional sure independence screening. Journal of the American Statistical Association, 111(515):1266–1277, July 2016. doi:10.1080/01621459.2015.1092974.
- Jerome Friedman, Trevor Hastie, and Rob Tibshirani. Regularization paths for generalized linear models via coordinate descent. *Journal of statistical software*, 33(1):1, 2010.
- Philippe Rigollet. Kullback-leibler aggregation and misspecified generalized linear models. *The Annals of Statistics*, pages 639–665, 2012.
- Sahand N. Negahban, Pradeep Ravikumar, Martin J. Wainwright, and Bin Yu. A unified framework for high-dimensional analysis of *m*-estimators with decomposable regularizers. *Statistical Science*, 27(4):538–557, November 2012. doi:10.1214/12-STS400.
- Chengchun Shi, Rui Song, Zhao Chen, and Runze Li. Linear hypothesis testing for high dimensional generalized linear models. *The Annals of Statistics*, 47(5):2671, 2019.
- Zhe Fei and Yi Li. Estimation and inference for high dimensional generalized linear models: A splitting and smoothing approach. *Journal of Machine Learning Research*, 22(58):1–32, 2021.
- Xingguo Li, Lin Yang, Jason Ge, Jarvis Haupt, Tong Zhang, and Tuo Zhao. On quadratic convergence of dc proximal Newton algorithm in nonconvex sparse learning. Advances in neural information processing systems, 30, 2017.
- Xiaotong Yuan, Ping Li, and Tong Zhang. Gradient hard thresholding pursuit. Journal of Machine Learning Research, 18(166):1–43, 2018.
- Jian Huang, Yuling Jiao, Lican Kang, Jin Liu, Yanyan Liu, and Xiliang Lu. GSDAR: A fast Newton algorithm for ℓ₀-regularized generalized linear models with statistical guarantee. Computational Statistics, 37(1):507–533, March 2022. doi:10.1007/s00180-021-01098-z.
- Jorge Nocedal and Stephen J. Wright. Numerical optimization. Springer, 1999.
- Robert Tibshirani, Jacob Bien, Jerome Friedman, Trevor Hastie, Noah Simon, Jonathan Taylor, and Ryan J. Tibshirani. Strong rules for discarding predictors in lasso-type problems. Journal of the Royal Statistical Society: Series B (Statistical Methodology), 74 (2):245–266, 2012. doi:https://doi.org/10.1111/j.1467-9868.2011.01004.x.

- Zemin Zheng, Jinchi Lv, and Wei Lin. Nonsparse learning with latent variables. *Operations Research*, 69(1):346–359, January 2021. doi:10.1287/opre.2020.2005.
- Wei Lin, Rui Feng, and Hongzhe Li. Regularization methods for high-dimensional instrumental variables regression with an application to genetical genomics. *Jour*nal of the American Statistical Association, 110(509):270–288, January 2015. doi:10.1080/01621459.2014.908125.