IS THIS NETWORK FOREST-BASED?

K.T. HUBER, V. MOULTON, G. E. SCHOLZ, L. VAN IERSEL

ABSTRACT. In evolutionary biology, networks are becoming increasingly used to represent evolutionary histories for species that have undergone non-treelike or reticulate evolution. Such networks are essentially directed acyclic graphs with a leaf set that corresponds to a collection of species, and in which non-leaf vertices with indegree 1 correspond to speciation events and vertices with indegree greater than 1 correspond to reticulate events such as gene transfer. Recently forest-based networks have been introduced, which are essentially (multi-rooted) networks that can be formed by adding some arcs to a collection of phylogenetic trees (or phylogenetic forest), where each arc is added in such a way that its ends always lie in two different trees in the forest. In this paper, we consider the complexity of deciding whether or not a given network is proper forest-based, that is, whether it can be formed by adding arcs to some underlying phylogenetic forest which contains the same number of trees as there are roots in the network. More specifically, we show that it can be decided in polynomial time whether or not a binary, tree-child network with $m \ge 2$ roots is proper forest-based in case m = 2, but that this problem is NP-complete for $m \ge 3$. We also give a fixed parameter tractable (FPT) algorithm for deciding whether or not a network in which every vertex has indegree at most 2 is proper forest-based. A key element in proving our results is a new characterization for when a network with m roots is proper forestbased which is given in terms of the existence of certain *m*-colorings of the vertices of the network.

Keywords forest-based network, phylogenetic network, tree-child network, phylogenetic forest, graph coloring

1. INTRODUCTION

Recently, the concept of forest-based networks has been introduced within the area of phylogenetics [5]. Informally, a forest-based network is defined as follows (full definitions of the terms used in the introduction are given in the next section). A *phylogenetic tree* is a rooted tree whose leaf-set corresponds to a collection of taxa or species; a *phylogenetic forest* is a collection of leaf-disjoint phylogenetic trees. A *forest-based network* is essentially a directed acyclic graph N that can be formed by adding a set of arcs to a phylogenetic forest so that the end vertices of each added arc lie in two different trees of the forest; N is *proper* if the number of sources or roots of the network is equal to the number of trees in the forest. For example, the network in Figure 1 is proper forest-based. Forest-based networks can be regarded as a certain type of *phylogenetic network*, and are related to the intensively studied *tree-based networks* [3] (see e.g. [10, 8] for recent reviews of phylogenetic networks, including more details concerning tree-based networks).

Date: August 23, 2023.

School of Computing Sciences, University of East Anglia, UK.



FIGURE 1. A proper forest-based network N on ten leaves. Each of the three phylogenetic trees in the underlying forest represents a hypothetical butterfly lineage with main wing pattern indicated next to the root of the tree. The network N is the result of adding dashed arcs in between pairs of trees in the forest. Each added arc corresponds to some genetic material being introduced into a lineage from one of the others, which results in a wing pattern change for the descendants.

Forest-based networks arise in the study of reticulate evolutionary processes in which species exchange genetic information through processes such as introgression [9] and lateral gene transfer [5]. In the case of introgression, the phylogenetic trees underlying a forest-based network correspond to the evolutionary histories of different subgroups or lineages within a certain species. The arcs in between different trees then represent the past interchange of genetic material between these lineages. A well-studied example of this phenomenon is butterfly evolution, where the genetic material that is swapped between lineages influences wing patterns [1, 11]. Figure 1 shows a hypothetical example to illustrate this phenomenom. The use of a special type of forest-based network called an *overlaid species forest* to analyse introgression can be found in [9].

In this paper we are interested in the following recognition problem for *networks* (a certain type of directed acyclic graph as defined in the next section):

(P) Is a given network N proper forest-based?

Our main results are as follows. A network is *binary* if all vertices have indegree and outdegree at most 2 and all non-root vertices have overall degree 1 or 3. A network is *tree-child* if each non-leaf vertex has at least one child with indegree 1. For a network N with v vertices, m roots, n leaves, r vertices with indegree at least 2, and maximum outdegree Δ , we shall prove that:

- (R1) If N is binary, tree-child and m = 2, then (P) can be decided in $O(n \cdot r)$ time.
- (R2) If N is binary, tree-child and $m \ge 3$, then (P) is NP-complete.
- (R3) If N is tree-child, $m \ge 2$, with maximum outdegree 2 and maximum indegree at most 3, then (P) is NP-complete.
- (R4) If every vertex in N has indegree at most 2, then there is a fixed parameter tractable algorithm with parameters r, m and Δ for deciding (P), which is linear in v.

We now briefly summarise the rest of the contents of this paper. In the next section, we present some formal definitions concerning networks. In Section 3, we derive a key characterization for when a network with $m \ge 2$ roots is proper forest-based in terms of the existence of an *m*-coloring of the vertices of the network that satisfies certain properties (Lemma 3.1). In Section 4, we establish Statement (R3) by reducing from the SET-SPLITTING problem (Theorem 4.1). Using colorings, in Section 5 we present an alternative proof for Statement (R3) in the special case $m \ge$ 3 by reducing from the GRAPH *m*-COLORABILTY problem. The construction that we use in this proof is then used again in Section 6 to prove that Statement (R2) holds (Theorem 6.2). Using the concept of so-called omni-extensions [5] we also prove Statement (R1) (Theorem 6.3). Finally, in Section 7 we prove Statement (R4), before concluding in Section 8 with a brief discussion of potential directions for future research.

2. DEFINITIONS

From now on, X is a finite set with $|X| \ge 2$. Suppose that N is a connected, directed acyclic graph (DAG) and v is a vertex in N. Then v is a *leaf* if it is a sink vertex, v is a *root* if it is a source vertex, and v is a *reticulation* if it has indegree at least 2. If v is not a leaf, then v is an *internal vertex* of N. We call an arc a = (u, v) of N *internal* if u and v are both internal vertices of N. If v is an internal vertex that has indegree 1 or less, then v is a *tree-vertex*.

We call N a *network* (on X) if it has leaf-set X (which we also denote by L(N)), each leaf has indegree 1, every root has outdegree at least 2, every reticulation has outdegree 1, and there is no vertex with indegree and outdegree 1. If N has m roots, we also call it an *m-network*¹. We say that two *m*-networks N and N' on X are *isomorphic* if there is a DAG isomorphism between N and N' which is the identity on X.

A network is *semi-binary* if all reticulations have indegree 2. It is *quasi-binary* if all treevertices have outdegree 2 and all reticulations have indegree 2 or 3. Note that a network is binary if it is quasi-binary and semi-binary. A network is *tree-child* if every internal vertex has a child that is a tree-vertex or a leaf.

A phylogenetic network (on X) is a network on X with exactly one root and a phylogenetic tree (on X) is a phylogenetic network on X with no reticulations. For technical reasons, we shall also call an isolated vertex v a phylogenetic tree (on $\{v\}$). We say that two distinct leaves x, y of a phylogenetic tree T form a cherry if they share a parent, and we denote such a cherry by $\{x, y\}$. We call a phylogenetic tree T on X a caterpillar tree (on X) if T has a unique cherry and every internal arc of T lies on the directed path from the root of T to the parent of the cherry.

A *phylogenetic forest* (on X) is a directed graph F whose connected components are phylogenetic trees and such that $L(T) \cap L(T') = \emptyset$ for any distinct trees T, T' in F and $X = \bigcup_{T \in F} L(T)$. For convenience, we will sometimes call a non-empty set of phylogenetic trees a phylogenetic forest.

Suppose N = (V,A) is an *m*-network on X, for some $m \ge 2$. Then N is called *forest-based* if there exists a subset $A' \subseteq A$ such that F' = (V,A') is a forest with leaf set X and every arc in A - A'has end vertices that are in different trees of F'. We call F' a *subdivision forest* of N. Moreover the phylogenetic forest F obtained from F' by repeatedly suppressing any vertices of indegree and outdegree 1 and any outdegree 1 roots until this is no longer possible is called a *base forest* of N. Note that, in particular, we can think of F as being embedded within N. In addition, we call a forest-based *m*-network *proper forest-based* if it has a base forest containing *m* trees. See [5, 6] for more on such networks.

¹Note that this is more general than the definition of an *m*-network given in [5].

3. COLORINGS AND PROPER FOREST-BASED NETWORKS

For *G* a (simple) graph and $C \neq \emptyset$ a finite set, a surjective map $\sigma : V(G) \to C$ is a |C|-coloring of *G*. We sometimes refer to the elements of *C* as colors. For $v \in V(G)$, we call $\sigma(v)$ the color of *v* under σ , or simply the color of *v* if σ is clear from the context. We call a coloring σ of *G* proper if $\sigma(x) \neq \sigma(y)$ holds for any two adjacent vertices $x, y \in V(G)$. We now prove a useful lemma which characterizes proper forest-based networks in terms of colorings of their vertex sets.

Lemma 3.1. Let N be an m-network on X, $m \ge 2$. Then N is proper forest-based if and only if there exists an m-coloring of N such that:

- (C1) Each non-root vertex of N has the same color as exactly one of its parents.
- (C2) Each internal vertex of N has the same color as at least one of its children.

Proof. Suppose first that N is proper forest-based. Let F' be a corresponding subdivision forest of N. We claim that the map $\sigma : V(N) \to F'$ that assigns to each $v \in V(N)$ the tree in F' that contains v in its vertex set is an *m*-coloring of N that satisfies (C1) and (C2).

To see (C1), let v be a non-root vertex of N. Since the root of each tree of F' is a root of N, v is not the root of $\sigma(v)$. So at least one of the parents of v has the same color as v. If v has two or more parents enjoying this property, then v has indegree 2 or more in $\sigma(v)$, a contradiction as $\sigma(v)$ is a tree. Hence, (C1) holds.

To see (C2), let v be an internal vertex of N. Since L(N) = L(F'), v is not a leaf of $\sigma(v)$. Hence, there exists at least one child u of v in N such that $\sigma(u) = \sigma(v)$. Thus, (C2) holds.

Conversely, suppose that there exists a coloring σ of N = (V,A) satisfying (C1) and (C2). Let F' be the graph with vertex set V and edge set $A' = \{(u,v) \in A : \sigma(u) = \sigma(v)\}$. By (C1), no vertex in F' has indegree greater than 1. So, F' = (V,A') is a subdivision of N in the form of a forest. By (C2), we have L(N) = L(F') and so F' is a subdivision forest of N. Since the end vertices of each arc in A - A' have different colors, they appear in different connected components (trees) of F'. Hence, N is proper forest-based.

Note that if σ is an *m*-coloring of an *m*-network *N* satisfying (C1) and (C2), then these two properties, together with the fact that the image set of σ has size exactly *m*, imply that no two roots of *N* have the same color under σ .

4. TREE-CHILD NETWORKS

In this section, we shall prove that Statement (R3) holds. To do this we shall reduce from the NP-complete SET-SPLITTING decision problem [4, page 221] which is as follows.

• Given some finite set *Y*, $|Y| \ge 3$, and a set \mathscr{C} of size-3 subsets of *Y*, is there a bipartition $\{A, B\}$ of *Y* such that, for all $S \in \mathscr{C}$, $S \cap A \neq \emptyset$ and $S \cap B \neq \emptyset$?

Theorem 4.1. For $m \ge 2$, the problem of deciding whether or not a quasi-binary tree-child *m*-network is proper forest-based is NP-complete.

Proof. The problem is in the class NP since, for each proper forest-based, quasi-binary, tree-child *m*-network, an *m*-coloring satisfying the conditions of Lemma 3.1 can function as a certificate and these conditions can be verified in polynomial time.

We shall prove NP-completeness by giving a reduction from SET-SPLITTING. Suppose that we are given a collection \mathscr{C} of size-3 subsets of X. For $m \ge 2$, we create an m-network as follows (see Figure 2 where we illustrate the various constructions that we perform as part of this proof in terms of an example). Let T_1 and T_2 denote two isomorphic caterpillars trees on a set Y with |X| + 1 leaves. Without loss of generality we may assume that $Y = X \cup \{l\}$ and that $l \notin X$ is a leaf in the unique cherry of T_1 (and therefore also of T_2). For all $x \in X$, we identify leaf x of T_1 with leaf x of T_2 . The resulting network has |X| reticulations. We call all vertices in the resulting DAG *GenI vertices*.

If m > 2, we add m - 1 vertices of indegree 0 as follows. For all $2 \le i \le m - 1$, we add three vertices r_i , h_i , l_i , and the arcs (r_i, h_i) , (h_i, l_i) , and (r_i, h_{i-1}) , where we define h_1 as the root of T_2 . Then, we add two vertices r_m , l_m and the arcs (r_m, l_m) and (r_m, h_{m-1}) . Furthermore, we choose for all r_i , $2 \le i \le m - 1$, the outgoing arc (r_i, h_{i-1}) and subdivide it by a new vertex s_i . To that vertex we then add a leaf l'_i via the arc (s_i, l'_i) . We call all vertices added during this step *GenO* vertices.

Assume for the remainder that $m \ge 2$. For all $x \in X$, we attach to x a path P_x of length c(x) + 1 via an arc (x, a_x) , where a_x is the first vertex on P_x and c(x) is the number of sets in \mathscr{C} containing x. We then bijectively label for each $x \in X$ the internal vertices of P_x with the elements in \mathscr{C} that contain x. We call all vertices added during this step *GenII vertices*. Finally, for all $S \in \mathscr{C}$ and all $x \in S$, we create a reticulation h_S with parents the vertices on P_x labelled by S and add a leaf l_S to h_S by adding the arc (h_S, l_S) . We call vertices added during this step *GenII vertices*.

Let N denote the resulting DAG. By construction, N is an *m*-network on L(N) that is quasibinary and tree-child. We now show that there exists a solution to the SET-SPLITTING problem for X and \mathscr{C} if and only if N is proper forest-based, which will complete the proof.

Suppose first that $\{A, B\}$ is a solution to the SET-SPLITTING problem for X and \mathscr{C} . We define an *m*-coloring $\sigma : V(N) \rightarrow \{1, ..., m\}$ for N as follows. Let $v \in V(N)$. If v is a GenI treevertex, we put $\sigma(v) = 1$ if $v \in V(T_1)$, and $\sigma(v) = 2$ if $v \in V(T_2)$. If v is a Gen0 vertex, then if there exists some $2 \le i \le m - 1$ such that $v \in \{r_i, h_i, l_i, s_i, l'_i\}$, we put $\sigma(v) = i$. Otherwise, $v \in \{r_2, h_2, l_2, r_m, l_m\}$ and we put $\sigma(v) = 2$ if $v \in \{r_2, l_2, h_2\}$, and if $v \in \{r_m, l_m\}$ we put $\sigma(v) = m$. If $v \in V(P_x) \cup \{x\}$, some $x \in X$, then we put $\sigma(v) = 1$ if $x \in A$ and $\sigma(x) = 2$ if $x \in B$. Finally, if $v \in \{h_S, l_S\}$, some $S \in \mathscr{C}$, then we put $\sigma(v) = 1$ if $|S \cap A| = 1$ and $\sigma(v) = 2$ if $|S \cap B| = 1$. Note that since $\{A, B\}$ is a solution to the SET-SPLITTING problem, precisely one of these equalities always holds. We claim that σ satisfies (C1) and (C2) of Lemma 3.1 which implies that N is proper forest-based.

To see that (C1) holds, note first that, by construction, all non-root vertices *v* have at least one parent *u* satisfying $\sigma(u) = \sigma(v)$. Suppose now that *v* is a reticulation-vertex. If m > 2 and *v* is a Gen0 vertex, then $v = h_i$ for some $2 \le i \le m - 1$. In particular, *v* is a child of r_i and so $\sigma(v) = \sigma(r_i) = i$, by definition. If *v* is a GenI vertex, then $\sigma(v) \in \{1,2\}$ and *v* has exactly two parents. Calling them v_1 and v_2 we have $\sigma(v_1), \sigma(v_2) \in \{1,2\}$ and $\sigma(v_1) \ne \sigma(v_2)$. Thus, exactly one of $\sigma(v_1) = \sigma(v)$ or $\sigma(v_2) = \sigma(v)$ holds. If *v* is a GenIII vertex, then *v* has three parents v_1, v_2, v_3 and two of them must have the same color under σ . Without loss of generality assume that that $\sigma(v_2) = \sigma(v_3)$. By definition, $\sigma(v) = \sigma(v_1)$ follows. Hence, (C1) holds.

To see that (C2) holds, let $v \in V(N) - L(N)$. If v is a Gen0 vertex (assuming that N has such vertices!), then either $v \in \{r_i, h_i, s_i\}$, some $2 \le i \le m - 1$, or $v \in \{r_2, h_2, r_m\}$. By definition of σ ,

there exists a child of *v* that has the same color under σ as *v*. If *v* is a non-reticulation GenI vertex, then *v* is an internal vertex of either T_1 or T_2 . Since, for all $i = 1, 2, T_i$ is a caterpillar tree and, by definition of σ , all vertices on the directed path from the root of T_i to *l* have the same color under σ , (C2) follows. If *v* is a GenII vertex or a reticulation GenI vertex, then $v \in \{x\} \cup V(P_x)$, some $x \in X$. Since P_x is a directed path whose first vertex is adjacent with *x*, the definition of σ implies (C2) again. Finally, if *v* is a GenIII vertex, then $v = h_S$, some $S \in \mathscr{C}$. By definition, $\sigma(h_S) = \sigma(l_S)$. Hence (C2) also holds in this case.

Conversely, suppose that *N* is proper forest-based. By Lemma 3.1, there exists an *m*-coloring σ of *N* satisfying (C1) and (C2). Note that, by construction, the set of all GenI reticulations of *N* is *X* and also that every element in *X* is a descendant of both r_2 and the root ρ_1 of T_1 . By (C1), it follows that either $\sigma(x) = \sigma(r_2)$ or $\sigma(x) = \sigma(\rho_1)$ holds for all $x \in X$. Let $A = \{x \in X : \sigma(x) = \sigma(\rho_1)\}$ and $B = \{x \in X : \sigma(x) = \sigma(r_2)\}$. Clearly, $\{A, B\}$ is a bipartition of *X* as $\sigma(r_2) \neq \sigma(\rho_1)$.

We claim that $\{A, B\}$ is a solution to the SET-SPLITTING problem. To see this, consider a set $S = \{x, y, z\} \in \mathscr{C}$. By construction, h_S has three ancestors, all of which are GenII vertices that are a descendant of x, y and z, respectively. Since a GenII vertex is a vertex on P_w , some $w \in X$, (C1) implies that $\sigma(w) = \sigma(u)$, for all $u \in V(P_w)$. Moreover, by (C2), exactly one parent u of h_S satisfies $\sigma(u) = \sigma(h_S)$. Without loss of generality, we may assume that u is a descendant of x. Hence, $\sigma(x) \neq \sigma(y) = \sigma(z)$. By definition of A and B, it follows that $S \cap A \neq \emptyset$ and $S \cap B \neq \emptyset$. Since this holds for all $S \in \mathscr{C}$, the claim follows.



FIGURE 2. For m = 2, the *m*-network *N* for $X = \{a, b, c, d, e\}$ and $\mathscr{C} = \{\{a, b, c\}, \{a, c, e\}, \{b, c, d\}\}$, as described in the proof of Theorem 4.1. Since m = 2, there are no Gen0 vertices. GenI, GenII, and GenIII vertices are indicated as vertices in a band labelled Gen I, GenII, and GenIII, respectively. For clarity purposes, we have indicated the reticulation with the set in \mathscr{C} its three parents correspond to and not the parents themselves. A 2-coloring $\sigma : V(N) \to \{\bullet, \circ\}$ associated to the solution $A = \{a, b\}, B = \{c, d, e\}$ of the SET-SPLITTING problem for (X, \mathscr{C}) .

IS THIS NETWORK FOREST-BASED?

5. TREE-CHILD NETWORKS REVISITED

In this section, we shall give an alternative proof for Statement (R3) in the special case $m \ge 3$ using colorings. We do this in part because the construction that we shall use in the proof will be used in the next section for establishing our results concerning binary, tree-child *m*-networks. We shall reduce from the GRAPH *m*-COLORABILTY decision problem for $m \ge 3$ ([4, page 190]) which is as follows.

• Given a (simple) graph G, does there exist a proper *m*-coloring of G?

Note that this problem can be solved in polynomial time for m = 2 but is NP-complete for each $m \ge 3$. Hence, the reduction below can only be used for $m \ge 3$.

Proposition 5.1. For $m \ge 3$, the problem of determining whether a quasi-binary tree-child mnetwork is proper forest-based is NP-complete.

Proof. Membership of NP can be argued in the same way as in the proof of Theorem 4.1. We prove NP-completeness by giving a reduction from GRAPH *m*-COLORABILTY.

Suppose that we are given a graph *G* with vertex set *X*. Then we construct an *m*-network *N* as follows (see Figure 3 where we illustrate the various constructions performed in this proof in terms of an example). Let T_1, \ldots, T_m denote *m* isomorphic caterpillars trees on a set *Y* with |X| + 1 leaves. Without loss of generality we may assume that $Y = X \cup \{l\}$ and that $l \notin X$ is a leaf in the unique cherry of T_1 (and therefore also of all $T_i, 2 \le i \le m$). For all $x \in X$ and all $1 \le i \le m$, we identify the leaves *x* to obtain a reticulation *x* of indegree *m*. We call all vertices in the resulting graph *GenI vertices*.

Denoting for all $x \in X$ the degree of x in G by $\deg_G(x)$, we attach a directed path P_x of length $\deg_G(x) + 1$ via an arc (x, a_x) to the first vertex a_x of P_x . We label each internal vertex of P_x with an edge in G that is incident with x and call all vertices added during this step *GenII vertices*. Finally, for all edges e of G, we create a new reticulation h_e with parents the two vertices in the DAG constructed thus far labelled e and add a leaf l_e as a child to h_e . We call vertices added during this step *GenIII vertices*.

Let N denote the resulting DAG. One can easily verify that N is an *m*-network that is quasibinary and tree-child. We now show that there exists a solution to GRAPH *m*-COLORABILTY for G if and only if N is proper forest-based, which will complete the proof.

Suppose first that there exists a proper *m*-coloring $\kappa : X \to \{1, ..., m\}$ of *G*. From κ , we derive an *m*-coloring $\sigma : V(N) \to \{1, ..., m\}$ of *N* as follows. Let $v \in V(N)$. If *v* is a GenI tree-vertex then there exists some $1 \le i \le m$ such that $v \in V(T_i)$. In this case, we put $\sigma(v) = i$. If *v* is a GenII vertex or a reticulation GenI vertex, then $v \in \{x\} \cup V(P_x)$, some $x \in X$, and we put $\sigma(v) = \kappa(x)$. Finally, if *v* is a GenIII vertex, then $v \in \{h_e, l_e\}$ for some edge $e = \{x, y\}$ of *G*. In this case, we choose $\sigma(v) \in \{\kappa(x), \kappa(y)\}$ if $v = h_e$ and we put $\sigma(v) = \sigma(h_e)$ if $v = l_e$.

To see that N is proper forest-based it suffices to show by Lemma 3.1 that σ is an *m*-coloring of N that satisfies Properties (C1) and (C2).

To see that (C1) holds, note first that, by construction, all non-root vertices v of N have at least one parent u satisfying $\sigma(u) = \sigma(v)$. Suppose now that v is a reticulation. Then v is either a reticulation GenI vertex or $v = h_e$ some edge e of G. If v is a reticulation GenI vertex then $v \in X$. Hence, v has m parents v_1, \ldots, v_m . Since, for each $1 \le i \le m$, there exists a unique tree

 T_i that contains v_i it follows that there exists a unique $1 \le j \le m$ such that $\sigma(v) = \sigma(v_j) = j$. If $v = h_e$ then let $x, y \in X$ such that $e = \{x, y\}$. Without loss of generality, assume that v_1 is a vertex on P_x and that v_2 is a vertex on P_y . Assume that we have chosen $\sigma(h_e) = \kappa(x)$ in the definition of σ . Then $\sigma(h_e) = \kappa(x) = \sigma(v_1)$. Since κ is a proper *m*-coloring of *G*, we also have $\sigma(v_2) = \kappa(y) \neq \kappa(x)$. Thus, (C1) holds.

To see that (C2) holds, let $v \in V(N) - L(N)$. If v is a non-reticulation GenI vertex, then v has at least one child u that is a non-reticulation GenI vertex. In particular, v and u belong to the same tree T_i , $1 \le i \le m$. Hence, $\sigma(v) = \sigma(u)$, by the definition of σ . If v is a GenII vertex or a reticulation GenI vertex, then v has exactly one child u that is a GenII vertex. By definition, $\sigma(u) = \sigma(v)$ also holds in this case. Finally, if v is a GenIII vertex, then $v = h_e$, some edge e of G. Hence, $\sigma(l_e) = \sigma(v)$ holds by definition. Thus, (C2) holds.

Conversely, suppose that *N* is proper-forest-based. By Lemma 3.1, there exists an *m*-coloring $\sigma : V(N) \rightarrow \{1, ..., m\}$ of *N* satisfying (C1) and (C2). Since the set of reticulation GenI vertices of *N* is *X*, the restriction of σ to *X* induces an *m*-coloring $\kappa : X \rightarrow \{1, ..., m\}$ of *G*.

We claim that κ is a proper *m*-coloring of *G*. To see the claim, consider an edge $e = \{x, y\}$ of *G*. By construction, there exists a (unique) GenIII reticulation *v* such that $v = h_e$. Let v_1 denote the parent of h_e on P_x . Similarly, let v_2 denote the parent of h_e on P_y . By (C1), $\sigma(v_1) = \kappa(x)$ and $\sigma(v_2) = \kappa(y)$ hold. Since, by (C2), $\sigma(h_e) = \sigma(v_i)$ for a unique $i \in \{1, 2\}$, say i = 1, it follows that $\kappa(y) = \sigma(v_2) \neq \sigma(h_e) = \sigma(v_1) = \kappa(x)$. Thus, κ is a proper *m*-coloring of *G*.



FIGURE 3. The 3-network *N* constructed from the graph *G* with vertex set $X = \{a, b, c, d, e\}$ and edge set $E(G) = \{\{a, b\}, \{a, c\}, \{b, c\}, \{b, d\}, \{c, d\}, \{d, e\}\}$, as described in the proof of Proposition 5.1. GenI, GenII and GenIII vertices are indicated as described in Figure 2. A 3-coloring $\sigma : V(N) \rightarrow \{\bullet, \circ, \times\}$ associated to the proper 3-coloring κ of *G* given by $\kappa(a) = \kappa(d) = \bullet, \kappa(b) = \kappa(e) = \circ$ and $\kappa(c) = \times$.

6. BINARY TREE-CHILD NETWORKS

In this section, we shall prove that Statements (R1) and (R2) both hold. We begin with some definitions. Suppose N is an *m*-network and $v \in V(N)$. If v is not a root of N, then we denote by

 $\mathscr{P}_N(v)$ the set of parents of v. Similarly, if v is not a leaf of N then we denote by $\mathscr{C}_N(v)$ the set of children of v.

Lemma 6.1. Let N be proper forest-based m-network, with $m \ge 2$, and let v be a reticulation of N with indegree 3 or more. Then there exists a parent p of v such that the network N' obtained from N by:

- (i) Introducing three vertices v_1 , v_2 and x_v .
- (ii) Removing the arcs (p, v) and (v, c), where c is the unique child of v in N.
- (iii) Adding arcs (v, v_1) , (v_1, v_2) , (v_2, c) , (v_1, x_v) and (p, v_2) .

is forest-based.

Proof. Since *N* is forest-based, Lemma 3.1 implies that there exists an *m*-coloring $\sigma : V(N) \to C$ of *N* in terms of a set *C* of colors such that (C1) and (C2) are satisfied. Let *p* be a parent of *v* satisfying $\sigma(p) \neq \sigma(v)$ (which must exist in view of (C1)). Let *N'* be the network obtained by applying Steps (i) – (iii) to *v* and *p*. Note that *N'* also has *m* roots.

We define an *m*-coloring $\sigma' : V(N') \to C$ of N' as follows. For $w \in V(N')$, we put $\sigma'(w) = \sigma(v)$ if $w \in \{v_1, v_2, x_v\}$, and $\sigma'(w) = \sigma(w)$ otherwise. Since, by construction, $V(N') = V(N) \cup \{v_1, v_2, x_v\}$ it follows that σ' is well-defined. To see that N' is proper forest-based, we claim that σ' satisfies (C1) and (C2).

To see that σ' satisfies (C1), let *w* be a non-root vertex of *N'*. If $w \notin \{v, v_1, v_2, x_v, c\}$, then $w \in V(N)$ and $\mathscr{P}_N(w) = \mathscr{P}_{N'}(w)$ In particular, $\sigma'(w) = \sigma(w)$, and $\sigma'(q) = \sigma(q)$, for all parents $q \in \mathscr{P}_N(w)$. Since, by (C1), there exists exactly one parent *q* in $\mathscr{P}_N(w)$ that satisfies $\sigma(q) = \sigma(w)$ it follows that *q* is the unique parent in $\mathscr{P}_N(w)$ satisfying $\sigma'(q) = \sigma'(w)$.

Assume that $w \in \{v, v_1, v_2, x_v, c\}$. If w is one of v_1, x_v or c then $|\mathscr{P}_N(w)| = 1$ and v, v_1 or v_2 is the unique parent in $\mathscr{P}_N(w)$, respectively. By the definition of σ' , it follows that $\sigma'(w) = \sigma(v)$ in case $w \in \{v_1, x_v\}$. If w = c then the choice of p combined with the definition of σ' and the fact that σ satisfies (C1) implies that $\sigma'(c) = \sigma(c) = \sigma(v) \neq \sigma(p)$. Similarly, if w = vthen, by (C1), there exists exactly one parent $q \in \mathscr{P}_N(w)$ satisfying $\sigma(q) = \sigma(v)$. By choice of p, we have $p \neq q$. Since $\mathscr{P}_{N'}(w) = \mathscr{P}_N(v) - \{p\}$ it follows that q is the only parent in $\mathscr{P}_{N'}(w)$ satisfying $\sigma'(w) = \sigma'(q)$. Finally, if $w = v_2$, then $\mathscr{P}_{N'}(w) = \{v_1, p\}$. By construction, $\sigma'(w) = \sigma'(v_1) = \sigma(v)$ and, by choice of p, $\sigma'(p) = \sigma(p) \neq \sigma(v)$. Hence, v_1 is the only parent in $\mathscr{P}_{N'}(w)$ that has the same color as w under σ' . Thus, σ' satisfies (C1), as claimed.

To see that σ' satisfies (C2), let w be an internal vertex of N'. If $w \notin \{v, v_1, v_2, p\}$, then $w \in V(N)$ and $\mathcal{C}_N(w) = \mathcal{C}_{N'}(w)$. In particular, $\sigma'(w) = \sigma(w)$ and $\sigma'(z) = \sigma(z)$, for all children $z \in \mathcal{C}_N(w)$. By (C2), there exists at least one child $z \in \mathcal{C}_N(w)$ satisfying $\sigma(z) = \sigma(w)$. So $\sigma'(z) = \sigma'(w)$ holds in this case.

Assume that $w \in \{v, v_1, v_2, p\}$. If w = v, then v_1 is the only child in $\mathscr{C}_{N'}(w)$. Hence, $\sigma'(v_1) = \sigma(w) = \sigma'(w)$, by the definition of σ' . If $w = v_1$, then $\mathscr{C}_{N'} = \{x_v, v_2\}$. Hence, $\sigma'(w) = \sigma'(v_2) = \sigma'(x_v) = \sigma(v)$, by the definition of σ' . If $w = v_2$, then $\mathscr{C}_{N'}(w) = \{c\}$. By definition of σ' , we have again $\sigma'(w) = \sigma(v)$. Moreover, $\mathscr{C}_N(v) = \{c\}$ and σ satisfies (C2). Hence, $\sigma(c) = \sigma(v)$. Since $\sigma'(c) = \sigma(c)$, we obtain $\sigma'(c) = \sigma'(w)$. Finally, if w = p, then since σ satisfies (C2), there exists at least one child z in $\mathscr{C}_N(p)$ satisfying $\sigma(z) = \sigma(p)$. Since, by choice of p, we have $z \neq v$ it follows that $z \in \mathscr{C}_{N'}(p)$. Hence, $\sigma'(z) = \sigma'(p)$, by the definition of σ' . Thus, σ' also satisfies (C2), as claimed.

K.T. HUBER, V. MOULTON, G. E. SCHOLZ, L. VAN IERSEL

As a consequence of Lemma 6.1, we immediately obtain that every quasi-binary network that is proper forest-based can be transformed into a binary network that is also proper forestbased. More precisely, let N be a forest-based quasi-binary m-network, with $m \ge 2$, and let v be a reticulation of N of indegree 3 or more. Then, in the network N' obtained by applying the operations presented in the statement of Lemma 6.1 to N and v, the indegree of v in N is reduced by one in N'. Moreover, by construction, all vertices w of N' such that $w \ne v$ and w is a reticulation that has indegree 3 or more in N' is also a vertex of N with the same indegree as in N'. In particular, the described operations can be recursively applied to the reticulations of N' of indegree 3 or more, until no such vertices remain. By Lemma 6.1, the resulting network remains forest-based.

Theorem 6.2. For $m \ge 3$, the problem of determining whether a binary tree-child m-network is forest-based is NP-complete.

Proof. Membership of NP can again be argued in the same way as in the proof of Theorem 4.1. As in the proof of Proposition 5.1, we reduce from the problem of finding a proper *m*-coloring of a graph *G* with vertex set *X*. Given such a graph, we use the construction of a quasi-binary, tree-child *m*-network described in the proof of Proposition 5.1 to obtain a quasi-binary, tree-child *m*-network N^s . We then recursively apply the operations in the statement of Lemma 6.1 to resolve all reticulations of N^s with indegree 3 or more to obtain a binary, tree-child *m*-network N^b .

We next show that N^b is proper forest-based if and only if G admits a proper *m*-coloring. To this end, suppose first that G admits a proper *m*-coloring. Then, by the proof of Proposition 5.1, N^s is proper forest-based. By Lemma 6.1, N^b is also proper forest-based.

Now suppose N^b is proper forest-based. Then, by Lemma 6.1, there exists an *m*-coloring of *N* in terms of a set *C* of colors that satisfies Properties (C1) and (C2). Restricting this coloring to *X* to obtain a coloring $\kappa : X \to C$ and then applying the same arguments as in the last paragraph of the proof of Proposition 5.1 implies that κ is a proper *m*-coloring of *G*.

To state the next result, we require further concepts from [6]. Let *N* be an *m*-network, $m \ge 2$, and let *v* be a vertex of *N*. We denote by $\gamma_N(v)$ the (necessarily unique) lowest ancestor of *v* in *N* whose indegree is not 1. Note that $\gamma_N(v)$ is either a root or a reticulation of *N*. Building on this definition, we define an undirected graph $\Gamma(N)$ as follows. The vertex set of $\Gamma(N)$ is the set of all vertices of *N* whose indegree is not 1. Two such vertices v_1 , v_2 are joined by an edge in $\Gamma(N)$ if there exists two distinct vertices u_1 , u_2 in *N* such that $\gamma_N(u_1) = v_1$, $\gamma_N(u_2) = v_2$, and u_1 and u_2 share a child in *N*. The intuitive idea behind these edges is that they indicate that the vertices v_1, v_2 need to be contained in different trees in a potential subdivision forest of *N* and so need to be assigned different colors.

As it turns out, the edges of the graph $\Gamma(N)$ are not sufficient to determine whether N is proper forest-based. This is caused by internal vertices of N for which all children in $\mathscr{C}_N(v)$ have indegree 2 or more. We call such a vertex an *omnian* (*vertex*) [7]. To decide whether N is proper forest-based we will use certain supergraphs of $\Gamma(N)$ called "omni-extensions". For a semi-binary network N, we define an *omni-extension* of $\Gamma(N)$ as a supergraph $\Gamma'(N)$ of $\Gamma(N)$ such that $V(\Gamma'(N)) = V(\Gamma(N))$ and for all omnians v of N there exists a child h of v such that $\{h, \gamma_N(u)\}$ is an edge of $\Gamma'(N)$, with u the parent of h in N other than v [5]. Note that $\Gamma(N)$ may

10

be an omni-extension of itself. This is the case, in particular, if N has no omnian vertex. If $\Gamma'(N)$ is an omni-extension of $\Gamma(N)$, and no proper subgraph of $\Gamma'(N)$ is an omni-extension of $\Gamma(N)$, we say that $\Gamma'(N)$ is a *minimal omni-extension* of $\Gamma(N)$.

We illustrate these concepts in Figure 4 for the network in Figure 1. Observe that vertex v in Figure 1 is an omnian. At least one of the children of v needs to be assigned the same color as v (in a colouring satisfying (C2) from Lemma 3.1). In this example, we choose child $h = h_3$. This means that the other parent u of h_3 needs to be assigned a different color than h_3 (by (C1)) and hence that $\gamma_N(u) = r_3$ needs to be assigned a different color than h_3 (again using (C1)). This is the intuitive idea behind adding the edge $\{h_3, r_3\}$.



FIGURE 4. (i) The graph $\Gamma(N)$ for the network N depicted in Figure 1. (ii) A minimal omni-extension $\Gamma'(N)$ of $\Gamma(N)$.

Theorem 6.3. Given a binary tree-child 2-network N, it can be determined in O(nr) time whether N or not is proper forest-based, where r is the number of reticulations of N and n = |L(N)|.

Proof. [5, Theorem 8] states that a 2-rooted network, in which all reticulations have indegree 2, is proper forest-based if and only if the graph $\Gamma(N)$ has a bipartite omni-extension. This theorem is applicable to N since it is binary. Since N is tree-child, it has no omnians. Hence, $\Gamma(N)$ is an omni-extension of $\Gamma(N)$.

We claim that *N* is proper forest-based if and only if $\Gamma(N)$ is bipartite. First suppose that *N* is proper forest-based. Then, by [5, Theorem 8] recalled above, $\Gamma(N)$ has a bipartite omniextension. Since $\Gamma(N)$ is a subgraph of every omni-extension of $\Gamma(N)$, it follows that $\Gamma(N)$ is bipartite. Conversely, if $\Gamma(N)$ is bipartite, then, since $\Gamma(N)$ is an omni-extension of $\Gamma(N)$, it follows again by [5, Theorem 8] recalled above that *N* is proper forest-based. The claim therefore holds.

To construct $\Gamma(N)$, we need to find, for each parent v of a reticulation of N, the vertex $\gamma_N(v)$. This takes O(|V(N)|) time per reticulation of N. Hence, the construction of $\Gamma(N)$ takes $O(|V(N)| \cdot r)$ time. Checking whether $\Gamma(N)$ is bipartite or not takes O(r) time, since $\Gamma(N)$ has at most r edges. Hence, the total running time is $O(|V(N)| \cdot r)$.

Finally, to obtain the running time stated in the theorem, note that *N* has O(n) vertices, since by [10, Proposition 10.7], a tree-child 1-network has fewer than 4n vertices. Adding a root ρ and an arc from ρ to each of the original roots of a tree-child 2-network preserves the tree-child property and increases the number of vertices by only 1. This concludes the proof.

7. AN FPT ALGORITHM

In this section, we establish Statement (R4). We shall present a fixed-parameter tractable (FPT) algorithm called CHECK for deciding whether a semi-binary *m*-network N, $m \ge 2$, is forest-based, with parameters the number *r* of reticulations of *N*, the number *m* of roots of *N* and the maximum outdegree Δ of *N*. Note that we do not require the network to be tree-child.

Algorithm 1 The algorithm CHECK.

Input: Semi-binary *m*-network *N*, some $m \ge 2$.

- **Output:** The statement "*N* is proper forest-based" or the statement "*N* is not proper forest-based".
 - 1: Construct $\Gamma(N)$ and find all minimal omni-extensions of $\Gamma(N)$.
- 2: for all minimal omni-extension of $\Gamma(N)$ do Add an edge between any two distinct roots of N to obtain a graph $\Gamma^*(N)$. Note that $\Gamma^*(N)$ is also an omni-extension of $\Gamma(N)$.
- 3: Find all proper *m*-colorings of $\Gamma^*(N)$.
- 4: **for all** proper *m*-coloring σ of $\Gamma^*(N)$ **do**
- 5: **for all** reticulations *h* of *N* and all roots ρ of *N* **do** check that if $\sigma(h) = \sigma(\rho)$ then there exists a directed path $P(\rho, h)$ from ρ to *h* in *N* such that $\sigma(h) = \sigma(h')$, for all reticulations *h'* of *N* on $P(\rho, h)$.
- 6: **if** $P(\rho, h)$ exists for all reticulations *h* of *N* and all roots ρ of *N* with $\sigma(h) = \sigma(\rho)$ **then** return "*N* is proper forest-based".
- 7: if for each minimal omni-extension of $\Gamma(N)$ there is no proper *m*-coloring of $\Gamma^*(N)$ with the required paths **then** return "*N* is not proper forest-based".

Correctness of the algorithm CHECK follows from Theorem 7.1 which is a slight strengthening of [5, Theorem 7] to minimal omni-extensions. For N an *m*-network, $m \ge 2$, we denote the set of roots and reticulations of N by RH(N).

Theorem 7.1. Let N be a semi-binary m-network, some $m \ge 2$, and let $\{s_1, \ldots, s_m\}$ be a set of m colors. Then N is a proper forest-based if and only if there exists a minimal omni-extension $\Gamma'(N)$ of $\Gamma(N)$ and a proper m-coloring $\sigma : RH(N) \to \{s_1, \ldots, s_m\}$ of $\Gamma'(N)$ satisfying:

- (F1) The restriction of σ to the set R(N) of roots of N is a bijection.
- (F2) For all $u \in R(N)$ and all reticulations v of N such that $\sigma(u) = \sigma(v)$ there exists a directed path P in N from u to v such that $\sigma(w) = \sigma(u)$ holds for all reticulations w of N that lie on P.

Proof. Suppose first that there exists a minimal omni-extension G of $\Gamma(N)$ and a proper m-coloring of G satisfying Properties (F1) and (F2). Then by [5, Theorem 7], N is proper forest-based.

Conversely, suppose that *N* is proper forest-based. Then by [5, Theorem 7], there exists an omni-extension *G* of $\Gamma(N)$ and a proper *m*-coloring σ of *G* satisfying Properties (F1) and (F2). Since (F1) and (F2) are independent of the structure of *G*, it follows for all subgraphs G^- of *G* with $V(G) = V(G^-)$ that σ is a proper *m*-coloring of G^- satisfying (F1) and (F2). In particular, if there exists an omni-extension of $\Gamma(N)$ and a proper *m*-coloring of *G* satisfying (F1) and (F2).

then there exists a minimal omni-extension of $\Gamma(N)$ and a proper *m*-coloring of *G* satisfying Properties (F1) and (F2).

We now analyze the run time of algorithm CHECK. The graph $\Gamma(N)$ can be constructed in O(r|V(N)|) time and can have at most Δ^{ω} minimal omni-extensions where ω is the number of omnians of N. Since N is semi-binary, ω is at most 2r (each omnian is the parent of at least one reticulation and each reticulation has two parents). All proper *m*-colorings of $\Gamma^*(N)$ can be found in $O(m^{r+m}(r+m)^2)$ time since $\Gamma^*(N)$ has r+m vertices (Line 3). Since, by construction, the set of roots on N forms a clique in $\Gamma^*(N)$ and we are interested in proper *m*-colorings of $\Gamma^*(N)$ it follows that for every reticulation h of N there exist a unique root ρ_h of N that has the same color under the *m*-coloring under consideration as h. In the worst case, checking the vertices on the directed path $P(\rho, h)$ takes O(|V(N)|) time per pair (ρ_h, h) (by deleting all reticulations that do not have the same color as ρ and then doing a depth-first search) (Line 5). The total run time of algorithm CHECK therefore is $O(\Delta^{2r}m^{r+m}(r+m)^2|V(N)|)$.

Theorem 7.2. For all $m \ge 2$, there exists an algorithm with running time $O(\Delta^{2r}m^{r+m}(r+m)^2v)$ to decide whether a semi-binary m-network with r reticulations, v vertices and maximum outdegree Δ is proper forest-based.

8. DISCUSSION

We have shown that it can be decided in polynomial time whether or not a binary, tree-child *m*-network *N* is proper forest-based for m = 2, but that this problem is NP-complete for $m \ge 3$. It would be interesting to know if the same problem can be solved in polynomial time in case m = 2 but *N* is not necessarily binary, for example, in case *N* is tree-sibling (i.e. every reticulation has at least one sibling vertex that is a tree vertex or a leaf), or *N* is an arbitrary 2-network. In addition, although we have shown that there is an FPT algorithm for deciding whether or not a semi-binary *m*-network is forest-based, it would be interesting to see if FPT-algorithms with improved run-times can be developed, or if an FTP algorithm can be found for arbitrary *m*-networks.

In this paper, we have not considered the problem of deciding whether or not an *m*-network is forest-based, $m \ge 1$, i.e. the problem where we do not insist that the underlying forest must have *m* trees. It would be interesting to know whether or not this is an NP-complete problem. Note that since an *m*-network *N* is forest-based if and only if it contains a subdivision forest in which every tree is an induced, directed path in *N* (cf. [5, Theorem 1]), this question is closely related to the induced path partition problem which is known to NP-complete [2].

Finally, for biological applications, it would be useful to develop new algorithms to construct forest-based networks from biological data. Hopefully the structural insights that we have developed in this paper for proper forest-based networks will provide some helpful insights for this problem.

Acknowledgement The authors would like to thank the Institute Mittag Leffler, Sweden, for hosting the "Emerging Mathematical Frontiers in Molecular Evolution" meeting where the ideas underlying this paper were conceived. LvI would like to thank the Netherlands Organization for Scientific Research (NWO) grant OCENW.KLEIN.125.

REFERENCES

- Nathaniel B Edelman, Paul B Frandsen, Miriam Miyagi, Bernardo Clavijo, John Davey, Rebecca B Dikow, Gonzalo García-Accinelli, Steven M Van Belleghem, Nick Patterson, Daniel E Neafsey, et al. Genomic architecture and introgression shape a butterfly radiation. *Science*, 366(6465):594–599, 2019.
- [2] Henning Fernau, Florent Foucaud, Kevin Mann, Utkarsh Padariya, and KN Rajath Rao. Parameterizing path partitions. In *International Conference on Algorithms and Complexity*, pages 187–201. Springer, 2023.
- [3] Andrew R Francis and Mike Steel. Which phylogenetic networks are merely trees with additional arcs? Systematic Biology, 64(5):768–777, 2015.
- [4] Michael R Garey and David S Johnson. Computers and Intractability: A Guide to the Theory of on NP-Completeness. Freeman, 1979.
- [5] Katharina T Huber, Vincent Moulton, and Guillaume E Scholz. Forest-based networks. Bulletin of Mathematical Biology, Article number 119, 2022.
- [6] Katharina T Huber, Vincent Moulton, and Guillaume E. Scholz. Overlaid species forest. *Discrete Applied Mathematics*, 309, 2022.
- [7] Laura Jetten and Leo van Iersel. Nonbinary tree-based phylogenetic networks. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 15(1):205–217, 2016.
- [8] Sungsik Kong, Joan Carles Pons, Laura Kubatko, and Kristina Wicke. Classes of explicit phylogenetic networks and their biological and mathematical significance. *Journal of Mathematical Biology*, 84(6):47, 2022.
- [9] Guillaume E. Scholz, Andrei A Popescu, Martin I Taylor, V Moulton, and Katharina T Huber. Osf-builder: a new tool for constructing and representing evolutionary histories involving introgression. *Systematic Biology*, 68:717–729, 2019.
- [10] Mike Steel. Phylogeny: discrete and random processes in evolution. SIAM, 2016.
- [11] Richard WR Wallbank, Simon W Baxter, Carolina Pardo-Diaz, Joseph J Hanly, Simon H Martin, James Mallet, Kanchon K Dasmahapatra, Camilo Salazar, Mathieu Joron, Nicola Nadeau, et al. Evolutionary novelty in a butterfly wing pattern through enhancer shuffling. *PLoS Biology*, 14(1):e1002353, 2016.