BackboneLearn: A Library for Scaling Mixed-Integer Optimization-Based Machine Learning

DIGALAKIS@HEC.FR

CHZIAKAS@GMAIL.COM

Vassilis Digalakis Jr

Christos Ziakas

Department of Information Systems and Operations Management, HEC Paris

Editor:

Abstract

We present BackboneLearn: an open-source software package and framework for scaling mixed-integer optimization (MIO) problems with indicator variables to high-dimensional problems. This optimization paradigm can naturally be used to formulate fundamental problems in interpretable supervised learning (e.g., sparse regression and decision trees), in unsupervised learning (e.g., clustering), and beyond; BackboneLearn solves the aforementioned problems faster than exact methods and with higher accuracy than commonly used heuristics. The package is built in Python and is user-friendly and easily extensible: users can directly implement a backbone algorithm for their MIO problem at hand. The source code of BackboneLearn is available on GitHub¹.

Keywords: Sparse regression, decision trees, clustering, mixed-integer optimization

1. Introduction

Mixed-integer optimization (MIO) problems with indicator variables are encountered in a wide array of applications ranging from (sparse) machine learning (ML) to network design and portfolio selection. For example, given data $X \in \mathbb{R}^{n \times p}$, responses $y \in \mathbb{R}^{n}$, and a desired sparsity level $k \ll p$, the sparse linear regression is formulated as $\min_{\beta} || y - X\beta ||_2^2$ s.t. $||\beta||_0 \leq k$; then, each regression coefficient β_j (and the corresponding feature j) is paired with an indicator $z_j = \mathbb{1}_{\beta_j \neq 0}$. Over the past decade, MIO-based methods for ML (Bertsimas and Dunn, 2019; Gambella et al., 2021) have scaled from being intractable beyond toy scales (e.g., sparse regression/decision tree problems with a few hundred/a dozen features) to now being able to handle much more realistically-sized problems: see, e.g., Hazimeh et al. (2022); Bertsimas et al. (2021) for sparse regression and Aghaei et al. (2021); Mazumder et al. (2022) for decision trees. The backbone framework, introduced by Bertsimas and Digalakis Jr (2022), is a general, heuristic framework (albeit with some theoretical guarantees) to scale such techniques even further: we solved, in minutes, sparse regression problems with tens of millions of features and decision tree problems with hundreds of thousands.

Besides the original work by Bertsimas and Digalakis Jr (2022), the backbone framework has been successfully implemented in vehicle routing (Bertsimas et al., 2019) and compressed sensing (Bertsimas and Johnson, 2023). Backbone-type algorithms have been shown

^{1.} Link: https://github.com/chziakas/backbone_learn

to be relevant in supervised ML, e.g., sparse SVM (Bi et al., 2003), in unsupervised ML, e.g., sparse PCA (Cory-Wright and Pauphilet, 2022), in magnet optimization (Kaptanoglu et al., 2022), in learning sparse nonlinear dynamics (Bertsimas and Gurnee, 2023), and, more recently, for mechanistic interpretability of large language models (Gurnee et al., 2023). Lastly, exact, safe screening-based approaches, such as the works of Atamturk and Gómez (2020); Deza and Atamtürk (2022), can also be described and implemented under the backbone framework.

In this paper, we describe BackboneLearn, an open-source software package that seeks to help data science practitioners (i) use the algorithms developed by Bertsimas and Digalakis Jr (2022) and extensions thereof (e.g., we develop a novel backbone algorithm for clustering) in combination with state-of-the-art solvers; (ii) easily implement their own BackboneLearner for their problem at hand (in supervised ML, unsupervised ML, and beyond); (iii) interface with various state-of-the-art MIO-based interpretable ML algorithms and packages, including the LOLearn (Hazimeh et al., 2023) and LOBnb (Hazimeh et al., 2022) packages for sparse regression and the ODTLearn (Vossler et al., 2023) package for optimal decision trees (in other words, BackboneLearn can be used as a joint feature selector and model fitter for the aforementioned methodologies). Overall, this project aims to bring together under a single framework and software package all the backbone-type approaches described in the previous paragraph, to facilitate adoption by practitioners; we believe this is especially relevant following the increased interest in and the established benefits of developing exact solutions for interpretable ML models.

2. The Backbone Framework

The backbone framework, upon which BackboneLearn is built, operates in two phases: we first extract a "backbone set" of potentially "relevant indicators" (i.e., indicators that are nonzero in the optimal solution) by solving a number of specially chosen, tractable subproblems; we then use traditional techniques to solve a reduced problem to optimality or near-optimality, considering only the backbone indicators. A screening step often precedes the first phase, to discard indicators that are almost surely irrelevant. Bertsimas and Digalakis Jr (2022) develop backbone methods for various supervised ML models (whereby each indicator corresponds to a feature), including sparse linear and logistic regression, and classification trees, all of which are implemented within BackboneLearn; in fact, for the case of sparse linear regression, their theoretical analysis shows that, under certain conditions and with high probability, the backbone set consists only of the truly relevant indicators. Extending their original work, BackboneLearn also implements a backbone algorithm for clustering and sets the foundation for a series of additional extensions.

The Backbone Algorithm. In Algorithm 1, we provide a general, modularized backbone algorithm. The input consists of (i) the data D (e.g., in supervised learning, D = (X, y), whereas in unsupervised learning D = X), (ii) a set of hyperparameters including the number of subproblems, the subproblem size, the number of features to be discarded through a screening test or "proxy," and the maximum allowable backbone size, and (iii) a set of application-specific functions. The latter includes the screen function that discards irrelevant indicators after calculating their utilities (denoted by s), the construct_subproblems lems function that builds a series of tractable subproblems (decreasing in number in each

backbone iteration t), and the fit_subproblem and fit functions that, respectively, solve the subproblems (possibly heuristically) and the "reduced" problem (considering only the indicators that have been selected in the backbone set \mathcal{B}). The output is the learned model (e.g., sparse regression coefficients; decision tree parameters; cluster assignment).

Algorithm 1 General Backbone Algorithm

Input: Data D,hyperparameters $(M, \beta, \alpha, B_{\max}),$ functions (screen, construct_subproblems, fit_subproblem, extract_relevant, fit). **Output:** Learned model. $t \leftarrow 0; \ \mathcal{U}_0, s \leftarrow \texttt{screen}(D, \alpha)$ repeat $\mathcal{B} \leftarrow \emptyset$ $(\mathcal{P}_m)_{m \in [M]} \leftarrow \texttt{construct_subproblems}(\mathcal{U}_t, s, \lceil \frac{M}{2^t} \rceil, \beta)$ for $m \in [M]$ do $model_m \leftarrow fit_subproblem(D, \mathcal{P}_m)$ $\mathcal{B} \leftarrow \mathcal{B} \cup \texttt{extract_relevant}(\texttt{model}_m)$ end for $t \leftarrow t+1; \ \mathcal{U}_t \leftarrow \mathcal{B}$ **until** $|\mathcal{B}| \leq B_{\text{max}}$ (or other termination criterion is met) model $\leftarrow \texttt{fit}(D, \mathcal{B})$

Backbone Examples. We proceed by giving more concrete examples of backbone sets for specific problems. For sparse linear regression, the backbone set can be written as:

$$\mathcal{B} = \bigcup_{m=1}^{M} \left\{ j : \beta_j^{(m)} \neq 0, \quad \boldsymbol{\beta}^{(m)} = \operatorname*{argmin}_{\substack{\boldsymbol{\beta} \in \mathbb{R}^p: \\ \|\boldsymbol{\beta}\|_0 \leqslant k_m, \\ \beta_j = 0 \quad \forall j \notin \mathcal{P}_m}} \|\boldsymbol{y} - \boldsymbol{X}\boldsymbol{\beta}\|_2^2 \right\}.$$

The solution to each subproblem $\beta^{(m)}$ can be solved using fast, heuristic methods. After \mathcal{B} is computed, we solve (to optimality) the original problem under the additional constraint $\beta_j = 0$, $\forall j \notin \mathcal{B}$. For optimal decision trees, \mathcal{B} consists of all features that have not been selected in any split node in any subproblem or have small importance across all subproblems.

For clustering, the goal is to group the *n* data points in \mathbf{X} into *k* clusters $\{S_1, ..., S_k\}$ to minimize $\sum_t \frac{1}{|S_t|} \sum_{\mathbf{x}_i, \mathbf{x}_j \in S_t} ||\mathbf{x}_i - \mathbf{x}_j||_2^2$. To develop a clustering backbone algorithm, we rely on the formulation by Grötschel and Wakabayashi (1989), who view the clustering problem as a graph clique partitioning problem and represent each cluster as a fully connected component. Then, **BackboneLearn** aims to sparsify the graph that contains all feasible clique partitionings. Formally, let $\mathcal{Z} = \{\mathbf{z}, \boldsymbol{\zeta} : \sum_t z_{it} = 1 \ \forall i, \sum_i z_{it} \geq b \ \forall t, \quad \zeta_{ijt} = z_{it}z_{jt} \ \forall i, j, t\}$, where z_{it} (respectively ζ_{ijt}) indicates whether point *i* is put into cluster *t* (points *i*, *j* are put together into cluster *t*), and $f(\boldsymbol{\zeta}; \mathbf{X}) = \sum_{i,j,k} \zeta_{ijk} ||\mathbf{x}_i - \mathbf{x}_j||^2$. The backbone set can be expressed as:

$$\mathcal{B} = \bigcup_{m=1}^{M} \left\{ (i,j) : \sum_{k} \zeta_{ijk}^{(m)} = 1, \quad \zeta^{(m)} = \operatorname{argmin}_{(z,\zeta\in\mathcal{Z})} f(\zeta; X^{(m)}) \right\}.$$

After \mathcal{B} is computed, we solve (to optimality) the original problem under the additional constraint $z_{it} + z_{jt} \leq 1 \quad \forall (i,j) \notin \mathcal{B} \quad \forall t$. To further scale the algorithm, we linearize the bilinear constraint and include additional ones (e.g., we also encode the set $\mathcal{B}^{\complement}$).

3. The BackboneLearn Package

Implementation, Usage, and Extensibility. BackboneLearn is implemented in Python 3.9 and can be installed by executing pip install backbone-learn. We use (i) Poetry for reproducibility and to automatically manage dependencies, (ii) continuous integration with the Pytest testing framework, and (iii) GitHub Actions; BackboneLearn achieved the highest rating for code quality by the code analysis tool Codacy. We interface Backbone-Learn with state-of-the-art, open-source packages: for sparse regression, we rely on LOLearn (Hazimeh et al., 2023), LOBnb (Hazimeh et al., 2022), and GLMNet (Zou and Hastie, 2005); for decision trees, we utilize ODTLearn (Vossler et al., 2023) and ScikitLearn (Pedregosa et al., 2011); for mixed-integer optimization, we use the open-source solver Cbc (Forrest and Lougee-Heimer, 2005) and the Python optimization modeling library PuLP (Mitchell et al., 2011).

The BackboneLearn documentation provides extensive examples for sparse regression, decision trees, clustering, and extensions. BackboneLearn for sparse regression is run using:

To implement custom backbone algorithms, BackboneLearn offers two primary classes for extension: BackboneSupervised for supervised ML and BackboneUnsupervised for unsupervised ML. Thus, a CustomBackboneAlgorithm requires implementing the set_solvers() method within the selected subclass, which, in turn, defines the algorithm's core components: (i) the CustomScreenSelector (optional screening method) including the calculate_util-ities() function, (ii) the CustomHeuristicSolver (subproblem solution method) with the get_relevant() and fit() functions, and (iii) the CustomExactSolver (reduced problem solution method) with the fit() and predict() functions.

Experiments. Our numerical experiments investigate the following questions: does **BackboneLearn** speed up exact methods, does it enhance the accuracy of fast heuristics, and is it consistent across different problems? All experiments were performed on a standard Apple M2 @ 3.50GHz running macOS Ventura release 13.4.1.(c) with 8Gb of RAM. The code for replicating our simulations is available on GitHub. Here, we limit our analysis to synthetic experiments; the practical relevance of the backbone framework has been documented in full-scale, real-world experiments and problems in Bertsimas and Digalakis Jr (2022); Bertsimas et al. (2019); Bertsimas and Johnson (2023).

In sparse regression, we generate synthetic data as per a ground truth sparse linear regression model under the fixed design setting (following Hazimeh et al. (2022)); we compute the full regularization path for GLMNet and LOBnb both when used independently and as part of BackboneLearn; we evaluate each method's (GLMNet, LOBnb, BackboneLearn) accuracy (using the \mathbb{R}^2 statistic) and total computational time. In *decision trees*, we generate binary classification data by evenly distributing a set of normally distributed clusters among classes and adding noise and feature interdependence; we cross-validate hyperparameters (e.g., tree

BACKBONELEARN

depth); we evaluate each method's (CART, ODTLearn, BackboneLearn) accuracy (using the AUC) and total computational time. In *clustering*, we generate noisy isotropic Gaussian blobs and, to create ambiguity, we assume the target number of clusters is greater than the true number; we evaluate each method's (KMeans, Exact, BackboneLearn) accuracy (using the Silhouette score) and total computational time. Below each method, we specify the problem size, defined in terms of the number of data points (n), features (p), and true relevant features or target clusters (k); we pick the problem sizes so that the exact methods are at their limits within the allowed one-hour budget that we impose.

Our results, detailed in Table 1 and averaged over 10 repetitions, verify the improved performance of BackboneLearn in terms of (i) significantly reducing the solution times of exact methods and (ii) improving upon the performance of heuristics. BackboneLearn consistently recovers the optimal solution (which, given our data generating process, is known) and achieves provable optimality (with suboptimality gaps under 1%) — albeit in reduced problems. Regarding runtime, in sparse regression BackboneLearn performs best for larger values of α , β , suggesting that, when possible, it is preferred to solve larger subproblems that include more signal; for decision trees, efficiency increases with smaller subproblems, in agreement with the known benefits of feature sampling in random forest feature sampling; lastly, for clustering, the effect of BackboneLearn's hyperparameters is negligible (the method effectively selects the best clustering among the ones examined in subproblems).

Problem	Method	Μ	а	b	Accuracy	Time (sec)	Backbone Size
Sparse Regression (n, p, k) = (500, 5000, 10)	GLMNet	-	-	-	0.871	15	-
	LOBnb	-	-	-	0.883	1175	-
	BbLearn	5	0.1	0.5	0.884	483	376
		5	0.5	0.9	0.884	94	40
		10	0.1	0.5	0.884	692	449
		10	0.5	0.9	0.884	202	87
Decision Trees (n, p, k) = (500, 100, 10)	CART	-	-	-	0.708	1	-
	ODTLearn	-	-	-	0.639	3600	-
	BbLearn	5	0.1	0.5	0.714	34	9
		5	0.5	0.9	0.714	2285	42
		10	0.1	0.5	0.714	108	10
		10	0.5	0.9	0.714	3137	46
Clustering (n, p, k) = (200, 2, 5)	KMeans	-	-	-	0.454	0	-
	Exact	-	-	-	-	3600	-
	BbLearn	5	-	1.0	0.481	116	3483
		10	-	1.0	0.481	111	3483

Table 1: Numerical Results.

4. Conclusion

We introduced BackboneLearn, an open-source software package and framework for scaling MIO problems with indicator variables to high-dimensional problems, addressing challenges in supervised and unsupervised learning, and beyond. BackboneLearn currently offers algorithms for sparse regression, decision trees, and clustering, and is easily extensible: users can directly implement a backbone algorithm for their MIO problem at hand. Our numerical experiments demonstrate BackboneLearn's ability to enhance the efficiency of exact meth-

ods and improve upon the accuracy of commonly used heuristics, validating the practical relevance of backbone-type algorithms. We aim for the BackboneLearnpackage to evolve into a hub for highly scalable MIO-based ML algorithms.

References

- Sina Aghaei, Andrés Gómez, and Phebe Vayanos. Strong optimal classification trees. arXiv preprint arXiv:2103.15965, 2021.
- Alper Atamturk and Andrés Gómez. Safe screening rules for 10-regression from perspective relaxations. In *International conference on machine learning*, pages 421–430. PMLR, 2020.
- Dimitris Bertsimas and Vassilis Digalakis Jr. The backbone method for ultra-high dimensional sparse machine learning. *Machine Learning*, 111(6):2161–2212, 2022.
- Dimitris Bertsimas and Jack Dunn. Machine learning under a modern optimization lens. Dynamic Ideas LLC Charlestown, MA, 2019.
- Dimitris Bertsimas and Wes Gurnee. Learning sparse nonlinear dynamics via mixed-integer optimization. Nonlinear Dynamics, 111(7):6585–6604, 2023.
- Dimitris Bertsimas and Nicholas Johnson. Compressed sensing: A discrete optimization approach. arXiv preprint arXiv:2306.04647, 2023.
- Dimitris Bertsimas, Patrick Jaillet, and Sébastien Martin. Online vehicle routing: The edge of optimization in large-scale applications. *Operations Research*, 67(1):143–162, 2019.
- Dimitris Bertsimas, Vassilis Digalakis Jr, Michael Linghzi Li, and Omar Skali Lami. Slowly varying regression under sparsity. *arXiv preprint arXiv:2102.10773*, 2021.
- Jinbo Bi, Kristin Bennett, Mark Embrechts, Curt Breneman, and Minghu Song. Dimensionality reduction via sparse support vector machines. *Journal of Machine Learning Research*, 3(Mar):1229–1243, 2003.
- Ryan Cory-Wright and Jean Pauphilet. Sparse pca with multiple components. arXiv preprint arXiv:2209.14790, 2022.
- Anna Deza and Alper Atamtürk. Safe screening for logistic regression with 10–12 regularization. arXiv, 2202, 2022.
- John Forrest and Robin Lougee-Heimer. Cbc user guide. In *Emerging theory, methods, and applications*, pages 257–277. INFORMS, 2005.
- Claudio Gambella, Bissan Ghaddar, and Joe Naoum-Sawaya. Optimization problems for machine learning: A survey. European Journal of Operational Research, 290(3):807–828, 2021.
- Martin Grötschel and Yoshiko Wakabayashi. A cutting plane algorithm for a clustering problem. *Mathematical Programming*, 45:59–96, 1989.

- Wes Gurnee, Neel Nanda, Matthew Pauly, Katherine Harvey, Dmitrii Troitskii, and Dimitris Bertsimas. Finding neurons in a haystack: Case studies with sparse probing. *arXiv* preprint arXiv:2305.01610, 2023.
- Hussein Hazimeh, Rahul Mazumder, and Ali Saab. Sparse regression at scale: Branch-andbound rooted in first-order optimization. *Mathematical Programming*, 196(1-2):347–388, 2022.
- Hussein Hazimeh, Rahul Mazumder, and Tim Nonet. L0learn: A scalable package for sparse learning using 10 regularization. *Journal of Machine Learning Research*, 24(205):1–8, 2023.
- Alan A Kaptanoglu, Tony Qian, Florian Wechsung, and Matt Landreman. Permanentmagnet optimization for stellarators as sparse regression. *Physical Review Applied*, 18(4): 044006, 2022.
- Rahul Mazumder, Xiang Meng, and Haoyue Wang. Quant-bnb: A scalable branch-andbound method for optimal decision trees with continuous features. In *International Conference on Machine Learning*, pages 15255–15277. PMLR, 2022.
- Stuart Mitchell, Michael OSullivan, and Iain Dunning. Pulp: a linear programming toolkit for python. *The University of Auckland, Auckland, New Zealand*, 65, 2011.
- Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, et al. Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12: 2825–2830, 2011.
- Patrick Vossler, Sina Aghaei, Nathan Justin, Nathanael Jo, Andrés Gómez, and Phebe Vayanos. Odtlearn: A package for learning optimal decision trees for prediction and prescription. arXiv preprint arXiv:2307.15691, 2023.
- Hui Zou and Trevor Hastie. Regularization and variable selection via the elastic net. Journal of the Royal Statistical Society Series B: Statistical Methodology, 67(2):301–320, 2005.