Dawning of a New Era in Gravitational Wave Data Analysis: Unveiling Cosmic Mysteries via Artificial Intelligence — A Systematic Review

Tianyu Zhao,^{1, 2, 3} Ruijun Shi,^{1, 3} Yue Zhou,² Zhoujian Cao,^{1, 3, 4, *} and Zhixiang Ren^{2, †}

¹Department of Astronomy, Beijing Normal University, Beijing 100875, China

²Peng Cheng Laboratory, Shenzhen, 518055, China

³Institute for Frontiers in Astronomy and Astrophysics,

⁴School of Fundamental Physics and Mathematical Sciences,

Hangzhou Institute for Advanced Study, UCAS, Hangzhou 310024, China

(Dated: November 28, 2023)

Background: Artificial intelligence (AI), with its vast capabilities, has become an integral part of our daily interactions, particularly with the rise of sophisticated models like Large Language Models. These advancements have not only transformed human-machine interactions but have also paved the way for significant breakthroughs in various scientific domains.

Aim of review: This review is centered on elucidating the profound impact of AI, especially deep learning, in the field of gravitational wave data analysis (GWDA). We aim to highlight the challenges faced by traditional GWDA methodologies and how AI emerges as a beacon of hope, promising enhanced accuracy, real-time processing, and adaptability.

Key scientific concepts of review: Gravitational wave (GW) waveform modeling stands as a cornerstone in the realm of GW research, serving as a sophisticated method to simulate and interpret the intricate patterns and signatures of these cosmic phenomena. This modeling provides a deep understanding of the astrophysical events that produce gravitational waves. Next in line is GW signal detection, a refined technique that meticulously combs through extensive datasets, distinguishing genuine gravitational wave signals from the cacophony of background noise. This detection process is pivotal in ensuring the authenticity of observed events. Complementing this is the GW parameter estimation, a method intricately designed to decode the detected signals, extracting crucial parameters that offer insights into the properties and origins of the waves. Lastly, the integration of AI for GW science has emerged as a transformative force. AI methodologies harness vast computational power and advanced algorithms to enhance the efficiency, accuracy, and adaptability of data analysis in GW research, heralding a new era of innovation and discovery in the field.

Keywords: Gravitational Wave, Artificial Intelligence, Deep Learning, Astrophysics, Data Analysis

I. INTRODUCTION

In today's rapidly evolving world, artificial intelligence (AI) stands as a beacon of transformation, seamlessly integrating into every facet of our lives. From the convenience of face recognition [1] unlocking our devices to the magic of speech synthesis [2] that brings virtual assistants to life, AI's influence is omnipresent. Diving deeper into the world of language, large language models (LLMs) like ChatGPT (GPT-3.5 and GPT-4) [3] and Llama 2 [4] have revolutionized our interaction with digital content. These advanced language models are now being harnessed for creative endeavors, such as co-writing novels, generating art-inspired poetry [5], and even composing music [6]. They're also playing pivotal roles in bridging communication gaps, offering real-time translations for diplomats and global travelers, and assisting in preserving endangered languages by generating rich linguistic content [3]. Beyond these linguistic marvels, AI's imprint extends to personalized healthcare, where it crafts treatments tailored to individual genetic profiles [7], and to our cities, optimizing the ebb and flow of traffic [8]. Venturing into the domain of scientific inquiry, AI emerges as a powerful ally, reshaping our methodologies and accelerating the pace of discovery [9]. Innovations like self-supervised learning are reimagining how we interpret complex datasets [10], while generative AI techniques are forging new pathways in diverse fields, from drug design [11] to the creation of advanced materials [12]. Delving into specific achievements, tools like AlphaFold2 [13] have unraveled the intricate puzzle of protein folding, offering unprecedented insights into the very fabric of biological life. Similarly, in the vast cosmos, AI assists astrophysicists in deciphering the myriad signals from the universe, unveiling celestial phenomena that were once shrouded in mystery [14]. As we journey further into this decade, AI promises to be more than just a technological marvel—it's poised to be the compass guiding our quest for knowledge, reshaping our world, and expanding the horizons of what's possible [15].

Beijing Normal University, Beijing 102206, China

^{*} Corresponding author: zjcao@bnu.edu.cn

[†] Corresponding author: renzhx@pcl.ac.cn

¹ https://www.soundsofspacetime.org/the-basics-of-binarycoalescence.html

https://www.britannica.com/science/relativity/Curved-space-time-and-geometric-gravitation



Figure 1. **Overview of the gravitational wave data analysis (GWDA) pipeline.** This figure delineates the comprehensive journey of the GWDA. It begins with the foundational step of signal waveform modeling, progressing to the meticulous phase of data quality management. Subsequent stages involve the crucial tasks of signal detection and parameter estimation, ultimately leading to the crowning achievement of scientific discovery. The visual elements in this figure are adapted from various sources, acknowledging the contributions of Ref. [16–25] and website^b.

In 2015, the detection of gravitational wave (GW) provided a monumental breakthrough in astrophysics [26], validating Einstein's century-old theoretical prediction [27] and introducing a new window to probe the universe's mysteries [28]. As depicted in Fig. 1, gravitational

https://www.ligo.org/science/GW-IFO.php

https://www.astronomy.com/science/is-the-universe-

infinite-or-finite-or-is-it-so-close-to-infinite-thatfor-all-practical-purposes-it-is/

binaries-might-be-right-around-the-corner/

wave data analysis (GWDA) is a complex endeavor that consist of many stages. Given the sensitivity of detectors like Laser Interferemeter Gravitational Wave Observatory (LIGO) [29] and Virgo [30], it's imperative to differentiate genuine GW signals from terrestrial interference [31]. This involves rigorous data quality labeling [32], glitch classification to categorize transient noise events [33], and noise suppression techniques to enhance the clarity of potential signals [34]. With cleaner data in hand, the focus then shifts to signal detection [35]. This stage, reliant on accurate waveform modeling, uses theoretical templates to predict GW signals from cosmic events, such as black hole mergers [36], and employs matched filtering-based signal searches to identify these events in the processed data [37]. Following a successful detection, the pipeline culminates in parameter estimation, where the goal is to decipher the astrophysical properties of the GW sources [38]. Each stage of the GWDA process, from data pre-processing to scientific discoveries, presents its unique set of challenges.

https://clipart-library.com/free/satellite-transparent-background.html

https://cplberry.com/2015/01/10/1408-0740/

https://cloud.tencent.com/developer/article/1737301

https://science.howstuffworks.com/math-concepts/bayestheorem.htm

https://news.northwestern.edu/stories/2023/06/ gravitational-waves-from-supermassive-black-hole-

https://gwosc.org/techdetails/

The sheer volume of data demands real-time analysis, yet traditional methods often lag, struggling to keep pace [39, 40]. Ensuring data quality in real-time is essential, but conventional techniques might not be agile enough to handle this task efficiently [41]. When it comes to signal detection, the non-stationary and non-Gaussian nature of the noise poses a significant hurdle, as traditional matched filters are optimized for Gaussian noise [42]. The generation of waveform templates, crucial for signal searching and parameter estimation, is often slow with classical methods, affecting the overall efficiency of the analysis [43, 44]. Furthermore, parameter estimation techniques like Markov-chain Monte Carlo (MCMC) face scalability issues, hampering their effectiveness [45, 46].

GWDA is confronted with challenges stemming from the high-dimensional parameter space and the presence of non-Gaussian artifacts in the interferometer background [47]. The introduction of AI, particularly deep learning (DL) algorithms, offers a promising avenue to address these challenges [48, 49]. These algorithms are characterized by their computational efficiency, leveraging accelerated hardware for rapid solutions [50]. Their scalability ensures they can handle extensive datasets, providing reliable model performance estimates [51]. The modular nature of these algorithms facilitates adaptability, allowing for the streamlined incorporation of new methodologies [52]. Furthermore, the generalization capabilities of DL models ensure consistent performance across varied GWDA scenarios [53]. In light of these advancements, our review undertakes:

- The paper reviews various AI-driven approaches to gravitational wave data analysis, **covering every stage** of the entire pipeline, from waveform modeling to scientific discoveries.
- We offer the first exploration of AI's application in gravitational waveform modeling, showcasing novel methodologies and their accuracy.
- We also present **the first exploration** of AI's role in dramatically accelerating parameter estimation within gravitational wave studies.
- This paper presents the most comprehensive review to date, seamlessly integrating the latest advancements in AI with their practical applications in the field of gravitational wave data analysis.
- Our study culminates in a **meta-analysis**, synthesizing insights and trends from diverse AI applications in gravitational wave data analysis, discussing the fusion of AI and gravitational wave data analysis, and opening new avenues for insights and **future research directions**.

With this exploration, we aim to offer a panoramic view, intertwining the intricacies of AI with the mysteries of GWs, underscoring the transformative potential of their collaboration.

The remainder of this review is structured to provide a comprehensive overview of the intersection between AI and GWDAs (Fig. 4). In Sec. II, we briefly introduce the development of DL. In Sec. III, we delve into waveform modeling, discussing both traditional methods and the advancements brought about by DL. Sec. IV is dedicated to data quality management, encompassing topics from data quality labeling to noise suppression. Signal detection, a pivotal stage in the analysis, is covered in Sec. V. where we explore various methods and their implications. Parameter estimation, a complex yet crucial aspect, is dissected in Sec. VI. Moving beyond the technicalities. Sec. VII sheds light on the broader scientific discoveries enabled by these methodologies. Lastly, in Sec. VIII, we offer a meta-analysis of the literature, discuss futuristic insights, and chart potential directions for the field.

II. DEEP LEARNING

With AlexNet's unprecedented performance in the ImageNet challenge, 2012 marked an important turning point in AI [89]. This accomplishment demonstrated the potential of neural networks for complex visual tasks. Convolutional neural networks (CNNs) rapidly ascended as the benchmark in image processing, leveraging spatial hierarchies through convolutional layers and pooling operations [90]. However, as network architectures deepened, the vanishing gradient problem became evident. Residual network (ResNet) addressed this, introducing skip connections to facilitate gradient flow [91]. Concurrently, for sequential data, recurrent neural networks (RNNs) emerged as a promising approach [92]. Their capacity to retain state was notable, but challenges with long-term dependencies persisted. WaveNet [93], designed for raw audio generation, addressed this by employing dilated convolutions, expanding the receptive field. In the unsupervised learning domain, AutoEncoders [94], with their encoder-decoder structure, excelled at deriving efficient data representations without relying on labels. Together, these innovations post-AlexNet have shaped the trajectory of DL, setting the stage for subsequent advancements.

Contrasted with discriminative models that have been the mainstay of DL, generative modeling has carved its own niche, offering unique capabilities [95]. Generative adversarial networks (GANs) [96] emerged as a groundbreaking approach, where two neural networks, a generator and a discriminator, engage in a game-theoretic framework [97]. The generator crafts synthetic data, while the discriminator discerns between real and generated samples. This adversarial process results in the generator producing increasingly realistic data [98]. Variational autoencoders (VAEs) [99] offered another perspective, framing generative modeling as a probabilistic graphical model where the encoder and decoder networks are conditioned on latent variables. Normalizing flows [100] and Diffusion models [101] further enriched the generative landscape, providing mechanisms to transform simple distributions



Figure 2. Evolution of deep learning in gravitational wave data analysis (GWDA). The green bars represent the number of published papers on GWDA employing deep learning techniques from 2013 to 2023. The red line traces the growth in the average size of training datasets used in these studies, highlighting the increasing reliance on larger datasets for enhanced model performance and generalization.

into complex data distributions. These generative models have been instrumental in the rise of artificial intelligencegenerated content (AIGC) [102], enabling the synthesis of high-fidelity images [103], videos [104], and even art [105]. The ability of these models to generate content that is often indistinguishable from real-world data has opened new avenues in digital media [106], virtual reality [107], and beyond.

As the field of DL progressed, the Transformer architecture emerged as a groundbreaking innovation, particularly for sequence-based tasks. Introduced by Vaswani et al. [108], the Transformer discarded the recurrent layers that characterized RNNs, instead relying on self-attention mechanisms to process input data. This self-attention allows the model to weight the significance of different parts of an input sequence, regardless of their positional distance, enabling it to capture long-range dependencies in the data with ease [109]. Unlike CNNs, which uses fixedsize filters to process data in local receptive fields, the Transformer's self-attention mechanism provides it with a dynamic receptive field, adjusting based on the content of the input [110]. This flexibility allows Transformers to excel in tasks where the importance of data points varies contextually [111]. Furthermore, while RNNs processes sequences step-by-step, leading to potential issues with long sequences due to vanishing and exploding gradients, transformers process all sequence elements in parallel. This parallel processing not only speeds up training but also alleviates the gradient issues associated with long

sequences [112]. Building on the foundational transformer architecture, LLMs like BERT [113] and GPT [114] have set new benchmarks in natural language processing. Chat-GPT, encompassing iterations like GPT-3.5 and GPT-4 [3], epitomizes the rapid evolution and capabilities of LLMs. These models, with their ability to understand, generate, and reason with text, have showcased the superiority of the transformer architecture over traditional CNNs and RNNs in handling sequence data [115].

While supervised learning and generative models have made significant strides, another paradigm, reinforcement learning from human feedback (RLHF), has emerged as a potent tool in the AI arsenal [116]. Traditional reinforcement learning often requires meticulously crafted reward functions or vast amounts of interaction data [117]. RLHF, however, sidesteps these challenges by leveraging human feedback as a primary source of reward signals [118]. This approach allows models to learn more complex behaviors without the need for explicit reward shaping. OpenAI's fine-tuning of models like GPT-4 using RLHF is a testament to the power of this approach [3]. By collecting comparison data, ranking different model responses, and using proximal policy optimization, models can be fine-tuned to produce safer and more useful outputs [119]. Simultaneously, the field of multi-agent systems is undergoing substantial development [120]. As AI models become more sophisticated, there's a growing interest in how they interact in shared environments [121]. Multiagent systems, where multiple AI entities collaborate or



5

Figure 3. Hierarchical breakdown of deep learning applications in gravitational wave data analysis. The pie chart provides a visual distribution of published papers on GWDA using deep learning, categorized by specific subdomains. Each segment represents a distinct area of application, showcasing the diversity and breadth of deep learning techniques in advancing gravitational wave research.

compete, offer insights into emergent behaviors, cooperation strategies, and even the evolution of communication [122]. The fusion of LLMs with multi-agent setups is particularly intriguing [123, 124]. Imagine agents equipped with the linguistic prowess of LLMs negotiating, strategizing, and evolving their communication protocols in real-time. Such advancements hint at a future where AI entities don't just operate in isolation but actively learn from, compete with, and collaborate with other AI entities, paving the way for more dynamic and adaptive AI ecosystems [125].

III. WAVEFORM MODELING

GW astronomy has experienced significant progress in recent years, with the evolution and modeling of binary black holes (BBHs) taking center stage [126]. The journey of these cosmic phenomena is typically segmented into three phases: the inspiral, merger, and ringdown, with the potential for tidal disruptions in systems involving neutron stars [127]. The accurate depiction of these stages through gravitational waveforms is vital for the detection of GW signals and the interpretation of the celestial narratives they unveil [128, 129].

The creation of waveform templates is an essential

aspect of GW data analysis. These templates act as blueprints for expected GW signals from diverse astrophysical origins and are crucial for the comparison with data collected by GW observatories. However, the production of these templates, particularly for intricate systems, poses significant computational challenges. The computational demands and the sparse nature of numerical relativity (NR) waveforms necessitate the use of more practical approaches. To this end, a variety of approximate waveform models have been developed, such as the IMRPhenom [131–133] and SEOBNR [134–136] families, which are calibrated against NR simulations to ensure accuracy and efficiency in GW data analysis.

In parallel with these developments, the field of waveform modeling is undergoing a transformative phase with the introduction of DL techniques. DL offers a promising pathway to expedite the generation of waveform templates by employing neural networks capable of quickly synthesizing the complex dynamics of compact binary mergers. This innovative approach is poised to revolutionize the way we model waveforms, potentially overcoming the computational bottlenecks of traditional methods. For a detailed overview of the advancements in waveform modeling facilitated by DL, refer to the comprehensive table in Tab. I.

Forecasting the evolution of GW waveforms is akin



Figure 4. The structure of our review. This tree chart delineates the structured progression of our in-depth exploration into the convergence of gravitational waves and artificial intelligence. Each branch represents a dedicated subdomain, emphasizing the harmonious integration of gravitational wave data analysis with the innovative strides of deep learning techniques.

to predicting the future behavior of time series data, a task where DL has shown significant promise. Time series forecasting has been extensively studied in various domains, from finance to weather prediction. In the context of GWs, forecasting waveforms can aid in realtime detections and analyses. DL models, particularly transformers, have the potential to revolutionize waveform forecasting. Khan *et al.* [55] stands as a testament to this potential, showcasing the capabilities of DL in predicting the evolution of GW signals.

In GW astronomy, the imperative for swift and accurate waveform modeling is ever-present. DL presents a promising pathway, but the intricate parameter space of GW signals can be daunting. Surrogate models, trained on NR waveforms, seamlessly integrate DL techniques to expedite traditional waveform calculations [59]. These

Table I. AI-Driven Waveform Modeling in Gravitational Wave Astronomy. This table illustrates the accuracy of various AI models in generating gravitational waveforms. The performance of each model is evaluated by the overlap, which quantifies the similarity between AI-generated waveforms and standard templates.

Paper	Task	Model	Overlap
Huerta et al. [130]	Waveform Generation	GP	0.99
McGinn et al. [53]	Waveform Generation	GAN	-
Liao and Lin [54];	Waveform Generation	CVAE	0.9841
Khan <i>et al.</i> [55]	Waveform Forecasting	Transformer	0.993
Islam <i>et al.</i> [59]	Surrogate Modeling	MLP	0.99

models stand as rapid waveform generators, adeptly spanning the vast GW parameter space [130]. Leading-edge research underscores the transformative potential of surrogate models, signifying a pivotal advancement in harmonizing traditional GW methodologies with the capabilities of AI.

IV. DATA QUALITY MANAGEMENT

Securing impeccable data quality is crucial in the realm of GW astronomy, where the quest to detect these elusive spacetime ripples hinges on the utmost precision. This section rigorously explores the critical aspects of data quality management, emphasizing the indispensable nature of accurate data labeling, meticulous glitch classification, and effective denoising. Each of these procedures plays a vital role in ensuring the integrity and reliability of the data, which is fundamental to the success of gravitational wave detection.

A. Data Quality Labeling

The detection of GW is a complex task, primarily due to the challenge of distinguishing these faint cosmic signals from background noise. The sensitivity of GW detectors is such that they pick up a myriad of noises, ranging from seismic activities to instrumental glitches [20]. This noise can often mimic or obscure the actual GW signals, making the task of identifying genuine events extremely challenging [137, 138]. The intricate nature of GW signals, often buried deep within the noise, requires sophisticated methods to accurately separate signals from noise. This complexity is a fundamental difficulty in GW detection, necessitating advanced techniques for noise analysis and signal extraction [24].

The quality of the data plays a crucial role in the successful detection and analysis of GW signals. High-quality data ensures that the signals extracted are accurate representations of astrophysical events. To achieve this, it's essential to label and categorize the data effectively [32]. Traditional methods of data quality monitoring involve manual labeling, which, while thorough, can be time-

consuming and subject to human error [139]. The vast volume of data generated by GW detectors adds to the complexity, as each data segment needs to be meticulously analyzed to determine its quality. This process is vital as it directly impacts the reliability of signal detection and the subsequent astrophysical interpretations [32].

DL has emerged as a powerful tool in addressing the challenges of data quality labeling in GW astronomy [60]. DL algorithms, particularly neural networks, have the capability to automate the process of data quality assessment, offering both efficiency and accuracy [140]. These algorithms can process large volumes of data rapidly, identifying patterns and anomalies that may indicate issues with data quality. Several studies have demonstrated the effectiveness of DL in automating the data quality labeling process, significantly reducing the time and effort required while maintaining, if not improving, the accuracy of the labels [41]. By ensuring that only high-quality data is fed into analysis pipelines, DL contributes significantly to the robustness and reliability of GW signal detection and analysis [32].

B. Glitch Classification

Glitches, or transient noise artifacts, are a recurring challenge in GW data analysis. These anomalies can significantly impede signal detection processes (see Fig. 5), necessitating their accurate classification and understanding [141]. The impact of glitches is twofold: they can either mimic authentic GW signals, leading to false positives, or they can obscure genuine signals, resulting in missed detections [142]. This dual nature of glitches makes them a critical focus in GW data analysis, as their presence can skew the results and interpretations of GW observations.

Traditionally, the classification of glitches has relied on a variety of methods. One notable initiative in this realm is the Gravity Spy project, which has been instrumental in tackling the glitch challenge [61]. This project has compiled a comprehensive dataset that serves as a crucial resource for the classification of glitches. Traditional methods often involve manual inspection or semi-automated techniques, where analysts use witness data—auxiliary



Figure 5. The influence of glitches on GW detection. This figure presents raw data from the LIGO Hanford and Livingston observatories, capturing the moment of GW170817. It vividly illustrates how glitches, with their power surpassing that of the actual signal, can significantly obstruct gravitational wave detection.

information from the detectors—to help identify and categorize these glitches. These methods, while effective, can be time-consuming and may not always capture the subtle nuances of different glitch types [143].

Table II. Comparative analysis of AI techniques in glitch classification. The table presents a comparison of various AI methodologies, all evaluated using the Gravity Spy dataset. Given the nature of this task as a classification challenge, accuracy serves as the metric for assessing the effectiveness of each approach.

Paper	Model	Accuracy
Mukund et al. [144]	DBNN	0.99
Powell et al. [145, 146]	WDF	0.92
Powell <i>et al.</i> [147]	GAN	0.99
Razzano and Cuoco [63]	SVM	0.971
Razzano and Cuoco [63]	CNN	0.998
Bahaadini et al. [148]	SVM	0.9821
Soni <i>et al.</i> [149]	CNN	0.988
Sakai <i>et al.</i> [150]	CNN	0.97
Fernandes et al. [151]	ConvNeXt	0.981
George et al. [152]	ResNet	0.988

The advent of DL has introduced a new paradigm in glitch classification, offering more sophisticated and efficient approaches. DL-based methods have shown promise in enhancing the accuracy and speed of glitch identification. Some of these techniques directly analyze time-series data from GW detectors, identifying patterns that are characteristic of specific types of glitches [153]. Another innovative approach involves transforming time-series data



Figure 6. **GW denoising by the transformer-based model.** The purple line depicts the original signal, buried in noise, while the green line shows the theoretical signal template. The orange dashed line represents the denoised signal, highlighting the model's efficacy in noise reduction. Adapted from Ref. [65].

into visual formats, allowing CNNs to classify glitches based on their visual signatures [63]. This method leverages the pattern recognition capabilities of CNNs to discern between different glitch types effectively. Looking ahead, the integration of DL in glitch classification is poised to play a pivotal role in the future of GW data analysis, potentially leading to more accurate detections and a deeper understanding of the cosmos [154]. For a detailed exploration of these DL methods, refer to the comprehensive table in Tab. II.

C. Data Denoising

In the realm of GW astronomy, noise is an unavoidable and challenging factor that significantly impacts signal detection [142]. The presence of noise in the data can drastically reduce the signal-to-noise ratio (SNR), leading to difficulties in identifying genuine GW events [37]. Effective denoising is therefore crucial, as it not only improves the SNR but also decreases the false alarm rate (FAR), making it easier to distinguish real signals from noise. Additionally, denoising plays a vital role in the convergence of MCMC parameter estimation processes. By clarifying the signal, denoising methods help in faster and more accurate extraction of signal from the noisy data, thereby enhancing the overall efficiency and reliability of GW signal analysis [24].

Traditional denoising methods in GW astronomy have focused on direct noise suppression techniques, encompassing a variety of approaches. These include variationalbased methods, wavelet-based methods, and techniques utilizing the Hilbert-Huang transform. Each of these strategies aims to remove noise components while preserving the integrity of potential GW signals. For instance, variational-based methods apply mathematical optimization techniques to filter out noise [155], while wavelet-based methods use wavelet transformations to reconstruct signals from data [156, 157]. The Hilbert-Huang transform, a novel approach, is particularly effective for non-linear and non-stationary data [158]. While effective in certain scenarios, these traditional approaches can be limited in their ability to handle the complex and dynamic nature of noise in GW data.

Deep neural network techniques have significantly advanced signal extraction in GWDA. These include dictionary learning [159], which employs basis waveforms for signal representation; WaveNet [160] for its sequential data handling capabilities; denoising autoencoders [161] for reconstructing signals from noisy data; and RNN [162] for capturing temporal dependencies. Notably, the transformer-based model, as discussed in Ref. [24, 65], has been applied to ground-based and space-based GW denoising and detection (Fig. 6), showcasing its potential in handling complex GW data.

V. SIGNAL DETECTION

A. BBH

The detection of GWs, perturbations in spacetime, is a formidable task, primarily due to the subtlety of these signals against a backdrop of overwhelming instrumental and terrestrial noise. The advent of interferometric detectors, notably LIGO and Virgo, has significantly enhanced the observational capabilities for GW astronomy. However, the increased sensitivity and observational bandwidth of these instruments have also introduced intricate data analysis challenges. A cornerstone of GWDA has been matched filtering [37], a technique that cross-correlates observed data with theoretical waveform templates. Given the high-dimensional parameter space associated with potential astrophysical sources, this method, while powerful, is computationally demanding, especially in the context of real-time analysis.

Machine learning, especially DL, has risen to prominence as a potent solution to the computational challenges inherent in GW detection. The initial forays into integrating DL algorithms with mock LIGO data underscored the viability and promise of these approaches [66, 67]. These models, trained on simulated waveforms, were subsequently tested on synthetic data. Impressively, their performance in discerning potential GW signatures from noise was on par with traditional matched filtering-based techniques, underscoring a pivotal advancement in GWDA [68], Tab. III lists out some related works, and their area under the curve (AUC) for detailed performance comparison corresponding receiver operating characteristic (ROC) curve is depicted in Fig. 7.

In light of the proven effectiveness of machine learning on simulated LIGO datasets, the subsequent logical step was its application to genuine observational data. This

Table III. Comparative evaluation of AI methods for BBH GW detection on synthetic data. This table showcases a detailed comparison of different AI techniques, each tested on synthetic data for BBH GW detection. As this task involves binary classification, the Area Under the Curve (AUC) is utilized as the key metric to gauge the performance and accuracy of these AI models.

Paper	Model	AUC
Gabbard et al. [68];	CNN	0.96
Wang <i>et al.</i> [69]	MFCNN	0.97
Xia et al. [163]	CNN	0.98
Ma et al. [52]	CNN	0.94
Ruan <i>et al.</i> [70]	MFCNN	0.99
Krastev [164]	CNN	0.99



Figure 7. Performance characterization of models' detection performance on synthetic data. This figure presents the receiver operating characteristic (ROC) curves of various deep learning models, as detailed in Tab. III. These curves illustrate the performance of each classifier in GW detection on synthetic data, effectively capturing their true positive rate against the false positive rate, thereby providing a clear visual representation of their efficacy in distinguishing between signal and noise. All data points are extracted from the original papers.

transition presented inherent complexities, primarily attributed to the non-Gaussian and non-stationary nature of the noise, which elevated false alarm rates. Addressing these challenges, Wang *et al.* [69] integrated a matched filtering sensing layer prior to the CNN, showcasing its performance on O1 data. Building upon foundational research [64, 165], Huerta *et al.* [51] employed a hardwareaccelerated WaveNet to probe for GW signals within a month-long span of LIGO data. Concurrently, Ren *et al.* [24] proposes WaveFormer, a deep learning-based data quality enhancement method for real observational gravitational wave processing, achieving state-of-the-art noise suppression performance, which paves a solid foundation for future strides in GW data processing and search. With these progressive strides, DL-centric pipelines [166, 167] have been meticulously honed and stand ready for deployment in the forthcoming LIGO O4 data analysis. See Tab. IV for a detailed performance comparison of FAR.

As the GW community approaches a transformative phase, the imminent deployment of space-based and thirdgeneration ground-based detectors heralds a new observational epoch. These advanced instruments, set to provide unparalleled observational capabilities, also bring forth intricate data analysis challenges, particularly due to overlapping GW signals [168]. Recent endeavors on Laser Interferometer Space Antenna (LISA) and Einstein Telescope (ET) mock data have shown promising results [65, 70, 169]. The ongoing advancement and incorporation of machine learning techniques remain crucial for effectively addressing these challenges in the forthcoming era.

Table IV. Comparative analysis of AI approaches for BBH GW detection using LIGO data. The table provides a comparison of various AI methodologies applied to the detection of GWs in LIGO data. In this context, where the focus is on minimizing erroneous detections, the false alarm rate (FAR) is employed as the primary metric to evaluate the effectiveness and precision of each AI technique.

Paper	Model	FAR
Krastev et al. [80]	CNN	$\mathcal{O}(10^3)$ per month
Zhang <i>et al.</i> [170]	BiGRU	1 per 18.2 hours
Wei et al. [165];	WaveNet	1 per 2.7 days
Tian <i>et al.</i> [171]	GNN	1 per month
Schäfer and Nitz [172]	CNN	$1 \text{ per } 10^4 \text{ months}$
Ren <i>et al.</i> [24]	Transformer	1 per 1000 years

B. EMRI

Extreme-mass-ratio inspirals (EMRIs) are among the most intriguing astrophysical phenomena in the universe. These events occur when a stellar-mass compact object, such as a neutron star or a stellar-mass black hole, spirals into a supermassive black hole found at the center of galaxies [173]. The detection of EMRIs holds significant scientific objectives. Firstly, they provide a unique probe into the spacetime geometry around supermassive black holes, allowing for precise tests of general relativity (GR) in strong-field regimes. Secondly, EMRIs can offer insights into the evolution and demographics of compact objects in galactic centers, shedding light on the formation and growth of supermassive black holes over cosmic time [174].

From a technical perspective, detecting EMRIs poses substantial challenges. The GW signals produced by EMRIs are weak and buried in the noise of GW detectors. Their waveform patterns are intricate due to the complex interplay of relativistic effects, making them difficult to model accurately [175]. Furthermore, the long duration of EMRI signals demands efficient and robust data analysis techniques to comb through vast amounts of data. Advanced computational methods, including machine learning and deep neural networks, are being explored to enhance the detection capabilities, such as Zhang et al. [71], Zhao et al. [72], Yun et al. [73] detecting EMRI signals using CNNs, achieving rapid detection of EMRIs with high accuracy in time domain, frequency domain, and time-frequency domain. These advancements are poised to play a pivotal role in the forthcoming era of GW astronomy, where space-based detectors like LISA [176], Taiji [177, 178], and TianQin [179] will offer unprecedented observational capabilities for EMRI detection.

C. GB

The study of GWs has unveiled a myriad of sources, each with its own unique signature and challenges. Among these, the continuous GW comes from the galactic binaries (GBs) or single neutron star, which stands as a testament to the universe's intricate symphony of gravitational interactions. This section delves into the nuances of GB, focusing on its detection in various scenarios and the innovative techniques employed.

Continuous GWs, unlike their transient counterparts, persist over extended observation periods. These waves, often emanating from sources like rapidly rotating neutron stars, present a distinct challenge due to their weak amplitude. Traditional data analysis methods often grapple with the intricacies of these continuous signals. However, the advent of DL has ushered in a new era of possibilities. Neural networks, with their ability to learn intricate patterns from vast amounts of data, have shown promise in detecting and analyzing these weak, continuous GW signals. Several DL models have been proposed, aiming to enhance the detection capabilities by leveraging the power of convolutional and recurrent architectures [74– 77, 180–182]. LIGO, with its ground-based detectors, has been at the forefront of efforts to integrate these advanced machine learning techniques into its data analysis pipeline. The synergy between LIGO's sensitivity and the prowess of DL is paving the way for potential detections in the near future.

The LISA is set to revolutionize our understanding of GWs from space. However, one of the inherent challenges LISA faces is the confusion noise. This noise arises from the superposition of countless unresolved sources, primarily binary systems, creating a cacophony that can mask potential signals. Addressing this requires sophisticated data analysis strategies and a deep understanding of the galactic GW foreground.

Gaussian Processes (GP) has emerged as a powerful

tool in the realm of GW research, particularly for GB GW separation. By leveraging the non-parametric nature of GPs, researchers can model the statistical properties of GBs, effectively separating it from potential signals. This technique holds promise, especially in scenarios with overlapping signals or in the presence of non-Gaussian noise, offering a robust method to extract meaningful information from the data.

VI. PARAMETER ESTIMATION

The extraction of astrophysical source properties from observed GW signals, a process integral to GW astronomy, is known as parameter estimation (PE). At the heart of PE lies the MCMC algorithm, a statistical method that has been instrumental in the field [183]. MCMC operates on the principle of building Markov chains, which are sequences of random samples that, over time, approximate the desired distribution of the parameters being estimated (see Fig. 8 for detail). This method is particularly effective in exploring high-dimensional parameter spaces, making it a staple in GWDA [184].

Despite the effectiveness of MCMC in providing detailed insights into complex data sets, it comes with its own set of challenges. The primary concerns are its computational intensity and occasional struggles with convergence, especially in scenarios involving intricate and voluminous data. These limitations become increasingly significant as the complexity of GW data escalates and the demand for rapid analysis grows [184].

In response to these challenges, the field of GW astronomy is witnessing a paradigm shift towards DL models. These advanced computational approaches are proving to be a game-changer, offering a way to address the inherent limitations of traditional PE methods like MCMC. With their ability to process large datasets efficiently and accurately, DL models are setting new standards in the speed and precision of GWDA, heralding a new era in the exploration of the universe's gravitational mysteries [46].

A. Point Estimation

a. Fast PE by MLP: One of the initial forays into DL for PE involved the use of Multi-Layer Perceptrons (MLP). These architectures, designed to provide a direct "point estimate" for each parameter, have the advantage of speed. Capable of delivering estimates in near-real-time, MLPs have become instrumental for scenarios where rapid response is paramount, such as in the case of multi-messenger astronomy [80].

b. Localization: Beyond the realm of intrinsic parameters, DL models have been extended to tackle extrinsic parameters. A salient application in this domain is the localization of GW sources. Through DL models that predict both sky location and distance, the astronomical community is better equipped to identify the precise origins of GW events, furthering the cause of multi-messenger observations [186].

B. Posterior Distribution

While point estimates are invaluable for quick insights, a deeper understanding of source properties necessitates the exploration of the full posterior distribution. To this end, several DL models have been proposed:

a. Flow-based Models: Flow-based architectures, which are known for their ability to model complex distributions (Fig. 8), have been a popular choice for density estimation and posteriors. Green et al. [187] and Shen et al. [188] first demonstrated the efficacy of these models in GW PE by proposing toy models for the low-dimensional parameter sub-space of BBH, then Green and Gair [189] extended the work to the full parameter space of BBH and evaluated on GW150914. Subsequently, Wang et al. [23] accelerated the convergence speed by intergrating domain knowledge into prior distribution. Recently, Dax et al. [46, 81, 82], Wildberger et al. [190], Williams et al. [191, 192], Bhardwaj et al. [193] have further refined these models, showcasing their performance on a variety of GW events. Wong et al. [194–196] developed a Jax-based framework for rapid PE. The ability of these models to capture the nuances of the posterior distribution, especially in scenarios with complex degeneracy, has been a key factor in their success. Furthermore, the computational efficiency of these models, coupled with their ability to generate samples, has been instrumental in addressing the challenges of traditional PE methods Now $DINGO^2$ has been used in the LIGO data analysis pipeline.

b. Conditional Variational Autoencoders (CVAE): Another promising avenue is the use of CVAE. As demonstrated by Gabbard *et al.* [197] and Green *et al.* [187], CVAEs, by conditioning on observed data, can generate samples that align closely with the true posterior distribution, offering a probabilistic perspective on source parameters.

c. Gaussian Processes (GP): For specialized sources such as GBs and EMRIs, GP have been employed, as seen in [78, 198]. Tailored to the unique signatures of these sources, GPs provides refined posterior estimates, enriching our comprehension of these intriguing astrophysical systems.

VII. AI FOR GW SCIENCE

GW astronomy has opened a new window to the universe, allowing us to probe extreme astrophysical and cosmological phenomena. With the increasing complexity

² https://github.com/dingo-gw/dingo



Figure 8. Flowchart of the MCMC algorithm and normalizing flow. This top of the diagram illustrates the step-by-step process of the Metropolis-Hastings algorithm, tracing its progression from the initial prior distribution to the final posterior distribution. The bottom part highlights the normalizing flow, a method that accelerates the process by leveraging a trained bijection composed of simple maps. This approach significantly enhances computational speed and efficiency in parameter estimation, offering a remarkable improvement over the traditional MCMC methodology. Adapted from Ref. [185].

Table V. Comparative analysis of AI techniques for GW parameter estimation. This table offers a comparison of various AI methods in GW parameter estimation, highlighting not only their effectiveness as measured by the Jensen-Shannon divergence (JS div.) against traditional MCMC results but also detailing the dimensionality of the parameter space each model is capable of sampling.

Paper	Dim	Model	JS div.
Green <i>et al.</i> [187]	$5\mathrm{D}$	CVAE	_
Green and Gair [189];	$15\mathrm{D}$	nflow	_
Dax et al. [46]	$15\mathrm{D}$	Dingo	2.2×10^{-3}
Gabbard et al. [197]	$15\mathrm{D}$	CVAE	~ 0.1
Dax et al. [82]	$15\mathrm{D}$	Dingo-IS	5×10^{-4}
Langendorff et al. [199]	30D	nflow	-

and volume of GW data, AI has emerged as a powerful tool to address various challenges and unlock new scientific potential in the field.

A. Fundamental Physics

GWs, ripples in the fabric of spacetime, have emerged as a revolutionary tool for astrophysical exploration. These waves, produced by cataclysmic events such as the merger of black holes or neutron stars, provide a pristine medium



Figure 9. Tree diagram of modified gravity theories. This diagram illustrates the hierarchical structure and interrelationships among various modified gravity theories. Branching from the root concept, each pathway represents a distinct theoretical development, offering insights into alternative explanations of gravitational phenomena beyond general relativity. Adapted from Ref. [200].

to probe the universe's most enigmatic phenomena [201]. Unlike electromagnetic radiation, which can be obscured or altered by intervening matter, GWs travels undisturbed, offering a direct and unadulterated glimpse into their sources. The detection of GWs has opened a new avenue to explore the strong-field regime of GR [202]. Traditional electromagnetic observations, while invaluable, often fall short in this domain, especially when it comes to events like black hole mergers. GW detections, on the other hand, allow scientists to test Einstein's theory under extreme conditions, shedding light on the intricate dance of massive celestial bodies and the spacetime they warp [202].

The promise of space-based observatories, particularly LISA, is immense. Positioned far from Earth's noisy environment, LISA aims to access the low-frequency GW spectrum [203]. This capability is anticipated to unveil events like supermassive black hole mergers, which have remained elusive to ground-based detectors, offering a new observational window into the dynamics of galactic centers [204]. The GW community eagerly anticipates the advent of third-generation observatories, such as the ET. These state-of-the-art facilities promise enhanced sensitivity and a broader frequency range [205]. With these advancements, scientists expect to detect a diverse array of sources, from the dramatic death throes of massive stars in core-collapse supernovae to potential signals from exotic compact objects. The enriched catalog of detections will undoubtedly deepen our understanding of the universe's violent processes.

While GR has withstood a century of scrutiny, GW observations offer a unique platform to test its predictions and probe potential deviations. The precision of these observations might reveal subtle signatures hinting at alternative theories of gravity, pushing the boundaries of our current understanding and opening doors to new realms of physics (Fig. 9). The synergy of advanced detector networks has been instrumental in refining parameter estimation techniques. As detectors' sensitivity improves, so does the accuracy with which we can determine the properties of GW sources. This precision not only allows for a more detailed understanding of individual events but might also offer subtle hints of new physics lurking in the shadows. Among the most tantalizing prospects in GW science is the detection of the stochastic gravitational wave background (SGWB). This omnipresent hum, a relic from the early universe, holds the potential to offer insights into primordial processes and interactions, painting a picture of the cosmos's infancy. Interdisciplinary efforts, merging the expertise of astrophysicists, general relativists, and data scientists, promise to usher in a new era of GW science. As technology advances and our observational capabilities expand, so too will our understanding of the cosmos, revealing its mysteries one GW at a time.

astronomy and AI not only underscores the interdisciplinary nature of modern astrophysics but also promises to address some of the most perplexing challenges in the field [85].

tension—the discrepancy between the Hubble constant

values derived from cosmic microwave background radia-

tion and those from local distance ladder measurements

(Fig. 10) [17]. While traditional methods have presented

conflicting results, AI-driven analyses of GW data could

provide an independent and precise measurement of the

Hubble constant [14]. By analyzing the GW signals from

binary mergers, AI can help refine our understanding of the universe's expansion rate, offering a potential resolu-

tion to the Hubble tension. This synergy between GW

Astrophysics С.

GWs emanates from some of the most violent and energetic processes in the universe, making them invaluable tools for astrophysical studies [207]. Neutron stars, the remnants of massive stellar explosions, are laboratories for extreme physics. Their equation of state (EoS) remains one of the outstanding puzzles in astrophysics [208]. AI-driven methods can assist in classifying different EoS models based on the GW signals emitted during neutron star mergers [86-88, 209]. Furthermore, core-collapse supernovae (CCSN) are cataclysmic events marking the end of a massive star's life. The EoS governing the processes inside these explosive events can be probed using GWs [210]. AI can aid in deciphering the intricate signals from CCSN, providing insights into the underlying physics [211]. As the number of GW detections grows, there's an increasing interest in understanding the population properties of the sources, be it BBHs, neutron stars (BNSs), or other exotic objects [212]. AI can assist in population synthesis studies, helping to unravel the formation and evolution histories of these compact objects [195].

VIII. DISCUSSION

As the application of DL techniques to GW analysis matures, several key themes and challenges emerge. This section delves into a meta-analysis of the current landscape, discusses the prospects of waveform forecasting, highlights the importance of gap imputation, and underscores the significance of multi-modality and interpretability in DL models.

Meta-Analysis Α.

B. Cosmology

GWs offer a unique lens to probe the cosmos, and their potential in cosmological studies is gradually being realized. One pressing issue in cosmology is the Hubble

The intersection of GW astronomy and DL has unfurled a vibrant tapestry of research, where the threads of data and scholarly publications weave a narrative of a field in perpetual evolution. Our meta-analysis, encapsulated in Fig. 2 and Fig. 3, endeavors to navigate through this



Figure 10. Evolving perspectives on the Hubble tension. This chart illustrates the varied estimates of the Hubble constant, highlighting the ongoing Hubble tension. It compares values obtained from the cosmic micro background (CMB), Cepheid variables (blue), and the Tip of the Red Giant Branch (TRGB) method (red). The divergence between CMB and Cepheid results, ranging from $67 \sim 74 \text{ km} \cdot \text{s}^{-1} \cdot \text{Mpc}^{-1}$ with TRGB in the middle findings intersecting, underscores the complexities and challenges in resolving the Hubble tension. Adapted from Ref. [206].

intricate weave, offering a synthesized view that melds quantitative analysis with a contemplative exploration of the journey thus far.

Fig. 2 unfolds a dual narrative: one of burgeoning data and the other of an escalating volume of research. The graph delineates the trajectory of the average training dataset size alongside the annual proliferation of papers, either published or pre-published on platforms like arXiv. This visual narrative, while ostensibly a testament to the field's quantitative growth, also subtly underscores the symbiotic relationship between data and research output. The burgeoning datasets not only fuel the development and refinement of DL models but also inspire a cascade of research endeavors, exploring novel methodologies and applications in the GW domain.

In this narrative, each data point is not merely a statistical marker but a milestone, indicative of the community's collective endeavors, challenges encountered, and the innovative solutions that ensued. The escalating dataset sizes reflect the technological advancements in GW detectors and data processing methodologies, while the swelling volume of publications mirrors the expanding research community and the diversification of research themes and methodologies. Each slice of the donut in Fig. 3 represents a distinct subdomain, waveform modeling, signal detection, parameter estimation, and more. These slices, while categorically distinct, are part of a cohesive whole, symbolizing the interconnectedness of various research areas within the GW and AI intersection. The size of each slice not only quantifies the volume of research dedicated to each subdomain but also subtly hints at the unique challenges and the potential impact of breakthroughs in these areas. This meta-analysis, while offering a retrospective view, also casts a speculative glance towards the future. The trends indicated in Fig. 2 are not merely historical data but potential predictors of future trajectories, offering insights that could guide resource allocation, research focus, and collaborative efforts in the coming years. In synthesizing this decade-long journey, our metaanalysis aspires to serve as both a reflective repository



Figure 11. **GW signal forecasting.** This figure illustrates the forecasting of the GW signal from BBH. The green line represents the template, and the orange line represents the forecasted signal.

and a strategic guide, anchoring past endeavors while subtly steering the research community towards future horizons, where the entwined paths of GW astronomy and DL continue to unravel new realms of possibilities and discoveries.

B. Waveform Forecasting

GW astronomy has ushered in a new era of understanding the universe, with waveform modeling playing a pivotal role in deciphering the signals from astrophysical cataclysms. Waveform forecasting, a subset of this modeling, focuses on predicting the evolution of these waveforms (Fig. 11), especially in scenarios where only a fragment of the waveform is known or computationally feasible to generate.

The importance of efficient waveform modeling cannot be overstated. Traditional waveform modeling, particularly for systems exhibiting higher modes or precession, demands significant computational resources [136]. The ability to forecast a waveform, rather than compute it in its entirety, offers a promising avenue to mitigate these computational challenges [213]. As the GW community moves towards real-time detections, the need for rapid template generation becomes essential [214]. Waveform forecasting can expedite this process, ensuring that potential GW events are not missed during live observations. Some astrophysical systems present intricate waveforms that are computationally intensive to model [215]. Forecasting provides a mechanism to capture the essence of these systems, offering a balance between accuracy and computational feasibility.

While traditional methods have laid the groundwork for waveform forecasting, they come with inherent limitations, especially when dealing with complex astrophysical systems [216]. Enter DL. Drawing inspiration from its



Figure 12. **GW signal imputation.** This figure illustrates the inpainting of the GW data gap. The green line represents the template, and the orange line represents the impainted signal.

successes in other domains, particularly sequence forecasting, DL holds the promise of revolutionizing waveform forecasting in GW astronomy [217]. The potential benefits include enhanced accuracy, reduced computational overhead, and the ability to handle a broader range of astrophysical systems.

However, the journey of integrating DL into waveform forecasting is not without challenges. The complexity of GW signals, the omnipresent detector noise, and the need for vast training datasets to train robust models are but a few of the hurdles to overcome [56].

In conclusion, as we stand on the cusp of a new frontier in GW astronomy, the symbiosis between DL and waveform forecasting is poised to play a transformative role. Collaborative efforts between the AI and GW communities will be instrumental in navigating this exciting journey ahead.

C. Gap Imputation

In the realm of time series data analysis, especially when dealing with time series data, the presence of gaps or missing data points can pose significant challenges [218]. These gaps can arise due to a myriad of reasons, from instrumental downtime to environmental disturbances or even data transmission issues [219]. GW data, with its intricate patterns and crucial reliance on continuity, is no exception to this challenge [220].

GW observations, by their nature, require continuous and uninterrupted data streams for accurate detection and analysis [221]. Any gaps in this data can lead to missed detections or, worse, misinterpretations of potential events (Fig. 12). Traditional methods employed in other fields to address missing data, such as linear interpolation or mean imputation, often fall short when applied to the complexities of GW signals [222]. These methods, while simple, may not capture the intricate patterns and dependencies inherent in GW data, leading to inaccuracies [223, 224].

Enter DL, a paradigm that has shown remarkable success in various domains, including gap imputation in time series data [225]. DL models, with their ability to learn and capture intricate patterns in data, hold significant promise for addressing the gap imputation challenge in GW data [226]. The potential benefits are manifold, from improved accuracy in imputation to the capability to handle large gaps that traditional methods might struggle with. However, the application of DL to GW data for gap imputation is not without its challenges. The non-stationary nature of GW data, combined with the omnipresent noise, necessitates careful consideration and design of DL models. Additionally, it is essential to ensure that the integration of imputed data does not lead to biases or inaccuracies in further analytical processes.

In conclusion, while DL offers a promising avenue for gap imputation in GW data, the field is ripe for research and exploration. Collaborative efforts between the AI and GW communities could pave the way for innovative solutions, ensuring that our observations of the universe remain as accurate and uninterrupted as possible.

D. Multi-Modality



Figure 13. Multi-modal representation of GW data for large AI model training. This figure showcases a comprehensive analysis framework combining time series data, spectrogram visualizations, and physical parameters. The time series plot captures the temporal dynamics of the GW signals, while the spectrogram provides a frequency-based perspective. The inclusion of physical parameters, such as mass and spin, offers a deeper understanding of the intrinsic physical properties.

The realm of AI, particularly in the domain of DL, has

witnessed a surge in the exploration and application of multi-modal techniques [227, 228]. These techniques harness information from multiple data sources or modalities, aiming to provide a more comprehensive understanding of the underlying phenomena. In many AI applications, multi-modality has proven to be transformative. For instance, in medical imaging, combining visual data from MRI scans with textual patient records has enhanced diagnostic accuracy and predictive modeling [229]. Similarly, in natural language processing, the fusion of textual, auditory, and visual cues in multi-modal sentiment analysis models has led to more nuanced and context-aware interpretations [230].

GW astronomy, while primarily reliant on signal data, has the potential to benefit from a multi-modal approach. Consider the richness of information available: beyond the GW signals, there are electromagnetic signals, neutrino observations, and more [231]. Each modality offers a unique perspective on astrophysical events. While current GW analyses have not vet integrated such diverse data streams, the success of multi-modal techniques in other AI domains suggests potential avenues for exploration. One can envision a future where GW detections are enhanced by concurrent observations from electromagnetic or neutrino observatories [232]. DL models, adept at handling multi-modal data, could be trained to extract features from each modality and then fuse these features to improve event characterization, source localization, and parameter estimation.

However, the integration of multi-modal data in GW analysis is not without challenges. The synchronization of data streams, the handling of disparate data resolutions and formats, and the development of fusion techniques tailored to the specificities of GW events are all areas that would require meticulous research and innovation (Fig. 13). Yet, the potential rewards are significant. A successful multi-modal approach could provide a more holistic view of astrophysical events, bridging gaps in our understanding and opening new frontiers in GW astronomy.

E. Interpretability

Interpretability in machine learning has garnered significant attention [233], especially when models are applied to complex scientific domains [234]. In the realm of GW analysis, understanding the decision-making process of models is not just a luxury but a necessity. This ensures that the predictions and insights derived are both reliable and scientifically meaningful. GW signals, with their intricate patterns and the profound astrophysical phenomena they represent, pose a unique challenge for DL models. While these models can achieve impressive performance metrics, deciphering their decision-making process in the context of such complex signals remains a formidable task.

Recent works have made strides in bridging this inter-



Figure 14. Interpretability showcase of the pretrained large AI model in GW waveform prediction. This figure features a colored mesh representing the attention map of the transformer model, which highlights the weights the model focuses on during analysis. The blue lines in the left and bottom panels show the input GW waveforms. The red line illustrates the waveform predicted by the model. The attention map demonstrates the model's capability for accurately modeling and forecasting gravitational wave signals. Adapted from Ref. [56].

pretability gap. For instance, Khan et al. [55] delved into

- F. Schroff, D. Kalenichenko, and J. Philbin, in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)* (IEEE, Boston, MA, USA, 2015).
- [2] Seamless Communication, "SeamlessM4T—massively multilingual & multimodal machine translation," (2023).
- [3] OpenAI, GPT-4 Technical Report, Tech. Rep. (OpenAI, 2023) arXiv:2303.08774.
- [4] H. Touvron, L. Martin, K. Stone, P. Albert, A. Almahairi, Y. Babaei, N. Bashlykov, S. Batra, P. Bhargava, S. Bhosale, et al., "Llama 2: Open foundation and finetuned chat models," (2023), arXiv:2307.09288.
- [5] M. Stinger, AI Poetry: Artificially Generated Poems Written by the Latest in AI Technology (Independently published, 2023).
- [6] J. Copet, F. Kreuk, I. Gat, T. Remez, D. Kant, G. Synnaeve, Y. Adi, and A. Défossez, "Simple and Controllable Music Generation," (2023), arXiv:2306.05284.
- [7] G. Eysenbach, JMIR Med. Educ. 9, e46885 (2023).
- [8] Y. Djenouri, A. Belhadi, G. Srivastava, and J. C.-W. Lin, Future Gener Comput Syst 139, 100 (2023).
- [9] H. Wang, T. Fu, Y. Du, W. Gao, K. Huang, Z. Liu, P. Chandak, S. Liu, P. Van Katwyk, A. Deac, et al., Nature 620, 47 (2023).
- [10] B. A. Olshausen and D. J. Field, Nature **381**, 607 (1996).

creating models that not only detect but also elucidate the characteristics of GW signals. Similarly, the studies by Shi *et al.* [56], Zhao *et al.* [65] have contributed to enhancing the transparency of models, especially Transformers, ensuring that their predictions can be traced back to understandable reasoning. An interpretable model in GW analysis offers more than just reliable predictions (see Fig. 14). It provides a window into the astrophysical processes that generate these ripples in spacetime. By understanding how a model discerns between different

unlocking new facets of our universe. As the field progresses, there's a palpable need for more research dedicated to enhancing interpretability. The fusion of traditional astrophysical knowledge with transparent machine learning models holds the promise of richer, more profound insights into the cosmos.

types of signals, researchers can gain deeper insights into the astrophysical events behind these waves, potentially

ACKNOWLEDGMENTS

The research was supported by the Peng Cheng Laboratory and by Peng Cheng Laboratory Cloud-Brain. This work was also supported in part by the National Key Research and Development Program of China Grant No. 2021YFC2203001 and in part by the NSFC (No. 11920101003 and No. 12021003). Z.C was supported by the "Interdisciplinary Research Funds of Beijing Normal University" and CAS Project for Young Scientists in Basic Research YSBR-006.

- [11] C. V. Theodoris, L. Xiao, A. Chopra, M. D. Chaffin, Z. R. Al Sayed, M. C. Hill, H. Mantineo, E. M. Brydon, Z. Zeng, X. S. Liu, et al., Nature **618**, 616 (2023).
- [12] A. Suwardi, F. Wang, K. Xue, M.-Y. Han, P. Teo, P. Wang, S. Wang, Y. Liu, E. Ye, Z. Li, et al., Adv. Mater. 34, 2102703 (2022).
- [13] J. Jumper, R. Evans, A. Pritzel, T. Green, M. Figurnov, O. Ronneberger, K. Tunyasuvunakool, R. Bates, A. Žídek, A. Potapenko, et al., Nature **596**, 583 (2021).
- [14] The LIGO Scientific Collaboration and The Virgo Collaboration, B. P. Abbott, R. Abbott, T. D. Abbott, F. Acernese, K. Ackley, C. Adams, T. Adams, P. Addesso, R. X. Adhikari, et al., Nature 551, 85 (2017).
- [15] S. Lucci, S. M. Musa, and D. Kopec, Artificial Intelligence in the 21st Century, 3rd ed. (Mercury Learning and Information, Duxbury, 2022).
- [16] D. Reitze, A. Lazzarin, and B. O'Reilly, *LIGO-Virgo Cumulative Event/Candidate Rate Plot 01-03*, Tech. Rep. LIGO-G1901322-v25 (LIGO, 2020).
- [17] W. L. Freedman, Astrophys. J 919, 16 (2021).
- [18] B. P. Abbott, R. Abbott, T. D. Abbott, M. R. Abernathy, F. Acernese, K. Ackley, C. Adams, T. Adams, P. Addesso, R. X. Adhikari, et al., Phys. Rev. Lett. **116**, 241103 (2016).
- [19] B. P. Abbott, R. Abbott, T. D. Abbott, F. Acernese,

K. Ackley, C. Adams, T. Adams, P. Addesso, R. X. Adhikari, V. B. Adya, et al., Phys. Rev. Lett. **119**, 141101 (2017).

- [20] D. Davis and M. Walker, Galaxies 10, 12 (2022).
- [21] N. Yunes, M. C. Miller, and K. Yagi, Nat Rev Phys 4, 237 (2022).
- [22] The LIGO Scientific Collaboration, The Virgo Collaboration, The KAGRA Collaboration, R. Abbott, T. D. Abbott, F. Acernese, K. Ackley, C. Adams, N. Adhikari, R. X. Adhikari, et al., "GWTC-3: Compact Binary Coalescences Observed by LIGO and Virgo During the Second Part of the Third Observing Run," (2021), arXiv:2111.03606.
- [23] H. Wang, Z. Cao, Y. Zhou, Z.-K. Guo, and Z. Ren, Big Data Min. Anal. 5, 53 (2022).
- [24] Z. Ren, H. Wang, Y. Zhou, Z.-K. Guo, and Z. Cao, "Intelligent noise suppression for gravitational wave observational data," (2022), arXiv:2212.14283.
- [25] T. Adams, D. Buskulic, V. Germain, G. M. Guidi, F. Marion, M. Montani, B. Mours, F. Piergiovanni, and G. Wang, Class. Quantum Gravity 33, 175012 (2016).
- [26] B. P. Abbott, R. Abbott, T. D. Abbott, M. R. Abernathy, F. Acernese, K. Ackley, C. Adams, T. Adams, P. Addesso, R. X. Adhikari, et al., Phys. Rev. Lett. **116**, 061102 (2016).
- [27] B. P. Abbott, R. Abbott, T. D. Abbott, M. R. Abernathy, et al. (LIGO Scientific Collaboration and Virgo Collaboration), Phys. Rev. Lett. **116**, 221101 (2016).
- [28] B. P. Abbott, R. Abbott, T. D. Abbott, M. R. Abernathy, F. Acernese, K. Ackley, C. Adams, T. Adams, P. Addesso, R. X. Adhikari, et al., Phys. Rev. Lett. **116**, 131103 (2016).
- [29] The LIGO Scientific Collaboration, J. Aasi, B. P. Abbott, R. Abbott, T. Abbott, et al., Class. Quantum Gravity 32, 074001 (2015).
- [30] F. Acernese, M. Agathos, K. Agatsuma, D. Aisa, et al., Class. Quantum Gravity 32, 024001 (2015).
- [31] D. V. Martynov, E. D. Hall, B. P. Abbott, R. Abbott, T. D. Abbott, C. Adams, R. X. Adhikari, R. A. Anderson, S. B. Anderson, K. Arai, et al., Phys. Rev. D 93, 112004 (2016), arXiv:1604.00439.
- [32] D. Davis, B. Hughey, T. Massinger, L. Nuttall, A. Stuver, and J. Zweizig, *Data Quality Vetoes Applied to the Analysis of LIGO Data from the Third Observing Run*, Tech. Rep. LIGO-T2100045-v2 (LIGO, 2021).
- [33] K. Mogushi, Reduction of Transient Noise Artifacts in Gravitational-Wave Data Using Deep Learning, Tech. Rep. LIGO-P2100159 (LIGO, 2021) arXiv:2105.10522.
- [34] F. Matichard, B. Lantz, R. Mittleman, et al., Class. Quantum Gravity 32, 185003 (2015).
- [35] S. Bose, A. Pai, and S. Dhurandhar, Int. J. Mod. Phys. D 09, 325 (2000), arXiv:gr-qc/0002010.
- [36] T. Zhao, Z. Cao, C.-Y. Lin, and H.-J. Yo, in *Handbook of Gravitational Wave Astronomy*, edited by C. Bambi, S. Katsanevas, and K. D. Kokkotas (Springer Singapore, Singapore, 2020) pp. 1347–1376.
- [37] L. S. Finn, Phys. Rev. D 46, 5236 (1992).
- [38] E. Poisson and C. M. Will, Phys. Rev. D 52, 848 (1995).
- [39] S. A. Usman, A. H. Nitz, I. W. Harry, C. M. Biwer, D. A. Brown, M. Cabero, C. D. Capano, T. D. Canton, T. Dent, S. Fairhurst, et al., Class. Quantum Gravity 33, 215004 (2016).
- [40] K. Cannon, S. Caudill, C. Chan, B. Cousins, J. D. Creighton, B. Ewing, H. Fong, P. Godwin, C. Hanna,

S. Hooper, et al., SoftwareX 14, 100680 (2021).

- [41] R. Essick, P. Godwin, C. Hanna, L. Blackburn, and E. Katsavounidis, Mach. Learn.: Sci. Technol. 2, 015004 (2020).
- [42] P. Jaranowski and A. Królak, Living Rev. Relativ. 15, 4 (2012).
- [43] A. Bohé, L. Shao, A. Taracchini, A. Buonanno, S. Babak, I. W. Harry, I. Hinder, S. Ossokine, M. Pürrer, V. Raymond, et al., Phys. Rev. D 95, 044028 (2017).
- [44] V. Varma, S. E. Field, M. A. Scheel, J. Blackman, L. E. Kidder, and H. P. Pfeiffer, Phys. Rev. D 99, 064045 (2019).
- [45] G. Ashton, M. Hübner, P. D. Lasky, C. Talbot, K. Ackley, S. Biscoveanu, Q. Chu, A. Divakarla, P. J. Easter, B. Goncharov, et al., Astrophys. J. Suppl. Ser. 241, 27 (2019).
- [46] M. Dax, S. R. Green, J. Gair, J. H. Macke, A. Buonanno, and B. Schölkopf, Phys. Rev. Lett. **127**, 241103 (2021).
- [47] P. B. Covas, A. Effler, E. Goetz, P. M. Meyers, A. Neunzert, M. Oliver, B. L. Pearlstone, V. J. Roma, R. M. S. Schofield, V. B. Adya, et al., Phys. Rev. D 97, 082002 (2018).
- [48] E. A. Huerta and Z. Zhao, in *Handbook of Gravitational Wave Astronomy*, edited by C. Bambi, S. Katsanevas, and K. D. Kokkotas (Springer Singapore, Singapore, 2021) pp. 1793–1820.
- [49] E. Cuoco, A. Iess, F. Morawski, and M. Razzano, in *Handbook of Gravitational Wave Astronomy*, edited by C. Bambi, S. Katsanevas, and K. D. Kokkotas (Springer Singapore, Singapore, 2020) pp. 1769–1792.
- [50] V. Benedetto, F. Gissi, G. Ciaparrone, and L. Troiano, Appl. Sci. 13, 9886 (2023).
- [51] E. A. Huerta, A. Khan, X. Huang, M. Tian, M. Levental, R. Chard, W. Wei, M. Heflin, D. S. Katz, V. Kindratenko, et al., Nat Astron 5, 1062 (2021), arXiv:2012.08545.
- [52] C. Ma, W. Wang, H. Wang, and Z. Cao, Phys. Rev. D 105, 083013 (2022), arXiv:2204.12058.
- [53] J. McGinn, C. Messenger, M. J. Williams, and I. S. Heng, Class. Quantum Gravity 38, 155005 (2021).
- [54] C.-H. Liao and F.-L. Lin, Phys. Rev. D 103, 124051 (2021).
- [55] A. Khan, E. A. Huerta, and H. Zheng, Phys. Rev. D 105, 024024 (2022).
- [56] R. Shi, Y. Zhou, T. Zhao, Z. Cao, and Z. Ren, "Compact Binary Systems Waveform Generation with Generative Pre-trained Transformer," (2023), arXiv:2310.20172.
- [57] V. Varma, D. Gerosa, L. C. Stein, F. Hébert, and H. Zhang, Phys. Rev. Lett. **122**, 011101 (2019).
- [58] V. Varma, S. E. Field, M. A. Scheel, J. Blackman, D. Gerosa, L. C. Stein, L. E. Kidder, and H. P. Pfeiffer, Phys. Rev. Res. 1, 033015 (2019), arXiv:1905.09300.
- [59] T. Islam, S. E. Field, S. A. Hughes, G. Khanna, V. Varma, M. Giesler, M. A. Scheel, L. E. Kidder, and H. P. Pfeiffer, Phys. Rev. D 106, 104025 (2022).
- [60] P. Godwin, Low-Latency Statistical Data Quality in the Era of Multi-Messenger Astronomy, Ph.D. thesis, The Pennsylvania State University, University Park, PA, USA (2020).
- [61] M. Zevin, S. Coughlin, S. Bahaadini, E. Besler, N. Rohani, S. Allen, M. Cabero, K. Crowston, A. K. Katsaggelos, S. L. Larson, et al., Class. Quantum Gravity 34, 064003 (2017).
- [62] L. Vazsonyi and D. Davis, Class. Quantum Gravity 40, 035008 (2023).

- 095016 (2018), arXiv:1803.09933.
 [64] W. Wei and E. A. Huerta, Phys. Lett. B 800, 135081 (2020), arXiv:1901.00869.
- [65] T. Zhao, R. Lyu, H. Wang, Z. Cao, and Z. Ren, Commun Phys 6, 212 (2023).
- [66] D. George and E. A. Huerta, Phys. Lett. B 778, 64 (2018), arXiv:1711.03121.
- [67] D. George and E. A. Huerta, Phys. Rev. D 97, 044039 (2018), arXiv:1701.00008.
- [68] H. Gabbard, M. Williams, F. Hayes, and C. Messenger, Phys. Rev. Lett. **120**, 141103 (2018), arXiv:1712.06041.
- [69] H. Wang, Z. Cao, X. Liu, S. Wu, and J.-Y. Zhu, Phys. Rev. D 101, 104003 (2020), arXiv:1909.13442.
- [70] W.-H. Ruan, H. Wang, C. Liu, and Z.-K. Guo, Phys. Lett. B 841, 137904 (2023).
- [71] X.-T. Zhang, C. Messenger, N. Korsakova, M. L. Chan, Y.-M. Hu, and J.-d. Zhang, Phys. Rev. D 105, 123027 (2022).
- [72] T. Zhao, Y. Zhou, R. Shi, Z. Cao, and Z. Ren, "DECODE: Dilated COnvolutional neural network for Detecting Extreme-mass-ratio inspirals," (2023), arXiv:2308.16422.
- [73] Q. Yun, W.-B. Han, Y.-Y. Guo, H. Wang, and M. Du, "Detecting extreme-mass-ratio inspirals for space-borne detectors with deep learning," (2023), arXiv:2309.06694.
- [74] C. Dreissigacker, R. Sharma, C. Messenger, R. Zhao, and R. Prix, Phys. Rev. D 100, 044009 (2019).
- [75] C. Dreissigacker and R. Prix, Phys. Rev. D 102, 022005 (2020).
- [76] B. Beheshtipour and M. A. Papa, Phys. Rev. D 101, 064009 (2020).
- [77] B. Beheshtipour and M. A. Papa, Phys. Rev. D 103, 064027 (2021).
- [78] M. Falxa, S. Babak, and M. Le Jeune, Phys. Rev. D 107, 022008 (2023).
- [79] A. Khan, E. A. Huerta, and A. Das, Phys. Lett. B 808, 135628 (2020), arXiv:2004.09524.
- [80] P. G. Krastev, K. Gill, V. A. Villar, and E. Berger, Phys. Lett. B 815, 136161 (2021).
- [81] M. Dax, S. R. Green, J. Gair, M. Deistler, B. Schölkopf, and J. H. Macke, in *International Conference on Learn*ing Representations (ICLR) (OpenReview.net, Virtual, 2022).
- [82] M. Dax, S. R. Green, J. Gair, M. Pürrer, J. Wildberger, J. H. Macke, A. Buonanno, and B. Schölkopf, Phys. Rev. Lett. 130, 171403 (2023).
- [83] I. Liodis, E. Smirniotis, and N. Stergioulas, "A neuralnetwork-based surrogate model for the properties of neutron stars in 4D Einstein-Gauss-Bonnet gravity," (2023), arXiv:2309.03991.
- [84] S. Bhagwat and C. Pacilio, Phys. Rev. D 104, 024030 (2021).
- [85] F. Stachurski, C. Messenger, and M. Hendry, "Cosmological Inference using Gravitational Waves and Normalising Flows," (2023), arXiv:2310.13405.
- [86] Y. Fujimoto, K. Fukushima, and K. Murase, Phys. Rev. D 101, 054016 (2020).
- [87] F. Morawski and M. Bejger, Astron. Astrophys. 642, A78 (2020).
- [88] M. C. Edwards, Phys. Rev. D 103, 024025 (2021).
- [89] A. Krizhevsky, I. Sutskever, and G. E. Hinton, in Advances in Neural Information Processing Systems (NeurIPS), Vol. 25, edited by F. Pereira, C. J. C. Burges,

L. Bottou, and K. Q. Weinberger (Curran Associates, Inc., Lake Tahoe, NV, USA, 2012).

- [90] K. Simonyan and A. Zisserman, in 3rd International Conference on Learning Representations (ICLR), edited by Y. Bengio and Y. LeCun (Computational and Biological Learning Society, San Diego, CA, USA, 2015) pp. 1–14, arXiv:1409.1556.
- [91] K. He, X. Zhang, S. Ren, and J. Sun, in 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR) (IEEE, Las Vegas, NV, USA, 2016) pp. 770–778.
- [92] K. Cho, B. van Merrienboer, Ç. Gülçehre, D. Bahdanau, F. Bougares, H. Schwenk, and Y. Bengio, in *Proceedings* of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP), edited by A. Moschitti, B. Pang, and W. Daelemans (ACL, Doha, Qatar, 2014) pp. 1724–1734.
- [93] A. van den Oord, S. Dieleman, H. Zen, K. Simonyan, O. Vinyals, A. Graves, N. Kalchbrenner, A. Senior, and K. Kavukcuoglu, in *Proc. 9th ISCA Workshop on Speech Synthesis Workshop (SSW 9)* (ISCA, Sunnyvale, CA, USA, 2016) p. 125, arXiv:1609.03499.
- [94] G. E. Hinton and R. R. Salakhutdinov, Science **313**, 504 (2006).
- [95] D. Ganguli, D. Hernandez, L. Lovitt, A. Askell, Y. Bai, A. Chen, T. Conerly, N. Dassarma, D. Drain, N. Elhage, et al., in 2022 ACM Conference on Fairness, Accountability, and Transparency (ACM, Seoul, Republic of Korea, 2022) pp. 1747–1764.
- [96] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, in Advances in Neural Information Processing Systems (NeurIPS), Vol. 27, edited by Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K. Weinberger (Curran Associates, Inc., Montreal, Canada, 2014).
- [97] C. Bowles, L. Chen, R. Guerrero, P. Bentley, R. N. Gunn, A. Hammers, D. A. Dickie, M. del C. Valdés Hernández, J. M. Wardlaw, and D. Rueckert, "GAN augmentation: Augmenting training data using generative adversarial networks," (2018), arXiv:1810.10863.
- [98] K. Shmelkov, C. Schmid, and K. Alahari, in Proceedings of the European Conference on Computer Vision ((ECCV)) (Springer, Munich, Germany, 2018) pp. 213– 229.
- [99] D. P. Kingma and M. Welling, in 2nd International Conference on Learning Representations (ICLR), edited by Y. Bengio and Y. LeCun (OpenReview.net, Banff, AB, Canada, 2014).
- [100] D. Rezende and S. Mohamed, in *Proceedings of the 32nd International Conference on Machine Learning (ICML)*, Proceedings of Machine Learning Research, Vol. 37, edited by F. Bach and D. Blei (PMLR, Lille, France, 2015) pp. 1530–1538.
- [101] J. Ho, A. Jain, and P. Abbeel, in Advances in Neural Information Processing Systems (NeurIPS), Vol. 33, edited by H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin (Curran Associates, Inc., Vancouver, Canada, 2020) pp. 6840–6851.
- [102] Y. Cao, S. Li, Y. Liu, Z. Yan, Y. Dai, P. S. Yu, and L. Sun, "A Comprehensive Survey of AI-Generated Content (AIGC): A History of Generative AI from GAN to ChatGPT," (2023), arXiv:2303.04226.
- [103] J. Xiang, J. Yang, Y. Deng, and X. Tong, in *Proceedings* of the IEEE/CVF International Conference on Computer Vision (ICCV) (IEEE, Paris, France, 2023) pp. 2195–

2205.

- [104] Y. Gao, Y. Zhou, J. Wang, X. Li, X. Ming, and Y. Lu, in Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (IEEE, Vancouver, Canada, 2023) pp. 5609–5619.
- [105] J. Oppenlaender, in *Proceedings of the 25th International Academic Mindtrek Conference* (ACM, Tampere Finland, 2022) pp. 192–202.
- [106] S. Karnouskos, IEEE Trans. Technol. Soc. 1, 138 (2020).
- [107] R. M. Geraci, Apocalyptic AI: Visions of heaven in robotics, artificial intelligence, and virtual reality (Oxford University Press, Oxford, UK, 2010).
- [108] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, in Advances in Neural Information Processing Systems (NeurIPS), Vol. 30, edited by I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (Curran Associates, Inc., Long Beach, CA, USA, 2017).
- [109] K. M. Choromanski, V. Likhosherstov, D. Dohan, X. Song, A. Gane, T. Sarlos, P. Hawkins, J. Q. Davis, A. Mohiuddin, L. Kaiser, et al., in *International Conference on Learning Representations (ICLR)* (OpenReview.net, Virtual, 2023).
- [110] A. M. P. Brasoveanu and R. Andonie, in 2020 24th International Conference Information Visualisation (IV) (IEEE, Melbourne, Australia, 2020) pp. 270–279.
- [111] S. Garg, D. Tsipras, P. Liang, and G. Valiant, in Advances in Neural Information Processing Systems (NeurIPS), edited by A. H. Oh, A. Agarwal, D. Belgrave, and K. Cho (Curran Associates, Inc., Virtual, 2022).
- [112] T. Dao, "FlashAttention-2: Faster Attention with Better Parallelism and Work Partitioning," (2023), arXiv:2307.08691.
- [113] J. Devlin, M. Chang, K. Lee, and K. Toutanova, in Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, (NAACL-HLT), edited by J. Burstein, C. Doran, and T. Solorio (Association for Computational Linguistics, Minneapolis, MN, USA, 2019) pp. 4171–4186.
- [114] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, and I. Sutskever, "Language models are unsupervised multitask learners," (2019).
- [115] S. Karita, N. Chen, T. Hayashi, T. Hori, H. Inaguma, Z. Jiang, M. Someki, N. E. Y. Soplin, R. Yamamoto, X. Wang, et al., in 2019 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU) (2019) pp. 449–456.
- [116] R. Ramamurthy, P. Ammanabrolu, K. Brantley, J. Hessel, R. Sifa, C. Bauckhage, H. Hajishirzi, and Y. Choi, in *The Eleventh International Conference on Learning Representations (ICLR)* (OpenReview.net, Virtual, 2022).
- M. J. Mataric, in *Machine Learning Proceedings 1994* (Elsevier, New Brunswick, NJ, USA, 1994) pp. 181–189.
- [118] S. Griffith, K. Subramanian, J. Scholz, C. L. Isbell, and A. L. Thomaz, in *Advances in Neural Information Processing Systems (NeurIPS)*, Vol. 26 (Curran Associates, Inc., Lake Tahoe, NV, USA, 2013).
- [119] Y. Gu, Y. Cheng, C. L. P. Chen, and X. Wang, IEEE Trans. Syst., Man, Cybern., Syst. 52, 4600 (2022).
- [120] K. Zhang, Z. Yang, and T. Başar, in *Handbook of Re-inforcement Learning and Control*, Vol. 325, edited by

K. G. Vamvoudakis, Y. Wan, F. L. Lewis, and D. Cansever (Springer International Publishing, Cham, 2021) pp. 321–384.

- [121] F. Christianos, L. Schäfer, and S. Albrecht, in Advances in Neural Information Processing Systems, Vol. 33 (Curran Associates, Inc., Virtual, 2020) pp. 10707–10717.
- [122] T. T. Nguyen, N. D. Nguyen, and S. Nahavandi, IIEEE Trans. Cybern. 50, 3826 (2020).
- [123] C.-M. Chan, W. Chen, Y. Su, J. Yu, W. Xue, S. Zhang, J. Fu, and Z. Liu, "ChatEval: Towards Better LLMbased Evaluators through Multi-Agent Debate," (2023), arXiv:2308.07201.
- [124] Q. Wu, G. Bansal, J. Zhang, Y. Wu, B. Li, E. Zhu, L. Jiang, X. Zhang, S. Zhang, J. Liu, et al., "AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversation," (2023), arXiv:2308.08155.
- [125] Y. Talebirad and A. Nadiri, "Multi-Agent Collaboration: Harnessing the Power of Intelligent LLM Agents," (2023), arXiv:2306.03314.
- [126] F. Pretorius, Phys. Rev. Lett. 95, 121101 (2005).
- [127] M. Shibata and K. Uryū, Phys. Rev. D 61, 064001 (2000), arXiv:gr-qc/9911058.
- [128] J. G. Baker, J. Centrella, D.-I. Choi, M. Koppitz, and J. Van Meter, Phys. Rev. Lett. 96, 111102 (2006).
- [129] M. Campanelli, C. O. Lousto, P. Marronetti, and Y. Zlochower, Phys. Rev. Lett. 96, 111101 (2006).
- [130] E. A. Huerta, C. J. Moore, P. Kumar, D. George, A. J. K. Chua, R. Haas, E. Wessel, D. Johnson, D. Glennon, A. Rebei, et al., Phys. Rev. D 97, 024031 (2018).
- [131] S. Khan, S. Husa, M. Hannam, F. Ohme, M. Pürrer, X. J. Forteza, and A. Bohé, Phys. Rev. D 93, 044007 (2016).
- [132] G. Pratten, C. García-Quirós, M. Colleoni, A. Ramos-Buades, H. Estellés, M. Mateu-Lucena, R. Jaume, M. Haney, D. Keitel, J. E. Thompson, et al., Phys. Rev. D 103, 104056 (2021).
- [133] H. Yu, J. Roulet, T. Venumadhav, B. Zackay, and M. Zaldarriaga, "IMRPhenomXODE: An Accurate and Efficient Waveform Model for Precessing Binary Black Holes," (2023), arXiv:2306.08774.
- [134] W.-B. Han and Z. Cao, Phys. Rev. D 84, 044014 (2011).
- [135] Z. Cao and W.-B. Han, Phys. Rev. D 96, 044028 (2017).
- [136] D. P. Mihaylov, S. Ossokine, A. Buonanno, H. Estelles, L. Pompili, M. Pürrer, and A. Ramos-Buades, "pySEOBNR: A software package for the next generation of effective-one-body multipolar waveform models," (2023), arXiv:2303.18203.
- [137] C. Pankow, K. Chatziioannou, E. A. Chase, T. B. Littenberg, M. Evans, J. McIver, N. J. Cornish, C.-J. Haster, J. Kanner, V. Raymond, et al., Phys. Rev. D 98, 084016 (2018), arXiv:1808.03619.
- [138] S. B. Coughlin, S. Bahaadini, N. Rohani, M. Zevin, O. Patane, M. Harandi, C. Jackson, V. Noroozi, S. Allen, J. Areeda, et al., Phys. Rev. D 99, 082002 (2019), arXiv:1903.04058.
- [139] A. J. Bekker and J. Goldberger, in 2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (IEEE, Shanghai, China, 2016) pp. 2682–2686.
- [140] J. Glanzer, S. Banagiri, S. B. Coughlin, S. Soni, M. Zevin, C. P. L. Berry, O. Patane, S. Bahaadini, N. Rohani, K. Crowston, et al., Class. Quantum Gravity 40, 065004 (2023).
- [141] J. D. Merritt, B. Farr, R. Hur, B. Edelman, and Z. Doc-

tor, Phys. Rev. D 104, 102004 (2021).

- [142] A. H. Nitz, Class. Quantum Gravity 35, 035016 (2018).
- [143] S. Mukherjee, R. Obaid, and B. Matkarimov, J. Phys.: Conf. Ser. 243, 012006 (2010).
- [144] N. Mukund, S. Abraham, S. Kandhasamy, S. Mitra, and N. S. Philip, Phys. Rev. D 95, 104059 (2017), arXiv:1609.07259.
- [145] J. Powell, D. Trifiro, E. Cuoco, I. S. Heng, and M. Cavaglia, Class. Quantum Gravity **32**, 215012 (2015), arXiv:1505.01299.
- [146] J. Powell, A. Torres-Forné, R. Lynch, D. Trifirò, E. Cuoco, M. Cavaglià, I. S. Heng, and J. A. Font, Class. Quantum Gravity 34, 034002 (2017), arXiv:1609.06262.
- [147] J. Powell, L. Sun, K. Gereb, P. D. Lasky, and M. Dollmann, Class. Quantum Gravity 40, 035006 (2023), arXiv:2207.00207.
- [148] S. Bahaadini, V. Noroozi, N. Rohani, S. Coughlin, M. Zevin, J. Smith, V. Kalogera, and A. Katsaggelos, Inform. Sci. 444, 172 (2018).
- [149] S. Soni, C. P. L. Berry, S. B. Coughlin, M. Harandi, C. B. Jackson, K. Crowston, C. Østerlund, O. Patane, A. K. Katsaggelos, L. Trouille, et al., Class. Quantum Gravity 38, 195016 (2021).
- [150] Y. Sakai, Y. Itoh, P. Jung, K. Kokeyama, C. Kozakai, K. T. Nakahira, S. Oshino, Y. Shikano, H. Takahashi, T. Uchiyama, et al., Sci. Rep. **12**, 9935 (2022), arXiv:2111.10053.
- [151] T. S. Fernandes, S. J. Vieira, A. Onofre, J. C. Bustillo, A. Torres-Forné, and J. A. Font, "Convolutional Neural Networks for the classification of glitches in gravitationalwave data streams," (2023), arXiv:2303.13917.
- [152] D. George, H. Shen, and E. A. Huerta, Phys. Rev. D 97, 101501 (2018).
- [153] G. Vajente, Y. Huang, M. Isi, J. C. Driggers, J. S. Kissel, M. J. Szczepanczyk, and S. Vitale, Phys. Rev. D 101, 042003 (2020), arXiv:1911.09083.
- [154] M. Razzano, F. Di Renzo, F. Fidecaro, G. Hemming, and S. Katsanevas, Nucl. Instrum. Methods Phys. Res. A: Accel. Spectrom. Detect. Assoc. Equip. **1048**, 167959 (2023), arXiv:2301.05112.
- [155] A. Torres, A. Marquina, J. A. Font, and J. M. Ibáñez, Phys. Rev. D 90, 084029 (2014).
- [156] N. J. Cornish, T. B. Littenberg, B. Bécsy, K. Chatziioannou, J. A. Clark, S. Ghonge, and M. Millhouse, Phys. Rev. D 103, 044006 (2021).
- [157] S. Klimenko, I. Yakushin, A. Mercer, and G. Mitselmakher, Class. Quantum Gravity 25, 114029 (2008), arXiv:0802.3232.
- [158] A. Akhshi, H. Alimohammadi, S. Baghram, S. Rahvar, M. R. R. Tabar, and H. Arfaei, Sci. Rep. 11, 20507 (2021).
- [159] A. Torres-Forné, A. Marquina, J. A. Font, and J. M. Ibáñez, Phys. Rev. D 94, 124040 (2016), arXiv:1612.01305.
- [160] W. Wei and E. A. Huerta, Phys. Lett. B 800, 135081 (2020), arXiv:1901.00869.
- [161] H. Shen, D. George, E. A. Huerta, and Z. Zhao, in 2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (IEEE, Brighton, UK, 2019) pp. 3237–3241, arXiv:1711.09919.
- [162] C. Chatterjee, L. Wen, F. Diakogiannis, and K. Vinsen, Phys. Rev. D: Part. Fields 104, 064046 (2021).
- [163] H. Xia, L. Shao, J. Zhao, and Z. Cao, Phys. Rev. D 103, 024040 (2021).

- [164] P. G. Krastev, Phys. Lett. B 803, 135330 (2020).
- [165] W. Wei, A. Khan, E. Huerta, X. Huang, and M. Tian, Phys. Lett. B 812, 136029 (2021).
- [166] V. Skliris, M. R. K. Norman, and P. J. Sutton, "Real-Time Detection of Unmodelled Gravitational-Wave Transients Using Convolutional Neural Networks," (2021), arXiv:2009.14611.
- [167] V. Skliris, Machine Learning to Extract Gravitational Wave Transients, Ph.D. thesis, Cardiff University, Cardiff, UK (2021).
- [168] L. Speri, N. Karnesis, A. I. Renzini, and J. R. Gair, Nat Astron 6, 1356 (2022).
- [169] W. Alhassan, T. Bulik, and M. Suchenek, Mon. Not. R. Astron. Soc. 519, 3843 (2023), arXiv:2211.13789.
- [170] Y. Zhang, H. Xu, M. Liu, C. Liu, Y. Zhao, and J. Zhu, Phys. Rev. D 106, 122002 (2022).
- [171] M. Tian, E. A. Huerta, and H. Zheng, "Physics-inspired spatiotemporal-graph AI ensemble for gravitational wave detection," (2023), arXiv:2306.15728.
- [172] M. B. Schäfer and A. H. Nitz, Phys. Rev. D 105, 043003 (2022).
- [173] Z. Pan and H. Yang, Phys. Rev. D 103, 103018 (2021), arXiv:2101.09146.
- [174] S. Babak, J. Gair, A. Sesana, E. Barausse, C. F. Sopuerta, C. P. L. Berry, E. Berti, P. Amaro-Seoane, A. Petiteau, and A. Klein, Phys. Rev. D 95, 103012 (2017), arXiv:1703.09722.
- [175] J. R. Gair, S. Babak, A. Sesana, P. Amaro-Seoane, E. Barausse, C. P. L. Berry, E. Berti, and C. Sopuerta, J. Phys.: Conf. Ser. 840, 012021 (2017), arXiv:1704.00009.
- [176] P. Amaro-Seoane, H. Audley, S. Babak, J. Baker, E. Barausse, P. Bender, E. Berti, P. Binetruy, M. Born, D. Bortoluzzi, et al., "Laser Interferometer Space Antenna," (2017), arXiv:1702.00786.
- [177] W.-R. Hu and Y.-L. Wu, Natl. Sci. Rev. 4, 685 (2017).
- [178] Z. Ren, T. Zhao, Z. Cao, Z.-K. Guo, W.-B. Han, H.-B. Jin, and Y.-L. Wu, Front. Phys. 18, 64302 (2023).
- [179] J. Luo, L.-S. Chen, H.-Z. Duan, Y.-G. Gong, S. Hu, J. Ji, Q. Liu, J. Mei, V. Milyukov, M. Sazhin, et al., Class. Quantum Gravity **33**, 035010 (2016), arXiv:1512.02076.
- [180] C. Dreißigacker, Searches for Continuous Gravitational Waves : Sensitivity Estimation and Deep Learning as a Novel Search Method, Ph.D. thesis, Leibniz Universität Hannover, Hannover, Germany (2020).
- [181] J. Bayley, C. Messenger, and G. Woan, Phys. Rev. D 102, 083024 (2020).
- [182] T. S. Yamamoto and T. Tanaka, Phys. Rev. D 103, 084049 (2021).
- [183] N. Christensen and R. Meyer, Phys. Rev. D 58, 082001 (1998).
- [184] J. S. Speagle, "A Conceptual Introduction to Markov Chain Monte Carlo Methods," (2020), arXiv:1909.12313.
- [185] J. Lee, W. Sung, and J.-H. Choi, Energies 8, 5538 (2015).
- [186] S. Sasaoka, Y. Hou, K. Somiya, and H. Takahashi, Phys. Rev. D 105, 103030 (2022).
- [187] S. R. Green, C. Simpson, and J. Gair, Phys. Rev. D 102, 104057 (2020), arXiv:2002.07656.
- [188] H. Shen, E. A. Huerta, E. O'Shea, P. Kumar, and Z. Zhao, Mach. Learn.: Sci. Technol. 3, 015007 (2022).
- [189] S. R. Green and J. Gair, Mach. Learn.: Sci. Technol. 2, 03LT01 (2021).
- [190] J. Wildberger, M. Dax, S. R. Green, J. Gair, M. Pürrer, J. H. Macke, A. Buonanno, and B. Schölkopf, Phys. Rev. D 107, 084046 (2023).

- [191] M. J. Williams, J. Veitch, and C. Messenger, Mach. Learn.: Sci. Technol. 4, 035011 (2023).
- [192] M. J. Williams, J. Veitch, and C. Messenger, Phys. Rev. D 103, 103006 (2021).
- [193] U. Bhardwaj, J. Alvey, B. K. Miller, S. Nissanke, and C. Weniger, "Peregrine: Sequential simulationbased inference for gravitational wave signals," (2023), arXiv:2304.02035.
- [194] K. W. K. Wong, G. Franciolini, V. De Luca, V. Baibhav, E. Berti, P. Pani, and A. Riotto, Phys. Rev. D 103, 023026 (2021).
- [195] K. W. K. Wong and M. Cranmer, in *International Con*ference on Machine Learning (ICML) (PMLR, Baltimore, MD, USA, 2022).
- [196] K. W. K. Wong, M. Isi, and T. D. P. Edwards, "Fast gravitational wave parameter estimation without compromises," (2023), arXiv:2302.05333.
- [197] H. Gabbard, C. Messenger, I. S. Heng, F. Tonolini, and R. Murray-Smith, Nat. Phys. 18, 112 (2022), arXiv:1909.06296.
- [198] M. Liu, X.-D. Li, and A. J. K. Chua, "Improving the scalability of Gaussian-process error marginalization in gravitational-wave inference," (2023), arXiv:2307.07233.
- [199] J. Langendorff, A. Kolmus, J. Janquart, and C. Van Den Broeck, Phys. Rev. Lett. 130, 171402 (2023).
- [200] P. Bull, Y. Akrami, J. Adamek, T. Baker, E. Bellini, J. Beltrán Jiménez, E. Bentivegna, S. Camera, S. Clesse, J. H. Davis, et al., Phys. Dark Universe **12**, 56 (2016), arXiv:1512.05356.
- [201] L. Bian, R.-G. Cai, S. Cao, Z. Cao, H. Gao, Z.-K. Guo, K. Lee, D. Li, J. Liu, Y. Lu, et al., Sci. China Phys. Mech. Astron. 64, 120401 (2021), arXiv:2106.10235.
- [202] K. G. Arun, E. Belgacem, R. Benkel, L. Bernard, E. Berti, G. Bertone, M. Besancon, D. Blas, C. G. Böhmer, R. Brito, et al., Living Rev. Relativ. 25, 4 (2022).
- [203] M. Bailes, B. K. Berger, P. R. Brady, M. Branchesi, K. Danzmann, M. Evans, K. Holley-Bockelmann, B. R. Iyer, T. Kajita, S. Katsanevas, et al., Nat Rev Phys 3, 344 (2021).
- [204] E. Barausse and A. Lapi, in *Handbook of Gravitational Wave Astronomy*, edited by C. Bambi, S. Katsanevas, and K. D. Kokkotas (Springer Singapore, Singapore, 2020) pp. 1–33.
- [205] M. Maggiore, C. V. D. Broeck, N. Bartolo, E. Belgacem, D. Bertacca, M. A. Bizouard, M. Branchesi, S. Clesse, S. Foffa, J. García-Bellido, et al., J. Cosmol. Astropart. Phys. **2020**, 050 (2020).
- [206] E. Di Valentino, Mon. Not. R. Astron. Soc. 502, 2065 (2021), arXiv:2011.00246.
- [207] B. P. Abbott, R. Abbott, T. D. Abbott, F. Acernese, K. Ackley, C. Adams, T. Adams, P. Addesso, R. X. Adhikari, V. B. Adya, et al., Phys. Rev. Lett. **119**, 161101 (2017).
- [208] B. P. Abbott, R. Abbott, T. D. Abbott, S. Abraham, F. Acernese, K. Ackley, C. Adams, R. X. Adhikari, V. B. Adya, C. Affeldt, et al., Astrophys. J. Lett. 892, L3 (2020).
- [209] S. Soma, L. Wang, S. Shi, H. Stöcker, and K. Zhou, Phys. Rev. D 107, 083028 (2023).
- [210] A. Saiz-Pérez, A. Torres-Forné, and J. A. Font, Mon. Not. R. Astron. Soc. 512, 3815 (2022).
- [211] M. L. Portilla, I. Di Palma, M. Drago, P. Cerda-

Duran, and F. Ricci, Phys. Rev. D **103**, 063011 (2021), arXiv:2011.13733.

- [212] R. Qiu, P. Krastev, K. Gill, and E. Berger, Phys. Lett. B, 137850 (2023), arXiv:2210.15888.
- [213] Y. Nie, N. H. Nguyen, P. Sinthong, and J. Kalagnanam, in *The Eleventh International Conference on Learn*ing Representations (ICLR) (OpenReview.net, Virtual, 2022).
- [214] B. P. Abbott, R. Abbott, T. D. Abbott, S. Abraham, F. Acernese, K. Ackley, C. Adams, R. X. Adhikari, V. B. Adya, C. Affeldt, et al., Astrophys. J. 875, 161 (2019).
- [215] M. L. Katz, A. J. K. Chua, L. Speri, N. Warburton, and S. A. Hughes, Phys. Rev. D 104, 064047 (2021), arXiv:2104.04582.
- [216] J. Durbin and S. J. Koopman, *Time Series Analysis by State Space Methods*, 2nd ed., Oxford Statistical Science Series No. 38 (Oxford University Press, Oxford, UK, 2012).
- [217] A. Gu, K. Goel, and C. Re, in *International Conference on Learning Representations (ICLR)* (OpenReview.net, 2022).
- [218] W.-C. Lin, C.-F. Tsai, and J. R. Zhong, Knowl.-Based Syst. 239, 108079 (2022).
- [219] L. Diener, S. Sootla, S. Branets, A. Saabas, R. Aichner, and R. Cutler, "INTERSPEECH 2022 Audio Deep Packet Loss Concealment Challenge," (2022), arXiv:2204.05222.
- [220] Q. Baghi and N. Korsakova, LISA Data Challenge: Spritz, Tech. Rep. (ESA, 2022).
- [221] Q. Baghi, J. I. Thorpe, J. Slutsky, J. Baker, T. D. Canton, N. Korsakova, and N. Karnesis, Phys. Rev. D 100, 022003 (2019).
- [222] J. Blackman, B. Szilagyi, C. R. Galley, and M. Tiglio, Phys. Rev. Lett. **113**, 021101 (2014), arXiv:1401.7038.
- [223] A. Blelly, J. Bobin, and H. Moutarde, Phys. Rev. D 102, 104053 (2020), arXiv:2005.03696.
- [224] A. Blelly, J. Bobin, and H. Moutarde, Mon. Not. R. Astron. Soc. 509, 5902 (2021), arXiv:2104.05250.
- [225] T. Emmanuel, T. Maupong, D. Mpoeleng, T. Semong, B. Mphago, and O. Tabona, J. Big Data 8, 140 (2021).
- [226] N. Li, X. Zheng, C. Zhang, L. Guo, and B. Yu, in *Interspeech 2022* (ISCA, Brno, Czech Republic, 2022) pp. 585–589.
- [227] G. Rani, M. G. Oza, V. S. Dhaka, N. Pradhan, S. Verma, and J. J. P. C. Rodrigues, Multimed. Syst. 28, 1251 (2022).
- [228] X. Pei, K. Zuo, Y. Li, and Z. Pang, Int. J. Comput. Intell. Syst. 16, 44 (2023).
- [229] E. Korot, Z. Guan, D. Ferraz, S. K. Wagner, G. Zhang, X. Liu, L. Faes, N. Pontikos, S. G. Finlayson, H. Khalid, et al., Nat. Mach. Intell. 3, 288 (2021).
- [230] S. Zhao, M. Gong, H. Fu, and D. Tao, IEEE Trans. Image Process. 30, 5264 (2021).
- [231] P. Mészáros, D. B. Fox, C. Hanna, and K. Murase, Nat. Rev. Phys. 1, 585 (2019).
- [232] B. P. Abbott, R. Abbott, T. D. Abbott, F. Acernese, K. Ackley, C. Adams, T. Adams, P. Addesso, R. X. Adhikari, V. B. Adya, et al., Astrophys. J. 848, L12 (2017).
- [233] Z. C. Lipton, Queue 16, 31 (2018).
- [234] F. Doshi-Velez and B. Kim, "Towards A Rigorous Science of Interpretable Machine Learning," (2017), arXiv:1702.08608.