# Learning a convex cost-to-go for single step model predictive control

Evren M. Turan<sup>1</sup>, Zawadi Mdoe<sup>1</sup> and Johannes Jäschke<sup>1</sup>

Abstract-For large systems that consider uncertainty the online solution of model predictive control problems can be computationally taxing, and even infeasible. This can be offset by using a shorter horizon, however this can in turn result in poor controller performance. In this work we consider the task of learning convex objective terms to allow the use of a short, potentially single step, control horizon to reduce the online computational cost. We consider two surrogates: (1) a convex interpolating function and (2) an input-convex neural network. We highlight that irrespective of the choice of surrogate the behaviour of the surrogate near the origin and ability of the surrogate to describe the feasible region are key concerns for the closed loop performance of the new MPC problem. We address these concerns by tailoring the design of the surrogate to ensure good performance in both aspects. The paper concludes with a numerical example, showing the clear and significant reduction in computational complexity through the use of these convex surrogates.

#### I. INTRODUCTION

Model predictive control (MPC) is an optimisation-based control method, in which a control action that minimises some objective while satisfying constraints is found by use of a model that predicts the (short-term) response of a system given the current state. To find the control action an optimisation problem has to be solved, which can be computationally infeasible for large problems or fast systems, especially when considering a robust MPC formulation. The computational burden can be reduced by considering a shorter horizon (by reducing the problem size), however this can often excessively deteriorate the controller performance. In this work, we aim to reduce the computational burden of (robust) MPC by learning a convex control objective that allows the use of a prediction and control horizon of one.

Various approaches have been considered to reduce the online computational delay of MPC. One approach is to compute the explicit feedback control law that is implicitly defined by the MPC problem. For a standard linear MPC problem this can be done by solving a multi-parametric programming problem [1]. This method is limited to relatively small-scale problems as the online computational requirements grows exponentially with the problem size. One can instead consider finding a "compact" parameterisation of the control policy by a neural network, trained in either an imitation learning [2] or optimize-and-learn framework [3]. However, these policies are difficult to adjust online.

An alternative approach is to consider solving a smaller problem online. However, a smaller problem does not necessarily yield an effective control policy – a naive implementation of an MPC problem with a horizon of 1 will often give bad results. However, if one uses a problem with a short horizon, with an appropriately designed cost-to-go then there would be no corresponding loss in performance when using the shorter horizon. We consider the problem of learning (offline) a convex surrogate of the cost-to-go of a linear, robust MPC problem with the primary aim of reducing the online computational cost of the MPC problem.

This is related to approaches in inverse optimal control and approximate dynamic programming. In inverse optimal control a data-set of state-input pairs from a controller or an expert is fitted to a simple MPC controller by learning a value function, such that the simple MPC controller is approximately optimal [4]. In approximate dynamic programming, the value function is approximated (commonly iteratively) based on some metric, e.g. [5] solved a semidefinite problem offline to find a convex quadratic value function to approximate the cost-to-go.

In this work, we approximate the cost-to-go by a convex surrogate. By choosing a convex surrogate we can use it in a convex MPC scheme and still maintain convexity, leading to low computational effort [6] and avoiding the standard difficulties of optimising over neural networks. Furthermore, the restriction of the surrogate to be convex can be regarded as a form of regularisation thus avoiding the difficulty of tuning the training problem to avoid overfittings. In particular, we focus on two convex surrogates: (1) an interpolating convex function given as the solution of a convex function, and (2) an input-convex neural network, which is a network that is non-convex to train, but convex to optimise over. In contrast to learning a control policy, this approach is more flexible as changes to problem data can be incorporated by partially lengthening the control horizon and updating the optimisation problem with the new data.

This approach is related to [7], [8]. In the former, a quadratic cost function is parameterised by a neural network such that the approximation error of the parametric quadratic objective and the cost-to-go is minimised. In the latter the parameters of a convex MPC problem are adjusted such that the performance metric of the policy implicitly defined by the convex MPC problem is maximised.

The paper is organised as follows: Section II briefly states the problem formulation, Section III introduces the two choices of convex surrogates (interpolating convex functions and input-convex neural networks), Section IV details how the cost-to-go is approximated, Section V numerically demonstrates the proposed approach and Section VI concludes the paper.

<sup>&</sup>lt;sup>1</sup>Department of Chemical Engineering, Norwegian University of Science and Technology (NTNU), Høgskoleringen 1, Trondheim, 7034, Norway evren.m.turan@ntnu.no, zawadi.n.mdoe@ntnu.no, johannes.jaschke@ntnu.no

## II. PROBLEM FORMULATION

Consider the convex MPC problem:

$$\mathcal{V}_{N}(\hat{x}) = \min_{u,x} \sum_{k=0}^{N-1} l_{k}(x_{k}, u_{k}) + V_{t}(x_{N})$$
(1a)

$$x_{k+1} = Ax_k + Bu_k, \qquad k = 0, \dots, N-1$$
 (1b)

$$u_k \in \mathcal{U}_k, \qquad k = 0, \dots, N-1$$
 (1c)

$$x_0 = \hat{x}, x_k \in \mathcal{X}_k, \qquad k = 1, \dots, N$$
 (1d)

where N is the horizon,  $x_k \in \mathcal{X}_k \subseteq \mathbb{R}^{n_x}$  are the states,  $u_k \in \mathcal{U}_k \subseteq \mathbb{R}^{n_u}$  are the control inputs,  $\hat{x} \in \mathbb{R}^{n_x}$  is the initial condition, and estimate of the current state of the process, k indexes the discrete time model,  $l_k$  is a convex stage cost,  $V_t$ is a convex terminal cost,  $\mathcal{V}_N$  is the optimal value function with horizon N, and  $\mathcal{U}_k \subset \mathbb{R}^{n_u}$  and  $\mathcal{X}_k \subset \mathbb{R}^{n_x}$  are convex constraint sets, typically defined by linear inequalities.

As (1) is a convex problem that depends on  $\hat{x}$ ,  $\mathcal{V}_N$  is a convex function of  $\hat{x}$ . Typically  $l_k$  and  $V_t$  are strictly convex quadratic functions:

$$l(x_k, u_k) = x_k^T Q x_k + u_k^T R u_k$$
(2a)

$$V_t(x_N) = x_N Q_f x_N \tag{2b}$$

where Q, R and  $Q_f$  are symmetric positive definite matrices.

Often  $V_t$  is chosen as the value function of the unconstrained infinite horizon control problem corresponding to (1), i.e. the linear quadratic regulator (LQR). If  $l_k$  and  $V_t$  are strictly convex quadratic functions then  $\mathcal{V}_N$  is a strictly convex piecewise quadratic function.

## A. Multistage MPC

Problem (1) is a *nominal* MPC problem as it assumes that the system is perfectly described by (1b). Realistically this is not the case due to uncertainty. This uncertainty can either be ignored (in which case we solve the nominal problem, (1)) or can be incorporated in some robust or probabilistic framework. Here we focus on the multistage MPC framework [9], although the main results can be applied to other formulations that maintain the convexity of the problem.

In a multistage MPC problem, we consider a similar system to (1) but explicitly consider the uncertainty by including predictions corresponding to  $S \in \mathbb{Z}_{++}$  different scenarios in which the process dynamics are different:

$$\mathcal{V}_N^{MS}(\hat{x}) = \min_{u,x} \sum_{s=1}^{S} w_s \mathcal{V}_{N,s}(\hat{x})$$
(3a)

$$\mathcal{V}_{N,s}(\hat{x}) = \left(\sum_{k=0}^{N-1} l_k(x_{k,s}, u_{k,s}) + V_t(x_{N,s})\right) \forall s \in S \quad (3b)$$

$$x_{k+1,s} = A_{k,s} x_{k,s} + B_{k,s} u_{k,s} + d_{k,s},$$
  

$$k = 0, \dots, N-1, \ \forall s \in S$$
(3c)

$$u_{k,s} \in \mathcal{U}_k, \qquad k = 0, \dots, N-1 \ \forall s \in S$$
 (3d)

$$x_{0,s} = \hat{x}, \ x_{k,s} \in \mathcal{X}_k, \qquad k = 1, \dots, N \ \forall s \in S$$
 (3e)

$$x_{k,s_1} = x_{k,s_2} \Rightarrow u_{k,s_1} = u_{k,s_2}, \ \forall s_1, s_2 \in S$$
 (3f)

where s indexes the different scenarios, and the objectives of the different scenarios are weighted by  $w_s > 0$  with  $\sum_s w_s = 1$ .  $A_{k,s}$ ,  $B_{k,s}$ , and  $d_{k,s}$  are realisation of the stochastic or uncertain parameters which are typically decided upon offline. Constraint (3f) is a non-anticipativity constraint that enforces the control action of two scenarios to be equal at a time point if the states of two scenarios are equal at the same time point.

The uncertainty realisations can be represented by a scenario tree, with branching representing a potential change in the uncertainty realisation. A tree is called fully-branched if branching occurs until the end of the prediction horizon, i.e. all possible system evolutions for a finite number of parameter realizations are considered. The size of the fully-branched scenario tree, and consequently the multistage MPC problem, grows exponentially with the horizon length and number of parameter values. Therefore, it is often computationally infeasible to solve a fully-branched multistage MPC problem with a long horizon.

## B. Only a step-ahead

Using Bellman's principle of optimality problems (1) and (3) may be reformulated as the single horizon problem. As (1) is a special case of (3) we only show the reformulation of (3):

$$\mathcal{V}_{N}^{MS}(\hat{x}) = \min_{u,x} \ l_{0}(\hat{x}, u_{0}) + \sum_{s=1}^{S} w_{s}(\mathcal{V}_{N-1}^{MS}(x_{1,s}))$$
(4a)

$$x_{1,s} = A_{0,s}\hat{x} + B_{0,s}u_0 + d_{0,s}$$
(4b)

$$u_0 \in \mathcal{U}_0, \ x_{1,s} \in \mathcal{X}_1 \tag{4c}$$

Only a single step prediction into the future is used, however the section of the trajectory that is left out is captured by the embedded value function,  $\mathcal{V}_{N-1}^{MS}$ , which is called the cost-to-go. Due to the structure of the problem, every MPC problem has an implicit cost-to-go  $\mathcal{V}_{N-1}^{ctg}$ . Due to considering considerably fewer variables than a problem with large N, the computational cost of solving a nominal MPC problem online could be greatly reduced if  $\mathcal{V}_{N-1}^{ctg}$ were known. This benefit is compounded when considering a multistage problem, as using a control horizon of 1 means that the problem size grows *linearly* and not exponentially with the number of cases, S.

## **III. APPROXIMATING CONVEX FUNCTIONS**

We consider the task of fitting a convex surrogate to data and focus on the application of this to the MPC setting in the following section. We restrict our attention to *convex* surrogates for  $\mathcal{V}_{N-1}^{MS}$  as these are easy to optimise over once trained. We consider two formulations for fitting a convex fto m data points using a least squares objective.

## A. Convex optimisation of a convex interpolating function

As f is convex, and the data is from a convex function, then all optimal f perfectly interpolates the data, i.e.

$$y_i - f(x_i) = 0, \qquad i = 1, \dots, m$$
 (5)

and from the definition of convexity there exists  $g_1, \ldots, g_m \in \mathbb{R}^{n_x}$  such that:

$$f(x_j) \ge f(x_i) + g_i^T(x_j - x_i), \qquad i, j = 1, \dots, m$$
 (6)

where the vector  $g_i$  is the subgradient of f at  $x_i$ . Thus, the original infinite-dimensional problem can be stated as the convex finite-dimensional quadratic program [6]:

$$\min_{\hat{y}_i, g_i} \sum_{i=1}^m (y_i - \hat{y}_i)^2$$
(7a)

s.t. 
$$\hat{y}_j \ge \hat{y}_i + g_i^T (x_j - x_i), \quad i, j = 1, \dots, m$$
 (7b)

where  $\hat{y}_i$  and  $g_i$  are the prediction and sub-gradient of f at  $x_i$ . Once solved one can use the optimal values to construct arbitrary convex functions that interpolate the data e.g. the piecewise affine function:

$$f_{PWA} = \max_{i=1,\dots,m} (\hat{y}_i + g_i^T (x - x_i))$$
(8)

However, as  $\hat{y} \in \mathbb{R}^m$  and each  $g_i \in \mathbb{R}^{n_x}$ , solving (8) involves  $m(n_x+1)$  variables leading to the problem rapidly becoming computationally intractable.

## B. Input-convex neural networks

It is practically reasonable to consider finding an approximate surrogate instead of an exact interpolating function. As such we consider training input-convex neural networks (ICNN) [10], [11]. Neural networks offer a offer relatively memory-efficient representations of the data, and hence avoid the memory issue of the previous formulation.

For ease of exposition, we consider a M-layer, fully connected ICNN. This network,  $f_{NN}$  is defined as:

$$z_{i+1} = \alpha_i (W_i^{(z)} z_i + W_i^{(x)} x_i + b_i),$$
  

$$i = 0, \dots, M - 1$$
(9a)

$$f_{NN}(x,\theta) = z_M \tag{9b}$$

$$0 \le W_i^{(z)}, \qquad i = 1, \dots, M - 1$$
 (9c)

$$\alpha_i$$
 convex and non-decreasing,  $i = 0, \dots, M - 1$  (9d)

where  $z_i$  are the activations of layer *i*,  $\alpha_i$  is that layer's activation function, and  $\theta_i = \{W_{0:M-1}^{(z)}, W_{0:M-1}^{(x)}, b_{0:M-1}\}$  are the parameters. Note that  $z_0 \equiv 0, W_0^{(z)} \equiv 0$ , and the final activation function,  $\alpha_{M-1}$  is often chosen as the identity.

A sufficient condition for the convexity of  $f_{NN}$  with respect to x is that the elements of  $W_{1:M-1}^{(z)}$  are non-negative, and  $\alpha_{0:M-1}$  are convex and non-decreasing [10]. This is because: (1) the composition of a convex and convex nondecreasing function is convex, and (2) non-negative weighted sums of convex functions preserve convexity [6].

Lastly, we note that if one considers M = 2,  $\alpha_1(y) = y$ ,  $W_1^{(z)} = I$ ,  $\alpha_2(y) = \max\{y_i, \ldots, y_{n_z}\}$ , where  $n_z$  is the hidden layer width, (i.e. a max-out layer) then the ICNN describes an alternative parameterisation of any convex piecewise-affine (PWA) function defined by (8).



Fig. 1: Illustration that a "good" convex approximator (red line) of  $\mathcal{V}_N$  (black line) can be a poor choice of function to minimize due to non-unique minimizers.

#### IV. LEARNING THE COST-TO-GO

As we wish to embed our surrogate in a control problem this leads to atypical considerations. In this section we describe design concerns of the convex surrogate for use in the MPC problem, and the problem of learning feasibility.

## A. Design of cost-to-go approximation

To simplify the notation in this section we use  $\mathcal{V}(x)$  instead of  $\mathcal{V}_{N-1}(x)$ . One may suppose that any convex approximation,  $\hat{\mathcal{V}}(x)$  of the cost-to-go, is good enough, provided the error  $\hat{\mathcal{V}}(x) - \mathcal{V}(x)$  is made small. However, we wish that using  $\hat{\mathcal{V}}(x)$  in (4) yields control actions similar to solving the full-horizon problem.

Often  $\mathcal{V}(x)$  is strictly convex , e.g. if  $l_k$  and  $V_t$  chosen as in (2). However,  $\hat{\mathcal{V}}(x)$  may not be strictly convex resulting in the minimiser of (4) not being unique. Indeed, if the training objective is the squared error then this is not unlikely. This (unwanted) behaviour is typified by Fig. 1 where a convex approximator approximates the region around the minimum by a line. If (4) has a non-unique minimum, then this implies that the controller using this approximation will show poor performance close to the origin.

Neither of the convex surrogates described previously meets the sufficient condition for being strictly convex. However, as the sum of a convex function and a strictly convex function is strictly convex, and most often the stage and terminal cost are quadratic functions we consider the surrogate:

$$\hat{\mathcal{V}}(x) = \hat{\mathcal{V}}_{fit}(x) + x^T P x \tag{10}$$

where  $\hat{\mathcal{V}}$  is the surrogate used in (4),  $\hat{\mathcal{V}}_{fit}(x,\theta)$  is the fitted surrogate, i.e. either (8) or (9), and  $P \succ 0$ . A potential approach is to simultaneously optimise  $\theta$  and the entries of *P*. However, it seems more practical to simply choose *P* and then optimise for  $\hat{\mathcal{V}}_{fit}$ .

To do this, one should ensure that  $x^T P x$  is a lower bound of  $\mathcal{V}_N^{MS}$ , as otherwise  $\hat{\mathcal{V}}_{fit}$  would need be non-convex for  $\hat{\mathcal{V}}$  to be close approximation of  $\mathcal{V}_N^{MS}$ . If the stage cost is defined as in (2) then one can simply select P = Q. However, a more powerful idea is to pick P based on the cost-to-go of an associated multistage linear quadratic regulator (LQR) problem with the same robust horizon.

Theorem 1: Let  $\mathbb{P}_N^{MS}$  denote a feasible N stage convex, linear multistage MPC problem (3), where the stage and terminal costs are convex and quadratic (2). Let the

optimal value function of  $\mathbb{P}_N^{MS}$  be  $\mathcal{V}_N^{MS}(x)$ . Similarly let  $\mathbb{P}_{LQR}^{MS}$  denote the multistage, infinite horizon, LQR problem corresponding to  $\mathbb{P}_N^{MS}$ , with  $d_{k,s} = 0$  and the same robust horizon as  $\mathbb{P}_N^{MS}$ . Let the optimal value function of  $\mathbb{P}_{LQR}^{MS}$  be  $\mathcal{V}_{LQR}^{MS}(x)$  and finite. Note that  $\mathcal{V}_{LQR}^{MS}(x)$  is given by:

$$\mathcal{V}_{LQR}^{MS}(x) = x^T P_{LQR}^{MS} x$$

where  $P_{LQR}^{MS}$  is the weighting matrix defined by the corresponding Riccati equation.

Let the terminal cost of the  $\mathbb{P}_N^{MS}$  be chosen such that

$$x^{T}Q_{f}x \geq \mathcal{V}_{LQR}^{MS}(x) \qquad \forall x$$
  
*i.e.*  $Q_{f} - P_{LQR}^{MS} \succcurlyeq 0$ 

and let  $d_{s,k}$  be chosen such that  $\sum_{s}^{S} w_s d_{s,k} = 0$ . Then  $\mathcal{V}_{LQR}^{MS}(x)$  is an under-estimator of  $\mathcal{V}_{N}^{MS}(x)$ . *Proof:* Consider  $\mathbb{P}_{N}^{MS}$  with  $A_{k,s} = A$ ,  $B_{k,s} = B$ , i.e. the uncertainty is only due to the additive disturbance. The value function,  $\mathcal{V}_N^{MS}(x)$ , can be explicitly written as a function of the scenario value function and disturbance:

$$\mathcal{V}_N^{MS}(x) = \sum_{s=1}^S w_s \mathcal{V}_{N,s}(\hat{x}) = \sum_{s=1}^S w_s \mathcal{V}_N(\hat{x}, d_s)$$

where  $d_s$  is a vector with elements  $d_{k,s}$ . As the value function is convex in  $d_s$ , by (the generalised) Jensen's inequality [6]:

$$\mathcal{V}_N(\hat{x}, 0) = \mathcal{V}_N\left(\hat{x}, \sum_{s=1}^S w_s d_s\right) \le \sum_{s=1}^S w_s \mathcal{V}_N(\hat{x}, d_s)$$

where by assumption  $\sum_{s}^{S} w_{s} d_{s,k} = 0$ . Thus, for an arbitrary  $\mathbb{P}_{N}^{MS}$ , we can find a lower bound of  $\mathcal{V}_N^{MS}(x)$  by considering the value function of the multistage problem the same scenario tree, but with  $d_{s,k} = 0$  for all k

and s.  $\bar{\mathcal{V}}_N^{MS}(x) = \mathcal{V}_N(\hat{x}, 0)$ . If  $Q_f = P_{LQR}^{MS}$  then  $\mathcal{V}_{LQR}^{MS}(x)$  is an under-estimator of  $\bar{\mathcal{V}}_N^{MS}(x)$ , and hence  $\mathcal{V}_N^{MS}(x)$ . This is because  $\mathbb{P}_{LQR}^{MS}$  is a relaxation of  $\bar{\mathbb{P}}_N^{MS}$  as it has the same objective and dynamics, without state or input constraints. For any other feasible choice of  $Q_f$ , by assumption  $x^T Q_f x > x^T P_{LOR}^{MS} x$  and hence  $\mathcal{V}_{LOR}^{MS}(x)$  remains an under-estimator.

Thus, by considering the associated LQR problem, P can be found for use in (10) that is a lower bound of  $\mathcal{V}_{N}^{MS}$ . Moreover, under additional assumptions of the origin this choice exactly describes the curvature around the origin.

Theorem 2: Let  $\mathbb{P}_N^{MS}$ ,  $\mathcal{V}_N^{MS}(x)$ ,  $\mathcal{V}_N(x, d_s)$ ,  $\overline{\mathcal{V}}_N^{MS}(x)$ ,  $\mathcal{V}_{LQR}^{MS}(x)$  be defined as in (1). Let the origin solution of  $\mathbb{P}_{N}^{\overline{MS}}$  have no active inequality constraints. Then in a region around origin

$$\mathcal{V}_N^{MS}(x) = \mathcal{V}_{LQR}^{MS}(x) + C$$

where  $C \ge 0$  is some constant.

*Proof:* Consider a set,  $\mathcal{N}$ , on which the optimal solution of  $\mathbb{P}_N^{MS}$  has no active inequality constraints. By assumption the origin is part of this set. Furthermore, as the dynamics and constraints are Lipschitz continuous, this set is not a singleton and contains some neighbourhood of the origin.

Consider some point  $\delta \in \mathcal{N}$ . As  $\mathbb{P}_N^{MS}$  has no active inequality constraints,

$$\mathcal{V}_{LQR}^{MS}(\delta) = ar{\mathcal{V}}_{N}^{MS}(\delta), \,\, orall \delta \in \mathcal{N}$$

Let C be the difference between the value functions with and without additive disturbances at the origin:

$$\mathcal{V}_N^{MS}(0) - \bar{\mathcal{V}}_N^{MS}(0) = C$$

Because of linearity of the dynamics and inactive constraints, the influence of the disturbance sequence on  $\mathcal{V}_N^{MS}$  can be regarded separately to the cost of starting at the state value, i.e. the value function can be decomposed as.

$$\mathcal{V}_{N}^{MS}(\delta) = \bar{\mathcal{V}}_{N}^{MS}(\delta) + C = \mathcal{V}_{LQR}^{MS}(\delta) + C$$

Thus, as long as the convex surrogate is zero in this neighbourhood around the origin then (4) with using the approximate value function, defines the same control law as (3), thus inheriting any stability properties around the origin it may have.

## B. Learning feasibility

In the above, a tacit assumption is that the state constraint set  $\mathcal{X}_1$  corresponds to the set of feasible states of the problem. If this is so then one can simply sample points in  $\mathcal{X}_1$  to train the network. However, in general, this is not the case, as there may exist initial conditions that are infeasible only for a problem with sufficiently long horizon. As the feasible region is convex we propose to find a separate convex approximator to learn a penalty term that describes the feasible region.

For simplicity of notation consider a nominal MPC problem with bound constraints on x. This can be reformulated as the soft-constrained problem:

$$\mathcal{V}_{N,\mu}(\hat{x},\mu) = \min_{u,x} \sum_{k=0}^{N-1} l_k(x_k, u_k) + V_t(x_N) + \mu \sum_{k=1}^N \|\eta_k^u + \eta_k^l\|_1$$
(11a)

$$x_0 = \hat{x} \tag{11b}$$

$$x_{k+1} = Ax_k + Bu_k, \ k = 0, \dots, N-1$$
 (11c)

$$u_k \in \mathcal{U}_k, \qquad k = 0, \dots, N - 1 \tag{11d}$$

$$x_k \le x^u + \eta_k^u, \qquad k = 1, \dots, N \tag{11e}$$

$$x_k > x^l - \eta_k^l, \qquad k = 1, \dots, N \tag{11f}$$

$$0 \le \eta_k^u, \qquad 0 \le \eta_l^u \tag{11g}$$

where  $\eta_k^u$  and  $\eta_k^l$  are slack variables,  $\mu$  is a penalty parameter and  $\mathcal{V}_{N,\mu}(\hat{x},\mu)$  is the optimal value function. As an exact penalty is used the optimum of (11) is equivalent to that of (1) if  $\mu > \mu^*$  where  $\mu^*$  is the largest Lagrange multiplier arising from the bound constraints of (1).

The cost-to-go,  $\mathcal{V}_{N-1,\mu}$  may be decomposed as:

$$\mathcal{V}_{N-1,\mu}(\hat{x},\mu) = \mathcal{V}_{N-1}(\hat{x}) + \mu \mathcal{F}_{N-1}(\hat{x})$$
 (12)

where  $\mu \mathcal{F}_N$  is the convex, piecewise linear contribution of the slack variables to the value function. One can either develop a surrogate to describe  $\mathcal{V}_{N-1,\mu}$  or two surrogates for the decomposed problem.

In this work, we consider the use of two surrogates, because our requirements of accuracy of the two terms are different. For example, the approximation of  $\mathcal{V}_{N-1}$  does not have to be accurate in the infeasible region, where  $\mathcal{F}_{N-1}$  is non-zero. Furthermore, the approximation of  $\mathcal{F}_{N-1}$  only needs to be accurate near the boundary of the feasible region. Any inaccuracy in the interior of the infeasible region can be captured by using a larger  $\mu$  in the one-step problem (4) (this term can be adjusted after optimisation of the surrogates).

# V. NUMERICAL RESULTS

To demonstrate our proposed approach we consider solving a multistage MPC problem, where the solution of the full horizon problem can take more than 1000 seconds. The code has been implemented in Julia. Problems (3), (4) and (7) are solved in JuMP [12] using IPOPT [13]. L-BFGS [14] is used to train the neural network, through NLopt [15]. For automatic differentiation we use [16].

#### A. Case study

We consider the two-state problem:

$$\min_{u,x} \frac{1}{S} \sum_{s=1}^{S} \left( \sum_{k=0}^{N-1} \left( x_{k,s}^{T} Q x_{k,s} + u_{k,s}^{T} R u_{k,s} \right) + x_{N,s}^{T} P x_{N,s} \right)$$
(13a)

$$x_{0,s} = \hat{x}, \qquad \forall s \in S$$
 (13b)

$$x_{k+1,s} = \begin{bmatrix} 2 & 1 \\ -1 & 2 \end{bmatrix} x_{k,s} + \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} u_{k,s} + d_s,$$

$$k = 0, \dots, N - 1, \ \forall s \in S \tag{13c}$$

$$||u_{k,s}||_{\infty} \le 1.0, \qquad k = 0, \dots, N-1 \ \forall s \in S$$
 (13d)

$$\|x_{k,s}\|_{\infty} \le 1.0, \qquad k = 1, \dots, N \ \forall s \in S \tag{13e}$$

$$\begin{aligned} x_{k,s_1} &= x_{k,s_2} \Rightarrow u_{k,s_1} = u_{k,s_2}, \\ \forall s_1 \in S, s_2 \in S, s_1 \neq s_2 \end{aligned} \tag{13f}$$

with Q = I, R = 2I, and P = 9.217I, based on the corresponding LQR problem. The uncertain parameter is  $d_k \in [-0.05, 0.05] \times [-0.05, 0.05]$ . We consider a control and robust horizon of N = 5. This corresponds to a scenario tree of 1024 scenarios.

## B. Training data

To generate training data for the neural network we solve (13) with a control horizon of N - 1 = 4, on a grid to generate 441 training points, solved with an absolute tolerance of  $10^{-8}$ . To allow for sampling infeasible start points we reformulate the state inequality as soft constraints with positively constrained slack variables which we include in the objective with a weighting of  $10^5$ . 80% of the data is used for training, with the remaining 20% used as a test set. As discussed in §IV-A we fit the surrogates network on  $V_{N-1}(x) - x^T P_{LQR}x$ . We normalise the value-function and feasibility data to have a range between zero and one



Fig. 2: Solve times with the interpolating convex functions.

based on the training data. Lastly, as the dimensionality of the problem is low we do not generate additional feasibility data.

## C. Use of interpolating convex functions

Using the training data we solve (8) to find the interpolating data. Note that (8) requires 123904 inequality constraints, with 1056 variables. Thus, even though the problem only has two states, there are a significant number of constraints. However, the problem can still be solved in a reasonably short time.

We use the optimal interpolating data to construct the one step ahead MPC problem:

$$\min_{u,x} \ l_0(\hat{x}, u_0) + \tilde{\mathcal{V}}_{N-1} \tag{14a}$$

$$x_{1,s} = A_{0,s}\hat{x} + B_{0,s}u_0 + d_{0,s}, \quad \forall s = 1\dots n_s \quad (14b)$$

$$u_0 \in \mathcal{U}_0, \ x_{1,s} \in \mathcal{X}_1 \tag{14c}$$

$$\hat{\mathcal{V}}_{N-1} = \sum_{i}^{D} w_s (\mathcal{V}_{fit,s} + \mu \mathcal{F}_{fit,s} + x_{1,s}^T P x_{1,s})$$
(14d)

$$\mathcal{V}_{fit,s} \ge \mathcal{V}_{est,i} + g'_{\mathcal{V},i}(x_{1,s} - x_{fit,i}),$$
  
$$\forall s = 1 \dots n_s, \ i = 1, \dots, m$$
(14e)

$$\mathcal{F}_{fit,s} \ge \mathcal{F}_{est,i} + g'_{\mathcal{F},i}(x_{1,s} - x_{fit,i}),$$
  
$$\forall s = 1 \dots n_s, \ i = 1, \dots, m$$
(14f)

$$0 \le \mathcal{V}_{fit,s}, \qquad 0 \le \mathcal{F}_{fit,s}, \qquad \forall s = 1 \dots n_s$$
 (14g)

Although this introduces many linear inequality constraints we note that this only introduces  $2n_s + 1$  new variables  $(\hat{\mathcal{V}}_{N-1}, \mathcal{V}_{fit,s}, \mathcal{F}_{fit,s})$ . Additionally, many of the inequality constraints can be eliminated during the presolve of the optimisation algorithm. Although it is theoretically possible for interpolating functions to perfectly interpolate they did not due to the optimisation tolerance, and had small negative values near zero. As such we introduce the constraint (14g) to prevent bad behaviour.

Te difference in the control output when solving the full and reduced horizon problems is very small: an average absolute error of 0.08 from feasible start locations, and 0.02 from infeasible points. In addition, despite the large number of linear inequality constraints the use of the interpolating functions gave a considerable speed up over multistage MPC, around 1–1.5 orders of magnitude, as shown in Fig. 2.



Fig. 3: Solve times with the input convex neural networks.



Fig. 4: Cost-to-go using the ICNN with 1 horizon.

#### D. Use of ICNNs

We select a network architecture with a single hidden layer of width 20 (i.e. M = 2), with activation functions:

$$\alpha_1 = \max(0.01x, x), \qquad \alpha_2 = \max(0.0, x)$$
(15)

We select this choice of  $\alpha_2$  as we know that the network output is non-negative. As the network is restricted to be convex, we do not perform any other form of regularisation. We use the same architecture and data points to learn the ICNN for the feasibility term.

After training the networks with L-BFGS [14], we setup a 1-step ahead MPC problem (4). We directly include the neural network as expressions in the MPC problem, i.e. we do not introduce additional constraints as in (14). Using a limited memory Hessian approximation with Ipopt is found to give more stable performance, potentially due to the piecewise nature of the neural network.

The one-stage MPC formulation yields a 2.5–3.5 order of magnitude speedup as shown in Fig. 3, while capturing nearly all aspects of the original MPC problem. This is also a significant speedup over the interpolating functions (Fig. 2). The approximated value function (shown in Fig. 4) has an average absolute error of 0.91 from feasible start locations. Despite this error, the average difference in the control output is very small: an average absolute error of 0.01 from feasible start locations, and 0.03 from infeasible start locations. This minor difference in the control output occurs predominately in the region near the end of the feasible region with the error being very close to zero for most of the interior.

## VI. DISCUSSION AND CONCLUSION

This paper introduces a novel approach in which convex objective terms are learnt to allow for effective 1-step ahead MPC problems. Unlike previous work [7] that restricted its attention to quadratic costs parameterised by neural networks, or [8] in which the parameters of a control problem are learnt, here we use general convex surrogates. In particular we examine the use of interpolating convex functions and input convex neural networks.

We demonstrate the proposed method on a multistage MPC problem and show that the 1-step ahead problem can achieve a nearly identical control policy while significantly reducing the computational time using both approaches. However, the use of input-convex neural networks is preferred as they allow for a larger reduction in the computational effort, while being easily trainable and scaling well with the amount of training data. Compared to learning the control policy, the proposed approach is more flexible as the online MPC problem can be changed based on new data.

#### REFERENCES

- A. Bemporad, M. Morari, V. Dua, and E. N. Pistikopoulos, "The explicit linear quadratic regulator for constrained systems," *Automatica*, vol. 38, no. 1, pp. 3–20, 2002.
- [2] B. Karg and S. Lucia, "Efficient Representation and Approximation of Model Predictive Control Laws via Deep Learning," *IEEE Transactions on Cybernetics*, vol. 50, no. 9, pp. 3866–3878, 2020.
- [3] E. M. Turan and J. Jäschke, "Closed-loop optimisation of neural networks for the design of feedback policies under uncertainty," *Journal of Process Control*, vol. 133, pp. 103–144, 2024.
- [4] A. Keshavarz, Y. Wang, and S. Boyd, "Imputing a convex objective function," in 2011 IEEE International Symposium on Intelligent Control, 2011.
- [5] Y. Wang and S. Boyd, "Performance bounds for linear stochastic control," Systems & Control Letters, vol. 58, no. 3, pp. 178–182, 2009.
- [6] S. P. Boyd and L. Vandenberghe, *Convex optimization*. Cambridge university press, 2004.
- [7] S. Abdufattokhov, M. Zanon, and A. Bemporad, "Learning Convex Terminal Costs for Complexity Reduction in MPC," in 60th IEEE Conference on Decision and Control (CDC), pp. 2163–2168, IEEE, 2021.
- [8] A. Agrawal, S. Barratt, S. Boyd, and B. Stellato, "Learning Convex Optimization Control Policies," *Proceedings of Machine Learning Research*, vol. 120, pp. 361–373, 2020.
- [9] S. Lucia, T. Finkler, and S. Engell, "Multi-stage nonlinear model predictive control applied to a semi-batch polymerization reactor under uncertainty," *Journal of Process Control*, vol. 23, no. 9, 2013.
- [10] B. Amos, L. Xu, and J. Z. Kolter, "Input convex neural networks," in *International Conference on Machine Learning*, pp. 146–155, PMLR, 2017.
- [11] K. Seel, A. B. Kordabad, S. Gros, and J. T. Gravdahl, "Convex neural network-based cost modifications for learning model predictive control," *IEEE Open Journal of Control Systems*, vol. 1, 2022.
- [12] M. Lubin, O. Dowson, J. D. Garcia, J. Huchette, B. Legat, and J. P. Vielma, "JuMP 1.0: recent improvements to a modeling language for mathematical optimization," *Mathematical Programming Computation*, 2023.
- [13] A. Wächter and L. T. Biegler, "On the implementation of an interior-point filter line-search algorithm for large-scale nonlinear programming," *Mathematical Programming*, vol. 106, no. 1, pp. 25– 57, 2006.
- [14] D. C. Liu and J. Nocedal, "On the limited memory BFGS method for large scale optimization," *Mathematical Programming*, vol. 45, no. 1-3, pp. 503–528, 1989.
- [15] S. G. Johnson, "The NLopt nonlinear-optimization package," 2014.
- [16] J. Revels, M. Lubin, and T. Papamarkou, "Forward-mode automatic differentiation in julia," arXiv preprint arXiv:1607.07892, 2016.