Study of Multiuser Multiple-Antenna Wireless Communications Systems Based on Super-Resolution Arrays

Silvio F. B. Pinto and Rodrigo C. de Lamare

Abstract—This work studies multiple-antenna wireless communication systems based on super-resolution arrays (SRAs). We consider the uplink of a multiple-antenna system in which users communicate with a multiple-antenna base station equipped with SRAs. In particular, we develop linear minimum mean-square error (MMSE) receive filters along with linear and successive interference cancellation receivers for processing signals with the difference co-array originating from the SRAs. We then derive analytical expressions to assess the achievable sum-rates associated with the proposed multiple-antenna systems with SRAs. Simulations show that the proposed multiple-antenna systems with SRAs outperform existing systems with standard arrays that have a larger number of antenna elements.

Index Terms—MIMO, Super-resolution, Sparse arrays, Multiple-antenna.

I. INTRODUCTION

In the last decade, multiple-antenna technology [1], [2], [3] has attracted the interest of researchers dedicated to the investigation of fifth generation (5G) mobile networks due to its substantial improvement in the capacity of wireless systems and networks. In the specific case of the multiple access channel, multiple-antenna systems employ a number of physical antennas at the base station (BS), which is often much larger than that of the total number of users. However, the higher spectral efficiency and resolution resulting from this excess of antennas comes at the expense of physical space, coupling effects [11], [12] among antenna elements and energy consumption [16]. Among some innovative solutions proposed to overcome these drawbacks are coarse quantization [17], which provides energy savings. Another is the use of sparse or super-resolution arrays (SRAs) [4], [5], [6], [7], [8], [9], [10] in the BS whose large degrees of freedom can be obtained by the virtual expansion of the number of physical sensors.

The essential feature that allows one to obtain more sensors than the physical ones leads to more compact antenna arrays, reduced electromagnetic coupling [5], [6] effects and significant energy savings. It is known that among the known types of sparse arrays such as nested, co-prime, minimum redundancy (MRAs) and minimum hole (MHAs) only the first and the second provide simple closed-form expressions for the array geometry and their sensor locations must be found from tabulated entries. Despite the co-prime arrays yield virtual ULAs consisting of smaller number of sensors than nested arrays and the MRA, they result in useful virtual ULAs. Therefore, it is desirable to take advantage of the properties of the mathematical properties common to both in order to formulate a unified approach for exploiting the benefits of their unequal spacing and virtual increase of sensors in multiple-antenna systems to increase achievable sum rates and accuracy. Previous works [13] studied nested arrays technique in a massive multi-input multi-output (MIMO) heterogeneous network and the problem

The authors are with the Center for Telecommunications Studies (CETUC), Pontifical Catholic University of Rio de Janeiro, RJ, Brazil. R. C. de Lamare is also with the Department of Electronics, University of York, UK. Emails: silviof@cetuc.puc-rio.br, delamare@cetuc.puc-rio.br of joint user association and interference nulling scheduling to maximize the sum rate of users of small and macro-cells, investigated its channel estimation [14] for massive MIMO in 2-D and extended to 3-D by [15]. However, neither of them focus on the possibility of unifying the processing of sparse arrays to apply them to MIMO systems.

In this work, we investigate the uplink of multiuser MIMO systems based on SRAs and develop receivers for processing signals with the difference co-array from the SRAs. In particular, we consider co-prime and two level nested arrays, in a single procedure that can be applied to multiuser MIMO systems from the point of view of the properties of the similar virtual ULAs obtained by preprocessing each one. We adopt a tailored geometry-based stochastic model [18], [23], [25], [26], [27] that preserves the structure of the steering vectors characterized by non-uniform delays, which is a sine qua non condition [19], [21] to obtain increased number of virtual sensors with these methods. This is provided by assuming no scattering for the propagation inside the single-cell and also that each path is associated to its user and its respective steering vector. We then derive linear minimum mean-square error (MMSE) receivers for processing signals with the difference co-array with super resolution. The performance appraisal of the proposed super resolution multiple-antenna processing through longstanding metrics shows that substantial gains can be achieved in terms of savings in the number of antennas and its resulting reduction of energy consumption, increased achievable sum-rates and improved bit error rate (BER), which encourages further research in this field.

This paper is structured as follows. Section II describes the system model and background for understanding the proposed super-resolution processing. Section III presents the proposed super-resolution multiple-antenna processing. Section IV formulates the proposed MMSE receiver, including its resulting Successive Interference Cancellation form, for Two-level Nested Arrays (TLNA) and Co-prime arrays (CPA), whereas Section V analyzes aspects of the sum-rate performance of the proposed super-resolution multiple-antenna processing Section VI presents and discusses numerical results whereas the conclusions are drawn in Section VII.

II. DEFINITIONS AND MULTIPLE-ANTENNA SYSTEM MODEL

In this section, we review some basic on sparse arrays to help the understanding of the subsequent material and then introduce the multiple-antenna system model. We assume that the multiple-antenna system model under consideration employs a sparse antenna array at the base station (BS).

A. Definitions

Definition 2.1. The difference coarray set [19] represented by \mathcal{D} is a set associated with the sensors' positions \mathcal{S} through

$$\mathcal{D} \triangleq \left\{ n_1 - n_2 \mid (n_1, n_2) \in \mathcal{S}^2 \right\} \tag{1}$$

Definition 2.2. The number of Degrees of Freedom [19], denoted by DoF, of a geometry specified by S is the cardinality of its difference coarray set, as follows:

$$DoF \triangleq \mathcal{D}$$
 (2)

Definition 2.3. A two-level nested array [19] is a sparse array consisting of the union of the sensors of two ULAs. The inner S_{in} presents M_1 sensors and the external S_{ou} possesses M_2 sensors. Their locations obey the criteria:

$$S_{in} = \{md, m = 1, 2, \dots M_1\}$$

$$S_{ou} = \{n(M+1) d, n = 1, 2, \dots M_2\}$$
(3)

For $M_1 = M_2 = \frac{M}{2}$, the resulting number of physical sensors is even and yields $\frac{M^2-2}{2} + M$ DoFs.

Definition 2.4. A coprime pair of arrays [21] is a sparse array with the sensors of two ULAs. The first one containing F sensors with intersensor spacing Qd and the other with 2Q - 1 sensors and intersensor gaps Fd. The locations of their F + 2Q - 1 sensors are driven by

$$S = \{Qfd, \ 0 \le f \le F - 1\} \cup \{Fqd, \ 1 \le q \le 2Q - 1\}$$
(4)

A coprime pair of arrays provides up to 2QF + 1 DoFs [21] using solely F + 2Q - 1 physical sensors.

B. System Model

Let us take into account the uplink of a single-cell MIMO system with a BS equipped with a sparse array composed by M physical sensors, possibly a TLNA or CPA, on which the data symbols $\{s_k\} \in \{s_1, s_2, \ldots, s_{i=K}\}$ included in radio frequency (RF) signals from K single-antenna users, impinge on, as depicted in Fig.1. The environment is assumed to be free of scatterers and, in contrast to massive MIMO settings, the number of physical sensors M is assumed to be not much greater than the number of received users K. It is also assumed that all users transmit their data at the same time.



Fig. 1. Uplink of a single-cell massive MIMO using sparse arrays

The received data vector $\mathbf{x}\left(t\right)\in\mathcal{C}^{M\times1}$ at the BS is expressed by

$$\mathbf{x}(t) = \mathbf{Hs}(t) + \mathbf{z}(t), \ t = 1, 2, \cdots T \text{ snapshots}$$
 (5)

where $\mathbf{x}(t) \in C^{M \times 1}$ denotes the discrete-time received data vector and $\mathbf{z}(t)$ is the noise vector drawn from $\mathcal{CN}(\mathbf{0}, \sigma_n^2 \mathbf{I}_M)$ and uncorrelated from the signal. The discrete-time signal vector $\mathbf{s}(t) \in C^{K \times 1}$ contains the transmitted symbols. The channel matrix $\mathbf{H} = [\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_K] \in \mathcal{C}^{M \times K}$ is estimated at the receiver. In [23], [24] a finite multipath channel model is devised for poor scattering environments, where the number of multipaths is much less than the number of BS antennas and users. In those works the channel vector $\mathbf{h}_k \in \mathcal{C}^{M \times 1}$ between the *k*th user and the BS is represented by

$$\mathbf{h}_{k} = \frac{\beta_{k}}{\sqrt{P}} \sum_{p=1}^{P} \mathbf{a}\left(\theta_{p}\right) g_{kp} \tag{6}$$

where g_{kp} is the random propagation gain coefficient between the kth user and the BS related to each path $p = p_1, p_2, \ldots, P$. In that studies g_{kp} is modeled as a Rayleigh fading coefficient with zero mean and unit variance, i.e., $g_{kp} \sim \mathcal{NC}(0, 1)$. Furthermore, the expression (6) is simplified by the assumption that the path loss coefficient β_k between the kth user and BS for all users is the same and normalized to unity. The steering vector $\mathbf{a}(\theta_p)$ characterizes the angle measured between the direction of motion of the plane wave front and a line drawn perpendicular to the array. The variable $\theta_p \in \left[-\frac{\pi}{2}, \frac{\pi}{2}\right]$ denotes the angle of arrival corresponding to the *p*th path, *d* stands for the sensors spacing and λ is the wavelength. However, that model assumes a uniform linear array (ULA) at BS and poor scattering, which results in possible multipaths.

Differently from the mentioned studies, the proposed model assumes that there is no scattering, which means that there is only one path between the *k*th user and the array. Thus, we can tailor (6) to the proposed model so that each path is associated to its user and its respective steering vector, similarly to line-of-sight propagation. Following this reasoning, it is possible to express the channel vector \mathbf{h}_k as follows:

$$\mathbf{h}_{k} = g_{k} \, \mathbf{a} \left(\theta_{k} \right) \tag{7}$$

where $g_k \sim \mathcal{NC}(0,1)$ and $\mathbf{a}(\theta_k)$ is the steering vector that describes the Direction of Arrival (DOA) for each specific sparse array and user.

It is known that sparse arrays can resolve $\mathcal{O}(M^2)$ signals as a result of the expanded difference coarrays obtained from differences of the distances between their sensors and the incidence of those differences. Nevertheless, some of the known subtypes of this class of arrays like MRA and MHA neither present closed forms nor even have a simple formation rule for the design of the set containing the sensors' positions S. Despite these drawbacks, it is possible to devise a method to be applied to TLNA and CPA, so that we can assess the theoretical performance of their class of arrays when applied to multiple-antenna communications.

III. PROPOSED SUPER-RESOLUTION MULTIPLE-ANTENNA PROCESSING

We start the exposition of the proposed super-resolution multiple-antenna processing (PSRMAP) method by taking the expectation of the outer product of the received signal vector (5), to obtain its covariance matrix $\mathbf{R}_x \in \mathcal{C}^{M \times M}$:

$$\mathbf{R}_{x} = \mathcal{E}\left\{\mathbf{x}\left(t\right) \ \mathbf{x}^{H}\left(t\right)\right\} = \sum_{k=1}^{K} \sigma_{k}^{2} \left(\mathbf{h}\left(\theta_{k}\right) \ \mathbf{h}^{H}\left(\theta_{k}\right)\right) + \sigma_{n}^{2} \mathbf{I}$$
(8)

from which we obtain a vector with increased dimension

$$\mathbf{v} = \operatorname{vec}\left(\mathbf{R}_{x}\right) = \left(\mathbf{H}^{*} \odot \mathbf{H}\right)\mathbf{p} + \sigma_{n}^{2} \vec{\mathbf{1}}_{n}, \quad \in \mathcal{C}^{M^{2}} \qquad (9)$$

where \odot denotes the Khatri-Rao product, $\mathbf{p} = \begin{bmatrix} \sigma_1^2, \sigma_2^2, \dots, \sigma_K^2 \end{bmatrix}^T$ and $\mathbf{1}_n = \begin{bmatrix} \mathbf{e}_1^T, \mathbf{e}_2^T, \dots, \mathbf{e}_M^T \end{bmatrix}^T$ stands for a column vector of all zeros except a 1 in the *i*th position. Both TLNA and CPA present *DoF* that allow the formulation of convenient non-negative definite matrices (NND), which can be combined with subspace methods to estimate a number of signals greater than the number of their respective receive physical sensors. In particular, a method like Multiple Signal Classification (MUSIC) combined with a TLNA with an even number of physical sensors can estimate up to $\frac{M^2}{4} + \frac{M}{2} - 1$, signals. If TLNA is replaced by CPA, the estimation can reach *FQ* signals.

The vector **v** in (9) obtained by vectorization of the covariance matrix of the received signal \mathbf{R}_x contains redundant information in the form of some elements that appear more than once. We can remove the repeated entries after their first appearance and arrange them so that the *i*th row coincides with the sensor situated at $\left(\frac{-M^2}{4} + \frac{-M}{2} + i\right) d$ and $\left(-2FQ - 1 + i\right) d$ for TLNA and CPA, respectively.

The reshaped vectors obtained after the removal of these redundancies can be expressed for TLNA and CPA respectively as follows:

$$\mathbf{v}_{t,c} = \mathbf{B}_{t,c} \,\mathbf{p} + \mathbf{e}_{t,c} \tag{10}$$

where the augmented array manifolds $\mathbf{B}_t = [\mathbf{q}_t(\theta_1), \mathbf{q}_t(\theta_2), \dots, \mathbf{q}_t(\theta_K)]$ and $\mathbf{B}_c = [\mathbf{q}_c(\theta_1), \mathbf{q}_c(\theta_2), \dots, \mathbf{q}_c(\theta_K)]$ are described by their steering vectors for TLNA and CPA, respectively, as

$$\mathbf{q}_{t}\left(\theta_{k}\right) = |g_{k}|^{2} \left[e^{-j2\pi \frac{d}{\lambda_{c}}\left(-\bar{M}+1\right)\sin\theta_{k}}, e^{-j2\pi \frac{d}{\lambda_{c}}\left(-\bar{M}+2\right)\sin\theta_{k}}, \\ \dots, e^{-j2\pi \frac{d}{\lambda_{c}}\left(\bar{M}-2\right)\sin\theta_{k}}, e^{-j2\pi \frac{d}{\lambda_{c}}\left(\bar{M}-1\right)\sin\theta_{k}} \right]^{T},$$

$$(11)$$

$$\mathbf{q}_{c}\left(\theta_{k}\right) = |g_{k}|^{2} \left[e^{-j2\pi \frac{d}{\lambda_{c}} \left(-\hat{M}+1\right)\sin\theta_{k}}, e^{-j2\pi \frac{d}{\lambda_{c}} \left(-\hat{M}+2\right)\sin\theta_{k}}, \\ \dots, e^{-j2\pi \frac{d}{\lambda_{c}} \left(\hat{M}-2\right)\sin\theta_{k}}, e^{-j2\pi \frac{d}{\lambda_{c}} \left(\hat{M}-1\right)\sin\theta_{k}} \right]^{T},$$

$$(12)$$

where k = 1, 2, ..., K, $\overline{M} = \frac{M^2}{4} + \frac{M}{2}$ and $\hat{M} = QF + 1$. The vectors $\mathbf{e}_t \in \mathcal{R}^{(2\overline{M}-1)\times 1}$ and $\mathbf{e}_c \in \mathcal{R}^{(2\hat{M}-1)\times 1}$ consist of all zeros, except for a 1 in the central position. In comparison with \mathbf{x} in (5), both \mathbf{v}_t and \mathbf{v}_c in (10) work as if the signals received by a longer difference coarray whose sensors positions are computed by the diverse values in the set $\{\vec{x}_i - \vec{x}_j \mid i \geq 1, j \leq M\}$, where \vec{x}_i stands for the position vector of the *i*th sensor. The source signal vector \mathbf{p} composed by the powers σ_k^2 , k = 1, 2, ..., K of the truly existing sources acts like coherent sources. This associated with the fact that the difference coarrays are ULAs allow the application of spatial smoothing to equations (10) to estimate full-rank covariance matrices, which are also NND. The resulting smoothed matrices obtained for TLNA [19], [20] and for CPA [21], [22] can be expressed respectively as follows:

$$\bar{\mathbf{R}}_{tss} = \frac{1}{\bar{M}} \sum_{i=1}^{\bar{M}} \mathbf{v}_{t_i} \, \mathbf{v}_{t_i}^H = \frac{1}{\bar{M}} \left[\left(\mathbf{B}_{t1} \, \Omega_t \, \mathbf{B}_{t1}^H \right) + \sigma_n^2 \mathbf{I}_{\bar{M}} \right]^2$$
(13) wh

$$\hat{\mathbf{R}}_{css} = \frac{1}{\hat{M}} \sum_{i=1}^{\hat{M}} \mathbf{v}_{c_i} \, \mathbf{v}_{c_i}^H = \frac{1}{\hat{M}} \left[\left(\mathbf{B}_{c1} \, \Omega_c \, \mathbf{B}_{c1}^H \right) + \sigma_n^2 \mathbf{I}_{\hat{M}} \right]^2 \tag{14}$$

where the vector \mathbf{v}_{t_i} is formed by the entries between the $(\bar{M} + 1 - i)$ and the $(2\bar{M} - i)$ rows of \mathbf{v}_t in (10) and \mathbf{B}_{t1} denotes an array manifold composed with the final \bar{M} rows of \mathbf{B}_t in (10). Similarly, \mathbf{v}_{c_i} is composed with the entries included between the $(2\hat{M} + 1 - i)$ and the $(2\hat{M} - i)$ rows of \mathbf{v}_t in (10) and \mathbf{B}_{c1} stands for an array manifold composed by the latest \bar{M} rows of \mathbf{B}_c in (10). More specifically, covariance matrices Ω_t in (13) and Ω_c in (14) respectively are expressed as $\Omega_t = \Omega_c = diag(\mathbf{p})$. Additionally, covariance matrices \mathbf{B}_{t1}^H and \mathbf{B}_{c1}^H are described by

$$\mathbf{B}_{t1}^{H}, \mathbf{B}_{c1}^{H} = \begin{bmatrix} 1 & \eta_{1} & \cdots & \eta_{1}^{(\gamma)} \\ 1 & \eta_{2} & \cdots & \eta_{2}^{(\gamma)} \\ \vdots & & \ddots & \\ 1 & \eta_{K} & \cdots & \eta_{K}^{(\gamma)} \end{bmatrix}$$
(15)

where $\gamma = (\bar{M} - 1)$ for \mathbf{B}_{t1}^{H} and $\gamma = (\hat{M} - 1)$ for \mathbf{B}_{c1}^{H} . The matrices $\bar{\mathbf{R}}_{t} = (\bar{\mathbf{R}}_{tss})^{1/2}$, for TLNA, and $\bar{\mathbf{R}}_{c} = (\bar{\mathbf{R}}_{css})^{1/2}$, for CPA, play a pivotal role in this work. Their augmented sizes, which are results of preprocessed signals collected by M and F + 2Q - 1 sparse physical sensors, provide resolution of up to $\frac{M^{2}}{4} + \frac{M}{2} - 1$ and QF signals, respectively.

IV. PROPOSED MMSE RECEIVERS

We can use the enlarged matrices $\mathbf{\bar{R}}_t$ and $\mathbf{\bar{R}}_c$ defined previously to determine the expressions of the augmented data vectors that give origin to them. Now, let us assume that our system model is similar to that described in Subsection II-B, except that our array is a ULA, composed with $J|_{=\bar{M};\hat{M}}$ in (11) and (12) sensors, which is the same number of equivalent sensors obtained at the end of the sparse (TLNA or CPA) array preprocessing. It receives signals transmitted simultaneously from the K single users assumed in Subsection II-B. Following this interpretation, we have that the received data vector $\mathbf{x}_U(t) \in C^{J \times 1}$ at the BS would be expressed by

$$\mathbf{x}_{U}(t) = \mathbf{H}_{U} \mathbf{s}(t) + \mathbf{z}(t), \ t = 1, 2, \cdots T \text{ snapshots}$$
(16)

where $\mathbf{H}_U = [\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_K] \in \mathcal{C}^{J \times K}$ stands for the channel, $\mathbf{z}(t)$ denotes the noise vector, assumed to be $\mathcal{CN}(\mathbf{0}, \sigma_n^2 \mathbf{I}_J)$. It is assumed to be uncorrelated from the signal. This long ULA whose number of physical sensors is equal to the number of the equivalent virtual sensors obtained by preprocessing CPA and TLNA presents the following received data covariance matrix:

$$\mathbf{R}_{U} = \mathcal{E}\left\{\mathbf{x}_{U}\left(t\right) \ \mathbf{x}_{U}^{H}\left(t\right)\right\} = \mathbf{H}_{U} \ \mathbf{R}_{ss} \ \mathbf{H}_{U}^{H} + \sigma_{n}^{2} \mathbf{I}_{J}$$
(17)

Now, we can rewrite $\mathbf{\bar{R}}_t$ for TLNA, and $\mathbf{\bar{R}}_c$, for CPA, in compact form, as follows:

$$\bar{\mathbf{R}}_{t,c} = \left(\bar{\mathbf{R}}_{tss,css}\right)^{1/2} = \frac{1}{\sqrt{J}} \left[\left(\mathbf{B}_{t1,c1} \,\Omega_{t,c} \,\mathbf{B}_{t1,c1}^{H} \right) + \sigma_{n}^{2} \mathbf{I}_{J} \right] \\ = \mathcal{E} \left\{ \mathbf{x}_{a} \left(t \right) \quad \mathbf{x}_{a}^{H} \left(t \right) \right\}$$
(18)

where

$$\mathbf{x}_{a}(t) = J^{-\frac{1}{4}} \left(\mathbf{B}_{t1,c1} \, \mathbf{s}_{a}(t) + \mathbf{z}_{a}(t) \right)$$
(19)

By comparing (18) and (17), it can be noticed that sparse augmented covariance matrices and similar corresponding to equivalent elongated ULAs possess the same number of equally spaced sensors, and for this reason, result in equivalent channel vectors. They also present transmit uncorrelated signals with different amplitudes but have the same SNR. As a matter of fact, except for the factor $\frac{1}{\sqrt{J}}$ in the enlarged covariance expressions of the sparse arrays (18), expressions (17) and (18) are similar. Now, let us consider the estimate of a data symbol s_a of the augmented discrete-time received data vector $\mathbf{x}_a(t)$ (5) using a suitable receive filter $\mathbf{w}_a(t)$ whose output is expressed by

$$\hat{s}_a(t) = \mathbf{w}_a^H(t) \ \mathbf{x}_a(t), \qquad (20)$$

where $1 \le t \le T$ snapshots. Equation (19), can be rewritten in terms of the desired signal and interferences, as follows:

$$\mathbf{x}_{a}(t) = J^{-\frac{1}{4}} \left(\mathbf{b}_{k} s_{k}(t) + \sum_{i=1; i \neq k}^{K} \mathbf{b}_{i} s_{i}(t) + \mathbf{z}_{J}(t) \right)$$
$$= J^{-\frac{1}{4}} \left(\mathbf{b}_{k} s_{k}(t) + \mathbf{i}(t) + \mathbf{z}_{J}(t) \right)$$
(21)

where the vectors \mathbf{b}_k , \mathbf{b}_i and $\mathbf{z}_J \in C^{J \times 1}$ denote the channel vectors corresponding to the desired user, the interferences, both obtained from the augmented channel matrices in (15) and the noise vector corresponding to TLNA or CPA. It can be noticed that $\mathbf{i}(t)$ is equal to the summation of the interferences combined with their respective channel vectors, i.e., $\sum_{\substack{i=1\\i\neq k}}^{K} \mathbf{b}_i s_i(t)$. It can be shown that the Mean-Squared Error (MSE) between the transmit symbol and its estimated value [61] can be expressed by the following expectation:

$$\mathcal{E}\left\{|\hat{s}-s|^{2}\right\} = J^{-\frac{1}{2}}\sigma_{k}^{2}\mathbf{w}_{a}^{H}\mathbf{b}_{k}\mathbf{b}_{k}^{H}\mathbf{w}_{a} - J^{-\frac{1}{4}}\sigma_{k}^{2}\mathbf{w}_{a}^{H}\mathbf{b}_{k} - J^{-\frac{1}{4}}\sigma_{k}^{2}\mathbf{b}_{k}^{H}\mathbf{w}_{a} + \sigma_{k}^{2} + J^{-\frac{1}{2}}\mathbf{w}_{a}^{H}\mathbf{R}_{i+n}\mathbf{w}_{a}$$
(22)

where

$$\mathbf{R}_{i+n} = \mathcal{E}\left\{\mathbf{i}\,\mathbf{i}^{H}\right\} + \mathcal{E}\left\{\mathbf{i}\,\mathbf{z}^{H}\right\}|_{=0} + \mathcal{E}\left\{\mathbf{z}\,\mathbf{i}^{H}\right\}|_{=0} + \mathcal{E}\left\{\mathbf{z}\,\mathbf{z}^{H}\right\}$$
(23)

is the equivalent interference-plus-noise covariance matrix, where the cross terms indicated in (23) are equal to zero matrices, according to the assumed uncorrelation between signal and noise. By differentiating the MSE in (22) with respect to the receive filter w and making it equal to 0, we can compute the minimum MSE (MMSE) receive filter, as follows:

$$J^{-\frac{1}{2}}\sigma_{k}^{2} \left(\mathbf{b}_{k} \mathbf{b}_{k}^{H}\right)^{T} \mathbf{w}_{a}^{*} - J^{-\frac{1}{4}}\sigma_{k}^{2} b_{k}^{*} + J^{-\frac{1}{2}}\mathbf{R}_{i+n}^{T} \mathbf{w}_{a}^{*} = 0$$
(24)

Note that the linear MMSE receive filters can be employed by many detectors employed at the BS for uplink receive processing techniques [28], [29], [30], [31], [36], [32], [39], [33], [35], [37], [34], [38], [41], [42], [43], [44], [45], [46], [40], [47], [48], [49], [50], [51], [52], [53], [54], [55], [56], [57], [58], [59].

A. Linear MMSE Receivers

In this subsection, we describe linear MMSE receivers with super-resolution, whose column vectors of its matrix form

$$\mathbf{W}_a = [\mathbf{w}_{a_1}, \mathbf{w}_{a_2}, \dots, \mathbf{w}_{a_K}]$$
 can be obtained by solving (24):

$$\mathbf{w}_{a_i} = J^{\frac{1}{4}} \, \sigma_k^2 \left(\mathbf{R}_{i+n} + \, \sigma_k^2 \, \mathbf{b}_k \mathbf{b}_k^H \right)^{-1} \mathbf{b}_k \ \in \mathcal{C}^{J \times 1}$$
(25)

Assuming perfect channel state information and that the statistical knowledge of the noise is available, the problem corresponds to estimating the transmitted symbol and then performing detection, which can be extracted from the estimate of the data symbol $\tilde{s}_a(t)$, which in turn can be expressed as follows:

$$\tilde{s}_a(t) = \text{Slicer}\left[\hat{s}_a(t)\right] \tag{26}$$

where $\hat{s}_{a}(t)$ is computed by (20).

B. Successive Interference Cancellation MMSE Receivers

The interference cancellation can be successfully combined with an MMSE filter to better evaluate the performance of sparse arrays in terms of uncoded BER. Specifically, in the norm-based ordered successive interference cancellation (OSIC) method [62], [63], which will be applied to our PSRMAP it is assumed that the received signal concentration of the *i*th transmitted signal is proportional to the norm of its corresponding channel vector $[\mathbf{B}_{t1}]_{(:,i)}$. Thus, before starting the procedure, the channel vectors are norm-ordered decreasingly. Except for the first step, which preserves the MMSE linear filter features, the subsequent refining steps remove the preceding interference according the decreasing order of the Euclidean norm of that vectors. The second step of OSIC is provided by the 2nd row of the MMSE linear filter applied to the first 'peeled' received vector $\tilde{\mathbf{x}}_1$, which is the difference between the received vector \mathbf{x}_{a} and the product of the first norm-ordered channel vector $J^{-\frac{1}{4}}\mathbf{b}_{t1,c1(1)}$ and its corresponding signal estimate $s_{a_1}(t)$. The process for estimating the 'peeled' received vector starts with rewriting (19) as follows

$$\mathbf{x}_{a}(t) = J^{-\frac{1}{4}} \left(\mathbf{b}_{t1,c1(1)} \, s_{a_{1}}(t) + \mathbf{b}_{t1,c1(2)} \, s_{a_{2}}(t) + \dots + \mathbf{b}_{t1,c1(K)} \, s_{a_{K}}(t) + \mathbf{z}_{a}(t) \right)$$
(27)

and after that, taking the desired difference:

$$\tilde{\mathbf{x}}_{1} = \mathbf{x}_{a}(t) - J^{-\frac{1}{4}} \mathbf{b}_{t1,c1(1)} s_{a_{1}}(t)
= J^{-\frac{1}{4}} \left(\mathbf{b}_{t1,c1(2)} s_{a_{2}}(t)
+ \dots + \mathbf{b}_{t1,c1(K)} s_{a_{K}}(t) + \mathbf{z}_{a}(t) \right)$$
(28)

V. ANALYSIS

In this section, we analyze aspects of the performance of the proposed super-resolution multiple-antenna processing. To this end, we assume Gaussian signalling and make use of suitable indicators such as Achievable Sum-Rate (ASR_a) . The computational complexity (CC_a) demanded for carrying out the proposed algorithm follows $\mathcal{O}(J^3)$ Floating Point Operations per second (FLOPs) mainly concentrated in its inversion matrix. The ASR can be defined [60], [23] as:

$$ASR_a \le \sum_{k=1}^{K} \log_2 \left(1 + SINR_k \right) \tag{29}$$

in which the received signal-to-interference plus noise ratio of the *k*th user $(SINR_k)$, which is taken at the output of the receiver is expressed by:

$$SINR_k = \frac{\sigma_s^2}{\sigma_i^2 + \sigma_w^2} \tag{30}$$

where σ_s^2 is the signal power, σ_j^2 is the interference power and σ_w^2 is the noise power. Recall that as our system is composed of a sole cell, the inter-cell interference is not considered. This ratio can be obtained by identifying and taking suitable parts of the expression of the variance of the estimate of the data symbol $\gamma = \mathcal{E}\left\{\hat{s}_a\left(t\right)\hat{s}_a^H\left(t\right)\right\}$ as follows:

$$\gamma = J^{-\frac{1}{2}} \underbrace{(\sigma_k^2 | \mathbf{w}_k^H \mathbf{b}_k |^2}_{signal power} + \underbrace{\sum_{i=1; i \neq k}^{intra-cell MUI} \sigma_i^2 | \mathbf{w}_k^H \mathbf{b}_i |^2}_{i=1; i \neq k} + \underbrace{\sigma_n^2 | \mathbf{w}_k ||^2}_{(31)}$$

where we have considered that the expected values of crossproduct terms are null as a result of the statistics assumed in Subsection II-B. From (29), (30) and (31), we obtain the expression of ASR_a for the considered sparse arrays, namely, *TLNA* and *CPA*, as follows:

$$ASR_{a} \leq \sum_{k=1}^{K} \log_{2} \left(1 + \frac{\sigma_{k}^{2} |\mathbf{w}_{k}^{H} \mathbf{b}_{k}|^{2}}{\sum_{i=1; i \neq k}^{K} \sigma_{i}^{2} |\mathbf{w}_{k}^{H} \mathbf{b}_{i}|^{2} + \sigma_{n}^{2} ||\mathbf{w}_{k}||^{2}} \right)$$
(32)

VI. NUMERICAL RESULTS

This section is intended to assess the performance of our PSRMAP from the point of view of the ASR and BER. To this end, we examine a scenario involving K = 8 singleantenna users. The transmitted signals containing 10^2 symbols under QPSK modulation experience a channel modeled as in (7) before impinging on TLNA, CPA and ULA-based MU-MIMO receivers. The first and the second arrays comprise $M \in \{8, 16\}$ non-uniformly spaced physical sensors whereas ULA consists of M = 16 uniformly spaced physical sensors. We set the number of independent trials to 10^3 .

In Fig.2, we plot the ASR corresponding to K = 8 users sending signals to a ULA comprising M = 16 physical sensors. We can compare its ASR to that achieved by TLNA and CPA consisting both of an smaller or equal amount of sensors, i.e. M = 8 and M = 16. It can be noticed that the smaller number of sensors for TLNA and CPA (M = 8) is just enough to provide better performance than that achieved by a ULA containing (M = 16) in all considered SNR range.

Fig.3 illustrates the performance of the uncoded BER for TLNA, CPA and ULA under norm-ordered successive interference cancellation applied to a MMSE receiver, as described in Subsection IV-B. A comparison among the curves makes clear that for TLNA and CPA with the same number of physical sensors, the first yields better results in the SNR range in question. Furthermore, the BER performance of a ULA consisting of M = 16 is worse than that of a pair $\{TLNA, CPA\}$ comprised of M = 8, i.e., its half, and also by the same pair consisting of the same number of sensors of a ULA M = 16.

We have proposed a sparse arrays processing common to two-level nested and co-prime arrays that can be applied to



Fig. 2. ASR for K = 8 single users. M= No. of physical sensors.

Fig. 3. Uncoded BER for K = 8 single users. M= No. of physical sensors.

multiple-antenna systems in the light of the properties of the similar virtual ULAs. It is assumed a geometry-based stochastic model and no scattering inside a single-cell. The proposed PSRMAP procedure resulted in substantial gains in terms of achievable rates, bit error ratio and the energy savings resulting from the much smaller number of sensor elements which is required to achieve the same performance of a given ULA. The obtained results motivate further studies in this area.

REFERENCES

- R. C. de Lamare, "Massive MIMO systems: Signal processing challenges and future trends," in URSI Radio Science Bulletin, vol. 2013, no. 347, pp. 8-20, Dec. 2013.
- [2] L. Lu, G. Y. Li, A. L. Swindlehurst, A. Ashikhmin and R. Zhang, "An Overview of Massive MIMO: Benefits and Challenges," in IEEE Journal of Selected Topics in Signal Processing, vol. 8, no. 5, pp. 742-758, Oct. 2014
- [3] W. Zhang et al., "Large-Scale Antenna Systems With UL/DL Hardware Mismatch: Achievable Rates Analysis and Calibration," in IEEE Transactions on Communications, vol. 63, no. 4, pp. 1216-1229, April 2015.
- [4] P. Pal and P. P. Vaidyanathan, "Nested Arrays: A Novel Approach to Array Processing With Enhanced Degrees of Freedom," in IEEE Transactions on Signal Processing, vol. 58, no. 8, pp. 4167-4181, Aug. 2010.
- [5] Liu, C.L.; Vaidyanathan, P. P., 'Super Nested Arrays: Linear Sparse Arrays With Reduced Mutual Coupling Part I: Fundamentals', *IEEE Transactions on Signal Processing*, 64(15), pp.3997-4012, Aug 2016.
- [6] Liu, C.L., Vaidyanathan, P. P., 'Super nested arrays: Sparse arrays with less mutual coupling than nested arrays', ICASSP, 2016.
 [7] X. Wang, Z. Yang, J. Huang and R. C. de Lamare, "Robust Two-
- [7] X. Wang, Z. Yang, J. Huang and R. C. de Lamare, "Robust Two-Stage Reduced-Dimension Sparsity-Aware STAP for Airborne Radar With Coprime Arrays," in IEEE Transactions on Signal Processing, vol. 68, pp. 81-96, 2020.
- [8] W. S. Leite and R. C. d. Lamare, "List-Based OMP and an Enhanced Model for DOA Estimation With Nonuniform Arrays," in IEEE Transactions on Aerospace and Electronic Systems, vol. 57, no. 6, pp. 4457-4464, Dec. 2021.
- [9] W. Shi, Y. Li and R. C. de Lamare, "Novel Sparse Array Design Based on the Maximum Inter-Element Spacing Criterion," in IEEE Signal Processing Letters, vol. 29, pp. 1754-1758, 2022.
- [10] X. Sheng, D. Lu, Y. Li and R. C. de Lamare, "Enhanced MISC-Based Sparse Array With High uDOFs and Low Mutual Coupling," in IEEE Transactions on Circuits and Systems II: Express Briefs, 2023.
- [11] Gupta, I. J., Kisienskiand A. A., 'Effect of Mutual Coupling on the Performance of Adaptive Arrays', *IEEE Transactions on Antennas and Propagation*, Vol. Ap-31, No. 5, September 1983.
- [12] Wu,Y., Linnartz, J. P., 'Effects of Antenna Mutual Coupling on the Performance of MIMO Systems', 29th Symposium on Information Theory in the Benelux, May 2008.
- [13] Feng, M., Mao, S., 'Interference Management and User Association for Nested Array-Based Massive MIMO HetNets', *IEEE Transactions on Vehicular Technology*, Vol. 67, No. 1, January 2018.
- [14] Zhu, F., Liang, Q. , 'Channel estimation for massive MIMO with 2-D nested array deployment', *Physical Communication*, Elsevier, 25, 432-437, 2017.
- [15] Yuan S., Liang, Q.,'3D nested distributed massive MIMO: Modeling and performance analysis', Ad Hoc Networks, Elsevier, 58, 6-12, 2017.

- [16] Pinto, S. F. B., Lamare, R.C., 'Quantization-Aware Block Diagonalization Algorithms for Multiple-Antenna Systems with Low-Resolution Signals', 24th Workshop on Smart Antennas, pp.1-6, Hamburg, Germany, Feb. 2020.
- [17] Pinto, S. F. B., Lamare, R. C., Block Diagonalization Precoding and Power Allocation for Multiple-Antenna Systems with Coarsely Quantized Signals, July 2021 *IEEE Trans. on Communications*, pp.99:1-1
- [18] Oestges, C., Clerckx, B., MIMO Wireless Networks Channels, Techniques and Standards for Multi-Antenna, Multi-User and Multi-Cell Systems', Elsevier, 2013.
- [19] Pal, P., Vaidyanathan, 'Nested Arrays: A Novel approach to array Processing with Enhanced degrees of Freedom', *IEEE Transactions on Signal Processing*, vol.58, no. 8, pp. 4167-4181, Aug. 2010.
- [20] Pinto, S. F., Lamare, R. C., 'Multi-Step Knowledge-Aided Iterative MUSIC for Direction Finding using Nested Arrays,' WSA, 2019.
- [21] Pal, P., Vaidyanathan, 'Coprime Sampling and the MUSIC Algorithm', Digital Signal Processing and Signal Processing Education Meeting, Sedona, AZ, USA, Jan. 2011.
- [22] Tan,Z., Nehorai, A., 'Direction of Arrival Estimation Using Co-Prime Arrays: A Super Resolution Viewpoint,' *IEEE Transactions on Signal Processing*, vol. 62, no. 21, pp. 5565-5576, Nov.1, 2014.
- [23] Hawej, M., Shayan, Y., 'Evaluation of Massive MU-MIMO Channel Estimation Based on Uplink Achievable Sum-rate Criteria', IEEE Canadian Conf. of Electrical and Computer Engineering, pp.1-5, 2019.
- [24] Hawej, M., Shayan, Y., 'Iterative weighted nuclear norm minimizationbased channel estimation for massive multi-user MIMO systems', IEEE 88th Vehicular Technology Conference, Chicago, USA, pp. 1-5, 2018.
- [25] Hawej, M., Shayan, Y., 'Compressive Sensing based Nuclear Norm Minimization Method for Massive MU-MIMO Channel Estimation', IEEE Canadian Conf. on Electrical and Computer Engineering, 2018.
- [26] Hawej, M., Shayan, Y., 'Pilot decontamination in massive multiuser MIMO systems based on low-rank matrixapproximation', *IET Communications*, Jan. 2019.
- [27] Zheng, K., Yin X., 'Massive MIMO Channel Models: A Survey', International Journal of Antennas and Propagation, ID 848071, 10 pages, 2014.
- [28] R. C. de Lamare and R. Sampaio-Neto, "Adaptive Reduced-Rank Processing Based on Joint and Iterative Interpolation, Decimation, and Filtering," in IEEE Transactions on Signal Processing, vol. 57, no. 7, pp. 2503-2514, July 2009.
- [29] R. C. De Lamare and R. Sampaio-Neto, "Minimum Mean-Squared Error Iterative Successive Parallel Arbitrated Decision Feedback Detectors for DS-CDMA Systems," in IEEE Transactions on Communications, vol. 56, no. 5, pp. 778-789, May 2008.
- [30] Y. Cai and R. C. de Lamare, "Space-Time Adaptive MMSE Multiuser Decision Feedback Detectors With Multiple-Feedback Interference Cancellation for CDMA Systems," in IEEE Transactions on Vehicular Technology, vol. 58, no. 8, pp. 4129-4140, Oct. 2009.
- [31] Fa, R.; de Lamare, R.C.: 'Multi-branch successive interference cancellation for MIMO spatial multiplexing systems: design, analysis and adaptive implementation', IET Communications, 2011, 5, (4), p. 484-494.
- [32] P. Li, R. C. de Lamare and R. Fa, "Multiple Feedback Successive Interference Cancellation Detection for Multiuser MIMO Systems," in IEEE Transactions on Wireless Communications, vol. 10, no. 8, pp. 2434-2439, August 2011.
- [33] R. C. de Lamare and R. Sampaio-Neto, "Adaptive Reduced-Rank Equalization Algorithms Based on Alternating Optimization Design Techniques for MIMO Systems," in IEEE Transactions on Vehicular Technology, vol. 60, no. 6, pp. 2482-2494, July 2011.
- [34] R. C. de Lamare and P. S. R. Diniz, "Set-Membership Adaptive Algorithms Based on Time-Varying Error Bounds for CDMA Interference Suppression," in IEEE Transactions on Vehicular Technology, vol. 58, no. 2, pp. 644-654, Feb. 2009
- [35] R. C. de Lamare and R. Sampaio-Neto, "Reduced-Rank Space-Time Adaptive Interference Suppression With Joint Iterative Least Squares Algorithms for Spread-Spectrum Systems," in IEEE Transactions on Vehicular Technology, vol. 59, no. 3, pp. 1217-1228, March 2010.
- [36] N. Song, R. C. de Lamare, M. Haardt and M. Wolf, "Adaptive Widely Linear Reduced-Rank Interference Suppression Based on the Multistage Wiener Filter," in IEEE Transactions on Signal Processing, vol. 60, no. 8, pp. 4003-4016, Aug. 2012
- [37] P. Clarke and R. C. de Lamare, "Joint Transmit Diversity Optimization and Relay Selection for Multi-Relay Cooperative MIMO Systems Using Discrete Stochastic Algorithms," in IEEE Communications Letters, vol. 15, no. 10, pp. 1035-1037, October 2011.
- [38] P. Clarke and R. C. de Lamare, "Transmit Diversity and Relay Selection Algorithms for Multirelay Cooperative MIMO Systems," in IEEE Transactions on Vehicular Technology, vol. 61, no. 3, pp. 1084-1098, March 2012.

- [39] P. Li and R. C. De Lamare, "Adaptive Decision-Feedback Detection With Constellation Constraints for MIMO Systems," in IEEE Transactions on Vehicular Technology, vol. 61, no. 2, pp. 853-859, Feb. 2012.
 [40] J. Liu and R. C. de Lamare, "Low-Latency Reweighted Belief Propa-
- [40] J. Liu and R. C. de Lamare, "Low-Latency Reweighted Belief Propagation Decoding for LDPC Codes," in IEEE Communications Letters, vol. 16, no. 10, pp. 1660-1663, October 2012
- [41] R. C. de Lamare, "Adaptive and Iterative Multi-Branch MMSE Decision Feedback Detection Algorithms for Multi-Antenna Systems," in IEEE Transactions on Wireless Communications, vol. 12, no. 10, pp. 5294-5308, October 2013.
- [42] A. G. D. Uchoa, C. T. Healy and R. C. de Lamare, "Iterative Detection and Decoding Algorithms for MIMO Systems in Block-Fading Channels Using LDPC Codes," in IEEE Transactions on Vehicular Technology, vol. 65, no. 4, pp. 2735-2741, April 2016.
- [43] Z. Shao, R. C. de Lamare and L. T. N. Landau, "Iterative Detection and Decoding for Large-Scale Multiple-Antenna Systems With 1-Bit ADCs," in IEEE Wireless Communications Letters, vol. 7, no. 3, pp. 476-479, June 2018.
- [44] T. Peng, R. C. de Lamare and A. Schmeink, "Adaptive Distributed Space-Time Coding Based on Adjustable Code Matrices for Cooperative MIMO Relaying Systems," in IEEE Transactions on Communications, vol. 61, no. 7, pp. 2692-2703, July 2013.
- [45] P. Li and R. C. de Lamare, "Distributed Iterative Detection With Reduced Message Passing for Networked MIMO Cellular Systems," in IEEE Transactions on Vehicular Technology, vol. 63, no. 6, pp. 2947-2954, July 2014.
- [46] Y. Cai, R. C. de Lamare and R. Fa, "Switched Interleaving Techniques with Limited Feedback for Interference Mitigation in DS-CDMA Systems," in IEEE Transactions on Communications, vol. 59, no. 7, pp. 1946-1956, July 2011.
- [47] Y. Cai, R. C. de Lamare, B. Champagne, B. Qin and M. Zhao, "Adaptive Reduced-Rank Receive Processing Based on Minimum Symbol-Error-Rate Criterion for Large-Scale Multiple-Antenna Systems," in IEEE Transactions on Communications, vol. 63, no. 11, pp. 4185-4201, Nov. 2015.
- [48] C. T. Healy and R. C. de Lamare, "Design of LDPC Codes Based on Multipath EMD Strategies for Progressive Edge Growth," in IEEE Transactions on Communications, vol. 64, no. 8, pp. 3208-3219, Aug. 2016.
- [49] J. Gu, R. C. de Lamare and M. Huemer, "Buffer-Aided Physical-Layer Network Coding With Optimal Linear Code Designs for Cooperative Networks," in IEEE Transactions on Communications, vol. 66, no. 6, pp. 2560-2575, June 2018.
- [50] A. R. Flores, R. C. de Lamare and B. Clerckx, "Linear Precoding and Stream Combining for Rate Splitting in Multiuser MIMO Systems," in IEEE Communications Letters, vol. 24, no. 4, pp. 890-894, April 2020.
- [51] Z. Shao, L. T. N. Landau and R. C. de Lamare, "Dynamic Oversampling for 1-Bit ADCs in Large-Scale Multiple-Antenna Systems," in IEEE Transactions on Communications, vol. 69, no. 5, pp. 3423-3435, May 2021.
- [52] R. B. Di Renna and R. C. de Lamare, "Adaptive Activity-Aware Iterative Detection for Massive Machine-Type Communications," in IEEE Wireless Communications Letters, vol. 8, no. 6, pp. 1631-1634, Dec. 2019.
- [53] R. B. Di Renna and R. C. de Lamare, "Iterative List Detection and Decoding for Massive Machine-Type Communications," in IEEE Transactions on Communications, vol. 68, no. 10, pp. 6276-6288, Oct. 2020.
- [54] L. T. N. Landau, M. Dörpinghaus, R. C. de Lamare and G. P. Fettweis, "Achievable Rate With 1-Bit Quantization and Oversampling Using Continuous Phase Modulation-Based Sequences," in IEEE Transactions on Wireless Communications, vol. 17, no. 10, pp. 7080-7095, Oct. 2018.
- [55] R. B. Di Renna, C. Bockelmann, R. C. de Lamare and A. Dekorsy, "Detection Techniques for Massive Machine-Type Communications: Challenges and Solutions," in IEEE Access, vol. 8, pp. 180928-180954, 2020.
- [56] Z. Shao, L. T. N. Landau and R. C. De Lamare, "Channel Estimation for Large-Scale Multiple-Antenna Systems Using 1-Bit ADCs and Oversampling," in IEEE Access, vol. 8, pp. 85243-85256, 2020.
- [57] R. B. D. Renna and R. C. de Lamare, "Dynamic Message Scheduling Based on Activity-Aware Residual Belief Propagation for Asynchronous mMTC," in IEEE Wireless Communications Letters, vol. 10, no. 6, pp. 1290-1294, June 2021.
- [58] R. B. Di Renna and R. C. de Lamare, "Joint Channel Estimation, Activity Detection and Data Decoding Based on Dynamic Message-Scheduling Strategies for mMTC," in IEEE Transactions on Communications, vol. 70, no. 4, pp. 2464-2479, April 2022.
- [59] A. B. L. B. Fernandes, Z. Shao, L. T. N. Landau and R. C. de Lamare, "Multiuser-MIMO Systems Using Comparator Network-Aided

- Receivers With 1-Bit Quantization," in IEEE Transactions on Communications, vol. 71, no. 2, pp. 908-922, Feb. 2023.
 [60] Marzetta, T.L., Larssson, E.G., 'Fundamentals of Massive MIMO', Cambridge University Press, 2016.
 [61] Li, J., Stoica, P., 'Robust Adaptive Beamforming', John Wiley & Sons, 2006.
 [62] Paulrai, A. Nabar, 'Interduction of Communication of Communications', and the statement of Communications', and the statement of Communication of Communications', and the statement of Communication of Communications', and the statement of Communications', and the statement of Communication of Communications', and the statement of Communication of Communications', and the statement of Communications', and the statement of Communication of Communications', and the statement of Communi
- [62] Paulraj, A., Nabar, 'Introduction to Space-Time Wireless Communica-
- [63] Wolniansky, P., Foschini, G., 'An architecture for realizing very high data rates over the rich-scattering wireless channel', Proc. URSI ISSSE, 295-300, September, 1998.