AutoNumerics-Zero: Automated Discovery of State-of-the-Art Mathematical Functions

Esteban Real¹² Yao Chen³ Mirko Rossini³ Connal de Souza³ Manav Garg³ Akhil Verghese³ Moritz Firsching² Quoc V. Le¹ Ekin Dogus Cubuk¹ David H. Park³

Abstract

Computers calculate transcendental functions by approximating them through the composition of a few limitedprecision instructions. For example, an exponential can be calculated with a Taylor series. These approximation methods were developed over the centuries by mathematicians, who emphasized the attainability of arbitrary precision. Computers, however, operate on few limited precision types, such as the popular float32. In this study, we show that when aiming for limited precision, existing approximation methods can be outperformed by programs automatically discovered from scratch by a simple evolutionary algorithm. In particular, over real numbers, our method can approximate the exponential function reaching orders of magnitude more precision for a given number of operations when compared to previous approaches. More practically, over float32 numbers and constrained to less than 1 ULP of error, the same method attains a speedup over baselines by generating code that triggers better XLA/LLVM compilation paths. In other words, in both cases, evolution searched a vast space of possible programs, without knowledge of mathematics, to discover previously unknown optimized approximations to high precision—for the first time. We also give evidence that these results extend beyond the exponential. The ubiquity of transcendental functions suggests that our method has the potential to reduce the cost of scientific computing applications.

1. Introduction

The numerical calculation of transcendental functions is of fundamental importance to the applied sciences. Exponentials and logarithms are pervasive; trigonometry permeates problems involving geometric shapes; and various special functions have been defined as solutions to important differential equations [6]. Multiple scientific fields, from robotics to molecular dynamics, regularly perform computationally intensive simulations where transcendental functions are central [61; 65; 57]. To evaluate these functions, computers rely on a handful of operations that can be executed by the hardware, such as additions and multiplications. As there is no finite sequence of such operations that will produce an exact result, transcendental functions must be approximated. Over the centuries, mathematicians have invented various approximation methods, such as asymptotic expansions, minimax optimization, and tabular approaches. The emphasis has been on techniques that can easily attain arbitrary precision. A simple example is the truncated Taylor series, which yields increasing precision with the inclusion of additional terms. Yet computers often perform calculations with a precision limit imposed by a data type supported

by the hardware, such as the popular 32-bit floating-point type (float32) [69]. Precision beyond the chosen data type is not useful. In this paper, we show that when optimizing for a given precision, existing mathematical methods can be matched or outperformed by a simple evolutionary algorithm working without human input.

The evolutionary algorithm, which we name AutoNumerics-Zero, discovers-from scratch-computer programs that optimize the trade-off between precision and a measure of efficiency, such as the number of operations or the speed. It does this automatically, starting from empty code, and using only simple operations. Importantly, it has no prior mathematical knowledge of asymptotics, perturbation theory, or any other numerical approximation method. That is, it starts with "zero knowledge". AutoNumerics-Zero uses a symbolic regression strategy [27; 52; 30] and executes it at scale. As is standard in symbolic regression, there is an outer loop of discrete optimization and an inner loop of continuous optimization. The outer loop discovers the symbolic structure of the program (e.g. " $x \times c_0 + c_1$ ", though in practice much more complex than this), while the inner loop optimizes the floating-point coefficients (" c_0 " and " c_1 "). The outer loop evolves a population of programs by alternatingly selecting the best and mutating them at random to generate more. For the selection stage, we develop a distributed variant of the popular NSGA-II algorithm that we call dNSGA-II. dNSGA-

¹Google DeepMind ²Google Research ³Google. Correspondence to: Esteban Real <ereal@google.com>.

II carries out selection without needing knowledge of the full population and thus it has a parallelization advantage. The programs in the population are represented as compute graphs. These are mutated by operators that were designed to be minimally disruptive of existing graph structure, as will be explained in the methods. For the inner loop, we diverge from the standard practice of using gradient-based methods [25] in favor of an evolutionary strategy, which allows us to avoid assumptions about real-valued arithmetic that do not hold for float32 numbers. This design was guided by the premise of searching directly for what we ultimate care about: programs optimized for computation at a given precision.

Using this approach, we discover programs that can compute approximations over (A) real numbers and (B) floating-point numbers. The results in this paper emphasize approximating the exponential, $g(x) = 2^x$, because it is a very well studied function and therefore has strong baselines. In spite of the strong baselines, we were able to match or improve on the best baselines attempted, including asymptotic expansions (Taylor series, Padé approximants, Chebyshev expansions, and continued fractions), minimax optimization [22], and a modern lattice reduction method [8; 11].

(A) The results over real numbers are intended to fairly compare the method against standard mathematics. Surprisingly, AutoNumerics-Zero discovers programs that attain orders of magnitude higher accuracy while using the same number of operations. These operations are restricted to the field of real numbers $(+, -, \times, \div)$ and no rounding is forced on intermediate calculations. This is the scenario under which mathematical solutions have typically been constructed. Within these constraints, the key advantage of evolutionary search is that it can consider programs that reuse intermediate results. We provide proofs of error bounds on our results.

(B) More practically, we perform a case study where we optimize floating-point precision and speed using the popular Python/JAX environment. In this context, we discover programs over floating-point numbers that optimize the execution time in a surprising way: evolved exponential programs are more than 3 times faster than the fastest baselines because the search process engineers code that triggers an unusual compilation path (which the baselines do not trigger). This is, of course, specific to the compiler we used, as that was the intention when optimizing time (instead of number of operations). This scenario reflects a need of scientific computing practice: if one is going to run a large computation on a given setting (hardware, compiler, etc.), one may want to first optimize directly on that particular setup, spending part of the budget on the optimization in order to save proportionally more resources during the large computation. In this case study, we set 1 ULP of error or less as our target. This error tolerance roughly corresponds

to allowing a mistake in the last bit of the mantissa; it is a tiny error that is generally considered acceptable for a high-quality numerical library [67].

Optimizing for fast floating-point computation illustrates the capabilities of the symbolic regression approach. Because only float32 operations are allowed, all intermediate values are rounded-to-nearest following the IEEE rules implemented by the hardware [69]. Rounding introduces peculiarities that traditional mathematics does not typically address; e.g. $a \div b$ is generally different from $(1 \div b) \times a$. The evolutionary method, on the other hand, will handle these correctly. Moreover, because evolution directly measures the speed, it is also accounting for compiler and hardware effects. This includes CPU decisions such as pipelining, prefetching, and speculative execution, as well as compiler choices. The evolutionary process is even regularized to handle noise when measuring speed [43]. Thus, evolution permits the end-to-end optimization of programs for fast floating-point computation on modern hardware, accounting for practical issues that would be hard to capture by mathematics.

In summary, our contributions are:

- AutoNumerics-Zero, a method to evolve programs that compute transcendental functions efficiently—searching from scratch and without knowledge of numerics;
- discovered programs for exponential computation over R that are much more precise than previously known mathematical expressions for a given number of field operations;
- a case study that discovers faster float32 exponential computation for a given hardware and compiler, illustrating AutoNumerics-Zero's end-to-end optimization ability;
- evidence of extensibility to other transcendental functions.

2. Results

We will demonstrate that evolutionary search at scale can produce state-of-the-art programs to compute transcendental functions. Section 2.1 will present the automated discovery of programs that optimize a real-valued exponential function to maximize precision for a given number of operations. Then, Section 2.2 will present a practical case study that focuses on a given compiler and hardware; in this case, we optimize speed (instead of number of operations) and floating-point precision (instead of real-valued precision). Finally, Section 2.4 will give evidence that the method can be extended to other transcendental functions.

2.1. Efficient Exponentials over Real Numbers

We evolved computer programs to calculate the exponential function $g(x) = 2^x$. It is only necessary to find a program valid on (0, 1] because the standard process of range reduction easily extends such a program to the entire real line

(details of range reduction can be found in Section 4.1). To evolve these programs, we use a two-level search process. A large-scale outer loop of genetic programming gradually improved a population of candidate programs to optimize two objectives, precision and number of operations. These candidate programs were represented as compute graphs with vertices implementing the $\{+, -, \times, \div\}$ binary operations and c_i symbols denoting coefficients. The outer loop generates new candidates by mutating the graphs randomly (inserting/deleting vertices and reconnecting edges). The coefficients for each candidate proposed are optimized in an inner loop using CMA-ES [33]. The initial population contained only identity programs, yet left to evolve for a large number of samples, highly optimized programs emerge. The precision was quantified in terms of the real-valued maximum relative error, as is standard. During the search, it was necessary to approximate the precision by calculating the maximum error over a restricted set of numbers (validation set " \mathcal{V} " in Section 4.3), resulting in a precision *upper* bound. As we are approximating a well-behaved function, in practice this upper bound is reasonably tight, though we do not rely on it for the final results below. The said restriction is essential for the search to complete in a reasonable amount of time; in spite of the restriction, discovered programs maintain their high precision when tested thoroughly. Section 2.3 has more details on the search process; here we focus on the outcomes.



Figure 1: Real-valued exponential programs discovered through evolutionary search (top row, orange) surpass the baselines (other rows, blue) for each given number of operations by many orders of magnitude in precision (note log-scale in ordinate axis). Each point denotes a program. The accuracy of evolved programs is an *under*estimate, obtained from proven error bounds; the accuracy of baselines is an *over*estimate, obtained from sampling. Thus, the gap between them is mathematically proven.

Once the search has produced optimized programs, we can test them thoroughly without relying on the approximations made during the search phase. To do this, we prove rigorous error bounds using interval arithmetic. The details are in Supplementary Section S2. Figure 1 shows the final results. Note that the base-10 logarithmic ordinate axis implies that for a given number of operations, the precision of the evolved functions is orders of magnitude better than all the baselines. We used several baseline methods. A common, yet sub-optimal, approach to computing an exponential is through a Taylor expansion. To minimize the number of operations, we can write the exponential in Horner's scheme¹ [40; 39]. Taylor expansion baselines of various orders are labeled "Polynomial/Taylor" in the figure. The method of Padé approximants derives a rational function from Taylor expansions. This rational function has improved convergence properties in the number of operations [6]. There is no proof of optimality for how the rational function should be written but it is natural to use a ratio of Horner scheme polynomials. Padé approximant baselines of various orders are labeled "Rational/Padé" in the figure. These expansion approaches are suboptimal because they produce exact coefficients at a single point but generally increasing error with distance from that point. A better method is to even out the error over the interval in question. Thus, we minimized the maximum relative error using the Remez algorithm [45], resulting in the corresponding "Polynomial/Minimax" and "Rational/Minimax" baseline points in the figure. We also included three types of continued fractions as baselines, due to Euler [13], Gauss [17], and Macon [35], the latter being developed explicitly to use as few computations as possible. Finally, we also include the Chebyshev approximation [59], which has the property that it can be obtained mechanically like a Taylor series, but it produces uniform maximal errors over the interval. As the figure shows, the discovered exponentials surpass all of these baselines for the given number of operations.

Figure 2 shows an example of a discovered function. A key element in its concise form is the reuse of intermediate results, evidenced by vertices with more than one out-edge. This type of reuse is encouraged by the search: one of the objectives is the number of actual operations in the program regardless of the form it is in (*e.g.* it does not need to be in the form of a polynomial or a ratio of two polynomials). More examples can be seen in Supplementary Section S1.

2.2. Fast Exponentials over Floating-point Numbers

We now take a more practical approach and optimize programs to compute the exponential function again, but this time optimizing its throughput speed. Speed necessarily depends on the compiler and the hardware so these should be included in the optimization loop. Fortunately, our method does not put any constraints on the search objectives, so we measure speed by direct timing. The other objective

¹Horner's scheme represents a polynomial in the form: $c_0 + x(c_1 + x(c_2 + x(c_3 + x...))).$



Figure 2: Discovered program for real-valued 2^x computation with 10 operations and proven maximum relative error under $5.4e \times 10^{-15}$.

remains the precision, except that now it is computed using the hardware operations available; that is, float32 arithmetic. Internal rounding is included in the calculations. We measure the precision in terms of the *floating-point* maximum relative error, as is standard. This means that the error is not measured relative to the magnitude of the true function but relative to a float32 unit-in-the-last-place (ULP) of the true function, a standard practice in when assessing the quality of a numerical approximation (see Section 4.3 for details). Because of this dependence on hardware and compiler, this should be seen as a case study specific to the settings we used, the *Skylake* CPU and the just-in-time compiler used by JAX [16] (details and version in Section 4.3).

While the search process uses approximations, these are accounted for when testing the final solutions. During the search, in addition to approximating the precision through a validation set " \mathcal{V} " as mentioned in the previous section, we also ignore potential double-rounding effects resulting from the limited precision of the ground truth. Again, this was to save time during the search, but the discovered programs maintain their high precision when tested thoroughly. Each final program is tested by exhaustively measuring the precision on a test set \mathcal{T} that contains all possible floating-point values. We also independently measure the speed multiple times again, as indicated in Section 4, to avoid any selection bias that may have taken place during the search. This is now possible because the final front contains only a handful of models with less than 1 ULP of error (i.e. precision above -1). We focus on this 1-ULP threshold because it is generally considered to be a reasonable error for high quality numerics [67]. Thus, we consider the top program to be the fastest with less than 1 ULP of error.

Figure 3 compares the best evolved solutions (orange points joined with lines) against strong baselines (isolated blue markers). The baselines included the minimax approach, which led to top results in the case of real-valued exponentials (Section 2.1). A difficulty with the standard (real-



Figure 3: The evolved float-valued programs surpass the baselines in our case study of the JAX just-in-time compiler and Skylake hardware architecture. The search process evolves code that manipulates the compiler so that it takes beneficial decisions. Each point denotes a discovered program; each line corresponds to one experiment; isolated points (blue) indicate baselines. Shaded area indicates $\pm 2SEM$. Vertical blue/orange lines mark the speed of the fastest baseline/evolved program with less than 1 unit-in-thelast-place (ULP) of error (*i.e.* precision p > -1). An ULP is the distance to the next largest floating-point number, therefore these programs are very precise. Precision was measured over all float32 numbers.

valued) minimax approach is that the coefficients obtained are optimized *real* numbers, yet we need floating-point numbers for standard numerical computations. Rounding the real coefficients is not generally the optimal choice within the floating-point lattice. This problem can be addressed with a lattice reduction method [8], which we used as a baseline to replace the "Polynomial/Minimax" points in this figure; the same method does not apply to rational functions so the "Rational/Minimax" baselines still use the standard method (optimizing at high precision and then rounding the coefficients). Taylor expansions and Padé approximants were included too due to their popularity. All rational base-



Figure 4: Discovered program for fast 2^x computation. This program has under 1 ULP of maximum relative float32 error. With default compiler settings it is more than 3 times faster than the baselines because it triggers a different compilation path.

lines were, again, represented as a ratio of polynomials, using only the one required division, which is the slowest operation for the hardware used. All polynomials, including the ones in those ratios, were represented in their Horner form; this has the advantage of allowing all their operations to be combined into fused multiply-adds (FMAs), giving the baselines the best possible speed with the given hardware.

Top evolved results are more than 3 times faster than top baselines (Figure 3), which illustrates the potential of this method in optimizing expressions for a given setup. The main reason for this enormous speedup is that evolution found a way to trigger a decision in the compiler that is normally not triggered for other representations of the exponential function. The operations present in the baseline function lead the XLA compiler to believe that it is relatively CPU-bound and so it is compiled in a manner that is optimized for parallel execution on multiple CPU cores. Conversely, the operations in the evolved function result in the XLA compiler deciding that the function is I/O bound and that parallel execution would not improve performance, resulting in the function being compiled for optimal singlethreaded performance. These decisions are made without knowledge of how the functions will be executed during evaluation. Since the evaluation measures single-threaded performance, the evolved function performs much better. More detail can be found in Supplementary Section S3. Writing an implementation of the exponential function by hand that ensures that the compiler decides it is CPU-bound would be impractical without intricate knowledge and understanding of the compiler's heuristics. Evolution, on the other hand, is able to overcome this obstacle naturally.

We found it surprising that the search process was able to find an expression that is almost floating-point-exact, while also remaining constrained to triggering the above compiler decision, which none of the baselines triggered. Figure 4 shows the discovered program. It is a novel representation of the exponential function. It is also particularly well tuned, as can be seen by performing small perturbations to its form. For example, the large speedup is lost by removing the multiplication by zero or rewriting the expression as a ratio of polynomials. From the high-level Python/JAX code, it is difficult to predict some of the changes that would cause speed degradation. For example, even though divisions tend to be more costly than multiplications, replacing the division in the top evolved program with a multiplication results in speed *losses*.

Perhaps surprisingly, even though the results are specific to the compiler and its settings, they turn out to be fairly transferable beyond the hardware in which they were evolved. Figure 5 shows that the improvements of the evolved functions over baselines are preserved when transferring to newer and older CPU architectures, spanning 10 years of hardware technology, including Intel and AMD processors. This is perhaps more a statement about the similarity of all these architectures rather than about the evolutionary search itself. Nevertheless, it may be of practical importance when applying our method in datacenters that are continuously being upgraded.

2.3. The Evolutionary Process

The dNSGA-II algorithm, just like NSGA-II and other multiobjective search methods [12], maintains a population of *individuals* (in our case, computer programs), so that the population's Pareto-front improves over time (Figure 6). In the process, we observe known effects such as convergent evolution, junk code, and bloat, which we briefly point out here.

Looking across different experiments in the previous section, with different evolutionary histories, we find some degree of *convergent evolution*. Similar features emerge, presumably



Figure 5: Transfer of discovered programs to other hardware platforms. Each point is an indepedent measurement of the ratio of the speed of the top evolved program to the top baseline, where "top" means "fastest with less than 1 ULP of error". Left-to-right: Skylake (used to search, 2015), Cascadelake (2019), Milan (2021), Rome (2019), Broadwell (2014), Haswell (2013).



Figure 6: Progress of the evolutionary search. Precision–speed Pareto fronts improve as the experiments advance; each line constitutes an average over 10 experiments.

because they are beneficial, such as code reuse (top program in 10 out of 10 experiments) and the use of a single division in the compiled program (top program in 9 of 10 experiments). Programs also accumulate "junk code" that gets compiled away during evaluation, like biological creatures accumulate so-called junk DNA that does not translate to proteins. An example found was a vertex V that is only used to compute V – V, so this vertex's upstream graph does not affect the compiled program (c_2 in Figure 4 arose this way). Overall, the evolutionary process led to high optimization but only where it mattered with regard to the imposed objectives.

Excessive code, known as *bloat* [4; 34], can accumulate in the way constants are represented during the evolutionary process. The excess code is not shown in Figures 2 or 4 for ease of readability. Supplementary Figure S2 shows the original *bloated* representation of the best evolved real-valued program: in it, for example, one of the constants (c_7) was represented by the evolutionary process as a 21-operation function of other constants. The values of constants like c_7 are independent of the program inputs, so the bloated code is removed by the compiler. Thus, these extra operations are irrelevant to the final program and do not affect timing measurements.

2.4. Other Transcendental Functions

In this section we will briefly demonstrate uses beyond the exponential. The exponential presented the challenge that it has strong baselines as it is a well-behaved function on which much research has been done. Yet, it also afforded some conveniences, which we will do without next.

The logarithm, unlike the exponential, presents the challenge that it vanishes at a finite value, resulting in difficulties when optimizing the relative error, yet we are able to find an approximation that seems to be more precise than the baselines. To emphasize the challenge, we seek a program to compute $\log_2(x)$ over float32 arithmetic on [1, 2), a domain which allows computing the logarithm on any other value through range reduction. Our approach can produce accurate results, within the conventional 1 ULP error limit (evaluated over all possible float32 values), even though the baseline methods we attempted never reached under 3 ULP. The choice of baselines required careful consideration of the definition of "error". Because we are measuring *relative* error, which becomes small when $\log_2(x) \approx 0$, baselines that have no error at x = 1 are reasonable. Taylor expansions and Padé approximants about x = 1 have this property; we considered increasing order until the float32 precision no longer improves. It is, however, possible to also include baselines that have small yet nonvanishing error near zero. This is because we are measuring the *floatingpoint* relative error, which has a denominator of ulp(loq(x)). This denominator is small but nonvanishing. As a result, we also attempt the Remez-based minimax method we used in previous sections. However, since that method optimizes the real-valued relative error, it does not handle the singularity at x = 0 well, so we regularize it by approximating on $x \in [1 + \epsilon, 2]$ as $\epsilon \to 0$. Still, it produced large errors. We highlight that in the case of the evolutionary approach, these detailed considerations were not needed.

Over real numbers, the relative error must vanish at the zeros of the function, which can pose additional difficulties. If there is only one zero, Taylor expansions and Padé approximants may be able to produce a finite error. Sometimes, however, these expansions converge slowly, a notorious example being that of the error function, erf about x = 0 for x > 1 [53], so we consider the domain $x \in [0, 2]$. Compared to these baselines, we find that the evolutionary method can produce relatively more compact functions with

reasonable precision. For example, with 5 operations, the most accurate program we discovered had an estimated precision of 2.3 (estimated using a test set \mathcal{T} with 1 million evenly spaced values). This is in comparison with a 1.5 estimated precision for the best Padé / Taylor approximation of the same complexity (Padé approximants for the error function have the lucky property of many vanishing terms, which is not the general case when approximating other functions). It is, however, slow to evolve functions with precision higher than \sim 3; the reason for this could be explored in future work.

Another challenge to rational approximation is posed by functions that are "wavy", like the Airy Ai function for negative values, where we find the evolutionary search finds compact and accurate programs. To avoid revisiting the issue of zeros, we displace the function vertically and seek for approximations to $f(x) = 1 + \operatorname{Ai}(-kx)$ on [0, 1], setting k = 7 to have roughly two oscillations (the value of k was chosen before running any search experiment). In this case, because the function does not vanish anywhere, it is preferable to distribute the error over the interval, so we compare against a Chebyshev approximation baseline. Even fairly complex programs can be evolved in this case. For example, the best 20-operations evolved program has an estimated precision of 4.7 (still using a test set \mathcal{T} with 1 million values), compared to 1.8 for the Chebyshev approximation of the same size, making the evolved function almost 3 orders of magnitude more accurate.

3. Discussion and Related Work

We have demonstrated that a simple evolutionary algorithm can discover mathematical functions that outperform handdesigns in two ways. First, we can find programs with very few operations that reach high precision over real numbers, providing a point of comparison with traditional mathematical expansions. Second, we can optimize precision and speed for a specific hardware and compiler. Throughout most of this paper, we optimized a well-studied function, the exponential, and compared it to many baselines. We then constructed scenarios that pose specific challenges involving the logarithm, the error function, and the Airy function. Now we put our results in context, discuss limitations, and suggest directions for future work.

3.1. Discovering New Mathematics

Recent work has discovered state-of-the-art mathematical algorithms for matrix multiplication [14] and sorting [36]. This was done by searching at scale using reinforcement learning (RL) over small-input problems (*e.g.* multiplying 4x4 matrices or sorting a 5-element array). In some cases, there exists a mechanism to generalize from the small *search input size* to a larger *target input size*. For example, in the

case of [14], the search-size multiplication can be used recursively to handle arbitrarily large target input sizes with beneficial scaling. The resulting matrix multiplication algorithm ends up being quite general, in spite of the discovery having been done in a limited search space and having only optimized the small-scale structure.

To the best of our knowledge, our work is the first to discover state-of-the-art mathematical algorithms through evolutionary search, though our method's discoveries are of a different kind from RL's findings above. Rather than searching at a small input size and having a mechanism for scaling the solution, we search directly at practical input sizes (e.g. 32-bits for floating-point values or 14 significant figures for real numbers-these are already useful for example in scientific computing and machine learning). Searching directly at the target input size allows the method to obtain gains from the large-scale structure of the solutions; in other words, as we evolve the entire program (and not a small component that gets composed iteratively), we can make arbitrary changes to the full program. Reaching higher precisions than 14 significant figures is in principle possible too, but would require utilizing data types that are more precise than float64 (we expect that some precision margin is required for the floating-point values to behave like real numbers). Our choice to carry out evolutionary computation was largely motivated by the simplicity of the method, but future work could explore if the RL approach can discover additional gains, find solutions faster, or generalize across input sizes.

Importantly, while we emphasized comparison against baselines, it should be noted that those baselines were handdesigned by human experts over time, whereas our method came up with its solutions in a fully automated fashion. Moreover, the automated method did this within a few days and reproducibly. The results included highly precise hardware-independent mathematical expressions. Thus, complex solutions that were previously unknown were discovered from scratch.

3.2. Relationship to Symbolic Regression Tasks

Our work is an example of *symbolic regression*, a task where a symbolic relationship has to be discovered automatically to fit given data. Symbolic regression has been used to find physics formulas by means of evolutionary computation [52; 32; 48; 66] or otherwise [9; 46; 49; 63; 7]. These studies demonstrate their respective approaches can parse simulated data to recover well-known important equations. Despite their success on complex systems (*e.g.* Navier-Stokes), symbolic regression has not been used to discover *previously unknown* physical laws, as far as we know. Using symbolic regression on true experimental data has only been used in very specialized situations [56; 29], where validating the

correctness of the discovered models is difficult. This may point to the challenges of analyzing true experimental data, which may require the regularizing nature of systematic thinking.

In contrast, our work does discover previously unknown symbolic relationships that we verified with mathematical proofs. We have achieved this by a strategic choice of task to solve: searching for programs to compute transcendental functions is well suited to symbolic regression. In particular, the task is defined in-silico, as opposed to "in nature" (*e.g.* discovering a physical law), so the simulated data and the real data are the same; there is no "reality gap" to bridge.

Previous studies have attempted the in-silico task of discovering arbitrary formulas from data, but the formulas were known ahead of time and the data was generated directly from them [64; 28; 41]. The formulas are toy expressions, sometimes belonging to an accepted benchmark, because the goal of the studies was to develop the search methodology. Future work could explore if the more sophisticated methods in those studies can apply to our task. In particular, it could be interesting to see how they fare against our simple method when applied at scale. It seems to be an open question whether evolutionary methods developed at small scales preserve their benefits at the larger scales available today.

3.3. Relationship to Program Discovery Methods

Our work uses genetic programming [27; 5; 55], and more generally, evolutionary computation [15; 20]. This field provides multiple algorithms but relatively little guidance as to their applicability [38]. Thus, we chose to use a simple method, staying as close as possible to existing techniques. We employed a direct encoding through compute graphs and evolved them via genetic programming, just as in the earliest versions of symbolic regression [27]. Selection was done through a variant of the classic NSGA-II algorithm of [12], as we needed to optimize two objectives. NSGA-II is a particularly popular multi-objective search algorithm, though there are others [68; 54]. Operating at datacenter scales required making adjustments to NSGA-II to enhance parallelizability, but we have kept the essential qualitative components (non-dominated sorting, crowding). The evaluation of each program involves a smaller search process to optimize the coefficients. This kind of two-level search approach is popular in some versions of symbolic regression [26; 25] and automated machine learning [21]. Using the Levenberg-Marquadt algorithm for coefficient optimization has been shown to be particularly effective [25], but we preferred to avoid differentiability assumptions that may not apply when optimizing over the floating-point lattice. Instead, we used the gradient-free CMA-ES method [19], making our setup purely evolutionary and free from prior

knowledge of numerics.

A related program discovery field is that of superoptimization [23; 3; 50], which aims at improving the speed of a program by searching through a space of related programs. In particular, [51] has demonstrated large speedups in floatingpoint programs, though at the cost of some precision. Unlike symbolic regression, superoptimization assumes that the correct program is known from the start. Thus, it requires writing out an expansion and optimizing its coefficients before engaging in the search process. In our work, we have focused on the discovery of the code from scratch, finding functions that exploit novel reusable expressions. Future work may explore to what extent benefits from both approaches may compound.

3.4. Immediate Cost, Long-term Gain, and Automation

The search process we present requires a large amount of compute, but its costs can be recovered in the long run if applied judiciously. The evolutionary run constitutes a one-time initial investment that produces the optimized program. Once found, the optimized program will yield gains in proportion to its use, relative to a less efficient program. For this strategy to be beneficial, it is therefore important to choose programs that are expected to be used frequently and to incur large costs, something that is easier done with an application in mind. Popular calculations (like the exponential) can satisfy this criterion, but so can very specific calculations that will be run repeatedly in a given setting. An example of the latter can be the search for a ground state of a cluster of atoms in molecular dynamics, where a pairwise energy potential must be applied over and over again in a supercomputer simulation. Thus, it would make sense to apply this method first to optimize the speed of the potential function on the supercomputer, and then run the simulation with the discovered function.

In time, compute generally becomes more available, so it makes sense to explore approaches that may be computelimited today [58]. It is also possible that method improvements result in much more efficient search processes, as it has happened in the related field of neural architecture search [31; 42].

Finally, it is also important to realize the advantages that we gain from this process: we are searching over the space of all rational functions, written in all possible ways—not just as a ratio of two complete polynomials—without requiring intervention from the user. It also allows, in principle, the incorporation of other instructions that the CPU can or will implement. Instructions might involve non-floating point types, such as bit shifts or integer operations; including these would require a typed version of the search space, which could be explored by future work. It is possible that range reduction algorithms may be discovered automatically

too, in ways similar to the recent automation of algorithm discovery for machine learning [44; 10; 24].

3.5. Freedom of Choice of Objectives

We expect that the approach presented can apply more generally than illustrated here because it has great freedom to choose the objectives of the search, a feature it derives from evolutionary computation. We have already illustrated this in the way we measured the speed objective, by timing the actual program. Alternatives that are more amenable to existing methods, such as a cost model based on the number of operations, proved inaccurate for estimating speed. Thus, the CPU provided a "black box" measurement for the speed objective. Similar freedom could be used for the precision objective, allowing many more potential applications. For example, we could search for the inverse f of a known function g by minimizing the error $|1 - g \circ f|$. As another example, we could search for the solution f to an ordinary differential equation $D(f)_{(x)} = 0$ by minimizing $\int_{x} |D(f)|(x)|$ (this error would be computed numerically during the evaluation process by applying the candidate program). Further, it should be possible to discover a program that simultaneously computes multiple functions that are often used together, such as sin and cos, noting that our method seems to produce programs that reuse intermediate expressions well (Section 2.3).

Many of the above situations cannot be handled by the baseline methods (*e.g.* the Remez algorithm or Pade approximants), which exhibit a larger "reality gap" as they cannot optimize speed or floating-point computation exactly. Out of all the baselines, the lattice reduction method goes the furthest in this direction in that it restricts the coefficients to the floating-point lattice [8; 11] but it cannot handle rounding in internal computations. Given the complexity of floating-point conventions, it seems we are far from a mathematical theory that can account for them, and even further from one that can account for all the intricacies of CPU architecture. On the other hand, evolutionary computation can address these issues today.

4. Methods

4.1. Target Functions and Their Domains

The main objective is to discover programs that compute a given *target function*, g(x). For the $g(x) = 2^x$ target function, we searched for an expression correct in the (0, 1]interval. This incurs no loss of generality because any input outside the interval can be quickly transformed to a corresponding input in [0, 1] using the standard process of *range reduction* (Method 1).

In addition to $g(x) = 2^x$, we also considered the following functions because of properties described in Section 2.4:

Method 1 Standard Range Reduction for $g(x) = 2^x$

input a floating-point value $x \in (-\infty, \infty)$. require a function $\tilde{g}(u)$ s.t. $\tilde{g}(u) = 2^x$ for $x \in [0, 1)$. require a function $\hat{g}(k)$ s.t. $\hat{g}(k) = 2^k$ for $k \in \mathbb{Z}$. output the value g(x). $\eta = \lfloor x \rfloor \quad \# \implies \eta \in \mathbb{Z}$ $\xi = x - \eta \quad \# \implies \xi \in [0, 1)$ return $\tilde{g}(\eta)\hat{g}(\xi)$

•
$$g(x) = log_2(x)$$
 on [1, 2);
• $g(x) = erf(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt$ on [0, 2]; and

•
$$g(x) = 1 + Ai(-kx)$$
 on [0, 1],

where Ai denotes the Airy function of the first kind.

We refer to these target functions as *real-valued* or *floating-point-valued* (or *float-valued* for short), depending on whether the domain intervals are considered subsets of the set of real numbers or the set of float32 numbers, respectively.

<u>Details:</u> The $g(x) = \log(x)$ target function can be rangereduced to the [1, 2) interval by a similar standard process. The other functions were introduced to illustrate specific points; we did not intend to cover the entire real / floating-point line.

4.2. Search Space

We search a space of restricted computer programs, represented as compute graphs, as is standard in genetic programming [27]. Thus, the space contains all possible directed acyclic graphs in principle, but we limited their size to 100 vertices to control execution time and memory use. One input vertex is required to represent the input to the function and we denote it by x. There is exactly one output vertex that we denote by f. Additional optional input vertices, denoted c_i , represent *coefficients*. These coefficients are free parameters optimized by a training process. All internal vertices represent instructions encoding the mathematical operations $\{+, -, \cdot, \div\}$. These set of operations was chosen for ease of comparison with real-valued approximations in traditional mathematical approaches, which have focused on the field of real numbers. For float-valued functions, the same subset makes sense as they are instructions natively available to the hardware; note even though the fused-multiply-add (FMA) instruction is not in the search space, it can still be emitted by the compiler by fusing $a \cdot \text{with } a +$. Such a restriction to 4 operations is not a hard requirement of our method, but is sufficient to find high quality code. The program graph in Figure 4 is an example. We highlight that searching for a computer program/graph is more appropriate than searching for a mathematical expression, as the graph can naturally encode the reuse of subgraphs (e.g. the "+" vertex with two out-edges in Figure 4). In figures, the order of arguments to an operation is determined by the top-to-bottom order of a vertex's in-edges. Finally, vertices are assigned

by the search process a fixed random integer *ordering parameter* (not shown in graph figures, but implicit in the code version), which resolves any ambiguities in the ordering of instructions, subordinate to the topological order of the graph.

4.3. Evaluation of Programs

Given a program (represented as a graph), we need to *evaluate* its quality. As shown in Method 2, we do this in two phases. The *training phase* translates the graph to a standard programming language by converting each of its vertices into JAX-NumPy operations (jnp.sum, jnp.multiply, *etc.*), which are packaged into a function. This function is then compiled with XLA [47] and its coefficients are optimized. After that, the *validation phase* binds the optimized coefficients, re-compiles the function, and measures its precision and speed, as outlined in Method 2. Because this evaluation process needs to be embedded in the search loop, we use Python/JAX as the programming language, which allows programmatically calling the compilation of arbitrary functions through its just-in-time (JIT) mechanism. This is a choice of convenience, not necessity.

Method 2 Program Evaluation for Float-valued Functions

input A graph representing a program with free coefficients $\{c_i\}$. require Static training (\mathcal{U}) and validation (\mathcal{V}) datasets. require A subroutine MRE that computes maximum relative error. output The input program's precision and speed. # Training phase: Pr(inputs, $\{c_i\}$) $\xleftarrow{}^{\text{translate to program}}$ graph Err($\{c_i\}$) $\xleftarrow{}^{\text{compile}}$ MRE(Pr(\mathcal{U} .inputs, $\{c_i\}$), \mathcal{U} .labels) $c_i^* = \operatorname{cma-es}(\text{Err}(\{c_i\}))$

Validation phase: PrValid(inputs) $\stackrel{\text{compile}}{\leftarrow}$ Pr(inputs, $\{c_i^*\}$) precision = -MRE(PrValid(\mathcal{V} .inputs), \mathcal{V} .labels) speed = 1/TimeExecution() return precision, speed

In the training phase, we optimize the coefficients of the program to maximize its precision. Precision is measured as the negative maximum relative error over a fixed set of inputs \mathcal{T} . For instance, in the (simplistic) case of training $f(x) = 1 + x \times (c_0 + x \times c_1)$ to (poorly) compute the target $g(x) = 2^x$, we would optimize c_0 and c_1 over $x \in \mathcal{T}$, where \mathcal{T} are evenly spaced values in [0, 1] (Section 4.1). The relative error is measured in one of two ways, depending on the type of target function. For real-valued target functions, we used the natural definition, |g(x) - f(x)|/|g(x)|. For float-valued functions, we used the standard approach: |q(x) - f(x)|/ulp(q(x)), where ulp(y) denotes one unit-in-the-last-place (ULP) of y. An ULP is defined as the distance to the closest larger value representable as a floating-point number. Altogether, for example, the precision of a program Pr representing a

float-valued target $g(x) = 2^x$ is:

$$p(\Pr) = 1 - \max_{x \in \mathcal{T}} \frac{|\Pr(x) - 2^x|}{\mathtt{ulp}(2^x)}$$

We used the CMA-ES method to train the coefficients. CMA-ES is an evolutionary algorithm; it keeps a population of candidate solutions which it improves iteratively by replacing it with a new population. In our case, each candidate is a vector of coefficients. The new population is a random gaussian perturbation with the mean of the previous population and a covariance matrix that is adapted to the distribution of the population [19].

In the validation phase, we measure the error again, but on a set \mathcal{V} with unseen examples, roughly 10 times as many as were used in \mathcal{T} . This helps reduce training overfitting. During validation, we also measure the *complexity* of the solution as a second objective for the search process. For real-valued functions, the complexity was defined as the number of operations. For float-valued functions, it was the *speed* of multiple evaluations in an embarrasingly parallel regime, optimizing for throughput. While a tweak of this process would have allowed measuring latency, we chose throughput with big-data applications in mind. Some precautions are necessary to get accurate timings. First, overheads must be sufficiently reduced, so instead of compiling a single execution of the f(x) program, we compile it to apply to a vector of all the numbers in \mathcal{V} . This is not enough, however, and so each input is acted upon by a stack of the form $f \circ q \circ f \circ q \dots$, where q is a clipping function to keep the values in range. Stacking ensures the optimizer does not compile away unused results. Finally, we must guard against interruptions by concurrent processes, as we are operating in a distributed environment with little control over task scheduling. For this, we perform many repeats of the timing measurement. Any measurement that is interrupted or must share the CPU should result in an overestimate of the timing. Thus, of all the repeats, the tightest approximation is the shortest measurement. A variant of this strategy is used in Python's timeit module.

Calculations were done using the float32 data type for float-valued functions and float64 for real-valued functions. The ground truth was computed in float80. For real values, the use of limited-precision types incurs a negligible amount of error, as demonstrated by the error bound proofs.

<u>Details</u>: The JAX version used was 0.4.11; the Jaxlib version was 0.4.11. All the lower level compilation was done by the XLA and LLVM included in Jaxlib. Version numbers could, in principle, be important to the float-valued speed results. T contains 10^3 evenly spaced values in the domains described in Section 4.1. Coefficients are initialized as $\pm 10^{-\alpha}$ where α is uniformly distributed in [0,8]; the sign up front has an even probability of being positive or negative. The coefficients are then trained with CMA-ES using a population size of 128, 10^4 generations, and the following early-stopping strategy: after the first 100 generations, if

the latest half of the generations did not result in any improvement in the maximum of the population, the training was stopped early. V contains 10^4 examples; they are allowed to overlap the training set because our training loss is the least error over the examples. For both training and validation, the ground truth for the labels is approximate as it was calculated in float80 and rounded to the experiment's precision; more thorough measurements were done to test the discovered functions (see Section 4.5). During the search process, JAX NumPy flushes subnormal numbers to zero; this could in principle affect float-valued results, but our testing of selected evolved functions accounted for this. For speed measurements, the vector of inputs has size 10000, the stack depth is 100, and the number of repeats is 1000.

4.4. Search Method

This section describes how candidate programs are obtained through discrete symbolic search. The *search method* constitutes an outer loop that produces new programs and calls the *evaluation method* of Section 4.3 to find the program's precision and speed. The precision and speed are then used as objectives to look for better programs, in the following way.

The symbolic search is carried out with another evolutionary algorithm, which we dub dNSGA-II, as it is our distributed variant of the popular NSGA-II approach [12]. As most evolutionary algorithms, NSGA-II maintains a population of P candidates, where P is the population size hyper-parameter. In our case, the candidates are the computer programs. The algorithm iterates on the population through alternating phases of *mutation* and *selection*. The mutation phase produces 2 P child programs by making random mutations to the existing *parent* programs. The selection phase, on the other hand, is common to all applications and is the key component of NSGA-II. It selects new parents from among the children by considering multiple optimization objectives. In our case, the objectives are the precision (r) and speed (s) of the programs. To do this, NSGA-II classifies the children into fronts in a process called non-dominated sorting. These fronts are disjoint subsets of the population with the property that elements within a front cannot dominate each other by this definition: program p_1 dominates p_2 iff p_1 is better than p_2 at one objective and no worse at all others; that is,

$$(r_{(p_1)} \ge r_{(p_2)} \land (s_{(p_1)} \ge s_{(p_2)}) \land (r_{(p_1)} > r_{(p_2)} \lor s_{(p_1)} > s_{(p_2)})$$

The first front contains all the programs not dominated by any other and is therefore the Pareto front of the population. The next front contains all the remaining programs not dominated by any other remaining program, and so on. The fronts are therefore ordered. NSGA-II will follow this order to select the top P programs as the next population. A difficulty arises in that the computational complexity of this process scales as P^2 , therefore becoming a bottleneck for large populations like the ones in our work.

To address the bottleneck, dNSGA-II recognizes that nondominated sorting works even on small samples of the population. This enables embedding the NSGA-II selection step in a fully distributed system, with some modifications. The result is that the non-distributed sorting procedure is now done by the workers instead of by a centralized server. Since the sample size is much smaller than P, this happens quickly. Moreover, these workers can now operate asynchronously, without imposing a selection semaphore that may result in idle workers and under-utilization of resources. The outline of the process is shown in Method 3. First, each worker receives a sample of 2 S programs from other workers. It then carries out the selection resulting in S parents. These are mutated to produce 2 S children, which are emitted for other workers to use. The sample is therefore treated analogously to a tournament in tournament selection approaches [18].

```
Method 3 dNSGA Outline
input a worker pool W of size W
input a sample size parameter S \ll W
output a set of W evolved programs.
   # We use Python notation for operations on lists:
   \# "+" = concatenate; "*" = repeat.
   parallel-for w \in W do async
     while w.is_running do
        if first iteration then
           # For the first generation, start from scratch.
           S = [1] * 2S # List of identity programs.
        else
           S = receive 2 S programs from random workers in \mathbb{W}
        end if
        \mathcal{P} = \texttt{SelectInStages}(\mathcal{S}) \# \texttt{Selects S parents from } \mathcal{S}.
        \mathcal{C} = [] # Generated children.
        for p in \mathcal{P} + \mathcal{P} do # Cycle through parents twice.
           C = C + [\texttt{MutateAndEvaluate}(p)]
        end for
        assert |\mathcal{C}| = 2 \, \mathrm{S}
        send C to other workers in \mathbb{W}
     end while
   end parallel-for
   return latest programs evaluated
```

In dNSGA-II, we also modified another aspect of NSGA-II's selection, a so-called *crowding* procedure used to favor programs so that the population remains evenly spread in precision–speed space. As explained above, parents are selected from the sorted fronts of the sample. This means that the best fronts will be kept, the worst lost, and one front in the middle may need to be split so that only some of its programs are kept. In order to decide which, NSGA-II ranks programs within this middle front according to their separation from their nearest neighbors. This procedure is fast but it discards information: we are picking the most spread out within the front but what we would really like is to maximize spread for the selected programs (including those from previously selected fronts and ignoring those in

the split front that we do not select). This information loss may in principle be more damaging in dNSGA-II, where we are using a small sample instead of the entire population. On the other hand, the small size of the sample means we do not need to worry about speed because the overall compute time is dominated by the program evaluations. Thus, we can afford a particularly trivial crowding selection criterion: when a front \mathcal{F} needs to be split, we select parents \mathcal{P} by removing programs from \mathcal{F} one at a time. To remove one program, the LeastCrowded method chooses the program that maximizes the minimum distance to all the programs already selected, \mathcal{P} , including those from previous fronts:

$$\texttt{LeastCrowded}(\mathcal{F}, \mathcal{P}) = \underset{\mathtt{Pr} \in \mathcal{F}}{\arg \max} \left(\min_{\mathtt{Pr'} \in \mathcal{P}} d(\mathtt{Pr}, \mathtt{Pr'}) \right)$$

where the distance d is the L^2 norm in precision–speed space, with appropriate non-dimensionalization. Other than simplicity, this criterion makes maximal use of the diversity information contained in the entire sample.

Another advantage of our modified crowding criterion is that it allows for selecting *in stages*, a way to emphasize particularly important areas of the search space. In the case of float-valued target functions, we care in particular about precisions above -1 ULP, so we use two stages: (1) we first select S/2 programs as indicated, but subject to the constraint that precision(Pr) > -1 ULP; (2) we select the remaining programs, to a total of S, in the same way but without the constraint. Note that stage (2) is necessary as there may not be any programs above -1 ULP. The details are shown in Method 4.

After being selected, a parent is mutated to produce a child through one of the random changes illustrated in Figure 7: (i) inserting a vertex by breaking an existing edge and connecting its inputs randomly while avoiding producing a cycle in the graph, (ii) deleting an existing vertex reconnecting its output to one of its inputs at random, or (iii) reconnecting an edge to a new input at random. Additionally, (iv) we may also do nothing. In all cases, the graph is afterward pruned to remove vertices that are no longer in the path from input (x) to output (f). Note that the first generation does not have any parents and so it is simply made up of identity programs; thus, we are starting the search "from scratch". Evaluation (Section 4.3) occurs right after the child is produced.

<u>Details</u>: $P = 10^4 = W$, where W is the number of distributed workers. Each worker runs on one core of a commodity CPU. While not required in principle, to match existing infrastructure, one machine was employed as a server that kept the last P programs provided by the workers; this server; in turn, passes the random samples to other workers on-demand. Experiments were stopped at one billion samples unless indicated otherwise. Selection: S = 20; crowding used raw ULPs and nanoseconds. Mutation: there was an even probability of making a change (mutations i–iii) or doing nothing (mutation iv); when making a change, there was an even probability of mutating the vertexes (mutations i

Method 4 dNSGA's SelectInStages Procedure (with NSGA-II components)

input a list S of candidates to select from

require a static list *stages* of configurations with parameters for each selection stage. Each stage sets the number of programs to select (stage.num_to_select) and a requirement on programs (stage.satisfies_requirement : $program \rightarrow bool$).

output a list \mathcal{P} of selected parents $[\mathcal{F}_i] = \text{NonDominatedSort}(\mathcal{S}) \# \text{Identical to NSGA-II.}$ $\mathcal{P} = [] \#$ Will contain selected parents. for stage in stages do i = 0 # Front index. # Like in NSGA-II, we start by selecting whole fronts. while $|\mathcal{P}| + |\mathcal{F}_i| < \texttt{stage.num_to_select} \mathbf{do}$ for p in \mathcal{F}_i do if stage.satisfies_requirement(p) then $\mathcal{F}_i = \mathcal{F}_i - \{p\}$ $\mathcal{P} = \mathcal{P} + \{p\}$ end if end for i = i + 1end while # Like in NSGA-II, we use crowding for the split front. while $|\mathcal{P}| < \texttt{stage.num_to_select} do$ $p = \texttt{LeastCrowded}(\mathcal{F}_i, \mathcal{P})$ if stage.satisfies_requirement(p) then $\mathcal{F}_i = \mathcal{F}_i - \{p\}$ $\mathcal{P} = \mathcal{P} + \{p\}$ end if end while end for assert $|\mathcal{P}| = S$ return \mathcal{P}



Figure 7: The mutations. Removals (blue) and additions (orange) are highlighted. " V_R " denotes a random preexisting vertex. "OR" indicates a random choice between edges.

or ii) or mutating an edge (mutation iii); when mutating a vertex, the probability of inserting (mutation i) was half the probability of deleting (mutation ii) so as to regularize the size of the graphs. When inserting a new vertex, the operation performed was randomly chosen from the four vertex operations $\{+, -, \times, \div\}$ or the insertion of a positively or negatively initialized coefficient, each with probability $\frac{1}{6}$. We did not tune these probabilities.

4.5. Testing Evolved Programs Against Baselines

Once the search is complete, we retrieve programs in the Pareto front of the final population and thoroughly assess their precision and, where applicable, their speed. We compare them against baselines, chosen from the following:

- **Polynomial/Taylor**: Horner-scheme Taylor expansions of order M (see below) about the middle of the interval (unless otherwise noted).
- **Rational/Pade**: Padé approximants of order (M,M) about the middle of the interval (unless otherwise noted), with Horner-scheme numerator and denominator.
- **Chebyshev**: Polynomial approximation of order M due to Chebyshev [59], where the coefficients were computed with numerical integration.
- C. Frac. / Euler: continued fractions due to Euler [13].
- C. Frac. / Gauss: continued fractions due to Gauss [17].
- C. Frac. / Macon: cont. fractions due to Macon [35].
- **Polynomial/Minimax**: Horner-scheme polynomials of order M. For the float-valued cases, the coefficients optimized with the Sollya library [11] by the lattice reduction method in [8]. For the real-valued cases, they were optimized in the same manner as the Rational/Minimax case below.
- **Rational/Minimax**: Ratios of order-M Horner scheme polynomials, with coefficients optimized with the *Mathematica* software suite [22] to mimize the real-valued maximum relative error. Mathematica carries out this optimization by first approximating the coefficients by fitting the rational function to a few points of the target function and then improving them with the Remez algorithm [45].

For each case, we use baselines with various M values. In the case of real-valued functions, we cover a wide range of precisions. In the case of float-values, we increase M until the results plateau.

To test the precision of programs and baselines, we use a tiered testing approach, placing more rigor on the verification of the top exponential programs while relying on approximations to compare most experiment results in bulk. For the best evolved real-valued exponential programs (Section 2.1), we prove upper bounds on the error (Section S2). For most bulk figure comparisons between real-valued evolved results and baselines (e.g. Sections 2.1 and 2.4), we measured the error over a test set \mathcal{T} that that is 1000 times larger than the validation set \mathcal{V} ; these should be reasonably tight lower bounds because the functions are well behaved. For our main float-valued results (Section 2.2), we were even more thorough, computing the error over all possible float32 values. For these experiments, we also verified that our results do not suffer from double rounding by repeating the precision testing with a ground truth that is not limited to float80 precision. Namely, we computed the ground truth with Taylor polynomials of order L using exact rational arithmetic and rounding the results to float32; this process was repeated iteratively while increasing L until the error did not change any more.

To test the speed of programs and baselines, we repeat 10

times the speed measurement described in Section 4.3. For special side-by-side comparisons between a handful of programs (*e.g.* Figures 5), we repeated the timing measurement 100 times in an interleaved manner. Relative speeds are measured with respect to the top baseline, where "top" is the fastest above 1 ULP, unless otherwise noted. When the ratio of two speeds is needed, multiple ratios were measured between consecutive timings in the interleaved measurement.

____ Details: To compute coefficients for the Polynomial/Minimax exponential baseline, we used the command: poly = fpminimax(2^xx,8,[|24...|],[0;1],relative);

To compute coefficients for the Rational/Minimax exponential baselines, we used the Mathematica command:

MiniMaxApproximation[2^x, x, 0, 1, M, M,

WorkingPrecision -> 100]

For other target functions, we proceeded in a similar manner, unless stated otherwise.

Author Contributions

ER led the project, mentoring MR, YC, CdS, MG, AV, and DHP. ER, MR, AV, MG, and DHP contributed to the methods. CdS and YC provided low-level programming expertise and assembly code analysis. MF contributed the error bound proofs. ER wrote the paper. EDK and QVL edited the paper and supported the project.

Acknowledgements

We would like to thank Daniel S. Fisher, Michael Brenner, Ben Laurie, Thomas Fischbacher, Rif A. Saurus, Matt Hoffman, and Kalyanmoy Deb for useful discussions; Sameer Agarwal and Rasmus Larsen for advice on numerics; Yingjie Miao, and Daiyi Peng for code contributions; and more generally the broader Google Research and Google DeepMind teams.

References

- [1] The XLA Authors. Openxla/xla. URL https://github.com/openxla/xla/blob/ 7a7cee6e31a01d0103c41b753c7e7fe6e0eeece8/ xla/service/cpu/parallel_task_ assignment.cc#L77, 2023.
- [2] The XLA Authors. Openxla/xla. URL https://github.com/openxla/xla/blob/ 7a7cee6e31a01d0103c41b753c7e7fe6e0eeece8/ xla/service/cpu/cpu_instruction_fusion. cc#L71,2023.
- [3] Sorav Bansal and Alex Aiken. Automatic generation of peephole superoptimizers. *ACM SIGARCH Computer Architecture News*, 2006.

- [4] Wolfgang Banzhaf and William B. Langdon. Some considerations on the reason for bloat. *Genetic Programming and Evolvable Machines*, 2002.
- [5] Wolfgang Banzhaf, Peter Nordin, Robert E Keller, and Frank D Francone. *Genetic programming: an introduction: on the automatic evolution of computer programs and its applications*. Morgan Kaufmann Publishers Inc., 1998.
- [6] Carl M Bender and Steven A Orszag. Advanced mathematical methods for scientists and engineers I: Asymptotic methods and perturbation theory. Springer Science & Business Media, 1999.
- [7] Luca Biggio, Tommaso Bendinelli, Alexander Neitz, Aurelien Lucchi, and Giambattista Parascandolo. Neural symbolic regression that scales. In *ICML*, 2021.
- [8] Nicolas Brisebarre and Sylvain Chevillard. Efficient polynomial l-approximations. In *ARITH*, 2007.
- [9] Steven L Brunton, Joshua L Proctor, and J Nathan Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *PNAS*, 2016.
- [10] Xiangning Chen, Chen Liang, Da Huang, Esteban Real, Kaiyuan Wang, Yao Liu, Hieu Pham, Xuanyi Dong, Thang Luong, Cho-Jui Hsieh, et al. Symbolic discovery of optimization algorithms. *arXiv*, 2023.
- [11] S. Chevillard, M. Joldeş, and C. Lauter. Sollya: An environment for the development of numerical codes. In *Mathematical Software - ICMS 2010*. Springer, 2010.
- [12] Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and TAMT Meyarivan. A fast and elitist multiobjective genetic algorithm: Nsga-ii. *IEEE transactions on evolutionary computation*, 2002.
- [13] Leonhard Euler. Introductio in analysin infinitorum, volume 2. Apud Marcum-Michaelem Bousquet & Socios, 1748.
- [14] Alhussein Fawzi, Matej Balog, Aja Huang, Thomas Hubert, Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Francisco J R Ruiz, Julian Schrittwieser, Grzegorz Swirszcz, et al. Discovering faster matrix multiplication algorithms with reinforcement learning. *Nature*, 2022.
- [15] Lawrence J Fogel, Alvin J Owens, and Michael J Walsh. Intelligent decision making through a simulation of evolution. *Behavioral science*, 1966.
- [16] Roy Frostig, Matthew James Johnson, and Chris Leary. Compiling machine learning programs via high-level tracing. *Systems for Machine Learning*, 2018.

- [17] Carl Friedrich Gauss. Disquisitiones generales circa seriem infinitam. 1813.
- [18] David E Goldberg and Kalyanmoy Deb. A comparative analysis of selection schemes used in genetic algorithms. *FOGA*, 1991.
- [19] Nikolaus Hansen and Andreas Ostermeier. Completely derandomized self-adaptation in evolution strategies. *Evolutionary computation*, 2001.
- [20] John H Holland. *Adaptation in natural and artificial systems*. MIT press, 1992.
- [21] Frank Hutter, Lars Kotthoff, and Joaquin Vanschoren. Automated machine learning: methods, systems, challenges. Springer Nature, 2019.
- [22] Wolfram Research, Inc. Mathematica, Version 12.0.0.0. Champaign, IL, 2023.
- [23] Rajeev Joshi, Greg Nelson, and Keith Randall. Denali: A goal-directed superoptimizer. ACM SIGPLAN Notices, 2002.
- [24] Stephen Kelly, Daniel S Park, Xingyou Song, Mitchell McIntire, Pranav Nashikkar, Ritam Guha, Wolfgang Banzhaf, Kalyanmoy Deb, Vishnu Naresh Boddeti, Jie Tan, et al. Discovering adaptable symbolic algorithms from scratch. *IROS*, 2023.
- [25] Michael Kommenda, Bogdan Burlacu, Gabriel Kronberger, and Michael Affenzeller. Parameter identification for symbolic regression using nonlinear least squares. *Genetic Programming and Evolvable Machines*, 2020.
- [26] Michael Kommenda, Gabriel Kronberger, Stephan Winkler, Michael Affenzeller, and Stefan Wagner. Effects of constant optimization by nonlinear least squares minimization in symbolic regression. In *GECCO*, 2013.
- [27] John R Koza and John R Koza. *Genetic programming:* on the programming of computers by means of natural selection. MIT press, 1992.
- [28] Matt J Kusner, Brooks Paige, and José Miguel Hernández-Lobato. Grammar variational autoencoder. In *ICML*, 2017.
- [29] William La Cava, Kourosh Danai, Lee Spector, Paul Fleming, Alan Wright, and Matthew Lackner. Automatic identification of wind turbine models using evolutionary multiobjective optimization. *Renewable Energy*, 2016.

- [30] William La Cava, Patryk Orzechowski, Bogdan Burlacu, Fabrício Olivetti de França, Marco Virgolin, Ying Jin, Michael Kommenda, and Jason H Moore. Contemporary symbolic regression methods and their relative performance. arXiv, 2021.
- [31] Hanxiao Liu, Karen Simonyan, and Yiming Yang. Darts: Differentiable architecture search. *ICLR*, 2019.
- [32] Zichao Long, Yiping Lu, Xianzhong Ma, and Bin Dong. Pde-net: Learning pdes from data. In *ICML*, 2018.
- [33] Ilya Loshchilov and Frank Hutter. Cma-es for hyperparameter optimization of deep neural networks. *arXiv*, 2016.
- [34] Sean Luke and Liviu Panait. A comparison of bloat control methods for genetic programming. *Evolutionary computation*, 2006.
- [35] Nathaniel Macon. On the computation of exponential and hyperbolic functions using continued fractions. *Journal of the ACM (JACM)*, 2(4):262–266, 1955.
- [36] Daniel J Mankowitz, Andrea Michi, Anton Zhernov, Marco Gelmi, Marco Selvi, Cosmin Paduraru, Edouard Leurent, Shariq Iqbal, Jean-Baptiste Lespiau, Alex Ahern, et al. Faster sorting algorithms discovered using deep reinforcement learning. *Nature*, 2023.
- [37] Jordan Ninin. Global optimization based on contractor programming: An overview of the ibex library. In Mathematical Aspects of Computer and Information Sciences: 6th International Conference, MACIS 2015, Berlin, Germany, November 11-13, 2015, Revised Selected Papers 6, pages 555–559. Springer, 2016.
- [38] Patryk Orzechowski, William La Cava, and Jason H Moore. Where are we now? a large benchmark study of recent symbolic regression methods. In *GECCO*, 2018.
- [39] Alexander M Ostrowski. On two problems in abstract algebra connected with horner's rule. In *Studies in Mathematics and Mechanics presented to Richard von Mises*. Academic Press San Diego, 1954.
- [40] V Ya Pan. Methods of computing values of polynomials. *Russian Mathematical Surveys*, 1966.
- [41] Brenden K Petersen, Mikel Landajuela, T Nathan Mundhenk, Claudio P Santiago, Soo K Kim, and Joanne T Kim. Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients. arXiv, 2019.

- [42] Hieu Pham, Melody Y Guan, Barret Zoph, Quoc V Le, and Jeff Dean. Efficient neural architecture search via parameter sharing. *ICML*, 2018.
- [43] Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V Le. Regularized evolution for image classifier architecture search. AAAI, 2019.
- [44] Esteban Real, Chen Liang, David So, and Quoc Le. Automl-zero: Evolving machine learning algorithms from scratch. In *ICML*, 2020.
- [45] E Ya Remez. Foundations of numerical methods of chebyshev approximation. *Kiev, Naukova dumka*, 1969.
- [46] Samuel H Rudy, Steven L Brunton, Joshua L Proctor, and J Nathan Kutz. Data-driven discovery of partial differential equations. *Science advances*, 2017.
- [47] Amit Sabne. Xla: Compiling machine learning for peak performance. 2020.
- [48] Subham Sahoo, Christoph Lampert, and Georg Martius. Learning equations for extrapolation and control. In *ICML*, 2018.
- [49] Hayden Schaeffer. Learning partial differential equations via data discovery and sparse optimization. *Proceedings of the Royal Society A*, 2017.
- [50] Eric Schkufza, Rahul Sharma, and Alex Aiken. Stochastic superoptimization. ACM SIGARCH Computer Architecture News, 2013.
- [51] Eric Schkufza, Rahul Sharma, and Alex Aiken. Stochastic optimization of floating-point programs with tunable precision. ACM SIGPLAN Notices, 2014.
- [52] Michael Schmidt and Hod Lipson. Distilling free-form natural laws from experimental data. *Science*, 2009.
- [53] Neil JA Sloane et al. The on-line encyclopedia of integer sequences, 2003.
- [54] Guido F Smits and Mark Kotanchek. Pareto-front exploitation in symbolic regression. 2005.
- [55] Lee Spector, William B Langdon, Una-May O'Reilly, and Peter J Angeline. Advances in genetic programming: volume 3. MIT Press, 1999.
- [56] Karolina Stanislawska, Krzysztof Krawiec, and Zbigniew W Kundzewicz. Modeling global temperature changes with genetic programming. *Computers & Mathematics with Applications*, 2012.
- [57] Vladimir Stegailov, Grigory Smirnov, and Vyacheslav Vecher. Vasp hits the memory wall: Processors efficiency comparison. *Concurrency and Computation: Practice and Experience*, 31(19):e5136, 2019.

- [58] Richard Sutton. The bitter lesson. *Incomplete Ideas* (*blog*), 2019.
- [59] P Tchébychev. Sur les questions de minima qui se rattechent a la raprésentation aproximative des fonctions. Imprimerie de l'Academie Impériale des Sciences, 1858.
- [60] The XLA team. Xla tensorflow, compiled, 2017. [Online; accessed 13-December-2023].
- [61] Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *IROS*, 2012.
- [62] Warwick Tucker. *Validated numerics: a short introduction to rigorous computations*. Princeton University Press, 2011.
- [63] Silviu-Marian Udrescu and Max Tegmark. Ai feynman: A physics-inspired method for symbolic regression. *Science Advances*, 2020.
- [64] Nguyen Quang Uy, Nguyen Xuan Hoai, Michael O'Neill, Robert I McKay, and Edgar Galván-López. Semantically-based crossover in genetic programming: application to real-valued symbolic regression. *Genetic Programming and Evolvable Machines*, 2011.
- [65] Arthur F Voter. Introduction to the kinetic monte carlo method. In *Radiation effects in solids*. Springer, 2007.
- [66] Yiqun Wang, Nicholas Wagner, and James M Rondinelli. Symbolic regression in materials science. *MRS Communications*, 2019.
- [67] Wikipedia contributors. Unit in the last place Wikipedia, the free encyclopedia, 2023. [Online; accessed 26-July-2023].
- [68] Eckart Zitzler, Marco Laumanns, and Lothar Thiele. Spea2: Improving the strength pareto evolutionary algorithm. 2001.
- [69] Dan Zuras, Mike Cowlishaw, Alex Aiken, Matthew Applegate, David Bailey, Steve Bass, Dileep Bhandarkar, Mahesh Bhat, David Bindel, Sylvie Boldo, et al. Ieee standard for floating-point arithmetic. *IEEE Std*, 754, 2008.

AutoNumerics-Zero: Automated Discovery of State-of-the-Art Mathematical Functions

Supplementary Material

S1. Discovered Programs

Supplementary Figure S1 contains all the real-valued evolved programs referred to in Figure 1 in Section 2.1. The constants (c_i) in the programs shown have been simplified, as the evolutionary process often represented them as complicated operations on other constants, which then the compiler collapses. For example, evolution may construct a constant c_3 in the following *bloated* form:

 $c_1 = 0.25$

 $c_2 = 0.5$

 $c_3 = c_1 * c_2$

In the figure, we would represent this constant in its *collapsed* form:

 $c_3 = 0.125$

Figure S2 shows the bloated and collapsed forms for the 10-operations program of Figure 2 and Supplementary Figure S1.

S2. Correctness Proofs

In Section S1, we provided nine real-valued evolved programs that approximate the exponential function 2^x , spanning the range between 2 and 10 operations. In this section, we prove that they are well-defined and we prove upper bounds on their real-valued maximum relative error. Because of the range reduction method (Section 4.1), it suffices to focus on the [0, 1] interval.

During the evolutionary process, the programs were only sampled at a finite subset of [0, 1] (the validation set " \mathcal{V} " in Section 4.3). Thus, the search does not guarantee that the functions represented by these programs are defined or well-behaved in all of [0, 1]. By construction, the functions are rational and thus they must be piecewise differentiable, yet they could have poles. Given a discovered function f, however, we can attempt to prove post-hoc that it does not have poles, as follows. First we rewrite the f as a ratio of two polynomials (this is always possible for a finite composition of real field operations). Then we attempt to bound the denominator away from zero by using an automated interval arithmetic proof (similar to the one described below for bounding the error of f, so we skip the details here). If the automated proof succeeds, then the f must be defined and differentiable on [0, 1]. The automated proof turns out to succeed for all the functions f2 to f10.

As the evolved programs represent differentiable functions, we can use interval arithmetic techniques to automatically construct the proofs. We chose the IBEX library to do the necessary calculations [37]. In outline, we construct a proof by iteratively splitting the [0, 1] interval and proving loose error bounds on subintervals. As the subintervals get smaller, so do their respective error bounds. The global bound is the maximum of all the subinterval bounds; thus, with more subdivisions, the global bound becomes tighter. In other words, we use the smallness of the subintervals to compensate for the looseness in their bounds.

In more detail, consider an evolved function $f: [0,1] \to \mathbb{R}$ for which we want to prove an error bound. Let $r: [0,1] \to \mathbb{R}$ be the relative error function w.r.t. the true exponential:

$$r(x) = \frac{f(x) - 2^x}{2^x}$$

We wish to prove a tight error bound ε on r over [0, 1]

For a given subinterval $[a, b] \subseteq [0, 1]$, we wish to establish a loose bound $\eta([a, b])$ for f over [a, b]. To do this, we first establish a Lipschitz bound L on the derivative, such that for all $x \in [a, b]$ we have $|f'(x)| \leq L$. This can be done by using interval arithmetic techniques:

$$L = \mathcal{UB}\left(\left|f'([a, b])\right|\right) \tag{1}$$

where \mathcal{UB} denotes the upper bound. We highlight that in Equation 1, all the operations are of the interval arithmetic kind; that is, given an interval I, the expression g(I) represents a new interval J satisfying $J \supseteq g(s) | \forall s \in I$. Interval arithmetic therefore gives us a method for *computing* L from f. More details can be found in [62].

Given the bound L on the derivative, we can apply the mean value theorem to deduce that for all x, y in [a, b] there is a c, such that

$$|f(x) - f(y)| = |f'(c)| \cdot |x - y| \le L|x - y|$$

In particular, let m be the midpoint: $m = \frac{a+b}{2}$. The above

implies that for all x in [a, b]:

$$|f(x) - f(m)| \le \frac{L|b-a|}{2}$$

This establishes that f(x) cannot deviate significantly from f(m) as the interval [a, b] becomes small. In fact, f(x) must lie within the interval $f([x, x]) + [-L, L] \cdot (b - a)/2$. In other words, using interval arithmetic notation:

$$\eta([a,b]) = \mathcal{UB}\left(\left|f([x,x]) + [-L,L] \cdot \frac{b-a}{2}\right|\right)$$

To prove a given error bound ε over the entire [0, 1] interval, we proceed as follows. First we calculate the upper bound η with the method described above. If $\eta \leq \varepsilon$, we are done. If $\eta > \varepsilon$, we subdivide the interval into two equal parts and apply the method recursively. If the method terminates, we have proven the error bound ε .

Using the method just described, we prove the bounds listed in Supplementary Table S1, confirming the results of Figure 1 in the main text.

Function	Error Bound
f2	0.0415
f3	0.00123
f4	0.0003072
f5	$6.372 imes 10^{-6}$
f6	4.016×10^{-7}
f7	8.417×10^{-10}
f8	1.360×10^{-11}
f9	2.15×10^{-13}
f10	5.40×10^{-15}

Table S1: Proven error bounds on evolved real-valued 2^x approximations. Each line corresponds to one of the programs in Figure S1 and to an "evolved" point in Figure 1.

S3. Speed of Evolved Float-Valued Program

In Section 2.2, we outlined the reason why the top evolved float-valued program is faster than all the baselines by a significant amount; here we provide additional detail. The cause of the relative speedups shown in Figure 3 is that the compiled baseline functions are routed by the compiler through a *parallel task assigner* dispatch function before reaching the actual computation of the exponential function. This adds significant overhead including function calls to the otherwise-simple exponential computation, dramatically reducing performance. In the version of the XLA compiler used here, the reason for this routing is a decision made in the *CPU Parallel Task Assigner* pass of the High Level Optimizer (HLO), which determines whether or not this dispatcher is added for each *fused computation* present in the function prior to this optimization pass. Fused computations are groups of operations that the compiler believes can be executed efficiently together in common loops [60]. The decision is made primarily based on the number of operations the fused computation contains in the HLO Intermediate Representation (IR) [1]. It also considers the number of bytes the fused computation processes, but that number is constant for all exponential function implementations that we evaluated. The grouping of HLO operations into fused computations is handled by the prior Fusion HLO pass, which decides whether groups of operations are fusable or not based on a series of heuristics [2]. Examining the intermediate HLO IR immediately prior to the CPU Parallel Task Assigner shows that the baseline has a single, long fused computation, but the evolved function's operations are split into two separate fused computations. Since the CPU Parallel Task Assigner pass operates at the fused computation level and not the full function level, it appears that the evolved function's computations have fewer operations (each), leading to the conclusion that the function is I/O-bound and should not be compiled for parallelization. Without the need for parallelization, the calls to the evolved function are not routed through the *parallel task assigner* dispatch function. With the baseline's longer fused computation, the conclusion is that the function is CPU-bound and therefore should be compiled with routing through the dispatch function. This behavior of performance being dramatically different according to complex compiler heuristics is difficult to predict when writing high-level code; on the other hand, the evolutionary process can optimize it without requiring any specific understanding of these issues.

<pre>def f2(x): c1 = -2.1258595374472384 c2 = -2.0413845597733418 x1 = c2 + x x2 = c1 / x1 return x2</pre>	<pre>def f3(x): c1 = -8.387819235563974 c2 = 1.4427239805682266 c3 = -3.4355225277901402 x1 = c3 + x x2 = c1 / x1 x3 = x2 - c2 return x3</pre>	<pre>def f4(x): c1 = -13.889185227358549 c2 = -6.3103598040432605 x1 = c2 + x c3 = 1.2011665727304095 x2 = c1 / x1 x3 = x2 - c3 x4 = x3 * x3 return x4</pre>
<pre>def f5(x): c1 = 25.596749740144819 c2 = 17.746150088734609 x1 = c1 / x c3 = -0.99999366143081858 c4 = -8.8505996518073289 x2 = x + x1 x3 = c4 + x2 x4 = c2 / x3 x5 = x4 - c3 return x5</pre>	, def f6(x): c1 = 34.839796464204852 c2 = -17.414314151974395 c3 = 100.52501140663516 x1 = c3 / x x2 = x + x1 x3 = c2 + x2 x4 = c1 / x3 c4 = -0.99999980025884683 x5 = x4 - c4 x6 = x5 * x5 return x6	<pre>def f7(x): c0 = -31.36503547149854 c1 = 237.4188094069423 c2 = 62.73011283808836 c3 = -0.9999999991613342 c4 = 90.500418999822784 x1 = c4 / x x2 = x + x1 x3 = c1 / x2 x4 = x3 + x2 x5 = c0 + x4 x6 = c2 / x5 x7 = x6 - c3 return x7</pre>
<pre>def f8(x): c1 = 947.16279416218413 c2 = -62.660057097633249 c3 = 361.59742194279426 x1 = c3 / x x2 = x + x1 x3 = 125.32011684077629 x4 = -0.9999999999334788 x5 = c1 / x2 x9 = x5 + x2 x6 = c2 + x9 x7 = x3 / x6 x8 = x7 - x4 x9 = x8 * x8 return x9</pre>	<pre>def f9(x): c1 = -125.28498998901401 c2 = 3786.1251186399709 c3 = -250.56998014383566 c4 = 1445.9842709817003 c5 = 0.99999999999994771 x1 = c4 / x x2 = x + x1 x3 = c2 / x2 x4 = x3 + x2 x5 = c1 + x4 x6 = c3 / x5 x7 = x6 - c5 x8 = x7 * x7 x9 = x8 * x8 return x9</pre>	def f10(x): c1 = 15141.981176922711 c2 = -250.55247494972059 c3 = 5783.5330096027765 c4 = 501.10494991027866 c5 = -0.999999999999999956 x1 = c3 / x x2 = x + x1 x3 = c1 / x2 x4 = x3 + x2 x5 = c2 + x4 x6 = c4 / x5 x7 = x6 - c5 x8 = x7 * x7 x9 = x8 * x8 x10 = x9 * x9 return x10

Figure S1: Discovered programs for real-valued 2^x computation, each using a different number of operations. "def fN(x)" defines the best program found that uses only N operations.

def f(x): b0 = 11296.180728464591 b1 = 0.00042576624350743454b2 = 11.541560327109721b3 = b2 + b2b4 = -0.499999999891864c5 = -0.9999999999999996b5 = b3 * b2b6 = b5 * b3b7 = b6 * b4b8 = b6 + b3b9 = b8 * b1b10 = b4 - b9b11 = b9 + b10b12 = b11 * b0b13 = c5 + b12 b14 = b13 / b8 b15 = b14 / b5 b16 = b2 / b15b17 = b16 - b16b18 = b17 / b7b19 = b6 + b11b20 = b19 - b17b20 = b10 = b17b21 = b20 + b12b22 = b21 + b18c4 = b1 + b22c2 = c4 * b4c3 = c4 * b2x1 = c3 / x $x^2 = x + x^1$ $b^{23} = b^1 * c^3$ $c^1 = b^{19} * b^{23}$ x3 = c1 / x2x4 = x3 + x2x5 = c2 + x4x6 = c4 / x5x7 = x6 - c5x8 = x7 * x7x9 = x8 * x8x10 = x9 * x9return x10

def f(x): c1 = 15141.981176922711 c2 = -250.55247494972059 c3 = 5783.5330096027765 c4 = 501.10494991027866 c5 = -0.9999999999999999960 x1 = c3 / x x2 = x + x1 x3 = c1 / x2 x4 = x3 + x2 x5 = c2 + x4 x6 = c4 / x5 x7 = x6 - c5 x8 = x7 * x7 x9 = x8 * x8 x10 = x9 * x9return x10

Figure S2: Bloated (left) and collapsed (right) versions of the evolved 10-operation real-valued exponential program.