Stratified distance space improves the efficiency of sequential samplers for approximate Bayesian computation

Henri Pesonen^{1,*} and Jukka Corander^{2,3,4}

 ¹Oslo Center for Biostatistics and Epidemiology, Oslo University Hospital, Oslo, Norway
 ²Department of Biostatistics, University of Oslo, Oslo, Norway
 ³Parasites and Microbes, Wellcome Sanger Institute, Hinxton, Cambridgeshire, UK
 ⁴Helsinki Institute for Information Technology HIIT, Department of Mathematics and Statistics, University of Helsinki Helsinki, Finland
 *Corresponding author: henri.e.pesonen@medisin.uio.no

Abstract

Approximate Bayesian computation (ABC) methods are standard tools for inferring parameters of complex models when the likelihood function is analytically intractable. A popular approach to improving the poor acceptance rate of the basic rejection sampling ABC algorithm is to use sequential Monte Carlo (ABC SMC) to produce a sequence of proposal distributions adapting towards the posterior, instead of generating values from the prior distribution of the model parameters. Proposal distribution for the subsequent iteration is typically obtained from a weighted set of samples, often called particles, of the current iteration of this sequence. Current methods for constructing these proposal distributions treat all the particles equivalently, regardless of the corresponding value generated by the sampler, which may lead to inefficiency when propagating the information across iterations of the algorithm. To improve sampler efficiency, we introduce a modified approach called stratified distance ABC SMC. Our algorithm stratifies particles based on their distance between the corresponding synthetic and observed data, and then constructs distinct proposal distributions for all the strata. Taking into account the distribution of distances across the particle space leads to substantially improved acceptance rate of the rejection sampling. We further show that efficiency can be gained by introducing a novel stopping rule for the sequential process based on the stratified posterior samples and demonstrate these advances by several examples.

Keywords— Approximate Bayesian Computation, Importance Sampling, Likelihood-free inference, Sequential Monte Carlo

1 Introduction

Likelihood-free inference (LFI) methods have become standard tools for statistical inference when the likelihood functions are not available in closed form but we are able to simulate from the model given permissible parameter values of our choice [Cranmer et al., 2020]. Simulation-based inference is geared to be one of the cornerstones of many intelligence-based systems [Lavin et al., 2021]. Approximate Bayesian computation (ABC) methods were within the first LFI methods and even the most basic rejection sampling ABC method can arguably still be relevant due to its simplicity and easy applicability when forward simulation from a model is possible [Pritchard et al., 1999, Beaumont et al., 2002, Tanaka et al., 2006]. ABC methods continue to be actively developed and its advanced extensions are being successfully used in new applications as LFI is gaining popularity in different research fields [Sisson et al., 2018, Lintusaari et al., 2017, Martin et al., 2021, Pesonen et al., 2022, Engebretsen et al., 2023].

Within the first extensions of ABC methods were sequential Monte Carlo ABC methods [Sisson et al., 2007, Toni et al., 2009, Moral et al., 2012]. They improve on the efficiency of rejection sampling based ABC methods by introducing a sequence of importance sampling distributions to improve acceptance rate of the proposed simulated samples. ABC SMC methods are actively developed and many proposals have been made to improve the accuracy and efficiency [Silk et al., 2013, Filippi et al., 2013, Bonassi and West, 2015, Simola et al., 2020]. Diverging from the sampling based ABC methods, synthetic likelihood (SL) methods [Wood, 2010, Price et al., 2018] directly find an estimate for the unknown likelihood function using a set of simulated samples. The development of both approaches, ABC and SL have been accelerated by the introduction of powerful machine learning techniques. Gutmann and Corander [2016] introduced an efficient Bayesian optimisation-based approach Bayesian optimisation for likelihood-free inference (BOLFI) to find a surrogate for the discrepancy metric as a function of the unknown parameters. Lueckmann et al. [2018], Papamakarios et al. [2019] introduced neural network-based flexible models that can be used as a surrogates for the likelihood function or directly for the posterior distribution.

In this study we introduce a new variant to the ABC SMC methods where we use the partitioning of the ABC acceptance regions to find better proposal distributions for the importance sampling and improve the posterior approximation. In Section 2 we discuss ABC SMC methods and present the theory for optimal selection of particular type of propagation distributions. We present the new inference methodology in Section 3 with a novel early stopping rule in Section 4. In Section 5 we present the results of the numerical experiments and conclude the article with discussion in Section 6.

2 Overview of ABC SMC methods

ABC methods are based on approximations to the underlying models that enable us to draw a sample from an approximation to posterior distribution $p(\theta \mid y^{\text{obs}})$. Instead of using the likelihood we draw a joint sample of the parameters θ_i (called particles) and observations y_i using the prior $p(\theta)$ and the simulator model $f(y \mid \theta)$ and retain N tuples (θ_i, y_i, w_i) where the simulated observation is sufficiently similar to the actual observation y^{obs} . Similarity is determined via a discrepancy measure $\rho(y, y^{\text{obs}})$ and an error tolerance threshold ϵ . Discrepancy measure and the threshold define an *ABC acceptance region* of simulated observations in the observation space. We define $\epsilon_0 := 0$, ABC acceptance region as $\Omega_{[\epsilon_a, \epsilon_b]} := \{y : \epsilon_a \le \rho(y, y^{\text{obs}}) < \epsilon_b\}$ and the ABC posterior as

$$p(\theta \mid y^{\text{obs}}) \approx p\left(\theta \mid y \in \Omega_{[0,\epsilon)}\right) = \frac{p(y \in \Omega_{[0,\epsilon)} \mid \theta) p(\theta)}{\int p(y \in \Omega_{[0,\epsilon)} \mid \theta) p(\theta) \mathsf{d}\theta}.$$
(1)

The proxy for the likelihood is

$$p(y \in \Omega_{[0,\epsilon)} \mid \theta) = \int f(y \mid \theta) \mathbb{I}\left(y \in \Omega_{[0,\epsilon)}\right) \mathsf{d}y,\tag{2}$$

where $\mathbb{I}(\cdot)$ is the indicator function. Often we use summary statistics S(y) and $S(y^{obs})$ instead of the original data, but here we assume that data can be either the non-transformed or summarised and will not consider the information loss related to the transformation.

This basic ABC method is referred to as the *rejection ABC*. Arguably the main problem with it is the potentially poor acceptance rate associated with reasonable thresholds ϵ which is generally caused by the use of prior as a proposal distribution. To make ABC algorithm more efficient, importance sampling based sequential Monte Carlo ABC (ABC SMC) techniques were introduced to produce a sequentially improving set of proposal distributions. To improve the ABC posterior, the algorithm uses a decreasing sequence of acceptance thresholds $\epsilon_1, \ldots, \epsilon_T$ and random walk proposal kernels $K_t(\theta^{(t+1)} \mid \theta^{(t)})$. Kernels are used to propagate a set of weighted samples $\left\{\left(\theta_i^{(t)}, w_i^{(t)}, y_i^{(t)}\right)\right\}_{i=1}^N$ that represent the current posterior distribution at iteration t to t + 1. The ABC posterior sample of the current iteration t is often used to set the parameters of the kernel. Although other choices are possible, most often the kernels are zero-centered Gaussian distributions where the covariance matrices Σ_t are empirically calculated from a set of weighted ABC posterior samples

$$K_t(\theta^{(t+1)} \mid \theta^{(t)}) = \operatorname{Normal}\left(\theta^{(t+1)} \mid \theta^{(t)}, \Sigma_t\right).$$
(3)

The ABC SMC joint proposal distribution for the transformation $t \rightarrow t + 1$ is of the form

$$q_t\left(\theta^{(t)},\theta^{(t+1)}\right) = \frac{p\left(\theta^{(t)} \mid y \in \Omega_{[0,\epsilon_t)}\right) K_t(\theta^{(t+1)} \mid \theta^{(t)}) \int f(y \mid \theta^{(t+1)}) \mathbb{I}\left(y \in \Omega_{[0,\epsilon_{t+1})}\right) \mathrm{d}y}{\int \int p\left(\theta^{(t)} \mid y \in \Omega_{[0,\epsilon_t)}\right) K_t(\theta^{(t+1)} \mid \theta^{(t)}) \int f(y \mid \theta^{(t+1)}) \mathbb{I}\left(y \in \Omega_{[0,\epsilon_{t+1})}\right) \mathrm{d}y \mathrm{d}\theta^{(t+1)} \mathrm{d}\theta^{(t)}}.$$
(4)

Filippi et al. [2013] derived an optimal Gaussian kernel (3) by minimizing the Kullback-Leibler (KL) discrepancy between (4) and

$$q_t'\left(\theta^{(t)}, \theta^{(t+1)}\right) = p\left(\theta^{(t)} \mid y \in \Omega_{[0,\epsilon_t)}\right) p\left(\theta^{(t+1)} \mid y \in \Omega_{[0,\epsilon_{t+1})}\right),\tag{5}$$

that is defined as

$$D_{\mathrm{KL}}\left(q_{t}||q_{t}'\right) = \int \int \log\left(\frac{q_{t}'\left(\theta^{(t)}, \theta^{(t+1)}\right)}{q_{t}\left(\theta^{(t)}, \theta^{(t+1)}\right)}\right) q_{t}'\left(\theta^{(t)}, \theta^{(t+1)}\right) \mathsf{d}\theta^{(t)} \mathsf{d}\theta^{(t+1)}.$$
(6)

Given the assumptions (3) and (5) we can derive an optimal covariance for the gaussian kernel

$$\Sigma^{(t)} = \int \int (\theta^{(t)} - \theta^{(t+1)}) (\theta^{(t)} - \theta^{(t+1)})^T p\left(\theta^{(t)} \mid y \in \Omega_{[0,\epsilon_t)}\right) p\left(\theta^{(t+1)} \mid y \in \Omega_{[0,\epsilon_{t+1})}\right) \mathsf{d}\theta^{(t)} \mathsf{d}\theta^{(t+1)},\tag{7}$$

that can be approximated using the ABC posterior sample by applying the threshold ϵ_{t+1} to select a re-weighted N' sized subset of it to represent $p\left(\theta^{(t+1)} \mid y \in \Omega_{[0,\epsilon_{t+1})}\right)$

$$\left\{ \left(\theta_{I(i)}^{(t+1)}, \widetilde{w}_{I(i)}^{(t+1)}, y_{I(i)}^{(t+1)}\right) \right\}_{i=1}^{N'} = \left\{ \left(\theta_{I(i)}^{(t)}, \frac{w_{I(i)}^{(t)}}{\sum_{j=1}^{N'} w_{I(j)}^{(t)}}, y_{I(i)}^{(t)}\right) : y_{I(i)} \in \Omega_{\left[0,\epsilon_{t+1}\right)} \right\}_{i=1}^{N'}.$$

$$\tag{8}$$

After obtaining the random walk proposal, we use it to generate candidates θ' by propagating randomly selected particles $\theta_i^{(t)}$ with sampling probabilities $w_i^{(t)}$ from ABC posterior using the kernel $\theta' \sim K_t \left(\theta^{(t+1)} | \theta_i^{(t)} \right)$ and generating new synthetic observations $y' \sim p(y \mid \theta')$. The new synthetic data are then compared against the observed data to determine whether or not it is within the acceptance regions of the next iteration $y' \in \Omega_{[0,\epsilon_{t+1})}$ and the sampling is repeated until a sample set of size N is obtained. The re-weighting follows the general importance sampling procedure

$$w_i^{(t+1)} \propto \frac{p\left(\theta_i^{(t+1)}\right)}{\sum_{j=1}^N w_j^{(t)} K_t\left(\theta_i^{(t+1)} | \theta_j^{(t)}\right)},\tag{9}$$

where the importance sampling distribution $\sum_{j=1}^{N} w_j^{(t)} K_t \left(\theta^{(t+1)} | \theta_j^{(t)} \right)$ is empirically estimated from the weighted sample as a Gaussian mixture.

Filippi et al. [2013] introduced a locally optimal Gaussian kernel with analogous covariance to (7) by optimising for the covariance for each particle $\theta_i^{(t)}$ separately, i.e. setting effectively $p\left(\theta \mid y \in \Omega_{[0,\epsilon_t)}\right) = \delta(\theta - \theta_i^{(t)})$, where $\delta(\cdot)$ is the delta function. This leads to a kernel covariance

$$\Sigma_i^{(t)} = \int (\theta_i^{(t)} - \theta^{(t+1)}) p\left(\theta^{(t+1)} \mid y \in \Omega_{\left[0, \epsilon_{t+1}\right]}\right) \mathsf{d}\theta^{(t+1)},\tag{10}$$

which can again be approximated based on the sample (8).

Stratified sampling ABC SMC 3

In most cases ABC SMC is superior to the basic rejection ABC algorithm, especially when the prior distribution of the parameters is far off from the posterior distribution. There are multiple approaches for improving the standard ABC SMC, by choosing different proposal and target distributions, determining the threshold sequence adaptively or setting rules for stopping the sequential process. Especially in the early iterations of the algorithm, the kernels calculated empirically from the data can have large scale parameters which in turn can result in slower convergence to the approximate posterior distribution that is within our tolerance of error. We can investigate ABC SMC more closely by looking at how the particles are accepted and how the weights for the particles are being formed. At tth iteration, ABC posterior sample approximation is $\left\{\left(\theta_{i}^{(t)}, w_{i}^{(t)}, y_{i}^{(t)}\right)\right\}_{i=1}^{N}$. By using ABC SMC algorithm that was described in Section 2, the posterior approximation at $(t+1) \text{th iteration will be } \left\{ \left(\theta_i^{(t+1)}, w_i^{(t+1)}, y_i^{(t+1)} \right) \right\}_{i=1}^{N_{\text{tot}}}, \text{ where } \theta_i^{(t+1)} \stackrel{\text{i.i.d}}{\sim} \sum_{j=1}^N w_j^{(t)} K_t(\theta^{(t+1)} \mid \theta_j^{(t)}), N_{\text{tot}} \ge N \text{ is the total} \right\}_{i=1}^{N_{\text{tot}}}$

number of simulated samples, and

$$w_{i}^{(t+1)} \propto \begin{cases} \frac{p(\theta_{i}^{(t+1)})}{\sum_{j=1}^{N} w_{j}^{(t)} K_{t}\left(\theta_{i}^{(t+1)} \mid \theta_{j}^{(t)}\right)}, & \text{if } y_{i}^{(t+1)} \in \Omega_{\left[0,\epsilon_{t+1}\right)}, \left[\text{ w.p. } \mathsf{P}\left(y \in \Omega_{\left[0,\epsilon_{t+1}\right)} \mid \theta_{i}^{(t+1)}\right)\right] \\ 0, & \text{if } y_{i}^{(t+1)} \notin \Omega_{\left[0,\epsilon_{t+1}\right)}, \left[\text{ w.p. } \mathsf{P}\left(y \notin \Omega_{\left[0,\epsilon_{t+1}\right)} \mid \theta_{i}^{(t+1)}\right)\right] \end{cases}$$
(11)

It would be computationally desirable to generate as much samples as possible with non-zero weights, i.e. so that $y_i^{(t+1)} \in$ $\Omega_{[0,\epsilon_{t+1})}$. If $\mathsf{P}\left(y \in \Omega_{[0,\epsilon_{t+1})} \mid \theta\right)$ would be available, it would be possible to query more samples from the parts of the parameter space that generate non-zero weighted samples with higher probability. Unfortunately this is in practice impossible in any realistic application of ABC. The average acceptance probability can be expressed as

$$\int \int p(y \in \Omega_{[0,\epsilon_{t+1})} \mid \theta^{(t+1)}) K_t(\theta^{(t+1)} \mid \theta^{(t)}) p\left(\theta^{(t)} \mid y \in \Omega_{[0,\epsilon_t)}\right) \mathsf{d}\theta^{(t)} \mathsf{d}\theta^{(t+1)},\tag{12}$$

which we aim to improve especially at the early iteration rounds t by introducing a novel importance sampling approach that modifies the locally optimal ABC SMC defined by the kernel covariance (10) using a partition of the ABC posterior approximation into components defined by a set of non-overlapping acceptance regions. The observation space bounded to the acceptance region at first threshold of ABC SMC can be partitioned based on the threshold sequence

$$\Omega_{[0,\epsilon_1)} = \bigcup_{t=1}^T \Omega_{[\epsilon_{t+1},\epsilon_t)},\tag{13}$$

where $\epsilon_{T+1} := 0$. We can use the partitioning and the law of total probability to write the ABC posterior correspondingly as

$$p\left(\theta^{(t)} \mid y \in \Omega_{[0,\epsilon_t)}\right) = \sum_{k=t}^{T} p\left(\theta^{(t)} \mid y \in \Omega_{[\epsilon_{k+1},\epsilon_k)}\right) \mathsf{P}\left(y \in \Omega_{[\epsilon_{k+1},\epsilon_k)} \mid y \in \Omega_{[0,\epsilon_t)}\right).$$
(14)

Example 1. We define a generative model for a single observation from a Gaussian model with mean θ and variance 1 with uniform prior for θ

$$p(y \mid \theta) = N(y \mid \theta, 1), \quad p(\theta) = \mathsf{Unif}_{[-6,6]}(\theta)$$
(15)

and observe $y^{obs} = 0$. Distance measure is the absolute difference between synthetic and observed data. Figure 1 illustrates the initial situation where an acceptance threshold sequence $\epsilon_{1:5}$ is selected as $[\infty, 4, 3, 2, 1]$. The first iteration ABC posterior corresponds to the prior and the threshold $\epsilon_1 = \infty$.



Figure 1: Example 1. Partitioning of the ABC posterior distribution based on the acceptance regions.

The partitioned posterior motivates the proposed ABC SMC approach. We make a modification to the transition kernel by removing the dependence on iteration t, and instead define it for each posterior component conditioned on the events of observations belonging to the acceptance regions $\Omega_{[\epsilon_{k+1},\epsilon_k)}$. Given the set of predefined acceptance regions and the ABC posterior sample at *i*th iteration, we first define a locally optimal transition kernel similar to (10) by taking into account which partitioned acceptance region band a particle resides in and then balance the particle selection probability by using approximations to the weights in (14) that we get as a by-product of previous iterations of ABC SMC.

Let $(\theta_i^{(t)}, y_i^{(t)}, w_i^{(t)}) \in \{(\theta^{(t)}, y^{(t)}, w^{(t)}) | y^{(t)} \in \Omega_{[\epsilon_{k+1}, \epsilon_k)}\}$ be a tuple that defines a particle from ABC posterior at iteration $t \le k < T$, that is within a partitioned acceptance region band $\Omega_{[\epsilon_{k+1}, \epsilon_k)}$. We seek a transition kernel covariance that is optimal for mutating the particle into acceptance region $\Omega_{[0, \epsilon_{k+1})}$. This can be achieved using the same approach as deriving locally optimal transition kernel covariance (10)

$$\Sigma_{i}^{\left(k\right)} = \int \left(\theta - \theta_{i}^{\left(t\right)}\right) \left(\theta - \theta_{i}^{\left(t\right)}\right)^{T} p\left(\theta \mid y \in \Omega_{\left[0, \epsilon_{k+1}\right)}\right) \mathrm{d}\theta$$

In Figure 2 we illustrate the cascading nature of the ABC posterior approximations at a single iteration *t* of the methods and how the transition kernels are locally optimally defined for each of the particles separately based on posterior component they belong to.



Figure 2: Example 1 continued. The particles residing in different partitioned components of the ABC posterior are being transitioned with a kernel defined by the cascading structure of improving ABC posterior estimates.

We express the average acceptance rate (12) as

$$\int \int \sum_{l=t+1}^{T} \sum_{k=t}^{T} p(y \in \Omega_{[\epsilon_{l+1},\epsilon_{l})} \mid \theta^{(t+1)}) K_{k}(\theta^{(t+1)} \mid \theta^{(t)}) p\left(\theta^{(t)} \mid y \in \Omega_{[\epsilon_{k+1},\epsilon_{k})}\right) d\theta^{(t)} d\theta^{(t+1)} \\
= \sum_{l=t+1}^{T} \sum_{k=t}^{T} \int \int p(y \in \Omega_{[\epsilon_{l+1},\epsilon_{l})} \mid \theta^{(t+1)}) K_{k}(\theta^{(t+1)} \mid \theta^{(t)}) p\left(\theta^{(t)} \mid y \in \Omega_{[\epsilon_{k+1},\epsilon_{k})}\right) d\theta^{(t)} d\theta^{(t+1)} \\
= \sum_{l=t+1}^{T} \sum_{k=t}^{T} C_{l,k}^{(t)},$$
(16)

where $C_{l,k}^{(t)}$ is the average rate of transitioning a particle from posterior $p(\theta^{(t)} \mid y \in \Omega_{[\epsilon_{k+1}, \epsilon_k)})$ with kernel $K_k(\cdot \mid \cdot)$ and generating a synthetic observation $y \in \Omega_{[\epsilon_{l+1}, \epsilon_l)}$. Given that we are approximating $C_{l,k}^{(t)} \approx C_{l,k}, l = t+1, \ldots, T, k = t, \ldots, T$ at each iteration of the ABC SMC, we can use these regional weights as a basis for a stratification strategy to compose an importance sampling distribution for more efficient simulation acceptance, by drawing samples from different partitioned posterior components proportionally to their average acceptance rates $C_{l,k}$. In practice we approximate $C_{l,k}$ by counting the frequencies $f_{l,k}^{(t)}$ how often samples drawn from

$$p(\theta^{(t+1,t)} \mid y \in \Omega_{\left[\epsilon_{k+1},\epsilon_{k}\right]}) := \int K_{k}(\theta^{(t+1)} \mid \theta^{(t)}) p(\theta^{(t)} \mid y \in \Omega_{\left[\epsilon_{k+1},\epsilon_{k}\right]}) \mathsf{d}\theta^{(t)}$$

generate observations $y \in \Omega_{[\epsilon_{l+1}, \epsilon_l)}$. This is carried out as a part of the weighted ABC sampling at each iteration. The probability that predicted observations generated from

$$p(y^{(t+1,t)} \mid y \in \Omega_{[\epsilon_{k+1},\epsilon_k]}) := \int p(y \mid \theta^{(t+1,t)}) p(\theta^{(t+1,t)} \mid y \in \Omega_{[\epsilon_{k+1},\epsilon_k]}) \mathrm{d}\theta^{(t+1,t)}$$

can be estimated at iteration t using the frequencies

$$\widehat{C}_{l,k}^{(t)} = \sum_{m=1}^{t} \frac{f_{l,k}^{(m)}}{\sum_{m'=1}^{t} \sum_{l'=1}^{T} f_{l',k}^{(m')}}, \quad l = 1, \dots, T, \quad k = t, \dots, T.$$
(17)



Figure 3: Example 1 continued. After the first ABC SMC iteration the particles are mutated and new set of synthetic observations are generated. We calculate the probabilities for each of the acceptance regions which are used to re-weight the ABC posterior sample weights.

The full weight for iteration t is obtained by first taking the sum over different acceptance regions that are within $\Omega_{[0,\epsilon_{t+1})}$

$$\widehat{W}_{k}^{(t)} = \sum_{l=t+1}^{T} \widehat{C}_{l,k}^{(t)} = \sum_{l=t+1}^{T} \sum_{m=1}^{t} \frac{f_{l,k}^{(m)}}{\sum_{m'=1}^{t} \sum_{l'=1}^{T} f_{l',k}^{(m')}}, \quad k = t, \dots, T.$$
(18)

We illustrate the cumulative predictive probability weighting in Figure 3. At iteration *t*, our approximation to the posterior importance sampling distribution can be constructed from the posterior distribution $\{(\theta_i^{(t)}, y_i^{(t)}, w_i^{(t)})\}_{i=1}^N$ as

$$\left\{ \left(\theta_{i}^{(t)}, y_{i}^{(t)}, \hat{w}_{i}^{(t)}, I_{i}^{(t)} \right) \right\}_{i=1}^{N} = \left\{ \left(\theta_{i}^{(t)}, y_{i}^{(t)}, \frac{w_{i}^{(t)} \cdot \widehat{W}_{k}^{(t)}}{\sum_{j=1}^{N} w_{j}^{(t)} \cdot \widehat{W}_{k}^{(t)}}, k \right) : y_{i}^{(t)} \in \Omega_{\left[\epsilon_{k+1}, \epsilon_{k}\right]} \right\}_{i=1}^{N}.$$

$$(19)$$

The proposed algorithm is summarised for a single iteration of ABC SMC in Algorithm 1.

Algorithm 1 Empirical estimation of posterior predictive probability of acceptance events

1: Input 1: Posterior sample $\{(\theta_i^{(t)}, y_i^{(t)}, w_i^{(t)}, I_i^{(t)})\}_{i=1}^N$. 2: Input 2: Frequencies $f_{l,k}^{(m)}$, m = 1, ..., t, k = 1, ..., T, l = 1, ..., T as in (17). 3: Calculate importance sampling distribution $\{(\theta_i^{(t)}, y_i^{(t)}, \hat{w}_i^{(t)}, I_i^{(t)})\}_{i=1}^N$ using (19) 4: Set n = 15: Set $f_{l,k}^{(t+1)} = 0, k = 1, \dots, T, l = 1, \dots, T$ while $n \leq N$ do Select $(\theta^{(t)}, y^{(t)}, I^{(t)})$ from $\{(\theta^{(t)}_i, y^{(t)}_i, \widehat{w}^{(t)}_i, I^{(t)}_i)\}_{i=1}^N$ with probability $\widehat{w}^{(t)}_i$ 7: Generate $\theta' \sim K_{I^{(t)}}(\theta \mid \theta^{(t)})$ Generate $y^{(t+1,t)} \sim f(y \mid \theta')$ Find k such that $y_m^{(t+1,t)} \in \Omega_{[\epsilon_{k+1},\epsilon_k)}$ 8: 9: 10: ${\rm Set}\; f_{k,I^{(t)}}^{(t+1)} = f_{k,I^{(t)}}^{(t+1)} + 1$ 11: if $y^{(t+1,t)} \in \Omega_{[0,\epsilon_{t+1})}$ then 12: $\theta_n^{(t+1)} = \theta'$ $y_n^{(t+1)} = y^{(t+1,t)}$ 13: 14: $I_n^{(t+1)} = k$ 15: Calculate $w_n^{(t)} \propto p(\theta_n) / \sum_{i=1}^N \widehat{w}_i^{(t)} K_{I^{(t)}}(\theta' \mid \theta_i^{(t)})$ 16: n = n + 117: 18: end if 19: end while 20: Normalise $w_n^{(t)} = w_n^{(t)} / \sum_{i=1}^N w_i^{(t)}$ 21: **Output 1:** Posterior sample $\{(\theta_i^{(t+1)}, w_i^{(t+1)}, y_i^{(t+1)}, I_i^{(t+1)})\}_{i=1}^N$ 22: **Output 2:** Frequencies $f_{l,k}^{(m)}, m = 1, ..., t + 1, k = 1, ..., T, l = 1, ..., T$

4 Stopping rule

ABC SMC is an iterative sampling algorithm that will require more computational resources after each iteration as the acceptance threshold is decreased, either adaptively or following a predetermined schedule, as in the case of the approach presented here. However, after some point the improvements we are obtaining from decreasing the threshold may not be significant enough to justify the required resources for improving the approximation. We propose a novel stopping rule based on the evolution of the prediction probabilities $C_{l,k}^{(t)}$. The prediction probabilities of the partitioned acceptance regions can be expressed as a probability mass function defined by the probabilities

$$P(y^{(t)} \in \Omega_{\left[\epsilon_{l+1}, \epsilon_{l}\right)}) \mid y \in \Omega_{\left[\epsilon_{k+1}, \epsilon_{k}\right)}) = C_{l,k}^{(t)}, \quad l = 1, \dots, T.$$

$$(20)$$

The target of the ABC SMC is the approximate posterior at the final iteration T and we use the probability mass $C_{:,T}^{(t)}$ as a proxy to monitor the evolution of the approximate posterior. We use notation $C_{:,k}^{(t)}$ to denote the probability mass function of the acceptance region events. If at the iteration t the approximate $\hat{C}_{:,t}^{(t)}$ is already resembling $\hat{C}_{:,T}^{(t)}$, we can consider stopping the algorithm early. Computationally this convenient as we can count the frequencies (17) as part of the proposed Algorithm 1. We can use the Kullback-Leibler (KL) divergence

$$D_{KL}\left(C_{:,T}^{(t)}||C_{:,t}^{(t)}\right) = \sum_{l=1}^{T} C_{l,T}^{(t)} \log\left(\frac{C_{l,T}^{(t)}}{C_{l,t}^{(t)}}\right)$$
(21)

as the quantified difference between the target and the current state. Note that by the definition we can start monitoring the convergence only after the second iteration as all the parameters on the first round are from the prior instead of the components of the partitioned approximate posterior.

Example 2. We illustrate the behaviour of the KL divergence using the model from Example 1 and augmenting the model with more acceptance regions that are defined by threshold sequence $\epsilon_{1:9} = [\infty, 4, 3, 2, 1, 0.8, 0.6, 0.4, 0.2]$. The experiment is carried out with N = 150000 samples. We calculate the posterior predictive probabilities of the acceptance regions using the cumulative frequencies and for each of the iterations we calculate the KL divergence between the consecutive probability mass functions. The evolution of KL is illustrated in Figure 4. We see how the KL divergence plateaus after the 5th iteration as the predicted probability mass function does not significantly change even when the threshold of the ABC posterior decreases.



Figure 4: Example 1 continued. Upper figure bars illustrate the predicted probability mass functions (pmf) 20. At each iteration we calculate pmf defined by (20) and the corresponding KL divergence (21) that is reported on the bottom Figure.

5 Results

We compare the proposed stratified sampling ABC SMC approach to a globally and locally optimal ABC SMC methods introduced in Section 2 denoted by *Global* and *Local*, respectively. Two version of the stratified sampling approach are tested here. *Stratified simple* uses only the new transition kernel, whereas *Stratified* used the transition kernel and the proposed importance sampling distribution. In each test case, we have fixed the unknown parameters θ_0 and repeated the experiment 50 times with different randomly generated observations $y^{obs} \sim p(y \mid \theta_0)$.

We assume that accuracy-wise all the methods will perform similarly as the main difference of the methods is the sampling strategy. We investigate the acceptance rates, and estimation accuracies in three examples which have been widely used in ABC literature for benchmarking methods. As estimation accuracy we report the medians of iteration-wise sample means in addition to the interval: median of the sample mean ± 1.96 · median of the sample standard deviation. In addition to accuracy we report the KL-divergence of the predicted acceptance region probabilities to investigate its usability as an early termination indicator. Acceptance rates and KL convergence monitoring quantity are reported as medians and interquartile ranges over the repetitions.

5.1 Banana shaped distribution

The first example is a two-parameter banana shaped posterior distribution, where the parameter dependence structure is a challenge for the sampling methods. The model was introduced by Haario et al. [1999] and used by e.g. Filippi et al. [2013]



Figure 5: Acceptance rates by iteration round for the four compared methods in the three experiments with 2, 3 and 4 parameters as described in Sections 5.1, 5.2 and 5.3. Acceptance rates are consistently higher for the proposed method in all experiments.

as a benchmarking example for ABC SMC. The likelihood and the prior are defined as

$$p(y \mid \theta_1, \theta_2) = \operatorname{Normal}\left(\begin{bmatrix} \theta_1 \\ \theta_1 + \theta_2^2 \end{bmatrix}, \begin{bmatrix} 1 & 0 \\ 0 & 0.5 \end{bmatrix} \right)$$
(22)

$$p(\theta_1, \theta_2) = \mathsf{Unif}_{[-50, 50]}(\theta_1) \cdot \mathsf{Unif}_{[-50, 50]}(\theta_2).$$
(23)

As divergence function we use Euclidean distance. Methods use the threshold sequence $[\infty, 100, 50, 20, 10, 5, 2, 1]$, and at each iteration the posteriors are approximated with 2000 samples. Acceptance rates provided by the proposed methods are significantly improved compared to local and global sampling strategies as seen in Figure 5. Even using only the proposed novel transition kernel (Stratified simple) the acceptance rate is better, but the stratified sampling strategy does improve the results markedly over almost all iterations. The estimation accuracy is slightly improved with the proposed methods and early termination convergence monitoring does indicate that the final iteration could be unnecessary. It is notable that the KL might be unreliable in the early iterations of the algorithm as indicated by the initial increase in the monitored divergence.



Figure 6: Evolution of the sample mean and 1.96 standard deviation and the early termination convergence diagnostic over 8 iterations in Banana-shaped distribution example. True parameter values used to simulate all the datasets are marked with dashed lines ($\theta_1 = \theta_2 = 0$).

5.2 Lotka-Volterra

Lotka-Volterra model is a stochastic kinetic system describing predator-prey dynamics. We adapt the implementation from Owen et al. [2015]. The system is defined by three reactions R1, R2 and R3

Prey birth (R1):
$$X_1 \rightarrow 2X_1$$
 (24)

Prey death & Predator birth (R2):
$$X_1 + X_2 \rightarrow 2X_2$$
 (25)

Predator death (R3):
$$X_2 \to 0.$$
 (26)

We simplify our model by fixing the initial numbers of prey and predator populations to 100 and 50, respectively, and not adding observation noise to the state. The prior distributions for the hazard rates r_i , i = 1, 2, 3 of the reactions are set as

$$\log(r_i) \sim \text{Unif}(-6, 1), \quad i = 1, 2, 3$$
 (27)

We use summarised data as observations and Euclidean distance function. The summaries are defined as

- S1 = Mean of prey population over the simulation
- S2 = Mean of predator population over the simulation
- S3 = Logarithm of variance of prey population over the simulation
- S4 = Logarithm of variance of predator population over the simulation
- $S5={\rm Auto-correlation}$ of lag 1 of prey population over the simulation
- $S6={\rm Auto-correlation}$ of lag 1 of predator population over the simulation
- S7 = Auto-correlation of lag 2 of prey population over the simulation
- S8 = Auto-correlation of lag 2 of predator population over the simulation

All methods use a threshold sequence $[\infty, 200, 100, 90, 80, 70, 60, 50]$, and at each iteration the posteriors are approximated with 2000 samples.

Acceptance rates are again significantly better with the proposed methods as reported in Figure 5. The estimation accuracy is better with the proposed methods, but the algorithms have not yet reached a stable state, but all methods should have improved performance when the threshold sequence would be continued.



Figure 7: Evolution of the sample mean and 1.96-standard deviation and the early termination convergence diagnostic over 8 iterations in Lotka-Volterra example. True parameter values used to simulate all observed datasets are marked with dashed horizontal lines ($r_1 = 2, r_2 = 0.01, r_3 = 1$).

5.3 g-and-k-distribution

The third test case we investigate is the univariate g-and-k distribution following [Drovandi and Pettitt, 2011]. We can draw a sample from the distribution by first sampling $z(p)_i \stackrel{i.i.d}{\sim} Normal(0,1)$, $i = 1, \ldots, 50$ and then drawing y_i for each $i = 1, \ldots, 50$

$$y_{i} \sim Q^{g^{g^{g}}}(z(p)_{i}; A, B, g, k)$$

= $A + B \cdot \left(1 + 0.8 \cdot \frac{1 - \exp(-g \cdot z(p)_{i})}{1 + \exp(-g \cdot z(p)_{i})}\right) (1 + z(p)_{i}^{2})^{k} z(p)_{i}.$ (28)

We use uniform prior distributions for the parameters

$$A, B, g \stackrel{\text{i.i.d}}{\sim} \mathsf{Unif}(0, 5)$$
$$k \sim \mathsf{Unif}(0, 2),$$

We use uniform prior distributions for the parameters

$$\begin{split} A,B,g &\stackrel{\mathrm{i.i.d}}{\sim} \mathsf{Unif}(0,5) \\ k &\sim \mathsf{Unif}(0,2), \end{split}$$

and as the summary statistic we use the ordered sequence of observations

 $[y_{I(1)}, y_{I(2)}, \dots, y_{I(50)}], \quad i < j \Rightarrow y_{I(i)} \le y_{I(j)}.$

Euclidean distance is used as the divergence metric. All methods use a threshold sequence $[\infty, 100, 70, 50, 30, 27, 23, 20]$, and at each iteration the posteriors are approximated with 5000 samples. We observe similar results than on the previous experiments. Acceptance rates are significantly improved given the new proposed methods as illustrated in the Figure 5. From Figure 8 we see that the estimation accuracy of the proposed method is a little better compared to local and global. The early termination quantity does not indicate convergence within the iterations which can also be seen the posterior mean estimate evolution.



Figure 8: Evolution of the sample mean and 1.96-standard deviation and the early termination convergence diagnostic over 8 iterations in g-and-k distribution example. True parameter values used to simulate all observed datasets are marked with dashed horizontal lines (A = 3, B = 1, g = 2, k = 0.5).

6 Conclusions

Here we introduced an approach to improve the acceptance rate of ABC SMC using a stratification of the acceptance region. Using the accumulated information of the posterior predictive distributions, we can re-weight the importance sampling distribution of the ABC SMC to draw particles that are more likely to produce observations that will be accepted at the subsequent iterations of the algorithm. In addition we described a transition kernel that takes the cascading formulation of the algorithm into account, and a novel early termination diagnostic based on the KL divergence of the predictive distribution of the acceptance regions.

Through simulations we confirm the feasibility of the method and demonstrate that it achieves significantly improved acceptance rate than the currently most popular versions of ABC SMC algorithm. A restriction of the method however is the requirement of fixing the threshold sequence beforehand. Further work could thus be done to relax this requirement and toimprove the adaptability of the method.

Acknowledgements

This research was supported by Research Council of Norway, grant no. 299941.

References

- M. A. Beaumont, W. Zhang, and D. J. Balding. Approximate bayesian computation in population genetics. *Genetics*, 162 (4):2025–2035, 2002.
- F. V. Bonassi and M. West. Sequential monte carlo with adaptive weights for approximate bayesian computation. *Bayesian Analysis*, 10(1):171–187, 2015. doi: 10.1214/14-BA891.

- K. Cranmer, J. Brehmer, and G. Louppe. The frontier of simulation-based inference. Proceedings of the National Academy of Sciences, 117(48):30055–30062, 2020. ISSN 0027-8424. doi: 10.1073/pnas.1912789117.
- C. C. Drovandi and A. N. Pettitt. Likelihood-free bayesian estimation of multivariate quantile distributions. *Computational Statistics and Data Analysis*, 55:2541–2556, 2011.
- S. Engebretsen, A. Diz-Lois Palomares, G. Rø, A. B. Kristoffersen, J. C. Lindstrøm, K. Engø-Monsen, M. Kamineni, L. Y. Hin Chan, Ø. Dale, J. E. Midtbø, K. L. Stenerud, F. Di Ruscio, R. White, A. Frigessi, and B. F. de Blasio. A real-time regional model for covid-19: Probabilistic situational awareness and forecasting. *PLOS Computational Biology*, 19(1): 1–26, 2023. doi: 10.1371/journal.pcbi.1010860.
- S. Filippi, C. P. Barnes, J. Cornebise, and M. P. Stumpf. On optimality of kernels for approximate bayesian computation using sequential monte carlo. *Statistical Applications in Genetics and Molecular Biology*, 12(1):87 – 107, 2013. doi: 10.1515/ sagmb-2012-0069.
- M. U. Gutmann and J. Corander. Bayesian optimization for likelihood-free inference of simulator-based statistical models. *Journal of Machine Learning Research*, 2016.
- H. Haario, E. Saksman, and J. Tamminen. Adaptive proposal distribution for random walk Metropolis algorithm. *Computational Statistics*, 14:375 395, 1999.
- A. Lavin, H. Zenil, B. Paige, D. Krakauer, J. Gottschlich, T. Mattson, A. Anandkumar, S. Choudry, K. Rocki, A. G. Baydin, C. Prunkl, O. Isayev, E. Peterson, P. L. McMahon, J. H. Macke, K. Cranmer, J. Zhang, H. M. Wainwright, A. Hanuka, M. Veloso, S. Assefa, S. Zheng, and A. Pfeffer. Simulation intelligence: Towards a new generation of scientific methods. *CoRR*, abs/2112.03235, 2021. URL https://arxiv.org/abs/2112.03235.
- J. Lintusaari, M. U. Gutmann, R. Dutta, S. Kaski, and J. Corander. Fundamentals and Recent Developments in Approximate Bayesian Computation. *Systematic Biology*, 66:66–82, 2017. doi: 10.1093/sysbio/syw077.
- J.-M. Lueckmann, G. Bassetto, T. Karaletsos, and J. H. Macke. Likelihood-free inference with emulator networks. *arXiv* preprint arXiv:1805.09294, 2018.
- G. M. Martin, D. T. Frazier, and C. P. Robert. Approximating bayes in the 21st century. Statistical Science, 2021.
- P. D. Moral, A. Doucet, and A. Jasra. An adaptive sequential Monte Carlo method for approximate Bayesian computation. *Statistics and Computing*, 22(5):1009–1020, 2012.
- J. Owen, D. J. Wilkinson, and C. S. Gillespie. Likelihood free inference for markov processes: a comparison. *Statistical Applications in Genetics and Molecular Biology*, 14(2):189–209, 2015. doi: 10.1515/sagmb-2014-0072.
- G. Papamakarios, D. C. Sterratt, and I. Murray. Sequential neural likelihood: Fast likelihood-free inference with autoregressive flows. In *Proceedings of the 22nd International Conference on Artificial Intelligence and Statistics (AISTATS) 2019*, volume 89, pages 837–848. Society for Artificial Intelligence and Statistics, PMLR, 4 2019.
- H. Pesonen, U. Simola, A. Köhn-Luque, H. Vuollekoski, X. Lai, A. Frigessi, S. Kaski, D. T. Frazier, W. Maneesoonthorn, G. M. Martin, and J. Corande. ABC of the Future. *International Statistical Review*, 2022.
- L. F. Price, C. C. Drovandi, A. Lee, and D. J. Nott. Bayesian synthetic likelihood. *Journal of Computational and Graphical Statistics*, 27(1):1–11, 2018.
- J. K. Pritchard, M. T. Seielstad, A. Perez-Lezaun, and M. W. Feldman. Population growth of human Y chromosomes: a study of Y chromosome microsatellites. *Molecular biology and evolution*, 16(12):1791–1798, 1999.
- D. Silk, S. Filippi, and M. Stumpf. Optimizing threshold-schedules for sequential approximate bayesian computation: applications to molecular systems. *Statistical Applications in Genetics and Molecular Biology*, 5(12):603–618, 2013.
- U. Simola, J. Cisewski-Kehe, M. U. Gutmann, and J. Corander. Adaptive approximate bayesian computation tolerance selection. *Bayesian Analysis*, 2020.
- S. Sisson, Y. Fan, and M. Beaumont. *Handbook of Approximate Bayesian Computation*. Chapman & Hall/CRC Handbooks of Modern Statistical Methods. CRC Press, Taylor & Francis Group, 2018. ISBN 9781439881507.
- S. A. Sisson, Y. Fan, and M. Tanaka. Sequential Monte Carlo without likelihoods. Proc. Natl. Acad. Sci. USA, 104(6):1760– 1765, 2007.
- M. M. Tanaka, A. R. Francis, F. Luciani, and S. A. Sisson. Using approximate bayesian computation to estimate tuberculosis transmission parameters from genotype data. *Genetics*, 104(3):1511–1520, 2006. doi: 10.1534/genetics.106.055574.
- T. Toni, D. Welch, N. Strelkowa, A. Ipsen, and M. Stumpf. Approximate bayesian computation scheme for parameter inference and model selection in dynamical systems. *Journal of the Royal Society Interface*, pages 6187–6202, 2009.
- S. Wood. Statistical inference for noisy nonlinear ecological dynamic systems. Nature, 466:1102–1107, 2010.