# Towards optimal control of systems with backlash

M. d. R. de Pinho<sup>a</sup>, M. Margarida A. Ferreira <sup>a</sup> and Georgi Smirnov<sup>b</sup>

<sup>a</sup>Universidade do Porto, Faculdade de Engenharaia, DEEC, SYSTEC, Porto, Portugal.

<sup>b</sup>Universidade do Minho, Dep. Matemática,

Physics Center of Minho and Porto Universities (CF-UM-UP),

Campus de Gualtar, Braga, Portugal.

mrpinho@fe.up.pt , mmf@fe.up.pt, smirnov@math.uminho.pt

#### Abstract

In this paper we consider time-optimal control problems for systems with backlash. Such systems are described by second order differential equations coupled with restrictions modeling the inelastic shocks. A main feature of such systems is the lack of uniqueness of solution to the Cauchy problem. Here, we introduce approximation systems where the forces during the impact are taken into account. Such approximations are relevant for two reasons. Firstly, we define a set of solutions as limits of the solutions to the approximation systems. This set may be smaller than the set of of the solutions usually considered in the literature. Secondly, such approximations are adequate to derive necessary condition to the time optimal control of interest. To the best of our knowledge, this is the first attempt to derive necessary conditions of optimality for optimal control problems involving systems with backlash.

## 1 Introduction

Backlash is present in many mechanical systems. The study of systems with backlash mainly concerns stabilization problems [\[9\]](#page-23-0). In this paper we consider time-optimal control problems for systems with backlash. Informally, such systems have the form:

$$
\ddot{z} = F(z, \dot{z}, u) - N_C(z), \ z \in C, \ u \in U(t),
$$

where C is a set and  $N_C(z)$  is a normal force that does not allow the system to cross the boundary of C. The shock with the boundary of C is assumed to be absolutely inelastic, i.e., after the collision the velocity  $\dot{z}$  loses its component normal to  $\partial C$ . When  $C = \{z : \psi(z) \leq z \}$  0} and  $\psi$  is a smooth function,  $N_C(z)$  has the form  $N\nabla\psi(z)$  for some  $N\geq 0$ . The study of these systems is hard and it has a long story. To our knowledge it was Moreau [\[8\]](#page-23-1) who first studied systems with completely inelastic impacts. Later, for second order differential equations Schatzman introduced the definition of solution involving measures with respect to time [\[10\]](#page-23-2) and Monteiro-Marques [\[7\]](#page-23-3) proved the first existence result for the Cauchy problem

<span id="page-1-0"></span>
$$
d\dot{z} = F(z, \dot{z}, u)dt - \nabla \psi(z) d\nu,
$$
  
\n
$$
z(0) = z_0,
$$
  
\n
$$
\dot{z}(0) = \dot{z}_0,
$$
\n(1)

where  $\nu \in BV([0, T], R^n)$ ,  $d\nu \ge 0$ ,  $\psi(z) d\nu = 0$  and, if  $\psi(z(t)) = 0$ , then  $\frac{d}{dt}\psi(z(t+0)) = 0$ . The solution is a pair  $(z, \dot{z}) \in AC([0, T], R^n) \times BV([0, T], R^n)$  satisfying the above conditions. We call it a *Moreau-Schatzman-Monteiro Marques solution* (MSMM solution). For general theorem on the existence of solution see, e.g., [\[2\]](#page-22-0). It is of foremost importance to notice that the solution may not be unique [\[1\]](#page-22-1).

The model with inelastic shocks is adequate for the description of systems with backlash when the motion of the bodies is rather slow. Moreover, for the study of optimal control problems, such model is simpler than the case of elastic shocks.

Noteworthly, the equation

$$
d\dot{z} = F(z, \dot{z}, u)dt - \nabla \psi(z) d\nu
$$

is of interest to describe dynamics of systems with hysteresis [\[6\]](#page-23-4) (backlash is an example of hysteresis).

In this paper, we focus on time-optimal control problems for such systems. Our aim is to derive necessary conditions of optimality. To do so we introduce approximating systems where forces during the impact are taken into account. Considering that the forces between interacting bodies go to infinity, we define solutions of [\(1\)](#page-1-0) as a set of limits of solutions to the approximating systems. This set of solutions, which we call backlash solutions, is included in the set of MSMM solutions.

The approximating techniques are in vein of our work on optimal control for systems involving sweeping processes [\[5\]](#page-23-5). Sweeping systems are first order systems. Optimal control problems involving those systems are nowadays well studied; see, e.g., [\[3,](#page-23-6) [4,](#page-23-7) [12\]](#page-23-8) and references therein.

The study of the second order system [\(1\)](#page-1-0) is much more involved than that of sweeping systems. Remarkably, and as we show here, the approximating techniques similar to those in [\[5\]](#page-23-5) allow us to derive necessary conditions of optimality for backlash solutions. Central to our analysis is the fact that necessary condition of optimality for time-optimal control problems involving the approximating systems are well known. Passing to the limit (i.e., considering that the acting forces go to infinity), we get the desired necessary conditions of optimality for backlash solutions.

To keep the focus on the main difficulties regarding the derivation of necessary conditions, we consider a time-optimal control problem. For simplicity of presentation, we assume the data smooth. This work may be easily generalized to cover optimal control problems with different costs, additional end point constraints and some nonsmooth data.

Since we focus on global solutions to the time-optimal control problem of interest, it is enough to show that there exists an optimal solution satisfying the necessary conditions. It is in this vein that we formulate our results here. One could use penalization techniques to show that any other optimal solution also satisfies the necessary conditions. However, this is not our aim; we concentrate on a solution and not on all of them.

Throughout this paper we denote the set of real numbers by  $R$  and the usual n-dimensional space of vectors  $x = (x^1, \ldots, x^n)$ , where  $x^i \in R$ ,  $i = \overline{1,n}$ , by  $R^n$ . The inner product of two vectors x and y in  $R^n$  is defined by

$$
\langle x, y \rangle = x^1 y^1 + \ldots + x^n y^n,
$$

and the norm of a vector  $x \in R^n$  is  $|x| = \langle x, x \rangle^{1/2}$ . If  $g: R^p \to R^q$ ,  $\nabla g$  represents the derivative. The partial derivative in order of a variable  $\xi$  is denoted by  $\partial_{\xi}$ . If  $a \in R$ , we set  $a_+ = \max\{a, 0\}$ . By  $\chi_E$  we denote the characteristic function of a set  $E \subset [0, 1]$ .

The space  $L_\infty([a, b]; R^p)$  (or simply  $L_\infty$  when the domains are clearly understood) is the Lebesgue space of essentially bounded functions  $h : [a, b] \rightarrow R^p$ . We say that  $h \in$  $BV([a, b]; R<sup>p</sup>)$  if h is a function of bounded variation. The space of continuous functions is denoted by  $C([a, b]; R^p)$  and the space of absolutely continuous functions by  $AC([a, b]; R^p)$ .

In this work, we use sequences and subsequences of functions indexed by  $\gamma$ . To simplify the notation, we write  $z_{\gamma}$  meaning  $z_{\gamma_k}$  or, when considering subsequences,  $z_{\gamma_{k_m}}$ , i.e., we omit the indexes unless the appearance of the index is absolutely necessary as in the case of construction of diagonal subsequences.

### 2 Definition of solution

Consider system  $(1)$ . In many situations, instead of z we can introduce new coordinates  $(x, y)$ , where  $y = \psi(z)$ , and rewrite the system in the following *canonical* form:

<span id="page-2-0"></span>
$$
\ddot{x} = f(x, y, \dot{x}, \dot{y}, u),\tag{2}
$$

$$
dy = g(x, y, \dot{x}, \dot{y}, u)dt - d\nu,
$$
\n(3)

$$
y \le 0, \ yd\nu = 0, \ d\nu \ge 0, \ u \in U \tag{4}
$$

$$
y(t) = 0 \Longrightarrow \dot{y}(t+0) = 0 \tag{5}
$$

Here, we focus on systems having this form. We start by defining a solution to system [\(2\)](#page-2-0) - [\(5\)](#page-2-0) suitable to derive necessary conditions of optimality.

We assume that  $U(t) \subset R^m$  is a convex compact set, the map  $t \to U(t)$  is bounded and measurable, and that the right-hand side of the control system has the following structure:

$$
f(x, y, v, w, u) = f_1(x, y, v) + f_2(x, y, v)w + f_3(x, y, v)u
$$

and

$$
g(x, y, v, w, u) = g_1(x, y, v) + g_2(x, y, v)w + g_3(x, y, v)u.
$$

Furthermore, we assume that  $f$  and  $g$  are sufficiently smooth functions and

<span id="page-2-1"></span>
$$
|f| \le M(1+|x|+|y|+|v|+|w|) \text{ and } |g| \le M(1+|x|+|y|+|v|+|w|). \tag{6}
$$

For  $a \in R$ , we denote  $a_+ = \max\{a, 0\} = \frac{1}{2}$  $\frac{1}{2}(a+|a|)$ . Let  $\gamma > 0$  and  $u_{\gamma} \in U$  be a measurable function.

Consider now the Cauchy problem

<span id="page-3-0"></span>
$$
\dot{x}_{\gamma} = v_{\gamma},\tag{7}
$$

$$
\dot{y}_{\gamma} = w_{\gamma},\tag{8}
$$

$$
\dot{v}_{\gamma} = f(x_{\gamma}, y_{\gamma}, v_{\gamma}, w_{\gamma}, u_{\gamma}),\tag{9}
$$

$$
\dot{w}_{\gamma} = g(x_{\gamma}, y_{\gamma}, v_{\gamma}, w_{\gamma}, u_{\gamma}) - \gamma(y_{\gamma})_{+}(w_{\gamma})_{+},
$$
\n(10)

$$
x_{\gamma}(0) = x_0, \ y_{\gamma}(0) = y_0, \ v_{\gamma}(0) = v_0, \ w_{\gamma}(0) = w_0.
$$
 (11)

The force  $\gamma(y_\gamma)_+(w_\gamma)_+$  appearing in [\(10\)](#page-3-0) is basically Hooke's law with the additional term  $(w_{\gamma})_+$  introduced to model the inelastic shock: the reaction force is active only when the systems moves outward the set C.

**Theorem 1.** Let  $\gamma_k \to \infty$  be a sequence of scalars and let  $u_{\gamma_{k_l}}$  be a sequence of admissible controls converging in weak\* topology of  $L_\infty([0,T], R^n)$  to some function  $\hat{u}(t) \in U(t)$ . For each  $k_l$ , let  $(x_{\gamma_{kl}}, y_{\gamma_{kl}}, v_{\gamma_{kl}}, w_{\gamma_{kl}})$  be a solution to the system [\(7\)](#page-3-0)-[\(11\)](#page-3-0).

Then the sequence  $(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}})$  has a subsequence converging to a limiting func $tion (\hat{x}, \hat{y}, \hat{v}, \hat{w}) \in AC([0,T], R^n) \times AC([0,T], R) \times AC([0,T], R^n) \times BV([0,T], R)$  where the convergence in  $AC$  is in the sense of the uniform norm and the convergence in BV is in the sense of the weak\* topology. Moreover,  $(\hat{x}, \hat{y}, \hat{v}, \hat{w}, \hat{u})$  solves the problem

<span id="page-3-1"></span>
$$
\dot{x} = v,\tag{12}
$$

$$
\dot{y} = w,\tag{13}
$$

$$
\dot{v} = f(x, y, v, w, u),\tag{14}
$$

$$
dw = g(x, y, v, w, u)dt - d\nu, \quad d\nu \ge 0, \quad yd\nu = 0,
$$
\n(15)

$$
y \le 0, \quad y(t) = 0 \Longrightarrow w(t+0) = 0,\tag{16}
$$

$$
x(0) = x_0, y(0) = y_0, v(0) = v_0, w(0) = w_0.
$$
\n
$$
(17)
$$

*Proof.* We fix a sequence  $\gamma_{k_l} \to \infty$ . From [\(7\)](#page-3-0) - [\(10\)](#page-3-0) and [\(6\)](#page-2-1) we have

$$
\frac{1}{2}\frac{d}{dt}(|x_{\gamma_{kl}}|^2 + |y_{\gamma_{kl}}|^2 + |v_{\gamma_{kl}}|^2 + |w_{\gamma_{kl}}|^2)
$$
\n
$$
\leq M_1 + M_2(|x_{\gamma_{kl}}|^2 + |y_{\gamma_{kl}}|^2 + |v_{\gamma_{kl}}|^2 + |w_{\gamma_{kl}}|^2) - \gamma_{kl}(y_{\gamma_{kl}})_+(w_{\gamma_{kl}})_+^2
$$
\n
$$
\leq M_1 + M_2(|x_{\gamma_{kl}}|^2 + |y_{\gamma_{kl}}|^2 + |v_{\gamma_{kl}}|^2 + |w_{\gamma_{kl}}|^2).
$$

Applying the Gronwall inequality we see that  $|x_{\gamma_{kl}}|^2 + |y_{\gamma_{kl}}|^2 + |v_{\gamma_{kl}}|^2 + |w_{\gamma_k}|^2$  is a bounded function. This implies that  $(x_{\gamma_{kl}}, y_{\gamma_{kl}})$  contains a uniformly converging subsequence. Hence (see [\(9\)](#page-3-0))  $v_{\gamma_{kl}}$  also contains a uniformly converging subsequence. From [\(10\)](#page-3-0) we get

$$
w_{\gamma_{k_l}} = w_0 + \int_0^T g_{\gamma_{k_l}} dt - \int_0^T \gamma_{k_l}(y_{\gamma_{k_l}})_+(w_{\gamma_{k_l}})_+ dt
$$

This implies that the sequence of functions

$$
\int_0^t \gamma_{k l}(y_{\gamma_{k l}})_+(w_{\gamma_{k l}})_+ ds
$$

is bounded in  $BV([0,T], R)$ . Therefore, the sequence of measures  $\gamma_{kl}(y_{\gamma_{kl}})_+(w_{\gamma_{kl}})_+dt$  contains a weak\* converging subsequence to some measure  $d\nu, \nu \in BV([0,T], R)$  (we do not relabel). From [\(10\)](#page-3-0), we deduce that there exists a constant  $K > 0$  such that

$$
\int_0^T |\dot{w}_{\gamma_{k_l}}| dt \leq K.
$$

It then follows that, without loss of generality,  $w_{\gamma_{k_l}}$  converges pointwisely to some function  $\hat{w} \in BV$ .

Going back to  $(7)$ ,  $(8)$  and  $(9)$  we get

$$
x_{\gamma_{k_l}} = x_0 + \int_0^t v_{\gamma_{k_l}}(s)ds,
$$
  
\n
$$
y_{\gamma_{k_l}} = y_0 + \int_0^t w_{\gamma_{k_l}}(s)ds,
$$
  
\n
$$
v_{\gamma_{k_l}} = v_0 + \int_0^t ((f_1)_{\gamma_{k_l}} + (f_2)_{\gamma_{k_l}} w_{k_l}(s))ds
$$
  
\n
$$
+ \int_0^t ((f_3)_{\gamma_{k_l}} - (\hat{f}_3)) u_{\gamma_{k_l}}(s)ds + \int_0^t (\hat{f}_3) u_{\gamma_{k_l}}(s)ds,
$$

where  $(f_i)_{\gamma_{k_l}} = f_i(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}), i = 1, 2, 3$ , and  $\hat{f}_3 = f_3(\hat{x}, \hat{y}, \hat{v})$ . Passing to the limit, we get  $(\hat{x}, \hat{y}, \hat{v}) \in \text{AC}([0, T], \mathbb{R}^n) \times \text{AC}([0, T], R) \times \text{AC}([0, T], R^n)$  satisfying equations  $(12) - (14)$  $(12) - (14)$  $(12) - (14)$ .

We now turn to [\(15\)](#page-3-1). Take any  $w^* \in C([0,T], R)$ . Turning to [\(10\)](#page-3-0) we have

$$
\int_0^T w^* \dot{w}_{\gamma_{k_l}} dt = \int_0^T w^* g_{\gamma_{k_l}} dt - \int_0^T \gamma_{k_l} (y_{\gamma_{k_l}})_+ (w_{\gamma_{k_l}})_+ w^* dt,
$$

where  $g_{\gamma_{k_l}} = (g_1)_{\gamma_{k_l}} + (g_2)_{\gamma_{k_l}} w_{\gamma_{k_l}} + (g_3)_{\gamma_{k_l}} u_{\gamma_{k_l}}, (g_i)_{\gamma_{k_l}} = g_i(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}})$ . Without loss of generality we deduce that the measures  $\dot{w}_{\gamma_{k_l}}dt$  and  $g_{\gamma_{k_l}}dt$  converge to  $d\hat{w}$  and  $d\hat{G}$ . Hence, we have

$$
d\hat{w} = d\hat{G} - d\nu.
$$

We now turn to  $\hat{G}$ . Take any  $z^* \in L^1([0,T];R)$ . We have

$$
\int_0^T z^* g_{\gamma_{k_l}} dt = \int_0^T z^* ((g_1)_{\gamma_{k_l}} + (g_2)_{\gamma_{k_l}} w_{\gamma_{k_l}}) dt + \int_0^T z^* ((g_3)_{\gamma_{k_l}} - \hat{g}_3) u_{\gamma_{k_l}} dt + \int_0^T z^* \hat{g}_3 u_{\gamma_{k_l}} dt,
$$

where  $(g_i)_{\gamma_{k_l}} = g_i(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}), i = 1, 2, 3$ , and  $\hat{g}_3 = g_3(\hat{x}, \hat{y}, \hat{v})$ . Passing to the limit, we conclude that

$$
d\hat{G} = \hat{g}_1 dt + \hat{g}_2 \hat{w} dt + \hat{g}_3 \hat{u} dt,
$$

where  $\hat{g}_i = g_i(\hat{x}, \hat{y}, \hat{v}), i = 1, 2, 3$ . It is a simple matter to see that we get  $d\nu \geq 0$  and  $\hat{y}d\nu = 0$ . Therefore we get [\(15\)](#page-3-1). It remains to see that [\(16\)](#page-3-1) holds.

Let us show that  $\hat{y}(t) \leq 0$ . We fix  $\gamma = \gamma_{kl}$  and omit the respective index. Let  $t_0$ and  $\tau$  be such that  $y(t_0) = 0$  and  $y(t_0 + \tau) = \max\{y(t) : t \in [0,T]\}\)$ , when  $y(t) > 0$ 

for  $t \in [t_0, t_0 + \tau]$  and  $y(t) < y(t_0 + \tau)$  for  $t \in [t_0, t_0 + \tau]$ . We now consider subintervals  $]t_j, t_j + \tau_j[\subset [t_0, t_0 + \tau], j = 0, 1, \dots$  where  $w(t) > 0, t \in ]t_j, t_j + \tau_j[$ ,  $w(t_j) = 0, w(t_j + \tau_j) = 0$ ,  $j = 1, 2, \ldots$  Clearly, the set of such subintervals is countable and there exists a  $t_* \leq t_0 + \tau$ such that  $t_j \to t_*$  and  $\lim_{j \to +\infty} y(t_j) = y(t_*)$ . Thus, we deduce  $t_* = t_0 + \tau$  (indeed, if  $t_* < t_0 + \tau$ , then there would be another subinterval where y would increase and, by construction of the subintervals  $[t_j, t_j + \tau_j]$ , this is not possible).

We now integrate [\(10\)](#page-3-0). Observing that  $\gamma(y)_+(w)_+ = \frac{\gamma}{2}$ 2  $\frac{d}{dt}y^2$  whenever  $y > 0$  and  $w > 0$ , we get

$$
\frac{\gamma}{2}(y^2(t_0 + \tau_0) - y^2(t_0)) = w(t_0) + \int_{t_0}^{t_0 + \tau_0} g dt,
$$
  
\n
$$
\frac{\gamma}{2}(y^2(t_1 + \tau_1) - y^2(t_1)) = \int_{t_1}^{t_1 + \tau_1} g dt,
$$
  
\n...  
\n
$$
\frac{\gamma}{2}(y^2(t_j + \tau_j) - y^2(t_j)) = \int_{t_j}^{t_j + \tau_j} g dt,
$$
  
\n...

Since  $y(t_i + \tau_i) \geq y(t_{i+1})$ , we get

$$
\frac{\gamma}{2}y^2(t_1) \le w(t_0) + \int_{t_0}^{t_0 + \tau_0} g dt,
$$
  

$$
\frac{\gamma}{2}(y^2(t_2) - y^2(t_1)) \le \int_{t_1}^{t_1 + \tau_1} g dt,
$$
  
...  

$$
\frac{\gamma}{2}(y^2(t_{j+1}) - y^2(t_j)) \le \int_{t_k}^{t_j + \tau_j} g dt,
$$
  
...

Adding these inequalities we obtain

$$
\frac{\gamma}{2}y^2(t_0 + \tau) \le w(t_0) + \int_{t_0}^{t_0 + \tau} |g| dt \le w(t_0) + M_3.
$$

Hence

$$
y(t_0 + \tau) \le \frac{M_4}{\sqrt{\gamma}} \to 0, \ \gamma \to \infty,
$$

and so we have  $\hat{y}(t) \leq 0$ .

Now we prove the inelastic shock condition. Notice that if  $y(t_0) = 0$ ,  $w(t_0) \ge 0$ , then, for small  $\theta > 0$ , we have

$$
0 \le w(t) \le \bar{M} - \frac{\gamma}{2}y^2(t), \ \ t \in [t_0, t_0 + \theta].
$$

Since the solution to the Cauchy problem

$$
\dot{y} = \bar{M} - \frac{\gamma}{2}y^2
$$
,  $y(t_0) = 0$ ,

is given by

$$
y(t) = \sqrt{\frac{2\bar{M}}{\gamma}} \frac{e^{\sqrt{2\bar{M}\gamma}(t-t_0)} - 1}{e^{\sqrt{2\bar{M}\gamma}(t-t_0)} + 1},
$$

we get

$$
w(t)\leq \bar{M}\left(1-\left(\frac{e^{\sqrt{2\bar{M}\gamma}(t-t_0)}-1}{e^{\sqrt{2\bar{M}\gamma}(t-t_0)}+1}\right)^2\right)\rightarrow 0,\; \gamma\rightarrow \infty.
$$

Thus we have the inelastic shock condition  $w(t_0 + 0) = 0$  satisfied.

Now we are in a position to define the solution to Cauchy problem  $(2)$  -  $(5)$ .

<span id="page-6-0"></span>**Definition 1.** We say that  $(x, y, v, w) \in AC([0, T], R^n) \times AC([0, T], R) \times AC([0, T], R^n) \times$  $BV([0,T], R)$  is a backlash solution corresponding to a control u, if  $(x, y, v, w, u)$  is a limit of some sequence of admissible control processes

$$
(x_{\gamma_{k\,l}},y_{\gamma_{k\,l}},v_{\gamma_{k\,l}},w_{\gamma_{k\,l}},u_{\gamma_{k\,l}})
$$

such that  $(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}})$  converges uniformly to  $(x, y, v)$ ,  $w_{\gamma_{k_l}}$  converges to w in the weak\* topology of  $BV([0,T], R)$  and  $u_{\gamma_{kl}}$  converges to u in the weak\* topology of  $L_{\infty}([0,T], R^m)$ , as  $l \to \infty$ .

In general the solution is not unique.

#### Comparison with MSMM solution

In general, the set of MSMM solutions is strictly larger than the set of backlash solutions. Indeed, let us consider a point body moving along a line:

$$
\ddot{y} = u - N, \ y \le 0, \ y(0) = \dot{y}(0) = 0.
$$

There exists  $u(\cdot) \in C^{\infty}$  such that the MSMM solution is not unique (see [\[1\]](#page-22-1)). Put  $U(t) =$  ${u(t)}$  and choose the sequence  $\gamma_k \to \infty$  such that the sequence of approximating solutions converges. So, we have a unique backlash solution.

# 3 Approximating problem

To simplify the forthcoming analysis we now proceed assuming that  $U(t) = U$ , where U is a compact and convex set.

 $\Box$ 

Let  $(\hat{x}, \hat{y}, \hat{v}, \hat{w}, \hat{u})$  be a global optimal solution of the problem

<span id="page-7-1"></span>
$$
T \to \min,\tag{18}
$$

$$
\dot{x} = v,\tag{19}
$$

$$
\dot{y} = w,\tag{20}
$$

$$
\dot{v} = f(x, y, v, w, u),\tag{21}
$$

$$
dw = g(x, y, v, w, u)dt - d\nu, \quad d\nu \ge 0, \quad yd\nu = 0,
$$
\n(22)

$$
y \le 0, \quad y(t) = 0 \Longrightarrow w(t+0) = 0,\tag{23}
$$

$$
x(0) = x_0, \ y(0) = y_0 < 0, \ v(0) = v_0, \ w(0) = w_0,\tag{24}
$$

$$
x(T) = x_1, \ y(T) = y_1 < 0, \ v(T) = v_1, \ w(T) = w_1. \tag{25}
$$

Let  $\hat{T}$  be the optimal time. According to the Definition [1](#page-6-0) there exists a sequence  $\gamma_{k_l} \to \infty$ such that

<span id="page-7-2"></span>
$$
(\hat{x}, \hat{y}, \hat{v}, \hat{w}, \hat{u}) = \lim_{l \to \infty} (x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}}),
$$
\n(26)

where  $(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}})$  is a control process of the system

$$
\dot{x}_{\gamma_{k_l}} = v_{\gamma_{k_l}},\tag{27}
$$

$$
\dot{y}_{\gamma_{k_l}} = w_{\gamma_{k_l}},\tag{28}
$$

$$
\dot{v}_{\gamma_{k_l}} = f(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}}),
$$
\n(29)

$$
\dot{w}_{\gamma_{k_l}} = g(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}}) - \gamma_{k_l}(y_{\gamma_{k_l}})_+(w_{\gamma_{k_l}})_+, \tag{30}
$$

$$
x_{\gamma_{k_l}}(0) = x_0, \ y_{\gamma_{k_l}}(0) = y_0, \ v_{\gamma_{k_l}}(0) = v_0, \ w_{\gamma_{k_l}}(0) = w_0.
$$
\n
$$
(31)
$$

There exists a sequence  $T_l$  such that  $\lim_{l \to \infty} T_l = \hat{T}$  and

$$
\lim_{l \to \infty} (x_{\gamma_{k_l}}(T_l), y_{\gamma_{k_l}}(T_l), v_{\gamma_{k_l}}(T_l), w_{\gamma_{k_l}}(T_l)) = (x_1, y_1, v_1, w_1).
$$

(Here we use the condition that  $y_1 < 0$ . This implies that  $\hat{w}$  is continuous in a neighborhood of  $\hat{T}$ .)

Now, we consider the following time-optimal control problem:

<span id="page-7-0"></span>
$$
T \to \min,\tag{32}
$$

$$
\dot{x} = v,\tag{33}
$$

$$
\dot{y} = w,\tag{34}
$$

$$
\dot{v} = f(x, y, v, w, u),\tag{35}
$$

$$
\dot{w} = g(x, y, v, w, u) - \gamma_{k_l} y_+ w_+, \tag{36}
$$

$$
x(0) = x_0, \ y(0) = y_0, \ v(0) = v_0, \ w(0) = w_0,
$$
\n
$$
(37)
$$

$$
x(T) = x_{\gamma_{k_l}}(T_l), \ y(T) = y_{\gamma_{k_l}}(T_l), \ v(T) = v_{\gamma_{k_l}}(T_l), \ w(T) = w_{\gamma_{k_l}}(T_l). \tag{38}
$$

This problem has an admissible solution  $(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}})$ . Denote by

$$
(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{u}_{\gamma_{k_l}})
$$

an optimal solution to this problem. The corresponding optimal time is  $\hat{T}_l \leq T_l$ , with  $\liminf \hat{T}_l = \hat{T}$  and, without loss of generality, we can consider that  $\hat{T}_l$  is a monotone increasing l→∞ sequence.

Applying necessary conditions of optimality to this problem we see that there exist  $(q, s, p, r) \in AC([0, \hat{T}], R^{n+1+n+1})$  (we omit the index  $\gamma_{k_l}$ ) and a constant  $H_l$  satisfying the following conditions (see [\[11,](#page-23-9) Theorem 8.7.1]):

<span id="page-8-0"></span>
$$
\dot{q} = -(\nabla_x \hat{f}_{\gamma_{k_l}})^* p - \nabla_x \hat{g}_{\gamma_{k_l}} r,\tag{39}
$$

$$
\dot{s} = -\langle \partial_y \hat{f}_{\gamma_{k_l}}, p \rangle - \partial_y \hat{g}_{\gamma_{k_l}} r + \gamma_{k_l} h_y (\hat{w}_{\gamma_{k_l}})_+ r,\tag{40}
$$

$$
\dot{p} = -q - (\nabla_v \hat{f}_{\gamma_{k_l}})^* p - \nabla_v \hat{g}_{\gamma_{k_l}} r,\tag{41}
$$

$$
\dot{r} = -s - \langle \partial_w \hat{f}_{\gamma_{k_l}}, p \rangle - \partial_w \hat{g}_v r + \gamma_{k_l} h_w (\hat{y}_{\gamma_{k_l}})_+ r,
$$
\n
$$
\max((a, \hat{y})_{k_l}, \hat{y}_{k_l}) = \langle \hat{g}_v, \hat{g}_v, \hat{g}_v, \hat{g}_v, \hat{g}_v \rangle
$$
\n(42)

$$
\max_{u \in U} (\langle q, \hat{v}_{\gamma_{k_l}} \rangle + s \hat{w}_{\gamma_{k_l}} + \langle p, f(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, u) \rangle \n+ r(g(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, u) - \gamma_{k_l}(\hat{y}_{\gamma_{k_l}}) + (\hat{w}_{\gamma_{k_l}}) + ) ) \n= \langle q, \hat{v}_{\gamma_{k_l}} \rangle + s \hat{w}_{\gamma_{k_l}} + \langle p, \hat{f}_{\gamma_{k_l}} \rangle + r(\hat{g}_{\gamma_{k_l}} - \gamma_{k_l}(\hat{y}_{\gamma_{k_l}}) + (\hat{w}_{\gamma_{k_l}}) + ) \equiv H_l \ge 0,
$$
\n(43)

$$
|q(\hat{T}_l)|^2 + |s(\hat{T}_l)|^2 + |p(\hat{T}_l)|^2 + |r(\hat{T}_l)|^2 = 1,
$$
\n(44)

where  $\hat{f}_{\gamma_{k_l}} = f(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}} = g(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{u}_{\gamma_{k_l}})$ . The functions

$$
h_y(t) = \begin{cases} 0, & \hat{y}_{\gamma_{k_l}}(t) < 0, \\ h \in [0, 1], & \hat{y}_{\gamma_{k_l}}(t) = 0, \\ 1, & \hat{y}_{\gamma_{k_l}}(t) > 0, \end{cases}
$$

and

$$
h_w(t) = \begin{cases} 0, & \hat{w}_{\gamma_{k_l}}(t) < 0, \\ h \in [0, 1], & \hat{w}_{\gamma_{k_l}}(t) = 0, \\ 1, & \hat{w}_{\gamma_{k_l}}(t) > 0, \end{cases}
$$

are measurable.

### 4 Main assumption

Recall that the set of density points of any measurable set  $A \subset [0, \hat{T}]$  is

$$
D_A = \{t \in A \; : \; \exists \; \lim_{\delta \downarrow 0} \frac{\text{meas} \left( [t - \delta, t + \delta] \cap A \right)}{2\delta} = 1 \}.
$$

It is well known that meas  $(A \setminus D_A) = 0$ .

Let  $E \subset [0, \hat{T}]$  be the set such that if  $t \in E$ , then t is a Lebesgue point of  $\dot{v}_{\gamma_{k_l}}, \dot{w}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}$  $\dot{q}$ ,  $\dot{s}$ ,  $\dot{p}$ , and  $\dot{r}$  simultaneously and such that  $\hat{y}_{\gamma_{k_l}}(t) \ge 0$ ,  $\hat{w}_{\gamma_{k_l}}(t) = 0$ .

In what follows we restrict attention to problems where conditions [\(39\)](#page-8-0) - [\(44\)](#page-8-0) for the approximating problems are such that meas  $(E) = 0$  or that

$$
\frac{d}{dt}(-\partial_w \hat{g}_{\gamma_{k_l}}r + \gamma_{k_l}h_w(\hat{y}_{\gamma_{k_l}})_+r) = 0, \quad t \in D_E.
$$

The above derivative is understood in the following sense: for any  $\phi$ 

$$
\frac{d}{dt}\phi(t^*) = \lim_{t \to t^* \atop D_E} \frac{\phi(t) - \phi(t^*)}{t - t^*}.
$$

We now present some examples to show how this main assumption can be verified.

<span id="page-9-0"></span>Example 1. Consider the system

$$
\ddot{y} = u - N, \ N \ge 0, \ y \le 0, \ u \in [-1, 1].
$$

The corresponding approximating system has the form

$$
\dot{y} = w,
$$
  

$$
\dot{w} = u - \gamma y_+ w_+.
$$

We apply the necessary conditions [\(39\)](#page-8-0)-[\(44\)](#page-8-0) to the the minimum time problem associated to the system above (see problem  $(32)$ – $(38)$ ). The adjoint system is

$$
\begin{aligned}\n\dot{s} &= \gamma h_y w_+ r, \\
\dot{r} &= -s + \gamma h_w y_+ r.\n\end{aligned}
$$

From the maximum condition [\(42\)](#page-8-0) we deduce that

$$
u = \begin{cases} 1, & r > 0, \\ -1, & r < 0. \end{cases}
$$

Let E be the set of all Lebesque point t of w; u, s, and r where  $y(t) \geq 0$  and  $w(t) = 0$ . If  $t \in D_E$ , then  $\dot{w}(t) = 0$ . Otherwise t is an isolated point of E or does not belong to E. Hence we have  $u(t) = 0$ . The maximum condition implies that  $r(t) = 0$ . Since  $s^2 + r^2 \neq 0$ , we obtain  $s(t) \neq 0$ . This implies that  $\dot{r}(t) = -s(t) \neq 0$ . Therefore  $t \notin D_E$ . So, in this example meas  $(E) = 0$ .

<span id="page-9-1"></span>Example 2. Consider a cylinder attached to a spring with a piston moving inside the cylin-der as in Figure [1.](#page-10-0) Assume that we apply a force  $u \in [-1,1]$  to the piston.

Informally, the equations of motion are

$$
M\ddot{X} = \alpha(\dot{Y} - \dot{X}) - kX - \beta \dot{X} + N,
$$
  
\n
$$
\ddot{Y} = \alpha(\dot{X} - \dot{Y}) + u - N,
$$
  
\n
$$
N \ge 0, \quad X \ge Y, \quad u \in [-1, 1],
$$



<span id="page-10-0"></span>Figure 1: Here,  $X$  is the position of the bottom of the cylinder and  $Y$  is the position of the piston. The parameters  $\alpha$  and  $\beta$  are the resistance coefficients while k is the stiffness of the spring. Moreover, we have  $V = \dot{X}$  and  $W = \dot{Y}$ .

where  $N$  is the reaction force. In the above  $M$  is the mass of the cylinder and the mass of the piston is 1.

Introducing new coordinates  $x = MX +Y$  and  $y = Y - X$  we obtain the system in canonical form

$$
\dot{x} = v,\n\dot{y} = w,\n\dot{v} = -a(x - y) - c(v - w) + u,\n\dot{w} = a(x - y) + c(v - w) - bw + u - 2N,
$$

where

$$
a = \frac{k}{M+1}
$$
,  $b = \alpha \frac{M+1}{M}$ ,  $c = \frac{\beta}{M+1}$ .

The approximating system has the form

$$
\dot{x} = v,\n\dot{y} = w,\n\dot{v} = -a(x - y) - c(v - w) + u,\n\dot{w} = a(x - y) + c(v - w) - bw + u - \gamma y_{+}w_{+},
$$

and the corresponding adjoint system is

<span id="page-10-1"></span>
$$
\dot{q} = a(p - r),\tag{45}
$$

$$
\dot{s} = -a(p - r) + \gamma h_y w_+ r,\tag{46}
$$

$$
\dot{p} = -q + c(p - r),\tag{47}
$$

$$
\dot{r} = -s - c(p - r) + br + \gamma h_w y_+ r. \tag{48}
$$

Moreover from the maximum condition we have

<span id="page-11-1"></span>
$$
u = \begin{cases} 1, & p+r > 0, \\ -1, & p+r < 0. \end{cases}
$$
 (49)

Let E be the set of all Lebesgue points t of v; wi, u, q, s, p, and r where  $y(t) \geq 0$  and  $w(t) = 0.$ 

If  $t \in D_E$ , then  $\dot{w}(t) = 0$  and we have

<span id="page-11-0"></span>
$$
0 = a(x(t) - y(t)) + cv(t) + u(t).
$$
\n(50)

Hence

<span id="page-11-2"></span>
$$
\dot{v}(t) = 2u(t). \tag{51}
$$

Consider a sequence  $t_j \in D_E$ ,  $j = 1, 2, \ldots$ , converging to t. Since at all points  $t_j$  equality [\(50\)](#page-11-0) holds, we get

$$
0 = a \frac{x(t_j) - x(t)}{t_j - t} - a \frac{y(t_j) - y(t)}{t_j - t} + c \frac{v(t_j) - v(t)}{t_j - t} + \frac{u(t_j) - u(t)}{t_j - t}.
$$

Passing to the limit, we obtain

$$
0 = av(t) + cv(t) + \lim_{k \to \infty} \frac{u(t_j) - u(t)}{t_j - t}.
$$

Seeking a contradiction, assume that  $p(t)+r(t) \neq 0$ . It follows from [\(49\)](#page-11-1) that  $u(t) = u(t<sub>j</sub>) =$  $\pm 1$  and we get

$$
0 = av(t) + cv(t).
$$

In the same way we have

$$
0 = av(t_j) + cv(t_j).
$$

From [\(51\)](#page-11-2) we obtain

$$
0 = av(t_j) \pm 2c.
$$

Passing to the limit in the equality

$$
0 = a \frac{v(t_j) - v(t)}{t_j - t},
$$

we get  $0 = \dot{v}(t) = 2u(t)$ . Hence by the maximum condition we have  $p(t) + r(t) = 0$ . The same is true for the points  $t_j$ . Passing to the limit in the equality

$$
0 = \frac{p(t_j) - p(t)}{t_j - t} + \frac{r(t_j) - r(t)}{t_j - t},
$$

we conclude that  $\dot{p}(t) + \dot{r}(t) = 0$ . In the same way we have  $\dot{p}(t_j) + \dot{r}(t_j) = 0$ . Since  $\ddot{p}(t)$ exists, we see from  $(47)$  that there exists  $\ddot{r}(t)$  and

$$
\ddot{r}(t) = -\ddot{p}(t) = \dot{q}(t) - c(\dot{p}(t) - \dot{r}(t)) = -\dot{s} - c(\dot{p}(t) - \dot{r}(t)).
$$

On the other hand, we have

$$
\ddot{r}(t) = -\dot{s} - c(\dot{p}(t) - \dot{r}(t)) + \frac{d}{dt}(br + \gamma h_w y_+ r).
$$

Hence

$$
\frac{d}{dt}(br + \gamma h_w y_+ r) = 0, \ \ t \in D_E.
$$

This shows that our main assumption holds for this example.

# 5 Necessary conditions

**Theorem 2.** There exists a solution  $(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$  to problem [\(18\)](#page-7-1)–[\(25\)](#page-7-1) such that there exist  $(q, \sigma, p, r, \mu) \in AC([0, \hat{T}], R^n) \times BV([0, \hat{T}], R) \times AC([0, \hat{T}], R^n) \times AC([0, \hat{T}], R) \times BV([0, \hat{T}], R)$ and a constant  $\bar{H}$  satisfying

<span id="page-12-1"></span>
$$
\dot{q} = -(\nabla_x \bar{f})^* p - \nabla_x \bar{g} r,\tag{52}
$$

$$
d\sigma = -\langle \partial_y \bar{f}, p \rangle dt - \partial_y \bar{g} r dt + d\mu,
$$
\n(53)

$$
\dot{p} = -q - (\nabla_v \bar{f})^* p - \nabla_v \bar{g} r,\tag{54}
$$

$$
\dot{r} = -\sigma - \langle \partial_w \bar{f}, p \rangle - \partial_w \bar{g}r,\tag{55}
$$

$$
\max_{u \in U(t)} (\langle q, \bar{v} \rangle + \sigma \bar{w} + \langle p, f(\bar{x}, \bar{y}, \bar{v}, \bar{w}, u) \rangle + rg(\bar{x}, \bar{y}, \bar{v}, \bar{w}, u)) \n= \langle q, \bar{v} \rangle + \sigma \bar{w} + \langle p, f(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u}) \rangle + rg(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u}) \equiv \bar{H} \ge 0,
$$
\n(56)

$$
|q(\hat{T})|^2 + |\sigma(\hat{T})|^2 + |p(\hat{T})|^2 + |r(\hat{T})|^2 = 1.
$$
\n(57)

where  $\bar{f} = f(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$  and  $\bar{g} = g(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$ . Moreover

$$
\bar{x}(\hat{T}) = x_1, \ \bar{y}(\hat{T}) = y_1, \ \bar{v}(\hat{T}) = v_1, \ \bar{w}(\hat{T}) = w_1,
$$

and  $d\mu = 0$ , whenever  $y(t) < 0$ .

*Proof.* Recall the definition [\(26\)](#page-7-2). For each  $k_l$ , consider the approximating problem [\(32\)](#page-7-0)–[\(38\)](#page-7-0). The corresponding necessary conditions for that problem are given by [\(39\)](#page-8-0)–[\(44\)](#page-8-0).

Fixing  $k_l$ , set

$$
\xi = s + \langle \partial_w \hat{f}_{\gamma_{k_l}}, p \rangle + \partial_w \hat{g}_{\gamma_{k_l}} r - \gamma_{k_l} h_w(\hat{y}_{\gamma_{k_l}})_+ r.
$$

Under our main assumption, we have

<span id="page-12-0"></span>
$$
\dot{\xi} = -\langle \partial_y \hat{f}_{\gamma_{k_l}}, p \rangle - \partial_y \hat{g}_{\gamma_{k_l}} r + \gamma_{k_l} h_y(\hat{w}_{\gamma_{k_l}})_+ r + \frac{d}{dt} \langle \partial_w \hat{f}_{\gamma_{k_l}}, p \rangle + \frac{d}{dt} (\partial_w \hat{g}_{\gamma_{k_l}} r)
$$
\n
$$
+ \begin{cases}\n-\frac{d}{dt}(\partial_w \hat{g}_{\gamma_{k_l}} r), & t \in D_E, \\
0, & t \in \{t : \hat{y}_{\gamma_{k_l}}(t) < 0 \text{ or } \hat{w}_{\gamma_{k_l}}(t) < 0\}, \\
-\gamma_{k_l} h_w \hat{w}_{\gamma_{k_l}} r - \gamma_{k_l} (\hat{y}_{\gamma_{k_l}})_+ \dot{r}, & t \in \{t : \hat{y}_{\gamma_{k_l}}(t) > 0 \text{ and } \hat{w}_{\gamma_{k_l}}(t) > 0\},\n\end{cases}
$$
\n
$$
= -\langle \partial_y \hat{f}_{\gamma_{k_l}}, p \rangle - \partial_y \hat{g}_{\gamma_{k_l}} r + \frac{d}{dt} \langle \partial_w \hat{f}_{\gamma_{k_l}}, p \rangle + \frac{d}{dt} (\partial_w \hat{g}_{\gamma_{k_l}} r)
$$
\n
$$
+ \begin{cases}\n-\frac{d}{dt}(\partial_w \hat{g}_{\gamma_{k_l}} r), & t \in D_E, \\
0, & t \in \{t : y(t) < 0 \text{ or } w(t) < 0\}, \\
-\gamma_{k_l}(\hat{y}_{\gamma_{k_l}})_+ \dot{r}, & t \in \{t : y(t) > 0 \text{ and } w(t) > 0\},\n\end{cases}
$$
\n(58)

and

$$
\dot{r} = -\xi.
$$

(In the above, notice that meas( $\{t : \hat{y}_{\gamma_{k_l}}(t) = 0, \hat{w}_{\gamma_{k_l}}(t) \neq 0\}$ ) = 0.) From these equations and recalling that  $\langle a, b \rangle \geq -|\langle a, b \rangle| \geq -\frac{|a|^2 + |b|^2}{2}$  $\frac{1}{2}$  for any two vectors a and b, we get

$$
\frac{1}{2}\frac{d}{dt}\xi^2 \ge -M_5(|q|^2 + \xi^2 + |p|^2 + r^2).
$$

Using the above inequality and multiplying [\(32\)](#page-7-0) by q, [\(34\)](#page-7-0) by p and  $\dot{r} = -\xi$  by r, we deduce that 1  $\overline{1}$ 

$$
\frac{1}{2}\frac{d}{dt}(|q|^2 + \xi^2 + |p|^2 + r^2) \ge -M_6(|q|^2 + \xi^2 + |p|^2 + r^2).
$$

Appealing now to the Gronwall inequality and the nontriviality condition

$$
|q(\hat{T}_l)|^2 + |s(\hat{T}_l)|^2 + |p(\hat{T}_l)|^2 + |r(\hat{T}_l)|^2 = 1,
$$

we see that  $|q|^2 + \xi^2 + |p|^2 + r^2$  is bounded

$$
|q|^2 + \xi^2 + |p|^2 + r^2 \le M_7
$$

and this estimate does not depend on  $\gamma$ .

Multiplying [\(58\)](#page-12-0) by sign  $(\xi(t))$  and integrating, we get

<span id="page-13-0"></span>
$$
|\xi(\hat{T}_l)| - |\xi(0)| \ge -M_8 + \int_0^{\hat{T}_l} \gamma_{k_l}(\hat{y}_{\gamma_{k_l}})_+ |\xi(t)| dt.
$$
\n(59)

Up to now we considered  $k_l$  fixed and so the adjoint variable had no subscript. From now on, we want to focus on the case where  $l \to \infty$  and so we need to identify the adjoint variables with the subscript  $\gamma_{k_l}$ . Set

$$
\sigma_{\gamma_{k_l}}=s_{\gamma_{k_l}}-\gamma_{k_l}h_w(\hat{y}_{\gamma_{k_l}})_+r_{\gamma_{k_l}}
$$

and

$$
\dot{\mu}_{\gamma_{k_l}} dt = \begin{cases}\n-\frac{d}{dt} (\partial_w \hat{g}_{\gamma_{k_l}} r_{\gamma_{k_l}}) dt, & t \in (D_E)_{\gamma_{k_l}}, \\
0, & t \in \{t \; : \; \hat{y}_{\gamma_{k_l}}(t) < 0 \text{ or } \hat{w}_{\gamma_{k_l}}(t) < 0 \}, \\
\gamma_{k_l} (\hat{y}_{\gamma_{k_l}})_+ \xi_{\gamma_{k_l}} dt, & t \in \{t \; : \; \hat{y}_{\gamma_{k_l}}(t) > 0 \text{ and } \hat{w}_{\gamma_{k_l}}(t) > 0 \}.\n\end{cases}
$$

Recall that  $\sigma_{\gamma_{k_l}} = s_{\gamma_{k_l}}$  whenever  $w_{\gamma_{k_l}} < 0$ . From [\(39\)](#page-8-0)–[\(44\)](#page-8-0) we have

<span id="page-13-1"></span>
$$
\dot{q}_{\gamma_{k_l}} = -(\nabla_x \hat{f}_{\gamma_{k_l}})^* p_{\gamma_{k_l}} - \nabla_x \hat{g}_{\gamma_{k_l}} r_{\gamma_{k_l}},\tag{60}
$$

$$
\dot{\sigma}_{\gamma_{k_l}} = -\langle \partial_y \hat{f}_{\gamma_{k_l}}, p_{\gamma_{k_l}} \rangle - \partial_y \hat{g}_{\gamma_{k_l}} r_{\gamma_{k_l}} + \dot{\mu}_{\gamma_{k_l}} \tag{61}
$$

$$
\dot{p}_{\gamma_{k_l}} = -q_{\gamma_{k_l}} - (\nabla_v \hat{f}_{\gamma_{k_l}})^* p_{\gamma_{k_l}} - \nabla_v \hat{g}_{\gamma_{k_l}} r_{\gamma_{k_l}},\tag{62}
$$

$$
\dot{r}_{\gamma_{k_l}} = \sigma_{\gamma_{k_l}} - \langle \partial_w \hat{f}_{\gamma_{k_l}}, p_{\gamma_{k_l}} \rangle - \partial_w \hat{g}_v r_{\gamma_{k_l}},
$$
\n
$$
\max_{u \in U} (\langle q_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}} \rangle + \sigma_{\gamma_{k_l}} \hat{w}_{\gamma_{k_l}} + \langle p_{\gamma_{k_l}}, f(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, u) \rangle
$$
\n(63)

+
$$
r_{\gamma_{k_l}} g(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, u))
$$
  
=  $\langle q_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}} \rangle + \sigma_{\gamma_{k_l}} \hat{w}_{\gamma_{k_l}} + \langle p_{\gamma_{k_l}}, \hat{f}_{\gamma_{k_l}} \rangle + r_{\gamma_{k_l}} \hat{g}_{\gamma_{k_l}} \equiv \hat{H}_l \ge 0,$  (64)

$$
|q_{\gamma_{k_l}}(\hat{T}_l)|^2 + |\sigma_{\gamma_{k_l}}(\hat{T}_l)|^2 + |p_{\gamma_{k_l}}(\hat{T}_l)|^2 + |r_{\gamma_{k_l}}(\hat{T}_l)|^2 = 1.
$$
\n(65)

Consider the interval  $[0, \hat{T}_1]$ . From [\(59\)](#page-13-0) we see that, without loss of generality, the measures  $\mu_{\gamma_{k_l}}dt$  converge in weak\* topology of to some measure  $d\mu^1$ ,  $\mu^1 \in BV([0, \hat{T}_1], R)$ . Hence (see [\(58\)](#page-12-0)), without loss of generality,  $\xi_{\gamma_{k_l}}$  also converges in weak\* topology of  $BV([0, \hat{T}_1], R)$ to some function  $\xi^1(t)$ . Therefore the sequence  $\sigma_{\gamma_{k_l}}$  also converges in weak\* topology of  $BV([0, \hat{T}_1], R)$  to some function  $\sigma^1(t)$  (we do not relabel). The functions  $(q_{\gamma_{k_l}}, \sigma_{\gamma_{k_l}}, p_{\gamma_{k_l}}, r_{\gamma_{k_l}})$ are bounded in  $[0, \hat{T}_1]$ . It follows from [\(60\)](#page-13-1), [\(62\)](#page-13-1) and [\(63\)](#page-13-1) that  $(q_{\gamma_{k_l}}, p_{\gamma_{k_l}}, r_{\gamma_{k_l}})$  are also bounded. Appealing to the Arzela-Ascoli Theorem we conclude that, without loss of generality,  $(q_{\gamma_{k_l}}, p_{\gamma_{k_l}}, r_{\gamma_{k_l}})$  uniformly converges to some function  $(q, p, r)$  in  $[0, \hat{T}_1]$  and the sequence  $\sigma_{\gamma_{k_l}}$  converges pointwisely to  $\sigma$  by Helly's first Theorem. Integrating [\(60\)](#page-13-1), [\(62\)](#page-13-1) and [\(63\)](#page-13-1) over  $[t, \hat{T}_1]$ , for  $t < \hat{T}_1$  we have

<span id="page-14-0"></span>
$$
q_{\gamma_{k_l}}(t) = q_{\gamma_{k_l}}(\hat{T}_1) - \int_t^{\hat{T}_1} (-(\nabla_x \hat{f}_{\gamma_{k_l}})^* p_{\gamma_{k_l}} - \nabla_x \hat{g}_{\gamma_{k_l}} r_{\gamma_{k_l}}) ds,
$$
\n(66)

$$
p_{\gamma_{k_l}}(t) = p_{\gamma_{k_l}}(\hat{T}_1) - \int_t^{\hat{T}_1} (-q_{\gamma_{k_l}} - (\nabla_v \hat{f}_{\gamma_{k_l}})^* p_{\gamma_{k_l}} - \nabla_v \hat{g}_{\gamma_{k_l}} r_{\gamma_{k_l}}) ds, \tag{67}
$$

$$
r_{\gamma_{k_l}}(t) = r_{\gamma_{k_l}}(\hat{T}_1) - \int_t^{\hat{T}_1} (-\sigma_{\gamma_{k_l}} - \langle \partial_w \hat{f}_{\gamma_{k_l}}, p_{\gamma_{k_l}} \rangle - \partial_w \hat{g}_v r_{\gamma_{k_l}}) ds \tag{68}
$$

It is easy to conclude that  $(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}})$  converge to some  $(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$ , where  $\bar{x} \in AC([0, \hat{T}_1], R^n)$ ,  $\bar{y} \in AC([0, \hat{T}_1], R)$ ,  $\bar{v} \in AC([0, \hat{T}_1], R^n)$ ,  $\bar{w} \in BV([0, \hat{T}_1], R)$  and  $\bar{\mu} \in$  $L_\infty((0, \hat{T}_1], R^m)$ , and, moreover,  $(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}})$  converge uniformly,  $w_{\gamma_{k_l}}$  converges in the weak\* topology in  $BV$  and  $u_{\gamma_{k_l}}$  converges in the weak\* topology in  $L_{\infty}$ . Passing to the limit in [\(66\)](#page-14-0) - [\(68\)](#page-14-0) we get

$$
q(t) = q(\hat{T}_1) - \int_t^{\hat{T}_1} (- (\nabla_x \bar{f})^* p - \nabla_x \bar{g} r) ds,
$$
\n(69)

$$
p(t) = p(\hat{T}_1) - \int_t^{\hat{T}_1} (-q - (\nabla_v \bar{f})^* p - \nabla_v \bar{g}r) ds,
$$
\n(70)

$$
r(t) = r(\hat{T}_1) - \int_t^{\hat{T}_1} (-\sigma - \langle \partial_w \bar{f}, p \rangle - \partial_w \bar{g}r) ds,
$$
\n(71)

where  $\bar{f} = f(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$  and  $\bar{g} = g(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$ . It follows that  $(q, p, r)$  are absolutely continuous.

Consider now any continuous function  $\sigma^*$  defined in [0,  $\hat{T}_1$ ]. Then we have

$$
\int_0^{\hat{T}_1} \sigma^* \dot{\sigma}_{\gamma_{k_l}} ds = \int_0^{\hat{T}_1} \sigma^* (-\langle \partial_y \hat{f}_{\gamma_{k_l}}, p_{\gamma_{k_l}} \rangle - \partial_y \hat{g}_{\gamma_{k_l}} r_{\gamma_{k_l}} + \dot{\mu}_{\gamma_{k_l}}) ds.
$$

Passing to the limit in above equality we get [\(53\)](#page-12-1) in the interval  $[0, \hat{T}_1]$ .

Next, we consider the interval  $[0, \hat{T}_2]$ . From the previous subsequences involving the control processes and dual variables we extract another sequence where the convergence holds in the interval  $[0, \hat{T}_2]$ , with  $\hat{T}_2 > \hat{T}_1$ . We repeat this process for all intervals  $[0, \hat{T}_3]$ ,

 $[0, \hat{T}_4]$ , etc. Then, we extract the diagonal subsequence to get convergence in the interval  $[0, T]$ .

We now concentrate on  $(64)$ . Since f and g are affine with respect to u, we have

$$
\langle q_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}} \rangle + \sigma_{\gamma_{k_l}} \hat{w}_{\gamma_{k_l}} + \langle p_{\gamma_{k_l}}, f(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, u) \rangle + r_{\gamma_{k_l}} g(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, u)
$$
  
=  $H_l^0 + \langle h_l, u \rangle$ 

and

$$
\langle q_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}} \rangle + \sigma_{\gamma_{k_l}} \hat{w}_{\gamma_{k_l}} + \langle p_{\gamma_{k_l}}, \hat{f}_{\gamma_{k_l}} \rangle + r_{\gamma_{k_l}} \hat{g}_{\gamma_{k_l}} \equiv H_l
$$
  
=  $H_l^0 + \langle h_l, \hat{u}_l \rangle \geq 0$ ,

for some  $H_l^0$  and  $h_l$ . Thus, [\(64\)](#page-13-1) reads

<span id="page-15-0"></span>
$$
\max_{u \in U} \left\{ H_l^0 + \langle h_l, u \rangle \right\} = H_l^0 + \langle h_l, \hat{u}_l \rangle. \tag{72}
$$

We now take limits in [\(72\)](#page-15-0), i.e., we want to prove that [\(72\)](#page-15-0) converges to

$$
\max_{u \in U} \left\{ \bar{H}^0 + \langle \bar{h}, u \rangle \right\} = \bar{H}^0 + \langle \bar{h}, \bar{u} \rangle. \tag{73}
$$

It is an easy matter to see that  $H_l^0$  and  $h_l$  are bounded functions converging pointwisely to some functions  $\bar{H}^0$  and  $\bar{h}$ . Without loss of generality, we deduce that  $\hat{H}_l \to \bar{H}$ . Next, we show that  $\bar{H}^0 + \langle \bar{h}, \bar{u} \rangle = \bar{H}$  almost everywhere. Seeking a contradiction, assume that

$$
\text{meas}(I^>) = \text{meas}\left\{t : \ \bar{H}^0 + \langle \bar{h}, \bar{u} \rangle > \bar{H} \right\} > 0.
$$

Integrating, we get

$$
\bar{H}\text{meas}(I^>) = \lim_{l \to \infty} \int_{I^>} \left( H_l^0 + \langle h_l, \hat{u}_l \rangle \right) dt = \lim_{l \to \infty} \int_{I^>} \left( H_l^0 + \langle h_l - \bar{h}, \hat{u}_l \rangle + \langle \bar{h}, \hat{u}_l \rangle \right) dt
$$

$$
= \int_{I^>} \left( \bar{H}^0 + \langle \bar{h}, \bar{u} \rangle \right) dt > \bar{H}\text{meas}(I^*).
$$

This means that  $\bar{H}^0 + \langle \bar{h}, \bar{u} \rangle \leq \bar{H}$  almost everywhere. Analogously we show that  $\bar{H}^0 + \langle \bar{h}, \bar{u} \rangle \geq$  $\overline{H}$ , proving our claim that  $\overline{H}{}^0 + \langle \overline{h}, \overline{u} \rangle = \overline{H}$ .

We now assume that there exists an interval  $\tilde{I} \subset [0, \hat{T}]$  of positive measure such that  $\max_{u \in U} \{ \bar{H}^0 + \langle \bar{h}, u \rangle \} > \bar{H}^0 + \langle \bar{h}, \bar{u} \rangle$  for all  $t \in \tilde{I}$ . Then, there exists an admissible control  $\tilde{u}$  such that

$$
\bar{H}^0 + \langle \bar{h}, \tilde{u} \rangle > \bar{H}^0 + \langle \bar{h}, \bar{u} \rangle = \bar{H} \text{ for all } t \in \tilde{I}.
$$

It follows that there exists  $\epsilon > 0$  such that

$$
\bar{H}\text{meas}(\tilde{I}) + 2\epsilon < \int_{\tilde{I}} (\bar{H}^0 + \langle \bar{h}, \tilde{u} \rangle) dt
$$
  
= 
$$
\int_{\tilde{I}} (H_l^0 + \langle h_l, \tilde{u} \rangle) dt + \int_{\tilde{I}} (\bar{H}^0 - H_l^0 + \langle \bar{h} - h_l, \tilde{u} \rangle) dt
$$
  
\$\leq H\_l \text{ meas}(\tilde{I}) + \epsilon \leq \bar{H}\text{meas}(\tilde{I}) + 2\epsilon\$.

So we deduce that measure of  $\tilde{I}$  is 0, proving [\(56\)](#page-12-1). The theorem is then proved.

The main disadvantage of these necessary conditions is that, in general, we cannot guarantee the non triviality condition

<span id="page-15-1"></span>
$$
|q(t)|^2 + |\sigma(t)|^2 + |p(t)|^2 + |r(t)|^2 > 0
$$
\n(74)

 $\Box$ 

for all  $t \in [0, \hat{T}]$ . Below we present a special case where [\(74\)](#page-15-1) is satisfied for all  $t \in [0, \hat{T}]$ .

# 6 The case when the target set is a stable neighborhood of an equilibrium point

To better explain the main idea we consider a linear control system

<span id="page-16-0"></span>
$$
\dot{z} = Az + Bu, \ u \in U,\tag{75}
$$

where  $U \subset R^m$  is a convex compact set containing zero in its interior. Assume that the system is controllable. Then there exists a linear feedback  $u = Cz$  such that the zero equilibrium position of the system

$$
\dot{z} = (A + BC)z
$$

is asymptotically stable. Then there exists a positive definite matrix  $V$  such that

$$
\langle Vz, (A + BC)z \rangle \le -\frac{1}{2}|z|^2.
$$

Now suppose that  $z(t)$  is a time-optimal trajectory of system [\(75\)](#page-16-0) in a problem with the terminal set  $S = \{z : \langle z, Vz \rangle \leq \epsilon\}$ . (If  $\epsilon > 0$  is sufficiently small, then  $Cz \in U, z \in S$ .) Then the transversality condition at the final point  $z(T) \in S$  is  $p(T) = -\frac{Vz(T)}{V \cdot z(T)}$  $\frac{Vz(T)}{|Vz(T)|}$ . Let u be the optimal control. By the maximum principle we have

$$
\langle p(T), Az(T) + Bu(T) \rangle \ge \langle p(T), (A + BC)z(T) \rangle \ge \frac{|z(T)|^2}{2|Vz(T)|} \ge \rho(\epsilon) > 0.
$$

This guarantees that the Hamiltonian, which is constant along the optimal trajectory, is strictly positive. For brevity we shall call such a set  $S$  a stable neighborhood of an equilibrium point.

The same is true for nonlinear systems where the terminal point  $(x_1, y_1, 0, 0)$  is an equilibrium position and the linearization at this point is controllable.

Let  $(x_1, y_1, 0, 0), y_1 < 0$ , be an equilibrium point of control system  $(19)-(22)$  $(19)-(22)$  $(19)-(22)$  and

$$
S = \{(x, y, v, w) : \langle (x - x_1, y - y_1, v, w), V(x - x_1, y - y_1, v, w) \rangle \le \epsilon\}
$$

be a small stable neighborhood of this point. Let  $(\tilde{x}, \tilde{y}, \tilde{v}, \tilde{w}, \tilde{u})$  be a global optimal solution of the problem

$$
T \to \min,\tag{76}
$$

$$
\dot{x} = v,\tag{77}
$$

$$
\dot{y} = w,\tag{78}
$$

$$
\dot{v} = f(x, y, v, w, u),\tag{79}
$$

$$
dw = g(x, y, v, w, u)dt - d\nu, \quad d\nu \ge 0, \quad d\nu = 0, \ y < 0,\tag{80}
$$

$$
x(0) = x_0, \ y(0) = y_0 < 0, \ v(0) = v_0, \ w(0) = w_0,\tag{81}
$$

 $(x(T), y(T), v(T), w(T)) \in S.$  (82)

Let  $\hat{T}$  be the optimal time. There exist a sequence  $\gamma_{k_l} \to \infty$  and a sequence  $u_{\gamma_{k_l}}$  converging to  $\tilde{u}$  in the weak\* topology of  $L_\infty([0,\hat{T}],R^m)$  such that

$$
(\tilde{x}, \tilde{y}, \tilde{v}, \tilde{w}) = \lim_{l \to \infty} (x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}),
$$

where  $(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}})$  is the solution to the Cauchy problem

$$
\dot{x}_{\gamma_{k_l}} = v_{\gamma_{k_l}},\tag{83}
$$

$$
\dot{y}_{\gamma_{k_l}} = w_{\gamma_{k_l}},\tag{84}
$$

$$
\dot{v}_{\gamma_{k_l}} = f(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}}),
$$
\n(85)

$$
\dot{w}_{\gamma_{k_l}} = g(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}}) - \gamma_{k_l}(y_{\gamma_{k_l}})_+(w_{\gamma_{k_l}})_+, \tag{86}
$$

$$
x_{\gamma_{k_l}}(0) = x_0, \ y_{\gamma_{k_l}}(0) = y_0, \ v_{\gamma_{k_l}}(0) = v_0, \ w_{\gamma_{k_l}}(0) = w_0.
$$
\n
$$
(87)
$$

We have

$$
(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}})(T_l) \in (x_1, y_1, 0, 0) + (1 + \delta_l)(S - (x_1, y_1, 0, 0)),
$$

where  $T_l \uparrow \hat{T}$  and  $\delta_l \downarrow 0$ . Consider the following time-optimal control problem:

$$
T \to \min,\tag{88}
$$

$$
\dot{x} = v,\tag{89}
$$

$$
\dot{y} = w,\tag{90}
$$

$$
\dot{v} = f(x, y, v, w, u),\tag{91}
$$

$$
\dot{w} = g(x, y, v, w, u) - \gamma_{k_l} y_+ w_+, \tag{92}
$$

$$
x(0) = x_0, y(0) = y_0, v(0) = v_0, w(0) = w_0,
$$
\n(93)

$$
(x(T), y(T), v(T), w(T)) \in (x_1, y_1, 0, 0) + (1 + \delta_l)(S - (x_1, y_1, 0, 0)).
$$
 (94)

This problem has an admissible process  $(x_{\gamma_{k_l}}, y_{\gamma_{k_l}}, v_{\gamma_{k_l}}, w_{\gamma_{k_l}}, u_{\gamma_{k_l}})$ . Denote by  $(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}})$  $\hat{w}_{\gamma_{k_l}}, \hat{u}_{\gamma_{k_l}}$  an optimal solution to this problem. The corresponding optimal time is  $\hat{T}_l \leq T_l$ .

Applying necessary conditions of optimality to this problem we see that there exist  $(q, s, p, r) \in AC([0, \hat{T}], R^{n+1+n+1})$  and a constant  $H_l$  satisfying the following conditions:

$$
\dot{q} = -(\nabla_x \hat{f}_{\gamma_{k_l}})^* p - \nabla_x \hat{g}_{\gamma_{k_l}} r,\tag{95}
$$

$$
\dot{s} = -\langle \partial_y \hat{f}_{\gamma_{k_l}}, p \rangle - \partial_y \hat{g}_{\gamma_{k_l}} r + \gamma_{k_l} h_y (\hat{w}_{\gamma_{k_l}})_+ r,\tag{96}
$$

$$
\dot{p} = -q - (\nabla_v \hat{f}_{\gamma_{k_l}})^* p - \nabla_v \hat{g}_{\gamma_{k_l}} r,\tag{97}
$$

$$
\dot{r} = -s - \langle \partial_w \hat{f}_{\gamma_{k_l}}, p \rangle - \partial_w \hat{g}_{\gamma_{k_l}} r + \gamma_{k_l} h_w(\hat{y}_{\gamma_{k_l}})_+ r,\tag{98}
$$

$$
\max_{u \in U} (\langle q, \hat{v}_{\gamma_{k_l}} \rangle + s \hat{w}_{\gamma_{k_l}} + \langle p, f(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, u) \rangle \tag{99}
$$

$$
+r(g(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, u) - \gamma_{k_l}(\hat{y}_{\gamma_{k_l}})_{+}(\hat{w}_{\gamma_{k_l}})_{+}))
$$
  
=  $\langle q, \hat{v}_{\gamma_{k_l}} \rangle + s\hat{w}_{\gamma_{k_l}} + \langle p, \hat{f}_{\gamma_{k_l}} \rangle + r(\hat{g}_{-} \gamma_{k_l}(\hat{y}_{\gamma_{k_l}})_{+}(\hat{w}_{\gamma_{k_l}})_{+}) \equiv H_l \ge \rho(\epsilon) > 0,$  (100)

$$
(q, s, p, r)(\hat{T}_l) = -\frac{V(\hat{x}_{\gamma_{k_l}} - x_1, \hat{y}_{\gamma_{k_l}} - y_1, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}})}{|V(\hat{x}_{\gamma_{k_l}} - x_1, \hat{y}_{\gamma_{k_l}} - y_1, \hat{v}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}})|},
$$
\n(101)

where  $\hat{f}_{\gamma_{k_l}} = f(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}} = g(\hat{x}_{\gamma_{k_l}}, \hat{y}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{w}_{\gamma_{k_l}}, \hat{u}_{\gamma_{k_l}})$ . The functions  $\epsilon$ 0,  $\hat{y}_{\gamma_{k_l}}(t) < 0$ ,

$$
h_y(t) = \begin{cases} 0, & y_{\gamma_{k_l}}(t) < 0, \\ h \in [0, 1], & \hat{y}_{\gamma_{k_l}}(t) = 0, \\ 1, & \hat{y}_{\gamma_{k_l}}(t) > 0, \end{cases}
$$

and

$$
h_w(t) = \begin{cases} 0, & \hat{w}_{\gamma_{k_l}}(t) < 0, \\ h \in [0, 1], & \hat{w}_{\gamma_{k_l}}(t) = 0, \\ 1, & \hat{w}_{\gamma_{k_l}}(t) > 0, \end{cases}
$$

are measurable.

Arguing as above we deduce that the following result holds.

**Theorem 3.** There exists a time-optimal control process  $(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$ ,

 $(q, \sigma, p, r, \mu) \in AC([0, \hat{T}], R^n) \times BV([0, \hat{T}], R) \times AC([0, \hat{T}], R^n) \times AC([0, \hat{T}], R) \times BV([0, \hat{T}], R)$ and a constant  $\bar{H}$  satisfying

$$
\dot{q} = -(\nabla_x \bar{f})^* p - \nabla_x \bar{g} r,\tag{102}
$$

$$
d\sigma = -\langle \partial_y \bar{f}, p \rangle dt - \partial_y \bar{g} r dt + d\mu,
$$
\n(103)

$$
\dot{p} = -q - (\nabla_v \bar{f})^* p - \nabla_v \bar{g} r,\tag{104}
$$

$$
\dot{r} = -\sigma - \langle \partial_w \bar{f}, p \rangle - \partial_w \bar{g} r,\tag{105}
$$

$$
\max_{u \in U} (\langle q, \bar{v} \rangle + \sigma \bar{w} + \langle p, f(\bar{x}, \bar{y}, \bar{v}, \bar{w}, u) \rangle + rg(\bar{x}, \bar{y}, \bar{v}, \bar{w}, u))
$$

$$
= \langle q, \bar{v} \rangle + \sigma \bar{w} + \langle p, f(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u}) \rangle + rg(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u}) \equiv \bar{H} \ge \rho(\epsilon) > 0, \qquad (106)
$$

$$
|q(\hat{T})|^2 + |\sigma(\hat{T})|^2 + |p(\hat{T})|^2 + |r(\hat{T})|^2 = 1.
$$
\n(107)

where  $\bar{f} = f(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$  and  $\bar{g} = g(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})$ . Moreover

$$
(\bar{x}, \bar{y}, \bar{v}, \bar{w}, \bar{u})(\hat{T}) \in S,
$$

and  $d\mu = 0$ , whenever  $y(t) < 0$ .

## 7 Examples

We now go back to the systems introduced in the Examples [1](#page-9-0) and [2.](#page-9-1)

### 7.1 Example 1

Consider the problem associated to the system in Example [1:](#page-9-0)

$$
T \to \min,
$$
  
\n
$$
\ddot{y} = u - N, \quad N \ge 0, \quad y \le 0, \quad u \in [-1, 1],
$$
  
\n
$$
y(0) = y_0 < 0, \quad \dot{y}(0) = v_0, \quad (y(T), \dot{y}(T)) \in S,
$$

where S is a small stable neighborhood of a point  $(y_1, 0)$ ,  $y_1 < 0$ . Applying the necessary conditions we get

$$
d\sigma = d\mu,
$$
  

$$
\dot{r} = -\sigma.
$$

Moreover from the maximum condition we have

$$
u = \begin{cases} 1, & r > 0, \\ -1, & r < 0. \end{cases}
$$

If  $y < 0$  we have  $d\sigma = 0$ . Hence  $r = at + b$ ,  $a^2 + b^2 > 0$ . Therefore the control is constant or changes sign just ones. The motion along the boundary  $y = 0$  is the passage from a positive velocity to zero. The optimal trajectories are show in the Figure [2.](#page-19-0)



<span id="page-19-0"></span>Figure 2: Time-optimal trajectories for Example 1. The bold vertical arrow along the w axis shows the jump of velocity when the trajectory reaches the boundary of the set  $C = \{(y, w): y \le 0\}.$ 

### 7.2 Example 2

Consider again a piston moving inside a cylinder as in Example [2](#page-9-1) . Equations of motion are

$$
M\ddot{X} = \alpha(\dot{Y} - \dot{X}) - kX - \beta \dot{X} + N,
$$
  
\n
$$
\ddot{Y} = \alpha(\dot{X} - \dot{Y}) + u - N,
$$
  
\n
$$
N \ge 0, \quad X \ge Y, \quad u \in [-1, 1].
$$

We introduce the coordinates  $x = MX +Y$  and  $y = Y - X$  and consider the problem

$$
T \to \min,
$$
  
\n
$$
\dot{x} = v,
$$
  
\n
$$
\dot{y} = w,
$$
  
\n
$$
\dot{v} = -a(x - y) - c(v - w) + u,
$$
  
\n
$$
\dot{w} = a(x - y) + c(v - w) - bw + u - N, \quad N \ge 0, \quad y \le 0, \quad u \in [-1, 1],
$$
  
\n
$$
x(0) = x_0, \quad y(0) = y_0 < 0, \quad v(0) = v_0 < 0, \quad w(0) = w_0 > 0,
$$
  
\n
$$
(x, y, v, w)(T) \in S,
$$

where S is a small stable neighborhood of a point  $(y_1, y_1, 0, 0), y_1 < 0$ . (The system is controllable near this point.) Here  $x_0 = MX_0 + Y_0$ ,  $y_0 = Y_0 - X_0$ ,  $X_0 > 0$ ,  $Y_0 < 0$ ,  $v_0 = M\dot{X}_0 < 0, w_0 = -\dot{X}_0$ , and  $y_1 = Y_0$ . Applying the necessary conditions we see that there exist nontrivial  $(q, \sigma, p, r)$  and  $\mu$  satisfying

$$
\dot{q} = a(p - r),
$$
  
\n
$$
d\sigma = -a(p - r)dt + d\mu,
$$
  
\n
$$
\dot{p} = -q + c(p - r),
$$
  
\n
$$
\dot{r} = -\sigma - c(p - r) + br.
$$

From the maximum condition we have

$$
u = \begin{cases} 1, & p+r > 0, \\ -1, & p+r < 0. \end{cases}
$$

Let  $y < 0$ . Then we have the system

$$
\dot{q} = a(p - r),
$$
  
\n
$$
\dot{\sigma} = -a(p - r),
$$
  
\n
$$
\dot{p} = -q + c(p - r),
$$
  
\n
$$
\dot{r} = -\sigma - c(p - r) + br,
$$

Since the system is controllable, the subspace  $\{(q, \sigma, p, r) : p + r = 0\}$  is not invariant. Therefore, if  $y < 0$  the optimal control changes its sign at most at a finite number of moments of time.

Now suppose that  $y(t) = 0, t \in [t_1, t_2], y(t) < 0, t < t_1$ . If  $p+r = 0$ , then  $0 = -q - \sigma + br$ and  $\dot{q} + \dot{\sigma} = \dot{\mu}$ . Hence  $\dot{\mu} = b(-\sigma + 2cr + br)$  and we get

$$
\dot{\sigma} = -a(p - r) + b(-\sigma + 2cr + br).
$$

Thus for  $(q, \sigma, p, r)$  we have the linear system with the matrix

$$
A = \left(\begin{array}{cccc} 0 & 0 & a & -a \\ 0 & -b & -a & a + 2cb + b^2 \\ -1 & 0 & c & -c \\ 0 & -1 & -c & c + b \end{array}\right).
$$

The characteristic polynomial of this matrix is

$$
\lambda^2(\lambda^2 - 2c\lambda + 2a).
$$

The two-dimensional subspace  $L = \{(q, \sigma, p, r) : p + r = 0\}$  is now invariant. Obviously  $(q, \sigma, p, r)(t) \in L$  only if  $p(t_1) + r(t_1) = 0$  or  $p(t_2) + r(t_2) = 0$ , i.e.,  $t_1$  or  $t_2$  are the points where the control may change its sign.

The complete analysis of all optimal solutions in this case is a hard problem. Let us consider a simple, but interesting, case. Assume that the initial conditions are such that the

piston under the control  $u = 1$  can stop the motion of the cylinder at some point  $X = Y > 0$ . Let us imagine for a moment that there is no friction in the system, i.e.  $b = c = 0$ . Then the optimal control has the following structure:

$$
u(t) = \begin{cases} 1, & t \in [0, t_1], \\ -1, & t \in [t_1, t_2], \\ 1, & t \in [t_2, T], \end{cases}
$$

as illustrated in Figure [3.](#page-21-0)



<span id="page-21-0"></span>Figure 3: Time-optimal control for Example 2.

The piston passes the position  $Y = 0$  at some moment of time  $t < t_1$  and at  $t = t_1$  changes the sign before the collision with the cylinder. At the moment of collision it is already reducing its speed, and after the collision, during the contact with the cylinder, it arrives to the position  $Y = 0$  with zero speed at  $t = t^*$ . Then, it moves to its initial position  $Y_0$  as the controlled point body considered in the first example.

In the presence of negligible friction, the optimal control driving the system to a small stable neighborhood of  $(y_1, y_1, 0, 0)$  has the same structure.



Figure 4: The four main phases of the motion (with negligible friction) in Example 2. Phase 1, when the cylinder moves away from the wall while the piston moves in the opposite direction with acceleration, is on the top left figure. Phase 2, on the right top, is when the piston starts braking before collision with the bottom of the cylinder. Phase 3, on the bottom left, is when the piston collides with the bottom of the cylinder. Finally, Phase 4 depicts the situation where the piston returns to its initial position while the cylinder remains in its equilibrium position.

#### Acknowledgements

The authors gratefully thank the support of Portuguese Foundation for Science and Technology (FCT) in the framework of the Strategic Funding UIDB/04650/2020.

Also we thank the support by the ERDF - European Regional Development Fund through the Operational Programme for Competitiveness and Internationalisation - COMPETE 2020, INCO.2030, under the Portugal 2020 Partnership Agreement and by National Funds, Norte 2020, through CCDRN and FCT, within projects To Chair (POCI-01-0145-FEDER-028247), Upwind (PTDC/EEI-AUT/31447/2017 - POCI-01-0145-FEDER-031447) and Systec  $R\&D$ unit (UIDB/00147/2020).

## References

- <span id="page-22-1"></span>[1] P. Ballard, The dynamics of discrete mechanical systems with perfect unilateral constraints. Arch. Ration. Mech. Anal. 154, pp. 199-274 (2000) .
- <span id="page-22-0"></span>[2] F. Bernicot, J. Venel, Existence of solutions for second-order differential inclusions involving proximal normal cones. J. Math. Pures Appl. 98 pp. 257-294 (2012).
- <span id="page-23-6"></span>[3] T. H. Cao, B. Mordukhovich, Optimality conditions for a controlled sweeping process with applications to the crowd motion model. Disc. Cont. Dyn. Syst. Ser. B, vol. 22, pp. 267–306 (2017).
- <span id="page-23-7"></span>[4] G. Colombo, R. Henrion, N. D. Hoang, B. S. Mordukhovich, Optimal control of the sweeping process over polyhedral controlled sets. Journal of Differential Equations, vol. 260, 4, pp. 3397–3447 (2016).
- <span id="page-23-5"></span>[5] M. d. R. de Pinho, M. M. A. Ferreira, G. V. Smirnov, Necessary conditions for optimal control problems with sweeping systems and end point constraints. Optimization, vol. 71, 11, pp. 3363–3381 (2022).
- <span id="page-23-4"></span>[6] M. A. Krasnosel'skii, A. V. Pokrovskii, Systems with Hysteresis. Springer (1989).
- <span id="page-23-3"></span>[7] M.D.P. Monteiro Marques, Differential Inclusions in Nonsmooth Mechanical Problems. Birkhauser, Basel, Boston, Berlin (1993).
- <span id="page-23-1"></span>[8] J.J. Moreau, Standard inelastic shocks and the dynamics of unilateral constraints. In Unilateral Problems in Structural Analysis: Proceedings of the Second Meeting on Unilateral Problems in Structural Analysis, Ravello, September 22–24, 1983, pp. 173- 221. Vienna: Springer Vienna (1985).
- <span id="page-23-0"></span>[9] M. Nordin, P.-O. Gutman, Controlling mechanical systems with backlash - a survey. Automatica, 38 , pp. 1633–1649 (2002) .
- <span id="page-23-2"></span>[10] M. Schatzman, A Class of Nonlinear Differential Equations of Second Order in Time. Nonlinear Analysis, Theory, Methods & Applications, 2, No 2, pp 355–373 (1978).
- <span id="page-23-9"></span>[11] R. B. Vinter, Optimal Control. Birkhäuser, Systems and Control: Foundations and Applications, Boston MA (2000).
- <span id="page-23-8"></span>[12] V. Zeidan, C. Nour, H. Saoud, A nonsmooth maximum principle for a controlled nonconvex sweeping process. Journal of Differential Equations, vol. 269 (11), pp. 9531– 9582 (2020).