Predicting Loss-of-Function Impact of Genetic Mutations: A Machine Learning Approach

Arshmeet Kaur, Morteza Sarmadi ∗†‡

February 2, 2024

Abstract

The innovation of next-generation sequencing (NGS) techniques has significantly reduced the price of genome sequencing, lowering barriers to future medical research; it is now feasible to apply genome sequencing to studies where it would have previously been cost-inefficient. Identifying damaging or pathogenic mutations in vast amounts of complex, high-dimensional genome sequencing data may be of particular interest for researchers. Thus, this paper's aims were to train machine learning models on the attributes of a genetic mutation to predict LoFtool scores (which measure a gene's intolerance to loss-of-function mutations). These attributes included, but were not limited to, the position of a mutation on a chromosome, changes in amino acids, and changes in codons caused by the mutation. Models were built using the univariate feature selection technique f-regression combined with K-nearest neighbors (KNN), Support Vector Machine (SVM), Random Sample Consensus (RANSAC), Decision Trees, Random Forest, and Extreme Gradient Boosting (XGBoost). These models were evaluated using five-fold cross-validated averages of r-squared, mean squared error, root mean squared error, mean absolute error, and explained variance. The findings of this study include the training of multiple models with testing set r-squared values of 0.97.

1 Introduction

Last year, Ultima Genomics announced that it could sequence a human genome for just one hundred dollars per person [\[1\]](#page-11-0). The reduced cost of genome sequencing means it may now be possible for research in the medical field to collect "omics" data (i.e., genomics, epigenomics, transcriptomics, epitranscriptomics, proteomics, and metabolomics) where it otherwise would have been too expensive to do so. With the generation of potentially vast amounts of data comes the need to develop informatics tools capable of handling and analyzing it. Machine learning and deep learning pose a solution [\[2\]](#page-11-1). Training machine-learning tools that can identify pathogenic variants in a genome sequence is potentially useful to researchers; previous research in the field of prediction of genetic pathogenicity has been focused on developing deep/machine learning models to predict mutations'

[∗]Date of submission: Jan 26, 2024

[†]Arshmeet Kaur is with Evergreen Valley College, 3095 Yerba Buena Rd, San Jose, CA 95135 (e-mail: Arka7783@stu.evc.edu).

[‡]Dr. Morteza Sarmadi, PhD and PostDoc at Massachusetts Institute of Technology 77 Massachusetts Ave, Cambridge, MA 02139 (Major: Bioengineering, Minor: Data Science), is an Research and Development scientist at Gilead Sciences: 333 Lakeside Dr, Foster City, CA 94404 (e-mail: mortezanear@yahoo.com).

functional effects. For example, methods like FATHMM-MKL and CADD are designed to predict functional consequences of coding and non-coding variants [\[3\]](#page-11-2). MetaRNN (developed in [\[4\]](#page-11-3)) is a deep learning method that distinguishes between benign and pathogenic rare mutations. Other research has focused on datasets of a specific disease, such as PathoPredictor, an ensemble method made for cardiomyopathy, epilepsy, or RASopathies [\[5\]](#page-11-4). Some studies test the generalizability of models by using existing methods on clinical data [\[6\]](#page-11-5).

The aim of this paper was to train machine learning models to predict LoFtool scores. To create the LoFtool gene score, researchers retrieved all high-confident loss-of-function mutations (defined as those that disrupt protein structure [\[7\]](#page-11-6)) from Fadista et al.'s 60,706 record Exome Aggregation Consortium dataset [\[8\]](#page-11-7). LoFtool provides a score that quantifies how intolerant a certain gene is to loss-of-function variants– in other words, how susceptible a gene is to disease if mutated. It ranks the percentile of intolerance. LoFtool differs from pathogenicity scores such as PolyPhen, SIFT, ENDEAVOR, or Prioritizer because it can extrapolate its measurements to the gene level instead of focusing on a single variant's pathogenicity. It is also possible to calculate the score without prior knowledge of the disease with which a gene is associated. The LoFtool score has been used in research for in silico experiments. For example, it was used to analyze the pathogenicity of the human SOD1 gene, specifically to get a score for an important noncoding Indel [\[9\]](#page-11-8). Or, as shown in [\[10\]](#page-11-9), LoFtool can be used to identify the most variant-intolerant genes or novel genes in a polygenic disease such as Type 2 diabetes. The contribution of our trained machine learning models to get LoFtool scores in a few seconds with high accuracy based on genetic attributes such as chromosome, strand type, gene, feature, exon number, and codon change could be useful to researchers.

2 Methods

2.1 Original Dataset

In this study, an open-source, public-domain dataset published in 2020 was used [\[11\]](#page-11-10). The original dataset, created from ClinVar data, contained genetic mutations from 23 chromosomes (X but not Y chromosome included) and 46 variables quantifying various attributes of the mutation, such as chromosome location or allelic frequency in the general population. To understand the original data in more detail, please consult the data card in [\[11\]](#page-11-10). To determine whether a variant is classified as pathogenic or benign, geneticists performed manual classification at labs, sorting variants into one of three categories: 1) benign or likely benign, 2) VUS (uncertain or conflicting pathogenicity [\[12\]](#page-11-11)) or 3) likely pathogenic or pathogenic. If different geneticists at different laboratories assigned different classifications, then $CLASS = 1$, and otherwise $CLASS = 0$. The original dataset was created so users could create classification models to predict the CLASS variable. However, to use the dataset to train models and predict pathogenicity scores, all rows where CLASS = 1 were deleted and the CLASS variable was dropped, eliminating all conflicting information on pathogenicity.

2.2 Data Preprocessing

High-dimensional data poses challenges to statistical methods. Oftentimes, high-dimensional data contains redundant information [\[13\]](#page-12-0). Thus, the first step of data cleaning was to drop all irrelevant and/or redundant variables, those with very sparse data, and those with very low variance (Table I). These were the final predictor variables: CHROM, POS, REF, ALT, AF ESP, AF EXAC, AF TGP, MC, IMPACT, SYMBOL, Feature, EXON, cDNA position, CDS position, Protein position, Amino acids, Codons, and STRAND. Several columns (cDNA position, CDS position, and Protein position) contained asterisks, question marks, and dashes in several entries, so these entries were all dropped.

2.3 Addressing Missing Values and Encoding Categorical Variables

All missing values for the target variable, LoFtool, were dropped (6.23 percent of the data). This incidentally also dropped all null values from other variables. To identify whether the dropping of null values caused low variance in any variables, distributions of all continuous and categorical variables were compared before and after data preprocessing and dropping missing values (see Supplementary Figures 1 and 2). Fortunately, no variables developed low variance and the distributions remained nearly identical. The final dataset contained 37220 entries with 19 variables.

Most of the categorical variables in the dataset were nominal, high-cardinality variables (variables with many possible categorical values). For example, SYMBOL and EXON had over twothousand unique categories. Due to this, regularized target encoding, which has been shown to outperform other methods of encoding, such as leaf, integer, and hot or dummy encoding for highcardinality features [\[14\]](#page-12-1), was used.

2.4 Visualizing Relationships Within in the Final Dataset

At this point, relationships between variables were explored, specifically the correlation between different predictors (Fig. 1). Studies focusing on machine learning algorithms in genomics have shown that correlations between predictor variables in feature sets should be considered [\[15\]](#page-12-2). A Pearson's correlation coefficient above 0.20 is typically considered a weak correlation, above 0.40 is a moderate correlation, and anything over 0.60 is considered a strong correlation [\[16\]](#page-12-3).

2.5 Visualizing Skew and Transforming Data

All continuous variables except for LoFtool (AF ESP, AF EXAC, AG TGP, cDNA position, CDS position, Protein position) were heavily right-skewed, which was considered when developing machine learning models [\[17\]](#page-12-4). These variables had to be transformed in further data preprocessing. The final, encoded dataset still contained heavily right-skewed variables with dramatic outliers (see Fig. 2): AF EXAC, AF ESP, AF TGP, cDNA position, CDS position, and Protein position variables. The presence of specialized outlier-robust machine learning models such as RANSAC [\[18\]](#page-12-5), [\[19\]](#page-12-6) suggests that traditional machine learning models may be thwarted by large proportions of outliers like those present in the cleaned data. RANSAC's key feature is that it is robust to a large amount of outliers in input data. Unlike other algorithms built for the same function, it works by using the smallest amount of entries possible from a dataset and slowly grows the number of entries. Additionally, logarithm and Yeo-Johnson transformations were used to create two new datasets. Logarithm transforming works by putting heavily skewed data on a log scale, which leads to a more normal distribution [\[20\]](#page-12-7); however, its validity in biomedical research and data analysis has been questioned [\[21\]](#page-12-8), [\[22\]](#page-12-9) and it has been pointed out that it is unique and only applicable for certain cases [\[23\]](#page-12-10). Because the validity of the Logarithm transformation has been questioned, I decided to create one dataset that was Yeo-Johnson transformed. The Yeo-Johnson transform is similar to the family of Box-Cox transformations, but it is able to handle negative entries [\[24\]](#page-12-11), [\[25\]](#page-12-12). Even after the transformation, many of the variables still contained significant outliers (Fig. 2).

Variable	α and β is the position of α Description
CLASS	all rows CLASS = 1 for SO ₁
	it doesn't provide the machine
	learning model with any impor-
	tant information
Consequence	Redundant to the MC column
CLNDISDB	Storage in different databases is
	not relevant
CLNDN	$\overline{\text{ClinVar's} \quad \text{name}}$ for informa-
	tion already in CLNDISDB col-
	umn, redundant. Also, stor-
	age in ClinVar is not relevant to
	pathogenicity
CLNVI	Variant's clinical sources are not
	relevant to pathogenicity
CLNDISDBINCL,	Sparse Data, 0.20 percent or less
CLNDNINCL,	of data is non-null
CLNSIGINCL,	
SSR, DISTANCE,	
MOTIF_NAME,	
MOTIF_POS,	
HIGH_INF_POS, MO-	
TIF_SCORE_CHANGE	
INTRON	Sparse Data, only 13 percent of
	data is non-null
CADD_RAW	Redundant, an untransformed
	version of CADD PHRED
BAM_EDIT	Is not relevant whether the file
	was edited or not
Allele	Redundant to ALT
CLNHGVS	Redundant to ALT and REF
	columns as well as CHROM and
	POS
BIOTYPE	Very low amount of variance,
	48738 protein_coding and only
	11 of any other type
ORIGIN	Contains values not described
	in the data documentation, also
	low variance with 47923 in one
	category
CLNVC	Very few values in categories
	other nucleotide than single
	variant
Feature_type	All values are uniform
CADD_PHRED,	Other gene scores, not relevant
BLOSUM62, SIFT,	to this study (deleted in a later
PolyPhen	supplementary coding file than
	others in this table but far before
	dropping nulls or encoding)

Table 1: Variables Dropped and Why

Variables removed due to (i) irrelevance, (ii) redundancy, (iii) low variance, and (iv) sparse data

$POS -$			0.011 0.014 0.013		0.33	0.33	0.33	-0.15	0.27	0.31		0.029 0.0015 0.09		0.011	0.3	0.3	0.25	0.028 0.067	
AF ESP - 0.011		$\overline{1}$	0.87	0.83						-0.025 -0.025 -0.025 -0.024 0.039 -0.0042 0.04 0.032 -0.068 -0.12 0.026 0.026 0.013 -0.036 -0.013									
AF EXAC - 0.014		0.87	$\overline{1}$	0.83						-0.02 -0.02 -0.02 -0.026 0.038 0.0042 0.034 0.025 -0.063 -0.11 0.026 0.025 0.014 -0.035 -0.018									
AF TGP - 0.013		0.83	0.83	$\mathbf{1}$						-0.025 -0.025 -0.025 -0.026 0.04 -0.0053 0.036 0.028 -0.069 -0.12 0.027 0.027 0.012 -0.034 -0.016									
cDNA position - 0.33		$-0.025 -0.02 -0.025$			$\overline{1}$	$\mathbf{1}$	$\mathbf{1}$	-0.17	0.32	0.23		0.014 -0.0012 0.061 0.06			0.36	0.36	0.37		0.06 0.091
CDS position - 0.33		$-0.025 -0.02 -0.025$			$\mathbf{1}$	$\mathbf{1}$	$\mathbf{1}$	-0.17	0.32	0.23		0.014 -0.0014 0.061 0.06			0.37	0.37	0.37	0.06	0.091
Protein position - 0.33		$-0.025 -0.02 -0.025$			$\mathbf{1}$	$\mathbf{1}$	$\overline{1}$	-0.17	0.32	0.23		0.014 -0.0014 0.061 0.06			0.37	0.37	0.37	0.06	0.091
STRAND -		-0.15 -0.024 -0.026 -0.026 -0.17 -0.17 -0.17						$\overline{1}$		-0.16 -0.064 -0.025 -0.0014 -0.044 -0.009 -0.19						-0.19		-0.16 0.0001 0.0015	
LoFtool-	0.27	0.039 0.038 0.04			0.32	0.32	0.32	-0.16	$\overline{1}$	0.31		0.077 0.057	0.09	0.044	0.95	0.95	0.61	0.12	0.18
CHROM - 0.31 -0.0042 0.0042 -0.0053 0.23						0.23	0.23	-0.064	0.31	1	0.026	0.02		0.037 0.012	0.34	0.34	0.3	0.043 0.075	
REF	0.029					0.04 0.034 0.036 0.014 0.014 0.014 -0.025 0.077 0.026					$\mathbf{1}$	0.64		0.054 0.059 0.077 0.076 0.033				0.25	0.35
		ALT - 0.0015 0.032 0.025 0.028 -0.0012 -0.0014 -0.0014 -0.0014 0.057 0.02									0.64	$\mathbf{1}$	0.062	0.087		0.055 0.055 0.015		0.25	0.32
	$MC - 0.09$	-0.068 -0.063 -0.069 0.061 0.061 0.061 -0.044 0.09								0.037 0.054 0.062			$\overline{1}$	0.49		0.092 0.092 0.019		0.2	0.15
IMPACT - 0.011		$-0.12 -0.11 -0.12$			0.06	0.06	0.06	-0.009 0.044				0.012 0.059 0.087	0.49	$\overline{1}$	0.037		$0.037 - 0.0022$	0.38	0.26
SYMBOL-	0.3		0.026 0.026 0.027		0.36	0.37	0.37	-0.19	0.95	0.34		0.077 0.055 0.092		0.037	$\overline{1}$	$\mathbf{1}$	0.66	0.11	0.17
Feature -	0.3		0.026 0.025 0.027		0.36	0.37	0.37	-0.19	0.95	0.34		0.076 0.055 0.092 0.037			$\mathbf{1}$	$\mathbf{1}$	0.66	0.11	0.17
EXON - 0.25				0.013 0.014 0.012	0.37	0.37	0.37	-0.16	0.61	0.3		0.033 0.015 0.019 -0.0022			0.66	0.66	$\overline{1}$	0.056 0.095	
Amino acids - 0.028 -0.036 -0.035 -0.034					0.06	0.06		0.06 0.0001	0.12	0.043	0.25	0.25	0.2	0.38	0.11	0.11	0.056	$\mathbf{1}$	0.64
Codons 0.067 -0.013 -0.018 -0.016 0.091 0.091 0.091 0.0015 0.18										0.075	0.35	0.32	0.15	0.26	0.17	0.17	0.095	0.64	$\mathbf{1}$
	SOd	ESP $\frac{1}{2}$	EXAC Æ,	AF_TGP	DNA_position	CDS_position	Protein_position	STRAND	LoFtool	CHROM	REF	ΗĪ	δ,	IMPACT	SYMBOL	Feature	EXON	Amino_acids	Codons

Figure 1: Correlation Matrix: POS, cDNA position, CDS position, Protein position, CHROM, SYMBOL, Feature, and EXON are correlated with LoFtool. As can be seen above, several of these variables were highly correlated with each other (e.g. cDNA position, CDS position, and Protein position). These variables were kept in mind to drop or add when testing machine learning models. More details are given in Tables II, III, and IV.

2.6 Feature Selection

With the finalized datasets, the next step was feature selection; redundant and low-variance features had already been manually filtered out in data cleaning, but selecting sets of relevant features trains the simplest possible model and helps avoid overfitting. Univariate feature selection techniques are quick, efficient, and good for high-dimensional datasets. In bioinformatics research, one would expect that univariate feature selection would be inferior to other types; however, in practice, univariate methods can yield better results (though it is important to note that researchers have explained this as being a result of limited sample size) [\[26\]](#page-12-13). To carry out univariate feature selection, scikit-learn's feature selection module's SelectKBest function was used, which chooses the top k features ($k = 10$ in this case) in each dataset [\[27\]](#page-12-14). Since LoFtool was a continuous target variable, and the problem was a regression problem, f-regression was used to select ten out of eighteen variables for use. For all data (df. loftool.csv, df. loftool.log.csv, df. loftool yj.csv), these features were selected: ['POS', 'cDNA position', 'CDS position', 'Protein position', 'STRAND', 'CHROM', 'SYMBOL', 'Feature', 'EXON', 'Codons']. Seeing the strong correlations between some of these features, some were taken out manually and important findings were added to Tables II, III, and IV.

2.7 Model Selection

To predict LoFtool, K Nearest Neighbors (KNN) Regressor, Support Vector Regressor (a type of SVM abbreviated SVR), Decision Trees, Random Forest Regressor, Extreme Gradient Boost (XGB), and RANSAC were used. To evaluate the performance of the models used, k-fold crossvalidation was used, as this method can test generalization and control overfitting of machine learning models [\[28\]](#page-12-15). Performance metrics that were calculated included averaged r-squared, mean squared error, root mean squared error, mean absolute error, and explained variance.

3 Results and Discussion

All models performed well (with an r-squared values ranging from 0.90-0.97) except of KNN Regressor (r-squared 0.44) and SVR (r-squared -0.32). XGBoost and Random Forest performed best with r-squared values of 0.97, and had identical metrics for MSE, RMSE, MAE, and EV as well. Decision tree (r-squared $= 0.96$) could be a more interpretable, quicker, and less computationally expensive than Random Forest or XGBoost, given the high accuracy. When highly correlated variables (POS, cDNA position, CDS position, Protein position) are dropped, the R-squared value more than doubled for KNN Regressor (r-squared 0.95) and SVR (r-squared0.92). This indicates that those features added noise rather than improving learning. This same effect was not observed in RANSAC, which indicates that the feature selection is dependent on the model used. RANSAC is robust to outliers [\[18\]](#page-12-5), [\[19\]](#page-12-6) and those columns that were dropped from the feature set contained significant outliers (see Fig. 2). This may explain the consistent accuracy with and without those columns included in training the RANSAC model. This suggests that KNN and SVR are less robust to outliers, supporting findings from [insert paper if I can find one that says that].

To gather more information on how skew of these input variables was affecting model performance, we applied the log and yeo-johnson transformations. As we can see in Table III, KNN performed well (r-squared = 0.90) when log transformation was applied to the input variables. The performance did not change when POS, cDNA position, CDS position, Protein position were dropped. This indicates that that the improved performance seen in KNN and SVR in Table 1 when these variables were dropped is more likely attributable to the features being heavily right skewed and the models KNN and SVR rather than being strongly correlated with each other. However, the performance of the model combined with transformation and feature selection is likely heavily impacted by the model chosen: RANSAC deteriorated after log transformation (r-squared $=$ -0.28) and performed well (r-squared = 0.90) when POS, cDNA position, CDS position, Protein position were dropped. Additionally, the ranking of models did not change between the non-transformed and log-transformed datasets, indicating that Decision Tree, Random Forest and XGB are all already relatively robust to outliers.

Summary:

All of the models were trained and tested on the datasets created. Tables II, III, and IV contain the averaged Cross-Validation scores for k-fold $(k=5)$ cross-validation. Random Forest and XGBoost Regressors performed the best in all three LoFtool datasets, with KNN and Decision Tree Regressor in close second. It did not seem to make a difference if the dataset was transformed or not, as several models achieved an r-squared value of 0.97 regardless of transformation. However,

notably, when cDNA position, CDS position, and Protein position, which had significant outliers, and were also very highly correlated with each other, (Figs. 1 and 2) were removed along with POS, models tended to perform much better. For example, as seen in Table II, KNN had an r-squared value of 0.44 and 0.95 before and after removal of cDNA position, CDS position, Protein position, and POS and SVR went from an r-squared of -0.32 to 0.92. RANSAC, which is robust to outliers, did not perform the best in any of the datasets. This study shows the potential use of machine learning in analysis of genetic mutations and trains a tool potentially useful to researchers in the fields of sequence analysis and pathogenicity prediction. Future research could further explore how varying data distributions and feature selection techniques affect the performance of models, or test generalizability of the model with larger datasets.

Exome Aggregration Consortium (ExAC) and Thousand Genome Project (TGP). Relative Position of Base in cDNA, Coding or Protein Sequence

Figure 2: Distribution of continuous variables before and after applying transformations. As can be seen in the plots, there were still many outliers left after both transformations. The log transformation normalized allele frequency columns more than the Yeo-Johnson transformation.

Dataset Used	Model Used	MSE RMSE MAE EV R2 Feature Selection
df_loftool	KNN Regressor	Univariate Feature Selection (f-0.44) -0.07 -0.26 -0.16 0.45
		regression)
	KNN Regressor	Univariate Feature Selection (f-0.95) -0.01 -0.08 -0.04 0.95
		regression) (POS, cDNA_position,
		CDS_positon, Protein_positon re-
		moved)
	Decision	Tree Univariate Feature Selection $(f-0.96)$ -0.07 -0.00 -0.03 0.96
	Regressor	regression)
	Random	Forest Univariate Feature Selection (f-0.97) -0.06 -0.00 -0.03 0.97
	Regressor	regression)
	XGB	Univariate Feature Selection $(f-0.97)$ -0.06 -0.03 0.97 -0.00
		regression)
	SVR	Univariate Feature Selection $(f-1)$ -0.32 -0.17 -0.41 -0.32 -0.10
		regression)
	SVR	Univariate Feature Selection $(f-0.92)$ -0.01 -0.10 -0.08 0.92
		regression) (POS, cDNA_position,
		CDS_positon, Protein_positon re-
		moved)
	RANSAC	$(f-0.90)$ -0.11 -0.01 -0.06 0.90 Univariate Feature Selection
		regression)
	RANSAC	Univariate Feature Selection $(f-0.90)$ -0.01 -0.11 -0.06 0.90
		regression) (POS, cDNA _{-position,}
		CDS _{-positon} , Protein _{-positon} re-
		moved)

Table 2: Non-transformed Dataset

Five-fold cross-validated averages of r-squared, mean squared error, root mean squared error, mean absolute error and explained variance for the dataset that had no transformations applied to it. Univariate Feature Selection (Using F-regression) Feature Set: ['POS', 'cDNA position', 'CDS position', 'Protein position', 'STRAND', 'CHROM', 'SYMBOL', 'Feature', 'EXON', 'Codons']

Dataset Used	Model Used	$\overline{R2}$ Feature Selection	MSE	RMSE MAE EV		
df_loftool_log	KNN Regressor	Univariate Feature Selection (f-0.90)	-0.01	-0.11	-0.07 $ 0.90$	
		regression)				
	KNN Regressor	Univariate Feature Selection (f-0.95)	-0.01	-0.08	-0.05 0.95	
		regression) (POS, cDNA_position,				
		CDS _{-positon} , Protein _{-positon} re-				
		moved)				
	Decision	Tree Univariate Feature Selection $(f-0.96)$	-0.00	-0.07	-0.03 0.96	
	Regressor	regression)				
	Random	Forest Univariate Feature Selection $(f-0.97)$	-0.00	-0.06	-0.03 0.97	
	Regressor	regression)				
	XGB	Univariate Feature Selection $(f-0.97)$	-0.00	-0.06	-0.03 0.97	
		regression)				
	SVR	Univariate Feature Selection (f-0.89)	-0.01	-0.12	-0.09 $ 0.89$	
		regression)				
	SVR	Univariate Feature Selection $(F 0.92)$	-0.01	-0.10	-0.08 0.92	
		regression) (POS, cDNA_position,				
		CDS _{-positon} , Protein _{-positon} re-				
		moved)				
	RANSAC	Univariate Feature Selection $(f- -0.28 -7.40)$		-0.39	-0.08	
		regression)				71.47
	RANSAC	Univariate Feature Selection (f-0.90)	-0.01	-0.11	-0.06	$ 0.90\rangle$
		regression) (POS, cDNA_position,				
		CDS _{-positon} , Protein _{-positon} re-				
		moved)				

Table 3: Log-transformed Dataset

Five-fold cross-validated averages of r-squared, mean squared error, root mean squared error, mean absolute error and explained variance for the dataset that was logarithm transformed. Univariate Feature Selection (Using F-regression) Feature Set: ['POS', 'cDNA position', 'CDS position', 'Protein position', 'STRAND', 'CHROM', 'SYMBOL', 'Feature', 'EXON', 'Codons']

	TQNIC I.	100 JOHNSON LIGHBIOLIKE DATASU		RMSE MAE EV				
Dataset Used	Model Used	Feature Selection		R2	MSE			
df_loftool_yj	KNN Regressor	Univariate Feature Selection (f-0.42)			-0.07	-0.27	-0.16 0.44	
		regression)						
	KNN Regressor	Univariate Feature Selection (f-0.95)			-0.01	-0.08	-0.04 0.95	
		regression) (POS, cDNA _{-position,}						
		CDS_positon, Protein_positon re-						
		moved)						
	Decision	Tree Univariate Feature Selection $(f-0.96)$			-0.01	-0.07	-0.03 0.96	
	Regressor	regression)						
	Random	Forest Univariate Feature Selection (f- $ 0.97 $			-0.00	-0.06	-0.03 0.98	
	Regressor	regression)						
	$\overline{\text{XGB}}$	Univariate Feature Selection (f-0.97)			-0.00	-0.06	-0.03 0.97	
		regression)						
	SVR	Univariate Feature Selection $(f-0.32 \mid 0.17 \mid 0.41)$					$-0.32 - 0.10$	
		regression)						
	$\overline{\text{SVR}}$	Univariate Feature Selection $(f-0.92)$			-0.01	-0.10	-0.08 0.92	
		regression) (POS, cDNA_position,						
		CDS_positon, Protein_positon re-						
		moved)						
	RANSAC	Univariate Feature Selection $(f-0.90)$				-0.14 -0.11	-0.07 $ 0.90$	
		regression)						
	RANSAC	Univariate Feature Selection $(f- 0.90)$			-0.01	-0.11	-0.06 0.90	
		regression) (POS, cDNA_position,						
		CDS_positon, Protein_positon re-						
		moved)						

Table 4: Yeo-Johnson Transformed Dataset

Five-fold cross-validated averages of r-squared, mean squared error, root mean squared error, mean absolute error and explained variance for the dataset that was Yeo-Johnson transformed. Univariate Feature Selection (Using F-regression) Feature Set: ['POS', 'cDNA position', 'CDS position', 'Protein position', 'STRAND', 'CHROM', 'SYMBOL', 'Feature', 'EXON', 'Codons']

:

References

- [1] Science.org. (2022, Jun. 15). A $$100$ Genome? New DNA Sequencers Could Be a 'Game Changer' for Biology, Medicine. [Online]. Availiable: https://www.science.org/content/article/100-genome-new-dna-sequencers-could-be-gamechanger-biology-medicine.
- [2] C. Caudai, A. Galizia, F. Geraci, L. Le Pera, V. Morea, E. Salerno, A. Via, and T. Colombo, "Ai applications in functional genomics," Computational and Structural Biotechnology Journal, vol. 19, pp. 5762–5790, 2021.
- [3] H. A. Shihab, M. F. Rogers, J. Gough, M. Mort, D. N. Cooper, I. N. Day, T. R. Gaunt, and C. Campbell, "An integrative approach to predicting the functional effects of non-coding and coding sequence variation," Bioinformatics, vol. 31, no. 10, pp. 1536–1543, 2015.
- [4] C. Li, D. Zhi, K. Wang, and X. Liu, "Metarnn: differentiating rare pathogenic and rare benign missense snvs and indels using deep learning," Genome Medicine, vol. 14, no. 1, p. 115, 2022.
- [5] P. Evans, C. Wu, A. Lindy, D. A. McKnight, M. Lebo, M. Sarmady, and A. N. Abou Tayoun, "Genetic variant pathogenicity prediction trained using disease-specific clinical sequencing data sets," Genome Research, vol. 29, no. 7, pp. 1144–1151, 2019.
- [6] A. C. Gunning, V. Fryer, J. Fasham, A. H. Crosby, S. Ellard, E. L. Baple, and C. F. Wright, "Assessing performance of pathogenicity predictors using clinically relevant variant datasets," Journal of medical genetics, 2020.
- [7] L. Gerasimavicius, B. J. Livesey, and J. A. Marsh, "Loss-of-function, gain-of-function and dominant-negative mutations have profoundly different effects on protein structure," Nature communications, vol. 13, no. 3895, Jul. 2022.
- [8] J. Fadista, N. Oskolkov, O. Hansson, and L. Groop, "Loftool: a gene intolerance score based on loss-of-function variants in 60 706 individuals," Bioinformatics, vol. 33, no. 4, pp. 471–474, Aug. 2016.
- [9] P. Tripathi, S. Agarwal, A. N. Sarangi, S. Tewari, and K. Mandal, "Genetic variation in sod1 gene promoter ins/del and its influence on oxidative stress in beta thalassemia major patients," International Journal of Hematology-Oncology and Stem Cell Research, vol. 14, no. 2, pp. 110– 117, Apr. 2020.
- [10] J. Taneera, S. Dhaiban, A. K. Mohammed, D. Mukhopadhyay, H. Aljaibeji, N. Sulaiman, J. Fadista, and A. Salehi, "Gnas gene is an important regulator of insulin secretory capacity in pancreatic β -cells," Gene, vol. 715, p. 144028, Jul. 2019.
- [11] K. Arvai, 2020. Genetic variant classifications, distributed by Kaggle, doi: 10.34740/KAG-GLE/DSV/1030915.
- [12] National Cancer Institute. NCI Dictionary of Genetics Terms. [Online]. Availiable: https://www.cancer.gov/publications/dictionaries/genetics-dictionary/def/vus. Accessed: Oct. 2023.
- [13] C. O. S. Sorzano and J. Vargas and A. Pascual Montano, "A survey of dimensionality reduction techniques," Mar. 2014, arXiv:1403.2877.
- [14] F. Pargent, F. Pfisterer, J. Thomas, and B. Bischl, "Regularized target encoding outperforms traditional methods in supervised machine learning with high cardinality features," Computational Statistics, vol. 37, no. 5, pp. 2671–2692, Mar. 2022.
- [15] K. K. Nicodemus and J. D. Malley, "Predictor correlation impacts machine learning algorithms: implications for genomic studies," Bioinformatics, vol. 25, no. 15, pp. 1884–1890, 2009.
- [16] The BMJ, "11. correlation and regression," [https://www.bmj.com/about-bmj/](https://www.bmj.com/about-bmj/resources-readers/publications/statistics-square-one/11-correlation-and-regression) [resources-readers/publications/statistics-square-one/11-correlation-and-regression,](https://www.bmj.com/about-bmj/resources-readers/publications/statistics-square-one/11-correlation-and-regression) Oct 2020.
- [17] J. Raymaekers and P. J. Rousseeuw, "Transforming variables to central normality," Machine Learning, pp. 1–23, 2021.
- [18] M. Zuliani, "Ransac for dummies," Vision Research Lab, University of California, Santa Barbara, Oct. 2009.
- [19] K. G. Derpanis, "Overview of the ransac algorithm," Image Rochester NY, vol. 4, no. 1, pp. 2–3, May. 2010.
- [20] D. Curran-Everett, "Explorations in statistics: the log transformation," Advances in physiology education, vol. 42, no. 2, pp. 343–347, Jun. 2018.
- [21] F. Changyong, W. Hongyue, L. Naiji, C. Tian, H. Hua, L. Ying et al., "Log-transformation and its implications for data analysis," Shanghai archives of psychiatry, vol. 26, no. 2, p. 105, Apr. 2014.
- [22] C. Feng, H. Wang, N. Lu, and X. M. Tu, "Log transformation: application and interpretation in biomedical research," Statistics in medicine, vol. 32, no. 2, pp. 230–239, Jul. 2012.
- [23] O. N. Keene, "The log transformation is special," Statistics in medicine, vol. 14, no. 8, pp. 811–819, Apr. 1995.
- [24] S. Weisberg, "Yeo-johnson power transformations," Department of Applied Statistics, University of Minnesota. Retrieved June, vol. 1, p. 2003, Oct. 2001.
- [25] I.-K. Yeo and R. A. Johnson, "A new family of power transformations to improve normality or symmetry," Biometrika, vol. 87, no. 4, pp. 954–959, Dec. 2000.
- [26] N. Weizing, "A review and comparative study on univariate feature selection techniques," M.S. thesis, Department of Mechanical Engineering, University of Cincinnati, Cincinnati, Ohio, 2012.
- [27] Scikit-Learn. 1.13. Feature Selection. [Online]. Availiable: https://www.cancer.gov/publications/dictionaries/genetics-dictionary/def/vus. Accessed: Oct. 2023.
- [28] D. Berrar, "Cross-validation." 2019.