Learning Families of Algebraic Structures from Text

Nikolay Bazhenov¹, Ekaterina Fokina², Dino Rossegger², Alexandra Soskova³, and Stefan Vatev³

¹Sobolev Institute of Mathematics, Novosibirsk bazhenov@math.nsc.ru ²Institute of Discrete Mathematics and Geometry, Technische Universität Wien {dino.rossegger,ekaterina.fokina}@tuwien.ac.at ³Faculty of Mathematics and Informatics, Sofia University {asoskova,stefanv}@fmi.uni-sofia.bg

Abstract

We adapt the classical notion of learning from text to computable structure theory. Our main result is a model-theoretic characterization of the learnability from text for classes of structures. We show that a family of structures is learnable from text if and only if the structures can be distinguished in terms of their theories restricted to positive infinitary Σ_2 sentences.

1 Introduction

The classical algorithmic learning theory goes back to the works of Putnam [16] and Gold [12]. A learner M receives step by step more and more data (finite amount at each step) on an object X to be learned, and M outputs a sequence of hypotheses that converges to a finitary description of X. The classical studies (up to the beginning of 2000s) mainly focused on learning for formal languages and for recursive functions, see the monograph [14].

Within the framework of computable structure theory, the work of Stephan and Ventsov [18] initiated investigations of learnability for classes of substructures of a given computable structure S. This approach was further developed, e.g., in the papers [13, 11].

Fokina, Kötzing, and San Mauro [10] considered various classes \mathfrak{K} of computable equivalence relations. For these \mathfrak{K} , they introduced the notions of *learnability from informant* (or **InfEx**-learnability) and *learnability from text* (**TxtEx**-learnability). The work [5] extended the notion of **InfEx**-learnability to arbitrary countable families of computable structures and obtained the following general model-theoretic characterization of **InfEx**-learnability. Let $\mathfrak{K} =$ { $\mathcal{A}_i : i \in \omega$ } be a family of computable structures such that $\mathcal{A}_i \ncong \mathcal{A}_j$ for $i \neq j$. Then \mathfrak{K} is learnable from informant if and only if there exists a family of infinitary Σ_2 sentences $\{\psi_i : i \in \omega\}$ such that

(†) for each i, A_i is the only member of \mathfrak{K} satisfying ψ_i .

In turn, the results of [5] led to discovering some unexpected connections between **InfEx**-learnability and results from descriptive set theory, see [3].

Until now, to our best knowledge, there was no notion of \mathbf{TxtEx} -learnability applicable for general classes of countable structures. This paper aims to close this gap. In Section 2, we introduce our new formal framework for classes of structures \mathfrak{K} : this approach allows us to simultaneously give both the known definition of **InfEx**-learnability and the new definition of **TxtEx**-learnability.

The main result of the paper (Theorem 3) shows that \mathbf{TxtEx} -learnability admits a model-theoretic characterization similar to the characterization of **InfEx**learnability discussed above: a family $\{\mathcal{A}_i : i \in \omega\}$ is \mathbf{TxtEx} -learnable if and only if there exists a family of Σ_2^p sentences $\{\psi_i : i \in \omega\}$ satisfying (†). Here Σ_n^p formulas are *positive infinitary* Σ_n formulas introduced in our previous work [4], see the formal details in Section 4.

2 The Formal Framework

Let us consider structures \mathcal{A} with domains a subset of ω . We consider computable signatures with = and \neq . We shall denote by $\mathcal{D}(\mathcal{A})$ the basic diagram of \mathcal{A} , i.e., $\mathcal{D}(\mathcal{A})$ contains exactly the positive and negative atomic sentences true in \mathcal{A} , and by $\mathcal{D}_{+}(\mathcal{A})$ the positive atomic diagram of \mathcal{A} , i.e., $\mathcal{D}_{+}(\mathcal{A})$ contains only the positive atomic sentences true in \mathcal{A} .

For a signature L, by Mod(L) we denote the set of all L-structures \mathcal{A} with $dom(\mathcal{A}) \subseteq \omega$. If not specified otherwise, we assume that every considered class $\mathfrak{K} \subseteq Mod(L)$ is closed under isomorphisms.

First we need to introduce the components of our learning framework. Let $\mathfrak{K} \subseteq Mod(L)$ be a family which contains precisely κ isomorphism types, where $\kappa \leq \omega$, those are the types of L-structures $\mathcal{A}_i, i \in \kappa$.

• The *learning domain* (LD) is the collection of all copies S of the structures from \mathfrak{K} such that dom $(S) \subseteq \omega$, i.e.,

$$\mathrm{LD}(\mathfrak{K}) = \bigcup_{i \in \kappa} \{ \mathcal{S} \in Mod(L) : \mathcal{S} \cong \mathcal{A}_i \}.$$

• The hypothesis space (HS) contains the indices i for $\mathcal{A}_i \in \mathfrak{K}$ (an index is viewed as a conjecture about the isomorphism type of an input structure \mathcal{S}) and a question mark symbol:

$$\operatorname{HS}(\mathfrak{K}) = \kappa \cup \{?\}.$$

• A learner M sees, stage by stage, some atomic facts about a given structure from $LD(\mathfrak{K})$. The learner M is required to output conjectures from $HS(\mathfrak{K})$. This is formalized as follows.

Let Atm denote the set of (the Gödel numbers) of all positive and negative atomic sentences in the signature $L \cup \omega$ (in other words, positive and negative atomic facts about possible *L*-structures on the domain ω). The restriction of *Atm* to only positive atomic sentences is denoted by Atm_+ . A *learner* M is a function from the set $(Atm)^{<\omega}$ (i.e., the set of all finite tuples of atomic facts) into $HS(\mathfrak{K})$.

• For an L-structure S, an *informant* \mathbb{I} for S is an arbitrary sequence $(\psi_0, \psi_1, \psi_2, ...)$ containing elements from Atm and satisfying

$$\mathcal{D}(\mathcal{S}) = \{\psi_i : i \in \omega\}.$$

• For an *L*-structure S, a *text* \mathbb{T} for S is an arbitrary sequence $(\psi_0, \psi_1, \psi_2, ...)$ containing elements from Atm_+ and satisfying

$$\mathcal{D}_+(\mathcal{S}) = \{\psi_i : i \in \omega\}$$

• For $k \in \omega$, by $\mathbb{I} \upharpoonright k$ (respectively, $\mathbb{T} \upharpoonright k$) we denote the corresponding sequence $(\psi_i)_{i < k}$.

Definition 1 ([6]). We say that the family \mathfrak{K} is **InfEx**-learnable if there exists a learner M such that for any structure $\mathcal{S} \in LD(\mathfrak{K})$ and any informant $\mathbb{I}_{\mathcal{S}}$ for \mathcal{S} , the learner eventually stabilizes to a correct conjecture about the isomorphism type of \mathcal{S} . More formally, there exists a limit

$$\lim M(\mathbb{I}_{\mathcal{S}} \upharpoonright n) = i$$

belonging to ω , and \mathcal{A}_i is isomorphic to \mathcal{S} .

Recall that a structure $\mathcal{A} = (A; \sim)$ is an *equivalence structure* if \sim is an equivalence relation on A. The paper [10] introduced the definition of **TxtEx**-learnability for equivalence structures. Here we generalize this definition to arbitrary structures.

Definition 2. We say that the family \mathfrak{K} is \mathbf{TxtEx} -learnable if there exists a learner M such that for any structure $\mathcal{S} \in \mathrm{LD}(\mathfrak{K})$ and any text $\mathbb{T}_{\mathcal{S}}$ for \mathcal{S} , the learner eventually stabilizes to a correct conjecture about the isomorphism type of \mathcal{S} . More formally, there exists a limit

$$\lim_{n \to \omega} M(\mathbb{T}_{\mathcal{S}} \upharpoonright n) = i$$

belonging to ω , and \mathcal{A}_i is isomorphic to \mathcal{S} .

In this paper, we give many examples of classes of equivalence structures. We use the notation $[\alpha_1 : \beta_1, \ldots, \alpha_n : \beta_n]$, where $\alpha_i, \beta_i \leq \omega$, to denote the equivalence structure with precisely β_i -many equivalence classes of size α_i , for all $i = 1, \ldots, n$ (and with no equivalence classes of other sizes).

Remark 1. The classes of equivalence structures $\mathcal{E} = \{ [\omega : 1, n : 1] \mid n \ge 1 \}$ and $\tilde{\mathcal{E}} = \{ [\omega : \omega, n : \omega] \mid n \ge 1 \}$ play an important role in this paper.

Remark 2. It is easy to observe that every **TxtEx**-learnable class is also **InfEx**-learnable (indeed, notice that an informant I for a structure \mathcal{A} can be effectively transformed into a text \mathbb{T}_I for this \mathcal{A}). Theorem 1.4 in [10] proves that the class $\mathfrak{K} = \{[\omega:1], [\omega:2]\}$ is **InfEx**-learnable, but not **TxtEx**-learnable.

3 Cantor-Continuous Embeddings

The Cantor space, denoted by 2^{ω} , can be represented as the collection of reals, equipped with the product topology of the discrete topology on the set $\{0, 1\}$. A basis for 2^{ω} is formed by the collection of $[\sigma] = \{f \in 2^{\omega} : \sigma \subset f\}$, for all finite binary strings σ . Here we will need the following characterization of the Cantor-continuous functions.

Proposition 1 (Folklore). A function $\Psi : 2^{\omega} \to 2^{\omega}$ is Cantor-continuous if and only if there exists a Turing operator Φ_e and a set $A \in 2^{\omega}$ such that $\Psi(X) = \Phi_e(A \oplus X)$ for all $X \in 2^{\omega}$.

Definition 3. For $i \in \{0, 1\}$, let \mathfrak{K}_i be a class of L_i -structures. A mapping Ψ is a Cantor-continuous embedding of \mathfrak{K}_0 into \mathfrak{K}_1 , denoted by $\Psi \colon \mathfrak{K}_0 \leq_{\text{Cantor}} \mathfrak{K}_1$, if Ψ is Cantor-continuous and satisfies the following:

- 1. For any $\mathcal{A} \in \mathfrak{K}_0$, $\Psi(\mathcal{D}(\mathcal{A}))$ is the characteristic function of the atomic diagram of a structure from \mathfrak{K}_1 . This structure is denoted by $\Psi(\mathcal{A})$.
- 2. For any $\mathcal{A}, \mathcal{B} \in \mathfrak{K}_0$, we have $\mathcal{A} \cong \mathcal{B}$ if and only if $\Psi(\mathcal{A}) \cong \Psi(\mathcal{B})$.

When the embedding $\mathfrak{K}_0 \leq_{\text{Cantor}} \mathfrak{K}_1$ is given by a Turing operator Φ_e , then we say that \mathfrak{K}_0 is *Turing computable embeddable* into \mathfrak{K}_1 , and we denote this by $\Phi_e \colon \mathfrak{K}_0 \leq_{tc} \mathfrak{K}_1$. The study of this notion was initiated in [7, 15]. One of the main tools in proving results about the Turing computable embeddability is the following Pullback Theorem. Here the Σ_{α}^c formulas are the usual computable infinitary Σ_{α} formulas as defined in [1]. A Σ_{α}^{\inf} formula is an infinitary Σ_{α} formula.

Theorem 1 (Pullback Theorem [15]). Let $\Phi_e: \mathfrak{K} \leq_{tc} \mathfrak{K}'$. Then for any computable infinitary sentence φ' in the signature of \mathfrak{K}' , we can effectively find a computable infinitary sentence φ in the signature of \mathfrak{K} such that for all $\mathcal{A} \in \mathfrak{K}$,

$$\mathcal{A} \models \varphi \text{ if and only if } \Phi_e(\mathcal{A}) \models \varphi'.$$

Moreover, for a nonzero $\alpha < \omega_1^{CK}$, if φ' is Σ_{α}^c (or Π_{α}^c), then so is φ .

As noted in [5], Theorem 1, can be relativized to an arbitrary oracle X. By Proposition 1, we directly obtain the following non-effective version of Theorem 1.

Corollary 1 (Non-effective Pullback Theorem). Let $\Psi: \mathfrak{K} \leq_{\text{Cantor}} \mathfrak{K}'$. Then for any infinitary sentence φ' in the signature of \mathfrak{K}' , there exists an infinitary sentence φ in the signature of \mathfrak{K} such that for all $\mathcal{A} \in \mathfrak{K}$,

$$\mathcal{A} \models \varphi \text{ if and only if } \Psi(\mathcal{A}) \models \varphi'.$$

Moreover, for a nonzero $\alpha < \omega_1$, if φ' is Σ_{α}^{\inf} (or Π_{α}^{\inf}), then so is φ .

4 Scott-Continuous Embeddings

The Scott topology, denoted by $\mathcal{P}(\omega)$, can be characterized as the product topology of the Sierpiński space on $\{0, 1\}$. The Sierpiński space on $\{0, 1\}$ is the topological space with open sets $\{\emptyset, \{1\}, \{0, 1\}\}$. A basis for $\mathcal{P}(\omega)$ is formed by the collection $[D] = \{A \subseteq \omega : D \subseteq A\}$, for all finite sets D.

Definition 4 (Case [8]). A set $A \in \mathcal{P}(\omega)$ defines a generalized enumeration operator $\Gamma_A : \mathcal{P}(\omega) \to \mathcal{P}(\omega)$ if and only if for each set $B \in \mathcal{P}(\omega)$,

$$\Gamma_A(B) = \{ x : \exists v (\langle x, v \rangle \in A \& D_v \subseteq B) \}.$$

When $A = W_e$ for some c.e. set W_e , we write Γ_e instead of Γ_{W_e} , which is the usual enumeration operator as defined in [8] and [9], for example.

Proposition 2 (Folklore). A mapping $\Gamma : \mathcal{P}(\omega) \to \mathcal{P}(\omega)$ is Scott-continuous if and only if Γ is a generalized enumeration operator.

As a direct corollary of Proposition 2, the following characterization will be useful.

Corollary 2. A mapping $\Psi : \mathcal{P}(\omega) \to \mathcal{P}(\omega)$ is Scott-continuous if and only if Ψ is

- (a) monotone, i.e., $A \subseteq B$ implies $\Psi(A) \subseteq \Psi(B)$, and
- (b) compact, i.e., $x \in \Psi(A)$ if and only if $x \in \Psi(D)$ for some finite $D \subseteq A$.

We define Scott-continuous embedding for classes of structures as an analogue of the Cantor-continuous embedding from Definition 3. Here we take into consideration only the *positive* atomic diagram $\mathcal{D}_+(\mathcal{A})$ of a structure \mathcal{A} , and not the basic (positive and negative) atomic diagram $\mathcal{D}(\mathcal{A})$ as in [15].

Definition 5. A mapping Γ is a Scott-continuous embedding of \mathfrak{K}_0 into \mathfrak{K}_1 , denoted by $\Gamma: \mathfrak{K}_0 \leq_{\text{Scott}} \mathfrak{K}_1$, if Γ is Scott-continuous and satisfies the following:

- 1. For any $\mathcal{A} \in \mathfrak{K}_0$, $\Gamma(\mathcal{D}_+(\mathcal{A}))$ is the positive atomic diagram of a structure from \mathfrak{K}_1 . This structure is denoted by $\Gamma(\mathcal{A})$.
- 2. For any $\mathcal{A}, \mathcal{B} \in \mathfrak{K}_0$, we have $\mathcal{A} \cong \mathcal{B}$ if and only if $\Gamma(\mathcal{A}) \cong \Gamma(\mathcal{B})$.

If we consider enumeration operators Γ_e , we obtain an effective version of Definition 5. We say that Γ_e is a *positive computable embedding* of \mathfrak{K}_0 into \mathfrak{K}_1 , and we denote it by $\Gamma_e: \mathfrak{K}_0 \leq_{pc} \mathfrak{K}_1$. Positive computable embeddings were first studied in [4]. To obtain an analogue of Theorem 1 for positive computable embeddings, we need to define a hierarchy of *positive* infinitary formulas.

Definition 6 ([4]). Fix a countable signature L. For every $\alpha < \omega_1$ define the sets of Σ^p_{α} and Π^p_{α} L-formulas inductively as follows.

- Let $\alpha = 0$. Then:
 - the Σ_0^p formulas are the finite conjunctions of atomic L-formulas.
 - the Π_0^p formulas are the finite disjunctions of negations of atomic *L*-formulas.
- Let $\alpha = 1$. Then:
 - $-\varphi(\bar{u})$ is a Σ_1^p formula if it has the form

$$\varphi(\bar{u}) = \mathbb{W}_{i \in I} \exists \bar{x}_i \psi_i(\bar{u}, \bar{x}_i)$$

where for each $i \in I$, $\psi_i(\bar{u}, \bar{x}_i)$ is a Σ_0^p formula, I is countable.

 $-\varphi(\bar{u})$ is a Π_1^p formula if it has the form

$$\varphi(\bar{u}) = \mathbb{M}_{i \in I} \forall \overline{x}_i \psi_i(\bar{u}, \bar{x}_i),$$

where for each $i \in I$, $\psi_i(\bar{u}, \bar{x}_i)$ is a Π_0^p formula, I is countable.

• Let $\alpha \geq 2$. Then:

 $- \varphi(\bar{u})$ is Σ^p_{α} formula if it has the form

$$\varphi(\bar{u}) = \mathbb{W}_{i \in I} \exists \bar{x}_i (\xi_i(\bar{u}, \bar{x}_i) \land \psi_i(\bar{u}, \bar{x}_i)),$$

where for each $i \in I$, $\xi_i(\bar{u}, \bar{x}_i)$ is a $\Sigma^p_{\beta_i}$ formula and $\psi_i(\bar{u}, \bar{x}_i)$ is a $\Pi^p_{\beta_i}$ formula, for some $\beta_i < \alpha$ and I countable.

 $- \varphi(\bar{u})$ is Π^p_{α} formula if it has the form

$$\varphi(\bar{u}) = \mathbb{M}_{i \in I} \forall \bar{x}_i (\xi_i(\bar{u}, \bar{x}_i) \lor \psi_i(\bar{u}, \bar{x}_i)),$$

where for each $i \in I$, $\xi_i(\bar{u}, \bar{x}_i)$ is a $\Sigma_{\beta_i}^p$ formula and $\psi_i(\bar{u}, \bar{x}_i)$ is a $\Pi_{\beta_i}^p$ formula, for some $\beta_i < \alpha$ and I countable.

A similar hierarchy of positive infinitary formulas can be also found in [17], where it is used in connection with the α -th enumeration jump. As usual, when we restrict to c.e. index sets I in the above definition, we obtain the hierarchy of *positive computable infinitary formulas*. For this hierarchy, we will use the notations Σ_{α}^{pc} and Π_{α}^{pc} .

Theorem 2 (Pullback Theorem [4]). Let $\Gamma_e : \mathfrak{K} \leq_{pc} \mathfrak{K}'$. Then for any positive computable infinitary sentence φ' in the signature of \mathfrak{K}' , we can effectively find a positive computable infinitary sentence φ in the signature of \mathfrak{K} such that for all $\mathcal{A} \in \mathfrak{K}$,

$$\mathcal{A} \models \varphi \text{ if and only if } \Gamma_e(\mathcal{A}) \models \varphi'.$$

Moreover, for a nonzero $\alpha < \omega_1^{CK}$, if φ' is Σ_{α}^{pc} (or Π_{α}^{pc}), then so is φ .

Since Theorem 2 can be relativized, it is straightforward to obtain a non-effective version.

Corollary 3. Let $\Gamma: \mathfrak{K} \leq_{\text{Scott}} \mathfrak{K}'$. Then for any positive infinitary sentence φ' in the signature of \mathfrak{K}' , there exists a positive infinitary sentence φ in the signature of \mathfrak{K} such that for all $\mathcal{A} \in \mathfrak{K}$,

$$\mathcal{A} \models \varphi \text{ if and only if } \Gamma(\mathcal{A}) \models \varphi'.$$

Moreover, for a nonzero $\alpha < \omega_1$, if φ' is Σ^p_{α} (or Π^p_{α}), then so is φ .

5 Characterization of TxtEx-Learnability

Recall the class $\tilde{\mathcal{E}}$ from Remark 1. In this section, we obtain the following characterization of **TxtEx**-learning:

Theorem 3. For a class $\mathfrak{K} = {\mathcal{B}_i : i \in \omega}$, the following are equivalent:

(1) The class \mathfrak{K} is \mathbf{TxtEx} -learnable.

- (2) $\Re \leq_{\text{Scott}} \tilde{\mathcal{E}}$.
- (3) There is a sequence of Σ_2^p sentences $\{\psi_i : i \in \omega\}$ such that for all i and j, $\mathcal{B}_j \models \psi_i$ if and only if i = j.

The proof of Theorem 3 is given as a sequence of lemmas.

(1) \Rightarrow (2). For a finite sequence σ and an *L*-structure \mathcal{A} , we say that σ is on $\mathcal{D}_+(\mathcal{A})$ if σ is an initial segment of some text for the structure \mathcal{A} .

Proposition 3. Let \mathfrak{K} be a class of structures which is **TxtEx**-learnable by a learner M, and let \mathcal{A} be a structure in \mathfrak{K} . For any finite σ on $\mathcal{D}_+(\mathcal{A})$, there exists an extension σ' of σ on $\mathcal{D}_+(\mathcal{A})$, such that for all τ on $\mathcal{D}_+(\mathcal{A})$, extending σ' , $M(\sigma') = M(\tau)$.

Proof. Assume that there exists σ on $\mathcal{D}_+(\mathcal{A})$ such that for all $\sigma' \succeq \sigma$, we can find $\tau \succ \sigma'$ such that $M(\sigma') \neq M(\tau)$. In this way it is clear that we can build an enumeration \mathbb{T} of $\mathcal{D}_+(\mathcal{A})$ such that $\lim_{n\to\infty} M(\mathbb{T} \upharpoonright n)$ does not exist, and we obtain a contradiction.

Lemma 1. For any **TxtEx**-learnable class $\mathfrak{K}, \mathfrak{K} \leq_{\text{Scott}} \tilde{\mathcal{E}}$.

Proof. For any finite enumeration $\sigma \in \omega^{<\omega}$ and ordinal $\alpha \leq \omega$, we define the auxiliary equivalence structure $\mathcal{A}_{\sigma,\alpha}$ with domain consisting of the elements $\{x_{\sigma,k}: k < \alpha\} \cup \{y_{\sigma,k}: k < \omega\}$ and $\mathcal{D}_+(\mathcal{A}_{\sigma,\alpha})$ saying that the elements $x_{\sigma,k}$ form an equivalence class of size at least α and the elements $y_{\sigma,k}$ form an equivalence class of size ω . Notice that $k \leq m$ implies $\mathcal{D}_+(\mathcal{A}_{\sigma,k}) \subseteq \mathcal{D}_+(\mathcal{A}_{\sigma,m})$.

Suppose M is a learner for the class \mathfrak{K} . We describe how the desired mapping Γ works. Given a finite set D, consider all finite enumerations σ of parts of D. First, we make sure that if $M(\sigma) = i$, then $\Gamma(D)$ contains the positive diagram of $\mathcal{A}_{\sigma,i+1}$. Second, if for some initial segment τ of σ , $M(\tau) \neq M(\sigma)$, then $\Gamma(D)$ contains the positive diagram of $\mathcal{A}_{\tau,\omega}$. More formally, let E_D be the set of all σ enumerating parts of D. Then $\Gamma(D)$ is the least set obeying the rules:

- (1) $\bigcup_{\sigma \in E_D} \{ \mathcal{D}_+(\mathcal{A}_{\sigma,i+1}) : M(\sigma) = i \} \subseteq \Gamma(D);$
- (2) $\bigcup_{\sigma \in E_D} \{ \mathcal{D}_+(\mathcal{A}_{\tau,\omega}) : \tau \prec \sigma \& M(\tau) \neq M(\sigma) \} \subseteq \Gamma(D).$

It is easy to see that Γ is motonone and compact, and hence Scott-continuous by Corollary 2.

Let $\mathcal{B}_i \in \mathfrak{K}$. We will show that $\Gamma(\mathcal{B}_i)$ is an equivalence structure of type $[\omega : \omega, i + 1 : \omega]$. By Proposition 3, there are infinitely many σ on $\mathcal{D}_+(\mathcal{B}_i)$ such that $M(\sigma) = i$ and for all $\tau \succ \sigma$, $M(\tau) = i$. By the construction of Γ , $\Gamma(\mathcal{B}_i)$ contains infinitely many equivalence classes of size i + 1. Assume that $\Gamma(\mathcal{B}_i)$ contains an equivalence class of a finite size $j + 1 \neq i + 1$. This can happen if there is a finite ρ on $\mathcal{D}_+(\mathcal{B}_i)$ such that $M(\rho) = j$ and the equivalence structure $\mathcal{A}_{\rho,j+1}$ is a part of $\Gamma(\mathcal{B}_i)$. Again by Proposition 3, there exists an extension ρ' of ρ such that $M(\rho') = M(\tau)$ for all τ extending ρ' . Since M learns \mathcal{B}_i , we have $M(\rho') = i$. It follows by the construction of Γ that the equivalence structure $\mathcal{A}_{\rho,j+1}$ is extended to $\mathcal{A}_{\rho,\omega}$ in $\Gamma(\mathcal{B})$.

 $(2) \Rightarrow (3)$. The next proposition shows the usefulness of Theorem 2 in giving a syntactic characterization of **TxtEx**-learnable classes.

Lemma 2. Let $\mathfrak{K} = {\mathcal{B}_i : i < \omega}$ be a class such that $\Gamma : \mathfrak{K} \leq_{Scott} \tilde{\mathcal{E}}$. Then there exist Σ_2^p sentences φ_i such that $\mathcal{B}_i \models \varphi_j$ if and only if i = j.

Proof. Without loss of generality, we may assume that $\Gamma(\mathcal{B}_i)$ is an equivalence structure \mathcal{A}_i of type $[\omega : \omega, i+1 : \omega]$. For \mathcal{A}_i , we have the infinitary Σ_2^p sentence

$$\varphi_i \stackrel{\text{def}}{=} \exists x_0 \cdots x_i \bigg[\bigwedge_{k \neq \ell \le i} (x_k \sim x_\ell \& x_k \neq x_\ell) \& \forall y (\neg y \sim x_0 \lor \bigvee_{\ell \le i} \neg y \neq x_\ell) \bigg].$$
(1)

Notice that we assume that \neq is in our signature, so $x_k \neq x_\ell$ is a positive atomic formula. By Theorem 2, we obtain Σ_2^p sentences for the structures \mathcal{B}_i in Æ.

 $(3) \Rightarrow (1)$. We give the final part of the proof:

Lemma 3. Let $\mathfrak{K} = {\mathcal{B}_i : i < \omega}$. Suppose that there exist Σ_2^p sentences φ_i such that $\mathcal{B}_i \models \varphi_j$ if and only if i = j. Then \mathfrak{K} is **TxtEx**-learnable.

Proof. Without loss of generality, suppose that the Σ_2^p sentence φ_i has the form

$$\varphi_i = \exists \bar{x}_i \bigg(\alpha_i(\bar{x}_i) \land \bigwedge_{j \in J_i} \forall \bar{y}_j \neg (\beta_{i,j}(\bar{x}_i, \bar{y}_j)) \bigg),$$

where α_i and $\beta_{i,j}$ are positive atomic formulas, and J_i is a countable set. We will describe how the learner M for the class \mathfrak{K} works.

Consider an arbitrary sequence σ of positive atomic formulas. We must determine the value of $M(\sigma)$. We find the least $\langle i, \bar{a} \rangle$ such that the Gödel code of $\alpha_i(\bar{a})$ is in the range of σ and no sentence of the form $\beta_{i,j}(\bar{a}, b_j)$ is in the range of σ . Then we let $M(\sigma) = i$.

Suppose $\mathcal{A} \cong \mathcal{B}_i$ and consider some text $\mathbb{T}_{\mathcal{A}}$ for \mathcal{A} . Since $\mathcal{A} \models \varphi_i$, find the least tuple \bar{a} such that $\mathcal{A} \models \alpha_i(\bar{a})$ and $\mathcal{A} \models \bigwedge_{j \in J_i} \forall \bar{y}_j \neg (\beta_{i,j}(\bar{a}, \bar{y}_j))$. It follows that the code of $\alpha_i(\bar{a})$ will appear in some initial segment of $\mathbb{T}_{\mathcal{A}}$ and none of the positive atomic sentences $\beta_{i,j}(\bar{a}, \bar{b}_j)$ will appear in $\mathbb{T}_{\mathcal{A}}$ for any \bar{b}_j and any $j \in J_i$. It follows that $\lim_{n \to \infty} M(\mathbb{T}_{\mathcal{A}} \upharpoonright n) = i$.

Lemma 3 and Theorem 3 are proved.

The choice of the class $\tilde{\mathcal{E}}$ in Theorem 3 seems somewhat arbitrary. The statement of Theorem 3 suggests the following definition.

Definition 7. A countably infinite class \Re_0 is **TxtEx**-complete if

- \mathfrak{K}_0 is **TxtEx**-learnable, and
- for any countable **TxtEx**-learnable class \mathfrak{K} , $\mathfrak{K} \leq_{\text{Scott}} \mathfrak{K}_0$.

Corollary 4. The class $\tilde{\mathcal{E}}$ is \mathbf{TxtEx} -complete.

6 TxtEx-Complete Classes

Consider a signature $L_{st} = \{<, =, \neq\} \cup \{P_i : i \in \omega\}$, where all P_i are unary. For each $i \in \omega$, we define a structure \mathcal{A}_i , where all $P_j^{\mathcal{A}_i}$ are disjoint infinite sets. In addition, for any two elements x, y, where $x \in P_j$ and $y \in P_k$ for $j \neq k, x$ and

y are incomparable under <. Let η denote the order type of the rationals, and, if $\mathcal{A}_{i,j}$ is the restriction of \mathcal{A}_i to the elements in P_j , then define

$$\mathcal{A}_{i,j} \cong \begin{cases} \eta, & \text{if } i \neq j \\ 1+\eta, & \text{if } i=j. \end{cases}$$

Let us denote $\Re_{st} = \{\mathcal{A}_i : i \in \omega\}$. This class is studied in [5], and by combining [5] with Corollary 1, the following characterization of **InfEx**-learnability is obtained.

Theorem 4 ([5]). For a class $\mathfrak{K} = \{\mathcal{B}_i : i \in \omega\}$, the following are equivalent:

- (1) The class \Re is InfEx-learnable.
- (2) $\Re \leq_{\text{Cantor}} \Re_{st}$.
- (3) There is a sequence of Σ_2^{inf} sentences $\{\psi_i : i \in \omega\}$ such that for all i and j, $\mathcal{B}_j \models \psi_i$ if and only if i = j.

This result suggests the following definition.

Definition 8. We say that a class \Re_0 is InfEx-complete if

- \mathfrak{K}_0 is InfEx-learnable;
- for any InfEx-learnable class \mathfrak{K} , $\mathfrak{K} \leq_{\text{Cantor}} \mathfrak{K}_0$.

It follows that the class \Re_{st} is **InfEx**-complete. Now we will show that \Re_{st} is also **TxtEx**-complete (see Proposition 4 below). To do this, we borrow some ideas from [2] to get a series of ancillary facts.

Lemma 4. $\tilde{\mathcal{E}} \leq_{pc} \mathfrak{K}_{st}$.

Proof. For each number $k \geq 1$, consider the enumeration operator Γ_{e_k} (which takes an equivalence structure as an input), where the domain of the output structure is the set of non-empty tuples

$$D_k = \left\{ (x_0, \dots, x_n) : \bigwedge_{i < n} x_i <_{\mathbb{N}} x_{i+1} \& |[x_i]_{\sim}| \ge k+1 \& |[x_n]_{\sim}| \ge k \right\},\$$

where the ordering between the tuples is given by $\overline{x} \prec \overline{y}$ if and only if \overline{x} is a proper extension of \overline{y} , or $x_i <_{\mathbb{N}} y_i$ for some index $i < \min\{|\overline{x}|, |\overline{y}|\}$.

If the input structure \mathcal{A} has type $[\omega : \omega, k : \omega]$, then $\Gamma_{e_k}(\mathcal{A})$ is a linear ordering with a least element and no greatest element, and, if the input structure \mathcal{A} has type $[\omega : \omega, m : \omega]$ for $m \neq k$, then $\Gamma_{e_k}(\mathcal{A})$ is a linear ordering with no least element and no greatest element.

Now, let Ψ_{a_k} be such that $\Psi_{a_k}(\mathcal{A})$ enumerates a copy of $1 + \eta$ in place of the elements enumerated by $\Gamma_{e_k}(\mathcal{A})$. At last, let $\Theta(\mathcal{A})$ enumerate the disjoint union of the structures $\Gamma_{e_k}(\mathcal{A})$ with P_k distinguishing the substructure enumerated by $\Gamma_{e_k}(\mathcal{A})$. It is now routine to check that $\tilde{\mathcal{E}} \leq_{pc} \mathfrak{K}_{st}$ via Θ .

Lemma 5. $\Re_{st} \leq_{pc} \mathcal{E}$.

Proof. Suppose that the input structure \mathcal{A} has domain $\{x_{k,i} : i, k \in \omega\}$, where $P_k^{\mathcal{A}} = \{x_{k,i} : i \in \omega\}$. We describe how the enumeration operator Γ_e works. The output structures of Γ_e will always have domain a subset of $\{y_{k,i}^j : k, i, j \in \omega\}$.

For any k, on input the finite diagram D_k describing a finite chain (inside $P_k^{\mathcal{A}}$) $x_{k,i_0} <_{\mathcal{A}} x_{k,i_1} <_{\mathcal{A}} \cdots <_{\mathcal{A}} x_{k,i_n}$, $\Gamma_e(D_k)$ is an infinite part of the output equivalence structure describing the following:

$$\bigwedge_{j < k} (y_{k,i_0}^j \sim y_{k,i_0}^{j+1}) \And \bigwedge_{\ell=1}^n \bigwedge_{j \in \omega} (y_{k,i_\ell}^j \sim y_{k,i_\ell}^{j+1}).$$

In other words, we associate with the current least element in the k-th linear ordering $P_k^{\mathcal{A}}$ an equivalence class of size k + 1, and with any other element in the k-th linear ordering we associate an infinite equivalence class.

Let \mathcal{A}_k be the restriction of \mathcal{A} to $P_k^{\mathcal{A}}$. If $\mathcal{A}_k \cong 1 + \eta$, then $\Gamma_e(\mathcal{A})$ will contain an equivalence class of size k + 1, and all other equivalence classes will be infinite.

Lemma 6. $\mathcal{E} \leq_{pc} \tilde{\mathcal{E}}$.

Proof. We define $\Gamma: \mathcal{E} \leq_{pc} \tilde{\mathcal{E}}$ is a straightforward manner: Γ essentially copies the input structure infinitely many times. \Box

By combining the previous three lemmas and Corollary 4 we obtain:

Proposition 4. The classes \mathcal{E} , $\tilde{\mathcal{E}}$, and \mathfrak{K}_{st} are **TxtEx**-complete.

7 Applications

Recall that [10, Theorem 1.4] proves that the class $\mathfrak{K} = \{[\omega : 1], [\omega : 2]\}$ is **InfEx**-learnable, but not **TxtEx**-learnable. We give a new simple proof of this fact using **TxtEx**-complete classes.

Proposition 5. The class $\Re = \{[\omega : 1], [\omega : 2]\}$ is InfEx-learnable, but not TxtEx-learnable.

Proof. Towards a contradiction, assume that \mathfrak{K} is **TxtEx**-learnable. A simple analysis of the proof of Lemma 1 shows that for the class $\mathfrak{K}_0 = \{[\omega : 1, 1 : 1], [\omega : 1, 2 : 1]\}$, we must have $\mathfrak{K} \leq_{\text{Scott}} \mathfrak{K}_0$ via some Scott-continuous operator Γ . Without loss of generality, suppose that for any structure \mathcal{A} of type $[\omega : 1], \Gamma(\mathcal{A})$ is an equivalence structure of type $[\omega : 1, 1 : 1]$.

Let b_0 be the element in $\Gamma(\mathcal{A})$ such that $|[b_0]_{\sim}| = 1$. By compactness, there is some finite part α of \mathcal{A} for which $b_0 \in \Gamma(\alpha)$. Now, partition \mathcal{A} into two infinite classes of infinite size such that α is contained entirely in one of the classes. In this way we produce a structure \mathcal{A}' of type $[\omega : 2]$ which is a substructure (w.r.t. positive atomic facts) of \mathcal{A} . Since Scott-continuity implies monotonicity, $\Gamma(\mathcal{A}') \subseteq \Gamma(\mathcal{A})$. Since $b_0 \in \Gamma(\alpha)$ and α is a finite part of \mathcal{A}' , $b_0 \in \Gamma(\mathcal{A}')$. But since $\Gamma(\mathcal{A}')$ has type $[\omega : 1, 2 : 1]$, it follows that there is at least one element c_0 such that $\Gamma(\mathcal{A}') \models b_0 \sim c_0$. Since $\Gamma(\mathcal{A}') \subseteq \Gamma(\mathcal{A})$, it follows that $\Gamma(\mathcal{A}) \models b_0 \sim c_0$. We reach a contradiction with the fact that $|[b_0]_{\sim}| = 1$ in $\Gamma(\mathcal{A})$. It is natural to search for **TxtEx**-learnable classes which are not **TxtEx**complete. Consider the class $\mathfrak{K} = \{\mathcal{A}_i : i \geq 1\}$, where \mathcal{A}_i is an equivalence structure of type $[i : \omega]$. It is clear that \mathfrak{K} is **TxtEx**-learnable, since for each structure \mathcal{A}_i we have a distinguishing Σ_2^p sentence $\psi_i := \varphi_{i-1}$ taken from Eq. (1).

To see that \mathfrak{K} is not **TxtEx**-complete, it is enough to consider the following.

Proposition 6. $\{[\omega:1,1:1], [\omega:1,2:1]\} \not\leq_{Scott} \{[1:\omega], [2:\omega]\}.$

Proof. Assume that $\Gamma: \{[\omega:1,1:1], [\omega:1,2:1]\} \leq_{\text{Scott}} \{[1:\omega], [2:\omega]\}$. Let \mathcal{B} be an equivalence structure of type $[\omega:1,1:1]$ and \mathcal{A} be a substructure (w.r.t. positive atomic facts) of \mathcal{B} of type $[\omega:1,2:1]$. By the monotonicity of Scott-continuous operators, $\Gamma(\mathcal{A}) \subseteq \Gamma(\mathcal{B})$. But $\Gamma(\mathcal{A})$ is an equivalence structure of type $[2:\omega]$ and $\Gamma(\mathcal{B})$ is an equivalence structure of type $[1:\omega]$. We reach a contradiction by observing that $[2:\omega]$ is not embeddable into $[1:\omega]$. \Box

Assume that the class \mathfrak{K} is **TxtEx**-complete, then $\mathcal{E} \leq_{\text{Scott}} \mathfrak{K}$. We can easily generalize the argument from Proposition 6 to reach a contradiction.

8 Further Discussion

Recall that the paper [3] explored some connections between InfEx-learnability and descriptive set theory. Here we elaborate more on this approach.

For $\alpha, \beta \in 2^{\omega}$, we define $\alpha E_0 \beta$ if and only if $(\exists n)(\forall m \ge n)[\alpha(n) = \beta(n)]$. In [3], a class of structures \mathfrak{K} is characterized as **InfEx**-learnable if and only if the isomorphism relation $\cong \upharpoonright \mathrm{LD}(\mathfrak{K})$ is (Cantor-)continuously reducible to the relation E_0 of eventual agreement on reals (i.e., there is a Cantor-continuous function Φ such that for all $\mathcal{A}, \mathcal{B} \in \mathfrak{K} \mathcal{A} \cong \mathcal{B}$ if and only if $\Phi(\mathcal{A}) E_0 \Phi(\mathcal{B})$. Motivated by this result we formulate the following question

Motivated by this result we formulate the following question.

Question 1. Characterize **TxtEx**-learnability in terms of Scott-continuous functions and familiar Borel equivalence relations.

Acknowledgements. Fokina was supported by the Austrian Science Fund FWF through the project P 36781. Rossegger was supported by the European Union's Horizon 2020 Research and Innovation Programme under the Marie Skłodowska-Curie grant agreement No. 101026834 — ACOSE. Soskova and Vatev were partially supported by FNI-SU 80-10-180/17.05.2023.

References

- C. J. Ash and J. F. Knight. Computable structures and the hyperarithmetical hierarchy. Vol. 144. Stud. Logic Found. Math. Elsevier Science B.V., 2000.
- N. A. Bazhenov, H. Ganchev, and S. Vatev. "Computable Embeddings for Pairs of Linear Orders". In: *Algebra and Logic* 60.3 (2021), pp. 163–187. ISSN: 0002-5232, 1573-8302. DOI: 10.1007/s10469-021-09639-7.
- [3] Nikolay Bazhenov, Vittorio Cipriani, and Luca San Mauro. "Learning algebraic structures with the help of Borel equivalence relations". In: *Theoretical Computer Science* 951 (2023). ISSN: 03043975. DOI: 10.1016/j.tcs.2023.113762.

- [4] Nikolay Bazhenov, Ekaterina Fokina, Dino Rossegger, Alexandra A. Soskova, and Stefan V. Vatev. A Lopez-Escobar Theorem for Continuous Domains. 2023. arXiv: 2301.09940.
- [5] Nikolay Bazhenov, Ekaterina Fokina, and Luca San Mauro. "Learning families of algebraic structures from informant". In: *Information and Computation* 275 (2020), p. 104590. ISSN: 08905401. DOI: 10.1016/j.ic.2020.104590.
- [6] Nikolay Bazhenov and Luca San Mauro. "On the Turing complexity of learning finite families of algebraic structures". In: *Journal of Logic and Computation* 31.7 (2021), pp. 1891–1900. ISSN: 0955-792X, 1465-363X.
 DOI: 10.1093/logcom/exab044.
- W. Calvert, D. Cummins, J. F. Knight, and S. Miller. "Comparing classes of finite structures". In: *Algebra Logic* 43.6 (2004), pp. 374–392. DOI: 10.1023/B:ALL0.0000048827.30718.2c.
- [8] John Case. "Enumeration reducibility and partial degrees". In: Annals of Mathematical Logic 2.4 (1971), pp. 419–439. ISSN: 00034843. DOI: 10.1016/0003-4843(71)90003-9.
- [9] S. Barry Cooper. "Enumeration reducibility, nondeterministic computations and relative computability of partial functions". In: *Recursion Theory Week.* Ed. by Klaus Ambos-Spies, Gert H. Müller, and Gerald E. Sacks. Vol. 1432. Lecture Notes in Mathematics. Berlin, Heidelberg: Springer Berlin Heidelberg, 1990, pp. 57–110. ISBN: 978-3-540-52772-5 978-3-540-47142-4. DOI: 10.1007/BFb0086114.
- [10] Ekaterina Fokina, Timo Kötzing, and Luca San Mauro. "Limit Learning Equivalence Structures". In: Proceedings of the 30th International Conference on Algorithmic Learning Theory. Ed. by Aurélien Garivier and Satyen Kale. Vol. 98. Proceedings of Machine Learning Research. PMLR, 22–24 Mar 2019, pp. 383–403.
- Ziyuan Gao, Frank Stephan, Guohua Wu, and Akihiro Yamamoto. "Learning Families of Closed Sets in Matroids". In: Computation, Physics and Beyond - International Workshop on Theoretical Computer Science, WTCS 2012. Ed. by Michael J. Dinneen, Bakhadyr Khoussainov, and André Nies. Vol. 7160. LNCS. Berlin: Springer, 2012, pp. 120–139. DOI: 10.1007/978-3-642-27654-5_10.
- [12] E. Mark Gold. "Language identification in the limit". In: Inf. Control 10.5 (1967), pp. 447–474. DOI: 10.1016/S0019-9958(67)91165-5.
- [13] Valentina S. Harizanov and Frank Stephan. "On the learnability of vector spaces". In: J. Comput. Syst. Sci. 73.1 (2007), pp. 109–122. DOI: 10.1016/j.jcss.2006.09.001.
- [14] Sanjay Jain, Daniel Osherson, James S. Royer, and Arun Sharma. Systems that learn. Cambridge, MA: MIT Press, 1999.
- [15] J. F. Knight, S. Miller, and M. Vanden Boom. "Turing computable embeddings". In: J. Symb. Log. 72.3 (2007), pp. 901–918. DOI: 10.2178/jsl/1191333847.
- [16] Hilary Putnam. "Trial and error predicates and the solution to a problem of Mostowski". In: J. Symb. Log. 30.1 (1965), pp. 49–57. DOI: 10.2307/2270581.
- [17] Ivan Soskov. "Degree spectra and co-spectra of structures". In: Annual of Sofia University 96 (2004), pp. 45–68.
- [18] Frank Stephan and Yuri Ventsov. "Learning algebraic structures from text". In: *Theor. Comput. Sci.* 268.2 (2001), pp. 221–273. DOI: 10.1016/S0304-3975(00)00272-3.