An Algorithmic Meta Theorem for Homomorphism Indistinguishability

Tim Seppelt

RWTH Aachen University

seppelt@cs.rwth-aachen.de

February 15, 2024

Two graphs *G* and *H* are *homomorphism indistinguishable* over a family of graphs \mathcal{F} if for all graphs $F \in \mathcal{F}$ the number of homomorphisms from *F* to *G* is equal to the number of homomorphism from *F* to *H*. Many natural equivalence relations comparing graphs such as (quantum) isomorphism, cospectrality, and logical equivalences can be characterised as homomorphism indistinguishability relations over various graph classes.

For a fixed graph class \mathcal{F} , the decision problem HOMIND(\mathcal{F}) asks to determine whether two input graphs G and H are homomorphism indistinguishable over \mathcal{F} . The problem HOMIND(\mathcal{F}) is known to be decidable only for few graph classes \mathcal{F} . We show that HOMIND(\mathcal{F}) admits a randomised polynomial-time algorithm for every graph class \mathcal{F} of bounded treewidth which is definable in counting monadic second-order logic CMSO₂. Thereby, we give the first general algorithm for deciding homomorphism indistinguishability.

This result extends to a version of HOMIND where the graph class \mathcal{F} is specified by a CMSO₂-sentence and a bound k on the treewidth, which are given as input. For fixed k, this problem is randomised fixed-parameter tractable. If k is part of the input then it is coNP- and coW[1]-hard. Addressing a problem posed by Berkholz (2012), we show coNP-hardness by establishing that deciding indistinguishability under the k-dimensional Weisfeiler–Leman algorithm is coNP-hard when k is part of the input.

1 Introduction

In 1967, Lovász [30] proved that two graphs *G* and *H* are isomorphic if and only if they are *homomorphism indistinguishable* over all graphs, i.e. they admit the same number of homomorphisms from every graph *F*. Subsequently, many graph isomorphism relaxations have been characterised as homomorphism indistinguishability relations. For example, two graphs are quantum isomorphic if and only if they are homomorphism indistinguishable over all planar graphs [32]. Moreover, two graphs satisfy the same sentences in *k*-variable first-order logic with counting quantifiers if and only if they are homomorphism indistinguishable over all graphs of treewidth less than *k* [20, 19]. A substantial list of similar results characterises notions from quantum information [32, 6], finite model theory [20, 23, 21], convex optimisation [19, 27, 37], algebraic graph theory [19, 27], machine learning [33, 40, 24], and category theory [18, 2] as homomorphism indistinguishability relations.

The wealth of such examples motivates a more principled study of homomorphism indistinguishability [4, 36, 39]. From a computational perspective, the central question on homomorphism indistinguishability concerns the complexity and computability of the following decision problem [36, Question 9]:

$\operatorname{HomInd}(\mathcal{F})$
INPUT: Graphs G and H.
QUESTION: Are <i>G</i> and <i>H</i> homomorphism indistinguishable over \mathcal{F} ?

Here, we consider the graph class \mathcal{F} to be fixed and not part of the input. The graphs G and H may be arbitrary graphs and do not necessary have to be in \mathcal{F} . Typically, the graph class \mathcal{F} is infinite. Thus, the trivial approach to HOMIND(\mathcal{F}) of checking whether G and H have the same number of homomorphisms from every $F \in \mathcal{F}$ does not even render HOMIND(\mathcal{F}) decidable.

In general, the understanding of $HOMIND(\mathcal{F})$ is limited and does not go beyond a short list of examples. For arguably artificial graph classes \mathcal{F} , $HOMIND(\mathcal{F})$ can be arbitrarily hard [13, 39]. However, even for natural graph classes \mathcal{F} the complexity-theoretic landscape of $HOMIND(\mathcal{F})$ is diverse:

For the class \mathcal{G} of all graphs, HOMIND(\mathcal{G}) is graph isomorphism [30], a problem representing a long standing complexity-theoretic challenge and currently only known to be in quasi-polynomial time [7]. For the class \mathcal{P} of all planar graphs, HOMIND(\mathcal{P}) is undecidable [32]. For the class \mathcal{K} of all cliques, HOMIND(\mathcal{K}) is decidable, yet C₌P-hard [13]. Finally, for the class \mathcal{TW}_k of all graphs of treewidth at most k, HOMIND(\mathcal{TW}_k) can be solved in polynomial time using the well-known k-dimensional Weisfeiler–Leman algorithm [20, 14].

In this work, we generalise the last example by establishing that $HOMIND(\mathcal{F})$ is tractable for every recognisable graph class \mathcal{F} of bounded treewidth thus giving the first general algorithm for deciding homomorphism indistinguishability.

Theorem 1.1. Let $k \ge 1$. If \mathcal{F} is a k-recognisable graph class of treewidth at most k - 1 then HomIND(\mathcal{F}) is in coRP.

Spelled out, Theorem 1.1 asserts that there exists a randomised algorithm for HOMIND(\mathcal{F}) which always runs in polynomial time, accepts all YES-instances and incorrectly accepts NO-instances with probability less than one half. Recognisability is a notion arising in the context of Courcelle's theorem [15] on model checking, cf. Definition 2.10. Courcelle showed that every graph class definable in counting monadic second-order logic CMSO₂ is recognisable. This subsumes graph classes defined by forbidden (induced) subgraphs and minors, and by the Robertson–Seymour Theorem, all minor-closed graph classes.

Thereby, Theorem 1.1 applies to e.g. the class of graphs of bounded branchwidth, *k*-outerplanar graphs, and the class of trees of bounded degree. The theorem also applies to the graph classes arising in homomorphism indistinguishability characterisations for the Lasserre semidefinite programming hierarchy [37]. In this way, we answer a question raised in [37] affirmatively, cf. Theorem 8.1.

The proof of Theorem 1.1 combines Courcelle's graph algebras [16] with the homomorphism tensors from [32, 27]. Graph algebras comprise labelled graphs and operations on them such as series and parallel composition. Homomorphism tensors keep track of homomorphism counts of labelled graphs. We show that recognisability and bounded treewidth guarantee that homomorphism tensors yield finite-dimensional representations of suitable graph algebras which certify homomorphism indistinguishability and are efficiently computable.

Observing that the dimension of the space of homomorphism tensors corresponds to the number of labels of the labelled graphs in the graph algebra which they represent, one might conjecture the following: The problem HomIND(\mathcal{F}) should be decidable if and only if the graph class \mathcal{F} can be generated as family of labelled graphs with a bounded number of labels, cf. Question 10.1. Indeed, for planar graphs \mathcal{P} , the result [32] of Mančinska and Roberson requires an unbounded number of labels and characterises homomorphism indistinguishability over \mathcal{P} as the existence of some infinite-dimensional operator. Intuitively, HomIND(\mathcal{P}) is undecidable as it requires solving an infinite-dimensional system of equations. Our Theorem 1.1 makes the other direction of this vague argument precise: We show that if the number of labels is bounded (e.g. the graph class has bounded treewidth) then considering finite-dimensional spaces suffices, rendering the problem tractable.

Theorem 1.1 can be strengthened in several ways. Firstly, the connection to Courcelle's theorem motivates considering the following parametrised problem:

HOMIND INPUT: Graphs G, H, a CMSO₂-sentence φ , an integer k. PARAMETER: $|\varphi| + k$. QUESTION: Are G and H homomorphism indistinguishable over $\mathcal{F}_{\varphi,k} := \{ \text{graph } F \mid F \models \varphi \text{ and tw } F \leq k - 1 \}$?

The logical sentence φ allows the graph class to be specified as part of the input. We generalise Theorem 1.1 as follows:

Theorem 1.2. There exists a computable function $f: \mathbb{N} \to \mathbb{N}$ and a randomised algorithm for HOMIND of runtime $f(|\varphi| + k)n^{O(k)}$ for $n := \max\{|V(G)|, |V(H)|\}$ which accepts all YES-instances and accepts NO-instances with probability less than one half.

While Theorem 1.1 does not depend on Courcelle's work beyond the notion of recognisability, Theorem 1.2 uses his result asserting that given a CMSO₂-sentence φ and $k \in \mathbb{N}$ a finite automaton can be computed which accepts width-*k* tree-decomposed graphs satisfying φ . Based on this automaton, our algorithm for Theorem 1.2 computes a basis for finite-dimensional vector spaces of homomorphism tensors associated to each of its states.

Theorem 1.1 is significant in light of the fact that HOMIND(\mathcal{F}) was previously not even known to be decidable for most graph classes \mathcal{F} in its scope. Despite that, it would be desirable to eliminate the need for randomness. We accomplish this for a large range of graph classes:

Theorem 1.3. Let $k \ge 1$. If \mathcal{F} is a k-recognisable graph class of pathwidth at most k - 1 then HOMIND(\mathcal{F}) is in polynomial time.

Furthermore, we show similarly to Theorem 1.2 that the analogue of HOMIND with pathwidth instead of treewidth admits a deterministic algorithm of runtime $f(|\varphi| + k)n^{O(k)}$, cf. Theorem 7.2.

Equipped with the parametrised perspective offered by HOMIND, we finally consider lower bounds on the complexity of this problem. Firstly, we show that it is coW[1]-hard and that the runtime of the algorithm that yielded Theorem 1.3 is optimal under the Exponential Time Hypothesis (ETH).

Theorem 1.4. HOMIND is coW[1]-hard under fpt-reductions. Unless ETH fails, there is no algorithm for HOMIND that runs in time $f(|\varphi| + k)n^{o(|\varphi|+k)}$ for any computable function $f \colon \mathbb{N} \to \mathbb{N}$.

Secondly, we show that, when disregarding the parametrisation, HOMIND is coNP-hard. We do so by showing coNP-hardness of the following problem involving the Weisfeiler–Leman (WL)

algorithm. Theorem 1.5 is a first step towards resolving a problem posed by Berkholz [8]: Is the decision problem in Theorem 1.5 EXPTIME-complete?

Theorem 1.5. The problem of deciding given graphs G and H and an integer $k \in \mathbb{N}$ whether G and H are k-WL indistinguishable is coNP-hard under polynomial-time many-one reductions.

WL is an important heuristic in graph isomorphism and tightly related to notions in finite model theory [14] and graph neural networks [40, 33, 24]. The best known algorithm for WL runs in time $O(k^2n^{k+1}\log n)$ [28], which is exponential when regarding k as part of the input. It was shown that when k is fixed then the problem is PTIME-complete [22]. Establishing lower bounds on the complexity of WL is a challenging problem [8, 9, 25].

2 Preliminaries

All graphs in this work are simple, undirected, and without multiple edges. For a graph G, we write V(G) for its vertex set and E(G) for its edge set. A homomorphism $h: F \to G$ from a graph F to a graph *G* is a map $V(F) \rightarrow V(G)$ such that $h(u)h(v) \in E(G)$ for all $uv \in E(F)$. Write hom(F, G)from the number of homomorphisms from F to G.

Two graph G and H are homomorphism indistinguishable over a class of graph \mathcal{F} , in symbols $G \equiv_{\mathcal{F}} H$, if hom(*F*, *G*) = hom(*F*, *H*) for all $F \in \mathcal{F}$. For an integer $n \geq 2$, *G* and *H* are homomorphism *indistinguishable over* \mathcal{F} *modulo* n, in symbols $G \equiv_{\mathcal{F}}^{n} H$, if hom $(F, G) \equiv \text{hom}(F, H) \mod n$ for all $F \in \mathcal{F}$, cf. [29].

Let log denote the logarithm to base 2. We recall the following consequences of (an explicit version of) the Prime Number Theorem [38].

Fact 2.1. For $n \ge e^{2000}$, the following hold:

- 1. the number of primes $n is at least <math>\frac{n^2}{2\log n}$,
- 2. the product of all primes $n is at least is <math>2^{n^2/2}$, 3. the probability that a random number $n < m \le n^2$ is prime is $\ge \frac{1}{2\log n}$.

Proof. Let ln denote the natural logarithm. Let $\pi(n)$ denote the number of primes $\leq n$. By [38, Theorem 30A], for $n \ge e^{2000}$,

$$\frac{n}{\ln n} < \pi(n) < \frac{n}{\ln n - 2}$$

Thus the desired quantity $\pi(n^2) - \pi(n)$ is at least

$$\frac{n^2}{2\ln n} - \frac{n}{\ln n - 2} \ge \frac{n^2}{2\ln n} - \frac{2n}{\ln n} = \frac{n^2 - 4n}{2\ln n} \ge \frac{n^2 \ln 2}{2\ln n}.$$

For the second claim, the product of the primes is $> n^{\frac{n^2}{2\log n}} = 2^{\frac{n^2}{2\log n}\log n} = 2^{n^2/2}$. For the third claim, $\frac{n^2}{2\log n} \cdot \frac{1}{n^2 - n} \ge \frac{1}{2\log n}$.

2.1 (Bi)labelled Graphs and Homomorphism Tensors

Let $k, \ell \geq 1$. A *k*-labelled graph is a tuple F = (F, u) where *F* is a graph and $u \in V(F)^k$ is a *k*-tuple with distinct entries. We say $u_i \in V(F)$, the *i*-th entry of *u*, carries the *i*-th label. Write $\mathcal{G}(k)$ for the class of k-labelled graphs. A k-labelled graph F = (F, u) is distinctly k-labelled if $u_i \neq u_i$ for all $1 \le i < j \le k$. Write $\mathcal{D}(k)$ for the class of distinctly *k*-labelled graphs.

A (k, ℓ) -bilabelled graph is a tuple F = (F, u, v) where F is a graph and $u \in V(F)^k$ and $v \in V(F)^\ell$. It is distinctly (k, ℓ) -bilabelled if $u_i \neq u_j$ for all $1 \leq i < j \leq k$ and $v_i \neq v_j$ for all $1 \leq i < j \leq \ell$. Note that u and v might share entries. We say $u_i \in V(F)$ and $v_i \in V(F)$ carry the *i*-th in-label and *out-label*, respectively. Write $\mathcal{G}(k, \ell)$ for the class of (k, ℓ) -bilabelled graphs and $\mathcal{D}(k, \ell)$ for the class of distinctly (k, ℓ) -bilabelled graphs.

For a graph *G*, and $\mathbf{F} = (F, \mathbf{u}) \in \mathcal{G}(k)$ define its *homomorphism tensor* $\mathbf{F}_G \in \mathbb{N}^{V(G)^k}$ whose \mathbf{v} -th entry is equal to the number of homomorphisms $h: F \to G$ such that $h(u_i) = v_i$ for all $i \in [k]$. Analogously, for $\mathbf{F} \in \mathcal{G}(k, \ell)$, define $\mathbf{F}_G \in \mathbb{N}^{V(G)^k \times V(G)^{\ell}}$. As the entries of homomorphism tensors are integral, we can view them as vectors in vector spaces over \mathbb{R} as in Section 3 or over finite fields \mathbb{F}_p as in Section 4.

As observed in [32, 27], cf. [37], (bi)labelled graphs and their homomorphism tensors are intriguing due to the following correspondences between combinatorial operations on the former and algebraic operations on the latter:

Dropping labels corresponds to sum-of-entries (soe): For $F = (F, u) \in \mathcal{G}(k)$, define soe $F \coloneqq F$ as the underlying unlabelled graph of F. Then for all graphs G, hom(soe F, G) = $\sum_{v \in V(G)^k} F_G(v) \Longrightarrow$ soe(F_G).

Gluing corresponds to Schur products: For F = (F, u) and F' = (F', u') in $\mathcal{G}(k)$, define $F \odot F' \in \mathcal{G}(k)$ as the distinctly *k*-labelled graph obtained by taking the disjoint union of *F* and *F'* and placing the *i*-th label at the vertex obtained by merging u_i with u'_i for all $i \in [k]$. Then for every graph *G* and $v \in V(G)^k$, $(F \odot F')_G(v) = F_G(v)F'_G(v) =: (F_G \odot F'_G)(v)$. One may similarly define the gluing product of two (k, ℓ) -bilabelled graphs.

Series composition corresponds to matrix products: For K = (K, u, v) and K' = (K', u', v') in $\mathcal{G}(k,k)$, define $K \cdot K' \in \mathcal{G}(k,k)$ as the bilabelled graph obtained by taking the disjoint union of K and K', identifying v_i with u'_i for $i \in [k]$, and placing the *i*-th in-label (out-label) on u_i (on v'_i) for $i \in [k]$. Then for all graphs G and $x, z \in V(G)^k$, $(K \cdot K')_G(x, z) = \sum_{y \in V(G)^k} K_G(x, y) K'_G(y, z) =$: $(K_G \cdot K'_G)(x, z)$. One may similarly compose a graph in $\mathcal{G}(k, k)$ with a graph in $\mathcal{G}(k)$ obtaining one in $\mathcal{G}(k)$. This operation correspond to the matrix-vector product.

Note that all operations above restrict from (bi)labelled graphs to distinctly (bi)labelled graphs. For example, the series product of two distinctly bilabelled graphs is distinctly bilabelled.

Permutation of labels corresponds to permutation of axes: Let $F = (F, u, v) \in \mathcal{G}(k, \ell)$ and write $\mathfrak{S}_{k+\ell}$ for the symmetric group acting on $k + \ell$ letters. For $\sigma \in \mathfrak{S}_{k+\ell}$, write $F^{\sigma} \coloneqq (F, x, y)$ where $x_i \coloneqq (uv)_{\sigma(i)}$ and $y_{j-k} \coloneqq (uv)_{\sigma(j)}$ for all $1 \le i \le k < j \le k + \ell$, i.e. F^{σ} is obtained from F by permuting the labels according to σ . Then for all graphs G, F_G^{σ} is obtained from F_G by permuting the axes of the tensor according to σ , cf. [37].

2.2 Labelled Graphs of Bounded Treewidth

Labelled graphs of bounded treewidth represent the technical foundation of most proofs in this article. Several versions of such have been discussed in previous works [27, 16, 21].

Let *F* be a graph. A *tree decomposition* of *F* is a pair (T, β) where *T* is a tree and $\beta \colon V(T) \to 2^{V(F)}$ is a map such that

1. the union of the $\beta(t)$ for $t \in V(T)$ is equal to V(F),

2. for every edge $e \in E(F)$ there exists $t \in V(T)$ such that $e \subseteq \beta(t)$,

3. for every vertex $u \in V(F)$ the set of vertices $t \in V(T)$ such that $u \in \beta(t)$ is connected in *T*. The *width* of (T, β) is the maximum over all $|\beta(t)| - 1$ for $t \in V(T)$. The *treewidth* tw *F* of *F* is the minimum width of a tree decomposition of *F*. A *path decomposition* is a tree decomposition (T, β) where *T* is a path. The *pathwidth* pw *F* of *F* is the minimum width of a path decomposition of *F*.

The following Lemmas 2.2 and 2.3 introduce tree and path decompositions with certain enjoyable properties.

Lemma 2.2 ([10, Lemma 8]). Let $k \ge 1$ and F be a graph such that $|V(F)| \ge k$. If tw $F \le k - 1$ then F admits a tree decomposition (T, β) such that

- 1. $|\beta(t)| = k$ for all $t \in V(T)$,
- 2. $|\beta(s) \cap \beta(t)| = k 1$ for all $st \in E(T)$.

If pw $F \le k - 1$ then F admits a path decomposition (T, β) satisfying Items 1 and 2.

The tree decompositions in Lemma 2.2 can be rearranged in order for the depth of the decomposition tree to give a bound on the number of vertices in the decomposed graph.

Lemma 2.3. Let $k \ge 1$ and F be a graph such that tw $F \le k - 1$ and $|V(F)| \ge k$. Then F admits tree decomposition (T, β) such that

- 1. $|\beta(t)| = k$ for all $t \in V(T)$,
- 2. $|\beta(s) \cap \beta(t)| = k 1$ for all $st \in E(T)$,
- 3. there exists a vertex $r \in V(T)$ such that the out-degree of every vertex in the rooted tree (T, r) is at most k.

Proof. Let (T, β) be a tree decomposition satisfying the assertions of Lemma 2.2. Pick a root $r \in V(T)$ arbitrarily. To ensure that the last property holds, the tree decomposition is modified recursively as follows:

By merging vertices, it can be ensured that no two children of *r* carry the same bag, i.e. that there exist no two children $s_1 \neq s_2$ of *r* such that $\beta(s_1) = \beta(s_2)$.

For every $v \in \beta(r)$, let C(v) denote the set of all children *t* of *r* such that $\beta(r) \setminus \beta(t) = \{v\}$, i.e. C(v) is the set of all children of *r* whose bags do not contain the vertex *v*. The collection C(v) for $v \in \beta(r)$ is a partition of the children of *r* in at most *k* parts.

Note that for two distinct children $t_1 \neq t_2$ in the same part C(v) it holds that $|\beta(t_1) \cap \beta(t_2)| = k - 1$. Rewire the children of *r* as follows: For every $v \in \beta(r)$ with $C(v) \neq \emptyset$, pick $t \in C(v)$, make *t* a child of *r* and all other elements of C(v) children of *t*.

The vertex *r* now has at most *k* children and the new tree decomposition still satisfies the assertions of Lemma 2.2. Proceed by processing the children of *r*. \Box

Inspired by Lemma 2.2, we consider the following family of distinctly labelled graphs. The *depth* of a rooted tree (T, r) is the maximal number of vertices on any path from r to a leaf.

Definition 2.4. Let $k, d \ge 1$. Define $\mathcal{TW}_d(k)$ as the set of all $F = (F, u) \in \mathcal{D}(k)$ such that F admits a tree decomposition (T, β) of width $\le k - 1$ satisfying the assertions of Lemma 2.3 with some $r \in V(T)$ such that $\beta(r) = \{u_1, \ldots, u_k\}$ and (T, r) is of depth at most d. Let $\mathcal{TW}(k) := \bigcup_{d \ge 1} \mathcal{TW}_d(k)$.

Crucially, this definition permits the following bound on the size of the graphs in $TW_d(k)$ in terms of *d* and *k*.

Lemma 2.5. Let $k, d \ge 1$. Every $F \in TW_d(k)$ has at most $\max\{k^d, d\}$ vertices.

Proof. Let (T,β) and $r \in V(T)$ be as in Definition 2.4. If k = 1, then every vertex in (T,r) has out-degree 1 and *F* at most *d* vertices.

Suppose that $k \ge 2$. The proof is by induction on the depth *d* of the rooted tree (T, r). If d = 1, then *T* contains only a single vertex and *F* has at most *k* vertices.

For the inductive step, let *F* be of depth *d*. If *r* has only a single neighbour *s*, then $S \coloneqq T - r$ is such that (S,s) is of depth d - 1. By the inductive hypothesis, $\left|\bigcup_{s \in V(S)} \beta(s)\right| \leq k^d$. Furthermore, $\left|\bigcup_{t \in V(T)} \beta(t) \setminus \bigcup_{s \in V(S)} \beta(s)\right| = 1$. Hence, *F* has at most $k^{d-1} + 1 \leq k^d$ many vertices.

If *r* has multiple neighbours, observe that due to Lemma 2.3 every vertex in $\beta(r)$ is also in $\beta(s)$ for some neighbour *s* of *r*. Hence, the number of vertices in *F* is bounded by the number of vertices covered by the subtrees of T - r rooted in *s*. Thus, *F* has at most $k^{d-1} \cdot k \leq k^d$ many vertices.



Figure 1: The (bi)labelled generators of TW(k) in wire notion of [32]. A vertex carries in-label (out-label) *i* if it is connected to the index *i* on the left (right) by a wire. Actual edges and vertices of the graph are depicted in black.

Clearly, if $F \in TW(k)$ then tw(soe F) $\leq k - 1$. Conversely, by Lemma 2.3, for every F with tw $F \leq k - 1$ and $|V(F)| \geq k$, there exists $u \in V(F)^k$ such that $(F, u) \in TW(k)$. Thus the underlying unlabelled graphs of the labelled graphs in TW(k) are exactly the graphs of treewidth $\leq k - 1$ on $\geq k$ vertices.

The family TW(k) is generated by certain small building blocks under series composition and gluing as follows.

Let $\mathbf{1} \in \mathcal{TW}_1(k)$ be the distinctly *k*-labelled graph on *k* vertices without any edges. For $i \in [k]$, let $\mathbf{J}^i = (J^i, (1, \dots, k), (1, \dots, i-1, \hat{i}, i+1, \dots, k))$ the distinctly (k, k)-bilabelled graph with $V(J^i) := [k] \cup \{\hat{i}\}$ and $E(J^i) := \emptyset$. Writing $\binom{[k]}{2}$ for the set of pairs of distinct elements in [k], let $A^{ij} = (A^{ij}, (1, \dots, k), (1, \dots, k))$ for $ij \in \binom{[k]}{2}$ be the distinctly (k, k)-bilabelled graph with $V(A^{ij}) := [k]$ and $E(A^{ij}) := \{ij\}$. These graphs are depicted in Figure 1. Let $\mathcal{B}(k) := \{\mathbf{J}^i \mid i \in [k]\} \cup \{A^{ij} \mid ij \in \binom{[k]}{2}\}$. Observe that $|\mathcal{B}(k)| \le k^2$.

It can be readily verified that if $F \in TW(k)$ and $B \in B(k)$ then $B \cdot F \in TW(k)$. Furthermore, if $F, F' \in TW(k)$ then $F \odot F' \in TW(k)$. Conversely, the elements of B(k) generate TW(k) in the following sense:

Lemma 2.6. Let $k \ge 1$. For every $\mathbf{F} \in \mathcal{TW}(k)$, one of the following holds:

1. *F* = 1,

- 2. $F = \prod_{ij \in A} A^{ij} \cdot F'$ for some $A \subseteq {\binom{[k]}{2}}$ and $F' \in \mathcal{TW}(k)$ with less edges than F,
- 3. $F = J^i \cdot F'$ for some $i \in [k]$ and $F' \in TW(k)$ with less vertices than F,
- 4. $F = F_1 \odot F_2$ for $F_1, F_2 \in TW(k)$ on less vertices than F.

Proof. Write F = (F, u) and let (T, β) and $r \in V(T)$ be for $F \in \mathcal{TW}(k)$ as in Definition 2.4.

For the second case, let $A = \{ij \in {[k] \choose 2} \mid u_i u_j \in E(F)\}$. Write F' for the graph obtained from F by deleting the edges $u_i u_j$ for $ij \in A$. Then $F' := (F', u) \in TW(k)$ and $F = \prod_{ij \in A} A^{ij} \cdot F'$.

If $A = \emptyset$, distinguish two cases: The vertex r has a unique neighbour $s \in V(T)$. By the assertions of Lemma 2.2, there exists a unique $i \in [k]$ such that $u_i \notin \beta(s)$. Let F' be the subgraph of F induced by $\bigcup_{t \in V(T) \setminus \{r\}} \beta(t)$ and write $v \in V(F')^k$ for the tuple of distinct vertices which coincides with u everywhere except at the *i*-th entry where it is equal to the unique vertex in $\beta(s) \setminus \beta(r)$. Then $F' := (F', v) \in TW(k)$ and $F = J^i \cdot F'$.

Finally, suppose that *r* has multiple neighbours $s_1, \ldots, s_m \in V(T)$. Let T_1 denote the connected component of $T - \{s_2, \ldots, s_m\}$ containing s_1 . Let T_2 denote the connected component of $T - \{s_1\}$ containing s_2, \ldots, s_m . For $j \in \{1, 2\}$, let F_j be the subgraph induced by $\bigcup_{t \in V(T_j)} \beta(t)$. Then F_1 contains less vertices than *F* since the vertex in $\beta(s_2) \setminus \beta(r)$ is not in F_1 . Symmetrically, F_2 contains

less vertices than *F*. Then $F_i := (F_i, u) \in TW(k)$ for $j \in \{1, 2\}$. As desired, $F = F_1 \odot F_2$.

2.3 Labelled Graphs of Bounded Pathwidth

The set-up from Section 2.2 can be adapted for pathwidth as follows.

Definition 2.7. For $k, d \ge 1$, write $\mathcal{PW}_d(k) \subseteq \mathcal{D}(k)$ for the class of all distinctly *k*-labelled graphs F = (F, u) such that there exists a path decomposition (P, β) of *F* where

- 1. $|\beta(t)| = k$ for all $t \in V(P)$,
- 2. $|\beta(s) \cap \beta(t)| = k 1$ for all $st \in E(P)$,
- 3. there exists a vertex $r \in V(P)$ of degree at most 1 such that $\beta(r) = \{u_1, \dots, u_k\}$,
- 4. $|V(P)| \le d$.

Let $\mathcal{PW}(k) \coloneqq \bigcup_{d>1} \mathcal{PW}_d(k)$.

By Lemma 2.2, for every graph *F* with pw $F \le k - 1$ on at least *k* vertices, there exists $u \in V(F)^k$ such that $(F, u) \in \mathcal{PW}(k)$. Conversely, the underlying graph of every $F \in \mathcal{PW}(k)$ has pathwidth at most k - 1. Analogously to Lemma 2.5, we obtain the following bound on the size of the graphs in $\mathcal{PW}_d(k)$:

Lemma 2.8. Let $k, d \ge 1$. Every $F \in \mathcal{PW}_d(k)$ has at most k + d - 1 vertices.

Proof. If d = 1, then the path decomposition (P, β) of F as in Definition 2.7 has at most one bag and F has at most k vertices. For larger d, observe that, when traversing the decomposition from one end of P to the other, every bag introduces exactly one new vertex. Thus, there are at most k + d - 1 vertices in F.

Similar to $\mathcal{TW}(k)$, $\mathcal{PW}(k)$ is generated by small building blocks. For $\mathcal{PW}(k)$, only series composition needs to be considered. Gluing is not permitted. Clearly, if $\mathbf{F} \in \mathcal{PW}(k)$ then $\mathbf{B} \cdot \mathbf{F} \in \mathcal{PW}(k)$ for every $\mathcal{B}(k)$.

Lemma 2.9. Let $k \ge 1$. For every $F \in \mathcal{PW}(k)$, one of the following holds:

1. F = 1, 2. $F = \prod_{ij \in A} A^{ij} \cdot F'$ for some $A \subseteq {\binom{[k]}{2}}$ and $F' \in \mathcal{PW}(k)$ with less edges than F, 3. $F = J^i \cdot F'$ for some $i \in [k]$ and $F' \in \mathcal{PW}(k)$ with less vertices than F.

Proof. Following the proof of Lemma 2.6, observe that the missing case does not occur.

2.4 Counting Monadic Second-Order Logic

We denote *first-order logic* over the relational signature {*E*} of graphs by FO. The logic MSO₁ is the extension of FO by variables X, Y, Z, ... which range over subsets of vertices and atomic formulas $x \in X$. The logic MSO₂ extends MSO₁ by first-order (monadic second-order) variables which range over edges (sets of edges) and atomic formulas inc(x, y) evaluates to true if x is assigned a vertex v and y is assigned an edge e such that v is incident with e. *Counting monadic second-order logic* CMSO₂ is the extension of MSO₂ by atomic formulas $card_{p,q}(X)$ for integers $p, q \in \mathbb{N}$ expressing $|X| \equiv p \mod q$. See [16] for further details.

2.5 Recognisability

We consider the following definition of recognisability [12].



Figure 2: Representatives for $\sim_{\mathcal{W}}$ for k = 1 and \mathcal{W} the class of paths from Example 2.11.

Definition 2.10. Let $k \ge 1$. For class of unlabelled graphs \mathcal{F} , define the equivalence relation $\sim_{\mathcal{F}}$ on the class of distinctly *k*-labelled graphs $\mathcal{D}(k)$ by letting $F_1 \sim_{\mathcal{F}} F_2$ if and only if for all $K \in \mathcal{D}(k)$ it holds that

$$\operatorname{soe}(\mathbf{K} \odot \mathbf{F}_1) \in \mathcal{F} \iff \operatorname{soe}(\mathbf{K} \odot \mathbf{F}_2) \in \mathcal{F}.$$

The class \mathcal{F} is *k*-recognisable if $\sim_{\mathcal{F}}$ has finitely many equivalence classes. The number of classes is the *k*-recognisability index of \mathcal{F} .

To parse Definition 2.10, first recall that $K \odot F_1$ is the *k*-labelled graph by gluing *K* and F_1 together at their labelled vertices. The soe-operator drops the labels yielding unlabelled graphs. Intuitively, $F_1 \sim_{\mathcal{F}} F_2$ iff both or neither of their underlying unlabelled graphs are in \mathcal{F} and the positions of the labels in F_1 and F_2 is equivalent with respect to membership in \mathcal{F} . Consider the following example:

Example 2.11. The class W of all paths is 1-recognisable. Its 1-recognisability index is 4. The equivalence classes are described by the representatives in Figure 2.

Proof. To show that the labelled graphs in Figure 2 cover all equivalence classes, let F = (F, u) be arbitrary. If F is not a path then $F \sim_{\mathcal{W}} C$. Indeed, for every $K \in \mathcal{D}(1)$, F is a subgraph of soe($K \odot F$). Hence, regardless of K, both soe($K \odot F$) and soe($K \odot C$) are not paths. If F is a path, then F and 1, P, or Q are equivalent depending on whether the degree of u is 0, 1, or 2.

To show that the representatives in Figure 2 are in distinct classes, observe for example that $\operatorname{soe}(P \odot P) \in \mathcal{W}$ while $\operatorname{soe}(P \odot Q) \notin \mathcal{W}$, thus $P \not\sim_{\mathcal{W}} Q$. Similarly, $\operatorname{soe}(1 \odot Q) \in \mathcal{W}$ whereas $\operatorname{soe}(P \odot Q) \notin \mathcal{W}$, thus $1 \not\sim_{\mathcal{W}} P$.

A more involved example is the following:

Example 2.12. Let \mathcal{F} be the family of *H*-subgraph-free graph for some graph *H*. Then \mathcal{F} is *k*-recognisable for every $k \ge 1$.

Proof. Suppose *H* has *m* vertices. For a distinctly *k*-labelled graph F = (F, u), consider the set $\mathcal{H}(F)$ of (isomorphism types of) distinctly *k*-labelled graphs F' = (F', u) where F' is a subgraph of *F* such that $V(F') \supseteq \{u_1, \ldots, u_k\}$ has at most k + m vertices. Clearly, there are only finitely many possible sets $\mathcal{H}(F)$. Furthermore, if $\mathcal{H}(F_1) = \mathcal{H}(F_2)$ then $F_1 \sim_{\mathcal{F}} F_2$. Indeed, if $K \in \mathcal{D}(k)$ is such that soe($K \odot F_1$) contains *H* as a subgraph then so does soe($K \odot F_2$) since F_1 and F_2 contain the same distinctly *k*-labelled graphs on at most k + m vertices.

Analogously, one may argue that every class defined by forbidden minors is recognisable.

Courcelle [15] proved that every CMSO₂-definable graph class is *recognisable*, i.e. it is *k*-recognisable for every $k \in \mathbb{N}$. Conversely, Bojańczyk and Pilipczuk [12] proved that if a recognisable class \mathcal{F} has bounded treewidth then it is CMSO₂-definable. Furthermore, they conjecture that *k*-recognisability is a sufficient condition for a graph class of treewidth at most k - 1 to be CMSO₂-definable.

For our purposes, it suffices to weaken Definition 2.10 as follows: The equivalence relation $\sim_{\mathcal{F}}$ can be defined on $\mathcal{TW}(k)$ instead of $\mathcal{G}(k)$. Then *K* ranges over $\mathcal{TW}(k)$. We chose the definition from [15, 12] in order to be aligned with the literature.

2.6 Cai-Fürer-Immerman Graphs

We recall the following version of the classical CFI graphs [14] from [36]. Let *G* be a graph without isolated vertices and $U: V(G) \to \mathbb{Z}_2$ a function from *G* to the abelian group on two elements \mathbb{Z}_2 . For a vertex $v \in V(G)$, write $E(v) \subseteq E(G)$ for the set of edges incident to v. The graph G_U has vertices (v, S) for every $v \in V(G)$ and $S: E(v) \to \mathbb{Z}_2$ such that $\sum_{e \in E(v)} S(e) = U(v)$. Two vertices (u, S) and (v, T) are adjacent in G_U if $uv \in E(G)$ and S(uv) + T(uv) = 0. Note that $|V(G_U)| = \sum_{v \in V(G)} 2^{\deg(v)-1}$.

By [36, Lemma 3.2], if $\sum_{v \in V(G)} U(v) = \sum_{v \in V(G)} U'(v)$ for $U, U': V(G) \to \mathbb{Z}_2$ then $G_U = G_{U'}$. We may thus write G_0 and G_1 for the *even* and the *odd* CFI graph of G. We recall the following properties:

Lemma 2.13 ([36, Corollary 3.7]). Let G be a connected graph and $U: V(G) \rightarrow \mathbb{Z}_2$. Then the following are equivalent:

- 1. $G_0 \cong G_{U'}$
- 2. $\sum_{v \in V(G)} U(v) = 0$,
- 3. $hom(G, G_0) = hom(G, G_U).$

3 Decidability

As a first step, we show that the problem HOMIND(\mathcal{F}) is decidable for every *k*-recognisable graph class \mathcal{F} of treewidth at most k - 1. We do so by establishing a bound on the maximum size of a graph $F \in \mathcal{F}$ for which hom(F, G) = hom(F, H) needs to be checked in order to conclude whether $G \equiv_{\mathcal{F}} H$.

For a graph class \mathcal{F} and $\ell \in \mathbb{N}$, define the class $\mathcal{F}_{<\ell} := \{F \in \mathcal{F} \mid |V(F)| \le \ell\}$.

Theorem 3.1. Let $k \ge 1$. Let \mathcal{F} be a graph class of treewidth $\le k - 1$ with k-recognisability index C. For graphs G and H on at most n vertices,

$$G \equiv_{\mathcal{F}} H \iff G \equiv_{\mathcal{F}_{\leq f(n,k,C)}} H$$

where $f(n, k, C) \coloneqq \max\{k^{2Cn^k}, 2Cn^k\}$.

Fix throughout a graph class \mathcal{F} as in Theorem 3.1. In reminiscence of Courcelle's theorem, we let Q denote the set of equivalence classes of $\sim_{\mathcal{F}}$, as defined in Definition 2.10, and call them *states*. A state $q \in Q$ is *accepting* if for a (and equivalently, every) F in q it holds that soe $F \in \mathcal{F}$. Write $A \subseteq Q$ for the set of all accepting states.

The states are fine enough to distinguish between graphs in \mathcal{F} and those not in \mathcal{F} . Furthermore, they are preserved under series composition and gluing, which are the operations under which all graphs in $\mathcal{TW}(k)$ can be generated by Lemma 2.6.

Lemma 3.2. For $F, F', F_1, F_2, F'_1, F'_2 \in \mathcal{D}(k)$, $L \in \mathcal{D}(k, k)$, 1. if $F_1 \sim_{\mathcal{F}} F'_1$ and $F_2 \sim_{\mathcal{F}} F'_2$ then $F_1 \odot F_2 \sim_{\mathcal{F}} F'_1 \odot F'_2$, 2. if $F \sim_{\mathcal{F}} F'$ then $L \cdot F \sim_{\mathcal{F}} L \cdot F'$.

Proof. Let $K = (K, u) \in \mathcal{D}(k)$ be arbitrary. Then $\operatorname{soe}((K \odot F_1) \odot F_2) \in \mathcal{F} \Leftrightarrow \operatorname{soe}((K \odot F_1) \odot F'_2) \in \mathcal{F} \Leftrightarrow \operatorname{soe}(K \odot F'_1 \odot F'_2) \in \mathcal{F}$.

For a (k,k)-bilabelled graph L = (L, u, v), write $L^* := (L, v, u)$ for the (k,k)-bilabelled graph obtained by swapping the in- and out-labels. Then soe $(K \odot (L \cdot F)) = \text{soe}((L^* \cdot K) \odot F)$. Thus the second claim follows from the first.

The key observation is that since $\sim_{\mathcal{F}}$ is preserved under these operations (Lemma 3.2) we can keep track of homomorphism counts of the graphs in each of the states using finite-dimensional vector spaces.

Suppose wlog that V(G) and V(H) are disjoint. To every state $q \in Q$, we associate vector spaces $S_d(q) \subseteq \mathbb{R}^{V(G)^k \cup V(H)^k}$ for $d \ge 1$. Recall that for a distinctly *k*-labelled graph $F \in \mathcal{D}(k)$, the vectors $F_G \in \mathbb{R}^{V(G)^k}$ and $F_H \in \mathbb{R}^{V(H)^k}$ are the homomorphism tensors of F w.r.t. G and H. Let $F_G \oplus F_H \coloneqq \begin{pmatrix} F_G \\ F_H \end{pmatrix} \in \mathbb{R}^{V(G)^k \cup V(H)^k}$ denote the vector obtained by appending F_H to F_G and define

$$S_d(q) \coloneqq \langle \{ F_G \oplus F_H \mid F \in \mathcal{TW}_d(k) \text{ in } q \} \rangle \subseteq \mathbb{R}^{V(G)^k \cup V(H)^k}$$

i.e. $S_d(q)$ is the subspace of $\mathbb{R}^{V(G)^k \cup V(H)^k}$ spanned by the stacked homomorphism tensors $F_G \oplus F_H$ for $F \in \mathcal{TW}_d(k)$ in state q. Clearly, $S_d(q)$ is a subspace of $S_{d+1}(q)$ for every $d \ge 1$. Finally, let $S(q) := \bigcup_{d>1} S_d(q)$.

Let $\mathcal{F}_{\geq k} := \{F \in \mathcal{F} \mid |V(F)| \geq k\}$ and write $\mathbf{1}_G$, $\mathbf{1}_H$ for the vectors in $\mathbb{R}^{V(G)^k \cup V(H)^k}$ which are one on $V(G)^k$ and $V(H)^k$, respectively, and zero everywhere else. The following Lemma 3.3 describes how to recover homomorphism counts from the vectors in the S(q).

Lemma 3.3. Two graph G and H are homomorphism indistinguishable over $\mathcal{F}_{\geq k}$ if and only if for every $q \in A$ and every $v \in S(q)$ it holds that $\mathbf{1}_{G}^{T}v = \mathbf{1}_{H}^{T}v$.

Proof. For the forward direction, note that S(q) is spanned by the $F_G \oplus F_H$ where $F \in \mathcal{TW}(k)$ is in q. Let F in $q \in A$ be arbitrary. Then soe $F =: F \in \mathcal{F}_{\geq k}$ and it holds that $\mathbf{1}_G^T(F_G \oplus F_H) =$ soe $(F_G) = \text{hom}(F, G) = \text{hom}(F, H) = \mathbf{1}_H^T(F_G \oplus F_H)$. Conversely, let $F \in \mathcal{F}_{\geq k}$ be arbitrary. Since tw $F \leq k - 1$, by Lemma 2.2, there exists $u \in V(F)^k$ such that $F := (F, u) \in \mathcal{TW}(k)$. Furthermore, F belongs to some accepting $q \in Q$. Thus, $F_G \oplus F_H \in S(q)$, and hence $\text{hom}(F, G) = \mathbf{1}_G^T(F_G \oplus F_H) =$ $\mathbf{1}_H^T(F_G \oplus F_H) = \text{hom}(F, H)$.

The bound in Theorem 3.1 is essentially due to a dimension argument. Each of the spaces $S(q) \subseteq \mathbb{R}^{V(G)^k \cup V(H)^k}$ is of dimension at most $2n^k$. Thus, the following Lemma 3.4 yields that $S_d(q) = S(q)$ for $d := 2Cn^k$ and all $q \in Q$.

Lemma 3.4. If $d \ge 1$ is such that $S_d(q) = S_{d+1}(q)$ for all $q \in Q$ then $S_d(q) = S(q)$ for all $q \in Q$.

Proof. We argue that $S_d(q) \subseteq S_{d+i}(q)$ for all $i \geq 1$ by induction on i. The base case holds by assumption. The space $S_{d+i+1}(q)$ is spanned by the $F_G \oplus F_H$ where $F \in \mathcal{TW}_{d+i+1}(k)$ is in q. For such F, by Lemma 2.6, there exist $A \subseteq \binom{[k]}{2}$, $L \subseteq [k]$, and $F^{\ell} \in \mathcal{TW}_{d+i}(k)$ for $\ell \in L$ such that

$$F = \prod_{ij \in A} A^{ij} \cdot \bigotimes_{\ell \in L} J^{\ell} F^{\ell}.$$

Let q_{ℓ} denote the state of F^{ℓ} . By assumption, there exist $K^{\ell m} \in \mathcal{TW}_d(k)$ in state q_{ℓ} and $\alpha_m \in \mathbb{R}$ such that $F_G^{\ell} \oplus F_H^{\ell} = \sum \alpha_m K_G^{\ell m} \oplus K_H^{\ell m}$. By Lemma 3.2,

$$F \sim_{\mathcal{F}} \prod_{ij \in A} A^{ij} \cdot \bigotimes_{\ell \in L} J^{\ell} K^{\ell m}$$

for all *m*. Thus, $F_G \oplus F_H$ can be written as linear combination of vectors in $S_{d+i}(q) \subseteq S_d(q)$, by induction.

This concludes the preparations for the proof of Theorem 3.1.

Proof of Theorem 3.1. It suffices to prove the backward implication. Since $k \leq k^{2Cn^k}$, it suffices to show that $G \equiv_{\mathcal{F}_{\geq k}} H$ by verifying the condition in Lemma 3.3. By Lemma 3.4, $S_d(q) = S(q)$ for $d := 2Cn^k$ and all $q \in Q$. Hence, S(q) is spanned by the $F_G \oplus F_H$ where $F \in \mathcal{TW}_d(k)$ is in state q. By Lemma 2.5, these graphs has at most max $\{k^d, d\} = \max\{k^{2Cn^k}, 2Cn^k\}$ vertices. Thus, $\mathbf{1}_G^T(F_G \oplus F_H) = \hom(\operatorname{soe} F, G) = \hom(\operatorname{soe} F, H) = \mathbf{1}_H^T(F_G \oplus F_H)$, as desired.

Finally, we adapt the techniques developed above to prove the following analogue of Theorem 3.1 for graph classes of bounded pathwidth:

Theorem 3.5. Let $k \ge 1$. Let \mathcal{F} be a graph class of pathwidth $\le k - 1$ with k-recognisability index C. For graphs G and H on at most n vertices,

$$G \equiv_{\mathcal{F}} H \iff G \equiv_{\mathcal{F}_{\leq f(n,k,C)}} H$$

where $f(n, k, C) := 2Cn^k + k - 1$.

Proof. We sketch how the proof of Theorem 3.1 needs to be adapted. Define $S_d(q)$ and S(q) as above with $\mathcal{PW}_d(k)$ instead of $\mathcal{TW}_d(k)$, cf. Section 2.3.

By Lemma 2.9, Observing that for every $F \in \mathcal{PW}_{d+1}(k)$ there exists $A \subseteq \binom{[k]}{2}$, $\ell \in [k]$, and $F' \in \mathcal{PW}_d(k)$ such that $F = AJ^{\ell}F'$ where $A := \prod_{ij \in A} A^{ij}$, Lemma 3.4 follows analogously. Thus, $S_d(q) = S(q)$ for all $q \in Q$ when $d := 2Cn^k$. By Lemma 2.8, this space is spanned by homomorphism tensors of graphs of size at most $2Cn^k + k - 1$. The statement follows as in Theorem 3.1.

Given Theorems 3.1 and 3.5, we suggest to consider the following general question: For a graph class \mathcal{F} , is there a function $f: \mathbb{N} \to \mathbb{N}$ such that $G \equiv_{\mathcal{F}} H$ if and only if $G \equiv_{\mathcal{F}_{\leq f(n)}} H$ for all graphs G and H on at most n vertices? If such an f exists, can be computed, and if membership in \mathcal{F} is decidable then HomIND(\mathcal{F}) is decidable.

Theorems 3.1 and 3.5 give such functions for every recognisable graph class of bounded treewidth. By [30], for the class \mathcal{G} of all graphs, f can be taken to be the identity $n \mapsto n$. By [32], there exists no such function for the class of all planar graphs \mathcal{P} which is computable.

4 Modular Homomorphism Indistinguishability in Polynomial Time

The insight that yielded Theorem 3.1 is that the spaces S(q) have polynomial dimension. In this section, we strengthen this result by showing that bases B(q) for the spaces S(q) can be efficiently computed. A technical difficulty arising here is that the numbers produced in the process can be of doubly exponential magnitude. In order to overcome this problem, we first consider the following problem:

MODHOMIND(\mathcal{F}) INPUT: Graphs *G* and *H*, a prime *p* in binary QUESTION: Are *G* and *H* homomorphism indistinguishable over \mathcal{F} modulo *p*?

It is easy to see that Lemmas 3.3 and 3.4 also hold when constructing the vector spaces over the finite field \mathbb{F}_p . Doing this has the advantage that all arithmetic operations can be carried out in $(\log p)^{O(1)}$. We prove the following:

Theorem 4.1. Let $k \ge 1$. If \mathcal{F} is a k-recognisable graph class of treewidth $\le k - 1$ then ModHomInd(\mathcal{F}) is in polynomial time.

For later reference, we recall the data describing the graph class \mathcal{F} which the algorithm utilises. Recall Q the set of equivalence classes (*states*) of $\sim_{\mathcal{F}}$ and $A \subseteq Q$ the set of accepting states from Section 3. Lemma 3.2 asserts that the operations generating $\mathcal{TW}(k)$ can be regarded as operations on the equivalence classes of $\sim_{\mathcal{F}}$. The algorithm is provided with a table encoding how each of the operation acts on the states.

Write $\pi: \mathcal{TW}(k) \to Q$ for the map that associates an $F \in \mathcal{TW}(k)$ to its state $q \in Q$. Write q_0 for the state of $\mathbf{1} \in \mathcal{TW}(k)$. Furthermore, write $g: Q \times Q \to Q$ and $b_B: Q \to Q$ for every $B \in \mathcal{B}(k)$ such that

$$g(\pi(\mathbf{F}), \pi(\mathbf{F}')) = \pi(\mathbf{F} \odot \mathbf{F}'), \tag{1}$$

$$b_{\boldsymbol{B}}(\boldsymbol{\pi}(\boldsymbol{F})) = \boldsymbol{\pi}(\boldsymbol{B} \cdot \boldsymbol{F}). \tag{2}$$

for every $F, F' \in TW(k)$ and $B \in B(k)$. Note that Q, A, g, q_0 and the $b_B, B \in B(k)$, are finite objects, which can be hard-coded. The map π does not need to be computable and is only needed for analysing the algorithm.

Finally, for a set $B \subseteq \mathbb{F}_p^n$, write $\langle B \rangle \subseteq \mathbb{F}_p^n$ for the \mathbb{F}_p -vector space spanned by B, cf. Lines 7 and 11. Having defined all necessary notions, we can now describe Algorithm 1.

Input: graphs *G* and *H*, a prime *p* in binary.

Data: k, Q, A, q_0 , g, b_B for $B \in \mathcal{B}(k)$.

Output: whether $G \equiv_{\mathcal{F}}^{p} H$.

¹ With brute force check whether *G* and *H* are homomorphism indistinguishable over the finite graph class $\mathcal{F}_{\leq k}$ modulo *p* and reject if not;

4 repeat foreach $B \in \mathcal{B}(k)$, $q \in Q$, $v \in B(q)$ do 5 $w \leftarrow (\boldsymbol{B}_{G} \oplus \boldsymbol{B}_{H}) v \coloneqq \begin{pmatrix} \boldsymbol{B}_{G} & 0 \\ 0 & \boldsymbol{B}_{H} \end{pmatrix} v;$ 6 if $w \notin \langle B(b_{\boldsymbol{B}}(q)) \rangle$ then 7 add w to $B(b_B(q))$; 8 foreach $q_1, q_2 \in Q, v_1 \in B(q_1), v_2 \in B(q_2)$ do 9 $w \leftarrow v_1 \odot v_2;$ 10 if $w \notin \langle B(g(q_1, q_2)) \rangle$ then 11 add *w* to $B(g(q_1, q_2))$; 12 **13 until** none of the B(q), $q \in Q$, are updated; **14** if $\mathbf{1}_G^T v = \mathbf{1}_H^T v$ for all $q \in A$ and $v \in B(q)$ then accept; 15 16 else reject; 17

Algorithm 1: MODHOMIND(\mathcal{F}) for *k*-recognisable \mathcal{F} of treewidth $\leq k - 1$.

Write $n := \max\{|V(G)|, |V(H)|\}$ and C := |Q|. The runtime of Algorithm 1 can be analysed as follows:

Lemma 4.2. There exists a computable function f such that Algorithm 1 runs in time $f(k, C)n^{O(k)}(\log p)^{O(1)}$.

Proof. Consider the following individual runtimes:

Counting homomorphism of a graph on k vertices into a graph on n vertices, can be done in time n^k . Hence, Line 1 requires time $f(k)n^k$ for some computable f.

Throughout the execution of Algorithm 1, the vectors in each B(q), $q \in Q$, are linearly independent. Thus, $|B(q)| \leq \dim S(q) \leq 2n^k$ and $\sum_{q \in Q} |B(q)| \leq 2Cn^k$. Hence, the body of the loop in Line 4 is entered at most $2Cn^k$ many times.

The loop in Line 5 iterates over at most $k^2 \cdot C \cdot 2n^k$ many objects. Computing the vector *w* takes polynomial time in $2n^k \cdot \log p$. The same holds for checking the condition in Lines 7 and 11, e.g. via Gaussian elimination. The loop in Line 9 iterates over at most $C^2 \cdot (2n^k)^2$ many objects.

Finally, checking the condition in Line 14 takes $C \cdot 2n^k \cdot (\log p)^{O(1)}$ many steps.

The following Lemma 4.3 yields that Algorithm 1 is correct.

Lemma 4.3. When Algorithm 1 terminates, B(q) spans S(q) for all $q \in Q$.

Proof. First observe that the invariant $B(q) \subseteq S(q)$ for all $q \in Q$ is preserved throughout Algorithm 1. Indeed, for example in Line 5, since $v \in B(q) \subseteq S(q)$, it can be written as linear combination of $F_G \oplus F_H$ for $F \in TW(k)$ of state q. Because $B \cdot F$ is in state $b_B(q)$ by Equation (2), $(B_G \oplus B_H)v$ is in the span of $B_GF_G \oplus B_HF_H \in S(b_B(q))$.

Now consider the converse inclusion. The proof is by induction on the structure in Lemma 2.6. By initialisation, $\mathbf{1}_G \oplus \mathbf{1}_H$ is in the span of $B(q_0)$.

For the inductive step, suppose that $F \in \mathcal{TW}(k)$ of state q is such that $F_G \oplus F_H = \sum_{v \in B(q)} \alpha_v v$ for some coefficients $\alpha_v \in \mathbb{F}_p$. Let $B \in \mathcal{B}(k)$ and $F' := B \cdot F$. Then $(B_G \oplus B_H)v$ is in the span of $B(b_B(q))$ for all $v \in B(q)$ by the termination condition. Hence, $F'_G \oplus F'_H = \sum_{v \in B(q)} \alpha_v (B_G \oplus B_H)v$ is in the span of $B(b_B(q))$.

Let $F^1, F^2 \in \mathcal{TW}(k)$ of states q_1, q_2 be such that $F^1_G \oplus F^1_H = \sum_{v \in B(q_1)} \alpha_v v$ and $F^2_G \oplus F^2_H = \sum_{w \in B(q_2)} \beta_w w$ for some coefficients $\alpha_v, \beta_w \in \mathbb{F}_p$. Since the algorithm terminated, all $v \odot w$ for $v \in B(q_1)$ and $w \in B(q_2)$ are in the span of $B(g(q_1, q_2))$. Then $(F^1 \odot F^2)_G \oplus (F^1 \odot F^2)_H = (F^1_G \oplus F^1_H) \odot (F^2_G \oplus F^2_H) = \sum_{v \in B(q_1), w \in B(q_2)} \alpha_v \beta_w(v \odot w)$ is in the span of $B(g(q_1, q_2))$.

This concludes the preparations for the proof of Theorem 4.1:

Proof of Theorem 4.1. Lemma 4.3 implies that the conditions in Lemma 3.3 and Line 14 are equivalent. Thus, *G* and *H* are homomorphism indistinguishable over $\mathcal{F}_{\geq k}$ modulo *p* if and only if Line 14 holds. The runtime bound is given in Lemma 4.2.

5 Polynomial Time for Bounded Pathwidth

In this section, we deduce Theorem 1.3 from Theorems 3.5 and 4.1. The idea is to run Algorithm 1 for a collection of primes whose product is larger than any relevant homomorphism count and invoking the Chinese Remainder Theorem. The bound in Theorem 3.5 is tight enough for this procedure to be in polynomial time. First consider the following Lemma 5.1.

Lemma 5.1. Let $N, n \in \mathbb{N}$ be such that $N \log n \ge e^{2000}$. Let \mathcal{F} be a graph class and G and H be graphs on at most n vertices. If $G \not\equiv_{\mathcal{F}_{\le N}} H$ then there exists a prime $N \log n such that <math>G \not\equiv_{\mathcal{F}_{\le N}}^p H$.

Proof. By Fact 2.1, the product *M* of the primes $N \log n \le p < (N \log n)^2$ is at least $2^{(N \log n)^2/2} > 2^{N \log n} = n^N$. If $G \not\equiv_{\mathcal{F}_{\le N}} H$ then there exist $F \in \mathcal{F}_{\le N}$ such that $\hom(F, G) \ne \hom(F, H)$. Both numbers are non-negative and at most n^N . Hence, $\hom(F, G) \not\equiv \hom(F, H) \mod M$. By the Chinese Reminder Theorem [34, Theorem 2.10], there exists $N \log n such that <math>\hom(F, G) \not\equiv \hom(F, H) \mod p$, as desired.

We can now deduce Theorem 1.3:

Theorem 1.3. Let $k \ge 1$. If \mathcal{F} is a k-recognisable graph class of pathwidth at most k - 1 then HOMIND(\mathcal{F}) is in polynomial time.

Proof. Let *G* and *H* be graphs on at most *n* vertices. By Theorem 3.5, $G \equiv_{\mathcal{F}} H$ if and only if $G \equiv_{\mathcal{F}_{\leq N}} H$ for $N \coloneqq 2Cn^k + k - 1$. We may assume wlog that $N \log n \ge e^{2000}$. By Lemma 5.1, the latter holds if and only if $G \equiv_{\mathcal{F}_{\leq N}}^p H$ for all primes $N \log n . Moreover, <math>G \equiv_{\mathcal{F}} H$ implies $G \equiv_{\mathcal{F}}^p H$, which implies $G \equiv_{\mathcal{F}_{\leq N}}^p H$, for all primes *p*. Hence, $G \equiv_{\mathcal{F}} H$ if and only if $G \equiv_{\mathcal{F}}^p H$ for all primes $N \log n . Thus, <math>G \equiv_{\mathcal{F}} H$ can be checked by enumerating all numbers between $N \log n$ and $(N \log n)^2$ and running Algorithm 1 for every prime [3].

Similarly, Lemma 5.1 places HOMIND(\mathcal{F}) for a *k*-recognisable graph class \mathcal{F} of treewidth at most k - 1 in coNP. Indeed, by Theorem 3.1, N can be taken to be exponential in n. Thus, the prime from Lemma 5.1 is a polynomial-size certificate for $G \not\equiv_{\mathcal{F}} H$ which can be verified in polynomial time by Theorem 4.1.

6 Randomised Polynomial Time

The chance that a random prime *p* of appropriate size certifies that $G \not\equiv_F H$ as in Lemma 5.1 is very high. This observation yields Theorem 1.1 via the following Lemma 6.1:

Lemma 6.1. Let $N, n \in \mathbb{N}$ be such that $N \log n \ge e^{2000}$. Let \mathcal{F} be a graph class and G and H be graphs on at most n vertices. If $G \not\equiv_{\mathcal{F}_{\le N}} H$ then the probability that a random prime $N \log n is such that <math>G \equiv_{\mathcal{F}_{\le N}}^p H$ is at most $\frac{2}{N \log n}$.

Proof. By assumption, there exist $F \in \mathcal{F}_{\leq N}$ such that $\hom(F, G) \neq \hom(F, H)$. Both numbers are non-negative and at most n^N . Thus, $\hom(F, G) \not\equiv \hom(F, H) \mod n^N$.

By the Chinese Reminder Theorem [34, Theorem 2.10], in every set *X* of at least $\frac{N \log n}{\log(N \log n)}$ many primes $N \log n , there exists a <math>p \in X$ such that $\hom(F, G) \not\equiv \hom(F, H) \mod p$. This is because $\prod_{p \in X} p > (N \log n)^{\frac{N \log n}{\log(N \log n)}} = n^N$.

By Fact 2.1, the probability that a random prime $N \log n is such that hom($ *F*,*G* $) <math>\equiv$ hom(*F*, *H*) mod *p* is

$$\leq \frac{N\log n}{\log(N\log n)} \cdot \frac{2\log(N\log n)}{(N\log n)^2} = \frac{2}{N\log n}$$

Since $G \equiv_{\mathcal{F}}^{p} H$ implies that hom $(F, G) \equiv \text{hom}(F, H) \mod p$, the desired probability is bounded by the same value.

The algorithm that yields Theorem 1.1 can now be stated as Algorithm 2.

Theorem 1.1. Let $k \ge 1$. If \mathcal{F} is a k-recognisable graph class of treewidth at most k - 1 then HomIND(\mathcal{F}) is in coRP.

Proof. Let $N := \max\{k^{2Cn^k}, 2Cn^k\}$ be the quantity from Theorem 3.1. We may suppose that $N \log n \ge e^{2000}$. Since $\log N$ is polynomial in the input size, Algorithm 2 runs in polynomial time, requiring a polynomial-time primality test [3].

For correctness, first observe that if $G \equiv_{\mathcal{F}} H$ then Algorithm 1 always accepts. If $G \not\equiv_{\mathcal{F}} H$ then Algorithm 1 might accept incorrectly. In each iteration, the probability of not rejecting is the probability of not sampling a prime plus the probability of *p* being such that $G \equiv_{\mathcal{F}}^{p} H$. By Fact 2.1 and Lemma 6.1, it is at most

$$1 - \frac{1}{2\log(N\log n)} + \frac{2}{N\log n} \le 1 - \frac{1}{4\log(N\log n)}.$$

By [1, 4.2.30], the total probability for accepting if $G \not\equiv_F H$ is at most $e^{-1} < 1/2$.

Input: graphs *G* and *H* Output: whether $G \equiv_{\mathcal{F}} H$ $n \leftarrow \max\{|V(G)|, |V(H)|\};$ $N \leftarrow \max\{k^{2Cn^k}, 2Cn^k\};$ for $\lceil 4\log(N\log n) \rceil$ times do $\begin{vmatrix} \text{Sample a random number } N\log n$ accept;

Algorithm 2: A randomised reduction from HOMIND(\mathcal{F}) to MODHOMIND(\mathcal{F}) for *k*-recognisable graph classes \mathcal{F} of treewidth $\leq k - 1$.

7 Fixed-Parameter Tractability

In this section, we deduce Theorem 1.2 from Theorem 1.1. The challenge is to efficiently compute from the CMSO₂-sentence φ and k the data describing the graph class $\mathcal{F}_{\varphi,k}$ for Algorithm 1. That this can be done was proven by Courcelle [16].

More precisely, Courcelle proved that for every CMSO₂-sentence φ and integer k one can compute a finite automaton processing expressions which encode (tree decompositions of) graphs of bounded treewidth. It is this automaton from which the data required by Algorithm 1 can be constructed. In order to state this argument precisely with minimal technical overhead, we introduce the following syntactical counterpart of TW(k).

Write $\mathfrak{TW}(k)$ for the set of *terms* defined inductively as the following formal expressions:

1. $\mathbf{1} \in \mathcal{TW}(k)$ is a term,

2. if $t_1, t_2 \in \mathfrak{TW}(k)$ then $t_1 \odot t_2 \in \mathfrak{TW}(k)$,

3. if $t \in \mathfrak{TW}(k)$ then $\mathbf{B} \cdot t \in \mathfrak{TW}(k)$ for every $\mathbf{B} \in \mathcal{B}(k)$.

The key difference between TW(k) and TW(k) is that for elements of the former the tree decomposition satisfying Definition 2.4 is implicit. For applying Courcelle's techniques, we require this decomposition to be explicit, as in TW(k).

There is a mapping val: $\mathfrak{TW}(k) \to \mathcal{TW}(k)$ interpreting the formal expressions above as concrete distinctly *k*-labelled graphs. By Lemma 2.6, this mapping is surjective. We require the following Theorem 7.1.

Theorem 7.1 (Courcelle). *Given a* CMSO₂-sentence φ and an integer $k \in \mathbb{N}$, one can compute a finite set Q, a subset $A \subseteq Q$, an element $q_0 \in Q$, and functions $g: Q \times Q \to Q$ and $b_B: Q \to Q$ for every $B \in \mathcal{B}(k)$ such that there exists a map $\pi: \mathfrak{TW}(k) \to Q$ satisfying

1.
$$\pi(\mathbf{1}) = q_0$$

2. *for* $t \in \mathfrak{TW}(k)$ *,* soe $(\operatorname{val}(t)) \models \varphi$ *iff* $\pi(t) \in A$ *,*

3. for all $t_1, t_2 \in \mathfrak{TW}(k)$, $\pi(t_1 \odot t_2) = g(\pi(t_1), \pi(t_2))$,

4. for all $t \in \mathfrak{TW}(k)$ and $\mathbf{B} \in \mathcal{B}(k)$, $\pi(\mathbf{B} \cdot t) = b_{\mathbf{B}}(\pi(t))$.

Proof. We sketch how the theorem follows from results in [16]. By the proof of [16, Theorem 6.3], one can compute, given φ and k, a finite deterministic automaton recognising whether a so called $F_{[k]}^{\text{HR}}$ -term evaluates to a graph satisfying φ .

 $F_{[k]}^{\text{HR}}$ plays the role of $\mathfrak{TW}(k)$. It is a many-sorted signature [16, Definition 2.123] whose sorts correspond to the sources (labels, in our terminology) of sourced (distinctly labelled) graphs of bounded treewidth. The operations of $F_{[k]}^{\text{HR}}$ are gluing, dropping of labels, and renaming of labels [16, Definition 2.32]. Note that the series product, gluing, and unlabelling from Section 2.1 can be derived from these. Moreover, our graph $\mathbf{1} \in \mathcal{TW}(k)$ in Figure 1a can be derived from the constants in $F_{[k]}^{\text{HR}}$.

A finite deterministic automaton processing $F_{[k]}^{\text{HR}}$ -terms [16, Defition 3.46] comprises a finite set of states Q, a set of accepting states $A \subseteq Q$, and a transition function δ mapping (q_1, \ldots, q_ℓ, f) to qwhere $q_1, \ldots, q_\ell, q \in Q$ and $f \in F_{[k]}^{\text{HR}}$ is an ℓ -ary operation, $\ell \ge 0$. Furthermore, there is map σ that associates to every $q \in Q$ a sort, that is a subset of [k] of labels.

The automaton processes $F_{[k]}^{\text{HR}}$ -terms, which in our case are elements of $\mathfrak{TW}(k)$. In order to derive the desired objects from this automaton, we keep those states for which σ evaluates to [k]. The maps g and b_B can be computed from δ . We mark a state q as accepting if δ maps q and soe (an operation derived from those in $F_{[k]}^{\text{HR}}$) to an accepting state. The state q_0 is the state produced by δ on the 0-ary derived function **1**. The map π (which we do not require to be computable) is defined by the semantics of the automaton.

Equipped with Theorem 7.1, we prove Theorem 1.2.

Theorem 1.2. There exists a computable function $f: \mathbb{N} \to \mathbb{N}$ and a randomised algorithm for HOMIND of runtime $f(|\varphi| + k)n^{O(k)}$ for $n := \max\{|V(G)|, |V(H)|\}$ which accepts all YES-instances and accepts NO-instances with probability less than one half.

Proof. Let $\mathcal{F} \coloneqq \mathcal{F}_{\varphi,k}$. Invoking Theorem 7.1, compute Q, A, q_0 , g, and b_B for $B \in \mathcal{B}(k)$ in time only depending on φ and k. Now invoke Algorithm 2, which calls Algorithm 1.

Since the data obtained from Theorem 7.1 describes an equivalence relation $t_1 \sim t_2$ iff $\pi(t_1) = \pi(t_2)$ on $\mathfrak{TW}(k)$ rather than on $\mathcal{TW}(k)$ as in Sections 3 and 4, the definitions in these sections need to be slightly adapted.

By Theorem 7.1, the following assertions analogous to Lemma 3.2 hold: If $\pi(t_1) = \pi(t_2)$ and $\pi(t_1') = \pi(t_2')$ for $t_1, t_2, t_1', t_2' \in \mathfrak{TW}(k)$ then $\pi(t_1 \odot t_1') = g(\pi(t_1), \pi(t_1')) = g(\pi(t_2), \pi(t_2')) = \pi(t_1 \odot t_1')$. Furthermore, for $\mathbf{B} \in \mathcal{B}(k)$, $\pi(\mathbf{B} \cdot t_1) = b_{\mathbf{B}}(\pi(t_1)) = b_{\mathbf{B}}(\pi(t_2)) = \pi(\mathbf{B} \cdot t_2)$.

Define S(q) for $q \in Q$ as the \mathbb{F}_p -vector space spanned by the $F_G \oplus F_H$ where $F = \operatorname{val}(t)$ for some $t \in \mathfrak{TW}(k)$ in state q.

Then the following analogue of Lemma 3.3 holds: Two graphs *G* and *H* are homomorphism indistinguishable over $\mathcal{F}_{\geq k}$ modulo *p* if and only if $\mathbf{1}_{G}^{T}v = \mathbf{1}_{H}^{T}v$ for every $v \in S(q)$ and $q \in A$. Indeed, if $F \in \mathcal{F}_{\geq k}$ then there there exist by Theorem 7.1 a $t \in \mathfrak{TM}(k)$ such that $\operatorname{soe}(F) \cong F$ for $F := \operatorname{val}(t)$. Then $\operatorname{hom}(F, G) \equiv \mathbf{1}_{G}^{T}(F_{G} \oplus F_{H}) \mod p$. The claim follows as in Lemma 3.3.

The proof of Lemma 4.3 goes through analogously, replacing structural induction on $\mathcal{TW}(k)$ via Lemma 2.6 by structural induction on the definition of $\mathfrak{TW}(k)$. The same holds for Lemma 3.3. Finally, Lemma 4.2 gives the desired runtime.

Analogously, the following Theorem 7.2 can be derived from Theorem 1.3. The difference between the problems PWHOMIND and HOMIND is that treewidth is replaced by pathwidth.

PWHomIND INPUT: Graphs G, H, a CMSO₂-sentence φ , an integer k. PARAMETER: $|\varphi| + k$. QUESTION: Are G and H homomorphism indistinguishable over $\mathcal{F}_{\varphi,k} := \{ \text{graph } F \mid F \models \varphi \text{ and } pw F \leq k - 1 \}$? Theorem 7.2 places PWHOMIND in the parametrised complexity class XP.

Theorem 7.2. There exists a computable function $f : \mathbb{N} \to \mathbb{N}$ and a deterministic algorithm for PWHo-MIND of runtime $f(|\varphi| + k)n^{O(k)}$.

Proof. The desired algorithm can be obtained as described in Theorem 1.2 disregarding the gluing operation. By Theorem 3.5, the relevant numbers are not too large and all necessary modulo can be computed explicitly as in Theorem 1.3.

8 Lasserre in Polynomial Time

By phrasing graph isomorphism as an integer program, heuristics from integer programming can be used to attempt to solve graph isomorphism. Prominent heuristics are the Sherali–Adams linear programming hierarchy and the Lasserre semidefinite programming hierarchy. While the (approximate) feasibility of each level of these hierarchies can be decided efficiently, it is known that a linear number of levels is required to decide graph isomorphism for all graphs [5, 26, 37].

In [37], for each $t \ge 1$, feasibility of the *t*-th level of the Lasserre hierarchy was characterised as homomorphism indistinguishability relation over a graph class \mathcal{L}_t constructed ibidem. Moreover, the authors asked whether there is a polynomial-time algorithm for deciding these relations. In this section, we give a randomised algorithm for this problem which is polynomial-time for every level.

The Lasserre semidefinite program can be solved approximately in polynomial time using e.g. the ellipsoid method. How to decide *exact* feasibility is generally unknown. Since \mathcal{L}_t is a minorclosed graph class of treewidth at most 3t - 1, Theorem 1.1 immediately yields a randomised polynomial-time algorithm for each level of the hierarchy. However, it is not clear how to compute the data in Theorem 7.1 for \mathcal{L}_t given t. The following Theorem 8.1 overcomes this problem by making the dependence on the parameter t effective:

LASSERRE INPUT: Graphs *G* and *H*, an integer $t \in \mathbb{N}$. QUESTION: Is the level-*t* Lasserre relaxation for the standard integer program for $G \cong H$ feasible?

Theorem 8.1. There exists a computable function $f: \mathbb{N} \to \mathbb{N}$ and a randomised algorithm deciding LASSERRE which always runs in time $f(t)n^{O(t)}$, accepts all YES-instances and accepts NO-instances with probability less than one half.

By [37], deciding LASSERRE amounts to deciding homomorphism indistinguishability over the graph class \mathcal{L}_t defined ibidem. We recall the definition:

A (t, t)-bilabelled graph A = (A, u, v) is *atomic* if all its vertices are labelled, i.e. every $v \in V(A)$ appears among the labelled vertices $u_1, \ldots, u_t, v_1, \ldots, v_t$. Let A_t denote the set of all atomic graphs. The class \mathcal{L}_t is the closure of A_t under series composition, parallel composition with atomic graphs, and arbitrary permutations of the labels, i.e. the action of the symmetric group \mathfrak{S}_{2t} on the 2t labels.

As in Section 7, write \mathfrak{L}_t for the following inductively defined set of formal expressions. We simultaneously define a complexity measure depth: $\mathfrak{L}_t \to \mathbb{N}$ on this set:

- 1. if *A* is atomic then $A \in \mathfrak{L}_t$ and depth $A \coloneqq 1$,
- **2.** if $w \in \mathfrak{L}_t$ and A is atomic then $A \odot w \in \mathfrak{L}_t$ and depth $(A \odot w) :=$ depthw,
- 3. if $w \in \mathfrak{L}_t$ and $\sigma \in \mathfrak{S}_{2t}$ then $w^{\sigma} \in \mathfrak{L}_t$ and depth $(w^{\sigma}) := \operatorname{depth} w$,
- 4. if $w_1, w_2 \in \mathfrak{L}_t$ then $w_1 \cdot w_2 \in \mathfrak{L}_t$ and depth $(w_1 \cdot w_2) \coloneqq \max\{\operatorname{depth} w_1, \operatorname{depth} w_2\} + 1$.

Clearly, each expression $w \in \mathfrak{L}_t$ can be associated with the (t, t)-bilabelled graph val $(w) \in \mathcal{L}_t$ it encodes.

As in Section 3, we first give an upper bound on the size of the graphs whose homomorphism counts need to be considered in order to decide LASSERRE.

Theorem 8.2. For $t \ge 1$ and graphs G and H on at most n vertices,

$$G \equiv_{\mathcal{L}_t} H \iff G \equiv_{(\mathcal{L}_t) < f(nt)} H$$

where $f(n,t) \coloneqq 2t \cdot 4^{n^{2t}}$.

Towards Theorem 8.2, we make the following observations:

Lemma 8.3. Let $t \ge 1$. If $w \in \mathfrak{L}_t$ then val(w) is a bilabelled graph on at most $2t \cdot 2^{depth(w)}$ vertices.

Proof. The proof is by induction on the definition of \mathfrak{L}_t . If w is atomic than val(w) has at most 2t vertices and depth(w) = 1.

If $w = A \odot w'$ for some atomic A then $val(w) = A \odot val(w')$ has at most as many vertices as val(w') since all vertices of A are labelled. This implies the claim. The case $w = (w')^{\sigma}$ for $\sigma \in \mathfrak{S}_{2t}$ is analogous.

If $w = w_1 \cdot w_2$ then the number of vertices in val(w) is at most the number of vertices in $val(w_1)$ plus the number of vertices in $val(w_2)$. This number is by induction at most $2t \cdot (2^{\operatorname{depth} w_1} + 2^{\operatorname{depth} w_2}) \le 2t \cdot 2 \cdot 2^{(\operatorname{depth} w)-1} = 2t \cdot 2^{\operatorname{depth} w}$, as desired.

For two graphs *G* and *H* on at most *n* vertices, define S_d for $d \ge 1$ as the subspace of $\mathbb{R}^{(V(G)^t \cup V(H)^t) \times (V(G)^t \cup V(H))}$ spanned by $L_G \oplus L_H := \begin{pmatrix} L_G & 0 \\ 0 & L_H \end{pmatrix}$ where $L = \operatorname{val}(w)$ for $w \in \mathfrak{L}_t$ with depth $(w) \le d$. The dimension of $S := \bigcup_{d>1} S_d$ is at most $2n^{2t}$. Thus, by the following Lemma 8.4, $S_d = S$ for $d := 2n^{2t}$.

Lemma 8.4. If $d \ge 1$ is such that $S_d = S_{d+1}$ then $S_d = S$.

Proof. We show by induction that $S_{d+i} \subseteq S_d$ for all $i \ge 1$. The base case follows by assumption. For the inductive step, we argue by structural induction that for every $w \in \mathfrak{L}_t$ with depth $(w) \le d+i+1$ and $L := \operatorname{val}(w)$ it holds that $L_G \oplus L_H \in S_d$. If w is atomic, then this clearly holds. If $w = A \odot w'$ then by the inner induction the homomorphism tensors of $\operatorname{val}(w')$ is in S_d . The Schur product of any matrix in this space with $A_G \oplus A_H$ is in S_d by definition. Thus, the claim follows. The case $w = (w')^{\sigma}$ for $\sigma \in \mathfrak{S}_{2t}$ is analogous. If $w = w' \cdot w'$ then depth(w'), depth $(w'') < \operatorname{depth}(w) \le d+i+1$. By the outer inductive hypothesis, $S_{d+i} \subseteq S_d$. Thus, writing $L' := \operatorname{val}(w')$ and $L'' := \operatorname{val}(w'')$, it holds that $L'_G \oplus L'_H, L''_G \oplus L''_H \in S_d$. Thus, writing $L := \operatorname{val}(w)$, $L_G \oplus L_H = (L'L'')_G \oplus (L'L'')_H = (L'_G \oplus L'_H)(L''_G \oplus L''_H) \in S_{d+1} \subseteq S_d$.

This concludes the preparations for the proof of Theorem 8.2.

Proof of Theorem 8.2. By Lemma 8.4, $S_d = S$ for $d := 2n^{2t}$. The space S_d is spanned by $L_G^i \oplus L_H^i$ for some $L^i \in \mathcal{L}_t$ on at most $2t \cdot 2^d$ vertices, by Lemma 8.3. For arbitrary $F \in \mathcal{L}_t$, there exist coefficients $\alpha_i \in \mathbb{R}$ such that $F_G \oplus F_H = \sum \alpha_i L_G^i \oplus L_H^i$. Hence,

hom(soe
$$\mathbf{F}, \mathbf{G}$$
) = $\mathbf{1}_{\mathbf{G}}^{T}(\mathbf{F}_{\mathbf{G}} \oplus \mathbf{F}_{H})\mathbf{1}_{\mathbf{G}} = \sum \alpha_{i}\mathbf{1}_{\mathbf{G}}^{T}(\mathbf{L}_{\mathbf{G}}^{i} \oplus \mathbf{L}_{H}^{i})\mathbf{1}_{\mathbf{G}}$
= $\sum \alpha_{i}$ hom(soe $\mathbf{L}^{i}, \mathbf{G}$) = hom(soe \mathbf{F}, H),

as desired.

We now describe Algorithm 3 for LASSERRE and prove Theorem 8.1.

19

```
Input: graphs G and H, t \in \mathbb{N}, a prime p in binary.
Output: whether G \equiv_{\mathcal{L}_t}^p H.
B \leftarrow \{ \mathbf{A}_G \oplus \mathbf{A}_H \mid \mathbf{A} \in \mathcal{A}_t \} \subseteq \mathbb{F}_p^{(V(G)^t \cup V(H)^t) \times (V(G)^t \cup V(H)^t)}:
repeat
     foreach A \in A_t, v \in B do
           w \leftarrow (A_G \oplus A_H) \odot v;
           if w \notin \langle B \rangle then
            add w to B;
     foreach v_1, v_2 \in B do
           w \leftarrow v_1 \cdot v_2;
           if w \notin \langle B \rangle then
            add w to B;
     foreach 1 \le i < j \le 2t, v \in B do
          w \leftarrow v^{(i \ j)};
           if w \notin \langle B \rangle then
            add w to B;
until B is not updated;
if \mathbf{1}_{G}^{T} v \mathbf{1}_{G} = \mathbf{1}_{H}^{T} v \mathbf{1}_{H} for all v \in B then
     accept;
else
     reject;
                                               Algorithm 3: Modular LASSERRE.
```

Proof of Theorem 8.1. Correctness follows as in Lemma 4.3 for Algorithm 1. For the runtime, note that the main loop is entered at most $2n^{2t}$ times. The subloops are entered $4t(2t - 1)2n^{2t} + 4n^{4t}$ times. The linear algebraic operations can be performed in time polynomial in $2n^{2t} \log p$. Thus the algorithm has runtime $O(t^2n^{Ct}(\log p)^C)$ for some constant $C \ge 4$.

To close the gap between modular homomorphism indistinguishability over \mathcal{L}_t and LASSERRE, invoke Lemma 6.1 and Theorem 8.2. Algorithm 2 yields the desired randomised algorithm with $\mathcal{F} := \mathcal{L}_t$ and adjusting $N \leftarrow 2t \cdot 4^{n^{2t}}$ in the second line.

9 Lower Bounds

In this final section, we establish two hardness results for the problem HOMIND. In both cases, we show hardness for natural families of graph classes. The approaches are orthogonal in the sense that reduction yielding coNP-hardness in Theorem 1.5 is from a fixed-parameter tractable problem while the reduction yielding coW[1]-hardness in Theorem 1.4 is not polynomial time.

9.1 coNP-Hardness

We show that the following problem is coNP-hard.

WL INPUT: Graphs *G* and *H*, an integer *k* QUESTION: Are *G* and *H k*-WL indistinguishable?

By [20, 14], *k*-WL indistinguishability coincides with homomorphism indistinguishability over the class of graphs of treewidth at most *k*. Hence, WL is clearly a special case of HOMIND, i.e. with

 φ set to true. Thus, the following Theorem 1.5 shows that when disregarding the parametrisation HomIND is coNP-hard under polynomial-time many-one reductions.

Theorem 1.5. The problem of deciding given graphs G and H and an integer $k \in \mathbb{N}$ whether G and H are *k*-WL indistinguishable is coNP-hard under polynomial-time many-one reductions.

Proof. For a graph *G*, write $\Delta(G)$ for its maximum vertex degree. The following problem is NP-complete by [11, Theorem 11]:

BOUNDEDDEGREETREEWIDTH INPUT: a graph *G* with $\Delta(G) \leq 9$, an integer *k* QUESTION: Is tw *G* < *k*?

By deleting isolated vertices, we may suppose that every connected component of *G* contains at least two vertices. If *G* has multiple connected components, take one vertex from each component and connect them in a pathlike fashion. This increases the maximum degree potentially by one but makes the graph connected. The treewidth is invariant under this operation. Thus, we may suppose that *G* is connected and $\Delta(G) \leq 10$.

Given such an instance, we produce the instance (G_0, G_1, k) of WL. Here, G_0 and G_1 are the even and odd CFI graphs as defined in Section 2.6.

Then G_0 and G_1 are *k*-WL indistinguishable if and only if tw $G \ge k + 1$. Indeed, by [14, 20] and [35, Lemma 4.4], since *G* is connected, if tw $G \ge k + 1$ then G_0 and G_1 are *k*-WL indistinguishable. Conversely, if tw G < k + 1 then G_0 and G_1 are distinguished by *k*-WL since hom(G, G_0) \neq hom(G, G_1) by Lemma 2.13 and [20].

Hence, (G, k) is a YES-instance of BOUNDEDDEGREETREEWIDTH if and only if (G_0, G_1, k) is a NOinstance of WL. The graphs G_0 and G_1 are of size $\sum_{v \in V(G)} 2^{\deg(v)-1} \le 2^9 n$, which is polynomial in the input.

9.2 coW[1]-Hardness

The second hardness result concerns HOMIND as a parametrised problem. Write $\mathcal{G}_{\leq k}$ for the class of all graphs on at most *k* vertices and consider the following problem:

HomIndSize INPUT: Graphs *G* and *H*, an integer $k \ge 1$. PARAMETER: *k* QUESTION: Are *G* and *H* homomorphism indistinguishable over the class $\mathcal{G}_{\le k}$?

The problem HOMINDSIZE fixed-parameter reduces to HOMIND and also to PWHOMIND. To that end, consider the first-order formula

$$\varphi_k := \exists x_1 \dots \exists x_k \forall y \bigvee_{i=1}^k (y = x_i)$$

for $k \in \mathbb{N}$. Then, a graph models φ_k if and only if it has at most k vertices. Furthermore, $|\varphi_k| = O(k)$. Hence, transforming the instance (G, H, k) of HOMINDSIZE to the instance $(G, H, \varphi_k, k - 1)$ of HOMIND gives the desired reduction. Since $|\varphi_k| + k = O(k)$, Theorem 9.1 implies Theorem 1.4.

Theorem 9.1. HOMINDSIZE is coW[1]-hard under fpt-reductions. Unless ETH fails, there is no algorithm for HOMINDSIZE that runs in time $f(k)n^{o(k)}$ for any computable function $f : \mathbb{N} \to \mathbb{N}$.

Proof. The proof is by reduction from the parametrised clique problem CLIQUE, which is well-known to be W[1]-complete and which does not admit an $f(k)n^{o(k)}$ -time algorithm for any computable f unless ETH fails [17, Theorems 13.25, 14.21].

Let *K* denote the *k*-vertex clique and K_0 and K_1 its even and odd CFI graphs as defined in Section 2.6. We first observe that $K_0 \equiv_{\mathcal{G}_{\leq k} \setminus \{K\}} K_1$. Indeed, by [36, Theorem 3.13], for every graph *F*, hom(*F*, K_0) \neq hom(*F*, K_1) if and only if there exists a *weak oddomorphism* $h: F \to K$ as defined in [36, Definition 3.9]. By definition, a weak oddomorphism is surjective on edges and vertices, i.e. for every $uv \in E(K)$ there exists $u'v' \in E(F)$ such that h(u'v') = uv. Hence, if hom(*F*, K_0) \neq hom(*F*, K_1) then *F* has at least *k* vertices and $\binom{k}{2}$ edges. The only graph in $\mathcal{G}_{\leq k}$ matching this description is *K*.

The reduction produces given the instance (G, k) of CLIQUE the instance $(G \times K_0, G \times K_1, k)$ of HOMINDSIZE where *K* is the *k*-vertex clique and × denotes the categorical product of two graphs. This instance can be produced in fixed-parameter time. Furthermore, the parameter *k* is not affected by this reduction. For correctness, consider the following cases:

If $G \times K_0 \equiv_{\mathcal{G}_{< k}} G \times K_1$ then hom(K, G) = 0. Indeed, by assumption and [31, (5.30)],

$$\hom(K, G) \hom(K, K_0) = \hom(K, G \times K_0) = \hom(K, G \times K_1) = \hom(K, G) \hom(K, K_1)$$

However, $hom(K, K_0) \neq hom(K, K_1)$ by Lemma 2.13, and thus hom(K, G) = 0.

Conversely, it holds that $K_0 \equiv_{\mathcal{G}_{\leq k} \setminus \{K\}} K_1$ and hence also $G \times K_0 \equiv_{\mathcal{G}_{\leq k} \setminus \{K\}} G \times K_1$ by the initial observation and [31, (5.30)]. Since hom(K, G) = 0, also $G \times K_0 \equiv_{\mathcal{G}_{\leq k}} G \times K_1$.

9.3 Beyond Treewidth

Theorem 1.1 establishes that $HOMIND(\mathcal{F})$ is decidable for every recognisable graph class of bounded treewidth. It would be desirable to give a necessary criterion for a graph class \mathcal{F} to be such that $HOMIND(\mathcal{F})$ is decidable/tractable.

In this section, we note that the requirement of bounded treewidth can be relaxed when one does not aim at a polynomial-time algorithm. In the following Theorem 9.2, $\chi(F)$ denotes the chromatic number of *F*. A typical graph class to which the theorem applies is the class \mathcal{K} of all cliques.

Theorem 9.2. Let φ be a CMSO₂-sentence and \mathcal{F} the class of all graphs satisfying φ . Suppose there exists a computable non-decreasing function $g: \mathbb{N} \to \mathbb{N}$ such that tw $F \leq g(\chi(F))$ for all $F \in \mathcal{F}$. Then HOMIND (\mathcal{F}) is decidable.

Proof. Let $n := \max\{|V(G)|, |V(H)|\}$. Observe that $G \equiv_{\mathcal{F}} H$ if and only if $G \equiv_{\mathcal{F} \cap \mathcal{TW}_{g(n)}} H$. Indeed, if $F \in \mathcal{F}$ has treewidth greater than g(n) then $\chi(F) > n$. Since G and H both have chromatic number at most n, there is neither a homomorphism $F \to G$ nor $F \to H$. Now invoke Theorem 1.2 with input φ and g(n).

The class \mathcal{K} is definable in first-order logic and has constant clique-width. Thus, from a model checking perspective, it is a rather simple graph class. However, as shown in [13], HOMIND(\mathcal{K}) is C₌P-hard and thus not in polynomial time unless the polynomial hierarchy collapses. This indicates that one cannot replace Courcelle's graph algebras for bounded treewidth, which were used in this work, by his graph algebras for bounded clique-width, which Courcelle uses to prove that MSO₁-model checking is fixed-parameter tractable on classes of bounded clique-width.

10 Conclusion

Theorem 1.1, our central result, asserts that deciding homomorphism indistinguishable is tractable over every recognisable graph class of bounded treewidth. Thereby, we make the intuition precise

that finite-dimensional spaces of homomorphism tensors of graphs with a bounded number of labels are sufficient to efficiently capture homomorphism indistinguishability.

A reasonable next step is to combine Theorem 1.1 with a hardness result giving necessary conditions on a graph class \mathcal{F} for HomIND(\mathcal{F}) to be undecidable. We propose the following working hypothesis:

Question 10.1. *Is it true that for a proper minor-closed graph class* \mathcal{F} *the problem* HomIND(\mathcal{F}) *is decidable if and only if* \mathcal{F} *has bounded treewidth?*

Theorem 1.1 establishes the backward implication. The only known minor-closed graph class \mathcal{F} for which HomIND(\mathcal{F}) is undecidable, is the class of planar graphs, as shown by Mančinska and Roberson [32]. An affirmative answer to Question 10.1 would imply a conjecture of Roberson [36, Conjecture 5] asserting that $\equiv_{\mathcal{F}}$ is not isomorphism for every proper minor- and union-closed class \mathcal{F} . However, even though the graph classes in Question 10.1 clearly need to satisfy some condition which rules out pathological behaviours, it is not clear whether closure under taking minors is the right one [36, 39].

Towards Question 10.1, one could try to devise reductions between HOMIND(\mathcal{F}_1) and HOM-IND(\mathcal{F}_2) for distinct (minor-closed) graph classes \mathcal{F}_1 and \mathcal{F}_2 . We are not aware of any such reduction.

A final question with repercussions beyond the scope of this work concerns the parametrised hardness of deciding Weisfeiler–Leman indistinguishability. If k is a made a parameter in the problem WL from Section 9.1, can one show coW[1]-hardness or even XP-completeness, cf. [8]?

Acknowledgements I was supported by the German Research Foundation (DFG) within Research Training Group 2236/2 (UnRAVeL) and by the European Union (ERC, SymSim, 101054974).

Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Research Council Executive Agency. Neither the European Union nor the granting authority can be held responsible for them.

I would like to thank Martin Grohe and Louis Härtel for fruitful discussions and their support. In particular, I thank Martin Grohe for making me aware of Chinese remaindering.

References

- [1] Milton Abramowitz and Irene A. Stegun. *Handbook of mathematical functions: with formulas, graphs, and mathematical tables.* Dover Publications, New York, 1965.
- [2] Samson Abramsky, Tomáš Jakl, and Thomas Paine. Discrete Density Comonads and Graph Parameters. In Helle Hvid Hansen and Fabio Zanasi, editors, *Coalgebraic Methods in Computer Science*, pages 23–44, Cham, 2022. Springer International Publishing. doi:10.1007/978-3-031-10736-8_2.
- [3] Manindra Agrawal, Neeraj Kayal, and Nitin Saxena. PRIMES is in P. *Annals of Mathematics*, 160(2):781–793, September 2004. doi:10.4007/annals.2004.160.781.
- [4] Albert Atserias, Phokion G. Kolaitis, and Wei-Lin Wu. On the Expressive Power of Homomorphism Counts. In 36th Annual ACM/IEEE Symposium on Logic in Computer Science, LICS 2021, Rome, Italy, June 29 July 2, 2021, pages 1–13, 2021. doi:10.1109/LICS52264.2021.9470543.
- [5] Albert Atserias and Elitza Maneva. Sherali-Adams Relaxations and Indistinguishability in Counting Logics. In *Proceedings of the 3rd Innovations in Theoretical Computer Science Conference*,

ITCS '12, pages 367–379, New York, NY, USA, 2012. Association for Computing Machinery. doi:10.1145/2090236.2090265.

- [6] Albert Atserias, Laura Mančinska, David E. Roberson, Robert Sámal, Simone Severini, and Antonios Varvitsiotis. Quantum and non-signalling graph isomorphisms. J. Comb. Theory, Ser. B, 136:289–328, 2019. doi:10.1016/j.jctb.2018.11.002.
- [7] László Babai. Graph Isomorphism in Quasipolynomial Time [Extended Abstract]. In Proceedings of the Forty-Eighth Annual ACM Symposium on Theory of Computing, STOC '16, pages 684–697, New York, NY, USA, 2016. Association for Computing Machinery. doi:10.1145/2897518.2897542.
- [8] Christoph Berkholz. Lower Bounds for Existential Pebble Games and k-Consistency Tests. In 2012 27th Annual IEEE Symposium on Logic in Computer Science, pages 25–34, Dubrovnik, Croatia, June 2012. IEEE. URL: http://ieeexplore.ieee.org/document/6280421/, doi:10.1109/LICS.2012.14.
- [9] Christoph Berkholz, Paul S. Bonsma, and Martin Grohe. Tight Lower and Upper Bounds for the Complexity of Canonical Colour Refinement. *Theory Comput. Syst.*, 60(4):581–614, 2017. doi:10.1007/s00224-016-9686-0.
- L. Bodlaender. *k*-arboretum [10] Hans А partial of graphs with bounded Theoretical Computer Science, 209(1):1-45, December URL: treewidth. 1998. https://www.sciencedirect.com/science/article/pii/S0304397597002284, doi:10.1016/S0304-3975(97)00228-4.
- L. Bodlaender Dimitrios M. Thilikos. Treewidth [11] Hans and for graphs November chordality. Discrete Applied Mathematics, with small 79(1-3):45-61, URL: https://linkinghub.elsevier.com/retrieve/pii/S0166218X97000310, 1997. doi:10.1016/S0166-218X(97)00031-0.
- [12] Mikołaj Bojańczyk and Michał Pilipczuk. Definability equals recognizability for graphs of bounded treewidth. In *Proceedings of the 31st Annual ACM/IEEE Symposium on Logic in Computer Science*, pages 407–416, New York NY USA, July 2016. ACM. URL: https://dl.acm.org/doi/10.1145/2933575.2934508, doi:10.1145/2933575.2934508.
- [13] Jan Böker, Yijia Chen, Martin Grohe, and Gaurav Rattan. The Complexity of Homomorphism Indistinguishability. In Peter Rossmanith, Pinar Heggernes, and Joost-Pieter Katoen, editors, 44th International Symposium on Mathematical Foundations of Computer Science (MFCS 2019), volume 138 of Leibniz International Proceedings in Informatics (LIPIcs), pages 54:1-54:13, Dagstuhl, Germany, 2019. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. URL: https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.MFCS.2019.54, doi:10.4230/LIPIcs.MFCS.2019.54.
- [14] Jin-Yi Cai, Martin Fürer, and Neil Immerman. An optimal lower bound on the number of variables for graph identification. *Combinatorica*, 12(4):389–410, December 1992. doi:10.1007/BF01305232.
- [15] Bruno Courcelle. The monadic second-order logic of graphs. I. Recognizable sets of finite graphs. Information and Computation, 85(1):12-75, March 1990. URL: https://www.sciencedirect.com/science/article/pii/089054019090043H, doi:10.1016/0890-5401(90)90043-H.

- [16] Bruno Courcelle and Joost Engelfriet. *Graph Structure and Monadic Second-Order Logic: A Language-Theoretic Approach.* Cambridge University Press, USA, 1st edition, 2012.
- [17] Marek Fedor V. Fomin, Łukasz Kowalik, Daniel Lokshtanov, Cygan, Dániel Marx, Marcin Pilipczuk, Michał Pilipczuk, and Saket Saurabh. Publishing, Parameterized Algorithms. Springer International Cham, URL: https://link.springer.com/10.1007/978-3-319-21275-3, 2015. doi:10.1007/978-3-319-21275-3.
- [18] Anuj Dawar, Tomás Jakl, and Luca Reggio. Lovász-Type Theorems and Game Comonads. In 36th Annual ACM/IEEE Symposium on Logic in Computer Science, LICS 2021, Rome, Italy, June 29 July 2, 2021, pages 1–13. IEEE, 2021. doi:10.1109/LICS52264.2021.9470609.
- [19] Holger Dell, Martin Grohe, and Gaurav Rattan. Lovász Meets Weisfeiler and Leman. 45th International Colloquium on Automata, Languages, and Programming (ICALP 2018), pages 40:1-40:14, 2018. URL: http://drops.dagstuhl.de/opus/volltexte/2018/9044/, doi:10.4230/LIPICS.ICALP.2018.40.
- [20] Zdeněk Dvořák. On recognizing graphs by numbers of homomorphisms. *Journal of Graph Theory*, 64(4):330–342, August 2010. doi:10.1002/jgt.20461.
- [21] Eva Fluck, Tim Seppelt, and Gian Luca Spitzer. Going Deep and Going Wide: Counting Logic and Homomorphism Indistinguishability over Graphs of Bounded Treedepth and Treewidth. In Aniello Murano and Alexandra Silva, editors, 32nd EACSL Annual Conference on Computer Science Logic (CSL 2024), volume 288 of Leibniz International Proceedings in Informatics (LIPIcs), pages 27:1–27:17, Dagstuhl, Germany, 2024. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. URL: https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.CSL.2024.27, doi:10.4230/LIPIcs.CSL.2024.27.
- Grohe. Finite-Variable [22] Martin Equivalence in Logics Complete for is Polynomial Time. Combinatorica, 19(4):507-532, October URL: 1999. http://link.springer.com/10.1007/s004939970004, doi:10.1007/s004939970004.
- [23] Martin Grohe. Counting Bounded Tree Depth Homomorphisms. In Proceedings of the 35th Annual ACM/IEEE Symposium on Logic in Computer Science, LICS '20, pages 507–520, New York, NY, USA, 2020. Association for Computing Machinery. doi:10.1145/3373718.3394739.
- [24] Martin Grohe. The Logic of Graph Neural Networks. In 36th Annual ACM/IEEE Symposium on Logic in Computer Science, LICS 2021, Rome, Italy, June 29 - July 2, 2021, pages 1–17. IEEE, 2021. doi:10.1109/LICS52264.2021.9470677.
- [25] Martin Grohe, Moritz Lichter, Daniel Neuen, and Pascal Schweitzer. Compressing CFI Graphs and Lower Bounds for the Weisfeiler–Leman Refinements. In 64th IEEE Annual Symposium on Foundations of Computer Science, FOCS 2023, Santa Cruz, CA, USA, November 6-9, 2023, pages 798–809. IEEE, 2023. doi:10.1109/F0CS57990.2023.00052.
- [26] Martin Grohe and Martin Otto. Pebble Games and Linear Equations. The Journal of Symbolic Logic, 80(3):797-844, 2015. URL: http://www.jstor.org/stable/43864249, doi:10.1017/jsl.2015.28.

- [27] Martin Grohe, Gaurav Rattan, and Tim Seppelt. Homomorphism Tensors and Linear Equations. In Mikołaj Bojańczyk, Emanuela Merelli, and David P. Woodruff, editors, 49th International Colloquium on Automata, Languages, and Programming (ICALP 2022), volume 229 of Leibniz International Proceedings in Informatics (LIPIcs), pages 70:1–70:20, Dagstuhl, Germany, 2022. Schloss Dagstuhl Leibniz-Zentrum für Informatik. URL: https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ICALP.2022.70, doi:10.4230/LIPIcs.ICALP.2022.70.
- [28] Neil Immerman and Eric Lander. Describing Graphs: A First-Order Approach to Graph Canonization. In Alan L. Selman, editor, *Complexity Theory Retrospective: In Honor of Juris Hartmanis on the Occasion of His Sixtieth Birthday*, July 5, 1988, pages 59–81. Springer New York, New York, NY, 1990. doi:10.1007/978-1-4612-4478-3_5.
- [29] Moritz Lichter, Benedikt Pago, and Tim Seppelt. Limitations of Game Comonads for Invertible-Map Equivalence via Homomorphism Indistinguishability. In Aniello Murano and Alexandra Silva, editors, 32nd EACSL Annual Conference on Computer Science Logic (CSL 2024), volume 288 of Leibniz International Proceedings in Informatics (LIPIcs), pages 36:1–36:19, Dagstuhl, Germany, 2024. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. URL: https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.CSL.2024.36, doi:10.4230/LIPIcs.CSL.2024.36.
- [30] László Lovász. Operations with structures. *Acta Mathematica Academiae Scientiarum Hungarica*, 18(3):321–328, September 1967. doi:10.1007/BF02280291.
- [31] László Lovász. *Large networks and graph limits*. Number volume 60 in American Mathematical Society colloquium publications. American Mathematical Society, Providence, Rhode Island, 2012.
- [32] Laura Mančinska and David E. Roberson. Quantum isomorphism is equivalent to equality of homomorphism counts from planar graphs. In 2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS), pages 661–672, 2020. doi:10.1109/F0CS46700.2020.00067.
- [33] Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and Leman Go Neural: Higher-Order Graph Neural Networks. Proceedings of the AAAI Conference on Artificial Intelligence, 33:4602-4609, July 2019. URL: https://aaai.org/ojs/index.php/AAAI/article/view/4384, doi:10.1609/aaai.v33i01.33014602.
- [34] Melvyn B. Nathanson. *Elementary Methods in Number Theory*, volume 195 of *Graduate Texts in Mathematics*. Springer New York, New York, NY, 2000. doi:10.1007/b98870.
- [35] Daniel Neuen. Homomorphism-Distinguishing Closedness for Graphs of Bounded Tree-Width, April 2023. URL: http://arxiv.org/abs/2304.07011.
- [36] David E. Roberson. Oddomorphisms and homomorphism indistinguishability over graphs of bounded degree, June 2022. URL: http://arxiv.org/abs/2206.10321.
- [37] David E. Roberson and Tim Seppelt. Lasserre Hierarchy for Graph Isomorphism and Homomorphism Indistinguishability. In Kousha Etessami, Uriel Feige, and Gabriele Puppis, editors, 50th International Colloquium on Automata, Languages, and Programming (ICALP 2023), volume 261 of Leibniz International Proceedings in Informatics (LIPIcs), pages 101:1–101:18, Dagstuhl, Germany, 2023. Schloss Dagstuhl – Leibniz-Zentrum für Informatik.

URL: https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ICALP.2023.101, doi:10.4230/LIPIcs.ICALP.2023.101.

- [38] Barkley Rosser. Explicit Bounds for Some Functions of Prime Numbers. American Journal of Mathematics, 63(1):211, January 1941. URL: https://www.jstor.org/stable/2371291, doi:10.2307/2371291.
- [39] Tim Seppelt. Logical Equivalences, Homomorphism Indistinguishability, and Forbidden Minors. In Jérôme Leroux, Sylvain Lombardy, and David Peleg, editors, 48th International Symposium on Mathematical Foundations of Computer Science (MFCS 2023), volume 272 of Leibniz International Proceedings in Informatics (LIPIcs), pages 82:1–82:15, Dagstuhl, Germany, 2023. Schloss Dagstuhl Leibniz-Zentrum für Informatik. URL: https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.MFCS.2023.82.
- [40] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How Powerful are Graph Neural Networks? In International Conference on Learning Representations, 2019. URL: https://openreview.net/forum?id=ryGs6iA5Km.