Text-Based Product Matching - Semi-Supervised Clustering Approach

Alicja Martinek^{*†}, Szymon Łukasik^{*†}, Amir H. Gandomi[‡] * NASK National Research Institute, Poland [†] AGH University of Kraków, Poland [‡] University of Technology Sydney, Australia Email: alicja.martinek@nask.pl, szymon.lukasik@nask.pl, amirhossein.gandomi@uts.edu.au

Abstract—Matching identical products present in multiple product feeds constitutes a crucial element of many tasks of ecommerce, such as comparing product offerings, dynamic price optimization, and selecting the assortment personalized for the client. It corresponds to the well-known machine learning task of entity matching, with its own specificity, like omnipresent unstructured data or inaccurate and inconsistent product descriptions. This paper aims to present a new philosophy to product matching utilizing a semi-supervised clustering approach. We study the properties of this method by experimenting with the IDEC algorithm on the real-world dataset using predominantly textual features and fuzzy string matching, with more standard approaches as a point of reference. Encouraging results show that unsupervised matching, enriched with a small annotated sample of product links, could be a possible alternative to the dominant supervised strategy, requiring extensive manual data labeling.

Index Terms—product matching, semi-supervised learning, deep learning

I. INTRODUCTION

Online shopping and purchasing services via e-commerce platforms are constantly gaining popularity. It happens due to the expanding digitalization of the retail sector and the growing utilization of advanced algorithms embedded in such platforms. According to Eurostat average share of European Union-based companies making a profit from e-commerce sales grew in ten years from 14% to 19% in 2021, peaking at 20.6% in 2022 [1]. Same source reports a 20% growth in proportion of e-shoppers among all Internet users, from 55% in 2012 to 75% in 2022 [2]. Meanwhile, in the United States, the share of online sales in the total market rose from 5.1% to 15.4% between Q1 2012 and Q2 2023 [3]. In such a setting, retailers are competing with each other not only in terms of profits, but also in cutting-edge technologies which drive the numbers.

The aforementioned increase in the number of transactions generates high volumes of data. This is where artificial intelligence thrives the most. So far, machine learning – the common branch of AI – has been used in many different areas of e-commerce. The most popular include, but are not limited to: recommendation engines [4], creating targeted marketing campaigns [5], [6], purchase predictions [7], dynamic pricing [8], [9] and optimization of retailer resources [10]. A datadriven approach to e-commerce is beneficial for both sides of the deal. In the end, the customer receives a personalized and seamless experience whilst the retailer becomes more competitive amongst the other sellers.

Product matching, an instance of the common entity matching task, is one of the key exercises for retailers. Its goal is to match identical products from two different product feeds. This is not a trivial task given the nature of textual data. Product descriptions often require specialized background knowledge and can be characterized by several different modes. This all accounts for the importance of high-reliability product matching. Once completed it allows for comparisons between offerings of the same product, which can be further used for dynamic price optimization and selecting a fitted assortment for the client. Mentioned actions are means to fulfilling the ultimate goal of every company - profit maximization.

The aim of this paper is to show how product matching can be achieved with the semi-supervised clustering algorithm. Such an approach allows to exploit all benefits of the unsupervised methods. Keeping in mind that data labeling is expensive and time-consuming, it is our motivation to fully gain from widely available data and enrich it with a smaller sample of annotated data. It has been demonstrated that the described method increases the accuracy of generated clusters [11]. Our framework also includes text-mining algorithms used for feature engineering. We focus on similarity measures as they are go-to calculations for text comparison tasks. The main contribution of this paper is to present a new view on the product matching problem. We do not invent a new algorithm but try to show fresh approach to handling such a task.

The paper is structured as below. Having given the introduction, Section 2 is a comprehensive review of current solutions to the product matching task. In addition, it also describes the feature engineering process. The following Section presents a deep dive into the proposed framework, delivering the details of the algorithm implementation. Preliminary results of conducted experiments are provided and thoroughly analyzed in Section 4. Finally, Section 5 covers conclusions and perspectives for possible future improvements to the proposed solution.

II. RELATED WORK

A. Product matching

Among the problems that can be solved with machine learning algorithms, product matching task is constantly

gaining importance due to exploding amount of data from online platforms. Retailers can leverage this information to better suit their offerings.

The core of product matching lies in obtaining pairs of matching goods, based on so-called product feeds. The feeds can originate from different sources, hence discrepancies in available attributes can become an obstacle. Such differences can manifest in distinct product taxonomies, reporting prices in varied currencies, including/excluding taxes or shipping costs, or inconsistent formulation of product names. The trick lies in conscious feature engineering that takes into consideration all possible data issues, not to mention missing information.

Carefully processed data that describes pairwise relations between items of merged feeds can be used to redefine the nature of the product matching problem. At this stage, the described task becomes a binary classification exercise. The target variable in such a setting takes a value of 1 when paired products represent the same physical good, and it becomes 0 otherwise. Models used for classification tasks usually output the probability of a record belonging to the given class (in this study, meaning that the products describe the same item).

There are many approaches to solving the assignment of entity matching. Most existing solutions are based on supervised learning methods. They include and are not limited to adapting XGBoost [12], using advanced natural language processing models as BERT [13]–[16], and incorporating deep neural networks [17]–[19] or fuzzy matching [20]. There even exist attempts to incorporate Large Language Models as chatGPT in the task of entity matching [21], [22].

Another important group of methods takes advantage of various types of data available in on-line selling systems. Multi-modal approach uses both textual representation of a product as well as images of given good [23], [24]. An interesting bridge between multi-modal concept and semi-surprised methodology can be found in [25], where authors present self-training ensemble model called GREED.

The second family of algorithms represents the unsupervised style of learning. These models can be successfully used for product matching. Existing solutions include text-mining techniques, however, they are reported to be outperformed by supervised methods [26]. The biggest advantage of unsupervised learning is that it can be performed on unlabelled data. The performance-to-cost-of-labeling is an inevitable trade-off that has to be faced by researchers and practitioners. This is the motivation to use a novel approach of semi-supervised algorithms as they can overcome the aforementioned tradeoff. The concept of constrained clustering [27]–[29] is a great example of such an algorithm and it will be described further in the paper.

B. Transforming textual data into numerical features

Correct representation of data is a key factor in modeling. Textual data whilst it is comprehensible for humans cannot be understood the same way by machines. In order to overcome this obstacle, textual data has to be transformed into its numerical counterpart. There exist a variety of methods for achieving the aforementioned goal. These methods include a bag of words algorithm, TF-IDF vectorization, and generating word embeddings. Another simple yet powerful concept revolves around similarity or distance measuring, proving to be successful in product matching [30]. Examples of popular distance metrics are:

- Levenshtein distance and its Damerau-Levenshtein extension [31] - these are calculated based on the number of edits one has to make in order to transform one string into another. They are found in a wide spectrum of applications, inter alia, in spell checking and fuzzy string matching.
- Jaccard distance [32] represents a token-level distance that compares sets of tokens present in both strings.
- Euclidean (L2) and cosine distances they operate on word embeddings, which are vectors generated to map words into n-dimensional space. Such transformation allows calculating of intuitive Euclidean distance as well as magnitude-independent cosine distance.

The content of features derived from the textual data can be various and is limited only by researchers' ingenuity. The selection of features is critical as attributes describing the data, regardless of undertaken methodology, have a direct impact on the performance of the model following the *garbage in* = *garbage out* principle.

C. Clustering

Clustering is a classic example of an unsupervised learning method. It can be implemented by the standard k-means algorithm, which generates groupings based on the distances between data points and computed centroids (centers of clusters). It reassigns the cluster numbers and adjusts centroids until stopping criteria are met. Limitations of this approach do not negatively influence our solution of product matching: a number of clusters is known a priori and is equal to 2 (matching and distinct products within a pair) and all features lay within the same range of values.



Fig. 1. Example of Must Link (solid line) and Can't Link (dashed line) constraints

An extension of the clustering algorithm – constrained clustering – allows feeding links describing relationships between data in such a way that they are included in the cluster assigning process. There are two types of these links:

- 1) Must Link (ML) pairing samples belonging to the same cluster,
- 2) Can't Link (CL) defining points that should not be grouped together in one cluster.

Figure 1 presents the impact of feeding constraints into the algorithm. Note that the data point in the middle was assigned to cluster B, due to the presence of the Can't Link constraint between it and a member of a well-defined cluster A.

There are many implementations of the k-means algorithm that adopt constraints. They include COP k-means [33], MPC k-means method, and others that can be found in *conclust* package in R [34].

A more advanced proposal in the field of constrained clustering involves deep learning algorithms [28], [35]–[37]. Deep clustering solutions utilize autoencoders that learn the data representation themselves. The biggest contribution of DEC (Deep Embedded Clustering), and its improved version called IDEC, is the introduction of clustering loss. It is used during the training process to optimize the objective of assigning clusters. IDEC, as an extension, brings in additional losses that aim to include more advanced constraints in the learning phase. Those losses include instance difficulty loss, triplet loss, and global size constraint loss. Results obtained on benchmark datasets (MNIST, Fashion MNIST, Reuters) were reported to outperform other known methods [28].

D. Evaluation metrics

Appropriate measurement of model performance is as important as any other part of the machine learning pipeline. Despite accuracy being the most intuitive way of assessing the performance it often can be deceiving. It happens when the tackled problem is defined on an imbalanced dataset. It is the case in product matching where the majority of relations between products from different feeds are of "no-match" type. In such a scenario, other metrics have to be used in order to fully describe model's ability of correct classification.

One of these metrics is the F Score often referred to as the F1 Score [38]. It builds upon the concepts of precision and recall which are derived from the confusion matrix. It is expressed as follows:

$$precision = \frac{TP}{TP + FP} \tag{1}$$

$$recall = \frac{TP}{TP + FN} \tag{2}$$

$$F \ Score = 2* \frac{precision*recall}{precision+recall} = \frac{TP}{TP + \frac{1}{2}*(FP + FN)},$$
(3)

where *TP* refers to True Positives, *FP* to False Positives and *FN* to False Negatives.

Precision and recall describe quantitatively how good the model is in capturing relevant signals and how much of the captured signal is relevant. In other words, precision reflects the fraction of True Positives among all samples labeled as positive. On the other hand, recall represents how many samples were positively classified compared to all positive records.

Another metric used for evaluation in this study is strictly intended for clustering problems. Rand Index describes the similarity between two clusters [39]. It is calculated as:

$$RI = \frac{number \ of \ agreeing \ pairs}{number \ of \ all \ pairs}.$$
 (4)

It checks if pairs of samples are classified the same way as in the true labels. The value of RI ranges between 0 and 1, with 1 representing entirely matching labels.

III. PROPOSED ALGORITHM

Our approach is based on the novel philosophy that product matching could be treated as a semi-supervised task with the knowledge about product *matchings/not matchings* incorporated into the clustering constraints. Improved Deep Embedded Clustering (IDEC) is used as the constrained clustering engine.

The solution proposed in this paper will be studied in the context of the standard dataset devoted to the task of product matching. Skroutz dataset [40] contains information sourced from online shopping platforms. For this particular research, we used the "Compact Cameras" subcategory of available product classes. We decided to use only one category of items because in such a setting the problem of distinguishing the same entities is less straightforward than comparing different groups of products. Each category uses words specific to the domain, hence intragroup data should be even better in investigating the robustness of the proposed approach. On the other hand, working with one category of products resembles more the routine of small retailers, as they are often specialized in given group of products and do not want to compare their goods with all available others.

In a given dataset, a single entity is described with the following fields: title, product category, and an ID used to identify same products. Products defined in this manner are paired together via cross-join and labeled if they represent the same physical item or not. The target variable was assembled based on the equality of the aforementioned IDs. Data was sampled to be imbalanced - only 25% of 20000 generated pairs is marked as matching goods.

The textual data in order to be comprehensible to the algorithms have to be changed into numerical vectors. Features engineered for the clustering task are as follows:

- 1) Fuzzy matching based title ratio, title partial ratio, and title token set ratio [41]. Generated features utilize the Levenshtein distance algorithm.
- Distance metric Jaccard distance which measures dissimilarity between two sets. It is expressed as a ratio of intersection to the union of sets of all tokens found in two product titles.

$$Jaccard(P_1, P_2) = \frac{|P_1 \cap P_2|}{|P_1 \cup P_2|},$$
 (5)

where P_1 and P_2 correspond to sets of tokens found within the titles. Word tokenizer divides the string describing the product into tokens.

3) Comparison of numbers found in the product titles calculated in a similar fashion as Jaccard distance while taking only numbers into consideration. This feature proves to be useful due to its ability to compare product properties, model numbers, and technical details, which often are numerical.

As a result, a pair of goods is represented by the numerical vector of 5 elements.

Our approach in general defines the product matching problem as a classification task. Despite the unsupervised nature of clustering algorithms, knowing true labels does not disrupt the algorithm's work, whilst allowing us to evaluate the performance of unsupervised and semi-supervised learning approaches. The task of matching products is then reformulated as an exercise of deciding if generated pair of products refers to the same entity or not. Such an approach cancels out one of the biggest shortcomings of clustering algorithms - the requirement for users to know the number of clusters prior to the calculations. In the case of the problem being solved in this paper, the number of clusters is equal to 2.

IV. EXPERIMENTAL SETTINGS AND RESULTS

In experiments run for this research, we tested the performance of IDEC algorithm under diverging sets of constraints applied to calculations. We examined the impact of increasing the amount of Must Link and Can't Link constraints separately. The third experiment tested the influence of balance between 0-0 and 1-1 pairs in Must Link constraints. We changed only one parameter at a time in order to draw conclusions about effects directly associated with the altered setting. We ran the calculations 10 times for each set of parameters while keeping the same set of constrained pairs for those runs. Further tests included comparison with other available methods, performance on different datasets and measuring the impact of various data distributions. IDEC was run with following parameters: batch size = 256, learning rate = 0.001, activation = ReLU, input dimension = 5, encoder dimensions = [200, 400, 800], decoder dimensions = [800, 400, 200], number of epochs = 20, ML an CL penalty = 1.

We split the dataset into train and test subsets. The fraction of matching pairs was preserved in both sets. Training data included 13400 samples, whereas the test set had 6600 records.

A. Constraints impact

Using constraints in pair with clustering introduces several new parameters that can have an impact on the algorithm's performance. In this research we analyzed the significance of:

- 1) Varying the number of Must Link Constraints percentage numbers are presented with regards to the amount of matching pairs in the training dataset.
- 2) Changing the amount of Can't Link Constraints also references the number of "Ones" present in training.

Records are sampled without replacement, hence a number of Can't Link constraints cannot exceed the number of Ones.

3) Modifying the fraction of 1-1 pairs in Must Link Constraints - given that '1' means that products represent the same good and '0' denotes a lack of match within a pair there is a possibility of defining a Must Link pair as a relation of 0-0 or 1-1. This parameter changes the balance between pairs of both types.

Preceding variables were changed in given ranges (where numbers in brackets represent actual number of constraints):

- Must Link Constraints: 5% (167), 10% (335), 15% (502), 20% (670), 25% (837), 30% (1005), 40% (1340), 50% (1675), 60% (2010), whilst the amount of CL was set to 10% and the fraction of 1-1 pairs to 100%;
- Can't Link Constraints: 5%, 10%, 15%, 20%, 25%, 30%, 40%, 50%, 60%, 70% (2345), 80% (2680), 90% (3015), whilst the amount of ML was set to 50% and the fraction of 1-1 pairs to 100%;
- Shifting the fraction of 1-1 pairs: from 0% to 100% with the interval of 10 whilst ML and CL were set to 50% and 20% correspondingly.



Fig. 2. Impact of increasing the amount of Must Link Constraints

The effect that the amount of Must Link constraints has on the performance of clustering can be seen in Figure 2. Surprisingly, an increase in the amount of information about 1-1 pairs does not generate more accurate results. Furthermore, adding more constraints led to substantial elongation in the run time of the network training process.

Contrary to the ML constraints, expanding the set of Can't Link information about the pairs contributes to achieving better results. Figure 3 depicts the relationship between the metric values and the percentage of CL constraints. The lowest F Score of 0.841 was be observed for 5% of constraints, whereas the highest value of 0.908 is associated with run having 70% of them. This analysis proves that sometimes less is better. Intuition would suggest the best performance at 100%, whereas obtained numbers show that higher amounts



Fig. 3. Impact of increasing the amount of Can't Link Constraints

of information can decrease the quality of results, which is a perfect example of over-fitting. It is also important to highlight that Can't Link constraints are easier to obtain in real-world scenarios - as they could be generated automatically, without costly surveys of retail experts.



Fig. 4. Impact of increasing the amount of 1-1 pairs in Must Link Constraints

Figure 4 shows where the perfect balance between types of Must Link Constraints lies. Observation of F Score curiously shows that the best results are achieved when there are 20% of 1-1 (actually matching products constraints) pairs and 80% of 0-0 pairs. We suspect that given the imbalanced nature of the data, increasing the signal for True Positives is treated by the model as forcing the outliers to be grouped together. Then instead of guidance on how to cluster points, the model gets explicit instructions resulting in over-fitting and therefore reducing the overall performance. This hypothesis is also supported by the results of the first experiment (Figure 2) where given a constant balance between types of pairs, a higher amount of constraints (simply increasing volume of 1-1 pairs) presented to the model did not improve its quality.

B. Comparison with other methods

The experiment designed in this paper aimed to investigate the advantage of semi-supervised algorithms in product matching over the traditional unsupervised and supervised learning represented by the k-means and XGBoost methods, respectively. In addition, more modern method was used to assess the product pairs. DeepMatcher algorithm [42] implements 3 ways of solving entity matching problems: *SIF (Smooth Inverse Frequency)* which is a simple, aggregate model; *RNN* that takes sequence into consideration and *Attention* aware of both sequences and data similarity.

F Score was maximized in order to select the best threshold for DeepMatcher classification. Results selected in that manner were then compared with best runs of IDEC, k-means and XGBoost with respect to the set of constraints discovered in previous experiment.

Table I presents the results of the best runs in each category of diverging parameters. The best run was picked with respect to the F Score as it is the most descriptive of the algorithm's performance given the task being solved. It reports the average and standard deviation calculated over all runs with particular settings. Results demonstrate that enriching data with some additional information, namely constraints, leads to higher quality results. An increase of 0.07 in the F Score measurements was observed, compared to the k-means algorithm. Despite this being a relatively small improvement it can lead to a substantially significant gain in the task of finding True Positives - pairs of products that match. This effect is especially desired having in mind the real-world application of the presented framework. The amount of real data that can be analyzed with this methodology far exceeds the sample of 20000 records used in this study. In big-data problems, even the smallest upgrade goes a long way.

Analysis of XGBoost results and its mirrored IDEC runs show that Deep Clustering performs better in all of the measured scenarios. It is worth mentioning that Deep Clustering approach outperformed the k-means algorithm in every reported metric. DeepMatcher, regardless of the used model, performs worse than proposed algorithm with respect to all evaluation metrics.

To further compare k-means and IDEC algorithms Table II presents examples of product pairs that were impossible for the simple algorithm to classify correctly. Analysis of these results allows drawing the conclusion that IDEC is more versatile and robust due to its ability to operate regardless of the length of compared strings, presence of typos, or distinctive ways of presenting product parameters.

C. Other datasets

Additionally, to fully examine quality of the proposed algorithm it was run on other data. Except for "Compact Cameras" category from Skroutz dataset the mixture category of other camera related categories was generated. This dataset called *cameras all* includes Analog Cameras, Mirrorless Cameras and Digital Single Lens Reflex Cameras. As for benchmarking standards a WDC (Web Data Commons) dataset was used for

Algorithm	Experiment	Accuracy	F Score	Rand Index
k-means	1	0.924 ± 0.0001	0.848 ± 0.0004	0.859 ± 0.0002
IDEC-ML5-CL10-F100	Must Link	0.941 ± 0.0052	0.893 ± 0.0078	0.889 ± 0.0093
IDEC-ML50-CL70-F100	Can't Link	0.956 ± 0.0025	0.917 ± 0.0044	0.915 ± 0.0045
IDEC-ML50-CL20-F40	Fraction 1-1	0.956 ± 0.0011	0.917 ± 0.0023	0.916 ± 0.0020
XGBoost-ML5-CL10-F100	Must Link	0.865 ± 0.0213	0.782 ± 0.0290	0.767 ± 0.0307
XGBoost-ML50-CL70-F100	Can't Link	0.871 ± 0.0234	0.789 ± 0.0339	0.777 ± 0.0352
XGBoost-ML50-CL20-F40	Fraction 1-1	0.910 ± 0.0242	0.837 ± 0.0407	0.837 ± 0.0339
DeepMatcher-attention		0.934 ± 0.0076	0.838 ± 0.0158	0.877 ± 0.0133
DeepMatcher-rnn		0.894 ± 0.0063	0.791 ± 0.0089	0.811 ± 0.0099
DeepMatcher-sif		0.859 ± 0.0197	0.643 ± 0.0314	0.758 ± 0.0283

 TABLE I

 Comparison of K-means, IDEC, XGBoost and DeepMatcher Algorithms.

 TABLE II

 Examples of pairs misclassified by K-Means while being correctly classified by IDEC.

Product 1	Product 2	
panasonic lumix bridge camera dc fz82 eu ka269712	panasonic lumix fz82 black eos 24 dosis i eos 60 dosis choris karta	
nikon coolpix a100 purple thiki nikon doro vna974e1	compact fotografiki nikon coolpix a100 purle se 3 atokes dosis	
aquapix w1024 b 10017 adiavrochi kamera mavri 10 mp	easypix aquapix w1024 splash red	
olympus tough tg 5 digital camera	olympus tg 5 red eos 24 dosis i eos 60 dosis choris karta	TP
sony dsc hx60	sony dsc rx10 iii	TN
canon powershot sx730 hs silver	canon powershot sx620 hs red 1073c003	TN
fotografiki michani nikon coolpix a100 red	fotografiki michani olympus tg 5 red	
cybershot dsc rx100m3	sony cybershot dsc rx10 m2 se 12 atokes dosis	TN

more calculations. Data about cameras (*wdc cameras*) from Version 2.0 of Large-Scale Product Matching Dataset [43] was employed to further check robustness of the semi-supervised approach. IDEC algorithm used constraints combination ML5-CL10-F100.

TABLE III IDEC PERFORMANCE ON VARIOUS DATASETS.

Dataset	Accuracy	F Score	Rand Index
cameras	0.941 ± 0.0052	0.893 ± 0.0078	0.889 ± 0.0093
cameras all	0.899 ± 0.0296	0.815 ± 0.0375	0.820 ± 0.0452
wdc cameras	0.789 ± 0.0284	0.665 ± 0.0505	0.668 ± 0.0313

Table III shows consistent, high performance achieved on diverse data sources. A drop in metric values for *wdc cameras* data might be caused by the fact that given dataset mixes product feeds from many pages and multiple languages. In that fashion some pairs are cross lingual, which might be hard for fuzzy features to reflect in the training data.

D. Class distribution impact

Another quality assessment test touches the subject of algorithm's performance at varying data distributions. For this experiment datasets with increasing percentage of matching pairs (ones) were synthetically generated from the *cameras* data. Percentages used for these datasets were as follows: 1, 3, 5, 10, 15, 20, 25. IDEC algorithm was run with the same constraints setup as in previous experiment (ML5-CL10-F100). Figure 5 presents increasing trend for all of reported metrics. The threshold of 10% brings substantial increase of F Score value, if doubled all metrics are performing over the value of 0.8.

It is worth mentioning that even WDC Gold Standard use datasets whose percentage of positive pairs range from 37% to 48% in the training data, for classes of shoes and computers respectively. It is far from the tested and real life scenarios.



Fig. 5. Impact of increasing the amount of matching pairs in the dataset

The implementation of the tested algorithms along with the full results of this study can be found in the repository [URL undisclosed for peer-review].

V. CONCLUSION

The given paper presents a framework that can be utilized for the problem of product matching. The nature of the data and given task requires the solution to be functional with as little information as is possible. Online shopping websites often do not bear consistent information across all offerings not to mention cross-platform discrepancies. The proposed solution uses only titles of the products and derives simple text-based features which, unlike generating word embeddings, do not require high computational power.

Results obtained with the Deep Clustering approach outperform standard k-means algorithm, XGBoost method as well as deep learning based solutions. These results demonstrate that enriching data with constraints, transforming the problem from the unsupervised to the semi-supervised domain, leads to a positive outcome. An increase in F Score metric of 0.07 can have a high impact on real-world applications of such product matching concepts. More advanced tests proved presented solution to be robust and high performing on diverse datasets as well as under various class distributions.

There exist multiple ways of improving this research and extending it to examine more possibilities for boosting the model's results. We tested IDEC performance while changing only one parameter at a time, but this could be expanded to diverging at least two attributes concurrently. Another path for improvement could utilize alternative existing constrained clustering algorithms such as COP k-means or the MPC version of it. Adding more features, for example related to the spread of prices of products, can be a valuable extension of the modeling process as well.

It has to be pointed out that within the subject of product matching of online offerings datasets are countless. In the era of widely available web scrapers, there is a possibility of gathering various features at the very source of the data - the on-line selling platforms. Solutions, as well as the data volumes, are only limited by the computational costs of running algorithms and storing records. For these reasons, product matching is an important task worth further research and development.

REFERENCES

- Eurostat, "E-commerce sales," isoc_ec_eseln2 dataset, Eurostat, September 2023.
- [2] Eurostat, "E-commerce continues to grow in the eu," tech. rep., Eurostat, Spetember 2023.
- [3] Statista, "E-commerce as share of total U.S. retail sales from 1st quarter 2010 to 3rd quarter 2021," dataset, Statista, September 2023.
- [4] D. Shankar, S. Narumanchi, H. Ananya, P. Kompalli, and K. Chaudhury, "Deep learning based large scale visual recommendation and search for e-commerce," arXiv preprint arXiv:1703.02344, 2017.
- [5] R. Gubela, A. Bequé, S. Lessmann, and F. Gebert, "Conversion uplift in e-commerce: A systematic benchmark of modeling strategies," *International Journal of Information Technology & Decision Making*, vol. 18, no. 03, pp. 747–791, 2019.
- [6] L. Zhou, "Product advertising recommendation in e-commerce based on deep learning and distributed expression," *Electronic Commerce Research*, vol. 20, no. 2, pp. 321–342, 2020.
- [7] R. Gupta and C. Pathak, "A machine learning framework for predicting purchase by online customers based on dynamic pricing," *Procedia Computer Science*, vol. 36, pp. 599–605, 2014.
- [8] Y. Narahari, C. Raju, K. Ravikumar, and S. Shah, "Dynamic pricing models for electronic business," *sadhana*, vol. 30, no. 2, pp. 231–256, 2005.
- [9] R. Maestre, J. Duque, A. Rubio, and J. Arévalo, "Reinforcement learning for fair dynamic pricing," in *Proceedings of SAI Intelligent Systems Conference*, pp. 120–135, Springer, 2018.
- [10] J. Li, T. Wang, Z. Chen, G. Luo, et al., "Machine learning algorithm generated sales prediction for inventory optimization in cross-border ecommerce," *International Journal of Frontiers in Engineering Technol*ogy, vol. 1, no. 1, 2019.

- [11] K. Sohn, D. Berthelot, C.-L. Li, Z. Zhang, N. Carlini, E. D. Cubuk, A. Kurakin, H. Zhang, and C. Raffel, "Fixmatch: Simplifying semisupervised learning with consistency and confidence," arXiv preprint arXiv:2001.07685, 2020.
- [12] S. Łukasik, A. Michałowski, P. A. Kowalski, and A. H. Gandomi, "Text-based product matching with incomplete and inconsistent items descriptions," in *International Conference on Computational Science*, pp. 92–103, Springer, 2021.
- [13] J. Tracz, P. I. Wójcik, K. Jasinska-Kobus, R. Belluzzo, R. Mroczkowski, and I. Gawlik, "Bert-based similarity learning for product matching," in *Proceedings of Workshop on Natural Language Processing in E-Commerce*, pp. 66–75, 2020.
- [14] R. Peeters, C. Bizer, and G. Glavaš, "Intermediate training of bert for product matching," *small*, vol. 745, no. 722, pp. 2–112, 2020.
 [15] R. Peeters and C. Bizer, "Supervised contrastive learning for product
- [15] R. Peeters and C. Bizer, "Supervised contrastive learning for product matching," in *Companion Proceedings of the Web Conference 2022*, ACM, apr 2022.
- [16] Y. Li, J. Li, Y. Suhara, A. Doan, and W.-C. Tan, "Deep entity matching with pre-trained language models," *Proceedings of the VLDB Endowment*, vol. 14, p. 50–60, Sept. 2020.
- [17] J. Li, Z. Dou, Y. Zhu, X. Zuo, and J.-R. Wen, "Deep cross-platform product matching in e-commerce," *Information Retrieval Journal*, vol. 23, no. 2, pp. 136–158, 2020.
- [18] A. Alabdullatif and M. Aloud, "Araprodmatch: A machine learning approach for product matching in e-commerce," *International Journal* of Computer Science & Network Security, vol. 21, no. 4, pp. 214–222, 2021.
- [19] R. Peeters and C. Bizer, "Supervised contrastive learning for product matching," arXiv preprint arXiv:2202.02098, 2022.
- [20] K. Amshakala and R. Nedunchezhian, "Using fuzzy logic for product matching," in *Computational Intelligence, Cyber Security and Computational Models* (G. S. S. Krishnan, R. Anitha, R. S. Lekshmi, M. S. Kumar, A. Bonato, and M. Graña, eds.), (New Delhi), pp. 171–179, Springer India, 2014.
- [21] R. Peeters and C. Bizer, "Entity matching using large language models," 2023.
- [22] R. Peeters and C. Bizer, "Using chatgpt for entity matching," 2023.
- [23] K. Gupte, L. Pang, H. Vuyyuri, and S. Pasumarty, "Multimodal product matching and category mapping: Text+ image based deep neural network," in 2021 IEEE International Conference on Big Data (Big Data), pp. 4500–4505, IEEE, 2021.
- [24] M. Wilke and E. Rahm, "Towards multi-modal entity resolution for product matching," in GvDB, 2021.
- [25] H. Tzaban, I. Guy, A. Greenstein-Messica, A. Dagan, L. Rokach, and B. Shapira, "Product bundle identification using semi-supervised learning," in *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '20, (New York, NY, USA), p. 791–800, Association for Computing Machinery, 2020.
- [26] A. Primpeli, R. Peeters, and C. Bizer, "The wdc training dataset and gold standard for large-scale product matching," in *Companion Proceedings* of *The 2019 World Wide Web Conference*, pp. 381–386, 2019.
- [27] M. Okabe and S. Yamada, "Clustering using boosted constrained kmeans algorithm," *Frontiers in Robotics and AI*, vol. 5, 2018.
- [28] H. Zhang, S. Basu, and I. Davidson, "A framework for deep constrained clustering-algorithms and advances," in *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 57–72, Springer, 2019.
- [29] E. Bair, "Semi-supervised clustering methods," Wiley Interdisciplinary Reviews: Computational Statistics, vol. 5, no. 5, pp. 349–361, 2013.
- [30] N. Gali, R. Mariescu-Istodor, and P. Fränti, "Similarity measures for title matching," in 2016 23rd International Conference on Pattern Recognition (ICPR), pp. 1548–1553, IEEE, 2016.
- [31] L. Yujian and L. Bo, "A normalized levenshtein distance metric," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 29, pp. 1091–1095, June 2007.
- [32] G. Ivchenko and S. Honov, "On the jaccard similarity test," *Journal of Mathematical Sciences*, vol. 88, no. 6, pp. 789–794, 1998.
- [33] K. Wagstaff, C. Cardie, S. Rogers, S. Schrödl, *et al.*, "Constrained kmeans clustering with background knowledge," in *Icml*, vol. 1, pp. 577– 584, 2001.
- [34] CRAN, "conclust: Pairwise constraints clustering," package, Apr 2022.
- [35] X. Guo, L. Gao, X. Liu, and J. Yin, "Improved deep embedded clustering with local structure preservation.," in *Ijcai*, pp. 1753–1759, 2017.

- [36] H. Zhang, T. Zhan, S. Basu, and I. Davidson, "A framework for deep constrained clustering," *Data Mining and Knowledge Discovery*, vol. 35, no. 2, pp. 593–620, 2021.
- [37] J. Xie, R. Girshick, and A. Farhadi, "Unsupervised deep embedding for clustering analysis," in *International conference on machine learning*, pp. 478–487, PMLR, 2016.
- [38] L. A. Jeni, J. F. Cohn, and F. De La Torre, "Facing imbalanced data-recommendations for the use of performance metrics," in 2013 *Humaine association conference on affective computing and intelligent interaction*, pp. 245–251, IEEE, 2013.
- [39] J. M. Santos and M. Embrechts, "On the use of the adjusted rand index as a metric for evaluating supervised classification," in *International conference on artificial neural networks*, pp. 175–184, Springer, 2009.
- [40] Kaggle, "Skroutz dataset for product matching," dataset, Apr 2022.
- [41] G. A. Rao, G. Srinivas, K. V. Rao, and P. P. Reddy, "A partial ratio and ratio based fuzzy-wuzzy procedure for characteristic mining of mathematical formulas from documents," *IJSC—ICTACT J Soft Comput*, vol. 8, no. 4, pp. 1728–1732, 2018.
- [42] S. Mudgal, H. Li, T. Rekatsinas, A. Doan, Y. Park, G. Krishnan, R. Deep, E. Arcaute, and V. Raghavendra, "Deep learning for entity matching: A design space exploration," in *Proceedings of the 2018 International Conference on Management of Data*, SIGMOD '18, (New York, NY, USA), p. 19–34, Association for Computing Machinery, 2018.
- [43] A. Primpeli, R. Peeters, and C. Bizer, "The wdc training dataset and gold standard for large-scale product matching," pp. 381–386, 05 2019.