Héctor Gramaglia

FAMAF, Facultad de Matemática, Astronomía, Física y Computación Universidad Nacional de Córdoba CIEM, Centro de Investigación y Estudios de Matemática

**Abstract:** Computational interpretations of linear logic allow static control of memory resources: the data produced by the program are endowed through its type with attributes that determine its life cycle, and guarantee safe deallocation. The use of linear types encounters limitations in practice, since linear data, in the traditional sense, do not so often appear in actual programs. Several alternatives have been proposed in the attempt to relax the condition of linearity, adding coercions to the language to allow linear objects to be temporarily aliased. In this work we propose a new alternative, whose virtue is to preserve the simplicity and elegance of the original system.

Key Phrases: Linear type systems. Functional programming languages.

### 1 Introduction

In the formulae-as-types interpretation of Girard's linear logic [7], the type of a value is not only a description of its "form", but also, in its computational interpretation, an ability to use it a certain number of times. This refinement plays a key role in advanced type systems that are developed for a variety of purposes, including static resource management and concurrent systems. A fundamental advantage of these systems, which Wadler calls "no discarding" [14], is the possibility of indicating, with an explicit program directive, when a linear data is allocated or deallocated from memory, guaranteeing that the evaluation will not be affected.

Inspired by the works of Wadler [14] and Cervesato and Pfenning [3], the extended Linear Lambda Calculus presented by Walker in [15] condenses the linear attributes into two features: the decoration with qualifiers<sup>1</sup> and the introduction of context splitting, obtaining a conceptually transparent generalization of a classic type system. Many works address the problem of weakening the notion of linearity for different specific purposes (Wadler [14]; Odersky [11]; Kobayashi [9]; Smith, Walker and Morrisett [13]; Aspinall and Hofmann [2]; Aiken, Foster, Kodumal and Terauchi [1],[6]).

The main objective of this work is to present a linear applicative language whose type system supports a relaxation of the notion of linearity to allow readonly access to linear data of a base type, but which at the same time preserves the simplicity and elegance of Walker's presentation [15].

<sup>&</sup>lt;sup>1</sup>The two qualifiers warn about the life cycle of a program data: an *unrestricted* data remains in the store supporting multiple aliasing, while a *linear* data is removed from the store after its (only) use.

To achieve our goal, we will introduce a third qualifier, which we will call the "hiding qualifier", and denote hi. The key to this addition is that it does not add a new modality for a program data, but rather is used internally to promote read-only access by relaxing context splitting, which manages the substructural properties of the system. It will only be necessary to modify the context split. As in [15], we will use an abstract machine that will make evident the main properties related to memory management.

For a complete description of the history of substructural logics and their applications to Computer Science see [15] and [5]. Several works use ideas similar to the qualifier hi. We can mention in this line Wadler's sequential let [14], the usage aspect given by Aspinally Hofmann in [2], the observer annotations of Oderskyn in [11], and the quasi linear types of Kobayashi in [9]. The qualifier hi presents similarities with the use  $\delta$  of [9], which constitutes a more general form of weakening of the linearity property. The distinctive character of our approach is that we retain the main virtue of the formulation given by Walker in [15]: substructurality is completely captured by the introduction of context splitting, as the only modification to the classical type system.

# 2 A linear applicative language

Our linear language is built from a qualified signature  $\Sigma^{q}$ , which is defined in Figure 1 from a heterogeneous signature  $\Sigma$ .

q	::=	li   un	qualifiers
ρ	::=	li   un   hi	pseudoqualifiers
В	::=	int   bool   array	base pretypes
au	::=	$(\varrho \ B,,\varrho \ B) \to q \ B$	operators types
$\Sigma^{q}$	::=	$\{(o^\tau:\tau)\ :\ (o:(B_1,,B_n)\toB)\in\Sigma,$	qualified signature
		$\tau = (\varrho_1  B_1,, \varrho_n  B_n) \to q  B \}$	
		Figura 1: Qualifiers and qualified signature	

Qualifying the base types will allow us to obtain different forms of evaluation for our language. Roughly speaking, we have three modalities for a base type  $\rho$  B (the qualifier hi will only be used for base types in the role of input). The *unrestricted* mode, represented by un B, indicates that the data can be used an unlimited number of times. The *linear* mode (li B) indicates that the data will be used once (without being hidden), and the *hidden* mode (hi B), indicates read-only use of a linear data (it is not deallocated from memory).

The abstract syntax of our language is shown in Figure 2. The abstract phrase x represents an infinite set of variables. The phrase spl e as p in e' is introduced in [15] to extract all the components of the tuple counting only one use. As usual, we allow a given variable to appear at most once in a context.

To preserve one of the invariants of linear systems we need to garantee that unrestricted data structures do not hold objects with linear types. To check this, we define the predicate q(T) by the following condition: q(T) if and only

if T = q' P and  $q \sqsubseteq q'$ . The relation  $q \sqsubseteq q'$  is reflexive, transitive, and satisfies  $Ii \sqsubseteq un$ . The extension of predicate q(T) to type contexts is immediate, as long as we previously extend it to pseudotypes. This is done in a trivial way: q(hi B) = true (refers to the fact that a hidden object has no usage restriction).

Р	::=	В	pretypes	е	::=	х	expressions
		$\langle T,,T \rangle$				$o^{\tau}(e,,e)$	
		$T\toT$				$q \ \langle e,,e\rangle$	
Т	::=	q P	types			e e	
Υ	··-=	TLAB	nseudotynes			q $\lambda x$ : T.e	
-		I   g D	pseudotypes			spl e as p i	n e
Π	::=	$[] \mid \Pi, \ x \ : \Upsilon$	type contexts			if e then e	else e
р	::=	$\langle x,,x\rangle$	patterns			$let\;x\equive\;in$	е
		F	figure 2: Syntax of the lin	iear l	anguage		

The linear type system we present below is based on the system defined in Walker in [15]. A central device of this system is the *context split*  $\Pi_1 \circ ... \circ \Pi_n = \Pi$ , a (n+1)-ary relation defined in Figure 3. For simplicity we will define the split for n = 2. The reader will have no difficulty in obtaining the definition for the general case.

$$\begin{array}{ll} \hline \Pi_1 \circ \Pi_2 = \Pi & (\varrho \neq \mathsf{li}) \\ \hline \Pi_1 \circ \Pi_2 = \Pi & (\Pi_1, \mathsf{x} : \varrho \mathsf{P}) \circ (\Pi_2, \mathsf{x} : \varrho \mathsf{P}) = \Pi, \mathsf{x} : \varrho \mathsf{P} \\ \hline \Pi_1 \circ \Pi_2 = \Pi & \Pi_1 \circ \Pi_2 = \Pi \\ \hline (\Pi_1, \mathsf{x} : \mathsf{li} \mathsf{P}) \circ \Pi_2 = \Pi, \mathsf{x} : \mathsf{li} \mathsf{P} & \Pi_1 \circ (\Pi_2, \mathsf{x} : \mathsf{li} \mathsf{P}) = \Pi, \mathsf{x} : \mathsf{li} \mathsf{P} \\ \end{array}$$

Figure 3: Context split

For convenience, we define the (0 + 1)-ary case as  $un(\Pi)^2$ .

But the context split, which is suitable for the typing of terms, is not suitable for the typing of expressions in general. By typing these, we must generate the possibility of a hidden use of a data as input of a basic operation. For this we define the *context pseudosplit*, for which we will use the  $\sqcup$  operator. Its definition coincides with the definition of the context split, except in the case of a linear base type (that is, a type of the form li B). In this case the occurrence of x : li B in the *i*-th context is preceded by occurrences of x as a hidden object. In the following rule *j* takes the values 1, ..., *n*.

$$\frac{\Pi_1 \sqcup ... \sqcup \Pi_n = \Pi}{(\Pi_1, \mathsf{x} : \mathsf{hi} \mathsf{ B}) \sqcup ... \sqcup (\Pi_{j-1}, \mathsf{x} : \mathsf{hi} \mathsf{ B}) \sqcup (\Pi_j, \mathsf{x} : \mathsf{li} \mathsf{ B}) \sqcup \Pi_{j+1} \sqcup ... = \Pi, \mathsf{x} : \mathsf{li} \mathsf{ B}}$$

To express the fact that an argument of a basic operator can be an expression of type  $q B_i$ , or a variable of pseudotype hi  $B_j$ , we introduce the *pseudotyping* 

<sup>&</sup>lt;sup>2</sup>It is relevant in the rule for  $o^{\tau}$ , when o is a constant symbol, that is  $\tau = \rho B$  (Figure 4).

*relation*  $\Pi \Vdash e : T$  as the extension of the relation  $\Pi \vdash e : T$  with the following rule:  $un(\Pi_1, \Pi_2)$  implies  $\Pi_1, x : hi B, \Pi_2 \Vdash x : hi B$ .

The rules of the linear type system are given in Figure 4.

$\begin{array}{c} un(\Pi_1)\\ un(\Pi_2)\\ \overline{\Pi_1,x:q\ B,\Pi_2\vdashx:q\ B} \end{array}$	$\tau = (\varrho_1 \ B_1,, \varrho_n \ B_n) \to q \ B$ $\frac{\Pi_i \Vdash e_i : \varrho_i \ B_i}{\Pi_1 \circ \ldots \circ \Pi_n \vdash o^{\tau}(e_1,, e_n) : q \ B}$
$ \begin{array}{l} \Pi_1 \vdash e : q \ \langle T_1,,T_n \rangle \\ \underline{\Pi_2,x_1:T_1,,x_n:T_n \vdash e':T'} \\ \overline{\Pi_1 \sqcup \Pi_2 \vdash} \\ spl \ e \ as \ \langle x_1,,x_n \rangle \ in \ e':T' \end{array} $	$ \begin{array}{c} \Pi_1 \vdash e_1 : T_1  q(T_1) \dots \\ \Pi_n \vdash e_n : T_n  q(T_n) \\ \hline \Pi_1 \sqcup \dots \sqcup \Pi_1 \vdash \\ q \ \langle e_1, \dots, e_n \rangle : q \ \langle T_1, , \dots, T_n \rangle \end{array} $
$\begin{array}{c} q(\Pi) \\ \Pi, x: T \vdash e: T' \\ \overline{\Pi \vdash q \ (\lambda x: T. \ e): q \ (T \to T')} \end{array}$	$\begin{array}{l} \Pi_1 \vdash e : q  \operatorname{bool} \\ \Pi_2 \vdash e_i : T \\ \overline{\Pi_1 \sqcup \Pi_2} \vdash if  e  then  e_1  else  e_2 : T \end{array}$
$ \begin{split} & \Pi_1 \vdash e:T \\ & \Pi_2,x:T \vdash e':T' \\ & \overline{\Pi_1 \sqcup \Pi_2 \vdash let \; x \equiv e \; in \; e':T' \end{split} $	$ \begin{split} & \Pi_0 \vdash e_0 : T \\ & \underline{\Pi_1 \vdash e_1 : T \to T'} \\ & \overline{\Pi_0 \sqcup \Pi_1 \vdash e_1 \ e_0 : T'} \end{split} $
Figure 4:	II ⊢ e : T.

Prevalues, values and store are defined in Figure 5. By o (without arguments) we denote the constants of  $\Sigma$ , that is, the function symbols of arity 0.

W	::=	0	prevalues	S	::=	[]	Stores
		$\langle x,,x\rangle$				S, x = v	
		$\lambda x$ : T.e					
v	::=	q w	values				
			Figure 5: Prevalues, values and	stor	e.		

The rules for typing the store are given in Figure 6. We must add to the rules given in [15] the rule (shi) for hidden data. The relation  $\vdash$  (S, e), which indicates that the pair formed by the store and the program are suitable to be evaluated, is also defined in Figure 6.

$$(\text{sem}) \xrightarrow{\vdash [] : []} (\text{shi}) \frac{\vdash S : \Pi \quad (v : \text{li } B) \in \Sigma^{q}}{\vdash (S, x = v) : (\Pi, x : \text{hi } B)}$$
$$(\text{sva}) \frac{\vdash S : \Pi_{1} \circ \Pi_{2} \quad \Pi_{1} \vdash v : T}{\vdash (S, x = v) : (\Pi_{2}, x : T)} \qquad \qquad \frac{\vdash S : \Pi \quad \Pi \vdash e : T}{\vdash (S, e)}$$
$$\xrightarrow{\text{Figure 6: Relations } \vdash S : \Pi \text{ and } \vdash (S, e)}$$

#### 2.1 Small-step semantic

Different ways of qualifying the operators  $o^{\tau}$ , with  $\tau = (\varrho_1 \ \mathsf{B}_1, ..., \varrho_n \ \mathsf{B}_n) \to \mathsf{q} \ \mathsf{B}$ , will give rise to various forms of evaluation, which will differ in the form of manage memory resources.

Evaluation context e[] and the context rule (cct) are defined in Figure 7.

	e[]	::=		(context hole)
			$\ddot{o}^{\tau}(x,, e[],, e)$	. ,
			q (x,,e[],,e)	
$\frac{(\mathbf{S}_0, \mathbf{e}_0) \rightarrow_{\beta} (\mathbf{S}_1, \mathbf{e}_1)}{(\mathbf{S}_0, \mathbf{e}_0) \rightarrow_{\beta} (\mathbf{S}_0, \mathbf{e}_0)}$			x e[]	
$(S_0,e[e_0])\to(S_1,e[e_1])$			if e[] then e else e	
			spl e[] as p in e	
			let $x \equiv e[]$ in e	
Figure 7:	Evalu	ation co	ntexts and contexts rule.	

To define the small-step semantics we will use the context-based semantics used in [15]. Its distinctive characteristic is the explicit management of the store S, for which we assume that no variables are repeated, and that when extending it a new variable is used, supplied by *new* S.

A sequence of the form  $x_1 \mapsto y_1, ..., x_n \mapsto y_n$  will denote a substitution in the usual way:  $x_1 \mapsto y_1$  denotes the identity map, modified in the variable  $x_1$ , where it takes the value  $y_1$ . Furthermore, if  $\delta$  is a substitution, then the modified substitution  $(\delta, x \mapsto y)$  is defined by the conditions  $(\delta, x \mapsto y) \times = y$ , and  $(\delta, x \mapsto y) = \delta z$  if  $z \neq x$ . We often will write  $\langle x_1, ..., x_n \rangle \mapsto \langle x'_1, ..., x'_n \rangle$  instead of  $x_1 \mapsto x'_1, ..., x_n \mapsto x'_n$ .

To represent memory deallocation we will use the operator  $\sim_{\varrho_1,\ldots,\varrho_n}$ , defined by the following conditions:

$$\begin{array}{rcl} \mathsf{x}=\mathsf{v},\mathsf{S}')\sim_{\mathsf{li}}\mathsf{x}&=&\mathsf{S},\mathsf{S}'\\ &\mathsf{S}\sim_{\varrho}\mathsf{x}&=&\mathsf{S}\\ &\mathsf{S}\sim_{[]}|]&=&\mathsf{S}\\ &\mathsf{S}\sim_{\varrho,\varrho\mathsf{s}}\mathsf{x},\mathsf{x}\mathsf{s}&=&(\mathsf{S}\sim_{\varrho}\mathsf{x})\sim_{\varrho\mathsf{s}}\mathsf{x}\mathsf{s}\end{array}$$

(S,

Terminal configurations will be pairs of the form (S, x). The rules of smallstep semantics are given in Figure 8. We can observe in the rule (eop) that the reading of the qualifier of each input is done from the specification  $\tau$ , and not from the store. In this way, hidden data is prevented from being deleted.

(eva)	$(S,v)  o_{eta} (S,x=v,x)$	(x = new S)					
(eop)	$(S,o^{\tau}(x_1,,x_n)) \rightarrow_{\beta}$	$(Sx_i = \varrho'_i w_i,$					
	$(S \sim_{\varrho_1,,\varrho_n} x_1,,x_n,x = o(w_1,,w_n),x)$	$\tau = (\varrho_1  B_1, \dots) \to q  B)$					
(eif)	$(S,if x then e_0 else e_1)  o_{eta} (S \sim_{q} x,e_0)$	(Sx=q  true)					
(eif)	$(S,if x then e_0 else e_1) \rightarrow_{\beta} (S \sim_{q} x,e_1)$	(Sx = q false)					
(esp)	$(S,spl\;x\;as\;p\;in\;e)  o_eta (S\sim_qx,[p\mapstop']e)$	(Sx = q p')					
(efu)	$(S,f x')\to_\beta (S\sim_qf,[x\mapstox']e)$	$(Sf = q \ \lambda x : T.e)$					
(ele)	$(S,let\;x\equivy\;in\;e)\to_\beta (S,[x\mapstoy]e),$						
	Figure 8: Evaluation Rules						

### **3** Preservation and progress

The fact of using two different splits is justified by the need to guarantee that the small-step semantics preserve typing. Indeed, suppose we use pseudosplit of contexts in the rule for  $\sigma^{\tau}$ . Then we could prove  $\vdash (x = \text{li } 3, y = \text{li } 1; x + \tau x * \sigma y)$ , with  $\tau = \langle \text{hi int}, \text{li int} \rangle \rightarrow \text{li int}$  and  $\sigma = \langle \text{li int}, \text{li int} \rangle \rightarrow \text{li int}$ . But in this case there would be no preservation (nor progress), since  $\vdash (z = \text{li } 2, ; x + \tau z)$  could not be proven. On the other hand, expressions like  $\langle x, x * \sigma y \rangle$  show the need for hi B to be a pseudotype (type that only occurs as input to an operator).

We now give some notation about contexts that we will use in this section. Given a statement  $S(\Pi)$  that refers to a generic context  $\Pi$ , we use  $S(\Pi_1 \circ ... \circ \Pi_n)$  to denote the existence of a context  $\Pi$  such that  $\Pi = \Pi_1 \circ ... \circ \Pi_n$  and  $S(\Pi)$ . We will say that the context  $\Pi_2$  is *complementary to*  $\Pi_1$  if there exists  $\Pi$  such that  $\Pi = \Pi_1 \circ \Pi_2$ . Note that for each context  $\Pi$  there exists only one context  $\Pi^{un}$  that satisfies  $\Pi = \Pi \circ \Pi^{un} = \Pi^{un} \circ \Pi$ . This context is denoted by  $\Pi^{un}$  since it is the subcontext of  $\Pi$  formed by the variables whose types  $\mathsf{T}$  satisfy  $\mathsf{un}(\mathsf{T})$ .

**Lemma** (Split) If n > 0 then:

- 1. If  $\vdash S : \Pi_1 \circ ... \circ \Pi_n$ , then there exist  $S_1, ..., S_n$  such that  $\vdash S_j : \Pi_j$ , for all j = 1, ..., n. Moreover,  $S_1, ..., S_n$  are all subsequences of S that, taken in pairs, do not have variables of linear types in common.
- 2. If  $\vdash S : \Pi_1 \sqcup ... \sqcup \Pi_n$ , then there exist  $S_1, ..., S_n$  such that  $\vdash S_j : \Pi_j$ , for all j = 1, ..., n. Moreover,  $S_1, ..., S_n$  are all subsequences of S that, taken in pairs, they do not have variables of linear types in common, except those of base type.

**Proof** The proof is by structural induction on  $\vdash S : \Pi$ , where  $\Pi = \Pi_1 \circ ... \circ \Pi_n$ . The delicate part of the argument is the case  $S = (S_0, x = v)$ ,  $\Pi = \Delta_2, x : II P$ , obtained from:

 $\frac{\vdash \mathsf{S}_0: \Delta_1 \circ \Delta_2 \quad \Delta_1 \vdash \mathsf{v}: \mathsf{li} \ \mathsf{P}}{\vdash \mathsf{S}_0, \mathsf{x} = \mathsf{v}: \Delta_2, \mathsf{x}: \mathsf{li} \ \mathsf{P}} \ .$ 

Let j such that  $\Pi_j = \Pi_j^0, x : \text{li P}$ . Then  $\Delta_2 = \Pi_1 \circ ... \circ \Pi_j^0 \circ ... \circ \Pi_n$ , and hence there exists  $\Pi'_j$  such that  $\Pi'_j = \Delta_1 \circ \Pi_j^0$  and  $\Delta_1 \circ \Delta_2 = \Pi_1 \circ ... \circ \Pi'_j \circ ... \circ \Pi_n$ , because the variables in  $\Delta_1$  with linear types cannot occur within  $\Pi_i$ , for  $i \neq j$ . Since  $\vdash \mathsf{S}_0 : \Delta_1 \circ \Delta_2$ , let  $\mathsf{S}_1, ..., \mathsf{S}_n$  be the stores given by the induction hypothesis. Take  $\mathsf{S}_1, ..., (\mathsf{S}_j, \mathsf{x} = \mathsf{v}), ..., \mathsf{S}_n$ . It can be proved that  $\vdash \mathsf{S}_j, \mathsf{x} = \mathsf{v} : \Pi_j$ , using that  $\Pi_j = \Pi_j^0, \mathsf{x} : \mathsf{li P}$  and  $\vdash \mathsf{S}_j : \Delta_1 \circ \Pi_j^0$ .  $\Box$ 

**Lemma** (Store) If  $\vdash S : \Pi, x : Ii P, \Pi_1$ , then there exists a context  $\Pi^*$  complementary to  $\Pi$  such that  $\vdash S \sim_{Ii} x : \Pi^* \circ \Pi, \Pi_1$ .

**Proof** The proof is by structural induction the derivation of  $\vdash S : \Pi, x : Ii P, \Pi_1$ . We take  $\Pi_1 = \emptyset$  as the base case, which follows since  $\vdash S \sim_{Ii} x : \Pi^* \circ \Pi$  and  $\Pi^* \vdash v : Ii P$  are the premises of the derivation of  $\vdash S : \Pi, x : Ii P$ . For the inductive step, consider the derivation:

$$\begin{array}{l} \displaystyle \displaystyle \frac{\vdash \mathsf{S},\mathsf{x}=\mathsf{v},\mathsf{S}_1:\Delta_1\circ(\Pi,\mathsf{x}:\mathsf{li}\;\mathsf{P},\Pi_1)\quad\Delta_1\vdash\mathsf{v}':\mathsf{T}}{\vdash \mathsf{S},\mathsf{x}=\mathsf{v},\mathsf{S}_1,\mathsf{x}'=\mathsf{v}':\Pi,\mathsf{x}:\mathsf{li}\;\mathsf{P},\Pi_1,\mathsf{x}':\mathsf{T}} \end{array} .$$

Let  $\overline{\Pi}, \overline{\Pi}_1$  such that  $\overline{\Pi}, x : \text{li } \mathsf{P}, \overline{\Pi}_1 = \Delta_1 \circ (\Pi, x : \text{li } \mathsf{P}, \Pi_1)$ . By the induction hypothesis, there exists  $\Pi^*$  complementary to  $\overline{\Pi}$  such that  $\vdash \mathsf{S}, \mathsf{S}_1 : \Pi^* \circ \overline{\Pi}, \overline{\Pi}_1$ . Thus  $\Pi^*$  and  $\Delta_1$  do not have linear variables in common. Then  $\Pi^* \circ \overline{\Pi}, \overline{\Pi}_1 = \Delta_1 \circ (\Pi^* \circ \Pi, \Pi_1)$ . Then  $\vdash \mathsf{S}, \mathsf{S}_1, x' = \mathsf{v}' : \Pi^* \circ \Pi, \Pi_1, x'\mathsf{T}$  follows.  $\Box$ 

**Corollary** (Store) If  $\vdash S : \Pi, x : Ii B, \Pi_1$  then  $\vdash S \sim_{Ii} x : \Pi, \Pi_1$ .

Lemma Context follows easily by structural induction. It will be key to use Lemma Split.

**Lemma** (Context) If  $\vdash S : \Pi$  and  $\Pi \vdash e[e_0] : T$ , then there exist  $S_0, \Pi_0, T_0$  such that  $\vdash S_0 : \Pi_0, S_0$  is a subsequence of S, and  $\Pi_0 \vdash e_0 : T_0$ .

Lemma (Sustitution) If

1.  $\Delta_1 \vdash \mathsf{li} \langle \mathsf{x}_1 : \mathsf{T}_1, ..., \mathsf{x}_n : \mathsf{T}_n \rangle$ 2.  $\Delta_2, \mathsf{z}_1 : \mathsf{T}_1, ..., \mathsf{z}_n : \mathsf{T}_n \vdash \mathsf{e} : \mathsf{T}$ 

= -27 - 1 + 17 + 7 - 7 + 7 + 7 + 7 + 17

then  $\Delta_1 \circ \Delta_2 \vdash [\mathsf{z}_1 \mapsto \mathsf{x}_1, ..., \mathsf{z}_n \mapsto \mathsf{x}_n]\mathsf{e} : \mathsf{T}$ 

**Proof** The proof is by structural induction on e. The delicate part of the argument deals with the binding constructors. Consider the case spl e as  $\langle w_1, ..., w_k \rangle$  in e'. Define the contexts  $\Delta_{21}, \Delta_{22}$  and the sequences  $z_{i_1}, z_{i_2}$  (subsequences of  $z_1, ..., z_n$ ) such that  $\Delta_2 = \Delta_{21} \circ \Delta_{22}$ ,

$$\mathsf{z}_1:\mathsf{T}_1,...,\mathsf{z}_n:\mathsf{T}_n=(\mathsf{z}_{i_1}:\mathsf{T}_{i_1})_{i_1}\circ(\mathsf{z}_{i_2}:\mathsf{T}_{i_2})_{i_2}$$
 and:

$$\frac{\Delta_{21}, (\mathsf{z}_{i_1}:\mathsf{T}_{i_1})_{i_1} \vdash \mathsf{e}:\mathsf{q}\;\langle\mathsf{T}_1^\mathsf{w},...,\mathsf{T}_k^\mathsf{w}\rangle}{\Delta_{22}, (\mathsf{z}_{i_1}:\mathsf{T}_{i_2})_{i_2}, \mathsf{w}_1:\mathsf{T}_1^\mathsf{w},...,\mathsf{w}_n:\mathsf{T}_k^\mathsf{w}\vdash \mathsf{e}':\mathsf{T}_k^\mathsf{w}} \\ \frac{\Delta_{22}, \mathsf{z}_1:\mathsf{T}_1,...,\mathsf{z}_n:\mathsf{T}_n\vdash}{\Delta_{22}, \mathsf{z}_1:\mathsf{T}_1,...,\mathsf{z}_n:\mathsf{T}_n\vdash} \quad \mathsf{spl}\;\mathsf{e}\;\mathsf{as}\;\langle\mathsf{w}_1,...,\mathsf{w}_n\rangle\;\mathsf{in}\;\mathsf{e}':\mathsf{T}_k^\mathsf{w}\vdash \mathsf{e}':\mathsf{T}_k^\mathsf{w}\vdash \mathsf{w}\vdash \mathsf{e}':\mathsf{T}_k^\mathsf{w}\vdash \mathsf{e}':\mathsf{T}_k^\mathsf{w}\vdash \mathsf{w}\vdash \mathsf{e}':\mathsf{T}_k^\mathsf{w}\vdash \mathsf{w}\vdash \mathsf{w}\vdash \mathsf{e}':\mathsf{T}_k^\mathsf{w}\vdash \mathsf{w}\vdash \mathsf{w}\vdash \mathsf{v}}:\mathsf{T}_k^\mathsf{w}\vdash \mathsf{v}\to \mathsf{v}}$$

Let  $w'_j$  be a rename of  $w_j$  to avoid capture, for j = 1, ..., k. Also let  $\Delta_i^x = \{x_j : T_j : (z_j : T_j) \in \Delta_i^z\}$ , for i = 1, 2. We will use  $i_1$  (resp.  $i_2$ ) to denotes the subscripts of the variables in  $\Delta_1^x$  (resp.  $\Delta_2^x$ ). We have that

$$\Delta_2^{\mathsf{x}}, \mathsf{w}_1': \mathsf{T}_1^{\mathsf{w}}, ..., \mathsf{w}_n': \mathsf{T}_k^{\mathsf{w}} \vdash \langle ..., \mathsf{x}_{i_2}, ..., \mathsf{w}_1', ..., \mathsf{w}_k' \rangle : \langle ..., \mathsf{T}_{i_2}, ..., \mathsf{T}_1^{\mathsf{w}}, ..., \mathsf{T}_k^{\mathsf{w}} \rangle$$

By the induction hypothesis, we have that:

- (A)  $\Delta_1^{\mathsf{x}} \circ \Delta_{21} \vdash [\mathsf{z}_{i_1} \mapsto \mathsf{x}_{i_1}]\mathsf{e} : \langle \mathsf{T}_1^{\mathsf{w}}, ..., \mathsf{T}_k^{\mathsf{w}} \rangle$
- (B)  $(\Delta_2^{\mathsf{x}}, \mathsf{w}_1' : \mathsf{T}_1^{\mathsf{w}}, ..., \mathsf{w}_n' : \mathsf{T}_k^{\mathsf{w}}) \circ \Delta_{22} \vdash [\mathsf{z}_{i_2} \mapsto \mathsf{x}_{i_2}, \mathsf{w}_j \mapsto \mathsf{w}_j']\mathsf{e}' : \mathsf{T}$

Note that  $[z_j \mapsto x_j](spl e as \langle w_1, ..., w_n \rangle$  in e') is the expression:

spl  $[z_j \mapsto x_j]e$  as  $\langle w'_1, ..., w'_n \rangle$  in  $[z_j \mapsto x_j, w_j \mapsto w'_j]e'$ ,

Hence  $\Delta_1 \circ \Delta_2 \vdash [z_j \mapsto x_j]$ (spl e as  $\langle w_1, ..., w_n \rangle$  in e') : T follows from (A), (B) and the observation that  $(\Delta_2^x, w'_1 : T_1^w, ..., w'_n : T_k^w) \circ \Delta_{22} = (\Delta_2^x \circ \Delta_{22}), w'_1 : T_1^w, ..., w'_n : T_k^w$ , because the  $w'_j$ 's are fresh variables.  $\Box$ 

**Theorem** (Preservation) If  $\vdash$  (S, e) and (S, e)  $\rightarrow$  (S', e'), then  $\vdash$  (S', e').

**Proof** Let  $e = e[e_0]$ ,  $e' = e[e'_0]$ , and suppose that  $\vdash S : \Pi$  and  $\Pi \vdash e[e_0] : T$ . The proof is by induction on the context e[]. We will prove that there exist  $S', \Pi'$  such that  $\vdash S' : \Pi'$  and  $\Pi' \vdash e[e'_0] : T$ .

**Case** e[] = []. We will prove the case  $e_0 = spl \times as \langle z_1, ..., z_n \rangle$  in  $e_1$ . Let  $Sx = q \langle x_1, ..., x_n \rangle$ . We have that that:

 $(\mathsf{S},\mathsf{spl} \mathsf{\ x \ as} \ \langle \mathsf{z}_1,...,\mathsf{z}_n \rangle \text{ in } \mathsf{e}_1) \rightarrow_\beta (\mathsf{S} \sim_\mathsf{q} \mathsf{x}, [\langle \mathsf{z}_1,...,\mathsf{z}_n \rangle \mapsto \langle \mathsf{x}_1,...,\mathsf{x}_n \rangle]\mathsf{e}_1)$ 

By typing we know that  $\Pi_1 \vdash x : q \langle T_1, ..., T_n \rangle$  and  $\Pi_2, z_1 : T_1, ..., z_n : T_n \vdash e_1 :$ T, where  $\Pi = \Pi_1 \sqcup \Pi_2$ . Let  $\mathbf{e}' = [\langle z_1, ..., z_n \rangle \mapsto \langle x_1, ..., x_n \rangle]\mathbf{e}$  and  $\mathbf{S}' = \mathbf{S} \sim_q \mathbf{x}$ .

If q = un, then  $un(T_i)$  for all *i*. If we apply the Substitution Lemma by defining  $\Delta_1 = \prod_{un}$  and  $\Delta_2 = \prod$ , then we obtain:  $\prod \vdash [\langle z_1, ..., z_n \rangle \mapsto \langle x_1, ..., x_n \rangle]e : T$ . Taking  $\prod' = \prod$ , the case follows immediately.

If  $\mathbf{q} = \mathbf{li}$ , let  $\Pi = \Delta_0, \mathbf{x} : \mathbf{li} \langle \mathsf{T}_1, ..., \mathsf{T}_n \rangle, \Delta$ . By Lemma Store there exists  $\Delta_1$  complementary to  $\Delta_0$  such that  $\Delta_1 \vdash \mathbf{li} \langle \mathbf{x}_1, ..., \mathbf{x}_n \rangle : \mathbf{li} \langle \mathsf{T}_1, ..., \mathsf{T}_n \rangle$  and  $\vdash \mathsf{S} \sim_{\mathsf{li}} \mathbf{x} : \Delta_0 \circ \Delta_1, \Delta$ . Then  $\Pi_1 = \Delta_1^{\mathsf{un}}, \mathbf{x} : \langle \mathsf{T}_1, ..., \mathsf{T}_n \rangle, \Delta^{\mathsf{un}}$  and  $\Pi_2 = \Delta_0, \Delta$ . Since  $\Delta_1, \Delta^{\mathsf{un}} \vdash \mathsf{li} \langle \mathbf{x}_1, ..., \mathbf{x}_n \rangle : \mathsf{li} \langle \mathsf{T}_1, ..., \mathsf{T}_n \rangle$ , by Lemma Sustitution,  $(\Delta_1, \Delta^{\mathsf{un}}) \circ (\Delta_0, \Delta) \vdash [\langle z_1, ..., z_n \rangle \mapsto \langle \mathbf{x}_1, ..., \mathbf{x}_n \rangle] \mathbf{e}_1 : \mathsf{T}$ . Let  $\Pi' = \Delta_0 \circ \Delta_1, \Delta$ . Since  $\Pi' = (\Delta_1, \Delta^{\mathsf{un}}) \circ (\Delta_0, \Delta)$ , the case follows.

**Case**  $e[] = q \langle x_1, ..., e_k[], ..., e_n \rangle$ . If S = S' then the case follows easily.

Suppose that  $S' = S \sim_{\mathsf{li}} x$  and  $\Pi = \Delta_0, x : \mathsf{li} \mathsf{P}, \Delta$ , where  $\mathsf{P}$  is not a base type (cases split and application). First we prove that there exists  $\Pi'$  such that  $\vdash \mathsf{S}' : \Pi'$ . By Lemma Store there exists  $\Delta_1$  complementary to  $\Delta_0$  such that  $\vdash \mathsf{S}' : \Delta_0 \circ \Delta_1, \Delta$ . Then, take  $\Pi' = \Delta_0 \circ \Delta_1, \Delta$  to obtain  $\vdash \mathsf{S}' : \Pi'$ .

Finally, we prove for the case  $S' = S \sim_{i} x$  that if  $\Pi \vdash e[e_0] : T$  then  $\Pi' \vdash e[e'_0] : T$ . Since  $\Pi = \Pi_1 \sqcup ... \sqcup \Pi_n$ , by Lemma Split there exist  $S_1, ..., S_n$  such that  $\vdash S_j : \Pi_j$ , for all j = 1, ..., n. By the induction hypothesis there exist  $\Pi'_k, S'_k$  such that  $\Pi'_k \vdash e_k[e'_0] : T_k$  and  $\vdash S'_k : \Pi'_k$ . It remains to prove that  $\Pi' = \Pi_1 \sqcup ... \sqcup \Pi'_k \sqcup ... \sqcup \Pi_n$ . This fact follows from the fact that  $S_1, ..., S_n$  are subsequences of S that, taken in pairs, do not have variables of linear types in common, except those of base type.

Suppose now that  $S' = S \sim_{\varrho_1,...,\varrho_m} x_1,...,x_m, x = q' b$  and  $\Pi = \Delta_0, (x_j : \varrho_j | B_j)_j, \Delta$  (case basic operator). Without loss of generality (for a simpler notation) we can assume that  $\varrho_j = |i|$  for all j. By Corollary Store (applied m times)  $\vdash S \sim_{|i|,...,|i|} x_1,...,x_m : \Delta_0, \Delta$ . Then, take  $\Pi' = \Delta_0, \Delta, x : q' \mid B$  to obtain  $\vdash S' : \Pi'$ .

It remains to check that  $\Pi' \vdash e[e'_0]$  : T. This fact follows with similar arguments to those used for the case  $S \sim_{ii} x$ , except in the case q' = ii, in which we must to take  $S'_j = (S_j, x = ii b)$ , for j = 1, ..., k - 1. Thus we can prove that  $\Pi' = (\Pi_1, x : hi B) \sqcup ... \sqcup (\Pi_{k-1}, x : hi B) \sqcup \Pi'_k \sqcup ... \sqcup \Pi_n$ .  $\Box$ 

**Corollary** (Progress) If  $\vdash$  (S, e) and e is not a variable, then there exist S', e' such that  $(S, e) \rightarrow (S', e')$ .

**Proof** Follows lemma Context and the observation that if  $\vdash S : \Pi$ , then:

 $\Pi x = q B$  implies Sx = q b, with  $(b : B) \in \Sigma$ .

 $\Pi x = hi B \text{ implies } Sx = li b, \text{ with } (b : B) \in \Sigma.$ 

 $\begin{array}{l} \Pi x = q \ \langle T_1,...,T_n \rangle \ \mathrm{implies} \ Sx = q \ \langle x_1,...,x_n \rangle, \ \mathrm{for \ some \ variables} \ x_1,...,x_n.\\ \Pi x = q \ (T \to T') \ \mathrm{implies} \ Sx = q \ (\lambda y: T.e), \ \mathrm{for \ some} \ y,e. \ \Box \end{array}$ 

## 4 Performance of weak-linearity

We are going to show some examples of well-typed weak-linear programs that will allow us to quantify the efficiency in the use of memory resources that weak-linearity provides.

For a better readability of the program, we remove the qualifiers from each operation  $o^{\tau}$  (we just write o). In the tables *fib*, *map* and *sort* we write on the left S, e and  $\Pi$ , and on the right the signature  $\Sigma^{q}$  with its operators in order of appearance. In all cases  $\vdash$  (S, e) is verified.

To test weak-linearity in non-trivial programs, we are going to allow recursive functions by adding self-referring definitions in the store S (they need to be unrestricted). It is not necessary to change the small-step semantics, but it is necessary to add the following rule for store typing:

$$\frac{\vdash S:\Pi \quad \Pi^{un}, f: un \ (T \to T') \vdash v: un \ (T \to T')}{\vdash (S, f = v): (\Pi, f: un \ (T \to T'))}$$

We will denote by  $C_p^{\text{li}}(n)$  the maximum number of memory locations used by program p, where n is the metavariable that appears in the program. Each memory location that holds an integer or boolean data counts 1, while an array data counts according to its size. We will use  $C_p^{\text{un}}(n)$  for the cost of the unrestricted version of p (all its qualifiers are un).

In the first program fib, the identity function id is used with the sole objective of allowing a hidden use of the object w, thus ensuring that the program returns two weak-linear data. On the other hand, the variable x must be returned to guarantee linearity (x must be used). The programs fib and map are examples of algorithms in which weak-linearity allows optimal efficiency  $(C_{fib}^{\text{li}}(n)$  and  $C_{map}^{\text{li}}(n)$  are  $\mathcal{O}(1)$ , while  $C_{fib}^{\text{un}}(n)$  is  $\mathcal{O}(n)$  and  $C_{map}^{\text{un}}(n)$  is  $\mathcal{O}(n^2)$ ).

sort shows a significant efficiency in the weak-linear version, and simultaneously shows the impossibility of obtaining a weak-linear version  $\mathcal{O}(1)$ , due to the strongly non-linear use of some variables of type integer. We observe that  $C_{sort}^{\text{li}}(n)$  is  $\mathcal{O}(n)$ , while  $C_{sort}^{\text{un}}(n)$  is  $\mathcal{O}(n^3)$ .

e		7
+	0	h
1	ı	υ

	J 10				
		$\Sigma^{q}$	(=)		(hi int, li int) $\rightarrow$ li bool
S	$f = un (\lambda x : li int.$		0		li int
-	if x = 0		1	:	li int
	then $ i(x 1 1)\rangle$		1		li int
	else spl $f(x - 1)$ as $\langle x, w, v \rangle$ in li $\langle x, id v, w + v \rangle$		(-)		(li int, li int) $\rightarrow$ li int
e	f n		1	:	li int
-			id		hi int $\rightarrow$ li int
П	$f : un (li int \rightarrow li (li int, li int, li int))$		(+)		(li int, li int) $\rightarrow$ li int
		I	'n		li int

map

	ma	P			
S	$a = \text{li } \{0, 1, 2, 3, \dots, n-1\},$ $f = \text{un } (\lambda x : \text{li int. } x + 1),$ $map = \text{un } (\lambda w : \text{li } \langle \text{li array, li int, li int} \rangle.$	$\Sigma^{q}$	(+) 1	:	(li int, li int) $\rightarrow$ li int li int
	spl w as $\langle a, i, n \rangle$ in if $i = n$ then li $\langle a, i, n \rangle$		(=) ·[·]	:	(hi int, hi int) $\rightarrow$ li bool (hi array, hi int) $\rightarrow$ li int
	else let $z \equiv a[i]$ in map(li $\langle a[i \leftarrow f z], i + 1, n \rangle$ )		·[· ← ·] (+)	:	(li array, hi int, li int) $\rightarrow$ li array (li int, li int) $\rightarrow$ li int
е П	map (li $\langle \langle a, 0, n \rangle$ ) a : li array f : un (li int $\rightarrow$ li int) map :		0	:	li int
	un (li (li array, li int, li int) $\rightarrow$ li (li array, li int, li int))		n	:	li int

	sort							
S	$a = li \{n - 1,, 1, 0\},\$							
	swap = un ( $\lambda$ w : li (li array, un int, un int).	$\Sigma^{q}$	·[ · ]	:	(hi array, un int) $\rightarrow$ li int			
	splwas (a,i,j) in		·[ · ]	:	(hi array, un int) $\rightarrow$ li int			
	let $z \equiv a[i]$ in let $y \equiv a[j]$ in		$\cdot [\cdot \leftarrow \cdot]$	:	(li array, un int, li int) → li array			
	let $a \equiv a[i \leftarrow y]$ in let $a \equiv a[j \leftarrow w]$		$\cdot [\cdot \leftarrow \cdot]$	:	(li array, un int, li int) → li array			
	ins = un $(\lambda z : spl z as \langle a, i \rangle$ in		(=)	:	(un int, li int) $\rightarrow$ li bool			
	if $i = 0$ then a		0	:	li int			
	else let $j \equiv i - 1$ in		(-)	:	(un int, li int) $\rightarrow$ un int			
	if a[i] < a[j]		1	:	li int			
	then ins(li (swap (li (a, i, j)), j))		·[ · ]	:	(hi array, un int) → li int			
	else ins(li (a, j)),		(<)	:	(li int, li int) $\rightarrow$ li bool			
	sort = un $(\lambda w : spl w as \langle a, i, j \rangle$ in		·[ · ]	:	(hi array, un int) $\rightarrow$ li int			
	if $i = j$ then a		(=)	:	(un int, un int) $\rightarrow$ li bool			
	else sort(li $(ins (li \langle a, i \rangle), i + 1, j))$		(+)	:	(un int, li int) $\rightarrow$ un int			
e	$sort(li \langle a, 0, n \rangle)$		1	:	li int			
П	a : li array, swap : un (li $\langle$ li array, un int, un int $\rangle \rightarrow$ li array),		0	:	un int			
	ins : un ( $\langle li array, un int \rangle \rightarrow li array$ ),		n	:	un int			
	sort : un ( $\langle li array, un int, un int \rangle \rightarrow li array$ )							

### 5 Conclusions

In this work we present a language that supports a weakened form of linearity, while preserving the simplicity and elegance of the original linear system. We extend the language presented in [15] by introducing a qualified signature. The only modification we introduce to this linear system is to add the qualifier hi, which allows read-only access to a base linear data, and introduce the pseudosplit of contexts. We only use the traditional split for basic operators. The key is that read-only access to a base linear data is only performed when it appears as a hidden input of a basic operation of the qualified signature.

Case studies are shown in which we can observe a significant improvement in the use of memory resources. Although the model we use to provide linear attributes to program's data is limited (we do not work with recursive types, for example), it shows that the notion of weak-linearity works by promoting considerable efficiency.

We consider that the work proposes a theoretical framework that express in a simple way some benefits of linear systems, and that it can be an adequate framework to study the relationship between substructurality and in-place update, a relationship that, although it has been addressed in numerous works, still presents clear challenges.

#### References

- Alexander Aiken, Jeffrey S. Foster, John Kodumal, and Tachio Terauchi. Checking and inferring local non-aliasing. In ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI), San Diego, California, pages 129-140, June 2003.
- [2] D. Aspinall, M. Hofmann. Another Type System for In-Place Update, D. Le Metayer (Ed.): ESOP 2002, LNCS 2305, pp. 36-52, 2002.
- [3] Iliano Cervesato and Frank Pfenning. A linear logical framework. Information and Computation, 179(1):19-75, November 2002.

- [4] J. Chirimar, C. Gunter and J. Riecke. Reference Counting as a Computational Interpretation of Linear Logic, Journal of Functional Programming, 6(2), 1995.
- [5] Kosta Dosen. A historical introduction to substructural logics. In K. Do"en and P. Schroeder-Heister, editors, Substructural Logics, pages 1-30. Oxford University Press, 1993.
- [6] Jeffrey Foster, Tachio Terauchi and Alex Aiken. Flow-sensitive type qualifiers. In ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI), Berlin, Germany, pages 1-12, June 2002.
- [7] J.Y. Girard, Linear logic, Theoretical Computer Science 50 (1987) 1-102.
- [8] J.Y. Girard and Y. Lafont, Linear Logic and Lazy Computation, in: TAP-SOFT 87, Volume 2, LNCS 250 (Springer-Verlag, Pisa) 52-66.
- [9] Naoki Kobayashi. Quasi-Linear Types, In Proceedings ACM Principles of Programming Languages, pages 29-42, 1999. 40, 50
- [10] Yves Lafont, The linear abstract machine, Theoretical Computer Science, Volume 59, Issues 1?2, July 1988, Pages 157-180
- [11] M. Odersky, Observers for linear types. In B. Krieg-Brückner, edi- tor, ESOP ?92: 4th European Symposium on Programming, Rennes, France, Proceedings, pages 390-407. Springer-Verlag, February 1992. Lecture Notes in Computer Science 582.
- [12] John C. Reynolds, Theories of Programming Languages, Cambridge University Press, 1998.
- [13] Frederick Smith, David Walker and Greg Morrisett. Alias types. In European Sym-posium on Programming (ESOP), Berlin, Germany, volume 1782 of Lecture Notes in Computer Science, pages 366-381. Springer-Verlag, April 2000.
- [14] P. Wadler, Linear types can change the world! In IFIP TC 2 Working Conference on Programming Concepts and Methods, Sea of Galilee, Israel, April 1990. Published as M. Broy and C. Jones, editors, Programming Concepts and Methods, North Holland, 1990.
- [15] David Walker. Subestructural Types Systems, in Advanced Topics in Types and Programming Languages. Benjamin C. Pierce, editor. The MIT Press, Cambridge, Massachusetts London, England 2005.
- [16] David Walker and Kevin Watkins. On regions and linear types. In ACM SIGPLAN International Conference on Functional Programming (ICFP), Firenze, Italy, pages 181-192, September 2001.
- [17] Keith Wansbrough and Simon Peyton Jones. Once upon a polymorphic type. In ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL), San Antonio, Texas, pages 15-28, January 1999.