ROY SHADMON, University of California, Santa Cruz, USA DANIEL SPENCER, Indiana University, USA OWEN ARDEN, University of California, Santa Cruz, USA

Distributed control systems require high reliability and availability guarantees, despite often being deployed at the edge of network infrastructure. Edge computing resources are less secure and less reliable than centralized resources in data centers. Replication and consensus protocols improve robustness to network faults and crashed or corrupted nodes, but these volatile environments can cause non-faulty nodes to temporarily diverge, increasing the time needed for replicas to converge on a consensus value, and give Byzantine attackers too much influence over the convergence process.

This paper proposes *proximal Byzantine consensus*, a new *approximate* consensus protocol where clients use statistical models of streaming computations to decide a consensus value. In addition, it provides an interval around the decision value and the probability that the true (non-faulty, noise-free) value falls within this interval. Proximal consensus (PC) tolerates unreliable network conditions, Byzantine behavior, and other sources of noise that cause honest replica states to diverge. We evaluate our approach for scalar values, and compare PC simulations against a vector consensus (VC) protocol simulation. Our simulations demonstrate that consensus values selected by PC have lower error and are more robust against Byzantine attacks. We formally characterize the security guarantees against Byzantine attacks and demonstrate attacker influence is bound with high probability. Additionally, an informal complexity analysis suggests PC scales better to higher dimensions than convex hull-based protocols such as VC.

## **1 INTRODUCTION**

Distributed control systems need timely access to *feedback data*—data from (or derived from) sensors—in order to make control decisions. The consequences of delayed, missing, or corrupted data depends on the system; from suboptimal performance to catastrophic failure. Hence, the lengths a control system designer's willingness to ensure data integrity and availability is frequently application specific. A manifestation of this dynamic are design parameters that characterize limits on the noise or error in the feedback data that the control system can tolerate. When a feedback data source processes sensor data in one or more stages before emitting it to the control system, noise effects accumulate, combining the inherent measurement noise of the sensors and noise caused by missing or delayed inputs at each processing stage. Feedback data from the physical world is almost always noisy to some extent, so systems are designed to tolerate an amount considered reasonable by the system designers. For sensitive control system parameters, however, exceeding the expected threshold could cause unpredictable, even dangerous, behavior.

Tolerating faulty behavior has been a central focus of distributed systems research for decades. By replicating system components and requiring a consensus among the components' outputs, fault tolerant protocols have been developed for many scenarios. A *crash-fault tolerant* (CFT) system preserves the safety (a "bad thing" never happens) and liveness (a "good thing" eventually happens) of the system despite up to an upper-bound of *F* replicas crashing, meaning they stop responding altogether. A *byzantine-fault tolerant* (BFT) system preserves these properties when up to *F* replicas behave arbitrarily, such as maliciously deviating from the protocol.

Noisy feedback data presents a challenge for fault-tolerance in distributed control systems since the noise makes it harder to ensure non-faulty consensus outputs. At a high level, CFT protocols such as Paxos [20] and BFT protocols such as PBFT [6] reach consensus by finding a quorum of replicas proposing identical values, with the size of the quorum ensuring that (1) a minimum number of non-faulty hosts are included, and (2) at least one of these non-faulty hosts participated in the previous phase or round. Together, these properties ensure that non-faulty nodes have a



(a) Tverberg-based consensus in one dimension.



Fig. 1. Tverberg consensus selects points within the convex hull of non-faulty replicas. Proximal consensus selects points most likely to have been produced by non-faulty replicas.

consistent view of the system state, and the system can always output values corresponding to the outputs of a quorum of non-faulty nodes (provided no more than F faults occur). In a distributed control system, however, non-faulty replicas might propose different values due to various sources of noise. Thus, a quorum of identical values may not exist.

Protocols that ensure *approximate* consensus among non-faulty replicas have been studied to address this challenge. Many of these protocols guarantee that consensus values are bound by the *convex hull* of the non-faulty outputs. The convex hull of a set of points is the smallest convex shape that contains all the points. In one dimension, the convex hull is a line interval, in two dimensions it is a polygon, and so on. The challenge of selecting a value in the convex hull of non-faulty outputs is that the identity of the faulty replicas is unknown, so it is not possible to determine the convex hull directly.

Figure 1a illustrates a common approach to approximate consensus based on *Tverberg points* [32]. Suppose one replica must choose an output value based on four proposed values: its own value and the values it received from the three other replicas, one of which may be faulty. In Figure 1a, these values are placed on a number line. The faulty value (*X*) is red and the non-faulty values (*A*, *B*, *C*) are blue. There are four quorums of size 3, but only two define intervals containing non-overlapping regions:  $Q1 = \{X, A, B\}$ , and  $Q2 = \{A, B, C\}$ .

By design, all quorums must contain at least two non-faulty values, so for a particular quorum Q, there must be at least one subset  $S \subseteq Q$  with |S| = 2 that contains no faulty values. The replica then selects a value in the intersection of the intervals (convex hulls) formed by each size-two subset. Tverberg's Theorem [31] guarantees this intersection is non-empty. Notice that even if a network partition prevented one of the non-faulty values from delivery, the replica can still select a value in the non-faulty interval of Q1. When more than one Tverberg point is available, most protocols choose some aggregate function of the points such as their mean.<sup>1</sup>

The convex hull guarantee<sup>2</sup> is a strong one: Byzantine attacks can never cause a consensus value to be outside a region defined only by non-faulty nodes. However, the larger the convex hull, the more power an attacker has to influence the output value. For example, if the attacker instead chose

<sup>&</sup>lt;sup>1</sup>In one dimension, Tverberg points correspond to the median [16], but the idea of convex hulls generalizes to higher dimensions, where Tverberg points represent a kind of "higher-dimensional median." In this paper, we focus only on scalar (one-dimensional) consensus.

<sup>&</sup>lt;sup>2</sup>Other approaches that guarantee containment in the convex hull of non-faulty outputs use centerpoints [1], Weighted-Mean Subsequence Reduced algorithms [33], or median-based algorithms [23] instead of Tverberg points. Although we do not discuss these approaches specifically, much of our analysis regarding consensus values bound by a non-faulty convex hull apply more generally.

*X* in Figure 1a to be to the right of *A*, *B*, and *C*, then the relevant quorum would be  $\{B,C,X\}$  and *C* would be a Tverberg point instead of *A*. Likewise, if a network partition prevented delivery of value *C*, any value proposed by the attacker between *A* and *B* would be chosen as the Tverberg point. In noisy or volatile environments, the distance between non-faulty outputs is likely to grow, giving attackers more influence over the chosen value.

This paper presents *proximal byzantine consensus*, an alternative to convex hull methods for finding consensus values in noisy environments. Rather than using a geometric basis such as Tverberg points to select values robustly, a proximal consensus replica uses statistical inference conditioned on the inputs it receives from other replicas. The core insight behind proximal consensus is that, since they are performing the same deterministic computation on highly correlated inputs, the outputs of non-faulty replicas should be similar. To exploit this similarity, proximal consensus replicas infer the most probable "ideal" output value (without noise) given the observations it has received.

If all values received by a replica were non-faulty, inferring the ideal output would be straightforward. Given prior distributions for the outputs and the noise, we would want to find the value that maximizes the probability density function (PDF)—the most probable value—of the unknown output distribution given the observed values. But since some of the values may be Byzantine, treating these values as legitimate observations would give attackers too much influence over the inferred output. Attempting to model the Byzantine values statistically is not an option since by definition Byzantine replicas behave arbitrarily: an attacker's previous behavior is not predictive of its future behavior.

Instead, for each possible quorum, proximal consensus infers the conditional probability distributions *assuming the observed values were produced by non-faulty nodes*. Figure 1b illustrates three PDFs, each conditioned on a different quorum of values (Q1, Q2, and Q3) received by a replica. Each curve represents the probability that the x-axis value is the ideal output if the values in that quorum were produced by non-faulty nodes. Since the conditional probability of an output is proportional to the similarity of the quorum values, as long as there are a sufficient number of non-faulty values in each quorum, the quorum that produces the PDF with the highest maximum value (Q1) is the most likely to contain only non-faulty values or faulty values that are similar to non-faulty values. If it contains faulty values, they must be at least as similar to non-faulty values as other non-faulty values are, otherwise exchanging those values would increase the maximum of the PDF. Thus, the replica's best choice based on the quorums in Figure 1b is 5, the most probable output given the values in Q1.

We discuss below the formal guarantees offered by proximal consensus and use proximal consensus in the design of two related protocols:

- A "one shot" protocol where replicas broadcast proposed values to clients without requiring coordination and clients locally determine the proximal consensus value and confidence interval.
- A coordinated protocol where replicas propose values until either a desired confidence interval is reached or a minimum number of messages are received.

These protocols require additional replicas compared to convex hull methods: proximal consensus requires a minimum of 4f + 1 replicas compared to 3f + 1, but this cost is offset by lower asymptotic complexity in higher dimensions (Section 4.1), stronger guarantees against Byzantine influence on outputs (Section 4.2), and significantly better accuracy (Section 5).

We empirically evaluate proximal consensus against a convex hull method based on byzantine vector consensus [32] by simulating their performance under varying noise distributions and network characteristics. Our results demonstrate that the output values produced by proximal

consensus are more accurate than *vector consensus*, a common convex hull protocol, across varying levels of noise. Specifically, we show that proximal consensus decreases the median percent error in comparison to vector consensus by an average of 56% to 65% under no attacks. When the system is under an optimal Byzantine attack, defined in Definition 4.3, we show that proximal consensus decreases the median percent error by 31% to 78%. In both scenarios we simulated a replica set with f = 1 to f = 4 Byzantine replicas when noise on the scale of 2% to 12% is introduced to the system. Our results are statistically significant at a confidence level of 99.9%.

## 2 PROXIMAL BYZANTINE CONSENSUS

We define the proximal Byzantine consensus problem below:

DEFINITION 2.1 (PROXIMAL BYZANTINE CONSENSUS PROBLEM). A node receiving outputs Q from non-faulty replicas modeled by random variable  $X \sim D$  over a channel with noise modeled by  $Y \sim D_{\epsilon}$ decides on a value v with confidence  $c_{X\cdot Y}$  such that:

$$v \in \left[ E(X \cdot (Y - \epsilon_L) \mid Q), \ E(X \cdot (Y + \epsilon_H) \mid Q) \right]$$

where  $Y - \epsilon_L$  and  $Y + \epsilon_H$  is the negative and positive range of the error, and  $c_{X,Y}$  is the confidence over that range.

In this paper, we give a solution for the (common) case where X and Y are independent and the noise distribution is unbiased, meaning the expected value of Y, E[Y], is 1.<sup>3</sup> The observations in Q are nominally derived from the same system input streams—each replica (attempts to) receive the same stream of outputs from a sensor or upstream replica set. However, since some replicas may experience network faults, we model the observed outputs of each replica scaled by an independent noise sample Y.

Rather than choosing interval parameters  $\epsilon_L$  and  $\epsilon_H$  directly as in other approximate byzantine consensus protocols, the system designer selects the required confidence  $c_{X\cdot Y}$ , and  $\epsilon_L$  and  $\epsilon_H$  are derived from  $c_{X\cdot Y}$  and the variance of output observations. Higher values of  $c_{X\cdot Y}$  result in wider intervals, as do output observations with higher variance. Informally, the noisier non-faulty values are, the more difficult it is to distinguish non-faulty outliers from Byzantine values, so we want the smallest values of  $\epsilon_L$  and  $\epsilon_H$  with sufficient confidence for the variance we seek to tolerate.

Here we exploit the fact that each observation in Q is the product of a single sample from X and multiple independent samples from Y to directly infer the error distribution parameters from the observed replica outputs, resulting in interval bounds  $\epsilon_L$  and  $\epsilon_H$  that are proportional to the variance of Y. However, a trivial variant of our solution also applies to systems where, rather than consuming the same input stream, the replicas consume independent, identically-distributed (IID) input streams. In this case, error distribution parameters cannot be inferred directly, so the bounds would be proportional to the variance of  $X \cdot Y$ . For simplicity, we only discuss the former configuration in the remainder of the paper.

Since X and Y are also conditionally independent with respect to Q, the interval of v simplifies to  $\int \left[ F(X \mid Q) - f(X$ 

$$v \in [E(X \mid Q) \cdot (1 - \epsilon_L), E(X \mid Q) \cdot (1 + \epsilon_H)]$$

In our solution presented in Section 4, we assume *X* and *Y* have stationary Gaussian distributions, but expect our approach is applicable to other distribution families.

Like other fault-tolerant protocols, proximal consensus relies on a majority of non-faulty replicas overwhelming the behavior of faulty replicas. What sets it apart from exact BFT protocols is that proximal consensus (PC) enables an *approximate* (or "proximal") consensus to be formed when, due to network faults or corrupted or crashed replicas, non-faulty replicas produce differing outputs

<sup>&</sup>lt;sup>3</sup>When  $E[Y] \neq 1$ , it implies the noise causes a skew in the observed outputs. In this case, our E[Y] = 1 assumption just causes consensus values to be similarly skewed.



Fig. 2. System Architecture for a fault-tolerant data pipeline.

based on incomplete or otherwise corrupted data. Furthermore, Proximal Byzantine Consensus is distinct from approximate consensus problems such as *asymptotic agreement* [22], *approximate scalar agreement* [13], and *approximate vector agreement* [26, 32] in that neither the problem nor the solution are defined in terms of the convex hull of non-faulty replica outputs.

The core idea behind proximal consensus is that even when the outputs of non-faulty nodes differ, these differences can be modeled statistically to account for the noise introduced into the replicated computations. Specifically, proximal consensus attempts to determine the subset of replica outputs most likely to have been produced by non-faulty replicas. For example, if we have *n* replicas and believe at most *f* of them could be faulty or malicious, then we want to determine the most likely subset of outputs of size 2f + 1. This ensures that a majority of outputs in the subset came from non-faulty replicas. Given that subset, we want to determine the most likely *ideal output*: what the output would be if the nodes received all messages in time to process them. To determine this ideal output, the nodes receiving the replica outputs consider the conditional probability of receiving each subset of 2f + 1 outputs from non-faulty nodes given the current statistical model of the output domain scaled by a noise factor.

## 3 SYSTEM DESIGN AND THREAT MODEL

**One-shot proximal consensus.** When timely outputs are prioritized over consistent ones, the "one-shot" variant of our proximal solution provides additional flexibility over existing approximate BFT protocols. These BFT protocols incorporate a convergence parameter  $\epsilon$  that could in theory produce quicker convergence on a consensus output, but may still require multiple rounds to terminate. Furthermore, it is difficult to assess the application-specific impact of larger values of  $\epsilon$  since the area of convergence in the convex hull may be largely under the control of the attacker.

In one-shot proximal consensus (Algorithm 2 in Appendix), clients receive outputs directly from upstream replica sets and calculate the proximal consensus value locally using Definition 4.1. Given the set of received values, the client calculates its confidence in the candidate consensus value. If the confidence exceeds a minimum threshold, it accepts the value and may act on it. Otherwise, a network fault may have interrupted message delivery, and the client must wait for additional messages, up to a total of n - f. If n - f messages have been received without meeting the minimum

confidence threshold, the client accepts the consensus value, but may choose not to act on it based on the low confidence.<sup>4</sup>

Since each client computes a value based on its own view of the replica outputs, the output values and intervals may differ between clients. However, since all intervals contain the ideal output with high probability, they (with high probability) overlap with the interval determined by a hypothetical client that successfully received all outputs. One-shot proximal consensus is particularly appropriate for replicating approximate data-stream computations where exact agreement between clients is unnecessary and occasional dropped or low-confidence values are tolerable.

**Coordinated proximal consensus**. Instead of having clients compute proximal consensus values themselves, coordinated proximal consensus (Algorithm 3 in Appendix) reaches a consensus value among the replicas before providing a result to the client. This workflow is closer to traditional consensus protocols and eliminates the case where clients may reach different decision values due to observing different subsets of replica outputs. Using a traditional consensus protocol, replicas first reach agreement on a set of (possibly different) outputs received from their peers. They each then deterministically compute the proximal consensus value and confidence interval, and send the results to the client. Since the replicas observe the same stream of observations, the updated distribution parameters of non-faulty replicas remain consistent.

In a *hybrid configuration*, a coordinated instance of proximal consensus can be used to correct temporary divergence between one-shot instances by periodically sending updated distribution parameters to its consumers (i.e., any clients computing one-shot consensus).

*System model.* Figure 2 illustrates a hybrid configuration of proximal consensus for the feedback dataflow of a distributed control system (DCS). Edges represent network connections between distributed components. Solid lines represent the one-shot dataflow path, which acts as a speculative "fast path" enabling consumers to receive a set of outputs with minimal dependency on inter-replica coordination. The dashed lines represent the additional processes of the coordinated dataflow path. These processes maintain a consistent set of inferred distribution parameters agreed upon by the replicas within the replica set. By periodically updating the downstream one-shot replicas with these parameters, the degree and duration of divergence between one-shot replicas is reduced.

System components that process, clean, and store data from upstream producers are called *consumers*. The end-user client in Figure 2 is a consumer, but so are the replicas in the first and second layers. System components that produce and stream data to downstream components are called *producers*. For example, the sensors on the left hand side of Figure 2 are producers, but the replicas in the first and second layers are also producers.

**Network model.** Proximal consensus is designed for robustness to both Byzantine and network faults, so asynchronous or partially synchronous settings are the most interesting since messages from sensors or non-faulty replicas may not arrive by the time a downstream consumer wishes to act. In a synchronous network, missing messages are considered faults, which reduces the ambiguity between faulty and non-faulty behavior since "noise" is attributable to faults. Synchronous proximal consensus is more interesting for the variant (see Section 2) where replicas consume IID input streams rather than subsets of the same stream, where noise may be due to the variance of the input streams or faulty behavior. We focus primarily on the non-synchronous case (asynchronous or partially synchronous) where, due to network delays, non-faulty node computations experience some noise when they must produce outputs based on a subset of stream inputs.

<sup>&</sup>lt;sup>4</sup>Whether or not to act on low-confidence values is somewhat application specific. For example, it may be preferable to respond quickly if the currently-received messages result in high confidence. Otherwise a client could wait for the "best possible" confidence, and act on the value as long as it exceeds a lower confidence threshold.

**Threat model.** Each replica set  $R_i$  contains  $n_i \ge 4f_i + 1$  replicas with up to  $f_i$  being Byzantine. Each round of proximal consensus produces a value v and an interval guarantee  $IG = [v - \hat{\epsilon}_L, v + \hat{\epsilon}_H]$ , where  $\hat{\epsilon}_L$  and  $\hat{\epsilon}_H$  are derived from the current parameters inferred for Y. The *IG* indicates an interval around v that contains the true output with high probability, and represents the uncertainty of v relative to the true output.

Replica sets and one-shot clients are configured with a confidence level  $c_i$  and an acceptable interval width,  $AIW_i$ . The  $c_i$  parameter defines what confidence is required for the interval guarantees of each proximal consensus decision. The  $AIW_i$  parameter is used to reduce consensus latency by specifying the (desired) minimum acceptable width of the interval defined by  $\epsilon_H$  and  $\epsilon_L$  for confidence level  $c_i$ .

Attacker influence is bounded by ensuring that any attack included in a selected quorum (and therefore able to influence the output) is at least as likely to have come from a non-faulty replica as the values that were *not* selected. The key to providing this guarantee is that a sufficient number of messages must be received so that a  $2f_i + 1$  quorum can be selected out of minimum  $3f_i + 1$  messages. Quorums need at least  $2f_i + 1$  outputs so that even in the worst case, when the only non-faulty quorum is the least likely one considered possible (e.g., containing outputs within the 99.7% confidence interval), the attacker's influence is still bounded by the interval guarantee. Intuitively, the *worst-case honest quorum* is split between extremal values, giving the attacker maximal influence. However, since each member of the selected quorum must be at least as likely as the (at least)  $f_i$  unselected messages, any attacks that are selected for the quorum must be as likely as an honest output that was not selected. We evaluate these guarantees formally in Section 4.2.

A quorum can also be selected when the resulting interval guarantee exceeds the  $AIW_i$  parameter. Essentially  $AIW_i$  acts as a proxy for unseen honest outputs, declaring an application-specific degree of influence that is considered tolerable. If a  $2f_i + 1$  quorum exists among the received outputs that results in an acceptable interval guarantee, then it is unnecessary to wait for  $3f_i + 1$  messages.

The need for  $3f_i + 1$  messages in the general case increases the minimum number of replicas to  $4f_i + 1$  for proximal consensus compared to convex hull approaches, most of which require only  $3f_i + 1$ . To ensure liveness while preserving the soundness of the interval guarantee, it is necessary that a replica can expect to eventually receive  $3f_i + 1$  messages. This is only possible if there are at least  $3f_i + 1$  non-faulty replicas since up to  $f_i$  Byzantine replicas could withhold outputs indefinitely. This also implies that in synchronous networks, as long as the upper-bound on message delivery is shorter than the desired reaction time, only  $3f_i + 1$  replicas are required since non-faulty replica outputs always arrive on time.

## 4 CONSENSUS AS PROBABILITY MAXIMIZATION

We present the mathematical foundations of proximal consensus using a simple example. Consider a stream of coin flips sent to a replica set that produces the observed count of tails results for the past *t* seconds. In Figure 3, the data source flips a coin twice and sends each result (both tails) to the replicas. Two non-faulty replicas and one Byzantine replica receive both observations. Although the Byzantine replica receives both messages, it outputs 0T, trying suppress the total tails count. The two non-faulty replicas send 2T, but only one output arrives at the client due to a network partition. Two other non-faulty replicas receive only one of the observations, thus outputting 1T to the client. From the clients view, any one (but only one) of the received values may be faulty, or they could all be non-faulty and the missing value may be from a faulty replica. Exact BFT protocols require a majority (typically two-thirds) of replicas to agree in order to decide on a value. In the Figure 3 scenario, no such majority exists. The client instead uses proximal consensus to determine the most likely number of tails given the outputs it received and its prior knowledge, if any, about the coin flipping process. It models each



Fig. 3. Counting the number of tails flipped.

coin flip as a sample from a uniform distribution of heads/tails, scaled by a randomized noise factor that accounts for error introduced by network latency or other transient sources of noise experienced by the client receiving inputs.

First consider the unconditional probability of receiving 2T. A non-faulty replica reports 2T if it observes two T messages from its source. Therefore, the probability of observing 2T is the joint probability of two tail flips and two delivered messages. The joint probability of two tail flips is  $P(TT) = \frac{1}{2} \cdot \frac{1}{2}$ . Now suppose  $R_1$  and  $R_2$  represent random variables for arrival times of the first and second messages at the replica. The joint probability of two delivered messages is  $P(R_1 \le t) \cdot P(R_2 \le t)$  where t is the deadline. This joint probability models the "noise" introduced by observing coin flips over the network. Assuming  $R_1$  and  $R_2$  are independent of the contents of the messages, the joint probability of two tail flips and two delivered messages is  $P(2T) = \frac{1}{4} \cdot P(R_1 \le t) \cdot P(R_2 \le t)$ .

Now consider receiving 1T from an honest node. Here, more than one scenario could have produced this output. There could have been only one tail: either TH or HT with the T message delivered, or there could be two tails (TT) but one of the messages failed to arrive in time. The following sum of joint probabilities represent these scenarios.

 $P(1T) = P(TH) \cdot P(R_1 \le t) + P(HT) \cdot P(R_2 \le t) + P(TT) \cdot (P(R_1 > t) \cdot P(R_2 \le t) + P(R_1 \le t) \cdot P(R_2 > t))$ 

Receiving ØT from an honest node could result from two heads or all tails messages being delayed.

$$P(0T) = P(HH) + P(TT) \cdot P(R_1 > t) \cdot P(R_2 > t) + P(TH) \cdot P(R_1 > t) + P(HT) \cdot P(R_2 > t)$$

Using these probabilities and the messages received from replicas, proximal consensus aims to determine the most likely *ideal output*: what a non-faulty node would output if there were no network or replica faults. Formally, let X be a random variable representing the sample space of the ideal output and x be a candidate output in the (ideal) output sample space  $(x \sim X)$ , and  $q_i \in Q$  be samples of the replica output sample space  $(q_i \sim XY)$  where Y is the noise distribution. Let q be a subset of size 2f + 1 = 3 of the observed events  $Q = \{q_1 = 2T, q_2 = 1T, q_3 = 0T, q_4 = 1T\}$ . The client's task is to find a pair (x, q) that maximizes the conditional probability  $P(X = x \mid q)$ :

DEFINITION 4.1 (PROXIMAL CONSENSUS OF Q).

$$PC(Q, n, f) \triangleq \underset{x \in X; q \in [Q]^{2f+1}}{\operatorname{argmax}} P(X = x \mid q)$$

In other words, the client finds the most likely output *x* from the output sample space *X* over all valid quorums *q* of size 2f + 1 = 3. This pair (x, q) maximizes the probability P(X = x | q).<sup>5</sup> It will sometimes be convenient to talk about the most likely output *x* resulting from a fixed quorum *Q*, which we will refer to as x = PC(Q, n, 0).

The observations during a round of proximal consensus are used to improve the inferred distribution parameters for subsequent rounds. Currently we consider analytical distribution families with known conjugate prior functions [3]. These functions update the prior distribution parameters

<sup>&</sup>lt;sup>5</sup>In Bayesian statistics, this process is often referred to as computing the *maximum a posteriori* or *highest posterior density interval (HPDI).* 

to form the *posterior distribution*, which takes into account the messages observed in the selected PC quorum. By only considering the selected PC messages, we reduce influence from faulty values at the time of inference.

The inference process infers *distributions* on the unknown distribution parameters rather than a single "best" choice of parameters—the values observed could have been produced by one of many potential source distributions. To choose the most likely output value, we must consider all of the potential distributions, weighted by the probability they could have produced the selected observations. Fortunately, for distribution families with conjugate prior functions, this task is straightforward using the *posterior predictive distribution* [3], which gives the likelihood of an output given the posterior distribution of the parameters.

**Computing a proximal consensus.** Like vector consensus, the consensus value x = PC(Q, n, f) may not necessarily be any of the outputs in Q. Since the outputs in Q are neither independent of the distribution they were produced from nor each other, we can expect non-faulty outputs to be similar in relatively reliable networks. Consequently, we can compute the conditional probability P(X = x | q) based on a similarity function proposed by Blok et al., [5] that relates the replica outputs and the candidate event:

DEFINITION 4.2 (CONDITIONAL PROBABILITY).

$$P(X = x \mid q) = P(x)^{\alpha}$$
 where  $\alpha = \frac{1 - sim([x, q])}{1 + sim([x, q])}^{1 - P(q)}$ 

For example, as the similarity of x with the 2f + 1 observations in q (sim([x, q])) approaches 1 (more similar),  $P(x)^{\alpha}$  approaches 1. Thus,  $\alpha = 0$  means x matches every output in q or P(q) = 1.

Using Definition 4.2, proximal consensus computes the global maxima point of each quorum  $q \in Q$  and returns the (x, q) pair that is most conditionally likely. Finally, the currently inferred mean of the replica output distribution  $(\mu_{XY} = E[XY])$  and variance of the error distribution  $(\sigma_{\epsilon} = \sqrt{\operatorname{Var}(Y)})$  are used to conservatively estimate a 99.7% interval guarantee (IG) for the chosen value:  $IG = [\mu_{XY} \cdot (1 - 3 \cdot \sigma_{\epsilon}), \mu_{XY} \cdot (1 + 3 \cdot \sigma_{\epsilon})]$ . Algorithm 1 and the mathematics of a proximal consensus (Equations 9-22) is provided in the Appendix.

### 4.1 Run-time complexity

In one dimensional convex hull methods, computing valid consensus points given a set of replica outputs (whether Tverberg points or centerpoints [1]) is equivalent to finding the median, and so has time complexity of  $O(f \log f)$ .<sup>6</sup> In higher dimensions *d*, the complexity rapidly increases. Currently-known Tverberg point algorithms have complexity  $O((2f + 1)^{d(d+1)+1})$  [16]. Based on prior work establishing that checking the validity of centerpoints is co-NP-complete [30], Abbas et al. [1] conjecture checking the validity of consensus points in convex hull methods is also co-NP-complete.

Approximate algorithms for computing Tverberg points exist (see [16] for an overview), but require more non-faulty nodes per tolerated faulty node:  $f < \Omega(\frac{n}{2^d})$  for Tverberg points, and  $f < \Omega(\frac{n}{d^2})$  for centerpoints [1]. Approximation parameters for these algorithms that guarantee fault tolerance [1] imply a runtime complexity of

$$O((2f+1)^{c\log d} \cdot (2d)^d)$$

<sup>&</sup>lt;sup>6</sup>Although in exact BFT protocols there is usually no reason to choose an *n* higher than the minimum (e.g., n = 3f + 1, implying  $O(n) \sim O(f)$ ), n > 3f + 1 can improve accuracy in our setting for both vector and proximal consensus. For this reason, we state asymptotic complexities in terms of *f* when they involve the size of the quorums needed to tolerate *f* faults, and use *n* only when it involves the total number of replicas.

More recent approximation algorithms [16] improve the runtime complexity in general, but it is not currently clear to what degree they improve the efficiency of valid consensus point calculations.

Convergence in vector consensus depends to some extent on computing valid consensus points for each potential 2f + 1 quorum of the received values, implying that the above calculations are performed up to  $\binom{n}{2f+1}$  times per round. Most vector consensus algorithms converge quickly, but it may take multiple rounds to decide a value. Assuming convergence occurs in a constant number of rounds, the computational complexity of agreement with vector consensus is  $O(\binom{n}{2f+1} \cdot f \log f)$  for one dimension, and for arbitrary dimensions (using approximate Tverberg point algorithms):

$$O(\binom{n}{2f+1} \cdot (2f+1)^{c \log d} \cdot (2d)^d)$$

Proximal consensus also considers each of the up to  $\binom{n}{2f+1}$  quorums, but the complexity of the calculations performed for each quorum scales significantly better. To compute the argmax with respect to a quorum q and consensus value x, our solution determines the x with maximum likelihood for a given q using a binary search over a search domain S quantized by a step size p. At each candidate x, evaluating the conditional probability involves computing the similarity score (21) of x with each of the 2f+1 quorum outputs, which is based on a normalized d-dimensional Euclidean distance (see (22)). The normalization step is  $O(\binom{2f+1}{2}) \sim O(f^2)$  [14] and the distance calculation is O(d). Thus each iteration of the search algorithm is  $O(f^3d)$ . The search requires up to  $O(\log k)$  iterations where  $k = \frac{|S|}{p}$  i.e., the number of intervals S in the search space implied by step size p.<sup>7</sup>

This paper presents a proximal consensus approach for one dimensional values. While our approach needs further study to evaluate its effectiveness in *d* dimensions, the complexity of the argmax calculation in *d* dimensions is easy to analyze. For general dimensions *d*, finding the maximally likely value for *x* in a uni-modal distribution for a given *q* can be accomplished with gradient descent (GD) algorithms, which have complexity  $O(dk^2)$ . Furthermore, stochastic gradient descent (SGD) algorithms significantly improve performance by approximating the gradient calculation. SGD algorithms are also less likely to converge on local maximums, and so may be appropriate for multi-modal distributions.

In summary, the asymptotic complexity of our proximal consensus algorithm is  $O(f \log k)$  and for *d* dimensions is expected to be (using exact gradient descent search):

$$O(\binom{n}{2f+1} \cdot f^3 d^2 k^2)$$

This indicates that although the runtime complexity of our algorithm has comparable or even slightly worse asymptotic complexity (k will typically be larger than f) in one dimension, it is significantly more efficient in higher dimensions than convex hull-based protocols.

## 4.2 Security guarantees against adversaries

We now present a detailed analysis of the maximum impact of Byzantine replicas on a replicated data stream. Byzantine adversaries are omniscient and adaptive in the sense that they have complete knowledge of the outputs of all correct replicas prior to choosing their malicious outputs to maximize the effectiveness of the attacks. As discussed in Section 3, for an attack to be effective, it must be likely enough to be a non-faulty output that it is included in the selected quorum. We formally define these attacks below:

<sup>&</sup>lt;sup>7</sup>To further improve efficiency our implementation limits the search to the the 99.7% credible interval of the distribution, which significantly reduces the size of k relative to step size.

DEFINITION 4.3 (EFFECTIVE ATTACKS). Let  $Q = \{r_1, ..., r_{(2f+1)}\}$  be a quorum containing 2f + 1 outputs from correct replicas,  $Q_L \subset Q$  be the smallest f + 1 honest outputs, and  $Q_H \subset Q$  be the largest f + 1 honest outputs. Furthermore, define  $A_L$  (resp.  $A_H$ ) to be a set of f Byzantine outputs aimed to suppress (inflate) the PC output. Let  $\phi_L = Q_L \cup A_L$  and  $\phi_H = Q_H \cup A_H$ . A suppressing attack is a set  $A_L$  such that

$$PC(Q, 2f + 1, 0) > PC(\phi_L, 2f + 1, 0)$$
 and  $P(X = PC(Q, 2f + 1, 0) | Q) \le P(X = PC(\phi_L, 2f + 1, 0) | \phi_L)$  (1)

An inflating attack is a set  $A_H$  such that

 $PC(Q, 2f + 1, 0) < PC(\phi_H, 2f + 1, 0) \text{ and } P(X = PC(Q, 2f + 1, 0) | Q) \le P(X = PC(\phi_H, 2f + 1, 0) | \phi_H)$  (2)

Satisfying assignments for  $A_L$  and  $A_H$  always exist by choosing  $A_L$  such that  $Q_L \cup A_L = Q$  or  $A_H$  with  $Q_H \cup A_H = Q$ . We call the  $A_L$  containing the lowest satisfying outputs a maximally suppressing attack and the  $A_H$  containing the highest satisfying outputs a maximally inflating attack.

Let  $X \sim N_{\chi}(\mu, \sigma)$  and  $Y \sim N_{\epsilon}(1, \sigma_{\epsilon})$  be independent random variables for, respectively, the output distribution of data stream  $\chi$  and the error distribution for the network channels  $\chi$  is broadcast on. The mean  $\mu$  and variance  $\sigma^2$  of X is unknown, as well as the variance  $\sigma^2_{\epsilon}$  of the error distribution. Since the error distribution is unbiased, we set the mean  $\mu_{\epsilon}$  of the error distribution to  $\mu_{\epsilon} = 1$ . We take a Bayesian approach to modeling the unknown parameters of these distributions:  $\mu, \sigma, \sigma_{\epsilon}$  are random variables. Outputs of size n replica sets are modeled using a sample  $x \leftarrow X$ , and between 3f + 1 and n samples  $y_i \leftarrow Y$  to give outputs  $xy_1, xy_2, ..., xy_n$ . Only these samples are directly observable by consumers, and are approximately (cf. [29]) distributed as  $XY \sim N_{\chi\epsilon} \left(\mu, \sigma_{XY} = \sqrt{\sigma^2 + (\mu^2 + \sigma^2) \cdot \sigma_{\epsilon}^2}\right)$ .

Therefore, our goal is to use observations from the replica outputs to infer the parameters  $(\mu, \sigma_{XY})$  of  $N_{\chi\epsilon}$ , which has a normal-inverse-gamma  $(N - \Gamma^{-1})$  prior distribution, and the error distribution variance  $\sigma_{\epsilon}$ , which has an inverse-gamma distribution. Our guarantee takes the form of a bound on the influence Byzantine replicas may have on the output of a proximal consensus round given an error distribution. Since the error distribution varies (inversely) with the similarity between non-faulty outputs, our guarantee is parameterized on a prediction interval (PI) for  $N_{\gamma\epsilon}$ .

The selected PI bounds the sample space of observed outputs under consideration: outputs from non-faulty replicas falling outside the PI are considered too unlikely to affect the ability of an attacker to do harm. For example, we might wish to consider all non-faulty outputs occurring within the 99.7% PI. Consequently, if the *most probable honest quorum* of a round contains outputs outside this interval, the stated bound could be violated. However, for even one of this quorum's 2f + 1 outputs to fall outside the 99.7% PI, all other honest outputs not in the quorum must also fall outside the PI. If n = 4f + 1, then only 2f + 1 received outputs are guaranteed to be non-faulty since f may be missing and f of the 3f + 1 received messages may be faulty. Therefore, the chance of one of these honest outputs falling outside the PI is  $0.3\%^{(2f+1)}$  since each output represents an independent sample from the error distribution  $N_{\epsilon}$ . For n > 4f + 1, the probability of a non-faulty output in the selected quorum falling outside the PI decreases as n increases.

In terms of Definition 2.1, let  $v \in [v_{\text{low}}, v_{\text{high}}]$  be the interval specifying the bounds on the value v decided by a client given a set of received replica outputs, and let  $c_{\chi\epsilon}$  be a percentage representing a credible interval  $I_{\chi\epsilon}$  on the observed output distribution  $N_{\chi\epsilon}$ . The attacker is only able to cause the consumer to decide a value  $v' \notin [v_{\text{low}}, v_{\text{high}}]$  if all but 2f outputs from honest nodes fall outside  $I_{\chi\epsilon}$ . Therefore, the confidence level  $c_{\epsilon}$  that v is bounded by  $[v_{\text{low}}, v_{\text{high}}]$  is equal to the probability of not receiving at least (n - f) - 2f honest outputs outside  $I_{\chi\epsilon}$ , thus

$$c_{\epsilon} = 1 - (1 - c_{\chi\epsilon})^{(n-3f)}$$
(3)

Notice that the attacker cannot affect this probability since it depends only on the similarity of honest outputs, which affects the  $I_{\chi\epsilon}$ . Furthermore, the above formula represents the probability of the bounds being violated *at all*. The larger the security bound violation, the less likely the consumer is to receive honest outputs that are sufficiently dissimilar to enable the attack.

To determine the bounds  $v_{\text{low}}$  and  $v_{\text{high}}$ , we consider the worst-case honest quorum for the output credible interval  $I_{\chi}^{\text{obs}}$ . These outputs give the attacker maximum power to influence the proximal consensus result. We consider the outputs in this quorum possible, hence in  $I_{\chi\epsilon}$ , but potentially very unlikely. In fact, we want to consider the *lowest probability* honest quorum, since minimizing P(X = PC(Q, 2f + 1, 0) | Q) in Definition 4.3 increases the attacker's potential choices for  $A_L$  and  $A_H$ . Therefore, the maximum influence an attacker has is a maximally inflating (or suppressing) attack when the outputs of the honest nodes form a worst-case honest quorum.

We determine the worst-case honest quorum as follows. Observe that P(X = PC(Q, 2f + 1, 0) | Q)in Definition 4.2 is minimized when the similarity  $sim([X, Q]^{norm})$ , defined in (21), is minimized, which in turn is minimized when the normalized distance  $dist(D = [X, Q]^{norm})$ , defined in (22), is maximized. Therefore, the worst-case honest quorum is an honest quorum of outputs in  $I_{\chi\epsilon}$  with a maximal normalized distance. The maximum distance between two honest outputs depends on the size of the credible interval  $I_{\chi\epsilon}$ . For  $c_{\chi\epsilon} = 99.7\%$ , the interval is  $I_{\chi} = \left[\mu \cdot (\mu_{\epsilon} - 3 \cdot \sigma_{\epsilon}), \mu \cdot (\mu_{\epsilon} + 3 \cdot \sigma_{\epsilon})\right]$ .

A maximal normalized distance, then, is a quorum with outputs evenly split between the upper and lower boundaries,  $Q_H$  and  $Q_L$  where  $Q = Q_H \cup Q_L$ . Since the quorum size is always odd (2f + 1), there are two choices depending on whether  $Q_H$  or  $Q_L$  is larger. Which choice represents the worst case depends on the attack. An attack "replaces" f honest outputs in Q with f malicious ones without increasing the normalized distance of the quorum. A suppressing attack has a greater effect if it can replace all elements of  $Q_H$ , so the worst-case honest quorum  $Q_S = Q_L^S \cup Q_H^S$  for a suppressing attack is when  $|Q_L^S| = f + 1$  and  $|Q_H^S| = f$ . Dually, the worst-case honest quorum  $Q_I = Q_L^I \cup Q_H^I$  for an inflating attack is when  $|Q_L^I| = f$  and  $|Q_H^I| = f + 1$ .

The maximally suppressing attack  $A_L$  is then a set of f outputs  $a_L$  where  $a_L$  is the smallest value such that dist $([A_L \cup Q_L^S]^{\text{norm}}) = \text{dist}(Q_S^{\text{norm}})$ . The maximally inflating attack  $A_H$  is a set of f outputs  $a_H$  where  $a_H$  is the largest value such that dist $([A_H \cup Q_H^I]^{\text{norm}}) = \text{dist}(Q_I^{\text{norm}})$ .

We define  $\Omega$  as the normalized Euclidean distance of the worst-case honest quorum Q. For  $c_{\chi\epsilon} = 99.7\%$ ,

$$\Omega = \begin{cases} \frac{6 \cdot \mu \cdot \sigma_{\epsilon} \cdot \sqrt{f \cdot (f+1)}}{\sigma} & \mu \neq 0\\ \frac{6 \cdot \sqrt{\sigma_{X \cdot Y}^2} \sqrt{f \cdot (f+1)}}{\sigma} & \text{otherwise} \end{cases}$$
(4)

$$\sigma_{X\cdot Y}^2 = (\sigma^2 + \mu^2) \cdot (\sigma_\epsilon^2 + \mu_\epsilon^2) - \mu^2 \cdot \mu_\epsilon^2$$
(5)

Since  $N_{\chi\epsilon}$  is symmetric, we have

$$a_L = \mu \cdot (\mu_{\epsilon} - 3 \cdot \sigma_{\epsilon}) - \frac{\Omega}{2} \qquad \qquad a_H = \mu \cdot (\mu_{\epsilon} + 3 \cdot \sigma_{\epsilon}) + \frac{\Omega}{2} \qquad (6)$$

Therefore the worst-case suppressing impact  $\Delta_S$  (for  $I_{\chi\epsilon}$ ) is

 $\Delta_S = |\operatorname{PC}(Q^S, 2f + 1, 0) - \operatorname{PC}(A_L \cup Q_L^S, 2f + 1, 0)|$ 

and the worst-case inflating impact  $\Delta_I$  is

$$\Delta_I = |\mathsf{PC}(Q^I, 2f + 1, 0) - \mathsf{PC}(A_H \cup Q^I_H, 2f + 1, 0)|$$

These values are useful since for any other honest quorum Q' and maximally suppressing (or inflating) attack  $A'_L(A'_H)$ , the impact of these attacks on Q' will be less than  $\Delta_S$  and  $\Delta_I$ .

Since we know that  $a_L \leq PC(A_L \cup Q_L^S, 2f+1, 0)$  and  $a_H \geq PC(A_H \cup Q_H^I, 2f+1, 0)$ , we only need to estimate the proximal consensus results for  $Q^S$  and  $Q^I$ . We observe that by the definition of  $Q^S$  and



Fig. 4. Evaluation results comparing the accuracy of PC and VC, as well as the PI and convex hull, respectively.

 $Q^I$ , selecting the mean of each quorum as the result minimizes the distances dist $(D = [x, Q^S]^{\text{norm}})$  and dist $(D = [x, Q^I]^{\text{norm}})$  between the result *x* and each honest output in the quorum.

Although choosing the mean of the worst-case quorums minimizes dist $(D = [x, Q^S]^{\text{norm}})$ , and therefore  $\alpha$  (Definition 4.2), it may not maximize  $P(x)^{\alpha}$ . However, since  $N_{\chi\epsilon}$  is uni-modal, the optimal x will be somewhere in the interval between the mean of  $Q^S$  (or  $Q^I$ ) and the mean of  $N_{\chi\epsilon}$ ,  $\mu \cdot \mu_{\epsilon}$ . This allows us to create the following bounds on the Byzantine impact:

$$\Delta_S \le |\mu \cdot \mu_{\epsilon} - a_L| \qquad \qquad \Delta_I \le |\mu \cdot \mu_{\epsilon} - a_H| \tag{7}$$

From this we derive bounds for  $\epsilon_L$  and  $\epsilon_H$  (Definition 2.1) solely in terms of distribution parameters and system parameter f:

$$\epsilon_L \le \left|\mu_{\epsilon} - \frac{a_L}{\mu}\right| \qquad \qquad \epsilon_H \le \left|\mu_{\epsilon} - \frac{a_H}{\mu}\right|$$
(8)

Notice from Equations (4)-(6), these bounds are expressed solely in terms of distribution parameters and system parameter f.

For a consumer of stream  $\chi$  receiving non-faulty outputs Q and faulty outputs  $Q_f$ , where  $|Q| \ge 2f + 1$ ,  $|Q_f| \le f$ , and  $n \ge 3f + 1$ ,  $PC(Q \cup Q_f, n, f) = v$  with confidence  $c_{\epsilon}$  (3) such that

$$v \in \left[ E(X \mid Q) \cdot (1 - \epsilon_L), \ E(X \mid Q) \cdot (1 + \epsilon_H) \right]$$

## **5 EVALUATION**

In this section, we evaluate the one-shot proximal consensus (PC) algorithm through repeated simulations,<sup>8</sup> comparing it with the approximate vector consensus (VC) algorithm from [32] on one-dimensional vectors.<sup>9</sup> We present two types of experiments, the first of which evaluates the median and maximum error under Byzantine and no attack scenarios. The second experiment evaluates the coverage of the prediction interval (PI) of PC and the convex hull coverage of VC. In all simulations, we did not make any timing assumptions and assumed the inter-replica network connection between VC replicas was synchronous. The first set of outputs provided by PC replicas was accepted regardless of how wide the resulting PI was. Results are statistically significant at a 99.9% confidence level, with a level of precision (error margin) e of  $\leq 1\%$  from the presented outcomes. The number of simulations  $n_0$  to produce these results are calculated by the following equation:  $n_0 = \frac{Z^2 \cdot \sigma^2}{e^2}$  [17], where Z = 3.09 is the Z-score and  $\sigma^2$  is the variance of an attribute(s) in

<sup>&</sup>lt;sup>8</sup>We focus on the one-shot PC variant; coordinated PC produces equal or better accuracy.

<sup>&</sup>lt;sup>9</sup>One-dimensional VC likely performs similarly to an approximate scalar consensus (e.g., [8, 13]), but we chose VC since it generalizes to higher dimensions.

the population. Consequently, the number of experimental runs for each data point in our results varies between 209 for  $\sigma_{\epsilon} = 0.02$  to 4503 for  $\sigma_{\epsilon} = 0.12$ .

Each simulation is comprised of one layer of n = 4f + 1 replicas where up to f replicas are Byzantine and a single client.<sup>10</sup> In each interval of the no-attack experiment, the client receives a set of n outputs from replicas generated by multiplying a true output x with n - f randomly generated error samples y, such that replica outputs are  $x \cdot y_1, \ldots x \cdot y_n$ . In the optimal attack experiment, the client receives n - f outputs and an additional f Byzantine outputs. We assume the strongest Byzantine attacker on both the PC and VC simulations that utilizes the noisy outputs of non-faulty replicas to maximally suppress or inflate the consensus output from the true output, whichever results in a higher percent error from the true output.

In the first simulation, since the client does not have prior parameters of the output distribution a priori, the client first generates prior parameters by iteratively updating a prior distribution using the Gaussian conjugate prior function with unknown parameters [27] over five independent PC rounds<sup>11</sup> comprised exclusively of n - f non-faulty replicas, which the error of the following (sixth) consensus round being used as an error sample for iteration *i* of  $n_0$  iterations, calculated using the expected standard deviation of Y ( $\sigma_{\epsilon}$ ).<sup>12</sup>

Figure 4a and 4b shows the median and maximum PC and VC percent error from the true output when under no Byzantine attack and Byzantine attack, respectively, as the standard deviation of the error distribution increases. The plotted maximum error of PC also considered the error during the five rounds in which the prior distribution was generated. Overall, in the no-attack scenario, our results show that the one-shot PC variant reduces the median percent error of VC by 56% - 65% and lowers the maximum percent error of VC by 23% - 30% over  $f = 1 \dots 4$ . In the Byzantine attack scenario, our results show that the one-shot PC variant reduces the median percent error of VC by 31% - 78% and lowers the maximum percent error of VC by 31% - 68% over  $f = 1 \dots 4$ .

Figure 4c compares the output of PC and VC to the true output after PC has converged on parameters over 500 rounds with non-faulty outputs sampled from  $X \cdot Y$  where  $X \sim \mathcal{N}(\mu = 294, \sigma = 10)$  and  $Y \sim \mathcal{N}(\mu = 1, \sigma = 0.06)$ , which is fewer rounds than the 839 repetitions run in our evaluations under the same parameters. The inferred parameters are then used as the prior for the response to each true output on the x-axis (100 outputs in total): each non-faulty output is the x-axis value multiplied by a sample from the error distribution. For the Byzantine attack scenario, an optimal attack of f outputs are selected instead. The blue and red shaded regions indicate the reported 68-95-99.7% PIs<sup>13</sup> for each PC output, and the green region indicates the convex hull at each VC output. The presented PIs are representations of the IG of one, two, and three standard deviations from the PC output. These results demonstrate that PC outputs and their PIs capture the true output even when the independent probability of the output is low.

## 6 RELATED WORK

The Byzantine Generals Problem [21] was first to influence a line of work that proved a distributed system can tolerate up to  $\frac{n-1}{3}$  faulty nodes in a complete network, where each pair of nodes are directly connected. This led to the development of traditional agreement protocols, known as *exact agreement*, which offered efficient algorithms to tolerate Byzantine faults (e.g., PBFT [6]) and crash

<sup>&</sup>lt;sup>10</sup>Although VC is presented as a 3f + 1 solution, for comparison purposes, the VC replica sets also contained 4f + 1 replicas. Additional non-faulty replicas only improve the accuracy of VC compared to a 3f + 1 replica set.

<sup>&</sup>lt;sup>11</sup>These rounds were initialized with (uninformative) prior distribution parameters  $\mu = 294$ ,  $\alpha = 1$ ,  $\beta = 1$ ,  $\nu = 1$ .

<sup>&</sup>lt;sup>12</sup>We conducted five iterative training rounds because our empirical evaluations under the specified configurations resulted in distribution parameters from n - f non-faulty outputs to closely match those from five iterative training rounds with an additional f Byzantine outputs.

<sup>&</sup>lt;sup>13</sup>The 68%-95%-99.7% PI is one, two, and three posterior standard deviations, centered on the PC output.

faults (e.g., Paxos [20]). Although many optimizations to agreement protocols [4, 18, 35] have been proposed to decrease consensus overhead and increase throughput, exact agreement protocols are only applicable in domains in which consistency is required, and applications in which approximate outputs are sufficient end up "overpaying" for fault-tolerance [9, 28].

The problem definition of *approximate agreement*, which proximal consensus provides, was first defined in The Weak Byzantine Generals Problem [19] but the first practical solution was presented by Dolev *et. al.* [13]. This work showed that approximate agreement on scalar values must satisfy two conditions: (1) all non-faulty replicas must eventually halt with outputs that are within  $\epsilon$  of each other, (2) the output of each non-faulty replica must be in the range of the initial values of the non-faulty replicas. When outputs are vectors, as presented in [32], condition (2) requires that the outputs of non-faulty replicas be constrained by the convex hull of the initial vector outputs of non-faulty replicas. Unfortunately, the area of the convex hull, including in the asynchronous case [10], or scalar range increases as non-faulty replicas diverge due to noise. The limitations of current approximate agreement and convex consensus solutions is two-fold: (1) the accuracy of the approximated output is not maximized (as shown in our evaluations), (2) there is no way to quantify the uncertainty of the approximated output but it also quantifies the uncertainty by computing the most likely output and by providing an IG on each consensus output.

Research in asymptotic agreement [22] enable replicated processes to eventually ensure values approach some limit. The primary mechanism for tolerating Byzantine replicas is to remove the f largest and f smallest outputs, where n > 2f. For n = 2f + 1 this mechanism is equivalent to taking the median of the received values, which is similar to the Tverberg point in one dimension [16] in our simulated vector consensus approach because we made no timing assumptions. Similarly, In-ConcReTeS [15] requires clients to define availability and freshness requirements and computes the median output if replicas provide inconsistent outputs. In Figures 4a and 4b, we demonstrate the median selected can be manipulated and is not necessarily the most accurate approach.

Optimistic BFT [7, 36] is a BFT event-streaming solution that operates with continuous one-way messaging as long as every computation round results in a quorum of 2f + 1 matching outputs. Unfortunately, even if an approximate output is available, inconsistent outputs will cause the system to stall until the inconsistency is resolved. Conversely, the consumers in proximal consensus can define an acceptable interval width in which a proximal consensus output based on inconsistent outputs can be accepted. Similarly, ASPAS [34] leverages two concurrent phases: frontend and backend. The frontend phase lets clients query directly from one appserver, and the backend phase enables appservers to coordinate their operation log via a BFT protocol. However, clients may have to rollback if the appserver in which they queried is Byzantine, whereas the influence of Byzantine replicas is always bounded by the least likely f non-faulty replicas or the AIW the client specifies.

Igor [24] executes each execution path in parallel when replicas produce inconsistent outputs until the correct path is determined, at which point the invalid paths are terminated. Instead, the hybrid configuration of proximal consensus allows the system to continue processing while bounding Byzantine influence in the one-shot variant, where divergence between non-faulty replicas is eventually corrected by replicas also running coordinated PC.

Approximate agreement in consensus resilient control [25] requires the voter to identify when values are sufficiently close for the outputs to be accepted. However, since the paper discusses the difficulty of doing so, it proposes to alternatively have replicas first reach agreement on the sensed values or to agree on the state update before presenting the outputs to the voter. We believe proximal consensus would be useful here.

## 7 CONCLUSION

Proximal consensus (PC) computes the statistically most likely output conditioned on the similarity relationship between a set of outputs while also bounding the influence of Byzantine attackers to within the an interval proportional to the variance of non-faulty outputs. In this paper, our simulations show a significant increase in accuracy compared to a Tverberg-based vector consensus (VC) protocol, we give analytical bounds on the maximal impact by Byzantine attackers, and compare the interval guarantee and convex hull guarantee of PC and VC. Finally, we provide asymptotic run-time complexities and show PC is significantly more efficient than convex hull-based protocols in higher dimensions.

## REFERENCES

- Waseem Abbas, Mudassir Shabbir, Jiani Li, and Xenofon Koutsoukos. 2022. Resilient distributed vector consensus using centerpoint. *Automatica* 136 (2022), 110046. https://doi.org/10.1016/j.automatica.2021.110046
- [2] Mohammad Ahsanullah, BM Golam Kibria, and Mohammad Shakil. 2014. Normal and student's t distributions and their applications. Vol. 4. Springer.
- [3] José M Bernardo and Adrian FM Smith. 2009. Bayesian theory. Vol. 405. John Wiley & Sons.
- [4] Alysson Bessani, Joao Sousa, and Eduardo EP Alchieri. 2014. State machine replication for the masses with BFT-SMART. In 2014 44th Annual IEEE/IFIP International Conference on Dependable Systems and Networks. IEEE, 355–362.
- [5] Sergey Blok, Douglas Medin, and Daniel Osherson. 2003. Probability from similarity. In AAAI Spring Symposium on Logical Formalization of Commonsense Reasoning. 36–42.
- [6] Miguel Castro and Barbara Liskov. 2002. Practical Byzantine Fault Tolerance and Proactive Recovery. ACM Transactions on Computer Systems (2002). https://doi.org/10.1145/571637.571640
- [7] Hua Chai and Wenbing Zhao. 2014. Byzantine fault tolerant event stream processing for autonomic computing. In 2014 IEEE 12th International Conference on Dependable, Autonomic and Secure Computing. IEEE, 109–114.
- [8] Bernadette Charron-Bost, Matthias Függer, and Thomas Nowak. 2015. Approximate consensus in highly dynamic networks: The role of averaging algorithms. In Automata, Languages, and Programming: 42nd International Colloquium, ICALP 2015, Kyoto, Japan, July 6-10, 2015, Proceedings, Part II 42. Springer, 528–539.
- [9] Pierre Civit, Seth Gilbert, Rachid Guerraoui, Jovan Komatovic, Anton Paramonov, and Manuel Vidigueira. 2023. All Byzantine Agreement Problems are Expensive. arXiv preprint arXiv:2311.08060 (2023).
- [10] Andrei Constantinescu, Diana Ghinea, Roger Wattenhofer, and Floris Westermann. 2023. Meeting in a Convex World: Convex Consensus with Asynchronous Fallback. Cryptology ePrint Archive (2023).
- [11] Per-Erik Danielsson. 1980. Euclidean distance mapping. Computer Graphics and image processing 14, 3 (1980), 227-248.
- [12] Philip J Davis. 1959. Leonhard euler's integral: A historical profile of the gamma function: In memoriam: Milton abramowitz. *The American Mathematical Monthly* 66, 10 (1959), 849–869.
- [13] Danny Dolev, Nancy A. Lynch, Shlomit S. Pinter, Eugene W. Stark, and William E. Weihl. 1986. Reaching Approximate Agreement in the Presence of Faults. J. ACM 33, 3 (may 1986), 499–516. https://doi.org/10.1145/5925.5931
- [14] Paul Erdős, Alfréd Rényi, et al. 1960. On the evolution of random graphs. Publ. math. inst. hung. acad. sci 5, 1 (1960), 17–60.
- [15] Arpan Gujarati, Ningfeng Yang, and Björn B Brandenburg. 2022. In-ConcReTeS: Interactive Consistency meets Distributed Real-Time Systems, Again!. In 2022 IEEE Real-Time Systems Symposium (RTSS). IEEE, 211–224.
- [16] Sariel Har-Peled and Timothy Zhou. 2021. Improved Approximation Algorithms for Tverberg Partitions. In 29th Annual European Symposium on Algorithms (ESA 2021) (Leibniz International Proceedings in Informatics (LIPIcs), Vol. 204), Petra Mutzel, Rasmus Pagh, and Grzegorz Herman (Eds.). Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl, Germany, 51:1–51:15. https://doi.org/10.4230/LIPIcs.ESA.2021.51
- [17] Glenn D Israel. 1992. Determining sample size. (1992).
- [18] Ramakrishna Kotla, Lorenzo Alvisi, Mike Dahlin, Allen Clement, and Edmund Wong. 2007. Zyzzyva: speculative byzantine fault tolerance. In Proceedings of twenty-first ACM SIGOPS symposium on Operating systems principles. 45–58.
- [19] Leslie Lamport. 1983. The weak Byzantine generals problem. Journal of the ACM (JACM) 30, 3 (1983), 668–676.
- [20] Leslie Lamport et al. 2001. Paxos made simple. ACM Sigact News 32, 4 (2001), 18-25.
- [21] Leslie Lamport, Robert Shostak, and Marshall Pease. 2019. The Byzantine generals problem. In Concurrency: the works of leslie lamport. 203–226.
- [22] Heath J. LeBlanc and Xenofon D. Koutsoukos. 2011. Consensus in Networked Multi-Agent Systems with Adversaries. In Proceedings of the 14th International Conference on Hybrid Systems: Computation and Control (Chicago, IL, USA) (HSCC '11). Association for Computing Machinery, New York, NY, USA, 281–290. https://doi.org/10.1145/1967701.1967742

- [23] Shuo Liu, Nirupam Gupta, and Nitin H Vaidya. 2021. Approximate byzantine fault-tolerance in distributed optimization. In Proceedings of the 2021 ACM Symposium on Principles of Distributed Computing. 379–389.
- [24] Andrew Loveless, Ronald Dreslinski, Baris Kasikci, and Linh Thi Xuan Phan. 2021. IGOR: Accelerating byzantine fault tolerance for real-time systems with eager execution. In 2021 IEEE 27th Real-Time and Embedded Technology and Applications Symposium (RTAS). IEEE, 360–373.
- [25] Aleksandar Matovic, Rafal Graczyk, Federico Lucchetti, and Marcus Völp. 2023. Consensual Resilient Control: Stateless Recovery of Stateful Controllers. In 35th Euromicro Conference on Real-Time Systems (ECRTS 2023). Schloss Dagstuhl-Leibniz-Zentrum für Informatik.
- [26] Hammurabi Mendes and Maurice Herlihy. 2013. Multidimensional approximate agreement in byzantine asynchronous systems. In Proceedings of the forty-fifth annual ACM symposium on Theory of computing. 391–400.
- [27] Kevin P Murphy. 2007. Conjugate Bayesian analysis of the Gaussian distribution. def 1,  $2\sigma^2$  (2007), 16.
- [28] Edo Roth and Andreas Haeberlen. 2021. Do Not Overpay for Fault Tolerance!. In 2021 IEEE 27th Real-Time and Embedded Technology and Applications Symposium (RTAS). IEEE, 374–386.
- [29] Antonio Seijas-Macías and Amílcar Oliveira. 2012. An approach to distribution of the product of two normal variables. Discussiones Mathematicae Probability and Statistics 32, 1-2 (2012), 87–99.
- [30] Shang-Hua Teng. 1992. Points, spheres, and separators: a unified geometric approach to graph partitioning. Ph.D. Dissertation.
- [31] Helge Tverberg. 1966. A generalization of Radon's theorem. Journal of the London Mathematical Society 1, 1 (1966), 123–128.
- [32] Nitin H Vaidya and Vijay K Garg. 2013. Byzantine vector consensus in complete graphs. In Proceedings of the 2013 ACM symposium on Principles of distributed computing. 65–73.
- [33] Kacper Wardega, Max von Hippel, Roberto Tron, Cristina Nita-Rotaru, and Wenchao Li. 2023. Byzantine Resilience at Swarm Scale: A Decentralized Blocklist Protocol from Inter-robot Accusations. arXiv preprint arXiv:2301.06977 (2023).
- [34] Houssam Yactine, Ali Shoker, and Georges Younes. 2021. ASPAS: As Secure as Possible Available Systems. In IFIP International Conference on Distributed Applications and Interoperable Systems. Springer, 57–73.
- [35] Maofan Yin, Dahlia Malkhi, Michael K Reiter, Guy Golan Gueta, and Ittai Abraham. 2019. HotStuff: BFT consensus with linearity and responsiveness. In Proceedings of the 2019 ACM Symposium on Principles of Distributed Computing. 347–356.
- [36] Wenbing Zhao. 2016. Optimistic byzantine fault tolerance. International Journal of Parallel, Emergent and Distributed Systems 31, 3 (2016), 254–267.

## APPENDIX

Algorithm 1 Proximal consensus for univariate Gaussian distribution with unknown parameters

- ▶ Conjugate prior parameters of Gaussian distribution with unknown 1:  $\mu_0$ ,  $\nu$ ,  $\alpha$ ,  $\beta$ parameters [27] ▶ Combinations of size 2f + 1
- 2: for Each every quorum  $q \in [Q]^{2f+1}$  do
- $\mu', \nu, \alpha, \beta \leftarrow$  Update conjugate prior based on  $q, \mu_0, \nu, \alpha, \beta \rightarrow$  Equations 9-13 in Appendix 3:  $\sigma'^2 \leftarrow \frac{\beta}{\alpha - 1}$ ▶ Compute the mean of the distribution variance represented by an 4: inverse-gamma distribution [27]
- for Each  $x_i \in X$  where  $X = [\mu' 3\sqrt{\sigma'^2}, \mu' + 3\sqrt{\sigma'^2}]$  do  $\triangleright X$  is a discretized search space 5:
- $C_{(x_i,q,IG)} \leftarrow \text{Calculate conditional probability } P(x_i \mid q)$ ▶ Definition 4.2 6:
- 7. end for
- 8: end for
- 9: **return**  $(x_i, q), IG \in C$  s.t. max $(C) \rightarrow$  Return  $(x_i, q)$  most conditionally likely and the interval guarantee

A]	gorit	hm 2	Replica	<i>r</i> –One-s	hot P	roximal	Consensus
----	-------	------	---------	-----------------	-------	---------	-----------

1:	$\mu_0, \nu, \alpha, \beta$ > Conjugate prior parameters o	f Gaussian distribution with unknown
	parameters [27]	
2:	while $ Q  < 3f + 1    IG_{PC(Q, Q ,f)} < AIW$ do	▷ See Section 3
3:	$Q \leftarrow$ wait for additional inputs	$\triangleright Q$ is the received output set
4:	end while	
5:	$(x_r, q), IG \leftarrow PC(Q,  Q , f)$	⊳ See Algorithm 1
6:	Output $x_r$ , $IG$ > Output $x_r$ as the next structure of $x_r$	eam output and the interval guarantee
7:	$\mu', \nu, \alpha, \beta \leftarrow$ Update conjugate prior based on $q, \mu_0, \nu, \alpha_2$	$\beta \rightarrow$ Equations 9-13 in Appendix

Algorithm 3 Replica *r*–Coordinated Proximal Consensus

▷ Conjugate prior parameters of Gaussian distribution with unknown 1:  $\mu_0$ ,  $\nu$ ,  $\alpha$ ,  $\beta$ parameters [27] 2:  $Q' \leftarrow \text{Run BA on } Q$ ▶ Byzantine agreement algorithm on all proposed outputs Q 3:  $(x_r, q), IG \leftarrow PC(Q', |Q'|, f)$ ▶ See Algorithm 1 ▷ Client is guaranteed to receive n - f matching  $x_r$ 's 4: Broadcast  $x_r$  to client 5:  $\mu', \nu', \alpha', \beta' \leftarrow$  Update conjugate prior based on  $q, \mu_0, \nu, \alpha, \beta$ ▹ Equations 9-13 in Appendix 6: if t > t' then  $\triangleright$  *t* is current time, *t'* is next parameter update time  $(\hat{\mu}, \hat{\nu}, \hat{\alpha}, \hat{\beta})_t \leftarrow \text{Run BA on } \mu', \nu', \alpha', \beta' \triangleright \text{Byzantine agreement on posterior parameters for}$ 7: checkpoint t Broadcast  $(\hat{\mu}, \hat{\nu}, \hat{\alpha}, \hat{\beta})_t$ ▶ Send updated parameters to one-shot replicas 8: 9: end if

The univariate Gaussian conjugate update function [27] with unknown mean and variance expressed by the prior parameters of a normal-inverse gamma distribution  $\mu_0$ ,  $\nu$ ,  $\alpha$ ,  $\beta$ , sample mean  $\bar{x}$  (Equation 13), and number of observations *n*:

$$\mu' = \frac{\nu\mu_0 + nx}{\nu + n} \tag{9}$$

$$\begin{aligned}
\nu &= \nu + n \tag{10} \\
\alpha' &= \alpha + \frac{n}{2} \tag{11}
\end{aligned}$$

$$\beta' = \beta + \frac{1}{2} \sum_{i=1}^{n} (x_i - \bar{x})^2 + \frac{n\nu}{\nu + n} \frac{(\bar{x} - \mu_0)^2}{2}$$
(12)

Equation for sample mean given *N* observations on variable *X*:

$$\bar{x} = \frac{1}{N} \sum_{i=1}^{N} X_i \tag{13}$$

Mathematics derivation for computing  $P(X | q = [h_1, h_2, h_3])$ :

$$P(X = x \mid h_1 \cap h_2 \cap h_3)$$

$$=P(x)^{\zeta^{1-r}(n_1+n_2+n_3)}$$
(14)

$$= P(x)^{\zeta^{1-P(h_1|h_2 \cap h_3) \cdot P(h_2|h_3) \cdot P(h_3)}}$$
(15)

$$= P(x)^{\zeta^{1-P(h_1)\psi^{1-P(h_2\cap h_3)} \cdot P(h_2)Y \cdot P(h_3)}}$$
(16)

$$= P(x)^{\zeta^{1-P(h_1)\psi^{1-P(h_2|h_3)} \cdot P(h_3)} \cdot P(h_2)^{\gamma} \cdot P(h_3)}$$
(17)

$$= P(x)^{\zeta^{1-P(h_1)\psi^{1-P(h_2)Y \cdot P(h_3)} \cdot P(h_2)Y \cdot P(h_3)}$$
(18)

where 
$$\gamma = \Psi^{1-P(h_3)}$$
  $\zeta = \frac{1 - \sin([x, h_1, h_2, h_3])}{1 + \sin([x, h_1, h_2, h_3])}$   $\Psi = \frac{1 - \sin([h_1, h_2, h_3])}{1 + \sin([h_1, h_2, h_3])}$ 

Process to compute the similarity of candidate output *x* and quorum *q*. Given D = [x, q] and the dimensionality of the outputs *d*, we create a list of coordinate points of the value and its PDF:  $P = \{(p_1, \ldots, p_d, f(p, v)) | p \in D\}$  value using the Student-t PDF function that relies on the  $\Gamma$  function [12] and a degrees of freedom parameter *v* where  $v \to \infty$  signifies the distribution's convergence to a Gaussian distribution and is determined based on the number of observations [2] where:

$$f(x,v) = \frac{\Gamma(\frac{\nu+1}{2})}{\sqrt{\pi\nu}\Gamma(\frac{\nu}{2})} (1 + \frac{x^2}{\nu})^{-\frac{\nu+1}{2}}$$
(19)

We then use the min-max normalization function independently on each index of P to normalize the values on a [0, 1] scale:

$$P_i^{\text{norm}} = \forall_{x \in P_i} \frac{x - \min(P_i)}{\max(P_i) - \min(P_i)}$$
(20)

where  $P_i$  is the collection of all values from index *i* from *P*. A generalized similarity function is:

$$sim(P^{norm}) = \frac{1}{1 + dist(P^{norm})}$$
(21)

where dist(P) is the cumulative d + 1 Euclidean distance [11] metric between each normalized coordinate pair  $P^{\text{norm}}$ :

$$d(P^{\text{norm}}) = \sqrt{\forall_{p,q \in P} \sum_{i=1}^{d+1} (p_i - q_i)^2}$$
(22)