

# A Lower Bound on the Competitive Ratio of the Permutation Algorithm for Online Facility Assignment on a Line

Tsubasa Harada \*

**Abstract:** In the online facility assignment on a line (OFAL) with a set  $S$  of  $k$  servers and a capacity  $c : S \rightarrow \mathbb{N}$ , each server  $s \in S$  with a capacity  $c(s)$  is placed on a line and a request arrives on a line one-by-one. The task of an online algorithm is to irrevocably assign a current request to one of the servers with vacancies before the next request arrives. An algorithm can assign up to  $c(s)$  requests to each server  $s \in S$ .

In this paper, we show that the competitive ratio of the permutation algorithm [6, 1] is at least  $k + 1$  for OFAL where the servers are evenly placed on a line. This disproves the result that the permutation algorithm is  $k$ -competitive by Ahmed et al. [1].

**Key Words:** Online algorithm, Competitive analysis, Online facility assignment, Online transportation problem, Online facility assignment on a line.

## 1 Introduction

### 1.1 Background

The *online facility assignment* (OFA) or *online transportation* problem was introduced by Kalyanasundaram and Pruhs [8]. In this problem, an online algorithm is given a set  $S$  of  $k$  servers and a capacity  $c : S \rightarrow \mathbb{N}$ . Then, the algorithm receives  $n$  requests one-by-one in an online fashion. The task of an online algorithm is to assign each request immediately to one of the  $k$  servers. Note that the number of requests  $n$  is at most the sum of each server's capacity, i.e.,  $n \leq \sum_{s \in S} c(s)$ . The maximum number of requests that can be assigned to a server  $s \in S$  is  $c(s)$ , and the assignment cannot be changed later once it has been decided. The cost of assigning a request to a server is determined by the distance between them. The goal of the problem is to minimize the sum of the costs of matching  $n$  requests.

A line is considered to be one of the most interesting metric space for this type of problem for decades [7, 9, 2, 3, 1, 5, 4]. We refer to a variant of OFA as *OFA on a line* (OFAL) where all servers and requests are placed on a line.

Ahmed et al. [1] dealt with classical competitive analysis for OFAL under the assumption that the servers are evenly placed and each server has the same capacity. We refer to the setting as  $\text{OFAL}_{eq}$ . Ahmed et al. [1] showed (with rough proofs) that the natural greedy algorithm is  $4k$ -competitive and the *permutation* algorithm<sup>1</sup> is  $k$ -competitive. On the other hand, Itoh et al. [5] analyzed the competitive ratio for  $\text{OFAL}_{eq}$  with small  $k \geq 2$ . They showed that (i) for  $k = 2$ , the greedy algorithm is 3-competitive and best possible, and (ii) for  $k = 3, 4$ , and 5, the competitive ratio of any algorithm is at least  $1 + \sqrt{6} > 3.449$ ,  $\frac{4+\sqrt{73}}{3} > 4.181$ , and  $\frac{13}{3} > 4.333$ , respectively.

---

\*Department of Mathematical and Computing Science, Tokyo Institute of Technology, 2-12-1 Ookayama, Meguro-ku, Tokyo 152-8550, Japan. Email: harada.t.ak@m.titech.ac.jp.

<sup>1</sup>Ahmed et al. call this algorithm *Optimal-fill*. The “optimal-fill” algorithm is essentially the same as the permutation algorithm that has already been proposed by Kalyanasundaram and Pruhs [6].

However, when  $k = 2$ , there is a discrepancy between Ahmed et al.'s result (R1) that the permutation algorithm is 2-competitive [1] and Itoh et al.'s result (R2) that the competitive ratio of any algorithm for OFAL<sub>eq</sub> is at least 3 [5]. There has been no research that resolve the contradiction between (R1) and (R2).

## 1.2 Our contribution

In this paper, we will show that the competitive ratio of the permutation algorithm [6] is in fact at least  $k + 1$  for OFAL<sub>eq</sub> (Theorem 1.1). This result disproves the claim that the permutation algorithm is  $k$ -competitive reported by Ahmed et al. [1] and resolves the contradiction between (R1) and (R2).

**Theorem 1.1.** *For OFAL<sub>eq</sub>, the competitive ratio of the permutation algorithm is at least  $k + 1$ .*

## 2 Preliminary

### 2.1 Online Facility Assignment on a Line

We define the online facility assignment problem on a line with  $k$  servers and a capacity  $c$  which is denoted by OFAL( $k, c$ ). Let  $S = \{s_1, \dots, s_k\} \subseteq \mathbb{R}$  be the set of  $k$  servers,  $\sigma = r_1 \dots r_n$  ( $r_i \in \mathbb{R}$  for  $1 \leq i \leq n \leq \sum_{s \in S} c(s)$ ) be a request sequence and  $c : S \rightarrow \mathbb{N}$  be a capacity. We can assign up to  $c(s)$  requests to each server  $s \in S$ .

The set  $S$  is given to an online algorithm in advance, while requests are given one-by-one from  $r_1$  to  $r_n$ . At any time of the execution of an algorithm, a server is called *free* if the number of requests assigned to it is less than its capacity, and *full* otherwise. When a request  $r_i$  is revealed, an online algorithm must assign  $r_i$  to one of the free servers. If  $r_i$  is assigned to  $s_j$ , the pair  $(r_i, s_j)$  is added to the current matching and the cost  $|r_i - s_j|$  is incurred for this pair. Once the pair  $(r_i, s_j)$  has been added, an algorithm cannot remove this pair later., The cost of the assignment is the sum of the costs of all the pairs contained in it. The goal of online algorithms is to minimize the cost of the final matching.

In this paper, we only deal with the case where all servers are evenly placed on a line. Without loss of generality, we assume that  $S = \{s_1, \dots, s_k\} = \{0, \dots, k - 1\}$ . For the case where each server has the same capacity, i.e.,  $c(s) = \ell$  for each  $s \in S$ , we use OFAL<sub>eq</sub>( $k, \ell$ ) to denote that problem.

### 2.2 Notations and Terminologies

For an (online/offline) algorithm ALG for OFAL<sub>eq</sub>( $k, \ell$ ) and a request sequence  $\sigma = r_1 \dots r_n$ , we use  $\text{ALG}(r_i; \sigma)$  to denote the cost of ALG incurred to assign  $r_i$  when ALG processes  $\sigma$ . For a subsequence  $\tau = r_{i_1} \dots r_{i_m}$  of  $\sigma$ , we use  $\text{ALG}(\tau; \sigma)$  to denote the total cost of ALG incurred to assign each  $r_{i_h}$  to the server  $s_{\text{alg}}(r_{i_h}; \sigma)$ , i.e.,

$$\text{ALG}(\tau; \sigma) = \sum_{h=1}^m \text{ALG}(r_{i_h}; \sigma).$$

When  $\tau = \sigma$ , we simply write  $\text{ALG}(\sigma)$  instead of  $\text{ALG}(\sigma; \sigma)$ .

We use OPT to denote the optimal *offline* algorithm, i.e., OPT knows the entire sequence  $\sigma = r_1 \dots r_n$  in advance and *minimizes* the total cost to assign all requests from  $r_1$  to  $r_n$ .

To evaluate the performance of an online algorithm ALG, we use the (strict) competitive ratio. We say that ALG is  $\alpha$ -competitive for OFAL<sub>eq</sub>( $k, \ell$ ) if  $\text{ALG}(\sigma) \leq \alpha \cdot \text{OPT}(\sigma)$  for any request

sequence  $\sigma$  for  $\text{OFAL}_{eq}(k, \ell)$ . For  $\text{OFAL}_{eq}(k, \ell)$ , the competitive ratio  $\mathcal{R}_{k, \ell}(\text{ALG})$  of ALG is defined to be the infimum of  $\alpha \geq 1$  such that ALG is  $\alpha$ -competitive for  $\text{OFAL}_{eq}(k, \ell)$ , i.e.,

$$\mathcal{R}_{k, \ell}(\text{ALG}) = \inf\{\alpha \geq 1 : \text{ALG is } \alpha\text{-competitive for } \text{OFAL}_{eq}(k, \ell)\}.$$

If ALG is not  $\alpha$ -competitive for any  $\alpha \geq 1$ , then we define  $\mathcal{R}_{k, \ell}(\text{ALG})$  to be  $\infty$ .

### 2.3 Permutation Algorithm

In this subsection, we define the permutation algorithm (denoted by PERM) for  $\text{OFAL}(k, c)$  [6, 1]. Fix any request sequence  $\sigma = r_1 \dots r_n$  for  $\text{OFAL}(k, c)$  arbitrarily and let  $M_i = \{(r_j, s^{(j)})\}_{j=1}^i$  be an optimal assignment of  $r_1 \dots r_i$ . For  $s \in S$ , we use  $n_i(s)$  to denote the number of  $j$  such that  $s^{(j)} = s$ , i.e., the number of requests assigned to  $s$  in  $M_i$ . It is known that there is a sequence of optimal assignments  $\{M_i\}_{i=1}^n$  that satisfies the following property [6]: for each  $i = 1, \dots, n$ ,

$$\text{there is a unique } s_1^* \text{ such that } n_i(s_1^*) = n_{i-1}(s_1^*) + 1 \text{ and } n_i(s) = n_{i-1}(s) \text{ for any } s \neq s_1^*. \quad (2.1)$$

Note that  $n_0(s) = 0$  for each  $s \in S$ . Since this property holds for optimal assignments, we can define PERM as follows: when an  $i$ -th request  $r_i$  is revealed, PERM computes the optimal assignment  $M_i$  of  $r_1 \dots r_i$  that satisfies (2.1) and then assigns  $r_i$  to  $s_i^*$ .

## 3 The Proof of Theorem 1.1

In this section, we will prove Theorem 1.1. To begin with, we show the following proposition.

**Proposition 3.1.** *Let ALG be any online algorithm for  $\text{OFAL}_{eq}(k, \ell)$  such that  $\mathcal{R}_{k, 1}(\text{ALG}) < \infty$ . Then,  $\mathcal{R}_{k, \ell}(\text{ALG}) \geq \mathcal{R}_{k, 1}(\text{ALG})$  for any  $\ell \in \mathbb{N}$ .*

**Proof:** If there exists a request sequence  $\sigma$  for  $\text{OFAL}_{eq}(k, \ell)$  such that  $\text{ALG}(\sigma) > 0$  and  $\text{OPT}(\sigma) = 0$ , then  $\text{ALG}(\sigma) \leq \alpha \cdot \text{OPT}(\sigma)$  does not hold for any  $\alpha \geq 1$ , i.e.,  $\mathcal{R}_{k, \ell}(\text{ALG}) = \infty$ . Then, we have  $\mathcal{R}_{k, 1}(\text{ALG}) < \mathcal{R}_{k, \ell}(\text{ALG})$ . In the rest of the proof, consider the case where  $\text{ALG}(\sigma) = 0$  if  $\text{OPT}(\sigma) = 0$  for any  $\sigma$ .

Let  $\mathcal{R}_{k, 1}(\text{ALG})$  be  $\alpha$ . By the definition of the competitive ratio, there exists a request sequence  $\sigma' = r'_1, \dots, r'_k$  such that  $\text{ALG}(\sigma') \geq \alpha \cdot \text{OPT}(\sigma')$ . Let us define a request sequence  $\sigma = r_1, \dots, r_{k\ell}$  for  $\text{OFAL}_{eq}(k, \ell)$  such that  $\text{ALG}(\sigma) \geq \alpha \cdot \text{OPT}(\sigma)$  as follows: for each  $i = 1, \dots, k$ , we first give  $\ell - 1$  requests on  $s_i$  and then give  $k$  requests from  $r'_1$  to  $r'_k$ . Since  $\text{OPT}(r_1 \dots r_{k(\ell-1)}; \sigma) = 0$ , we have  $\text{ALG}(r_1 \dots r_{k(\ell-1)}; \sigma) = 0$ . Hence, both ALG and OPT can assign only one request to each server after processing  $r_{k(\ell-1)}$ . Thus, we obtain

$$\text{ALG}(\sigma) = \text{ALG}(\sigma') \geq \alpha \cdot \text{OPT}(\sigma') = \alpha \cdot \text{OPT}(\sigma).$$

and this implies that  $\mathcal{R}_{k, \ell}(\text{ALG}) \geq \alpha = \mathcal{R}_{k, 1}(\text{ALG})$ . ■

Now we are ready to prove Theorem 1.1. We will show that there exists a request sequence  $\sigma = r_1 \dots r_k$  for  $\text{OFAL}_{eq}(k, 1)$  such that

$$\text{PERM}(\sigma) \geq (k + 1 - \epsilon)\text{OPT}(\sigma)$$

for any  $\epsilon > 0$ . By Proposition 3.1, this implies  $\mathcal{R}_{k, \ell}(\text{PERM}) \geq k + 1$ . We consider the following two cases: (1)  $k$  is even and (2)  $k$  is odd.

(1)  $k$  is even

Define  $\sigma = r_1 \dots r_k$  as follows: for  $j = 1, \dots, k/2$ , let

$$\begin{aligned} r_{2j-1} &= s_{k/2+j} - \frac{1}{2} - \epsilon_{2j-1} \text{ and} \\ r_{2j} &= s_{k/2-j+1} - \frac{1}{2} + \epsilon_{2j}, \end{aligned}$$

where

$$\epsilon_i = \begin{cases} \frac{\epsilon}{8} \cdot 2^{i-k} & i < k, \\ \frac{1}{2} & i = k. \end{cases} \quad (3.1)$$

Recall that  $s_i = i-1$  for  $i = 1, \dots, k$ . By the definition of PERM, we have that for  $j = 1, \dots, k/2$ , PERM assigns  $r_{2j-1}$  to  $s_{k/2-j+1}$  and  $r_{2j}$  to  $s_{k/2+j}$ . In addition, we consider the offline algorithm OFF that assigns  $r_{2j-1}$  to  $s_{k/2+j}$  and  $r_{2j}$  to  $s_{k/2-j+1}$ . Then, we have

$$\begin{aligned} \text{PERM}(\sigma) &= |r_1 - s_{k/2}| + |r_2 - s_{k/2+1}| + \dots + |r_{k-1} - s_1| + |r_k - s_k| \\ &\geq \left(\frac{1}{2} - \epsilon_1\right) + \left(\frac{3}{2} - \epsilon_2\right) + \dots + \left(\frac{2k-3}{2} - \epsilon_{k-1}\right) + (k-1) \\ &= \frac{(k-1)(k+1)}{2} - (\epsilon_1 + \dots + \epsilon_{k-1}) \\ &= \frac{(k-1)(k+1)}{2} - \frac{\epsilon}{8} (2^{1-k} + \dots + 2^{-1}) \\ &\geq \frac{(k-1)(k+1)}{2} - \frac{\epsilon}{8} \end{aligned}$$

and

$$\begin{aligned} \text{OPT}(\sigma) &\leq \text{OFF}(\sigma) \\ &= |r_1 - s_{k/2+1}| + |r_2 - s_{k/2}| + \dots + |r_{k-1} - s_{k-1}| + |r_k - s_1| \\ &\leq \left(\frac{1}{2} + \epsilon_1\right) + \left(\frac{1}{2} + \epsilon_2\right) + \dots + \left(\frac{1}{2} + \epsilon_{k-1}\right) + 0 \\ &\leq \frac{k-1}{2} + \frac{\epsilon}{8}. \end{aligned}$$

Therefore, we finally get

$$\begin{aligned} \frac{\text{PERM}(\sigma)}{\text{OPT}(\sigma)} &\geq \frac{\text{PERM}(\sigma)}{\text{OFF}(\sigma)} \geq \frac{\frac{(k-1)(k+1)}{2} - \frac{\epsilon}{8}}{\frac{k-1}{2} + \frac{\epsilon}{8}} = k + 1 - \frac{(k+2)\frac{\epsilon}{8}}{\frac{k-1}{2} + \frac{\epsilon}{8}} \\ &\geq k + 1 - \frac{\epsilon}{4} \cdot \frac{k+2}{k-1} \geq k + 1 - \epsilon. \end{aligned}$$

## (2) $k$ is odd

Define  $\sigma = r_1 \dots r_k$  as follows: for  $j = 1, \dots, (k+1)/2$ , let

$$\begin{aligned} r_{2j-1} &= s_{(k-1)/2+j} + \frac{1}{2} - \epsilon_{2j-1} \text{ and} \\ r_{2j} &= s_{(k-1)/2-j+1} + \frac{1}{2} + \epsilon_{2j}, \end{aligned}$$

where we do not apply the formula  $r_{2j} = s_{(k-1)/2-j+1} + \frac{1}{2} + \epsilon_{2j}$  for  $j = (k+1)/2$ . Note that  $\{\epsilon_i\}_{i=1}^k$  is defined by the formula (3.1). By the definition of PERM, for  $j = 1, \dots, (k+1)/2$ , PERM

assigns  $r_{2j-1}$  to  $s_{(k-1)/2-j+1}$  and  $r_{2j}$  to  $s_{(k-1)/2+j}$ . In addition, we consider the offline algorithm OFF that assigns  $r_{2j-1}$  to  $s_{(k-1)/2+j}$  and  $r_{2j}$  to  $s_{(k-1)/2-j+1}$ . Thus, similarly to the case (1), we can show that

$$\begin{aligned} \text{PERM}(\sigma) &\geq \frac{(k-1)(k+1)}{2} - \frac{\epsilon}{8}, \\ \text{OPT}(\sigma) &\leq \text{OFF}(\sigma) \leq \frac{k-1}{2} + \frac{\epsilon}{8}, \end{aligned}$$

and then  $\text{PERM}(\sigma)/\text{OPT}(\sigma) \geq k+1 - \epsilon$ . This completes the proof.

## 4 Concluding Remarks and Open Problems

In this paper, we showed that the competitive ratio of PERM is at least  $k+1$  for  $\text{OFAL}_{eq}(k, \ell)$ . We conjecture that the competitive ratio of PERM is exactly  $k+1$ , but we have not yet been able to prove it. Furthermore, since we found that PERM is not  $k$ -competitive, it is possible that the competitive ratio of PERM depends on a capacity  $\ell$ .

## References

- [1] Abu Reyan Ahmed, Md Saidur Rahman, and Stephen Kobourov. Online facility assignment. *Theoretical Computer Science*, 806:455–467, 2020.
- [2] Antonios Antoniadis, Neal Barcelo, Michael Nugent, Kirk Pruhs, and Michele Scquizzato. A  $o(n)$ -competitive deterministic algorithm for online matching on a line. In *International Workshop on Approximation and Online Algorithms*, pages 11–22. Springer, 2014.
- [3] Antonios Antoniadis, Carsten Fischer, and Andreas Tönnis. A collection of lower bounds for online matching on the line. In *LATIN 2018: Theoretical Informatics: 13th Latin American Symposium, Buenos Aires, Argentina, April 16-19, 2018, Proceedings 13*, pages 52–65. Springer, 2018.
- [4] Tsubasa Harada, Toshiya Itoh, and Shuichi Miyazaki. Capacity-insensitive algorithms for on-line facility assignment problems on a line. *online ready in Discrete Mathematics, Algorithms and Applications*, 2023.
- [5] Toshiya Itoh, Shuichi Miyazaki, and Makoto Satake. Competitive analysis for two variants of online metric matching problem. *Discrete Mathematics, Algorithms and Applications*, 13(06):2150156, 2021.
- [6] Bala Kalyanasundaram and Kirk Pruhs. Online weighted matching. *Journal of Algorithms*, 14(3):478–488, 1993.
- [7] Bala Kalyanasundaram and Kirk Pruhs. On-line network optimization problems. *Online algorithms: the state of the art*, pages 268–280, 2005.
- [8] Bala Kalyanasundaram and Kirk R Pruhs. The online transportation problem. *SIAM Journal on Discrete Mathematics*, 13(3):370–383, 2000.
- [9] Elias Koutsoupias and Akash Nanavati. The online matching problem on a line. In *International Workshop on Approximation and Online Algorithms*, pages 179–191. Springer, 2003.