Hitting Meets Packing: How Hard Can it Be?

Jacob Focke¹, Fabian Frei¹, Shaohua Li¹, Dániel Marx¹, Philipp Schepper¹, Roohani Sharma², and Karol Węgrzycki^{2,3}

¹CISPA Helmholtz-Center for Information Security ²Max Planck Institute for Informatics, SIC ³Saarland University

Abstract

We study a general family of problems that form a common generalization of classic hitting (also referred to as covering or transversal) and packing problems. An instance of X-HITPACK asks: Can removing k (deletable) vertices of a graph G prevent us from packing ℓ vertex-disjoint objects of type X? This problem captures a spectrum of problems with standard hitting and packing on opposite ends. Our main motivating question is whether the combination X-HITPACK can be significantly harder than these two base problems. Already for one particular choice of X, this question can be posed for many different complexity notions, leading to a large, so-far unexplored domain at the intersection of the areas of hitting and packing problems.

At a high level, we present two case studies: (1) X being all cycles, and (2) X being all copies of a fixed graph H. In each, we explore the classical complexity as well as the parameterized complexity with the natural parameters $k + \ell$ and treewidth. We observe that the combined problem can be drastically harder than the base problems: for cycles or for H being a connected graph on at least 3 vertices, the problem is $\Sigma_2^{\rm P}$ -complete and requires double-exponential dependence on the treewidth of the graph (assuming the Exponential-Time Hypothesis). In contrast, the combined problem admits qualitatively similar running times as the base problems in some cases, although significant novel ideas are required. For X being all cycles, we establish a $2^{\text{poly}(k+\ell)} \cdot n^{O(1)}$ algorithm using an involved branching method, for example. Also, for X being all edges (i.e., $H = K_2$; this combines VERTEX COVER and MAXIMUM MATCHING) the problem can be solved in time $2^{\text{poly}(\text{tw})} \cdot n^{O(1)}$ on graphs of treewidth tw. The key step enabling this running time relies on a combinatorial bound obtained from an algebraic (linear delta-matroid) representation of possible matchings.

1 Introduction

In the combinatorial optimization literature, many algorithmic problems can be classified into one of two dual classes: either as a packing problem or as a hitting problem. In *packing problems*, the goal is to find a large pairwise independent collection of objects of certain type. For example, one of the most-studied problems, MAXIMUM MATCHING, can be described as finding a pairwise vertex-disjoint collection of at least ℓ edges. Network flow problems require finding a large collection of edge-disjoint paths from *s* to *t*. More generally, one can define the *X*-PACKING problem for any type *X* of objects. In *hitting problems* (sometimes referred to as *transversal* or *covering* problems), the task is to find a small set of elements that *hits* (i.e., intersects) every object of a certain type *X*. For example, the VERTEX COVER problem can be described as finding a set of at most *k* vertices that intersect every edge (i.e., contains at least one endpoint of each edge). The minimum *s*-*t* cut problem can be interpreted as finding a set of edges that intersects every *s*-*t* path. A quick note on terminology is in order here. The name of a covering problem typically refers to the type of objects used to cover, rather than the type of objects being covered. For example, CYCLE COVER usually refers to the problem of covering the vertices

A table of contents is provided on page 84 at the end of this work.

of the graph with few (not necessarily disjoint) cycles, and *not* the problem of hitting every cycle with a small set of vertices (which is usually called FEEDBACK VERTEX SET). For this reason, we prefer to use X-HITTING for the problem where the task is to find a set of elements or vertices that intersect every object of type X.

There is a well-known duality phenomenon connecting hitting and packing problems. If there are ℓ disjoint objects of type X, then clearly we need at least ℓ elements to hit every such object. In other words, the optimum of X-HITTING is at least the optimum of X-PACKING. For some type of objects (such as edges in bipartite graphs and *s*-*t* paths), celebrated duality theorems demonstrate that there is always equality between the two optimum values. These duality results and their variants underlie many of the polynomial-time exact algorithms in combinatorial optimization. For problems where the two optimum values do not coincide, it is natural to ask how large the gap can be. Erdős and Pósa [24] showed that if ℓ is the maximum number of vertex-disjoint cycles, then all the cycles can be hit by a set of $k = O(\ell \log \ell)$ vertices. More generally, we say that a type X of objects has the *Erdős–Pósa property* if the hitting optimum can be bounded by a function of the packing optimum. For example, it is known that the Erdős–Pósa property holds for undirected cycles passing through a set S [39, 67] or directed cycles [71], but it does not hold for cycles of odd length [70].

In this paper, we study a different, algorithmic, question that connects hitting and packing problems. Let X be a type of objects in graphs, and consider the following problem. Given a graph G and integers k and ℓ , the task is to find a set S of at most k vertices such that G - S does not contain ℓ disjoint copies of objects of type X. This unified formulation captures both X-HITTING and X-PACKING problems: for $\ell = 1$, it asks if every object can be hit with k vertices; for k = 0, it asks whether it is impossible to find ℓ disjoint objects. Therefore, X-HITPACK is at least as hard as X-HITTING and the complement of X-PACKING. Note that deterministic algorithms, on which we focus in this paper, always work for the complement of a problem as well. The main meta-question that we explore is how hard such a combination of two problems may become:

If some type of algorithm exists for both X-HITTING and X-PACKING, then is there such an algorithm for X-HITPACK as well?

The main message of this paper is that the formulation of this question leads to a whole new unexplored continent of interesting and challenging questions. As we shall see, in some settings the combined problem is indeed strictly harder, while in other settings a qualitatively similar algorithm can be obtained for the combined problem, albeit only after developing significantly more involved techniques.

To make the problem statement more robust, we extend the problem by assuming that the input graph contains a set U of undeletable vertices and the solution S has to be disjoint from U. Such undeletable vertices may be needed to express problems where the objects X are, say, *s*-*t* paths or paths between terminals, and we do not want to allow the deletion of terminals. Note that this generalization makes our algorithmic results slightly stronger, while it makes the lower bound results slightly weaker. Formally, for a type X of objects, the problem is defined as follows.

<i>X-</i> НітРаск	
Input:	Graph G, set $U \subseteq V(G)$, integers k and ℓ
Question:	Is there a set $S \subseteq V(G) \setminus U$ of size $\leq k$ such that $G - S$
	does not contain ℓ vertex-disjoint objects of type X ?

There are two ways of looking at the X-HITPACK problem. It can be considered as a *weaker* version of hitting: the solution does not have to destroy all sets in X, but up to ℓ disjoint sets are allowed to survive in G - S. An alternative view is to interpret it as a more stable version of packing. We have to decide not only whether ℓ disjoint objects exist but whether the graph may lose this property even if up to k arbitrary vertices are removed. Such a robust version of packability is clearly desirable in many



Figure 1.1: The areas of hitting and packing problems intersect in combinatorial duality and Erdős–Pósa property results, and in the algorithmic study of combined hitting and packing problems.

situations, and the problem of detecting this property is precisely the complement of X-HITPACK. Frei et al. [31] recently initiated a systematic complexity study of a related stability notion, where a graph is *vertex-stable* if some parameter cannot change upon deletion of a single vertex. Our X-HITPACK models an even more robust notion of stability, however, since multiple vertices may be deleted depending on the input.

Returning to the overarching question how hard X-HITPACK may become compared to X-HITTING, and X-PACKING, let us start with examples where all of them are polynomial-time solvable. If X is simply the set of edges of a bipartite graph, then the hitting problem (VERTEX COVER) and the packing problem (MAXIMUM MATCHING) are both known to be polynomial-time solvable and the size of the minimum vertex cover and the maximum matching are known to be the same. Let d be this value. A set of k vertices can decrease the size of the maximum matching only by at most k, thus the answer is no if $d-k \ge \ell$. Otherwise, if $d-k < \ell$, then deleting any k vertices of a minimum vertex cover decreases the size of a maximum matching by k (as deleting d - k further vertices of the vertex cover decreases this size to 0), showing that the answer is yes. This argument works for other objects where exact duality theorems are known, for example for internally vertex-disjoint s-t paths (since the maximum number of disjoint paths is equal to the minimum s-t separator).

In general, however, no such exact duality theorem is available. In such a case, X-HITTING and X-PACKING are two very different problems that may require different techniques. Then, solving X-HITPACK would require combining the two solution techniques in a nontrivial way, and it very well may be the case that X-HITPACK is a qualitatively harder problem that both X-HITTING and X-PACKING. Let us point out that one can explore different aspects of hardness (NP-hardness, exact running times, parameterized complexity, approximation, etc.), thus already for one particular choice of X, one can ask many different question. This means that understanding the X-HITPACK problem is a two-dimensional question: one dimension is the choice of X and the other dimension is the notion of complexity. We present two case studies (the objects X being cycles of arbitrary size or subgraphs isomorphic to a fixed graph H) and explore different aspects of the complexity of X-HITPACK. See Table 1 for an overview of our results.

Case Study 1: Cycles. Let us first consider the case when the type X of objects are the cycles in the given graph G. Thus, X-HITTING is exactly FEEDBACK VERTEX SET (the problem of deciding whether there is a set S of up to k vertices such that G - S has no cycle), X-PACKING is CYCLE PACKING (asking whether are there ℓ vertex-disjoint cycles), and X-HITPACK is the problem of asking if it is possible to remove a set S of k (deletable) vertices such that the remaining graph does not contain ℓ vertex-disjoint cycles.

FEEDBACK VERTEX SET and CYCLE PACKING are both known to be NP-complete. As we have seen, CYCLE-HITPACK generalizes both FEEDBACK VERTEX SET and the *complement* of CYCLE PACKING, thus it is unlikely to be in NP. Indeed, a solution S of size k is *not* a good certificate, as it is hard to verify due to the NP-hardness of CYCLE PACKING. We show that CYCLE-HITPACK is in fact located further up in the polynomial hierarchy.

Theorem 1.1. [See page 61.] *CYCLE-HITPACK is* Σ_2^P *-complete.*

Another jump in complexity can be observed if we consider how the problems behave on graphs of bounded treewidth. The study of parameterized algorithms and complexity on such graphs has been a fruitful area of research, as many NP-hard problems become tractable when restricted to graphs of small treewidth. In many cases, the problems are fixed-parameter tractable (FPT) parameterized by treewidth: there is an algorithm solving the problem in time $f(tw) \cdot n^{O(1)}$ for some function f. By now, there is a strong understanding on how the complexity of different problems depend on the treewidth of the graph, with a number of nontrivial algorithmic techniques and tight conditional lower bounds appearing in the literature [9, 10, 15, 16, 18, 23, 26, 27, 40, 48, 49, 53, 59–61, 64, 65]. The function f is typically of the form 2^{poly(tw)}, and we know of only a handful of problems where a double- or even triple-exponential dependence on treewidth is necessary assuming the Exponential-Time Hypothesis (ETH) [32, 47, 49, 59, 66]. One may see a pattern that problems at higher level of the polynomial hierarchy may need more than exponential dependence on treewidth, but note that there are problems in NP that need double-exponential dependence (metric dimension [32]) and there are #P-hard counting problems¹ that can be solved with single-exponential dependence [16, 26, 27, 60]. Both FEEDBACK VERTEX SET and CYCLE PACKING can be solved in time $2^{\text{poly}(\text{tw})} \cdot n^{O(1)}$ (it is known that, assuming ETH, the optimal dependence on treewidth is $2^{O(tw)}$ and $2^{O(tw \log tw)}$ for the two problems, respectively). Does CYCLE-HITPACK, the common generalization of the two problems, also admit an algorithm of this running time? We answer this question in the negative: the dependence becomes double-exponential on treewidth.

Theorem 1.2. [See page 46.] CYCLE-HITPACK can be solved in time $2^{2^{O(\text{tw}\log tw)}} \cdot n^{O(1)}$, where tw is the treewidth of the input graph.

We complement this upper bound by a matching lower bound which not only proves the doubleexponential dependence for the larger parameter pathwidth but also that the additional logarithmic factor cannot be avoided.

Theorem 1.3. [See page 77.] Assuming ETH, CYCLE-HITPACK has no $2^{2^{o(pw \log pw)}} \cdot n^{O(1)}$ time algorithm, where pw is the pathwidth of the input graph.

FEEDBACK VERTEX SET is known to be fixed-parameter tractable (FPT) parameterized by k, in fact, it can be solved in time $2^{O(k)} \cdot n^{O(1)}$ [11, 19, 34, 44]. CYCLE PACKING is FPT parameterized by ℓ , but it is an open question whether there is a $2^{O(\ell)} \cdot n^{O(1)}$ time algorithm: the current best algorithm has running time $2^{O(\ell \log^2 \ell / \log \log \ell)}$ [55]. As CYCLE-HITPACK is NP-hard for k = 0 and also for $\ell = 1$, the natural parameter for the problem is $p := k + \ell$.

We can try to use the following approach to show that CYCLE-HITPACK is FPT parameterized by p. Suppose that the input graph G has $p = k + \ell$ disjoint cycles. Then for every set S of k vertices, the graph G - S has ℓ disjoint cycles, implying that G is a no-instance of CYCLE-HITPACK. Therefore, we can assume that G has at most p disjoint cycles. Then the Erdős–Pósa Theorem implies that G has a feedback vertex set of size $O(p \log p)$, which also implies that G has treewidth $O(p \log p)$. Now we can try to use an algorithm for CYCLE-HITPACK parameterized by treewidth. However, in light of Theorem 1.3, any such algorithm would give a running time with double-exponential dependence on p. Can we improve this running time to $2^{\text{poly}(p)} \cdot n^{O(1)}$, to qualitatively match the running times of the FEEDBACK VERTEX SET and CYCLE PACKING algorithms? We show that this is indeed possible, and hence we do not see such a drastic jump in complexity similar to the Σ_2^p -completeness of the problem and the double-exponential dependence on treewidth.

¹By Toda's theorem [75], it is known that #P contains the entire polynomial hierarchy.

Theorem 1.4. [See page 16.] *CYCLE-HITPACK can be solved in time* $2^{\text{poly}(p)} \cdot n^{O(1)}$ (where $p \coloneqq k + \ell$).

The proof exploits that *G* has a feedback vertex set *F* of size $O(p \log p)$. By a simple branching argument, we assume that the solution *S* is disjoint from *F*. Then we interpret a packing of cycles as a collection of paths connecting some neighbors of *F* in the forest G - F. Our goal is to hit every such collection of paths that would lead to a collection of ℓ cycles. With a branching algorithm, we collect paths that have to be hit, until we can conclude that our collection of paths cannot be hit by *k* vertices.

Case Study 2: *H*-subgraphs. Next, let us consider the setting where the type X of objects are the (not necessarily induced) subgraphs isomorphic to a fixed graph *H*. Thus, *H*-HITTING is the problem of removing a set *S* of *k* vertices such that no subgraph isomorphic to *H* remains, *H*-PACKING is finding ℓ disjoint copies of *H* as subgraphs, and *H*-HITPACK is the problem of removing a set *S* of *k* vertices such that the remaining graph does not contain ℓ disjoint copies of *H*.

For every fixed connected graph *H* with at least 3 vertices, *H*-HITTING [43] and *H*-PACKING [50] are NP-complete. Similarly to the case of CYCLE-HITPACK, the *H*-HITPACK problem lies on the second level of the polynomial hierarchy.

Theorem 1.5. [See page 61.] For any fixed connected graph H with at least three vertices, H-HITPACK is Σ_2^{P} -complete.

Similarly to CYCLE-HITPACK, we again see a jump to double-exponential dependency on treewidth and pathwidth. For the case of general graphs *H*, we provide an algorithm whose running time asymptotically matches the one of the algorithm for CYCLE-HITPACK.

Theorem 1.6. [See page 35.] For any fixed connected graph H, H-HITPACK can be solved in time $2^{2^{O(\text{tw}\log \text{tw})}} \cdot n^{O(1)}$, where tw is the treewidth of the input graph.

In the case when H is a clique, we exploit that we are only packing complete graphs which leads to an improvement where we remove the logarithmic factor from the exponent.

Theorem 1.7. [See page 29.] For any fixed integer $q \ge 2$, q-CLIQUE-HITPACK can be solved in time $2^{2^{O(tw)}} \cdot n^{O(1)}$, where tw is the treewidth of the input graph.

By designing the matching lower bound for CYCLE-HITPACK in such a way that the construction already works for SQUARE-HITPACK, we obtain a matching lower bound for SQUARE-HITPACK.

Theorem 1.8. [See page 73.] Assuming ETH, SQUARE-HITPACK has no $2^{2^{o(pw \log pw)}} \cdot n^{O(1)}$ time algorithm, where pw is the pathwidth of the input graph.

For the case of general H we provide a separate reduction. In contrast to the matching lower bound for the case of SQUARE-HITPACK, we present a lower bound which is only matching for the case of cliques as for cliques we provide an improved algorithm. For the case when H is neither a clique nor a C_4 , it remains open to remove the logarithmic factor from the running time or to improve the lower bound accordingly.

Theorem 1.9. [See page 66.] Assuming ETH, for any fixed connected graph H with at least three vertices, H-HITPACK has no $2^{2^{o(pw)}} \cdot n^{O(1)}$ time algorithm, where pw is the pathwidth of the input graph.

It is known that *H*-HITTING parameterized by *k* and *H*-PACKING parameterized by ℓ are both fixedparameter tractable (FPT), in fact, for fixed *H*, they can be solved in time $2^{O(k)} \cdot n^{O(1)}$ and $2^{O(\ell)} \cdot n^{O(1)}$, respectively. For *H*-HITTING, this follows from a simple bounded-depth search tree algorithm, while color coding [3] or representative set techniques [28] can be used for *H*-PACKING. There is an easy bounded-tree search tree algorithm showing that *H*-HITPACK is FPT parameterized by $p := k + \ell$.

Theorem 1.10. For any fixed graph H that might be unconnected, H-HITPACK can be solved in time $2^{O(p \log p)} \cdot n^{O(1)}$ (where $p := k + \ell$).

Proof. First, we use the $2^{O(\ell)} \cdot n^{O(1)}$ *H*-PACKING algorithm to find ℓ copies of *H* if they exist [3, 28]. The solution *S* has to contain at least one of the $|V(H)| \cdot \ell = O(\ell)$ vertices of this packing. Thus, we can branch on choosing one of these vertices, delete that vertex from the graph, and decrease our quota *k* of deletions by one. We repeat this process until either k = 0 or there are no ℓ disjoint copies of *H* in the graph.

This results in a search tree of size $\ell^{O(k)} = 2^{O(p \log p)}$ and thus, concludes the proof.

We leave open the potentially challenging question of whether this running time of the algorithm can be improved to $2^{O(p)} \cdot n^{O(1)}$: none of the techniques used for *H*-HITTING and *H*-PACKING seem directly relevant for such improvement. In other words, it is easy to show that *H*-HITPACK is also FPT, but whether quantitatively same FPT algorithms can be obtained for this more general problem is a far from trivial question.

The Curious Case of EDGE-HITPACK. Let us consider now the case of *H*-HITPACK where *H* consists of only a single edge, i.e., $H = K_2$. Then EDGE-HITTING is the NP-complete problem VERTEX COVER, while EDGE-PACKING is the polynomial-time solvable MAXIMUM MATCHING problem. This implies that, unlike in the cases where *H* has at least 3 vertices, EDGE-HITPACK is in NP: given a solution *S*, we can verify in polynomial time that G - S has no matching of size ℓ .

While we do not have a $2^{O(k+\ell)} \cdot n^{O(1)}$ time algorithm for *H*-HITPACK for general *H*, we present a very simple algorithm solving EDGE-HITPACK in time $3^{k+\ell} \cdot n^{O(1)}$. The algorithm essentially relies on an augmenting-path argument, hence it gives no indication on how other *H*-HITPACK problems could be solved with a similar running time.

Theorem 1.11. [See page 28.] *EDGE-HITPACK can be solved in time* $3^{k+\ell} \cdot n^{O(1)}$.

Theorem 1.9 showed that double-exponential dependence on treewidth is needed to solve the *H*-HITPACK problem when *H* is connected and has at least 3 vertices, that is, already for the TRIANGLE-HITPACK problem (we will also denote this problem as TRIANGLE-HITPACK). However, EDGE-HITPACK can be solved with only exponential dependence on treewidth.

Theorem 1.12. [See page 33.] *EDGE-HITPACK can be solved in time* $2^{\text{poly}(\text{tw})} \cdot n^{O(1)}$, where tw is the treewidth of the graph.

Let us give an intuitive explanation for this difference in running time between EDGE-HITPACK and TRIANGLE-HITPACK. There is a well-understood methodology for designing algorithms on tree decompositions: for each rooted subtree of the tree decomposition, we define a certain number of subproblems, each asking for the existence of a certain class of partial solutions. The running time typically depends on how many equivalence classes of partial solutions we need to consider. For example, in the TRIANGLE-PACKING problem, the class of partial packings is described by the subset of the bag that is covered by the packing, so there are $2^{\text{poly}(tw)}$ different classes of partial solutions. For the TRIANGLE-HITTING problem, a partial solution is a set of vertices that destroys every triangle in a rooted subtree of the tree decomposition, and its class is described by its intersection with the bag.

For the combination, TRIANGLE-HITPACK, a partial solution is a set of vertices that does not necessarily destroy every triangle in the subtree of the tree decomposition, but may still leave some triangle packings of size $< \ell$ in the graph. Therefore, a partial solution *S* can be described by what kind of triangle packings survive after deleting *S*, that is, by describing which subsets of the bag can be covered/avoided by triangle packings of a certain size. This means that the class of a partial solution is described by a set system over a bag of the decomposition. As the set systems arising this way can be fairly arbitrary in the TRIANGLE-HITPACK problem, there are up to $2^{2^{\text{poly(tw)}}}$ such set systems and hence up to that many different classes of partial solutions. This is the intuitive reason why a doubleexponential dependence on treewidth is needed for the problem TRIANGLE-HITPACK.

In the case of EDGE-HITPACK, the set systems describing a partial solution show how the bag can be covered by matchings of a certain size. Such set systems have lots of structure and cannot be completely

Object X	UB $p = k + \ell$		UB Treewidth		LB Treewidth		Completeness	
Edge	3 ^{<i>p</i>}	Th. 1.11	2 ^{poly(tw)}	Th. 1.12	no 2 ^{o(tw)}	[52, Th. 1]	NP	[33, Th. 3.3]
Triangle			22 ^{O(tw)}	Th 17			Σ_2^{P}	Th. 9.12
q-Clique	$2^{O(p\log p)}$) Th. 1.10		111. 1.7	no $2^{2^{o(tw)}}$	Th. 1.9		
Conn. <i>H</i> , 3+ vert.			$n2^{O(tw \log tw)}$	ፕዜ 1 (Σ_2^{P}	Th. 1.5
Square	$2^{O(p\log p)}$) Th. 1.4		111. 1.0	no $2^{2^{o(tw \log tw})}$	^{v)} Th. 1.8		
Cycles	$2^{\operatorname{poly}(p)}$	Th. 1.4	$2^{2^{O(tw\logtw)}}$	Th. 1.2	no $2^{2^{o(tw \log tw})}$	^{v)} Th. 1.9	Σ_2^{P}	Th. 1.1

Table 1: An overview of the main results for X-HITPACK. For ease of comparability, we omit the common factor $n^{O(1)}$ from the FPT running times.

arbitrary; in particular, they are related to (delta)-matroids. Inspired by an argument of Wahlström [77], we give a combinatorial bound showing that such set systems can be represented algebraically with $O(tw^3)$ bits, hence there are at most $2^{O(tw^3)}$ different set systems that can arise. Interestingly, our proof is not algorithmic, but it is sufficient to bound the running time of our algorithm. In fact, we have to make no adjustment to the algorithm of Theorem 1.6 solving *H*-HITPACK when *H* is a clique: the algorithm was designed in a way that a combinatorial proof on the relevant set systems immediately bounds the running time of the algorithm.

Discussion and Open Problems. We have initiated the study of a natural common generalization of hitting problems and packing problems. Certain basic techniques for hitting and packing problems can be lifted to this generalization, but we have seen that the generalization can be significantly harder and more challenging, requiring us to revisit classic problems from a new perspective. The familiar landscape of hitting and packing problems with their known properties and well-established techniques is replaced by a strange world where many of the known techniques are inapplicable, new techniques have to be brought in, and the problem has to be approached with a completely different mindset that takes into account the more complicated quantifier structure of the problem definition.

We have presented a selection of algorithmic results and lower bounds for X-HITPACK problems, but they probably just scratch the surface of a rich family of unexplored challenging problems. We list a few open questions and potential research directions to stimulate further work in this area.

- Is there a $2^{O(k+\ell)} \cdot n^{O(1)}$ time algorithm for *H*-HITPACK for every fixed (connected) graph *H*?
- Is the X-HITPACK problem FPT in *k* and *l* where X are the odd cycles in the graph? Note that the corresponding hitting problem ODD CYCLE TRANSVERSAL is well-known to be FPT by different techniques [56, 69, 72], and ODD CYCLE PACKING is also FPT using an extension of graph minor algorithms with parity conditions [41, 42].
- Is the X-HITPACK problem FPT in k and ℓ where X are the induced cycles of length at least 4 in the graph? The hitting problem CHORDAL DELETION [2, 12, 38, 57] and the packing problem CHORDLESS CYCLE PACKING [58] are both FPT.
- In general, one could explore if induced versions of the *H*-HITPACK problems are different compared to the case when we are considering not necessarily induced subgraphs isomorphic to *H*.
- We defined our framework in terms of removing vertices and vertex-disjoint packings, but one could analogously study a problem defined by removing edges and edge-disjoint packings. This setting may pose very different challenges compared to the problems studied in this paper.

- A natural generalization of CYCLE-HITPACK is to consider the X-HITPACK problem where X is the set of all minor models of a fixed graph H (CYCLE-HITPACK is equivalent to the case when H is K_3). Observe that if we denote by $\ell \cdot H$ the graph consisting of ℓ disjoint copies of H, then the X-HITPACK problem defined for minor models of H is equivalent to removing k vertices such that the resulting graph does not contain $\ell \cdot H$ as a minor. Problems of this form where intensively studied [1, 25, 29]. Thus this gives a way of solving the problem for fixed k, ℓ , and H, but understanding the optimal form of the running time could be an interesting question. The same problem can be studied also in the context of topological minors.
- One could ask how the Erdős-Pósa Property relates to the complexity of the X-HITPACK problem, but it is not obvious how to formulate this question in a way that leads to meaningful results. Note first that for problems involving copies of a fixed graph *H*, the Erdős-Pósa Property trivially holds (in some sense, this was implicitly used by the simple algorithm of Theorem 1.10). The algorithm of Theorem 1.4 explicitly used the Erdős-Pósa Property for cycles as a starting step. This might be a useful starting step in other cases where *H*-minor models satisfy this property (which is known to be the case exactly when *H* is planar). However, note that the argument sketched in the previous item works irrespective of whether *H*-minor models satisfy the Erdős-Pósa Property, although it may affect the running time.
- Tournaments (i.e., directed graphs with exactly one directed edge between any pair of vertices) form a well-studied class of directed graphs where many hitting and packing problems are more tractable compared to general directed graphs [4, 6, 7, 13, 14, 21, 30, 46, 54, 63, 68, 78]. Which of these results generalize to the combined hitting and packing problem?
- Investigating the approximability of X-HITPACK problems is another completely unexplored area. The proper notion of approximation for these kind of problems seems to be the following: if there is a solution S of size k such that G S has no ℓ disjoint objects of type X, can we find a set S' of size at most $c \cdot k$ such that G S' has no $c \cdot \ell$ disjoint objects of type X. That is, it this approximate sense, it is ok to find a somewhat larger set S' that has the somewhat weaker property that it prevents only packings of $c \cdot \ell$ disjoint objects.

2 Technical Overview

In this section, we give a brief overview of our results, highlighting the main technical ideas and putting them in context. The remaining sections of the paper prove these results in the order presented below. Note that, besides these individual technical contributions, it can be considered an equally important conceptual contribution that we demonstrate that the combination of hitting and packing can lead to a wide range of interesting and challenging problems.

2.1 Algorithmic Results

 $2^{\text{poly}(k+\ell)} \cdot n^{O(1)}$ **Time Algorithm for CYCLE-HITPACK.** As noted earlier, we may assume in this problem that the graph *G* has a feedback vertex set *F* of size $O((k + \ell) \text{ poly}(k + \ell))$, otherwise the Erdős–Pósa Theorem implies that the answer is no. Instead of using the fact that this gives a bound on the treewidth and trying to use a general algorithm parameterized by treewidth, we present an algorithm with running time $2^{\text{poly}(k+|F|)} \cdot n^{O(1)}$ where *F* is a feedback vertex set.

With a standard branching step, we can guess which vertices of *F* are in the solution, remove these vertices from *G*, adjust *k* appropriately, and then assume that the feedback vertex set *F* is undeletable. To sketch the main ideas of the proof, let us assume that G - F is not only a forest, but every component of G - F is a path. If *C* is a cycle in *G*, then it contains at least one vertex of *F*, and C - F consists of one or more (sub-)paths in G - F. If a graph contains a packing of ℓ cycles, then we may assume that each cycle is an induced cycle (this can be achieved by possibly shortening some cycles). If *C* is an induced

cycle, then every path *P* of *C* – *F* is of the following form: *P* goes from a neighbor of some $f_1 \in F$ to a neighbor of some $f_2 \in F$ (possibly $f_1 = f_2$) such that the internal vertices of *P* are adjacent to neither f_1 nor f_2 . Let us call this a *usable path*.

Suppose that we have a packing of ℓ (induced) cycles in *G*. The solution has to contain a vertex of a cycle *C* of this packing, that is, a vertex of one of the paths C - F (as *F* is undeletable). We branch on choosing a cycle *C* of the packing and choosing a path *P* of C - F that is broken by the solution, but we *do not* choose a vertex of *P*. Instead, we put *P* into a collection \mathcal{P} of forbidden paths that need to be broken by the solution. Then we find a packing of ℓ cycles that does not use any of the forbidden paths. Such a collection can be found by branching on the number and type of paths in the packing and then by a dynamic programming algorithm that scans paths in G - F in a left-to-right order and tries to find disjoint paths of these types that are not on the forbidden list \mathcal{P} . Once we have such a collection, we once again branch on a path that has to be broken by the solution and put it into the collection \mathcal{P} . We repeat this procedure as long as we are able to find an appropriate packing.

If the algorithm is not able to find a packing of ℓ cycles that does not use any forbidden path, then we need to check if there is a set of k vertices that can break every forbidden path in \mathcal{P} . This can be done by a simple polynomial-time algorithm (find a minimum number of points covering a set of intervals). If there is such a set S, then it forms a solution; if there is no such set, then this is an incorrect branch of the algorithm.

To bound the running time, we need to bound the depth of the search tree, that is, the number of paths we put into the solution. The key observation is that a vertex v can cover at most $|F|^2$ different usable paths. If v covers a useful path P from u_1 to u_2 , then u_1 should be the last vertex before v that is the neighbor of some $f_1 \in F$ and u_2 is the first vertex after v that is the neighbor of some $f_2 \in F$. Therefore, if $|\mathcal{P}| > k|F|^2$, then surely there is no set S of k vertices intersecting all these paths. This observation gives a poly(k + |F|) bound on the height of the search tree. As we branch into poly(|F|) cases in each step, the claimed running time follows.

With additional work, this algorithmic idea can be extended to the case when G - F is not a collection of paths, but a general forest. The situation becomes significantly more complicated due to high degree vertices in the forest, paths with many branch nodes, and other issues, but the difficulties can be overcome by additional layers of arguments (see Section 3 for details).

 $3^{k+\ell} \cdot n^{O(1)}$ **Time Algorithm for EDGE-HITPACK.** Let us sketch a very simple branching algorithm. We measure our progress by $k + \ell + 1 - v(G[U])$, where v(G[U]) is the size of the maximum matching in the graph induced by the undeletable vertices. Let us find a maximum matching M in G[U]. We have $v(G[U]) < \ell \le v(G)$, hence there is an augmenting path increasing the size of M. Let u and v be the two endpoints of the augmenting path. We branch into three directions:

- *u* is in the solution: remove *u*, decrease *k* by one.
- *v* is in the solution: remove *v*, decrease *k* by one.
- neither *u* nor *v* is in the solution: put *u* and *v* into *U*.

As the last branch strictly increases the size of the maximum matching in U, we can conclude that the measure $k + \ell + 1 - \nu(G[U])$ strictly decreases in each branch, giving a bound of $k + \ell$ on the depth of the search tree.

 $2^{2^{O(\mathsf{tw})}} \cdot n^{O(1)}$ Time Algorithm for *H*-HITPACK When *H* Is a Clique. A typical way of designing algorithms for bounded-treewidth graphs is the following. Let us recall the definition of tree decompositions. A *tree decomposition* of graph *G* is a rooted tree *T* with a collection $\{X_t \subseteq V(G) \mid t \in V(T)\}$ of sets called *bags*. The conditions for a tree decomposition are:

- For any vertex *u* in *G*, the nodes in *T* with bags containing *u* form a connected subtree of *T*.
- For any edge *uv* in *G*, there exists a node in *T* with a bag containing both *u* and *v*.

The width of a tree decomposition (T, B) is $\max_{t \in V(T)} |X_t| - 1$. The *treewidth* tw of *G* is the minimum possible width of a tree decomposition. *Pathwidth* is defined similarly, with *T* restricted to be a path. We denote by V_t the set of vertices appearing in the bags of the nodes in the subtree rooted at some node *t*. Similarly, we define G_t as the graph induced by the vertices or rather given by the edges introduced in the subtree rooted at node *t*.

For *H*-HITPACK, the solution *S* has a part $S \cap V_t$ that somehow influences packings of cliques that intersect V_t . A key observation is that a clique *K* is either fully contained in V_t , or intersects only the root bag X_t , i.e., $K \cap V_t = K \cap X_t$. Based on this observation, we can argue that the effect of $S \cap V_t$ can be described by the following information:

- The intersection $S \cap X_t$.
- For every $D \subseteq X_t$, the maximum size of a packing in $G[V_t \setminus S] D$.

Note that if the maximum packing size in $G[V_t \setminus S]$ is m, then the maximum packing size in $G[V_t \setminus S] - D$ is between m - |D| and m. Thus all the relevant information about $S \cap V_t$ can be described by the set $S \cap X_t$ (2^{tw+1} possibilities) and by a sequence of 2^{tw+1} integers between 0 and tw + 1 ((tw + 2) 2^{tw+1} possibilities), leading to a bound of $2^{2^{O(tw)}} \cdot n$ different ways $S \cap X_t$ can behave. With this bound at hand, we can follow the standard methodology of designing algorithms on tree decompositions: we define subproblems at each node t corresponding to the different behaviors of S and solve these subproblems in a bottom-up manner. The dominating factor of the running time is the number of subproblems at each node of the tree decomposition, leading to a $2^{2^{O(tw)}} \cdot n^{O(1)}$ time algorithm.

 $2^{\text{poly}(\text{tw})} \cdot n^{O(1)}$ Time Algorithm for EDGE-HITPACK. When *H* is a single edge, we can improve the running time the following way. As noted above, the behavior of the set $S \cap V_t$ can be described by the set $S \cap X_t$ and by a function showing how the size of the maximum matching decreases if we remove a subset $D \subseteq X_t$, that is, by the function $g(D) = v(G[V_t \setminus S]) - v(G[V_t \setminus S] - D)$. Because of the highly structured nature of the matching problem, this function cannot be arbitrary and can be compactly described, hence the number of possibilities is much smaller than $2^{2^{O(tw)}}$. Let us first consider the related function f(D), which is 0 or 1 depending on whether $G[V_t \setminus S] - D$ has a perfect matching or not. This function describes a so-called *delta-matroid* and has an algebraic representation as a skew-symmetric matrix. Following a proof sketch² of Wahlström [77], this matrix can be turned into a representation with $O(tw^3)$ bits. Formally, in Section 6 we prove the following lemma.

Lemma 2.1. Let G be an n-vertex graph over a vertex set $V \supseteq [k]$ for some integer k. Let $f_{G,k}: 2^{[k]} \to \mathbb{Z}^+$ be the function defined by $f_{G,k}(S) = v(G - S)$. For each k and n, there are $n \cdot 2^{O(k^3)}$ functions $f_{G,k}$ that can arise this way.

Then a simple graph-theoretic construction can be used to compactly describe the function g using the compact representation of the function f. Interestingly, our proof of obtaining the algebraic representation is not algorithmic, but it is sufficient for our purposes: the dynamic-programming algorithm on the tree decomposition can be designed in a way that it needs only a combinatorial bound on the number of different subproblems that has a solution in the current graph, but does not need to be able to compute which subproblems have no solution in any graph. Therefore, the algorithm for *H*-HITPACK with *H* being a clique does not need any modification at all to achieve this running time.

The crucial combinatorial insight that allows us to achieve $O(tw^3)$ -bits and prove Lemma 2.1 is the following statement.

²The given proof sketch does not treat the question of what field to choose and the obvious way of handling this issue does not lead to the claimed bound (as confirmed by the author). Our proof needs additional arguments to ensure the existence of a representation over a suitable field.

Lemma 2.2. Let G be a graph over a vertex set $V \supseteq [k]$ for some integer k. Let us define the function $h_{G,k}: 2^{[k]} \rightarrow \{0,1\}$ the following way:

$$h_{G,k}(S) = \begin{cases} 1 & if G - S \text{ has a perfect matching,} \\ 0 & otherwise. \end{cases}$$

For each integer k, the number of distinct functions $h_{G,k}$ is $2^{O(k^3)}$.

Note, that naively the number of such functions is double-exponential in k. Now, we present the proof of Lemma 2.2 and use algebraic tools, in particular, representation of linear delta-matroids and multivariate polynomials over finite fields. For a field \mathbb{F} , we denote by $\mathbb{F}[x_1, \ldots, x_n]$ the ring of n-variable polynomials with coefficients from \mathbb{F} . We have to be careful to make a distinction between the *zero polynomial* of $\mathbb{F}[x_1, \ldots, x_n]$, which is the polynomial where every coefficient is zero, and a *vanishing polynomial* over \mathbb{F} , which is a polynomial that is 0 for every substitution of values from \mathbb{F} to the variables. For example, $x^{|\mathbb{F}|} - x$ is a nonzero vanishing polynomial over the field \mathbb{F} . The following observation can be used to argue that some nonzero polynomial is not vanishing.

Observation 2.3. If $P \in \mathbb{F}[x_1, ..., x_n]$ is an *n*-variable polynomial over the field \mathbb{F} and every variable x_i has degree less than $|\mathbb{F}|$ in *P*, then *P* is a vanishing polynomial if and only if it is the zero polynomial.

The proof of Lemma 2.2 follows from the fact that polynomials $P \in \mathbb{F}[x_1, \ldots, x_n]$ where every variable has degree less than \mathbb{F} are in one-to-one correspondence with functions $f \colon \mathbb{F}^n \to \mathbb{F}$. Indeed, both sets have size exactly $|\mathbb{F}|^{|\mathbb{F}|^n}$ and Lagrange interpolation shows that for any function $f \colon \mathbb{F}^n \to \mathbb{F}$, there is a corresponding polynomial where the degree of every variable is less than $|\mathbb{F}|$.

Proof of Lemma 2.2. For notational convenience, let us assume that V = [n]. Let \mathbb{F} be a field of size 2^{k+2} . Let *A* be the Tutte matrix corresponding to *G*, that is, an element $a_{i,j}$ is defined as

$$a_{i,j} \coloneqq \begin{cases} x_{i,j} & \text{if } i \text{ and } j \text{ are adjacent and } i < j, \\ -x_{i,j} & \text{if } i \text{ and } j \text{ are adjacent and } i > j, \\ 0 & \text{if } i \text{ and } j \text{ are not adjacent.} \end{cases}$$

We consider each entry of A as an n^2 -variate polynomial from $\mathbb{F}[x_{1,1}, \ldots, x_{n,n}]$. For $X \subseteq [n]$, we denote by A[X] the principal submatrix of A corresponding to the rows and columns described by X. It is well known that G[X] has a perfect matching if and only if $\det(A[X])$ is a nonzero polynomial. Let us denote by S^c the complement of S, i.e., the set of rows/columns *not* indexed by S. Thus for every $S \subseteq [k]$, we have

$$G - S$$
 has a perfect matching $\Leftrightarrow \det(A[S^c])$ is nonzero (\star)

We would like to obtain a matrix A' with the same property (\star), but over \mathbb{F} (so the elements of A' are *not* polynomials). Let S_1, \ldots, S_t be the subsets of [k] such that G-S has a perfect matching. For $\ell \in [t]$, the polynomial $P_\ell = \det(A[S_\ell^c])$ is a nonzero polynomial where every variable $x_{i,j}$ has degree at most 2 (as every variable appears at most twice in the Tutte matrix). The product $P = \prod_{\ell=1}^t P_\ell$ is also a nonzero polynomial (as \mathbb{F} is a field, $\mathbb{F}[x_{1,1}, \ldots, x_{n,n}]$ is an integral domain) where every variable has degree at most $2t \leq 2 \cdot 2^k < |\mathbb{F}|$. Therefore, Observation 2.3 implies that P is not vanishing. This means that we can substitute values to the variables such that P evaluates to a nonzero value, which also means that every P_ℓ is nonzero under this substitution. Let A' be obtained from A by this substitution. It is easy to see that this matrix A' over \mathbb{F} has the desired property (\star): if S has no perfect matchings, then det $(A'[S^c]) = 0$ (as this already holds for A), while if S has a perfect matching, then the determinant is one of the polynomials P_ℓ , and hence it evaluates to a nonzero value under the substitution.

Now we argue that we can obtain a $k \times k$ matrix A'' that also has the property (\star) Matrix A' represents the set system $\mathcal{X} = \{X \mid \det(A'[X]) \neq 0\}$ over [n], which is known to be a delta-matroid. The set system $\mathcal{X}' = \{X \in [k] \mid X \cup ([n] \setminus [k]) \in \mathcal{X}\}$ is a set system over [k], which is called the

contraction of X. It is known (see, e.g., Wahlström [77]) that given some $[n] \times [n]$ matrix A' over \mathbb{F} representing X, we can use algebraic operations to compute a $k \times k$ matrix A'' representing X'. Now we can verify that this matrix A'' indeed satisfies property (\star)

As A'' has property (\star) we can deduce from A'' the value of the function f for any $S \subseteq [k]$. As A'' is an $k \times k$ matrix over a field of size 2^{k+2} , it can be described by $k^2(k+2)$ bits. Therefore, $O(k^3)$ bits are sufficient to describe the function $h_{G,k}$, that is, there are at most $2^{O(k^3)}$ such functions.

 $2^{2^{O(\text{tw}\log \text{tw})}} \cdot n^{O(1)}$ Time Algorithm for *H*-HITPACK for Arbitrary Connected *H*. The dynamic programming approach becomes significantly more complicated if we generalize it to *H*-HITPACK where *H* is not a clique. The main issue is that now it is no longer true that in every packing every copy of *H* intersecting *V*_t is either fully contained in *V*_t or intersects *V*_t only in *X*_t. As *H* is not a clique, it can be the case that a copy is split by *X*_t (see Figure 2.1). Therefore, we need to argue about *partial packings* in *V*_t that may contain some partial copies of *H* split by *X*_t. When reasoning about such a partial packing, we need to describe not only which vertices of *X*_t the partial packing covers, but also how the partial copies partition *X*_t. We formalize this intuitive idea by the notion of *types*. The type of a (partial) packing contains the following information:

- A set of those vertices in *X_t* that are not covered by the packing including the vertices which are deleted.
- A partition of the vertices in X_t describing which vertices contribute to the same copy of H.
- For each part of the partition, a mapping between the vertices of X_t and the vertices of the partial copy of H, so we can determine which vertices of H have been packed and which vertices of H still need to be packed.

Clearly there are at most 2^{tw+1} choices for the set of uncovered vertices. Since we consider a fixed graph *H*, the precise mapping for each of the at most tw + 1 parts can be described by $|H|^{tw+1}$ possible functions although involving a significant notational overhead in the formal description. However, the partition of the vertices into the different parts dominates the number of possible types for which there are tw^O(tw) possibilities for each node. Due to this larger number of types, the running time of the algorithm involves an additional logarithmic factor which we avoid for the case when *H* is a clique.

Similar to the algorithm when packing cliques, we also have to remember the size of the largest packing for each type. As this number could potentially range from 0 to ℓ , a naive bound for the number of possible states is $\ell^{tw^{O(tw)}}$ which does not depend on the treewidth only. However, since each graph H has only a fixed size, the packing number for two different types cannot differ by too much. Indeed, the size of two optimal partial packings with different types can differ by at most $O(|H| \cdot tw)$ as each partial packing of H can "block" at most |H| vertices from being packed in the other packing. This observation drastically reduces the number of states for each node to $tw^{tw^{O(tw)}}$ which then determines the running time of the algorithm.

 $2^{2^{O(\text{tw}\log \text{tw})}} \cdot n^{O(1)}$ Time Algorithm for CYCLE-HITPACK. For the case of CYCLE-HITPACK the situation is different from the cases before. Since we are not dealing with a fixed graph H but an infinitely sized family of graphs, we cannot decide a priori which graphs are packed where. However, as we can exploit that all possible graphs must be cycles, we can still characterize the interaction with a bag X_t in a compact way. The main observation is that it does not matter in which cycle (i.e., of which length) the vertices appear in a partial packing as we allow cycles of all possible lengths. Instead, it suffices to classify the vertices of a bag X_t into three groups which are "uncovered", "covered with one incident edge", and "covered with two incident edges". Despite this partition of the vertices is possible, it is not sufficient to fully describe the behavior of a partial packing with a bag. We also have to be able to recognize when adding a new edge to the packing would close a cycle. For this we need to remember which vertices (from the bag) appear in the same cycle. However, we do not have to store this



Figure 2.1: If *H* is not a clique (e.g., *H* is a cycle on 5 vertices), then restricting a packing to V_t may result in partial copies of *H* that contain vertices from $V_t \setminus X_t$. Therefore, the description of a partial packing needs to include how these partial copies interact with X_t .

information for all vertices in the bag but only for those vertices that are incident to exactly one edge as only these vertices are eligible to obtain another edge. This information between the endpoints of the partial cycles, i.e., paths, can be efficiently described by a perfect matching between these vertices. Hence, the type of a partial cycle-packing is a four-tuple with the following information:

- A set of vertices that are not covered by the packing which includes the deleted vertices.
- A set of vertices that have one incident edge in the packing.
- A set with the remaining vertices which have two incident edges in the packing, that is, these vertices are already fully covered.
- A perfect matching for the vertices with one incident edge abstracting the paths between the endpoints.

When treating the perfect matching as a special form of a partition, the connection to the algorithm for the general case become apparent; for general H, the type also contains a partition of the vertices describing which vertices appear in the same copy of H. From this perspective it comes as no surprise that for CYCLE-HITPACK the number of types is at most tw^O(tw) as well.

Similar to the algorithm for H-HITPACK when H is one fixed graph, the interaction of a solution with bag further includes the information of how many cycles can be packed for each possible type of partial packing. Interestingly, when considering two different types, there is no obvious bound for the difference in the number of packable cycles. However, if for some type the number of cycles that can be packed is too low then there is no benefit in proceeding with this type. More formally, consider a type T where we can pack at least tw cycles less than for the optimal packing where no vertex of the bag is covered. Even if all partial cycles for a packing of type T could be closed, the total number of cycles is still lower than for the packing where none of the vertices from the bag are covered. Hence, proceeding with this type T never results in a maximal packing and therefore, all packings that have this specific type T at this node can be discarded immediately.

With this observation it then follows that even for CYCLE-HITPACK the total number of subproblems at each node can be bounded by $2^{2^{O(tw \log tw)}} \cdot n$.

2.2 Lower Bounds

 Σ_2^{P} -completeness of TRIANGLE-HITPACK. The containment in Σ_2^{P} for TRIANGLE-HITPACK is clear, as we can guess the set of deleted vertices and use an NP-oracle to determine the size of the maximum packing. To establish the Σ_2^{P} -hardness, we reduce from a special Σ_2^{P} -complete satisfiability problem, the SMALLEST UNSATISFIABLE SUBFORMULA problem (SUS) [73, 76]. For SUS the input is a

CNF-formula φ together with a parameter k and the task is to decide if there *exists* a collection of at most k clauses of φ (we refer to this as subformula) such that, *for all* assignments, the subformula is not satisfied, i.e., the subformula is unsatisfiable. This "exists, for all" formulation of SUS already gives a hint for the reduction to TRIANGLE-HITPACK.

We construct a graph consisting of clause gadgets, variable gadgets, and literal edges. Each of the clause gadgets consist of a single triangle with a distinguished deletable vertex. The interpretation of this vertex is as follows: if the vertex is deleted, then the clause is activated/selected, and otherwise, the clause remains inactive (which we consider as the default state). Each variable gadget consists of a cycle of triangles such that there are exactly two maximum triangle packings, one corresponding to setting the variable to true and the other packing corresponding to setting the variable to false. As a last component the graph contains literal edges which connect the variable gadgets to the clause gadgets depending on the occurrence of the literals in the clauses. Intuitively the idea is that once the distinguished vertex of a clause gadget is deleted, which corresponds to a selected clause, it should not be possible to find a large packing as otherwise we could transform this packing (for the variable gadgets) into an assignment which satisfies all selected clauses.

To strengthen the result, we prove the hardness for tripartite graphs by reducing from 3CNF-SUS (the restriction of SUS to 3CNF-formulas), for which we also provide the Σ_2^P -completeness as, to our knowledge, no proof appeared in the literature, although the completeness was claimed (see Section 9.1 for further discussion).

 $Σ_2^{P}$ -completeness of *H*-HITPACK. For connected graphs *H* other than the triangle, the $Σ_2^{P}$ -completeness result can be obtained from TRIANGLE-HITPACK by a clean reduction. Kirkpatrick and Hell [43] showed how to reduce a triangle packing problem to arbitrary *H*-packing problems for connected *H* with at least 3 vertices. However, they considered the problem of finding a packing that covers every vertex of the graph and the arguments do not readily work for problems where not every vertex needs to be covered. Nevertheless, we show that with additional arguments and by extending their construction, a reduction can be obtained from TRIANGLE-HITPACK to *H*-HITPACK, showing the $Σ_2^{P}$ -completeness of the latter problem.

 $Σ_2^{P}$ -completeness of Cycle-HitPack. This hardness proof is obtained by observing that in the $Σ_2^{P}$ -completeness proof of TRIANGLE-HITPACK, every cycle relevant for a packing is a triangle.

Double-exponential Lower Bounds for *H***-HITPACK Parameterized by Treewidth.** We reduce from an instance of 3-SAT with *n* variables and *m* clauses to achieve a double-exponential lower bound by constructing a graph with pathwidth $O(\log m)$. Although the starting point is again a 3CNF-formula as for the $\Sigma_2^{\rm P}$ -hardness, the interpretation and the basic ideas differ because of the change in the quantification. For SUS the task is to check if there *exists* a set of *clauses* such that, *for all assignments* to the variables, the formula is not satisfiable. For 3-SAT the task is to check if there *exists an assignment* for the variables such that *for all clauses* at least one literal of the clause is satisfied, i.e., for each clause not all three literals are false. While as before, we use gadgets consisting of a long cycle with attached triangles, the overall construction of how these gadgets interact is substantially different. The critical difference to the $\Sigma_2^{\rm P}$ -hardness proof lies in the way we verify the satisfying assignment. Here, we do not explicitly construct a different gadget for every clause as this would result in a construction with treewidth linear in the number of clauses.

Our constructed instance comprises three parts, which we refer to as left, middle, and right. The deleted vertices on the right correspond to a choice of the satisfying assignment. The left part consists of the so-called *selector gadgets*. Each selector gadget models one bit of the binary encoding of some clause. So, if there are m clauses, we have roughly log m selector gadgets. For each selector gadget we introduce three pairs of vertices in the middle. Intuitively, there are three pairs since each clause contains three literals, and there are pairs to encode whether the bit corresponding to this selector gadget is 0 or 1. Then a packing of the vertices on the left, i.e., a packing for the selector gadgets,



Figure 2.2: An illustration of the construction for the double exponential lower bound for *H*-HITPACK. The two topmost gadgets determine the clause number we consider. Each gadget $C_{\lambda,j,p}$ at the bottom encodes that literal λ appears in the *j*th clause at position *p*. The hollow vertices indicate deleted vertices representing an assignment.

The packing represented by the colored triangles represents the evaluation of the second clause that is $C_2 = (\overline{x}_1 \lor x_2 \lor x_3)$, which is not satisfied by the chosen assignment of x_1 = true and $x_2 = x_3$ = false.

can interact in *m* different ways with the $O(\log(m))$ vertices in the middle. Each of these possibilities corresponds to a different selection of (the encoding of) a clause.

We verify the satisfying assignment by ensuring that no matter how we might choose a maximum packing on the left (i.e., no matter which clause we look at), the maximum packing on the right is small. This corresponds to verifying that each clause is satisfiable. A crucial difference to the Σ_2^{P} -hardness proof lies in the fact that, here, the small packing is ensured by the variable gadgets (if a solution exists) and not by the clause gadget.

The treewidth of the construction is $O(\log(m))$ since this is the number of vertices with which the gadgets interact (and each gadget separately has constant treewidth).

Double-exponential Lower Bound for SQUARE-HITPACK and CYCLE-HITPACK Parameterized by Treewidth. We first prove the lower bound for SQUARE-HITPACK and then extend it to CYCLE-HITPACK as follows. We define the reduction for SQUARE-HITPACK in a way such that whenever a cycle packing \mathcal{P} contains a *large* cycle of length at least five, then we can repack \mathcal{P} to obtain a packing \mathcal{P}' by replacing this large cycle with a C_4 . This keeps the number of cycles the same (or might actually increase it) while reducing the number of large cycles. Hence, the maximum possible cycle packing only contains cycles of length four.

The basic high-level idea for the lower bound for SQUARE-HITPACK is similar to the previous one for the general case. However, instead of having a middle part with $O(\log m)$ vertices (which dominates the pathwidth), we have to find a different way of encoding the clause numbers by only using $O(\log m/\log \log m)$ vertices.

To make this possible, we have to change the way the gadgets on the left and right side interact with the vertices in the middle. For the previous construction the gadgets only cover a single vertex while the remaining part of the triangle is entirely contained either in the left or the right half. When packing four-cycles we can change this and allow that those cycles which contain vertices in the middle have exactly one vertex on the left side and exactly one vertex on the right side. With this method, the position of the cycle can be described by a matching for the vertices in the middle. The idea is to introduce two groups of *t* vertices each where $t! \approx m$. Then there are t! possible perfect matchings between the vertices from the first group and the vertices from the second group. With this it is possible

to associate with each clause a unique perfect matching on these vertices. The gadgets on the left and right side are then adjusted such that they connect each pair of vertices from the matching by a path of length two.

Since choosing $t \approx \log m / \log \log m$ satisfies the above property, there are $O(\log m / \log \log m)$ vertices in the middle part which then determines the pathwidth of the graph.

3 CYCLE-HITPACK Parameterized by $k + \ell$

In this section we prove the following Theorem 1.4.

Theorem 1.4. *CYCLE-HITPACK can be solved in time* $2^{\text{poly}(p)} \cdot n^{O(1)}$ (where $p \coloneqq k + \ell$).

Recall that an instance $I = (G, U, k, \ell)$ of CYCLE-HITPACK consists of a graph G, a set $U \subseteq V(G)$ of undeletable vertices, a budget k for the number of vertices that can be deleted, and an integer ℓ as a strict upper bound on the size of the cycle packing in the graph after removing the solution, that is, the size of the cycle packing in the resulting graph can be only strictly smaller than ℓ .

We will make use of a known close relationship between the parameter $k + \ell$ and the feedback vertex set size of *G*.

Step 0: From $k + \ell$ to Feedback Vertex Sets. The main work of this section is to show the following result.

Theorem 3.1. An instance (G, U, k, ℓ) of CYCLE-HITPACK given with a feedback vertex set F of the n-vertex graph G can be solved in time $2^{\text{poly}(|F|+k)} \cdot n^{O(1)}$.

With Theorem 3.1 in hand, it is then straight-forward to prove Theorem 1.4.

Proof of Theorem 1.4. From the Erdős–Pósa Theorem [24], either *G* has $k + \ell$ vertex-disjoint cycles, or it has a feedback vertex set of size $O((k + \ell) \log(k + \ell))$. In particular, from [20, Theorem 2.3.2], if the size of a minimum feedback vertex set in *G* is larger than $k^* = 4(k+\ell)(\log(k+\ell) + \log\log(k+\ell) + 4) + k + \ell - 1$, then *G* has at least $k + \ell$ vertex disjoint cycles. Using the $2^{O(k^*)} \cdot n^{O(1)}$ algorithm for finding a feedback vertex set of size at most k^* [44], we can compute such a feedback vertex set, or otherwise conclude that *G* has at least $(k + \ell)$ vertex-disjoint cycles.

If the algorithm computes a feedback vertex set *F* of size at most k^* then, by Theorem 3.1, we can obtain a solution for the instance (G, U, k, ℓ) in total time

$$2^{\text{poly}(k^*+k)} \cdot n^{O(1)} = 2^{\text{poly}(k+\ell)} \cdot n^{O(1)}.$$

Otherwise, there are $(k + \ell)$ disjoint cycles in *G*. Then (G, U, k, ℓ) is a No-instance (as deleting any set of at most *k* vertices results in a graph which contains at least ℓ vertex-disjoint cycles).

So it remains to prove Theorem 3.1. To shorten notation, from now on, whenever we consider an instance (G, U, k, ℓ) of CYCLE-HITPACK that is given with a feedback vertex set F of G, we will use (G, U, F, k, ℓ) to denote this instance. Suppose we are given an instance $I = (G, U, F, k, \ell)$ of CYCLE-HITPACK. The idea behind the algorithm is as follows.

- 1. We guess the intersection of the solution with the feedback vertex set *F*. The intersection is then removed and the remaining vertices from the feedback vertex set are made undeletable.
- 2. We reduce the degree of the instance such that it is bounded in terms of k and |F|. For this we first mark parts of the graph that should not be removed and then iteratively delete parts that are not marked. This marking procedure ensures that for all possible solutions there is a way to tweak the cycle packing to avoid the deleted vertices by only using vertices from the parts that have been marked.

- 3. We introduce the notion of usable paths and cycles and show that it suffices to rule out large cycle packings that consists of usable cycles only.
- 4. We use a branching procedure to generate instances of a simpler problem where we only have to hit paths from a given candidate set by the solution. We design the candidate sets in a way such that the equivalence to the original instance is preserved.
- 5. For each such candidate set of paths we check whether there is a set of deletable vertices such that every path that should be hit is indeed hit. That is, we solve the easier problem and therefore, solve the original problem.

Based on this high-level overview of the algorithm we now formalize the individual steps of the algorithm.

Step 1: Making the Feedback Vertex Set Undeletable. In the first step, the algorithm guesses the intersection of an optimal solution with the set *F*. For each such guess $F' \subseteq F$, the algorithm creates a new instance $(G - F', F \setminus F', U \cup (F \setminus F'), k - |F'|, \ell)$. The following result immediately follows.

Lemma 3.2. The instance (G, U, F, k, ℓ) is a Yes-instance of CYCLE-HITPACK, if and only if there is some $F' \subseteq F$ such that $(G - F', U \cup (F \setminus F'), F \setminus F', k - |F'|, \ell)$ is a Yes-instance.

The rest of the algorithm solves each of these $2^{|F|}$ instances and reports Yes if at least one of these instances reports Yes. Therefore, for the remaining section we assume that the instance (G, U, F, k, ℓ) satisfies $F \subseteq U$, that is, the vertices in F are undeletable.

Some Useful Notation. Before we proceed, we first introduce some notations. For each $i \in F$, we denote by N_i the set of neighbors of i in G - F. Note that every cycle of G intersects F. We denote the forest G - F by G'.

Let *C* be a cycle packing in *G*. For a cycle $C \in C$ and a sub-path P_1 of *C* such that $V(P_1) \subsetneq V(C)$, by $C \setminus P_1$, we denote the set of subgraphs obtained from *C* by replacing the cycle *C* with the path $C - P_1$. By $V(C \setminus P_1)$ we denote the vertex set of $C \setminus P_1$. Let u_0, v_0 be the endpoints of $C - P_1$ and let u_1, v_1 be the endpoints of P_1 . Let P_2 be a path with endpoints u_2, v_2 such that $V(P_2) \cap V(C \setminus P_1) = \emptyset$ and u_0u_2 and v_0v_2 are edges of *G*. By $(C \setminus P_1) \cup P_2$ we denote the cycle packing obtained from $C \setminus P_1$ by replacing the path $C - P_1$ with the cycle formed by $C - P_1$ together with P_2 and the edges u_0u_2 and v_0v_2 .

For any cycle packing *C* of *G*, the *G'*-*paths of C* are the paths obtained by deleting *F* from the cycles of *C*. Since *F* is a feedback vertex set of *G*, we have $|C| \le |F|$. As deleting one vertex of *F* increases the number of paths (obtained from *C*) by at most one, we get the following observation, which we use frequently.

Observation 3.3. Let C be a cycle packing of G. Then the number of G'-paths of C is at most |F|.

For a graph *G* and two vertex sets $X, Y \subseteq V(G)$, an (X, Y)-path in *G* is a path from some $x \in X$ to some $y \in Y$; that is, one endpoint belongs to *X* and the other endpoint belongs to *Y*. To simplify notation we also say that a $(\{u\}, \{v\})$ -path in *G* is a (u, v)-path in *G*, that is, a path with the two endpoints *u* and *v*. In the following, when referring to an (N_i, N_j) -path *P* we also implicitly require that $V(P) \cap F = \emptyset$.

We say that a path *P* is contained in a tree *T* if $V(P) \subseteq V(T)$. Similarly, we say that a cycle *C* contains a path *P* if $V(P) \subseteq V(C)$.

Step 2: Bounding the Degree of *G*'. As a next step we prove a bound on the degree of the vertices. To this end, we design a procedure to modify the given instance until the resulting instance has low degree, that is, the largest degree is at most $O(|F|^3 + k|F|^2)$. Formally, we set

$$\Upsilon := |F|^3 + (k+3)|F|^2 + (k+2)|F|$$
(3.1)

and then remove vertices from the instance until the maximum degree of G' it at most Υ . We say that an instance *is of low degree with respect to* Υ if, for all $v \in V(G')$, it holds that $\deg_{G'}(v) \leq \Upsilon$.

Lemma 3.4. Let $I = (G, U, F, k, \ell)$ be an instance of CYCLE-HITPACK with $F \subseteq U$. In time O(poly(|G|)) we can construct an equivalent instance $I_1 = (G_1, U_1, F, k, \ell)$ of low degree with respect to Υ , i.e., for all $v \in V(G_1) \setminus F$, the new graph G_1 satisfies $\deg_{G_1-F}(v) \leq \Upsilon$, and $E(G_1) \subseteq E(G)$ and $F \subseteq U_1 \subseteq U$.

Proof. Consider an arbitrary vertex $v \in V(G')$ such that $\deg_{G'}(v) \ge \Upsilon + 1$. Let *T* be the tree of *G'* containing *v* and root *T* at *v*. For all neighbors $u \in N_{G'}(v)$ of *v*, we denote by T_u the subtree of *T* rooted at the vertex *u*. We perform the following MARKING PROCEDURE to mark certain subtrees rooted at the children of *v*.

- 1. Initially, all trees in $\{T_u \mid u \in N(v)\}$ are unmarked.
- 2. For every pair $(i, j) \in F \times F$, repeat the following. If there are at least k + |F| + 2 unmarked trees in $\{T_u \mid u \in N_{G'}(v)\}$ each of which contains an (N_i, N_j) -path, then mark an arbitrary set of k + |F| + 2 of them; otherwise, mark all of them.

Once this marking step is performed for every pair $(i, j) \in F \times F$ (or if all trees rooted at the children of v are already marked), we continue marking the remaining unmarked trees in the following step.

3. For every $i \in F$, if there are at least k + |F| + 2 unmarked trees in $\{T_u \mid u \in N_{G'}(v)\}$ that contain some vertex of N_i , then mark an arbitrary set of k + |F| + 2 of them; otherwise, mark all of them.

Observe that the number of marked trees is at most

$$|F|^{2}(k+|F|+2) + |F|(k+|F|+2) = |F|^{3} + (k+3)|F|^{2} + (k+2)|F| = \Upsilon.$$

Claim 3.5. Let T_x be an unmarked tree in the set $\{T_u \mid u \in N_{G'}(v)\}$. Pick an arbitrary leaf w of T_x . Then the original instance I is equivalent to the reduced instance $I' = (G - \{w\}, U \setminus \{w\}, F, k, \ell)$.

Proof of Claim. If $S \subseteq V(G) \setminus U$ is a solution to the input instance (G, U, F, k, ℓ) , then $S \setminus \{w\}$ is a solution to the instance $(G - \{w\}, U \setminus \{w\}, F, k, \ell)$. This proves the forward direction of the equivalence.

We now prove the backward direction. Let $S \subseteq V(G) \setminus \{w\}$ be a solution of the reduced instance I'. For the sake of a contradiction, assume there is a cycle packing C in G-S of size at least ℓ . This implies that there must be a cycle $C \in C$ which contains w. Since F is a feedback vertex set, it intersects all cycles and hence, there exist $i, j \in F$ (where i could be the same as j) such that C contains an (N_i, N_j) -path. Moreover, there is an (N_i, N_j) -path P in C that is also contained in T and goes through w and therefore, intersects T_x (as T is rooted at v and x is a neighbor of v).

In the following we prove that (due to the marking procedure), we can replace the path P by another path Q that does not use w. For this we argue that there is at least one marked tree T_u for some $u \in N_{G'}(v)$ that does not intersect with the given cycle cover of the set S. We distinguish two cases depending on whether the path P is entirely contained in T_x or also goes through v.

To simplify notation we set $\mathcal{T} := \{T_u \mid u \in N_{G'}(v)\}$ in the following.

Case 1. The path *P* is contained in T_x , that is, $V(P) \subseteq V(T_x)$. By the MARKING PROCEDURE and the fact that T_x is unmarked, there are k + |F| + 2 trees in \mathcal{T} , denote this set by \mathcal{T}_0 , that have been marked for the pair $(i, j) \in F \times F$.

Note that at most *k* trees in \mathcal{T}_0 are hit by *S*. Let \mathcal{T}_1 denote the set of the trees in \mathcal{T}_0 that are not hit by *S*. From the size bound on *S*, we directly get that $|\mathcal{T}_1| \ge |\mathcal{T}_0| - k \ge |F| + 2$.

For the next step, let \mathcal{P} be the set of G'-paths of C. Let \mathcal{T}_2 be the set of trees from \mathcal{T}_1 that do not intersect a path from \mathcal{P} . Suppose that a path Q of \mathcal{P} goes through v. In this case Q can intersect up to two trees in \mathcal{T}_1 . Since the paths of \mathcal{P} are vertex-disjoint, each path in $\mathcal{P} \setminus \{Q\}$ can intersect

at most one tree in \mathcal{T}_1 . By Observation 3.3, we know that the number of G'-paths of C is at most |F|. Hence, the size of \mathcal{T}_2 is at least $|\mathcal{T}_1| - (|F| + 1) \ge 1$. So, let T_y be an arbitrary tree in \mathcal{T}_2 .

Since T_y was marked for the pair (i, j) by the above MARKING PROCEDURE, it contains an (N_i, N_j) path P' which is disjoint from $C \setminus P$ and the solution S. Therefore, $(C \setminus P) \cup P'$ forms a cycle
packing of size at least ℓ in $(G - \{w\}) - S$. But this immediately contradicts our assumption that S is a solution for the instance I'.

Case 2. The path *P* passes through both *v* and *w*. Without loss of generality, we can assume that *P* ends in T_x at some vertex of N_i .

By the MARKING PROCEDURE there are at least k + |F| + 2 marked trees in \mathcal{T} that contain some vertex of N_i . Denote this set of trees by \mathcal{T}_0 .

At most *k* trees in \mathcal{T}_0 are intersected by the solution *S*. Moreover, at most |F| trees in \mathcal{T}_0 are intersected by *C* (recall that *P* also intersects T_x which is not marked). Let \mathcal{T}_1 be the set of the remaining trees in \mathcal{T}_0 . We directly get that $|\mathcal{T}_1| \ge |\mathcal{T}_0| - k - |F| \ge 2$. From the size bound on \mathcal{T}_1 , we get that there is at least one tree in \mathcal{T}_1 , say T_y , that is disjoint from *C* and *S* and contains some vertex of N_i .

Denote the unique (N_i, y) -path from a neighbor of i to y by P_1 . Let P_0 be the subpath of P from w to x in the tree T_x . Since P_1 is disjoint from S and C, we can use P_1 to replace the path P_0 in the cycle packing. Formally, $(C \setminus P_0) \cup P_1$ is a cycle packing of size at least ℓ in the reduced graph after deleting the solution S. But this immediately contradicts our assumption that S is a solution.

After applying the above MARKING PROCEDURE and Claim 3.5 for all vertices of high degree exhaustively, the instance satisfies $\deg_{G'}(v) \leq \Upsilon$ for every $v \in V(G')$.

It remains to prove the running time of the above procedure. As for each vertex the procedure runs in time polynomial in the size of the graph, the stated runtime directly follows.

Step 3: Usable Paths and Cycle Packings. As a next step we define the notion of *usable paths* and *usable cycle packings*. We then show that it is enough to restrict our attention to usable cycle packings (and not care about other cycle packings). This notion is crucial to bound the depth of the branching tree that we describe a little later.

For any $i, j \in F$ (where *i* could be the same as *j*), we denote by $G^{i,j}$ the sub-forest of *G'* obtained as follows: repeatedly delete leaves that do not belong to $N_i \cup N_j$ from *G'* until all leaves are contained in $N_i \cup N_j$.

For any two vertices $u, v \in N_i \cup N_j$, we define $dist_{\geq 3}^{i,j}(u, v)$ as the number of internal vertices on the unique (u, v)-path in $G^{i,j}$ whose degrees are at least 3 in $G^{i,j}$. If there is no (u, v)-path in $G^{i,j}$, we define $dist_{\geq 3}^{i,j}(u, v) = +\infty$.

Definition 3.6 (Usable Paths and Cycle Packings). For any two vertices $i, j \in F$ (i = j is allowed), an (N_i, N_j) -path P from u to v is called usable if the following three conditions hold:

- (i) path P is contained in $G^{i,j}$,
- (ii) path P is a minimal (N_i, N_j) -path, meaning no subpath of P of length less than |P| is an (N_i, N_j) -path, an (N_i, N_i) -path, or an (N_j, N_j) -path, and
- (*iii*) dist^{*i*,*j*}_{>3}(*u*, *v*) $\leq |F| + 1$.

We say that a cycle packing C is usable if all its G'-paths are usable.

With this definition we prove as a next step that it suffices to focus on usable cycle packings only. Hence, all other cycle packings can be ignored. **Lemma 3.7.** If a graph G with a feedback vertex set F has a cycle packing of size ℓ , then G has a usable cycle packing of size ℓ .

Proof. Let *C* be a cycle packing in *G* of size ℓ such that the number of *G'*-paths of *C* that are not usable is minimized. Let *P* be a *G'*-path of *C* which is not a usable path and let *u* and *v* be the endpoints of *P*. Let *i*, *j* \in *F* be the neighbors of *u*, *v* such that the cycle of *C* that contains *P* also contains the edges *ui* and *vj*. This especially implies that *P* is an (*N_i*, *N_j*)-path in *G'*.

If *P* is not a minimal (N_i, N_j) -path, then let *P'* be a subpath of *P* that is a minimal (N_i, N_j) -path (minimal (N_i, N_i) -path or (N_j, N_j) -path). Hence, $C' = (C \setminus P) \cup P'$ is also a cycle packing of size ℓ in *G*. Therefore, we can assume that all *G'*-paths of *C* are minimal.

Next we assume that P is a minimal (N_i, N_j) -path and that $\operatorname{dist}_{\geq 3}^{i,j}(u, v) \geq |F| + 2$. Let $x_1, \ldots, x_{|F|+1}$ be the internal vertices of P traversed from u in order such that each of them is a vertex of degree at least 3 in $G^{i,j}$. For all $q \in [|F|+1]$, we define the unique tree T(q) as the tree in $G^{i,j} - E(P)$ containing x_q . From Observation 3.3, we know that C contains at most |F| distinct G'-paths. Hence, there exists some $q_0 \in [|F|+1]$ such that $T(q_0) \setminus \{x_{q_0}\}$ does not intersect C. Moreover, since x_{q_0} is a vertex of degree at least 3 in $G^{i,j}$, tree $T(q_0)$ contains at least one vertex from $N_i \cup N_j$.

Now we distinguish two cases depending on how many vertices from $N_i \cup N_j$ appear in $T(q_0)$.

One vertex from $N_i \cup N_j$ appears in $T(q_0)$. Formally, we have that $|V(T(q_0)) \cap (N_i \cup N_j)| = 1$. Let w be this vertex, that is, w is the leaf of T(q).

In this case $T(q_0)$ is a path in $G^{i,j}$ and let P' be the unique (u, w)-path in $G^{i,j}$ (and thus in G'). By assumption about u and v, we get that $dist_{\geq 3}^{i,j}(u, w) \leq |F| + 1$ and P' is a usable path.

In conclusion we get that $C' = (C \setminus P) \cup P'$ is also a cycle packing of size ℓ in *G*.

Multiple vertices from $N_i \cup N_j$ **appear in** $T(q_0)$. In this case we formally get that $|V(T(q_0)) \cap (N_i \cup N_j)| \ge 2$. Let u' and v' be two distinct vertices in $T(q_0)$ such that they are also contained in $N_i \cup N_j$. Moreover, we require that the unique path P' from u' to v' does not contain any other vertex from $N_i \cup N_j$. Since $T(q_0)$ is either a path or a tree with at least two leaves and, by definition of $G^{i,j}$, all leaves belong to $N_i \cup N_j$, we can choose u' and v' such that $dist_{\ge 3}^{i,j}(u',v') \le 1$.

We get that $C' = (C \setminus P) \cup P'$ is also a cycle packing of size ℓ in G or C' contains a cycle packing of size ℓ (after removing the path from i to j) in case $u', v' \in N_i$ or $u', v' \in N_j$ (note that a path starting from i and ending with i is also a cycle).

In both of the above cases, we get a cycle packing of size ℓ with strictly larger number of usable G'-paths. This contradicts the choice of C and thus, completes the proof for the lemma.

Rich Pairs and a Bound for the Number of Usable Paths. For all $i, j \in F$, we bound the number of usable (N_i, N_j) -paths that are hit by a fixed vertex $v \in G'$ by some value Γ or prove that this pair is rich. We say that a pair $(i, j) \in F \times F$ is a *rich pair* if, for any cycle packing *C* of *G*, there are at least k + 1 vertex-disjoint $(N_i \cup N_j, N_i \cup N_j)$ -paths in *G'* that are disjoint from *C*.

We show that, if a pair (i, j) is not rich, then Γ is the maximum number of usable (N_i, N_j) -paths that can be hit by any fixed vertex, where we define Γ as

$$\Gamma := (\Upsilon(2|F| + k)(|F| + 3))^2.$$
(3.2)

This bound is the key property to obtain a small depth of the branching tree of the branching procedure that we describe later. See Figure 3.1 for an illustration of Lemma 3.8.

Lemma 3.8. Let G be a graph of low degree with regard to Υ . For all $v \in V(G')$ and $i, j \in F$, either (i, j) is a rich pair, or the number of usable (N_i, N_j) -paths that are hit by v, i.e., intersected by vertex v, is at most Γ .



Figure 3.1: An illustration from the proof of Lemma 3.8. The four highlighted paths at the bottom belong to the assumed maximal collection \mathcal{P} . For convenience, we use *i* and *j* to denote the neighbors of vertex $i, j \in F$ respectively. The nodes with diamond shape belong to $A = \bigcup_{P \in \mathcal{P}} A_P$, and after removing these nodes, there is one component which has more than one leaf (appearing in the box). Then, we can add the highlighted path in this box to \mathcal{P} and thus, strictly increase the size of \mathcal{P} .

Proof. Fix some vertex $v \in V(G')$, some $i, j \in F$ and let T_v be the tree of $G^{i,j}$ that contains v. We define T as a maximal subtree of T_v containing v such that every (N_i, N_j) -path contained in T is usable and every leaf of T is in $N_i \cup N_j$. We root T at v. Observe that the vertices of $N_i \cup N_j$ appear only at the leaves of T, as otherwise some (N_i, N_j) -paths in T would not be minimal (and thus not usable).

From the definition of usable paths, it follows that every usable (N_i, N_j) -path in G' that is hit by v has its endpoints in the set $(N_i \cup N_j) \cap V(T)$, which is precisely the set of leaves of T. Hence, the number of usable (N_i, N_j) -paths hit by v is at most $|(N_i \cup N_j) \cap V(T)|^2$.

Based on this, our new goal is to prove that either (i, j) is a rich pair, or the number of leaves of *T* is at most $\sqrt{\Gamma} = \Upsilon(2|F| + k)(|F| + 3)$.

We say that two vertices of *T* are *incomparable* if neither vertex is a descendant of the other one in *T*. For a path *P* in *T*, we define lca(P) as the lowest common ancestor of the two endpoints of *P* in *T*. Consider a maximal collection \mathcal{P} of pairwise disjoint $((N_i \cup N_j), (N_i \cup N_j))$ -paths in *T* such that the following two conditions hold:

- For two distinct paths $P_1, P_2 \in \mathcal{P}$, $lca(P_1)$ is incomparable with $lca(P_2)$.
- For every path $P \in \mathcal{P}$, there is no other $((N_i \cup N_j), (N_i \cup N_j))$ -path P' in T such that lca(P') is a descendant of lca(P).

Observe that any path in G' can intersect at most two paths in \mathcal{P} . In particular, since any cycle packing C of G has at most |F| different G'-paths, at most 2|F| paths in \mathcal{P} can intersect C. Therefore, if $|\mathcal{P}| \ge 2|F|+k+1$, then (i, j) is a rich pair. For the remainder of the proof we assume that $|\mathcal{P}| \le 2|F|+k$. Recall that we aim to bound the number of leaves of T.

For each $P \in \mathcal{P}$, we additionally define the set A_P as the set of vertices on the unique path from lca(P) to v that have degree at least three in $G^{i,j}$. We directly get that $|A_P| \leq dist_{\geq 3}^{i,j}(v, lca(P)) + 2 \leq |F| + 3$, since all (N_i, N_j) -paths in T are usable.

We set $A = \bigcup_{P \in \mathcal{P}} A_P$ and get $|A| \le (2|F| + k)(|F| + 3)$ as $|\mathcal{P}| \le 2|F| + k$. As a next step we define the graph $T' = T \setminus A$. Since *T* is connected and deg_{*G'*}(*u*) $\le \Upsilon$ for every $u \in V(G')$, the graph *T'* has at

most $\Upsilon(2|F|+k)(|F|+3)$ components. In particular, every connected component of T' contains at most one vertex of $N_i \cup N_j$. Suppose for contradiction that one component of T' has at least two vertices of $N_i \cup N_j$. Then in this component we can find an $((N_i \cup N_j), (N_i \cup N_j))$ -path \widehat{P} satisfying that (i) $lca(\widehat{P})$ does not belong to A; (ii) there is no other $((N_i \cup N_j), (N_i \cup N_j))$ -path P' in T such that lca(P')is descendant of $lca(\widehat{P})$. Condition (i) implies that for any $P \in \mathcal{P}$, lca(P) is incomparable with $lca(\widehat{P})$. Then we could strictly increase the size of \mathcal{P} , contradicting the maximality of \mathcal{P} .

Therefore, the number of vertices of $(N_i \cup N_j) \cap V(T)$, i.e., the number of leaves of *T*, is at most $\Upsilon(2|F| + k)(|F| + 3)$.

Step 4: The Branching Procedure. For a given instance (G, U, F, k, ℓ) , we now design a branching procedure, which we call Get-Candidates. This procedure generates $2^{\text{poly}(|F|+k)}$ candidate instances of a different (relatively easier) problem. We design these instances such that (i) it is enough to look for a solution for these candidate instances, and (ii) each of these candidate instances can be solved in time $2^k n^{O(1)}$.

We first present an informal description of the branching procedure. First, observe that if the input instance is a Yes-instance and C is a cycle-packing of size ℓ , then every solution, i.e., set of vertices that are deleted, hits at least one of the G'-paths of C. The branching procedure stores two complementary sets **avail** and **hit** of G'-paths such that it first finds a usable cycle packing C of size ℓ in G which only uses paths in **avail** and then branches on *which* particular G'-path of C is hit by the solution, that is, which path is added to **hit** and removed from **avail**. Note that unlike typical branching algorithms, this procedure does not branch on the choice of a fixed vertex into the solution. Instead, in one branch, it considers a set of vertices (namely a G'-path) that is guaranteed to be hit by the solution.

We first describe the procedure to find a usable cycle packing which uses paths from a specified set only. For this we make use of the subroutine in Lemma 3.9.

Lemma 3.9. Let *H* be a forest *H* on *n* vertices and $\mathcal{P}_1, \ldots, \mathcal{P}_f$ be *f* collections of paths of *H*. In time $2^{O(f)} \cdot n^{O(1)}$, we can find *f* pairwise vertex-disjoint paths P_1, \ldots, P_f such that, for each $i \in [f]$, it holds that $P_i \in \mathcal{P}_i$ whenever such paths exist or correctly answer No otherwise.

Note that the notation used in Lemma 3.9 is independent of the notation of the algorithm that we have built so far. As the proof of this lemma uses standard bottom-up dynamic programming over rooted trees, we defer the proof to Section 3.1.

With this subroutine, we can design the first ingredient of the branching procedure.

Lemma 3.10. Let (G, U, F, k, ℓ) be an instance of CYCLE-HITPACK and let avail be some set of G'-paths. In time $2^{O(|F| \log |F|)} \cdot n^{O(1)}$ we can find a usable cycle packing C of size ℓ in G whose G'-paths are contained in avail.

Proof. Our goal is to use Lemma 3.9 to find disjoint paths in the graph G' that can be extended to a usable cycle packing of size ℓ in G. As input of the algorithm in Lemma 3.9 we use f collections of (N_{i_1}, N_{j_1}) -paths, ..., (N_{i_f}, N_{j_f}) -paths where $(i_1, j_1), \ldots, (i_f, j_f)$ are distinct pairs of $F \times F$. However, these pairs cannot be chosen arbitrarily as we must be able to extend the paths to a cycle packing. To find these pairs, we start with some preprocessing.

Observe that a cycle packing *C* naturally induces a collection of such pairs from $F \times F$ based on the vertices from *F* that appear in each cycle. But it can also happen that vertices in *F* appear in only one pair because they are connected to some other vertex in *F* by an edge. Based on these observations we show how to compute all possible sets of pairs that have to be considered.

We first consider all possible permutations π of F. Note that this does not provide any information about the cycles and how the vertices in F are connected. To resolve this, we introduce four special symbols \rightarrow_{edge} , \rightarrow_{path} , \frown_{edge} , and \frown_{path} and insert one of them after each position in the permutation π . The permutation is then a string π' of length 2|F|. The first two symbols, i.e., \rightarrow_{edge} and \rightarrow_{path} , indicate how two consecutive vertices in the permutation are connected, either by an edge or by a path in *G'*. The other two symbols, i.e., \frown_{edge} and \frown_{path} , indicate that the cycle is closed by an edge or a path in *G'* to the first vertex of the cycle, the previous vertex in π' following a symbol \frown_{edge} or \frown_{path} .

For example the string $1 \rightarrow_{\text{path}} 3 \rightarrow_{\text{edge}} 4 \swarrow_{\text{path}} 5 \rightarrow_{\text{edge}} 2 \curvearrowright_{\text{path}}$ represents two cycles; the first cycle starts at 1 and is then connected to 3 by a path in G', vertex 3 has an edge to 4 and from 4 there is a path in G' back to 1; the second cycle starts at 5 and has an edge to 2 and from there a path in G' back to 5.

By first choosing the permutation of *F* and then inserting the symbols, we get that there are at most $|F|! \cdot 4^{|F|} \in 2^{O(|F|\log|F|)}$ possible strings to consider. For each generated string, we check for each occurrence of \rightarrow_{edge} and \frown_{edge} whether the corresponding edge exists (for ease of notation we assume in this step that the vertices in *F* have self-loops). For each occurrence of \rightarrow_{path} and \frown_{path} , we add the corresponding pair (i, j) to a list $\mathcal{L}_{\pi'}$. We additionally discard the string if it represents less than ℓ cycles.

It remains to define the sets $\mathcal{P}_{i,j}$ for all $(i, j) \in \mathcal{L}_{\pi'}$ that serve as input for the algorithm from Lemma 3.9. For each $(i, j) \in \mathcal{L}_{\pi'}$, we pick the (N_i, N_j) -paths in the set **avail** which is given as input.

Now for each collection of sets of candidates we invoke the algorithm from Lemma 3.9. If the algorithm outputs a set of disjoint paths, we complete it to a usable cycle packing according to the above preprocessing. If no set of disjoint paths was found, we proceed to the next possible set of pairs, i.e., string π' , and repeat the procedure.

Eventually we find a usable cycle packing of size ℓ for G whose G'-paths are contained in **avail** or can conclude that no such packing exists.

Now we have everything ready to state the branching procedure Get-Candidates. Recall that we are working with the instance (G, U, F, k, ℓ) , where set U contains the undeletable vertices, set F is a feedback vertex set of G, and $F \subseteq U$. Throughout the following branching procedure, the instance (G, U, F, k, ℓ) is fixed. We can imagine that each node of the branching tree for Get-Candidates has a pair (avail, hit) associated with it, where avail and hit are sub-collections of usable (N_i, N_j) -paths for some $i, j \in F$. The set hit corresponds to the collection of G'-paths that have been guessed so far to be hit by the solution and the set avail contains all G'-paths that can still be used for a cycle packing. Therefore we also get avail \cap hit = \emptyset .

The idea of the branching procedure is that at each node of the branching tree, one finds a usable cycle packing of size ℓ with a set of r different G'-paths that are contained in **avail**. Then we branch into r directions (nodes) where each of the r nodes includes one of the r G'-paths into the set **hit** in the associated pair (**avail**, **hit**).

Now, we present the branching procedure formally.

Lemma 3.11 (Get-Candidates). Let (G, U, F, k, ℓ) be an instance of CYCLE-HITPACK of low degree. In time $2^{O((|F|^2k\Gamma)\log|F|)} \cdot n^{O(1)}$ we can construct a list of candidates $\{I_1, \ldots, I_p\}$ (for some $p \in 2^{O((|F|^2k\Gamma)\log|F|)}$), where for each $q \in [p]$, $I_q = (avail_q, hit_q)$, such that the instance (G, U, F, k, ℓ) is a Yes-instance if and only if there exists an index $q_0 \in [p]$ and a set $X \subseteq V(G) \setminus U$ of size at most k such that X hits all paths in hit_{q_0} .

Proof. We describe the branching procedure by constructing the labeled branching tree. For the root node of the branching tree initialize **avail** as the set of all usable (N_i, N_j) -paths in G' for every $i, j \in F$, and set **hit** = \emptyset .

At a node labelled (avail, hit), the Get-Candidates procedure performs the following two steps:

- **Step 1.** Use Lemma 3.10 to find a usable cycle packing *C* of size ℓ in *G* whose *G*'-paths are contained in **avail**.
- **Step 2.** Let \mathcal{P} be the *G'*-paths of *C*. Branch into $r := |\mathcal{P}|$ directions, by creating new child nodes associated with the label (avail \ {*P*}, hit \cup {*P*}) for all $P \in \mathcal{P}$.
- **First Stopping Criterion.** The branching procedure stops when *G* has no usable cycle packing of size ℓ whose *G*'-paths are totally contained in **avail**.

Second Stopping Criterion. The branching procedure also stops when the depth of the current branch in the branching tree is strictly more than $|F|^2 \cdot k\Gamma$.

At the end of the branching procedure, let the set of *candidates* be $\{I_1, \ldots, I_p\}$, where for each $q \in [p]$, $I_q = (avail_q, hit_q)$. Let \mathcal{L}_+ be the list of *promising candidates*, in which there are no usable cycle packing of size ℓ whose G'-paths are totally contained in avail, and let \mathcal{L}_- , called the *discarded* candidates, be the remaining candidates. The branching procedure returns \mathcal{L}_+ as the output.

As a first step we analyze the running time of the branching procedure.

Claim 3.12 (Running time of Get-Candidates). The running time of the branching procedure Get-Candidates is $2^{O((|F|^2k\Gamma)\log|F|)} \cdot n^{O(1)}$.

Proof of Claim. First, observe that for any pair (avail, hit) that is associated with some node of the branching tree of Get-Candidates, the size of the sets avail and hit is at most n^2 , where *n* is the number of vertices of the input graph *G*. This is because the sets avail and hit contain paths of *G'*, which is a forest. Since there is a unique path between any two vertices in a tree, the total number of paths in *G'* and hence in avail and hit is at most quadratic in the input size.

By Lemma 3.10, Step 1 of Get-Candidates can be executed in time $2^{O(|F| \log |F|)} \cdot n^{O(1)}$. Further from the second stopping condition of Get-Candidates, the depth of the branching tree is $|F|^2 k \Gamma$. Moreover, the width is at most |F| as the algorithm branches into $|\mathcal{P}|$ directions in Step 2 and, by Observation 3.3, it holds that $|\mathcal{P}| \leq |F|$.

We conclude that the number of nodes of the branching tree of Get-Candidates is $2^{O(|F|^2 k \Gamma \log |F|)}$. The running time follows directly.

As a next step we show that the output of the branching procedure can be used to recover the solution for the original instance.

Claim 3.13. If there exists (avail, hit) $\in \mathcal{L}_+$ and a set $X \subseteq V(G) \setminus U$ of size at most k such that X hits all paths in hit, then the instance (G, U, F, k, ℓ) is a Yes-instance.

Proof of Claim. By the design of the branching procedure Get-Candidates, at least one path of the *G*'-paths of every usable cycle packing of size ℓ are hit by *X* as otherwise **hit** would not have been added to \mathcal{L}_+ in the first stopping criterion. Hence, in $G \setminus X$, there are no usable cycle packings of size ℓ . From Lemma 3.7, we know that if *G* has a cycle packing of size ℓ , then *G* also has a *usable* cycle packing of size ℓ . It follows that in $G \setminus X$ there are no cycle packings of size ℓ . Since $X \subseteq V(G) \setminus U$ and $|X| \leq k$, set *X* is a solution to (G, U, F, k, ℓ) .

It remains to show that a solution for the original instance propagates to the new instances.

Claim 3.14. If the instance (G, U, F, k, ℓ) is a Yes-instance, then there exists (avail, hit) $\in \mathcal{L}_+$ and a set $X \subseteq V(G) \setminus U$ of size at most k such that X hits all paths in hit.

Proof of Claim. Suppose that *X* is a solution to the instance (G, U, F, k, ℓ) , that is, the vertex set $X \subseteq V(G) \setminus U$ is of size at most *k* such that *X* hits every cycle packing of size ℓ in G - X.

To construct the set hit, we analyze the branching procedure. In every step of Get-Candidates where we can find a usable cycle packing C of size ℓ in G, there is at least one path P of the G'-paths that is hit by X. Assume that this path is an (N_i, N_j) -path for some $i, j \in F$. We claim that we can choose P such that the corresponding (i, j) pair is not rich.

Suppose for contradiction that all of the G'-paths hit by X correspond to rich pairs of $F \times F$. Then by the definition of rich pairs, there are for every cycle packing at least k + 1 vertex-disjoint (N_i, N_j) -paths that are disjoint from the cycle packing. Hence, we can pick one of these paths that is not hit by X and replace the original path by it to get a new cycle packing C'. Thus X cannot hit all cycle packings of size ℓ , contradicting that X is a solution to the instance (G, U, F, k, ℓ) . Therefore, our claim above holds and we can choose P such that the corresponding pair is not rich.

Then following the branching procedure Get-Candidates, we can find a path in the branching tree which leads to a leaf node t of the branching tree, that is, we go to the child of the current node where P is included in corresponding set **hit**. By our choice of the paths in the set **hit**, all paths in the set **hit** associated with the leaf node t are hit by X by our claim above.

It remains to show that *t* is a promising candidate. Suppose that the depth of *t* in the branching tree is less than $|F|^2 \cdot k\Gamma$. In this case it is true that we cannot find a usable cycle packing \overline{C} at node *t* whose *G'*-paths are contained in **avail**. Hence, candidate *t* is promising.

Suppose that the depth of *t* in the branching tree is equal to $|F|^2 \cdot k\Gamma$ and we can still find a usable cycle packing \overline{C} at node *t* whose *G'*-paths are contained in **avail**. This implies that \overline{C} is not hit by *X*. By Lemma 3.8, *X* can hit at most $|F|^2 \cdot k\Gamma$ usable paths (every path in **hit** does not correspond to a rich pair by our claim). This contradicts that *X* is a solution to the instance (G, U, F, k, ℓ) . Thus *t* corresponds to a promising candidate, say (**avail**, **hit**). By the way we branch among all children of a node in the branching tree, the paths of **hit** are all hit by *X*. This completes the proof for this claim.

This concludes the proof of the branching procedure Get-Candidates.

Step 5: Solving Instances with Promising Sets. According to Lemma 3.11, to complete the algorithm, it suffices to consider an instance together with a promising candidate (**avail**, **hit**) and find a set of at most k vertices that intersect all paths in **hit**. Recall that the set **hit** contains paths of the forest G'.

If we do not have any undeletable vertices, i.e., if $U = \emptyset$, then this problem is equivalent to VERTEX MULTICUT ON TREES, which is polynomial-time solvable [17, Folklore]. If there are undeletable vertices, i.e., when $U \neq \emptyset$, then this problem resembles EDGE MULTICUT ON TREES which can be solved in $O(2^k \cdot n)$ time [35]. We give this algorithm dealing with promising sets in Lemma 3.15. If one can find a solution for any of the promising sets, then the algorithm reports that (G, U, F, k, ℓ) is a Yes-instance; otherwise, it reports a No.

Lemma 3.15 (Path-Hitting on Forests). Given a forest G', a set $U \subseteq V(G')$ of undeletable vertices, a collection of paths \mathcal{P} of this forest and an integer k. In time $2^k \cdot n^{O(1)}$, one can find a set $X \subseteq V(G') \setminus U$ of size at most k, if it exists, such that X hits all paths in \mathcal{P} .

Proof. Without loss of generality we can assume that G' is a tree that is rooted at some arbitrary vertex as otherwise we consider the trees of the forest sequentially and root each tree arbitrarily.

Let $P_{u,v}$ be a path from u to v in \mathcal{P} such that the lowest common ancestor (lca) of two endpoints of any other path in \mathcal{P} is not a descendant of the lca of u and v in G'. Let the lca of u and v be denoted as lca(u, v).footnoteObserve that lca $(u, v) \in \{u, v\}$ is possible. We define two distinguished vertices on the path $P_{u,v}$ as follows. Let u', v' be the first vertices on the path from lca(u, v) to u, v such that $u', v' \notin U$, respectively. We claim that there exists a minimum-sized set X disjoint from U that hits all paths in \mathcal{P} such that X contains either u' or v'. Once the claim is proven, it yields a straightforward branching algorithm with running time $2^k \cdot n^{O(1)}$.

We now show that our claim is true. Let \overline{X} be a minimum-sized set that is disjoint from U and intersects all paths in \mathcal{P} . In particular, \overline{X} intersects the $(u, \operatorname{lca}(u, v))$ -path or the $(\operatorname{lca}(u, v), v)$ -path of $P_{u,v}$. Without loss of generality, assume that \overline{X} intersects the $(u, \operatorname{lca}(u, v))$ -path of $P_{u,v}$ (the other case is symmetric) and let $\overline{u} \in \overline{X}$ be a vertex on the $(u, \operatorname{lca}(u, v))$ -path. We claim that $X = \overline{X} \setminus \{\overline{u}\} \cup \{u'\}$ is also a set that hits all paths in \mathcal{P} of minimum size. Suppose not, then there exists another path P_1 in \mathcal{P} , say with endpoints u_1 and v_1 , which is not hit by X and goes through \overline{u} . By the choice of $P_{u,v}$ as the path where the lca of the two endpoints is lowest in the tree, the path P_1 also goes through $\operatorname{lca}(u, v)$, and hence u'. Thus, P_1 is hit by X which proves the claim. This completes the proof for the lemma. \Box

Using Lemma 3.15, for each promising candidate (avail, hit), a set of size at most k that hits all paths in hit can be found in $2^k \cdot n^{O(1)}$ time, if it exists. We are now ready to complete the proof of Theorem 3.1 which we restate here for convenience.

Theorem 3.1. An instance (G, U, k, ℓ) of CYCLE-HITPACK given with a feedback vertex set F of the n-vertex graph G can be solved in time $2^{\text{poly}(|F|+k)} \cdot n^{O(1)}$.

Proof. Let $I = (G, U, F, k, \ell)$ be the input instance of CYCLE-HITPACK. The overall algorithm works as follows.

- 1. For each subset $D \subseteq F$ where $|D| \leq k$, we construct a new instance $I_D = (G D, U \cup (F \setminus D), F \setminus D, k |D|, \ell)$, that is, we guess the subset of the feedback vertex set that is deleted. where the feedback vertex set is undeletable.
- 2. For each instance I_1 from the first step we use the algorithm from Lemma 3.4 to create a new instance $I_2(I_1)$ of low degree with regard to Υ .
- 3. For each instance I_2 from the second step, we use the branching procedure Get-Candidates from Lemma 3.11 to generate a list $\mathcal{L}_+(I_2)$ of promising candidates.
- 4. For each instance I₂ from the second step and each candidate (avail, hit) in the corresponding list L₊(I₂) from the third step, we check if there is a set X of deletable vertices that hits every path in hit by using Lemma 3.15. If this is the case, then output Yes. Otherwise we proceed with the next set in L₊(I₂) or with the next instance from the first step.
- 5. If no branch outputs Yes, then the algorithm outputs No.

We first prove the correctness of the algorithm. The correctness of the branching in the first step follows from Lemma 3.2. For the second step the correctness follows directly from the properties of the algorithm in Lemma 3.4. The correctness of the remaining steps follows from the design of the procedure Get-Candidates in Lemma 3.11 and by Lemma 3.15.

It remains to analyze the running time of the entire algorithm. The first step takes time $2^{|F|} \cdot n^{O(1)}$. By Lemma 3.4, the second step can be applied in time polynomial in the size of the instance. According to Lemma 3.11, the branching procedure Get-Candidates runs in time $2^{O((|F|^2k\Gamma) \log |F|)} \cdot n^{O(1)}$, and the number of promising sets it generates is $2^{O((|F|^2k\Gamma) \log |F|)}$. The last step takes time $2^k \cdot n^{O(1)}$. As by assumption we have $\Gamma = \text{poly}(|F| + k)$, the entire procedure runs in time

$$2^{|F|} \cdot 2^{O((|F|^2 k \Gamma) \log |F|)} \cdot 2^k \cdot n^{O(1)} = 2^{\text{poly}(|F|+k)} \cdot n^{O(1)}$$

which concludes the proof.

3.1 Proof of Lemma 3.9: Finding Vertex-Disjoint Paths

We now prove Lemma 3.9, which we restate here for convenience.

Lemma 3.9. Let H be a forest H on n vertices and $\mathcal{P}_1, \ldots, \mathcal{P}_f$ be f collections of paths of H. In time $2^{O(f)} \cdot n^{O(1)}$, we can find f pairwise vertex-disjoint paths P_1, \ldots, P_f such that, for each $i \in [f]$, it holds that $P_i \in \mathcal{P}_i$ whenever such paths exist or correctly answer No otherwise.

Proof. We first show that it suffices to consider the case when *H* is a tree.

The Graph *H* is a Forest. Assume that *H* is a forest and let H_1, \ldots, H_r be the *r* different trees of *H*. For a subforest *H'* of *H* and a set of indices $I \subseteq [f]$, we define CoverPath(H', I) to be true if and only if *H'* contains a pairwise vertex-disjoint collection of paths $\{P_i \in \mathcal{P}_i \mid i \in I\}$.

Suppose that we can answer CoverPath(H', I) for any $I \subseteq [f]$ when H' is tree. For ease of notation, for all $j \in [r]$, we denote by \mathcal{H}_j the union of the first j trees of H, formally, we define $\mathcal{H}_j \coloneqq H_1 \uplus \cdots \uplus H_j$. It vacuously follows that CoverPath(H', \emptyset) = true for any forest H'. With these assumptions, for all $j \in [r]$ and all $I \subseteq [f]$, we can use the following dynamic program to compute CoverPath(H_j, I):

$$CoverPath(\mathcal{H}_j, I) := \bigvee_{I' \subseteq I} CoverPath(H_j, I') \land CoverPath(\mathcal{H}_{j-1}, I \setminus I')$$

Then the final output of the algorithm is CoverPath(H, [f]). The correctness of this step follows because all H_i 's are disjoint trees and $H = \mathcal{H}_r$.

If we assume that we can compute $\text{CoverPath}(H_j, I)$ for each $j \in [r]$ and $I \subseteq [f]$ in time $2^{O(f)} \cdot n^{O(1)}$, then the above dynamic program solves the problem on forests in time $2^{O(f)} \cdot n^{O(1)}$. As a next step we design the claimed algorithm for trees.

The Graph H is a Tree. Based on the above reasoning, we now focus on the case when H is a tree. We prove this lemma using bottom-up dynamic programming on H. To begin, we arbitrarily root the tree H. For each $v \in V(H)$, let H_v be the subtree rooted at v in H. For any vertex set $W \subseteq V(H)$ (of vertices that are incomparable, i.e., no vertex in W is a descendant of any other vertex in W), let H_W be the disjoint union of the subtrees rooted at each vertex $v \in W$. For a vertex v in H, we denote by child(v) be the set of children of v in H.

Our goal is to compute three tables *T*, T_{child} , and T_{path} such that, for all $I \subseteq [f]$, vertices $v \in V(H)$, and paths *P* in collection with $v \in V(P)$,

 $T[v, I] = \text{true} \iff \text{there are vertex-disjoint paths } \{P_i \in \mathcal{P}_i \mid i \in I\} \text{ in } H_v,$ $T_{\text{child}}[v, I] = \text{true} \iff \text{there are vertex-disjoint paths } \{P_i \in \mathcal{P}_i \mid i \in I\} \text{ in } H_{\text{child}(v)}, \text{ and } T_{\text{path}}[v, P, I] = \text{true} \iff \text{there are vertex-disjoint paths } \{P_i \in \mathcal{P}_i \mid i \in I\} \text{ in } H_v \setminus V(P).$

We compute the table entries T[v, I], $T_{child}[v, I]$ and $T_{path}[v, P, I]$ using a bottom-up dynamic programming on the rooted tree H.

We first we define the base cases. If $I = \emptyset$, then we set $T[v, \emptyset] = \text{true for every } v \in V(H)$. Similarly, if v is a leaf and $I = \{i\}$, then we set true if and only if $\{v\} \in \mathcal{P}_i$ (otherwise we define the table entry to be false). Finally, if v is a leaf and $|I| \ge 2$, then we can directly set T[v, I] to false.

For the remaining case, when $v \in V(H)$ is not a leaf and $|I| \ge 2$, then we compute the table entry by setting

$$T[v, I] := T_{\text{child}}[v, I] \lor \bigvee_{i \in I} \bigvee_{\substack{P \in \mathcal{P}_i, \\ v \in V(P)}} T_{\text{path}}[v, P, I \setminus \{i\}].$$

Observe that $T_{child}[v, I]$ and $T_{path}[v, P, I]$ can be computed with the analogous dynamic programming to CoverPath. Note that in $T_{path}[v, P, I]$ table we again end in the disjoint case. To address that we can add a dummy-vertex adjacent to every root of the trees in the forest.

Next we prove the correctness of the table entries.

Claim 3.16. For all vertices v of H, all sets $I \subseteq [f]$, all paths P in collection with $v \in V(P)$, the table entries T[v, I], $T_{child}[v, I]$, and $T_{path}[v, P, I]$ are computed correctly.

Proof of Claim. We give a proof by induction on the depth of v in H. We focus on the proof of correctness for the table T. The correctness proofs for T_{child} and T_{path} follow analogously.

Suppose there exists a collection of pairwise vertex-disjoint paths $\{P_i \in \mathcal{P}_i \mid i \in I\}$ in H_v . If v does not appear in any of these paths, i.e., $v \notin \bigcup_{i \in I} V(P_i)$, then the paths in $\{P_i \in \mathcal{P}_i \mid i \in I\}$ are also contained in $H_{\text{child}(v)}$ and by induction $T_{\text{child}}[v, I]$ = true. Moreover, if there is an index $i \in I$ such that path $P_i \in \mathcal{P}_i$ contains v, i.e., $v \in V(P_i)$, then $\{P_{i'} \mid i' \in I \setminus \{i\}\}$ are paths in $H_v - V(P_i)$. By induction this implies $T_{\text{path}}[v, P, I \setminus \{i\}]$ = true, which finishes this direction of the proof.

For the other direction, suppose that T[v, I] = true. We show that in this case there exists a collection of pairwise vertex-disjoint paths $\{P_i \in \mathcal{P}_i \mid i \in I\}$ in H_v . It is straightforward to verify the bases cases. Therefore, we focus on the case when v is not a leaf and $|I| \ge 2$.

From the definition of the table entry it follows that if T[v, I] = true, then (1) table entry $T_{\text{child}}[v, I]$ is true or³ (2) there is some index $\hat{i} \in I$ and some path $P \in \mathcal{P}_{\hat{i}}$ with $v \in V(P)$ such that $T_{\text{path}}[v, P, I \setminus \{\hat{i}\}]$ is true. In case (1), by induction, $H_{\text{child}}(v)$ contains the desired collection of paths. For case (2), the

³Case (1) and (2) are not necessarily disjoint.

induction hypothesis implies that $H_v - V(P)$ contains paths $\{P_i \mid i \in I \setminus \{i\}\}$ that are pairwise vertexdisjoint. From the fact that $P \in \mathcal{P}_{\hat{i}}$, it directly follows that $\{P_i \mid i \in I \setminus \{i\}\} \cup \{P\}$ is the desired collection of paths in H_v .

It remains to analyze the running time of the algorithm. Observe that the number of states in the tables T, T_{child} , and T_{path} is $2^{O(f)} \cdot n^{O(1)}$. Moreover, to compute a single table entry $2^{O(f)} \cdot n^{O(1)}$ operations are required.

4 EDGE-HITPACK Parameterized by $k + \ell$: Single-Exponential Algorithm

In this section, we prove Theorem 1.11.

Theorem 1.11. *EDGE-HITPACK can be solved in time* $3^{k+\ell} \cdot n^{O(1)}$.

Proof. For a graph *G*, we denote by v(G) the matching number of *H*, that is, the size of the maximum matching in *H*. It is well-known that a maximum matching (and thus the matching number) for a graph *H* can be computed in polynomial time using the algorithm by Edmonds [22] or by Micali and Vazirani [62] for example.

Let $I = (G, U, k, \ell)$ be the given instance of EDGE-HITPACK. The algorithm starts by some preprocessing of the instance to identify trivial Yes and No instances.

- Compute the matching number v(G) of G. If v(G) is smaller than ℓ , then directly answer Yes.
- Otherwise, compute the matching number $\nu(G[U])$ of G[U], that is, the subgraph induced by the undeletable vertices. If $\nu(G[U])$ is at least ℓ , then directly output No.
- Additionally, the algorithm outputs No if k < 0.

After this preprocessing, the algorithm proceeds as follows.

- 1. Compute a maximum matching M of G[U].
- 2. Invoke Edmonds' blossom algorithm [22] to compute an augmenting path *P* for *M* in *G*, that is, a path that starts and ends with vertices not covered by *M* and alternates between edges not in *M* and edges in *M*.

If no such augmenting path exists, then output Yes.

- 3. Let u and v be the two endpoints of P. Note that a single edge with both endpoints not in M is also an augmenting path and that at least one of u and v is deletable as otherwise M would not be the largest matching in G[U].
- 4. Construct three instances I₁ = (G \ {u}, U, k − 1, ℓ) if u ∉ U, I₂ = (G \ {v}, U, k − 1, ℓ) if v ∉ U, and (G, U ∪ {u, v}, k, ℓ), corresponding to the case that u is deleted, that v is deleted and that u and v are made undeletable. Solve these three instances recursively and output Yes if the algorithm return Yes for at least one instance.

To analyze the running time of the algorithm, we define a branching measure μ with $\mu(I) := k + \ell - 1 - \nu(G[U])$. By the preprocessing, $\mu(I)$ is always non-negative and from the definition of μ we get $\mu(I) \le k + \ell$.

If the algorithm deletes u or v, then the measure $\mu(I_1)$ and $\mu(I_2)$ decreases by one as k decreases by one. If the algorithm puts $\{u, v\}$ into U, then the measure $\mu(I_3)$ decreases by one as $\nu(G[U])$ increases by one because u and v are the endpoints of the augmenting path for the previously largest matching.

Observe that all steps of the algorithm can be computed in polynomial time. Since $\mu(I)$ decreases in each step and the algorithm branches into three cases, the bound on the runtime follows.

The correctness of the algorithm follows from the definition of our problem and the well-known Berge's theorem [5], which says that a matching M in a graph G is maximum if and only if there is no augmenting path with M.

5 *q*-СLIQUE-HITPACк Parameterized by Treewidth: Double-Exponential Algorithm

In this section we consider the *H*-HITPACK problem when parameterizing by treewidth and provide an algorithmic upper bound when *H* is a complete graph. The algorithm in this section serves two purposes. First, it is a smooth introduction to the more involved algorithm for *H*-HITPACK for general *H* in Section 7 with the additional advantage that the algorithm in this section has a slightly better dependence on tw. The second purpose is that it can be used as a black-box in Section 6 to get a single-exponential dependence on tw in the case when $H = K_2$.

Formally, in this section we prove the following theorem.

Theorem 1.7. For any fixed integer $q \ge 2$, q-CLIQUE-HITPACK can be solved in time $2^{2^{O(tw)}} \cdot n^{O(1)}$, where tw is the treewidth of the input graph.

Although the running time is double-exponential in treewidth, we provide a standard dynamic program based on the tree decomposition of the graph. Note that the claimed runtime allows us to omit the requirement that such a tree decomposition has to be given with the input graph because we can compute an optimal tree decomposition as the first step of the algorithm.

Intuition. For each bag, we consider the different ways in which a partial solution $D \subseteq V_t \setminus U$ could interact with the bag X_t . We describe this interaction by a triple (k_0, D_0, f_0) with the following interpretation.

- The set *D* contains exactly k_0 vertices not in X_t . Moreover, inside a bag X_t the set *D* deletes all the vertices in D_0 .
- For every set $A \subseteq X_t \setminus D_0$ the function $f_0(A)$ stores the following integer. We interpret A as the set of vertices we want to avoid, and f(A) is the size of the largest packing for $G_t D$ where additionally no vertex from A is covered.

The runtime is essentially bounded by the number of functions f_0 we have to consider. As there are 2^{tw+1} vertex subsets and for each such subset we want to store a value between 0 and *n*, the number of functions is at most $n^{2^{tw+1}}$. We later show that we can get a significantly better bound on the number of functions, which then leads to the claimed running time.

To formally exploit these properties, we have to design a dynamic program whose style deviates from the classical approaches for such algorithms. In most cases, we first aggregate the information from the appropriate states for the child nodes and then compute the entry for the parent node. However, we proceed in a different direction. When considering a state for a child node, we check for which states of the parent node this information is relevant. By this approach, it is not necessary to consider all possible table entries but only those where we store a non-zero entry (i.e., an entry corresponding to a valid partial solution).

Classes. Before we state the algorithm, we first introduce some notation. For any graph G' we let $v_{K_q}(G')$ be the K_q -packing number of G' (i.e., the number of vertex-disjoint complete copies of K_q). Consider a node t_0 of the tree decomposition, an integer $k_0 \in [0..k]$, a subset $D_0 \subseteq X_t$ of vertices, and a function $f_0: 2^{X_t \setminus D_0} \to [0..n]$. We say that a set $D \subseteq V_{t_0} \setminus U$ is of class (k_0, D_0, f_0) for t_0 if the following conditions are satisfied:

- 1. $|D \setminus D_0| = k_0$ and $D \cap X_{t_0} = D_0$.
- 2. for all $A \subseteq X_{t_0} \setminus D_0$ we have $f_0(A) = v_{K_q}(G_{t_0} (D \cup A))$.

For each node t_0 of the tree decomposition, we compute a list $\mathcal{L}(t_0)$ of classes for t_0 such that $(k_0, D_0, f_0) \in \mathcal{L}(t_0)$ if and only if there is a set $D \subseteq V_{t_0} \setminus U$ that is of class (k_0, D_0, f_0) .

Before we state the algorithm, we first define five procedures to extend the classes for a child of node to a class for the parent node. The first two procedure correspond to the introduce node, the third and fourth to the forget node, and the last one to the join node.

Lemma 5.1 (Introduce 1). Let t_0 be an introduce node with the unique child t_1 and let $v \notin U$ be the vertex introduced.

There is a procedure Intro₁ that, for a given class $c_1 = (k_1, D_1, f_1)$ for t_0 , computes in time $O(2^{tw})$ a class $c_0 = (k_0, D_0, f_0)$ for t_0 such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$, if D is of class c_1 for t_1 , then $D \cup \{v\}$ is of class c_0 for t_0 .

Proof. We set $c_0 = (k_1, D_1 \cup \{v\}, f_1)$ as the class for t_0 . Since v not contained in G_{t_1} but contained in $D_0 = D_1 \cup \{v\}$, the two graph $G_{t_1} - D_1$ and $G_{t_0} - (D_1 \cup \{v\})$ are identical. Hence, it trivially follows that $D \cup \{v\}$ is of class c_0 for t_0 .

Next we consider the case when the vertex introduced is not deleted.

Lemma 5.2 (Introduce 2). Let t_0 be an introduce node with the unique child t_1 and let v be the vertex introduced.

There is a procedure $Intro_2$ that, for a given class $c_1 = (k_1, D_1, f_1)$, computes in time $O(2^{tw})$ a class $c_0 = (k_1, D_1, f_0)$ for t_0 such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$, if D is of class c_1 for t_1 , then D is of class c_0 for t_0 .

Proof. We define the function $f_0: 2^{X_{t_0} \setminus D_1} \to [0..n]$ where, for all $A \subseteq X_{t_0} \setminus D_1$, we set

$$f_{0}(A) := \begin{cases} f_{1}(A \setminus \{v\}) & \text{if } v \in A, \\ \max \left(f_{1}(A), 1 + \max_{\substack{C \subseteq X_{t} \setminus (D_{0} \cup A) \\ C \text{ is } K_{q} \text{ containing } v}} f_{1}(A \cup C \setminus \{v\}) \right) & \text{otherwise.} \end{cases}$$
(5.1)

Then the new class is defined as $c_0 = (k_1, D_1, f_0)$. Consider some set $A \subseteq X_{t_0} \setminus D_1$. If $v \in A$, then $G_{t_1} - (D \cup A \setminus \{v\})$ is identical to $G_{t_0} - (D \cup A)$ since v is introduced at t_0 . Thus, $v_{K_q}(G_{t_0} - (D \cup A)) = v_{K_q}(G_{t_1} - (D \cup A \setminus \{v\})) = f_1(A \setminus \{v\}) = f_0(A)$.

For the case when $v \notin A$ we split the proof into two parts.

 $f_0(A) \leq v_{K_q}(G_{t_0} - (D \cup A))$. First, consider the case when $f_0(A) = f_1(A)$. Since every packing for $G_{t-1} - (D \cup A)$ is also a packing for $G_{t_0} - (D \cup A)$, we get $f_1(A) = v_{K_q}(G_{t_1} - (D \cup A)) \leq v_{K_q}(G_{t_0} - (D \cup A))$.

Let $C \subseteq X_{t_0} \setminus (D_0 \cup A)$ be a *q*-clique containing *v*. Every packing for $G_{t_0} - (D \cup A \cup C)$ can be extended to a packing for $G_{t_0} - (D \cup A)$ by covering the vertices in *C* with the same copy of K_q . Hence, $v_{K_q}(G_{t_0} - (D \cup A)) \ge v_{K_q}(G_{t_0} - (D \cup A \cup C)) + 1$. Since $G_{t_0} - (D \cup A \cup C)$ does not contain *v*, the graphs $G_{t_0} - (D \cup A \cup C)$ and $G_{t_1} - (D \cup A \cup C \setminus \{v\})$ are identical, which implies that the packing number is the same. Hence, $v_{K_q}(G_{t_0} - (D \cup A \cup C)) \ge f_1(A \cup C \setminus \{v\})$ follows by the assumption about f_1 .

 $f_0(A) \ge \nu_{K_q}(G_{t_0} - (D \cup A))$. Let *P* be the packing for $G_{t_0} - (D \cup A)$ containing exactly $\nu_{K_q}(G_{t_0} - (D \cup A))$ cliques. If *v* is not covered by *P*, then *P* is also a packing for $G_{t_1} - (D \cup A)$ and contains at most $\nu_{K_q}(G_{t_1} - (D \cup A))$ cliques, which is exactly $f_1(A)$ by assumption. Hence, *P* contains at most $f_0(A)$ cliques by the definition of f_0 .

In the case when v is covered, there must be a clique $C \subseteq X_{t_0} \setminus (D_0 \cup A)$ containing v such that C is covered by the same copy of K_q . Hence, the number of cliques in P is at most $v_{K_q}(G_{t_0} - (D \cup A \cup C)) + 1$. Since v must be avoided in this case, P contains at most $v_{K_q}(G_{t_1} - (D \cup A \cup C \setminus \{v\})) + 1$ cliques and this is equal to $f_1(A \cup C \setminus \{v\}) + 1$ which is bounded by $f_0(A)$ by the definition of f_1 .

This concludes the proof as the function f_0 can be constructed in time $O(2^{|X_t \setminus D_1|})$.

The following two cases correspond to the forget nodes. The first procedure deals with the setting when the forgotten vertex is deleted.

Lemma 5.3 (Forget 1). Let t_1 be a forget node with the unique child t_0 and let v be the vertex forgotten.

There is a procedure Forget_1 that, for a given class $c_1 = (k_1, D_1, f_1)$, computes in time $O(2^{\text{tw}})$ a class $c_0 = (k_1 + 1, D_1 \setminus \{v\}, f_1)$ such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$ with $v \in D$, if D is of class c_1 for t_1 , then D is of class c_0 for t_0 .

Proof. From $|D \setminus D_1| = k_1$ and the assumption that v is forgotten at t_0 , we get that $|D \setminus (D_1 \setminus \{v\})| = |D \setminus D_1| + 1 = k_1 + 1$. Since v is deleted, we get that $G_{t_0} - D = G_{t_1} - D$. Thus, the bound on the packing number follows trivially, as we consider the same graph in both settings.

In contrast to the previous case, we now assume that the vertex forgotten is not deleted.

Lemma 5.4 (Forget 2). Let t_1 be a forget node with the unique child t_0 and let v be the vertex forgotten. There is a procedure Forget_2 that, for a given class $c_1 = (k_1, D_1, f_1)$, computes in time $O(2^{\text{tw}})$ a class $c_0 = (k_1, D_1, f_1)$ such that for following holds: For all sets $D \subseteq V_{t_1} \setminus U$ with $v \notin D$, if D is of class c_1 for t_1 , then D is of class c_0 for t_0 .

Proof. Let $A \subseteq X_{t_0} \setminus D_1$. Observe that every packing for $G_{t_0} - (D \cup A)$ is also a packing for $G_{t_1} - (D \cup A)$ as both graphs are identical. As the packing number for $G_{t_1} - D - A$ is equal to $f_1(A)$, this is also the packing number for $G_{t_0} - D - A$.

The last procedure covers the case of the join node.

Lemma 5.5 (Join Node). Let t_0 be a join node and let t_1 and t_2 be the two children of t_0 .

There is a procedure Join, that, for a given class $c_1 = (k_1, D_1, f_1)$ for t_1 and a given class $c_2 = (k_2, D_1, f_2)$ for t_2 , computes in time $2^{O(tw)}$ a class $c_0 = (k_1 + k_2, D_1, f_0)$ such that the following holds: For all sets $D' \subseteq V_{t_1} \setminus U$ and for all sets $D'' \subseteq V_{t_2} \setminus U$, if D' is of class c_1 for t_1 and D'' is of class c_2 for t_2 , then $D' \cup D''$ is of class c_0 .

Proof. We define a function $f_0: 2^{X_{t_0} \setminus D_1} \to [0..n]$ where, for all $A \subseteq X_{t_0} \setminus D_0$, we set

$$f_0(A) := \max_{A_1 \uplus A_2 = X_{t_0} \setminus (D_0 \cup A)} f_1(A \cup A_1) + f_2(A \cup A_2).$$
(5.2)

To simplify notation, we set $D = D' \cup D''$ in the following. By the classes of D' and D'' we get $D' \cap D'' = D_1$, which implies that $|D \setminus D_1| = |D' \setminus D_1| + |D'' \setminus D_1| = k_1 + k_2$

Consider some set $A \subseteq X_{t_0} \setminus D_1$ and let P be a maximum packing for $G_{t_0} - (D \cup A)$. By the definition of a tree decomposition, the packing P cannot contain a clique that covers vertices in $G_{t_1} - X_{t_1}$ and $G_{t_2} - X_{t_2}$ simultaneously. Hence, there exists partition $\widetilde{A}_1 \uplus \widetilde{A}_2 = X_{t_0} \setminus (D_1 \cup A)$ such that $v_{K_q}(G_{t_0} - (D \cup A)) = v_{K_q}(G_{t_1} - (D \cup A \cup \widetilde{A}_1)) + v_{K_q}(G_{t_2} - (D \cup A \cup \widetilde{A}_2))$.

From the definition of f_0 and the properties of f_1 and f_2 , it follows that

$$f_0(A) \ge f_1(A \cup \widetilde{A}_1) + f_2(A \cup \widetilde{A}_2)$$

= $v_{K_q}(G_{t_1} - (D' \cup A \cup \widetilde{A}_1)) + v_{K_q}(G_{t_2} - (D'' \cup A \cup \widetilde{A}_2))$
= $v_{K_q}(G_{t_0} - (D \cup A)).$

Now let \overline{A}_1 and \overline{A}_2 be the sets maximizing the sum in (5.2). Then it directly follows that

$$f_0(A) = f_1(A \cup \overline{A}_1) + f_2(A \cup \overline{A}_2)$$

= $v_{K_q}(G_{t_1} - (D \cup A \cup \overline{A}_1)) + v_{K_q}(G_{t_2} - (D \cup A \cup \overline{A}_2))$
 $\leq v_{K_q}(G_{t_1} - (D' \cup A \cup \widetilde{A}_1)) + v_{K_q}(G_{t_2} - (D'' \cup A \cup \widetilde{A}_2))$
= $v_{K_q}(G_{t_0} - (D \cup A).$

This concludes the proof that (5.2) is a correct definition. To construct the function f for each A, we just need to iterate over at most 2^{tw} possible subsets. Hence, the output can be computed in time $2^{O(tw)}$.

Now we have everything ready to state the algorithm solving q-CLIQUE-HITPACK.

Proof of Theorem 1.7. Given the instance $I = (G, U, k, \ell)$, we first compute an optimal tree decomposition of *G* and then transform the decomposition into a nice tree decomposition where the root and leaf nodes have an empty bag. For all leaf nodes t_0 of the tree decomposition, we set $\mathcal{L}(t_0) = \{(0, \emptyset, \emptyset \mapsto 0)\}$.

We traverse the nodes of the tree decomposition in post-order and for each node t_0 with at least one child we perform the following actions (depending on the type of node t_0).

- **Introduce Node.** Let t_1 be the unique child of t_0 and let v be the vertex introduced at t_0 , that is, $X_{t_0} = X_{t_1} \cup \{v\}$. Repeat the following for all classes $c_1 \in \mathcal{L}(t_1)$: If $v \in V(G) \setminus U$, then use Intro₁ and Intro₂ on c_1 to compute two classes c_0 and c'_0 and add both to the list $\mathcal{L}(t_0)$. Otherwise, we have $v \notin V(G) \setminus U$ and apply Intro₂ on c_1 to compute the class c''_0 and add it to the list $\mathcal{L}(t_0)$.
- **Forget Node.** Let t_1 be the unique child of t_0 and let v be the vertex forgotten, that is, $X_{t_0} = X_{t_1} \setminus \{v\}$. Repeat the following for all classes $c_1 \in \mathcal{L}(t_1)$: If $v \in D_1$, then use Forget₁ on c_1 to compute the class c_0 and add it to the list $\mathcal{L}(t_0)$. Otherwise, we have $v \notin D_1$ and use Forget₂ on c_1 to compute the class c'_0 and add it to the list $\mathcal{L}(t_0)$.
- **Join Node.** Let t_0 be the unique parent of the nodes t_1 and t_2 . Repeat the following for all pairs of classes $(c_1, c_2) \in \mathcal{L}(t_1) \times \mathcal{L}(t_2)$ where $c_1 = (k_1, D_1, f_1)$ and $c_2 = (k_2, D_2, f_2)$: Check that $D_1 = D_2$ and if so apply Join on (c_1, c_2) to get a class c_0 for t_0 and add it to the list $\mathcal{L}(t_0)$.

It remains to define the output of the procedure. For this let r be the root of the tree decomposition. Then, the algorithm outputs Yes if there is a class $(k_0, \emptyset, \emptyset \mapsto \ell_0) \in \mathcal{L}(r)$ for some $k_0 \in [0..k]$ and $\ell_0 \in [0..\ell - 1]$.

Correctness. Next we prove that this dynamic program is correct.

Claim 5.6 (Correctness). For all nodes t_0 , integers $0 \le k_0 \le k$, vertex sets $D_0 \subseteq X_t \setminus U$, and functions $f_0: 2^{X_t \setminus D_0} \to [0..n]$, the following two statements are equivalent:

- There is a set $D \subseteq V_t \setminus U$ of class (k_0, D_0, f_0) for t_0 .
- $(k_0, D_0, f_0) \in \mathcal{L}(t_0).$

Proof of Claim. By the definition of the dynamic program, it suffices to show that the first statement implies the second statement. We prove the correctness inductively based on the type of the node in the tree decomposition.

Leaf Node. Since the bags of the leaf nodes do not contain any vertices, no vertices can be deleted. By assumption, the leaf nodes do not have children and hence, there is only the empty packing which contains no copy of K_q . **Introduce Node.** If the set D is of class c_0 and $v \in D$, then $D \setminus \{v\}$ is of some class c_1 for t_1 . By induction, we get $c_1 \in \mathcal{L}(t_1)$. From the algorithm and the properties of Intro₁, we obtain a class c such that D is of class c for t_0 . Moreover, the algorithm adds c to $\mathcal{L}(t_0)$. Since each set D has exactly one class for each node, we have $c_0 = c$ and thus, $c_0 \in \mathcal{L}(t_0)$.

Note, that if $v \notin D$, then we similarly get that $c_0 \in \mathcal{L}(t_0)$ by using Intro₂.

Forget Node. The result follows analogously to the introduce node.

Join Node. Assume that D is of class c_0 . If we consider $D' = D \cap V_{t_1}$ and $D'' = D \cap V_{t_2}$, we have that D' and D'' are of classes c_1 and c_2 for t_1 and t_2 , respectively. By the induction hypothesis it follows that $c_1 \in \mathcal{L}(t_1)$ and $c_2 \in \mathcal{L}(t_2)$. From the definition of the algorithm and the properties of Join, it follows that $D' \cup D'' = D$ is of some class c for t_0 . By the uniqueness of classes, we conclude $c = c_0$ and therefore, $c_0 \in \mathcal{L}(t_0)$.

As the last step we prove the running time of the algorithm.

Claim 5.7. Let *L* denote the maximum length of a list $\mathcal{L}(t)$ for all nodes *t*. Then, the algorithm terminates in time $L^2 \cdot 2^{\text{poly}(tw)} \cdot \text{poly}(n)$.

Proof of Claim. Computing a nice tree decomposition is possible in time $2^{\text{poly}(\text{tw})} \cdot \text{poly}(n)$ [17, Chapter 7]. Observe that handling the join nodes dominates the running time as we have to consider up to L^2 different pairs of classes. Because each new class can be computed in time $2^{\text{poly}(\text{tw})}$, the claim follows.

We conclude the proof by bounding the number of classes (k_0, D_0, f_0) that can appear for each node t_0 . There are k choices for k_0 and at most 2^{tw+1} choices for D_0 . By a naive bound, the number of choices of function f_0 is $n^{2^{tw+1}}$. We claim that the number of functions appearing in the algorithm is actually $2^{2^{O(tw)}}$. This would conclude the proof, as it means that the running time of the algorithm is $2^{2^{O(tw)}}$ poly(n).

Recall, that $f_0(\emptyset)$ is the maximum integer in the image of f_0 . Moreover, the smallest integer is at most tw + 1 smaller because avoiding single additional vertex can decrease the packing number by at most one. Therefore, the maximum and the minimum in the image differ by at most tw + 1. In conclusion, the number of functions is bounded by $n \cdot (tw + 1)^{2^{tw+1}}$ as there are *n* choices for the maximum (obtained at $f_0(\emptyset)$) and tw + 1 choices for the values of the remaining 2^{tw+1} subsets.

6 EDGE-HITPACK Parameterized by Treewidth: Single-Exponential Algorithm

In this section, we show that for q = 2, the algorithm of Section 5 for *q*-CLIQUE-HITPACK runs in time $2^{\text{poly}(\text{tw})} \cdot n^{O(1)}$ without *any changes whatsoever* to the algorithm.

Theorem 1.12. *EDGE-HITPACK can be solved in time* $2^{\text{poly}(\text{tw})} \cdot n^{O(1)}$, where tw is the treewidth of the graph.

In light of Claim 5.7, it is sufficient to give an upper bound on the number of different classes that subsets $D \subseteq V_t \setminus D$ can have at each node t of the tree decomposition. As $|D \setminus D_0|$ can take at most ndifferent values and $D \cap X_t$ can take at most 2^{tw+1} different values, it boils down to bounding the number of different functions $f(A) = v(G_t - (D \cup A))$ that can arise for a fixed graph G_t and different sets D(note that function $v_{K_2} = v$ denotes the size of the maximum matching). The main combinatorial result of this section is precisely such a bound. This immediately shows that the algorithm of Theorem 1.7 for q = 2 runs in time $2^{\text{poly}(\text{tw})} \cdot n^{O(1)}$, proving Theorem 1.12. **Lemma 2.1.** Let G be an n-vertex graph over a vertex set $V \supseteq [k]$ for some integer k. Let $f_{G,k}: 2^{[k]} \to \mathbb{Z}^+$ be the function defined by $f_{G,k}(S) = v(G - S)$. For each k and n, there are $n \cdot 2^{O(k^3)}$ functions $f_{G,k}$ that can arise this way.

Before, we prove Lemma 2.1 we restate Lemma 2.2. Note, that we have already proven Lemma 2.2 in Section 2.

Lemma 2.2. Let G be a graph over a vertex set $V \supseteq [k]$ for some integer k. Let us define the function $h_{G,k}: 2^{[k]} \rightarrow \{0,1\}$ the following way:

$$h_{G,k}(S) = \begin{cases} 1 & if G - S \text{ has a perfect matching,} \\ 0 & otherwise. \end{cases}$$

For each integer k, the number of distinct functions $h_{G,k}$ is $2^{O(k^3)}$.

The following lemma proves a stronger statement, giving a bound on the number of possibilities for a more expressive function that describes how that size of the maximum matching changes when removing a set *S*. We prove this generalization using a simple purely graph-theoretical construction. Let v(G) be the size of the maximum matching in *G*. Observe that removing a vertex cannot increase this value and can decrease it only by at most 1. Thus v(G) - v(G - S) is always between 0 and |S|.

Lemma 6.1. Let G be a graph over a vertex set $V \supseteq [k]$ for some integer k. Let $g_{G,k}: 2^{[k]} \to \{0, 1, ..., k\}$ be the function defined by $g_{G,k}(S) = v(G) - v(G - S)$. For each k, there are $2^{O(k^3)}$ functions $g_{G,k}$ that can arise this way.

Proof. Let d = v(G). Let us construct the graph G^* from G by introducing n - 2d + 2k independent vertices that are adjacent to every original vertex of G. Graph G^* has as set V^* of $n^* = 2n - 2d + 2k$ vertices. Let $t = \min\{3k, n - 2d + 2k\} \le 3k$. For notational convenience, let us rename the vertices of G^* such that t of the newly introduced vertices form the set $\{k + 1, \ldots, k + t\}$. Let $k_0 := k + t$, we have $[k_0] \subseteq V^*$. Let $h_{G^*,k_0}: 2^{[k_0]} \to \{0,1\}$ be the function defined for G^* and k_0 as in Lemma 2.2. We claim that $g_{G,k}(S)$ for any $S \subseteq [k]$ can be deduced from the function h_{G^*,k_0} . As Lemma 2.2 asserts that there are at most $2^{\mathcal{O}(k_0^3)} = 2^{\mathcal{O}(k^3)}$ possible functions h_{G^*,k_0} , the same bound also holds for the number of possible functions $g_{G,k}$.

Let $S \subseteq [k]$ be an arbitrary subset and let s = |S|. Then G - S has a matching of size at least d - s, which leaves at most n - s - 2(d - s) = n + s - 2d vertices uncovered. As every matching in G - Shas size at most d, every matching leaves at least n - s - 2d vertices uncovered. Let us show how the existence of a matching in G - S that leaves at most a certain number of vertices uncovered can be deduced from the function f. Let $x \in \{0, 1, \dots, 2k\}$ such that $n - s - 2d + x \ge 0$ (hence $s - x \le n - 2d$) and let c = 2k + s - x. Note that $s \le k$ implies that $c \le 3k$ and $s - x \le n - 2d$ implies $c \le n - 2d + 2k$. Thus $c \le t$ and let $S^* = S \cup \{k + 1, \dots, k + c\}$. We claim that G - S has a matching leaving at most n - s - 2d + x vertices uncovered if and only if $G^* - S^*$ has a perfect matching. Consider a matching M of G - S that leaves n - s - 2d + x vertices uncovered. In $G^* - S^*$, the number of newly introduced vertices is exactly n - 2d + 2k - c = n - 2d + x - s, thus M can be completed to a perfect matching M^* of $G^* - S^*$. Similarly, if G - S has a perfect matching, then n - 2d + 2k - c = n + x - s - 2d newly introduced vertices are covered in this matching. If we remove the edges of M^* incident to these edges, then we obtain a matching of G - S avoiding exactly this number n + x - s - 2d of vertices of G - S. Thus $f_{G,k}(S) \le i$ for any $S \subseteq [k]$ and any $0 \le i \le k$ can be deduced given the function h_{G^*,k_0} .

Now the proof of Lemma 2.1 follows immediately.

Proof of Lemma 2.1. In the *n* vertex graph *G*, there are *n* possibilities for the value of v(G). Let us consider those functions $f_{G,k}$ that arise from some *n*-vertex graph *G* with v(G) = d for some fixed integer *d*. Then by Lemma 6.1, there are $2^{O(k^3)}$ possibilities for the function $g_{G,k} = d - v(G - S)$, which implies that there are only that many possibilities for the function $f_{G,k}$. Considering every possible *d*, this proves the bound of $n \cdot 2^{O(k^3)}$.



(c) A graphical representation of the type (part, H_1 , h_1 , H_2 , h_2) for the partial packing. The three left-most vertices are not covered and form part 0, the highlighted five-vertex graph in the middle forms H_1 , and the highlighted four-vertex graph on the right corresponds to H_2 . The functions h_1 and h_2 map the vertices in H_1 and H_2 as depicted.

(a) The graph H. Graph of H is packed.

Figure 7.1: An illustration for a node t of how a partial packing and its type relate to each other. The black vertices and edges correspond to the edges and vertices of G. The deleted vertices are indicated by hollow dots. The highlighted vertices and edges show how the copies of H are packed to the vertices of G. A highlighted vertex or edge with a white filling, indicates that we do not know to which vertices and edges of G the ones of H correspond.

7 *H*-HITPACк Parameterized by Treewidth: Double-Exponential Algorithm

In Section 5 we have seen the algorithm for H-HITPACK parameterized by treewidth when H is a clique. In the following we consider the general case when H is an arbitrary connected graph with at least three vertices. Note that if H has only two vertices, the problem is precisely K_2 -HITPACK. In this case the result follows by Theorem 1.7 or rather by Theorem 1.12 proving the improved running time. Formally, we prove Theorem 1.6.

Theorem 1.6. For any fixed connected graph H, H-HITPACK can be solved in time $2^{2^{O(\text{tw}\log \text{tw})}} \cdot n^{O(1)}$, where tw is the treewidth of the input graph.

Recall that for the case when H is a clique we heavily exploited that, for each clique appearing in the final packing, there is one bag containing all vertices covered by this clique. By this property we could describe the states for each node by a function based on the subsets of the bag.

When now considering the more general case we do not have this assumption anymore. Instead, a copy of the graph H in the packing might cover vertices from many different bags (think of a long path for example). Hence, the algorithm does not "see" all vertices of the copy at the same time and therefore, also has to deal with *partial packings*. Such a partial packing is some variant of a packing where we also allow that *subgraphs* of H appear in the packing (in a controlled way). For each such partial packing we define a *type* which describes how the packing interacts with the bag. See Figure 7.1 for an illustration of these concepts.

Then the idea of the algorithm is as follows. For each node t we consider all possible types that a packing could have with respect to this node. For each such type T, we store a bound on the maximum number of copies of H that can appear in any partial packing of type T.

We start by introducing the notation and concepts needed to formally state the dynamic program. The algorithm is then presented in Section 7.1, its correctness is proven in Section 7.2, and the runtime is analyzed in Section 7.3.

Partial *H*-packings. Let $I = (G, U, k, \ell)$ be an instance of *H*-HITPACK and let tw be the treewidth of *G*. As a first step the algorithm computes an optimal tree decomposition of *G* Now consider a node *t* of the computed tree decomposition of width tw. It is well-known that this can be done in time $2^{\text{poly}(tw)}$ poly(*n*) [8, 45]. We additionally introduce some notation when working with tree decompositions. When *t* denotes some node of a tree decomposition, then we define X_t as the associated bag. We denote by V_t the vertex set of the subtree of the tree decomposition that is rooted in *t*, and define $G_t = G[V_t]$ as the corresponding graph.

For some integers $p, q \ge 0$, a tuple $P = (h_1, \ldots, h_p, \overline{H}_1, \overline{h}_1, \overline{H}_2, \overline{h}_2, \ldots, \overline{H}_q, \overline{h}_q)$ is a partial *H*-packing for G_t (or just t for short) if the following holds:

- Each h_i is an injective homomorphism from H to $G_t \setminus X_t$. We refer to these as the *complete copies* of H (in P).
- Each \overline{H}_j is an induced subgraph of H, and each \overline{h}_j is an injective homomorphism from \overline{H}_j to G_t whose image has a non-empty intersection with X_t . We refer to these as the *partial copies* of H (in P).⁴
- The images of all h_i , \overline{h}_j are pairwise vertex disjoint.
- For each *j* ∈ [*q*], we refer to a vertex of *H*_j that has a neighbor in *H* outside of *H*_j as a *border* vertex of *H*_j. All such border vertices are mapped to a vertex from *X_t* by *h*_j.

Types. Next, we define so-called *types* for *t*. Intuitively, such a type describes how a partial *H*-packing for G_t interacts with the vertices from the bag X_t . For this we first consider a function part, which partitions the vertices in the bag X_t . Here, we also introduce a part 0, which we interpret to include those vertices that are not covered by any copy of *H*. All other parts of the partition are associated with some induced subgraph H_i of *H* together with a function h_i that specifies which vertex from the bag belongs to which vertex of H_i , that is, h_i points out H_i as a (not necessarily induced) subgraph on the vertices in X_t . Formally, we represent these (labeled) subgraphs by injective homomorphisms from H_i to $G[X_t]$. In addition, h_i includes information about the vertices of *H* that are not in H_i . These vertices are labeled using two special symbols \uparrow and \downarrow to indicate that they lie above X_t , i.e., not in V_t , or below X_t , i.e., in $V_t \setminus X_t$, respectively.

Definition 7.1 (Type for t, D-avoiding). For some $0 \le w \le |X_t|$, a type T for t is defined as a tuple $T = (\text{part}, H_1, h_1, \ldots, H_w, h_w)$ such that

- part is a function $X_t \rightarrow [0..w]$ and, for each $i \in [w]$, we set $X_t(i) \coloneqq \text{part}^{-1}(i)$,
- for all $i \in [w]$, H_i is a non-empty induced subgraph of H with $|X_t(i)|$ vertices, and
- for all $i \in [w]$, h_i is a function from V(H) to $X_t(i) \cup \{\downarrow,\uparrow\}$ such that $h_i|_{V(H_i)}$ is an injective homomorphism from H_i to $G[X_t(i)]$.

If for some set $D \subseteq X_t$ it holds that part(v) = 0 for all $v \in D$, then we say that T is D-avoiding.

In the following definition we define the type of a partial *H*-packing.

Definition 7.2 (Type of a partial *H*-packing). Let $P = (h_1, \ldots, h_p, \overline{H}_1, \overline{h}_1, \ldots, \overline{H}_q, \overline{h}_q)$ be a partial *H*-packing for G_t with regard to X_t .

- Let part: $X_t \to [0..q]$ be the function with $part(v) = j \in [q]$ if $v \in X_t$ is in the image of \overline{h}_j ; and part(v) = 0 otherwise.
- For all $j \in [q]$, we set $\widehat{H}_j := \overline{H}_j \left[\overline{h}_j^{-1}(X_t)\right]$.

⁴Note that $\overline{H}_i = H$ is possible and this counts as a partial copy as long as the image intersects the bag X_T .
• For all $j \in [q]$, we define $\hat{h}_j : V(H) \to X_t \cup \{\uparrow, \downarrow\}$ with

$$\widehat{h}_{j}(a) \coloneqq \begin{cases} \uparrow, & a \notin \overline{h}_{j}^{-1}(V_{t}), \\ \overline{h}_{i}(a), & a \in \overline{h}_{j}^{-1}(X_{t}), \\ \downarrow, & a \in \overline{h}_{j}^{-1}(V_{t} \setminus X_{t}). \end{cases}$$

Then $T = (\text{part}, \widehat{H}_1, \widehat{h}_1, \dots, \widehat{H}_q, \widehat{h}_q)$ is the type of P.

Remark 7.3. It is straightforward to check that the type of a partial *H*-packing for G_t with regard to X_t is a type for t with w = q.

With the definition of partial *H*-packings of a certain type, we define the *T*-completion number.

Definition 7.4 (*T*-completion number). Let *T* be a type for *t*. Consider the partial *H*-packings for G_t with respect to X_t that have type *T*. The *T*-completion number of G_t (with respect to X_t) is the maximum number of complete copies of *H* obtained for such a partial *H*-packing of type *T*.

We prove a bound on the number of types in terms of tw and the size of H.

Lemma 7.5. Let *H* be a fixed graph. For all nodes *t* and all sets $D \subseteq X_t$, let $\mathcal{T}_t(D)$ denote the set of all possible *D*-avoiding types for *t*.

Then we get that $|\mathcal{T}_t(D)| \leq \operatorname{tw}^{\mathcal{O}(\operatorname{tw·poly}(|H|))}$.

Proof. As $w \leq |X_t| \leq tw + 1$ there are at most $(tw + 2)^{tw+1}$ choices for the function part. For each H_i there are at most $2^{|V(H)|}$ choices, and for each h_i there are at most $(tw + 3)^{|V(H)|}$ choices. Hence, the total number of types is bounded by

$$(\mathsf{tw}+2)^{\mathsf{tw}+1} \cdot \left(2^{|V(H)|} \cdot (\mathsf{tw}+3)^{|V(H)|}\right)^{\mathsf{tw}+1}$$

which is upper bounded by $tw^{O(tw \cdot poly(|H|))}$ and thus proves the claim.

As a next step we define some notation which we use to modify types. We will use the following notation for neighborhoods: For a vertex v of G, we use $N_G(v)$ to denote the neighborhood of v in G, that is, the set of all vertices that share an edge with v. For a subset U of the vertices of G, we use $N_U(v)$ to denote the set of neighbors of v in U.

Extending Types by a Vertex. Let $T = (\text{part}, H_1, h_1, \dots, H_w, h_w)$ be some type for t and let v be a vertex not in G_t and thus, also not in X_t . For all $i \in [0..w]$, we define extend $(T, v \mapsto i)$ as the set of all possible types for t' with $X_{t'} = X_t \cup \{v\}$ that extend T in the sense that now the vertex v is contained in the *i*th part (which might be a new one). These extensions also consider all possible ways in which v could appear in the corresponding (partial) copy of H.

Formally, we define extend $(T, v \mapsto i)$ as follows:

• If v is not covered by a (partial) copy of H then it is included in part 0:

$$\operatorname{extend}(T, v \mapsto 0) \coloneqq \{ (\operatorname{part}|_{v \mapsto 0}, H_1, h_1, \dots, H_w, h_w) \}.$$

$$(7.1)$$

• Suppose v is covered by a vertex a of a copy of H for which the corresponding induced subgraph H_i of H already covers other vertices of X_t (this implies that a is not in H_i), i.e., the corresponding (partial) copy of H is already considered as part of the type T. Then v is included in part i, let part' be the corresponding extension of part. Moreover, H_i is adjusted to include the vertex a, so let $H_{i,a} := H[V(H_i) \cup \{a\}]$. Finally, $h_{i,a}$ is a mapping from V(H) to $X_{t'} \cup \{\uparrow, \downarrow\}$ that is identical to h_i , with the exception that $h_{i,a}(a) = v$. Ultimately, as we care about subgraph copies of H in G, edges of H should be preserved, and so we need only consider the set \mathcal{A} containing those vertices a of H with $N_{H_i}(a) \in N_{X_t}(v)$. So, for each $i \in [w]$, we define

$$\operatorname{extend}(T, v \mapsto i) \coloneqq \bigcup_{a \in \mathcal{A}} \{ (\operatorname{part}', H_1, h_1, \dots, H_{i,a}, h_{i,a}, \dots, H_w, h_w) \}.$$
(7.2)

Finally, suppose that v is covered by some copy of H that has not been considered yet. Then a new part w + 1 is introduced, and v is mapped to w + 1 by part", the corresponding extension of part. The corresponding partial copy of H then only holds the single vertex a, and a corresponding mapping h_a maps every vertex of H to ↑, except for a, which is mapped to v. We set

$$\operatorname{extend}(T, v \mapsto w + 1) \coloneqq \bigcup_{a \in V(H)} \{ (\operatorname{part}'', H_1, h_1, \dots, H_w, h_w, H[\{a\}], h_a) \}.$$
(7.3)

For the case when i = 0, we know that there is only one type $T' \in \text{extend}(T, v \mapsto 0)$. Hence, we abuse notation and directly write $\text{extend}(T, v \mapsto 0)$ whenever we refer to T'.

Removing Vertices from Types. Now we define the converse of the previous operation, that is, the modification of the types when we remove a vertex from a bag X_t . Let $T = (part, H_1, h_1, ..., H_w, h_w)$ be some type for t, and let v be a vertex of the considered bag. Let $X_{t'} = X_t \setminus \{t\}$. We define a set of types remove(T, v) for t' as follows:

• If v was not covered by any copy of H, i.e., if part(v) = 0, then we can simply remove it by restricting part. Formally we set

$$remove(T, v) = \{ (part |_{X_{t'}}, H_1, h_1, \dots, H_w, h_w) \}.$$
(7.4)

• Suppose v is the last vertex in its part of X_t , that is, there is an $i \in [w]$ with part(v) = i and $|V(H_i)| = 1$. Then remove this part from the type. It turns out that in this situation we can assume that the corresponding copy of H is completely below t', i.e., if h_i maps every vertex of H to \downarrow , except for v. The reason for this is that otherwise some vertices covered by the respective copy of H would supposedly be not in $G_{t'}$ (that is, "above" t'), and some vertices covered by H would be in $G_{t'}$ but none of them would be in $X_{t'}$, which is a contradiction to the fact that H is connected and $X_{t'}$ a separator. In this case we set

$$remove(T, v) = \{ (part |_{X_{t'}}, H_1, h_1, \dots, H_{i-1}, h_{i-1}, H_{i+1}, h_{i+1}, \dots, H_w, h_w) \}.$$
(7.5)

Finally, suppose that part(v) = i for some i ∈ [w], and that |V(H_i)| > 1. In this case v is removed from part, and its preimage h_i⁻¹(v) is removed from H_i, while the updated homomorphism h'_i is identical to h_i, with the exception that h_i⁻¹(v) is now mapped to ↓ (since it covers a vertex "below" the bag X_{t'}). By the same argument as in the previous case, we can assume that none of the vertices in N_H(h_i(v)) are mapped to ↑ by h_i. We set

remove
$$(t, v) = \{ (\text{part} |_{X_{t'}}, H_1, h_1, \dots, H_i - h_i^{-1}(v), h'_i, \dots, H_w, h_w) \}.$$
 (7.6)

Combining Types. The last operation is used to combine two types. We use this later for the join nodes. Let $T_1 = (\text{part}, H_1, h_1, \ldots, H_w, h_w)$ and $T_2 = (\text{part}', H'_1, h'_1, \ldots, H'_w, h'_w)$ be two types for the same node *t*. We define the addition of T_1 and T_2 as $T_1 \oplus T_2$ if the following requirements are met (otherwise, $T_1 \oplus T_2$ is undefined):

- part = part',
- $H_i = H'_i$ (for each $i \in [w]$),
- $h_i|_{H_i} = h'_i|_{H'_i}$ (for each $i \in [w]$), and
- $\{h_i(a), h'_i(a)\} \neq \{\downarrow\}$ for all $a \in V(H)$.

Then we define, for all $i \in [w]$, the combined function $(h_i \oplus h'_i)$ with

$$(h_i \oplus h'_i)(a) \coloneqq \begin{cases} \uparrow, & h_i(a) = h'_i(a) = \uparrow, \\ v, & h_i(a) = h'_i(a) = v, \\ \downarrow, & (h_i(a), h'_i(a)) \in \{(\uparrow, \downarrow), (\downarrow, \uparrow)\}, \end{cases} \quad \forall a \in V(H).$$

$$(7.7)$$

Here the idea is that the way the vertices in X_t are covered does not change. If for one type some vertex appears below and for the other above, then this vertex appears below for the combined type. If both types require that the vertex appears above, then this also holds for the combined type.

Formally, we define the final type as

$$T_1 \oplus T_2 \coloneqq (\operatorname{part}, H_1, h_1 \oplus h'_1, \dots, H_w, h_w \oplus h'_w)$$

$$(7.8)$$

Before we give the algorithm we prove one structural result that allows us to get an improved running time.

Lemma 7.6. Let G be a graph and t be a node of its tree decomposition. Moreover, consider $D \subseteq V_t$ and $D_0 = D \cap X_t$. Let L be the maximum T-completion number taken over all types T of some partial H-packing for $G_t - D$ with respect to $X_t \setminus D$. Then, for all $T \in \mathcal{T}_t(D_0)$, if there is a partial H-packing of type T, then there is a partial H-packing of type T with at least $\max\{L - |X_t| \cdot |V(H)|, 0\}$ complete copies of H.

Proof. Let *P* be some partial *H*-packing for $G_t - D$ with respect to $X_t \setminus D$ containing *L* complete copies of *H*.

Fix some arbitrary type $T \in \mathcal{T}_t(D_0)$ and some partial *H*-packing *Q* of type *T* for $G_t - D$. Note that the complete copies of *H* contained in some partial packing do not affect its type. So, by removing all complete copies of *H* in *Q*, we obtain another partial *H*-packing *Q'* of type *T*. Since each vertex in X_t can be covered by at most one vertex from a copy of *H* in *Q'*, the partial packing *Q'* contains (partial) copies of *H* with a total of at most $R := |X_t| \cdot |V(H)|$ vertices.

Now let P' be the packing obtained from P by removing all (partial) copies of H that cover some vertex of G_t that is also covered by a partial copy in Q'. Since there are at most R vertices covered by partial copies of Q', the partial packing P' contains at least L - R complete copies of H. By the construction of P', the packings P' and Q' are vertex-disjoint and therefore, $P' \cup Q'$ is a partial H-packing of type T which contains at least L - R complete copies of H. This concludes the proof. \Box

Now we are ready to state the algorithm for *H*-HITPACK parameterized by treewidth.

7.1 Dynamic Program

Now, we present an algorithm behind the proof of Theorem 1.6. The algorithm is a dynamic program based on the tree decomposition of the input graph and fills a table entry $A[t_0, k_0, D_0, \ell_0, f_0]$ for all

- nodes t_0 , integers $k_0 \in [0..k]$ and $\ell_0 \in [0..\ell]$,
- subsets $D_0 \subseteq X_{t_0} \setminus U$,
- functions $f_0: \mathcal{T}_t(D_0) \to [0..(\mathsf{tw}+1) \cdot |V(H)|] \cup \{\bot\}.$

Now, we define featured sets which are precisely the sets the algorithm counts.

Definition 7.7 (Featured set). We say that a vertex set $D \subseteq V_{t_0} \setminus U$ with $D_0 \subseteq D$ and $|D \setminus D_0| = k_0$ is featured in $(t_0, k_0, D_0, \ell_0, f_0)$ if the following two conditions hold:

• For every type $T \in \mathcal{T}_t(D_0)$ with $f_0(T) \neq \bot$, the *T*-completion number for $G_{t_0} - D$ (i.e., the maximum number of complete copies of *H* in a partial *H*-packing of type *T*) is exactly $\ell_0 - f_0(T)$.

• For every type $T \in \mathcal{T}_t(D_0)$ with $f_0(T) = \bot$, there is no partial H-packing for $G_{t_0} - D$ of type T.

Henceforth, we define $A[t_0, k_0, D_0, \ell_0, f_0]$ to be the number of sets that are *featured* in $(t_0, k_0, D_0, \ell_0, f_0)$. This concludes the definition of the dynamic programming table. Note that here we solve the counting version. For the decision version, it would suffice if table *A* stores Boolean values.

Let *r* be the root node of the tree decomposition such that the corresponding bag X_r does not contain any vertices. Note that the only valid type for *r* is the empty type, which we denote by (\emptyset) . Then the algorithm returns

$$\sum_{k_0=0}^k \sum_{\ell_0=0}^{\ell-1} A[r, k_0, \emptyset, \ell_0, (\emptyset) \mapsto 0],$$

as the number of solutions for the given instance of *H*-HITPACK.

As the program deals with each table entry separately, fix some node *t*, some integer $k_0 \in [0..k]$, some set $D_0 \subseteq X_t$, some integer $\ell_0 \in [0..\ell]$, and some function $f: \mathcal{T}_t(D_0) \to [0..(\mathsf{tw}+1) \cdot |V(H)|] \cup \{\bot\}$. For ease of notation we define $R := (\mathsf{tw}+1) \cdot |V(H)|$ for the range of the integers in the image of *f*.

Leaf Node. If *t* is a leaf node we set $A[t, 0, \emptyset, 0, (\emptyset) \mapsto 0] := 1$. For all other combinations we set the table entry to be 0.

Introduce Node. Let *t'* be the child of *t* and let *v* be the vertex introduced at *t*, that is, $X_t = X_{t'} \cup \{v\}$.

Case 1: $v \in D_0$. Then, we first define the function $f' : \mathcal{T}_{t'}(D_0 \setminus \{v\}) \to [0..R] \cup \{\bot\}$ such as

$$f'(T') = f(\operatorname{extend}(T', v \mapsto 0)). \tag{7.9}$$

Using this we set the table entry as

$$A[t, k_0, D_0, \ell_0, f] \coloneqq A[t', k_0, D_0 \setminus \{v\}, \ell_0, f'].$$
(7.10)

Case 2: $v \notin D_0$. We first perform two checks for the function f.

First, we iterate over all types $T \in \mathcal{T}_t(D_0)$. Let i = part(v) be the partition of v in T. If i = 0, then the check succeeds directly for this type. Otherwise, we let $a \in V(H_i)$ be the vertex such that $h_i(a) = v$ in T. For all $b \in N_{H_i}(v)$, we check if $h_i(b) \in N_G(v)$. If this condition is true, we proceed to the next type. Otherwise, we check whether $f(T) = \bot$. If this test fails for any type, we define the table entry of A to be 0.

As a second step, for all $T' \in \mathcal{T}_{t'}(D_0)$, we check if there exists $c_{T'} \in [0..R]$ such that, for all $T \in \bigcup_{i=0}^{tw+1} \operatorname{extend}(T', v \mapsto i)$ with $f(T) \neq \bot$, it holds that $f(T) = c_{T'}$. If this condition is satisfied, we define the function $f' \colon \mathcal{T}_{t'}(D_0) \to [0..R] \cup \{\bot\}$ with $f'(T') = c_{T'}$ and set

$$A[t, k_0, D_0, \ell_0, f] \coloneqq A[t', k_0, D_0, \ell_0, f']$$
(7.11)

Otherwise, the table entry is set to 0.

Forget Node. Let t' be the unique child of t and let v be the vertex forgotten, that is, $X_t = X_{t'} \setminus \{v\}$. First, we define function $f_1: \mathcal{T}_{t'}(D_0 \cup \{v\}) \to [0..R] \cup \{\bot\}$ as

$$f_1(T') = f(\text{remove}(T', v)).$$
 (7.12)

Next, we define function $f_2: \mathcal{T}_{t'}(D_0) \to [0..R+1] \cup \{\bot\}$ as

$$f_2(T') = \begin{cases} \bot, & \text{if } f(\text{remove}(T', v)) = \bot, \\ f(\text{remove}(T', v)) + 1, & \text{if } part(v) \neq 0 \text{ and } |H_{part(v)}| = 1, \\ f(\text{remove}(T', v)), & \text{otherwise.} \end{cases}$$
(7.13)

We define

$$r_{\min} = \min_{T' \in \mathcal{T}_{t'}(D_0): f_2(T') \neq \bot} f_2(T') \quad \text{and} \quad r_{\max} = \max_{T' \in \mathcal{T}_{t'}(D_0): f_2(T') \neq \bot} f_2(T')$$

as the smallest and largest value in the image of f_2 respectively. Now, we have two cases. If $v \in U$, then we can assume that $r_{\max} - r_{\min} \leq R$ (otherwise the table entry can be set to 0 directly) and we fill out the table

$$A[t, k_0, D_0, \ell_0, f] \coloneqq A[t', k_0, D_0, \ell_0 - r_{\min}, f_2 - r_{\min}].$$
(7.14)

Otherwise, we know that $v \notin U$. If $r_{max} - r_{min} \leq R$, then we fill the table entry as

$$A[t, k_0, D_0, \ell_0, f] \coloneqq A[t', k_0 - 1, D_0 \cup \{v\}, \ell_0, f_1] + A[t', k_0, D_0, \ell_0 - r_{\min}, f_2 - r_{\min}].$$
(7.15)

Otherwise we ignore the second part of the definition and set

$$A[t, k_0, D_0, \ell_0, f] \coloneqq A[t', k_0 - 1, D_0 \cup \{v\}, \ell_0, f_1].$$
(7.16)

Join Node. Now, we describe the join operation. Let t_1 , t_2 be the two children of t with the same bag as t.

We need to guarantee that \perp propagates correctly. Therefore, we introduce the following definition.

Definition 7.8 (Compatible Tuples). We say that three integers $\ell_0, \ell_1, \ell_2 \in [0..\ell]$ and three functions f, f_1, f_2 from types to $[0..R] \cup \{\bot\}$ are compatible if the following conditions are satisfied:

- exist T_1 and T_2 with $f_1(T_1) = f_2(T_2) = 0$, and
- $f(T_1 \oplus T_2) = \perp$ if and only if $f_1(T_1) = \perp$ or $f_2(T_2) = \perp$ for any types T_1, T_2 , and
- $\ell_0 f(T_1 \oplus T_2) = \ell_1 f_1(T_1) + \ell_2 f_2(T_2)$ for all types T_1, T_2 (if none of the terms is \perp).

Now, we let $A[t, k_0, D_0, \ell_0, f]$ be

$$\sum_{\substack{k_1,k_2 \in [0..k]:\\k_0=k_1+k_2}} \sum_{\substack{\ell_1,\ell_2,f_1,f_2\\\text{compatible with } \ell_0,f_0}} A[t_1,k_1,D_0,\ell_1,f_1] \cdot A[t_2,k_2,D_0,\ell_2,f_2].$$
(7.17)

This concludes the description of the dynamic programming recursion.

7.2 Correctness

It remains to prove the correctness of this dynamic program.

Lemma 7.9 (Correctness). For all nodes t, integers $k_0 \in [0..k]$, vertex sets $D_0 \subseteq X_t$, integers $\ell_0 \in [0..\ell]$, functions $f : \mathcal{T}_t(D_0) \to [0..R] \cup \{\bot\}$, and integers $c \ge 0$, the following two statements are equivalent:

- (P.1) There are exactly c pairwise different vertex sets $D \subseteq V_t \setminus U$ with $D_0 \subseteq D$ and $|D \setminus D_0| = k_0$ such that, for all types $T \in \mathcal{T}_t(D_0)$, the T-completion number for $G_t D$ is exactly $\ell_0 f(T)$ if $f(T) \neq \bot$ or there is no partial H-packing of type T.
- $(P.2) \ A[t, k_0, D_0, \ell_0, f] = c.$

Proof. We prove the statement inductively by handling each possible type of a node *t* of the tree decomposition individually.

Leaf Node. There is only one way to select no vertices from the empty set and hence, the statement is trivially true.

Introduce Node. We distinguish two subcases based on whether v is in D_0 .

Case 1: $v \in D_0$. We first consider the case when $v \in D_0$. Recall that v is not part of any (partial) covering in this case. Recall the definition of function f' from Equation (7.9):

$$f': \mathcal{T}_{t'}(D_0 \setminus \{v\}) \to [0..R] \cup \{\bot\} \text{ where } f'(T') = f(\mathsf{extend}(T', v \mapsto 0)).$$

Our goal is to show that (P.1) for $(t, k_0, D_0, \ell_0, f, c)$ is equivalent to (P.1) for $(t', k_0, D_0 \setminus \{v\}, \ell_0, f', c)$. Then, by the induction hypothesis, this is equivalent to (P.2) for $(t', k_0, D_0 \setminus \{v\}, \ell_0, f', c)$ and, by the definition of the table entry from Equation (7.10), this is equivalent to (P.2) for $(t, k_0, D_0 \setminus \{v\}, \ell_0, f, c)$.

To prove the above equivalence, we define a bijection ψ from the partial solutions for (t, k_0, D_0, ℓ_0, f) to the partial solutions for $(t', k_0, D_0 \setminus \{v\}, \ell_0, f')$. For a partial solution D for t with the claimed properties from (P.1), ψ maps D to $D' := D \setminus \{v\}$ as the corresponding partial solution for t'.

We first show that ψ is well-defined. For some partial solution D for t and for some type $T' \in \mathcal{T}_{t'}(D_0 \setminus \{v\})$, let P be a partial H-packing for $G_{t'} - (D \setminus \{v\})$ of type T' with regard to $X_{t'}$ with the maximum number of complete copies of H. Observe that $G_{t'} - (D \setminus \{v\}) = G_t - D$ as vertex v is introduced at t. Moreover, the type of P with regard to X_t is extend $(T', v \mapsto 0)$. Hence, there are exactly $\ell_0 - f(\text{extend}(T', v \mapsto 0))$ copies of H in P, which is equal to $\ell_0 - f'(T')$ by the definition of f'.

As injectivity follows from the definition of ψ , it remains to show that ψ is surjective. Consider some partial solution D' for t' with the properties from (P.1). Fix some type $T \in \mathcal{T}_t(D_0)$ and a partial H-packing P for $G_t - (D' \cup \{v\})$ of type T with the maximum number of complete copies of H. Since P does not contain v, packing P has type remove(T, v) with regard to $X_{t'}$. Hence, it contains at most $\ell_0 - f'(\text{remove}(T, v)) = \ell_0 - f(\text{extend}(\text{remove}(T, v), v \mapsto 0))$ copies of H. Moreover, as it is a packing with the maximum number of complete copies of H, it contains exactly that many copies of H. From Equations (7.1) and (7.4), we get that extend(remove $(T, v), v \mapsto 0) = T$ because we assumed that $v \in D_0$. Hence, the right-hand side is equal to $\ell_0 - f(T)$, and thus, finishes the proof of the surjectivity.

Case 2: $v \notin D_0$. First, consider the case where for some type $T' \in \mathcal{T}_{t'}(D_0)$, there are two types $T_1 \neq T_2 \in \bigcup_{i=0}^{tw+1} \operatorname{extend}(T, v \mapsto i)$ with $f_1(T_1), f_2(T_2) \neq \bot$ such that $f(T_1) \neq f(T_2)$. We claim that in this case, there is no solution for t with the claimed properties from (P.1). Assume otherwise and let the solution be \widetilde{D} . Without loss of generality, it suffices to consider the case when $f(T_1) > f(T_2)$. Let P_2 be a partial H-packing for $G_t - \widetilde{D}$ of type T_2 with the maximum T-completion number. After removing v from P_2 , we get a packing for $G_{t'} - \widetilde{D}$. This packing $P_2 - v$ can be extended to a partial H-packing for $G_t - \widetilde{D}$ of type T_1 by choosing the packing for v appropriately. Let P'_2 be this new packing. Since P'_2 and P_2 contain the same number of complete copies of H, packing P'_2 contains $\ell_0 - f(T_2) > \ell_0 - f(T_1)$ copies of H. But this contradicts the assumption that the T_1 -completion number for $G_t - \widetilde{D}$ is exactly $\ell_0 - f(T_1)$. Thus, in this case, we have correctly set the value of the table entry to 0.

Hence, for each type $T' \in \mathcal{T}_{t'}(D_0)$, there is a constant $c_{T'}$ such that, the function f' is defined as

$$f': \mathcal{T}_{t'}(D_0) \to [0..R] \cup \{\bot\}$$
 where $f'(T') = c_{T'}$.

As for the first case, our goal is to show that (P.1) for $(t, k_0, D_0, \ell_0, f, c)$ is equivalent to (P.1) for $(t', k_0, D_0, \ell_0, f', c)$. Then, the induction hypothesis implies that the latter result is equivalent to (P.2) for $(t', k_0, D_0, \ell_0, f', c)$, and by the definition of the table entry in Equation (7.11), we get that this is equivalent to (P.2) for $(t, k_0, D_0, \ell_0, f', c)$.

In the following, we show that every partial solution D for (t, k_0, D_0, ℓ_0, f) is also a partial solution for $(t', k_0, D_0, \ell_0, f')$ and vice versa, that is, we prove a bijection between the two sets of solutions.

Let *D* be a partial solution for *t*. Consider some type $T' \in \mathcal{T}_{t'}(D_0)$. Fix some arbitrary type $\overline{T} \in \bigcup_{i=0}^{tw+1} \operatorname{extend}(T', v \mapsto i) \subseteq \mathcal{T}_t(D_0)$. We can extend all partial *H*-packings for $G_{t'} - D$ of type *T'* to a partial *H*-packing for $G_t - D$ of type \overline{T} by extending the packing for *v* according to \overline{T} because *v* is not yet covered by the packing. Hence, the *T'*-completion number for $G_{t'} - D$ is at most the \overline{T} -completion number for $G_t - D$, which is precisely $\ell_0 - f(\overline{T}) = \ell_0 - f'(T')$.

Now, let \widetilde{P} be the partial *H*-packing of type \widetilde{T} containing the largest number of complete copies of *H*. By our assumptions about *f*, the packing \widetilde{P} contains exactly $\ell_0 - f(\widetilde{T})$ copies of *H*. Removing the vertex *v* from \widetilde{P} , we get a new partial *H*-packing for $G_{t'} - D$ of type remove (\widetilde{T}, v) with regard to $X_{t'}$. By our choice of \widetilde{T} , we get $T' = \text{remove}(\widetilde{T}, v)$, and thus, the packing also have type T'. Therefore, the T'-completion number is exactly $\ell_0 - f'(T')$.

Next, we prove the reverse direction. Consider some partial solution D' for $(t', k_0, D_0, \ell_0, f')$. Fix some type $T \in \mathcal{T}_t(D_0)$ and let P be a partial H-packing for $G_t - D'$ of type T with the maximum number of complete copies. Observe that the number of complete copies of H does not change if we remove v from P. Moreover, P - v has type remove(T, v) with regard to $X_{t'}$. Hence, the number of complete copies of H in P is at most $\ell_0 - f'$ (remove(T, v)). From Equations (7.1) to (7.5), we get that this is at most $\ell_0 - f(T)$. We conclude that D' is a partial solution for (t, k_0, D_0, ℓ_0, f) .

Let P' be some partial H-packing of type remove(T, v) containing the largest number of complete copies of H. By our assumptions about f', the packing P' contains exactly $\ell_0 - f'(T')$ copies of H. Since v is not covered in P', we can extend P' to a new partial H-packing P of type T by choosing the packing for v according to T. We see that P and P' contain the same number of complete copies of H, which is equal to $\ell_0 - f'(remove(T, v))$, and by the definition of f' it is also equal to $\ell_0 - f(T)$.

Forget Node. Assume out of the *c* partial solutions from (P.1) c_1 additionally satisfy $v \in D$ and the remaining $c_2 \coloneqq c - c_1$ satisfy $v \notin D$. Recall, from Equations (7.12) and (7.13), that the function $f_1: \mathcal{T}_{t'}(D_0 \cup \{v\}) \rightarrow [0..R] \cup \{\bot\}$ satisfies

$$f_1(T') = f(\text{remove}(T', v))$$

and the function $f_2: \mathcal{T}_{t'}(D_0) \to [0..R+1] \cup \{\bot\}$ satisfies

$$f_2(T') = \begin{cases} \bot, & \text{if } f(\text{remove}(T', v)) = \bot, \\ f(\text{remove}(T', v)) + 1, & \text{if } part(v) \neq 0 \text{ and } |H_{part(v)}| = 1, \\ f(\text{remove}(T', v)), & \text{otherwise.} \end{cases}$$

Also recall that r_{\min} is the smallest integer from the image of f_2 and r_{\max} is the largest integer in the image.

We claim that if $r_{\max} - r_{\min} > R$, then $c_2 = 0$. Assume otherwise and let D be such a solution satisfying the constraints in (P.1). Let $T_{\min} \in \mathcal{T}_t(D_0)$ be a type such that $f(T_{\min}) = r_{\min}$ and $T_{\max} \in \mathcal{T}_t(D_0)$ analogously for r_{\max} . Since there is a partial H-packing for $G_t - D$ of type T_{\max} and a partial H-packing for $G_t - D$ of type T_{\min} with $\ell_0 - f(T_{\min})$ copies of H, by Lemma 7.6, the T_{\max} -completion number is at least $\ell_0 - f(T_{\min}) - R > \ell_0 - r_{\max}$. But this contradicts the assumption that the T_{\max} completion number is exactly $\ell_0 - f(T_{\max}) = \ell_0 - r_{\max}$. Hence, we can safely assume in the following that $r_{\max} - r_{\min} \leq R$. Moreover, observe that subtracting r_{\min} from ℓ_0 and f_2 is only needed to adjust the range of the function f_2 to be in [0..R]. Hence, we omit this from the proof in the following to keep notation simple.

Assume that $v \notin U$ first (the case when $v \in U$ is analogous). Our goal is to show that (P.1) for $(t, k_0, D_0, \ell_0, f, c)$ is equivalent to the two combined properties (P.1) for $(t', k_0, D_0, \ell_0, f_1, c_1)$ and (P.1) for $(t', k_0 - 1, D_0 + v, \ell_0, f_2, c_2)$ together. Then we can use the induction hypothesis to get the equivalence to (P.2) for both cases and then by the definition of the dynamic programming table *A* this is equivalent to (P.2) for $(t, k_0, D_0, \ell_0, f, c)$.

For both settings we show that the partial solutions for t precisely coincide with the partial solutions for t', that is, there is a bijection between these partial solutions. Nevertheless, we handle both cases separately.

Case 1: v is deleted. Fix some partial solution D with $v \in D$ and the properties from (P.1). Consider some type $T' \in \mathcal{T}_{t'}(D_0 \cup \{v\})$. Observe that $G_{t'} - D = G_t - D$ and hence, every partial H-packing for $G_{t'} - D$ of type T' is also a partial H-packing for $G_t - D$ of type remove(T', v) with regard to X_t . Therefore, the T'-completion number for $G_{t'} - D$ is at most the remove(T', v)-completion number for $G_t - D$ which is by assumption $\ell_0 - f(\text{remove}(T', v))$ and by definition of f_1 this is equal to $\ell_0 - f_1(T')$.

Moreover, let *P* be the partial *H*-packing for $G_t - D$ of type remove(T', v) with the maximum number of complete copies of *H*. Since *P* is also a partial *H*-packing for $G_{t'} - D$ of type *T'*, the *T'*-completion number of $G_{t'} - D$ is at least $\ell_0 - f(\text{remove}(T', v)) = \ell_0 - f_1(T')$.

Now consider some partial solution D' for $(t', k_0 - 1, D_0 \cup \{v\}, \ell_0, f_1)$. Pick some arbitrary type $T \in \mathcal{T}_t(D_0)$. Let P be some partial H-packing for $G_t - D'$ of type T. Then, since $v \in D'$, we get that P is a partial H-packing for $G_{t'} - D'$ of type extend $(T, v \mapsto 0)$. By assumption the number of complete copies of H in P is at most $\ell_0 - f_1(\text{extend}(T, v \mapsto 0))$ which is, by the definition of f_1 , equal to $\ell_0 - f(\text{remove}(\text{extend}(T, v \mapsto 0), v))$ and by Equations (7.1) and (7.4) equal to $\ell_0 - f(T)$.

Let P' be some partial H-packing for $G_{t'} - D'$ of type extend $(T, v \mapsto 0)$ with the maximum number of complete copies of H. Since v is not contained in the packing, this is also a partial H-packing for $G_t - D'$ of type T containing $\ell_0 - f_1(\text{extend}(T, v \mapsto 0))$ copies of H. Hence, by the definition of f_1 , the T-completion number is exactly $\ell_0 - f(T)$.

Case 2: v is not deleted. Consider some partial solution D with $v \notin D$ for (t, k_0, D_0, ℓ_0, f) . We show that D is also a partial solution for $(t', k_0, D_0, \ell_0, f_2)$. Consider some type $T' \in \mathcal{T}_{t'}(D_0)$ with part $(v) \neq 0$ and $|H_{part(v)}| = 1$. Pick some partial H-packing P' for $G_{t'} - D$ of type T'. By our assumption we know that v is covered by a copy of H that is entirely contained in P'. Hence, with respect to X_t there is one more copy of H in P' then with respect to $X_{t'}$. Moreover, the packing P' has type remove(T', v) with regard to X_t . Hence, the T'-completion number for $G_{t'} - D$ is at most the remove(T', v)-completion number for $G_t - D$ minus 1; by assumption this number is equal to $\ell_0 - f(\text{remove}(T', v)) - 1$ which is equal to $\ell_0 - f_2(T')$ by the definition of f_2 .

On the other side, let *P* be the partial *H*-packing of type remove(T', v) containing exactly $\ell_0 - f(\text{remove}(T', v))$ copies of *H*. We directly get that *P* is a partial *H*-packing of type *T'* containing exactly $\ell_0 - f(\text{remove}(T', v)) - 1$ copies of *H*. Hence, by the definition of f_2 from Equation (7.13), the *T'*-completion number of $G_{t'} - D$ is exactly $\ell_0 - f_2(T')$.

Now consider some type $T' \in \mathcal{T}_{t'}(D_0)$, with part(T') = 0 or $|H_{part(v)}| > 1$. Again pick some partial *H*-packing *P'* for $G_{t'} - D$ of type *T'*. Since *v* is either not covered by any (partial) copy of *H* or part of a (partial) copy covering at least one more vertex from $X_{t'}$, the number of complete copies of *H* in *P'* with respect to $X_{t'}$ is equal to the number of complete copies of *H* in *P'* with respect to $X_{t'}$. Moreover, observe that *P'* has type remove(*T'*, *v*) with regard to X_t . Hence, the *T'*-completion number for $G_{t'} - D$ is at most the remove(*T'*, *v*)-completion number for $G_t - D$ which is, by assumption, exactly $\ell_0 - f(\text{remove}(T', v))$ and this is equal to $\ell_0 - f_2(T')$ by the definition of f_2 .

On the other side, let *P* be the partial *H*-packing of type remove(T', v) containing exactly $\ell_0 - f(\text{remove}(T', v))$ copies of *H*. Since *v* is either not covered or part of a partial packing containing some other vertex from X_t , the packing *P* is a partial *H*-packing of type *T'* containing exactly $\ell_0 - f(\text{remove}(T', v)) - 1$ copies of *H*. Hence, by the definition of f_2 from Equation (7.13), the *T'*-completion number of $G_{t'} - D$ is exactly $\ell_0 - f_2(T')$.

For the reverse direction consider some partial solution D' for $(t', k_0, D_0, \ell_0, f_2)$. Let $T \in \mathcal{T}_t(D_0)$ be some type and P some partial H-packing for $G_t - D'$ of type T. There is a unique type $T' \in \bigcup_{i=1}^{tw+1} \operatorname{extend}(T, v \mapsto i)$ such that P is a partial H-covering for $G_{t'} - D'$ of type T'. The number of complete copies of H in P with respect to $X_{t'}$ is at most $\ell_0 - f_2(T')$. Observe that when v is not covered or covered by a copy of H also covering other vertices from $X_{t'}$, then P contains as many copies of Hwith respect to $X_{t'}$ as with respect to X_t . By the definition of f_2 , we get $\ell_0 - f_2(T') = \ell_0 - f(\operatorname{remove}(T', v))$. Otherwise, we know that P with respect to X_t contains one copy of H more than P with respect to $X_{t'}$. By assumption the latter is at most $\ell_0 - f_2(T') - 1$ which is equal to $\ell_0 - (f(\operatorname{remove}(T', v)) + 1) - 1$. Using Equations (7.2) and (7.5) we conclude that in both cases the T-completion number is at most $\ell_0 - f(T)$.

On the other side, let P' be a partial H-packing of type T' with $\ell_0 - f_2(T')$ complete copies of H. By an argument similar to the ones before, we get that P' contains $\ell_0 - f_2(T)$ complete copies of H with respect to X_t . Hence, the *T*-completion number is exactly $\ell_0 - f_2(T)$.

Join Node Let *D* be one of the *c* different partial solutions. We define two new sets D_1 and D_2 as $D_1 := D \cap V_{t_1}$ and $D_2 := D \cap V_{t_2}$. By the structure of the tree decomposition, we have $D_1 \cap D_2 = D_0$. We choose k_1 and k_2 as $k_1 = |D_1 \setminus D_0|$ and $k_2 = |D_2 \setminus D_0|$.

Our first goal is to construct two functions, f_1 and f_2 , and define two integers ℓ_1 and ℓ_2 in $[0..\ell]$ such that ℓ_1, ℓ_2, f_1, f_2 are compatible with ℓ_0, f_0 . Moreover, we define them such that D_1 is one of the c_1 partial solutions for $(t_1, k_1, D_0, \ell_1, f_1)$ from (P.1) and D_2 is one of the c_2 partial solutions for $(t_2, k_2, D_0, \ell_2, f_2)$ from (P.1).

For all $T \in \mathcal{T}_t(D_0)$, let $\mathcal{P}(T)$ be the set of all possible partial *H*-packings for $G_t - D$ of type *T*. For all types $T_1 \in \mathcal{T}_{t_1}(D_0)$ and $T_2 \in \mathcal{T}_{t_2}(D_0)$, we define the following two sets of partial packings:

$$\mathcal{P}(T \to T_1) := \{ P' = P \cap V_{t_1} \mid P \in \mathcal{P}(T), P' \text{ has type } T_1 \text{ w.r.t. } X_{t_1} \}$$
$$\mathcal{P}(T \to T_2) := \{ P' = P \cap V_{t_2} \mid P \in \mathcal{P}(T), P' \text{ has type } T_2 \text{ w.r.t. } X_{t_2} \}$$

Based on this definition, for all $T_1 \in \mathcal{T}_{t_1}(D_0)$, we consider all packings in $\mathcal{P}(T \to T_1)$ and define $\lambda(T \to T_1)$ as the maximum number of complete copies of H in these packings. Likewise, we define the value $\lambda(T \to T_2)$ based on $\mathcal{P}(T \to T_2)$ for all $T_2 \in \mathcal{T}_{t_2}(D_0)$. We set

$$\ell_1 \coloneqq \max_{T_1 \in \mathcal{T}_{t_1}(D_0)} \max_{T \in \mathcal{T}_t(D_0)} \lambda(T \to T_1) \quad \text{and} \quad \ell_2 \coloneqq \max_{T_2 \in \mathcal{T}_{t_2}(D_0)} \max_{T \in \mathcal{T}_t(D_0)} \lambda(T \to T_2).$$

We define the two functions f_1 and f_2 as

$$f_1: \mathcal{T}_{t_1}(D_0) \to [0..\ell] \text{ with } f_1(T_1) = \ell_1 - \max_{T \in \mathcal{T}_\ell(D_0)} \lambda(T \to T_1) \text{ and}$$

$$f_2: \mathcal{T}_{t_2}(D_0) \to [0..\ell] \text{ with } f_2(T_2) = \ell_2 - \max_{T \in \mathcal{T}_\ell(D_0)} \lambda(T \to T_2).$$

We first argue that the image of f_1 and f_2 is actually contained in [0..R] as otherwise, there would be no solution. Assuming there is a solution, we directly deduce from Lemma 7.6 that the *T*-completion numbers for different types *T* differ by at most *R*. Hence, if one type violated this property, it would lead to a contradiction.

Next, we prove that D_1 is a solution for $(t_1, k_1, D_0, \ell_1, f_1)$ and D_2 is a solution for $(t_2, k_2, D_0, \ell_2, f_2)$. Since the proofs for both cases are almost identical, we will focus only on the proof for t_1 .

Let T_1 be some type in $\mathcal{T}_{t_1}(D_0)$, and let P_1 be a partial H-packing for $G_{t_1} - D_1$ of type T_1 . Choose $T \in \mathcal{T}_t(D_0)$ such that $\ell_0 - f_1(T_1) = \ell_1 - \lambda(T \to T_1)$, and let P be the corresponding partial H-packing for $G_t - D$ of type T. Now, observe that $P' := (P \cap V_{t_2}) \cup P_1$ is also a partial packing for $G_t - D$ and has type T_1 with regard to X_{t_1} . Therefore, $P' \cap V_{t_1}$ is a packing of type T_1 and thus is contained in $\mathcal{P}(T \to T_1)$. Moreover, this packing contains at most $\ell_1 - f_1(T_1)$ copies of H according to the definition of f_1 . Since

$$P' \cap V_{t_1} = ((P \cap V_{t_2}) \cup P_1) \cap V_{t_1} = P_1,$$

this implies that the T_1 -completion number is at most $\ell_0 - f_1(T_1)$.

By the definition of the function f_1 , it directly follows that there is a partial *H*-packing of type T_1 containing $\ell_0 - f_1(T_1)$ complete copies of *H*. Hence, combined with the previous result, the T_1 -completion number is exactly $\ell_0 - f_1(T_1)$.

For the reverse direction, fix some k_1, k_2 with $k_1 + k_2 = k_0$, ℓ_1, ℓ_2 , and f_1, f_2 such that, for all T_1, T_2 with $T_1 \oplus T_2 = T$, it holds that ℓ_1, ℓ_2, f_1, f_2 are compatible with ℓ_0, f_0 . We show that if there is a partial solution D_1 for $(t_1, k_1, D_0, \ell_1, f_1)$ and a partial solution D_2 for $(t_2, k_2, D_0, \ell_2, f_2)$, then the set $D_1 \cup D_2$ is a partial solution for $(t, k_1 + k_2, D_0, \ell_0, f)$.

For ease of notation, we set $D = D_1 \cup D_2$. Now consider some type $T \in \mathcal{T}_t(D_0)$ and some partial H-packing for $G_t - D$ of type T. As a first step, we observe that $P \cap V_{t_1}$ is a partial packing for $G_{t_1} - D = G_{t_1} - D_1$. Since the type of $P \cap V_{t_1}$ is T_1 for some $T_1 \in \mathcal{T}_t(D_0)$, the number of complete copies of

H in $P \cap V_{t_1}$ is at most $\ell_1 - f_1(T_1)$. Similarly, the number of complete copies in $P \cap V_{t_2}$ is at most $\ell_2 - f_2(T_2)$, where T_2 is such that $T_1 \oplus T_2 = T$. Hence, the number of complete copies of *H* in *P* is at most $\ell_1 - f_1(T_1) + \ell_2 - f_2(T_2) = \ell_0 - f(T)$.

Next, we show that the bound for the *T*-completion number is tight. Let T_1 and T_2 be types such that $T_1 \oplus T_2 = T$. Choose a partial *H*-packing P_1 of type T_1 containing $\ell_1 - f_1(T_1)$ copies of *H*. Likewise, let P_2 be a partial *H*-packing of type T_2 with $\ell_2 - f_2(T_2)$ complete copies of *H*. It follows that $P_1 \cup P_2$ is a partial *H*-packing of type *T* with $\ell_0 - f_1(T_1) + \ell_2 - f_2(T_2)$ complete copies of *H*. Hence, the *T*-completion number for $G_t - D$ is exactly $\ell_0 - f(T)$.

Now, for all tuples (t_1, k_1, D_0, f_1) and (t_2, k_2, D_0, f_2) , we can use the induction hypothesis to conclude that (P.1) is equivalent to (P.2). By the definition of the table entry from Equation (7.17), this is equivalent to (P.2). This concludes the proof of correctness of the dynamic program.

7.3 Running Time

As the last step we prove the bound on the running time of the dynamic program.

Claim 7.10. For a fixed graph *H*, the above algorithm runs in time $2^{2^{O(\text{tw} \log \text{tw})}} \cdot \text{poly}(n)$ to fill the table *A*.

Proof of Claim. By Lemma 7.5, for each node and each subset of the bag there are at most $\tau := tw^{O(tw \operatorname{poly}|H|)}$ different types. Hence, the size of the table *A* is bounded by

$$O(n \cdot \mathsf{tw}) \cdot k \cdot 2^{\mathsf{tw}+1} \cdot (\ell+1) \cdot (R+1)^{\tau} \le 2^{\tau \cdot O(\log(R+1))} \cdot \operatorname{poly}(n).$$

Now we analyze the time it takes to compute a single table entry. Observe, that is suffices to check the join nodes, as this running time dominates the running time for the other node types. Using a brute-force approach to compute the entry and a naive bound for the running time yields

$$k^2 \cdot ((R+1)^{\tau})^2 \cdot \tau^2 \le 2^{3 \cdot \tau \cdot \log(R+1)} \cdot \operatorname{poly}(n).$$

Combined with the first observation from above, we get that the algorithm has the following runtime:

$$\left(2^{3\cdot\tau\cdot\log(R+1)}\cdot\operatorname{poly}(n)\right)\cdot\left(2^{\tau\cdot\log(R+1)}\cdot\operatorname{poly}(n)\right)\leq 2^{4\cdot\tau\cdot\log(R+1)}\cdot\operatorname{poly}(n)$$

Note, that this is at most $2^{2^{O(\text{tw-log tw-poly}|H|)}} \cdot \text{poly}(n)$. The claimed running time follows, since *H* is a fixed graph.

The proof of Theorem 1.6 now follows from Lemma 7.9 and Claim 7.10.

8 CYCLE-HITPACK Parameterized by Treewidth: Double-Exponential Algorithm

In this section we extend the result from Section 7 to the case where we want to pack cycles of arbitrary length (at least length 3). Formally, we prove Theorem 1.2.

Theorem 1.2. CYCLE-HITPACK can be solved in time $2^{2^{O(tw \log tw)}} \cdot n^{O(1)}$, where tw is the treewidth of the input graph.

The underlying idea for this algorithm is the same as for the other algorithms for cliques and finite graphs. However, as we are not packing a fixed, single finite graph H but rather an infinitely sized family of graphs, we need a different way to represent the intersection of a partial packing with the vertices and edges from a bag. For this description, we heavily exploit that we are packing cycles and not some other family of graphs that could be unstructured or significantly more complex to describe, for example, the family of planar graphs.

The crucial observation is that every partial cycle-packing consists of a collection of cycles and paths. Hence, the vertices in a bag (and actually all other vertices) can be grouped into three groups, which can intuitively be described as follows.

- 1. The group of vertices that are not part of any cycle or path (this includes the deleted vertices).
- 2. The group of vertices that are the endpoints of a path that is later extended to a cycle.
- 3. The group of vertices that are contained in a cycle or contained in a path but not as their endpoints.

As a next step, we first formalize this idea by introducing some notation. Since the final algorithm operates on a tree decomposition, we define the notation only in this context.

Definition 8.1 (Partial Cycle-Packing). Let G be a graph and let t be a node of its tree decomposition. A partial cycle-packing for G_t (or just t for short) is a set \mathcal{P} of vertex disjoint paths and cycles in G_t such that for every path P in \mathcal{P} , the endpoints of P are contained in the bag X_t .

Depending on how a partial cycle-packing interacts with the vertices in a bag, we define different types to classify the different cycle-packings. See Figure 8.1 for an illustration of an example for a type.

Definition 8.2 (Types and *D*-avoidance). Let *G* be a graph and let *t* be a node of its tree decomposition. A type *T* for *t* is defined as a tuple $T = (Y_0, Y_1, Y_2, M)$ where Y_0, Y_1, Y_2 form a partition of X_t and *M* is a perfect matching for the vertices in Y_1 .

Let \mathcal{P} be a partial cycle-packing for G_t . We set

- $Y_0 := \{v \in V(\mathcal{P}) \cap X_t \mid \deg_{\mathcal{P}}(v) = 0\}$ as the set of all vertices in X_t that are not part of any path or cycle in \mathcal{P} ,
- $Y_1 := \{v \in V(\mathcal{P}) \cap X_t \mid \deg_{\mathcal{P}}(v) = 1\}$ as the set of all vertices in X_t that are endpoints of a path in \mathcal{P} ,
- $Y_2 := \{v \in V(\mathcal{P}) \cap X_t \mid \deg_{\mathcal{P}}(v) = 2\}$ as the set of all vertices in X_t that are either in a path (but not as endpoints) or in a cycle, and
- $M := \{\{u, v\} \in Y_1 \times Y_1 \mid u \neq v, \exists P \in \mathcal{P} : u, v \in P\}$ as the perfect matching on Y_1 describing which endpoints appear in the same path of the partial packing.

Then we say that \mathcal{P} is of type $T = (Y_0, Y_1, Y_2, M)$ for t. If for some set $D \subseteq X_t$ it holds that $D \subseteq Y_0$, then we say that type T is D-avoiding. We denote the set of all D-avoiding types for t by $\mathcal{T}_t(D)$.

When considering partial cycle-packings of a certain type, we want to formally describe the number of cycles that potentially could be packed in the remaining graph while preserving this type. We formalize this by the *T*-completion number.

Definition 8.3 (*T*-completion number). *Let G be a graph and let t be a node of its tree decomposition.*

For a type T for t, we define the T-completion number of G_t , denoted by $v^{\circ}(T)$, as the maximum number of complete cycles in \mathcal{P} over all possible cycle-packings \mathcal{P} of type T for G_t . The number of partial cycles, i.e., paths, is not included in this count.

Intuitively the completion number of different types can vary and for some types its "low" while for others its "high". Our next step is to define what we mean by a "low" completion number which then transfers to the corresponding type.

Definition 8.4 (Low Types). Let G be a graph and let t be a node of its tree decomposition. Consider two D-avoiding types $T, T' \in \mathcal{T}_t(D)$ for t such that (1) type \widehat{T} maximizes the \widehat{T} -completion number and (2) type T is such that $v^{\circ}(T) < v^{\circ}(\widehat{T}) - 2(\mathsf{tw} + 1)$. Then we say that T is low (for t).

We first prove that low types are not relevant for cycle-packings of maximum size.

Lemma 8.5. Let G be a graph and let t be a node of its tree decomposition. Consider a type T for t that is low. Then, there is no maximum cycle-packing \mathcal{P} for G such that \mathcal{P} has type T restricted to G_t .

Proof. Consider a maximum cycle-packing \mathcal{P} for the entire graph *G*. Assume for contradiction's sake that for some node *t* of the tree decomposition the type of \mathcal{P} restricted to G_t is *T* and *T* is low for *t*. We claim that $v^{\circ}(T) < v^{\circ}(T_{\emptyset}) - (tw + 1)$ where $T_{\emptyset} = (X_t, \emptyset, \emptyset, \emptyset)$ is the type for *t* where no vertex of the bag is contained in the packing.

First, let \widehat{T} be a type for t proving that T is low, that is, type \widehat{T} maximizes the \widehat{T} -completion number and let $\widehat{\mathcal{P}}$ be a corresponding cycle-packing. Removing all paths and cycles from $\widehat{\mathcal{P}}$ that intersect X_t , yields a (partial) cycle-packing of type T_{\emptyset} . Because of the removed paths and cycles we get $v^{\circ}(T_{\emptyset}) \ge v^{\circ}(\widehat{T}) - (tw + 1)$. Hence, from

$$v^{\circ}(T) < v^{\circ}(T) - 2(\mathsf{tw} + 1) \le v^{\circ}(T_{\emptyset}) - (\mathsf{tw} + 1)$$

the claim follows.

Now we move back to proving the statement. We define \mathcal{P}_0 as the restriction of \mathcal{P} to the graph G_t and $\overline{\mathcal{P}}$ as the restriction of \mathcal{P} to the graph $G - G_t$ where we additionally remove all paths. For convenience, we denote the type of $\overline{\mathcal{P}}$ for $G - G_t$ by \overline{T} . Additionally, consider a (partial) cycle-packing \mathcal{P}_{\emptyset} of type T_{\emptyset} containing $\nu^{\circ}(T_{\emptyset})$ complete cycles.

With these definitions at hand, we define a new packing \mathcal{P}' as the union of \mathcal{P}_{\emptyset} and $\overline{\mathcal{P}}$. Clearly \mathcal{P}' is a cycle-packing for the graph *G* as the packing \mathcal{P}_{\emptyset} does not cover vertices from the bag. Next we analyze the relation between the size of \mathcal{P} and \mathcal{P}' . From the above constructions and assumptions we get

$$\begin{aligned} |\mathcal{P}| &\leq v^{\circ}(T_0) + |\overline{\mathcal{P}}| + (\mathsf{tw} + 1) \\ &< v^{\circ}(T_{\varnothing}) - (\mathsf{tw} + 1) + v^{\circ}(\overline{T}) + (\mathsf{tw} + 1) \\ &= v^{\circ}(T_{\varnothing}) + v^{\circ}(\overline{T}) \\ &= |\mathcal{P}'| \end{aligned}$$

which proves that \mathcal{P}' contains more cycles than \mathcal{P} . This contradicts our assumption that \mathcal{P} is a maximum cycle-packing, no node of the decomposition has a type that is low.

Since we are actually solving the CYCLE-HITPACK problem, we are not interested in just packing cycles but rather in deleting vertices such that we cannot pack to many cycles in the remaining graph. Therefore, it is necessary to argue about all partial cycle-packings for some graph G_t at the same time. This idea is formalized by the concept of classes.

Definition 8.6 (Classes). Let G be a graph and let t be a node of its tree decomposition.

Moreover, let $k_0 \in [0..|V(G)|]$ be a non-negative integer, D_0 a subset of vertices from X_t , $\ell_0 \in [0..|V(G)|]$ be a non-negative integer, and $f_0: \mathcal{T}_t(D_0) \to [0..2\text{tw} + 2] \cup \{\bot, \heartsuit\}$.

We say that a set $D \subseteq V_t \setminus U$ is of class $c_0 = (k_0, D_0, \ell_0, f_0)$ for t if

- $|D \setminus D_0| = k_0 \text{ and } D \cap X_t = D_0$,
- there is a type $T \in \mathcal{T}_t(D_0)$ with $f_0(T) = 0$, and
- for all types $T \in \mathcal{T}_t(D_0)$,
 - *if there is no partial cycle-packing of type* T *for* t*, then* $f_0(T) = \bot$ *,*
 - if T is low for t or, for every partial packing \mathcal{P} of type T for t, there is a descendant t' of t such that the type of \mathcal{P} for t' is low, then $f_0(T) = \Im$, or
 - otherwise if the T-completion number for G_t is exactly $\ell_0 a$ for some $a \in [0..2tw + 2]$, then $f_0(T) = a$.

To simplify notation we assume that \perp and \Im are invariant under arithmetic operations where \perp takes precedence over \Im , that is, $\Im + \perp = \perp$.



(a) An example for a partial cycle-packing for G_t . The bold edges correspond to the edges in the partial packing.



(b) A graphical representation of the type (Y_0, Y_1, Y_2, M) of the depicted partial packing. The small group of the three round vertices at the top middle corresponds to Y_0 , the vertices at the bottom represent Y_2 , and the remaining vertices form Y_1 . The matching M between the vertices in Y_1 is represented by the dashed edges.

Figure 8.1: An illustration for a node t of how a partial cycle-packing and its type relate to each other. The black vertices and edges correspond to the edges and vertices of G. The deleted vertices are indicated by hollow dots.

Before stating the algorithm, we provide a bound for the number of *D*-avoiding types and classes for a fixed node *t*. These bounds follow directly from the definition of the two concepts.

Lemma 8.7. Let G be a graph and let t be a node of its tree decomposition of width tw. For a set $D \subseteq X_t$, the number of D-avoiding types for t, i.e., the size of $\mathcal{T}_t(D)$, is at most $\tau \in 2^{O(\mathsf{tw}\log\mathsf{tw})}$. The number of classes for t is at most $2^{2^{O(\mathsf{tw}\log\mathsf{tw})}} \cdot n^2$.

Proof. We start by bounding the number of *D*-avoiding types for a fixed set *D* and then use this result to bound the number of classes.

The number of partitions of X_t into the three sets Y_0 , Y_1 , and Y_1 is bounded by 3^{tw+1} . The choices for the set M which contains a perfect matching for Y_1 , is bounded by the number of permutations on $|Y_1|$ elements. Hence, the number of types is at most $\tau := 3^{tw+1} \cdot (tw+1)^{tw+1} = 2^{O(tw \log tw)}$.

To bound the number of classes (k_0, D_0, ℓ_0, f_0) for t, observe that there are at most n + 1 choices for k_0 , exactly 2^{tw+1} choices for the set D_0 , at most n+1 choices for the integer ℓ_0 , and at most $(2(tw+1)+3)^{\tau}$ choices for the function f_0 . Combining this yields that there are at most

$$n \cdot 2^{\mathsf{tw+1}} \cdot n \cdot (2\mathsf{tw} + 5)^{2^{\mathcal{O}(\mathsf{tw}\log\mathsf{tw})}} = 2^{2^{\mathcal{O}(\mathsf{tw}\log\mathsf{tw})}} \cdot n^2$$

different classes for a node t.

8.1 Auxiliary procedures

The algorithm for CYCLE-HITPACK is a dynamic program based on a given tree decomposition. We state the program in a bottom-up manner. For this we define five different procedures each of which compute the value for the parent node based on the values for the child nodes. To simplify the procedures we make use of introduce edge nodes and assume that each edge is introduced exactly once.

IntroVtx_{del}. The introduced vertex is deleted and thus, included in the part of the partition corresponding to uncovered vertices. See Lemma 8.8.

- IntroVtx_{not-del}. The introduced vertex is not deleted. Since we are using introduce edge nodes, the vertex is isolated and must be contained in the set corresponding to uncovered vertices for all types. See Lemma 8.9.
- IntroEdge_{del}. The endpoints of the introduced edge are deleted and thus, the edge cannot be included in any packing. See Lemma 8.10.
- IntroEdge_{not-del}. Both endpoints of the introduced edge are not deleted. Thus, this edge can be included in the possible packings but it can also not be included in a packing. See Lemma 8.11.
- Forget_{del}. The vertex forgotten at the node is deleted. By forgetting this vertex we have to change the budget for the number of vertices being deleted. See Lemma 8.12.
- Forget_{not-del}. The vertex forgotten at the node is not deleted. As the new class forgets whether the vertex was used in a packing or remained uncovered, two types for the child combine into one type for the parent. See Lemma 8.13.
- Join. The two classes for the two child nodes are combined into a new class for the parent where the existing paths might be joined to paths or cycles. See Lemma 8.16.

We start with the introduce vertex nodes where we have two different cases. The first case corresponds to the choice that v is deleted.

Lemma 8.8 (Introduce Vertex Node With a Deleted Vertex). Let t_0 be an introduce vertex node with child t_1 and let $v \in V_{t_0} \setminus U$ be the vertex introduced.

There is a procedure IntroVtx_{del} that, for a given class $c_1 = (k_1, D_1, \ell_1, f_1)$ for t_1 , computes in time $O(\tau)$ a class $c_0 = (k_1, D_1 \cup \{v\}, \ell_1, f_0)$ for t_0 such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$, if D is of class c_1 for t_1 , then $D \cup \{v\}$ is of class c_0 for t_0 .

Proof. We define the function f_0 as follows. For all types $T \in \mathcal{T}_{t_1}(D_1)$ with $T = (Y_0, Y_1, Y_2, M)$ we set

$$f_0(Y_0 \cup \{v\}, Y_1, Y_2, M) \coloneqq f_1(T).$$

Since vertex *v* does not appear in the graph G_{t_1} , and is deleted from G_{t_0} by considering $D_0 = D_1 \cup \{v\}$, the graphs $G_{t_1} - D_1$ and $G_{t_0} - D_0$ are identical. Hence, if the set *D* is of class c_1 for t_1 , then $D \cup \{v\}$ is of class c_0 for t_0 .

The second case for the introduce vertex node corresponds to the case when the vertex is not deleted.

Lemma 8.9 (Introduce Vertex Node With a Usable Vertex). Let t_0 be an introduce vertex node with child t_1 and let $v \in V_{t_0}$ be the vertex introduced.

There is a procedure IntroVtx_{not-del} that, for a given class $c_1 = (k_1, D_1, \ell_1, f_1)$ for t_1 , computes in time $O(\tau)$ a class $c_0 = (k_1, D_1, \ell_1, f_0)$ for t_0 such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$, if D is of class c_1 for t_1 , then D is of class c_0 for t_0 .

Proof. Observe that v is an isolated vertex in G_{t_0} . Hence, it especially does not have any neighbors in $G_{t_0} - X_{t_0}$. This implies that all partial solutions for t_0 cannot include v in a partial cycle-packing. Thus, all types for t_0 can be described by all types for t_1 where we add v to the set of uncovered vertices.

Observe that the intuitive idea agrees with the setting from the previous case, where the vertex is deleted. However, since in the current case the introduced vertex might receive some edge at some point in the future, the sets of types are strictly speaking not identical and thus, both cases need to be handled separately.

Based on this observation, we define the new function f_0 as follows. For all $T \in \mathcal{T}_{t_1}(D_1)$ with $T = (Y_0, Y_1, Y_2, M)$, we set

$$f_0(Y_0 \cup \{v\}, Y_1, Y_2, M) \coloneqq f_1(T).$$

With this definition it follows directly that every set $D \subseteq V_{t_1} \setminus U$ with class c_1 for t_1 is also of class c_0 for t_0 .

Next we consider the introduce edge nodes where we also provide two different procedures. The first one corresponds to the case where the edge cannot be selected in a packing because at least one of its endpoints is deleted.

Lemma 8.10 (Introduce Edge Node With a Deleted Endpoint). Let t_0 be an introduce edge node with child t_1 and let uv be the edge introduced.

There is a procedure IntroEdge_{del} that, for a given class $c_1 = (k_1, D_1, \ell_1, f_1)$ for t_1 , computes in time $O(\tau)$ a class $c_0 = (k_1, D_1, \ell_1, f_1)$ for t_0 such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$ with $D \cap \{u, v\} \neq \emptyset$, if D is of class c_1 for t_1 , then D is of class c_0 for t_0 .

Proof. If (at least) one of the endpoints of the introduced edge is deleted, i.e., contained in the set D_1 and thus, D, the edge cannot be part of any (partial) cycle-packing. Hence, the class of any such set D does not change.

The next procedure handles the case when both endpoints of the introduced edge are not deleted, meaning that the edge could be included in a packing.

Lemma 8.11 (Introduce Edge Node With Usable Endpoints). Let t_0 be an introduce edge node with child t_1 and let uv be the edge introduced.

There is a procedure IntroEdge_{not-del} that, for a given class $c_1 = (k_1, D_1, \ell_1, f_1)$ for t_1 computes in time $O(\tau)$ a class $c_0 = (k_1, D_1, \ell_0, f_0)$ for t_0 such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$ with $D \cap \{u, v\} = \emptyset$, if D is of class c_1 for t_1 , then D is of class c_0 for t_0 .

Proof. It remains to define f_0 . For this we first define a function f which we derive f_0 later from. In the definition of f we consider six possible cases where two of them are symmetric. For all types $T \in \mathcal{T}_{t_1}(D_1)$ with $T = (Y_0, Y_1, Y_2, M)$, we define

Case 0:	$f(Y_0,$	Y_1 ,	<i>Y</i> ₂ ,	M) := $f_1(T)$,
Case 1:	$\text{if } u \in Y_0 \land v \in Y_0$				
	$f(Y_0 \setminus \{u,v\},$	$Y_1 \cup \{u, v\},$	<i>Y</i> ₂ ,	$M \cup \{uv\}$) := $f_1(T)$,
Case 2a:	$\text{ if } u \in Y_0 \land yv \in M$				
	$f(Y_0 \setminus \{u\},$	$Y_1 \setminus \{v\} \cup \{u\},\$	$Y_2 \cup \{v\},$	$M \setminus \{vy\} \cup \{uy\}$) := $f_1(T)$,
Case 2b:	$\text{ if } xu \in M \land v \in Y_0$				
	$f(Y_0 \setminus \{v\},$	$Y_1 \setminus \{u\} \cup \{v\},\$	$Y_2 \cup \{u\},$	$M \setminus \{xu\} \cup \{xv\}$) := $f_1(T)$,
Case 3:	$\text{if } xu \in M \land yv \in N$	1			
	$f(Y_0,$	$Y_1 \setminus \{u, v\},\$	$Y_2 \cup \{u,v\},$	$M \setminus \{xu, yv\} \cup \{xy\}$	$) := f_1(T)$, and
Case 4:	if $uv \in M$				
	$f(Y_0,$	$Y_1 \setminus \{u, v\},\$	$Y_2 \cup \{u,v\},$	$M \cup \{uv\}$	$) := f_1(T) - 1$

where $x, y \in Y_1$ are such that u, v, x, y are all distinct. Recall, that \perp and \Im are invariant under arithmetic operations, this especially implies $\perp -1 = \perp$ and $\Im - 1 = \Im$.

Observe that f is a function from $\mathcal{T}_{t_0}(D_0)$ to $[-1..2tw + 2] \cup \{\perp, \mathring{\gamma}\}$. If there is no type $T \in \mathcal{T}_{t_0}(D_0)$ such that f(T) = -1, then we define $f_0 = f$. Otherwise, we define f_0 based on f where, for all types $T \in \mathcal{T}_{t_0}(D_0)$,

$$f_0(T) \coloneqq \begin{cases} f(T), & \text{if } f(T) \in \{ \vec{\gamma}, \perp \}, \\ \vec{\gamma}, & \text{if } f(T) = 2(\mathsf{tw} + 1), \\ f(T) + 1, & \text{otherwise.} \end{cases}$$

As a last step it remains to define ℓ_0 . If $f_0 = f$, then we set $\ell_0 = \ell_1$ and otherwise we set $\ell_0 = \ell_1 + 1$ which is complementing the definition of f_0 .

Now consider a set $D \subseteq V_{t_1} \setminus U = V_{t_0} \setminus U$ with $D \cap \{u, v\} = \emptyset$ that is of class c_1 for t_1 . We claim that D is of class c_0 for t_0 . To prove this, fix some type $T_0 \in \mathcal{T}_{t_0}(D_1)$.

If a packing of type T_0 does not contain the edge uv, then this packing is also of type T_0 for t_1 . This is Case 0 in the definition above.

If the edge is selected, then there is a unique type T_1 for t_1 resulting from deleting the edge. Depending on how the inclusion of edge uv changed the type, we consider four different cases:

Case 1: A new path is created.

Case 2: A path is extended by this edge.

Case 3: Two paths are connected to each other.

Case 4: A cycle is closed.

For the first three cases, the number of cycles does not change. Only for Case 4, we obtain one more cycle in the type for t_0 which was not present in the type for t_1 .

As a next step we consider forget nodes. Depending on whether the forgotten vertex is deleted or not, we consider two disjoint cases.

Lemma 8.12 (Forget Node With a Deleted Vertex). Let t_0 be a forget node with child t_1 and let $v \notin U$ be the vertex forgotten.

There is a procedure Forget_{del} that, for a given class $c_1 = (k_1, D_1, \ell_1, f_1)$ for t_1 with $v \in D_1$, computes in time $O(\tau)$ a class $c_0 = (k_1 + 1, D_1 \setminus \{v\}, \ell_1, f_0)$ for t_0 such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$, if D is of class c_1 for t_1 , then D is of class c_0 for t_0 .

Proof. The function f_0 basically agrees with f_1 except that every type for t_0 does not include v. As every type for t_1 includes v, there is a simple one-to-one correspondence between the types for t_0 and t_1 .

Formally, we define the function $f_0: \mathcal{T}_{t_0}(D_1 \setminus \{v\}) \to [0..2\mathsf{tw} + 2] \cup \{\bot, \mathring{\gamma}\}$ as follows. For all types $T \in \mathcal{T}_{t_1}(D_1)$ with $T = (Y_0, Y_1, Y_2, M)$, we set

$$f_0(Y_0 \setminus \{v\}, Y_1, Y_2, M) \coloneqq f_1(Y_0, Y_1, Y_2, M) = f_1(T).$$

When considering a set $D \subseteq V_{t_1} \setminus U$ of class c_1 for t_1 , we immediately get, by our choice of f_0 , that D is of class c_0 for t_0 .

The next procedure covers the second case for a forget node where the vertex forgotten is not deleted and thus, could potentially appear in cycle-packings.

Lemma 8.13 (Forget Node With a Usable Vertex). Let t_0 be a forget node with child t_1 and let u be the vertex forgotten.

There is a procedure $\text{Forget}_{\text{not-del}}$ that, for a given class $T_1 = (k_1, D_1, \ell_1, f_1)$ computes in time $O(\tau)$ a class $c_0 = (k_1, D_1, \ell_1, f_0)$ such that the following holds: For all sets $D \subseteq V_{t_1} \setminus U$ with $v \notin D$, if D is of class c_1 , then D is of class c_0 .

Proof. We define f_0 as follows. For all types $T \in \mathcal{T}_{t_0}(D_1)$ with $T = (Y_0, Y_1, Y_2, M)$, we set

$$f_0(T) \coloneqq \ell_1 - \max(\ell_1 - f_1(Y_0 \cup \{v\}, Y_1, Y_2, M), \ell_1 - f_1(Y_0, Y_1, Y_2 \cup \{v\}, M))$$

where we assume that $a > \gamma > \bot$ for all $a \in \mathbb{N}$.

Observe that when the vertex v is not deleted, it can either be covered or uncovered. In both cases we can get the same type for t_0 , although the packing has different types for t_1 .

The last procedure handles the case for join nodes. Here we have to combine two partial cyclepackings to form a new one. In order to make this combination formal, we define a function reduce which operates on the union of two matchings and combines them such that partial packings are joined together whenever possible and cycles are closed as soon as two partial cycle-packings form together a cycle. **Definition 8.14.** Let G be a graph and let t be a join node of its tree decomposition. We define the function

$$\mathsf{reduce}: 2^{X_t \times X_t} \times \mathbb{N} \to 2^{X_t \times X_t} \times \mathbb{N}$$

as reduce $(M, \lambda) := (M, \lambda)$ if, for all distinct $u, v, w \in X$, the set M satisfies $|M \cap \{uv, vw\}| \le 1$. Otherwise, we define

$$\operatorname{reduce}(M,\lambda) := \begin{cases} (M \setminus \{uv, vw\} \cup \{uw\}, \lambda), & \text{if } uv, vw \in M \land uw \notin M, \\ (M \setminus \{uv, vw\}, \lambda+1), & \text{if } uv, vw \in M \land uw \in M. \end{cases}$$

With this function reduce in mind, we now formally define the combination of two types.

Definition 8.15 (Combination of Types). Let *G* be a graph and let t_0 be a join node of its tree decomposition with children t_1 and t_2 . Let $T_1 \in \mathcal{T}_{t_1}(D_1)$ be a type for t_1 with $T_1 = (Y'_0, Y'_1, Y'_2, M')$ and $T_2 \in \mathcal{T}_{t_2}(D_1)$ be a type for t_2 with $T_2 = (Y''_0, Y''_1, Y''_2, M'')$.

The combination of T_1 and T_2 is undefined whenever $Y'_2 \not\subseteq Y''_0$ or $Y''_2 \not\subseteq Y'_0$, that is, when a vertex would be incident to at least three selected edges in the combined packing. Otherwise, we define a new type $T_0 = (Y_0, Y_1, Y_2, M)$ with

$$Y_0 := Y'_0 \cap Y''_0$$

$$Y_1 := (Y'_1 \cap Y''_0) \cup (Y'_0 \cap Y''_1)$$

$$Y_2 := Y'_2 \cup Y''_2 \cup (Y'_1 \cap Y''_1)$$

where the set M is defined as the set such that (M, λ) is the fix point of the function reduce on input $((M' \setminus M'') \cup (M'' \setminus M'), |M' \cap M''|).$

We say that T_1 and t_2 can be combined to type T_0 by creating λ cycles and denote this by $T_1 \oplus T_2 \stackrel{+\lambda}{=} T_0$.

With this definition we can now state the procedure for the join node.

Lemma 8.16 (Join). Let t_0 be a join node with children t_1 and t_2 .

There is a procedure Join that, for given classes $c_1 = (k_1, D_1, \ell_1, f_1)$ for t_1 and $c_2 = (k_2, D_2, \ell_2, f_2)$ for t_2 with $D_1 = D_2$, computes in time $O(\tau^3)$ a class $c_0 = (k_1 + k_2, D_1, \ell_0, f_0)$ for t_0 such that the following holds: For all sets $D' \subseteq V_{t_1} \setminus U$ and all sets $D'' \subseteq V_{t_2} \setminus U$ if D' is of class c_1 for t_1 and D'' is of class c_2 for t_2 , then $D' \cup D''$ is of class c_0 for t_0 .

Proof. First observe that we assumed that each edge is introduced exactly once in the underlying tree decomposition. Hence, the edge cannot appear in the partial packing for the left subtree *and* the partial packing for the right subtree. Moreover, every type for t_0 can be split into a component coming from t_1 and a part coming from t_2 depending on the edges that have been introduced so far.

We first define a function f which serves as the basis for defining f_0 . For all types $T_0 \in \mathcal{T}_{t_0}(D_1)$, we set

$$f(T) \coloneqq \max_{\substack{T_1 \in \mathcal{T}_{t_1}(D_1) \\ T_2 \in \mathcal{T}_{t_2}(D_1) \\ T_1 \oplus T_2^{+\lambda} T_0}} \begin{cases} \ell_1 - f_1(T_1) + \ell_2 - f_2(T_2) + \lambda, & \text{if } f_1(T_1), f_2(T_2) \in \mathbb{N}, \\ & \text{if } \forall \in \{f_1(T_1), f_2(T_2)\} \not \geqslant \bot \\ & \text{if } \bot \in \{f_1(T_1), f_2(T_2)\}, \end{cases}$$

where we assume that $a > \gamma > \bot$ for all $a \in \mathbb{N}$.

Based on this we now define f_0 and ℓ_0 . For some type \widehat{T} maximizing $f(\widehat{T})$, we set $\ell_0 \coloneqq f(\widehat{T})$. We construct f_0 based on f where, for all types $T \in \mathcal{T}_{t_0}(D_0)$, we set

$$f_0(T) := \begin{cases} f(T), & \text{if } f(T) \in \{ \mathcal{V}, \bot \}, \\ \mathcal{V}, & \text{if } f(T) < \ell_0 - 2(\mathsf{tw} + 1), \\ \ell_0 - f(T), & \text{otherwise.} \end{cases}$$

With this definition it follows directly that for two given sets $D' \subseteq V_{t_1}$ of class c_1 for t_1 and $D'' \subseteq V_{t_2}$ of class c_2 for t_2 , the set $D' \cup D''$ is of class c_0 for t_0 .

8.2 Dynamic program

Now we have everything ready to state the algorithm solving CYCLE-HITPACK, that is, prove Theorem 1.2 which we restate for convenience.

Theorem 1.2. CYCLE-HITPACK can be solved in time $2^{2^{O(tw \log tw)}} \cdot n^{O(1)}$, where tw is the treewidth of the input graph.

Proof of Theorem 1.2. Given an instance $I = (G, U, k, \ell)$ of CYCLE-HITPACK, we first compute an optimal tree decomposition of *G* and then transform this decomposition into a nice tree decomposition with introduce edge nodes where each edge is introduced once and the additional requirement that the root and leaf nodes have empty bags.

The algorithm computes, for each node t of the tree decomposition, a list $\mathcal{L}(t)$ of classes c for this node such that there is a set $D \subseteq V_t \setminus U$ that is of class c.

The dynamic program traverses the tree decomposition in post-order and for each node t_0 we perform the following actions (depending on the type of node t_0).

- **Leaf Node.** For each leaf node t_0 of the tree decomposition, we define the list $\mathcal{L}(t_0)$ explicitly by setting $\mathcal{L}(t_0) \coloneqq \{(0, \emptyset, 0, (\emptyset, \emptyset, \emptyset, \emptyset) \mapsto 0)\}.$
- **Introduce Vertex Node.** Let t_1 be the unique child of t_0 and let v be the vertex introduced at t_0 , that is, $X_{t_0} = X_{t_1} \cup \{v\}$. Repeat the following two steps for all classes $c_1 \in \mathcal{L}(t_1)$:
 - Apply IntroVtx_{not-del} from Lemma 8.9 on c_1 to compute the class c_0 and add c_0 to the list $\mathcal{L}(t_0)$.
 - If $v \in V(G) \setminus U$, i.e., the vertex v can be deleted, then use IntroVtx_{del} from Lemma 8.8 to compute a class c'_0 and add c'_0 to the list $\mathcal{L}(t_0)$ as well.
- **Introduce Edge Node.** Let t_1 be the unique child of t_0 and let uv be the edge introduced. Repeat the following for all classes $c_1 \in \mathcal{L}(t_1)$:
 - If $u \in D_1$ or $v \in D_1$, then use IntroEdge_{del} from Lemma 8.10 on c_1 to compute the class c_0 and add c_0 to the list $\mathcal{L}(t_0)$.
 - Otherwise we get $u, v \notin D_1$. Then, we use IntroEdge_{not-del} from Lemma 8.11 on c_1 to compute the class c'_0 and add c'_0 to the list $\mathcal{L}(t_0)$.
- **Forget Node.** Let t_1 be the unique child of t_0 and let v be the vertex forgotten, that is, $X_{t_0} = X_{t_1} \setminus \{v\}$. Repeat the following for all classes $c_1 \in \mathcal{L}(t_1)$:
 - If $v \in D_1$, then use Forget_{del} from Lemma 8.12 on c_1 to compute the class c_0 and add c_0 to the list $\mathcal{L}(t_0)$.
 - If $v \notin D_1$, then use $\text{Forget}_{\text{not-del}}$ from Lemma 8.13 on c_1 to compute the class c'_0 and add c'_0 to the list $\mathcal{L}(t_0)$.
- **Join Node.** Let t_0 be the unique parent of the nodes t_1 and t_2 . Repeat the following for all pairs of classes $(c_1, c_2) \in \mathcal{L}(t_1) \times \mathcal{L}(t_2)$: Check that $D_1 = D_2$ and if so apply the procedure Join from Lemma 8.16 on (c_1, c_2) to get a class c_0 for t_0 and add c_0 to the list $\mathcal{L}(t_0)$.

It remains to define the output of the algorithm. For this let r be the root of the tree decomposition. Then, the algorithm outputs Yes if the list $\mathcal{L}(r)$ contains a class $(k_0, \emptyset, \ell_0, (\emptyset, \emptyset, \emptyset, \emptyset) \mapsto 0)$ for some $k_0 \in [0..k]$ and $\ell_0 \in [0..\ell - 1]$. **Correctness.** It remains to prove the correctness and the running time of this algorithm. We first show correctness by proving the following claim.

Claim 8.17 (Correctness). For all nodes t_0 , integers $0 \le k_0 \le k$, vertex sets $D_0 \subseteq X_t \setminus U$, integers $0 \le \ell_0 < \ell$, and functions $f_0: \mathcal{T}_t(D_0) \to [0..2tw+2] \cup \{\bot, \heartsuit\}$, the following two statements are equivalent:

- There is a set $D \subseteq V_t \setminus U$ of class (k_0, D_0, ℓ_0, f_0) for t_0 .
- $(k_0, D_0, \ell_0, f_0) \in \mathcal{L}(t_0).$

Proof of Claim. By the definition of the procedures from Lemmas 8.8 to 8.13 and 8.16 and the definition of the list for the leaf nodes, it directly follows that the second statement implies the first one.

Therefore, we only have to prove that the first statement implies the second statement. We prove this inductively based on the type of the node t_0 in the tree decomposition.

- **Leaf Node.** Since the bags of the leaf nodes do not contain any vertices, no vertices can be deleted. By assumption, the leaf nodes do not have children and hence, the only possible class is the empty class, which we included in the list.
- **Introduce Vertex Node.** If the set *D* is of class c_0 for t_0 and $v \in D$, then $D \setminus \{v\}$ is of some class c_1 for t_1 . By induction we get $c_1 \in \mathcal{L}(t_1)$. From the algorithm and the properties of IntroVtx_{del}, we obtain a class *c* for t_0 such that *D* is of class *c* for t_0 . Moreover, the algorithm adds c_0 to $\mathcal{L}(t_0)$. Since each set *D* has exactly one class for each node, we have $c_0 = c$ and thus, $c_0 \in \mathcal{L}(t_0)$.

Note, that if $v \notin D$, then we similarly get that $c_0 \in \mathcal{L}(t_0)$ by using IntroVtx_{not-del}.

- **Introduce Edge Node.** The correctness follows analogously to the introduce vertex node by distinguishing the two cases whether an endpoint of the introduced edge was deleted or both endpoints are not deleted.
- **Forget Node.** The result follows analogously to the introduce vertex node by splitting into the two cases of *v* being deleted or not.
- **Join Node.** Assume that D is of class c_0 . If we consider $D' = D \cap V_{t_1}$ and $D'' = D \cap V_{t_2}$, we have that D' and D'' are of some classes c_1 and c_2 for t_1 and t_2 , respectively. By the induction hypothesis it follows that $c_1 \in \mathcal{L}(t_1)$ and $c_2 \in \mathcal{L}(t_2)$.

From the definition of the algorithm and the properties of the procedure Join, it follows that $D' \cup D'' = D$ is of some class c for t_0 . By the uniqueness of classes, we conclude that $c = c_0$ and therefore, $c_0 \in \mathcal{L}(t_0)$.

As the last step we prove the running time of the algorithm depending on the size of the lists.

Claim 8.18. Let *L* denote the maximum length of a list $\mathcal{L}(t)$ for all nodes *t*. Then, the algorithm terminates in time $L^2 \cdot 2^{\text{poly}(tw)} \cdot \text{poly}(n)$.

Proof of Claim. Computing a nice tree decomposition is possible in time $2^{\text{poly}(\text{tw})} \cdot \text{poly}(n)$ [17, Chapter 7.6]. Observe that handling the join nodes dominates the running time as we have to consider up to L^2 different pairs of classes. Since each new class can be computed in time $2^{\text{poly}(\text{tw})}$, the claim follows.

From Lemma 8.7 we know that for each node of the tree decomposition, the number of distinct classes is at most $2^{2^{O(\text{tw}\log \text{tw})}} \cdot \text{poly}(n)$. Hence, the final running time directly follows from Claim 8.18 which concludes the proof by Claim 8.17.

9 $\Sigma_2^{\mathbf{P}}$ -Completeness Results

In this section we show the completeness of the CYCLE-HITPACK problem and the *H*-HITPACK problem for the second level of the polynomial hierarchy. Formally, we prove Theorems 1.1 and 1.5.

Towards proving these results, we first show in Lemma 9.1 that the problems are contained in $\Sigma_2^{\rm P}$. Then, by the proof of Theorem 9.10, which is given in Section 9.2, we show the $\Sigma_2^{\rm P}$ -hardness of TRIANGLE-HITPACK which we extend to CYCLE-HITPACK. In Section 9.3 we lift the hardness of TRIANGLE-HITPACK to the general *H*-HITPACK problem by proving Lemma 9.13.

The Σ_2^{p} -completeness results for CYCLE-HITPACK and H-HITPACK from Theorems 1.1 and 1.5 then follow from Lemma 9.1 together with the hardness results from Sections 9.2 and 9.3, respectively.

Lemma 9.1. For any connected graph H, the problems H-HITPACK and CYCLE-HITPACK are in Σ_2^P .

Proof. We observe that for a given graph G, the problem of deciding if there is a H-packing of size at least ℓ is in NP, as the H-packing itself constitutes a polynomial witness. We assume oracle access to the problem.

Next, we can solve *H*-HITPACK by guessing the deleted vertices non-deterministically and subsequently verifying that an *H*-packing of size at least ℓ does not exist in the remaining graph. This can be achieved with an NP-oracle by querying it and negating the answer. Therefore, *H*-HITPACK can be solved in non-deterministic polynomial time using an NP oracle. Hence, *H*-HITPACK \in NP^{NP} = Σ_2^P . An analogous argument shows that CYCLE-HITPACK $\in \Sigma_2^P$.

9.1 Satisfiability Problems Complete for Σ_2^{P}

In this section, we introduce some satisfiability problems which are complete for the second level of the polynomial hierarchy.

We begin with the formal definition of the prototypical Σ_2^{P} -complete problem, which is based on Boolean formulas in disjoint normal form (DNF).

Note that in this paper, for a variable x, we let \overline{x} denote the negation of x. Moreover, we say that x is a positive literal and \overline{x} is a negative literal. Finally, note that a maximal group of disjoint literals in a DNF is commonly referred to as a *term*. For example, the 3-DNF formula $\psi = (x_1 \wedge x_2 \wedge \overline{x}_3) \vee (x_4 \wedge x_5 \wedge \overline{x}_1)$ has 5 variables, 6 literals and 2 terms. One of the terms of ψ is $(x_1 \wedge x_2 \wedge \overline{x}_3)$.

Definition 9.2. Let $Q3DNF_2$ denote the problem of deciding whether a given formula φ in disjunctive normal form with terms of length at most three on the variable set $X \cup Y$, where $X = \{x_1, \ldots, x_m\}$ and $Y = \{y_1, \ldots, y_n\}$ for some natural numbers m and n, has an assignment to the variables in X such that the remaining formula is a tautology. That is,

 $Q3DNF_2 = \{\varphi(x_1, ..., x_m, y_1, ..., y_n) \in 3DNF \mid \exists x_1, ..., x_m \forall y_1, ..., y_n : \varphi = 1\}.$

In his seminal work, Stockmeyer [74] proved this problem to be Σ_2^{P} -complete.

Theorem 9.3 ([74, Theorem 4.1.2]). The problem $Q3DNF_2$ is log-space Σ_2^P -complete.

We define the related problem where the underlying SAT-formula is in CNF.

Definition 9.4. Denote by $Q3CNF_2$ the problem of deciding whether a given formula φ in conjunctive normal form with clauses of length at most three on the variable set $X \cup Y$, where $X = \{x_1, \ldots, x_m\}$ and $Y = \{y_1, \ldots, y_n\}$ for some natural numbers m and n, has an assignment to the variables in X such that remaining formula is unsatisfiable. That is,

$$Q3CNF_2 = \{\varphi(x_1, ..., x_m, y_1, ..., y_n) \in 3CNF \mid \exists x_1, ..., x_m \not\exists y_1, ..., y_n : \varphi = 1\}$$

By using De Morgan's laws and basic properties of quantification and their negation, we can extend the Σ_2^{P} -completeness of Q3DNF₂ from Theorem 9.3 to Q3CNF₂.

Corollary 9.5. The problem $Q3CNF_2$ is log-space Σ_2^{P} -complete.

Proof. For any given 3DNF-formula $\varphi(x_1, \ldots, x_m, y_1, \ldots, y_n)$, let ψ be the 3CNF-formula obtained from φ by replacing every literal by its negation and swapping every \vee for \wedge and vice versa.

This yields a log-space reduction from Q3DNF₂ to Q3CNF₂. On the one hand, logarithmic space is clearly sufficient to transform φ into ψ . On the other hand, φ is equivalent to $\neg \psi(x_1, \ldots, x_m, y_1, \ldots, y_n)$, by the laws of De Morgan and distributivity. Therefore, the formula

$$\exists x_1, \ldots, x_m \,\forall y_1, \ldots, y_n \colon \varphi(x_1, \ldots, x_m, y_1, \ldots, y_n) = 1$$

is equivalent to

$$\exists x_1, \ldots, x_m \,\forall y_1, \ldots, y_n \colon \neg \psi(x_1, \ldots, x_m, y_1, \ldots, y_n) = 1$$

which is in turn equivalent to

$$\exists x_1, \dots, x_m \not\exists y_1, \dots, y_n \colon \psi(x_1, \dots, x_m, y_1, \dots, y_n) = 1.$$

As a next step we first formally define the size of a formula.

Definition 9.6 (Formula Size). The size $|\varphi|$ of a CNF-formula φ is the number of its clauses. We say that φ is smaller than another formula φ' if $|\varphi| < |\varphi'|$.

The last two problems we introduce consider subformulas of a given CNF-formula. For this reason we first formally introduce this intuitive concept.

Definition 9.7 (Subformula). Given a CNF-formula $\varphi = C_1 \land \dots \land C_m$ consisting of *m* clauses, we call any formula φ' that results from deleting an arbitrary subset of these clauses a subformula of φ and denote this by $\varphi' \subseteq \varphi$. If additionally $\varphi' \neq \varphi$, that is, the deleted subset is nonempty, the resulting subformula is called proper and we write $\varphi' \subseteq \varphi$. If ψ is a (proper) subformula of ψ' , then ψ' is a (proper) superformula of ψ .

With this definition, we define the problems SUS and its corresponding version 3CNF-SUS for 3CNFs.

Definition 9.8 (Smallest Unsatisfiable Subformula). SUS is the problem of deciding, given a formula φ and an integer k, whether φ has an unsatisfiable subformula of size at most k. 3CNF-SUS is the problem restricted to CNF formulas with at most three literals per clause.

Umans, Fortnow and Killian have reportedly proven the $\Sigma_2^{\rm P}$ -completeness of SUS (calling the problem MIN DNF TAUTOLOGY) [73, p. 35, L7, MIN DNF TAUTOLOGY], but only Umans published a proof, and only for the version that does not limit the number of literals in a clause [76, Theorem 2]. Several years later and apparently without knowledge of Uman's proof, Liberatore [51, Theorem 2] reproved this statement by a more direct reduction, but still without the restriction to at most three literals per clause. Although not strictly necessary for our purposes, we extend this result by providing the missing proof of the $\Sigma_2^{\rm P}$ -hardness for 3CNF-SUS.

Theorem 9.9. 3CNF-SUS is Σ_2^{P} -complete.

Proof. For membership in Σ_2^{P} , guess a subformula of size *k* and verify its unsatisfiability with the NP-oracle.

We now reduce Q3CNF₂ to 3CNF-SUS. Given an instance $\varphi(x_1, \ldots, x_m, y_1, \ldots, y_n) = C_1 \land \cdots \land C_t$ with *t* clauses for the problem Q3CNF₂, that is normalized to contain exactly three literals per clause by duplicating literals if necessary. First, replace every literal that is a positive occurrence of x_i by a negative occurrence of the new variable z_i , and write the *t* clauses of the resulting formula as $(\lambda_1^1 \lor \lambda_1^2 \lor \lambda_1^3) \land \cdots \land (\lambda_t^1 \lor \lambda_t^2 \lor \lambda_t^3)$. Note that any of these literals might be a negative or positive occurrence of y_j for any $j \in [n]$ since we did not modify these variables at all. The instance for 3CNF-SUS is (ψ, k) , where, using the definition $s = \lceil \log m \rceil$, we have $k = 2^{s+1} - (m+1) + (2t+2)m + 2t$ and $\psi = W \wedge V \wedge \bigwedge_{i=1}^m (X_i \wedge Z_i) \wedge \bigwedge_{j=1}^t \Gamma_j$ with

$$W = \bigwedge_{i=1}^{2^{s}-1} (\overline{w}_{2i} \vee \overline{w}_{2i+1} \vee w_{i}),$$

$$V = \bigwedge_{i=2^{s}}^{2^{s+1}-(m+1)} (w_{i}),$$

$$X_{i} = (x_{i}^{2t}) \wedge (\overline{x}_{i}^{1} \vee x_{i}) \wedge (\overline{x}_{i} \vee w_{2^{s+1}-i}) \wedge \bigwedge_{j=1}^{2t-1} (\overline{x}_{i}^{j+1} \vee x_{i}^{j}),$$

$$Z_{i} = (z_{i}^{2t}) \wedge (\overline{z}_{i}^{1} \vee z_{i}) \wedge (\overline{z}_{i} \vee w_{2^{s+1}-i}) \wedge \bigwedge_{j=1}^{2t-1} (\overline{z}_{i}^{j+1} \vee z_{i}^{j}), \text{ and}$$

$$\Gamma_{i} = (\overline{w}_{1} \vee \lambda_{i}^{1} \vee u_{i}) \wedge (\overline{u}_{i} \vee \lambda_{i}^{2} \vee \lambda_{i}^{3}).$$

This construction is clearly possible in logarithmic space. Note that ψ contains exactly

$$2^{s+1} - (m+1) + 2m(3+2t-1) + 2t = k + (2t+2)m$$

clauses. Each of these clauses can be interpreted as an implication as illustrated in Figure 9.1. We now prove the correctness of the reduction. Intuitively, all clauses of ψ are selected with the only exception that, for each $i \in [m]$, either X_i or Z_i is not included entirely.

Observe that setting all variables to 1 satisfies all clauses from $W \wedge V \wedge \bigwedge_{i=1}^{m} (X_i \wedge Z_i)$. It follows that any unsatisfiable formula includes a nonempty set of clauses from $\bigwedge_{j=1}^{t} \Gamma_i$. Moreover, since assigning 0 to both w_1 and all u_i satisfies all of $\bigwedge_{j=1}^{t} \Gamma_i$, and w_1 is the only variable shared with the remaining clauses $W \wedge V \wedge \bigwedge_{i=1}^{t} (X_i \wedge Z_i)$, an unsatisfiable subformula also includes a subset of clauses from $W \wedge \bigwedge_{i=1}^{m} (X_i \wedge Z_i)$ such that any assignment satisfying this subset is forced to assign 1 to w_1 . It follows that an unsatisfiable subformula includes all of W. This is because W contains clauses that represent a binary tree of implications of the form $w_{2i} \wedge w_{2i+1} \rightarrow w_i$ that needs to be included in full to force any assignment satisfying all selected clauses from $W \wedge V \wedge \bigwedge_{i=0}^{m} (X_i \wedge Z_i)$ to set w_1 at the root of the implication tree to 1. Furthermore, any unsatisfiable subformula contains some clauses that forces any assignment satisfying them to set all the leaves of the mentioned binary tree, namely $w_{2^s}, \ldots, w_{2^{s+1}}$, to be set to 1. Including the set V of singleton clauses does this for all but the last m leaves. For each remaining leaf $w_{2^{s+1}-1}$, either X_i and Z_i must be included.

We have seen so far that any unsatisfiable subformula of ψ must contain a clause from $\bigwedge_{j=1}^{t} \Gamma_i$, all of $W \wedge V$, and, for each pair of implication chains X_i and Z_i , one chain in its entirety. Including up to 2t clauses of the other chain of a pair cannot affect the satisfiability because only the last two of the 2t + 2 clauses contain variables occurring outside of the chain, namely x_i and $w_{2^{s+1}-i}$, and including such a clause and activating it via uninterrupted implication chain from the only unconditional clause at the head of the chain, either (x_i^r) or (z_i^r) , requires at least 2t + 1 clauses.

In addition to the $2^{s+1} - (m+1) + (2t+2)m$ clauses from $W \wedge V$ and, for each $i \in [m]$, either X_i or Z_i , we may include exactly 2t more clauses until the threshold of k is reached, which exactly suffices to include all of $\bigwedge_{j=1}^t \Gamma_t$ but not any pertinent part of an additional implication chain, which would require at least 2t + 1 clauses. Therefore, ψ has an unsatisfiable subformula of size at most k if and only if its subformula containing all clauses except, for each $i \in [m]$, either X_i or Z_i , is unsatisfiable. Any assignment that satisfies all clauses from X_i or Z_i must assign 1 to x_i or z_i , respectively, while the other variable can be set to 0 to satisfy as many clauses as possible from $\bigwedge_{i=1}^t \Gamma_i$. This corresponds to a consistent assignment of either 0 or 1 to each variable from x_1, \ldots, x_m , whereas assignments to y_1, \ldots, y_n are not restricted in any way.



Figure 9.1: Illustration of the implications encoded by the different sets of clauses used in the reduction of the proof of Theorem 9.9. Note that the clauses correspond to the arrows in the illustration, not the depicted variables. For example, the clause $(\overline{w}_2 \vee \overline{w}_3 \vee w_1)$ is equivalent to the implication $(w_2 \wedge w_3) \rightarrow w_1$ represented by the bottom-most arrow of W in the illustration, the left-most arrow right below it represent implication $w_1 \rightarrow (\lambda_1^1 \vee u_1)$ equivalent to the clause $(\overline{w}_1 \vee \lambda_1^1 \vee u_1)$, and the clause (z_1^{2t}) corresponds to arrow at the top right starting from nowhere, which is interpreted as an implication with a true antecedent, equivalent to the clause (z_1^{2t}) .

Any assignment satisfying all included clauses except possibly those of $\bigwedge_{i=1}^{t} \Gamma_i$ assigns 1 to w_1 . Such an assignment satisfies the first clause of Γ_i if its sets λ_i^1 or u_i to 1. If u_i is set to 1, then satisfying the second clause of Γ_i requires λ_i^2 or λ_i^3 to be set to 1. For any assignment setting w_1 to 1, two clauses of Γ_i are thus equivalent to C_i for each $i \in [m]$ and $\bigwedge_{i=1}^{t} \Gamma_i$ is equivalent to $\bigwedge_{i=1}^{t} C_i = \varphi(x_1, \ldots, x_m, y_1, \ldots, y_n)$.

This shows that φ is in Q3CNF₂ if and only if ψ has an unsatisfiable subformula of size at most *k*.

Note that we do not know the exact minimum size of an unsatisfiable subformula since not all

clauses from $\bigwedge_{j=1}^{t} \Gamma_j$ might be needed. But the threshold k is sufficiently large for all of them to be included in any case.

9.2 $\Sigma_2^{\rm P}$ -Hardness for TRIANGLE-HITPACK and CYCLE-HITPACK

We use the Σ_2^{P} -hardness of SUS from Theorem 9.9 to prove the Σ_2^{P} -hardness of TRIANGLE-HITPACK. The completeness for Σ_2^{P} then directly follows from Lemma 9.1.

Theorem 9.10. The problem TRIANGLE-HITPACK is Σ_2^{P} -hard on tripartite graphs.

Proof. We reduce from SUS by mapping any given pair (φ, k) , where $\varphi = C_1 \land \cdots \land C_m$ is a formula with *m* clauses on the variable set $\{x_1, \ldots, x_n\}$, to an instance (G, U, k, ℓ) of TRIANGLE-HITPACK as described below. The entire construction is shown in Figure 9.2 for a simple example.

Construction. The graph *G* contains, for every variable x_i , a *triangle cycle* of 2m triangles, each conjoined to the next at one vertex. Formally, we have four sets of *m* vertices each,

 $V_i = \{v_i^1, \dots, v_i^m\}, \quad \overline{V}_i = \{\overline{v}_i^1, \dots, \overline{v}_i^m\}, \quad W_i = \{w_i^1, \dots, w_i^m\}, \quad \text{and} \quad \overline{W}_i = \{\overline{w}_i^1, \dots, \overline{w}_i^m\},$

and the edges of the triangles $\{w_i^j, v_i^j, \overline{w}_i^j\}$ and $\{\overline{w}_i^j, \overline{v}_i^j, w_i^{j+1}\}$ for every $j \in [m]$, identifying w_i^{m+1} with w_i^1 for convenience.

For every clause C_j , we add a *clause triangle* $\{a_j, b_j, c_j\}$. Moreover, for every literal in this clause, we add two *literal edges* from a_j and b_j to a *literal vertex*, namely v_i^j if the literal is x_i and \overline{v}_i^j if the literal is \overline{x}_i for some $i \in [n]$. We call the vertices of this clause gadget the *clause vertices*.

Finally, we choose $\ell = mn + m$ as the number of triangles that should not be possible to pack and $U = V(G) \setminus \{c_1, \ldots, c_m\}$ as the set of undeletable vertices. The number of vertices we are allowed to delete is *k*. This finishes the construction of the instance (G, U, k, ℓ) .

Correctness. We now prove the correctness of the reduction. A maximum triangle packing of the graph *G* consists, without loss of generality, of the *m* clause triangles and every second triangle of each triangle cycle; these are $m + n \cdot m$ triangles in total. These triangles cover all vertices except, for each *i*, either V_i or \overline{V}_i . We interpret V_i being uncovered as assigning 1 to x_i and \overline{V}_i being uncovered as assigning 0 to x_i .

Deleting c_j means that we cannot keep the *j*th clause triangle in a maximum packing. But we can keep the edge $\{a_j, b_j\}$ and replace c_j by any of its literal vertices unless they are already covered. Since either V_i or \overline{V}_i is always covered, it follows that we can still pack mn + m triangles into the graph from which a set *D* of vertices has been deleted if and only if the *corresponding subformula* consisting of the clauses $\{C_j \mid c_j \in D\}$ is satisfiable; otherwise, it is impossible to pack this many triangles. It follows immediately that from *G* we can obtain a graph without a triangle packing of size k = mn + m by deleting *k* deletable vertices if and only if φ has an unsatisfiable subformula of size at most *k*.

As a next step we extend the previous result to CYCLE-HITPACK. For this we make use of the problem TRIANGLE-HITPART which is defined as follows.

Definition 9.11 (TRIANGLE-HITPART). The problem TRIANGLE-HITPART asks, given a graph G, a vertex set $U \subseteq V(G)$, and an integer k, whether it is possible to delete exactly k vertices from the graph G such that the vertices of the remaining graph cannot be partitioned into triangles.

Note that we require the deletion of *exactly* k vertices for this partition version of the problem since allowing for the deletion of less than k vertices would render the problem trivial for any positive k: If the number of vertices in the graph is divisible by 3, deleting one vertex; otherwise, leave it as it is, gives a graph with no triangle-partition. We could also require the deletion of exactly k vertices for the packing version of the problem. All of our results still hold because deleting more vertices can never increase the packing number of the remaining graph.

We will prove the following two theorems at once.



Figure 9.2: Construction of $G(\varphi)$ for the simple instance (φ, k) with k = 1 and $\varphi = (x_1 \lor x_2 \lor \overline{x_3}) \land (\overline{x_1} \lor x_2 \lor x_3)$. Note that within the variable gadgets, w_1^3 , w_2^3 , and w_3^3 are identified with $w_1^1 w_2^1$, and w_3^1 , respectively, creating one *triangle cycle* for each variable. Each clause has its own gadget consisting of a triangle and additional *literal edges* connecting it to the variable gadgets.

The dashed vertex c_2 is deleted, which corresponds to activating the second clause of the formula. The bold lines show a maximum triangle packing of the remaining graph. The remaining packed triangle correspond to the satisfying assignment $x_1 \mapsto 0, x_2 \mapsto 1, x_3 \mapsto 1$. The maximum packing has a total size of mn + m = 8, showing that this is a no-instance, which is trivial in this case since all subformulas of φ are satisfiable.

Theorem 1.1. *CYCLE-HITPACK is* Σ_2^{P} *-complete.*

Theorem 9.12. The problem TRIANGLE-HITPART is Σ_2^{P} -hard on tripartite graphs.

Proof of Theorems 1.1 and 9.12. We extend the construction used in the proof of Theorem 9.10 as follows. We have already observed that for a no-instance all subgraphs of *G* resulting from deleting up to *k* deletable vertices have a triangle packing of size mn + m where all uncovered vertices are from $V \cup \overline{V}$. For *k* deleted vertices, exactly mn - k among these vertices remain uncovered. We extend *G* to a new graph *G'* by adding, for each $r \in [mn - k]$, a vertex pair $\{y_r, z_r\}$ and, for each vertex $v \in V \cup \overline{V}$, the edges of the triangle $\{v, y_r, z_r\}$.

Each new vertex pair $\{y_r, z_r\}$ can be used for packing exactly one triangle that covers exactly one arbitrary vertex from $V \cup \overline{V}$. This enables us to turn any of the previously considered packings of size mn + m of G after the deletion of k vertices into a triangle partition of size mn + m + (mn - k) = 2mn + m - k of G' after the deletion of the same vertices. Conversely, for any triangle partition of G', which necessarily has size 2mn + m - k, we obtain a packing of size exactly mn + m for G by removing the mn - k triangles containing any of the new vertex pairs.

This provides a direct reduction from SUS both to TRIANGLE-HITPART and, because a triangle partition is the most efficient way of packing as many cycles as possible into a graph, to CYCLE-HITPACK. □

9.3 $\Sigma_2^{\rm P}$ -Hardness for *H*-HITPACK

Now, we focus on the proof of the following statement.

Theorem 1.5. For any fixed connected graph H with at least three vertices, H-HITPACK is Σ_2^{P} -complete.

The containment in Σ_2^P follows from Lemma 9.1. The hardness result follows immediately from the hardness result for TRIANGLE-HITPACK, Theorem 9.10, together with a polynomial-time reduction from TRIANGLE-HITPACK to *H*-HITPACK, formally stated in Lemma 9.13. We actually prove a stronger

result and additionally show that this reduction is *pathwidth-preserving*, by which we mean that for an input graph G of TRIANGLE-HITPACK, the H-HITPACK oracle is called by the algorithm only on input graphs whose pathwidth exceeds the pathwidth of G by at most some additive constant. While we do not need this stronger version in the current section, we use it in Section 10.

Lemma 9.13. Let *H* be a fixed connected graph with at least three vertices. There is a polynomial-time pathwidth-preserving reduction from TRIANGLE-HITPACK to H-HITPACK.

Towards proving Lemma 9.13, let us first give some intuition and introduce some definitions.

Intuition. The naive idea is to introduce, for each triangle *T* of the given instance, a copy of the graph *H*, say H_T , and to identify three (arbitrary) vertices of H_T with the vertices of the triangle *T*. However, in this construction there is no guarantee that, in an *H*-packing of this modified instance, H_T is covered only by one copy of *H*. Instead, it could be the case that one part of H_T is covered by one copy of *H*, while another part of H_T is covered by a different copy. To avoid this situation, rather than identifying the vertices of the triangle *T* with corresponding vertices in H_T directly, we introduce long chains (of gadgets) between these vertices. We create, for each vertex *v* of a triangle *T*, a chain $C_{T,v}$ consisting of modified copies of *H* (which we later formally introduce as diamond gadgets) that allow us to propagate the information whether *T* was covered. Again, as this propagation is not enforced, there might be packings that do not properly propagate this information. However, the construction of these diamond gadgets and the length of the chain ensure that these undesired packings have size far from the maximum. To make the construction with the chains work, we require that *H* is connected, and in order to have distinct vertices in H_T corresponding to the vertices of the triangle *T*, we need the requirement that *H* have size at least 3.

Diamond Gadgets. Inspired by Kirkpatrick and Hell [43], we define the *diamond gadget* as follows. Let *H* be a connected graph with at least two vertices. Let *u* and *u'* be vertices with maximum distance in *H*. Since *H* is connected, this distance is finite, and since *H* has at least two vertices, *u* and *u'* are distinct. We introduce a new vertex \overline{u} that is a copy of *u* in the sense that it is incident precisely to the neighbors of *u*. The graph *H* together with this new vertex \overline{u} and the corresponding new edges forms the *diamond gadget* (of *H*), which we abbreviate by the symbol \diamond . We say that *u* and \overline{u} are the *connecting vertices* of \diamond .

We point out two choices of packing H into \diamond (there might be more): (1) the packing that covers the original copy of H (with the corresponding vertices), in particular, it covers u. We say that this is the *forward packing* for \diamond , or (2) the packing that is identical to the forward packing, except that it covers \overline{u} instead of u, we say this is the *backward packing* for \diamond .

Proof of Lemma 9.13. Let *H* be an arbitrary connected graph with at least three vertices. Given an instance $I_{\Delta} = (G, U, k, \ell)$ of TRIANGLE-HITPACK, we define an instance I_H of *H*-HITPACK as follows. We set $n_H := |V(H)|$, and we denote by \mathcal{T} the set of all triangles in *G*.

For each triangle $T \in \mathcal{T}$ and each vertex v of T we introduce a gadget $C_{T,v}$ (cf. Figure 9.3) as follows:

- For all $i \in [10n_H]$, we create a copy of the gadget \diamond , denoted by $\diamond_{T.v}^{(i)}$
- For all $i \in [10n_H 1]$, we identify vertex \overline{u} of $\diamond_{T,v}^{(i)}$ with vertex u of $\diamond_{T,v}^{(i+1)}$.
- The gadget $C_{T,v}$ consists of the union of the diamond gadgets $\diamond_{T,v}^{(1)}, \ldots, \diamond_{T,v}^{(10n_H)}$.
- If, for all $i \in [10n_H]$, we choose the forward packing for $\diamond_{T,v}^{(i)}$, then we say this is the *forward* packing for $C_{T,v}$.
- If, for all *i* ∈ [10n_H], we choose the backward packing for \$\$⁽ⁱ⁾_{T,v}\$, then we say this is the *backward* packing for C_{T,v}.



Figure 9.3: An illustration of H_T for T = xyz. The three rows of diamond gadgets correspond to the chains $C_{T,x}$, $C_{T,y}$, and $C_{T,z}$, respectively. The dashed edges of the triangle are deleted in the construction.

For each triangle $T \in \mathcal{T}$ and for every vertex $v \in T$, we identify v with the connecting vertex u of $\diamond_{T,v}^{(1)}$. For every triangle T = xyz in G, we introduce a copy of H, denoted by H_T . We identify the connecting vertices \overline{u} of $\diamond_{T,x}^{(10n_H)}, \diamond_{T,y}^{(10n_H)}, \diamond_{T,z}^{(10n_H)}$ with three (arbitrary) distinct vertices v_p, v_q, v_r of H_T , respectively. In order to avoid the situation that the edges in the triangles of G are used for packing H, we delete all edges which are originally in G. The construction for some triangle T is illustrated in Figure 9.3.

Let G' be the resulting graph. We define $U' := U \cup V(G') \setminus V(G)$ as the set of undeletable vertices of G', that is, the deletable vertices are precisely the deletable vertices from G. We set k' := k and $\ell' := 30n_H \cdot |\mathcal{T}| + \ell$. Let $I_H = (G', U', k', \ell')$ be the instance of H-HITPACK. This finishes the construction. Now we prove the correctness of this reduction.

Claim 9.14. If I_{Δ} is a Yes-instance of TRIANGLE-HITPACK, then I_H is a Yes-instance of H-HITPACK.

Proof of Claim. Let *S* be some solution of $I_{\Delta} = (G, U, k, \ell)$. Since the deletable vertices of *G* are also deletable in *G*' and by definition of I_H , we get $S \subseteq V(G') \setminus U'$ and $|S| \leq k = k'$. In the remainder we prove that all *H*-packings of $G' \setminus S$ have size less than ℓ' .

Assume, for the sake of contradiction that there is an *H*-packing \mathcal{P}' for G' - S containing at least ℓ' copies of *H*. In the next steps we show that we can assume that \mathcal{P}' is either the forward packing or the backward packing on all gadgets $C_{T,v}$. A priori, this is not clear as, while we delete the edges of the original graph *G*, each original vertex can be contained in multiple triangles of *G*, and therefore might now be connected to multiple gadgets $C_{T,v}$, $C_{T',v}$, and so on. So, a copy of *H* in some packing could cover some part of $C_{T,v}$ and some part of $C_{T',v}$ (other than just *v*). We argue that without loss of

generality, we can assume that this is not the case.

- 2. Now suppose that in P' there is a copy of H that covers both connecting vertices of some diamond gadget. Then no other copy of H covers vertices of this diamond gadget. Then we can replace this copy of H by the forward or backward packing for this diamond gadget without changing the size (or feasibility) of P'. Thus, we can assume that in the H-packing P' there is no copy of H covering both connecting vertices of some diamond gadget.
- 3. Consider some diamond gadget $\diamond_{T,v}^{(i)}$ and the corresponding distinguished vertices u, \overline{u} , and u'. Suppose some copy of H in \mathcal{P}' covers some vertex w outside of $\diamond_{T,v}^{(i)}$. We argue that this copy of H cannot cover u': First, as H is connected, the vertices u' and w have to be connected in G. Consider a shortest path between u' and w in G. It has to go through one of the connecting vertices u or \overline{u} , say through u. This implies that the distance between u' and w is strictly larger than the distance between u' and u. Since the distance between u' and u equals the diameter of H, the graph H cannot cover both w and u'. So we have shown that a copy of H that covers u'covers no vertex outside of the corresponding gadget $\diamond_{T,v}^{(i)}$. By the previous deductions, we know that such a copy covers precisely one of u or \overline{u} , and actually due to the fact that $\diamond_{T,v}^{(i)}$ has precisely |V(H)| + 1 vertices, such a copy of H then covers all vertices of $\diamond_{T,v}^{(i)}$ apart from one of \overline{u} or u. So, summarizing, if u' is covered, then we can assume that $\diamond_{T,v}^{(i)}$ is covered according to the forward packing or backward packing, respectively.
- 4. Suppose that for some *T* and *v*, there is (at least) one gadget ◇⁽ⁱ⁾_{T,v} for which the corresponding vertex *u'* is covered by *P*. Let *i*_{min} ∈ [10*n_H*] be the smallest such index. From the previous point, we can assume that the copy of *H* that covers *u'* covers ◇^(*i*min)_{T,v} according to either the forward or the backward packing. Suppose it is the backward packing the other case is analogous. Then *ū* of ◇^(*i*min+1)_{T,v} is already covered by the backward packing of ◇^(*i*min+1)_{T,v} and consequently there is at most one other copy of *H* in the packing *P* that covers vertices of ◇^(*i*min+1)_{T,v}. This copy then has to cover the vertex corresponding to *u* (in ◇^(*i*min+1)_{T,v}). Therefore, we can replace this copy of *H* by the backward packing of ◇^(*i*min+1)_{T,v} without violating the feasibility of the packing. Using the argument iteratively, we can assume that for all *i* ≥ *i*min the corresponding gadget is covered according to the backward packing. Now let us look at ◇^(*i*min-1)_{T,v}. By assumption, the corresponding vertex *u'* is not covered. Let us consider a copy of *H* it follows that it has to cover some vertices outside of $\langle^{($ *i* $min-1)}_{T,v}$. Thus, it cannot cover *ū* since then it would have to cover other vertices in $\diamond^{($ *i* $min-1)}_{T,v}$. However, all of these vertices are already covered. It follows that such a copy of *H* would have to cover *u*, and importantly this means that there is only one such copy in *P* that covers vertices of $\diamond^{($ *i* $min-1)}_{T,v}$. We know that feasibility of the packing. Again, we can use the argument iteratively for all *i* < *i*min. So we can assume the backward packing on *C*_{T,v}. Similarly we could assume the forward packing on *C*_{T,v} if $\diamond^{($ *i* $min-1)}_{T,v}$.
- 5. Finally, suppose there are *T* and *v* such that, for all $i \in [10n_H]$, the vertex u' from $\diamond_{T,v}^{(i)}$ is not covered by the packing \mathcal{P}' . In this case the packing covers at most $10(n_H 1) \cdot n_H$ vertices of $C_{T,v}$.

Note also, that since *H* is connected, each copy of *H* in the packing that covers vertices within $C_{T,v}$ as well as outside, has to cover one of the three vertices of the triangle *T*. Consequently, there can be at most 3 such copies of *H* in the packing. Using this fact, together with the fact that at most $10(n_H - 1) \cdot n_H$ vertices of $C_{T,v}$ are covered, we conclude that at most $10(n_H - 1) + 3$ copies of *H* cover vertices of $C_{T,v}$. Hence we can replace these copies of *H* with the backward packing for $C_{T,v}$ and obtain an overall packing that is strictly larger as we now pack $10n_H$ copies of *H* to cover $C_{T,v}$.

So we have shown that in \mathcal{P}' , every copy of H either corresponds to a backward or forward packing for a diamond gadget or covers precisely the vertices of some H_T (if it were to cover some vertices of H_T and some vertices outside of H_T then these outside vertices are part of some diamond gadget and this would contradict the fact that this diamond gadget is covered either by the forward or backward packing).

Recall that we assumed for contradiction that $|\mathcal{P}'| \geq \ell' = 30n_H \cdot |\mathcal{T}| + \ell$. By the construction of the graph, the packing \mathcal{P}'' contains already $30n_H \cdot |\mathcal{T}|$ copies of H from the chains $C_{T,v}$. Then it contains at least an additional ℓ copies of H that cover H_T for some triangle T = xyz. However, then the corresponding gadgets $C_{T,x}$, $C_{T,x}$, and $C_{T,x}$ have to be covered according to the *forward* packing as otherwise the vertices at the intersection of H_T and these chains would be covered twice. It follows that the vertices of the triangle T are covered. So this would imply that there is a triangle-packing of size at least ℓ in $G \setminus S$, contradicting that S is a solution for I.

We conclude that $I_H = (G', U', k', \ell')$ is a Yes-instance of *H*-HITPACK which finishes the proof of the claim.

Now we prove the reverse direction.

Claim 9.15. If $I_H = (G', U', k', \ell')$ is a Yes-instance of H-HITPACK, then $I_{\Delta} = (G, U, k, \ell)$ is a Yes-instance of TRIANGLE-HITPACK.

Proof of Claim. Let S' be some solution for I_H . Since I_H and I_{\triangle} have the same set of deletable vertices, we have $S' \subseteq V(G) \setminus U$. Moreover, since k' = k, it also holds that $|S'| \leq k$. To show that S' is a solution for I_{\triangle} , it remains to prove that G - S' has no \triangle -packing of size at least ℓ .

Suppose for contradiction's sake that there is a \triangle -packing \mathcal{P} of size at least ℓ in G - S. We define a corresponding H-packing \mathcal{P}' in $G' \setminus S'$ as follows.

- For every triangle $T \in \mathcal{P}$ and every vertex $v \in T$, we add to \mathcal{P}' the forward packing for $C_{T,v}$ (containing $10n_H$ copies of H), and a copy of H that covers precisely H_T . Note that this is feasible as the forward packing does not cover any vertices from H_T . This gives a total of $30n_H + 1$ copies of H in the packing \mathcal{P}' per triangle in \mathcal{P} .
- For every triangle $T \in \mathcal{T} \setminus \mathcal{P}$ and every vertex $v \in T$, we add the backward packing for $C_{T,v}$ to \mathcal{P}' . This gives a total of $30n_H$ copies of H per triangle outside of \mathcal{P} .

It is straightforward to see that the resulting packing \mathcal{P}' is indeed feasible, and it has size at least $30n_H |\mathcal{T}| + \ell = \ell'$. This finishes the proof of the claim.

It remains to show that the pathwidth of G' exceeds that of G by at most some additive constant.

Claim 9.16. If G has pathwidth pw, then G' has pathwidth pw + O(1).

Proof of Claim. Suppose there is a path decomposition for *G* of width pw. For every triangle T = xyz of *G*, there is at least one bag that contains all vertices of *T*. We replace it with a bag X_T that contains all vertices of $C_{T,x}$, $C_{T,y}$, $C_{T,z}$, and of H_T . This gives a valid path decomposition of *G'*. Since the number of vertices in $C_{T,x}$, $C_{T,y}$, $C_{T,z}$, and H_T depends only on *H* (which is fixed), the pathwidth of *G'* is pw + O(1).

This finishes the proof of Lemma 9.13.

10 Double-Exponential Lower Bounds Parameterized by Pathwidth

In this section, we prove Theorems 1.3 and 1.9, which state double exponential lower bounds for *H*-HITPACK and CYCLE-HITPACK in terms of the pathwidth of the input graph. Note that this directly implies corresponding lower bounds in terms of treewidth. Let us first consider Theorem 1.9 and restate it for convenience. We consider Theorem 1.3 later in Section 10.3.

Theorem 1.9. Assuming ETH, for any fixed connected graph H with at least three vertices, H-HITPACK has no $2^{2^{o(pw)}} \cdot n^{O(1)}$ time algorithm, where pw is the pathwidth of the input graph.

Often such lower bounds are stated in their strengthened version, in which it is assumed that a path decomposition of width pw is given as part of the input. However, this is no strengthening in our case since the runtime lower bound is double exponential in pw and it is well-known that a path decomposition of *G* can be computed in time exponential in pw² and linear in *n* [45].

Again, we first give a hardness result for TRIANGLE-HITPACK.

Lemma 10.1. Let φ be a 3-SAT instance with n variables and m clauses. In time $O(n + m \log m)$, we can construct an instance $I = (G, U, k, \ell)$ of TRIANGLE-HITPACK such that

- φ is satisfiable if and only if I has a solution,
- G has pathwidth at most $O(\log m)$, and
- G is of size $O(m \log m)$.

The proof of Lemma 10.1 is given in Section 10.1. As a second step, we then apply the pathwidthpreserving reduction from TRIANGLE-HITPACK to H-HITPACK (for any fixed, connected graph H), as stated in Lemma 9.13. Here are the details.

Proof of Theorem 1.9. Assume that *H*-HITPACK could be solved in time $2^{2^{o(pw)}} n^{O(1)}$. Let φ be an instance of 3-SAT with *n* variables and *m* clauses. We use Lemma 10.1, to obtain an instance I_{φ} of TRIANGLE-HITPACK with pathwidth $O(\log(m))$ that has a solution if and only if φ has a solution. Now we can execute our hypothetical algorithm for *H*-HITPACK instead of each oracle call of the reduction from Lemma 9.13 on input I_{φ} . Note that this procedure solves a given instance φ of 3-SAT. Moreover, in total the procedure takes time

$$2^{2^{o(pw(I_{\Delta})+O(1))}} \cdot |I_{\Delta}|^{O(1)} \le 2^{2^{o(\log m)}} \cdot (n+m)^{O(1)} \le 2^{o(n+m)}.$$

This gives a contradiction, as the ETH ([36] combined with the Sparsification Lemma [37]) implies that 3-SAT cannot be solved in $2^{o(n+m)}$ time [17, Theorem 14.4].

10.1 Lower Bound for TRIANGLE-HITPACK

Before proving Lemma 10.1, i.e., the lower bound for TRIANGLE-HITPACK, we first provide some intuition for the construction. Let φ be the 3-SAT formula. The graph of the instance *I* of TRIANGLE-HITPACK contains a vertex set *Z* (of size $O(\log m)$) that separates the graph into two halves, referred to as the left and right half. We use the vertices in *Z* to represent (the *identifier* of) some clause. The right half encodes the assignment to the variables of φ by deleting certain vertices, while the left half is used to select a clause for which we want to check if it is satisfied by the assignment. Then each clause will correspond to some maximal triangle packing in the constructed graph.

In order to ensure that each clause is satisfied, we want to *rule out* the possibility that all literals of some clause are *unsatisfied*. This is done in the following way: If the set of vertex deletions in the right half of the graph specifies an assignment of variables that leaves all literals of some clause unsatisfied, then the maximal triangle packing (after the deletions) that corresponds to that particular clause will have size at least ℓ . This way a variable assignment is not a solution if and only if the corresponding deletion set is also not a solution (as it allows too large of a packing).

To ensure that three unsatisfied literals of some clause yield a large triangle packing, we construct gadgets on the right half that contribute a large number of triangles to the packing whenever the literal is not satisfied by the clause. Conversely, if the clause is satisfied by the literal, the gadget contributes only a small number of triangles to the packing. In terms of quantifiers and negations, we will check that *for all* clauses it holds that it is *not* the case that they contain three *unsatisfied* literals (or equivalently that each clause has at least one satisfied literal).

Proof of Lemma 10.1. Let φ' be the given 3-SAT formula with n' variables $x_1, \ldots, x_{n'}$ and m' clauses.

Preprocessing the Formula. We assume in the following that no clause of φ' contains the same literal multiple times. Moreover, there is no clause that contains only one literal. Otherwise we could greedily set the value of this literal and simplify the formula accordingly. Additionally, we replace clauses containing exactly two literals. For two literals λ_1 and λ_2 , let $C = (\lambda_1 \lor \lambda_2)$ be such a clause of φ' and let y be a fresh variable. We replace this clause C by the two clauses

$$(\lambda_1 \lor \lambda_2 \lor y) \land (\lambda_1 \lor \lambda_2 \lor \overline{y}).$$

After doing this replacement for all clauses with only two literals, let φ'' be the resulting 3-SAT formula with $n'' \leq n' + m'$ variables $x_1, \ldots, x_{n''}$ and $m'' \leq 2m'$ clauses. It is easy to verify that φ' is satisfiable if and only if φ'' is satisfiable.

For a technical reason, which becomes clear later, we modify the formula φ'' further. For each $i \in [n'']$, we add the following four new clauses to the formula

$$(x_i \lor \overline{x}_i \lor x_{i+1}) \land (x_i \lor \overline{x}_i \lor \overline{x}_{i+1}) \land (x_i \lor \overline{x}_i \lor x_{i+2}) \land (x_i \lor \overline{x}_i \lor \overline{x}_{i+2}),$$

where we set $x_{n''+1} = x_1$ and $x_{n''+2} = x_2$ to keep notation simple.

Let φ be the resulting formula. Again, it can be easily verified that φ is satisfiable if and only if φ'' is satisfiable. By duplicating clauses, we can also achieve that φ contains exactly 2^c clauses for some appropriate $c \ge 4$. Hence, in the following we set $m = 2^c \in O(m')$ as the number of clauses of φ and $n = n'' \in O(n' + m')$ as the number of variables.

Gadgets. For the construction of the gadgets we use an idea which we refer to as a cycle of triangles. To formalize this idea, we define the following gadget which we later use to define the other gadgets.

Claim 10.2 (Auxiliary Gadget). For all integers $r \ge 2$, there is a graph TriCyc_r with 2r distinguished vertices v_1, \ldots, v_r and $\overline{v}_1, \ldots, \overline{v}_r$ such that:

- 1. This graph has exactly two maximum triangle packings P and \overline{P} of size r.
- 2. Packing P covers v_1, \ldots, v_r and none of the vertices $\overline{v}_1, \ldots, \overline{v}_r$.
- 3. Packing \overline{P} covers $\overline{v}_1, \ldots, \overline{v}_r$ and none of the vertices v_1, \ldots, v_r .

Proof. Intuitively, the gadget TriCyc_r consists of 2r triangles arranged in a cycle such that two triangles share one endpoint.

Formally, the graph TriCyc_r consists of a cycle with 2r vertices u_0, \ldots, u_{2r-1} where, for all $i \in [2r-1]$, u_{i-1} is adjacent to u_i, u_{2r-1} is connected to u_0 , and no other edges exist between these vertices. Moreover, there are vertices v_1, \ldots, v_r and $\overline{v}_1, \ldots, \overline{v}_r$ such that, for all $i \in [r]$, v_i is connected to u_{2i-2} and u_{2i-1} , and \overline{v}_i is connected to u_{2i-1} and $u_{2i \mod 2r}$.

We define the two packings *P* and \overline{P} as follows:

 $P := \{ (u_{2i-1}, v_i, u_{2i \mod 2r}) \mid i \in [r] \} \text{ and } \overline{P} := \{ (u_{2i-2}, \overline{v}_i, u_{2i-1}) \mid i \in [r] \}$

It is easy to check that these two sets actually define a packing of r triangles with the properties (2) and (3). It remains to show that there is no other packing of r (or more) triangles. But this follows



Figure 10.1: Left figure presents a Sel₄ gadget. The highlighted triangles depict the triangle packing P_{true} . Right figure presents Lit₄ along with the unique maximum triangle packing P_{false} .

directly from the fact that the gadget TriCyc_r contains only triangles with vertex set $\{v_i, u_{2i-2}, u_{2i-1}\}$ or $\{\overline{v}_i, u_{2i-1}, u_{2i \mod 2r}\}$ for some $i \in [r]$, since we assumed that $r \ge 2$. Hence, whenever r (or more) triangles are contained in a packing that is different from \overline{P} and P, then all of these triangles cannot be pairwise vertex disjoint as the neighboring triangles intersect.

Based on this gadget TriCyc, we define the following gadget, which we use to "generate" the clause number (see Figure 10.1). Although this gadget is just a special case of the gadget TriCyc, we provide it with a separate name to keep notation simple in the later proof.

Claim 10.3 (Selector Gadget). For all integers $r \ge 2$, there is a graph Sel_r with 2r distinguished vertices v_1, \ldots, v_r and $\overline{v}_1, \ldots, \overline{v}_r \in V$ such that

- 1. there are exactly two packings of 3r triangles denoted by P_0 and P_1 ,
- 2. P_0 covers v_1, \ldots, v_r and none of the vertices $\overline{v}_1, \ldots, \overline{v}_r$,
- 3. P_1 covers $\overline{v}_1, \ldots, \overline{v}_r$ and none of the vertices v_1, \ldots, v_r ,
- 4. there is no packing of more than 3r triangles, and

Proof of Claim. We use the graph TriCyc_{3r} as the graph Sel_r but only pick a third of the distinguished vertices of TriCyc_{3r} as the distinguished vertices of Sel_r (see Claim 10.2). Let v'_1, \ldots, v'_{3r} and $\overline{v}'_1, \ldots, \overline{v}'_{3r}$ be the distinguished vertices of UniVar_{3r} . For all $i \in [r]$, we choose $v_i \coloneqq v'_{3i}$ and $\overline{v}_i \coloneqq \overline{v}'_{3i-2}$ as the distinguished vertices of Sel_r . The properties of the gadget follow immediately from Claim 10.3.

With the construction of Sel_r at hand, we have everything ready to define the gadgets for encoding the literals. For this gadget the size of the two largest solutions differs (see Figure 10.1).

Claim 10.4 (Literal Gadget). For all integers $r \ge 4$, there is a graph Lit_r with r distinguished vertices $v_1, \ldots, v_r \in V$ such that

- 1. there is a packing P_{true} of 3r 1 triangles that covers none of v_1, \ldots, v_r ,
- 2. there is exactly one packing P_{false} of 3r triangles that covers v_1, \ldots, v_r , and



Figure 10.2: An overview of the lower-bound construction. On the left, we have the *selector gadget* that can cover either blue vertices (on the right) or red vertices (on the left) in the green group. The middle layer consists of $O(\log(m))$ groups of 6 vertices. Each group corresponds to the bit of the clause index. The right part represents the *literal gadget*, ensuring satisfaction of the corresponding literal in the clause. Importantly, the middle layer consists of only $O(\log(m))$ vertices. Both the literal and selector gadgets have a constant treewidth, resulting in a created instance with a treewidth of $O(\log(m))$.

3. there is no triangle packing with more than 3r triangles.

Proof of Claim. We define Lit_{*r*} based on the gadget Sel_{*r*} as follows. The vertex and edge set of Lit_{*r*} is the same as that of Sel_{*r*} with the only modification that we identify the vertices \overline{v}_1 and \overline{v}_3 with each other. We use the vertices v_1, \ldots, v_r as the distinguished vertices of Lit_{*r*}.

First observe that identifying \overline{v}_1 with \overline{v}_3 does not create any new triangles. This directly implies the third property of the gadget. By this choice it directly follows that there is exactly one packing of 3r triangles which is precisely the packing P_1 for Sel_{*r*}. Moreover, the only other packing of 3r triangles for Sel_{*r*}, i.e., P_0 , contains \overline{v}_1 and \overline{v}_3 . As we identified these two vertices, this reduces the number of triangles by one. (There are now two choices for the packing P_{true} .) Hence, the first and second property of the gadget follow.

Construction of the Instance. We present the overview of the construction in Figure 10.2. Before defining the graph *G*, we introduce some more notation. For an integer $0 < N \le 2^c$, we define bin(*N*) as the binary encoding of N - 1 with *c* bits. For all $j \in [c]$, we denote by bin(*N*)[*j*] the *j*th bit of the binary encoding of N - 1.

With this notation, we can now formally define the graph *G* of the instance *I*. For all $\gamma \in [c]$, $b \in \{0, 1\}$, and $p \in \{1, 2, 3\}$, we create a vertex $z_{p,b}^{(\gamma)}$ and define $Z \coloneqq \{z_{p,b}^{(\gamma)}\}_{\gamma,b,p}$ as the set of these 6*c* vertices.

The left side of the graph is defined as follows. For all $\gamma \in [c]$, we create a copy Sel^(γ) of the gadget Sel₃ and identify the copies of the vertices v_1, v_2, v_3 with the vertices $z_{1,0}^{(\gamma)}, z_{2,0}^{(\gamma)}, z_{3,0}^{(\gamma)}$ and identify the copies of the vertices $\overline{v}_1, \overline{v}_2, \overline{v}_3$ with the vertices $z_{1,1}^{(\gamma)}, z_{2,1}^{(\gamma)}, z_{3,1}^{(\gamma)}$. There are no other vertices in the left side of the instance.

For the right side we let $\Lambda = \{x_1, \overline{x}_1, \dots, x_n, \overline{x}_n\}$ be the set of all literals corresponding to the variables of φ . Note that from the preprocessing it follows that all of them appear in some clause. For each literal $\lambda \in \Lambda$, we define a set $C_{\lambda} \subseteq [m] \times \{1, 2, 3\}$ such that $(j, p) \in C_{\lambda}$ if and only if literal λ appears in the *j*th clause at position *p*.

For all $\lambda \in \Lambda$ and all $(j, p) \in C_{\lambda}$, we create a vertex d_{λ} and introduce a copy of the gadget Lit_{c+1} denoted by $\operatorname{Lit}_{\lambda,j,p}$. For each such gadget $\operatorname{Lit}_{\lambda,j,p}$ and all $\gamma \in [c]$, we identify the copy of the vertex v_{γ} from Lit_{c+1} with the vertex $z_{p,1-\operatorname{bin}(j)[\gamma]}^{(\gamma)}$. The copy of the vertex v_{c+1} from Lit_{c+1} is identified with d_{λ} . Intuitively, the vertex d_{λ} synchronizes the "behavior" of all gadget copies that belong to the same literal. This completes the definition of the graph *G*.

Let *V* be the set of vertices of *G*, then the set of undeletable vertices $U := V \setminus \{d_{\lambda} \mid \lambda \in \Lambda\}$, that is,

only the d_{λ} 's can be deleted. To conclude the construction, we set k := n as the bound on the number of vertices we are allowed to delete and set $\ell := 3m(3c+2)+9c+3$ as the strict upper bound on the number of triangles that we are allowed to pack after the vertex deletions. The resulting TRIANGLE-HITPACK instance is $I = (G, U, k, \ell)$.

Correctness. In the next two steps we show that the construction is correct. We do this by handling both directions individually.

Claim 10.5. If φ is satisfiable, then I has a solution.

Proof of Claim. Let π be an assignment for the variables x_1, \ldots, x_n such that φ is satisfied under π . Based on π , we define the solution *S* for *I* as

$$S := \{d_{x_i} \mid i \in [n] \text{ and } \pi(x_i) = \text{true}\} \cup \{d_{\overline{x}_i} \mid i \in [n] \text{ and } \pi(x_i) = \text{false}\}.$$

By the definition of *S*, we get that |S| = n = k. It remains to show that *S* is indeed a solution for *I*.

For the sake of a contradiction, assume that *S* is not a solution and let \mathcal{P} be a maximum size packing of triangles of size at least ℓ . Let us analyze this packing \mathcal{P} . Let *q* be the number of literal gadgets that contribute the maximum possible 3c + 3 triangles to \mathcal{P} . (These are those gadgets that contribute a packing according to P_{false} .) From Claim 10.4 it follows that this triangle packing P_{false} covers precisely *c* vertices from *Z* (one for each $\gamma \in [c]$). As *Z* has size 6c it follows that $q \leq 6$, as otherwise some vertex from *Z* would be covered twice.

We strengthen this bound and argue that $q \leq 3$. Assume otherwise and let (λ_i, j_i, p_i) for $i \in [4]$ be four gadgets $\operatorname{Lit}_{\lambda_i, j_i, p_i}$, each contributing 3c + 3 triangles. As $p_i \in [3]$, there must be distinct $i_1, i_2 \in [4]$ such that $p_{i_1} = p_{i_2}$. For ease of notation assume that $i_1 = 1, i_2 = 2$ and $p_1 = 1$. By Claim 10.4, the two gadgets cover c vertices in $\{z_{1,b}^{(\gamma)}\}_{\gamma,b}$. As each vertex can only be covered by one triangle, we get that all vertices in $\{z_{1,b}^{(\gamma)}\}_{\gamma,b}$ are covered. However, if that is the case, then from the properties of Claim 10.3, it follows that, for all $\gamma \in [c]$, the gadget $\operatorname{Sel}^{(\gamma)}$ can contribute at most 8 triangles to the packing. Now note that every literal gadget that does not contribute 3c + 3 triangles to the packing \mathcal{P} contributes at most 3c + 2 triangles, according to Claim 10.4.

Hence, the size of the packing \mathcal{P} is at most 3m(3c+2) + 8c + q. Therefore, \mathcal{P} can have size at least $\ell = 3m(3c+2) + 9c + 3$ if and only if $q \ge c+3$. Since we know that $q \le 6$, we get $c \le 3$ which contradicts the assumption that $c \ge 4$.

Combining the two above results, we have that $q \leq 3$. First suppose that $q \leq 2$. Then the size of \mathcal{P} is at most 3m(3c+2) + 9c + 2, which contradicts the fact that its size should be at least ℓ . Thus, it remains to consider the case q = 3. Let λ_i , j_i for $i \in [3]$ such that $\operatorname{Lit}_{\lambda_i, j_i, p_i}$ contributes the maximum possible 3c+3 triangles to \mathcal{P} for all $i \in [3]$, i.e., these literal gadgets contribute triangles according to the packing P_{false} . We claim that $j_1 = j_2 = j_3$. For the sake of a contradiction, assume otherwise and assume without loss of generality that $j_1 \neq j_2$. Thus, there is some $\gamma \in [c]$ such that $\operatorname{bin}(j_1)[\gamma] \neq \operatorname{bin}(j_2)[\gamma]$. This means that exactly one of $\operatorname{Lit}_{\lambda_1, j_1, p_1}$ or $\operatorname{Lit}_{\lambda_2, j_2, p_2}$ covers a vertex in $z_{1,0}^{(\gamma)}, z_{2,0}^{(\gamma)}, z_{3,0}^{(\gamma)}$, whereas the other covers a vertex in $z_{1,1}^{(\gamma)}, z_{2,1}^{(\gamma)}, z_{3,1}^{(\gamma)}$. Thus, by the properties from Claim 10.3, $\operatorname{Sel}^{(\gamma)}$ contributes at most 8 triangles to the packing. Hence, the size of the packing is bounded by $3m \cdot (3c+2) + (c-1)9 + 8 + 3$ which contradicts the assumption about the size of \mathcal{P} , i.e., $|\mathcal{P}| \geq \ell$. Hence, we actually get that $j_1 = j_2 = j_3$.

So, for $j = j_1 = j_2 = j_3$ and for all $i \in [3]$, the gadgets $\operatorname{Lit}_{\lambda_i, j, i}$ contribute 3c + 3 triangles to \mathcal{P} . Then Claim 10.4 implies that d_{λ_i} is not deleted (since it is part of the packing P_{false}), i.e., $d_{\lambda_i} \notin S$. Hence, by our definition of *S* it must hold that $\pi(\lambda_i) = \text{false}$ for all $i \in [3]$ which contradicts the assumption that π satisfies φ .

Now we prove the reverse direction.

Claim 10.6. If *I* has a solution, then φ is satisfiable.

Proof of Claim. Let $S \subseteq V \setminus U$ be a solution for *I*. The idea is to define a satisfying assignment π for φ based on *S*. To show that this is possible, we first introduce some notation. We define, for all $i \in [n]$, $S(i) := |\{d_{x_i}, d_{\overline{x_i}}\} \cap S|$ as the number of vertices selected for each variable. We first claim that, for all $i \in [n]$, the solution *S* satisfies S(i) < 2.

The Solution is Good. We say that a solution *S* is *good* if for each $i \in [n]$ we have S(i) = 1. To simplify notation, we write S(i + n) := S(i) and similarly for the indices of the variables. Now assume for contradiction that there is some $i \in [n]$ such that S(i) = 2. Since we defined k = n, this implies that there must be some $b \in [n]$ such that S(b) = 0. Moreover, we claim that there must be some $b \in [n]$ such that S(b) = 0. Moreover, we claim that there must be some $b \in [n]$ such that S(b) = 0 and, additionally, S(b + 1) + S(b + 2) < 4. Again for contradiction assume that, for all $b \in [n]$ with S(b) = 0, it holds that S(b + 1) + S(b + 2) = 4. We define the following sets

$$N_0 := \{i \in [n] \mid S(i) = 0 \land S(i+1) + S(i+2) = 4\}$$

$$N_1 := \{i \in [n] \mid S(i) = 1\}$$

$$N_2 := \{i \in [n] \mid S(i) = 2 \land i - 1, i - 2 \notin N_0\}.$$

Observe that each $i \in N_0$ contributes four selected vertices to *S*, each $i \in N_1$ contributes one vertex, and each $i \in N_2$ contributes two vertices to *S*. Moreover, this covers all vertices in *S*, as there is no index $i \in [n]$ with S(i) = 0 and S(i + 1) + S(i + 2) < 4. Hence, we get that

$$k = \sum_{i \in [n]} S(i) = 4|N_0| + |N_1| + 2|N_2| = n + |N_0| + |N_2|.$$

However, since we assumed that $N_0 \neq \emptyset$, we arrive at a contradiction as k = n and conclude that there is some $b \in [n]$ such that S(b) = 0 and S(b + 1) + S(b + 2) < 4.

In the next step we show that this also leads to a contradiction, thereby disproving that there is some $i \in [n]$ with S(i) = 2. We do this by constructing a large packing which would imply that S is not a solution. By our modification of φ , for all $\lambda \in \{x_{b+1}, \overline{x}_{b+1}, x_{b+2}, \overline{x}_{b+2}\}$, there is a clause $(x_b \vee \overline{x}_b \vee \lambda)$ in φ . By the above reasoning we know that there is at least one choice of λ such that $d_{\lambda} \notin S$. Assume without loss of generality that $\lambda = x_{b+1}$, the other cases follow analogously. Let $q \in [m]$ be the number of the clause $(x_b \vee \overline{x}_b \vee x_{b+1})$. We set $Q = \{(x_b, q, 1), (\overline{x}_b, q, 2), (x_{b+1}, q, 3)\}$ to simplify notation.

For all $\lambda \in \Lambda$ and $(j, p) \in C_{\lambda}$ where $(\lambda, j, p) \notin Q$, we can use the packing P_{true} from Claim 10.4 to find a packing of 3c + 2 triangles for the gadget $\text{Lit}_{\lambda,j,p}$ such that no vertex from $Z \cup \{d_{\lambda}\}$ is covered. (Recall that d_{λ} corresponds to the vertex v_{c+1} in the respective gadget, and the vertices in Z are identified with vertices of the form v_{γ} .) This contributes $(3m - 3) \cdot (3c + 2)$ triangles.

Also by Claim 10.4, for every $(\lambda, j, p) \in Q$, we can find a packing of 3c + 3 triangles for $\text{Lit}_{\lambda, j, p}$ since $d_{\lambda} = v_{c+1}$ is not deleted in these gadgets. Observe that the vertex sets of these packings are disjoint because the position p is different for each choice (and thus we consider different copies of the gadget Lit_{c+1}). This contributes 3(3c + 3) additional triangles to the packing.

Note that, by construction of *G*, the triangle packings of the three gadgets $\text{Lit}_{x_b,j,1}$, $\text{Lit}_{\overline{x}_b,j,2}$, and $\text{Lit}_{x_{b+1},j,3}$ cover, for each $\gamma \in [c]$, exactly one of the sets $\{z_{1,0}^{\gamma}, z_{2,0}^{\gamma}, z_{3,0}^{\gamma}\}$ or $\{z_{1,1}^{\gamma}, z_{2,1}^{\gamma}, z_{3,1}^{\gamma}\}$, and they cover none of the vertices of the respective other set. Thus, for every $\gamma \in [c]$, we can find a packing of 9 triangles for the gadget $\text{Sel}^{(\gamma)}$. This contributes 9*c* additional triangles to the packing.

Hence, the final packing consists of

$$(3m-3) \cdot (3c+2) + 3(3c+3) + 9c = 3m(3c+2) + 9c + 3$$

triangles which contradicts our assumption that *S* is a solution because we defined $\ell = 3m \cdot (3c+2)+9c+3$. We conclude that it cannot happen that S(i) = 2 for any $i \in [n]$.

Constructing and Verifying the Assignment. Now we can define the assignment π for φ . For all $i \in [n]$, we set

$$\pi(x_i) := \begin{cases} \text{true,} & \text{if } d_{x_i} \in S, \\ \text{false,} & \text{otherwise} \end{cases}$$

By the fact that the solution S is good, this assignment is well-defined and each variable is assigned some truth-value.

Now we argue that π satisfies φ . For the sake of a contradiction, assume that π does not satisfy φ . Then there is at least one clause that is not satisfied by π . Fix some arbitrary index $j \in [m]$ of such an unsatisfied clause. Next we construct a packing of at least ℓ triangles in G - S.

For all $\gamma \in [c]$, there is, by Claim 10.3, some triangle packing $P^{(\gamma)}$ for the gadget Sel^(γ) such that the vertices $z_{1,\text{bin}(j)[\gamma]}^{(\gamma)}, z_{2,\text{bin}(j)[\gamma]}^{(\gamma)}, z_{3,\text{bin}(j)[\gamma]}^{(\gamma)}$ are covered by this packing (this is the packing $P_{\text{bin}(j)[\gamma]}$ of the corresponding gadget). By Claim 10.3, we know that each packing $P^{(\gamma)}$ contains exactly 9 triangles.

Let λ_1 , λ_2 , and λ_3 be the literals such that the *j*th clause is $(\lambda_1 \lor \lambda_2 \lor \lambda_3)$.

- For all literals $\lambda \in \Lambda \setminus \{\lambda_1, \lambda_2, \lambda_3\}$, and for all $(j', p) \in C_\lambda$, we use Claim 10.4 to obtain a triangle packing P_λ of size 3c + 2 for the gadget Lit_{λ,j,p}. As argued before, we can choose $P_\lambda = P_{\text{true}}$ such that it does not cover any vertex from $Z \cup \{d_\lambda\}$. Hence, we do not have to check whether the vertex d_λ is contained in *S*, that is, to check whether it is deleted.
- For the literals λ_p with $p \in [3]$, and for all $(j', p) \in C_{\lambda_p}$ with $j' \neq j$, we also select a triangle packing of size 3c+2 for the gadget $\text{Lit}_{\lambda_p,j',p}$. Again, this triangle packing does not use the vertex d_{λ_p} or any vertex from Z.
- Finally, for the literals λ_p with $p \in [3]$, consider the gadget $\operatorname{Lit}_{\lambda_p,j,p}$. Recall that $\pi(\lambda_p) =$ false as we assume that the clause is unsatisfied. Hence, $d_{\lambda_p} \notin S$. Thus, by Claim 10.4, we can choose the triangle packing that contains d_{λ_p} for $\operatorname{Lit}_{\lambda_p,j,p}$, that is, the packing of size 3c + 3 that contains all of the vertices of the form $v_{\gamma} = z_{p,1-\operatorname{bin}(j)[\gamma]}^{(\gamma)}$.

Let P_{λ_p} be the combined packing for the gadgets $\operatorname{Lit}_{\lambda_p,j',p}$ for all $(j', p) \in C_{\lambda_p}$. We first argue why the final packing is actually a packing, that is, why the triangles from the right are disjoint from the triangle packing for the left side of the graph. For this fix some $\gamma \in [c]$. We know that the gadget $\operatorname{Sel}^{(\gamma)}$ covers the vertices $z_{p,\operatorname{bin}(j)[\gamma]}^{(\gamma)}$ for all $p \in [3]$. By our choice above, for all $p \in [3]$, the gadget $\operatorname{Lit}_{\lambda_p,j,p}$ covers the vertices $z_{p,1-\operatorname{bin}(j)[\gamma]}^{(\gamma)}$ for all $\gamma \in [c]$. Hence, the two vertex sets are actually disjoint which implies that the triangles from the packing are disjoint.

It remains to analyze the size of the resulting packing. We know that $|P^{(\gamma)}| = 9$, $|P_{\lambda}| = 3c + 2$ for all $\lambda \in \Lambda \setminus {\lambda_1, \lambda_2, \lambda_3}$, and that $|P_{\lambda_p}| = (|C_{\lambda_p}| - 1) \cdot (3c + 2) + (3c + 3)$ for all $p \in [3]$. Hence, the entire packing has size

$$c \cdot 9 + \sum_{\lambda \in \Lambda \setminus \{\lambda_1, \lambda_2, \lambda_3\}} |C_{\lambda}| \cdot (3c + 2)$$

+ $(3c + 2)(|C_{\lambda_1}| - 1) + (3c + 2)(|C_{\lambda_2}| - 1) + (3c + 2)(|C_{\lambda_3}| - 1) + 3(3c + 3)$
= $9c + \sum_{\lambda \in \Lambda} (3c + 2)|C_{\lambda}| + 3$
= $9c + 3m \cdot (3c + 2) + 3$

=

which is equal to ℓ . Since this is a contradiction to our assumption that we are given a solution for the TRIANGLE-HITPACK instance, we conclude that π actually satisfies the formula φ .

It remains to prove that the reduction also satisfies the required properties about the size and the pathwidth of G.

Claim 10.7. Graph G has pathwidth at most $O(\log m)$ and the size of G if bounded by $O(m \log m)$.

Proof of Claim. The number of Sel^(γ) gadgets is precisely *c* and each gadget is of constant size. Each gadget Lit_{$\lambda,p,j}$ is of size O(c) (by Claim 10.4), and there are 3*m* such gadgets in total. As we already accounted for the vertices in *Z* by the other gadgets, the size of the graph can be bounded above by</sub>

$$O(c) + 3m \cdot O(c) = O(m \log m).$$
For the bound on the pathwidth we first observe that if we delete *Z*, then the graph consists of c + 3m disjoint components. Moreover, each such component either corresponds to a gadget $\text{Sel}^{(\gamma)}$, which has constant size, or to a gadget $\text{Lit}_{\lambda,p,j}$, which has size $O(c) = O(\log m)$. Thus, the pathwidth of the entire graph can be bounded by $O(\log m)$.

We finish the proof by recalling that φ is satisfiable if and only if the original formula φ' is satisfiable. Moreover, based on our initial modifications to φ , we get $m \in O(m')$ which concludes the proof.

10.2 Lower Bound for SQUARE-HITPACK

In this section we consider the problem SQUARE-HITPACK and provide a lower bound matching the running time of the general algorithm from Section 7 as stated in Theorem 1.6. Formally, we prove Theorem 1.8, which we restate here for convenience.

Theorem 1.8. Assuming ETH, SQUARE-HITPACK has no $2^{2^{o(pw \log pw)}} \cdot n^{O(1)}$ time algorithm, where pw is the pathwidth of the input graph.

Our reduction starts from 3-SAT and follows roughly the same outline as the reduction for the general case. However, to obtain this stronger bound with the logarithmic factor, we have to construct an instance of SQUARE-HITPACK with smaller pathwidth. More precisely, if we can find a reduction such that the pathwidth is bounded by $O(\log m/\log \log m)$, then the claimed lower bound would follow immediately.

To understand how this can be achieved, recall that the encoding of the clause number was the limiting factor for the bound on the pathwidth in previous reduction. By encoding the index of the clauses in binary, the pathwidth of the graph became $O(\log m)$. When now considering SQUARE-HITPACK, we can actually find a better way of representing the clause number. Recall that in the previous construction, each gadget (independent of its type) covered vertices from their respective half and one additional vertex from the middle only. In the following we allow that a cycle can go from the left side to the right half of the graph. Then the cycle can actually be described by pair of vertices form the middle.

We use this idea as follows while again designing a graph with two halves. The left half contains gadgets corresponding to selecting the clause and the gadgets on the right side correspond to setting the variables and checking whether the literals are satisfied. For the vertices in the middle, we now have two groups (high and low) of O(t) vertices each where t is chosen such that t! = m (this is for example possible by setting $t = O(\log m/\log \log m)$). The clause number is then encoded by a perfect matching from the vertices of the high group to the vertices of the low group. This gives us t! possible perfect matchings which then clearly suffices to represent all clauses.

We define the gadgets on the left such that they connect each vertex from the high group to a vertex from the low group by a path of length two (i.e., a half of a C_4) which then induces a perfect matching. The gadgets on the right side then have to complete these cycles by another path of length two to form a C_4 . We define these literal gadgets such that this is only possible if the corresponding literal was not satisfied. The interpretation is again that a large C_4 -packign corresponds to an unsatisfied clause and thus, also formula while a small packing indicates a satisfying assignment.

We note that for this construction to work we crucially rely on the fact that we can transfer information from one half to the other half for which we exploit that we are packing cycles of length four.

In the following we give the formal details.

Proof of Theorem 1.8. Let φ' be the given 3-SAT formula with n' variables $x_1, \ldots, x_{n'}$ and m' clauses. We preprocess the formula in a similar way to that in Section 10.1, and we get a formula φ with n variables and m clauses. Let t be the minimum integer such that t! is at least the number of clauses of the formula. Next, we duplicate arbitrarily selected clause to guarantee that the final formula has exactly t! clauses.

Gadgets. As a next step we define two types of gadgets, one for the literals and one for selecting the clause.

Claim 10.8 (Literal Gadget for C_4). For all integers $r \ge 2$, there is a graph CLit_r with 2r distinguished vertices v_1, \ldots, v_r and $\overline{v}_1, \ldots, \overline{v}_r \in V$ such that

- 1. there are exactly two packings of C_4 's of size 3r denoted by P_0 and P_1 ,
- 2. P_0 covers v_1, \ldots, v_r and none of the vertices $\overline{v}_1, \ldots, \overline{v}_r$,
- 3. P_1 covers $\overline{v}_1, \ldots, \overline{v}_r$ and none of the vertices v_1, \ldots, v_r ,
- 4. there is no packing of C_4 's of size greater than 3r.

Proof of Claim. Intuitively, our literal gadget $CLit_r$ is the graph obtained by replacing every triangle in UniVar_r with a C_4 .

First, we create 6r copies of C_4 , which we denote as $a_1b_1c_1d_1, \ldots, a_{6r}b_{6r}c_{6r}d_{6r}$. We identify d_i with $b_{i+1 \mod 6r}$ for every $i \in [6r]$. For every $i \in [r]$, we name a_{6i-5} as v_i . Next, for every $i \in [r]$ we name vertex a_{6i-2} as \overline{v}_i . This concludes the construction of graph CLit_r.

Let $P_0 = \{a_{2i+1}b_{2i+1}c_{2i+1}|i \in [3r]\}$ and $P_1 = \{a_{2i}b_{2i}c_{2i}d_{2i} | i \in [3r]\}$ be the two distinguished packings. We can easily verify that properties 2 and 3 of this claim are true.

Observe, that any C_4 in the graph is of the form $a_i b_i c_i d_i$ for some $i \in [6r]$. This means that an arbitrary C_4 in any packing in the graph must cover both vertices of $\{b_i d_i\}$ for some $i \in [6r]$. It follows that properties 1 and 4 are true as $\{b_{2i+1}, d_{2i+1}\} \mid i \in [3r]\} = \{\{b_{2i}, d_{2i}\} \mid i \in [3r]\}$, every C_4 in a packing must contain b_i, d_i for some i and both sets have size 3r only.

We also introduce the selector gadget CSel. Intuitively, CSel is a *chain* of five 4-cycles. Formally, CSel is constructed from 5 copies of C_4 , denoted as $a_1b_1c_1d_1, \ldots, a_5b_5c_5d_5$. Then, we identify vertices d_i with b_{i+1} for every $i \in \{1, 2, 3, 4\}$. This concludes the construction of CSel.

Construction of the Instance. Now we describe how to construct the instance of C_4 -HITPACK from a processed instance of 3-SAT. For all $\gamma \in [t]$, $g \in \{0, 1\}$, and $p \in \{1, 2, 3\}$, we create a vertex $z_{p,g}^{(\gamma)}$ and define $Z := \{z_{p,g}^{(\gamma)}\}_{\gamma,g,p}$ as the set of vertices in the middle.

The left side of the graph is as follows. For each pair $(i, j) \in [t] \times [t]$, we create a copy of the selector gadget, denoted by $CSel^{(i,j)}$. For each gadget $CSel^{(i,j)}$, we connect a_1, a_3 , and a_5 (where a_i is the vertex in the *i*th C_4 of $CSel^{(i,j)}$) as follows to six vertices in Z:

- We make a_1 adjacent to the two vertices $z_{1,0}^i$ and $z_{1,1}^j$.
- We make a_3 adjacent to the two vertices $z_{2,0}^i$ and $z_{2,1}^j$.
- We make a_5 adjacent to the two vertices z_{30}^i and z_{31}^j .

The right side of the graph is as follows. Let $\Lambda = \{x_1, \overline{x}_1, \dots, x_n, \overline{x}_n\}$ be the set of all literals corresponding to the variables of φ . Note that from the preprocessing it follows that all of them appear in some clause. For each literal $\lambda \in \Lambda$, we define a set $\text{ClauseID}_{\lambda} \subseteq [m] \times \{1, 2, 3\}$ such that $(j, p) \in \text{ClauseID}_{\lambda}$ if and only if literal λ appears in the *j*th clause at position *p*.

We create two vertices $d_i^{(\text{true})}$ and $d_i^{(\text{false})}$ for each $i \in [n]$. For all $\lambda \in \Lambda$ and all $(j, p) \in \text{ClauselD}_{\lambda}$, we introduce a copy of the gadget CLit_{t+1} denoted by $\text{CLit}_{\lambda,j,p}$. Depending on the literal λ we consider two cases.

- The literal λ is a positive literal, that is, $\lambda = x_i$ for some variable x_i :
 - Then, we identify v_{t+1} of the gadget $\text{CLit}_{\lambda,j,p}$ with $d_i^{(\text{true})}$. Moreover, we identify \overline{v}_{t+1} of the gadget $\text{CLit}_{\lambda,j,p}$ with $d_i^{(\text{false})}$.

• The literal λ is a negative literal, that is, $\lambda = \overline{x}_i$ for some variable x_i :

Then we identify v_{t+1} of the gadget $\text{CLit}_{\lambda,j,p}$ with $d_i^{(\text{false})}$. Moreover, we identify \overline{v}_{t+1} of the gadget $\text{CLit}_{\lambda,j,p}$ with $d_i^{(\text{true})}$.

Let $\sigma_1, \sigma_2, \ldots, \sigma_m$ be *m* different permutation functions of *t* elements, chosen in arbitrary order. Note that there are *t*! different permutation functions of *t* elements and *t*! = *m*. For each gadget $\text{CLit}_{\lambda,j,p}$ and each $\gamma \in [t]$, we connect \overline{v}_{γ} and $z_{p,0}^{(\gamma)}$ with an edge, and connect \overline{v}_{γ} and $z_{p,1}^{(\sigma_j(\gamma))}$ with an edge. This concludes the construction of the graph *G*.

Let V be the set of vertices of G, then the set of undeletable vertices is $U := V \setminus \{d_i^{(\text{true})}, d_i^{(\text{false})} \mid i \in [n]\}$. We set k := n as the bound on the number of vertices we are allowed to delete and set $\ell := 3t^2 + 9m(t+1) + 2t$. The constructed C_4 -HITPACK instance is $I = (G, U, k, \ell)$. This concludes the description of the construction. Clearly, the runtime of the reduction is polynomial. It remains to prove its correctness and analyze the pathwidth of G.

Correctness. Now, we show that the construction is correct. We do this by handling both directions individually.

Claim 10.9. If φ is satisfiable, then I has a solution.

Proof of Claim. Let π be an assignment for the variables x_1, \ldots, x_n such that φ is satisfied under π . Based on π , we define the solution for I as

$$S \coloneqq \{d_i^{(\text{true})} \mid i \in [n] \text{ and } \pi(x_i) = \text{true}\} \cup \{d_i^{(\text{false})} \mid i \in [n] \text{ and } \pi(x_i) = \text{false}\}.$$

It remains to show that *S* is indeed a solution for *I*, i.e., there is no packing of ℓ vertex-disjoint 4-cycles in $G \setminus S$.

For the sake of contradiction, assume that \mathcal{P} is a maximum-size packing of 4-cycles of size at least ℓ . Let us analyze this packing \mathcal{P} . First we check the right side of the graph G, which is the set of all literal gadgets. Each of $\text{CLit}_{\lambda,j,p}$ can contribute at most 3(t + 1) many 4-cycles to \mathcal{P} (if we ignore the 4-cycles of \mathcal{P} in the middle that are incident with vertices of the literal gadgets). There are 3m literal gadgets and thus the literal gadgets can contribute at most 3m(3t + 3) many 4-cycles in total.

It remains to check the left part and the middle part of *G*. Since there are 6*t* vertices in the middle, the middle part can contribute at most 3*t* many 4-cycles to \mathcal{P} . We show that the middle part contributes exactly 3*t* many 4-cycles to \mathcal{P} . Otherwise, the size of \mathcal{P} is strictly less than $3t+3(t^2-t)+2t+3m(3t+3) = t$, a contradiction to our assumption.

Next, we argue that there are exactly t selector gadgets which are incident with at least one C_4 of \mathcal{P} contributed by the middle part. Suppose that there are q > t selector gadgets which are incident with at least one C_4 of \mathcal{P} contributed by the middle part. Then the size of \mathcal{P} is at most $3t + 3(t^2 - q) + 2q + 3m(3t + 3) < t$, a contradiction to our assumption. Thus it holds that there are exactly t selector gadgets which are incident with at least one C_4 of \mathcal{P} contributed by the middle part. Since there are 6t vertices in the middle part, it follows that there are exactly t selector gadgets each of which is incident with three 4-cycles of \mathcal{P} contributed by the middle part. Thus the left part can contribute at most $2t + (t^2 - t) \cdot 3 = 3t^2 - t$ many 4-cycles to \mathcal{P} . By the construction, these t selector gadgets actually define a permutation of t elements, say σ_h ($h \in [m]$), according to the vertices of Z to which they are adjacent.

Note that to pack 3t many 4-cycles in the middle part and 3m(3t + 3) many 4-cycles on the right part (to make sure that $|\mathcal{P}| \ge t$), the only possible situation is that each of the three literal gadgets corresponding to the *h*th clause C_h are incident with *t* many 4-cycles of \mathcal{P} in the middle part. Moreover, each of the three literal gadgets also contributes 3(t + 1) many 4-cycles to \mathcal{P} . By the definition of the solution *S*, all three literals of C_h are set to false by the assignment π . Thus, the clause C_h is not satisfied by π , contradicting that π is a satisfying assignment.

As a result, there is no packing of ℓ vertex-disjoint 4-cycles in $G \setminus S$ and S is a solution to I.

Now we prove the reverse direction.

Claim 10.10. If *I* has a solution, then φ is satisfiable.

Proof of Claim. Let $S \subseteq V \setminus U$ be a solution for *I*. By a very similar analysis to that in Claim 10.6, we can show that the solution *S* is *good*, that is, for no variable x_i , both vertices $d_i^{(\text{true})}$ and $d_i^{(\text{false})}$ are deleted (see Section 10.1 for more details). We define the assignment π for φ as follows. For all $i \in [n]$, we set

$$\pi(x_i) \coloneqq \begin{cases} \text{true,} & \text{if } d_i^{(\text{true})} \in S, \\ \text{false,} & \text{otherwise.} \end{cases}$$

By the fact that the solution S is good, this assignment is well-defined and each variable is assigned some boolean value.

Now we argue that π satisfies φ . For the sake of a contradiction, assume that π does not satisfy φ . Hence, there is at least one clause that is not satisfied by π and let $j \in [m]$ be the index of such an unsatisfied clause. Next we construct a packing \mathcal{P} of at least ℓ many 4-cycles in G - S.

Let $C_j = (\lambda_1 \lor \lambda_2 \lor \lambda_3)$ be this specific clause. Since $\pi(\lambda_p) =$ false for each $p \in [3]$, vertex v_{t+1} is not deleted in each of $\text{CLit}_{\lambda_p,j,p}$ by the construction. By Claim 10.8, we can add t + 1 many 4-cycles (the packing P_0 covering v_1, \ldots, v_{t+1}) for the literal gadget $\text{CLit}_{\lambda_p,j,p}$ to \mathcal{P} for each $p \in [3]$. Consider a vertex \overline{v}_{γ} (where $\gamma \in [t]$) of the literal gadget $\text{CLit}_{\lambda_p,j,p}$ (where $p \in [3]$). Recall that \overline{v}_{γ} is adjacent to $z_{p,0}^{(\gamma)}$ and $z_{p,1}^{(\sigma_j(\gamma))}$. Let a_{2p-1} be the vertex of $\text{CSel}^{(\gamma,\sigma_j(\gamma))}$ which is adjacent to both $z_{p,0}^{(\gamma)}$ and $z_{p,1}^{(\sigma_j(\gamma))}$. Then, we get the C_4 that covers \overline{v}_{γ} , a_{2p-1} , $z_{p,0}^{(\gamma)}$ and $z_{p,1}^{(\sigma_j(\gamma))}$. Thus we get a packing \mathcal{P}_{mid} of 3t many 4-cycles of this form and by our construction these cycles are vertex-disjoint. We add all of the 4-cycles in \mathcal{P}_{mid} to \mathcal{P} .

For any literal gadget $\operatorname{CLit}_{\lambda,j',p}$ such that $j' \neq j$, by Claim 10.8, we can add t + 1 many 4-cycles to \mathcal{P} as only one vertex of v_{t+1} and \overline{v}_{t+1} is deleted in the gadget. For a selector gadget $\operatorname{CSel}^{(i,j)}$, note that it is incident with either three or none of the 4-cycles of $\mathcal{P}_{\operatorname{mid}}$ by our construction. If it is incident with three 4-cycles of $\mathcal{P}_{\operatorname{mid}}$, then we add two 4-cycles of $\operatorname{CSel}^{(i,j)}$ which does not cover any vertex of $\mathcal{P}_{\operatorname{mid}}$ to \mathcal{P} . Otherwise we add three 4-cycles of $\operatorname{CSel}^{(i,j)}$ to \mathcal{P} .

We can verify that the 4-cycles in \mathcal{P} are pairwise vertex-disjoint. The size of \mathcal{P} is $3m(3t+3)+3t+2t+3(t^2-t) = \ell$. This contradicts the fact that *S* is a solution for *I*. Thus we can conclude that the constructed assignment π satisfies φ .

It remains to prove that the reduction also satisfies the required properties about the size and the pathwidth of G.

Claim 10.11. Graph G has pathwidth at most O(t).

Proof of Claim. Observe that if we delete *Z*, then the graph consists of $t^2 + 3m$ disjoint components. Moreover, each such component either corresponds to a gadget $CSel^{(i,j)}$, which has constant size, or to a gadget $CLit_{\lambda,j,p}$, which has size O(t) = O(t). Thus, the pathwidth of the entire graph can be bounded by O(t).

Recall that t! = m, which means that $m = 2^{O(t \log t)} = 2^{O(pw \log pw)}$. Observe that this concludes the proof of Theorem 1.8 because a $2^{2^{o(pw \log pw)}} \cdot |V(G)|^{O(1)}$ algorithm for C_4 -HITPACK would yield a $2^{o(m)}$ algorithm for 3-SAT with m clauses.

10.3 Lower Bound for Cycle-HitPack

In this section we prove Theorem 1.3, which we restate for convenience.

Theorem 1.3. Assuming ETH, CYCLE-HITPACK has no $2^{2^{o(pw \log pw)}} \cdot n^{O(1)}$ time algorithm, where pw is the pathwidth of the input graph.

We note that this result does not follow from the statement of Theorem 1.8 although a C_4 is obviously a cycle. The main reason is that there might be a large cycle packing despite the fact that there is no large C_4 packing (e.g., the graph itself is a long cycle).

However, in the following we argue that our reduction from Theorem 1.8 was already stated such that it works for CYCLE-HITPACK. The crucial piece is the following lemma.

Lemma 10.12. Let $I = (G, U, k, \ell)$ be the C_4 -HITPACK instance from Theorem 1.8. Let $S \subseteq V(G) \setminus U$ be a set of vertices and \mathcal{P} be an arbitrary cycle-packing for G - S containing at least one cycle that is not a C_4 . Then, there is a C_4 -packing \mathcal{P}' for G - S such that $|\mathcal{P}'| \geq |\mathcal{P}|$.

Proof. Recall that the constructed graph is based on two different types of gadgets. The gadgets of the form CSel were used to select some clause number and the gadgets of the form $CLit_{t+1}$ encoded the literals appearing in the formula.

Consider some cycle *C* of length at least 5 in the packing \mathcal{P} . This cycle *C* cannot be contained in the gadget CSel since such a gadget does not contain any other cycles besides the five 4-cycles which are arranged as a path by construction. Suppose *C* is entirely contained in some gadget CLit_{t+1} . Let us denote this gadget by *F* for ease of notation. Then, by the structure of these gadgets, *C* intersects all 4-cycles in *F*. In particular, there is no other cycle in \mathcal{P} that is entirely contained in *F*. Also, as a *non*-distinguished vertex of *F* is not part of any edge outside of *F*, such a vertex cannot be contained in any cycle of \mathcal{P} , other than possibly *C*. Hence, removing the cycle *C* and then adding some maximal packing of C_4 in *F* that does *not* contain any distinguished vertex gives another feasible packing of size at least that of \mathcal{P} .

Now consider some cycle *C* of length at least 5 in the packing \mathcal{P} that is *not* entirely contained in some gadget. In this case we know that *C* enters some gadget *F* at some distinguished vertex and leaves *F* at some other distinguished vertex. However, from the construction of the gadgets it is straightforward to see that this path that is the intersection of *C* with the gadget *F* goes through at least two C_4 's in *F* all of whose vertices are non-distinguished vertices. Therefore, removing *C* from the packing \mathcal{P} and adding one of these C_4 instead gives another feasible packing of size at least that of \mathcal{P} (and fewer cycles of length at least 5).

Now we can directly prove Theorem 1.3.

Theorem 1.3. Assuming ETH, CYCLE-HITPACK has no $2^{2^{o(pw \log pw)}} \cdot n^{O(1)}$ time algorithm, where pw is the pathwidth of the input graph.

Proof of Theorem 1.3. It clearly suffices to prove that the construction gives a reduction from 3-SAT to CYCLE-HITPACK with the properties from Lemma 10.1. Then, the result follows by the same arguments as Theorem 1.9.

Since we did not modify our construction, it suffices to prove the first property, that is, the 3-SAT formula φ and the CYCLE-HITPACK instance *I* are equivalent. If φ is satisfiable, we know that *I* has a solution for TRIANGLE-HITPACK, that is, after removing at most *k* vertices there is no large packing of C_4 . Lemma 10.12 implies that there is also no large packing of cycles as otherwise there would also be a large packing of C_4 .

For the converse direction assume that at most k vertices of I can be deleted such that there is no large cycle-packing. Since every C_4 -packing is also a cycle-packing, this implies that there is no large C_4 packing. Hence, formula φ must be satisfiable.

References

- Isolde Adler, Martin Grohe, and Stephan Kreutzer. Computing excluded minors. In Proceedings of the Nineteenth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2008, pages 641–650.
 SIAM, 2008. URL: http://dl.acm.org/citation.cfm?id=1347082.1347153.
- [2] Akanksha Agrawal, Daniel Lokshtanov, Pranabendu Misra, Saket Saurabh, and Meirav Zehavi. Feedback Vertex Set Inspired Kernel for Chordal Vertex Deletion. ACM Trans. Algorithms, 15(1):11:1–11:28, 2019. doi:10.1145/3284356.
- [3] Noga Alon, Raphael Yuster, and Uri Zwick. Color-Coding. J. ACM, 42(4):844-856, 1995. doi: 10.1145/210332.210337.
- [4] Jørgen Bang-Jensen, Alessandro Maddaloni, and Saket Saurabh. Algorithms and Kernels for Feedback Set Problems in Generalizations of Tournaments. *Algorithmica*, 76(2):320–343, 2016. doi:10.1007/s00453-015-0038-2.
- [5] Claude Berge. Two theorems in graph theory. *Proceedings of the National Academy of Sciences*, 43(9):842–844, 1957.
- [6] Stéphane Bessy, Marin Bougeret, R. Krithika, Abhishek Sahu, Saket Saurabh, Jocelyn Thiebaut, and Meirav Zehavi. Packing Arc-Disjoint Cycles in Tournaments. *Algorithmica*, 83(5):1393–1420, 2021. doi:10.1007/s00453-020-00788-2.
- [7] Stéphane Bessy, Fedor V. Fomin, Serge Gaspers, Christophe Paul, Anthony Perez, Saket Saurabh, and Stéphan Thomassé. Kernels for feedback arc set in tournaments. *J. Comput. Syst. Sci.*, 77(6):1071–1078, 2011. doi:10.1016/j.jcss.2010.10.001.
- [8] Hans L. Bodlaender. A Linear-Time Algorithm for Finding Tree-Decompositions of Small Treewidth. SIAM J. Comput., 25(6):1305–1317, 1996. doi:10.1137/S0097539793251219.
- [9] Hans L. Bodlaender, Marek Cygan, Stefan Kratsch, and Jesper Nederlof. Deterministic single exponential time algorithms for connectivity problems parameterized by treewidth. *Inf. Comput.*, 243:86–111, 2015. doi:10.1016/j.ic.2014.12.008.
- [10] Glencora Borradaile and Hung Le. Optimal Dynamic Program for *r*-Domination Problems over Tree Decompositions. In 11th International Symposium on Parameterized and Exact Computation, IPEC 2016, volume 63 of LIPIcs, pages 8:1–8:23. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2016. doi:10.4230/LIPIcs.IPEC.2016.8.
- [11] Yixin Cao. A Naive Algorithm for Feedback Vertex Set. In 1st Symposium on Simplicity in Algorithms, SOSA 2018, January 7-10, 2018, volume 61 of OASIcs, pages 1:1–1:9. Schloss Dagstuhl -Leibniz-Zentrum für Informatik, 2018. doi:10.4230/OASIcs.SOSA.2018.1.
- [12] Yixin Cao and Dániel Marx. Chordal Editing is Fixed-Parameter Tractable. *Algorithmica*, 75(1):118–137, 2016. doi:10.1007/s00453-015-0014-x.
- [13] Maria Chudnovsky, Alexandra Ovetsky Fradkin, and Paul D. Seymour. Tournament immersion and cutwidth. J. Comb. Theory, Ser. B, 102(1):93–101, 2012. doi:10.1016/j.jctb.2011. 05.001.
- [14] Maria Chudnovsky, Alex Scott, and Paul D. Seymour. Disjoint paths in unions of tournaments. J. Comb. Theory, Ser. B, 135:238–255, 2019. doi:10.1016/j.jctb.2018.08.007.

- [15] Radu Curticapean, Nathan Lindzey, and Jesper Nederlof. A Tight Lower Bound for Counting Hamiltonian Cycles via Matrix Rank. In Proceedings of the Twenty-Ninth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2018, pages 1080–1099. SIAM, 2018. doi: 10.1137/1.9781611975031.70.
- [16] Radu Curticapean and Dániel Marx. Tight conditional lower bounds for counting perfect matchings on graphs of bounded treewidth, cliquewidth, and genus. In *Proceedings of the Twenty-Seventh Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2016*, pages 1650–1669. SIAM, 2016. doi:10.1137/1.9781611974331.ch113.
- [17] Marek Cygan, Fedor V. Fomin, Łukasz Kowalik, Daniel Lokshtanov, Dániel Marx, Marcin Pilipczuk, Michał Pilipczuk, and Saket Saurabh. *Parameterized Algorithms*. Springer, 2015. doi:10.1007/978-3-319-21275-3.
- [18] Marek Cygan, Jesper Nederlof, Marcin Pilipczuk, Michał Pilipczuk, Johan M. M. van Rooij, and Jakub Onufry Wojtaszczyk. Solving Connectivity Problems Parameterized by Treewidth in Single Exponential Time. *ACM Trans. Algorithms*, 18(2):17:1–17:31, 2022. doi:10.1145/3506707.
- [19] Frank K. H. A. Dehne, Michael R. Fellows, Michael A. Langston, Frances A. Rosamond, and Kim Stevens. An 2^{O(k)}n³ FPT Algorithm for the Undirected Feedback Vertex Set Problem. *Theory Comput. Syst.*, 41(3):479–492, 2007. doi:10.1007/s00224-007-1345-z.
- [20] Reinhard Diestel. Graph theory 3rd ed. Graduate texts in mathematics, 173(33):12, 2005.
- [21] Michael Dom, Jiong Guo, Falk Hüffner, Rolf Niedermeier, and Anke Truß. Fixed-parameter tractability results for feedback set problems in tournaments. J. Discrete Algorithms, 8(1):76–86, 2010. doi:10.1016/j.jda.2009.08.001.
- [22] Jack Edmonds. Paths, trees, and flowers. Canadian Journal of mathematics, 17:449-467, 1965.
- [23] László Egri, Dániel Marx, and Paweł Rzążewski. Finding List Homomorphisms from Boundedtreewidth Graphs to Reflexive Graphs: a Complete Complexity Characterization. In 35th Symposium on Theoretical Aspects of Computer Science, STACS 2018, volume 96 of LIPIcs, pages 27:1–27:15. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2018. doi:10.4230/LIPIcs.STACS. 2018.27.
- [24] P. Erdős and L. Pósa. On independent circuits contained in a graph. Canad. J. Math., 17:347–352, 1965.
- [25] Michael R. Fellows and Michael A. Langston. On search, decision and the efficiency of polynomialtime algorithms (extended abstract). In *Proceedings of the 21st Annual ACM Symposium on Theory* of Computing, May 14-17, 1989, pages 501–512. ACM, 1989. doi:10.1145/73007.73055.
- [26] Jacob Focke, Dániel Marx, Fionn Mc Inerney, Daniel Neuen, Govind S. Sankar, Philipp Schepper, and Philip Wellnitz. Tight Complexity Bounds for Counting Generalized Dominating Sets in Bounded-Treewidth Graphs. In *Proceedings of the 2023 ACM-SIAM Symposium on Discrete Algorithms, SODA 2023*, pages 3664–3683. SIAM, 2023. doi:10.1137/1.9781611977554. ch140.
- [27] Jacob Focke, Dániel Marx, and Paweł Rzążewski. Counting list homomorphisms from graphs of bounded treewidth: tight complexity bounds. In *Proceedings of the 2022 ACM-SIAM Symposium on Discrete Algorithms, SODA 2022*, pages 431–458. SIAM, 2022. doi:10.1137/1. 9781611977073.22.
- [28] Fedor V. Fomin, Daniel Lokshtanov, Fahad Panolan, and Saket Saurabh. Efficient Computation of Representative Families with Applications in Parameterized and Exact Algorithms. *J. ACM*, 63(4):29:1–29:60, 2016. doi:10.1145/2886094.

- [29] Fedor V. Fomin, Daniel Lokshtanov, Fahad Panolan, Saket Saurabh, and Meirav Zehavi. Hitting topological minors is FPT. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, *STOC 2020*, pages 1317–1326. ACM, 2020. doi:10.1145/3357713.3384318.
- [30] Fedor V. Fomin, Daniel Lokshtanov, Venkatesh Raman, and Saket Saurabh. Fast Local Search Algorithm for Weighted Feedback Arc Set in Tournaments. In Proceedings of the Twenty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2010. AAAI Press, 2010. URL: http://www. aaai.org/ocs/index.php/AAAI/AAAI10/paper/view/1829.
- [31] Fabian Frei, Edith Hemaspaandra, and Jörg Rothe. Complexity of stability. J. Comput. Syst. Sci., 123:103-121, 2022. URL: https://doi.org/10.1016/j.jcss.2021.07.001, doi:10.1016/J.JCSS.2021.07.001.
- [32] Esther Galby. Double-exponential lower bounds for parameterisations by treewidth. Invited talk at Graph Width Parameters: from Structure to Algorithms (GWP 2023), Satellite Workshop of ICALP 2023, 2023.
- [33] M. Garey and D. Johnson. Computers and Intractability: A Guide to the Theory of NP-Completeness. W. H. Freeman and Company, 1979.
- [34] Jiong Guo, Jens Gramm, Falk Hüffner, Rolf Niedermeier, and Sebastian Wernicke. Compressionbased fixed-parameter algorithms for feedback vertex set and edge bipartization. *J. Comput. Syst. Sci.*, 72(8):1386–1396, 2006. doi:10.1016/j.jcss.2006.02.001.
- [35] Jiong Guo and Rolf Niedermeier. Fixed-parameter tractability and data reduction for multicut in trees. *Networks*, 46(3):124–135, 2005. doi:10.1002/net.20081.
- [36] Russell Impagliazzo and Ramamohan Paturi. On the Complexity of k-SAT. J. Comput. Syst. Sci., 62(2):367-375, 2001. doi:10.1006/jcss.2000.1727.
- [37] Russell Impagliazzo, Ramamohan Paturi, and Francis Zane. Which problems have strongly exponential complexity? *J. Comput. Syst. Sci.*, 63(4):512–530, 2001. URL: https://doi.org/10.1006/jcss.2001.1774, doi:10.1006/JCSS.2001.1774.
- [38] Bart M. P. Jansen and Marcin Pilipczuk. Approximation and Kernelization for Chordal Vertex Deletion. *SIAM J. Discret. Math.*, 32(3):2258–2301, 2018. doi:10.1137/17M112035X.
- [39] Naonori Kakimura, Ken-ichi Kawarabayashi, and Dániel Marx. Packing cycles through prescribed vertices. *J. Comb. Theory, Ser. B*, 101(5):378–381, 2011. doi:10.1016/j.jctb.2011.03.004.
- [40] Ioannis Katsikarelis, Michael Lampis, and Vangelis Th. Paschos. Structural parameters, tight bounds, and approximation for (k, r)-center. Discret. Appl. Math., 264:90–117, 2019. doi:10. 1016/j.dam.2018.11.002.
- [41] Ken-ichi Kawarabayashi and Bruce A. Reed. Odd cycle packing. In Leonard J. Schulman, editor, Proceedings of the 42nd ACM Symposium on Theory of Computing, STOC 2010, Cambridge, Massachusetts, USA, 5-8 June 2010, pages 695–704. ACM, 2010. doi:10.1145/1806689. 1806785.
- [42] Ken-ichi Kawarabayashi, Bruce A. Reed, and Paul Wollan. The Graph Minor Algorithm with Parity Conditions. In Rafail Ostrovsky, editor, *IEEE 52nd Annual Symposium on Foundations of Computer Science, FOCS 2011, Palm Springs, CA, USA, October 22-25, 2011*, pages 27–36. IEEE Computer Society, 2011. doi:10.1109/FOCS.2011.52.
- [43] David G. Kirkpatrick and Pavol Hell. On the Complexity of General Graph Factor Problems. *SIAM J. Comput.*, 12(3):601–609, 1983. doi:10.1137/0212040.

- [44] Tomasz Kociumaka and Marcin Pilipczuk. Faster deterministic Feedback Vertex Set. *Inf. Process. Lett.*, 114(10):556–560, 2014. doi:10.1016/j.ipl.2014.05.001.
- [45] Tuukka Korhonen and Daniel Lokshtanov. An Improved Parameterized Algorithm for Treewidth. In Barna Saha and Rocco A. Servedio, editors, *Proceedings of the 55th Annual ACM Symposium on Theory of Computing, STOC 2023*, pages 528–541. ACM, 2023. doi:10.1145/3564246. 3585245.
- [46] Mithilesh Kumar and Daniel Lokshtanov. Faster Exact and Parameterized Algorithm for Feedback Vertex Set in Tournaments. In 33rd Symposium on Theoretical Aspects of Computer Science, STACS 2016, volume 47 of LIPIcs, pages 49:1–49:13. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2016. doi:10.4230/LIPIcs.STACS.2016.49.
- [47] Michael Lampis. Model Checking Lower Bounds for Simple Graphs. Log. Methods Comput. Sci., 10(1), 2014. doi:10.2168/LMCS-10(1:18)2014.
- [48] Michael Lampis, Stefan Mengel, and Valia Mitsou. QBF as an alternative to courcelle's theorem. In Theory and Applications of Satisfiability Testing - SAT 2018 - 21st International Conference, SAT 2018, Held as Part of the Federated Logic Conference, FloC 2018, volume 10929 of Lecture Notes in Computer Science, pages 235–252. Springer, 2018. doi:10.1007/978-3-319-94144-8_15.
- [49] Michael Lampis and Valia Mitsou. Treewidth with a Quantifier Alternation Revisited. In 12th International Symposium on Parameterized and Exact Computation, IPEC 2017, volume 89 of LIPIcs, pages 26:1–26:12. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2017. doi:10.4230/ LIPIcs.IPEC.2017.26.
- [50] John M. Lewis and Mihalis Yannakakis. The Node-Deletion Problem for Hereditary Properties is NP-Complete. J. Comput. Syst. Sci., 20(2):219–230, 1980. doi:10.1016/0022-0000(80) 90060-4.
- [51] Paolo Liberatore. Redundancy in logic I: CNF propositional formulae. Artif. Intell., 163(2):203– 232, 2005. URL: https://doi.org/10.1016/j.artint.2004.11.002, doi: 10.1016/J.ARTINT.2004.11.002.
- [52] Daniel Lokshtanov, Dániel Marx, and Saket Saurabh. Known algorithms on graphs of bounded treewidth are probably optimal. ACM Trans. Algorithms, 14(2):13:1–13:30, 2018. doi:10. 1145/3170442.
- [53] Daniel Lokshtanov, Dániel Marx, and Saket Saurabh. Slightly Superexponential Parameterized Problems. *SIAM J. Comput.*, 47(3):675–702, 2018. doi:10.1137/16M1104834.
- [54] Daniel Lokshtanov, Pranabendu Misra, Joydeep Mukherjee, Fahad Panolan, Geevarghese Philip, and Saket Saurabh. 2-Approximating Feedback Vertex Set in Tournaments. ACM Trans. Algorithms, 17(2):11:1–11:14, 2021. doi:10.1145/3446969.
- [55] Daniel Lokshtanov, Amer E. Mouawad, Saket Saurabh, and Meirav Zehavi. Packing Cycles Faster Than Erdős Pósa. SIAM J. Discret. Math., 33(3):1194–1215, 2019. doi:10.1137/ 17M1150037.
- [56] Daniel Lokshtanov, N. S. Narayanaswamy, Venkatesh Raman, M. S. Ramanujan, and Saket Saurabh. Faster Parameterized Algorithms Using Linear Programming. ACM Trans. Algorithms, 11(2):15:1–15:31, 2014. doi:10.1145/2566616.
- [57] Dániel Marx. Chordal Deletion is Fixed-Parameter Tractable. *Algorithmica*, 57(4):747–768, 2010. doi:10.1007/s00453-008-9233-8.

- [58] Dániel Marx. Chordless Cycle Packing Is Fixed-Parameter Tractable. In 28th Annual European Symposium on Algorithms, ESA 2020, September 7-9, 2020, volume 173 of LIPIcs, pages 71:1–71:19. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020. doi:10.4230/LIPIcs.ESA. 2020.71.
- [59] Dániel Marx and Valia Mitsou. Double-Exponential and Triple-Exponential Bounds for Choosability Problems Parameterized by Treewidth. In Ioannis Chatzigiannakis, Michael Mitzenmacher, Yuval Rabani, and Davide Sangiorgi, editors, 43rd International Colloquium on Automata, Languages, and Programming, ICALP 2016, July 11-15, 2016, Rome, Italy, volume 55 of LIPIcs, pages 28:1–28:15. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2016. doi:10.4230/ LIPIcs.ICALP.2016.28.
- [60] Dániel Marx, Govind S. Sankar, and Philipp Schepper. Degrees and Gaps: Tight Complexity Results of General Factor Problems Parameterized by Treewidth and Cutwidth. In 48th International Colloquium on Automata, Languages, and Programming, ICALP 2021, volume 198 of LIPIcs, pages 95:1–95:20. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2021. doi: 10.4230/LIPIcs.ICALP.2021.95.
- [61] Dániel Marx, Govind S. Sankar, and Philipp Schepper. Anti-Factor Is FPT Parameterized by Treewidth and List Size (But Counting Is Hard). In 17th International Symposium on Parameterized and Exact Computation, IPEC 2022, volume 249 of LIPIcs, pages 22:1–22:23. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2022. doi:10.4230/LIPIcs.IPEC.2022.22.
- [62] Silvio Micali and Vijay V. Vazirani. An $O(\sqrt{|V|}|E|)$ algorithm for finding maximum matching in general graphs. In 21st Annual Symposium on Foundations of Computer Science, Syracuse, New York, USA, 13-15 October 1980, pages 17–27. IEEE Computer Society, 1980. doi:10.1109/SFCS.1980.12.
- [63] Pranabendu Misra, Venkatesh Raman, M. S. Ramanujan, and Saket Saurabh. A Polynomial Kernel for Feedback Arc Set on Bipartite Tournaments. *Theory Comput. Syst.*, 53(4):609–620, 2013. doi: 10.1007/s00224-013-9453-4.
- [64] Karolina Okrasa, Marta Piecyk, and Paweł Rzążewski. Full Complexity Classification of the List Homomorphism Problem for Bounded-Treewidth Graphs. In *28th Annual European Symposium on Algorithms, ESA 2020*, volume 173 of *LIPIcs*, pages 74:1–74:24. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020. doi:10.4230/LIPIcs.ESA.2020.74.
- [65] Karolina Okrasa and Paweł Rzążewski. Fine-Grained Complexity of the Graph Homomorphism Problem for Bounded-Treewidth Graphs. SIAM J. Comput., 50(2):487–508, 2021. doi: 10.1137/20M1320146.
- [66] Guoqiang Pan and Moshe Y. Vardi. Fixed-Parameter Hierarchies inside PSPACE. In 21th IEEE Symposium on Logic in Computer Science (LICS 2006), 12-15 August 2006, Seattle, WA, USA, Proceedings, pages 27–36. IEEE Computer Society, 2006. doi:10.1109/LICS.2006.25.
- [67] M. Pontecorvi and Paul Wollan. Disjoint cycles intersecting a set of vertices. *J. Comb. Theory, Ser. B*, 102(5):1134–1141, 2012. doi:10.1016/j.jctb.2012.05.004.
- [68] Venkatesh Raman and Saket Saurabh. Parameterized algorithms for feedback set problems and their duals in tournaments. *Theor. Comput. Sci.*, 351(3):446–458, 2006. doi:10.1016/j.tcs. 2005.10.010.
- [69] M. S. Ramanujan and Saket Saurabh. Linear-Time Parameterized Algorithms via Skew-Symmetric Multicuts. ACM Trans. Algorithms, 13(4):46:1–46:25, 2017. doi:10.1145/3128600.

- [70] Bruce A. Reed. Mangoes and Blueberries. *Combinatorica*, 19(2):267–296, 1999. doi:10.1007/s004930050056.
- [71] Bruce A. Reed, Neil Robertson, Paul D. Seymour, and Robin Thomas. Packing Directed Circuits. *Combinatorica*, 16(4):535–554, 1996. doi:10.1007/BF01271272.
- [72] Bruce A. Reed, Kaleigh Smith, and Adrian Vetta. Finding odd cycle transversals. *Oper. Res. Lett.*, 32(4):299–301, 2004. doi:10.1016/j.orl.2003.10.009.
- [73] Marcus Schaefer and Christopher Umans. SIGACT news complexity theory column 37. Guest column: Completeness in the polynomial-time hierarchy: Part I: A compendium. *SIGACT News*, 33(3):32–49, 2002. doi:10.1145/582475.582484.
- [74] Larry J. Stockmeyer. The Polynomial-Time Hierarchy. *Theor. Comput. Sci.*, 3(1):1–22, 1976. doi: 10.1016/0304-3975(76)90061-X.
- [75] S. Toda. PP is as hard as the polynomial-time hierarchy. SIAM J. Comput., 20(5):865-877, 1991.
- [76] Christopher Umans. Hardness of Approximating Sigma2P Minimization Problems. In 40th Annual Symposium on Foundations of Computer Science, FOCS 99, pages 465–474. IEEE Computer Society, 1999. doi:10.1109/SFFCS.1999.814619.
- [77] Magnus Wahlström. Representative set statements for delta-matroids and the mader deltamatroid. In Proceedings of the 2024 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 780–810. SIAM, 2024.
- [78] Mingyu Xiao and Jiong Guo. A Quadratic Vertex Kernel for Feedback Arc Set in Bipartite Tournaments. *Algorithmica*, 71(1):87–97, 2015. doi:10.1007/s00453-013-9783-2.

Contents

1	Introduction	1
2	Technical Overview	8
	2.1 Algorithmic Results	8
	2.2 Lower Bounds	13
3	CYCLE-HITPACK Parameterized by $k + \ell$	16
	Step 0: From $k + \ell$ to Feedback Vertex Sets	16
	Step 1: Making the Feedback Vertex Set Undeletable	17
	Step 2: Bounding the Degree of G'	17
	Step 3: Usable Paths and Cycle Packings	19
	Step 4: The Branching Procedure	22
	Step 5: Solving Instances with Promising Sets	25
	3.1 Proof of Lemma 3.9: Finding Vertex-Disjoint Paths	26
4	EDGE-HITPACK Parameterized by $k + \ell$: Single-Exponential Algorithm	28
5	<i>q</i> -CLIQUE-HITPACK Parameterized by Treewidth:	
	Double-Exponential Algorithm	29
6	EDGE-HITPACK Parameterized by Treewidth:	
	Single-Exponential Algorithm	33
7	H-HITPACK Parameterized by Treewidth:	
	Double-Exponential Algorithm	35
	7.1 Dynamic Program	39
	7.2 Correctness	41
	7.3 Running Time	46
8	Cycle-HiтPacк Parameterized by Treewidth:	
	Double-Exponential Algorithm	46
	8.1 Auxiliary procedures	49
	8.2 Dynamic program	54
9	$\Sigma_2^{\mathbf{P}}$ -Completeness Results	56
	9.1 Satisfiability Problems Complete for $\Sigma_2^{\mathbf{P}}$	56
	9.2 $\Sigma_2^{\mathbf{P}}$ -Hardness for TRIANGLE-HITPACK and CYCLE-HITPACK	60
	9.3 $\Sigma_2^{\mathbf{P}}$ -Hardness for H -HITPACK	61
10	Double-Exponential Lower Bounds Parameterized by Pathwidth	66
	10.1 Lower Bound for TRIANGLE-HITPACK	66
	10.2 Lower Bound for SQUARE-HITPACK	73
	10.3 Lower Bound for CYCLE-HITPACK	76
Re	References	