CQBG* : Advanced Academic Team Worker Recommendation **Models**

Mi Wu

ABSTRACT

Collaborator recommendation is an important task in academic domain. Most of the existing approaches have the assumption that the recommendation system only need to recommend a specific researcher for the task. However, academic successes can be owed to productive collaboration of a whole academic team. In this work, we propose a new task: academic team worker recommendation: with a given status: student, assistant professor or prime professor, research interests and specific task, we can recommend an academic team formed as (prime professor, assistant professor, student). For this task, we propose a model CQBG-R(Citation-Query Blended Graph-Ranking). The key ideas is to combine the context of the query and the papers with the graph topology to form a new graph(CQBG), which can target at the research interests and the specific research task for this time. The experiment results show the effectiveness of the proposed method.

KEYWORDS

Network Representation Learning, Teamwork, Collaborator recommendation

ACM Reference Format:

Mi Wu. 2018. CQBG* : Advanced Academic Team Worker Recommendation Models. In Woodstock '18: ACM Symposium on Neural Gaze Detection, June

INTRODUCTION 1

Collaborator recommendation is an important topic in information retrieval and data mining community. It has many application in real world. For example, in technology companies, the program manager may want to form a team to development new produces; in sport competition, a coach may want to find some new team members to strength their ability; in academic community, some researchers may want to form a team to publish some high quality papers.

A lot of works have been done in the academic team recommendation area, these methods usually includes finding experts in a specific area, recommending coauthor for a researcher or finding advisor for an applying student. Despite all the great achievements, there still have some disadvantages. One of the disadvantage of these methods is all the collaborator recommendation is from one Person perspective. However, nowadays' academic achievements

Woodstock '18, June 03-05, 2018, Woodstock, NY

© 2018 Association for Computing Machinery.

ACM ISBN 978-1-4503-9999-9/18/06...\$15.00

https://doi.org/10.1145/1122445.1122456

like interdisciplinary projects or papers often need the efforts of many people in the form of a team. Different people take different roles in the team to extend the boundary of the research. For example, the prime professor needs to point out the direction of the whole project clearly, young assistant professors must have a good understanding of the detail of the research and advise students and PhD students have to come up with some novel ideas and implement the algorithms. In this scenario, recommending collaborators from one Person perspective is on a coarse resolution and makes no sense like recommending an old professor in high position for a first-year PhD student.

In recent years, team formulation has been studied from different aspects like team member replacement and the performance of the whole team with regard to each member. In addition, the development in network representation learning provides effective tools for more challenging recommendation tasks. So, for this research track project, we try academic team worker recommendation. For this task, given some conditions like field: data mining, information retrieval or machine learning, the academic level: student, assistant professor or prime professor and other information, we will recommend the remaining partners in an academic team for these conditions.

To solve this problem, we develped a models CQBG-R(Citation-Query Blended Graph-Ranking). We first extract the text informa-03–05, 2018, Woodstock, NY. ACM, New York, NY, USA, 5 pages. https://doi.org/10.1145/1122445.1122456P dataset and build a citation network according to the collaboration between different researchers, and we call this network CQBG. The contribution can be formed as the follow:

- The first team recommendation work in academic research domain.
- We have combined the topology of the graph and the context information of queries and papers and brought up a novel graph-CQBG(Citation-Query Blended Graph-Ranking).
- · Our model can achieve good academic team worker recommendation performance and interpretability.

RELATED WORK 2

Network Representation Learning 2.1

Network is an important type of data storage. As deep learning has been applied successfully to image and language sequence, researchers try to introduce this powerful tool in to data in the form of network. However, compared to image or language sequence, network lacks a fixed kind of data form, which is easy to be handled. So, Network representation learning has attracted a lot of attention. Network Representation Learning also refers to Network Embedding, which means encoding the information of the whole network into low dimensional vector. Many algorithms of network representation learning have been raised in recent years. Theses algorithms can mainly be divided into two categories:

- Algorithms for network without attributes
- · Algorithms for network with attribute information

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Network without attributes means the network G is composed of (V, E), V is the set of nodes: $\{v_1, v_2, \dots, v_n\}$ and E denotes the set of all edges: $\{e_1, e_2, \dots, e_m\}$. all the information stored in network without attributes is reflected in the topology in the network like the connection between nodes and the degree of nodes. So, algorithms targeting at network without attributes try to encode the topology of network into the low dimensional vector. In this learning process, the vector should be able to reconstruct the whole network. For example, the nodes closed to each other should have similar vectors. Based on such assumption, researchers raise many models like DeepWalk[17]. Algorithms for network without attributes achieve good performance in some tasks. However, networks in real life can be much more complex such as some network's nodes may have content or attribute attached to them or the nodes and edges have various types. For these networks, algorithms like [15, 16, 22] have been raised.

2.2 Collaborator Recommendation

Recommendation systems have been studied for a long time. They range from online websites recommendation [4], mobile applications [23] to academic recommendation [21]. The existing research work about collaborator recommendation can be partitioned into two main categories (Topic based model and non-topic based model). The topic based model could be divided into two subcategories: cross domain recommendation and single domain recommendation. And the non-topic based model could be divided into three subcategories: heterogeneous network based recommendation, homogeneous network based recommendation and non-graph based model. In a real academic network, there are multiple type of attributes among nodes, e.g. people, paper, conference, and there are multiple types of links among nodes, e.g. publish, write. Without considering these information, the performance wouldn't be great. sun et al. [19] proposed a Collaborator Recommendation algorithm on heterogeneous network, which aims at predicting whether two authors in the network who have never co-author before will coauthor sometime in the future. In [20], the authors recommends Collaborators in heterogeneous network according to the similarity between two researchers. They used the number of common meta-path between two researchers to measure the similarity between them. Different from the heterogeneous network based recommendation, it aims at recommending collaborators who work at a specific search topic. In other words, given a specific researcher R and the topic T, e.g. data mining, machine learning, recommendation with Topics will find the candidates who are most likely to work with R on the required topics. Liu et al. [14] proposed an algorithm to solve "Context-aware Academic Collaborator Recommendation". "Context-aware" means considering the topic information when recommend collaborators. Tang et al. [21] proposed a cross domain collaboration recommendation with topic information of researches. Despite its popularity in both industry and research community, only a few of researches have been proposed for collaborator recommendation or team member recommendation, especially for academic domain. So, in our research , we will try recommending academic team for a specific target.

2.3 Graph Reasoning

Graph reasoning has been studied for a long time [10, 12, 13, 25], and it has many applications, such as knowledge graph completion [24], question answering [5, 7–9], fact checking [6, 11, 13], entity alignment [25], recommender system [1, 2] and so on. Under the umbrella of knowledge graph reasoning, conversational question answering is an important task [10].

3 PROBLEM DEFINITION

In this paper, we aim to recommend the top k team members for a user with a specified research interest and a prefer topic. For convenience expression, we also use task query to denote prefer topic in this paper. We denote the name of the user as N, the research interest as r and the prefer topic/task query as q. Here we give an example to show the goal of our task. Assume we want to recommend a team for professor Jiawei Han, and his research interest is Data Mining, his prefer topic is heterogeneous network. And he wants to form a team with three different roles which are (PrimeProfessor, AssistantProfessor, Student). Because Jiawei Han is a prime professor, so our algorithm will recommend two different role researchers to him. These researchers belongs to two different roles which are AssistantProfessor and Student. More specifically speaking, our algorithm will recommend "Yizhou Sun" and "Junheng Hao" to Professor Jiawei Han who are Assistant Professor and PhD Student in University of California, Los Angeles, respectively.

Definition 3.1. Role Role is the group of a user belongs to. e.g.Prime Professor, Assistant professor, Student.

Definition 3.2. Research interest Research interest is the research area of the user.

Definition 3.3. Query Query is the project topic the user like to work, e.g. "Heterogeneous network mining".

Definition 3.4. Citation Graph Citation graph is the graph of citations between users.

Definition 3.5. Query Graph Query graph is the graph got by BM25.

Definition 3.6. CQBG CQBG is the graph merged by Citation Graph and Query Graph.

Symbols	Definition	
ni	the node needed to be recommend	
N	the set of all authors	
$G^l = \{N, E^l\}$	an attributed query graph	
$G^c = \{N, E_G\}$	an attributed data graph	
G = (N, E)	Citation-Query Blended Graph	
q	task query	
$F(n_j n_i,q)$	matching function	
ei	the embedding vector of node v_i	
v_i	the node in the graph	

Table 1: Notations and Definition

Given: A researcher name n_i , the role of the researcher, the research interest r, a task query q and a user input parameter k

Woodstock '18, June 03–05, 2018, Woodstock, NY

Output: The top k team pairs, and each pair and n_i form three width different roles which are (*PrimeProfessor*, *AssistantProfessor*, *Student*).

4 METHODOLOGY

Before the elaboration of our model, we first present the data we used and the information we utilized to construct the graph.

4.1 Dataset

Citation Network ¹ incorporates bibliographic information derived from the mainstream journals and proceedings of computer science. It is a list of items in which each item contains necessary information of one paper, including title, authors, abstract, publishing time, name of conference or journal, citation list (the papers that cited this paper). In detail, the dataset contains 2,244,021 papers and 4,354,534 citations.

4.2 Citation-Query Blended Graph

First we divided the information of one paper into two classes, relation and text data. The relation data contains the author and citation list, contrary to the text data that consists of the title and abstract. To fully leverage these two types of data, we propose the Citation-Query Blended Graph.

Citation Graph. We build the co-authorship graph $G^c(N, E^c)$ based on the relation data, in which each node is denoted by an author and an edge represent the relation between two authors quantified by their past collaborated work. In the research community, for example, the edge weight between two scientists can be related to the number of publications they have collaborated. Here, we count the citations of each paper and sum the citations of papers of they collaborated, as the following.

Given two authors n_i and n_j , the edge weight e_{ij}^c of n_i and n_j is defined as:

$$e_{ij}^c = \sum_{p \in D(n_i, n_j)} C(p),$$

where $D(n_i, n_j)$ is the set of papers where n_i and n_j are collaborated and C(p) is the number of citations of paper p.

Query Graph. Recall that the user will input a task query, which should account for how the works of an author are related to the query. There, we leverage the text data to measure the correlation between the author and the query. First, we make a document for each paper simply by incorporating the title and abstract, denoted by *D*. We use $D(n_i, n_j)$ to represent the papers collaborated by n_i and n_j . By modifying a famous model BM25[18], we assign an edge weight for any two authors, building query graph $G^q(N, E^q)$, as the followings.

Given a query *q* and two authors n_i and n_j , the edge weight e_{ij}^q of n_i and n_j is defined as:

$$e_{ij}^q = \sum_{d \in D(n_i, n_j)} BM(q, d),$$

and

$$BM25(d(n_j),q) = \sum_{w \in q} c(w,q)c'(w,d)\log\frac{|\mathbf{D}|+1}{\mathrm{df}(w)},$$

where

$$c'(w,d) = \frac{(k+1)c(w,d)}{c(w,d) + k(1-b+b\frac{|d|}{\operatorname{avg}(d)})}$$

c(w, q) is the frequency of *w* occurring in *q* and c(w, d) is the frequency of *w* occurring in *d*. **D** is the set of all the documents and df(*w*) is the number of papers having *w*. avg(d) is the average length of all documents. *k* and *b* are two parameters to penalize the length of document and c(w, d).

In this paper, we just use their default value 1.5 and 0.75. **CQB Graph.** With the citation graph and query graph, we blend then into a graph G(N, E).

Given two node n_i and n_j , the edge weight e_{ij} between n_i and n_j is computed as:

$$e_{ij} = \operatorname{Norm}(e_{ij}^c) + \operatorname{Norm}(e_{ij}^l)$$

where Norm() denotes a normalization function,

$$Norm(e_{ij}^{c}) = \frac{e_{ij}^{c} - min\{e_{ij}^{\prime c} : e_{ij}^{\prime c} \in E^{c}\}}{max\{e_{ij}^{\prime c} : e_{ij}^{\prime c} \in E^{c}\} - min\{e_{ij}^{\prime c} : e_{ij}^{\prime c} \in E^{c}\}}$$

and

$$Norm(e_{ij}^{l}) = \frac{e_{ij}^{l} - min\{e_{ij}^{\prime l} : e_{ij}^{\prime l} \in E^{l}\}}{max\{e_{ij}^{\prime l} : e_{ij}^{\prime l} \in E^{l}\} - min\{e_{ij}^{\prime l} : e_{ij}^{\prime l} \in E^{l}\}}$$

Therefore e_{ij} combines two scores out of which one is to measure the work effectiveness of two users and author one is to capture the correlation between the their collaborated works and the query.

Next, we will design a traditional model and a graph representation learning model.

4.3 Hierarchical Tree

Given a worker n_i who needs to be recommended an academic team, we need design a model to rank all the remaining authors. Note that in this paper, we totally assume three roles, which indicates we need recommend other two role for n_i . Therefore, we provide three criteria to estimate the academic level for each author.

Criteria 1: Paper. There, we need two thresholds t_1 and t_2 , $t_1 < t_2$. Let $|D(n_i)|$ be the number of papers n_i published. Then

$$n_i = \begin{cases} \text{prime professor} & |D(n_i)| > t_2\\ \text{assistant professor} & t_2 \ge |D(n_i)| > t_1\\ \text{student} & |D(n_i)| \le t_1. \end{cases}$$

Criteria 2: Citation. Given two thresholds t_1 and t_2 , let $D(n_i)$ be the number of papers n_i published, and C(p) be the number of citations of this paper, $C(n_i) = \sum_{p \in D(n_i)} C(p)$. Then

$$n_i = \begin{cases} \text{prime professor} & C(n_i) > t_2 \\ \text{assistant professor} & t_2 \ge C(n_i) > t_1 \\ \text{student} & C(n_i) \le t_1. \end{cases}$$

Criteria 3: Neighbor. Given two thresholds t_1 and t_2 , let $Degree(n_i)$ be the degree of n_i in G, which indicates the number of authors n_i has collaborated with. Then

¹http://arnetminer.org/citation

	prime professor	$Degree(n_i) > t_2$
$n_i = \langle$	assistant professor	$t_2 \ge \text{Degree}(n_i) > t_1$
	student	Degree $(n_i) \leq t_1$.

In this paper, we used the Criteria 1 to classify all the nodes and t_2 is set as 40 and t_1 is set as 20.

4.4 CQBG-R

Given a worker n_i who needs to be recommended an academic team, we design a model to rank each class nodes respectively. Note that if we know the role of n_i , we only rank other two classes. However, if we do not its role, we will assign a role for n_i estimated by the criteria mentioned above.

Let n_j be a node of a class needed to be scored. Then we design our first model based on two intuitions:

- the recommended author should have good reputation and correlation with the query based on his/her past collaborations with other authors.
- (2) the recommended author should be closed to n_j in order to have low communication cost.

We quantify the first intuition by computing the average weight of n_j , because each edge contains the information of their reputation of collaborated works (e.g., citations) and the correlation of their works with query (e.g., BM25 score), as the followings:

$$I_1 = \frac{\sum_{j' \in N(n_j)} e_{ij}}{|N(n_j)|}$$

where $N(n_i)$ is the set of neighbors of n_i .

To measure the intuition2, we utilize the shortest path in *G*, i.e., they have lower communication cost if they have shorter path, as the followings:

$$I_2 = \frac{1}{|SP(n_i, n_j)|}$$

where $|SP(n_i, n_j)|$ is the shortest path between n_i and n_j in *G*.

Given n_i and q, eventually, we design our model F score for each $n_j \in N, n_j \neq n_i$ as:

$$F(n_j|n_i, q) = I_1 * I_2 = \frac{\sum_{j' \in N(n_j)} e_{ij}}{|N(n_j)||SP(n_i, n_j)|}$$

For each node of each class, we will compute its F score and recommend top authors to n_i .

5 EXPERIMENTS

In this part, we will present some results of CQBG-R and CQBG-NE-R and analyze the results. For CQBG-R model, apart from BM25 model, we also use the TF-IDF model to calculate the score of papers. For CQBG-NE-R model, we use various network embedding model to function as the NE model in CQBG-NE-R model, For randomwalk based methods, we ran RandomWalk, Node2vec and LINE. For GNN based methods, we ran GCN(Graph Convolutional Network)[3] and PAGNN(position aware graph neural networks)[26]. Because our work is the first academic team worker recommendation work, we do not have some baselines to beat and we can only analyze the results based on the citations or past collaborations between the member of the the team. This part has three subsections: the first is the results of CQBG-R model, the second part is the results of CQBG-NE-R model and the third part is the analysis and discussion on the experiments result.

For the experiment part, we conduct three queries: for each query, the role of the researcher is different and the the interest and tasks for the query are also different. For the three query, the role of researcher for the first query is **assistant professor** and the researcher is **Jay Lee**. The research interest is **Data mining** and the task is **heterogeneous network**. The role of researcher for the second query is **prime professor** and the researcher is **Gamal Fahmy**. The research interest of query 2 is **computer security** and the task is **information security**. The role of researcher for the third query is student and the researcher is **David Kuilman**. The research interest for query 3 is **computer networks** and the task is **network algorithm**

5.1 Results of CQBG-R model

For CQBG-R model, we ran two different algorithms: TF-IDF and BM25 to calculate the scores of the papers of filtered candidates.

5.1.1 TF-IDF score calculating result. For TF-IDF score calculating result in Table2, the first two rows are the top@1, top@2recommending academic team for query 1. The middle two rows are the top@1, top@2 recommending academic team for query 2. The last two rows are the top@1, top@2 recommending academic team for query 3. It is all the same for the remaining model results.

Table 2: TF-IDF score calculating result

Priority	Top@1	Top@2
Assistant professor	Terry Coppock	Riichiro Mizoguchi
Student	Haitao Sun	Mathew Scott
Prime professor	Vijayalakshmi Atluri	Anil K. Jain
Student	Pierre-Alain Fouque	Michael K. Reiter
Prime professor	Andreas F. Molisch	Chuang Lin
Assistant professor	Subhabrata Sen	Naixue Xiong

After evaluation, we find that using TF-IDF to calculate the score of papers is not so accurate. For query 2, we observe closely the paper selected for constructing CQBG and find that this paper is not related closely to the querying task.

5.1.2 BM25 score calculating result. the parameters for BM25 score calculating function is set as k = 1.5 and b = 0.75. Using BM25 as papers' score function performs better than TF-IDF such as query3 we find that the two professors recommended have published papers related to it.

CQBG* : Advanced Academic Team Worker Recommendation Models

Table 4: CQBG-PAGNN-R model result

Priority	Top@1	Top@2
Assistant professor	Ram D. Sriram	Qi Hao
Student	Kossi P. Adzakpa	Kondo H. Adjallah
Prime professor	David Wagner	Pierangela Samarati
Student	Christopher Kruegel	Yang Xiao
Prime professor	Xuemin Shen	Serge Fdida
Assistant professor	Ying-Dar Lin	Song Chong

Table 3: BM25 score calculating result

Priority	Top@1	Top@2
Assistant professor	Shih-Chung Kang	Shang-Hsien Hsieh
Student	Jon Wicks	Haoyun Wu
Prime professor	Min Wu	Allen Roginsky
Student	Vern Paxson	Roberto Di Pietro
Prime professor	Robert Schober	C. Siva Ram Murthy
Assistant professor	Bo Sun	Ben Y. Zhao

5.1.3 CQBG-PAGNN-R model result. This model is designed to test the effect of the position on the embedding result. The results in Table 8 show that after adding the position information, the whole framework will recommend some team members, who are close to the querying researcher, which are not what we want.

6 CONCLUSION

To the best of our knowledge, we are the first to focus on academic team recommendation, compared to previous person-based recommendation. This problem is challenging as it involves different roles and different types of data. First, it usually is difficult to gain the real academic level of each author and determine the role they can be. Second, the input of this problem includes a text query, which constrains that the recommended author have to have related experiences with this query.

REFERENCES

- Boxin Du, Lihui Liu, and Hanghang Tong. 2021. Sylvester Tensor Equation for Multi-Way Association. In Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD '21). Association for Computing Machinery, New York, NY, USA, 311–321.
- [2] Boxin Du, Lihui Liu, Jiejun Xu, Fei Wang, and Hanghang Tong. 2023. Neural Multi-network Diffusion towards Social Recommendation. In *arXiv*, Vol. 3. Association for Computing Machinery, New York, NY, USA, 11.
- [3] Thomas N Kipf and Max Welling. 2016. Semi-supervised classification with graph convolutional networks. arXiv preprint arXiv:1609.02907 3, 4 (2016), 3308–3318.
- [4] G. Linden, B. Smith, and J. York. 2003. Amazon.com recommendations: itemto-item collaborative filtering. *IEEE Internet Computing* 7, 1 (Jan 2003), 76–80. https://doi.org/10.1109/MIC.2003.1167344
- [5] Lihui Liu, Yuzhong Chen, Mahashweta Das, Hao Yang, and Hanghang Tong. 2023. Knowledge Graph Question Answering with Ambiguous Query. In Proceedings of the ACM Web Conference 2023. Association for Computing Machinery, New York, NY, USA, 3308–3318.
- [6] Lihui Liu, Boxin Du, Yi Ren Fung, Heng Ji, Jiejun Xu, and Hanghang Tong. 2021. KompaRe: A Knowledge Graph Comparative Reasoning System. In Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery and Data

Woodstock '18, June 03-05, 2018, Woodstock, NY

Mining (KDD '21). Association for Computing Machinery, New York, NY, USA, 3308–3318.

- [7] Lihui Liu, Boxin Du, Heng Ji, ChengXiang Zhai, and Hanghang Tong. 2021. Neural-Answering Logical Queries on Knowledge Graphs. In Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD '21). Association for Computing Machinery, New York, NY, USA, 1087–1097.
- [8] L. Liu, B. Du, J. xu, and H. Tong. 2019. G-Finder: Approximate Attributed Subgraph Matching. In 2019 IEEE International Conference on Big Data (Big Data). Association for Computing Machinery, New York, NY, USA, 513–522.
- [9] Lihui Liu, Boxin Du, Jiejun Xu, Yinglong Xia, and Hanghang Tong. 2022. Joint Knowledge Graph Completion and Question Answering. In Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining. Association for Computing Machinery, New York, NY, USA, 3308–3318.
- [10] Lihui Liu, Blaine Hill, Boxin Du, Fei Wang, and Hanghang Tong. 2023. Conversational Question Answering with Reformulations over Knowledge Graph. arXiv preprint arXiv:2312.17269 3, 4 (2023), 3308–3318.
- [11] Lihui Liu, Houxiang Ji, Jiejun Xu, and Hanghang Tong. 2022. Comparative Reasoning for Knowledge Graph Fact Checking. In 2022 IEEE International Conference on Big Data (Big Data). Association for Computing Machinery, New York, NY, USA, 3308–3318.
- [12] Lihui Liu and Hanghang Tong. 2023. Knowledge Graph Reasoning and Its Applications. In Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining. Association for Computing Machinery, New York, NY, USA, 5813–5814.
- [13] Lihui Liu, Ruining Zhao, Boxin Du, Yi Ren Fung, Heng Ji, Jiejun Xu, and Hanghang Tong. 2022. Knowledge Graph Comparative Reasoning for Fact Checking: Problem Definition and Algorithms. *Data Engineering* 3, 4 (2022), 11.
- [14] Zheng Liu, Xing Xie, and Lei Chen. 2018. Context-aware Academic Collaborator Recommendation. In Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD '18). ACM, New York, NY, USA, 1870–1879. https://doi.org/10.1145/3219819.3220050
- [15] Mingdong Ou, Peng Cui, Jian Pei, Ziwei Zhang, and Wenwu Zhu. 2016. Asymmetric Transitivity Preserving Graph Embedding. In KDD. ACM, New York, NY, USA, 3308–3318.
- [16] Mingdong Ou, Peng Cui, Fei Wang, Jun Wang, and Wenwu Zhu. 2015. Non-transitive Hashing with Latent Similarity Components. In Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '15). ACM, New York, NY, USA, 895–904. https://doi.org/10.1145/2783258.2783283
- [17] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. 2014. DeepWalk: Online Learning of Social Representations. In Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '14). ACM, New York, NY, USA, 701–710. https://doi.org/10.1145/2623330.2623732
- [18] Stephen Robertson, Hugo Zaragoza, et al. 2009. The probabilistic relevance framework: BM25 and beyond. Foundations and Trends[®] in Information Retrieval 3, 4 (2009), 333–389.
- [19] Y. Sun, R. Barber, M. Gupta, C. C. Aggarwal, and J. Han. 2011. Co-author Relationship Prediction in Heterogeneous Bibliographic Networks. In 2011 International Conference on Advances in Social Networks Analysis and Mining. ACM, New York, NY, USA, 121–128. https://doi.org/10.1109/ASONAM.2011.112
- [20] Yizhou Sun, Jiawei Han, Xifeng Yan, Philip S. Yu, and Tianyi Wu. 2011. Pathsim: Meta path-based top-k similarity search in heterogeneous information networks. In *In VLDB*' 11. ACM, New York, NY, USA, 121–128.
- [21] Jie Tang, Sen Wu, Jimeng Sun, and Hang Su. 2012. Cross-domain Collaboration Recommendation. In Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '12). ACM, New York, NY, USA, 1285–1293. https://doi.org/10.1145/2339530.2339730
- [22] Suhang Wang, Jiliang Tang, Charu Aggarwal, Yi Chang, and Huan Liu. 2017. Signed network embedding in social media. In *Proceedings of the 2017 SIAM international conference on data mining*. SIAM, ACM, New York, NY, USA, 327– 335.
- [23] Qiang Xu, Jeffrey Erman, Alexandre Gerber, Zhuoqing Mao, Jeffrey Pang, and Shobha Venkataraman. 2011. Identifying Diverse Usage Behaviors of Smartphone Apps. In Proceedings of the 2011 ACM SIGCOMM Conference on Internet Measurement Conference (IMC '11). ACM, New York, NY, USA, 329–344. https://doi.org/10.1145/2068816.2068847
- [24] Weikai Xu, Lihui Liu, and Hanghang Tong. 2022. ABM: Attention-based Message Passing Network for Knowledge Graph Completion. In 2022 IEEE International Conference on Big Data (Big Data). IEEE, Association for Computing Machinery, New York, NY, USA, 339–348.
- [25] Yuchen Yan, Lihui Liu, Yikun Ban, Baoyu Jing, and Hanghang Tong. 2021. Dynamic Knowledge Graph Alignment. Proceedings of the AAAI Conference on Artificial Intelligence 35, 5 (May 2021), 4564–4572.
- [26] Jiaxuan You, Rex Ying, and Jure Leskovec. 2019. Position-aware Graph Neural Networks. arXiv preprint arXiv:1906.04817 3, 4 (2019), 3308–3318.