WindGP: Efficient Graph Partitioning on Heterogenous Machines

Li Zeng, Haohan Huang, Binfan Zheng, Kang Yang, Shengcheng Shao, Jinhua Zhou, Jun Xie, Rongqian Zhao, Xin Chen Huawei Technologies Co., Ltd, China {zengli43,huanghaohan,zhengbinfan1,yangkang18,shaoshengcheng}@huawei.com

{zhoujinhua1,xiejun1,zhaorongqian,chenxin}@huawei.com

ABSTRACT

Graph Partitioning is widely used in many real-world applications such as fraud detection and social network analysis, in order to enable the distributed graph computing on large graphs. However, existing works fail to balance the computation cost and communication cost on machines with different power (including computing capability, network bandwidth and memory size), as they only consider replication factor and neglect the difference of machines in realistic data centers. In this paper, we propose a general graph partitioning algorithm WindGP, which can support fast and high-quality edge partitioning on heterogeneous machines. WindGP designs novel preprocessing techniques to simplify the metric and balance the computation cost according to the characteristics of graphs and machines. Also, best-first search is proposed instead of BFS/DFS, in order to generate clusters with high cohesion. Furthermore, WindGP adaptively tunes the partition results by sophisticated local search methods. Extensive experiments show that WindGP outperforms all state-of-the-art partition methods by $1.35 \times 27 \times$ on both dense and sparse distributed graph algorithms, and has good scalability with graph size and machine number.

PVLDB Reference Format:

Li Zeng, Haohan Huang, Binfan Zheng, Kang Yang, Shengcheng Shao, and Jinhua Zhou, Jun Xie, Rongqian Zhao, Xin Chen. WindGP: Efficient Graph Partitioning on Heterogenous Machines. PVLDB, 14(1): XXX-XXX, 2022.

doi:XX.XX/XXX.XX

PVLDB Artifact Availability:

The source code, data, and/or other artifacts have been made available at URL_TO_YOUR_ARTIFACTS.

1 INTRODUCTION

Nowadays, many data can be modeled as graphs, such as financial transactions, social network, and road network. With the strong representativity of graphs, researchers as well as industries can find out a lot valuable information by applying graph analysis algorithms (e.g., triangle counting [56], PageRank [42], subgraph matching [55, 59, 61], path finding [57] and Graph Neural Network [23, 43, 50]) on these graph data. In big-data era, distributed graph

computing is widely used to process massive data in academic and industry (e.g., Huawei, Facebook, Google), supporting many important real-life applications such as financial fraud detection [13], social network analysis [37], and online commodity recommendation [15]. Generally, the routine of distributed graph computing includes three parts: computation, communication, synchronization. This is the BSP (Bulk Synchronous Parallel) paradigm [21], which is widely used in many frameworks such as Gemini [67] and PowerGraph [22]. Figure 1 shows that BSP divides the whole process into several sequential supersteps, where a barrier exist between two supersteps. In each superstep, on each machine, the communication occurs after the local computation. In the end of each superstep, all machines are synchronized to ensure that they maintain the correct information before next superstep. Thus, all machines need to wait for the slowest one, causing the long-tail effect [33]. As [33] shows, with the growing data size and data complexity, the performance of distributed computing on billion-scale graphs is far from enough.



Figure 1: The routine of BSP

The quality of graph partition has great impact on the performance of distributed graph computing [3, 62]. If the partition is highly skewed, the overall performance is dragged down by the long-tail effect. Besides, if there are many connections between partitions, the communication cost will become the bottleneck. Therefore, a partition can be called *good* only when it is balanced and the number of cross-partition nodes/edges is small.

A running example of graph partition is given in Figure 2. For vertex-centric partition, the vertices of the original graph *G* is divided into three parts: $\{a, b, c\}, \{d, e\}, \{f\}$. Similarly, the edges of *G* are divided for edge-centric partition: $\{\overline{ab}, \overline{bc}\}, \{\overline{de}, \overline{ef}\}, \{\overline{cf}\}$. The number of cross-partition edges in vertex-centric partition is two because *c* and *e* needs to communicate with *f*. The number of cross-partition nodes in edge-centric partition is also two due to the synchronization of *c* and *f* between two partitions.

This work is licensed under the Creative Commons BY-NC-ND 4.0 International License. Visit https://creativecommons.org/licenses/by-nc-nd/4.0/ to view a copy of this license. For any use beyond those covered by this license, obtain permission by emailing info@vldb.org. Copyright is held by the owner/author(s). Publication rights licensed to the VLDB Endowment.

Proceedings of the VLDB Endowment, Vol. 14, No. 1 ISSN 2150-8097. doi:XXXXXXXXXX

The problem of graph partition on homogeneous machines has been throughly studied, such as [27, 40, 62, 64]. They mainly use two different metric (balance ratio and edge-cut/replication factor) and propose many optimization techniques in graph exploration and greedy selection. All machines are viewed identically and partitions are randomly assigned to these machines.



With the expiration of Moore Law [14], heterogeneous computing is favored by more and more organizations because various heterogeneous hardwares have mushroomed all over the area. On the one hand, machines with different configurations (e.g., CPU cores/frequency, memory capacity, network bandwidth) exist due to the evolution of hardwares [36, 49]. In all data centers, machines are purchased in different decades with different configurations. On the other hand, heterogeneous computing is the trend in super computing area and real-life applications due to better performance and cheaper price. In Telecom field, the machine resource in a region of carrier companies is limited and heterogeneous, where graph algorithms on billions of edges need to be performed locally to search reachable paths or find the cause of network faults. Note that telecom data can not be transfered to cloud computing due to strict data privacy, thus they can only be processed by several low-memory edge servers or even personal computers. As a result, distributed graph computing on heterogeneous machines [35, 45, 53] is becoming more and more important nowadays. This implies higher requirement and new challenges on graph partition methods.

Unfortunately, existing solutions of graph partition do not support heterogeneous machines. Though they can be simply modified to adapt to heterogeneous situations by adding constraints of memory capacity, the results are terrible when measuring quality or running distributed graph algorithms [53]. Previous algorithms (except for [36]) can not generate high-quality graph partition on heterogeneous machines because they do not utilize the characteristics of different machines. Besides, they can not achieve a good balance between computing cost and communication cost. Our techniques address these problems and boost the performance of distributed graph computing on various machines.

Note that the optimization of graph partition is orthogonal to the accelerative techniques of distributed graph algorithms [42, 56]. Though a graph algorithm has different implementations, the performance of each implementation can be further boosted by the improvement of the partition quality. Specifically, the best partition strategies of different graph algorithms may vary [9, 67], but a common base is essential for fast application and extension in realistic systems [22, 67]. Algorithm-specific optimization can be explored base on our generic strategy, which is not in the scope of this paper. Besides, though the computation cost of various tasks are different, it is proportional to the number of nodes or edges [48]. Thus, our solution can be applied to different tasks when given the corresponding amount of work per node/edge.

Our contributions can be concluded below:

- We design a scalable framework of graph partitioning, which can support fast and high-quality edge partitioning on heterogeneous machines.
- Graph-oriented preprocessing techniques are utilized to simplify the metric and balance the computation cost according to the characteristics of graphs and machines.
- Best-first search scheme is proposed instead of BFS/DFS, in order to generate partitions with high cohesion.
- Sophisticated subgraph-local search methods are adopted to tune the partition results adaptively.
- Extensive experiments on both dense and sparse distributed graph algorithms show that WindGP outperforms all state-of-the-art partition methods by 1.35×~27×.

The rest of this paper is organized as follows. Section 2 gives the formal problem definition and reviews state-of-the-art implementations including both vertex-centric and edge-centric methods. Section 3 presents our framework and optimization techniques. The extensions of WindGP is discussed in Section 4. The evaluation of our solution is in Section 5. Finally, Section 6 concludes the paper.

2 BACKGROUND

In this section, we first present the formal definition of our problem, then list the related work. The common notations within the paper are summarized in Table 2.

2.1 **Problem Definition**

DEFINITION 1. (Graph) A graph is denoted as $G = \{V, E\}$, where V is the set of vertices; $E \subseteq V \times V$ is the set of undirected edges. V(G) and E(G) are used to denote vertices and edges of graph G, respectively. Note that \overline{uv} is equivalent to \overline{vu} in undirected graphs.

DEFINITION 2. (Subgraph) Given a graph $G = \{V, E\}$, a subgraph of G is denoted as $G' = \{V', E'\}$, where vertex sets V' and edge sets E' in G' are subsets of V and E, respectively, denoted as $V' \subseteq V$ and $E' \subseteq E$.

DEFINITION 3. (*p-edge Partition*) Given a graph $G = \{V, E\}$, *p* is the number of partitions, then the *p*-edge partition of *G* is denoted as a sequence of subgraphs $EP(G) = \{G_i, \forall i \in [1, p]\}$, such that: (1) G_i is a subgraph of *G* and $\forall u \in V(G_i), \exists uv \in E(G_i);$ (2) $\bigcup_i E(G_i) = E(G)$ and $E(G_i) \cap E(G_j) = \emptyset, \forall i \neq j$. For the *i*-th partition, $V(G_i)$ and $E(G_i)$ can also be simplified as V_i

and E_i .

DEFINITION 4. (Problem Statement) Given a graph $G = \{V, E\}$ and p machines $Machine_i = \{M_i, C_i^{node}, C_i^{edge}, C_i^{com}\}, \forall i \in [1, p],$ the heterogeneous-machine graph partition problem is to find the best edge partition EP(G) that minimizes the total cost TC, where $(1) TC = max_i\{T_i\},$ where $T_i = T_i^{cal} + T_i^{com}$;

(2) $M_i \ge M^{node} \times |V_i| + M^{edge} \times |E_i|$, M_i is the memory size of the *i*-th machine while M^{node} and M^{edge} are the memory occupation of a node and an edge, respectively;

(3) $T_i^{cal} = C_i^{node} \times |V_i| + C_i^{edge} \times |E_i|$, where C_i^{node} and C_i^{edge} are the computing cost of a node and an edge, respectively; (4) $T_i^{com} = \sum_{v \in V_i} \sum_{j \neq i}^{v \in V_j} (C_i^{com} + C_j^{com})$, where C_i^{com} is the commu-

nication cost of the i-th machine;

This paper aims to provide fast and high-quality solutions for the problem of heterogeneous-machine graph partition (Definition 4). Obviously, this problem is edge-centric, i.e., any edge of *G* can only exist in a single partition, but this does not hold for vertex. As heterogeneous machines are rather different from homogeneous configurations, we propose a new metric *TC* to measure the total time cost of each kind of edge partition. *TC* considers both computing cost and communication cost, while the traditional replication factor [51, 62, 64] ($RF = \frac{\sum_{u \in G} |S(u)|}{|V(G)|}$) only considers the communication cost (*S*(*u*) represents the set of partitions that *u* exists).

Equivalence of metrics. The new metric *TC* theoretically corresponds to the load balance and the *RF* metric. In homogeneous cases, T_i^{cal} is proportional to $|V_i|$ or $|E_i|$ according to the design of distributed framework. Besides, assuming $C_i^{com} = 1 \forall i$ and |V(G)| is fixed, we can deduce $\sum_i T_i^{com} = \sum_{u \in G} |S(u)| \times (|S(u)| - 1) = \Theta(RF^2)$, which is consistent with *RF* and both of them can be used to measure the communication cost. Comparative experiments on both dense algorithms (PageRank [42], Triangle [56]) and sparse algorithms (BFS [6], SSSP [17]) shows that *TC* is proportional to the distributed running time with <10% error (see Table 1). Furthermore, given a specific graph algorithm, the computation cost of a node or an edge is the same for different nodes/edges. Therefore, *TC* is used as the metric of partition quality in heterogeneous environments.

NP-Hardness. The problem of heterogeneous-machine graph partition can be proved to be NP-hard for any $p \ge 2$. First, let α' be the balance ratio in [62], the problem of *p*-edge partition with minimal *RF* (i.e., *MIN-RF*(*p*, α')) is NP-hard [5, 62]. Second, the problem of *MIN-RF*(*p*, α') can be reduced to our problem because it is a special case that all machines are homogeneous and the memory size is set to $\frac{\alpha'|E|}{p}$ (let $M^{node} = 0$ and $M^{edge} = 1$).

Quantification of Machine Resource. Similar to [20, 24, 54, 66], the resources of machines can be quantified by relative rates:

- memory capacity: let Mem_i GB be the memory size of each machine, M_i is calculated by $\frac{10^9 \times Mem_i}{4 \times gcd(\{Mem_i\})}$.
- compute ability: each machine multiplies a float-point with an integer, repeat this process many times and yield the averaged *FPTime_i*, then C_i^{node} is $\frac{FPTime_i}{gcd(\{FPTime_i\})}$; C_i^{edge} is computed by two operations (sum and multiplication) and set to $\frac{FPTime'_i}{gcd(\{FPTime_i\})}$.
- network bandwidth: each machine sends/receives 4KB data many times, the averaged time cost is $COTime_i$, thus $C_i^{com} = \frac{COTime_i}{1024 \times gcd(\{FPTime_i\})}$.

In this paper, we assume each node occupies 32 bits and there is no attribute for node/edge computing. Thus, M^{node} is set to $\frac{1}{gcd(\{Mem_i\})}$ and $M^{edge} = 2 \times M^{node}$. If attributes exist in computing, *FPTime* and M^{node} should be multiplied with an appropriate number. Though different graph algorithms have various computing cost for a node or an edge, the total cost is proportional to the number of nodes or

edges, which implies that the quantification of machine resource can be simply combined with specific graph algorithms.

Assume there are three heterogeneous machines and the configuration of machines is $Machine_0 = \{7, 0, 1, 1\}$, $Machine_1 = \{7, 0, 2, 2\}$ and $Machine_2 = \{5, 0, 1, 1\}$ (C_i^{node} is set to 0 for simplicity). Let M^{node} be 1 and M^{edge} be 2. In Figure 2(b), according to Definition 4, a valid edge partition is $\{\overline{ab}, \overline{bc}\}$ on $Machine_0$, $\{\overline{de}, \overline{ef}\}$ on $Machine_1$, and $\{\overline{cf}\}$ on $Machine_2$. The computing cost and communication cost of these machines are $\{2, 2\}$, $\{4, 3\}$ and $\{1, 5\}$, respectively. The corresponding TC is 7, while the RF value is 1.33. In contrast, another solution is $\{\overline{ab}\}$ on $Machine_0$, $\{\overline{bc}, \overline{cf}\}$ on $Machine_1$, and $\{\overline{de}, \overline{ef}\}$ on $Machine_2$, and the corresponding TC and RF are 10 and 1.33. Obviously, the RF remains unchanged, while the TC becomes larger when adjusting the assignment of partitions to machines. Therefore, the existing partition methods that work well on homogeneous machines can generate terrible results on heterogeneous machines.

In this paper, we focus on the partition algorithm on a single machine, i.e., the entire graph G is partitioned by a single machine and the partition results are moved to heterogeneous machines for distributed running. Without loss of generality, we assume that at least one edge partition is feasible for given graph G and machines, and partition G_i is assigned to machine $Machine_i$. Though our solution can be easily extended to process directed graphs, vertex/edge labels or label sets, that is not our focus. Complex optimizations of distributed system (e.g., aggregated communication and overlapping of computation phases) are algorithm-specific, which will be explored in the future. Unless otherwise specified, we use u, N(u), deg(u), num(L), and |A| to denote a vertex, the neighbor set of u, degree of u, the number of currently valid elements in set L, and the size of set A, respectively.

 Table 1: The relationship between TC and distributed running time (unit:s)

Sol.	TC	PageRank	Triangle	SSSP	BFS
HDRF [40]	2.7G	2.3K	0.7K	1K	0.11K
NE [62]	5.6G	4.4K	1.5K	1.8K	0.2K

* The selected graph is TW on 9-machine cluster in the experiment section.

2.2 Related Work

Graph partition problem includes offline partition and streaming partition: offline partition reads the graph data entirely into memory and divide the graph structure; in contrast, streaming partition reads the graph data batch by batch, and it needs to decide the location of nodes/edges in each batch immediately. In this paper, we mainly focus on offline partition. Existing work related to offline graph partition can be mainly divided into two categories: vertex-centric partition (a.k.a., edge-cut) and edge-centric partition(a.k.a., vertexcut).

Vertex-centric Partition. The edge-cut solutions divide vertices of graph *G* into different partitions, ensuring the load balancing and minimizing the edge-cut. This can be formulized as $max_{i \in [i,p]}|V_i| \le \frac{\alpha'|V|}{p}$ and $min\{\sum_{\overline{uv}\in G} S(u) \neq S(v)\}$. Some earlier solutions uses random hash to assign a partition for each vertex *v*, e.g., f(v) = hash(v)%p. Though the random hash is very fast, it destroys the

graph locality, thus has high edge-cut value. In contrast, METIS [27] adopts a multi-level paradigm, which makes better use of the locality. However, it is rather slow and has prohibitive memory occupation on large graphs. Later, LDG [44] and Fennel [47] utilize graph locality in a simpler way: put adjacent nodes together in one partition to reduce edge-cut. Greedily, they assign the vertex *u* to the partition that has the most neighbors of *u*. Overall, on scale-free graphs whose degrees follow power-law distribution, some super nodes have > 10^6 edges, which can cause severe bottleneck in a single machine due to load imbalance and terrible communication. Therefore, edge-centric partition is preferred on large power-law graphs.

Edge-centric Partition. The vertex-cut solutions divides edges of graph G into different partitions, ensuring the load balance and minimizing the vertex-cut metric (i.e., replication factor). This can be formulized as $max_{i \in [i,p]} |E_i| \le \frac{\alpha' |E|}{p}$ and $min\{RF\}$. Some earlier solutions (e.g., PowerGraph [22]) intuitively use greedy algorithms, prioritizing the partitions that have two endpoints of the given edge. In order to reduce RF, [22] limits the number of replication for each vertex to $2\sqrt{p}$ in the algorithm design. DBH [51] and Ginger [9] utilize the power-law distribution and ensure that edges of low-degree vertices are put together. More advanced HDRF [40] computes a score for each partition when assigning an edge e and choose the partition with the highest score. The main difference is that for each edge \overline{uv} , HDRF selects the partition that u or v has the largest partial degree, while DBH selects the partition that u (assuming deg(u) < deg(v)) resides in. The state-of-the-art algorithms are NE [62] and EBV [64]. By linear graph exploration, NE generates the partitions one by one and achieves the lowest RF currently. It improves the locality of each subgraph (partition G_i) by choosing node u that have the lowest $|N(u) \setminus V_i|$ during exploration. However, NE has two main shortcomings, which limit its performance. On the one hand, NE neglects nodes that have large $|N(u) \cap V_i|$ but $|N(u) \setminus V_i|$ is not the minimum. Thus, it selects low-deg nodes frequently, which can generate a long-tail DFS search path with tiny cohesion. For example, in Figure 3, NE chooses the sequence ('A', 'B',...,'F') rather than the node 'G' that has more connection with V_i . On the other hand, NE may stop extending the current partition on high-degree nodes, causing high communication cost. The latest algorithm EBV quantifies the proportion of replicated vertices and the balance of vertices/edges assignment as significant parameters. It also sorts the order of edges by the sum of end-vertices' degrees from small to large. In this way, it can accelerate the processing of power-law graphs by alleviating the imbalance of communication between multiple machines.



Figure 3: The shortcoming of NE

Both of the two kinds of solutions above can only support homogeneous machines. They can not guarantee on generating feasible partitions on heterogeneous machines and the quality of partition is unacceptable even if some solution exists. Besides, existing solutions mainly optimize for power-law graphs, but there are still some real-life graphs that are not scale-free, e.g., mesh-like graphs road. Heterogeneous Distributed Computing. Distributed computing on big data has been well studied [7, 34], but in graph computing we need to utilize the characteristics of both graphs and clusters. Recently, the heterogeneous computing on deep neural network (DNN) arises [26, 32], which leads the trend of enabling heterogeneous resources. The literature includes two works for heterogeneous graph algorithms: [49] only consider different computing power, while GrapH [36] targets at various communication cost. [49] coarsen G first, then partition it and finally project it back to G. GrapH uses streaming partition and group machines into different clusters according to their network traffic. Due to the lack of collaborative optimization on machines with heterogeneous memory, computing power and network traffic, none of them can achieve a good balance between computation and communication. They use different framework and can not be combined with other solutions directly, thus we compare WindGP with them in Section 5.4. HaSGP [66] considers the heterogeneity of both computing and communication, but it has three limitations: (1) neglects different memory capacity; (2) as a streaming algorithm, lacks optimization in subgraph locality; (3) targets at high-bandwidth network and considers multi-core conflict. In its experiments, only four and 32 nodes are used and the heterogeneity of both computing and communication are not considered in the same cluster. Besides, heterogeneous computing is mainly used in low-end scenarios whose network bandwidth is far smaller than memory bandwidth, thus limiting the application of HaSGP. The state-of-the-art HAEP [65] adopts the same metrics (balance ratio α' and replication factor RF) as homogeneous cases, and proposes heuristic neighbor expansion to improve subgraph locality. However, α' and RF can not depict the quality of heterogeneous partition well, as analyzed in Section 2.1. In addition, HAEP includes both computing and communication heterogeneity in the same cluster, but still omits the memory heterogeneity. Furthermore, the maximum cluster and the maximum dataset only contain 32 nodes and 117M edges respectively, which is not enough to prove the scalability.

Variants. For large graphs, the memory of a single machine is not enough, thus we need streaming partition or distributed partition. In some scenarios, the graph data come as time series, this can only be handled by streaming algorithms [2, 39]. Generally, hashbased methods perform terrible on communication cost, but they can adapt to streaming graph partition naturally. With the rising of AI techniques, learning-based partition also develops a lot. For example, GAP [38] is an approximated edge-cut algorithm based on graph neural network.

Optimization Methods. Heterogeneous-machine graph partition problem is closely related to *combinatorial optimization*. Exact methods like branch and bound [29] can find exact solution for small-size problem. Open-source and commercial solvers like COIN-OR CBC [16], ZIB SCIP [19] and GUROBI [4] have integrated powerful heuristics and can solve medium problems within acceptable time. However, in realistic applications that have billions of edges and millions of nodes, exact methods can hardly find a feasible solution due to the exponential complexity of computation. Thus, approximation methods and local search methods [25] and [41] have been proposed.

G	graph to be partitioned
<i>v</i> , <i>u</i>	vertices in a graph or subgraph
Gi	the <i>i</i> -th partition of G
V_i, E_i	the node set and edge set of G_i
M ^{node} , M ^{edge}	the memory occupation of a node and an edge,
	respectively
Machine _i	the <i>i</i> -th machine
$M_i, C_i^{node}, C_i^{edge}, C_i^{com}$	the memory size, the computing cost of a
	node, the computing cost of an edge and the
	communication cost of a node in the <i>i</i> -th ma-
	chine, respectively
$T_i, T_i^{cal}, T_i^{com}$	the total cost, computing cost and the commu-
	nication cost the <i>i</i> -th machine, respectively
<i>S</i> (<i>u</i>)	the set of partitions that <i>u</i> exists
<i>N</i> (<i>u</i>)	the neighbor set of vertex u in G
$N_i(u)$	the neighbor set of vertex u in G_i
deg(u)	the degree of vertex u in G
$deg_i(u)$	the degree of vertex u in G_i
n _{i,j}	the number of replica nodes between partition
	<i>i</i> and <i>j</i>
L	The size of set L
num(L)	the number of currently valid elements in set
	L
δ_i	the precomputed capacity of partition G_i
$I_B(v)$	the indicator function: whether v exists in
	other partition
α', RF	the load balance ratio and the replication fac-
	tor in homogeneous partitioning, respectively
α	the threshold controlling the balance between
	$N(u) \setminus S$ and $N(u) \cap S$
β	the threshold controlling the impact of border
	vertices
Ŷ	the threshold of edges above which partitions
	should be destroyed
θ	the proportion of edges to be removed in a
	partition
N_0, T_0	the number of local and global try times

Table 2: Notations

3 ALGORITHM

3.1 Overview

In this section, we propose a comprehensive and general edge partitioning algorithm WindGP, which can divide the original graph *G* to *p* subgraphs $G_i = (V_i, E_i)$ (*p* subgraphs corresponding to *p* machines), where $E_i \cap E_j = \emptyset$, $\forall i \neq j$ with low communication cost and balanced calculation cost. This algorithm consists of three main parts. Firstly, the upper bound (δ_i) of the edge set $(|E_i|)$ is obtained by *graph-oriented preprocessing*, which can provide a good guidance for the partition expansion in the second part. Secondly, for each partition E_i , edges are iteratively added to E_i by *best-first search* until $|E_i| \geq \delta_i$. Thirdly, our post-processing performs *subgraph-local search* on the initial solution $\{E_i | 1 \leq i \leq p\}$ obtained in the previous two steps to generate a better solution $\{E_i^*\}$ with lower total cost *TC* (see Definition 4). Note that the previous two steps can generate a good solution with higher quality than traditional algorithms, which means the final local search may not be performed if the running time is limited (e.g., in real-time graph processing scenarios). The overview of our framework is in Figure 4.



Figure 4: The framework of WindGP

3.2 Graph-oriented Preprocessing

The first part of our algorithm is to compute the upper bound $(|\delta_i|)$ for each subgraph $G_i, \forall i \in [1, p]$. Recall that the objective function in the problem statement tries to minimize the maximum of the sum of calculation time and communication time. Obviously, the optimal δ_i corresponds to the optimal partition and the computation of optimal δ_i is also NP-hard. Thus, we convert the problem to a lightweight mixed integer programming (MIP) problem by utilizing graph characteristics. Note that calculation time of each machine is solely determined by the number of edges and vertices of G_i . In contrast, the communication time is much complicated and much harder to be balanced. Experiments on graphs with hundreds of edges show that the calculation time is nearly balanced in the optimal solution, while the communication time is not. This inspires us to balance the calculation time first, which results in a near-optimal solution space. Thus, we need to assign appropriate upper bound for each subgraph to achieve the balance. Further improvement can be achieved by the final post-processing, which may slightly disturb the balance of calculation to get better solutions. In this way, the computation of optimal δ_i can be formulated below:

minimize λ

subject to
$$\sum_{i} |E_{i}| = |E|$$
$$|E_{i}| \leq \frac{M_{i}}{M^{edge} + M^{node} \times |V_{i}|/|E_{i}|} \quad \forall 1 \leq i \leq p \quad (1)$$
$$\lambda \geq C_{i}^{edge} |E_{i}| + C_{i}^{node} |V_{i}| \quad \forall 1 \leq i \leq p$$
$$|E_{i}| \in \{1, 2, \dots, |E|\} \quad \forall 1 \leq i \leq p$$

where $(|E_i|, |V_i|, |E|, |V|)$ means the number of elements of (E_i, V_i, E, V) , respectively. Here auxiliary decision variable λ represents the maximum calculation time of each machine and our objective is to minimize λ . The first constraint shows that the sum of these capacities is equal to the edge size of the original graph *G*. In addition, the memory occupation in each subgraph should not exceed the memory

size of the corresponding machine, as shown in the second constraint. Furthermore, the third constraint requires that the maximum calculation time is not smaller than the calculation time of each machine. Finally, the fourth constraint indicates that all capacities should be integers within [1, |E|].

To further simplify the problem, the vertex set size of machine *i* (i.e., $|V_i|$) can be replaced by the average ratio in the entire graph as $|V_i| = \frac{|V|}{|E|} \times |E_i|$. This simplification works because each partition is expected to be a "normal" graph which has characteristics similar to the original graph *G*. In practice, the number of edges is much larger than that of vertices even on sparse graphs (usually 10 ~ 100×), not to mention dense graphs. Besides, the computation of a vertex is usually less costly than the computation of an edge. Therefore, this simplification is error-bounded, and in all experiments it does not affect the search of optimal solutions. After the simplification, let $C_i = C_i^{edge} + \frac{|V|}{|E|} \times C_i^{node}$, the original equations are equivalent to

minimize
$$\lambda$$

subject to $\sum_{i} |E_{i}| = |E|$
 $(M^{edge} + M^{node} \times |V|/|E|)|E_{i}| + \alpha_{i} = M_{i}$
 $C_{i}|E_{i}| - \lambda + \beta_{i} = 0$
 $|E_{i}| \in \{1, 2, ..., |E|\}$

$$(2)$$

where $\{\alpha_i, \beta_i \ge 0 | 1 \le i \le p\}$ are auxiliary variables used to convert inequalities into equations. The above MIP problem has p+1 decision variables and 2p + 1 constraints.

3.2.1 Exact Method. General integer programming (IP) problems have been proven to be NP-hard [10]. As a generalization of IP, MIP problems are also NP-hard and viewed as one of the most challenging areas in applied mathematics. Most of the state-of-the-art MIP solvers (e.g., ZIB Scip [19] and Gurobi [4]) implements a tree search algorithm framework called branch-and-bound [29], and they can solve the problem efficiently if the machine number is not too large. However, as the data volume and the computing power grow exponentially [12], there are many application scenarios where the problem becomes too large to process for a MIP solver. To resolve this issue, we propose a graph-oriented heuristic that can help solve the MIP problem iteratively.

Algorithm 1: Computing the bound δ_i for edge partitions
Input: $ E , C_i^{edge}, M_i, \forall i \in [1, p]$
Output: $o_i, \forall i \in [1, p]$
1 procedure GeneratingCapacity($ E , C_i^{eage}, M_i$)
2 $R = E , I = \{1, 2,, p\}$
3 while $R > 0$ do
$4 \qquad T = \sum_{i \in I} \frac{1}{C_i}$
5 for $i \in [1, p]$ do
6 if δ_i already allocated then
7 continue
8 $\delta_i^1 = \frac{R}{T} \times \frac{1}{C_i}$
9 $\delta_i^2 = \frac{ M_i }{M^{edge} + M^{node} \times V / E }$
10 if $\delta_i^1 > \delta_i^2$ then
11 $\delta_i = \delta_i^2, R \leftarrow R - \delta_i, I \leftarrow I \setminus \{i\}$
12 return $\delta_i, \forall i \in [1, p]$

3.2.2 Graph-oriented Heuristic. The intuition behind the heuristic is straightforward. If we omit the heterogeneous memory sizes of machines, in the best case the calculation time should be the same for each machine. Based on this claim, we try to allocate edges to each machine so that their computation time is a constant (i.e., let $C_i \times \delta_i = \omega, \forall i \in [1, p]$). Thus, we have $|E| = \sum_i \delta_i = \omega \sum_i \frac{1}{C_i}$, and δ_i can be calculated by $\frac{|E|}{\sum_i \frac{1}{C_i}} \times \frac{1}{C_i}$. However, the computed edge size may exceed the memory size of the machine. In such cases, we choose to limit its edge size with respect to the memory size of the corresponding machine.

Algorithm 1 lists the details of our heuristic. The algorithm first estimates the capacity of the edge set for each machine, i.e., δ_i^1 . Then it checks whether δ_i^1 meets the constraint of memory size. If the memory consumption exceeds the memory size, we fix its edge set capacity so that both the memory size constraint and the integer constraint are respected. The same process is repeated recursively for the remaining machines and remaining edge number until no edge is left.

LEMMA 1. If not consider the integer constraints, Algorithm 1 can find the optimal solution.

PROOF. Apparently, our solution can find the optimal if all machine's memory is enough (Line 10 never occurs). Let $f(E, p) = \lambda$, we have $f(E, p) \ge f(E', p)$ when E > E'. By mathematical induction, we assume f(E, p) is optimal $\forall E' < E$. For specific *E* and *p*, assume *i* is the machine that satisfies Line 10, then all of M_i is used by Algorithm 1 and $f(E_i, 1) < f(E - E_i, p - 1)$. If this is not optimal, it must be $E_i^* < E_i$ in the optimal solution $f^*(E, p)$, thus $f(E - E_i, p - 1) < f^*(E - E_i^*, p - 1)$, which violates the optimal condition.

THEOREM 1. Approximation Error Bound Compared with the optimal solution for Equation 2, the error bound of Algorithm 1 is $\frac{p^2}{|E|}$.

PROOF. If δ_i^1 is not integer and is smaller than δ_i^2 , we always use the flooring integer. If this not optimal, we can compare the difference with the optimal (using the ceiling integer). The difference part is only one edge, thus we have $f(E + 1, p) - f(E, p) \le C_i$ and $f(E, p) - f^*(E, p) \le pC_i$ as in each iteration at least one partition can be decided. $f^*(E, p) \ge \frac{|E|C_i}{p}$, thus the error is bounded by $\frac{pC_i}{|E|C_i} = \frac{p^2}{|E|}$.

In general settings ($|E| > 10^7$), the error bound is much smaller than $\frac{1}{10}$. Experiments in Section 5.2 also verifies the quality of Algorithm 1.

Analysis. In each round, at least one machine is allocated or all remaining machines are allocated. Thus, the number of rounds is bounded by *p*. Within each round, two *for* loops are needed excluding the variables that can be pre-computed (e.g., C_i , $\sum_i \frac{1}{C_i}$ and δ_i^2). Overall, the time complexity of Algorithm 1 is $O(p \times 2p + p) = O(p^2)$, which is far more efficient than the exponential-complexity MIP solvers. This makes the preprocessing the least time-consuming part in the entire WindGP algorithm as *p* (usually < 10³) is much smaller

than the size of graph G (~ 10⁷). The space complexity is linear (O(p)), which can be deduced simply.

3.3 Partition Expansion: Best-first Search

Once the edge set capacities are computed for each machine, we can generate *p* partitions for these machines one by one. Specifically, for machine *i*, edge set E_i is selected from the working partition G_i containing all unassigned edges so far. The number of edges in each partition is strictly restricted by the capacity, thus the computation cost is marginally balanced on heterogeneous machines. The next challenge is the balance of communication cost, which is the goal of this section. Let core set C be the set of vertices whose unassigned edges are all allocated successfully in current machine and boundary set S be the vertex set covered by E_i . During each iteration, one vertex v_{sel} is selected for expansion according to the strategy below. Degree Balanced Generation. Heuristically, vertices with lower degree and shorter distance (from new candidate vertices to the core set *C*) are preferred. If $S \setminus C = \emptyset$, v_{sel} is selected by the *vertexSelection* procedure, which can be designed from perspective of degree and distance instead of naive random selection. Otherwise, in order to improve the subgraph cohesiveness, we focus on both two kinds of edges $(N(u) \setminus S$ and $N(u) \cap S$), while NE only considers the first kind. Considering two nodes u and v such that $|N(u) \setminus S| = |N(v) \setminus S|$ and $|N(u) \cap S| > |N(v) \cap S|$, u is preferred because it contributes to higher cohesiveness. A hyper-parameter $\alpha(0 \le \alpha \le 1)$ is built to control the balance:

$$v_{sel} = argmin_{v \in S \setminus C}[|N(v) \setminus S| - \alpha |N(v) \cap S|]$$

= $argmin_{v \in S \setminus C}[|N(v) \setminus S| - \alpha (|N(v)| - |N(v) \setminus S|)]$ (3)
= $argmin_{v \in S \setminus C}[(1 + \alpha)|N(v) \setminus S| - \alpha |N(v)|]$

In practice, α can be fine tuned to improve the performance.

Border Generation. In order to reduce the communication cost, we pay more attention to the *border vertex* (i.e., vertices that exist in multiple machines). Obviously, for a border vertex v, its communication cost is smaller if v only exists in two machines. Let B bet the set of all border vertices that have been found. Namely, B should be updated with all border vertices of partition i after the expansion procedure of partition i finishes. Let I_B be the indicator function as follow:

$$I_B(v) = \begin{cases} 1, & \text{if } v \in B\\ 0, & \text{if } v \notin B \end{cases}$$
(4)

During the expansion, we prefer the border vertices controlled by a hyper-parameter β ($0 \le \beta \le 1$). Combined with the Degree Balanced Generation strategy, we define the final priority function as follow:

$$v(v) = (1+\alpha)|N(v) \setminus S| - (\alpha + I_B(v)\beta)|N(v)|$$
(5)

And,

n

$$v_{sel} = argmin_{v \in S \setminus C} w(v) \tag{6}$$

The tuning of α and β is in our experiments.

The combination of degree balanced generation and border generation is called the *Best-First Search*, which is superior to traditional breadth-first search (BFS) or depth-first search (DFS). During the graph exploration, BFS maintains a frontier queue and expand these frontiers one by one, then it inserts new frontiers to the queue. In contrast, best-first search expands from one of the frontiers that have the minimum w(v) and update the frontier queue. Our method is better than NE expansion [62], because NE only consider the size of $N(v) \setminus S$ and may generate long-tail DFS paths (as analyzed in Section 2.2).

Taking Figure 5 as a specific example, let *X*, *Y* and *Z* be the candidate vertices and *X* be the node that exist in previous partitions, i.e., $X \in B$. The thick edges are the "incoming" edges, namely the edges connecting to set *S*, and the thin edges are the "outgoing" edges. Assuming that $\alpha = 0.3$ and $\beta = 0.3$, we have w(X) = (0.3 + 1)*2-(0.3+0.3*1)*4 = 0.2, w(Y) = (0.3+1)*2-(0.3+0)*5 = 1.1, w(Z) = (0.3 + 1)*2 - (0.3 + 0)*4 = 1.4. Consequently, the vertex *X* should be expanded in current step.



Figure 5: An example of vertex expansion

The entire procedure of our heuristic expansion is shown in Algorithm 2, while the update rule of core set and boundary set is described in Algorithm 3. To generate one edge partition E_i , WindGP expands from a selected vertex iteratively until the size of this partition exceeds the capacity δ_i (computed in Section 3.2). During each iteration, the vertex v with the minimum w(v) is selected if the candidate set is not empty; otherwise, the vertex is chosen from all remaining vertices in V. Once v is decided, *AllocEdges* procedure (Algorithm 3) is called to expand v and process the 1-hop and 2-hop neighbors of v. Note that $D = N(x) \setminus S$ are new boundary nodes, and the edges between D and previous boundary set are moved from E to E_i . These new added edges belongs to the remaining edge set E rather than E(G) and they also include \overline{xy} (Line 6 of Algorithm 3). Finally, the border vertex set B is supplemented with the new generated border vertices in current partition.

Analysis. All edges are allocated in Algorithm 3, thus the total time complexity of calling *AllocEdges* in Algorithm 2 is $O(|E_i|)$ as each edge is only removed once from *E*. In practice, the operation of vertex selection in Line 5 and Line 7 can be accelerated by *Min*-*Heap* [18], and the heap size is bounded by V_i . Therefore, the total complexity of these two lines is $|V_i| \log |V_i|$ as the *While* loop is executed at most V_i times (i.e., each vertex only enters the heap once). Besides, the set operations (including set union, set intersection and set minus) can be implemented by *bitmap* [58], which can optimize the complexity of Algorithm 2 is $O(|E_i| + |V_i| \log |V_i|) = O(|E_i| + |V_i| \log |V_i|)$. As for space complexity, the set structure *C* and *S* contain no more than V_i nodes, thus the space complexity is

 $O(|V_i| + |V(G)| + |E_i|) = O(|V(G)| + |E_i|)$ except for the storage of the entire graph *G*.

Algorithm 2: Generate one edge partition E:				
Input: $E(G) \setminus \sum_{j \le i} E_j, V, \delta_i, \alpha, \beta, B$				
Output: <i>E_i</i>				
1 procedure $EXPAND(E(G) \setminus \sum_{j < i} E_j, \delta_i)$				
$2 C, S, E_i \leftarrow \emptyset$				
3 while $ E_i \leq \delta_i$ do				
4 if $S \setminus C = \emptyset$ then				
5 $x \leftarrow vertexSelection(V \setminus C)$				
6 else				
7 $x \leftarrow$				
$argmin_{v \in S \setminus C}[(1+\alpha) N(v) \setminus S - (\alpha + I_B(v)\beta) N(v)]$				
8 AllocEdges(C, S, $E_i, x, E \setminus \sum_{j < i} E_j$)				
9 $B \leftarrow B \cup (S \setminus C)$				
10 return E _i				

Algorithm 3: Allocate edges for core vertex x

rocedure $AllocEdges(C, S, E_i, x, E)$				
$C \leftarrow C \cup \{x\}, S \leftarrow S \cup \{x\}$				
3 foreach $y \in N(x) \setminus S$ do				
$S \leftarrow S \cup \{y\}$				
foreach $z \in N(y) \cap S$ do				
$E_i \leftarrow E_i \cup \{\overline{yz}\}$				
$E \leftarrow E \setminus \{\overline{yz}\}$				
if $ E_i \geq \delta_i$ then				
return				

3.4 Post-Processing: Subgraph-local Search

In this section, Subgraph-Local Search (SLS) is proposed to improve the partition generated by previous stages. According to [25, 41], the quality of edge partition result can be enhanced by moving or swapping edges between partitions. By utilizing the characteristics of local subgraph, SLS iteratively finds a better solution in the neighborhood of current solution. The operator of designing a neighborhood in the solution space and finding better solution by SLS is critically important. A "good" operator should not only specify the promising neighborhood that leads to better solutions, but also avoid getting stuck in local optimal. In this paper, we design two SLS operators. The first one is the destroy-and-repair operator that aims to find better solutions, and the second one is the re-partition operator that attempts to get escaped from local optima. We first apply the first operator to current result and count the number of consecutive fail-to-improve times. If it exceeds the pre-determined threshold (N_0 , set to 5 by default), the current result is viewed as local optimal and the re-partition operator is applied. Algorithm 4 gives the main procedure.

Destroy-and-Repair. When applying the destroy-and-repair operation, part of the current partition is removed by a destroy step and rebuilt by a repair step while the remaining part is preserved. In the destroy step, the non-optimal part is specified for future reconstruction. Hence there are two key decisions: the first one is

1 p	rocedure SLS($\{E_i 1 \le i \le p\}, T_0, N_0, k$)
2 /*	* N ₀ and T ₀ are the number of local and global try times,
	respectively */
3 W	while $T_0 > 0$ do
4	if $DestroyRepair(\{E_i 1 \le i \le p\})$ then
5	$n \leftarrow 0$
6	else
7	$n \leftarrow n+1$
8	if $n \geq N_0$ then
9	$REPARTITION(\{E_i 1 \le i \le p\}, k)$
10	$n \leftarrow 0$
11	$T_0 \leftarrow T_0 - 1$

which machines to destroy, and the second one is which edges to destroy in the selected machine. A quantile parameter γ is leveraged to decide the threshold (Line 4 of Algorithm 5), and machines with time cost above this threshold are destroyed. For each destroyed machine, a proportion θ ($0 < \theta < 1$, set to 1% by default) of total edges are removed. The *last-in-first-out* rule is adopted to select the edges to be removed, because in this way the connectivity of edges can be preserved in current machine. By adjusting γ , we can control the threshold, which is $min{T_i}$ and $max{T_i}$ when γ is 0 and 1 respectively. In our work, γ is set to 0.9 by default, which is easier for repairing.





In the repair step, the key point is to decide the most suitable machine for each destroyed edge when reconstructing the partition. A greedy heuristic is used to balance the assignment. For each destroyed edge e, we first select the machines where endpoints of e already exist. If more than one machine is selected, we select the machine that has the lowest time cost.

Re-partition. When the destroy-and-repair operator fails to improve the current partition, it may be a local optimum. Methodologically, diversification of SLS operators is needed to deal with this case, because different operators construct different types of neighborhood. In our method, a re-partition operator is applied. We specify k subgraphs from current partition $\{E_i | i \in I, I \subseteq \{1, 2, ...p\}, |I| = k\}$, and apply Algorithm 2 on the union of these subgraphs to get new partitions while the unselected partitions keeps unchanged. In such a way the partitions among the selected machines is fully changed. Hence, this move is in a scale larger than destroy-and-repair, and it is promising to get escaped from local optimum. When choosing the subset I for re-partition, we first select the subgraph G_i with the largest $T_i = T_i^{cal} + T_i^{com}$, then select k - 1 subgraphs $\{G_j\}$ with the maximum $n_{i,j}$ from remaining partitions, where $n_{i,j}$ is the number of replica nodes between G_i and G_j .

Analysis. In destroy-and-repair procedure (Algorithm 5), $\theta|E_i|$ edges are selected to be reassigned. For each edge, we need to greedily

Algorithm 5: destroy-and-repair

1 **procedure** DestroyRepair($\{E_i | 1 \le i \le p\}$) **2** for i = 1, 2, ..., p do $T_i = T_i^{com} + T_i^{cal}$ 3 4 $thd \leftarrow min_{1 \le i \le p}T_i + \gamma * (max_{1 \le i \le p}T_i - min_{1 \le i \le p}T_i)$ 5 $S \leftarrow \emptyset$ 6 for *i* = 1, 2, ...*p* do if $T_i \ge thd$ then 7 $C \leftarrow Remove and get a proposition of \theta edges in E_i$ 8 $S \leftarrow S \cup C$ 9 10 $\{T_i^{com}\}, \{T_i^{cal}\}, \{T_i\} \leftarrow UpdateObjective(\{E_i | 1 \le i \le p\})$ 11 for $\overline{xy} \in S$ do $A(x) \leftarrow \{i | x \in V_i, 1 \le i \le p\}$ 12 $A(y) \leftarrow \{i | y \in V_i, 1 \le i \le p\}$ 13 if $A(x) \cap A(y) \neq \emptyset$ then 14 $i \leftarrow BalancedGreedyRepair(A(x) \cap A(y), \{T_i\})$ 15 if (i = 0) or $(A(x) \cup A(y) \neq \emptyset$ and $A(x) \cap A(y) = \emptyset$) then 16 $i \leftarrow BalancedGreedyRepair(A(x) \cup A(y), \{T_i\})$ 17 **if** (i = 0) or $A(x) \cup A(y) = \emptyset$ then 18 $i \leftarrow BalancedGreedyRepair(\{1, 2, ...p\}, \{T_i\})$ 19 $E_i \leftarrow E_i \cup \{\overline{xy}\}$ 20 $\{T_i^{com}\}, \{T_i^{cal}\}, \{T_i\} \leftarrow UpdateObjective(\{E_i| 1 \leq i \leq i \leq i \})$ 21 *p*}) 22 if objective TC is improved then return true 23 24 else return false 25

Algorithm 6: BalancedGreedyRepair				
1 procedure BalancedGreedyRepair($S, \{T_i\}$)				
2 $v \leftarrow infinity$				
$j \leftarrow 0$				
4 for $i \in S$ do				
5 $criteria \leftarrow T_i$				
6 if criteria < v and (memory of partition i is enough) then				
7 $v \leftarrow criteria$				
8 $j \leftarrow i$				
9 return <i>j</i> ;				

search the most suitable machine among all *p* machines. Thus, the time complexity of destroy-and-repair is O(p|E|) and the space complexity is O(|E|). In re-partition procedure (Algorithm 7), the worst-case time complexity is equivalent to Algorithm 2 (i.e., O(|E| + |V|log|V|)), while the space complexity is O(|V| + |E|). In Algorithm 4, the running time of the entire SLS algorithm is bounded by a threshold T_0 , which limits the number of iterations that SLS performs. In practice, the number of iterations is usually a small constant (<10), thus the time complexity is $O(p|E| + |E| + |V|\log |V|) = O(p|E| + |V|\log |V|)$.

To sum up, the total time complexity of WindGP can be computed by accumulating three phases:

$$Time = O(p^{2} + \sum_{i} (|E_{i}| + |V_{i}| \log |V_{i}|) + T)$$

= $O(p^{2} + p|E| + |V| \log |V|)$ (7)

Algorithm 7: Re-partition

1	procedure REPARTITION($\{E_i 1 \le i \le p\}, k$)
2	$i \leftarrow argmax_{1 \le j \le p} \{T_j\}$
3	$q \leftarrow k$ -th largest value among $\{n_{i,j} j \neq i\}$
4	$I \leftarrow \{j n_{i,j} > q, j \neq i\} \cup \{i\}$
5	$E' \leftarrow EXPAND(\cup_{m \in I} E_m, \delta)$
6	return $E' \cup \{E_j j \notin I\}$

And the space complexity can be formulized as:

$$Space = O(p + max_i|E_i| + |V| + |E| + |V| + |E|)$$

= $O(p + |V| + |E|)$ (8)

Obviously, both the time complexity and the space complexity of WindGP are linear to the graph size.

4 EXTENSIONS

In this section, we discuss several extensions of our algorithm (WindGP). Though WindGP focuses on solving the problem defined in Definition 4, it can be generalized to more scenarios such as *directed labelled graph*, *vertex-centric partition* and *Map-Reduce based system*.

Directed Graph and Labelled Graph. For directed graphs, WindGP can be adjusted by distinguishing incoming/outgoing edges as well as in/out degrees in Algorithm 2, i.e., the way of graph traversal changes. Real-life graphs may contain many node/edge labels (e.g., properties or features), which also need to be stored and computed. In order to process these property graphs, we maintain the mapping (f) between node/edge ID and label sets. The graph structure is partitioned first, then the label sets are assigned to corresponding partition by the mapping f. Note that the calculation costs of a node and an edge (i.e., C_i^{node} and C_i^{edge} , respectively) as well as the memory occupation (M^{node} and M^{edge}) need to be increased according to the size of label sets.

Vertex-Centric Partition. Except for edge-centric partition, vertexcentric partition is also frequently used in real applications. However, the research of edge-cut on heterogeneous machines is still blank. Though WindGP is originally designed for vertex-cut, it can adapt to edge-cut simply. Firstly, WindGP needs to generate the result of edge partition (i.e., *p* partitions). For each vertex *u*, it may exist in several machines. Let $deg_i(u)$ and deg(u) be the degree of *u* in G_i and *G*, respectively, We need to re-assign all vertices to *p* machines according to the current edge partition. Intuitively, if we place vertex *u* in machine *j* with larger partial degree of *u*, the *edge-cut* of *u* should be smaller. Thus, each vertex *u* should be placed in the *k*-th machine with the maximum $\frac{deg_k(u)}{deg(u)+1}$ as long as machine *k* is not full. Finally, we enumerate all edges of *G* and put each edge \overline{uv} in the partitions that *u* and *v* belong to.

Map-Reduce based system. The routine of distributed running is different on map-reduce based systems such as GraphX [52] and Giraph [1]. The communications can only occur after all local calculations are over, as shown in Figure 7. In this case, the execution time should be $max_i(max_i(T_{cal}^i) + T_{com}^i)$, which is different from *TC* defined in Definition 4. This can also be processed well by our 3-phase mechanism, while the only difference is the object goal in the post-processing phase.



Figure 7: The routine of Map-Reduce based Graph Engine

Streaming graph partition on heterogeneous machines is also fascinating, but it is rather different from our algorithms, thus we leave it to future work. Besides, modern graphs have tens of billions of edges or trillions of attributes, which is hard to be partitioned by a single machine. For example, Graph Neural Network (GNN) usually has embeddings with hundreds of features [63]. Therefore, distributed graph partition on heterogeneous machines is also an interesting direction.

Except for the variants, we can also extend WindGP algorithm to support multi-threading for speedup. For example, Algorithm 3, Algorithm 5 and Algorithm 6 can be accelerated by *OpenMP* to utilize multiple cores in the running machine.

5 EXPERIMENTS

We evaluate our method WindGP as well as all counterparts on a machine running CentOS 7 system with 24 Intel E5-2690 2.60GHz cores, 128GB memory and 1TB disk. WindGP is implemented with C++ and compiled with g++ 7.3.0, and the optimization flag is set to -O2. According to the experiments of previous work [62, 64], we select four state-of-the-art algorithms as counterparts: METIS [27], HDRF [40], NE [62], EBV [64]. To provide a fair comparison, we modify these algorithms to meet the requirement of heterogeneousmachine edge partition, i.e., adding constraints of memory capacity of each machine. Note that METIS is originally a vertex-centric method, thus we transform it into the edge-centric solution in the same way discussed in [62]: with the node degree as the node weight, it partitions G using *qpmetis* command, then assigns each edge \overline{uv} to the machine that u or v exists randomly as long as the machine has enough memory. In our experiments, the main metric is the TC score (Definition 4), which measures the quality of partition results. Besides, the running time of distributed graph algorithms on different partition results is also evaluated in Section 5.4. The comparison with heterogeneous solutions [36, 49, 65, 66] is included in the final part.

5.1 Dataset

We mainly evaluate all solutions on some representative dataset in the Stanford Network Analysis Project (SNAP [31]) such as TW (Twitter [28]), CO (com-Orkut), LJ(soc-LiveJournal), PO (soc-Pokec), CP (cit-Patents [30]) and RN (roadNet-CA). The details of these datasets are listed in Table 3. Besides, we also use a synthetic

Table 3:	Statistics	of Datasets

Name	V	E	MD^1	Type ²
CO	3,072,441	117,185,083	33,313	rs
LJ	4,847,570	33,099,465	20,290	rs
PO	1,632,803	30,622,564	20,518	rs
CP	3,774,768	16,518,947	793	rs
RN	1,965,206	2,766,607	8	rm
TW	41,652,230	1,202,513,046	3M	rs
DB	233M	1.1B	17M	rs
FR	65M	1.8B	5.2K	rs
YH	417M	2.8B	2.5K	rs

¹ Maximum degree of the graph.

² Graph type: r:real-world, s:scale-free, and m:mesh-like.

generator (R-MAT [8]) to generate a series of power-law graphs for the scalability test in Section 5.3. In Section 5.4, graphs with billions of edges are used for distributed graph computing because modern graph and machine resource are usually very large.

To eliminate the influence of randomness in some algorithms (e.g., NE [62]), all tasks are run 10 times and the averaged result is recorded as the metric. In our experiments, the executing time of all partition algorithms is required to be smaller than 1 hour (for graphs with billions of edges) and 10 minutes (for other datasets), respectively.

Machine Configuration. The quantification of machine resource is detailed in Section 2.1, and experiments are done on different homogeneous clusters to verify the feasibility of our methodology.

We mainly use two types of machines: *super machine* and *normal machine*. For simplicity, M^{node} and M^{edge} are set to 1 and 2 respectively. Recall that in Definition 4, the configuration of each machine is a quadruple: $(M_i, C_i^{node}, C_i^{edge}, C_i^{com})$. On large graphs (e.g., TW and CO), there are 100 machines (20 super machines and 80 normal machines), and the configuration of super machine and normal machine is $(10^8, 10, 15, 15)$ and $(3 \times 10^7, 5, 10, 10)$, respectively. In contrast, there are 30 machines (10 super machines and 20 normal machines) on other datasets and the configuration is $(10^7, 10, 15, 15)$ and $(3 \times 10^6, 5, 10, 10)$. In Section 5.3, we also study the impact of the number of machine types and the machine number.

Parameter Tuning. Several hyper-parameters are used in our solution as well as others. For each algorithm, comprehensive tests are conducted on all datasets and the best parameter is found out for each dataset. In WindGP, α and β are both set to 0.3, and other parameters like γ and θ keep the default value as specified in Section 3. The details of hyper-parameter tuning in WindGP is listed in Table 4, 5, 6, 7, 8, and 9. Lookup in Table 2 for the meaning of these hyper-parameters.

As for α , it controls the balance between $N(u) \setminus S$ and $N(u) \cap S$. On LJ, CP and RN, the average degree is low (<7), thus the longtail effect caused by small $N(u) \cap S$ is more prominent. While on other high-degree graphs, much larger $N(u) \setminus S$ generates too many borders which raises the communication cost. Overall, the best value is set to 0.3 for α .

As for β , it controls the impact of border vertices. On graphs with low average degree, border vertices are much fewer, thus the impact of border vertex number and $N(u) \setminus S$ are both slight. In contrast,

Т	able	4:	Tuning	of α	in	WindGP
---	------	----	--------	-------------	----	--------

TC	0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9
TW	64M	62M	61M	60M	61M	62M	65M	70M	76M	85M
CO	34M	32M	31M	31M	32M	33M	36M	39M	45M	52M
LJ	34M	28M	25M	23M	23M	24M	25M	25M	27M	28M
РО	25M	23M	21M	21M	21M	23M	25M	29M	33M	38M
СР	20M	15M	12M	11M	11M	11M	12M	13M	13M	14M
RN	26M	20M	17M	15M	15M	16M	18M	18M	19M	19M

there are too many borders on TW, CO and PO, raising *TC* in two directions. Overall, the best value is set to 0.3 for β .

According to Algorithm 5 in Section 3.4, γ is the threshold of edges above which partitions should be destroyed. When γ is set to 1, only partitions with the maximum cost will be destroyed, which limits the improvement of subgraph-local search. Once γ decreases, *TC* drops rather slightly with much higher executing time. For example, the best *TC* is achieved by $\gamma = 0$, but the speedup is <9%, while the executing time of post-processing is >10 times longer. Besides, as the subgraph-local search needs several iterations, only a small percentage of partitions should be destroyed in each iteration. Thus, the best value is set to 0.9 for γ .

To select a appropriate proportion of edges in each destroyed machine, we vary γ from 0.002 to 0.02 and evaluate *TC*. Obviously, too small γ limits the optimization space of *destroy-and-repair*, while γ larger than 0.1 does not bring extra gain. In conclusion, θ is set to 1% by default.

As for the number of local and global try times N_0 and T_0 , a thorough study is conducted that varies them from 1 to 9 for each dataset. To sum up, it is enough to set $N_0 = 5$, and the best value of T_0 varies on different graphs.

5.2 Evaluation by the metric *TC*

Analysis of optimization techniques. Recall that WindGP propose three novel techniques: preprocessing capacity, best-first search, post-processing. To evaluate the efficiency of each technique in WindGP, we conduct the experiments on six real graphs and depict the results in Figure 8. Let WindGP be the entire solution, WindGP⁺ denotes the solution that removes post-processing from WindGP. Similarly, WindGP^{*} denotes the solution that removes best-first search from WindGP⁺, while WindGP⁻ is the naive solution without all optimization techniques, which iteratively explores the graph to form a partition as long as the machine memory and load balance ratio permit. Its expansion scheme is similar to NE [62], which tends to form a subgraph with high cohesion by connectivity-based expansion. In order to view the details of all partitions precisely, the histograms of the costs of different partitions on CP and LJ are also listed in Figure 9, Figure 10 and Figure 11, respectively.

Obviously, *TC* of WindGP* is much lower than WindGP⁻, and the speedup is $5 \times$ on TW, $4.5 \times$ on CO, $3.3 \times$ on LJ, $3.8 \times$ on PO, $7.5 \times$ on CP, and $8.8 \times$ on RN, respectively. This prominent improvement comes from the pre-computed capacity of edges in each machine. Different from the naive solution that only considers the upper bound of machine memory and homogeneous load balance ratio, our strategy combines the computation cost and the memory size of all machines to generate a nearly best plan that can balance the computation cost across these heterogeneous machines (as shown in Figure



Figure 8: Comparison of different techniques in WindGP $(\ln TC)$ is the logarithm of TC)

9(b) and Figure 10(b)). Note that traditional partition methods use $\frac{|E|}{p}$ as the capacity of edges, which can not be used in heterogeneous scenarios because the memory of some machines may be not enough while other machines may have memory size larger than $\frac{|E|}{p}$. Besides, the traditional threshold does not distinguish the difference of node/edge computation cost between heterogeneous machines. Recall that in Section 3.2 we deduce the error bound $\frac{p^2}{|E|}$, and the experiment on small graphs with hundreds of edges shows that the difference between our solution and the optimal is always within 5%, which can be further refined by the post-processing. According to the theoretical bound, on larger graphs the error should be much smaller.

The second technique (i.e., the best-first search) further boosts the performance by optimizing the expansion process, leading to > 1.1× on TW, CO and LJ. The performance gain is mainly acquired by lowering the total communication cost (as shown in Figure 9(c) and Figure 10(c)). The degree balanced generation as well as border generation can help reduce the number of cross-machine vertices and improve the subgraph cohesion. However, on low-degree graphs (CP and RN), the speedup is rather limited (only ~ 1.04×) due to the small percentage of communication cost. On CP, the percentage of communication cost is < 30% on sparse graphs (i.e., graphs with low average degree $\frac{|E|}{|V|}$), while it is > 50% on LJ and CO. Especially, the effect is tiny on RN because it is mesh-like graph and its structure is naturally balanced.

Finally, the post-processing technique (subgraph-local search) brings > $1.15 \times$ speedup by flattening the total cost between all

Table 5:	Tuning	of β	in	WindGP
----------	--------	------------	----	--------

TC	0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9
TW	80M	71M	65M	60M	61M	62M	64M	64M	67M	70M
CO	42M	37M	33M	31M	32M	33M	33M	33M	34M	34M
LJ	24M	24M	23M	23M	24M	25M	25M	25M	26M	27M
PO	30M	25M	22M	21M	22M	22M	24M	25M	25M	26M
CP	13M	13M	12M	11M	11M	12M	12M	13M	14M	15M
RN	15M	15M	15M	15M	15M	15M	16M	17M	17M	17M

Table 6: Tuning of y in WindGP

TC	0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
TW	58M	58M	58M	58M	59M	59M	60M	60M	60M	60M	68M
CO	30M	30M	30M	30M	31M	31M	31M	31M	31M	31M	33M
LJ	22M	22M	22M	22M	22M	23M	23M	23M	23M	23M	25M
PO	20M	20M	20M	20M	21M	21M	21M	21M	21M	21M	23M
CP	10M	10M	11M	12M							
RN	15M	16M									

Table 7: Tuning of θ in WindGP

TC	0.002	0.004	0.006	0.008	0.01	0.012	0.014	0.016	0.018	0.02
TW	67M	65M	64M	63M	60M	60M	60M	60M	60M	60M
CO	40M	38M	35M	33M	31M	31M	31M	31M	31M	31M
LJ	25M	25M	24M	24M	23M	23M	23M	23M	23M	23M
PO	26M	24M	23M	23M	21M	21M	21M	21M	21M	21M
CP	12M	12M	12M	11M	11M	11M	11M	11M	11M	11M
RN	16M	15M	15M	15M	15M	15M	15M	15M	15M	15M

Table 8: Tuning of N₀ in WindGP

TC	1	2	3	4	5	6	7	8	9
TW	68M	64M	62M	61M	60M	60M	60M	60M	60M
CO	35M	34M	32M	32M	31M	31M	31M	31M	31M
LJ	25M	24M	23M						
PO	25M	24M	22M	22M	21M	21M	21M	21M	21M
CP	12M	12M	11M						
RN	16M	15M							

Table 9: Tuning of T₀ in WindGP

TC	1	2	3	4	5	6	7	8	9
TW	70M	66M	64M	63M	61M	61M	60M	60M	60M
CO	35M	33M	32M	32M	32M	31M	31M	31M	31M
LJ	26M	24M	24M	23M	23M	23M	23M	23M	23M
PO	25M	23M	22M	22M	21M	21M	21M	21M	21M
CP	12M	11M							
RN	17M	15M							

machines. Note that the previous two techniques balance the computation cost and the communication cost respectively, however, they do not balance the total cost well. In fact, the effect of best-first search is sometimes restricted because it can not disturb the balance of computation cost. Besides, during expansion the information is not complete (e.g., the first partition has no communication cost), which further drags down the performance. Subgraph-local search breaks this restriction by allowing the computation cost to be imbalanced between heterogeneous machines, as long as the total cost drops. Based on the global view with complete information, it moves or swaps edges between machines to lower the highest total cost.

Comparison with counterparts. Figure 12 lists the comparison of WindGP (the entire solution) with the state-of-the-art algorithms on heterogeneous machines. As reported in previous work [62], METIS can not partition too large graphs like TW due to its prohibitive memory occupation. Among four counterparts, NE performs the best on most datasets except for CP and RN. The two low-degree graphs have relatively larger computation cost and lower communication cost, thus the expansion scheme of NE can not optimize a lot. In contrast, METIS and HDRF perform better on CP and RN due to their elaborated consideration of computation cost in the partition objective. As for EBV solution, though it is carefully designed to reduce the impact of skew on power-law graphs, its objective is not equivalent to the maximum total cost and it can not be well adapted to heterogeneous cases.

WindGP outperforms all counterparts by > $3.7 \times$ speedup on all power-law graphs. Especially, on enormous social network like TW and CO, the improvement is $1 \sim 2$ orders of magnitudes. This fantastic effect is produced by the perfect combination of three novel techniques in WindGP, which not only address the difference between heterogeneous machines, but also leverage the characteristics of graphs. The improvement is more prominent when the graph is larger and more skewed, because higher computation and communication cost implies larger optimization space. Though the performance of WindGP is limited on mesh-like graphs like RN, it still brings $1.35 \times$ speedup. To sum up, WindGP shows $1.35 \times 27 \times$ speedup compared with the state-of-the-art partition algorithms.



Figure 11: The histogram of partitions of WindGP on CO

cluster on LJ

5.3



Figure 12: Comparison of different partition algorithms ($(\ln TC)$ is the logarithm of TC))

Due to the lightweight preprocessing and limited iterations in post-precessing, the complexity of WindGP is linear to the graph size and machine number, which is similar to NE. As for the executing time of partition methods, Table 11 shows that their executing time is in the same scale, while WindGP is 11% slower than NE, Scalability Test bility with the graph s

Alg.

HDRF

NE

WindGP

Scalability with the graph size. To evaluate the scalability of graph size, we use the same configuration of machines as on Twitter. R-MAT generator [8] is used to generate eight scale-free graphs, with the number of edges range from $\sim 4 \times 10^6$ to $\sim 5 \times 10^8$ (nearly double each time). The parameters of R-MAT follow the setting of Graph 500 [11]. The ratio of the graph's edge count to its vertex count

which is acceptable in real cases as partitioning is not time sensitive.

Besides, extra experiments (Table 10) with the best two counterparts

(HDRF and NE) show that the performance of WindGP on homoge-

neous clusters is not worser than others, as Section 2.1 proves that

the *TC* metric is equivalent to load balance and *RF* in homogeneous scenarios. Furthermore, the running time of distributed graph algo-

rithms on the partition results is also evaluated (see Section 5.4),

Table 10: Evaluation of PageRank on homogeneous 30-machine

RF

3.33

1.55

1.56

TC

105M

19M

20M

time (s)

92

18

18

which corresponds to the comparative results of TC.

 α'

1.1

1.1

1.0

Table 11: Evaluation of partitioning time (s) on traditional methods

Dataset	METIS	HDRF	NE	EBV	WindGP
CO	200	15	80	91	89
LJ	71	5	23	30	25
PO	68	4	21	24	23
СР	32	3	12	14	13
RN	6	1	2	2.3	2.1

(i.e., half the average degree of a vertex in the graph) is 16. The "scale" factor is the logarithm base two of the number of vertices and it starts from 18 and increases by 1 each time. Details of these synthetic graphs are listed in Table 12.

Table 12: Statistics of Graph 500 Datasets

Name	V	E	MD^1	Type ²
S18	262,144	3,800,348	25,707	s
S19	524,288	7,729,675	41,358	s
S20	1,048,576	15,680,861	67,086	s
S21	2,097,152	31,731,650	107,400	s
S22	4,194,304	64,097,004	170,546	s
S23	8,388,608	129,250,705	272,176	s
S24	16,777,216	260,261,843	431,690	s
S25	33,554,432	523,467,448	684,732	s

¹ Maximum degree of the graph.

² Graph type: r:real-world, s:scale-free, and m:mesh-like.



Figure 13: The scalability with Graph 500 datasets

The experimental result is shown in Figure 13. Obviously, the performance of WindGP is still the best when transferring to Graph 500 datasets. WindGP not only has the minimum *TC* on all graphs (S18 ~ S25), but also displays the slowest growth as the graph size increases. Generally, the curve of WindGP has a \leq 1.8 slope. In contrast, the curves of other algorithms all show > 2 slope. Though the average degree remains the same, larger generated graphs are more skewed and has larger communication cost when partitioned. Our best-first search as well as the post-processing play a significant

role when reducing the communication cost. As a result, WindGP performs well even on graphs with billions of edges.

Scalability with the machine number. We select LJ dataset and vary the machine number from 30 to 90 (increasing by 15 for each). The ratio of super machines is all set to $\frac{1}{3}$. Figure 15 shows the result. Generally, TC drops as the machine number increases, because more resources can be utilized to balance the cost. However, the drop tends to be tiny when the machine number is larger than 30 (called saturation point), which is the default setting for LJ. Inherently, the saturation point is decided by the number of communities in the dataset. Though more machines can help reduce the computation cost, the communication cost also rises if high-cohesion subgraph is separated into different machines. For the same reason, NE and EBV do not fully utilize these machines, as they tend to place as many edges as possible in several super machines to minimize the communication cost. In contrast, WindGP performs well on all settings. If the machine number is lower than saturation point, WindGP utilizes more machines to store major subgraphs; otherwise, it treats added machines as temporary buffers for post-processing.



Figure 14: The scalability with the machine number on LJ

Scalability with the number of machine types. In previous experiments, we use two kinds of machines by default. Here we vary the number of machine types from one to six and test the performance on LJ with 30 machines. The added type is extracted from normal machines, increase the machine memory, computation and communication cost. Note that the 2-type setting here is different from the default setting. Compared to the single-type setting (i.e., homogeneous cases where all machines are normal machine), 2-type setting transforms 5 machines to slightly bigger machine with larger computation and communication cost as well as larger memory size.

Generally, TC increases as the number of machine types grows, i.e., the homogeneous cases achieve the minimum TC for all solutions. Note that NE performs extremely good on homogeneous cases, even better than WindGP. However, both NE and EBV fail to adapt to heterogeneous cases and their TC rises sharply when the number grows. Comparatively, WindGP achieves the slowest growth due to its flexible preprocessing technique, which can pre-computes appropriate edge capacities for all machine settings. Thus, WindGP is not sensitive to the number of machine types.



Figure 15: The scalability with the number of machine types on LJ

5.4 Evaluation of Distributed Graph Algorithms

To evaluate the real performance of distributed graph computing, we choose PageRank [42] and Single-Source Shortest Path ([17]) and perform the test on Plato system [46]. These two algorithms are the most representative dense and sparse algorithms, respectively. In PageRank, all edges are computed and all nodes are updated in each iteration. In contrast, the number of active nodes as well as edges grows first until the largest point, then reduces until the end. Modern machines have large memory and computing power, thus graphs with billions of edges are added in this section. Except for TW, referring to [66] and [60], we add DB (0.23B nodes and 1.1B edges), FR (65M nodes, 1.8B edges), and YH (0.41B nodes and 2.8B edges). Similar to [62], we use nine machines connected with Gigabit Ethernet, and $\frac{1}{3}$ of them are super machines. The resource of the real cluster is listed below:

- 3 super machines: 1.6GHz (4), 6GB memory, 100Gbps
- 6 normal machines: 1.6GHz (8), 2GB memory, 150Gbps

The memory capacity, computation cost and communication cost of each machine $(M_i, C_i^{node}, C_i^{edge} \text{ and } C_i^{com})$ is estimated according to the quantification process in Section 2.1. Note that the machine configuration is different from previous settings, thus *TC* is also evaluated. Table 14, 15, 16 and 17 list the comparison of *TC* and distributed running time (seconds).

Comparison with Non-heterogeneous Solutions. Compared with non-heterogeneous solutions, WindGP has the lowest *TC* value on all datasets, and the improvement is rather prominent (>6×) on enormous skewed graphs (TW and DB, the maximum degree is 3M and 17M respectively). FR and YH have relatively much smaller skew (the maximum degree is 5.2K and 2.5K respectively), thus the speedup of WindGP is restricted to $3 \times \sim 4 \times$. For most cases, a reduction of *TC* (i.e., the estimated total cost) means a reduction in the running time of distributed graph computing as the partition

quality is improved. This further verifies the analysis in Section 2.1 that *TC* is nearly proportional to the distributed running time. Though the optimization effect of our techniques is tiny on mesh-like graphs like RN, the running time still drops a little thanks to our sophisticated post-processing technique which considers all kinds of corner cases. The running time of both PageRank and SSSP is much larger than that on homogeneous machines, because the distributed computing on heterogeneous machines is much more complicated. Super machines have large memory but high computation and communication cost, while the case of normal machines is reversed. This limits the optimization space if all normal machines are full, which corresponds to the analysis in Section 5.3.

Comparison with Heterogeneous Solutions. As shown in Table 13, when compared with heterogeneous solutions ([49], GrapH, HaSGP, HAEP), WindGP also shows > $1.49 \times$ and > $1.39 \times$ speedup in the running time of PageRank and SSSP respectively, as it performs collaborative optimization on machines with heterogeneous memory capacity, computing power and network bandwidth. Note that the speedup is calculated by comparing WindGP with the best counterpart HAEP. None of the counterparts takes care of the heterogeneous memory capacity, thus they can not compete with WindGP when optimizing the computation cost. Specifically, [49] only optimizes load balance while [36] targets at communication cost. Thus, the computing time of [49] is similar to ours, but its communication time is ~50% longer. [36] has >20% longer computing time, and its communication time is also ~18% longer as it lacks the bestfirst search and comprehensive subgraph-local tuning. HaSGP is a streaming partition algorithm, which performs terrible when running on severely skewed graphs like TW and DB. The degree distribution of FR and YH is much more balanced, thus [49] performs better than GrapH as it balances the computation cost better while existing communication-optimized methods (NE, GrapH, HAEP) have nonprominent effect on these two graphs. Inherently, most nodes have the same scale of neighbors, and there is no significant difference when we select which one as the boundary. However, WindGP can optimize this case well because the border generation in Section 3.3 restricts the border vertex to reside in as fewer machines as possible.

Comparing PageRank and SSSP, obviously the speedup on PageRank is always higher than that on SSSP. The biggest difference is on DB, which has the largest degree skew and the lowest averaged degree (i.e., 4.7) among four large graphs. In PageRank, all nodes need to join each iteration while only partial nodes are active in SSSP. The largest skew enlarges the optimization space of WindGP in PageRank, while the lowest averaged degree limits our techniques in SSSP (just like the cases in mesh-like RN). This indicates that WindGP works well on dense algorithms like PageRank, but further improvement can be developed on sparse algorithms like SSSP.

To sum up, compared with existing non-heterogeneous and heterogeneous solutions, WindGP successfully reduces the *TC* metric as well as the running time of distributed graph computing for all graphs. On average, WindGP reduces *TC* and the distributed running time by $1.9 \times -6.7 \times$ and $1.4 \times -5.7 \times$, respectively. As for the executing time of heterogeneous partition methods, Table 11 shows that the gap is not prominent.

DataSet			Pag	geRank			SSSP					
DataSet	[49]	GrapH	HaSGP	HAEP	WindGP	speedup	[49]	GrapH	HaSGP	HAEP	WindGP	speedup
TW	1287	681	1,015	529	353	1.49×	667	309	618	254	182	1.39×
DB	1168	609	970	501	280	1.78×	621	305	597	226	158	1.43×
FR	2,017	2,259	2,380	1,307	681	1.92×	1,132	1,218	1,846	580	312	1.86×
YH	3,204	3,980	3,012	2,201	1,048	2.1×	1.910	2,203	2,018	1,038	509	2.04×

Table 13: Distributed running time of heterogeneous algorithms (unit:s)

Table 14: The TC metric on nine machines

Dataset	HDRF	NE	WindGP
TW	2,790,667,265	5,649,273,080	401,478,360
СО	938,849,480	565,506,575	189,439,055
LJ	182,987,265	205,252,940	57,918,640
PO	278,052,160	196,995,825	50,954,100
СР	106,732,065	195,154,235	31,504,615
RN	9,632,230	61,151,165	4,950,860

Table 15: Performance of distributed graph computing (unit:s)

Data		PageRar	ık	TriangleCount				
Data	HDRF	NE	WindGP	HDRF	NE	WindGP		
TW	2,380	4,417	353	1,046	1,520	182		
CO	791	398	125	325	147	97		
LJ	112	201	54	33	33	25		
PO	130	187	41	29	22	18		
CP	64	166	27	11	12	11		
RN	11	52	9	7	9	5		

6 CONCLUSIONS

We introduce a graph partitioning algorithm WindGP, which supports fast and high-quality partitioning on heterogeneous machines. WindGP consists of three phases: preprocessing, graph exploration, post-processing. First, novel preprocessing is utilized to simplify the metric and balance the computation cost according to the characteristics of graphs and machines. Besides, best-first search is proposed instead of BFS/DFS, in order to generate communities with high cohesion. Furthermore, subgraph-local search is adopted to tune the partition results adaptively. Experiments on real-world graphs show that WindGP outperforms the state-of-the-art partition methods by $1.35 \times 27 \times$. In future, targeting at specific graph algorithms (e.g., PageRank), WindGP can be further enhanced by utilizing algorithmic characteristics.

DataSet	TC			PageRank			SSSP		
	HDRF	NE	WindGP	HDRF	NE	WindGP	HDRF	NE	WindGP
TW	2.7G	5.6G	0.4G	2,380	4,417	353	1,046	1,820	182
DB	2.5G	4.2G	0.3G	2,146	3,709	280	965	1,227	158
FR	5.1G	4.4G	1.0G	5,012	4,183	681	1,398	1,260	312
YH	6.8G	5.9G	1.7G	8,149	5,980	1,048	2,012	1,865	509

Table 16: Performance of distributed graph computing (unit:s)

 Table 17: Distributed running time of heterogeneous algorithms (unit:s)

Data		PageRa	ık	TriangleCount			
	[49]	GrapH	WindGP	[49]	GrapH	WindGP	
TW	1287	681	353	667	309	182	
CO	411	208	125	198	116	97	
LJ	98	81	54	32	31	25	
PO	201	126	41	38	27	18	
CP	53	108	27	18	20	11	
RN	10	32	9	7	21	5	

 Table 18: Evaluation of partitioning time on heterogeneous methods

Dataset	[49]	GrapH	HaSGP	HAEP	WindGP
TW	105	92	91	112	101
DB	109	90	90	110	108
FR	156	137	138	170	152
YH	301	218	210	312	293

REFERENCES

- 2018. Apache Giraph. In Encyclopedia of Social Network Analysis and Mining, 2nd Edition, Reda Alhajj and Jon G. Rokne (Eds.). Springer.
- [2] Zainab Abbas, Vasiliki Kalavri, Paris Carbone, and Vladimir Vlassov. 2018. Streaming Graph Partitioning: An Experimental Study. *Proc. VLDB Endow.* 11, 11 (2018), 1590–1603.
- [3] Yaroslav Akhremtsev, Peter Sanders, and Christian Schulz. 2020. High-Quality Shared-Memory Graph Partitioning. *IEEE Trans. Parallel Distributed Syst.* 31, 11 (2020), 2710–2722.
- [4] Bob Bixby. 2007. The gurobi optimizer. Transp. Re-search Part B 41, 2 (2007), 159–178.
- [5] Florian Bourse, Marc Lelarge, and Milan Vojnovic. 2014. Balanced graph edge partition. In *The 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, KDD '14, New York, NY, USA - August 24 - 27, 2014*, Sofus A. Macskassy, Claudia Perlich, Jure Leskovec, Wei Wang, and Rayid Ghani (Eds.). ACM, 1456–1465.
- [6] Aydin Buluc and Kamesh Madduri. 2011. Parallel Breadth-First Search on Distributed Memory Systems. In IEEE International Conference on High Performance Computing, Data, and Analytics.
- [7] Junliang Wang A B C, Chuqiao Xu D, Jie Zhang A B, and Ray Zhong E. 2021. Big data analytics for intelligent manufacturing systems: A review. *Journal of Manufacturing Systems* (2021).
- [8] Deepayan Chakrabarti, Yiping Zhan, and Christos Faloutsos. 2004. R-MAT: A Recursive Model for Graph Mining. In Proceedings of the Fourth SIAM International Conference on Data Mining, Lake Buena Vista, Florida, USA, April 22-24, 2004, Michael W. Berry, Umeshwar Dayal, Chandrika Kamath, and David B. Skillicorn (Eds.). SIAM, 442–446.
- [9] Rong Chen, Jiaxin Shi, Yanzhe Chen, Binyu Zang, Haibing Guan, and Haibo Chen. 2018. PowerLyra: Differentiated Graph Computation and Partitioning on Skewed Graphs. ACM Trans. Parallel Comput. 5, 3 (2018), 13:1–13:39.
- [10] Michele Conforti, Gérard Cornuéjols, Giacomo Zambelli, et al. 2014. Integer programming. Vol. 271. Springer.
- [11] Eduardo F. D'Azevedo and Neena Imam. 2015. Graph 500 in OpenSHMEM. In OpenSHMEM and Related Technologies. Experiences, Implementations, and Technologies - Second Workshop, OpenSHMEM 2015, Annapolis, MD, USA, August 4-6, 2015. Revised Selected Papers (Lecture Notes in Computer Science), Manjunath Gorentla Venkata, Pavel Shamis, Neena Imam, and M. Graham Lopez (Eds.), Vol. 9397. Springer, 154–163.
- [12] Peter J Denning and Ted G Lewis. 2016. Exponential laws of computing growth. Commun. ACM 60, 1 (2016), 54–65.
- [13] A. Deutsch, X. Yu, M. Wu, and V. Lee. 2019. TigerGraph: A Native MPP Graph Database. arXiv (2019).
- [14] Chris Edwards. 2021. Moore's Law: what comes next? Commun. ACM 64, 2 (2021), 12–14.
- [15] Wenfei Fan, Tao He, et al. 2021. GraphScope: A Unified Engine For Big Graph Processing. Proc. VLDB Endow. 14, 12 (2021), 2879–2892.
- [16] John Forrest and Robin Lougee-Heimer. 2005. CBC user guide. In *Emerging theory, methods, and applications*. INFORMS, 257–277.
- [17] Sebastian Forster and Danupon Nanongkai. 2017. A Faster Distributed Single-Source Shortest Paths Algorithm. FOCS (2017).
- [18] Greg N. Frederickson. 1993. An Optimal Algorithm for Selection in a Min-Heap. Inf. Comput. 104, 2 (1993), 197–214.
- [19] Gerald Gamrath, Daniel Anderson, Ksenia Bestuzheva, Wei-Kun Chen, Leon Eifler, Maxime Gasse, Patrick Gemander, Ambros Gleixner, Leona Gottwald, Katrin Halbig, et al. 2020. The SCIP optimization suite 7.0. (2020).
- [20] Peter Garraghan, Paul Townend, and Jie Xu. 2013. An Analysis of the Server Characteristics and Resource Utilization in Google Cloud. In 2013 IEEE International Conference on Cloud Engineering, IC2E 2013, San Francisco, CA, USA, March 25-27, 2013. IEEE Computer Society, 124–131.
- [21] Alexandros V. Gerbessiotis and Leslie G. Valiant. 1994. Direct Bulk-Synchronous Parallel Algorithms. J. Parallel Distributed Comput. 22, 2 (1994), 251–267.
- [22] Joseph E. Gonzalez, Yucheng Low, Haijie Gu, Danny Bickson, and Carlos Guestrin. 2012. PowerGraph: Distributed Graph-Parallel Computation on Natural Graphs. In 10th USENIX Symposium on Operating Systems Design and Implementation, OSDI 2012, Hollywood, CA, USA, October 8-10, 2012, Chandu Thekkath and Amin Vahdat (Eds.). USENIX Association, 17–30.
- [23] William L. Hamilton, Zhitao Ying, and Jure Leskovec. 2017. Inductive Representation Learning on Large Graphs. In Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA, Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (Eds.). 1024–1034.
- [24] Nikolas Herbst, André Bauer, Samuel Kounev, Giorgos Oikonomou, Erwin Van Eyk, George Kousiouris, Athanasia Evangelinou, Rouven Krebs, Tim Brecht, Cristina L. Abad, and Alexandru Iosup. 2018. Quantifying Cloud Performance and Dependability: Taxonomy, Metric Design, and Emerging Challenges. ACM Trans. Model. Perform. Evaluation Comput. Syst. 3, 4 (2018), 19:1–19:36.

- [25] Juraj Hromkovič. 2013. Algorithmics for hard problems: introduction to combinatorial optimization, randomization, approximation, and heuristics. Springer Science & Business Media.
- [26] Xianyan Jia, Le Jiang, Ang Wang, Wencong Xiao, Ziji Shi, Jie Zhang, Xinyuan Li, Langshi Chen, Yong Li, Zhen Zheng, Xiaoyong Liu, and Wei Lin. 2022. Whale: Efficient Giant Model Training over Heterogeneous GPUs. In 2022 USENIX Annual Technical Conference (USENIX ATC 22).
- [27] George Karypis and Vipin Kumar. 1998. A Fast and High Quality Multilevel Scheme for Partitioning Irregular Graphs. SIAM J. Sci. Comput. 20, 1 (1998), 359–392.
- [28] Haewoon Kwak, Changhyun Lee, Hosung Park, and Sue B. Moon. 2010. What is Twitter, a social network or a news media?. In WWW. ACM, 591–600.
- [29] Eugene L Lawler and David E Wood. 1966. Branch-and-bound methods: A survey. Operations research 14, 4 (1966), 699–719.
- [30] Jure Leskovec, Jon M. Kleinberg, and Christos Faloutsos. 2005. Graphs over time: densification laws, shrinking diameters and possible explanations. In SIGKDD. ACM, 177–187.
- [31] Jure Leskovec and Andrej Krevl. 2014. SNAP Datasets: Stanford Large Network Dataset Collection. http://snap.stanford.edu/data.
- [32] Ji Liu, Zhihua Wu, Dianhai Yu, Yanjun Ma, Danlei Feng, Minxu Zhang, Xinxuan Wu, Xuefeng Yao, and Dejing Dou. 2021. HeterPS: Distributed Deep Learning With Reinforcement Learning Based Scheduling in Heterogeneous Environments. *Future Generation Computer Systems* (2021).
- [33] Yi Lu, James Cheng, Da Yan, and Huanhuan Wu. 2014. Large-Scale Distributed Graph Computing Systems: An Experimental Evaluation. *Proc. VLDB Endow.* 8, 3 (2014), 281–292.
- [34] Mohammad Sultan Mahmud, Joshua Zhexue Huang, Salman Salloum, Tamer Z. Emara, and Kuanishbay Sadatdiynov. 2020. A Survey of Data Partitioning and Sampling Methods to Support Big Data Analysis. *Big Data Mining and Analytics* 2 (2020), 17.
- [35] Anum Masood, Ehsan Ullah Munir, M. Mustafa Rafique, and Samee Ullah Khan. 2015. HETS: Heterogeneous Edge and Task Scheduling Algorithm for Heterogeneous Computing Systems. In 17th IEEE International Conference on High Performance Computing and Communications, HPCC 2015, 7th IEEE International Symposium on Cyberspace Safety and Security, CSS 2015, and 12th IEEE International Conference on Embedded Software and Systems, ICESS 2015, New York, NY, USA, August 24-26, 2015. IEEE, 1865–1870.
- [36] Christian Mayer, Muhammad Adnan Tariq, Chen Li, and Kurt Rothermel. 2016. GrapH: Heterogeneity-Aware Graph Computation with Adaptive Partitioning. In 36th IEEE International Conference on Distributed Computing Systems, ICDCS 2016, Nara, Japan, June 27-30, 2016. IEEE Computer Society, 118–128.
- [37] Tao Meng, Lijun Cai, Tingqin He, Lei Chen, and Ziyun Deng. 2018. K-Hop Community Search Based On Local Distance Dynamics. *KSII Trans. Internet Inf. Syst.* 12, 7 (2018), 3041–3063.
- [38] Azade Nazi, Will Hang, Anna Goldie, Sujith Ravi, and Azalia Mirhoseini. 2019. GAP: Generalizable Approximate Graph Partitioning Framework. *CoRR* abs/1903.00614 (2019).
- [39] Anil Pacaci and M. Tamer Özsu. 2019. Experimental Analysis of Streaming Algorithms for Graph Partitioning. In Proceedings of the 2019 International Conference on Management of Data, SIGMOD Conference 2019, Amsterdam, The Netherlands, June 30 - July 5, 2019, Peter A. Boncz, Stefan Manegold, Anastasia Ailamaki, Amol Deshpande, and Tim Kraska (Eds.). ACM, 1375–1392.
- [40] Fabio Petroni, Leonardo Querzoni, Khuzaima Daudjee, Shahin Kamali, and Giorgio Iacoboni. 2015. HDRF: Stream-Based Partitioning for Power-Law Graphs. In Proceedings of the 24th ACM International Conference on Information and Knowledge Management, CIKM 2015, Melbourne, VIC, Australia, October 19-23, 2015, James Bailey, Alistair Moffat, Charu C. Aggarwal, Maarten de Rijke, Ravi Kumar, Vanessa Murdock, Timos K. Sellis, and Jeffrey Xu Yu (Eds.). ACM, 243–252.
- [41] David Pisinger and Stefan Ropke. 2010. Large neighborhood search. In Handbook of metaheuristics. Springer, 399–419.
- [42] Luca Pretto. 2002. A Theoretical Analysis of Google's PageRank. In String Processing and Information Retrieval, 9th International Symposium, SPIRE 2002, Lisbon, Portugal, September 11-13, 2002, Proceedings (Lecture Notes in Computer Science), Alberto H. F. Laender and Arlindo L. Oliveira (Eds.), Vol. 2476. Springer, 131–144.
- [43] Yunsheng Shi, Zhengjie Huang, Shikun Feng, Hui Zhong, Wenjing Wang, and Yu Sun. 2021. Masked Label Prediction: Unified Message Passing Model for Semi-Supervised Classification. In Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI 2021, Virtual Event / Montreal, Canada, 19-27 August 2021, Zhi-Hua Zhou (Ed.). ijcai.org, 1548–1554.
- [44] Isabelle Stanton and Gabriel Kliot. 2012. Streaming graph partitioning for large distributed graphs. In *The 18th ACM SIGKDD International Conference on Knowl*edge Discovery and Data Mining, KDD '12, Beijing, China, August 12-16, 2012, Qiang Yang, Deepak Agarwal, and Jian Pei (Eds.). ACM, 1222–1230.
- [45] Muhammad Sulaiman, Zahid Halim, Mustapha Lebbah, Muhammad Waqas, and Shanshan Tu. 2021. An Evolutionary Computing-Based Efficient Hybrid

Task Scheduling Approach for Heterogeneous Computing Environment. J. Grid Comput. 19, 1 (2021), 11.

- [46] Tencent. 2019. Plato. https://github.com/Tencent/plato.
- [47] Charalampos E. Tsourakakis, Christos Gkantsidis, Bozidar Radunovic, and Milan Vojnovic. 2014. FENNEL: streaming graph partitioning for massive scale graphs. In Seventh ACM International Conference on Web Search and Data Mining, WSDM 2014, New York, NY, USA, February 24-28, 2014, Ben Carterette, Fernando Diaz, Carlos Castillo, and Donald Metzler (Eds.). ACM, 333–342.
- [48] Shiv Verma, Luke M. Leslie, Yosub Shin, and Indranil Gupta. 2017. An Experimental Comparison of Partitioning Strategies in Distributed Graph Processing. *Proc. VLDB Endow.* 10, 5 (2017), 493–504.
- [49] Yiwei Shen Verma and Guosun Zeng. 2005. An unbalanced partitioning scheme for graph in heterogeneous computing. *International Conference on Grid and Cooperative Computing* (2005).
- [50] Hongwei Wang, Miao Zhao, Xing Xie, Wenjie Li, and Minyi Guo. 2019. Knowledge Graph Convolutional Networks for Recommender Systems. In *The World Wide Web Conference, WWW 2019, San Francisco, CA, USA, May 13-17, 2019,* Ling Liu, Ryen W. White, Amin Mantrach, Fabrizio Silvestri, Julian J. McAuley, Ricardo Baeza-Yates, and Leila Zia (Eds.). ACM, 3307–3313.
- [51] Cong Xie, Ling Yan, Wu-Jun Li, and Zhihua Zhang. 2014. Distributed Power-law Graph Computing: Theoretical and Empirical Analysis. In Advances in Neural Information Processing Systems 27: Annual Conference on Neural Information Processing Systems 2014, December 8-13 2014, Montreal, Quebec, Canada, Zoubin Ghahramani, Max Welling, Corinna Cortes, Neil D. Lawrence, and Kilian Q. Weinberger (Eds.). 1673–1681.
- [52] Reynold S. Xin, Joseph E. Gonzalez, Michael J. Franklin, and Ion Stoica. 2013. GraphX: a resilient distributed graph system on Spark. In First International Workshop on Graph Data Management Experiences and Systems, GRADES 2013, co-located with SIGMOD/PODS 2013, New York, NY, USA, June 24, 2013, Peter A. Boncz and Thomas Neumann (Eds.). CWI/ACM, 2.
- [53] Jilong Xue, Zhi Yang, Shian Hou, and Yafei Dai. 2015. When computing meets heterogeneous cluster: Workload assignment in graph computation. In 2015 IEEE International Conference on Big Data (IEEE BigData 2015), Santa Clara, CA, USA, October 29 - November 1, 2015. IEEE Computer Society, 154–163.
- [54] Muhammad Zakarya and Lee Gillam. 2019. Modelling resource heterogeneities in cloud simulations and quantifying their accuracy. *Simul. Model. Pract. Theory* 94 (2019), 43–65.
- [55] Li Zeng, Yan Jiang, Weixin Lu, and Lei Zou. 2020. Deep Analysis on Subgraph Isomorphism. arXiv (2020).
- [56] Li Zeng, Kang Yang, Haoran Cai, Jinhua Zhou, Rongqian Zhao, and Xin Chen. 2022. HTC: Hybrid vertex-parallel and edge-parallel Triangle Counting. *HPEC* (2022).
- [57] Li Zeng, Qiheng You, Jincheng Lu, Shizheng Liu, Weijian Sun, Rongqian Zhao, and Xin Chen. 2023. KBQA: Accelerate Fuzzy Path Query on Knowledge Graph. DEXA (2023).
- [58] Li Zeng, Jinhua Zhou, Shijun Qin, Haoran Cai, Rongqian Zhao, and Xin Chen. 2022. SQLG+: Efficient k-hop Query Processing on RDBMS. In *Database* Systems for Advanced Applications - 27th International Conference, DASFAA 2022, Virtual Event, April 11-14, 2022, Proceedings, Part III (Lecture Notes in Computer Science), Arnab Bhattacharya, Janice Lee, Mong Li, Divyakant Agrawal, P. Krishna Reddy, Mukesh K. Mohania, Anirban Mondal, Vikram Goyal, and Rage Uday Kiran (Eds.), Vol. 13247. Springer, 430–442.
- [59] Li Zeng and Lei Zou. 2018. Redesign of the gStore system. Frontiers Comput. Sci. (2018).
- [60] Li Zeng, Lei Zou, and M. Tamer Ozsu. 2022. SGSI: A Scalable GPU-Friendly Subgraph Isomorphism Algorithm. *IEEE Transactions on Knowledge and Data Engineering* (2022).
- [61] Li Zeng, Lei Zou, M. Tamer Özsu, Lin Hu, and Fan Zhang. 2020. GSI: GPUfriendly Subgraph Isomorphism. In 36th IEEE International Conference on Data Engineering, ICDE 2020, Dallas, TX, USA, April 20-24, 2020. IEEE, 1249–1260.
- [62] Chenzi Zhang, Fan Wei, Qin Liu, Zhihao Gavin Tang, and Zhenguo Li. 2017. Graph Edge Partitioning via Neighborhood Heuristic. In Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, Halifax, NS, Canada, August 13 - 17, 2017. ACM, 605–614.
- [63] Dalong Zhang, Xin Huang, Ziqi Liu, Jun Zhou, Zhiyang Hu, Xianzheng Song, Zhibang Ge, Lin Wang, Zhiqiang Zhang, and Yuan Qi. 2020. AGL: A Scalable System for Industrial-purpose Graph Machine Learning. *Proc. VLDB Endow.* 13, 12 (2020), 3125–3137.
- [64] Shuai Zhang, Zite Jiang, Xingzhong Hou, Zhen Guan, Mengting Yuan, and Haihang You. 2021. An Efficient and Balanced Graph Partition Algorithm for the Subgraph-Centric Programming Model on Large-scale Power-law Graphs. In 41st IEEE International Conference on Distributed Computing Systems, ICDCS 2021, Washington DC, USA, July 7-10, 2021. IEEE, 68–78.
- [65] Xian Zhang, Junchang Xin, Jinyi Chen, Beibei Wang, and Zhiqiong Wang. 2023. HAEP: Heterogeneous Environment Aware Edge Partitioning for Power-Law Graphs. In Database Systems for Advanced Applications - 28th International Conference, DASFAA 2023, Tianjin, China, April 17-20, 2023, Proceedings, Part

III (Lecture Notes in Computer Science), Xin Wang, Maria Luisa Sapino, Wook-Shin Han, Amr El Abbadi, Gill Dobbie, Zhiyong Feng, Yingxiao Shao, and Hongzhi Yin (Eds.), Vol. 13945. Springer, 331–340.

- [66] Ying Zhong, Chenze Huang, and Qingbiao Zhou. 2023. HaSGP: an effective graph partition method for heterogeneous-aware. *Computing* 105, 2 (2023), 455–481.
- [67] Xiaowei Zhu, Wenguang Chen, Weimin Zheng, and Xiaosong Ma. 2016. Gemini: A Computation-Centric Distributed Graph Processing System. In 12th USENIX Symposium on Operating Systems Design and Implementation, OSDI 2016, Savannah, GA, USA, November 2-4, 2016, Kimberly Keeton and Timothy Roscoe (Eds.). USENIX Association, 301–316.