

LC-Tsallis-INF: Generalized Best-of-Both-Worlds Linear Contextual Bandits

Masahiro Kato¹ and Shinji Ito²

¹Mizuho-DL Financial Technology Co., Ltd., masahiro-kato@fintec.co.jp

²NEC Corporation and RIKEN AIP, i-shinji@nec.com

Abstract

This study considers the *linear contextual bandit problem* with independent and identically distributed (i.i.d.) contexts. In this problem, existing studies have proposed *Best-of-Both-Worlds* (BoBW) algorithms whose regrets satisfy $O(\log^2(T))$ for the number of rounds T in a stochastic regime with a suboptimality gap lower-bounded by a positive constant, while satisfying $O(\sqrt{T})$ in an adversarial regime. However, the dependency on T has room for improvement, and the suboptimality-gap assumption can be relaxed. For this issue, this study proposes an algorithm whose regret satisfies $O(\log(T))$ in the setting when the suboptimality gap is lower-bounded. Furthermore, we introduce a *margin condition*, a milder assumption on the suboptimality gap. That condition characterizes the problem difficulty linked to the suboptimality gap using a parameter $\beta \in (0, \infty]$. We then show that the algorithm's regret satisfies $O\left(\{\log(T)\}^{\frac{1+\beta}{2+\beta}} T^{\frac{1}{2+\beta}}\right)$. Here, $\beta = \infty$ corresponds to the case in the existing studies where a lower bound exists in the suboptimality gap, and our regret satisfies $O(\log(T))$ in that case. Our proposed algorithm is based on the *Follow-The-Regularized-Leader with the Tsallis entropy* and referred to as the α -*Linear-Contextual (LC)-Tsallis-INF*.

1 Introduction

This study considers the linear contextual bandit problem with adversarial corruption and proposes a best-of-both-worlds (BoBW) algorithm whose regret upper bound tightly depends on the number of rounds T .

In each round of our bandit trial, (i) a decision-maker observes independent and identically distributed (i.i.d.) contexts, (ii) selects an arm based on the context and past observations up to that round, and (iii) incurs a loss corresponding to the selected arm. The decision-maker's objective is to minimize the cumulative loss incurred throughout the trial.

The contextual bandit problem has been widely studied in fields such as sequential treatment allocation (Tewari & Murphy, 2017), personalized recommendations (Beygelzimer et al., 2011), and online advertising (Li et al., 2010). This study assumes linear models between the loss and contexts, known as the linear contextual bandit problem (Abe & Long, 1999). This field encompasses numerous related work (Chen et al., 2020; Li et al., 2021; Ding et al., 2022).

The data-generating process (DGP) of a loss in each round is categorized into stochastic or adversarial regimes. Optimal algorithms typically differ between the stochastic and adversarial regimes. However, there exist BoBW algorithms that are effective in both regimes (Bubeck & Slivkins, 2012; Seldin & Slivkins, 2014; Auer & Chiang, 2016; Seldin & Lugosi, 2017; Zimmert & Seldin, 2021; Lee et al., 2021).

Kato & Ito (2023) and Kuroki et al. (2023) independently propose BoBW algorithms for linear contextual bandits. They both employ a Follow-The-Regularized-Leader (FTRL) algorithm with the Shannon entropy and an entropy-adaptive update rule for learning rates (Ito et al., 2022). Their algorithms' regrets satisfy $O(\log^2(T))$ regarding T . Furthermore, Kuroki et al. (2023) develops an algorithm with $O(\log(T))$ regret upper bound using the reduction framework proposed by Dann et al. (2023a). Although this approach gives a tighter upper bound regarding T , it is known to have

Table 1: Comparison of regrets. We categorize regret upper bounds based on the regimes and the assumption on \mathcal{G} . We make \checkmark in the “ \sqrt{C} ” column if algorithms’ upper bounds depend on the corruption level $C \geq 0$ tightly under the adversarial corruption represented by the corruption parameter C . The “Assumption on \mathcal{G} ” column denotes which one, full information is accessible, or $O(\text{poly}(T))$ samples are drawn from \mathcal{G} , to compute Σ_t^{-1} . Note that Liu et al. (2023) does not assume the access to \mathcal{G} , by incurring some computation costs.

	Regret		\sqrt{C}	Assumption on \mathcal{G}
	Stochastic	Adversarial		
1/2-LC-Tsallis-INF (Ours)	$O\left(\frac{L\sqrt{K}\left(d+\frac{1}{\lambda_{\min}}\right)}{\Delta_*} \log(T)\right)$	$O\left(\sqrt{\log(KT)}\left(d+\frac{1}{\lambda_{\min}}\right)T\right)$	\checkmark	Full information.
A margin condition with β .	$O\left(\left\{\frac{1+\beta}{\beta\Delta_*}\right\}^{\frac{\beta}{2+\beta}} \left\{L\sqrt{K}\left(d+\frac{1}{\lambda_{\min}}\right) \log(T)\right\}^{\frac{1+\beta}{2+\beta}} T^{\frac{1}{2+\beta}}\right)$ where $\beta \in (0, \infty]$.	-	-	Full information.
	$O\left(\frac{L\sqrt{K}\left(d+\frac{\log(T)}{\lambda_{\min}}\right)}{\Delta_*} \log(T)\right)$	$O\left(\sqrt{\log(KT)}\left(d+\frac{1}{\lambda_{\min}}\right)T\right)$	\checkmark	$O(\text{poly}(T))$ samples.
	$O\left(\left\{\frac{1+\beta}{\beta\Delta_*}\right\}^{\frac{\beta}{2+\beta}} \left\{L\sqrt{K}\left(d+\frac{\log(T)}{\lambda_{\min}}\right) \log(T)\right\}^{\frac{1+\beta}{2+\beta}} T^{\frac{1}{2+\beta}}\right)$ where $\beta \in (0, \infty]$.	-	-	$O(\text{poly}(T))$ samples.
BoBW-RealFTRL (Kato & Ito, 2023)	$O\left(\frac{D}{\Delta_*}\right)$ where $D = \log(T)\left(\frac{1}{\lambda_{\min}} + d \log(K)\right) \log(KT)$.	$O\left(\sqrt{\log(KT)TD}\right)$	\checkmark	Full information.
(Kuroki et al., 2023)	$O\left(\frac{D'}{\Delta_*}\right)$ where $D' = \log(T)\left(\frac{\log(T)}{\lambda_{\min}} + d \log(K)\right) \log(KT)$.	$O\left(\sqrt{\log(KT)TD}\right)$	\checkmark	$O(\text{poly}(T))$ samples.
BoBW reduction with a base algorithm of ReallinExp3 (Proposition 8, Kuroki et al., 2023)	$O\left(\frac{K^2}{\Delta_*} \left(d + \frac{1}{\lambda_{\min}}\right)^2 \log(K) \log(T)\right)$	$O\left(\sqrt{TK^2} \left(d + \frac{1}{\lambda_{\min}}\right)^2 \log(K)\right)$	\checkmark	Full information
Logdet-FTRL (poly(K, d, T) in computation)	-	$O\left(d^2\sqrt{T} \log(T)\right)$	-	No access
Linear EXP4 (T^d in computation) (Liu et al., 2023)	-	$O\left(d\sqrt{T} \log(T)\right)$	-	No access
OFUL (Abbasi-yadkori et al., 2011)	$O(d \log(1/\delta)/\Delta)$ with probability $1 - \delta$ $O(d \log(T)/\Delta)$ with probability $1 - 1/T$	-	-	N/A
RealLinExp3 (Neu & Olkhovskaya, 2020)	-	$O\left(\log(T)\sqrt{d \log(K)T}\right)$	-	$O(\text{poly}(T))$ samples

some limitations. For example, Kuroki et al. (2023) reports that it is feasible only when we know the inverse of the covariance matrix, and it may not be practical due to the difficulty in implementation. To overcome this issue, Kuroki et al. (2023) proposes their FTRL-based algorithm.

This study aims to improve the dependency on T . The $O(\log^2(T))$ regret is caused by the use of the Shannon entropy in the FTRL. Therefore, to improve upper bounds, we apply the Tsallis entropy instead of the Shannon entropy (Zimmert & Seldin, 2021; Masoudian & Seldin, 2021), which allows us to obtain $O(\log(T))$ regret.

Furthermore, Kato & Ito (2023) and Kuroki et al. (2023) only discuss a case where there exists a positive lower bound for a suboptimality gap, which is considered to be restrictive in linear contextual bandits. This study introduces a milder assumption on the suboptimality gap, called a *margin condition*, and characterizes the problem difficulty using a parameter $\beta \in (0, +\infty]$. We then show that our proposed algorithm’s regret satisfies $O\left(\left\{\log(T)\right\}^{\frac{1+\beta}{2+\beta}} T^{\frac{1}{2+\beta}}\right)$. The condition assumed in Kato & Ito (2023) and Kuroki et al. (2023) corresponds to a margin condition with $\beta = \infty$, and in that case, the regret upper bound becomes $O(\log(T))$.

Since our proposed algorithm is based on the FTRL with the Tsallis entropy, we refer to it as the α -Linear-Contextual (LC)-Tsallis-INF. We explain the details below.

1.1 Organization and Main Contribution

Section 2 formulates the linear contextual bandit problem. We assume that X_t is generated from a *known* distribution \mathcal{G} and induces a d -dimensional *feature* vector $\phi(a, X_t) \in \mathbb{R}^d$ for each arm $a \in [K]$ (See Assumption 2.1).

This study considers a case where there is a mapping from an arm-independent context to an arm-dependent context, called a *feature*. Our setting is standard in linear contextual bandits (Abbasi-yadkori et al., 2011; Li et al., 2021) but differs from the setting in Neu & Olkhovskaya (2020), Kato & Ito (2023), and Kuroki et al. (2023), which assume linear models between a loss and an arm-independent context. We also develop upper bounds of the BoBW-RealFTRL algorithm by Kato & Ito (2023) and Kuroki et al. (2023) under this setting in Appendix D.

In Section 4, we define three regimes for the loss DGP: an adversarial regime (Neu & Olkhovskaya, 2020), a stochastic regime with a margin condition

(Li et al., 2021), and a linear contextual adversarial regime with a self-bounding constraint. In an adversarial regime, the nature chooses the loss in each round based on past observations up to that round. A margin condition is an assumption on the suboptimality gap, the difference between the expected losses of the best and suboptimal arms. Specifically, the margin condition is given as $\mathbb{P}(\Delta(X_0) \leq h) \leq \frac{1}{2} \left(\frac{h}{\Delta_*}\right)^\beta$, where $\beta \in (0, \infty]$ is a margin condition parameter, $\Delta(X_0)$ is the suboptimality gap given context X_0 generated from \mathcal{G} , d is the dimension of features, $\Delta_* > 0$ is a universal constant, and h satisfies $0 \leq h \leq \Delta_*$. When $\beta = \infty$, it implies a constant gap Δ_* for any context X_0 . The detailed definition is provided in Definition 4.1. A linear contextual adversarial regime with a self-bounding constraint assumes the existence of constants $\Delta_* > 0$ and $C > 0$ such that $R_T \geq \Delta_* \mathbb{E} \left[\sum_{t=1}^T \sum_{a \in [K]} \pi_t(a | X_t) \right] - C$, where K is the number of arms, $\pi_t(a | X_t)$ is the probability of selecting arm a in round t given context X_t . The detailed definition is provided in Definition 4.2.

Section 5 presents our algorithm, the α -Linear-Contextual-Tsallis-INF (α -LC-Tsallis-INF), which is an FTRL-based approach with an α -Tsallis-entropy regularization.

A key component of our algorithm is the inverse of the covariance matrix of a (arm-dependent) feature multiplied by a policy π_t in each round $t \in [T]$, which is denoted by Σ_t in Section 2.2. While the true inverse of Σ_t is given under the full information about \mathcal{G} , we need to approximate it when only finite samples are obtainable from \mathcal{G} . We develop two regret upper bounds for two cases where full information about \mathcal{G} is known and only $O(\text{poly}(T))$ samples are obtainable from \mathcal{G} . In the latter, we approximate Σ_t by employing the Matrix Geometric Resampling (MGR) algorithm.

In Section 6, we derive regret upper bounds of the 1/2-LC-Tsallis-INF (α -LC-Tsallis-INF with $\alpha = 1/2$) for each regime, depending on the knowledge about \mathcal{G} , which affects the availability of the inverse of Σ_t . When we have full information about \mathcal{G} , the regret upper bound in an adversarial regime for our proposed algorithm is $O\left(\sqrt{\sqrt{K}\left(d + \frac{1}{\lambda_{\min}}\right)T}\right)$, where λ_{\min} is the smallest eigenvalue of a feature covariance matrix induced by an exploratory policy (See Assumption 2.3). In a stochastic regime with a margin condition, the regret satisfies

$$O\left(\left\{\frac{1+\beta}{\beta\Delta_*}\right\}^{\frac{\beta}{2+\beta}} \left\{L\sqrt{K}\left(d + \frac{1}{\lambda_{\min}}\right)\log(T)\right\}^{\frac{1+\beta}{2+\beta}} T^{\frac{1}{2+\beta}}\right),$$

where L is the lowest probability of contexts (See Assumption 2.2). In an adversarial regime with a self-bounding constraint,

the regret satisfies $O\left(\frac{L\sqrt{K}\left(d + \frac{1}{\lambda_{\min}}\right)}{\Delta_*}\log(T) + \sqrt{\frac{CL\sqrt{K}\left(d + \frac{1}{\lambda_{\min}}\right)}{\Delta_*}}\sqrt{\log_+\left(\frac{\Delta_*T}{C}\right)}\right)$, where $\log_+(x) := \max\{1, \log(x)\}$ and recall that β is a parameter of a margin condition. When $C = 0$, we define $\log_+\left(\frac{\Delta_*T}{C}\right) = 1$. When Σ_t^{-1} is approximated by the MGR algorithm, we multiply each regret upper bound by $\log(T)$ in a stochastic regime and by $\sqrt{\log(T)}$ in an adversarial regime.

Our derived upper bound demonstrates a tighter dependence on T compared to the existing FTRL-based algorithms proposed by Kato & Ito (2023) and Kuroki et al. (2023). Furthermore, their results consider only the case with $\beta = \infty$ in a stochastic regime, while our study addresses more general cases depending on the margin condition with various parameters β . Additionally, compared to the reduction approach with $O(\log(T))$ regret by Kuroki et al. (2023), our algorithm is easy to implement and has a tighter dependence on K . A more detailed comparison is provided in Section 1.2. In Appendix D, we derive an upper bound of their algorithm under a margin condition, depending on β .

In summary, our contributions lie in the proposition of an algorithm whose upper bound tightly depends on T and the analysis under a margin condition and the arm-dependent feature setting. Our results correspond to the refinement and generalization of the results by Neu & Olkhovskaya (2020), Kato & Ito (2023), and Kuroki et al. (2023).

1.2 Related Work

In Table 1, we compare our algorithm's regrets with those in existing work Neu & Olkhovskaya (2020) propose the RealLinExp3 for adversarial linear contextual bandits. In a stochastic regime, the regret upper bound is significantly affected by a margin condition, an assumption on the suboptimality gap given a context. We refer to regret upper bounds with the assumption of a margin condition as problem-dependent, while we refer to regret upper bounds without assuming specific assumptions on data distribution, such as a margin condition, as problem-independent. Dani et al. (2008) propose the ConfidenceBall, and Abbasi-yadkori et al. (2011) propose OFUL. Both present upper bounds in both problem-dependent and problem-independent analyses. In their problem-dependent analyses, they assume the existence of Δ_* for a lower bound of the suboptimality gap, corresponding to a margin condition with $\beta = \infty$. Goldenshluger & Zeevi (2013), Wang et al. (2018), and Bastani & Bayati (2020) pro-

pose algorithms in a case with $\beta = 1$. Furthermore, Li et al. (2021) propose the ℓ_1 -ConfidenceBall based algorithm whose upper bound tightly depends on β .

By extending the RealLinEXP3 of Neu & Olkhovskaya (2020), Kato & Ito (2023) and Kuroki et al. (2023) independently propose FTRL-based algorithms that work in both adversarial and stochastic regimes using the Shannon entropy regularization. Kato & Ito (2023) proposes the BoBW-RealFTRL algorithm whose regret upper bound is $O\left(\min\left\{\frac{D}{\Delta_*} + \sqrt{\frac{CD}{\Delta_*}}, \sqrt{\log(KT)TD}\right\}\right)$ in a linear contextual adversarial regime with a self-bounding constraint when only finite samples are available from \mathcal{G} , where $D = K \log(T) \left(\frac{\log(T)}{\lambda_{\min}} + d \log(K)\right) \log(KT)$. They also show that in an adversarial regime, the upper bound is $O\left(\sqrt{TK\left(d + \frac{\log(T)}{\lambda_{\min}}\right) \log(T) \log(K)}\right)$.

Kuroki et al. (2023) also develops an algorithm called the FTRL-LC and derives its upper bound when the true inverse of Σ_t is given, in addition to those when the inverse is approximated using finite samples from \mathcal{G} . If Σ_t^{-1} is known, the above regret upper bounds are divided by $\log(T)$ in a stochastic regime and by $\sqrt{\log(T)}$ in an adversarial regime. Note that the algorithms proposed by Kato & Ito (2023) and Kuroki et al. (2023) are almost the same, and we follow the terminology and formulations of Kato & Ito (2023).

Furthermore, Kuroki et al. (2023) develops another BoBW algorithm in linear contextual bandits using the reduction approach by Dann et al. (2023a). The regret achieves $O(\log(T))$, but the algorithm may not be practical in implementation and requires the full information about \mathcal{G} .

Several other studies relate to linear contextual bandits with adversarial corruption. Lykouris & Vassilvtskii (2018), Gupta et al. (2019), and Zhao et al. (2021) consider other corruption frameworks characterized by a constant $\tilde{C} \in [0, T]$, which is different but related to our linear contextual adversarial regime with a self-bounding constraint. He et al. (2022) uses another constant $\tilde{C}^\dagger \in [0, T]$, closely related to \tilde{C} . For details, also see Remark 2 in Kato & Ito (2023).

As well as Kato & Ito (2023) and Kuroki et al. (2023), we employ the self-bounding technique (Zimmert & Seldin, 2021; Wei & Luo, 2018; Masoudian & Seldin, 2021) and an entropy-adaptive update rule for learning rates, which have been proven effective in providing BoBW guarantees for online learning in feedback graph contexts (Ito et al., 2022), multi-armed bandits (MAB) (Jin et al., 2023), partial monitoring (Tsuchiya et al., 2023a), linear

bandits (Kong et al., 2023), episodic Markov Decision Processes (MDPs) (Dann et al., 2023b), and sparse bandits (Tsuchiya et al., 2023b).

However, under existing studies employing the Shannon entropy, regrets usually do not satisfy $O(\log(T))$, as Kato & Ito (2023) and Kuroki et al. (2023) show $O(\log^2(T))$ regret. In contrast, Zimmert & Seldin (2021) shows that under the Tsallis entropy, we can design an algorithm whose regret satisfies $O(\log(T))$ in MAB. As well as Zimmert & Seldin (2021), Rouyer & Seldin (2020), and Masoudian & Seldin (2021), we also employ the Tsallis entropy to tighten the dependence on T in linear contextual bandits. Compared to the algorithm with the reduction approach by Kuroki et al. (2023), our algorithm is easy to implement and has a tighter dependence regarding K .

2 Problem Setting

Suppose that there are T rounds and K arms. We denote the sets of rounds and arms by $[T] := \{1, 2, \dots, T\}$ and $[K] := \{1, 2, \dots, K\}$, respectively.

In each round $t \in [T]$, a decision-maker observes a context $X_t \in \mathcal{X}$, where \mathcal{X} is an arbitrary context space, and chooses an arm $A_t \in [K]$ based on the context X_t and past observations. Each arm $a \in [K]$ is linked to a loss $\ell_t(a, X_t)$, which depends on $X_t \in \mathcal{X}$, arm $a \in [K]$, and round $t \in [T]$. After choosing arm A_t in round t , the decision-maker incurs the corresponding loss $\ell_t(A_t, X_t)$. Our goal is to minimize the cumulative loss $\sum_{t=1}^T \ell_t(A_t, X_t)$. We introduce the setting in more detail in the following subsection.

Notation. Let $\langle \cdot, \cdot \rangle$ denote inner products in Euclidean space and let $\|\cdot\|_2$ denote the ℓ_2 norm. Let $\|\cdot\|_{\text{op}}$ denote the operator norm of a symmetric positive semidefinite matrix.

2.1 Procedure in a Trial

This section describes the decision-making procedure. We refer to a function that the decision-maker follows in arm selection as a *policy*. Let Π be the set of all possible policies $\pi : \mathcal{X} \rightarrow \mathcal{P}_K := \left\{u = (u_1 \ u_2 \ \dots \ u_K)^\top \in [0, 1]^K \mid \sum_{k=1}^K u_k = 1\right\}$ with its a -th element $\pi(a \mid x)$.

Specifically, we consider sequential decision-making with the following steps in each round $t \in [T]$:

1. The nature decides $\{\ell_t(a, x)\}_{a \in [K], x \in \mathcal{X}}$ based on \mathcal{F}_{t-1} .
2. The decision-maker observes a context $X_t \in \mathcal{X}$, generated from a known distribution \mathcal{G} .

3. Based on the observed context X_t , the decision-maker selects a policy $\pi_t(X_t) \in \mathcal{P}_K$.
4. The decision-maker chooses action $A_t \in [K]$ with probability $\pi_t(A_t | X_t)$.
5. The decision-maker incurs a loss $\ell_t(A_t, X_t)$.

The goal of the decision-maker is to select actions in a way that minimizes the total loss $\sum_{t=1}^T \ell_t(A_t, X_t)$.

2.2 Definition and Assumptions about Contexts

We assume that X_t is an i.i.d. random variable generated from a context distribution \mathcal{G} over the support \mathcal{X} , which is assumed to be known to the decision-maker. Because the randomness of X_t is independent of t , we use X_0 to denote an i.i.d. random variable from the context distribution \mathcal{G} .

We define X_t as a context that is independent of an arm. This setting of contexts follows the approach used in [Neu & Olkhovskaya \(2020\)](#). However, it differs from the approach in several other related studies on linear contextual bandits, including [Li et al. \(2010\)](#) and [Liu et al. \(2023\)](#), which utilize arm-dependent contexts. We refer to such contexts as *features* to differentiate it from arm-independent contexts.

To obtain features, we define a feature map that transforms a context $x \in \mathcal{X}$ into a feature $\phi(a, x) \in \mathcal{Z} \subseteq \mathbb{R}^d$, where \mathcal{Z} is a d -dimensional feature space. We assume that the feature map is known to the decision-maker, as well as \mathcal{G} .

In our analysis, the inverse of the covariance matrix

$$\Sigma(E) := \mathbb{E}_{X_t \sim \mathcal{G}, A_t \sim E_{X_t}} \left[\phi(A_t, X_t) \phi^\top(A_t, X_t) \right].$$

plays an important role, where $E := \{E_x\}_{x \in \mathcal{X}}$ is a set of conditional distributions E_x of a given x , and recall that X_0 is a sample from the context distribution \mathcal{G} independent of past observations $\mathcal{F}_{t-1} = \{(X_s, A_s, \ell_s(A_s, X_s))\}_{s=1}^{t-1}$.

We summarize the assumptions about contexts below.

Assumption 2.1 (Contextual distribution). We assume the following for context X_t and $\phi(\cdot, \cdot)$:

- Context $X_t \in \mathcal{X}$ is an i.i.d. random variable from a *known* context distribution \mathcal{G} , where \mathcal{X} is some arbitrary support.
- There is a *known* feature map $\phi : [K] \times \mathcal{X} \rightarrow \mathcal{Z}$, which maps $x \in \mathcal{X}$ to feature $\phi(a, x) \in \mathcal{Z} \subset \mathbb{R}^d$

When considering a stochastic regime with an adversarial corruption with the Tsallis entropy, we additionally use the following assumption on a context X_t .

Assumption 2.2 (Context distribution with finite support). We assume the following for context distribution:

- A context space \mathcal{X} is $\mathcal{X} := \{x_1, x_2, \dots, x_S\}$ for $S \in \mathbb{N}$.
- For any $x \in \mathcal{X}$, $\mathbb{P}_{X_0 \sim \mathcal{G}}(X_0 = x) \geq 1/L$ given a universal constant $L \geq S$.

In regret analysis, Σ_t plays an important role. To analyze Σ_t , we make the following assumption.

Assumption 2.3 (Eigenvalue condition for $\Sigma(E)$). For any $x \in \mathcal{X}$, there exist an exploration policy $e^*(x) \in \mathcal{P}_K$ whose distribution is E_x^* and a universal constant $\lambda_{\min} > 0$ such that for $E^* = \{E_x^*\}_{x \in \mathcal{X}}$, the matrix $\Sigma(E^*)$ is positive definite and its smallest eigenvalue is larger than λ_{\min} .

Our definition includes a setting of [Neu & Olkhovskaya \(2020\)](#), which assumes that the covariance of arm-independent contexts has its smallest eigenvalue $\tilde{\lambda}_{\min} > 0$.

If $|\mathcal{X}| = 1$, the setting boils down to non-contextual linear bandits. In this case, we can take e^* by using the G -optimal design. See Chapter 21 in [Lattimore & Szepesvári \(2020\)](#).

2.3 Linear Contextual Bandits

This study assumes linear models between $\ell_t(a, x)$ and x .

Assumption 2.4 (Linear models). For all $a \in [K]$ and any $x \in \mathcal{X}$, the following holds:

$$\ell_t(a, x) = \langle \phi(a, x), \theta_t \rangle + \varepsilon_t(a),$$

where $\theta_t \in \Theta$ is a d -dimensional parameter with a parameter space $\Theta \subset \mathbb{R}^d$, and $\varepsilon_t(a)$ is an error term such that $\mathbb{E}[\varepsilon_t(a) | X_t, \mathcal{F}_{t-1}] = 0$.

For the linear models and related variables, we make the following assumptions.

Assumption 2.5 (Bounded variables). The following hold:

1. There exists a universal constant $C_{\mathcal{Z}} > 0$ such that for any $z \in \mathcal{Z}$, $\|z\|_2 \leq C_{\mathcal{Z}}$ holds.
2. There exists a universal constant $C_{\Theta} > 0$ such that for each $\theta \in \Theta$, $\|\theta\|_2 \leq C_{\Theta}$ holds.
3. There exists a universal constant $C_{\mathcal{E}} > 0$ such that for all $a \in [K]$, $|\varepsilon_t(a)| \leq C_{\mathcal{E}}$ holds.

Under this assumption, there exists $C_{\ell} := C(C_{\mathcal{Z}}, C_{\Theta}, C_{\mathcal{E}})$ such that for all $\ell_t(a, X_t)$, each $a \in [K]$, and any $x \in \mathcal{X}$. $|\ell_t(a, x)| = |\langle \phi(a, x), \theta_t \rangle + \varepsilon_t(a)| \leq C_{\ell}$ holds.

The parameter θ_t is generated in different ways according to the regimes of the DGP. We defined them in Section 4.

3 Regret

This section defines the (pseudo) regret, a relative measure of the cumulative loss, to evaluate the performance of the decision-maker's policy. Let \mathcal{R} be the set of all possible $\rho : \mathcal{X} \rightarrow [K]$. The quality of a decision by the decision-maker is measured by its total expected regret, defined as

$$R_T := \max_{\rho \in \mathcal{R}} \mathbb{E} \left[\sum_{t=1}^T \left\{ \ell_t(A_t, X_t) - \ell_t(\rho(X_t), X_t) \right\} \right],$$

where the expectation is taken over the randomness of policies of the decision-maker, as well as the sequence of random contexts, $\{X_t\}_{t \in [T]}$, and losses, $\{\ell_t(\cdot, X_t)\}_{t \in [T]}$.

Here, we also define an optimal policy a_T^* as

$$a_T^* = \arg \min_{\rho \in \mathcal{R}} \mathbb{E} \left[\sum_{t=1}^T \left\langle \phi(\rho(X_t), X_t), \theta_t \right\rangle \right].$$

Then, the regret is equal to $R_T = \mathbb{E} \left[\sum_{t=1}^T \left\langle \phi(A_t, X_t) - \phi(a_T^*(X_t), X_t), \theta_t \right\rangle \right]$.

Neu & Olkhovskaya (2020) refers to a function ρ as a linear-classifier policy, while π_t is called stochastic policies. In our study, decision-makers compare their stochastic policies π_t to the optimal linear-classifier policy a_T^* using the regret.

4 Data-Generating Process

In each $t \in [T]$, the nature chooses $\{\ell_t(\cdot, x)\}_{x \in \mathcal{X}}$ based on the past observations \mathcal{F}_{t-1} . We consider three regimes for the DGP of losses $\{\ell_t\}_{t \in [T]}$: an adversarial regime, a stochastic regime with a margin condition, and a linear contextual adversarial regime with a self-bounding constraint.

4.1 Adversarial Regime

First, we introduce the adversarial regime, where we do not make any assumptions about the behavior of the nature. In this case, it is known that the lower bound is $O(\sqrt{T})$ when there is no context (Auer et al., 2002).

Note that adversarial linear contextual bandits can be defined in various ways. For example, some studies consider contextual bandits with adversarial contexts and fixed losses (Chu et al., 2011;

Abbasi-yadkori et al., 2011). Meanwhile, other studies address contextual bandits with adversarial contexts and adversarial losses (Kanade & Steinke, 2014; Hazan et al., 2016). This study focuses exclusively on contextual bandits with i.i.d. contexts and adversarial losses, as studied by Rakhlin & Sridharan (2016) and Syrgkanis et al. (2016). This study follows the setting of Neu & Olkhovskaya (2020), Kato & Ito (2023), and Kuroki et al. (2023).

4.2 Stochastic Regime with a Margin Condition

Next, we define a *margin condition*, which is often assumed in linear contextual bandits to characterize the difficulty of the problem instance (Li et al., 2021).

Since this section focuses on a stochastic regime, regression coefficients are fixed, and we denote them by θ_0 ; that is, $\theta_1 = \dots = \theta_t = \theta_0$. Note that under a stochastic regime,

$$\begin{aligned} R_T &= \mathbb{E} \left[\sum_{t=1}^T \sum_{a \in [K]} \Delta(a | X_t) \pi_t(a | X_t) \right] \\ &\geq \mathbb{E} \left[\sum_{t=1}^T \Delta(X_t) \sum_{a \neq a_T^*(X_t)} \pi_t(a | X_t) \right] \\ &= \mathbb{E} \left[\sum_{t=1}^T \Delta(X_t) (1 - \pi_t(a_T^*(X_t) | X_t)) \right], \end{aligned} \quad (1)$$

where $\Delta(a | x) = \left\langle \phi(a, x) - \phi(a_T^*(x), x), \theta_0 \right\rangle$, and

$$\Delta(x) = \min_{a \neq a_T^*(x)} \left\{ \left\langle \phi(a, x), \theta_0 \right\rangle - \left\langle \phi(a_T^*(x), x), \theta_0 \right\rangle \right\}.$$

Recall that π_t is our defined policy in round t (Section 2.1).

Regarding this suboptimality gap $\Delta(X)$, we define a stochastic regime with a margin condition as follows.

Definition 4.1 (Stochastic regime with a margin condition). Consider a stochastic regime with fixed regression coefficient $\theta_0 \in \Theta$, where for all $t \in [T]$, all $a \in [K]$ and any $x \in \mathcal{X}$, the loss is generated as $\ell_t(a, x) = \langle \phi(a, x), \theta_0 \rangle + \varepsilon_t(a)$. Furthermore, there exists a universal constant $\Delta_* > 0$, independent of T , and $\beta \in (0, +\infty)$, such that for any $h \in [0, \Delta_*]$, it holds that

$$\mathbb{P}(\Delta(X_t) \leq h) \leq \frac{1}{2} \left(\frac{h}{\Delta_*} \right)^\beta.$$

The margin condition plays a crucial role in regret analysis, as discussed in (1).

Note that when $\beta = \infty$, $\Delta(x) \geq \Delta_*$ holds for any $x \in \mathcal{X}$ and all $t \in [T]$, which is discussed in the following section.

A margin condition in Li et al. (2021) restricts the range of h as $[D\sqrt{\log(d)/T}, \Delta_*]$ for some universal constant $D > 0$, and they derive matching lower and upper bounds.

4.3 Adversarial Regime with a Self-Bounding Constraint

This section defines a regime with an adversarial corruption. Let $\Delta_* > 0$ be a universal constant, as used in Definition 4.1. If $\Delta(x) \geq \Delta_*$ holds for any $x \in \mathcal{X}$ in a stochastic regime, then the regret can be lower bounded as $R_T \geq \Delta_* \mathbb{E} \left[\sum_{t=1}^T \left(1 - \pi_t(a_t^*(X_t)) \right) \right]$.

Based on this intuition, we define a *linear contextual adversarial regime with a self-bounding constraint* below, as well as introduced by Kato & Ito (2023).

Definition 4.2 (Linear contextual adversarial regime with a self-bounding constraint). We say that the DGP is in a (Δ_*, C, T) -adversarial regime with a self-bounding constraint for some $\Delta_*, C > 0$ if the regret R_T is lower bounded as

$$R_T \geq \mathbb{E} \left[\sum_{t=1}^T \sum_{a \neq a_t^*(X_t)} \Delta_t(a | X_t) \pi_t(a | X_t) \right] - C,$$

where $\Delta_t(a | x) = \left\{ \left\langle \phi(a, x), \theta_t \right\rangle - \left\langle \phi(a_t^*(x), x), \theta_t \right\rangle \right\}$, and for all $a \in [K]$ and any $x \in \mathcal{X}$, $\Delta_t(a | x) \geq \Delta_*$ holds.

A linear contextual adversarial regime with a self-bounding constraint encompasses several important settings. For examples, see examples in Kato & Ito (2023). Note that in an adversarial regime, there exists $a \in [K]$ and $x \in \mathcal{X}$ such that $\Delta_t(x) := \left\langle \phi(a, x), \theta_t \right\rangle - \left\langle \phi(a_t^*(x), x), \theta_t \right\rangle < 0$. This is because $\Delta(a | x)$ and $\Delta_s(a | x)$ can take a different value for some $a \in [K]$ and $x \in \mathcal{X}$ if $t \neq s$.

5 Algorithm

In this section, we propose an algorithm for linear contextual bandits with adversarial corruption. We refer to our proposed algorithm as the α -Linear-Contextual (LC)-Tsallis-INF because it modifies the Tsallis-INF (Zimmert & Seldin, 2021), which is an FTRL-based algorithm with the Tsallis entropy regularization without contexts. Here, $\alpha \in (0, 1)$ is a parameter of the Tsallis-entropy. While we provide our algorithm for general α , we show the regret upper bound only for $1/2$. The pseudo-code is shown in Algorithm 1.

5.1 Proposed Algorithm: α -LC-Tsallis-INF

This section provides a BoBW algorithm for linear contextual bandits. We first define an estimator of θ_t and then develop an FTRL-based algorithm using this estimator.

For simplicity, when selecting an arm a with probability $\pi_t(a | x)$ given $x \in \mathcal{X}$, we denote $\Sigma(E)$ by Σ_t , where E is defined corresponding to π_t . Note that Σ_t is equal to

$$\Sigma_t = \mathbb{E}_{X_t \sim \mathcal{G}} \left[\sum_{a \in [K]} \pi_t(a | X_t) \phi(a, X_t) \phi^\top(a, X_t) \right].$$

Regression coefficient estimator. We define an estimator of the regression parameter θ_t as

$$\hat{\theta}_t := \hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right) := \tilde{\Sigma}_t^\dagger \phi(A_t, X_t) \ell_t(A_t, X_t),$$

where $\tilde{\Sigma}_t^\dagger$ is defined as

$$\tilde{\Sigma}_t^\dagger = \begin{cases} \Sigma_t^{-1} & \text{if the full information about } \mathcal{G} \text{ is given} \\ \hat{\Sigma}_t^\dagger & \text{if only finite samples are given from } \mathcal{G} \end{cases},$$

and $\hat{\Sigma}_t^\dagger$ is an approximation of Σ_t^{-1} by the MGR algorithm defined in Definition 2.

When $\tilde{\Sigma}_t^\dagger = \Sigma_t^{-1}$ holds, this estimator is unbiased for θ_t from $\mathbb{E} \left[\hat{\theta}_t(\Sigma_t) | \mathcal{F}_{t-1} \right] = \mathbb{E} \left[\Sigma_t^{-1} \phi(A_t, X_t) \ell_t(A_t, X_t) | \mathcal{F}_{t-1} \right] = \Sigma_t^{-1} \Sigma_t \theta_t = \theta_t$.

FTRL with the α -Tsallis entropy and $\hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right)$. By using the regression coefficient estimator $\hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right)$, we define our proposed algorithm, the α -LC-Tsallis-INF.

In each round $t \in [T]$, the α -LC-Tsallis-INF selects an arm with the following policy:

$$\pi_t(X_t) := (1 - \gamma_t) q_t(X_t) + \gamma_t e^*(X_t), \quad (2)$$

where recall that e^* is an exploration policy defined in Assumption 2.3, and

$$q_t(x) := \arg \min_{q \in \mathcal{P}_K} \left\{ \sum_{s=1}^{t-1} \left\langle \hat{\ell}_s(x), q \right\rangle + \frac{1}{\eta_t} \psi(q) \right\}, \quad (3)$$

$$q_1(x) := (1/K \ 1/K \ \dots \ 1/K)^\top,$$

$$\psi(q(x)) := \frac{1}{\alpha} \left(1 - \sum_{a \in [K]} q^\alpha(a | x) \right).$$

Here, the regularizer $\psi(q(x))$ is referred to as the α -Tsallis entropy (Zimmert & Seldin, 2021). We have not

yet specified η_t and γ_t . These parameters are defined in the following sections, depending on two cases: when the true Σ_t^{-1} is given, and it is approximated using finite samples from \mathcal{G} with the MGR algorithm, respectively.

5.2 The α -LC-Tsallis-INF with Σ_t^{-1}

First, we consider a case where Σ_t^{-1} is available under the full information about \mathcal{G} . To define the remaining parameters, we introduce the following notations: for each $t \in [T]$,

$$a_t^\dagger(x) := \arg \max_{a \in [K]} q_t(a | x),$$

$$\omega_t := \sup_{x \in \mathcal{X}} \min_{a \in [K]} \{1 - q_t(a | x)\} = \sup_{x \in \mathcal{X}} \left\{1 - q_t(a_t^\dagger(x))\right\}.$$

Then, we specify the parameters as $\gamma_t = \min\{1, \tilde{\gamma}_t\}$,

$$\eta_t := c^\dagger \sqrt{\frac{\sqrt{K}}{t \left(d + \frac{1}{\lambda_{\min}}\right)}}, \quad \tilde{\gamma}_t := \frac{8C_Z^2 C_\ell}{\lambda_{\min}} \eta_t \sqrt{\omega_t},$$

where $c^\dagger > 0$ is some universal constant.

5.3 The α -LC-Tsallis-INF with $\hat{\Sigma}_t^{-1}$

Next, we consider a case where Σ_t^{-1} is approximated with finite samples from \mathcal{G} by the MGR algorithm. In this case, our remaining task is to estimate Σ_t^{-1} . The difficulty of this task stems from the dependency on A_t , which varies across rounds. To address this issue, we employ the MGR proposed by [Neu & Olkhovskaya \(2020\)](#).

The MGR algorithm assumes that we have access to the distribution \mathcal{G} of X_t and estimates Σ_t^{-1} by using simulations with finite samples generated from \mathcal{G} . We show the MGR algorithm in [Algorithm 2](#). Note that we slightly modified the MGR algorithm in [Neu & Olkhovskaya \(2020\)](#) to estimate Σ_t^{-1} , while [Neu & Olkhovskaya \(2020\)](#) estimates $\Sigma_t^{-1}(a) := \mathbb{E}^{-1}[\mathbb{1}[A_t = a]\phi(a, X_0)\phi^\top(a, X_0)]$ in their setting with arm-independent contexts.

In [Algorithm 2](#), we define $U^{(k,j)}$ for which $\mathbb{E}[U^{(k,j)} | \mathcal{F}_{t-1}] = \Sigma_t$ holds. Here, we also have $\mathbb{E}[V^k | \mathcal{F}_{t-1}] = \mathbb{E}\left[\prod_{j=1}^k (I - \delta U^{(k,j)}) | \mathcal{F}_{t-1}\right] = (I - \delta \Sigma_t)^k$. Therefore, $\hat{\Sigma}_t^\dagger$ works as a good estimator of Σ_t^{-1} on expectations when $M_t = \infty$ because we have $\mathbb{E}\left[\hat{\Sigma}_t^\dagger | \mathcal{F}_{t-1}\right] = \delta I + \delta \sum_{k=1}^\infty (I - \delta \Sigma_t)^k = \mathbb{E}\left[\hat{\Sigma}_t^\dagger | \mathcal{F}_{t-1}\right] = \delta I + \delta \sum_{k=1}^\infty (I - \delta \Sigma_t)^k = \delta \sum_{k=0}^\infty (I - \delta \Sigma_t)^k = \delta (\delta \Sigma_t^{-1})^{-1} = \Sigma_t^{-1}$.

Algorithm 1 α -LC-Tsallis-INF.

Parameter: Learning rate $\eta_1, \eta_2, \dots, \eta_T > 0$.

for $t = 1, \dots, T$ **do**

Observe X_t .

Draw $A_t \in [K]$ following the policy $\pi_t(X_t) := (1 - \gamma_t)q_t(X_t) + \gamma_t e^*(X_t)$ defined in [\(2\)](#).

Observe the loss $\ell_t(A_t, X_t)$.

Compute $\hat{\theta}_t$.

end for

Algorithm 2 (Modified) MGR ([Neu & Olkhovskaya, 2020](#)).

Input: Context distribution \mathcal{G} and policy π_t .

for $k = 1, \dots, M_t$ **do**

for $j = 1, \dots, k$ **do**

Draw $X^{(k,j)} \sim \mathcal{G}$.

Compute $U^{(k,j)} =$

$\sum_{a \in [K]} \pi_t(a | X^{(k,j)}) \phi(a, X^{(k,j)}) \phi^\top(a, X^{(k,j)})$.

end for

Compute $V^{(k)} = \prod_{j=1}^k (I - \delta U^{(k,j)})$.

end for

Return: $\hat{\Sigma}_t^\dagger = \delta I + \delta \sum_{k=1}^{M_t} V^{(k)}$.

If M_t is finite, we analyze an approximation error of Σ_t^{-1} and discuss the influence on regret upper bounds. In such a case, we set the parameters as

$$\eta_t := c^\dagger \sqrt{\frac{\sqrt{K}}{t \left(d + \frac{\log(T)}{\lambda_{\min}}\right)}}, \quad \gamma_t := \min\{1, \tilde{\gamma}_t\},$$

$$\tilde{\gamma}_t := \frac{8C_Z^2 C_\ell \log(T)}{\lambda_{\min}} \eta_t \sqrt{\omega_t}, \quad M_t := \frac{1}{8\eta_t \sqrt{\omega_t}} - 1,$$

and $\delta := \frac{1}{C_Z^2 C_\ell}$,

where $c^\dagger > 0$ is some universal constant.

The MGR algorithm requires contextual distribution \mathcal{G} and policy π_t in simulation. Several studies attempt to relax this assumption, such as [Luo et al. \(2021\)](#) and [Liu et al. \(2023\)](#), by incurring some computational costs ([Table 1](#)).

6 Regret Analysis for the 1/2-LC-Tsallis-INF

We provide upper bounds for the regret of the α -LC-Tsallis-INF algorithm when $\alpha = 1/2$ (1/2-LC-Tsallis-INF).

For the 1/2-Tsallis-INF with a regression coefficient

estimator $\hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right)$, let us define

$$\xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right) := \begin{cases} \sqrt{K} \left(d + \frac{1}{\lambda_{\min}} \right) & \text{if } \tilde{\Sigma}_t^\dagger = \Sigma_t^{-1} \\ \sqrt{K} \left(d + \frac{\log(T)}{\lambda_{\min}} \right) & \text{if } \tilde{\Sigma}_t^\dagger = \hat{\Sigma}_t^{-1} \end{cases}.$$

This is one of the leading factors in our upper bounds.

Then, we show the following upper bound, from which we derive upper bounds in adversarial and stochastic regimes. We show the proof in Appendix A.1 and A.4.

Theorem 6.1 (General regret bounds). *Consider the 1/2-LC-Tsallis-INF with the estimator $\hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right)$. Assumptions 2.1 and 2.3–2.5 hold. Then, the regret satisfies*

$$R_T = O \left(\mathbb{E} \left[\sum_{t=1}^T \frac{\sqrt{\xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right) \omega_t}}{\sqrt{t}} \right] \right).$$

Because $\omega_t \leq 1$, by replacing ω_t with 1 in Theorem 6.1, we can directly obtain a regret upper bound in the adversarial regime in the following theorem.

Theorem 6.2 (Regret upper bound in an adversarial regime). *Consider the 1/2-LC-Tsallis-INF with the estimator $\hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right)$. Assume that the loss is generated under an adversarial regime. Suppose that Assumptions 2.1 and 2.3–2.5 hold. Then, the regret satisfies*

$$R_T = O \left(\sqrt{\xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right) T} \right).$$

Note that this result does not require Assumptions 2.2, which restricts the context support to be finite.

Next, we show a regret upper bound in a stochastic regime with a margin condition, which depends on the parameter $\beta \in (0, \infty]$. Recall that β decides the behavior of $\Delta(x)$. The proof is shown in Appendix A.5.

Theorem 6.3 (Regret upper bound in a stochastic regime with a margin condition). *Consider the 1/2-LC-Tsallis-INF with the estimator $\hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right)$. Assume that the loss is generated under a stochastic regime with a margin condition (Definition 4.1). Suppose that Assumption 2.1–2.5 hold. Then, the regret satisfies $R_T =$*

$$O \left(\left\{ \frac{1 + \beta}{\beta \Delta_*} \right\}^{\frac{\beta}{2+\beta}} \left\{ L \xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right) \log(T) \right\}^{\frac{1+\beta}{2+\beta}} T^{\frac{1}{2+\beta}} \right).$$

For example, when $\beta = \infty$, then the regret is upper bounded as $R_T = O \left(\frac{1}{\Delta_*} L \xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right) \log(T) \right)$. When

$\beta = 1$, then the regret is upper bounded by $R_T = O \left(\left\{ \frac{1}{\Delta_*} \right\}^{\frac{1}{3}} \left\{ L \xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right) \log(T) \right\}^{\frac{2}{3}} T^{\frac{1}{3}} \right)$.

Lastly, we derive a regret upper bound in a linear contextual adversarial regime with a self-bounding constraint, which is a generalization of the stochastic and adversarial regimes under $\beta = \infty$ in a margin condition. We provide the proof in Appendix A.6.

Theorem 6.4 (Regret upper bound in a linear contextual adversarial regime with a self-bounding constraint). *Consider the 1/2-LC-Tsallis-INF with the estimator $\hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right)$. Assume that the loss is generated under a linear contextual adversarial regime with a self-bounding constraint (Definition 4.2). Suppose that Assumption 2.1–2.5 hold. Then,*

$$R_T = O \left(\frac{L \xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right)}{\Delta_*} \log(T) \right) + C.$$

holds. Moreover, for $\frac{K-1}{\Delta_*} \left(\log \left(\frac{T \Delta_*^2}{K-1} \right) + 1 \right) \leq C \leq \Delta_* T$, the regret satisfies

$$R_T = O \left(\sqrt{\frac{C L \xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right)}{\Delta_*}} \sqrt{\log \left(\frac{\Delta_* T}{C} \right)} \right).$$

Theorem 6.4 implies that the regret satisfies $R_T =$

$$O \left(\frac{L \xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right)}{\Delta_*} \log(T) + \sqrt{\frac{C L \xi^{\text{Tsallis}} \left(\tilde{\Sigma}_t^\dagger \right)}{\Delta_*}} \sqrt{\log_+ \left(\frac{\Delta_* T}{C} \right)} \right),$$

tightly depending on T . Recall $\log_+(x) = \max\{1, \log(x)\}$.

7 Conclusion

We presented a BoBW algorithm for linear contextual bandits whose regret upper bounds tightly depend on T . By extending the existing FTRL-based approach provided by Kato & Ito (2023) and Kuroki et al. (2023), we developed an FTRL-based algorithm employing the Tsallis-entropy. Our proposed algorithm, the 1/2-LC-Tsallis-INF, exhibits tighter dependence on T compared to the algorithm proposed by Kato & Ito (2023) and Kuroki et al. (2023) in the stochastic regime. Compared to the reduction approach by Kuroki et al. (2023), our algorithm is easy to implement and its regret has a tighter dependency regarding T . Furthermore, we derived a regret upper bound dependent on a margin condition. Specifically, when we know the full information about \mathcal{G} , in a

stochastic regime with a margin condition, we derived a regret upper bound

$$O\left(\left\{\frac{1+\beta}{\beta\Delta_*}\right\}^{\frac{\beta}{2+\beta}}\left\{L\sqrt{K}\left(d+\frac{1}{\lambda_{\min}}\right)\log(T)\right\}^{\frac{1+\beta}{2+\beta}}T^{\frac{1}{2+\beta}}\right),$$

where β is a parameter of the margin condition. In the linear contextual bandit with a self-bounding constraint, we derived a regret upper bound

$$O\left(\frac{L\sqrt{K}\left(d+\frac{1}{\lambda_{\min}}\right)\log(T)}{\Delta_*}+\sqrt{\frac{CL\sqrt{K}\left(d+\frac{1}{\lambda_{\min}}\right)}{\Delta_*}}\sqrt{\log_+\left(\frac{\Delta_*T}{C}\right)}\right),$$

where C is a parameter of an adversarial corruption. Additionally, in the adversarial regime, our algorithm has $O\left(\sqrt{L\sqrt{K}\left(d+\frac{1}{\lambda_{\min}}\right)T}\right)$ regret upper bound. The important remaining problem is to improve the dependence on T when $\beta \in (0, \infty)$ in a stochastic regime.

Broader Impact

This paper presents work whose goal is to advance the field of the theory of the multi-armed bandit problem. There are many potential societal consequences of our work, none of which we feel must be specifically highlighted here.

References

- Abbasi-yadkori, Y., Pál, D., and Szepesvári, C. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2011.
- Abe, N. and Long, P. M. Associative reinforcement learning using linear probabilistic concepts. In *International Conference on Machine Learning (ICML)*, 1999.
- Auer, P. and Chiang, C.-K. An algorithm with nearly optimal pseudo-regret for both stochastic and adversarial bandits. In *Conference on Learning Theory (COLT)*, 2016.
- Auer, P., Cesa-Bianchi, N., and Fischer, P. Finite-time analysis of the multiarmed bandit problem. *Machine Learning*, 47(2):235–256, 2002.
- Bastani, H. and Bayati, M. Online decision making with high-dimensional covariates. *Operations Research*, 68(1), 2020.
- Beygelzimer, A., Langford, J., Li, L., Reyzin, L., and Schapire, R. Contextual bandit algorithms with supervised learning guarantees. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2011.
- Bubeck, S. and Slivkins, A. The best of both worlds: Stochastic and adversarial bandits. In *Conference on Learning Theory (COLT)*, 2012.
- Chen, C., Luo, L., Zhang, W., Yu, Y., and Lian, Y. Efficient and robust high-dimensional linear contextual bandits. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2020.
- Chu, W., Li, L., Reyzin, L., and Schapire, R. Contextual bandits with linear payoff functions. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2011.
- Dani, V., Hayes, T. P., and Kakade, S. M. Stochastic linear optimization under bandit feedback. In *Annual Conference Computational Learning Theory (COLT)*, 2008.
- Dann, C., Wei, C.-Y., and Zimmert, J. A blackbox approach to best of both worlds in bandits and beyond. In Neu, G. and Rosasco, L. (eds.), *Conference on Learning Theory (COLT)*, volume 195, pp. 5503–5570. PMLR, 2023a.
- Dann, C., Wei, C.-Y., and Zimmert, J. Best of both worlds policy optimization. In *International Conference on Machine Learning (ICML)*, 2023b.
- Ding, Q., Hsieh, C.-J., and Sharpnack, J. Robust stochastic linear contextual bandits under adversarial attacks. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2022.
- Goldenshluger, A. and Zeevi, A. A linear response bandit problem. *Stochastic Systems*, 2013.
- Gupta, A., Koren, T., and Talwar, K. Better algorithms for stochastic bandits with adversarial corruptions. In *Conference on Learning Theory (COLT)*, 2019.
- Hazan, E., Koren, T., Livni, R., and Mansour, Y. Online learning with low rank experts. In *Conference on Learning Theory (COLT)*, 2016.
- He, J., Zhou, D., Zhang, T., and Gu, Q. Nearly optimal algorithms for linear contextual bandits with adversarial corruptions. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

- Ito, S., Tsuchiya, T., and Honda, J. Nearly optimal best-of-both-worlds algorithms for online learning with feedback graphs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.
- Jin, T., Liu, J., and Luo, H. Improved best-of-both-worlds guarantees for multi-armed bandits: Ftrl with general regularizers and multiple optimal arms. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.
- Kanade, V. and Steinke, T. Learning hurdles for sleeping experts. *ACM Transactions on Computation Theory*, 6(3), 2014.
- Kato, M. and Ito, S. Best-of-both-worlds linear contextual bandits, 2023. arXiv:2312.16489.
- Kong, F., Zhao, C., and Li, S. Best-of-three-worlds analysis for linear bandits with follow-the-regularized-leader algorithm. In *Conference on Learning Theory (COLT)*, 2023.
- Kuroki, Y., Rumi, A., Tsuchiya, T., Vitale, F., and Cesa-Bianchi, N. Best-of-both-worlds algorithms for linear contextual bandits, 2023.
- Lattimore, T. and Szepesvári, C. *Bandit Algorithms*. Cambridge University Press, 2020.
- Lee, C.-W., Luo, H., Wei, C.-Y., Zhang, M., and Zhang, X. Achieving near instance-optimality and minimax-optimality in stochastic and adversarial linear bandits simultaneously. In *International Conference on Machine Learning (ICML)*, 2021.
- Li, K., Yang, Y., and Narisetty, N. N. Regret lower bound and optimal algorithm for high-dimensional contextual linear bandit. *Electronic Journal of Statistics*, 15(2):5652 – 5695, 2021.
- Li, L., Chu, W., Langford, J., and Schapire, R. E. A contextual-bandit approach to personalized news article recommendation. In *International Conference on World Wide Web (WWW)*, 2010.
- Liu, H., Wei, C.-Y., and Zimmert, J. Bypassing the simulator: Near-optimal adversarial linear contextual bandits. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.
- Luo, H., Wei, C.-Y., and Lee, C.-W. Policy optimization in adversarial mdps: Improved exploration via dilated bonuses. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 34, pp. 22931–22942, 2021.
- Lykouris, T. and Vassilvtiskii, S. Competitive caching with machine learned advice. In *International Conference on Machine Learning (ICML)*, 2018.
- Masoudian, S. and Seldin, Y. Improved analysis of the tsallis-inf algorithm in stochastically constrained adversarial bandits and stochastic bandits with adversarial corruptions. In *Conference on Learning Theory (COLT)*, 2021.
- Neu, G. and Olkhovskaya, J. Efficient and robust algorithms for adversarial linear contextual bandits. In *Conference on Learning Theory (COLT)*, 2020.
- Rakhlin, A. and Sridharan, K. Bistro: An efficient relaxation-based method for contextual bandits. In *International Conference on Machine Learning (ICML)*, 2016.
- Rouyer, C. and Seldin, Y. Tsallis-inf for decoupled exploration and exploitation in multi-armed bandits. In *Conference on Learning Theory (COLT)*, volume 125, pp. 3227–3249. PMLR, 2020.
- Seldin, Y. and Lugosi, G. An improved parametrization and analysis of the EXP3++ algorithm for stochastic and adversarial bandits. In *Conference on Learning Theory (COLT)*, 2017.
- Seldin, Y. and Slivkins, A. One practical algorithm for both stochastic and adversarial bandits. In *International Conference on Machine Learning (ICML)*, 2014.
- Syrsganis, V., Luo, H., Krishnamurthy, A., and Schapire, R. E. Improved regret bounds for oracle-based adversarial contextual bandits. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2016.
- Tewari, A. and Murphy, S. A. From ads to interventions: Contextual bandits in mobile health. In *Mobile Health: Sensors, Analytic Methods, and Applications*, pp. 495–517, 2017.
- Tsuchiya, T., Ito, S., and Honda, J. Best-of-both-worlds algorithms for partial monitoring. In *International Conference on Algorithmic Learning Theory (ALT)*, 2023a.
- Tsuchiya, T., Ito, S., and Honda, J. Stability-penalty-adaptive follow-the-regularized-leader: Sparsity, game-dependency, and best-of-both-worlds. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023b.

- Wang, X., Wei, M., and Yao, T. Minimax concave penalized multi-armed bandit model with high-dimensional covariates. In *International Conference on Machine Learning (ICML)*, 2018.
- Wei, C.-Y. and Luo, H. More adaptive algorithms for adversarial bandits. In *Conference on Learning Theory (COLT)*, 2018.
- Zhao, H., Zhou, D., and Gu, Q. Linear contextual bandits with adversarial corruptions, 2021. URL <https://openreview.net/forum?id=Wz-t1o0TWa>.
- Zimmert, J. and Seldin, Y. Tsallis-inf: An optimal algorithm for stochastic and adversarial bandits. *Journal of Machine Learning Research*, 22(1), 2021.

A Proof of Theorems 6.1 and 6.4

This section provides the proofs for Theorem 6.1. In Appendix A.1, we provide preliminary results for the proof. Then, in Appendix A.2, we decompose the regret into the stability and penalty terms. In Appendix A.3, we upper bound those terms. Lastly, in Appendix A.4, we prove Theorem 6.1.

A.1 Preliminaries for the Proof of Theorem 6.1

Let X_0 be a sample from the context distribution \mathcal{G} independent of \mathcal{F}_T . Let $D(p, q)$ denote a Bregman divergence between $p, q \in \Pi$ with respect to ψ_t ; that is,

$$D(p, q) := \psi(p) - \psi(q) - \langle \nabla \psi(q), p - q \rangle.$$

In our proof, the following proposition plays an essential role.

Proposition A.1 (From Lemma 4.4 in Kato & Ito (2023)). *Consider the 1/2-LC-Tsallis-INF with our defined parameters. Then, the regret satisfies*

$$R_T \leq \mathbb{E} \left[\sum_{t=1}^T \left\{ C_\ell \gamma_t + \langle \widehat{\ell}_t(X_0), q_t(X_0) - q_{t+1}(X_0) \rangle - \frac{1}{\eta_t} D(q_{t+1}(X_0), q_t(X_0)) - \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) H(q_t(X_0)) \right\} \right. \\ \left. + 2 \underbrace{\sum_{t=1}^T \max_{a \in [K]} \left| \mathbb{E} [\langle X_t, \theta_t(a) - \widehat{\theta}_t(a) \rangle] \right|}_{= \text{bias term}} \right],$$

where

$$H(q(x)) := 2 \left(- \sum_{a \in [K]} \sqrt{q(x | x + 1)} \right)$$

For the completeness, we show the proof below.

Proof. Let us define $\pi^* \in \Pi$ as $\pi^*(a_T^*(x) | x) = 1$ and $\pi^*(a | x) = 0$ for all $a \in [K] \setminus \{a_T^*(x)\}$ for any $x \in \mathcal{X}$.

Recall that in (3), we defined q_t as

$$q_t(x) := \arg \min_{q \in \mathcal{P}_K} \left\{ \sum_{s=1}^{t-1} \langle \widehat{\ell}_s(x), q \rangle + \frac{1}{\eta_t} \psi(q) \right\}$$

for $t \geq 2$.

From the definition of our algorithm, we have

$$R_T = \mathbb{E} \left[\sum_{t=1}^T \left\{ \ell_t(A_t, X_t) - \ell_t(a_T^*(X_t), X_t) \right\} \right] \\ = \mathbb{E} \left[\sum_{t=1}^T \langle \ell_t(X_t), \pi_t(X_t) - \pi^*(X_t) \rangle \right] \\ = \mathbb{E} \left[\sum_{t=1}^T \langle \ell_t(X_t), q_t(X_t) - \pi^*(X_t) \rangle + \sum_{t=1}^T \gamma_t \langle \ell_t(X_t), e^*(X_t) - q_t(X_t) \rangle \right] \\ \leq \mathbb{E} \left[\sum_{t=1}^T \langle \ell_t(X_t), q_t(X_t) - \pi^*(X_t) \rangle + C_\ell \sum_{t=1}^T \gamma_t \right] \\ = \mathbb{E} \left[\sum_{t=1}^T \langle \ell_t(X_0), q_t(X_0) - \pi^*(X_0) \rangle + C_\ell \sum_{t=1}^T \gamma_t \right]$$

$$\begin{aligned}
&= \mathbb{E} \left[\sum_{t=1}^T \langle \widehat{\ell}_t(X_0), q_t(X_0) - \pi^*(X_0) \rangle + C_\ell \sum_{t=1}^T \gamma_t \right] + \mathbb{E} \left[\sum_{t=1}^T \langle \ell_t(X_0) - \widehat{\ell}_t(X_0), q_t(X_0) - \pi^*(X_0) \rangle \right] \\
&\leq \mathbb{E} \left[\sum_{t=1}^T \langle \widehat{\ell}_t(X_0), q_t(X_0) - \pi^*(X_0) \rangle + C_\ell \sum_{t=1}^T \gamma_t \right] + 2 \sum_{t=1}^T \max_{a \in [K]} \left| \mathbb{E} \left[\langle X_0, \theta_t(a) - \widehat{\theta}_t(a) \rangle \right] \right|. \tag{4}
\end{aligned}$$

We show that for any $x \in \mathcal{X}$ and any $p^* \in \mathcal{P}_K$, we have

$$\sum_{t=1}^T \langle \widehat{\ell}_t(x), q_t(x) - p^*(x) \rangle \leq \sum_{t=1}^T \left\{ \langle \widehat{\ell}_t(x), q_t(x) - q_{t+1}(x) \rangle - \frac{1}{\eta_t} D(q_{t+1}(x), q_t(x)) - \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) H(q_t(x)) \right\}. \tag{5}$$

This result follows from the definition of q_t ; that is,

$$\begin{aligned}
&\left\langle \sum_{t=1}^T \widehat{\ell}_t(x), p^*(x) \right\rangle + \frac{1}{\eta_T} \psi(p^*(x)) \\
&\geq \left\langle \sum_{t=1}^T \widehat{\ell}_t(x), q_{T+1}(x) \right\rangle + \frac{1}{\eta_T} \psi(q_{T+1}(x)) \\
&\geq \left\langle \sum_{t=1}^{T-1} \widehat{\ell}_t(x), q_{T+1}(x) \right\rangle + \langle \widehat{\ell}_T(x), q_{T+1}(x) \rangle + \frac{1}{\eta_T} \psi(q_{T+1}(x)) \\
&\geq \left\langle \sum_{t=1}^{T-1} \widehat{\ell}_t(x), q_T(x) \right\rangle + \langle \widehat{\ell}_T(x), q_{T+1}(x) \rangle + \frac{1}{\eta_T} \psi(q_T(x)) + \frac{1}{\eta_T} D(q_{T+1}, q_T) \\
&\geq \sum_{t=1}^T \left\{ \langle \widehat{\ell}_t(x), q_{t+1}(x) \rangle + \left(\frac{1}{\eta_{t-1}} - \frac{1}{\eta_t} \right) \psi(q_t(x)) + \frac{1}{\eta_t} D(q_{t+1}, q_t) \right\}.
\end{aligned}$$

Combining (5) with (4) yields the statement. \square

Facts on the Tsallis entropy. The Bregman divergence associated with the α -Tsallis entropy

$$\psi(q(x)) = -\frac{1}{\alpha} \left(\sum_{a \in [K]} q_t^\alpha(a | x) + 1 \right)$$

is given as the following lemma.

Lemma A.2. For any $x \in \mathcal{X}$, $\alpha \in (0, 1)$, the α -Tsallis entropy $\psi(q(x)) = -\frac{1}{\alpha} \left(\sum_{a \in [K]} q_t^\alpha(a | x) + 1 \right)$ and $p(x), q(x) \in \mathcal{P}_K(K)$, the Bregman divergence is given as

$$D(p(x), q(x)) = \frac{1}{\alpha} \sum_{a \in [K]} (q^\alpha(a | x) + \alpha(p(a | x) - q(a | x))q^{\alpha-1}(a | x) - p^\alpha(a | x)) = \sum_{a \in [K]} d(p(a | x), q(a | x)),$$

where for $p, q \in (0, 1)$, we define

$$d(p, q) := \frac{1}{\alpha} q^\alpha + (p - q)q^{\alpha-1} - \frac{1}{\alpha} p^\alpha \leq \frac{1 - \alpha}{2} (\min\{p, q\})^{\alpha-2} (p - q)^2.$$

Estimation error of Σ_t^{-1} . When estimating Σ_t^{-1} , we incur its estimation error. To measure the estimation error, we focus on bias of $\widehat{\theta}_t(\widehat{\Sigma}_t^\dagger)$ caused from the estimation error, which is upper bounded as follows:

Lemma A.3. Suppose that Assumptions 2.1–2.5 hold. Then, under the MGR with $\gamma_t := \frac{8C_z^2 C_\ell \log(T)}{\delta \lambda_{\min}} \eta_t \sqrt{\omega_t}$, $M_t = \frac{1}{8\eta_t \sqrt{\omega_t}} - 1$ and $\delta = \frac{1}{C_z^2 C_\ell}$, we have

$$\left| \mathbb{E} \left[\langle X_t, \theta_t - \widehat{\theta}_t(\widehat{\Sigma}_t^\dagger) \rangle \right] \right| \leq \frac{C_z C_\Theta}{T}.$$

Proof. As well as the proof of Lemma 5 in Neu & Olkhovskaya (2020), we have

$$\left| \mathbb{E} \left[\langle \phi(a, X_t), \theta_t - \hat{\theta}_t \rangle \right] \right| \leq C_Z C_\Theta \exp(-\gamma_t \delta \lambda_{\min} M_t).$$

Then, we have

$$\begin{aligned} \exp(-\gamma_t \delta \lambda_{\min} M_t) &= \exp\left(-\frac{8C_Z^2 C_\ell \log(T)}{\lambda_{\min}} \eta_t \sqrt{\omega_t} \cdot \delta \lambda_{\min} M_t\right) \\ &\leq \exp(-8 \log(T) \eta_t \sqrt{\omega_t} \cdot M_t) \\ &\leq \exp\left(-8 \log(T) \eta_t \sqrt{\omega_t} \cdot \left\{ \frac{1}{8\eta_t \sqrt{\omega_t}} - 1 \right\}\right) \leq \exp(-\log(T)) = \frac{1}{T}, \end{aligned}$$

where recall that we defined $M_t = \frac{1}{8\eta_t \sqrt{\omega_t}} - 1$ □

Upper bound of the estimator of $x^\top \tilde{\Sigma}_t^{-1} z$ for $x, z \in \mathcal{X}$. In our analysis, we are required to upper bound $x^\top \tilde{\Sigma}_t^{-1} X_t$ for any $x \in \mathcal{X}$. This section provides an upper bound of $x^\top \tilde{\Sigma}_t^{-1} z$ for $x, z \in \mathcal{X}$, which also gives an upper bound for $\mathbb{E} \left[\pi_t(a | X_0) \hat{\ell}_t^2(a | X_0) | \mathcal{F}_{t-1} \right]$.

Lemma A.4. *When $\tilde{\Sigma}_t^{-1} = \hat{\Sigma}_t^{-1}$, we consider the MGR with $M_t = \frac{1}{8\eta_t \sqrt{\omega_t}} - 1$ and $\delta = \frac{1}{C_Z^2 C_\ell}$. Suppose that Assumptions 2.1, 2.3, and 2.5 hold. Then, for any $x, z \in \mathcal{Z}$, it holds that*

$$x^\top \tilde{\Sigma}_t^{-1} z \leq \frac{1}{C_\ell} \frac{1}{8\eta_t \sqrt{\omega_t}}$$

for $\tilde{\Sigma}_t^{-1} \in \left\{ \Sigma_t^{-1}, \hat{\Sigma}_t^{-1} \right\}$.

Proof. When $\tilde{\Sigma}_t^{-1} = \hat{\Sigma}_t^{-1}$, the result follows from

$$\left| x^\top \tilde{\Sigma}_t^{-1} z \right| \leq C_Z^2 \|\hat{\Sigma}_t^{-1}\|_{\text{op}} \leq C_Z^2 \delta \left(1 + \sum_{m=1}^M \|V^k\|_{\text{op}} \right) \leq C_Z^2 \delta (M+1) = (M+1)/C_\ell. \quad (6)$$

When $\tilde{\Sigma}_t^{-1} = \Sigma_t^{-1}$, we obtain the result from Assumption 2.5 and the Cauchy-Schwarz inequality. □

This lemma directly yields the following lemma.

Lemma A.5. *When $\tilde{\Sigma}_t^{-1} = \hat{\Sigma}_t^{-1}$, we consider the MGR with $M_t = \frac{1}{4\eta_t \sqrt{\omega_t}} - 1$ and $\delta = \frac{1}{C_Z^2 C_\ell}$. Suppose that Assumptions 2.1–2.5 hold. Then, for any $x, z \in \mathcal{Z}$, from (6), it holds that*

$$\left| \hat{\ell}_t(a, x) \right| = \left| x^\top (a) \tilde{\Sigma}_t^\dagger \phi^\top(a, X_t) \ell_t(a, X_t) \right| \leq \left\{ C_Z^2 \delta (M+1) \right\} \cdot C_\ell \leq \frac{1}{8\eta_t \sqrt{\omega_t}}$$

for $\tilde{\Sigma}_t^{-1} \in \left\{ \Sigma_t^{-1}, \hat{\Sigma}_t^{-1} \right\}$.

Proof. When $\tilde{\Sigma}_t^{-1} = \hat{\Sigma}_t^{-1}$, from Lemma A.4, the result follows from

$$\left| \tilde{\ell}_t(a, x) \right| \leq C_\ell \frac{1}{C_\ell} \frac{1}{8\eta_t \sqrt{\omega_t}} = \frac{1}{8\eta_t \sqrt{\omega_t}}.$$

When $\tilde{\Sigma}_t^{-1} = \Sigma_t^{-1}$, the result follows from $\left| \hat{\ell}_t(a, x) \right| \leq C_\ell \left| x^\top (a) \tilde{\Sigma}_t^\dagger \phi^\top(a, X_t) \right| \leq C_\ell \frac{1}{C_\ell} \frac{1}{8\eta_t \sqrt{\omega_t}}$. □

Margin condition. To utilize a margin condition for deriving a regret upper bound, we show the following lemma. The proof is shown in Appendix B.

Lemma A.6. Let $U \in [0, 1]$ and $V \in \mathbb{R}$ be some random variables. Let $\Delta_* > 0$ be some universal constant. For $\beta \in (0, \infty]$, if the random variable U has a mean $\mathbb{E}[U] = \mu$ and the random variable V satisfies

$$F(h) := \mathbb{P}(V \leq h) \leq \frac{1}{2} \left(\frac{h}{\Delta_*} \right)^\beta$$

for any $h \in [0, \Delta_*]$, and $\mu \in [0, \frac{1}{2}]$ holds, then

$$\mathbb{E}[UV] \geq \frac{\Delta_* \beta}{2(1 + \beta)} (2\mu)^{\frac{1+\beta}{\beta}}$$

holds.

A.2 Stability and Penalty Decomposition

Following the standard analysis of FTRL methods, we decompose the regret into stability and penalty terms. Based on the result in Lemma A.1, let us define $r_T(x)$ as

$$r_T(x) := \mathbb{E} \left[\sum_{t=1}^T \left\{ C_\ell \gamma_t + \left\langle \widehat{\ell}_t(X_0), q_t(X_0) - q_{t+1}(X_0) \right\rangle - \frac{1}{\eta_t} D(q_{t+1}(X_0), q_t(X_0)) - \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) H(q_t(X_0)) \mid X_0 = x \right\} \right].$$

This function $r_T(x)$ bounds R_T as

$$R_T \leq \mathbb{E}[r_T(X_0)] + 2 \underbrace{\sum_{t=1}^T \max_{a \in [K]} \left| \mathbb{E} \left[\langle X_t, \theta_t(a) - \widehat{\theta}_t(a) \rangle \right] \right|}_{= \text{bias term}}.$$

The standard FTRL analysis breaks the pseudo-regret into penalty and stability terms. Following this approach, we decompose the pointwise regret upper bound $r_T(x)$ as follows:

$$\begin{aligned} r_T(x) = \mathbb{E} \left[\underbrace{\sum_{t=1}^T \left\{ C_\ell \gamma_t + \left\langle \widehat{\ell}_t(X_0), q_t(X_0) - q_{t+1}(X_0) \right\rangle - \frac{1}{\eta_t} D(q_{t+1}(X_0), q_t(X_0)) \mid X_0 = x \right\}}_{= \text{stability term}} \right. \\ \left. - \underbrace{\sum_{t=1}^T \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) H(q_t(X_0)) \mid X_0 = x}_{= \text{penalty term}} \right]. \end{aligned} \quad (7)$$

where $\widehat{L}_t(x) = \sum_{s=1}^t \widehat{\ell}_s(x)$.

We show upper bounds by upper bounding the stability, penalty, and bias terms.

A.3 Upper Bounds for the Stability, Penalty, and Bias Terms

In this section, for any $x \in \mathcal{X}$, we derive upper bounds for the following terms separately:

$$\text{stability}_t(x) := C_\ell \gamma_t + \left\langle \widehat{\ell}_t(x), q_t(x) - q_{t+1}(x) \right\rangle - \frac{1}{\eta_t} D(q_{t+1}(x), q_t(x)), \quad (8)$$

$$\text{penalty}_t(x) := - \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) H(q_t(X_0)), \quad (9)$$

$$\text{bias} := \sum_{t=1}^T \max_{a \in [K]} \left| \mathbb{E} \left[\langle X_t, \theta_t(a) - \widehat{\theta}_t(a) \rangle \right] \right|. \quad (10)$$

(I) Bounding the stability term. To bound the stability term, we obtain the following lemma. Recall that for any $x \in \mathcal{X}$ and $q(x) \in \mathcal{P}_K$, we defined $a^\dagger(x) \in \arg \max_{a \in [K]} q(a | x)$.

Lemma A.7. Consider the 1/2-LC-Tsallis-INF with the estimator $\widehat{\theta}_t \left(\widetilde{\Sigma}_t^\dagger \right)$. Assumptions 2.1, and 2.3–2.5 hold. If

$$|\ell_t(a | x)| \leq \frac{1-\alpha}{4} \min \{q(a^\dagger(x) | x), 1 - q(a^\dagger(x) | x)\}^{\alpha-1}$$

holds for all $a \in [K] \setminus a^\dagger$, then we have

$$\begin{aligned} & \left\langle \widehat{\ell}_t(x), q(x) - p(x) \right\rangle - \frac{1}{\eta_t} D(p(x), q(x)) \\ & \leq \frac{4}{1-\alpha} \left(\sum_{a \neq a^\dagger(x)} q^{2-\alpha}(a | x) \ell_t^2(a | x) + \min \{q(a^\dagger(x) | x), 1 - q(a^\dagger(x) | x)\}^{2-\alpha} \ell_t^2(a^\dagger(x), x) \right). \end{aligned}$$

The proof is shown in Appendix C.1. By using this lemma, we show the following upper bound for the stability term.

Lemma A.8 (Upper bound for the stability term). Consider the 1/2-LC-Tsallis-INF with the estimator $\widehat{\theta}_t \left(\widetilde{\Sigma}_t^\dagger \right)$. Assumptions 2.1, and 2.3–2.5 hold. Consider $T_0 \in [T]$ such that

$$T_0 \geq \begin{cases} 4 \left(\frac{8C_{\mathbb{Z}}^2 C_\ell c^\dagger}{\lambda_{\min}} \right)^2 \frac{\sqrt{K}}{\left(d + \frac{1}{\lambda_{\min}}\right)} & \text{if } \widetilde{\Sigma}_t^{-1} = \Sigma_t^{-1} \\ 4 \left(\frac{8C_{\mathbb{Z}}^2 C_\ell \log(T)}{\lambda_{\min}} c^\dagger \right)^2 \frac{\sqrt{K}}{\left(d + \frac{\log(T)}{\lambda_{\min}}\right)} & \text{if } \widetilde{\Sigma}_t^{-1} = \widehat{\Sigma}_t^{-1}. \end{cases} \quad (11)$$

If $\min_a \eta_t \widehat{\ell}_t(a, x) = \min_a \eta_t \phi^\top(a, x) \widetilde{\Sigma}_t^\dagger \phi(a, X_t) \ell_t(a, X_t) \geq -1$ holds, then for all $t \geq T_0$

$$\text{stability}_t(x) \leq 2\eta_t \sqrt{\omega_t} \sum_{a \in [K]} \widehat{\ell}_t^2(a | x) \pi_t(a | x)$$

holds, where recall that the stability term $\text{stability}_t(x)$ is defined in (8).

Note that the condition “ $t \geq T_0$ ” is introduced to specify a range of t , where $\gamma_t \leq 1/2$ holds from the definitions of γ_t , $\widetilde{\gamma}_t$, and η_t . When Σ_t^{-1} is given, recall that we have $\gamma_t = \min\{1, \gamma_t\}$,

$$\eta_t = c^\dagger \sqrt{\frac{\sqrt{K}}{t \left(d + \frac{1}{\lambda_{\min}}\right)}}, \quad \text{and} \quad \widetilde{\gamma}_t = \frac{8C_{\mathbb{Z}}^2 C_\ell}{\lambda_{\min}} \eta_t \sqrt{\omega_t}.$$

Here, we have

$$\widetilde{\gamma}_t \leq \frac{8C_{\mathbb{Z}}^2 C_\ell c^\dagger}{\lambda_{\min}} \sqrt{\frac{\sqrt{K}}{t \left(d + \frac{1}{\lambda_{\min}}\right)}}.$$

Then, we have

$$\gamma_t \leq \frac{8C_{\mathbb{Z}}^2 C_\ell c^\dagger}{\lambda_{\min}} \sqrt{\frac{\sqrt{K}}{t \left(d + \frac{1}{\lambda_{\min}}\right)}}.$$

Therefore, $\gamma_t \leq 1/2$ holds for $t > T_0$ such that

$$T_0 \geq 4 \left(\frac{8C_{\mathbb{Z}}^2 C_\ell c^\dagger}{\lambda_{\min}} \right)^2 \frac{\sqrt{K}}{\left(d + \frac{1}{\lambda_{\min}}\right)}. \quad (12)$$

Similarly, when $\tilde{\Sigma}_t^{-1} = \widehat{\Sigma}_t^{-1}$, $\gamma_t \leq 1/2$ holds for $t > T_0$ such that

$$T_0 \geq 4 \left(\frac{8C_{\mathbb{Z}}^2 C_\ell \log(T)}{\lambda_{\min}} c^\dagger \right)^2 \frac{\sqrt{K}}{\left(d + \frac{\log(T)}{\lambda_{\min}} \right)}. \quad (13)$$

Proof of Lemma A.8. We first check the condition of Lemma A.7. From Lemma A.5, we have

$$\eta_t \left| \widehat{\ell}_t(a, x) \right| \leq \frac{1}{8\sqrt{\omega_t}}.$$

Additionally, we have

$$\begin{aligned} \omega_t &\geq q_t(a | x) \quad \forall a \in [K], \forall x \in \mathcal{X}, \\ \omega_t &\geq (1 - q_t(a | x)) \quad \forall a \in [K], \forall x \in \mathcal{X}, \end{aligned}$$

which yields

$$\frac{1}{\sqrt{\omega_t}} \leq \frac{1}{\min \left\{ q_t(a | x), (1 - q_t(a | x)) \right\}^{1/2}}.$$

Therefore,

$$\eta_t \left| \widehat{\ell}_t(a, x) \right| \leq \frac{1}{8} \frac{1}{\min \left\{ q_t(a | x), (1 - q_t(a | x)) \right\}^{1/2}}.$$

holds.

Then, by using this results, from Lemma A.7, for any $x \in \mathcal{X}$, we obtain

$$\begin{aligned} &\left\langle \widehat{\ell}_t(x), q_t(x) - q_{t+1}(x) \right\rangle - \frac{1}{\eta_t} D(q_{t+1}(x), q_t(x)) \\ &= \frac{1}{\eta_t} \left\{ \left\langle \eta_t \widehat{\ell}_t(x), q_t(x) - q_{t+1}(x) \right\rangle - D(q_{t+1}(x), q_t(x)) \right\} \\ &\leq \eta_t \left\{ \sum_{a \neq a_t^\dagger(x)} \widehat{\ell}_t^2(a | x) q_t^{3/2}(a | x) + \widehat{\ell}_t^2(a_t^\dagger(x) | x) \min \left\{ q_t(a_t^\dagger(x) | x), 1 - q_t(a_t^\dagger(x) | x) \right\}^{3/2} \right\} \\ &\leq \eta_t \left\{ \sum_{a \neq a_t^\dagger(x)} \widehat{\ell}_t^2(a | x) q_t(a | x) \sqrt{\omega_t} + \widehat{\ell}_t^2(a_t^\dagger(x) | x) q_t(a_t^\dagger(x) | x) (1 - q_t(a_t^\dagger(x) | x))^{1/2} \right\} \\ &\leq \sqrt{\omega_t} \eta_t \sum_{a \in [K]} \widehat{\ell}_t^2(a | x) q_t(a | x) \leq 2\sqrt{\omega_t} \eta_t \sum_{a \in [K]} \widehat{\ell}_t^2(a | x) \pi_t(a | x), \end{aligned}$$

Here, we used

$$\begin{aligned} \min \left\{ q_t(a_t^\dagger(x) | x), 1 - q_t(a_t^\dagger(x) | x) \right\}^{3/2} &= \min \left\{ q_t(a_t^\dagger(x) | x), 1 - q_t(a_t^\dagger(x) | x) \right\} \min \left\{ q_t(a_t^\dagger(x) | x), 1 - q_t(a_t^\dagger(x) | x) \right\}^{1/2} \\ &\leq q_t(a_t^\dagger(x) | x) \left\{ 1 - q_t(a_t^\dagger(x) | x) \right\}^{1/2} \quad \forall x \in \mathcal{X}, \end{aligned}$$

from the definition of $a_t^\dagger(x) | x$ and ω_t . We also used $\pi_t \geq (1 - \gamma_t)q_t \geq q_t/2$.

This completes the proof. \square

(II) **Bounding the penalty term.** Next, we bound $\text{penalty}_t(x)$.

Lemma A.9 (Upper bound of the penalty term). *For any $\alpha \in [0, 1]$, the penalty term of α -LC-Tsallis-INF satisfies*

$$\text{penalty}_t(x) = -\left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}}\right) H(q_t(x)) \leq 2\left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}}\right) \sqrt{K\omega_t},$$

where recall that the penalty term $\text{penalty}_t(x)$ is defined in (9).

Proof. The statement directly follows from the following inequality: for any $x \in \mathcal{X}$,

$$\begin{aligned} -H(q_t(x)) &= 2\left(\sum_{a \in [K]} \sqrt{q_t(a|x)} - 1\right) \leq 2\sum_{a \neq a^\dagger(x)} \sqrt{q_t(a|x)} \\ &\leq 2\sqrt{(K-1)\sum_{a \neq a^\dagger(x)} q_t(a|x)} = 2\sqrt{(K-1)(1 - q_t(a^\dagger(x)|x))} \leq 2\sqrt{K\omega_t}. \end{aligned}$$

□

(iii) **Bounding the bias term.** Lastly, we upper bound the bias term, which appears from the estimation error of Σ_t^{-1} .

Corollary A.10. *If $\tilde{\Sigma}_t^\dagger = \Sigma_t^{-1}$, then we have*

$$\text{bias} = 0.$$

If $\tilde{\Sigma}_t^\dagger = \Sigma_t^{-1}$, suppose that Assumptions 2.1–2.5 hold. Then, under the MGR with $\gamma_t := \frac{8C_Z^2 C_\ell \log(T)}{\delta \lambda_{\min}} \eta_t \sqrt{\omega_t}$, $M_t = \frac{1}{8\eta_t \sqrt{\omega_t}} - 1$ and $\delta = \frac{1}{C_Z^2 C_\ell}$, we have

$$\text{bias} \leq 2C_Z C_\Theta.$$

Recall that the bias term bias is defined in (10).

Proof. If $\tilde{\Sigma}_t^\dagger = \Sigma_t^{-1}$, then $\text{bias} = 0$ holds from the definition of the bias term bias .

If $\tilde{\Sigma}_t^\dagger = \Sigma_t^{-1}$, and the conditions hold, then Lemma A.3 directly yields Lemma A.10. □

A.4 Proof of Theorem 6.1

Then, we prove Theorem 6.1 as follows.

Proof. We prove the regret upper bound only when the true Σ_t^{-1} is given. We omit the proof of regret upper bound where Σ_t^{-1} is approximated by the MGR algorithm because we can show it similarly.

From Lemma A.8, for

$$T_0 \geq \begin{cases} 4\left(\frac{8C_Z^2 C_\ell}{\lambda_{\min}} c^\dagger\right)^2 \frac{\sqrt{K}}{\left(d + \frac{1}{\lambda_{\min}}\right)} & \text{if } \tilde{\Sigma}_t^{-1} = \Sigma_t^{-1} \\ 4\left(\frac{8C_Z^2 C_\ell \log(T)}{\lambda_{\min}} c^\dagger\right)^2 \frac{\sqrt{K}}{\left(d + \frac{\log(T)}{\lambda_{\min}}\right)} & \text{if } \tilde{\Sigma}_t^{-1} = \hat{\Sigma}_t^{-1}, \end{cases}$$

we have

$$\text{stability}_t(x) \leq 2\eta_t \sqrt{\omega_t} \sum_{a \in [K]} \hat{\ell}_t^2(a|x) \pi_t(a|x).$$

for all $t \geq T_0$.

From Lemma A.9, we have

$$\text{penalty}_t(x) \leq 2 \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K\omega_t}.$$

Therefore, for $t \geq T_0$, we can bound the pointwise regret as

$$r_t(x) \leq 2\sqrt{\omega_t}\eta_t \sum_{a \in [K]} \widehat{\ell}_t^2(a | x) \pi_t(a | x) + 2 \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K\omega_t} + C_\ell \gamma_t.$$

From the regret decomposition using the stability, penalty, and bias terms in (7), we have

$$\begin{aligned} R_T &\leq \underbrace{\mathbb{E}[\text{stability}_t(X_0)]}_{-} \underbrace{\mathbb{E}[\text{penalty}_t(X_0)]}_{= \text{penalty term}} + \text{bias} \\ &\leq 2T_0C_\ell + \sum_{t=T_0+1}^T \mathbb{E} \left[\sqrt{\omega_t}\eta_t \sum_{a \in [K]} \widehat{\ell}_t^2(a | X_0) \pi_t(a | X_0) + 2 \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K\omega_t} + C_\ell \gamma_t \right] + \text{bias} \\ &\leq 2T_0C_\ell + \sum_{t=1}^T \mathbb{E} \left[\sqrt{\omega_t}\eta_t \sum_{a \in [K]} \widehat{\ell}_t^2(a | X_0) \pi_t(a | X_0) + 2 \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K\omega_t} + \gamma_t \right] + \text{bias} \\ &= 2T_0C_\ell + \sum_{t=1}^T \mathbb{E} \left[\sqrt{\omega_t}\eta_t \widehat{\theta}_t^\top \left(\sum_{a \in [K]} \pi_t(a | X_0) \phi(a, X_0) \phi^\top(a, X_0) \right) + 2 \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K\omega_t} + C_\ell \gamma_t \right] + \text{bias} \\ &= 2T_0C_\ell + \sum_{t=1}^T \mathbb{E} \left[\sqrt{\omega_t}\eta_t \widehat{\theta}_t^\top \Sigma_t + 2 \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K\omega_t} + C_\ell \gamma_t \right] + \text{bias}. \end{aligned}$$

When the true Σ_t^{-1} is given, we have

$$\begin{aligned} R_T &\leq 2T_0C_\ell + O \left(\sum_{t=1}^T \mathbb{E} \left[\sqrt{\omega_t}\eta_t \phi^\top(a, X_t) \Sigma_t^{-1} \Sigma_t \Sigma_t^{-1} \phi(A_t, X_t) + 2 \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K\omega_t} + \gamma_t \right] \right) \\ &\leq 2T_0C_\ell + O \left(\sum_{t=1}^T \mathbb{E} \left[\sqrt{\omega_t}\eta_t d + \eta_t 2 \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K\omega_t} + \gamma_t \right] \right) \\ &= O \left(\mathbb{E} \left[\sum_{t=1}^T \left(\eta_t \left(d + \frac{1}{\lambda_{\min}} \right) + \left(\frac{1}{\eta_t} - \frac{1}{\eta_{t-1}} \right) \sqrt{K} \right) \sqrt{\omega_t} \right] \right), \end{aligned}$$

where we used bias = 0. Because we defined $\eta_t = c^\dagger \sqrt{\frac{\sqrt{K}}{t(d + \frac{1}{\lambda_{\min}})}}$, we have

$$R_T = O \left(\mathbb{E} \left[\sum_{t=1}^T \frac{\sqrt{\sqrt{K}(d + \frac{1}{\lambda_{\min}})\omega_t}}{\sqrt{t}} \right] \right).$$

When Σ_t^{-1} is approximated by the MGR algorithm, we have

$$\begin{aligned} R_T &\leq 2T_0C_\ell + O \left(\sum_{t=1}^T \mathbb{E} \left[\sqrt{\omega_t}\eta_t \phi^\top(a, X_t) \Sigma_t^{-1} \Sigma_t \Sigma_t^{-1} \phi(A_t, X_t) + 2\sqrt{K\omega_t} + \gamma_t + \text{bias} \right] \right) \\ &\leq 2T_0C_\ell + O \left(\sum_{t=1}^T \mathbb{E} \left[\sqrt{\omega_t}\eta_t d + \eta_t 2\sqrt{K\omega_t} + \gamma_t + \text{bias} \right] \right) \end{aligned}$$

$$= O\left(\frac{\sqrt{K} \log(T)}{\lambda_{\min}(d/\log(T) + 1)} + \mathbb{E}\left[\sum_{t=1}^T \left(\eta_t \left(d + \frac{\log(T)}{\lambda_{\min}}\right) + \left(\frac{1}{\eta_t} - \frac{1}{\eta_t}\right) \sqrt{K}\right) \sqrt{\omega_t}\right]\right),$$

where we used $T_{\text{bias}} = C_{\mathcal{Z}} C_{\Theta}$ from Lemma A.3. Because we defined $\eta_t = c^\dagger \sqrt{\frac{\sqrt{K}}{t(d + \frac{\log(T)}{\lambda_{\min}})}}$, we have

$$R_T = O\left(\frac{\sqrt{K} \log(T)}{\lambda_{\min}(d/\log(T) + 1)} + \mathbb{E}\left[\sum_{t=1}^T \frac{\sqrt{\sqrt{K}(d + \frac{\log(T)}{\lambda_{\min}})} \omega_t}{\sqrt{t}}\right]\right).$$

□

A.5 Proof of Theorem 6.3

As we discussed in the proof of Lemma A.8, from the definitions of γ_t , $\tilde{\gamma}_t$, and η_t , there exists $T_0 > 0$ such that for all $t > T_0$, $\gamma_t \leq 1/2$ holds. Since

$$R_T \geq \mathbb{E}\left[\sum_{t=1}^T \Delta(X_t) \sum_{a \neq a_T^*(X_t)} \pi_t(a | X_t)\right]$$

holds, by using a_T^\dagger , the regret is lower bounded as

$$\begin{aligned} R_T &\geq \mathbb{E}\left[\sum_{t=1}^T \Delta(X_t) \sum_{a \neq a_T^*(X_t)} \pi_t(a | X_t)\right] \geq \frac{1}{2} \mathbb{E}\left[\sum_{t=T_0+1}^T \Delta(X_t) \sum_{a \neq a_T^*(X_t)} q_t(a | X_t)\right] \\ &\geq \frac{1}{2} \mathbb{E}\left[\sum_{t=T_0+1}^T \Delta(X_t) (1 - q_t(a_T^*(X_t) | X_t))\right] \geq \frac{1}{2} \mathbb{E}\left[\sum_{t=T_0+1}^T \Delta(X_t) (1 - q_t(a_T^\dagger(X_t) | X_t))\right]. \end{aligned}$$

where we used $\pi_t(a | x) \geq (1 - \gamma_t) q_t(a | x) \geq q_t(a | x)/2$ for any $a \in [K]$ and $x \in \mathcal{X}$.

Proof of Theorem 6.4. We use the statement in Theorem 6.1 and results in its proof. From the Cauchy-Schwarz inequality and the Jensen inequality, we have

$$\begin{aligned} R_T &= 2T_0 C_\ell + O\left(\mathbb{E}\left[\sum_{t=T_0+1}^T \frac{\sqrt{\sqrt{K}(d + \frac{1}{\lambda_{\min}})} \omega_t}{\sqrt{t}}\right]\right) \\ &= 2T_0 C_\ell + O\left(\sqrt{\sqrt{K}\left(d + \frac{1}{\lambda_{\min}}\right)} \sqrt{\sum_{t=T_0+1}^T \frac{1}{t}} \sqrt{\sum_{t=1}^T \mathbb{E}[\omega_t]}\right) \\ &= 2T_0 C_\ell + O\left(\sqrt{\sqrt{K}\left(d + \frac{1}{\lambda_{\min}}\right) \log(T)} \sqrt{\sum_{t=T_0+1}^T \mathbb{E}[\omega_t]}\right). \end{aligned}$$

Let c be a universal constant such that $0 < c < 1$. Let $\tilde{\mathbb{E}}_t^X$ be expectation of X over $\tilde{\mathcal{X}}_t$. Let $\tilde{\mathcal{X}}_t$ be a subset of \mathcal{X} defined as follows:

$$\tilde{\mathcal{X}}_t := \left\{x \in \mathcal{X} : \min_{a \in [K]} \{1 - q_t(a | x)\} \geq c\omega_t\right\},$$

where recall that $\omega_t = \max_{x \in \mathcal{X}} (1 - q_t(a_T^\dagger(x)))$. We use

$$\tilde{\mathbb{E}}_t^X \left[\min_{a \in [K]} \{1 - q_t(a | X_0)\} \mid \mathcal{F}_{t-1} \right] = \sum_{s \in \tilde{\mathcal{X}}_t} \min_{a \in [K]} \{1 - q_t(a | s)\} \mathbb{P}_{X_0 \sim \mathcal{G}}(X_0 = s).$$

Note that $\arg \max_{x \in \mathcal{X}} \min_{a \in [K]} \{1 - q_t(a | x)\} \in \tilde{\mathcal{X}}_t$ by definition, where $\omega_t = \sup_{x \in \mathcal{X}} \min_{a \in [K]} \{1 - q_t(a | x)\} = \max_{x \in \mathcal{X}} \min_{a \in [K]} \{1 - q_t(a | x)\}$ holds.

Then we have

$$\overline{\mathbb{E}_t^X [\min_{a \in [K]} \{1 - q_t(a | X_0)\} | \mathcal{F}_{t-1}]} \leq cL.$$

Therefore, we have

$$\begin{aligned} R_T &= 2T_0C_\ell + O \left(\sqrt{\sqrt{K}(d + \frac{1}{\lambda_{\min}})} \log(T) \sqrt{\sum_{t=T_0+1}^T \mathbb{E} [\omega_t]} \right) \\ &= 2T_0C_\ell + O \left(\sqrt{\sqrt{K}(d + \frac{1}{\lambda_{\min}})} \log(T) \sqrt{\sum_{t=T_0+1}^T \mathbb{E} \left[\frac{\omega_t \tilde{\mathbb{E}}_t^X [\min_{a \in [K]} \{1 - q_t(a | X_0)\} | \mathcal{F}_{t-1}]}{\tilde{\mathbb{E}}_t^X [\min_{a \in [K]} \{1 - q_t(a | X_0)\} | \mathcal{F}_{t-1}]} \right]} \right) \\ &= 2T_0C_\ell + O \left(\sqrt{\sqrt{K}(d + \frac{1}{\lambda_{\min}})} \log(T) \sqrt{\sum_{t=T_0+1}^T \mathbb{E} \left[cL \tilde{\mathbb{E}}_t^X \left[\min_{a \in [K]} \{1 - q_t(a | X_0)\} | \mathcal{F}_{t-1} \right] \right]} \right) \\ &= 2T_0C_\ell + O \left(\sqrt{\sqrt{K}(d + \frac{1}{\lambda_{\min}})} \log(T) \sqrt{L \sum_{t=T_0+1}^T \mathbb{E} \left[\tilde{\mathbb{E}}_t^X \left[\min_{a \in [K]} \{1 - q_t(a | X_0)\} | \mathcal{F}_{t-1} \right] \right]} \right). \end{aligned}$$

Note that for any $x \in \mathcal{X}$, it holds that

$$\min_{a \in [K]} \{1 - q_t(a | x)\} \leq \frac{1}{2}.$$

Therefore, from Lemma A.6, we have

$$\mathbb{E} \left[\Delta(X_0) \min_{a \in [K]} \{1 - q_t(a | X_0)\} \right] \geq \Delta_* \frac{\beta}{1 + \beta} \left(\mathbb{E} \left[\min_{a \in [K]} \{1 - q_t(a | X_0)\} \right] \right)^{\frac{1+\beta}{\beta}},$$

which yields

$$\mathbb{E} \left[\min_{a \in [K]} \{1 - q_t(a | X_0)\} \right] \leq \left(\frac{1 + \beta}{\beta \Delta_*} \mathbb{E} \left[\Delta(X_0) \min_{a \in [K]} \{1 - q_t(a | X_0)\} \right] \right)^{\frac{\beta}{1+\beta}}.$$

From the definition of $\tilde{\mathbb{E}}_t^X$, we also have

$$\mathbb{E} \left[\tilde{\mathbb{E}}_t^X \left[\min_{a \in [K]} \{1 - q_t(a | X_0)\} | \mathcal{F}_{t-1} \right] \right] \leq \mathbb{E} \left[\min_{a \in [K]} \{1 - q_t(a | X_0)\} \right]$$

Therefore, we obtain

$$\begin{aligned} R_T &= 2T_0C_\ell + O \left(\sqrt{L\sqrt{K}(d + \frac{1}{\lambda_{\min}})} \log(T) \sqrt{\sum_{t=T_0+1}^T \mathbb{E} \left[\tilde{\mathbb{E}}_t^X \left[\min_{a \in [K]} \{1 - q_t(a | X_0)\} | \mathcal{F}_{t-1} \right] \right]} \right) \\ &= O \left(\sqrt{L\sqrt{K}(d + \frac{1}{\lambda_{\min}})} \log(T) \sqrt{\sum_{t=1}^T \left(\frac{1 + \beta}{\beta \Delta_*} \mathbb{E} \left[\Delta(X_0) \min_{a \in [K]} \{1 - q_t(a | X_0)\} \right] \right)^{\frac{\beta}{1+\beta}}} \right) \\ &= O \left(\sqrt{L\sqrt{K}(d + \frac{1}{\lambda_{\min}})} \log(T) \sqrt{T^{\frac{1}{1+\beta}} \left(\frac{1 + \beta}{\beta \Delta_*} \sum_{t=1}^T \mathbb{E} \left[\Delta(X_0) \min_{a \in [K]} \{1 - q_t(a | X_0)\} \right] \right)^{\frac{\beta}{1+\beta}}} \right). \end{aligned}$$

From the definition of the regret, as discussed in (1),

$$R_T \geq \sum_{t=1}^T \mathbb{E} [\Delta(X_t)(1 - \pi_t(a^\dagger(X_t) | X_t))] \geq \frac{1}{2} \sum_{t=1}^T \mathbb{E} \left[\Delta(X_0) \min_{a \in [K]} \{1 - q_t(a | X_0)\} \right]$$

holds. Therefore, we obtain

$$R_T = O \left(\sqrt{L\sqrt{K} \left(d + \frac{1}{\lambda_{\min}}\right) \log(T)} \sqrt{T^{\frac{1}{1+\beta}} \left(\frac{1+\beta}{\beta\Delta_*}\right)^{\frac{\beta}{1+\beta}} R^{\frac{\beta}{2(1+\beta)}}} \right).$$

Finally, we obtain

$$R_T = O \left(\left\{ \frac{1+\beta}{\beta\Delta_*} \right\}^{\frac{\beta}{2+\beta}} \left\{ L\sqrt{K} \left(d + \frac{1}{\lambda_{\min}}\right) \log(T) \right\}^{\frac{1+\beta}{2+\beta}} T^{\frac{1}{2+\beta}} \right).$$

□

A.6 Proof of Theorem 6.4

Proof of Theorem 6.4. We prove the regret upper bound only when the true Σ_t^{-1} is given. We omit the proof of regret upper bound where Σ_t^{-1} is approximated by the MGR algorithm because we can show it similarly.

Recall that from the definitions of γ_t , $\tilde{\gamma}_t$, and η_t , for all $t \geq T_0$ such that

$$T_0 \geq 4 \left(\frac{8C_{\mathcal{Z}}^2 C_{\ell} c^\dagger}{\lambda_{\min}} \right)^2 \frac{\sqrt{K}}{\left(d + \frac{1}{\lambda_{\min}}\right)},$$

we have $\gamma_t \leq 1/2$.

From the Jensen inequality, we have

$$\begin{aligned} R_T &= O \left(\mathbb{E} \left[\sum_{t=1}^T \frac{\sqrt{L\sqrt{K} \left(d + \frac{1}{\lambda_{\min}}\right) \omega_t}}{\sqrt{t}} \right] \right) \\ &= O \left(T_0 + \frac{\sqrt{L\sqrt{K} \left(d + \frac{1}{\lambda_{\min}}\right)}}{K-1} \sum_{t=T_0+1}^T \sum_{a \neq a^*} \sqrt{\frac{\mathbb{E} [\min_{b \in [K]} \{1 - q_t(b | X_0)\}]}{t}} \right) \\ &= O \left(T_0 + \frac{\sqrt{L\sqrt{K} \left(d + \frac{1}{\lambda_{\min}}\right)}}{K-1} \sum_{t=1}^T \sum_{a \neq a^*} \sqrt{\frac{u_t}{t}} \right), \end{aligned}$$

where $a^* \in [K]$ is an arbitrary arm just put for using the result of Theorem 4 in Masoudian & Seldin (2021), and

$$u_t = \begin{cases} \mathbb{E} [\min_{b \in [K]} \{1 - q_t(b | X_0)\}] & \text{if } t \geq T_0 \\ 0 & \text{if } t < T_0 \end{cases}.$$

Note that the sum $\sum_{a \neq a^*}$ is introduced just for satisfying the conditions of Theorem 4 in Masoudian & Seldin (2021), although it apparently looks a bit meaningless.

Recall that from Definition 4.2, we have

$$R_T \geq \mathbb{E} \left[\sum_{t=1}^T \sum_{a \neq a_t^*(X_t)} \Delta_t(a | X_t) \pi_t(a | X_t) \right] - C.$$

Therefore, we have

$$\begin{aligned}
R_T &\geq \frac{1}{2} \mathbb{E} \left[\sum_{t=T_0+1}^T \sum_{a \neq a_t^*(X_t)} \Delta_t(a | X_t) q_t(a | X_t) \right] - C \\
&\geq \frac{1}{2} \Delta_* \mathbb{E} \left[\sum_{t=T_0+1}^T \sum_{a \neq a_t^*(X_t)} q_t(a | X_t) \right] - C \\
&\geq \frac{1}{2} \Delta_* \mathbb{E} \left[\sum_{t=T_0+1}^T \min_{b \in [K]} \{1 - q_t(b | X_0)\} \right] - C \\
&= \frac{1}{2} \sum_{t=T_0+1}^T \sum_{a \neq a^*} \frac{\Delta_*}{K-1} \mathbb{E} \left[\min_{b \in [K]} \{1 - q_t(b | X_0)\} \right] - C \\
&= \frac{1}{2} \sum_{t=1}^T \sum_{a \neq a^*} \frac{\Delta_*}{K-1} u_t - C,
\end{aligned}$$

where recall that in Definition 4.2, we assumed that there exists $\Delta_* > 0$ such that for all $a \in [K]$ and any $x \in \mathcal{X}$, $\Delta_t(a | x) > \Delta_*$ holds.

From Theorem 4 in Masoudian & Seldin (2021), we obtain

$$\begin{aligned}
R_T &= O \left(T_0 + \left(\frac{\sqrt{L\sqrt{K}(d + \frac{1}{\lambda_{\min}})}}{K-1} \right)^2 \frac{(K-1)^2}{\Delta_*} \sum_{t=1}^T \left\{ \log(T) + 3 - 2 \log \left(\frac{\sqrt{L\sqrt{K}(d + \frac{1}{\lambda_{\min}})}}{K-1} \right) \right\} \right) + C \\
&= O \left(T_0 + \frac{L\sqrt{K}(d + \frac{1}{\lambda_{\min}})}{\Delta_*} \sum_{t=1}^T \left\{ \log(T) + 3 - 2 \log \left(\frac{\sqrt{L\sqrt{K}(d + \frac{1}{\lambda_{\min}})}}{K-1} \right) \right\} \right) + C.
\end{aligned}$$

Moreover for $\frac{K-1}{\Delta_*} \left(\log \left(\frac{T\Delta_*^2}{K-1} \right) + 1 \right) \leq C \leq \Delta_* T \leq C \leq \Delta_* T$, we have

$$R_T = O \left(T_0 + \sqrt{\frac{CL\sqrt{K}(d + \frac{1}{\lambda_{\min}})}{\Delta_*}} \sum_{t=1}^T \left\{ \sqrt{\log_+ \left(\frac{\Delta_* T}{C} \right) + 2} \right\} \right) + W,$$

where

$$W := \frac{L\sqrt{K}(d + \frac{1}{\lambda_{\min}})}{\Delta_*} \left(\log_+ \left(\frac{\Delta_* T}{C} \right) + \sqrt{2 \log_+ \left(\frac{\Delta_* T}{C} \right) + 2} \right).$$

By substituting $T_0 = 4 \left(\frac{8C_z^2 C_\ell}{\lambda_{\min}} c^\dagger \right)^2 \frac{\sqrt{K}}{(d + \frac{1}{\lambda_{\min}})}$, we obtain the statement. \square

B Proof of Lemma A.6

Proof. For simplicity, let us assume that V has a density function. This assumption implies that the cumulative density function of V is a continuous and monotonically increasing function. Then, $Z := F(V)$ follows the uniform distribution $\text{Unif}[0, 1]$ over the support $[0, 1]$.

Let us define

$$g(z) := \mathbb{E}[U | Z = z].$$

Then, we have $g(z) \in [0, 1]$, and the expected values of U and UV are given as follows:

$$\mathbb{E}[U] = \mathbb{E}_{W \sim \text{Unif}[0,1]} [g(W)] = \int_0^1 g(W) dw = \mu, \tag{14}$$

$$\mathbb{E}[UV] = \mathbb{E}_{W \sim \text{Unif}[0,1]}[g(W)F^{-1}(W)] = \int_0^1 g(w)F^{-1}(w)dw, \quad (15)$$

where $\mathbb{E}_{W \sim \mathcal{J}}$ denotes an expectation operator for a random variable W under a probability distribution \mathcal{J} .

Here, note that F^{-1} is a monotonically decreasing function. Therefore, for $g(w) \in [0, 1]$, under (14), a function g^* minimizes (15) if $g^*(w) := \mathbb{1}[w \leq \mu]$.

In conclusion, we obtain

$$\mathbb{E}[UV] \geq \int_0^1 g^*(w)F^{-1}(w)dz = \int_0^\mu F^{-1}(w)dw. \quad (16)$$

Furthermore, because we assumed $F(h) \leq \frac{1}{2} \left(\frac{h}{\Delta_*}\right)^\beta$ for any $h \in [D, \Delta_*]$, we have $F^{-1}(w) \geq \Delta_*(2w)^{\frac{1}{\beta}}$ for $w \in [F(D), F(\Delta_*)] = \left[\frac{1}{2}\frac{D}{\Delta_*}, \frac{1}{2}\right]$, which implies

$$\int_0^\mu F^{-1}(w)dw \geq \int_0^\mu \Delta_*(2w)^{\frac{1}{\beta}} dw \geq \int_{\frac{1}{2}\frac{D}{\Delta_*}}^\mu \Delta_*(2w)^{\frac{1}{\beta}} dw = \frac{\Delta_*}{2(1+\beta)}(2\mu)^{\frac{1+\beta}{\beta}}, \quad (17)$$

where we used $0 \leq \mu \leq \frac{1}{2}$. From (16) and (17), we obtain the statement. \square

C Proof of Lemma A.7

To show Lemma A.7, we show the following lemmas.

Lemma C.1. For $p, q \in [0, 1]$ and $\ell \geq -\frac{1-\alpha}{2}q^{\alpha-1}$, we have

$$\ell \cdot (q - p) - d(p, q) \leq \frac{2q^{2-\alpha}\ell^2}{1-\alpha}. \quad (18)$$

The proof is shown in Appendix C.

Lemma C.2. Given $x \in \mathcal{X}$, fix arbitrary $a^\dagger(x) \in [K]$ and $q \in \mathcal{P}_K$. If $\ell_t(a | x) \geq -\frac{1-\alpha}{4}q^{\alpha-1}(a | x)$ for all $a \in [K]$, then we have

$$\langle \ell_t(x), q(x) - p(x) \rangle - D(p, q) \leq \frac{4}{1-\alpha} \left(\sum_{a \in [K]} q^{2-\alpha}(a | x) \ell_t^2(a | x) \right) \quad (19)$$

for any $p \in \mathcal{P}_K$.

If $\ell_t(a^\dagger(x) | x) \leq -\frac{1-\alpha}{4}q^{\alpha-1}(a^\dagger(x) | x)$ for all $a \in [K] \setminus \{a^\dagger(x)\}$, then we have

$$\langle \ell_t(x), q(x) - p(x) \rangle - D(p, q) \leq \frac{4}{1-\alpha} \left(\sum_{a \neq a^\dagger(x)} q^{2-\alpha}(a | x) \ell_t^2(a | x) + (1 - q(a^\dagger(x) | x))^{2-\alpha} \ell_t^2(a^\dagger(x) | x) \right) \quad (20)$$

for any $p \in \mathcal{P}_K$.

The proof is shown in Appendix C.2.

Then, we prove Lemma A.7 as follows.

Proof of Lemma A.7. By definition of $a^\dagger(x)$, for all $a \in [K] \setminus \{a^\dagger(x)\}$, we have

$$q(a | x) \leq q(a^\dagger(x)) \quad \text{and} \quad q(a | x) \leq 1 - q(a^\dagger(x)).$$

Then, for all $a \in [K] \setminus \{a^\dagger(x)\}$, from $|\ell_t(a | x)| \leq \frac{1-\alpha}{4} \min \{q(a^\dagger(x) | x), 1 - q(a^\dagger(x), x)\}^{\alpha-1}$, we have

$$|\ell_t(a | x)| \leq \frac{1-\alpha}{4} \min \{q(a^\dagger(x) | x), 1 - q(a^\dagger(x), x)\}^{\alpha-1} \leq \frac{1-\alpha}{4} q^{\alpha-1}(a | x)$$

If $q(a^\dagger(x | x)) \leq 1 - q(a^\dagger(x | x))$, from (19) in Lemma C.2, we have

$$\begin{aligned} & \langle \widehat{\ell}_t(x), q(x) - p(x) \rangle - D(p(x), q(x)) \\ & \leq \frac{4}{1-\alpha} \left(\sum_{a \in [K]} q^{2-\alpha}(a | x) \ell_t^2(a | x) \right) \\ & \leq \frac{4}{1-\alpha} \left(\sum_{a \neq a^\dagger(x)} q^{2-\alpha}(a | x) \ell_t^2(a | x) + \min \{q(a^\dagger(x) | x), 1 - q(a^\dagger(x) | x)\}^{2-\alpha} \ell_t^2(a^\dagger(x), x) \right). \end{aligned}$$

If $q(a^\dagger(x | x)) > 1 - q(a^\dagger(x | x))$, from (20) in Lemma C.2, we have

$$\begin{aligned} & \langle \widehat{\ell}_t(x), q(x) - p(x) \rangle - D(p(x), q(x)) \\ & \leq \frac{4}{1-\alpha} \left(\sum_{a \neq a^\dagger(x)} q^{2-\alpha}(a | x) \ell_t^2(a | x) + (1 - q(a^\dagger(x) | x))^{2-\alpha} \ell_t^2(a^\dagger(x), x) \right) \\ & \leq \frac{4}{1-\alpha} \left(\sum_{a \neq a^\dagger(x)} q^{2-\alpha}(a | x) \ell_t^2(a | x) + \min \{q(a^\dagger(x) | x), 1 - q(a^\dagger(x) | x)\}^{2-\alpha} \ell_t^2(a^\dagger(x), x) \right). \end{aligned}$$

□

C.1 Proof of Lemma C.1

Proof. For any given q and ℓ , the LHS of (18) is concave in p . Hence, this is maximized when

$$\frac{d}{dp} \left\{ \ell \cdot (q - p) - d(p, q) \right\} = -\ell - q^{\alpha-1} + p^{\alpha-1} = 0. \quad (21)$$

We then have

$$p = (q^{\alpha-1} + \ell)^{\frac{1}{\alpha-1}} \leq \left(q^{\alpha-1} - \frac{1-\alpha}{2} q^{\alpha-1} \right)^{\frac{1}{\alpha-1}} = q \left(1 - \frac{1-\alpha}{2} \right)^{\frac{1}{\alpha-1}} \leq 2q, \quad (22)$$

where the first equality follows from (21) and the first inequality follows from the assumption of $\ell \geq -\frac{1-\alpha}{2} q^{\alpha-1}$. Furthermore, from the intermediate value theorem and the fact that $p^{\alpha-2}$ is monotone decreasing in p , we have

$$\begin{aligned} |\ell| & = |p^{\alpha-1} - q^{\alpha-1}| \\ & \geq \min \left\{ |(\alpha-1)p^{\alpha-2}|, |(\alpha-1)q^{\alpha-2}| \right\} |p - q| \\ & = (1-\alpha) \max \{p, q\}^{\alpha-2} |p - q|, \end{aligned}$$

where the first inequality follows from (21) and the second inequality follows from the intermediate value theorem. This implies

$$|p - q| \leq \frac{1}{1-\alpha} \cdot \max \{p, q\}^{2-\alpha} |\ell|. \quad (23)$$

We then have

$$\ell \cdot (p - q) - d(p, q) \leq |\ell| |q - p| \leq \frac{\ell^2}{1-\alpha} \max \{p, q\}^{2-\alpha} \leq \frac{4\ell^2}{1-\alpha} q^{2-\alpha},$$

where the second inequality follows from (23) and the last inequality follows from (22). □

C.2 Proof of Lemma C.2

Proof. We have

$$\begin{aligned}
& \langle \ell_t(x), q(x) - p(x) \rangle - D(p, q) \\
&= \frac{1}{2} \sum_{a \neq a^\dagger(x)} \left\{ 2\ell_t(a | x) \cdot (q(a | x) - p(a | x)) - d(p(a | x), q(a | x)) \right\} \\
&\quad + \frac{1}{2} \left(2\ell_t(a^\dagger(x) | x) \cdot (q(a^\dagger(x) | x) - p(a^\dagger(x) | x)) - d(p(a^\dagger(x) | x), q(a^\dagger(x) | x)) - \sum_{a \neq a^\dagger(x)} d(p(a | x), q(a | x)) \right) \\
&\leq \frac{1}{2} \sum_{a \neq a^\dagger(x)} \left\{ 2\ell_t(a | x) \cdot (q(a | x) - p(a | x)) - d(p(a | x), q(a | x)) \right\} \\
&\quad + \frac{1}{2} \min \left(2\ell_t(a^\dagger(x) | x) \cdot (q(a^\dagger(x) | x) - p(a^\dagger(x) | x)) - d(p(a^\dagger(x) | x), q(a^\dagger(x) | x)), \right. \\
&\qquad \qquad \qquad \left. 2\ell_t(a^\dagger(x) | x) \cdot (q(a^\dagger(x) | x) - p(a^\dagger(x) | x)) - \sum_{a \neq a^\dagger(x)} d(p(a | x), q(a | x)) \right).
\end{aligned}$$

From Lemma C.1, if $\ell_t(a | x) \geq -\frac{1-\alpha}{2}q^{\alpha-1}(a | x)$, we have

$$2\ell_t(a^\dagger(x) | x) \cdot (q(a^\dagger(x) | x) - p(a^\dagger(x) | x)) - \sum_{a \neq a^\dagger(x)} d(p(a | x), q(a | x)) \leq \frac{8q^{2-\alpha}(a | x)\ell_t^2(a | x)}{1-\alpha}.$$

Furthermore, we have

$$(q(a^\dagger(x) | x) - p(a^\dagger(x) | x)) = (1 - p(a^\dagger(x))) - (1 - q(a^\dagger(x) | x)) = \sum_{a \neq a^\dagger(x)} (p(a | x) - q(a | x)).$$

As we have $(1 - q(a^\dagger(x) | x))^{\alpha-1} \leq q^{\alpha-1}(a | x)$ for any $a \in [K] \setminus \{a^\dagger(x)\}$, if $\ell_t(a^\dagger(x) | x) \leq \frac{1-\alpha}{4}(1 - q(a^\dagger(x) | x))^{\alpha-1}$, we then have

$$-\ell_t(a^\dagger(x) | x) \geq -\frac{1-\alpha}{4}q^{\alpha-1}(a | x)$$

for any $a \in [K] \setminus \{a^\dagger(x)\}$. Hence, Lemma C.1 implies

$$\begin{aligned}
& 2\ell_t(a^\dagger(x) | x) \cdot (q(a^\dagger(x) | x) - p(a^\dagger(x) | x)) - \sum_{a \neq a^\dagger(x)} d(p(a | x), q(a | x)) \\
&= \sum_{a \neq a^\dagger(x)} \left\{ -2\ell_t(a^\dagger(x) | x) \cdot (q(a | x) - p(a | x)) - d(p(a | x), q(a | x)) \right\} \\
&\leq \frac{2}{1-\alpha} \sum_{a \neq a^\dagger(x)} (2\ell_t(a^\dagger(x) | x))^2 q^{2-\alpha}(a^\dagger(x) | x) \\
&\leq \frac{8}{1-\alpha} \sum_{a \neq a^\dagger(x)} \ell_t^2(a^\dagger(x) | x) \left(\sum_{a \neq a^\dagger(x)} q(a | x) \right)^{2-\alpha} \\
&= \frac{8}{1-\alpha} (1 - q(a^\dagger(x) | x))^{2-\alpha} \ell_t^2(a^\dagger(x) | x).
\end{aligned}$$

□

D The BoBW-RealFTRL with the Feature Map

In Neu & Olkhovskaya (2020), Kato & Ito (2023), and Kuroki et al. (2023), the focus is on arm-independent contexts, and linear models are considered, defined as $\ell_t(a, x) = \langle x, \theta_t(a) \rangle + \varepsilon_t(a)$, where $x \in \mathbb{R}^d$ represents a d -dimensional (arm-independent) context, and $\theta_t(a)$ is a d -dimensional arm-dependent regression coefficient. This paper modifies the BoBW-RealFTRL proposed by Kato & Ito (2023), which is almost the same as the FTRL-LC independently proposed by Kuroki et al. (2023), and its regret upper bound for the arm-dependent feature setting. These algorithms employ the Shannon-entropy, instead of the Tsallis-entropy, in the FTRL.

D.1 The BoBW-RealFTRL

Then, we define our policy, called the BoBW-RealFTRL, as

$$\pi_t(X_t) := (1 - \gamma_t)q_t(X_t) + \gamma_t e^*(X_t), \quad (24)$$

where

$$\begin{aligned} q_t(x) &\in \arg \min_{q \in \mathcal{P}_K} \left\{ \sum_{s=1}^{t-1} \langle \widehat{\ell}_s(x), q \rangle + \frac{1}{\eta_t} \psi(q) \right\} \quad \text{for } t \geq 2, \\ q_1(x) &:= (1/K \ 1/K \ \cdots \ 1/K)^\top, \\ \psi(q(x)) &:= - \sum_{a \in [K]} q(a | x) \log \left(\frac{1}{q(a | x)} \right), \\ \frac{1}{\eta_{t+1}} &:= \frac{1}{\eta_t} + \frac{1}{\eta_1} \frac{1}{\sqrt{1 + (\log(K))^{-1} \sum_{s=1}^t H(q_s(X_s))}}. \end{aligned}$$

Let $\psi_t(q(x)) := \frac{1}{\eta_t} \psi(q(x))$.

Then, as well as the α -LC-Tsallis-INF, we consider two cases where the true Σ_t^{-1} is given, and it is approximated by using finite samples generated from \mathcal{G} . For each case, we specify the remaining parameters in the FTRL-based algorithm.

The BoBW-RealFTRL with Σ_t^{-1} . First, we consider a case where the true Σ_t^{-1} is given. In this case, we specify the remaining parameters as follows:

$$\frac{1}{\eta_1} := \zeta \sqrt{\log(T) \left(\frac{1}{\delta \lambda_{\min} \log(K)} + d \right)}, \quad \text{quad and} \quad \gamma_t := \frac{\eta_t}{2\lambda_{\min}}.$$

The BoBW-RealFTRL with an approximated Σ_t^{-1} . Next, we consider a case where Σ_t^{-1} is approximated by using the MGR algorithm defined in Algorithm 2. In this case, we set the parameters as follows:

$$\begin{aligned} \frac{1}{\eta_1} &:= \zeta \sqrt{\log(T) \left(\frac{\log(T)}{\delta \lambda_{\min} \log(K)} + d \right)}, \\ \gamma_t &:= \frac{\eta_t}{2\lambda_{\min}} \log(T), \\ M_t &:= \frac{2}{\eta_t} - 1, \quad \text{and} \quad \delta := \frac{1}{C_Z^2 C_\ell}. \end{aligned}$$

Algorithm 3 BoBW-RealFTRL.

Parameter: Learning rate $\eta_1, \eta_2, \dots, \eta_T > 0$.

Initialization: Set $\theta_0 = 0$.

for $t = 1, \dots, T$ **do**

 Observe X_t .

 Draw $A_t \in [K]$ following the policy $\pi_t(X_t) := (1 - \gamma_t)q_t(X_t) + \gamma_t e^*(X_t)$ defined in (24).

 Observe the loss $\ell_t(A_t, X_t)$.

 Compute $\hat{\theta}_t$.

end for

D.2 Regret Analysis

This section provides upper bounds for the regret of our proposed BoBW-RealFTRL algorithm.

To derive upper bounds, we define the following quantities:

$$Q(a_T^* | x) = \sum_{t=1}^T \left\{ 1 - q_t(a_T^*(x) | x) \right\},$$
$$\bar{Q}(a_T^*) = \mathbb{E}[Q(a_T^* | X_0)].$$

As well as $\xi^{\text{Tsallis}}(\tilde{\Sigma}_t^\dagger)$, for the BoBW-RealFTRL with a regression coefficient estimator $\hat{\theta}_t(\tilde{\Sigma}_t^\dagger)$, let us define

$$\xi^{\text{Shannon}}(\tilde{\Sigma}_t^\dagger) := \begin{cases} \log(K) \left(\frac{1}{\lambda_{\min}} + d \right) & \text{if } \tilde{\Sigma}_t^\dagger = \Sigma_t^{-1} \\ \log(K) \left(\frac{\log(T)}{\lambda_{\min}} + d \right) & \text{if } \tilde{\Sigma}_t^\dagger = \hat{\Sigma}_t^{-1}. \end{cases}$$

Then, we show the following upper bound, which holds for general cases such as adversarial and stochastic regimes. We show the proof in Sections E.1 and E.2.

Theorem D.1 (General regret bounds). *Consider the BoBW-RealFTRL with the estimator $\hat{\theta}_t(\tilde{\Sigma}_t^\dagger)$. Assumptions 2.1–2.5 hold. Then, the decision-maker incurs the following regret:*

$$R_T = O \left(\left(\eta_1 \log(T) \frac{\xi^{\text{Shannon}}(\tilde{\Sigma}_t^\dagger)}{\log(K)} + \frac{1}{\eta_1} \sqrt{\log(K)} \right) \sqrt{\log(KT)} \max \left\{ \bar{Q}^{1/2}(a_T^*), 1 \right\} \right).$$

For each situation, we derive a specific upper bound. The proof is shown in Appendix E.

First, from $\bar{Q}(a_T^*) \leq T$, the following regret bound holds without any assumptions on the loss; that is, it holds in an adversarial regime.

Theorem D.2 (Regret upper bound in an adversarial regime). *Consider the BoBW-RealFTRL with the estimator $\hat{\theta}_t(\tilde{\Sigma}_t^\dagger)$. Assume that the loss is generated under an adversarial regime. Suppose that Assumption 2.1 and 2.3 hold. Then, the regret satisfies*

$$R_T = O \left(\log(KT) \sqrt{T \log(T) \xi^{\text{Shannon}}(\tilde{\Sigma}_t^\dagger)} \right).$$

Next, we derive a regret upper bound in a stochastic regime with a margin condition.

Theorem D.3 (Regret upper bound in a stochastic regime with a margin condition). *Consider the BoBW-RealFTRL with the estimator $\hat{\theta}_t(\tilde{\Sigma}_t^\dagger)$. Assume that the loss is generated under a stochastic regime with a margin condition (Definition 4.1). Suppose that Assumption 2.1, 2.3–2.5 hold. Then, the regret satisfies*

$$R_T = O \left(\left\{ \frac{1 + \beta}{\beta \Delta_*} \right\}^{\frac{\beta}{2 + \beta}} \left\{ \log(KT) \sqrt{\log(T) \xi^{\text{Shannon}}(\tilde{\Sigma}_t^\dagger)} \right\}^{\frac{1 + \beta}{2 + \beta}} T^{\frac{1}{2 + \beta}} \right).$$

We omit the proof because it is almost the same as that for Theorem 6.3 for the 1/2-LC-Tsallis-INF

Furthermore, we derive a regret bound under the linear contextual adversarial regime with a self-bounding constraint. The proof is provided in Appendix E.3

Theorem D.4 (Regret bounds under the linear contextual adversarial regime with a self-bounding constraint). *Consider the BoBW-RealFTRL with the estimator $\hat{\theta}_t(\tilde{\Sigma}_t^\dagger)$. Assume that the loss is generated under a linear contextual adversarial regime with a self-bounding constraint (Definition 4.2). Suppose that Assumption 2.1, 2.3–2.5 hold. Then, the regret satisfies*

$$R_T = O\left(\frac{D}{\Delta_*} + \sqrt{\frac{CD}{\Delta_*}}\right),$$

where $D = \log(T)\xi^{\text{Shannon}}(\tilde{\Sigma}_t^\dagger) \log(KT)$.

Note that the BoBW-RealFTRL does not require Assumption 2.2 in stochastic regimes.

E Proof of Theorems D.1 and D.4

E.1 Preliminaries for the Proof of Theorem D.1

Let X_0 be a sample from the context distribution \mathcal{G} independent of \mathcal{F}_T . Let $D_t(p, q)$ denote the Bregman divergence of $p, q \in \Pi$ with respect to ψ_t ; that is,

$$D_t(p, q) = \psi_t(p) - \psi_t(q) - \langle \nabla \psi_t(q), p - q \rangle.$$

Let us define $\pi^* \in \Pi$ as $\pi^*(a^*(x) | x) = 1$ and $\pi^*(a | x) = 0$ for all $a \in [K] \setminus \{a^*(x)\}$.

From Lemma 4.4 in Kato & Ito (2023) (our Proposition A.1), we have the following stability and penalty terms decomposition:

$$\begin{aligned} R_T \leq \mathbb{E} \left[\sum_{t=1}^T \left\{ \gamma_t + \underbrace{\langle \hat{\ell}_t(X_0), q_t(X_0) - q_{t+1}(X_0) \rangle - D_t(q_{t+1}(X_0), q_t(X_0))}_{= \text{stability term}} \right. \right. \\ \left. \left. + \underbrace{\psi_t(q_{t+1}(X_0)) - \psi_{t+1}(q_{t+1}(X_0))}_{= \text{penalty term}} + \psi_{T+1}(\pi^*(X_0)) - \psi_1(q_1(X_0)) \right\} \right] \\ + 2 \underbrace{\sum_{t=1}^T \max_{a \in [K]} \left| \mathbb{E} \left[\langle X_t, \theta_t(a) - \hat{\theta}_t(a) \rangle \right] \right|}_{= \text{bias term}}. \end{aligned}$$

We can bound the bias term by using Corollary A.10 derived for Theorem E.3. Therefore, we consider bounding stability and penalty terms.

Bounding the stability term. For the stability term $\langle \hat{\ell}_t(X_0), q_t(X_0) - q_{t+1}(X_0) \rangle - D_t(q_{t+1}(X_0), q_t(X_0))$, we use the following proposition from Ito et al. (2022).

Proposition E.1 (From Lemma 8 in Ito et al. (2022)). *Consider the BoBW-RealFTRL with the estimator $\hat{\theta}_t(\tilde{\Sigma}_t^\dagger)$. For any $\ell : \mathcal{X} \rightarrow \mathbb{R}^K$ and $p, q \in \Pi$, we have*

$$\langle \ell_t(x), p(x) - q(x) \rangle - D_t(q(x), p(x)) \leq \frac{1}{\eta_t} \sum_{a \in [K]} p(a | x) \xi(\eta_t \ell_t(a, x)).$$

for any $x \in \mathcal{X}$, where $\xi(x) := \exp(-x) + x - 1$.

If $\eta_t \widehat{\ell}(a, x) \geq -1$ holds, then Proposition E.1 implies

$$\left\langle \widehat{\ell}_t(x), q_t(x) - q_{t+1}(x) \right\rangle - D_t(q_{t+1}(x), q_t(x)) \leq \eta_t \sum_{a \in [K]} \pi_t(a | x) \widehat{\ell}_t^2(a, x).$$

For the RHS, we apply the following proposition from Neu & Olkhovskaya (2020).

Proposition E.2 (From Lemma 6 in Neu & Olkhovskaya (2020)). *For each $t \in [T]$, our strategy satisfies*

$$\mathbb{E} \left[\sum_{a \in [K]} \pi_t(a | X_0) \widehat{\ell}_t^2(a, X_0) | \mathcal{F}_{t-1} \right] \leq 3d.$$

E.2 Proof of Theorem D.1

Then, we obtain the following lemma, as well as Lemma 4.9 in Kato & Ito (2023).

Lemma E.3. *The regret for the BoBW-RealFTRL with $\widehat{\Sigma}_{t,a}^\dagger$ satisfies*

$$R_T \leq \mathbb{E} \left[\sum_{t=1}^T \left\{ \gamma_t + 3\eta_t d + \left(\frac{1}{\eta_{t+1}} - \frac{1}{\eta_t} \right) \psi(q_{t+1}(X_0)) \right\} \right] + \frac{1}{\eta_1} \log(K) + 2C_Z C_\Theta.$$

Proof of Lemma E.3. From Lemma A.1, we have

$$\begin{aligned} R_T \leq \mathbb{E} \left[\sum_{t=1}^T \left(\gamma_t + \left\langle \widehat{\ell}_t(X_0, d), \pi_t(X_0) - q_{t+1}(X_0) \right\rangle - D_t(q_{t+1}(X_0), \pi_t(X_0)) \right. \right. \\ \left. \left. + \psi_t(q_{t+1}(X_0)) - \psi_{t+1}(q_{t+1}(X_0)) \right) + \psi_{T+1}(\pi^*(X_0)) - \psi_1(q_1(x)) \right] \\ + 2 \sum_{t=1}^T \max_{a \in [K]} \left| \mathbb{E} \left[\langle X_t, \theta_{t,a} - \widehat{\theta}_{t,a} \rangle \right] \right|. \end{aligned}$$

First, we show

$$\mathbb{E} \left[\left\langle \widehat{\ell}_t(X_0), \pi_t(X_0) - q_{t+1}(X_0) \right\rangle - D_t(q_{t+1}(X_0), \pi_t(X_0)) \right] \leq 3\eta_t d. \quad (25)$$

To show this, we confirm $\eta_t \widehat{\ell}_t(a, x) \geq -1$, which is necessary to derive an upper bound from Proposition E.1. We have

$$\begin{aligned} \eta_t \cdot \left\langle X_0, \widehat{\theta}_t(a) \right\rangle &= \eta_t \cdot X_0^\top \widehat{\Sigma}_{t,a}^\dagger X_t \left\langle X_t, \theta_{t,a} \right\rangle \mathbb{1}[A_t = a] \geq -\eta_t C_\ell \cdot \left| X_0^\top \widehat{\Sigma}_{t,a}^\dagger X_t \right| \\ &\geq -\eta_t C_Z^2 C_\ell \left\| \widehat{\Sigma}_{t,a}^\dagger \right\|_{\text{op}} \geq -\eta_t C_Z^2 C_\ell \delta \left(1 + \sum_{k=1}^{M_t} \|V_{k,a}\|_{\text{op}} \right) = -\frac{\eta_t}{2} (M_t + 1), \end{aligned}$$

where we used that $\delta = \frac{1}{C_Z^2 C_\ell}$. Here, recall that we defined M_t as $2\frac{1}{\eta_t} - 1$. Therefore, $\eta_t \widehat{\ell}_t(a, x) = -1$ holds. Then, we have

$$\begin{aligned} &\left\langle \widehat{\ell}_t(x), \pi_t(x) - q_{t+1}(x) \right\rangle - D_t(q_{t+1}(x), \pi_t(x)) \\ &\leq \frac{1}{\eta_t} \sum_{a \in [K]} \pi_t(a | x) \xi \left(\eta_t \widehat{\ell}_t(a, x) \right) \leq \eta_t \sum_{a \in [K]} \pi_t(a | x) \widehat{\ell}_t^2(a, x). \end{aligned}$$

Then, from Proposition E.2, we have (25).

From $\psi_t(q(x)) = -\frac{1}{\eta_t}\psi(q(x))$, we have

$$\begin{aligned} & \sum_{t=1}^T (\psi_t(q_{t+1}(x)) - \psi_{t+1}(q_{t+1}(x))) + \psi_{T+1}(\pi^*(x)) - \psi_1(q_1(x)) \\ & \leq \sum_{t=1}^T \left(\frac{1}{\eta_{t+1}} - \frac{1}{\eta_t} \right) \psi(q_{t+1}(x)) + \frac{1}{\eta_1} \log(K). \end{aligned}$$

From Lemma A.3, we have

$$\sum_{t=1}^T \max_{a \in [K]} \left| \mathbb{E} \left[\langle X_t, \theta_{t,a} - \hat{\theta}_{t,a} \rangle \right] \right| \leq \sum_{t=1}^T C_Z C_\Theta / T = C_Z C_\Theta.$$

□

From this result, we obtain the following lemma. We omit the proof.

Lemma E.4. *Assume the conditions in Theorem E.3. Consider the BoBW-RealFTRL with the estimator $\hat{\theta}_t \left(\tilde{\Sigma}_t^\dagger \right)$. Then, we have*

$$R_T \leq \bar{c} \sqrt{\mathbb{E} \left[\sum_{t=1}^T \psi(q_t(X_0)) \right]} + 2C_Z C_\Theta,$$

where $\bar{c} = O \left(\eta_1 \log(T) \left(\frac{\log(T)}{\lambda_{\min} \log(K)} + d \right) + \frac{1}{\eta_1} \sqrt{\log(K)} \right)$.

Next, we consider bounding $\sum_{t=1}^T \psi(q_t(x))$ by $Q(a_T^* | x)$ as shown in the following proposition.

Proposition E.5 (From Lemma 4 in Ito et al. (2022)). *For any $a^* : \mathcal{X} \rightarrow [K]$, the following holds:*

$$\sum_{t=1}^T \psi(q_t(x)) \leq Q(a_T^* | x) \log \left(\frac{eKT}{Q(a_T^* | x)} \right),$$

where e is Napier's constant.

By using the above lemmas and propositions, we prove Theorem 6.1.

Proof of Theorem 6.1. From Lemma E.5, if $Q(a_T^* | x) \leq e$, we have $\sum_{t=1}^T \psi(q_t(x)) \leq e \log(KT)$ and otherwise, we have $\sum_{t=1}^T \psi(q_t(x)) \leq Q(a_T^* | x) \log(KT)$. Hence, we have $\sum_{t=1}^T \psi(q_t(x)) \leq \log(KT) \max\{e, Q(a_T^* | x)\}$. From Lemma E.4, we have

$$\begin{aligned} R_T & \leq \bar{c} \sqrt{\sum_{t=1}^T \mathbb{E} [\psi(q_t(X_0))]} + 2C_Z C_\Theta \\ & = O \left(\left(\eta_1 \log(T) \left(\frac{\log(T)}{\lambda_{\min} \log(K)} + d \right) + \frac{1}{\eta_1} \sqrt{\log(K)} \right) \sqrt{\log(KT) \max\{\bar{Q}^{1/2}, 1\}} \right). \end{aligned}$$

□

E.3 Proof of Theorem D.4

Proof of Theorem D.4. From the definition of the contextual adversarial regime with a self-bounding constraint, we have

$$R_T \geq \Delta_* \cdot \mathbb{E} \left[\sum_{t=1}^T \left(1 - \pi_t(a^*(X_0) | X_0) \right) \right] - C = \Delta_* \cdot \bar{Q}(a_T^*) - C.$$

Therefore, from Lemma E.4, for any $\lambda > 0$, we have

$$\begin{aligned}
R_T &= (1 + \lambda)R_T - \lambda R_T \\
&= (1 + \lambda)O\left(c\sqrt{\log(KT)}\sqrt{\sum_{t=1}^T \mathbb{E}[\psi(q_t(X_0))]} \right) - \lambda R_T \\
&\leq (1 + \lambda)O\left(c\sqrt{\log(KT)}\sqrt{\sum_{t=1}^T \mathbb{E}[\psi(q_t(X_0))]} \right) - \lambda\Delta_* \cdot \bar{Q}(a_T^*) + \lambda C,
\end{aligned}$$

where

$$c = \left(\eta_1 \log(T) \left(\frac{\log(T)}{\lambda_{\min} \log(K)} + d\right) + \frac{1}{\eta_1} \sqrt{\log(K)}\right).$$

Here, as well as the proof of Theorem 6.1, from Lemma E.5, if $Q(a_T^* | x) \leq e$, we have $\sum_{t=1}^T \psi(q_t(x)) \leq e \log(KT)$ and otherwise, we have $\sum_{t=1}^T \psi(q_t(x)) \leq Q(a_T^* | x) \log(KT)$. Hence, we have $\sum_{t=1}^T \psi(q_t(x)) \leq \log(KT) \max\{e, Q(a_T^* | x)\}$. Here, to upper bound R_T , it is enough to only consider a case with $Q(a_T^* | x) \geq e$, and we obtain

$$R_T \leq (1 + \lambda)O\left(c\sqrt{\log(KT)}\sqrt{\bar{Q}(a_T^*) \log(KT)}\right) - \lambda\Delta_* \cdot \bar{Q}(a_T^*) + \lambda C \leq \frac{O\left(\{(1 + \lambda)c\}^2 \sqrt{\log(KT)}\right)}{2\lambda\Delta_*} + \lambda\Delta_*.$$

where the second inequality follows from $a\sqrt{b} - \frac{c}{2}b \leq \frac{a^2}{c^2}$ holds for any $a, b, c > 0$. By choosing

$$\lambda = \sqrt{\frac{c^2 \log(KT)}{\Delta_*} / \left(\frac{c^2 \log(KT)}{\Delta_*} + 2C\right)}.$$

Then, we obtain $R_T = O\left(c^2 \log(KT)/\Delta_* + \sqrt{C c^2 \log(KT)/\Delta_*}\right)$. □