On HTLC-Based Protocols for Multi-Party Cross-Chain Swaps*

Emily Clark¹, Chloe Georgiou¹, Katelyn Poon¹, and Marek Chrobak¹

¹University of California at Riverside

March 18, 2024

Abstract

In his 2018 paper, Herlihy introduced an atomic protocol for multi-party asset swaps across different blockchains. His model represents an asset swap by a directed graph whose nodes are the participating parties and edges represent asset transfers, and rational behavior of the participants is captured by a preference relation between a protocol's outcomes. Asset transfers between parties are achieved using smart contracts. These smart contracts are quite intricate and involve solving computationally intensive graph problems, limiting practical significance of his protocol. His paper also describes a different protocol that uses only standard hash time-lock contracts (HTLC's), but this simpler protocol applies only to some special types of digraphs. He left open the question whether there is a simple and efficient protocol for cross-chain asset swaps in arbitrary digraphs. Motivated by this open problem, we conducted a comprehensive study of *HTLC-based protocols*, in which all asset transfers are implemented with HTLCs. Our main contribution is a full characterization of swap digraphs that have such protocols.

1 Introduction

In his 2018 paper [8], Herlihy introduced a model for multi-party asset swaps across different blockchains. In this model an asset swap is represented by a strongly connected directed graph (digraph), with each vertex corresponding to one party and each arc representing a pre-arranged asset transfer between two parties. Given such a digraph, the goal is to design a protocol to implement the transfer of all assets. There is no guarantee that all parties will follow the protocol — some parties may attempt to cheat, even colluding between themselves, or behave irrationally. The protocol must guarantee, irrespective of the behavior of other parties, that each honest party will end up with an outcome that it considers acceptable. The protocol should also discourage cheating, so that any coalition of parties cannot improve its outcome by deviating from the protocol. These two conditions are called *safety* and *strong Nash equilibrium*, respectively. A protocol that satisfies these conditions is called *atomic* (see the formal definitions in Section 3).

In this model, Herlihy [8] developed an atomic protocol for multi-party asset swaps in arbitrary strongly connected digraphs. This result constitutes a major advance in our understanding of fundamental principles of asset swaps, as it shows that it is possible, in principle, to securely implement complex transactions involving multiple parties even if their assets are hosted on multiple blockchains. Yet the practical significance of his protocol is limited due to its intricacy and high computational complexity. Asset transfers in this protocol are realized via smart contracts that need to store and process the whole swap digraph, and designing these contracts involves solving NP-hard graph problems, like finding long paths or a small feedback vertex set. To achieve the safety property, it uses an elaborate cryptographic scheme involving nested digital signatures.

^{*}Research supported by NSF grant CCF-2153723.

Another concern is privacy: since the execution of the protocol requires the parties to know the topology of the whole swap digraph, they also receive information about asset transfers between other parties.

Herlihy's paper [8] also mentions a simplified and more efficient version of his protocol. In terms of cryptographic tools, this simpler protocol uses only standard smart contracts called *hash time-lock contracts* (HTLC's), that require only one secret/hashlock pair and a time-out mechanism. This protocol, however, has only limited applicability: it works correctly only for special types of digraphs, that we call *bottleneck digraphs* in our paper¹. These are strongly connected digraphs in which all cycles overlap on at least one vertex.

This raises a natural question, already posed in [8]: *Is there a simple and efficient protocol for multi-party asset swaps that is atomic and works on all strongly connected digraphs?*

Our contributions. Our work was motivated by the above question. Specifically, the question we address is this: *Is it possible to solve the cross-chain swap problem with an atomic protocol that is computationally efficient and uses only HTLCs for asset transfers?* We show that, while such HTLC-based protocols are not possible for arbitrary digraphs, the class of digraphs that have such protocols is much broader than just bot-tleneck digraphs. In fact, we give a complete characterization of digraphs that have HTLC-based protocols. We call them *reuniclus graphs*². A reuniclus graph consists of a number of (weakly) biconnected components, with each component being an induced bottleneck subgraph. These components form a hierarchical tree-like structure, where the bottleneck of each non-root component is an articulation vertex belonging to its parent component. (See the formal definition in Section 4.2).

To establish our characterization, we need to formalize the concepts of HTLCs and HTLC-based protocols. In our model, an HTLC is a smart contract used to transfer an asset from its seller to its buyer that (roughly) works like this: After it's created by the seller, the contract stores (escrows) this asset secured with a hashlock value and with a timeout (expiration) value, both provided by the seller. To claim this asset, the buyer must provide a secret value that matches the hashlock. If the asset is not successfully claimed by the buyer before its timeout, the contract automatically returns the asset to the seller. In a HTLC-based protocol, all asset transfers are implemented with HTLCs, and each party is allowed to generate one secret/hashlock pair, with the hashlock value obtained from the secret value using a one-way permutation.

In this terminology, our main contribution can be stated as follows:

Theorem 1. A swap digraph G has an atomic HTLC-based protocol if and only if G is a reuniclus digraph.

The proof of Theorem 1 conists of two parts. The sufficiency condition is proved in Section 4, where we provide an HTLC-based atomic protocol for asset swaps in reuniclus digraphs. Our most technically challenging contribution is the proof of the necessity condition, presented in Section 5. This proof shows that non-reuniclus digraphs do not have atomic HTLC-protocols for asset swaps.

Along the way we also obtain a full characterization of digraphs that admit HTLC-protocols when only one party is allowed to create a secret/hashlock pair. Herlihy [8] showed that bottleneck graphs have such protocols. We complement this result by proving that the bottleneck property is also necessary.

Our asset-swap model is in fact a slight generalization of the one in [8], as it uses a relaxed definition of the preference relation, which allows each party to customize some of the preferences between its outcomes. As we explain in Section 3, all crucial properties of the model in [8] remain valid. Among these, the most critical is given in Lemma 1, which says that in this model the strong Nash equilibrium property is in essence a consequence of the safety property of a protocol; thus, in a way, it comes "for free".

Related work. The problem of securely exchanging digital products between two untrustful parties has been studied since 1990s under the name of *fair exchange*. As simultaneous exchange is not feasible in a typical electronic setting, protocols for fair exchage rely on a trusted party and use cryptographic tools to

¹Herlihy calls such graphs *single-leader digraphs*.

²Graphical representations of these digraphs resemble visually a type of Pokemon called Reuniclus.

reduce the need for this trusted party to interfere – see for example [12, 6, 3, 1, 2]. In the asset-swap model from [8], adopted in our paper, one can think of smart contracts as playing the role of trusted parties.

Starting in early 2000's, with different users holding assets on a quickly growing number of different blockchains, cross-chain interoperability tools became necessary to allow these users to trade their assets. An atomic swap concept was one of the proposed tools to address this issue. The concept itself and some early implementations of asset-swap protocols (see, for example [14]) predate the work of Herlihy [8], although his paper was first to provide systematic treatment of such protocols and extend it to multiple parties.

In recent years there has been intensive research activity aimed at improving various aspects of assetswap protocols. The preference relation of the participants in the model from [8] is very rudimentary, and some refinements of this preference model were studied in [4, 10]. Some proposals [11, 15] address the issue of "griefing", when one party needs to wait for the counter-party to act, while its assets are locked and unaccessible. Other directions of study include investigations of protocol's time and space complexity [10], privacy issues [5], and generalizations of swaps to more complex transactions [9, 13, 7].

2 Graph Terminology

Let G = (V, A) be a digraph with vertex set V and arc set A. Throughout the paper we assume that digraphs do not have self-loops or parallel arcs. If $(u, v) \in A$ is an arc, we refer to v as an *out-neighbor* of u and to u as an *in-neighbor* of v. By N_v^{in} we denote the set of in-neighbors of v, by A_v^{in} its set of in-coming arcs, N_v^{out} are the out-neighbors of v and A_v^{out} are its outgoing arcs.

To simplify notation, for a vertex v we will sometimes write $u \in G$ instead of $v \in V$. Similarly, for an arc (u, v), notation $(u, v) \in G$ means that $(u, v) \in A$.

We use standard terminology for directed graphs. A path in G is a sequence of vertices, each (except last) having an arc to the next one, without repeating an arc. A cycle is a path in which the last vertex is equal to the first one. A *simple path* is a path that does not repeat a vertex. A *simple cycle* is a cycle where all vertices are different except the first and last being equal.

A digraph H = (V', A') is a subgraph of G if $V' \subseteq V$ and $A' \subseteq A$. H is called an *induced subgraph* of G if A' contains all arcs from A connecting vertices in V'. The concept of induced subgraphs will be important.

Recall that a digraph G is called *strongly connected* if for every pair of vertices u and v there is a path from u to v. We are mostly interested in strongly connected digraphs.

A set $U \subseteq V$ of vertices is called a *feedback vertex set* in a digraph G if every cycle in G includes at least one vertex from U.

For a digraph G we will sometimes consider its undirected structure. A vertex v is caled an *articulation* vertex of G if removing v from (the undirected version of) G creates a graph that has more connected components than G. We say that G is *biconnected* if G is (weakly) connected and has no articulation vertices.

3 Multi-Party Asset Swaps

In broad terms, the *multi-party asset swap problem* we want to solve is this: There is a collection V of parties. Each party has a collection of assets that it wishes to exchange for some other set of assets. For example, Alice may own a pair of skis and a pair of ski boots that she would like to exchange for an iPad and a pair of earbuds. (In practice, these are typically digital assets, like crypto-currency, but we can also consider a scenario where ownership titles to physical assets are swapped.) Suppose that there is a way to match these exchanges perfectly, namely to reassign assets from its current owner to its new owner in such a way that each party will be assigned exactly their specified collection of desired assets. This reassignment is called a

multi-party asset swap. We now would like to design a protocol to arrange the transfers of all assets in this swap. We do not assume that the parties are honest. Some parties may not follow the rules of the protocol, attempting to achieve an outcome better than the one they originally specified. (For example, they may end up with an extra new asset, or retain some of their own assets.) Other parties may just behave irrationally. To address this, the asset-swap protocol must satisfy, at the minimum, the following two properties: (i) if all parties follow the protocol then all prearranged asset transfers will take place, and (ii) an outcome of any honest party (that follows the protocol) is guaranteed to be acceptable (not worse than its initial holdings), even if some other parties deviate from the protocol or collaboratively attempt to cheat.

Clearing service. We assume the existence of a *market clearing service*. Each party submits its proposed exchange (the two collections of its current and desired assets) to this clearing service. If a multi-party swap is possible, the clearing service constructs a digraph G = (V, A) representing this swap. Each arc (u, v) of G represents the intended transfer of one asset from its current owner u to its new owner v. (In the context of this transfer, we refer to u as "the seller" and to v as "the buyer".) For simplicity, we assume that any party can transfer only one asset to any other party. This way G does not have any parallel arcs. In our notations we will also identify assets with arcs, so (u, v) denotes both an arc of G and the asset of u to be transferred to v. The market clearing service ensures that G is strongly connected and satisfies other assumptions of the swap protocol, if there are any. It then informs each party of the steps of the swap protocol that this party should execute. Importantly, we *do not* assume that the parties trust the market clearing service.

Secrets and hashlocks. Our protocols use a cryptographic tool of one-way functions. We allow each party v to create a *secret value* s_v , and convert it into a *hashlock value* $h_v = H(s_v)$, where H() is a one-way permutation. The value of s_v is secret, meaning that no other party has the capability to compute s_v from h_v . The hashlock values can be made public.

Hash time-lock contracts (HTLCs). Asset transfers are realized vwith smart contracts, which in practice are simply appropriate pieces of code running on a blockchain. For our purpose, the internal processing within smart contracts is not relevant; in our model these are just "black-box" objects with a specified functionality. The contracts used in our model are called *hash time-lock contracts*, or *HTLCs*, for short, and are defined as follows: Each contract is associated with an arc of G. For an arc (u, v), its associated contract is used to transfer the asset (u, v) from u to v. It is created by party u, with u providing it with the asset, time-out value τ , and a hashlock value h. Once this contract is created, the possession of the asset is transferred from u to the contract; in other words, the asset is in this contract's escrow. The counter-party v can access the contract to verify whether its correctness; in particular, it can learn the hashlock value h. There are two ways in which the asset can be released:

- One, v (the buyer) can claim it. To claim it successfully, v must provide a value s such that H(s) = h not later than at time τ . When this happens, the smart contract transfers the asset to v, and it also gives the value of s to u. One can think of this as an exchange of the asset for the secret value s.
- Two, the contract can expire. As soon as the current time exceeds τ , and if the asset has not been successfully claimed, the contract returns the asset to its seller u.

All contracts considered in our paper are HTLCs, so the terms "contract" and "HTLC" are from now on synonymous. Further overloading notation and terminology, we will also refer to the contract on arc (u, v) as "contract (u, v)". If this contract has hashlock h_x of a party x (where x may be different from u and v), we will say that it is *protected by hashlock* h_x or simply *protected by party* x. Note that this does not mean that this contract was created by x.

Swap protocols. We assume that the time is discrete, consisting of unit-length time steps, starting at time 0. A swap protocol \mathbb{P} specifies for each party and each time step what actions this party executes at this step. These actions may involve internal computation or external actions, like communication.

In an execution of \mathbb{P} there is no guarantee that all parties actually follow \mathbb{P} . It may happen that some parties may deviate from \mathbb{P} for some reason, for example in an attempt to improve their outcomes, or they may just behave erratically. When we refer to an *honest* or *conforming* party u, we mean that u follows \mathbb{P} , except when it can infer from an interaction with some other party that not all parties follow \mathbb{P} . From that point on, u may behave arbitrarily (but still rationally, so it would not do anything that might worsen its ultimate outcome).

The execution of a protocol results in some assets being transferred between parties. We assume that when the process completes, even if some parties do not follow the protocol, an asset associated with arc (u, v) will end up either in the possession of u or in the possession of v.

In an *HTLC-based protocol*, all asset transfers are implemented with HTLCs, and no other interaction between the parties is allowed. Each party is allowed to create one secret/hashlock pair. These hashlock values are distributed via smart contracts. (These values can in fact be simply made public.) A more formal definition can be found in Section 5.

Outcomes. For each party v, v's outcome associated with an execution of a protocol \mathbb{P} is specified by the sets of asets that are relinguished and acquired by v in this execution. Thus such an outcome is a pair $\omega = \langle \omega^{in} | \omega^{out} \rangle$, where $\omega^{in} \subseteq A_v^{in}$ and $\omega^{out} \subseteq A_v^{out}$. To reduce clutter, instead of arcs, in $\langle \omega^{in} | \omega^{out} \rangle$ we can list only the corresponding in-neighbors and out-neighbors of v; for example, instead of $\langle \{(x, v), (y, v)\} | \{v, z\} \rangle$ we will write $\langle x, y | z \rangle$.

An outcome $\omega = \langle \omega^{in} | \omega^{out} \rangle$ of some party u is called *acceptable* if in this outcome u retains all its own assets or it gains all incoming assets. That is, either $\omega^{in} = A_v^{in}$ or $\omega^{out} = \emptyset$ (or both). Following Herlihy [8], we define several types of outcomes for each party v:

- $DEAL_v = \langle A_v^{in} | A_v^{out} \rangle$ represents an outcome where all prearranged asset transfers involving v are completed.
- NODEAL $_v = \langle \emptyset | \emptyset \rangle$ represents an outcome where none of prearranged asset transfers involving v is completed.
- DISCOUNT_v = { $\langle A_v^{in} | \omega^{out} \rangle$: $\omega^{out} \neq A_v^{out}$ }. That is, DISCOUNT_v is the set of outcomes in which all of v's incoming asset transfers are completed, but not all outgoing transfers are.
- FREERIDE_v = { $\langle \omega^{in} | \emptyset \rangle : \omega^{in} \neq \emptyset$ }. That is, FREERIDE_v is the set of outcomes in which none of v's outgoing asset transfers is completed, but some of its incoming transfers are.

We will skip the subscript v in these notations whenever v is understood from context. These four types of outcomes are exactly all acceptable outcomes, that is ω is acceptable if and only if

 $\omega \in {\text{NoDeal}} \cup {\text{Deal}} \cup {\text{FreeRide}} \cup {\text{Discount}}$

(This is in fact how [8] defines the acceptable outcomes.) All other outcomes are of type UNDERWATER and are considered unacceptable.

For a set C of parties, its set A_C^{in} of incoming arcs consists of arcs (u, v) with $u \notin C$ and $v \in C$. The set A_C^{out} of outgoing arcs is defined analogously. With this, the concept of outcomes and its properties, as defined above, extend naturally to sets of parties (that we refer occasionally as "coalitions"). For example, an outcome of C is *acceptable* if it either contains all incoming arcs of C or does not contain any outgoing arcs of C.



Figure 1: Four types of acceptable outcomes. Solid arrows represent transferred assets and dotted arrows represent those that are not.



Figure 2: An example of a preference relation of a node v whose neighborhoods are $N_v^{in} = \{a, b\}$ and $N_v^{out} = \{x, y\}$. Arrows represent preferences.

The preference relation. A *preference relation* of a party v is a partial order on the set of all outcomes for v that satisfies the following three properties:

- (*p1*) If $\omega_1^{in} \subseteq \omega_2^{in}$ and $\omega_1^{out} \supseteq \omega_2^{out}$, then ω_2 is preferred to ω_1 . In other words, it is better to receive more assets and relinguish fewer assets.
- (p2) If $\omega \in$ UNDERWATER then NODEAL is preferable to ω .
- (p3) DEAL is better than NODEAL. Otherwise, v would have no incentive to participate in the protocol.

The preference relation of a party v captures which outcomes are more desirable for v. Its intended to capture rational behavior of parties, leading to the definition of Nash equilibrium property, given below.

Protocol properties. Following [8], we define the following properties of a swap protocol \mathbb{P} :

- *Liveness*: \mathbb{P} is called *live* if all assets are transferred (that is, each party ends up in DEAL), providing that all parties follow \mathbb{P} .
- Safety: \mathbb{P} is called *safe* if each honest party ends up in an acceptable outcome, independently of the behavior of other parties.
- Strong Nash Equalibrium: \mathbb{P} has the strong Nash equilibrium property if no party has an incentive to deviate from the protocol. More precisely, for any set C of parties (a coalition), if all parties outside C follow the protocol then the parties in C cannot improve the outcome of C by deviating from the protocol.
- Atomicity: P is called *atomic* if its live, safe, and has the strong Nash equilibrium property.

The lemma below is a mild extension of the one given by Herlihy [8]. The difference is that in our definition of the preference relation we allow some FREERIDE outcomes to be preferable to DEAL, which



Figure 3: Illustration of Cases 1 and 2 in the proof of Lemma 1. Solid arrows represent transferred assets and dotted arrows represent those that are not. In the figure on the left, j = 6. In the figure on the right, k = 7 and j = 3.

was not the case in [8]. The point of the lemma is that, in Herlihy's preference model, the strong Nash equilibrium property comes for free, namely that each protocol has this property as long as it satisfies the liveness and safety properties. The strong connectivity assumption is necessary for the safety property to hold, see [8].

Lemma 1. Assume that digraph G is strongly connected. If a protocol \mathbb{P} is live and safe then \mathbb{P} is atomic.

Proof. Assume that \mathbb{P} is live and safe. To prove that \mathbb{P} is atomic, we need to show that it satisfies the strong Nash equilibrium property, as defined above.

Towards contradiction, suppose that some coalition C has an outcome ω preferable to DEAL, even though all other parties outside C follow \mathbb{P} . Since ω is preferable to DEAL, it must be either in DISCOUNT or in FREERIDE. We now consider these two cases, in each reaching a contradiction. (See Figure 3 for illustration.)

<u>Case 1</u>: $\omega \in \text{DISCOUNT}$. That is, all incoming assets of C are transferred, but some outgoing asset (x, y) of C is not. Since G is strongly connected, there is a path $Q = y_1 y_2 \dots y_k$ in G from $y = y_1$ to $x = y_k$. Let y_j be the first vertex on this path that is in C. By the choice of y_1 , we have j > 1. As y_1 follows the protocol, the safety condition guarantees that its outcome is acceptable. Since (x, y_1) is not transferred and y_1 's outcome is acceptable, all outgoing assets of y_1 are also not transferred. In particular, asset (y_1, y_2) is not transferred. The same argument gives us that if j > 2 then all outgoing assets of y_2 are not transferred. Repeating this for all vertices y_1, y_2, \dots, y_{j-1} , we will eventually obtain that the asset (y_{j-1}, y_j) is not transferred. But (y_{j-1}, y_j) is an incoming asset of C, so C's outcome ω cannot be in DISCOUNT.

<u>Case 2</u>: $\omega \in \text{FREERIDE}$. That is, at least one incoming asset of C is transferred, but no outgoing asset of C is transferred. Consider a transferred asset (x, y) that is incoming into C. Since G is strongly connected, there is a path $Q = y_1 y_2 \dots y_k$ in G from $y = y_1$ to $x = y_k$. Let y_j be the last vertex in C on this path. Then (y_j, y_{j+1}) , being an outgoing asset from C, is not transferred. Since y_{j+1} follows the protocol, the safety condition guarantees that its outcome is acceptable. Since (y_j, y_{j+1}) is not transferred and y_{j+1} 's outcome is acceptable, all outgoing asset of y_{j+1} are also not transferred. In particular, (y_{j+1}, y_{j+2}) is not transferred. The same argument gives us that if $j+2 \leq k$ then all outgoing assets of y_{j+2} are not transferred. Repeating this for all remaining vertices on the path, we will eventually obtain that asset $(y_k, y) = (x, y)$ is not transferred, which is a contradiction. So C's outcome ω cannot be in FREERIDE.

4 An Atomic Protocol for Reuniclus Digraphs

In this section we give an atomic asset-swap protocol for reuniclus digraphs. The concept of reuniclus digraphs was introduced informally in Section 1, and the formal definition is given below in Section 4.2.

We present this protocol in two steps. First, in Section 4.1, we describe an atomic protocol for bottleneck digraphs called Protocol BDP (short for *bottleneck-digraph protocol*). This protocol is essentially equivalent to a simplified version of Herlihy's protocol (see [8], Section 46). We include it here for the sake of completeness, as it is an essential ingredient of our full protocol for reuniclus digraphs, called Protocol RDP (short for *reuniclus-digraph protocol*), that is presented in Section 4.2.

4.1 Protocol BDP for Bottleneck Digraphs

A vertex v in a digraph G is called a *bottleneck vertex* if it belongs to each cycle of G. In other words, v is a singleton feedback vertex set of G. If G is strongly connected and has a bottleneck vertex then we refer to G as a *bottleneck digraph*.

We now describe Protocol BDP, an atomic asset-swap protocol for bottleneck digraphs. Given a bottleneck digraph G, one bottleneck vertex of G is designated as the *leader*. This leader, denoted ℓ , creates its secret/hashlock pair (s_{ℓ}, h_{ℓ}) . The other vertices are called *followers*. Protocol BDP has two phases. The first phase, initiated by ℓ , creates all contracts. Each follower waits for all the incoming contracts to be created, and then creates the outgoing contracts. The timeout values for all incoming contracts are strictly larger than the timeout values for all outgoing contracts. In the second phase the assets are claimed, starting with ℓ claiming its incoming assets. Now the process proceeds backwards. For each follower v, when any of its outgoing assets is claimed, v learns the secret value s_{ℓ} , and it can now claim its incoming assets.

The detailed description of this protocol is given in Figure 4. In the protocol, D_v^- denotes the *maximum* distance from ℓ to v, defined as the maximum length of a simple path from ℓ to v. In particular, $D_{\ell}^- = 0$. For $y \neq \ell$, the value of D_y^- can be computed recursively using the formula

$$D_{y}^{-} = \max_{z \in N_{y}^{in}} D_{z}^{-} + 1 \tag{1}$$

This is in essence the standard recurrence for computing the longest path in acyclic digraphs. (One can think of G as a DAG by splitting ℓ into two vertices, one with the outgoing arcs of ℓ and the other with the incoming arcs of ℓ .) The values D_y^- are used in contract creation times.

By D^* we denote the maximum length of a simple cycle in G. This cycle is just a path from ℓ to ℓ that does not repeat any vertices except for ℓ , so $D^* = \max_{z \in N_{\ell}^{in}} D_z^- + 1$, analogously to (1).

In the timeout values, the notation D_v^+ is the maximum distance from v to ℓ . These values satisfy a recurrence symmetric to (1), namely $D_\ell^+ = 0$ and for $y \neq \ell$

$$D_y^+ = \max_{z \in N_y^{out}} D_z^+ + 1$$
 (2)

Naturally, we then also have $\max_{z \in N_{\ell}^{out}} D_z^+ + 1 = D^*$. Note that, for each party v, the timeouts of all incoming contracts (u, v) are equal $D^* + D_v^+$, exactly the time when v is scheduled to claim them. And, by equation (2), if $v \neq \ell$ then $D^* + D_v^+$ is larger than the timeout $D^* + D_w^+$ of each outgoing contract (v, w).

Figure 5 shows an example of a bottleneck digraph and its timeout values in Protocol BDP.

Theorem 2. If G is a bottleneck digraph, then Protocol BDP is an atomic swap protocol for G.

Proof. According to Lemma 1, it is sufficient to prove only the liveness and safety properties.

Liveness. For the liveness property, we need to prove that if all parties follow BDP then all assets will be transferred, and thus all parties end up in DEAL. Assume all parties follow the protocol. In the first phase, according to equation (1), each party has one time unit after all its incoming contracts are placed to create its outgoing contracts. Thus all contracts will be successfully created and the last contract will be created by the last in-neighbor of ℓ , in step $\max_{z \in N_e^{out}} D_z^+ = D^* - 1$, so before the second phase starts. In the second

Protocol BDP for leader ℓ :	Protocol BDP for a follower <i>u</i> :
• At time 0: Create a secret s_{ℓ} and compute	• At time D_u^- : Check if all the incoming contracts are
$h_{\ell} = H(s_{\ell})$. For each arc (ℓ, v) , create the	created, correct, and have the same hashlock value,
contract with hashlock h_ℓ and timeout $ au_{\ell v} =$	say h. (If not, abort.) For each arc (u, v) , create con-
$D^* + D_v^+.$	tract with hashlock h and timeout $\tau_{uv} = D^* + D_v^+$.
• At time D^* : Check if all the incoming con-	• At time $D^* + D_u^+$: Check if any of the outgoing
tracts are created, correct, and have the same	assets was claimed. (If not, abort.) Let s be the secret
hashlock value h_{ℓ} . (If not, abort.) Claim all	obtained from the contract for some claimed outgoing
incoming assets using secret s_{ℓ} .	assets. Use s to claim all incoming assets.

Figure 4: Protocol BDP, with the protocol of the leader on the left, and the protocol of the followers on the right. Each bullet-point step takes one time unit. To check correctness of an incoming contract, the buyer verifies if the seller created it according to the protocol; in particular, whether the contract contains the desired asset and whether the timeout values are correct.



Figure 5: An example of a bottlebeck digraph G and the timeout values for Protocol BDP for G. The longest cycle in G is $\ell, b, f, g, h, d, e, j, \ell$, so $D^* = 8$.

phase each asset (u, v) will be claimed at time $D^* + D_v^+$, and at that time u will receive the secret s_ℓ . By equation (2), $D^* + D_u^+$ is larger than $D^* + D_v^+$. So u will be able to successfully claim all incoming assets at time $D^* + D_u^+$, which is also the timeout value for these assets. This shows that Protocol BDP satisfies the liveness property.

Safety. Consider some party v, and assume that v follows the protocol. We need to show that v will end up in an acceptable outcome, even if other parties deviate from the protocol. In other words, we need to show that either all incoming assets of v are transferred or all outgoing assets of v are not transferred. We consider two cases, when v is the leader and when v is a follower.

<u>Case 1</u>: $v = \ell$. If some incoming contract of ℓ is not created before time D^* , ℓ will abort the protocol³. Since ℓ does not reveal its secret, none of ℓ 's outgoing assets can be claimed. So all outgoing contracts will expire and their assets will be returned to ℓ . In this case, ℓ 's outcome is NODEAL, so it is acceptable.

Next, suppose that all incoming contracts of ℓ are created before time D^* . According to the protocol, each incoming contract (u, ℓ) of ℓ has timeout $\tau_{u\ell} = D^* + D^+_{\ell} = D^*$. Thus ℓ can claim all incoming assets at time D^* , so its outcome will be DEAL or DISCOUNT, both acceptable.

<u>Case 2</u>: $v \neq \ell$. If some incoming contract of v is not created before time D_v^- , v likewise will abort the protocol. Then none of v's outgoing assets will be claimed and the incoming contracts will expire, so the outcome will be NODEAL, which is acceptable.

Next suppose that at time D_v^- all incoming contracts of v are created, correct, and all have the same

³It may be tempting, if ℓ has any incoming contract created, to claim its asset, even if some other incoming contract is not created. This, however, would make the protocol unsafe, because then ℓ could lose some of its outgoing assets.

hashlock value h. Then v will create all outgoing contracts with the same hashlock h. (We remark here that, as other parties may not follow the protocol, it is not necessarily true that $h = h_{\ell}$.) At time $D^* + D_v^+$, if none of the outgoing assets of v are claimed then the outgoing assets will be returned to v, so v's outcome will be NODEAL or FREERIDE. On the other hand, if any asset (v, w) is claimed, it must be claimed no later than at time $\tau_{vw} = D^* + D_w^+$, and at this time v will obtain a secret value s. Since v used the same hashlock h on the outgoing contracts as the one on the incoming contracts, it must be that H(s) = h, for otherwise w would not be able to successfully claim (v, w). So s will also work correctly for any incoming contract. Since $\tau_{vw} < D^* + D_v^+$, and $D^* + D_v^+$ is the timeout of all v's incoming contracts, v will successfully claim all incoming assets at time $D^* + D_v^+$. Thus v's outcome would be either DEAL or DISCOUNT, both of which are acceptable.

We remark that some optimizations can reduce the number of steps needed in Protocol BDP. For example, it is not necessary for a follower u to wait until step $D^* + D_u^+$ to claim the incoming assets. Instead, u can claim all its incoming assets as soon as any of its outgoing assets is claimed.

4.2 **Protocol BDP for Reuniclus Digraphs**

Reuniclus digraphs. Let G be a strongly connected digraph. We call G a *reuniclus digraph* if there are vertices $b_1, b_2, ..., b_p \in G$, induced subgraphs $G_1, G_2, ..., G_p$ of G, and a rooted tree \mathcal{K} whose nodes are $b_1, b_2, ..., b_p$, with the following properties:

- (rg1) Each digraph G_j is a bottleneck subgraph, with b_j being its bottleneck vertex. We call G_j a *bottleneck* component of G.
- (rg2) If $i \neq j$, then

$$G_i \cap G_j = \begin{cases} \{b_j\} & \text{if } b_i \text{ is the parent of } b_j \text{ in } \mathcal{K} \\ \emptyset & \text{otherwise} \end{cases}$$

Part (rg2) says that G_i and G_j are either disjoint or only share one vertex, which is the bottleneck b_j of G_j . We call G_j the *home component* of b_j . We refer to \mathcal{K} as the *control tree* of G. (See Figure 6 for an example.) We extend the tree terminology to relations between bottleneck components, or between bottleneck vertices and components, in a natural fashion. For example, if b_i is the parent of b_j in \mathcal{K} then we refer to G_i as the parent component of b_j , to G_j as the child component of b_i . The same convention applies to the ancestor and descendant relations.

Intuitively, a reuniclus graph G can be divided into bottleneck components. Among these, most of are pairwise disjoint. Overlaps are allowed only between two components if one is the parent of the other in the control tree \mathcal{K} , in which case the overlap is just a single vertex that is the bottleneck of the child component.

From the definition, we have that the set of all bottleneck vertices in G forms a feedback vertex set of G. These bottleneck vertices are articulation vertices of G. The bottleneck components are not necessarily biconnected; each bottleneck component may consist of several biconnected components that share the same bottleneck vertex.

Protocol RDP. Protocol RDP can be thought of as a hierachical extension of Protocol BDP. Each bottleneck vertex b_j is called the leader of G_j . It creates its own secret/hashlock pair (s_j, h_j) , and its hashlock h_j is used to safely transfer assets within G_j , while the transfer of assets in the descendants components of b_j is "delegated" to the children of b_j in \mathcal{K} . We assume that the root component of \mathcal{K} is G_1 , and its bottleneck b_1 is called the *main leader*, that will be also denoted by ℓ . All non-leader vertices are called *followers*.

Protocol RDP has two parts. In the first part all contracts are created and in the second part the parties claim their incoming assets. In the first phase, at time 0 all leaders create the outgoing contracts within their



Figure 6: An example of a reuniclus graph (left) and its control tree (right). The bottleneck components (circled) are B, U, X, Y and Z. Their designated bottleneck vertices are b, u, x, y and z. Note that Z consists of two biconnected components.

home bottleneck components. Then the contracts are propagated within the bottleneck components, to some degree independently; except that each leader b_j creates its outgoing contracts in its parent component G_i only after all its incoming contracts, both in G_i and G_j , are created. This in fact ensures that at that time all contracts in its descendant components will be already created.

In the asset claiming phase, the main leader ℓ is the first to claim the incoming contracts. The behavior of followers is the same as in Protocol BDP: they claim the incoming assets one step after all their outgoing assets were claimed. The behavior of all non-main leaders is more subtle. Each such leader b_j waits until all its outgoing assets *in the parent component* are claimed, and then it claims all of its incoming assets. (So b_j does not wait for the outgoing assets in its home component to be claimed.)

The full protocol for non-main leaders b_j is given in Figure 7. Figure 8 shows timeout values for the reuniclus graph in Figure 6. In what follows we explain some notations used in the protocol.

As before, we use notation D_y^+ for the maximum distance from y to ℓ in G (see the formula (1) in Section 4.1). The formula (2) remains valid as is. We also need the concept analogous to the maximum distance from a leader, but this one is a little more subtle than for bottleneck graphs, because we now need to consider paths whose initial bottleneck vertex can be repeated once later on the path. Formally, if $v \in G_i$, then B_v^- denotes the maximum length of a path with the following properties:

- (i) it starts at some leader b_j that is a descendant of b_i (possibly $b_j = b_i$),
- (ii) it ends in v, and
- (iii) it does not repeat any vertices, with one possible exception: it can only revisit b_j , and if it does, it either ends or leaves G_j (and continues in the parent component of b_j).

(This can be interpreted as a maximum path length in a DAG obtained by splitting each leader into two vertices, one with the outgoing arcs into its home component and the other with all other arcs.) For example, in the example in Figure 6, one allowed path for v = u is x - y - z - d - x - j - u.

These values can be computed using auxiliary values B_{uv}^- defined for each edge (u, v). Call an edge (u, v) a *bottleneck edge* if u is a bottleneck vertex, say $u = b_j$, and $v \in G_j$. That is, bottleneck edges are the edges from bottleneck vertices that go into their home components. First, for each bottleneck edge (b_j, v) let $B_{bv}^- = 0$. Then, for each vertex u and each non-bottleneck edge (u, v) let

$$B_u^- = B_{uv}^- = \max_{(x,u)} B_{xu}^- + 1$$
(3)

where the maximum is over all edges (x, u) entering u. By B^* we denote the value of B_{ℓ}^- .

Protocol BDP for a leader $b_j \in G_i \cap G_j$:

• At time 0: Generate secret s_j and compute $h_j = H(s_j)$. For each arc (b_j, v) in G_j , create contract with hashlock h_j and timeout $\tau_{b_jv} = B^* + D_v^+$.

• At time B_u^- : Check if all incoming contracts are in place, if they are correct, if all the hashlocks in the incoming contracts in G_i have the same value h, and if all the hashlocks in the incoming contracts in G_j are equal h_j . (If not, abort.) For each arc (b_j, v) in G_i create its contract with hashlock h and timeout $\tau_{b_iv} = B^* + D_v^+$.

• At time $B^* + D_u^+$: Check if any of the outgoing assets in G_i was claimed. (If not, abort.) Let s be the secret obtained from the contract for some claimed outgoing assets in G_i . Claim all its incoming assets, using secret s in G_i and using secret s_j in G_j .

Figure 7: Protocol RDP for a sub-leader b_j , namely the bottleneck vertex of G_j that also belongs to its parent graph G_i . Recall that B_u^- is the maximum distance from some leader to u along a path that satisfies conditions (i)-(iii), and that $B^* = B_\ell^-$. D_v^+ is the maximum length of a simple path from v to ℓ , as defined in Section 4.1. As explained in the text, the protocols for the main leader and the pure followers are the same as in Protocol BDP.



Figure 8: Timeout values and hashlocks for Protocol RDP for the graph in Figure 6. The main leader is $\ell = b$. We have $B^* = 9$ (this is the length of path y - c - y - z - d - g - x - j - u - b).

The values B_z^- determine contract creation times. As shown in Figure 7, each leader b_j will create its contracts in its home component at time 0. Each other contract (u, v) will be created at time B_u^- . The last contract will be created by some in-neighbor of ℓ at time step $B^* - 1$. Then ℓ will initiate the contract claiming phase at time B^* . Analogous to Protocol BDP, each party u will claim its incoming contracts at time $B^* + D_u^+$, which is its timeout value.

Theorem 3. If G is a reuniclus digraph, then Protocol RDP is an atomic swap protocol for G.

Proof. According to Lemma 1, it is sufficient to prove only the liveness and safety properties.

Liveness. The liveness property is quite straightforward. Each party $u \neq \ell$ has exactly one time unit, after its last incoming contract is created, to create its outgoing contracts, according to (3). This will complete the contract creation at time $B^* - 1$. Thus at time B^* leader ℓ can claim its incoming assets. For any other party u, each incoming asset (x, u) of u has timeout $\tau_{xu} = B^* + D_u^+$. By formula (2), if u is a follower then all the outgoing assets of u will be claimed before time τ_{xu} , and if u is a non-main leader then all of u's ougoing assets in its parent component will be claimed before time τ_{xu} . So u can claim all incoming assets at time τ_{xu} .

Safety. The proof of the safety condition for the main leader ℓ and pure followers is the same as in

Protocol BDP for bottleneck digraphs. So here we focus only on non-main leaders.

Let b_j be a non-main leader whose parent component is G_i . Assume that b_j follows the protocol. So, according to Protocol RDP, b_j will create its outgoing contracts in G_j at time 0. Before creating its outgoing contracts in G_i , b_j checks if *all* incoming contracts are created. If any of its incoming contracts is not created or if any value in this contract is not as specified in the protocol, b_j will abort without creating its outgoing contracts in G_i . Thus its outcome will be NODEAL.

So assume that all incoming contracts of b_j are created and correct; in particular all incoming contracts in G_j have hashlock h_j and all incoming contracts in G_i have the same hashlock h (which may or may not be equal to h_i). Then b_j creates its outgoing contracts in G_i , as in the protocol. We now need to argue that if any of b_j 's outgoing assets is successfully claimed then b_j successfully claims *all* its incoming assets.

Suppose that some outgoing asset of b_j , say (b_j, w) is successfully claimed by w. Two cases arise, depending on whether w is in G_i or G_j .

If $w \in G_i$ (the parent component of b_j) then from contract (b_j, w) will provide b_j with some secret value s for which H(s) = h, because b_j used h for its outgoing contracts in G_i . At this point, b_j has both secret values s and s_j , and, by formula (2), the timeout of all incoming contracts of b_j is greater than the timeout of (b_j, w) . Therefore b_j has the correct secrets and at least one time unit to claim all incoming contracts, and its outcome will be DEAL or DISCOUNT, thus acceptable.

In the second case, $w \in G_j$, the home component of b_j . For w to successfully claim (b_j, w) , it must have the value of s_j . But, as b_j follows the protocol, it releases s_j only when claiming all incoming assets. So at this time b_j already has all incoming assets. Therefore in this case the outcome of b_j is also either DEAL or DISCOUNT.

5 A Characterization of Digraphs that Admit SHL-Based Protocols

In this section we provide a full characterization of digraphs that have HTLC-based protocols, showing that these are exactly the reuniclus digraphs. The concept of HTLC-based protocols was informally introduced in Section 1. For our characterization we need a more precise definition that we provide next.

Formal definition of HTLC-based protocols. We will say that a protocol \mathbb{P} is an *HTLC-based protocol* if \mathbb{P} consists of discrete time steps, each taking one time unit, and in each step any party v is allowed to execute any number of the following actions:

- Create a secret/hashlock pair: v can create a secret value s_v and compute the corresponding hashlock $h_v = H(s_v)$. We assume that v can create only one hashlock.
- *Create contract*: If $(v, w) \in G$, v can create an HTLC for transferring the asset (v, w) to w. This contract can be created only once. It must be secured with a hashlock h_x of some party x that created a secret/hashlock pair.
- Claim asset: If $(u, v) \in G$ and the contract (u, v) is placed and and not yet expired (that is, the current time does not exceed the timeout value τ_{uv} of this contract), then v can claim asset (u, v), providing that v knows the secret value s_y corresponding to the hashlock value h_y that protects this contract.

Parties have read access to the incoming contracts, so that they can verify their correctness and obtain their hashlock values. This allows a protocol to propagate the hashlock values. But the model also allows the parties to make the hashlock values public or distribute them selectively to other parties. There are no restrictions on local computation, with one obvious exception, namely that the parties cannot break any cryptographic tools used in smart contracts.

We now turn to our characterization, captured by Theorem 1 in Section 1, that we restate here for convenience: **Theorem 1.** A swap digraph G has an atomic HTLC-based protocol if and only if G is a reuniclus digraph.

The rest of this section is devoted to the proof of Theorem 1. By straightforward inspection, Protocol RDP from Section 4.2 is HTLC-based: each party creates at most one secret/hashlock pair, and all contracts are created and claimed following the rules detailed above. This already proves the (\Leftarrow) implication in Theorem 1.

It remains to prove the (\Rightarrow) implication, namely that the existence of an atomic HTLC-based protocol implies the reuniclus property of the underlying graph. We divide the proof into two parts. First, in Section 5.1 we establish some basic properties of HTLC-based protocols. Using these properties, we then wrap up the proof of the (\Rightarrow) implication in Section 5.2.

5.1 Basic Properties of HTLC-Based Protocols

Let \mathbb{P} be an HTLC-based protocol for a strongly connected digraph G, and for the rest of this section assume that \mathbb{P} is atomic. We now establish some fundamental properties that must be satisfied by \mathbb{P} . To be more precise, whenever we say that \mathbb{P} has a certain property, we mean that this property is satisfied in the *conforming execution* of \mathbb{P} on G, that is when all parties are *conforming* (or, equivalently, *honest*), that is they follow \mathbb{P} .

Withouth loss of generality we can assume that in \mathbb{P} each asset (u, v) is claimed by v exactly at the expiration time τ_{uv} of contract (u, v). This is because otherwise we can decrease the timeout value τ_{uv} to the time step when v claims asset (u, v) in \mathbb{P} , and after this change \mathbb{P} remains HTLC-based and atomic. Note also that the liveness property of \mathbb{P} implies that τ_{uv} must be larger than the creation time of contract (u, v).

Most of the proofs of protocol properties given below use the same fundamental approach, based on an argument by contradiction: we show that if \mathbb{P} did not satisfy the given property then there would exist a (non-conforming) execution of \mathbb{P} in which some parties, by deviating from \mathbb{P} , would force a final outcome of some conforming party to be unacceptable, thus violating the safety property.

Lemma 2. If some party successfully claims an incoming asset at some time t, then all contracts in the whole graph must be placed before time t.

Proof. Assume that a party v successfully claims an asset (u, v) at time t. Towards contradiction, suppose that there is some arc (x, y) for which the contract is still not placed at time t. Since G is strongly connected, there is a path $y = u_1, u_2, ..., u_p = u$ from y to u in G. Let also $u_0 = x$ and $u_{p+1} = v$. Now consider an execution of \mathbb{P} in which all parties except x are conforming, x follows \mathbb{P} up to time t - 1, but later it never creates contract (x, y). This execution is indistinguishable from the conforming execution up until time t - 1, so at time t node v will claim contract (u, v). Since the first asset on path $u_0, u_1, ..., u_{p+1}$ is not transferred and the last one is, there will be a party u_j on this path, with $1 \le j \le p$, for which asset (u_{j-1}, u_j) is not transferred but (u_j, u_{j+1}) is. But then the outcome of u_j is unacceptable even though u_j is honest, contradicting the safety property of \mathbb{P} .

Lemma 2 is important: it implies that \mathbb{P} must consist of two phases: the *contract creation* phase, in which all parties place their outgoing contracts (by the liveness property, all contracts must be created), followed by the *asset claiming* phase, when the parties claim their incoming assets.

Recall that by a *contract protected by* x we mean a created contract with hashlock h_x . (Here, x is not necessarily the party that created the contract.)

Lemma 3. Suppose that at a time t a party v creates an outgoing contract protected by a party different than v. Then all v's incoming contracts must be created before time t.

Proof. Suppose the property in the lemma does not hold for some party v, that is, at some time t, v creates a contract (v, w) protected by hashlock h_x of some party $x \neq v$, while some incoming contract (u, v) is not yet created.

We consider another execution of the protocol. In this execution, v is conforming. Also, up until time t - 1 all parties follow the protocol, so that v's behavior at time t will not change and it will create contract (v, w). Then at time t some parties will deviate from the protocol. Specifically, (i) at time t party x will give its secret value s_x to w (this is needed only if $x \neq w$), (ii) using s_x , party w will claim asset (v, w) at time t + 1, and (iii) u will never create contract (u, v). As a result, v will lose its asset (v, w) without getting asset (u, v), so v's outcome is not acceptable. This contradicts the safety property of \mathbb{P} , so we can conclude that \mathbb{P} must satisfy the lemma.

Consider now the snapshot of of \mathbb{P} right after the contract creation phase, when all contracts are already in place but none of the assets are yet claimed. The corollary below follows directly from Lemma 3.

Corollary 4. (a) If on some path each contract except possibly first is not protected by its seller, then along this path the contract creation times strictly increase. (b) Each cycle must contain a contract protected by its seller.

Next, we establish some local properties of \mathbb{P} . Namely, in the next four lemmas we will show that for each party v there is at most one other party that protects contracts involving v. We will also establish some relations between the timeout values of the contracts involving v.

Lemma 5. If a party v has an incoming contract protected by some party x different from v then

- (a) Party v has at least one outgoing contract protected by x.
- (b) All contracts involving v are protected either by v or by x.

Proof. Let (u, v) be an incoming contract protected by x, where $x \neq v$.

(a) This claim is easy: if v didn't have an outgoing contract protected by x, then even in the conforming execution it would never receive the secret value s_x needed to claim (u, v). That would violate the liveness property of \mathbb{P} .

(b) We first show that all outgoing contracts must be protected by v or x. Suppose that it is not true, namely that some outgoing contract (v, w) is protected by some party y, where $y \notin \{v, x\}$. Let t be the time right after all contracts are created. We change the behavior of some parties, as follows. Up to time t - 1 they follow the protocol. At time t, y can provide w with secret s_y , allowing w to claim (v, w) at time t + 1. All parties other than v and w don't do anything starting at time t. Then v will not receive the secret s_x needed to claim asset (u, v), so it will end up in an unacceptable outcome, contradicting the safety property. We can thus conclude that all outgoing contracts not protected by v must be protected by x.

Next, consider incoming contracts not protected by v. If (u', v) is an incoming contract of v protected by some party $x' \notin \{v, x\}$ then, by part (a), v would have at least one outgoing contract protected by x', contradicting that all outgoing contracts are protected either by v or x. This completes the proof of (b). \Box

Lemma 6. Let $P = u_1, u_2, ..., u_k$ be a simple path whose last contract is protected by some party $z \notin \{u_1, u_2, ..., u_{k-1}\}$. Then for each i = 1, ..., k - 1, contract (u_i, u_{i+1}) is protected by one of the parties $u_{i+1}, u_{i+2}, ..., u_{k-1}, z$. Consequently, each contract on P is not protected by its seller.

Proof. The second part of the lemma follows trivially from the first.

We prove the first part by induction, proceeding backwards on P. The claim is true for i = k-1, because, by our assumption, contract (u_{k-1}, u_k) is protected by z. Inductively (going backwards on P), assume that the lemma holds for i = k-1, k-2, ..., j, where $j \ge 2$. In particular, by the inductive assumption, (u_j, u_{j+1}) is protected by some party $u' \in \{u_{j+1}, u_{j+2}, ..., u_{k-1}, z\}$, Since P is a simple path, we have $u' \neq u_j$. Then Lemma 5 implies that contract (u_{j-1}, u_j) is protected either by u_j or by u'. Therefore contract (u_{j-1}, u_j) is protected by one of the parties $u_j, u_{j+1}, ..., u_{k-1}, z$. So the lemma holds for i = j - 1, completing the inductive step.

Lemma 7. If all incoming contracts of a party v are protected by v then all outgoing contracts of v are also protected by v.

Intuitively, if v had an outgoing contract protected by some other party x but not an incoming contract protected by x, then this outgoing contract would be "redundant" for v, since v does not need the secret from this contract to claim an incoming contracts. The lemma shows that the issue is not just redundancy — this is in fact not even possible if the protocol is atomic.

Proof. We prove the lemma by contradiction. Suppose that all v's incoming contracts are protected by v, but v has an outgoing contract (v, w) protected by some other party x. Let $P = u_1, u_2, ..., u_p$ be a simple path from w to v, that is $u_1 = w$ and $u_p = v$. Then Lemma 6 implies that all contracts on P are not protected by their sellers. The contract $(u_p, u_1) = (v, w)$ is not protected by its seller v. This would give us a cycle, namely $C = u_p, u_1, ..., u_{p-1}, u_p$, in which each contract is not protected by the seller. But this contradicts Corollary 4(b), completing the proof of the lemma.

Lemma 8. If a party v has an outgoing contract protected by some party x different from v then it has an incoming contract protected by x.

Proof. This follows quite easily from the lemmas above. Consider the incoming contracts of v. Not all of them can be protected by v, because otherwise Lemma 7 would imply that all outgoing contracts would also be protected by v, contradicting the assumption of the lemma. So some incoming contract is protected by some party $x' \neq v$. But then Lemma 5(b) implies that all outgoing contracts must be protected by either v or x', so we must have x' = x.

Lemma 9. A party v has an incoming contract protected by v if and only if it has an outgoing contract protected by v.

Proof. (\Rightarrow) Suppose that v has an incoming contract (u, v) protected by v. By Lemma 8, u has an incoming contract (u', u) protected by v. If $u' \neq v$, by the same argument, u' must also have an incoming contract protected by v. Repeating this process, we obtain a backward path with all contracts protected by v. If this path did not reach v it would have to create a cycle in which all contracts are protected by a party (namely v) outside this cycle, but this would contradict Corollary 4(b).

(\Leftarrow) The argument is symmetric to that in part (a). Suppose that v has an outgoing contract protected by v, say (v, w). If $w \neq v$ then, by Lemma 5, w has an outgoing contract protected by v. Repeating this process, we obtain a path with all contracts protected by v. If this path did not reach v it would have to create a cycle, but this would contradict Corollary 4(b).

The theorem below summarizes the local properties of the contracts involving a party v. See also the illustration of this theorem in Figure 9.

Theorem 4. Consider the contracts involving a party v, both incoming and outgoing.

- (a) For each party x (which may or may not be v), v has an incoming contract protected by x if and only if v has an outgoing contract protected by x.
- (b) If there are any contracts protected by v, then at least one incoming contract protected by v has a smaller timeout than all outgoing contracts protected by v.



Figure 9: Illustration of Theorem 4. Each contract is labelled by its timeout and the party that protects it. Per part (b), the minium timout 19 of incoming contracts protected by v which is itself smaller than the minimum timeout 20 of outgoing contracts protected by v. Per part (c), the maximum timeout 18 of outgoing contracts protected by x is smaller than the minium timout 19 of all incoming contracts.

(c) There is at most one party $x \neq v$ that protects a contract involving v. For this x, all timeouts of the outgoing contracts protected by x are smaller than all timeouts of the incoming contracts (no matter what party protects them).

Proof. (a) This part is just a restatement of the properties established earlier. For x = v, the statement is the same as in Lemma 9. For $x \neq v$, if v has an incoming contract protected by x then, by Lemma 5, it must have an outgoing contract protected by x, and if v has an outgoing contract protected by x then, by Lemma 8, it must have an incoming contract protected by x.

(b) Let (v, w) be an outgoing contract protected by v whose timeout value τ_{vw} is smallest. Consider any path P from w to v with all contracts on P protected by v. (This path must exist. To see this, starting from w follow contracts protected by v. By Corollary 4(b), eventually this process must end at v.) Then part (b) of Theorem 4 implies that along this path timeut values must decrease, so its last contract (u, v) must satisfy $\tau_{uv} < \tau_{vw}$. So the timeout value of (u, v) is smaller than that of (v, w), and thus also smaller than all timeout values of the outgoing contracts protected by v.

(c) Let $x \neq v$. If v has an incoming contract protected by x then, by Lemma 5, all contracts involving v but not protected by v are protected by x. If v has an outgoing contract protected by x then Lemma 8 implies that some incoming contract is protected by x, which leads to the same conclusion.

We now consider the claims about the timeout values. Let (v, w) be an outgoing contract protected by x, and let (u, v) be an incoming contract. Towards contradiction, suppose that in \mathbb{P} the timeouts of these contracts satisfy $\tau_{uv} \leq \tau_{vw}$. Denote by t the first step of \mathbb{P} after the contract creation phase. We consider two cases, depending on whether (u, v) is protected by x or v.

<u>Case 1</u>: contract (u, v) is protected by x. Suppose that in \mathbb{P} the timeout of contract (u, v) is $\tau_{uv} \leq \tau_{vw}$. We consider an execution of \mathbb{P} where all parties follow \mathbb{P} until itme t - 1. Then, starting at time t, we alter the behavior of some parties, as follows: all parties other than v, w and x will abort the protocol, x will provide its secret s_x to w, and w will claim asset (v, w) at time τ_{vw} . This way, the earliest v can claim asset (u, v) is at time $\tau_{vw} + 1$, which is after timeout τ_{uv} of (u, v). Thus v ends up in an unacceptable outcome, giving us a contradiction, which completes the proof of (b).

<u>Case 2</u>: contract (u, v) is protected by v. We can assume that its timeout τ_{uv} is minimum among all incoming contracts protected by v. (Otherwise, in the argument below replace (u, v) by the incoming contract protected by v that has minimum timeout.) Let (v, y) be any outgoing contract protected by v. From part (b), we have that $\tau_{uv} < \tau_{vy}$. Let also (z, v) be any incoming contract protected by x.

We now consider an execution of \mathbb{P} where all parties follow the protocol until time t - 1. At time t, all parties other than u, v, x, y, z abort the protocol, and x gives its secret s_x to w. As time proceeds, v may

notice that some parties do not follow the protocol, so, even though v is honest, from this time on it is not required to follow the protocol. We show that independently of v's behavior, it will end up in an unacceptable outcome, contradicting the safety property of \mathbb{P} .

To this end, we consider two possibilities. If v does not claim (u, v) at or before time τ_{uv} , then w can claim (v, w) at time τ_{vw} , so v will lose asset (v, w) without getting asset (u, v). On the other hand, if v claims (u, v), then u can give secret s_v to y that can then claim asset (v, y), and w will not claim asset (v, w), so v will not be able to claim asset (z, v), as it will not have secret s_x . In both cases, the outcome of v is unacceptable.

We now use the above properties to establish some global properties of \mathbb{P} . These properties involve paths and cycles in *G*. The first corollary extends Corollary 4, and is a direct consequence of Theorem 4(b).

Corollary 10. If on some path each contract except possibly first is not protected by the seller, then along this path the timeout values strictly decrease.

The next corollary follows from Corollaries 4 and 10.

Corollary 11. Let P be a path such that all contracts on P except possibly first are protected by a party x that is not an internal vertex of P. Then all contract creation times along P strictly increase and all timeout values strictly decrease.

Corollary 12. (a) Let (u, v) be a contract protected by some party x other than v. Consider a path P starting with arc (u, v), that doesn't contain x as an internal vertex and on which each contract is not protected by its seller. Then all contracts along P are protected by x.

(b) Let (u, v) be a contract protected by some party x other than u. Consider a path P ending with arc (u, v), that doesn't contain x as an internal vertex and on which each contract is not protected by its buyer. Then all contracts along P are protected by x.

Proof. (a) The corollary follows easily by repeated application of Theorem 4. Let (v, w) be the second arc on P. By the assumption, (v, w) is not protected by v, and since v has an incoming contract protected by x and $x \neq v$, Theorem 4 implies that contract (v, w) must be also protected by x. If w = x, this must be the end of P. If $w \neq x$, then w has an incoming contract protected by x, so we can repeat the same argument for w, and so on. This implies part (a).

(b) The proof for this part is symmetric to that for part (a), with the only difference being that we proceed now backwards from u along P.

Theorem 5. (a) Let P be a simple path starting at a vertex x whose last contract is protected by x. Then all contracts on P are protected by x.

(b) Let Q be a simple path ending at a vertex x whose first contract is protected by x. Then all contracts on Q are protected by x.

Proof. (a) Let $P = u_1, u_2, ..., u_{p+1}$, where $u_1 = x$ and (u_p, u_{p+1}) is protected by x. The proof is by contradiction. Suppose that P violates part (a), namely it contains a contract not protected by x. (In particular, this means that $p \ge 2$.) We can assume that among all simple paths that violate property (a), P is shortest. (Otherwise replace P in the argument below by a shortest violating path.) Then (u_{p-1}, u_p) is not protected by x, because otherwise the prefix of P from x to u_p would be a violating path shorter than P. So (u_{p-1}, u_p) is protected by u_p . Using Lemma 6, each contract on the path $u_1, u_2, ..., u_p$ is not protected by the seller. Since (u_p, u_{p+1}) is protected by x and $x \neq u_p$, each contract on P is not protected by its seller.

Next, we claim that there is a simple path P' from u_{p+1} to x whose all contracts are protected by x. If $u_{p+1} = x$, this is trivial, so assume that $u_{p+1} \neq x$. Then, since u_{p+1} has an incoming contract protected by x and $x \neq u_{p+1}$, u_{p+1} must have an outgoing contract (u_{p+1}, w) protected by x. If w = x, we are done.



Figure 10: Illustration of the proof of Theorem 5(a). Path P is marked with solid arrows, path P' is marked with dashed arrows. Here, p = 8 and $u_1 = x$. The labels on edges show the parties that protect them.

Else, we repeat the process for w, and so on. Eventually, extending this path we must end at x, for otherwise we would have a cycle with all contracts protected by x but not containing x, contradicting Corollary 4(b). This proves that such path P' exists. Since all contracts on P' are protected by x, they are not protected by their sellers.

Finally, let C be the cycle obtained by combining paths P and P'. (See Figure 10.) As shown above, every contract on C is not protected by its seller. But this contradicts Corollary 4, completing the proof of part (a).

(b) Let $Q = v_0, v_1, ..., v_q$, where $v_q = x$ and (v_0, v_1) is protected by x. Towards contradiction, suppose that some contract on Q is not protected by x. Analogously to part (a) we can make two assumptions: One, we can assume that $q \ge 2$ and (v_1, v_2) is not protected by x, which implies that it is protected by v_1 . Two, we can assume that there is a simple path Q' from v_1 to x with all contracts protected by x.

The rest of the proof is also similar to the proof of (a), but with a twist (because we do not have an analogue of Corollary 4 for buyers). The idea is to divide Q into segments protected by the same party, for each segment take a reverse path protected by this party, and combine these reverse paths into a path T from v_q to v_1 , with each contract not protected by its seller.

We now describe this construction. By the argument identical (except for reversing direction) to that in Lemma 6, each contract (v_i, v_{i+1}) , for $i \ge 1$, is protected by one of parties $v_1, v_2, ..., v_i$. Further, for each party v_i , where $i \notin \{0, q-1\}$, the contracts protected by v_i (if any) form a segment of Q starting at v_i . Let A consist of all indices i for which contract (v_i, v_{i+1}) is protected by v_i , and also include q in A. Order A in increasing order $a_1 < a_2 < ... < a_s$. So $a_1 = 1$, $a_s = q$, and for each r = 1, 2, ..., s - 1 the segment $v_{a_r}, v_{a_r+1}, ..., v_{a_{r+1}}$ of Q has all contracts protected by v_a .



Figure 11: Illustration of the proof of Theorem 5(b). Path Q is marked with solid arrows. Here, q = 9 and $v_9 = x$. Path Q' is marked with dashed arrows. Q is divided into three segments, protected by v_1 , v_4 , and v_6 , respectively. So $a_1 = 1$, $a_2 = 4$, $a_3 = 6$, and $a_4 = 9$. The corresponding reverse paths are T_1 , T_4 and T_6 , marked with dotted arrows.

For each r = 2, 3, ..., s, contract (v_{a_r-1}, v_{r_a}) is protected by v_{r_a-1} . By the same argument as in (a), we then obtain that there is a simple path T_{a_r-1} from v_{r_a} to v_{a_r-1} with all contracts protected by v_{a_r-1} , so none

protected by its seller. The concatenation of these paths forms a path T from $v_{r_s} = v_q$ to $v_{a_1} = v_1$. So each contract on T is not protected by its seller.

To finish, combine the two paths T and Q' into a cycle C. On C, each contract is not protected by the seller. This contradicts Corollary 4, completing the proof. \Box

5.2 Proof of the (\Leftarrow) Implication in Theorem 1

In this section we use the protocol properties established in the previous section to prove necessary conditions for a digraph to admit an atomic HTLC protocol. We start with protocols that use only one common hashlock for the whole graph.

Lemma 13. Suppose that G has an atomic HTLC protocol \mathbb{P} in which only one party creates a secret/hashlock pair. Then G must be a bottleneck graph.

Proof. Strong connectivity is a required property for *any* atomic protocol to exist, see [8]. If x is the party that created the secret/hashlock pair, then Corollary 4 implies that any cycle in G must contain x. Thus x is a bottleneck of G, proving the theorem.

We now consider the general case, when all parties are allowed to create secret/hashlock pairs. The lemma below establishes the (\Rightarrow) implication in Theorem 1.

Lemma 14. Suppose that G has an atomic HTLC protocol \mathbb{P} . Then G must be a reuniclus digraph.

Proof. Recall what we have established so far in Section 5.1. From Theorem 4(c) we know that, for each party u, all contracts involving u as a party are protected either by u or by just one other party. Using this property, we define the control relation on parties, as follows: If u has any contracts protected by some other party x, we will say that x controls u. Let \mathcal{K} be a digraph whose vertices are the parties that created secret/hashlock pairs, and each arc (u, x) represents the control relation, meaning that x controls u. We want to prove that \mathcal{K} is a tree.

Each node in \mathcal{K} has at most one outgoing arc. This property already implies that each connected component of \mathcal{K} is a so-called *1-tree*, namely a graph that has at most one cycle. So in order to show that \mathcal{K} is actually a tree, it is sufficient to show the two claims below.

Claim 15. *K* does not have any cycles.

We now prove Claim 15. Towards contradiction, suppose that \mathcal{K} has a cycle, say $C = v_1, v_2, ..., v_k, v_{k+1}$, where $v_{k+1} = v_1$. Consider any arc (v_i, v_{i+1}) on C. This arc represents that v_{i+1} controls v_i . So, in G, v_i has an outgoing contract protected by v_{i+1} . Let P_i be any path in G starting with this contract and ending at v_{i+1} . Then Theorem 5(b) gives us that all contracts on P_i protected by v_{i+1} . Combining these paths $P_1, ..., P_k$ we obtain a cycle C' in G. Then in C', each contract is not protected by its seller, which would contract Corollary 4(b). This completes the proof of Claim 15.

Claim 16. \mathcal{K} has only one tree.

From Claim 15 we know that each (weakly) connected component of \mathcal{K} is a tree. The roots of these trees have the property that they are not protected by any other party. To prove Claim 16, suppose towards contradiction that \mathcal{K} has two different trees, and denote by r and r' the roots of these trees. Since r, r' are roots of trees, all contracts involving r are protected by r and all contracts involving r' are protected by r and all contracts involving r' are protected by r'. Consider any simple path $P = u_1, u_2, ..., u_k$ from $u_1 = r$ to $r' = u_k$. Since the last contract on P is protected by r' and r' is not in $\{u_1, u_2, ..., u_{k-1}\}$, Lemma 6 implies that all contracts on this path are not protected by their sellers. But this contradicts the fact that (u_1, u_2) is protected by u_1 . This completes the proof of Claim 16.

We now continue with the proof of the theorem. Denote by $b_1, b_2, ..., b_p$ the nodes of \mathcal{K} . For each b_j , define G_j to be the subgraph induced by the contracts protected by b_j . That is, for each contract (u, v) protected by b_j we add vertices u, v and arc (u, v) to G_j . The necessary properties (rg1) and (rg2) follow from our results in Section 5.1. It remains to show that subgraphs graphs $G_1, G_2, ..., G_p$, together with tree \mathcal{K} , satisfy conditions (rg1) and (rg2) that characterize reuniclus graphs.

Consider some $u \neq b_j$ that is in G_j . By the definition of G_j , u is involved in a contract protected by b_j . Then Theorem 4 gives us that u has both an incoming and outgoing contract protected by b_j . Take any path P starting at an outgoing contract of u protected by b_j and ending at b_j . Then Theorem 5(b) implies that all contracts on P are protected by b_j . By the same reasoning, there is a path P' starting at b_j and ending with an incoming contract of u protected by b_j . Then, by Theorem 5(a) all contracts on P' are protected by b_j . This gives us that G_j is strongly connected. And, by Corollary 4, G_j cannot contain a cycle not including b_j . Therefore G_j is a bottleneck graph with b_j as its bottleneck.

We also need to prove that G_j is in fact an induced subgraph, that is, if $u, v \in G_j$ and G has an arc (u, v), then $(u, v) \in G_j$ as well. That is, we need to prove that (u, v) is protected by b_j . Suppose, towards, contradiction, that (u, v) is protected by some $b_i \neq b_j$. Then both u and v are involved in contracts protected by both b_i and b_j , and this implies that $u = b_i$ and $v = b_j$, or vice versa. And this further implies that b_i would be protected by b_j and vice versa, which would be a cycle in \mathcal{K} , contradicting that \mathcal{K} is a tree. This completes the proof of property (rg1).

Finally, consider property (rg2). If a vertex u is not any of designated bottlebeck vertices $b_1, b_2, ..., b_p$, then, by Theorem 4, all its contracts are protected by the same party, which means that it belongs to exactly one graph G_j . On the other hand, if $u = b_j$, then again by Theorem 4, it is involved in only in contracts protected by itself and one other party, say b_i . But then it belongs only to G_j and G_i , completing the proof of (rg2).

References

- N. Asokan, Matthias Schunter, and Michael Waidner. Optimistic protocols for fair exchange. In Proceedings of the 4th ACM Conference on Computer and Communications Security, CCS '97, pages 7–17, New York, NY, USA, 1997. ACM.
- [2] N. Asokan, Victor Shoup, and Michael Waidner. Optimistic fair exchange of digital signatures. *IEEE Journal on Selected Areas in Communications*, 18:593–610, 1997.
- [3] Michael Ben-Or, Oded Goldreich, Silvio Micali, and Ronald L. Rivest. A fair protocol for signing contracts. In Wilfried Brauer, editor, *Automata, Languages and Programming*, pages 43–52, Berlin, Heidelberg, 1985. Springer Berlin Heidelberg.
- [4] Eric Chan, Marek Chrobak, and Mohsen Lesani. Cross-chain swaps with preferences. In 36th IEEE Computer Security Foundations Symposium, CSF 2023, Dubrovnik, Croatia, July 10-14, 2023, pages 261–275. IEEE, 2023.
- [5] Apoorvaa Deshpande and Maurice Herlihy. Privacy-preserving cross-chain atomic swaps. In International Conference on Financial Cryptography and Data Security, pages 540–549. Springer, 2020.
- [6] Matt Franklin and Gene Tsudik. Secure group barter: Multi-party fair exchange with semi-trusted neutral parties. In Rafael Hirchfeld, editor, *Financial Cryptography*, pages 90–102, Berlin, Heidelberg, 1998. Springer Berlin Heidelberg.
- [7] Ethan Heilman, Sebastien Lipmann, and Sharon Goldberg. The arwen trading protocols. In *International Conference on Financial Cryptography and Data Security*, pages 156–173. Springer, 2020.

- [8] Maurice Herlihy. Atomic cross-chain swaps. In *Proceedings of the 2018 ACM Symposium on Principles of Distributed Computing*, PODC '18, pages 245–254, New York, NY, USA, 2018. ACM.
- [9] Maurice Herlihy, Barbara Liskov, and Liuba Shrira. Cross-chain deals and adversarial commerce. *arXiv* preprint arXiv:1905.09743, 2019.
- [10] Soichiro Imoto, Yuichi Sudo, Hirotsugu Kakugawa, and Toshimitsu Masuzawa. Atomic cross-chain swaps with improved space and local time complexity, 2019.
- [11] Subhra Mazumdar. Towards faster settlement in htlc-based cross-chain atomic swaps, 2022.
- [12] Silvio Micali. Simple and fast optimistic protocols for btcwiki electronic exchange. In *Proceedings of the Twenty-second Annual Symposium on Principles of Distributed Computing*, PODC '03, pages 12–19, New York, NY, USA, 2003. ACM.
- [13] Sri AravindaKrishnan Thyagarajan, Giulio Malavolta, and Pedro Moreno-Sánchez. Universal atomic swaps: Secure exchange of coins across all blockchains. *Cryptology ePrint Archive*, 2021.
- [14] Tier Nolan. Alt chains and atomic transfers. https://bitcointalk.org/index.php? topic=193281.msg2224949#msg2224949, 2013. [Online; accessed 23-January-2021].
- [15] Yingjie Xue and Maurice Herlihy. Hedging against sore loser attacks in cross-chain transactions. In Proceedings of the 2021 ACM Symposium on Principles of Distributed Computing, PODC'21, page 155–164, New York, NY, USA, 2021. Association for Computing Machinery.