# A Simple and Near-Optimal Algorithm for Directed Expander Decompositions

Aurelio L. Sulser<sup>\*</sup> ETH Zurich asulser@ethz.ch Maximilian Probst Gutenberg<sup>\*</sup> ETH Zurich maximilian.probst@inf.ethz.ch

#### Abstract

In this work, we present the first algorithm to compute expander decompositions in an *m*edge *directed* graph with near-optimal time  $\tilde{O}(m)^1$ . Further, our algorithm can maintain such a decomposition in a dynamic graph and again obtains near-optimal update times. Our result improves over previous algorithms [BGS20, HKGW23] that only obtained algorithms optimal up to subpolynomial factors. At the same time, our algorithm is much simpler and more accessible than previous work.

In order to obtain our new algorithm, we present a new push-pull-relabel flow framework that generalizes the classic push-relabel flow algorithm [GT88] which was later dynamized for computing expander decompositions in *undirected* graphs [HRW20, SW19]. We then show that the flow problems formulated in recent work [HKGW23] to decompose directed graphs can be solved much more efficiently in the push-pull-relabel flow framework.

<sup>\*</sup>The research leading to these results has received funding from grant no. 200021 204787 of the Swiss National Science Foundation.

<sup>&</sup>lt;sup>1</sup>In this article, we use  $\tilde{O}(\cdot)$  notation to suppress factors logarithmic in m, i.e.  $O(m \log^c m) = \tilde{O}(m)$  for every constant c > 0.

# 1 Introduction

Over the past two decades, expanders and expander decompositions have been pivotal in advancing fundamental algorithmic graph problems. The development and application of the first fast algorithm to compute near-expander decompositions was given in the development of the first near-linear time Laplacian solvers [ST04], a breakthrough in modern graph algorithms.

Subsequently, a line of research [HRW20, WN17, NS17, NSWN17] has focused on strengthening this result by developing fast flow-based pruning techniques that refine near-expander decompositions into expander decomposition techniques. This line of research culminated in [SW19] where a new, faster, simpler, and more user-friendly expander decomposition framework was presented. This advancement has catalyzed the widespread use of expander decompositions as a tool in graph algorithms and was instrumental in the recent surge of applications of expander decompositions in both static and dynamic graph settings for various cut, flow, and shortest path problems [ST04, KLOS14, HRW20, WN17, NS17, NSWN17, CK19, BGS20, Liu23, BvdBPG<sup>+</sup>22, VDBLL<sup>+</sup>21, Sar21, CDK<sup>+</sup>21, Li21, CS21, GRST21, Chu21, BGS22, BGS22, KMP22, JS22, VDBCP<sup>+</sup>23, KMG24, CKL<sup>+</sup>24, JST24].

In this work, we study the problem of computing and maintaining expander decompositions in *directed* graphs, defined as follows.

**Definition 1.1** (Directed Expander Decomposition). Given an m-edge directed graph G, we say a partition  $\mathcal{X}$  of the vertex set of G and a subset of edges  $E^r \subseteq E$  forms an  $(\beta, \phi)$ -expander decomposition if

- 1.  $\forall X \in \mathcal{X}, G[X] \text{ is a } \phi\text{-expander meaning there is no cut } (S, \overline{S}) \text{ such that } \frac{\min\{e_G(S, \overline{S}), e_G(\overline{S}, S)\}}{\min\{\operatorname{vol}_G(S), \operatorname{vol}_G(\overline{S})\}} < \phi, \text{ and } \phi$
- 2.  $|E^r| \leq \beta \cdot \phi \cdot m$ , and
- 3. the graph  $(G \setminus E^r) / \mathcal{X}$ , that is the graph G minus the edges in  $E^r$  where expander components in  $\mathcal{X}$  are contracted into supernodes, is a directed acyclic graph (DAG).

In our algorithm, we implicitly maintain an ordering of the partition sets in  $\mathcal{X}$  and let  $E^r$  be the edges that go 'backward' in this ordering of expander components. Note that we can only obtain a meaningful bound on the number of such 'backward' edges since a bound on *all* edges between expander components cannot be achieved as can be seen from any graph G that is acyclic (which implies that  $\mathcal{X}$  has to be a collection of singletons by Item 1 forcing all edges to be between components).

Directed expanders and expander decompositions have been introduced in [BGS20] in an attempt to derandomize algorithms to maintain strongly connected components and single-source shortest paths in directed graphs undergoing edge deletions. The latter problem is heavily motivated by the fact that the maximum flow problem can be reduced to the single-source shortest path problem in directed graphs undergoing edge deletions. While a fast algorithm for the maximum flow problem has been given in [CKL<sup>+</sup>22], this would yield an alternative, possibly simpler and more combinatorial approach. This is hinted at by the recent simple and combinatorial negative single-source shortest paths algorithm in [BNWN22] that heavily relies on low-diameter decompositions for directed graphs which are inspired by the generalization of expander decompositions (see also [BGWN20]); and exemplified by the work in [CK24] which presents a faster combinatorial algorithm for the bipartite matching problem, a special case of the maximum flow problem, that heavily builds on directed expander decompositions.<sup>2</sup>

But while expander decompositions for directed graphs have been explored in recent work [BGS20, HKGW23, CK24] and static and dynamic algorithms are known with *almost-optimal*<sup>3</sup> runtime and approximation guarantees, current techniques remain cumbersome and inaccessible.

#### 1.1 Our Contribution

In this article, we finally give a simple algorithm that generalizes the algorithm from [SW19] in a clean way and is thus very accessible even to a non-expert audience. Further, our algorithm is the first to obtain near-optimal runtimes for both static and dynamic expander decompositions in directed graphs. Our result is summarized in the theorem below.

**Theorem 1.2.** Given a parameter  $\phi \leq c/\log^2 m$  for a fixed constant c > 0, and a directed medge graph G undergoing a sequence of edge deletions, there is a randomized data structure that constructs and maintains a  $(O(\log^6 m), \Omega(\phi/\log^8 m))$ -expander decomposition  $(\mathcal{X}, E^r)$  of G. The initialization of the data structure takes time  $O(m \log^5(m)/\phi)$  and the amortized time to process each edge deletion is  $O(\log^7(m)/\phi^2)$ .

If the sequence of edge deletions is of length at most m/2, then our algorithm further has the property that it updates  $\mathcal{X}$  such that it is refining over time meaning that at any current time,  $\mathcal{X}$ is a refinement of its earlier versions (every expander component in  $\mathcal{X}$  is a subset of an expander component in any earlier expander decomposition). Our algorithms are deterministic, however, they rely on calling a fast randomized algorithm to find balanced sparse cuts or certify that no such cut exists (see [KRV09, Lou10]).

Our new techniques are much simpler and more accessible than previous work, besides also being much faster. We hope that by giving a simpler algorithm for directed expander decompositions, we can help to make this tool more accessible to other researchers in the field with the hope that this can further accelerate recent advances in dynamic and static graph algorithms.

#### 1.2 Our Techniques

**High-Level Strategy.** We obtain our result by following the high-level strategy of [SW19] for undirected graphs: we draw on existing literature (specifically [KRV09, Lou10]) for an algorithm that either outputs a balanced sparse cut which allows us to recurse on both sides; or outputs a witness that no such cut exists. This witness can be represented as an expander graph W that embeds into  $G \cup F$  with low congestion where F is a set of few *fake* edges. In the second case, we set up a flow problem to extract a large expander (the first algorithm only finds balanced sparse cuts, so many unbalanced sparse cuts might remain) which suffices to again recurse efficiently.

The (Dynamic) Flow Problem in [SW19]. To outline our algorithm, we first sketch the techniques of [SW19]. In [SW19], the following sequence of flow problems is formulated: initially,

 $<sup>^{2}</sup>$ For a more detailed discussion of expander decomposition techniques and applications both in directed and undirected graphs, we refer the interested reader to Appendix A.1.

<sup>&</sup>lt;sup>3</sup>In this article, we follow the convention to say that an algorithm runs in *almost-optimal* time if the algorithm is optimal up to a subpolynomial factor  $m^{o(1)}$  in the size of the input graph. We say that the algorithm is *near-optimal* if the runtime is optimal up to polylog(m), i.e. polylogarithmic factors in m.

we add  $8/\phi$  units of source mass to each endpoint of an edge in F and then ask to route the mass in G where each vertex v is a sink of value  $\deg_G(v)$  and each edge has capacity  $8/\phi$ . It then runs an (approximate) maximum flow algorithm on the flow problem. Whenever the algorithm detects that no feasible flow exists<sup>4</sup>, it finds a cut  $(A, \overline{A})$  where A is the smaller side of the cut and then asks the same problem in the network  $G[\overline{A}]$  where this time the source mass is assigned for each edge in  $E_G(A, \overline{A}) \cup (F \cap \overline{A})$ . The algorithm terminates once the flow problem can be solved and outputs the final induced graph.

In [SW19], it is shown that once a feasible flow exists then the (induced) graph is a  $\Omega(\phi)$ expander. Further, it shows that the amount of source mass decreases over the sequence of flow
problems proportional to the volume of the set A of vertices that are removed at each step. This
yields that the final induced graph is still large. Thus, the final graph outputted is a large expander,
as desired.

Finally, [SW19] shows that in the sequence of flow problems, each problem can be warm-started by re-using the flow computed in the previous instance to detect a cut induced on the remaining vertex set. This result is obtained by two main insights:

- 1. if the flow f to find the cut  $(A, \overline{A})$  is a *pre-flow*, that is a flow that respects capacities and has no negative excess at any vertex (i.e. it does not route away more flow from a vertex than is inputted by the source), then the induced flow  $f[\overline{A}]$  is a pre-flow in the flow problem formulated for  $G[\overline{A}]$ , and
- 2. the classic push-relabel framework can naturally be extended to warm-start on such a flow  $f[\bar{A}]$  as it is built to just further refine pre-flows at every step.

This dynamization of the push-relabel framework allows to bound the cost of computation of *all* flow problems linearly in the volume of the set of vertices that are removed from the graph.

The (Dynamic) Flow Problem in Directed Graphs. In directed graphs, while the above flow problem upon becoming feasible also certifies that the remaining graph is an  $\Omega(\phi)$ -expander, the argument that the sequence of flow problems terminates does not work: the asymmetry of cuts might force us for a small cut  $E_G(A, \bar{A})$  to induce on  $\bar{A}$  but have many edges in  $E_G(\bar{A}, A)$  each of which would add  $8/\phi$  source flow to the new flow problem.

To recover the argument that the sequence of flow problems terminates (with the remaining expander graph being large), both [BGS20, HKGW23] suggest to set-up the flow problems more carefully such that each cut  $(A, \overline{A})$  that is found in this sequence and induced upon is a *sparse* cut. Here, we only describe the less lossy flow problem formulation developed in [HKGW23]. To ensure that each cut  $(A, \overline{A})$  that is found is a sparse cut, [HKGW23] proposes a slightly different flow problem: instead of adding source mass  $8/\phi$  per endpoint of an edge that is fake or not fully contained in the induced graph, it tailors the amount of new source mass using the witness graph W, possibly injecting much less source mass in the process.

But while correctness and termination of the flow problem sequence are now ensured, this leaves a significant problem: the current flow  $\boldsymbol{f}$  that was used to find the cut  $(A, \bar{A})$  no longer has the property that  $\boldsymbol{f}[\bar{A}]$  is a *pre-flow* in the flow problem formulated on network  $G[\bar{A}]$  even if  $\boldsymbol{f}$  is a pre-flow. While capacity constraints are still enforced, i.e.  $\boldsymbol{f}[\bar{A}]$  still is a pseudo-flow, some vertices

<sup>&</sup>lt;sup>4</sup>Technically, the algorithm might already output cuts when some cut has capacity less than a constant times the amount of flow that is required to be routed through the cut.

might now have negative excess since the flow f might have routed up to  $8/\phi$  units of flow via an edge (u, v) in  $E_G(A, \bar{A})$  but in the flow problem on  $G[\bar{A}]$  for the same edge, less than  $8/\phi$  units of flow mass were added to v.

Thus, dynamizing the push-relabel framework does not appear natural for this sequence of problems as it crucially requires that the maintained flow is a pre-flow at all times. In [HKGW23], an involved batching technique is used instead (based on the technique in [NSWN17]) that does not use dynamic flow problems but instead reduces to few static flow problems, however, at the loss of quality and runtime by subpolynomial factors.

**The Push-Pull-Relabel Framework.** The main technical contribution of this paper is a new framework that refines pseudo-flows as efficiently as the push-relabel framework refines pre-flows. Thus, we give a generalization of the latter widely-used and well-studied framework that we believe might have applications well beyond our problem.

Recall that the classic push-relabel framework maintains labels  $\ell$  for all vertices and a pre-flow f. In each iteration, it 'pushes' positive excess flow at a vertex v to a vertex at a lower label (to be precise to a vertex at level  $\ell(v) - 1$ ); or if no 'push' is possible, it increases the labels of some vertices, it 'relabels'. Using a clever potential-based analysis, one can show that it suffices to only increase the labels to a certain threshold before all flow is settled (for the flow problems that we consider in this paper this threshold can be even lower as it suffices to settle 'most' of the source mass).

In our framework, we allow inducing on vertex sets, without compensating by adding source mass, which might create negative excess leaving f a pseudo-flow (instead of a pre-flow). Now, while our framework applies the same strategy for 'pushes' and 'relabels', we also need a new operation 'pull'. Intuitively, our algorithm tries to 'pull' back the source mass that now causes the negative excess (this unit of mass was 'pushed' to some other vertices as we require the source mass function to be non-negative). To do so, a vertex v with negative excess can 'pull' mass from vertices at a lower level (again it can only pull from a vertex at level  $\ell(v) - 1$ ). But it is not difficult to construct an example where this strategy does not suffice: therefore, we also need to sometimes decrease the label of a vertex to ensure correctness.

However, the latter change to the 'relabel' operation breaks the property that labels are monotonically increasing over time. A property that is crucial in the existing efficiency analysis. Instead, we give a much more careful, but still simple, argument to analyze the potentials that bound the number of push, pull, and relabeling operations that deal with the non-monotonicity of the levels over time.

Combining this framework with the above-discussed set-up of dynamic flow problems as proposed in [HKGW23] then yields the first near-optimal algorithm to compute an expander decomposition in a directed graph. Further, our technique extends seamlessly to also deal with edge deletions to G, yielding an algorithm to prune expander graphs that undergo edge deletions.

**Roadmap.** In the remainder of the article, we first give preliminaries in Section 2, then present our new push-pull-relabel framework in Section 3 and finally show how to obtain our result in Theorem 1.2 using the new framework in Section 4.

## 2 Preliminaries

**Graphs.** We let deg<sub>G</sub> denote the degree vector of graph G. For all vertex  $v \in V$ , we have deg<sub>G</sub>(v) equal to the number of edges incident to v (both incoming and outgoing are counted). We denote by  $vol_G(S)$  for any  $S \subseteq V$ , the sum of degrees of vertices in S. We denote by  $E_G(A, B)$  for any  $A, B \subseteq V$  the set of directed edges in E(G) with start in A and end in B. We define e(G) = |E(G)| and  $e_G(A, B) = |E_G(A, B)|$ . For any partition  $\mathcal{P}$  of V(G), we denote the graph obtained by contracting each partition class to a single vertex by  $G/\mathcal{P}$ . Two vertices in  $G/\mathcal{P}$  are adjacent if there is an edge between the corresponding partition classes in G.

**Flows.** We call a tuple  $(G, \boldsymbol{c}, \Delta, \nabla)$  a flow problem, if G is a directed graph, the capacity function  $\boldsymbol{c}: V(G) \times V(G) \to \mathbb{R}^+$  is such that for all  $(u, v) \notin E$  we have  $\boldsymbol{c}(u, v) = 0$ , and  $\Delta, \nabla: V(G) \to \mathbb{R}^+$  denote the source and the sink capacities. We denote flows on G as functions  $\boldsymbol{f}: V(G) \times V(G) \to \mathbb{R}$  such that  $\boldsymbol{f}$  is anti-symmetric, i.e.  $\boldsymbol{f}(u, v) = -\boldsymbol{f}(v, u)$ . Given a vertex  $v \in V(G)$  we introduce the notation  $\boldsymbol{f}(v) = \sum_u \boldsymbol{f}(v, u), \boldsymbol{f}^+(v) = \frac{1}{2} \sum_u (|\boldsymbol{f}(v, u)| + \boldsymbol{f}(v, u)), \boldsymbol{f}^-(v) = \frac{1}{2} \sum_u (|\boldsymbol{f}(u, v)| - \boldsymbol{f}(u, v))$ . Likewise, we define  $\boldsymbol{c}(v) = \sum_u \boldsymbol{c}(v, u) + \boldsymbol{c}(u, v), \boldsymbol{c}^+(v) = \sum_u \boldsymbol{c}(v, u), \boldsymbol{c}^-(v) = \sum_u \boldsymbol{c}(u, v)$ . Given a flow  $\boldsymbol{f}$ , we say a vertex  $v \in V(G)$  has positive excess if  $\Delta_{\boldsymbol{f}}^+(v) = \max(\Delta(v) - \boldsymbol{f}(v) - \nabla(v), 0) > 0$  and v has negative excess if  $\Delta_{\boldsymbol{f}}^-(v) = \max(\boldsymbol{f}(v) - \Delta(v), 0) > 0$ . For a subset  $\tilde{V} \subseteq V(G)$ , we induce the flow  $\boldsymbol{f}$ , and the sink  $\nabla$ , source  $\Delta$  and edge capacities  $\boldsymbol{c}$  onto  $G[\tilde{V}]$  in a function sense and write  $\boldsymbol{f}|_{\tilde{V}}, \nabla|_{\tilde{V}}, \Delta|_{\tilde{V}}, \boldsymbol{c}|_{\tilde{V}}$ . We say that a flow  $\boldsymbol{f}$  is a *pseudo-flow* if it satisfies the capacity constraints:

$$\forall (u,v) \in V(G) \times V(G) : -\boldsymbol{c}(v,u) \leq \boldsymbol{f}(u,v) \leq \boldsymbol{c}(u,v).$$

We say f is a *pre-flow* if f is a pseudo-flow and has no negative excess at any vertex. We say a flow f is *feasible* if it is a pre-flow and additionally no vertex has positive excess.

**Expanders.** Given graph G = (V, E), we say a cut  $(S, \overline{S})$  is  $\phi$ -out sparse if  $\operatorname{vol}_G(S) \leq e(G)$  and  $e_G(S, \overline{S}) < \phi \cdot \operatorname{vol}_G(S)$ , where  $e_G(S, \overline{S})$  denotes the number of edges with tail in S and head in  $\overline{S} = V \setminus S$ , and  $\operatorname{vol}_G(S)$  denotes the sum of degrees of all vertices in S. We say G is an  $\phi$ -out expander if it has no  $\phi$ -out-sparse cut. We say G is a  $\phi$ -expander if G and  $G^{rev}$ , the graph were all edges of G are reversed, are both  $\phi$ -out expander.

The next lemma that is folklore is crucial in our expander pruning argument.

**Lemma 2.1.** Given a  $\phi$ -expander G = (V, E), then take  $S \subseteq V$  and a set of edge deletions D. We have that  $e_{G \setminus D}(S, V \setminus S) < \frac{\phi}{4} \cdot \operatorname{vol}_G(S)$  implies  $\operatorname{vol}_G(S) < \frac{4 \cdot |D|}{3\phi}$ .

*Proof.* If 
$$\operatorname{vol}_G(S) \ge \frac{4 \cdot |D|}{3\phi}$$
, then  $e_{G \setminus D}(S, V \setminus S) \ge \phi \cdot \operatorname{vol}_G(S) - |D| \ge \frac{\phi}{4} \operatorname{vol}_G(S)$ .

**Graph Embeddings.** Given two graphs H and G over the same vertex set V, we say that  $\Pi$  is an embedding of H into G if for every edge  $e = (u, v) \in E(G)$ ,  $\Pi(e)$  is a simple uv-path in G. We define the congestion of an edge  $e \in E(G)$  induced by the embedding  $\Pi$  to be the maximum number of paths in the image of  $\Pi$  that contain e. We define the congestion of  $\Pi$  to be the maximum congestion achieved by any such edge  $e \in E(G)$ .

**Expander Decompositions with Witnesses.** For the rest of the article, we use a definition of expander decompositions that encodes much more structure than given in Definition 1.1. In particular, the definition below incorporates the use of witness graphs which are instrumental to our algorithm.

**Definition 2.2.** Given a graph G, we say  $(W, \Pi)$  is a  $\psi$ -(out-)witness for G if

- 1. W is a  $\psi$ -(out-)expander, and
- 2.  $\Pi$  embeds W into G with congestion at most  $\frac{\psi}{\phi}$ , and
- 3.  $\forall v \in V(W) : \deg_G(v) \le \deg_W(v) \le \frac{\deg_G(v)}{\psi}$ .

The next fact established that a  $\psi$ -(out-)witness for G in fact certifies that G is a  $\phi$ -(out-) expander, justifying the name witness.

**Fact 2.3** (see [HKGW23], Claim 2.1). If  $(W, \Pi)$  is a  $\psi$ -(out-)witness for G, then G is a  $\phi$ -(out-) expander.

**Definition 2.4** (Augmented Expander Decomposition). We call a collection  $\mathcal{X}$  together with a subset  $E^r \subseteq E$  a  $(\beta, \phi, \psi)$ -expander decomposition of a graph G, if

1.  $\forall (X, W, \Pi) \in \mathcal{X}, G[X] \text{ is a } \phi\text{-expander with } \psi\text{-witness } (W, \Pi).$ 

2. 
$$|E^r| \leq \beta \cdot \phi \cdot e(G)$$

3.  $(G \setminus E^r) / \mathcal{P}$  is a DAG, where  $\mathcal{P} = \{X \mid (X, W, \Pi) \in \mathcal{X}\}.$ 

Given two expander decompositions  $(\mathcal{X}_1, E_1^r)$  of the graph G and  $(\mathcal{X}_2, E_2^r)$  of the graph  $G \setminus \mathcal{D}$ , where  $\mathcal{D} \subseteq E(G)$ , we say  $(\mathcal{X}_2, E_2^r)$  refines  $(\mathcal{X}_1, E_1^r)$  if 1) for all partition classes  $X_2$ , where  $(X_2, W_2, \Pi_2) \in \mathcal{X}_2$ , there is a class  $X_1$ , where  $(X_1, W_1, \Pi_1) \in \mathcal{X}_1$ , such that  $X_2 \subseteq X_1$  and 2)  $E_1^r \subseteq E_2^r \cup \mathcal{D}$ .

# 3 The Push-Pull-Relabel Framework

In the push-relabel framework as presented in [GT88], we are trying to compute a feasible flow for a flow problem  $(G, \mathbf{c}, \Delta, \nabla)$  by maintaining a pre-flow  $\mathbf{f}$  together with a level function  $\ell$ . The algorithm then runs in iterations terminating once  $\mathbf{f}$  has no positive excess at any vertex anymore. In each iteration of the algorithm, the algorithm identifies a vertex v that still has positive excess at a vertex v. This positive excess is then pushed to neighbors on lower levels such that the capacity constraint is still enforced. If this is not possible v is relabeled meaning that its label  $\ell(v)$  is increased.

In this section, we are extending the push-relabel framework to the dynamic setting, where we allow for increasing the source function  $\Delta$  and inducing on subgraphs of G. To do so, we need to introduce the notion of negative excess. Because for a flow  $\mathbf{f}$  of the flow problem, it might happen that when inducing the flow  $\mathbf{f}|_{G[\tilde{V}]}$  to a subgraph  $G[\tilde{V}]$  there is a vertex  $v \in \tilde{V}$  such that more flow is leaving the vertex than is entering or sourced, i.e.  $\Delta_{\mathbf{f}|_{G[\tilde{V}]}}^- = \mathbf{f}|_{G[\tilde{V}]}^+(v) - \mathbf{f}|_{G[\tilde{V}]}^-(v) - \Delta(v) > 0$ . We say that such a vertex has negative excess. Hence, we need to extend the discussion to include negative excess in the dynamic version. Similar to the standard push-relabel algorithm, we maintain a pseudo-flow  $\mathbf{f}$  and a vertex labelling  $\boldsymbol{\ell}$  in so-called valid states  $(\mathbf{f}, \boldsymbol{\ell})$ . The only difference is that in the standard push-relabel algorithm the pseudo-flow  $\mathbf{f}$  is in fact a pre-flow.

**Definition 3.1.** Given a level function  $\boldsymbol{\ell}: V(G) \to [h]$  and a pseudo-flow  $\boldsymbol{f}$ , we call a tuple  $(\boldsymbol{f}, \boldsymbol{\ell})$ a state for  $(G, \boldsymbol{c}, \Delta, \nabla)$  if for all edges e = (u, v) having  $(\boldsymbol{\ell}(u) > \boldsymbol{\ell}(v) + 1)$  implies  $\boldsymbol{f}(e) = \boldsymbol{c}(e)$ . We call the state  $(\boldsymbol{f}, \boldsymbol{\ell})$  valid if for all vertices  $v \in V(G)$  1)  $0 < \Delta_{\boldsymbol{f}}^{-}(v)$  implies  $\boldsymbol{\ell}(v) = 0$ , 2)  $0 < \Delta_{\boldsymbol{f}}^{+}(v)$  implies  $\boldsymbol{\ell}(v) = h$ .

For the remainder of the paper, we fix  $h = O\left(\frac{\log(n)}{\phi}\right)$ . To provide the reader with some intuition about the definitions, we remark that the pseudo-flow of a valid state is not feasible in the usual sense. Indeed, some vertices might still have positive or negative excess. But these vertices are guaranteed to either be at level h or at level 0. Moreover, we point out that if a valid state  $(f, \ell)$ has no vertices at level h, then f might still not be a feasible flow since there might be vertices with negative excess. But it is straightforward to obtain from f a feasible flow: extract from f at each vertex v exactly  $\Delta(v)$  unit flow paths (possibly self loops).

**Lemma 3.2.** Given any flow problem  $(G = (V, E), \mathbf{c}, \Delta, \nabla)$ , where  $\nabla \geq \deg$ . Then, there is a deterministic data structure VALIDSTATE $(G, \mathbf{c}, \Delta, \nabla)$  (see Algorithm 1) that initially computes a valid state  $(\mathbf{f}, \boldsymbol{\ell})$  and after every update of the form

- INCREASESOURCE( $\delta$ ) : where  $\delta \in \mathbb{N}_{>0}^n$ , we set  $\Delta$  to  $\Delta + \delta$ ,
- REMOVEVERTICES(S): where  $S \subseteq \tilde{V}$ , sets  $\tilde{V}$  to  $\tilde{V} \setminus S$  (initially  $\tilde{V} = V$ ).

the algorithm explicitly updates the tuple  $(\mathbf{f}, \boldsymbol{\ell})$  such that thereafter  $(\mathbf{f}, \boldsymbol{\ell})$  is a valid state for the current flow instance  $(G[\tilde{V}], \mathbf{c}|_{\tilde{V}}, \Delta|_{\tilde{V}}, \nabla|_{\tilde{V}})$ .

The algorithm runs in total time  $O\left(h \cdot \left(\|\Delta\|_1 + \sum_t \min\left(\mathbf{c}(\tilde{V}_{t+1}, S_t), \mathbf{c}(S_t, \tilde{V}_{t+1})\right) + \nabla(S_t)\right)\right)$ , where  $\Delta$  denotes the final versions of the variable, and  $\tilde{V}_t$  and  $S_t$  denote the sets  $\tilde{V}$  and S after the t-th update to the data structure.

*Proof.* Since we keep on performing push, pull or relabel operations as long as there is a vertex v with  $\Delta^+(v) > 0, \ell(v) < h$  or  $\Delta^-(v) > 0, \ell(v) > 0$ , it is guaranteed that the algorithm computes a valid state eventually. It thus suffices to bound the run-time.

Note that by maintaining at each vertex  $v \in V$ , a linked-list L[v] containing all non-saturated edges (v, u) where  $\ell(v) = \ell(u) + 1$ , we can implement a push in time O(1). We can maintain such a linked-list for every vertex by spending time  $O(\deg(v))$  every time we relabel a vertex v plus O(1)time for each push. We maintain a corresponding list L'[v] for all pull operations. It thus suffices to bound the contribution of the push, pull, and relabel operations to the run-time. Let us index by t the push, pull, relabel operations as well as the calls to INCREASESOURCE, REMOVEVERTICES in the order they occur.

Let us introduce functions  $\mathbf{p}_t$ ,  $\mathbf{n}_t$  that correspond to the total amount of positive/ negative units in the network that can be settled. These functions will satisfy  $\forall v \in V, \Delta^+(v) = \max(\mathbf{p}_t - \mathbf{n}_t, 0), \Delta^-(v) = \max(\mathbf{n}_t - \mathbf{p}_t - \nabla(v), 0)$ . Initially, we have  $\mathbf{p}_0 = \Delta$ ,  $\mathbf{n}_0 = \nabla$ , where  $\Delta$  denotes the variable at initialization of the data structure. We describe how  $\mathbf{p}_t$ ,  $\mathbf{n}_t$  evolve over time. If the t-th action is

- 1. a push of  $\psi$  units from u to v, then  $\mathbf{p}_{t+1}(u) = \mathbf{p}_t(u) \psi, \mathbf{p}_{t+1}(v) = \mathbf{p}_t(v) + \psi$
- 2. a pull of  $\psi$  units from u to v, then  $\mathbf{n}_{t+1}(u) = \mathbf{n}_t(u) + \psi$ ,  $\mathbf{n}_{t+1}(v) = \mathbf{n}_t(v) \psi$

- 3. INCREASESOURCE( $\delta$ ), then  $\mathbf{p}_{t+1} = \mathbf{p}_t + \delta$
- 4. REMOVEVERTICES(S), then

$$\forall v \in V_{t+1} : \mathbf{p}_{t+1}(v) = \mathbf{p}_t(v) + \mathbf{f}(v, S), \mathbf{n}_{t+1}(v) = \mathbf{n}_t(v) + \mathbf{f}(S, v)$$
  
$$\forall v \in V \setminus \tilde{V}_{t+1} : \mathbf{p}_{t+1}(v) = \mathbf{p}_t(v), \mathbf{n}_{t+1}(v) = \mathbf{n}_t(v)$$

Clearly  $\|\mathbf{p}_t\|_1$  and  $\|\mathbf{n}_t\|_1$  are non-decreasing, we denote the final values by p, n. We remark that  $\sum_v \min(\mathbf{p}_t(v), \mathbf{n}_t(v))$  is the amount that is settled at time t. Since we are always only moving excess positive or negative units the function  $\min(\mathbf{p}_t(v), \mathbf{n}_t(v))$  is non-decreasing for all v. We point out that in fact we only push away negative units when  $n_t(v) > p_t(v) + \nabla$ , the function  $\min(p_t(v) + \nabla(v), n_t(v))$  is thus as well non-decreasing.

# Claim 3.3. We can bound the size of p, n by $O\left(\|\Delta\|_1 + \sum_t \min(\boldsymbol{c}(\tilde{V}_{t+1}, S_t), \boldsymbol{c}(S_t, \tilde{V}_{t+1})) + \nabla(S_t)\right)$ .

Proof. Let t be an index such that  $\|\mathbf{p}_{t+1}\|_1 - \|\mathbf{p}_t\|_1 > 0$ . Then, at index t we either make a call to INCREASESOURCE or to REMOVEVERTICES. Since  $\Delta$  is point-wise non-decreasing, we can bound the contribution to  $\mathbf{p}_t$  of the calls to INCREASESOURCE by  $O(\|\Delta\|_1)$ . To bound the contribution of the calls to REMOVEVERTICES, we remark that if at index t there was a call to REMOVEVERTICES we must have for all  $v \in \tilde{V}_{t+1}, \mathbf{p}_{t+1}(v) - \mathbf{p}_t(v) = \mathbf{f}(v, S_t)$ , where  $S_t$  are the vertices removed at index t. Summing over all vertices in V, we obtain  $\|\mathbf{p}_{t+1}\|_1 - \|\mathbf{p}_t\|_1 = \mathbf{f}(\tilde{V}_{t+1}, S_t) \leq \mathbf{c}(\tilde{V}_{t+1}, S_t)$ . We remark that all the flow  $\mathbf{f}(\tilde{V}_{t+1}, S_t)$  pushed into  $S_t$  either is stuck in  $S_t$  or flows out again. Since the algorithm ensures that the positive excess at a vertex u does at no time exceed  $\deg(u) \leq \nabla(u)$ , we can bound the total amount of flow that is stuck in  $S_t$  by  $2 \cdot \nabla(V)$ . Hence, we have  $\mathbf{f}(\tilde{V}_{t+1}, S_t) \leq \mathbf{c}(S_t, \tilde{V}_i) + 2 \cdot \nabla(S_i)$ . Summing over all indices at which we call REMOVEVERTICES yields the bound  $O\left(\sum_t \min(\mathbf{c}(\tilde{V}_{t+1}, S_t), \mathbf{c}(S_t, \tilde{V}_t) + \nabla(S_t))\right)$  on the contribution of these calls. This establishes the bound on p, the bound on n is similar.

Claim 3.4. The contribution to the run-time of the relabeling operations is bounded by

$$O\left(\sum_{v \in V} \deg(v) \sum_{0 \le t} |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)|\right) \le O(h \cdot n).$$

Proof. Clearly, we can bound the contribution by  $O\left(\sum_{v \in V} \deg(v) \sum_{0 \leq t} |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)|\right)$ . It thus suffices to bound this expression. We treat each  $v \in V(G)$  individually. Pick a minimal partition  $0 = s_1 < t_1 < s_2 < \ldots$  (either ending in  $s_l$  or  $t_l$ ) such that 1)  $\forall s_i \leq t \leq t_i : \boldsymbol{\ell}_{t+1}(v) \geq \boldsymbol{\ell}_t(v)$ , 2)  $\forall t_i \leq t \leq s_{i+1} : \boldsymbol{\ell}_{t+1}(v) \leq \boldsymbol{\ell}_t(v)$ . Since the partition is minimal, we are guaranteed that  $\boldsymbol{\ell}_{s_i}(v) < \boldsymbol{\ell}_{t_i}(v)$  and  $\boldsymbol{\ell}_{t_i}(v) > \boldsymbol{\ell}_{s_{i+1}}(v)$ . This implies that  $\mathbf{n}_t(v) \leq \mathbf{p}_t(v)$  at some index t between  $s_i$  and  $t_i$ , and  $\mathbf{p}_t(v) + \nabla(v) \leq \mathbf{n}_t(v)$  at some index t between  $t_i$  and  $s_{i+1}$ . These two facts in turn imply, since the function  $\min(\mathbf{p}_t(v) + \nabla(v), \mathbf{n}_t(v))$  is non-decreasing, that  $\mathbf{n}_{s_j}(v) \geq \nabla(v) \cdot j$ . Moreover, we note that

$$\deg(v) \cdot \sum_{t < s_{j+1}} |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)| \le \sum_{i \le j} \nabla(v) \cdot 2h \le 2h \cdot \mathbf{n}_{s_j}(v),$$

where the 2h is due to the fact that  $\ell_k(v)$  is non-decreasing between  $s_i, t_i$  and non-increasing between  $t_i, s_{i+1}$ . Increasing j and summing over v concludes the argument.

**Claim 3.5.** The contribution to the run-time of the push operations and the pull operations is bounded by  $O(h \cdot (p+n))$ .

Proof. Let us introduce the function  $\Phi(t) = \sum_{v \in V} \Delta_t^+(v) \cdot \ell_t(v)$ . We remark that any push operation of  $\psi$  units from u to v decreases  $\Delta_t^+(u)$  by  $\psi$  and increases  $\Delta_t^+(v)$  by at most  $\psi$  while preserving all other  $\Delta_t^+$  entries. Hence, any such push operation decreases the function  $\Phi$ . This allows us to bound the run-time contribution of the push operations by  $\sum_{0 \leq t} \max(\Phi(t) - \Phi(t+1), 0)$ . Since  $\Phi(t) \geq 0$  for all t, it suffices to bound the increases to  $\Phi$ 

$$\sum_{0 \le t} \max(\Phi(t+1) - \Phi(t), 0) \le \sum_{0 \le t} \max(\|\Delta_{t+1}^+\|_1 - \|\Delta_t^+\|_1, 0) \cdot \boldsymbol{\ell}_t(v) + \sum_v \Delta_{t+1}^+(v) \cdot |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)|$$

$$\le h \cdot p + \sum_v \sum_{0 \le t} \Delta_{t+1}^+(v) \cdot |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)|$$

$$\le O(h \cdot (p+n)) + \sum_v \sum_{0 \le t} (\Delta_{t+1}^+(v) - \deg(v)) \cdot |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)|$$
(1)

where the first inequality is due to the fact that any operation either preserves  $\Delta^+$  or  $\ell$ . In the second inequality, we used that  $\ell_t(v) \leq h, \max(\|\Delta_{t+1}^+\|_1 - \|\Delta_t^+\|_1, 0) = \max(\|\mathbf{p}_{t+1}\|_1 - \|\mathbf{p}_t\|_1, 0)$  and the definition of p. In the third, we used Claim 3.4. To bound the remaining term, we treat each vertex v individually. Pick a minimal partition  $s_1 < t_1 < s_2 < t_2 < \ldots$  (either ending in  $s_l$  or  $t_l$ ) such that 1)  $\forall s_i < t \leq t_i$ : we have  $\Delta_t^+(v) - \deg(v) > 0, 2) \ \forall t_i < t \leq s_{i+1}$ : we have  $\Delta_t^+(v) - \deg(v) > 0, 2) \ \forall t_i < t \leq s_{i+1}$ : we have  $\Delta_t^+(v) - \deg(v) > 0, 2) \ \forall t_i < t \leq s_{i+1}$ .

$$\sum_{0 \le t} \left( \Delta_{t+1}^+(v) - \deg(v) \right) \cdot |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)| \le \sum_i \sum_{s_i \le t \le t_i} \left( \Delta_{t+1}^+(v) - \deg(v) \right) \cdot |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)|.$$

Since the level  $\ell(v)$  can only increase on any segment  $s_i < t < t_i$ , we have

$$\sum_{s_i \leq t \leq t_i} \left( \Delta_{t+1}^+(v) - \deg(v) \right) \cdot |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)| \leq h \cdot \left( \max\{\Delta_t^+(v) \mid s_i < t \leq t_i\} - \deg(v) \right) \\ \leq h \cdot \sum_{s_i \leq t \leq t_i} \max\left( \Delta_{t+1}^+(v) - \Delta_t^+(v), 0 \right) + h \cdot \left( \Delta_{s_i}^+(v) - \deg(v) \right) \\ \leq h \cdot \sum_{s_i \leq t \leq t_i} \max\left( \mathbf{p}_{t+1}(v) - \mathbf{p}_t(v), 0 \right),$$

where we used in the last inequality that  $\Delta_{s_i}^+ = \deg(v)$  and that any increase in  $\Delta_t(v)$  is due to an increase in  $\mathbf{p}_t(v)$ . Since  $\forall s_i < t \leq t_i$  we have  $\Delta_t^+(v) - \deg(v) > 0$ , the *t*-th action cannot be a push towards v. Hence, all actions contributing to the sum  $\sum_{s_i \leq t \leq t_i} \max(\mathbf{p}_{t+1}(v) - \mathbf{p}_t(v), 0)$  must be function calls. We denote the set of indices t, where the *t*-th action is a function call, by T. The bound simplifies to  $\sum_{0 \leq t} (\Delta_{t+1}^+(v) - \deg(v)) \cdot |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)| \leq h \cdot \sum_{t \in T} \mathbf{p}_{t+1}(v) - \mathbf{p}_t(v)$ . Summing overall v, we get  $\sum_{v} \sum_{0 \leq t} (\Delta_{t+1}^+(v) - \deg(v)) \cdot |\boldsymbol{\ell}_{t+1}(v) - \boldsymbol{\ell}_t(v)| \leq h \cdot \sum_{t \geq 0} \|\mathbf{p}_{t+1}\|_1 - \|\mathbf{p}_t\|_1 \leq h \cdot p$ . This yields the bound on the run-time contribution of the push operations. In the case of pull operations, we use the function  $\Phi(t) = \sum_{v \in V} \Delta_t^-(v) \cdot (h - \boldsymbol{\ell}_t(v))$ . The argument is the same as above.

Algorithm 1 VALIDSTATE $(G, c, \Delta, \nabla, h)$ 

def Init  $\tilde{V} \leftarrow V(G), (\boldsymbol{c}, \Delta, \nabla) \leftarrow (\boldsymbol{c}, \Delta, \nabla), (\boldsymbol{f}, \boldsymbol{\ell}) \leftarrow (\boldsymbol{0}, \boldsymbol{0})$ PUSHRELABEL def INCREASESOURCE( $\delta$ )  $\Delta \leftarrow \Delta + \delta$ PUSHRELABEL def REMOVEVERTICES(S) $\tilde{V} \leftarrow \tilde{V} \setminus S, (\boldsymbol{c}, \Delta, \nabla) \leftarrow (\boldsymbol{c}|_{\tilde{V}}, \Delta|_{\tilde{V}}, \nabla|_{\tilde{V}}), (\boldsymbol{f}, \boldsymbol{\ell}) \leftarrow (\boldsymbol{f}|_{\tilde{V}}, \boldsymbol{\ell}|_{\tilde{V}})$ PullRelabel PUSHRELABEL def PUSHRELABEL while  $\exists v$  where  $\ell(v) < h$  and  $\Delta^+(v) > 0$  do Let v be a vertex minimizing  $\ell(v)$ . if  $\exists (v, u)$  such that  $c_f(v, u) > 0, \ell(v) = \ell(u) + 1$  then  $\psi = \min\left(\Delta_f^+(v), c_f(v, u), \max(\deg(u) - \Delta_f^+(u), 0)\right)$  $\boldsymbol{f}(v, u) \leftarrow \boldsymbol{f}(v, u) + \psi, \boldsymbol{f}(u, v) \leftarrow -\boldsymbol{f}(v, u) // \text{ Sends } \psi \text{ units of pos. excess from } v \text{ to } u$ else  $\boldsymbol{\ell}(v) \leftarrow \boldsymbol{\ell}(v) + 1$ end if end while def PullRelabel while  $\exists v$  where  $\ell(v) > 0$  and  $\Delta^{-}(v) > 0$  do Let v be a vertex maximizing  $\ell(v)$ if  $\exists (u, v)$  such that  $c_f(u, v) > 0, \ell(u) = \ell(v) + 1$  then 
$$\begin{split} \psi &= \min\left(\Delta_f^-(v), \boldsymbol{c}_f(u, v), \deg(u)\right) \\ \boldsymbol{f}(v, u) \leftarrow \boldsymbol{f}(v, u) + \psi, \boldsymbol{f}(u, v) \leftarrow -\boldsymbol{f}(v, u) \; // \; \text{Sends} \; \psi \; \text{units of neg. excess from } v \; \text{to} \; u \end{split}$$
else  $\ell(v) \leftarrow \ell(v) - 1$ end if end while

# 4 Directed Expander Decompositions via the Push-Pull-Relabel Framework

In this section, we present a full proof of our main technical result that states that if G is initially a  $\phi$ -expander, then an expander decomposition can be maintained efficiently. The algorithm behind this theorem heavily relies on the new push-pull-relabel algorithm presented in the previous section.

**Theorem 4.1.** Given a  $\phi$ -expander G = (V, E) with  $\psi$ -witness  $(W, \Pi)$ , there is a deterministic data structure BIDIRECTEDEXPANDERPRUNING $(G, W, \Pi)$  (see Algorithm 2). After every update of the form

• REMOVEEDGES(D): where  $D \subseteq E$ , sets  $\mathcal{D}$  to  $\mathcal{D} \cup D$  (initially  $\mathcal{D} = \emptyset$ ),

provided  $\frac{4}{\psi} \cdot |\Pi^{-1}(\mathcal{D})| < \frac{e(G)}{14}$ , the algorithm explicitly updates  $\tilde{V} \subseteq V$  and the tuple  $(E^r, \mathcal{X})$ , where  $E^r \subseteq E(G)$  and  $\mathcal{P}$  is a partition of V (initially  $E^r, \mathcal{P} = \emptyset$ ), such that thereafter

- 1. the graph  $\tilde{G} = (G \setminus D) \left[ \tilde{V} \right]$  is a  $\frac{\phi \cdot \psi^4}{400}$ -expander with a  $\frac{\psi^2}{20}$ -witness  $(\tilde{W}, \Pi)$ ,
- 2.  $|E^r| \leq \frac{\phi}{4} \cdot \sum_{P \in \mathcal{P}} \operatorname{vol}_G(P)$
- 3.  $\sum_{P \in \mathcal{P}} \operatorname{vol}_W(P) \le 4 \cdot |\Pi^{-1}(\mathcal{D})|$
- 4.  $(G \setminus (\mathcal{D} \cup E^r))/(\mathcal{P} \cup \{\tilde{V}\})$  is a directed acyclic graph (DAG).

The algorithm runs in total time  $O\left(\frac{h}{\psi^2} \cdot |\Pi^{-1}(\mathcal{D})|\right)$ , where  $\mathcal{D}$  denotes the variable at the end of all updates.

Following the high-level approach of [SW19], we obtain our main result Theorem 1.2 for the special case where G is static by running a generalization of the cut-matching game to directed graphs [KRV09, Lou10] and then apply Theorem 4.1 to handle unbalanced cuts. Combining this result again with Theorem 4.1, we obtain our main result Theorem 1.2 in full generality. Both of these reductions have been known from previous work [BGS20, HKGW23]. Due to space constraints, we defer the former reduction to Appendix A.2 and the latter to Appendix A.3.

#### 4.1 Reduction to Out-Expanders

In this subsection, we show that the task of maintaining an expander decomposition as described in Theorem 4.1 can be reduced to a simpler problem that only requires maintaining out-expanders (however under edge and vertex deletions). In particular, we reduce to the following statement whose proof is deferred to Section 4.2.

**Lemma 4.2.** For every  $\phi$ -out-expander G = (V, E) with  $\psi$ -out-witness  $(W, \Pi)$ , there is a deterministic data structure DIRECTEDEXPANDERPRUNING $(G, W, \Pi)$  (see Algorithm 3). After every update of the form

- REMOVEVERTICES(S): where  $S \subseteq \tilde{V}$ , sets  $\tilde{V}$  to  $\tilde{V} \setminus S$  and S to  $S \cup S$  (initially  $\tilde{V} = V, S = \emptyset$ ),
- REMOVEEDGES(D): where  $D \subseteq E(\tilde{V}) \setminus \mathcal{D}$ , sets  $\mathcal{D}$  to  $\mathcal{D} \cup D$  (initially  $\mathcal{D} = \emptyset$ ),

provided  $\frac{4}{\psi} \cdot |\Pi^{-1}(\mathcal{D})| < \frac{e(G)}{14}$ , the algorithm explicitly updates  $\tilde{V} \subseteq V$  and the tuple  $(E^r, \mathcal{X})$ , where  $E^r \subseteq E$  and  $\mathcal{P}$  is a partition of  $V \setminus \left(\mathcal{S} \cup \tilde{V}\right)$  (initially  $E^r = \emptyset, \mathcal{P} = \emptyset$ ), such that thereafter

- 1. the graph  $(G \setminus D) \left[ \tilde{V} \right]$  is a  $\frac{\phi \cdot \psi^4}{400}$ -expander with a  $\frac{\psi^2}{20}$ -witness  $(\tilde{W}, \tilde{\Pi})$ ,
- 2.  $|E^r| \leq \frac{\phi}{4} \cdot \sum_{P \in \mathcal{P}} \operatorname{vol}_G(P),$

- 3.  $\sum_{P \in \mathcal{P}} \operatorname{vol}_W(X) \leq \frac{4}{3} \cdot \left| \Pi^{-1}(E_{G \setminus \mathcal{D}}(V \setminus \mathcal{S}, \mathcal{S}) \cup \mathcal{D}) \right|,$
- 4.  $(G \setminus (\mathcal{D} \cup E^r)[V \setminus \mathcal{S}]) / (\mathcal{P} \cup \{\tilde{V}\})$  is a DAG.

The algorithm runs in total time  $O\left(h \cdot \left(\frac{|\Pi^{-1}(\mathcal{D})|}{\psi^2} + \sum_t \boldsymbol{c}(\tilde{V}_{t+1}, S_t) + \nabla(S_t)\right)\right)$ , where  $S_t$  denotes the input set S at the t-th external call to REMOVEVERTICES(·) and  $\tilde{V}_t$  the set  $\tilde{V}$  at the same time.

Without further ado, we present Section 4.1 which implements this reduction.

#### Algorithm 2 BIDIRECTEDEXPANDER PRUNING $(G, W, \Pi)$

def INIT  $(\tilde{V}_1, \mathcal{P}_1, E_1^r) \leftarrow \text{DIRECTEDEXPANDERPRUNING}(G, W_1, \Pi_1)$   $(\tilde{V}_2, \mathcal{P}_2, E_2^r) \leftarrow \text{DIRECTEDEXPANDERPRUNING}(G, W_2, \Pi_2)$   $\tilde{V} \leftarrow \tilde{V}_1 \cap \tilde{V}_2, \mathcal{P} \leftarrow \mathcal{P}_1 \cup \mathcal{P}_2, E^r \leftarrow E_1^r \cup E_2^r // \text{ dynamically updated}$ def REMOVEEDGES(D)

 $(\tilde{V}_1, \mathcal{P}_1, E_1^r)$ .REMOVEEDGES(D) $(\tilde{V}_2, \mathcal{P}_2, E_2^r)$ .REMOVEEDGES(D)ADJUSTPARTITION

```
def AdjustPartition

while \tilde{V}_1 \neq \tilde{V}_2 do

(\tilde{V}_1, \mathcal{P}_1, E_1^r).REMOVEVERTICES(\tilde{V}_1 \setminus \tilde{V}_2)

(\tilde{V}_2, \mathcal{P}_2, E_2^r).REMOVEVERTICES(\tilde{V}_2 \setminus \tilde{V}_1)

end while
```

*Proof.* Item 1, 2, and 4 are direct consequences of Lemma 4.2. For item 3, we remark that item 3 of Lemma 4.2 implies that

$$\sum_{P \in \mathcal{P}} \operatorname{vol}_{W}(P) = \sum_{P \in \mathcal{P}_{1}} \operatorname{vol}_{W}(P) + \sum_{P \in \mathcal{P}_{2}} \operatorname{vol}_{W}(P) \le \frac{4}{3} \cdot |\Pi^{-1}(E_{2}^{r} \cup \mathcal{D})| + \frac{4}{3} \cdot |\Pi^{-1}(E_{1}^{r} \cup \mathcal{D})|$$
(2)

$$\leq \frac{4}{3} \cdot \left( |\Pi^{-1}(E^r)| + 2 \cdot |\Pi^{-1}(\mathcal{D})| \right).$$
(3)

It thus suffices to bound  $|E^r|$ . In a similar spirit, we can as well find an upper-bound on the run-time in terms of  $|E^r|$  and  $|\mathcal{D}|$ . Using the run-time bound of Lemma 4.2, we readily obtain the run-time bound for BIDIRECTEDEXPANDERDECOMPOSITION

$$O\left(h \cdot \left(\frac{|\Pi^{-1}(\mathcal{D})|}{\psi^2} + \sum_{P \in \mathcal{P}_1} \boldsymbol{c}(P, \tilde{V}_P) + \nabla(P) + \sum_{P \in \mathcal{P}_2} \boldsymbol{c}(\tilde{V}_P, P) + \nabla(P)\right)\right).$$

By item 2 and item 3 of Lemma 4.2, the bound simplifies as well to  $O\left(\frac{h}{\psi^2} \cdot \left(|\Pi^{-1}(\mathcal{D})| + |\Pi^{-1}(E^r)|\right)\right)$ , where  $\tilde{V}_P$  is the variable  $\tilde{V}$  right after the removal of P. We turn to bounding  $|E^r|$ . Combining item 2 and item 3 of Lemma 4.2, one obtains  $|E_1^r| \leq \frac{\phi}{3} \cdot \left(|\Pi^{-1}(E_2^r)| + |\Pi^{-1}(\mathcal{D})|\right)$ . By symmetry, we also have that  $|E_2^r| \leq \frac{\phi}{3} \cdot (|\Pi^{-1}(E_1^r)| + |\Pi^{-1}(\mathcal{D})|)$ . Combining the two bounds yields

$$\frac{\phi}{\psi} \cdot |\Pi^{-1}(E^r)| \le |E^r| = |E_1^r| + |E_2^r| \le \frac{\phi}{3} \cdot \left(|\Pi^{-1}(E^r)| + 2 \cdot |\Pi^{-1}(\mathcal{D})|\right)$$

We may thus bound  $|\Pi^{-1}(E^r)| \leq |\Pi^{-1}(\mathcal{D})|$ , which concludes the argument.

## 4.2 Maintaining Out-Expanders

It remains to prove Lemma 4.2. Algorithm 3 gives an implementation.

```
\mathcal{D} \leftarrow \mathcal{D} \cup D
(f, \ell).INCREASESOURCE(\frac{4}{\psi} \deg_{\Pi^{-1}(D)})
ADJUSTPARTITION()
```

```
def RemoveVertices(S)
```

```
\begin{split} \tilde{V} &\leftarrow \tilde{V} \setminus S \\ (\boldsymbol{f}, \boldsymbol{\ell}). \text{REMOVEVERTICES}(S) \\ (\boldsymbol{f}, \boldsymbol{\ell}). \text{INCREASESOURCE}(\frac{4}{\psi} \deg_{\Pi^{-1}(E_{G \setminus \mathcal{D}}(\tilde{V}, S))}) \\ \text{AdjustPartition}() \end{split}
```

```
def ADJUSTPARTITION()

while \exists v \in \tilde{V} with \ell(v) = h do

S \leftarrow \text{PRUNEORCERTIFY}(G \setminus \mathcal{D}, \ell)

\mathcal{P} \leftarrow \mathcal{P} \cup \{S\}

E^r \leftarrow E^r \cup E_{G \setminus \mathcal{D}}(S, \tilde{V})

REMOVEVERTICES(S)
```

```
end while
```

```
def PRUNEORCERTIFY(G, \ell)

S \leftarrow \emptyset, i \leftarrow h

repeat

S \leftarrow S \cup \left\{ v \in \tilde{V} \mid \ell(v) = i \right\}

i \leftarrow i - 1

until \operatorname{vol}_G \left( \{ v \in \tilde{V} \mid \ell(v) \le i \} \right) < (1 + \phi) \cdot \operatorname{vol}_G(S)

return the cut S
```

*Proof of Lemma 4.2.* We remark that item 4 follows immediately from line 20 in ADJUSTPARTITION. To establish item 1, it suffices to prove the next claim.

Claim 4.3. After every call to ADJUSTPARTITION,  $(G \setminus D)[\tilde{V}]$  is a  $\frac{\phi\psi^4}{400}$ -out-expander with an  $\frac{\psi^2}{20}$ -out-witness  $\tilde{W}$ .

*Proof.* We will construct a new  $\frac{\psi^2}{20}$ -witness  $\tilde{W}$  for the graph  $(G \setminus \mathcal{D})[\tilde{V}]$  with an embedding  $\tilde{\Pi}$  of congestion  $\frac{20}{\phi\psi^2}$  and such that  $\forall v \in \tilde{V} : \deg_G(v) \leq \deg_{\tilde{W}}(v) \leq \frac{20 \cdot \deg_G(v)}{\psi^2}$ . This implies that  $(G \setminus \mathcal{D})[\tilde{V}]$  is a  $\frac{\phi\psi^4}{400}$ -expander. In order to construct  $(\tilde{W}, \tilde{\Pi})$  we first pick a path-decomposition of  $\boldsymbol{f}$  such that at every vertex exactly  $\max(0, \boldsymbol{f}^+(v) - \boldsymbol{f}^-(v))$  paths begin and at most  $\max(0, \boldsymbol{f}^-(v) - \boldsymbol{f}^+(v))$  end.

We initialize  $\tilde{W}$  as  $W_0 := (W \setminus \Pi^{-1}(\mathcal{D}))[\tilde{V}]$ . For any vertex  $v \in \tilde{V}$ , we pick  $\min(\max(0, f^+(v) - f^-(v)), \Delta(v))$  paths starting with v. For any such path  $p_{v,w}$  starting in v and ending in w, we add the edge e = (v, w) to  $\tilde{W}$  and embed this edge through  $\tilde{\Pi}(e) = p_{v,w}$ . If  $\max(0, f^+(v) - f^-(v)) < \Delta(v)$  then we additionally add  $\Delta(v) - \max(0, f^+(v) - f^-(v))$  self-loops to v. We observe that we added exactly  $\Delta(v)$  out-edges to v. Since  $(f, \ell)$  is valid by Lemma 3.2 and  $\forall v \in \tilde{V} : \ell(v) < h$ , we added at most  $f^-(v) - f^+(v) + \Delta(v) \leq \nabla(v)$  incoming edges to v. Hence, we can relate the degree in  $\tilde{W}$  to the degree in W and in G by

$$\deg_{\tilde{W}}(v) \le \deg_{W_0}(v) + \nabla(v) + \Delta(v) \le \deg_{W_0}(v) + \deg_W(v) + \frac{4}{\psi} \left( \deg_W(v) - \deg_{W_0}(v) \right)$$
$$\le \frac{5}{\psi} \deg_W(v) \le \frac{5}{\psi^2} \deg_G(v) \tag{4}$$

and by the upper-bound  $\deg_G(v) \leq \deg_W(v) = \deg_{W_0}(v) + \deg_{\Pi^{-1}(\mathcal{D})}(v) \leq \deg_{W_0}(v) + \Delta(v) \leq \deg_{\tilde{W}}(v)$ , where the first inequality is due to (3), and the last due to the fact that we add at least  $\Delta(v)$  out-going edges to v when constructing  $\tilde{W}$  from W. We point out that the new embedding  $\tilde{\Pi}$  is a combination of the old embedding  $\Pi$  and flow paths with congestion at most  $\frac{16}{\phi\psi^2}$ . Hence, it is clear that  $\tilde{\Pi}$  is an embedding with congestion at most  $\frac{20}{\phi\psi^2}$ . What remains to be proven is that  $\tilde{W}$  is a  $\frac{\psi^2}{20}$ -expander.

Assume by contradiction that there is  $S \subseteq \tilde{V} : \operatorname{vol}_{\tilde{W}}(S) \leq e(W)$  and  $e_{\tilde{W}}(S, \tilde{V} \setminus S) < \frac{\psi^2}{20} \operatorname{vol}_{\tilde{W}}(S)$ . We note that this in particular implies that  $\operatorname{vol}_W(S) \leq \frac{4}{3} \operatorname{vol}_{\tilde{W}}(S)$ , since otherwise we have  $\frac{e(W)}{7} > 2 \cdot \Delta(V) \geq \operatorname{vol}_W(S) - \operatorname{vol}(\bar{S}) \geq \min(\operatorname{vol}_W(\bar{S})/3, e(W) - 2 \cdot \operatorname{vol}_W(\bar{S})) \geq e(W)/7$ .

On the other hand, we add to any vertex  $v \in S$  at least  $\Delta(v)$  outgoing edges and at most  $\sum_{v \in S} \nabla(v)$  of these edges can end in S, we add at least  $\sum_{v \in S} \Delta(v) - \sum_{v \in S} \nabla(v) = \Delta(S) - \operatorname{vol}_W(S)$  edges going across the cut  $(S, \tilde{V} \setminus S)$ . Since  $\Delta(S) - \operatorname{vol}_W(S) \leq \frac{\psi}{5} \operatorname{vol}_{\tilde{W}}(S)$  together with  $\operatorname{vol}_{\tilde{W}}(S) \leq 2 \cdot \Delta(S) + \operatorname{vol}_W(S)$ , we have (using  $\psi \leq \frac{1}{2}$ )

$$\Delta(S) \le \operatorname{vol}_W(S) + \frac{\psi}{5} \operatorname{vol}_{\tilde{W}}(S) \le \left(1 + \frac{1}{10}\right) \operatorname{vol}_W(S) + \frac{\Delta(S)}{5}.$$
(5)

This in turn implies that  $e_W(S,\bar{S}) - e_{W_0}(S,\bar{S}) \leq \operatorname{vol}_W(S) - \operatorname{vol}_{W_0}(S) = \frac{\psi}{4} \cdot \Delta(S) \leq \frac{\psi}{2} \operatorname{vol}_W(S)$ and  $\operatorname{vol}_{\tilde{W}}(S) \leq 5 \operatorname{vol}_W(S)$ . Since  $e_W(S,\bar{S}) \geq \frac{3 \cdot \psi}{4} \cdot \operatorname{vol}_W(S)$  (using  $\operatorname{vol}_W(S) \leq \frac{4}{3} \operatorname{vol}_{\tilde{W}}(S)$ ), we have  $e_{\tilde{W}}(S,\bar{S}) \geq e_{W_0}(S,\bar{S}) \geq \frac{\psi}{4} \operatorname{vol}_W(S) \geq \frac{\psi^2}{20} \operatorname{vol}_{\tilde{W}}(S)$ , contradicting the assumption that  $(S,\bar{S})$  is out-sparse.

It remains to prove items 2 and 3. Item 2 is a direct consequence of the next claim.

Claim 4.4. At the end of each while-loop iteration of ADJUSTPARTITION(), we have that  $e_{G\setminus \mathcal{D}}(S, \tilde{V}) \leq \frac{\phi}{2} \cdot \operatorname{vol}_G(S)$ , where we denote by S the set as defined in the current iteration in Line 18.

*Proof.* Let us consider the sets  $S_i = \{v \in \tilde{V} \mid \ell(v) \geq i\}$ . We observe that  $\operatorname{vol}_G(S_1) \leq 2m$ . Thus, by our choice of h, there exists  $1 \leq i < h$  such that  $\operatorname{vol}_{G \setminus \mathcal{D}}(S_i) < (1 + \frac{\phi}{4}) \cdot \operatorname{vol}_{G \setminus \mathcal{D}}(S_{i+1})$  and thus the loop of PRUNEORCERTIFY breaks. We observe that

$$e_{G\setminus\mathcal{D}}(S_{i+1}, V\setminus S_{i+1}) \le e_{G\setminus\mathcal{D}}(S_{i+1}, S_i\setminus S_{i+1}) + e_{G\setminus\mathcal{D}}(S_{i+1}, V\setminus S_i)$$
$$\le \left(\operatorname{vol}_{G\setminus\mathcal{D}}(S_i) - \operatorname{vol}_{G\setminus\mathcal{D}}(S_{i+1})\right) + e_{G\setminus\mathcal{D}}(S_{i+1}, \tilde{V}\setminus S_i)$$

According to the definition of state (3.1), we have that the capacity of the edges  $e \in E_{G \setminus \mathcal{D}}(S_{i+1}, \tilde{V} \setminus S_i)$  are saturated and the edges  $e \in E_{G \setminus \mathcal{D}}(\tilde{V} \setminus S_i, S_{i+1})$  do not carry any flow. Moreover, since  $(f, \ell)$  is valid we have that  $\forall v \in S_{i+1} : f^+(v) \leq f^-(v) + \Delta(v)$ . Hence, we can bound

$$\boldsymbol{c}_{G\setminus\mathcal{D}}(S_{i+1},\tilde{V}\setminus S_i) \leq \Delta(S_{i+1}) + \boldsymbol{f}^-(S_{i+1}) \leq \Delta(S_{i+1}) + \left(\boldsymbol{c}_{G\setminus\mathcal{D}}(S_i) - \boldsymbol{c}_{G\setminus\mathcal{D}}(S_{i+1})\right).$$

Using that the capacity of each edge is  $\frac{16}{\phi\psi^2}$  and the second inequality of (3), we obtain the bound

$$e_{G\setminus\mathcal{D}}(S_{i+1}, \tilde{V}\setminus S_{i+1}) \leq \frac{\phi\cdot\psi^2\cdot\Delta(S_{i+1})}{16} + \left(\operatorname{vol}_{G\setminus\mathcal{D}}(S_i) - \operatorname{vol}_{G\setminus\mathcal{D}}(S_{i+1})\right)$$
$$\leq \frac{\phi\cdot\psi\cdot\operatorname{vol}_W(S_{i+1})}{4} + \frac{\phi}{4}\cdot\operatorname{vol}_{G\setminus\mathcal{D}}(S_{i+1}) \leq \frac{\phi}{2}\cdot\operatorname{vol}_G(S_{i+1}),$$

For item 3 and the run-time bound, we additionally remark that  $\bigcup_{P \in \mathcal{P}: X \neq \tilde{V}} X$  is a sparse cut in  $W \setminus \Pi(\tilde{\mathcal{D}})$ , where  $\tilde{\mathcal{D}} = e_G(V \setminus S, S) \cup \Pi^{-1}(\mathcal{D})$ , since

$$e_{W\setminus\Pi^{-1}(\tilde{\mathcal{D}})}\left(\bigcup_{P\in\mathcal{P}}P,V\setminus\bigcup_{P\in\mathcal{P}}P\right)\leq\frac{\psi}{\phi}\cdot e_{G\setminus\tilde{\mathcal{D}}}\left(\bigcup_{P\in\mathcal{P}}P,V\setminus\bigcup_{P\in\mathcal{P}}P\right)\leq\frac{\psi}{\phi}\cdot|E^{r}|\leq\frac{\psi}{4}\cdot\operatorname{vol}_{W}\left(\bigcup_{P\in\mathcal{P}}P\right),$$

where we used item 2 in the second inequality and (3). Hence, Lemma 2.1 implies item 3. According to Lemma 3.2, we can bound the run-time by

$$O\left(h \cdot \left(\|\Delta\|_1 + \sum_t \boldsymbol{c}(\tilde{V}_i, S_t) + \nabla(S_t) + \sum_{P \in \mathcal{P}} \boldsymbol{c}(P, \tilde{V}_P) + \nabla(P)\right)\right),$$

where  $S_t$  denotes all external calls to REMOVEVERTICES and  $\tilde{V}_t, \tilde{V}_P$  denotes  $\tilde{V}$  right after the call to REMOVEVERTICES with  $S_t, P$ , respectively. This is equivalent to

$$O\left(h \cdot \left(\frac{|\Pi^{-1}(\mathcal{D})|}{\psi} + \sum_{t} \boldsymbol{c}(\tilde{V}_{t}, S_{t}) + \nabla(S_{t}) + \frac{1}{\phi\psi^{2}} \cdot |E^{r}| + \sum_{P \in \mathcal{P}} \operatorname{vol}_{W}(P)\right)\right),$$

where we used that all edges of  $\bigcup_{P \in \mathcal{P}} e(P, \tilde{V}_P)$  are in  $E^r$  and have capacity at most  $\frac{16}{\phi\psi^2}$  to bound  $\sum_{P \in \mathcal{P}} c(P, \tilde{V}_P)$ . We remark that by item 2 and (3) we have that  $|E^r| = O(\frac{\phi}{2} \cdot \sum_{P \in \mathcal{P}} \operatorname{vol}_W(P))$  and by item 3 that

$$\frac{1}{\phi\psi^2}|E^r| + \sum_{P\in\mathcal{P}} \operatorname{vol}_W(P) \le \frac{1}{3} \cdot \left(\frac{1}{\psi^2} + 1\right) \cdot \left|\Pi^{-1}(E_{G\setminus\mathcal{D}}(V\setminus\mathcal{S},\mathcal{S})\cup\mathcal{D})\right|$$

and thus the run-time bound simplifies to  $O\left(h \cdot \left(\frac{|\Pi^{-1}(\mathcal{D})|}{\psi^2} + \sum_t \boldsymbol{c}(\tilde{V}_t, S_t) + \nabla(S_t)\right)\right)$ .

# Acknowledgement

The authors are thankful for many fruitful discussions and feedback on an earlier version of the paper from Rasmus Kyng, Simon Meierhans and Thatchaphol Saranurak.

# References

[BGS20]	Aaron Bernstein, Maximilian Probst Gutenberg, and Thatchaphol Saranurak. Deterministic decremental reachability, scc, and shortest paths via directed expanders and congestion balancing. In 2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS), pages 1123–1134. IEEE, 2020. , 1, 2, 3, 11, 21
[BGS22]	Aaron Bernstein, Maximilian Probst Gutenberg, and Thatchaphol Saranurak. De- terministic decremental sssp and approximate min-cost flow in almost-linear time. In 2021 IEEE 62nd Annual Symposium on Foundations of Computer Science (FOCS), pages 1000–1008. IEEE, 2022. 1, 20, 21
[BGWN20]	Aaron Bernstein, Maximilian Probst Gutenberg, and Christian Wulff-Nilsen. Near- optimal decremental sssp in dense weighted digraphs. In 2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS), pages 1112–1122. IEEE, 2020. 1
[BNWN22]	Aaron Bernstein, Danupon Nanongkai, and Christian Wulff-Nilsen. Negative-weight single-source shortest paths in near-linear time. In 2022 IEEE 63rd Annual Symposium on Foundations of Computer Science (FOCS), pages 600–611. IEEE, 2022. 1, 20
[BPWN19]	Aaron Bernstein, Maximilian Probst, and Christian Wulff-Nilsen. Decremental strongly-connected components and single-source reachability in near-linear time. In <i>Proceedings of the 51st Annual ACM SIGACT Symposium on theory of computing</i> , pages 365–376, 2019. 21
[BvdBPG <sup>+</sup> 22]	Aaron Bernstein, Jan van den Brand, Maximilian Probst Gutenberg, Danupon Nanongkai, Thatchaphol Saranurak, Aaron Sidford, and He Sun. Fully-dynamic graph sparsifiers against an adaptive adversary. In 49th International Colloquium on Automata, Languages, and Programming (ICALP 2022). Schloss Dagstuhl-Leibniz-Zentrum für Informatik, 2022. 1, 21
[CDK <sup>+</sup> 21]	Parinya Chalermsook, Syamantak Das, Yunbum Kook, Bundit Laekhanukit, Yang P Liu, Richard Peng, Mark Sellke, and Daniel Vaz. Vertex sparsification for edge con- nectivity. In <i>Proceedings of the 2021 ACM-SIAM Symposium on Discrete Algorithms</i> (SODA), pages 1206–1225. SIAM, 2021. 1, 20
[CGL+20]	Julia Chuzhoy, Yu Gao, Jason Li, Danupon Nanongkai, Richard Peng, and Thatchaphol Saranurak. A deterministic algorithm for balanced cut with appli- cations to dynamic connectivity, flows, and beyond. In 2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS), pages 1158–1167. IEEE,

2020. 21

- [CGP<sup>+</sup>20] Timothy Chu, Yu Gao, Richard Peng, Sushant Sachdeva, Saurabh Sawlani, and Junxing Wang. Graph sparsification, spectral sketches, and faster resistance computation via short cycle decompositions. SIAM Journal on Computing, (0):FOCS18– 85, 2020. 20
- [Chu21] Julia Chuzhoy. Decremental all-pairs shortest paths in deterministic near-linear time. In Proceedings of the 53rd Annual ACM SIGACT Symposium on Theory of Computing, pages 626–639, 2021. 1, 21
- [CK19] Julia Chuzhoy and Sanjeev Khanna. A new algorithm for decremental single-source shortest paths with applications to vertex-capacitated flow and cut problems. In Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing, pages 389–400, 2019. 1, 21
- [CK24] Julia Chuzhoy and Sanjeev Khanna. A faster combinatorial algorithm for maximum bipartite matching. In Proceedings of the 2024 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 2185–2235. SIAM, 2024. 1, 2, 20
- [CKL<sup>+</sup>22] Li Chen, Rasmus Kyng, Yang P Liu, Richard Peng, Maximilian Probst Gutenberg, and Sushant Sachdeva. Maximum flow and minimum-cost flow in almost-linear time. In 2022 IEEE 63rd Annual Symposium on Foundations of Computer Science (FOCS), pages 612–623. IEEE, 2022. 1, 20, 21
- [CKL<sup>+</sup>24] Li Chen, Rasmus Kyng, Yang P Liu, Simon Meierhans, and Maximilian Probst Gutenberg. Almost-linear time algorithms for incremental graphs: Cycle detection, sccs, *s-t* shortest path, and minimum-cost flow. *to appear at STOC'24*, 2024. 1, 20
- [CS21] Julia Chuzhoy and Thatchaphol Saranurak. Deterministic algorithms for decremental shortest paths via layered core decomposition. In *Proceedings of the 2021* ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 2478–2496. SIAM, 2021. 1, 21
- [GRST21] Gramoz Goranci, Harald Räcke, Thatchaphol Saranurak, and Zihan Tan. The expander hierarchy and its applications to dynamic graph algorithms. In *Proceedings* of the 2021 ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 2212–2228. SIAM, 2021. 1, 21
- [GT88] Andrew V Goldberg and Robert E Tarjan. A new approach to the maximum-flow problem. *Journal of the ACM (JACM)*, 35(4):921–940, 1988., 6
- [HKGW23] Yiding Hua, Rasmus Kyng, Maximilian Probst Gutenberg, and Zihang Wu. Maintaining expander decompositions via sparse cuts. In Proceedings of the 2023 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 48–69. SIAM, 2023. , 2, 3, 4, 6, 11
- [HRW20] Monika Henzinger, Satish Rao, and Di Wang. Local flow partitioning for faster edge connectivity. *SIAM Journal on Computing*, 49(1):1–36, 2020. , 1

[JS22] Wenyu Jin and Xiaorui Sun. Fully dynamic st edge connectivity in subpolynomial time. In 2021 IEEE 62nd Annual Symposium on Foundations of Computer Science (FOCS), pages 861–872. IEEE, 2022. 1, 21 [JST24] Wenyu Jin, Xiaorui Sun, and Mikkel Thorup. Fully dynamic min-cut of superconstant size in subpolynomial time. In Proceedings of the 2024 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 2999–3026. SIAM, 2024. 1, 21 [KLOS14] Jonathan A Kelner, Yin Tat Lee, Lorenzo Orecchia, and Aaron Sidford. An almostlinear-time algorithm for approximate max flow in undirected graphs, and its multicommodity generalizations. In Proceedings of the twenty-fifth annual ACM-SIAM symposium on Discrete algorithms, pages 217–226. SIAM, 2014. 1, 20 [KMG24] Rasmus Kyng, Simon Meierhans, and Maximilian Probst Gutenberg. A dynamic shortest paths toolbox: Low-congestion vertex sparsifiers and their applications. to appear at STOC'24, 2024. 1, 20 [KMP22] Rasmus Kyng, Simon Meierhans, and Maximilian Probst. Derandomizing directed random walks in almost-linear time. In 2022 IEEE 63rd Annual Symposium on Foundations of Computer Science (FOCS), pages 407–418. IEEE, 2022. 1, 20 [KRV09] Rohit Khandekar, Satish Rao, and Umesh Vazirani. Graph partitioning using single commodity flows. Journal of the ACM (JACM), 56(4):1-15, 2009. 2, 11, 21 Ken-ichi Kawarabayashi and Mikkel Thorup. Deterministic edge connectivity in [KT18] near-linear time. Journal of the ACM (JACM), 66(1):1-50, 2018. 20 [Li21] Jason Li. Deterministic mincut in almost-linear time. In Proceedings of the 53rd Annual ACM SIGACT Symposium on Theory of Computing, pages 384–395, 2021. 1,20 [Liu23] Yang P Liu. Vertex sparsification for edge connectivity in polynomial time. In 14th Innovations in Theoretical Computer Science Conference (ITCS 2023). Schloss Dagstuhl-Leibniz-Zentrum für Informatik, 2023. 1, 20 [Lou10] Anand Louis. Cut-matching games on directed graphs. arXiv preprint arXiv:1010.1047, 2010. 2, 11, 21 [LSY19] Yang P Liu, Sushant Sachdeva, and Zejun Yu. Short cycles via low-diameter decompositions. In Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms, pages 2602–2615. SIAM, 2019. 20 [NS17] Danupon Nanongkai and Thatchaphol Saranurak. Dynamic spanning forest with worst-case update time: adaptive, las vegas, and o  $(n1/2-\varepsilon)$ -time. In Proceedings of the 49th Annual ACM SIGACT Symposium on Theory of Computing, pages 1122-1129, 2017. 1, 21 [NSWN17] Danupon Nanongkai, Thatchaphol Saranurak, and Christian Wulff-Nilsen. Dynamic minimum spanning forest with subpolynomial worst-case update time. In 2017 IEEE 58th Annual Symposium on Foundations of Computer Science (FOCS), pages 950-961. IEEE, 2017. 1, 4, 21

- [PY19] Merav Parter and Eylon Yogev. Optimal short cycle decomposition in almost linear time. In 46th International Colloquium on Automata, Languages, and Programming (ICALP 2019). Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2019. 20
- [Sar21] Thatchaphol Saranurak. A simple deterministic algorithm for edge connectivity. In Symposium on Simplicity in Algorithms (SOSA), pages 80–85. SIAM, 2021. 1, 20
- [ST04] Daniel A Spielman and Shang-Hua Teng. Nearly-linear time algorithms for graph partitioning, graph sparsification, and solving linear systems. In *Proceedings of the* thirty-sixth annual ACM symposium on Theory of computing, pages 81–90, 2004. 1, 20
- [SW19] Thatchaphol Saranurak and Di Wang. Expander decomposition and pruning: Faster, stronger, and simpler. In *Proceedings of the Thirtieth Annual ACM-SIAM* Symposium on Discrete Algorithms, pages 2616–2635. SIAM, 2019. 1, 2, 3, 11, 20
- [VDBCP<sup>+</sup>23] Jan Van Den Brand, Li Chen, Richard Peng, Rasmus Kyng, Yang P Liu, Maximilian Probst Gutenberg, Sushant Sachdeva, and Aaron Sidford. A deterministic almost-linear time algorithm for minimum-cost flow. In 2023 IEEE 64th Annual Symposium on Foundations of Computer Science (FOCS), pages 503–514. IEEE, 2023. 1, 20
- [VDBLL<sup>+</sup>21] Jan Van Den Brand, Yin Tat Lee, Yang P Liu, Thatchaphol Saranurak, Aaron Sidford, Zhao Song, and Di Wang. Minimum cost flows, mdps, and l1-regression in nearly linear time for dense instances. In *Proceedings of the 53rd Annual ACM SIGACT Symposium on Theory of Computing*, pages 859–869, 2021. 1, 20
- [vdBLN<sup>+</sup>20] Jan van den Brand, Yin-Tat Lee, Danupon Nanongkai, Richard Peng, Thatchaphol Saranurak, Aaron Sidford, Zhao Song, and Di Wang. Bipartite matching in nearlylinear time on moderately dense graphs. In 2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS), pages 919–930. IEEE, 2020. 20
- [WN17] Christian Wulff-Nilsen. Fully-dynamic minimum spanning forest with improved worst-case update time. In *Proceedings of the 49th Annual ACM SIGACT Sympo*sium on Theory of Computing, pages 1130–1143, 2017. 1, 21

# A Appendix

#### A.1 Previous Work

**Expander Decompositions for Static Flow Problems.** In static graph settings, expander decompositions have been employed in many recent algorithms for electrical, maximum flow and min-cost flow problems. As mentioned, they were instrumental in the first Laplacian solver [ST04] that computes electrical flows, and still are used in recent Laplacian solvers, for example in the recent first almost-linear deterministic Laplacian solver for directed graphs [KMP22].

For the maximum and min-cost flow problems, expander decompositions have been crucial, as seen in [KLOS14, vdBLN<sup>+</sup>20, VDBLL<sup>+</sup>21, BGS22] and the recent development of an almost-linear time algorithm for max flow and min-cost flow in directed graphs [CKL<sup>+</sup>22]. In [CKL<sup>+</sup>22], the static min-cost flow problem in a directed graph is transformed via advanced convex optimization methods into a dynamic problem in an undirected graph. This dynamic problem is then solved efficiently by a data structure that uses the undirected expander decomposition algorithm from [SW19] internally. By simple reductions, the result in [CKL<sup>+</sup>22] also gave the first almost-linear time algorithms for the problems of negative Single Source Shortest Path (SSSP) and bipartite matching, but also to compute expanders in directed graphs.

Since the breakthrough result in  $[CKL^+22]$  (and follow-up work  $[VDBCP^+23, KMG24, CKL^+24]$ ), a natural new research initiative has emerged: can we solve the min-cost flow problem without relying on advanced convex optimization methods, or put differently, can it be solved with purely *combinatorial* methods? This question aims to further our understanding of the min-cost flow problem by developing a radically different (possibly more accessible) perspective but is also motivated by the quest to find a simpler and more practical algorithm. This initiative has already led to significant achievements, including a near-linear time algorithm for Negative SSSP [BNWN22] and a purely combinatorial approach to bipartite matching [CK24] that improves current combinatorial approaches in dense graphs, a barrier that stood since the 80s.

Directed expander decomposition has emerged as a critical tool in this landscape, exemplified by the work of [BNWN22], who utilized directed low-diameter decompositions akin to directed expander decompositions, and [CK24], who directly applied directed expander decompositions. The aim of our new accessible directed expander decomposition framework is to further accelerate this essential research initiative, contributing significantly to the field of graph algorithms.

**Expander Decompositions for Graph Problems beyond Flows.** In undirected graphs, expander decompositions have also been crucial in all deterministic almost-linear time global mincut algorithms for undirected graphs [KT18, Sar21, Li21] in computing short-cycle decompositions [CGP<sup>+</sup>20, PY19, LSY19], and in finding min-cut preserving vertex sparsifiers [CDK<sup>+</sup>21, Liu23]. It is noteworthy that the above achievements pertain exclusively to undirected graphs. Directed graphs have yet to benefit from the application of expander decompositions. In the directed setting only considerably less efficient algorithms are known. We hope that our directed expander decomposition framework will facilitate adapting the existing methodologies used in undirected graphs to the directed context, or will inspire novel strategies to address these algorithmic challenges.

**Expander Decompositions in Dynamic Graphs.** In dynamic graphs, which are characterized by ongoing edge insertions and deletions, expanders have played a significant role in the undirected setting. They have been fundamental in achieving new worst-case update time and derandomization

results in dynamic connectivity [WN17, NS17, NSWN17, CGL<sup>+</sup>20], in single-source shortest paths [CK19, BGS20, CS21, Chu21, BGS22], in approximate (s, t)-max-flow and (s, t)-min-cut algorithms [GRST21], and in developing sparsifiers resistant to adaptive adversaries [BvdBPG<sup>+</sup>22, CKL<sup>+</sup>22]. Notably, they were also a key component in the first subpolynomial update time c-edge connectivity algorithm [JS22] and bounded-value min-cut algorithm [JST24].

In the context of directed graphs, there remains a significant gap in our understanding. A notable challenge is the absence of near-linear time solutions for many problems, such as decremental Single-Source Shortest Paths (SSSP). Where solutions do exist, such as for decremental Strongly Connected Components (SCC), they are typically effective only against oblivious adversaries, as highlighted in [BPWN19]. Furthermore, in scenarios where algorithms are devised to tackle adaptive adversaries, the trade-off is often a drastic reduction in speed, a fact exemplified in [BGS20]. However, the use of directed expander decompositions in these algorithms suggests that enhancing these decompositions could be key to developing faster and more robust algorithms for directed dynamic graphs.

#### A.2 Static Expander Decomposition

In this section, we discuss how we can use the algorithm BIDIRECTEDEXPANDERPRUNING of Theorem 4.1 as a subroutine for a static expander decomposition. But before we turn to the outline of the algorithm, we recall the directed version of the cut-matching game.

**Theorem A.1** ([KRV09, Lou10]). Given a directed graph G = (V, E) of m edges and a parameter  $\phi$ , the cut-matching game takes  $O((m \log^3 m)/\phi)$  time and either returns

- 1.  $a O(\log^2(m))$ -witness  $(W, \Pi)$  certifying that  $G \cup \mathcal{F}$  is a  $\phi$ -expander for some set of <u>fake</u> edges  $\mathcal{F}$  where  $|\Pi^{-1}(\mathcal{F})| \leq c \cdot \frac{m}{\log^2(m)}$ , where c > 0, or
- 2. a balanced sparse cut  $(A, \bar{A})$  in  $G: e_G(A, \bar{A}) \leq O\left(\phi \cdot \log^2(m) \cdot \min(\operatorname{vol}_G(A), \operatorname{vol}_G(\bar{A}))\right)$  such that  $\operatorname{vol}_G(A), \operatorname{vol}_G(\bar{A}) = \Omega(m/\log^4 m).$

The statement above slightly deviates from well-known cut-matching game formulations. It is more common that the cut-matching game either certifies that G is a  $\phi$ -expander or provides a cut that might be unbalanced. But it is straightforward to obtain the formulation in Theorem A.1. Recall that the cut-matching algorithm attempts to embed a witness using  $O(\log^2(m))$  single commodity flows. A cut  $(A, \bar{A})$  is provided if the algorithm fails to route one of these network flows. If one uses the push-relabel algorithm for routing these single commodity flows, it is easy to see that one obtains a pre-flow f such that all positive excess flow is stuck on the smaller side of the cut and the total amount is at most  $\min(\operatorname{vol}_G(A), \operatorname{vol}_G(\bar{A}))$ . Thus, one can readily find a source-sink pair matching F of size at most  $\min(\operatorname{vol}_G(A), \operatorname{vol}_G(\bar{A}))$  and extend the pre-flow to an actual routing in  $G \cup F$ . Indeed if the cut  $(A, \bar{A})$  is unbalanced, the algorithm picks such a set of fake edges Fand routes the remaining excess flow along these edges. It then continues with routing the next single-commodity flow in G. If the algorithm eventually manages to embed a witness, the witness will actually be embedded into  $G \cup \mathcal{F}$ , where  $\mathcal{F}$  is the union of all the fake edge sets F added over all rounds.

In Algorithm 4, we then use BIDIRECTEDEXPANDERPRUNING to remove the set  $\mathcal{F}$  of fake edges from  $G \cup \mathcal{F}$  making only marginal adjustments to the witness embedding.

**Theorem A.2.** Given a directed graph G, we can compute a  $\left(O(\log^6 m), \phi, O\left(\frac{1}{\log^2 m}\right)\right)$ -expander decomposition  $(\mathcal{X}, E_r)$  in run time  $O(m \log^4(m)/\phi)$ .

*Proof.* Item 1 and 3 of the Definition of an expander decomposition are immediate from the algorithm. We prove item 2 and the run-time bound by induction on the size of the graph. For the induction step, we consider a call to EXPANDERDECOMPOSITION(G) where G has m edges. There are two cases to consider, either we find a balanced sparse cut in G and make a recursive call or we don't and remove the fake edges  $\mathcal{F}$  at the end.

In the first case, we can bound

$$|E^{r}| \leq |E_{1}^{r}| + |E_{2}^{r}| + e_{G}(A, A)$$
  
$$\leq c_{1} \cdot \phi \cdot \log^{6}(e(A)) \cdot e(A) + c_{1} \cdot \phi \cdot \log^{6}(e(\bar{A})) \cdot e(\bar{A}) + O(\phi \cdot \log^{2}(m) \cdot m)$$
  
$$\leq (c_{1} \cdot \log^{6}(m)) \cdot \phi \cdot m$$

where we used in the second inequality the induction assumption and item 2 of Theorem A.1 and  $c_1 > 0$  is a constant large enough. Similarly, we bound the run-time by the contributions of the call to CUTMATCHING and the two calls to EXPANDERDECOMPOSITION with  $G[A], G[\bar{A}]$ . Again by Theorem A.1 and by the induction assumption, we can bound these contributions by

$$O(m \cdot \log^3(m)/\phi) + c_2 \cdot m_1 \cdot \log^4(m_1)/\phi + c_2 \cdot m_2 \cdot \log^4(m_2)/\phi \le (c_2 \cdot \log^4(m)) \cdot \phi \cdot m,$$

where  $c_2 > 0$  ia again a constant large enough. In the second case, we can use item 2 and item 3 of Theorem 4.1 to bound  $|E^r| \leq O(|\Pi^{-1}(\mathcal{F})|)$ . While the run-time is determined by the call to CUTMATCHING and the call to REMOVEEDGES. The run-time of the call to CUTMATCHING is again bounded by  $m \cdot \log^3(m)/\phi$ . To bound the run-time of the call to REMOVEVERTICES, we point out that the run-time of the update is in  $O\left(\frac{h}{\psi^2} \cdot |\Pi^{-1}(\mathcal{F})|\right)$  according to Theorem 4.1 and that by induction assumption the run-time of the recursive calls in line 4 is bounded by

$$\sum_{P \in \mathcal{P}_1} \frac{|P| \cdot \log^4(|P|)}{\phi} \le \frac{\log^4(m)}{\phi} \cdot \sum_{P \in \mathcal{P}_1} |P| = \frac{\log^4(m)}{\phi} \cdot |\Pi^{-1}(|\mathcal{F}|)| = O(\frac{m \log^2(m)}{\phi})$$

where we used item three of Theorem 4.1 in the last inequality.

Algorithm 4 EXPANDER DECOMPOSITION(G)

while CUTMATCHING(G) provides a cut (A, A) do  $(\mathcal{P}_1, E_1^r) \leftarrow \text{ExpanderDecomposition}(G[A])$  $(\mathcal{P}_2, E_2^r) \leftarrow \text{ExpanderDecomposition}(G[\bar{A}])$ return  $(\mathcal{P}_1 \cup \mathcal{P}_2, E_1^r \cup E_2^r \cup E_G(A, \overline{A}))$ end while CUTMATCHING(G) provides  $(W, \Pi)$  embedded into  $G \cup \mathcal{F}$ return REMOVEEDGES $(G, W, \Pi, \mathcal{F})$ def REMOVEEDGES $(G, W, \Pi, \mathcal{D})$  $((\tilde{V}, \tilde{W}, \tilde{\Pi}), \mathcal{P}, E_0^r) \leftarrow \text{BiDirectedExpanderPruning}(G, W, \Pi)$  $((\tilde{V}, \tilde{W}, \tilde{\Pi}), \mathcal{P}, E_0^r)$ . REMOVEEDGES $(\mathcal{D})$  $\mathcal{X} \leftarrow \{(\tilde{V}, \tilde{W}, \tilde{\Pi})\}, E^r \leftarrow E_1^r$ for  $P \in \mathcal{P}$  do  $(\mathcal{X}_1, E_1^r) \leftarrow \text{ExpanderDecomposition}(P)$  $\mathcal{X} \leftarrow \mathcal{X} \cup \mathcal{X}_1$  $E^r \leftarrow E^r \cup E_1^r$ end for return  $(\mathcal{X}, E^r)$ 

## A.3 Dynamic Expander Decomposition

In this section, we discuss how we can use the algorithm BIDIRECTEDEXPANDERPRUNING and the algorithm EXPANDERDECOMPOSITION as a subroutines for a dynamic expander decomposition.

**Theorem A.3.** For every  $(\beta, \phi, \psi)$ -expander decomposition  $(\mathcal{X}, E_r)$  of a directed graph G, there is a randomized data structure DYNAMICEXPANDERDECOMPOSITION(G) (see Algorithm 5). For up to  $c \cdot \phi \cdot \psi \cdot e(G)$  calls, where c is a fixed constant, of the form

• REMOVEEDGE(d): where  $d \in E(V)$ , adds d to  $\mathcal{D}$  (initially  $\mathcal{D} = \emptyset$ )

the algorithm explicitly updates the tuple  $(\mathcal{X}, E^r)$  after each call, such that thereafter  $(\mathcal{X}, E^r)$  is a  $\left(4 \cdot \beta, \frac{\phi \psi^4}{400}, \frac{\psi^2}{20}\right)$ -expander-decomposition for  $G \setminus \mathcal{D}$  refining the previous. The run-time is bounded by  $O\left(\frac{|\mathcal{D}|}{\phi^2} \cdot \log e(G) \cdot \max\left(\log^3 |\mathcal{D}|, \frac{1}{\psi^2}\right)\right)$ .

Algorithm 5 DYNAMICEXPANDERDECOMPOSITION( $\mathcal{X}_0, E_0^r$ )

1: def Init  $(\mathcal{X}, E^r) \leftarrow (\mathcal{X}_0, E_0^r)$ 2: for  $X \in \mathcal{X}$  do 3:  $(V_X, \mathcal{P}_X, E_X^r) \leftarrow \text{BiDirectedExpanderPruning}(X, W_X, \Pi_X)$ 4: 5:end for 6: 7: def REMOVEEDGE(d)Find  $(X, W, \Pi) \in \mathcal{X}$  such that  $d \in E(X)$ . 8:  $((V_X, W_X, \Pi_X), \mathcal{P}_X, E_X^r)$ . REMOVEEDGES(d)9: Replace  $(X, W, \Pi)$  by  $(V_X, W_X, \Pi_X)$ 10: for  $X_1$  new in  $\mathcal{P}_X$  do 11:  $(\mathcal{X}_1, E_1^r) \leftarrow \text{ExpanderDecomposition}(X_1)$ 12: $\mathcal{X} \leftarrow \mathcal{X} \cup \mathcal{X}_1$ 13: $E^r \leftarrow E^r \cup E_1^r$ 14: end for 15:

Proof sketch. Item 1 of the definition of the directed expander decomposition is a direct consequence of item 1 in Theorem 4.1 and the fact that we apply EXPANDERDECOMPOSITION to all sets that are pruned away. Item 3 is implied by item 4 of Theorem 4.1 and Theorem A.2. For item 2 we note that all edges  $E^r$  have either been removed during BIDIRECTEDEXPANDERPRUNING or EXPANDERDECOMPOSITION. In the first subroutine we removed at most  $|\mathcal{D}|/\phi$  according to item 2 and item 3, and, according to Theorem A.2, in the second subroutine at most  $\phi \cdot \beta \cdot p$ , where p is the sum of all  $|X_1|$  of line 12. Item 3 implies that p is bounded by  $4 \cdot |\Pi^{-1}(\mathcal{D})| = 4 \cdot \frac{|\mathcal{D}|}{\phi} = 2 \cdot e(G)$ . Similarly the run-time is determined by the edge removals of BIDIRECTEDEXPANDERPRUNING and the calls to EXPANDERDECOMPOSITION. Hence, we may bound the run-time by  $O\left(\frac{h}{\psi^2} \cdot |\Pi^{-1}(\mathcal{D})|\right) + O\left(q \cdot \log^4(q)/\phi\right) = O\left(\frac{|\mathcal{D}|}{\phi^2} \cdot \log e(G) \cdot \max\left(\log^3 |\mathcal{D}|, \frac{1}{\psi^2}\right)\right)$ .

To obtain Theorem 1.2, we combine Theorem A.2 and Theorem A.3. After  $O(\phi \cdot \psi \cdot e(G))$  deletions, we restart the maintenance of the expander decomposition with Theorem A.2.