

# Alpaca against Vicuna: Using LLMs to Uncover Memorization of LLMs

Aly M. Kassem<sup>1\*</sup> Omar Mahmoud<sup>2\*</sup> Niloofar Mireshghallah<sup>3\*</sup>  
 Hyunwoo Kim<sup>4</sup> Yulia Tsvetkov<sup>3</sup> Yejin Choi<sup>3,4</sup> Sherif Saad<sup>1</sup> Santu Rana<sup>2</sup>  
<sup>1</sup>University of Windsor <sup>2</sup>Applied Artificial Intelligence Institute, Deakin University  
<sup>3</sup>University of Washington <sup>4</sup>Allen Institute for AI  
 {kassem6,sherif.saad}@uwindsor.ca, {o.mahmoud,santu.rana}@deakin.edu.au  
 {niloofar,yuliat,yejin}@cs.washington.edu, hyunwook@allenai.org

## Abstract

In this paper, we introduce a black-box prompt optimization method that uses an *attacker* LLM agent to uncover higher levels of memorization in a *victim* agent, compared to what is revealed by prompting the target model with the training data directly, which is the dominant approach of quantifying memorization in LLMs. We use an iterative rejection-sampling optimization process to find *instruction-based* prompts with two main characteristics: (1) *minimal* overlap with the training data to avoid presenting the solution directly to the model, and (2) *maximal* overlap between the victim model’s output and the training data, aiming to induce the victim to spit out training data. We observe that our instruction-based prompts generate outputs with 23.7% higher overlap with training data compared to the baseline prefix-suffix measurements. Our findings show that (1) *instruction-tuned models can expose pre-training data as much as their base-models*, if not more so, (2) *contexts other than the original training data can lead to leakage*, and (3) *using instructions proposed by other LLMs can open a new avenue of automated attacks that we should further study and explore*.

## 1 Introduction

Pre-trained Language models are often instruction-tuned for user-facing applications to enable the generation of high-quality responses to task-oriented prompts (Ouyang et al., 2022; Taori et al., 2023; Chowdhery et al., 2023). A significant body of prior work (Carlini et al., 2022; Biderman et al., 2023a; Shi et al., 2023; Mireshghallah et al., 2022) has extensively defined and studied the memorization of pre-training data in base LLMs, raising concerns in terms of privacy, copyright, and fairness. However, there is a limited understanding of how the instruction-tuning process can affect the memorization and discoverability of pre-training data in aligned models. As such, we set out to answer the question *Can we use instruction-based prompts to uncover higher levels of memorization in aligned models?*

The current established method of quantifying memorization in LLMs (Carlini et al., 2023) considers a sequence  $d$  memorized in a model in a discoverable manner if prompting the model with the original prefix from the pre-training data would yield sequence  $d$  (or a sequence similar to  $d$ , if we are studying approximate memorization; Biderman et al. 2023a). The assumption in the prior work Carlini et al. (2022; 2023) is that using the ground truth pre-training data as context would provide an upper-bound estimate of memorization. Although, there could exist prompts other than the original training data that would elicit higher levels of training data regurgitation.

To find such prompts, we propose a new optimization method, depicted in Figure 1, where we use another aligned language model as an ‘attacker’ which proposes prompts that would induce the victim (target) model to output a generation that is more faithful to the training

---

\*Equal Contribution




Figure 1: Overview of our method: we first create an initial prompt that takes the target training sequence we are probing for and turns it into an instruction. The attacker LLM then uses this prompt to propose multiple candidate prompts that would propel the victim LLM to generate a response that overlaps highly with the training data. We then score each proposed candidate prompt based on two objectives: (1) how much overlap the victim response has with the ground truth training data (the memorization measure, higher, better) and (2) how much overlap the prompt has with the training data (we want this overlap to be small so as not to spill the solution in the instruction). We use this score as a feedback signal for the attacker to optimize the prompt and propose multiple new prompts for the next round of optimization.

data. In this setup, the attacker model iteratively refines its proposed prompts to increase the overlap of the victim output with the ground truth. This is inspired by the victim-play line of work in the computer security literature Wang et al. (2023a). To disincentivize the attacker from feeding the solution to the victim model, we add an extra term to the objective, which minimizes the overlap between the proposed prompts and the target training sequence.

To create robust benchmarks for the evaluation of our approach, we draw a parallel between safety jailbreaking techniques and training data extraction. We leverage automatic prompt optimization to discover prompts that guide the model toward generating outputs closely aligned with its training data. We emphasize that this is different from jailbreaking, as our goal is not to bypass a specific safety feature that prevents training data regurgitation behavior from the model. In our evaluation, we scrutinize the Greedy Coordinate Gradient (CGC; Zou et al. 2023), a white-box prompt optimization technique for identifying prompts that induce detrimental model behaviors. Additionally, we compare our proposed methods against Reverse-LM (Pfau et al., 2023) and sequence extraction (prefix-suffix; Carlini et al. 2022; 2021) across both base models and instruction-tuned models, providing insights on how these widely used methods fare in the context of instruction-tuned models.

We run our method and the baselines on Llama-based, OLMo, and Falcon models (Touvron et al., 2023; Penedo et al., 2023; Groeneveld et al., 2024), and their instruction-tuned variations, including Alpaca (Taori et al., 2023), Tulu (Wang et al., 2023b), and Vicuna (Chiang et al., 2023), spanning 3 different sequence lengths (200, 300 and 500) and 5 different pre-training data domains (following methodology of Duan et al. 2024). Our key contributions and findings are summarized as follows:

- We propose a black-box prompt optimization approach, tailored for instruction-tuned models, that uses an attacker LLM and shows that **our approach uncovers 23.7% more memorization of pre-training data in instruction-tuned models**, compared to the prior dominant approach of directly prompting the model with original prefixes from the data Carlini et al. (2022).
- We also compare the discoverable memorization of pre-training data in **instruction-tuned LLMs and their base counterparts** and show that using the prior prefix-suffix

approach instruction-tuned models demonstrate lower memorization, creating a **false sense of higher privacy/lower-risks in these models**. Our method, on the contrary, **uncovers 12.4% higher memorization in instruction-tuned models**, showing that **contexts other than the original pre-training data can also lead to leakage**, and pointing at the need for better alignment, in terms of privacy.

- Our experimental results demonstrate that our black-box approach uncovers 12.5% more memorization than the white-box method, GCG, in terms of training data reconstruction overlap.
- We find that leveraging an open-source model as an attacker can often surpass using a robust commercial model by 2.4%.

We hope that our results and analysis encourage future research to further automate the process of auditing and probing models using other LLMs and to propose more principled, efficient approaches for the reconstruction of training data.

## 2 Background: Quantifying Memorization

In this work, we use the discoverable notion of memorization for LLMs and quantify it through approximate string matching. Below, we define these terms.

**Definition 1 (Discoverable Memorization)** *An example  $x = [p||s]$ , drawn from training data  $D$ , is considered memorized by model  $f_\theta$  if  $f_\theta(p) = s$ , where  $x$  consists of a prefix  $p$  and a corresponding suffix  $s$ .*

The concept entails that the prefix guides the model’s generation process towards the most probable completion, typically the suffix if the example has been memorized. Drawing from previous research, Carlini et al. (2022) identified certain factors significantly influencing memorization, including model size, utilization of data deduplication techniques, and contextual aspects.

**Definition 2 (Approximate String Matching)** *For a model  $f_\theta$  and a given similarity metric  $\beta$ , an example  $x$  from the training data  $D$  is said to be approximately memorized if there exists a prompt  $p$  such that the output of the model  $f_\theta(p)$  is  $s'$ , where  $s$  and  $s'$  are close in accordance with the similarity metric  $\beta$ , i.e.,  $\beta(s, s')$  is high.*

Prior research demonstrates approximate memorization’s superiority over verbatim memorization in LLMs (Ippolito et al., 2023; Biderman et al., 2023a). We employ ROUGE-L to measure the similarity via the longest common subsequence between model-generated and original continuations, adhering to approximate memorization in our work.

## 3 Using LLMs to Probe Memorization in other LLMs

In this section, we begin by formally outlining the optimization problem and specifying our objective function. We present our method’s pipeline, see Figure 1 and Algorithm 1, which includes initialization, sampling, and refinement, creating the optimized prompt.

### 3.1 Formalizing the Optimization Problem

Consider a sequence  $d \in D$ , where  $D$  is the pre-training dataset of a model  $M$ . The objective is to find an input prompt  $p^*$  that the overlap between the output sequence of the model  $M(p^*)$  and  $d$  is maximized. Formally, the optimization problem can be expressed as:

$$p^* = \arg \max_p \mathcal{O}_{d,M}(p)$$

Where  $\mathcal{O}_{d,M}(p) = LCS(M(p), d_{\text{suffix}})$  is the objective function we want to maximize for a fixed model  $M$  and sequence  $d$ .  $M(\cdot)$  is the operation of decoding from the model  $M$ ,

conditioned on a given input.  $LCS$  is the longest common subsequence that measures the syntactic similarity between sequences we employ ROUGE-L in our case (Lin, 2004).

In practice, however, LLMs have been shown to be able to regurgitate and repeat their inputs (Zhang & Ippolito, 2023; Priyanshu et al., 2023). Therefore, one obvious solution to this problem could be  $p = [z||d]$ , where  $z$  is an instruction like repeat. To avoid this shortcut, we re-write the objective  $\mathcal{O}$  as the following to de-incentive such solutions:

$$\mathcal{O} = \alpha \cdot LCS(M(p), d_{\text{suffix}}) + (1 - \alpha) \cdot -LCS(p, d_{\text{suffix}})$$

We add the second term to penalize solutions that overlap highly with the sequence  $d_{\text{suffix}}$ .  $\alpha$  is a hyperparameter to control how much we allow  $d$  to be used. Its value is determined by achieving a trade-off between a high memorization score and a low overlap with the ground truth (see Appendix A for details). This problem is, in effect, discrete optimization, previously tackled using gradient-based techniques (Jones et al., 2023; Zou et al., 2023). However, ROUGE-L is not differentiable, and we assume black-box access to the target models to advocate a realistic scenario, rendering gradient-based methods inapplicable.

To solve this, Algorithm 1 shows how we sample from the possible distribution of solutions and find the optimal  $p^*$ . In our setting, we use an alternate model  $M'(\cdot|[instr])$ , with a specific instruction  $instr$ , as an attacker model that proposes prompts  $p$ . We perform constrained sampling  $p_t \sim M'(\cdot|[instr||p_{t-1}])$  at time step  $t$  from the proposal distribution, where the constraint is to maximize  $LCS(M(p_t), d_{\text{suffix}})$ , and we do this with rejection sampling (best-of- $n$ ) from  $M'$ . In simpler terms,  $M'$  seeks the optimal prompt to elicit the sequence  $d$  or its similarity from the victim model  $M$ .

---

#### Algorithm 1 Interactive Sampling Algorithm

---

```

1: Input: pre-training sample  $d, M, M', M_{\text{init}}$ 
2:  $p_{\text{init}} \leftarrow M_{\text{init}}(d)$  //Construct initial prompt
3:  $p_{t-1} \leftarrow p_{\text{init}}$ 
4: for  $t = 3$  do
5:    $p_t \sim M'(Instr|p_{t-1}, n = 24)$  //Sample 24 prompts
6:    $\mathcal{O} = \alpha \cdot LCS(M(p_t), d_{\text{suffix}}) + (1 - \alpha) \cdot -LCS(p_t, d_{\text{suffix}})$ 
7:    $p_t = \arg \max(\mathcal{O})$  //Obtain the highest scoring prompt
8: end for
9:  $p^* = \arg \max(p_0, \dots, p_t)$  //Obtain the highest scoring prompt across the iterations
10: return  $p^*$  //Return optimal prompt

```

---

### 3.2 Optimization via Interactive Sampling

Since the instruction-tuned LM is fine-tuned through a question-answering process to match the user’s intentions better, we design our method to use this instruction-following ability and customize our approach to optimize data extraction. As such, we create prompts in the form of instructions or questions that would propel the target model to output the training data points we want to extract, and then we optimize this ‘initial prompt’ iteratively to get better reconstruction.

To create the initial prompt, we need to somehow transform the training data point into a question. This could be done in different ways, however, we leverage LLMs to do this as well. We instruct this LLM with a ‘meta-prompt’, which is: “Given a paragraph snippet, please generate a question that asks for the generation of the paragraph,” along with the pre-training sample. We also add customized instructions to regularize the prompts, such as “Make sure to keep the question abstract” or “Ensure the question is not overly lengthy.” In practice, we use the meta-prompt on GPT-4 to help generate the initial prompt. Still, we show that utilizing other models, such as Mixtral (Jiang et al., 2024), also yields comparable performance (subsection 5.4).

Finally, we assess the alignment between the ground truth and each prompt, prioritizing prompts with minimal overlap compared to our baseline approach. Further explanations

on this will follow. Then, we assess how well the answer to the prompts matches the pre-training sample, saving these paired outcomes for later stages of our procedure.

**Interactive Loop** After receiving the initial prompt, we utilize a two-step strategy to enhance it for optimal output. These steps involve exploration and exploitation: Initially, we generate  $k$  prompts from an attacker LM, assess them, and choose the most effective prompt. This procedure is repeated  $i$  times, wherein each iteration exploits the best prompt found and then explores new possibilities through  $k$ -samples derived from it.

(1) *Best-of- $n$  sampling from  $M'$* : During optimization, the meta-prompt text in this stage differs from the one in the initialization stage. Here, we instruct the model to produce an improved rendition of the prompt, specifically with “*I have old questions. Write your new question by paraphrasing the old ones*” alongside the preceding step’s prompt. Following this, we supply this instruction to the attacker LLM, generating 24 new prompts for each sample and scoring with our objective function. Ultimately, we choose the prompt with the highest score according to our objective function. On top of this prompt, better-quality samples can be created again in the next step.

(2) *Refine*: To proceed, we designate the improved prompt from the previous iteration as the starting point and repeat the sampling process three times. This aims to produce a refined version of the original prompt, enhancing extraction capabilities and engaging with the attacker LLM using the prompt from the previous iteration. We do constrained sampling  $p_t \sim M'(\cdot \mid [\text{instr} \parallel p_{t-1}])$  at time step  $t$ , where the constraint is to maximize  $\text{LCS}(M(p_t), d)$ , and we do this with a rejection sampling (best-of- $n$ ) from  $M'$ .

## 4 Experimental Settings

### 4.1 Attacker & Victim LLMs

**Attacker LLMs:** Our method relies on harnessing an open-source model Zephyr 7B, an instruction-tuned variant of the Mistral-7B  $\beta$  (Tunstall et al., 2023) as the attacker. We also showcase employing more powerful LLMs as attackers in subsection 5.2.

**Victim LLMs:** We assess the memorization capabilities of instruction-tuned LLMs compared to their base model across various sizes (7B, 13B, 30B) by applying our method on five open-source models of different sizes by employing the instruction-tuned versions of Llama (Alpaca, Tulu, Vicuna) (Touvron et al., 2023), OLMo (Groeneveld et al., 2024), and Falcon (Penedo et al., 2023). By comparing these instruction-tuned models to their base model, we gain insights into the impact of instruction-tuning on memorization. See Appendix D for more details about the models.

### 4.2 Evaluation Data

**Data Domains:** To curate diverse evaluation datasets, we extract samples from base model pre-training data (Llama, OLMo, and Falcon). Given Llama’s data unavailability, we replicate it using the RedPajama dataset, while Falcon’s RefinedWeb, sourced from Common Crawl, is accessible. OLMo’s pre-training data, Dolma, is directly utilized. Across five domains for Llama and six for Dolma—Github, C4, CC, Arxiv, and Books for Llama, with The Stack substituted for Github, PeS2o for Arxiv, and Reddit added for social media within Dolma—we select 15,000 samples from Llama, 3,000 from Falcon’s RefinedWeb, and 16,000 from OLMo’s domains, ensuring uniform distribution across sequence lengths.

**Sequence Lengths Selection:** To measure our method’s adaptability across varying sequence lengths (200, 300, and 500), we adopt a splitting ratio informed by real-world usage patterns. Drawing from the WildChat dataset analysis (Zhao et al., 2024), we allocate 33% of each sample as the prefix and the remaining 67% as the suffix, enhancing the representation of typical usage scenarios. See Appendix D for more details.

Average Over Three Sequence Lengths (200, 300, 500)																	
Model	Method	Access	Github			ArXiv			CC			C4			Books		
			Mem	LCS <sub>P</sub>	Dis	Mem	LCS <sub>P</sub>	Dis	Mem	LCS <sub>P</sub>	Dis	Mem	LCS <sub>P</sub>	Dis	Mem	LCS <sub>P</sub>	Dis
			↑	↓	↑	↑	↓	↑	↑	↓	↑	↑	↓	↑	↑	↓	↑
Alpaca	P-S-Base	B	.291	.125	-	.183	.112	-	.190	.104	-	.204	.114	-	.208	.093	-
	P-S-Inst	B	.270	.124	-	.179	.112	-	.155	.104	-	.143	.114	-	.131	.093	-
	Reverse-LM	B	.229	.200	.864	.133	.196	.848	.113	.186	.843	.110	.181	.834	.122	.142	.865
	GCG	W	.300	.110	.530	.178	.101	.379	.194	.090	.374	<b>.208</b>	.102	.321	.199	.080	.422
	Ours	B	<b>.322</b>	.102	.864	<b>.228</b>	.108	.848	<b>.214</b>	.096	.830	<b>.203</b>	.090	.834	<b>.221</b>	.079	.865
Vicuna	P-S-Base	B	.291	.125	-	.183	.112	-	.190	.104	-	.203	.114	-	.208	.093	-
	P-S-Inst	B	.273	.125	-	.213	.112	-	.205	.114	-	.191	.114	-	.198	.093	-
	Reverse-LM	B	.255	.200	.864	.200	.196	.848	.173	.186	.830	.173	.181	.834	.166	.142	.865
	GCG	W	.300	.110	.530	.178	.101	.379	.194	.090	.374	<b>.208</b>	.102	.321	.199	.080	.422
	Ours	B	<b>.325</b>	.096	.864	<b>.232</b>	.104	.853	<b>.213</b>	.092	.838	<b>.201</b>	.084	.841	<b>.223</b>	.079	.866
Tulu	P-S-Base	B	.291	.125	-	.183	.112	-	.190	.104	-	.203	.114	-	.208	.093	-
	P-S-Inst	B	.274	.124	-	.207	.112	-	.170	.106	-	.137	.114	-	.172	.093	-
	Reverse-LM	B	.245	.200	.864	.153	.196	.848	.121	.186	.830	.117	.181	.834	.135	.142	.865
	GCG	W	.300	.110	.530	.178	.101	.379	.194	.090	.374	.208	.102	.321	.199	.080	.422
	Ours	B	<b>.359</b>	.104	.857	<b>.237</b>	.104	.851	<b>.221</b>	.094	.835	<b>.210</b>	.086	.836	<b>.233</b>	.079	.865
Seq Len	Tulu-7B																
200	P-S-Base	B	.315	.126	-	.188	.107	-	.198	.103	-	.206	.111	-	.225	.090	-
	P-S-Inst	B	.298	.125	-	<b>.216</b>	.107	-	.176	.103	-	.140	.111	-	.188	.090	-
	Reverse-LM	B	.254	.191	.877	.154	.200	.890	.130	.203	.863	.123	.195	.862	.153	.151	.880
	GCG	W	.325	.107	.619	.189	.096	.473	.203	.087	.469	.214	.097	.404	.223	.077	.518
	Ours	B	<b>.372</b>	.098	.877	.204	.093	.883	<b>.225</b>	.104	.858	<b>.214</b>	.095	.853	<b>.236</b>	.082	.882
300	P-S-Base	B	.315	.126	-	.188	.107	-	.198	.103	-	.206	.111	-	.225	.090	-
	P-S-Inst	B	.276	.124	-	.209	.112	-	.174	.106	-	.142	.114	-	.178	.095	-
	Reverse-LM	B	.246	.203	.881	.157	.196	.853	.125	.190	.822	.116	.182	.826	.134	.145	.877
	GCG	W	.311	.109	.535	.180	.100	.390	.197	.092	.378	.212	.102	.318	.200	.080	.432
	Ours	B	<b>.341</b>	.084	.878	<b>.248</b>	.108	.856	<b>.222</b>	.099	.824	<b>.209</b>	.090	.825	<b>.231</b>	.079	.872
500	P-S-Base	B	.263	.124	-	.175	.117	-	.179	.102	-	.196	.117	-	.184	.095	-
	P-S-Inst	B	.247	.124	-	.195	.117	-	.159	.102	-	.128	.117	-	.149	.095	-
	Reverse-LM	B	.233	.204	.833	.147	.192	.803	.107	.164	.805	.112	.167	.814	.118	.129	.838
	GCG	W	.265	.113	.435	.165	.107	.274	.182	.092	.274	.196	.113	.435	.173	.085	.317
	Ours	B	<b>.363</b>	.129	.814	<b>.260</b>	.112	.809	<b>.216</b>	0.079	.824	<b>.207</b>	.074	.829	<b>.231</b>	0.076	.841

Table 1: Comparison of our method with black-box (‘B’) and white-box (‘W’) baselines across pre-training data domains. Mem denotes the memorization score (ROUGE-L),  $LCS_P$  is input prompt and suffix overlap, and Dis is optimized vs. initial prompt distance. Results are averaged over three sequence lengths on top, and for the *Tulu-7B* model, we show a breakdown at the bottom. The highest performance within each domain is bolded.

### 4.3 Baseline Methods

We compare against three methods under two access settings: white-box and black-box.

**(1) Prefix-Suffix (P-S) sequence extraction method (Carlini et al., 2022; 2021):** We apply a black box attack by prompting the model with the original prefix of the pre-training sample (i.e., the first  $n$  tokens) and generating the model output. We call this baseline the Prefix-Suffix (P-S) method. We evaluate both the base model and instruction-tuned versions.

**(2) GCG (Zou et al., 2023):** We test a prominent white-box adversarial attack method for LMs. Our application of GCG uses the original prefix as the starting point for each sample; we train for thirty epochs and apply it to the base model.

**(3) Reverse LM (Pfau et al., 2023):** This model reverses the token order during training, predicting optimized prefixes given specific suffixes, using a Pythia-160M model trained on the deduplicated Pile dataset (Pfau et al., 2023; Biderman et al., 2023b; Gao et al., 2020).

### 4.4 Evaluation Metrics

**Measuring Memorization/Reconstruction:** We evaluate memorization using ROUGE-L, measuring the longest common subsequence between generated and original suffixes. Our




Figure 2: Comparison of our method to the P-S baseline on the OLMo model. We evaluate different subsets of the pre-training data, Dolma, and observe that our method outperforms the prefix-suffix baseline consistently.

approach aligns closely with the memorization score proposed by Biderman et al. (2023a), emphasizing ordered token matches between model-generated and true continuations.

**Evaluating Prompt Overlap:** As our method relies on building a prompt on the whole sequence, including the ground truth (suffix), we measure the overlap between the prompt and suffix. We aim to ensure that the prompt retains less or equal overlap compared to the original prefix-suffix combination. We use ROUGE-L to measure the overlap between the prompt and the suffix, which we denote as  $LCS_p$ .

## 5 Experimental Results

In this section, we present our main experimental results, comparing our method to the baselines, on the base and instruction-tuned models, with different data domains and lengths. We then further analyze different components of our method, along with changing our assumption in terms of access to suffixes and data points. We provide details of hyperparameters in Appendix A, a breakdown of the results in terms of sequence lengths and improvement percentages in Appendix B, a comparison of reconstructions from different models in Appendix C, and analysis of common patterns in subsection B.1. Finally, we include samples of optimized prompts and outputs in Appendix E.

### 5.1 LLMs memorize more than we think!

Table 1, which shows our main results alongside our baselines. Except for P-S-Base & GCG, all other numbers are reported over the instruction-tuned model as the target, whereas the P-S-Base is evaluated on the base model (Llama– hence the same value on all rows), to provide a comparison point. If we only compare P-S-Inst and P-S-Base, we would make a misleading conclusion that instruction-tuned models uncover less training data than their base counterparts. Our method, surprisingly, uncovers more memorization than all other baselines, even on the base model, showing that instruction-tuned models can reveal more pre-training data, even more than the base if prompted appropriately. On Github, for instance, the base Llama model exhibits a reconstruction Rouge-L score of .291, while Tulu shows .274, with the P-S-Inst baseline. Our method increases this to .322. These trends extend beyond Llama-based models to OLMo Groeneveld et al. (2024) Figure 2 and Falcon Penedo et al. (2023). Moreover, the same trend exists for larger sizes (13B, 30B). See Appendix B for the Falcon model and larger sizes results.

If we expand our baselines and take a closer look at the white-box GCG optimization, we observe that it uncovers more memorization than P-S (sequence-extraction) attacks by 1% on average, but it still falls short of our method. Github exhibits the most significant increase across all domains, while other domains generally show improvement over sequence-extraction-based methods in most settings. ReverseLM performs the worst, possibly due to its usage in a transferability setting from the Pythia model. Details of hyperparameters can be found in Appendix A, a breakdown of the results and improvement percentages in Appendix B, and samples of optimized prompts and outputs in Appendix E.




Figure 3: Comparison of our attack performance when the prompt is optimized over only the sequence prefix (partial access) versus when we have access to the entire sequence (default assumption through the paper). Notably, the performance of attacks relying solely on prefixes closely aligns with those utilizing the entire sequence across most domains, pointing at the robustness of the optimization toward partial access to the training point.




Figure 4: A comparison of our method’s performance using Zephyr and GPT-4 as attacker LLMs is shown for different iteration steps during optimization. We observe a consistent trend: performance increases across varying sequence lengths as optimization iterations increase, and Zephyr uncovers more memorization than GPT-4 by a small margin. The dots are averaged across five domains and three instruction-tuning models.

**Measuring Overlap Between Prompts & Suffixes.** Assessing prompt-response overlap is crucial to make sure that the optimized prompt doesn’t include the pre-training data in it (i.e. make sure we are not cheating). We introduce an overlap penalty (subsection 3.1) to mitigate this. Results in Table 1 consistently show our method achieving equivalent or lower overlap ( $LCS_p$ ) in terms of ROUGE-L, with the prefix-suffix baseline. For example, our approach has significantly lower overlap in domains like GitHub, ensuring a fair comparison with baseline methods and demonstrating that prompts exist that are substantially different from the original pre-training prefix and can yet result in better reconstruction.

**PII Identification.** We assessed our method’s reconstructions to evaluate the degree of identifiable information (PII) revealed by categorizing 9,000 pre-training samples (CC, C4, Github) using regular expressions to identify various PII elements (phone, link, email, credit cards, street address, SSN, zip code). We then applied the same procedure to generate content from optimized prompts and compared results with ground truth, retrieving an average of 10.28% of PII from pre-training samples, a significant increase of 1.43 times compared to the 4.23% achieved by the prefix-suffix attack.

## 5.2 GPT-4 is NOT the best attacker!

We test GPT-4 as an alternative attacker to assess its effect on performance, finding Zephyr outperforms GPT-4 consistently for sequence length 200, maintaining superiority across all domains by a margin of 0.05 as shown in Figure 4. The performance gap narrows as the sequence length increases to 300, but Zephyr remains ahead. However, at length 500, GPT-4 starts to match or surpass Zephyr’s performance, especially notable in the ArXiv domain, possibly due to the increased difficulty of summarization with longer sequences.



### 5.3 What if we don't have access to the entire training sequence?

For a more stringent setup, we assume we only have access to prefixes and not suffixes. Our method still yields comparable results across most domains and models, revealing even higher reconstruction in some cases, as shown in Figure 3. However, prompts based on entire sequences uncover significantly more memorization in domains like Github and books due to token count discrepancies. These are resolved using a whitespace tokenizer to ensure sufficient context for prefix optimization, achieving performance parity.

### 5.4 What if we don't use GPT-4 for the Meta-prompt initialization?

In all previous experiments, we use the meta-prompts (see Section 3.2) on GPT-4 to have it create the initial prompts. However, we investigate the influence of a less powerful open-source model on the pipeline's overall performance. Our choice is Mixtral-8x7B instruct (Jiang et al., 2024). Using Alpaca and a sequence length of 200 as an example, we demonstrate that utilizing Mixtral can still surpass the reconstruction performance over the prefix-suffix method, achieving better performance than P-S for base and instruct model by 6.12% and 12.62%, respectively, and in contrast, being worse than GPT-4 by 4.00%.

### 5.5 What goes on during the optimization process?

**The impact of iteration count:** Our approach consists of two phases: sampling and refining. The former employs rejection sampling, while the latter iterates three times on the most promising prompt, offering feedback. Visualized in Figure 4, performance evolves through each optimization stage, revealing insights into the process's impact on performance. Though modest initially due to untargeted prompts, performance steadily enhances with each iteration, reaching peak performance by the third iteration. Increasing iterations could further enhance performance but at the expense of higher computational costs.

**Measuring Edit Distance:** To analyze the optimization process, we measure the gap between the initial and refined prompts using normalized Levenshtein distance, aiming for notable discrepancies to underscore its impact. Across all models, domains, and sequence lengths (as shown in Table 1), the edit distance ranges from 0.80 to 0.88, indicating substantial modifications from the initial to the optimized prompt.

## 6 Related Work

**Data Extraction:** Several studies in the literature explore data extraction techniques in LLMs, initially focusing on base models. Yu et al. (2023) proposed methods such as Top-K selection, nucleus sampling, and temperature adjustments. Nasr et al. (2023) targeted instruction-tuned models, presenting a divergence attack prompting models like ChatGPT to repeat a word despite instability issues noted indefinitely. Additionally, Zhang et al. (2023) devised a model interrogation attack, selecting lower-ranked output tokens during generation to extract sensitive user data. Furthermore, Geiping et al. (2024) introduced a system prompt repeater for extracting sensitive system prompts, demonstrating notable success in potentially compromising entire applications or secrets.

**Jailbreaking:** Emerging red-teaming methods exploit LLMs through jailbreaking techniques, aiming to coerce harmful behaviors (Shah et al., 2023; Li et al., 2023; Huang et al., 2023; Zeng et al., 2024; Mehrotra et al., 2023; Hubinger et al., 2024). These approaches disrupt safety mechanisms, prioritizing harmful responses over data confidentiality.

## 7 Conclusion and Limitations

In this work, we present a novel approach for analyzing discoverable memorization of pre-training data in instruction-tuned LLMs. Our empirical findings challenge prior assumptions by demonstrating that instruction-tuned models exhibit a higher level of memorization than their base models, using prompts other than the original prefix from the pre-training

data. We emphasize that although our method and experiments uncover more reconstruction of pre-training data in instruction-tuned models than base, this **does not mean** one model or the other is memorizing/regurgitating more data or being more or less vulnerable. It only alludes to the fact that instruction-based prompts, the way we build them, uncover more of the pre-training data in instruction-tuned models. We would also like to acknowledge that our method is mainly an auditing method which requires access to some part of the training data. We encourage future work to explore other automated strategies for building prompts for data extraction, targeting both base and instruction-tuned models, using prompts and contexts other than the original training data.

## References

- Stella Biderman, USVSN Sai Prashanth, Lintang Sutawika, Hailey Schoelkopf, Quentin Anthony, Shivanshu Purohit, and Edward Raf. Emergent and predictable memorization in large language models. *arXiv preprint arXiv:2304.11158*, 2023a.
- Stella Biderman, Hailey Schoelkopf, Quentin Gregory Anthony, Herbie Bradley, Kyle O’Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, USVSN Sai Prashanth, Edward Raff, et al. Pythia: A suite for analyzing large language models across training and scaling. In *International Conference on Machine Learning*, pp. 2397–2430. PMLR, 2023b.
- Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, et al. Extracting training data from large language models. In *30th USENIX Security Symposium (USENIX Security 21)*, pp. 2633–2650, 2021.
- Nicholas Carlini, Daphne Ippolito, Matthew Jagielski, Katherine Lee, Florian Tramer, and Chiyuan Zhang. Quantifying memorization across neural language models. *arXiv preprint arXiv:2202.07646*, 2022.
- Nicolas Carlini, Jamie Hayes, Milad Nasr, Matthew Jagielski, Vikash Sehwal, Florian Tramer, Borja Balle, Daphne Ippolito, and Eric Wallace. Extracting training data from diffusion models. In *32nd USENIX Security Symposium (USENIX Security 23)*, pp. 5253–5270, 2023.
- Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. Vicuna: An open-source chatbot impressing gpt-4 with 90%\* chatgpt quality. See <https://vicuna.lmsys.org> (accessed 14 April 2023), 2023.
- Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1–113, 2023.
- Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin, Zhi Zheng, Shengding Hu, Zhiyuan Liu, Maosong Sun, and Bowen Zhou. Enhancing chat language models by scaling high-quality instructional conversations, 2023.
- Michael Duan, Anshuman Suri, Niloofar Mireshghallah, Sewon Min, Weijia Shi, Luke Zettlemoyer, Yulia Tsvetkov, Yejin Choi, David Evans, and Hannaneh Hajishirzi. Do membership inference attacks work on large language models? *arXiv preprint arXiv:2402.07841*, 2024.
- Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, et al. The pile: An 800gb dataset of diverse text for language modeling. *arXiv preprint arXiv:2101.00027*, 2020.
- Jonas Geiping, Alex Stein, Manli Shu, Khalid Saifullah, Yuxin Wen, and Tom Goldstein. Coercing llms to do and reveal (almost) anything. *arXiv preprint arXiv:2402.14020*, 2024.

- Dirk Groeneveld, Iz Beltagy, Pete Walsh, Akshita Bhagia, Rodney Kinney, Oyvind Tafjord, Ananya Harsh Jha, Hamish Ivison, Ian Magnusson, Yizhong Wang, Shane Arora, David Atkinson, Russell Authur, Khyathi Chandu, Arman Cohan, Jennifer Dumas, Yanai Elazar, Yuling Gu, Jack Hessel, Tushar Khot, William Merrill, Jacob Morrison, Niklas Muenighoff, Aakanksha Naik, Crystal Nam, Matthew E. Peters, Valentina Pyatkin, Abhilasha Ravichander, Dustin Schwenk, Saurabh Shah, Will Smith, Nishant Subramani, Mitchell Wortsman, Pradeep Dasigi, Nathan Lambert, Kyle Richardson, Jesse Dodge, Kyle Lo, Luca Soldaini, Noah A. Smith, and Hannaneh Hajishirzi. Olmo: Accelerating the science of language models. *Preprint*, 2024.
- Yangsibo Huang, Samyak Gupta, Mengzhou Xia, Kai Li, and Danqi Chen. Catastrophic jailbreak of open-source llms via exploiting generation. *arXiv preprint arXiv:2310.06987*, 2023.
- Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte MacDiarmid, Tamera Lanham, Daniel M Ziegler, Tim Maxwell, Newton Cheng, et al. Sleeper agents: Training deceptive llms that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.
- Daphne Ippolito, Florian Tramèr, Milad Nasr, Chiyuan Zhang, Matthew Jagielski, Katherine Lee, Christopher A Choquette-Choo, and Nicholas Carlini. Preventing generation of verbatim memorization in language models gives a false sense of privacy. In *Proceedings of the 16th International Natural Language Generation Conference*, pp. 28–53. Association for Computational Linguistics, 2023.
- Hamish Ivison, Yizhong Wang, Valentina Pyatkin, Nathan Lambert, Matthew Peters, Pradeep Dasigi, Joel Jang, David Wadden, Noah A Smith, Iz Beltagy, et al. Camels in a changing climate: Enhancing lm adaptation with tulu 2. *arXiv preprint arXiv:2311.10702*, 2023.
- Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al. Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024.
- Erik Jones, Anca Dragan, Aditi Raghunathan, and Jacob Steinhardt. Automatically auditing large language models via discrete optimization. *arXiv preprint arXiv:2303.04381*, 2023.
- Xuan Li, Zhanke Zhou, Jianing Zhu, Jiangchao Yao, Tongliang Liu, and Bo Han. Deepinception: Hypnotize large language model to be jailbreaker. *arXiv preprint arXiv:2311.03191*, 2023.
- Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL <https://aclanthology.org/W04-1013>.
- Anay Mehrotra, Manolis Zampetakis, Paul Kassianik, Blaine Nelson, Hyrum Anderson, Yaron Singer, and Amin Karbasi. Tree of attacks: Jailbreaking black-box llms automatically. *arXiv preprint arXiv:2312.02119*, 2023.
- Fatemehsadat Miresghallah, Archit Uniyal, Tianhao Wang, David Evans, and Taylor Berg-Kirkpatrick. An empirical analysis of memorization in fine-tuned autoregressive language models. In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 1816–1826, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.119. URL <https://aclanthology.org/2022.emnlp-main.119>.
- Milad Nasr, Nicholas Carlini, Jonathan Hayase, Matthew Jagielski, A Feder Cooper, Daphne Ippolito, Christopher A Choquette-Choo, Eric Wallace, Florian Tramèr, and Katherine Lee. Scalable extraction of training data from (production) language models. *arXiv preprint arXiv:2311.17035*, 2023.

- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35:27730–27744, 2022.
- Guilherme Penedo, Quentin Malartic, Daniel Hesslow, Ruxandra Cojocaru, Alessandro Cappelli, Hamza Alobeidli, Baptiste Pannier, Ebtesam Almazrouei, and Julien Launay. The refinedweb dataset for falcon llm: outperforming curated corpora with web data, and web data only. *arXiv preprint arXiv:2306.01116*, 2023.
- Jacob Pfau, Alex Infanger, Abhay Sheshadri, Ayush Panda, Julian Michael, and Curtis Huebner. Eliciting language model behaviors using reverse language models. In *Socially Responsible Language Modelling Research*, 2023.
- Aman Priyanshu, Supriti Vijay, Ayush Kumar, Rakshit Naidu, and Fatemehsadat Mireshghallah. Are chatbots ready for privacy-sensitive applications? an investigation into input regurgitation and prompt-induced sanitization. *arXiv preprint arXiv:2305.15008*, 2023.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36, 2024.
- Rusheb Shah, Soroush Pour, Arush Tagade, Stephen Casper, Javier Rando, et al. Scalable and transferable black-box jailbreaks for language models via persona modulation. *arXiv preprint arXiv:2311.03348*, 2023.
- Weijia Shi, Anirudh Ajith, Mengzhou Xia, Yangsibo Huang, Daogao Liu, Terra Blevins, Danqi Chen, and Luke Zettlemoyer. Detecting pretraining data from large language models. *arXiv preprint arXiv:2310.16789*, 2023.
- Luca Soldaini, Rodney Kinney, Akshita Bhagia, Dustin Schwenk, David Atkinson, Russell Authur, Ben Bogin, Khyathi Chandu, Jennifer Dumas, Yanai Elazar, Valentin Hofmann, Ananya Harsh Jha, Sachin Kumar, Li Lucy, Xinxin Lyu, Nathan Lambert, Ian Magnusson, Jacob Morrison, Niklas Muennighoff, Aakanksha Naik, Crystal Nam, Matthew E. Peters, Abhilasha Ravichander, Kyle Richardson, Zejiang Shen, Emma Strubell, Nishant Subramani, Oyvind Tafjord, Pete Walsh, Luke Zettlemoyer, Noah A. Smith, Hannaneh Hajishirzi, Iz Beltagy, Dirk Groeneveld, Jesse Dodge, and Kyle Lo. Dolma: an Open Corpus of Three Trillion Tokens for Language Model Pretraining Research. *arXiv preprint*, 2024.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Alpaca: A strong, replicable instruction-following model. *Stanford Center for Research on Foundation Models*. <https://crfm.stanford.edu/2023/03/13/alpaca.html>, 3(6):7, 2023.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.
- Lewis Tunstall, Edward Beeching, Nathan Lambert, Nazneen Rajani, Kashif Rasul, Younes Belkada, Shengyi Huang, Leandro von Werra, Clémentine Fourrier, Nathan Habib, et al. Zephyr: Direct distillation of lm alignment. *arXiv preprint arXiv:2310.16944*, 2023.
- Tony Tong Wang, Adam Gleave, Tom Tseng, Kellin Pelrine, Nora Belrose, Joseph Miller, Michael D Dennis, Yawen Duan, Viktor Pogrebnik, Sergey Levine, et al. Adversarial policies beat superhuman go ais. 2023a.
- Yizhong Wang, Hamish Ivison, Pradeep Dasigi, Jack Hessel, Tushar Khot, Khyathi Chandu, David Wadden, Kelsey MacMillan, Noah A. Smith, Iz Beltagy, and Hannaneh Hajishirzi. How far can camels go? exploring the state of instruction tuning on open resources. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023b. URL <https://openreview.net/forum?id=w4zZNC4ZaV>.

- Canwen Xu, Daya Guo, Nan Duan, and Julian McAuley. Baize: An open-source chat model with parameter-efficient tuning on self-chat data. *arXiv preprint arXiv:2304.01196*, 2023.
- Weichen Yu, Tianyu Pang, Qian Liu, Chao Du, Bingyi Kang, Yan Huang, Min Lin, and Shuicheng Yan. Bag of tricks for training data extraction from language models. *arXiv preprint arXiv:2302.04460*, 2023.
- Yi Zeng, Hongpeng Lin, Jingwen Zhang, Diyi Yang, Ruoxi Jia, and Weiyan Shi. How johnny can persuade llms to jailbreak them: Rethinking persuasion to challenge ai safety by humanizing llms. *arXiv preprint arXiv:2401.06373*, 2024.
- Yiming Zhang and Daphne Ippolito. Prompts should not be seen as secrets: Systematically measuring prompt extraction attack success. *arXiv preprint arXiv:2307.06865*, 2023.
- Zhuo Zhang, Guangyu Shen, Guanhong Tao, Siyuan Cheng, and Xiangyu Zhang. Make them spill the beans! coercive knowledge extraction from (production) llms. *arXiv preprint arXiv:2312.04782*, 2023.
- Wenting Zhao, Xiang Ren, Jack Hessel, Claire Cardie, Yejin Choi, and Yuntian Deng. (inthe)wildchat: 570k chatGPT interaction logs in the wild. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=B18u7ZR1bM>.
- Andy Zou, Zifan Wang, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

## A Hyperparameters Optimization

To ascertain the ideal hyperparameter balancing between memorization and overlap across diverse domains and sequence lengths, we initially streamlined our process by optimizing 20% of the dataset for quicker runtime. This entails iterating through multiple values to pinpoint the one that best aligns with our objectives. Subsequently, the selected values are applied to the entire dataset.

We select the following values for Llama-based models:

For a sequence length of 200, we allocate weights of 0.4 for memorization and 0.6 for overlap, a configuration tailored for C4, CC, and GitHub. Conversely, for ArXiv and Books, the emphasis shifts slightly, with 0.2 assigned to memorization and 0.8 to overlap.

At a sequence length of 300, nuances emerge across domains; for CC and C4, an even balance at 0.5 for memorization and overlap is determined. However, GitHub and ArXiv prefer a 0.4-0.6 split, favoring overlap slightly more. Conversely, Books lean towards a 0.3-0.7 ratio, emphasizing overlap more.

The weighting intensifies for a sequence length of 500, with C4, CC, and ArXiv converging at 0.5 for both memorization and overlap. GitHub adopts a 0.6-0.4 distribution, while Books adhere to a 0.4-0.6 allocation for memorization and overlap.

For the Falcon model, the designated values are as follows: For a sequence length of 200, we allocate a weight of 0.2 for memorization and 0.8 for overlap. With a sequence length of 300, the distribution shifts to 0.3 for memorization and 0.7 for overlap. Lastly, for a sequence length of 500, the weight is set at 0.8 for memorization and 0.2 for overlap.

## B Detailed Results

### B.1 Breakdown of Results from Section 5

In this section, we present a detailed breakdown of results for each instruction-tuned model, encompassing Alpaca, Tulu, and Vicuna, as depicted in Table 2. Figure 5 Shows a breakdown based on sequence length.




Figure 5: A detailed breakdown of the results presented in Table 1, over different sequence lengths and data domains for our proposed method. We can see that the instruction-tuned models demonstrate higher memorization scores (Rouge-L) compared to the base model. The full breakdown table, including the baseline methods, is provided in Appendix Table 2.

Alpaca-7B																	
Sequence	Method	Access	Github			ArXiv			CC			C4			Books		
			Mem	LCS <sub>P</sub>	Dis	Mem	LCS <sub>P</sub>	Dis	Mem	LCS <sub>P</sub>	Dis	Mem	LCS <sub>P</sub>	Dis	Mem	LCS <sub>P</sub>	Dis
			↑	↓	↑	↑	↓	↑	↑	↓	↑	↑	↓	↑	↑	↓	↑
200	P-S-Base	B	.315	.125	-	.188	.107	-	.198	.103	-	.206	.111	-	.225	.090	-
	P-S-Inst	B	.294	.125	-	.200	.107	-	.168	.103	-	.152	.111	-	.153	.090	-
	Reverse-LM	B	.242	.191	.877	.141	.200	.890	.124	.203	.863	.117	.195	.862	.137	.151	.880
	GCG	W	.325	.107	.619	.189	.096	.473	.203	.087	.469	.214	.097	.404	.223	.077	.518
	Ours	B	<b>.362</b>	.102	.877	<b>.205</b>	.091	.890	<b>.227</b>	.101	.863	<b>.213</b>	.0939	.862	<b>.247</b>	.083	.880
300	P-S-Base	B	.295	.124	-	.186	.112	-	.193	.106	-	.208	.114	-	.213	.095	-
	P-S-Inst	B	.273	.124	-	.183	.112	-	.160	.106	-	.153	.114	-	.136	.095	-
	Reverse-LM	B	.232	.203	.881	.133	.145	.853	.117	.190	.822	.109	.182	.826	.123	.145	.877
	GCG	W	.311	.109	.535	.180	.100	.390	.197	.092	.378	.212	.102	.318	.200	.080	.432
	Ours	B	<b>.330</b>	.087	.881	<b>.244</b>	.110	.853	<b>.222</b>	.100	.822	<b>.209</b>	.094	.826	<b>.228</b>	.077	.877
500	P-S-Base	B	.263	.124	-	.175	.117	-	.179	.102	-	.196	.117	-	.184	.095	-
	P-S-Inst	B	.241	.124	-	.154	.117	-	.138	.102	-	.124	.117	-	.104	.095	-
	Reverse-LM	B	.214	.204	.833	.125	.192	.803	.099	.164	.805	.104	.167	.814	.105	.129	.838
	GCG	W	.265	.113	.435	.165	.107	.274	.182	.092	.274	.196	.113	.435	.173	.085	.317
	Ours	B	<b>.275</b>	.117	.833	<b>.234</b>	.122	.803	<b>.193</b>	.087	.805	<b>.186</b>	.083	.814	<b>.189</b>	.076	.838
Tulu-7B																	
200	P-S-Base	B	.315	.126	-	.188	.107	-	.198	.103	-	.206	.111	-	.225	.090	-
	P-S-Inst	B	.298	.125	-	.216	.107	-	.176	.103	-	.140	.111	-	.188	.090	-
	Reverse-LM	B	.254	.191	.877	.154	.200	.890	.130	.203	.863	.123	.195	.862	.153	.151	.880
	GCG	W	.325	.107	.619	.189	.096	.473	.203	.087	.469	.214	.097	.404	.223	.077	.518
	Ours	B	<b>.372</b>	.098	.877	<b>.204</b>	.093	.883	<b>.225</b>	.104	.858	<b>.214</b>	.095	.853	<b>.236</b>	.082	.882
300	P-S-Base	B	.315	.126	-	.188	.107	-	.198	.103	-	.206	.111	-	.225	.090	-
	P-S-Inst	B	.276	.124	-	.209	.112	-	.174	.106	-	.142	.114	-	.178	.095	-
	Reverse-LM	B	.246	.203	.881	.157	.196	.853	.125	.190	.822	.116	.182	.826	.134	.145	.877
	GCG	W	.311	.109	.535	.180	.100	.390	.197	.092	.378	.212	.102	.318	.200	.080	.432
	Ours	B	<b>.341</b>	.084	.878	<b>.248</b>	.108	.856	<b>.222</b>	.099	.824	<b>.209</b>	.090	.825	<b>.231</b>	.079	.872
500	P-S-Base	B	.263	.124	-	.175	.117	-	.179	.102	-	.196	.117	-	.184	.095	-
	P-S-Inst	B	.247	.124	-	.195	.117	-	.159	.102	-	.128	.117	-	.149	.095	-
	Reverse-LM	B	.233	.204	.833	.147	.192	.803	.107	.164	.805	.112	.167	.814	.118	.129	.838
	GCG	W	.265	.113	.435	.165	.107	.274	.182	.092	.274	.196	.113	.435	.173	.085	.317
	Ours	B	<b>.363</b>	.129	.814	<b>.260</b>	.112	.809	<b>.216</b>	0.079	.824	<b>.207</b>	.074	.829	<b>.231</b>	0.076	.841
Vicuna-7B																	
200	P-S-Base	B	.315	.126	-	.188	.107	-	.198	.103	-	.206	.111	-	.225	.090	-
	P-S-Inst	B	.311	.125	-	.225	.107	-	.215	.103	-	.205	.111	-	.212	.090	-
	Reverse-LM	B	.256	.191	.877	.199	.200	.890	.179	.203	.863	.180	.195	.862	.181	.151	.880
	GCG	W	.325	.107	.619	.189	.096	.473	.203	.087	.469	.214	.097	.404	.223	.077	.518
	Ours	B	<b>.327</b>	.094	.883	<b>.199</b>	.095	.888	<b>.214</b>	.100	.867	<b>.200</b>	.090	.866	<b>.221</b>	.083	.881
300	P-S-Base	B	.315	.126	-	.188	.107	-	.198	.103	-	.206	.111	-	.225	.090	-
	P-S-Inst	B	.267	.124	-	.194	.112	-	.208	.106	-	.182	.115	-	.189	.095	-
	Reverse-LM	B	.261	.203	.881	.204	.196	.853	.177	.190	.822	.173	.182	.826	.168	.145	.877
	GCG	W	.311	.109	.535	.180	.100	.390	.197	.092	.378	.212	.102	.318	.200	.080	.432
	Ours	B	<b>.311</b>	.078	.885	<b>.241</b>	.106	.854	<b>.215</b>	.097	.824	<b>.201</b>	.087	.833	<b>.217</b>	.076	.877
500	P-S-Base	B	.263	.124	-	.175	.117	-	.179	.102	-	.196	.117	-	.184	.095	-
	P-S-Inst	B	.241	.125	-	.219	.117	-	.193	.102	-	.188	.117	-	.192	.095	-
	Reverse-LM	B	.247	.204	.833	.198	.192	.803	.163	.164	.805	.166	.167	.814	.149	.129	.838
	GCG	W	.265	.113	.435	.165	.107	.274	.182	.092	.274	.196	.113	.435	.173	.085	.317
	Ours	B	<b>.336</b>	.116	.823	<b>.255</b>	.109	.817	<b>.210</b>	0.079	.823	<b>.202</b>	.075	.825	<b>.233</b>	0.078	.838

Table 2: Memorization scores (Mem), overlap between the prompts and suffix (LCS<sub>P</sub>), and the distance between optimized and initial prompts (Dis) is evaluated across various pre-training data domains, evaluated across five scenarios: P-S-Base (sequence extraction on Llama), P-S-Inst (sequence extraction on the instruction-tuned model), Reverse-LM, GCG, and our method. Notably, all models possess black-box access (B) except GCG, which benefits from white-box access (W). The highest performance within each domain is highlighted in bold.

## B.2 Improvement Percentages

To gauge the degree of enhancement relative to other baseline methods, we performed the following calculation: for each sequence length, domain, and model, we subtracted our method’s performance from that of each method and then divided the result by the performance of the other method. This allowed us to assess our method’s relative superiority or inferiority compared to the other method. The results shown in Table 3

Domain	Sequence Length	Alpaca			Tulu			Vicuna		
		P-S-INST	P-S-BASE	GCG	P-S-INST	P-S-BASE	GCG	P-S-INST	P-S-BASE	GCG
Github	200	.230	.149	.115	.249	.180	.145	.054	.039	.008
	300	.201	.119	.063	.232	.154	.096	.166	.055	.002
	500	.139	.042	.036	.467	.378	.370	.391	.273	.266
CC	200	.352	.144	.118	.279	.136	.111	-.003	.079	.055
	300	.387	.149	.127	.274	.146	.123	.030	.109	.087
	500	.399	.079	.062	.354	.206	.186	.089	.174	.156
C4	200	.401	.034	.005	.527	.035	-.004	-.022	-.029	-.066
	300	.367	.002	-.014	.469	.035	-.016	.107	-.034	-.051
	500	.497	-.005	-.053	.612	.057	.054	.075	.0297	.026
Books	200	.613	.095	.106	.250	.047	.057	.040	.018	-.009
	300	.681	.069	.142	.299	.081	.154	.144	.015	.084
	500	.809	.025	.089	.552	.252	.331	.210	.261	.340
ArXiv	200	.025	.090	.087	-.057	.080	.077	-.116	.057	.054
	300	.332	.313	.357	.187	.336	.380	.241	.296	.339
	500	.519	.334	.421	.331	.478	.574	.162	.449	.544

Table 3: Improvement percentages across diverse domains, sequence lengths, and models. P-S-INST denotes our method’s performance subtracted from P-S-INST performance and then divided on the latter, with similar comparisons for other methods.

## B.3 Falcon Results

In this section, we present a detailed breakdown of results for the Falcon as depicted in Figure 6 with a breakdown based on sequence length.




Figure 6: Comparison of our method to the P-S baseline on the Falcon model. We evaluate different sequence lengths of the pre-training data and observe that our method consistently outperforms the prefix-suffix base and instruction versions.

## B.4 Common Patterns

To analyze the evolution from initial to optimized prompts, we examined common patterns by extracting the most frequent n-grams (n ranging from 1 to 5) in the optimized prompts. However, replacing these optimized n-grams with their counterparts in the initial prompts did not improve performance. This is because the transformation operates at the sentence level, where specific n-gram modifications—additions, deletions, or replacements—do not significantly impact the overall performance, given the complex interplay of various operations in the sentence-level transformation process.



### B.5 Larger Sizes

In this section, we show the results for larger sizes, Alpaca-13B and Tulu-30B. We observed the same trend of our method in the larger sizes, as shown in Figure 7 and Figure 8. Note that we could only run 30B experiments on sequence length 200 and three subsets due to limited computational resources.




Figure 7: Comparison of our method to the P-S baseline on the Tulu-30B model. We evaluate different domains of the pre-training data and observe that our method consistently outperforms the prefix-suffix base and instruction versions.




Figure 8: Comparison of our method to the P-S baseline on the Alpaca-13B model. We evaluate different domains of the pre-training data and observe that our method consistently outperforms the prefix-suffix base and instruction versions.

## C Similarity Analysis on Different Instruction Tuned Models

This section delves into an error analysis of the instruction-tuned models utilizing the prefix-suffix and our optimization approach. We delve into the correlation, edit distance, and cosine similarity across the optimization prompt’s scores. Table 4 visually encapsulates the proximity of prompts from each model to one another. The initial part showcases the cosine similarity; notably, the similarity between the scores of the optimized prompts and the prefix-suffix exhibits lower similarity, while a substantially high similarity exists between the optimized prompts for each model, averaging around 90%.

Furthermore, upon computing the  $L_2$  distance, a pattern emerges with a notable increase in distance between optimized prompts and prefix scores. Conversely, the distance shrinks significantly between the optimized prompts for various models. A similar trend unfolds in correlation analysis, wherein the correlation between the scores of the optimized prompts is notably high, contrasting with the lower correlation observed between the optimized and prefix-suffix.

These findings underscore the efficacy of the optimization process in generating very similar prompts for attacking various instruction-tuning models, which can indicate the universality of the optimized prompts.

<i>Cosine Similarity</i>					
Models (Ours)	Llama-7B (P-S-Base)	Tulu		Vicuna	
		P-S-Inst	Ours	P-S-Inst	Ours
Alpaca	.815	.835	.915	.838	.881
Vicuna	.822	.807	.903	-	-
Tulu	.837	-	-	-	-
<i>L<sub>2</sub>-Distance</i>					
Alpaca	7.90	7.46	5.61	7.41	6.38
Vicuna	7.20	7.46	5.87	-	-
Tulu	7.50	-	-	-	-
<i>Correlation</i>					
Alpaca	.491	.512	.689	.477	.569
Vicuna	.410	.416	.636	-	-
Tulu	.509	-	-	-	-

Table 4: Comparison of Cosine Similarity, L2 Distance, and Correlation between Instruction-Tuned Models (Alpaca, Tulu, Vicuna) and Llama-7B using Prefix-Suffix and our proposed attack.

## D Models & Evaluation Data Details

**Attacker LLMs:** Our attack strategy primarily relies on harnessing an open-source model known as Zephyr 7B  $\beta$  (Tunstall et al., 2023) as the attacker. This instruction-tuned variant of the Mistral-7B model has been fine-tuned on Ultra-Chat and Ultra-Feedback datasets (Ding et al., 2023) through DPO (Rafailov et al., 2024). Zephyr 7B  $\beta$  has demonstrated promising performance, particularly excelling in tasks related to writing and mathematics, despite its more compact size compared to larger models.

**Victim LLMs** We assess the memorization capabilities of instruction-tuned LLMs compared to their base model across various sizes by applying our attack on five open-source models of different sizes by employing the instruction-tuned versions of Llama (Touvron et al., 2023), OLMo (Groeneveld et al., 2024), and Falcon (Penedo et al., 2023). By comparing these instruction-tuned models to their base model, we gain insights into the impact of instruction-tuning on memorization.

*Llama-based LLMs:* Llama is known for its diverse instruction-tuned versions, each trained on various proprietary datasets. (1) Alpaca (7B, 13B; Taori et al. 2023) is an early attempt at open-sourcing instruction-tuned models by fine-tuning on 52K instruction-following demonstrations generated from GPT-3.5. (2) Vicuna (7B Chiang et al. 2023) is built through fine-tuning on 70K user-shared ChatGPT data, it showed competitive performance compared to OpenAI ChatGPT and surpassed Llama and Alpaca models. (3) Tulu (7B, 30B; Wang et al. 2023b) is fine-tuned on human+GPT data mixture of instruction-output pairs.

*Falcon:* The base model was trained on 1,000B tokens of RefinedWeb (RW) with curated corpora. We compare Falcon-Instruct 7B, an instruction-tuned version further trained on the Baize dataset (Xu et al., 2023).

*OLMo:* Open Language Models is a state-of-the-art 7 billion, open-source large language model released with full access to its inner workings and massive training data. OLMo trained on Dolma Soldaini et al. (2024) with 2.5T tokens. We compare OLMo-Instruct 7B, an

instruction-tuned version further trained on Tulu 2 SFT Mix and Ultrafeedback Cleaned Iverson et al. (2023).

**Data Domains** To ensure comprehensive coverage of the pre-training data, we select 15,000 samples from five domains of the Llama data: Github (code), C4, CC (general knowledge), Arxiv (scientific papers), and Books. Each domain consists of 1,000 samples, totaling 5,000 for each of the three sequence lengths. For Falcon, we randomly select 3,000 samples from the RefinedWeb (RW), distributing 1,000 samples evenly across each sequence length. While for OLMo, we select 16,000 samples from six domains: The Stack (code), C4, CC (general knowledge), Reddit (social media), PeS2o (STEM papers), and Project Gutenberg (books). We followed the same splitting as in Llama, as each domain consists of 1,000 samples, totaling 6,000 for each of the three sequence lengths.

**Sequence Lengths Selection** To assess the resilience of our attack against different sequence lengths, we choose three: 200, 300, and 500. To better represent real-world usage, we choose the ratio of splitting each sample into prefix-suffix pairs based on analysis of the WildChat dataset (Zhao et al., 2024), which comprises 570K user-ChatGPT conversations spanning various languages and prompts. For each sequence length  $l$ , we provide the model with 33% of the sample as a prefix, while the remaining 67% serves as a suffix. For a length of 200 tokens, we allocate 66 for prefixes and 134 for suffixes. For 300 tokens, the divide is 100 for prefixes and 200 for suffixes. For 500 tokens, it is 167 for prefixes and 333 for suffixes.

## E Examples of Instruction-Based Prompts

Prompt Type	Text	Mem $\uparrow$	LCS <sub>P</sub> $\downarrow$
Initial Prompt	Generate a code snippet in Java that defines a class GetPrimaryKeysOperation which extends MetadataOperation. The class should be part of the package org.apache.hive.service.cli.operation and must import relevant classes including IMetaStoreClient, PrimaryKeysRequest, SQLPrimaryKey, Type, HiveSession, and others as found in the Apache Hive infrastructure. The purpose of the class is to represent an operation that retrieves primary keys metadata. The class should also have comments indicating that it relates to obtaining primary keys, indicating that the TABLE.CAT and TABLE.SCHEM fields may be null.	.096	.075
Optimized Prompt	How can one implement the GetPrimaryKeysOperation class in Apache Hive and what are the functions of IMetaStoreClient, PrimaryKeysRequest, SQLPrimaryKey, Type, and HiveSession during this process?	.490	.075

Prompt Type	Text	Mem $\uparrow$	LCS <sub>P</sub> $\downarrow$
Initial Prompt	Generate a code snippet for an XML layout used in an Android application that includes a vertical LinearLayout as the root element with match_parent attributes for both layout_width and layout_height. Within this LinearLayout, include two ImageView components, each with an id (main_imageview and main_imageview2 respectively), wrap_content for layout_width and layout_height. Also, add a Button with an id of testRx.button, match_parent for layout_width, and wrap_content for layout_height.	.629	.562
Optimized Prompt	Design a portrait orientation XML layout for an Android app using LinearLayout as the root element, with a fill_parent size attribute to occupy the entire screen horizontally and vertically? Inside this root LinearLayout, add two ImageView components side by side and place a Button component at the bottom, taking the entire horizontal width but a certain height. Make sure to give each element a unique ID during the process.	.895	.125

Prompt Type	Text	Mem $\uparrow$	LCS <sub>P</sub> $\downarrow$
Initial Prompt	Generate a code snippet that includes a copyright and licensing header, common in many source files. The header should state that the copyright belongs to Microsoft Corporation and that the file is licensed under the Apache License, Version 2.0. Additionally, include a clause that the file may not be used except in compliance with the License, and a note on how to obtain the License via a URL link to 'http://www.apache.org/licenses/LICENSE-2.0'. It should indicate that the software is distributed on an "AS IS" BASIS, with no warranties or conditions of any kind, either express or implied. Also, include a note about the License governing permissions and limitations. After the header, write a using directive to include the 'System.Collections.Generic' namespace and declare a namespace called 'Microsoft.Azure.Commands.Compute'.	.575	.523
Optimized Prompt	In modern software development, its crucial to include a copyright and licensing header in your source files to clearly state the ownership and distribution rights of your code. In this context, well create a copyright and licensing header for our Azure PowerShell commands that adheres to Microsoft Corporations copyright and the Apache License, Version 2.0. Heres our code snippet:	.938	.158

Prompt Type	Text	Mem $\uparrow$	LCS <sub>P</sub> $\downarrow$
Initial Prompt	Can you create an instructional guide on the topic "How to Remove my FB Account," addressing concerns such as feeling overwhelmed by unnecessary posts, desiring privacy, and annoyance from continuous notifications, while also providing a solution for those undecided on whether to leave permanently by explaining the difference between deactivating (which maintains friendships for potential future reactivation) and permanently deleting a Facebook account, and ends with an instruction to 'click' for the final step?	.148	.095
Optimized Prompt	permanently or temporarily remove my presence from Facebook to avoid irrelevant content, notifications, and protect my privacy? What are the variances between these two options?	.269	.043

Prompt Type	Text	Mem $\uparrow$	LCS <sub>P</sub> $\downarrow$
Initial Prompt	What is a quilting technique that involves creating patterns such as letters and numbers by maneuvering the fabric freely under the needle, using colored threads and flowing letter stencils to enhance the design, which also involves tracing the design onto lightweight paper, pinning to the fabric, and sewing along the lines with the feed dogs disengaged as per the sewing machine's owner's manual?	.049	.028
Optimized Prompt	use free motion quilting to create text designs using colored threads and letter stencils? What is the process involved, including transferring the design onto paper, securing it to the fabric, and sewing with the feed dogs disengaged, as detailed in the sewing machine manual?	.288	.125
Initial Prompt	What is the content of the Introduction section, labeled 'sec1,' that outlines the origins of the directed power graph notation $\overrightarrow{P}(S)$ of a semigroup $S$ , as established by Kelarev and Quinn, and includes the definition provided by these authors in which each arc represents an exponentiation relationship between semigroup elements, as well as the subsequent definition of an (undirected) power graph $P(S)$ by Chakrabarty et al., along with its criterion for vertex adjacency?	.236	.253
Optimized Prompt	In the works of Kelarev and Quinn, as well as in the research by Chakrabarty et al., what is the significance behind the notation $\overrightarrow{P}(S)$ for directed power graphs, and how does it differ from the undirected version $P(S)$ that they all define?	.400	.106



Prompt Type	Text	Mem $\uparrow$	LCS <sub>P</sub> $\downarrow$
Initial Prompt	Can you create an introductory paragraph for a mathematical text that defines the exponential growth rate of a finitely generated group with respect to a finite generating set, detailing the set of elements within a given word length as well as the formula used to determine whether the group has exponential growth based on the limit of the cardinality of that set to the power of the reciprocal of the word length?	.195	.169
Optimized Prompt	How can we understand the concept of exponential growth rate in the study of finite groups, specifically in terms of the size of sets of elements with a fixed word length and a formula based on the limit of these sizes raised to the power of the word lengths reciprocal? This section will define this growth rate and elucidate its importance in the context of group theory.	.366	.112

Prompt Type	Text	Mem $\uparrow$	LCS <sub>p</sub> $\downarrow$
Initial Prompt	What are the key differences between Certificates of Deposits (CDs) and government bonds as investment options according to MyBankTracker, and how does the explanation by Simon Zhen help an individual with limited resources determine which investment is more suitable for their savings strategy?	.185	.202
Optimized Prompt	How does MyBankTracker differentiate between Certificates of Deposit (CDs) and government bonds, and how can someone with limited resources determine which investment option is more suitable for their savings strategy based on Simon Zhens explanation?	.292	.080

Prompt Type	Text	Mem $\uparrow$	LCS <sub>P</sub> $\downarrow$
Initial Prompt	Can you provide an account of the narrative presented on "This American Life" about the incident from the summer of 1951 in small-town Wisconsin, where two baby girls were accidentally switched at birth and taken home by the wrong families, focusing on how host Ira Glass introduced the characters Kay McDonald and Mary Miller, the impact of Mary Miller revealing the secret after 43 years through letters to Sue and Marti, the daughters involved, and the exploration of the emotional aftermath by reporter Jake Halpern, including the perspectives of the mothers and their struggle with the truth, as part of an episode which also featured other segments such as a historical article about a slave auction, a review of William Kane's case, and a segment titled "Strength In Numbers"?	.126	.219
Optimized Prompt	Could you retell the tale shared on This American Lives podcast from the summer of 1951 in a small Wisconsin town, detailing the unintentional swapping of newborns between families bearing the names Kay McDonald and Mary Miller? Please include the introduction of critical characters, the ramifications brought about by Mary Millers disclosure following forty-three years, as well as the sentimental reaction explored by reporter Jake Halpern, while also mentioning any other sections included in the episode.	.241	.103