collapse: Advanced and Fast Statistical Computing and Data Transformation in R

Sebastian Krantz 💿

Kiel Institute for the World Economy

Abstract

collapse is a large C/C++-based infrastructure package facilitating complex statistical computing, data transformation, and exploration tasks in R - at outstanding levels of performance and memory efficiency. It also implements a class-agnostic approach to R programming, supporting vector, matrix and data frame-like objects and their popular variants (e.g., 'factor', 'ts', 'xts', 'tibble', 'data.table', 'sf'), enabling its seamless integration with large parts of the R ecosystem. This article introduces the package's key components and design principles in a structured way, supported by a rich set of examples. A small benchmark demonstrates its computational performance.

Keywords: statistical computing, vectorization, data manipulation and transformation, summary statistics, class-agnostic programming, R.

1. Introduction

 $collapse^1$ is a large C/C++-based R package that provides an integrated suite of statistical and data manipulation functions. Most of these statistical functions are vectorized along multiple dimensions (notably along groups and columns) and perform high-cardinality operations² very efficiently. It also offers vectorizations for advanced operations such as weighted statistics (including mode and quantiles), functions and classes for fully indexed (time-aware) computations on time series and panel data, recursive (list-processing) tools to deal with nested data and advanced descriptive statistical tools. This functionality is supported by efficient algorithms for intensive operations like grouping, unique values, matching, ordering, etc., tailored to R's data structures, and powerful data manipulation functions. The package also supplies many features for memory efficient R programming, such as data transformation and math by reference, and aversion of logical vectors. collapse is class-agnostic, i.e., it provides most statistical operations for atomic vectors, matrices, and data frames/lists, and seamlessly supports key variants of these objects used in the R ecosystem (e.g., 'tibble', 'data.table', 'sf', 'xts', 'pdata.frame'). It is globally and interactively configurable, which includes setting different defaults for key function arguments (such as na.rm arguments to statistical functions, default TRUE), and modifying the package namespace itself.³

¹Website: https://sebkrantz.github.io/collapse/

²With many columns and/or groups relative to data size.

³collapse's namespace is fully compatible with base R and the tidyverse, but can be interactively modified to overwrite key functions like unique, match, %in%, table, subset, mutate, summarise etc. with much faster collapse equivalents. See Section 8.

What is the purpose of combining all of this in a package? The short answer is to make computations in R as flexible and powerful as possible. The more elaborate answer is to (1) facilitate complex data transformation, exploration, and computing tasks in R; (2) increase performance and parsimony by avoiding R-level repetition;⁴ (3) increase the memory efficiency and flexibility of R programs;⁵ and (4) to create a new foundation package for statistics and data manipulation in R that implements successful ideas developed in the R ecosystem and other programming environments such as Python or STATA (StataCorp LLC. 2023), including some new ideas, in a stable, high performance, and broadly compatible manor.⁶

R already has a large and tested data manipulation and statistical computing ecosystem. Notably, the tidyverse (Wickham et al. 2019) provides a consistent toolkit for data manipulation in R, centered around the 'tibble' (Müller and Wickham 2023) object and tidy data principles (Wickham 2014). data.table (Dowle and Srinivasan 2023) provides an enhanced high-performance data frame with parsimonious data manipulation syntax. sf (Pebesma 2018) provides a data frame for spatial data and supporting functionality. tsibble (Wang et al. 2020) and xts (Ryan and Ulrich 2023) provide classes and operations for time series data, the former via an enhanced 'tibble', the latter through an efficient matrix-based class. Econometric packages like **plm** (Croissant and Millo 2008) and **fixest** (Bergé 2018) also provide solutions to deal with panel data and irregularity in the time dimension. Packages like matrixStats (Bengtsson 2023) and Rfast (Papadakis et al. 2023) offer fast statistical calculations along the rows and columns of matrices and faster basic statistical procedures. DescTools (Signorell 2023) provides a wide variety of descriptive statistics, including weighted versions. survey (Lumley 2004) allows statistical computations on complex survey data. labelled (Larmarange 2023) provides tools to deal with labelled data. Packages like tidyr (Wickham et al. 2023b), purrr (Wickham and Henry 2023) and rrapply (Chau 2022) provide some functions to deal with nested data and messy structures.

collapse relates to and integrates key elements from these projects. It offers tidyverse-like data manipulation at the speed and stability of data.table for any data frame-like object. It can turn any vector/matrix/data frame into a time-aware indexed series or frame and perform operations such as lagging, differencing, scaling or centering, encompassing and enhancing core manipulation functionality of plm, fixest, and xts. It also performs fast (grouped, weighted) statistical computations along the columns of matrix-like objects, complementing and enhancing matrixStats and Rfast. Its low-level vectorizations and workhorse algorithms are accessible at the R and C-levels, unlike data.table, where most vectorizations and algorithms are internal. It also supports variable labels and intelligently preserves attributes of all objects, complementing labelled. It provides general (recursive) tools to deal with nested data, enhancing tidyr, purr, and rrapply. Finally, it provides a small but consistent and powerful

 $^{^4 \}rm Such$ as applying R functions across columns or split-apply-combine computing to apply functions across groups or other divisions of data.

⁵E.g., by avoiding object conversions and the need for certain classes to do certain things, such as converting to data frame or 'data.table' to do something "by groups" and then convert back to matrix to continue with linear algebra, and in general to reduce the need for metaprogramming.

⁶Examples of such ideas are **tidyverse** syntax, vectorized aggregations (**data.table**), data transformation by reference (Python, **pandas**), vectorized and verbose joins (**polars**, **STATA**), indexed time series and panel data (**xts**, **plm**), summary statistics for panel data (**STATA**), reshaping labelled data (myself) etc...

Sebastian Krantz

set of descriptive statistical tools, yielding sufficient detail for most data exploration purposes, requiring users to invoke packages like **DescTools** or **survey** only for specific statistics. In summary, **collapse** is a foundation package for statistical computing and data manipulation in R that enhances and integrates seamlessly with the R ecosystem while being outstandingly computationally efficient. A significant benefit is that, rather than piecing together a fragmented ecosystem oriented at different classes and tasks, many core computational tasks can be done with **collapse**, and easily extended by more specialized packages. This tends to result in R scripts that are shorter, more efficient, and more lightweight in dependencies.

Other programming environments such as Python and Julia now also offer computationally very powerful libraries for tabular data such as **DataFrames.jl** (Bouchet-Valat and Kamiński 2023), **Polars** (Vink *et al.* 2023), and **Pandas** (Wes McKinney 2010; **pandas** Development Team 2023), and supporting numerical libraries such as **Numpy** (Harris *et al.* 2020), or **StatsBase.jl** (JuliaStats 2023). In comparison with these, **collapse** offers a class-agnostic approach bridging the divide between data frames and atomic structures, has more advanced statistical capabilities,⁷ supports recursive operations, variable labels, verbosity for critical operations such as joins, and is extensively globally configurable. In short, it is very utile for complex statistical workflows, rich datasets (e.g., surveys), and for integrating with different parts of the R ecosystem. On the other hand, **collapse**, for the most part, does not offer a sub-column-level parallel architecture and is thus not highly competitive with top frameworks, including **data.table**, on aggregating billion-row datasets with few columns.⁸ Its vectorization capabilities are also limited to the statistical functions it provides and not, like **DataFrames.jl**, to any Julia function. However, as demonstrated in Section 3.1, vectorized statistical functions can be combined to calculate more complex statistics in a vectorized way.

The package has a built-in structured documentation facilitating its use. This documentation includes a central overview page linking to all other documentation pages and supplementary topic pages which briefly describe related functionality. The names of these extra pages are collected in a global macro .COLLAPSE_TOPICS and can be called directly with help():

R> .COLLAPSE_TOPICS

[1]	"collapse-documentation"	"fast-statistical-functions"
[3]	"fast-grouping-ordering"	"fast-data-manipulation"
[5]	"quick-conversion"	"advanced-aggregation"
[7]	"data-transformations"	"time-series-panel-series"
[9]	"list-processing"	"summary-statistics"
[11]	"recode-replace"	"efficient-programming"
[13]	"small-helpers"	"collapse-options"

⁷Such as weighted statistics, including various quantile and mode estimators, support for fully timeaware computations on irregular series/panels, higher order centering, advanced (grouped, weighted, paneldecomposed) descriptive statistics etc., all supporting missing values.

⁸As can be seen in the DuckDB Benchmarks: **collapse** is highly competitive on the 10-100 million observations datasets, but deteriorates in performance at larger data sizes (except for joins where it remains competitive). There may be performance improvements for "long data" in the future, but, at present, the treatment of columns as fundamental units of computation is a tradeoff for the highly flexible class-agnostic architecture.

R> help("collapse-documentation")

collapse is too large and complex to fully present it in a single article, or even to present selected topics in depth. The following sections therefore briefly introduce its key components: (2) the *Fast Statistical Functions* and their (3) integration with data manipulation functions; (4) architecture for time series and panel data; (5) joins and reshaping; (6) list processing functions; (7) descriptive tools; and (8) global options. Section 9 provides a small benchmark, Section 10 concludes. For deeper engagement with **collapse**, a short vignette summarizing available documentation and resources is an excellent starting point.

2. Fast statistical functions

The Fast Statistical Functions, comprising fsum(), fprod(), fmean(), fmedian(), fmode(), fvar(), fsd(), fmin(), fmax(), fnth(), ffirst(), flast(), fnobs() and fndistinct(), are a consistent set of S3-generic statistical functions providing fully vectorized statistical operations in R. Specifically, operations such as calculating the mean via the S3 generic fmean() function are vectorized across columns and groups. They may also involve weights or transformations of the original data. The basic syntax of these functions is

FUN(x, g = NULL, [w = NULL], TRA = NULL, [na.rm = TRUE], use.g.names = TRUE, drop = TRUE, [nthreads = 1L], ...)

with arguments x - data (vector, matrix or data frame-like), g - groups (atomic vector, list of vectors, or 'GRP' object), w - weights, TRA - transformation, na.rm - missing values, use.g.names - attach group names upon aggregation (if g is used), drop - drop dimensions (i.e., simplify to atomic vector if is.null(g) and x is matrix or data frame-like), nthreads - multithreading.⁹ The following examples, taken from the collapse for tidyverse Users vignette demonstrate their basic usage to calculate (column-wise, grouped, weighted) statistics on different objects. As laid out in the vignette on object handling, statistical functions have basis S3 methods for vectors ('default'), 'matrix', and 'data.frame', which call corresponding C implementations that intelligently preserve object attributes. Thus, the functions can be applied to a broad set of 'matrix' or 'data.frame'-based objects without the need to define explicit methods. Users can also directly call the basis methods in case S3 dispatch does not yield the intended outcome. For example, fmean.default(EuStockMarkets) computes the mean of the entire matrix.

```
R> fmean(mtcars$mpg)
```

[1] 20.09

R> fmean(EuStockMarkets)

DAX SMI CAC FTSE 2531 3376 2228 3566

⁹Not all functions are multithreaded, and parallelism is implemented differently for different functions (detailed in the documentation). The use of single instruction multiple data (SIMD) parallelism in single-threaded mode also implies limited gains from multithreading for simple operations such as fsum().

```
R> fmean(mtcars[5:10])
   drat
             wt
                    qsec
                              vs
                                      \mathtt{am}
                                             gear
 3.5966
         3.2173 17.8488 0.4375
                                 0.4062 3.6875
R> fmean(mtcars$mpg, w = mtcars$wt)
[1] 18.55
R> fmean(mtcars$mpg, g = mtcars$cyl)
    4
          6
                8
26.66 19.74 15.10
R> fmean(mtcars$mpg, g = mtcars$cyl, w = mtcars$wt)
    4
          6
                8
25.94 19.65 14.81
R> fmean(mtcars[5:10], g = mtcars$cyl, w = mtcars$wt)
   drat
           wt qsec
                         vs
                                am
                                    gear
4 4.031 2.415 19.38 0.9149 0.6498 4.047
6 3.569 3.152 18.12 0.6212 0.3788 3.821
8 3.206 4.133 16.89 0.0000 0.1204 3.241
R> fmean(mtcars$mpg, g = mtcars$cyl, TRA = "fill") |> head(20)
 [1] 19.74 19.74 26.66 19.74 15.10 19.74 15.10 26.66 26.66 19.74 19.74 15.10
[13] 15.10 15.10 15.10 15.10 15.10 26.66 26.66 26.66
```

2.1. Transformations

The final example invoking TRA expands the mean vector to full length, like stats::ave(mtcars\$mpg, mtcars\$cyl), but much faster. The TRA argument invokes the TRA() function for column-wise (grouped) replacing and sweeping operations (by reference). Its syntax is

TRA(x, STATS, FUN = "-", g = NULL, set = FALSE, ...)

where STATS is a vector/matrix/data.frame of statistics used to transform x. Table 1 lists the 11 possible FUN operations, toggled using either an integer or string. TRA() is called internally in the *Fast Statistical Functions*, the TRA argument is passed to FUN. Thus fmean(x, g, w, TRA = "-") is equivalent to TRA(x, fmean(x, g, w), "-", g). The set argument can also be passed to *Fast Statistical Functions* to toggle transformation by reference. The following examples demonstrate how this design allows flexible ad-hoc transformations using R's built-in airquality dataset with daily measurements in New York from May to September 1973.

Int	String	Description
0	"replace_na"/"na"	replace missing values in x
1	"replace_fill"/"fill"	replace data and missing values in \mathbf{x}
2	"replace"	replace data but preserve missing values in ${\tt x}$
3	"_"	subtract (i.e., center)
4	"-+"	center on overall average statistic
5	"/"	divide (i.e., scale)
6	"%"	compute percentages (i.e., divide and multiply by 100)
7	"+"	add
8	"*"	multiply
9	"%%"	modulus (i.e., remainder from division by STATS)
10	"-%%"	subtract modulus (i.e., make data divisible by ${\tt STATS})$

Table 1: Available FUN choices in TRA().

R> fnobs(airquality)

Ozone	Solar.R	Wind	Temp	Month	Day
116	146	153	153	153	153

This imputes columns Ozone and Solar. R by reference using the month median.

R> fmedian(airquality[1:2], airquality\$Month, TRA = "replace_na", set = TRUE)

This performs different grouped and/or weighted transformations at once.

```
R> airquality |> fmutate(ozone_deg = Ozone / Temp,
+ rad_day = fsum(as.double(Solar.R), Day, TRA = "/"),
+ ozone_amed = Ozone > fmedian(Ozone, Month, TRA = "fill"),
+ ozone_resid = fmean(Ozone, list(Month, ozone_amed), ozone_deg, "-")
+ ) |> head(3)
```

	Ozone	Solar.R	Wind	Temp	Month	Day	ozone_deg	rad_day	$ozone_amed$	ozone_resid
1	41	190	7.4	67	5	1	0.6119	0.191	TRUE	-10.279
2	36	118	8.0	72	5	2	0.5000	0.135	TRUE	-15.279
3	12	149	12.6	74	5	3	0.1622	0.168	FALSE	-3.035

2.2. Grouping objects and optimization

Whereas the g argument supports ad-hoc grouping with vectors and lists/data frames, the cost of grouping can be optimized by using factors or, even better, 'GRP' objects, which readily contain all information **collapse**'s vectorized statistical functions might require to operate across groups. These objects can be created with GRP(). Its syntax is

GRP(X, by = NULL, sort = TRUE, decreasing = FALSE, na.last = TRUE, return.groups = TRUE, return.order = sort, method = "auto", ...)

The example below creates and displays a 'GRP' object from 3 columns in mtcars. The by argument also supports column names or indices, and X could also be an atomic vector.

```
R> str(g <- GRP(mtcars, ~ cyl + vs + am))</pre>
Class 'GRP' hidden list of 9
 $ N.groups
               : int 7
               : int [1:32] 4 4 3 5 6 5 6 2 2 5 ...
 $ group.id
 $ group.sizes : int [1:7] 1 3 7 3 4 12 2
 $ groups
              :'data.frame':
                                     7 obs. of 3 variables:
  ..$ cyl: num [1:7] 4 4 4 6 6 8 8
  ..$ vs : num [1:7] 0 1 1 0 1 0 0
  ..$ am : num [1:7] 1 0 1 1 0 0 1
 $ group.vars : chr [1:3] "cyl" "vs" "am"
             : Named logi [1:2] TRUE FALSE
 $ ordered
  ..- attr(*, "names")= chr [1:2] "ordered" "sorted"
              : int [1:32] 27 8 9 21 3 18 19 20 26 28 ...
 $ order
  ..- attr(*, "starts")= int [1:7] 1 2 5 12 15 19 31
  ..- attr(*, "maxgrpn")= int 12
  ..- attr(*, "sorted")= logi FALSE
 $ group.starts: int [1:7] 27 8 3 1 4 5 29
 $ call
               : language GRP.default(X = mtcars, by = ~cyl + vs + am)
```

'GRP' objects make grouped statistical computations in **collapse** fully programmable. Below, the object is used with the *Fast Statistical Functions* and some utility functions to efficiently aggregate data (with optional frequency weights).

```
R> dat <- get_vars(mtcars, c("mpg", "disp")); w <- mtcars$wt;</pre>
R> add_vars(g$groups,
     fmean(dat, g, w, use.g.names = FALSE) |> add_stub("w_mean_"),
+
     fsd(dat, g, w, use.g.names = FALSE) |> add_stub("w_sd_")) |> head(2)
+
  cyl vs am w_mean_mpg w_mean_disp w_sd_mpg w_sd_disp
1
    4 0
          1
                  26.00
                               120.3
                                        0.000
                                                     0.0
2
    4 1 0
                  23.02
                               137.1
                                        1.236
                                                    11.6
Similarly, data can be transformed, here using the S3 generic fscale() function.
```

```
R> mtcars |> add_vars(fmean(dat, g, w, "-") |> add_stub("w_demean_"),
+ fscale(dat, g, w) |> add_stub("w_scale_")) |> head(2)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb	w_demean_mpg
Mazda RX4	21	6	160	110	3.9	2.620	16.46	0	1	4	4	0.4357
Mazda RX4 Wag	21	6	160	110	3.9	2.875	17.02	0	1	4	4	0.4357
	w_de	emear	n_disp	o w_s	scale_	_mpg w	scale	_dis	sp			
Mazda RX4			5.027	7	0.6	6657	0	.665	57			
Mazda RX4 Wag			5.027	7	0.6	657	0	.665	57			

This programming access can become very useful. For example, the useR 2022 presentation Slides 18-19 aggregates the EORA Global Supply Chain Database from the country to the world region level. After defining a single grouping object, a list of value-added shares matrices (VB) and outputs (O) for years 1990-2021, is aggregated with no grouping cost using a single line of code like lapply(VB_list, function(x) x\$VB |> fsum(g) |> t() |> fmean(g, x\$O) |> t()). On an M1 Mac using 4 threads, this computation, involving 44.7 million summations and 2.6 million weighted means, takes only 0.33 seconds.¹⁰

3. Integration with data manipulation functions

collapse also provides a broad set of fast data manipulation functions familiar to R and tidyverse users, including fselect(), fsubset(), fgroup_by(), fsummarise(), ftransform(), fmutate(), across(), frename(), fcount(), etc. These are integrated with the *Fast Statistical Functions* to enable vectorized statistical operations in a familiar data frame oriented and tidyverse-like workflow. For example, the following code calculates the mean of columns

```
R> mtcars |> fsubset(mpg > 11) |> fgroup_by(cyl, vs, am) |>
+
     fsummarise(across(c(mpg, carb, hp), fmean),
                qsec_w_med = fmean(qsec, wt)) |> head(2)
+
  cyl vs am mpg carb
                          hp qsec w med
    4
       0
          1 26.0 2.000 91.00
                                   16.70
1
          0 22.9 1.667 84.67
                                   21.04
2
    4
       1
```

mpg, carb and hp, and the weighted mean of qsec, after subsetting and grouping the data. This code is very fast (especially with many groups) because data does not need to be split by groups at all. There is also no need to call lapply() inside the across() statement: fmean.data.frame() is applied to a subset of the data containing the three columns.¹¹ The *Fast Statistical Functions* also have a method for grouped data, so fsummarise is not always needed. The following example calculates weighted group means. By default (keep.w = TRUE) fmean.grouped_df also sums the weights in each group.¹²

```
R> mtcars |> fsubset(mpg > 11, cyl, vs, am, mpg, carb, hp, wt) |>
+ fgroup_by(cyl, vs, am) |> fmean(wt) |> head(2)
```

cyl vs am sum.wt mpg carb hp 1 4 0 1 2.140 26.00 2.00 91.0 2 4 1 0 8.805 23.02 1.72 83.6

¹⁰Another recent example involved numerically optimizing a parameter a in an equation of the form $y_j = \sum_i x_{ij}^a \ \forall j \in J$ where there are J groups (1 million in my case), and the optimal value of a is determined by the proximity of the aggregated vector \mathbf{y} to another vector \mathbf{z} . Thus each iteration of the numerical routine raises the vector \mathbf{x} to a different power (a), sums it in 1 million groups (j) to generate \mathbf{y} , and computes the Euclidean distance to \mathbf{z} (using collapse::fdist). Without grouping objects and vectorization, this would have been difficult to handle within reasonable computing times (of a few seconds on the M1).

¹¹Internally, the g argument of the statistical functions is set as a keyword argument by fsummarise/across and the function is evaluated on a suitable subset of columns. Thus w becomes the second positional argument...

¹²'grouped_df' methods in collapse support grouped data created with either fgroup_by() or dplyr::group_by(). The latter requires an additional C routine to convert the dplyr grouping object to a 'GRP' object, and is thus less efficient.

3.1. Vectorizations for advanced tasks

fsummarise() and fmutate() can also evaluate arbitrary statistical functions in the classical way (split-apply-combine) and handle more complex expressions involving multiple columns and/or functions. However, using any *Fast Statistical Function* causes the whole expression to be vectorized, i.e., evaluated only once and not for every group. This eager vectorization approach enables efficient grouped calculation of more complex statistics. The example below calculates grouped (vs) bivariate regression slopes (mpg ~ carb) in a vectorized way.

```
R> mtcars |> fgroup_by(vs) |>
+ fmutate(dm_carb = fmean(carb, TRA = "-")) |>
+ fsummarise(slope = fsum(mpg, dm_carb) %/=% fsum(dm_carb^2))
vs slope
1 0 -0.5557
2 1 -2.0706
```

Apart from vectorization, this code avoids 3 intermediate copies: (1) fmean(carb, TRA = "-") avoids an expanded vector of group means, (2) fsum(mpg, dm_carb) uses the weights (w) argument to fsum() to avoid materializing a multiplication (as in fsum(mpg * dm_carb)), and (3) division by reference (%/=%) avoids allocating an additional vector for the final result. Under the hood, the expression boils down to an (expensive) grouping step, 5 allocations (of which 2 full length), and 6 loops in C to calculate the result. Any modern laptop can calculate 1 million regression slopes in less than 1 second like this. Another very neat example, shared by Andrew Ghazi in a recent blog post,¹³ vectorizes an expression to compute the p value across 300k groups for a simulation study, yielding a 70x performance increase over **dplyr**.

collapse also vectorizes advanced statistics, such as weighted medians and modes. The following example calculates a weighted set of summary statistics by groups, with weighted quantiles type 8 following Hyndman and Fan (1996).¹⁴ and a weighted maximum mode.¹⁵

```
R> mtcars |> fgroup_by(cyl, vs, am) |>
     fmutate(o = radixorder(GRPid(), mpg)) />
+
     fsummarise(mpg_min = fmin(mpg),
+
                mpg_Q1 = fnth(mpg, 0.25, wt, o = o, ties = "q8"),
+
                mpg_mean = fmean(mpg, wt),
+
                mpg_median = fmedian(mpg, wt, o = o, ties = "q8"),
+
                mpg_mode = fmode(mpg, wt, ties = "max"),
+
                mpg_Q3 = fnth(mpg, 0.75, wt, o = o, ties = "q8"),
+
                mpg_max = fmax(mpg)) |> head(3)
+
         am mpg_min mpg_Q1 mpg_mean mpg_median mpg_mode mpg_Q3 mpg_max
  cvl vs
               26.0
                               26.00
                                           26.00
                                                     26.0
    4
       0
          1
                     26.00
                                                            26.00
                                                                     26.0
1
2
    4
          0
                     21.90
                               23.02
                                           23.16
                                                     24.4
                                                            24.38
                                                                     24.4
       1
               21.5
               21.4
                     22.37
                               27.74
                                           28.28
                                                     30.4
                                                            31.51
                                                                     33.9
    4
       1
          1
З
```

 $^{13} \rm https://and rewghazi.github.io/posts/collapse_is_sick/sick.html$

 14 collapse calculates weighted quantiles by replacing the sample size with the sum of weights and 1 with the minimum non-zero weight in the respective quantile definition. See fquantile for more details.

¹⁵The weighted maximum mode is the largest element with the maximum sum of weights.

Both weighted mode and quantiles have a sub-column parallel implementation,¹⁶ and, as shown above, can also harness an (optional) optimization by computing an overall ordering vector and passing it to each quantile function to avoid repeated partial sorting (using quickselect) of the same elements within groups. For advanced data aggregation, **collapse** also provides a convenience function, **collap()**, which (by default) uses **fmean** for numeric and **fmode** for non-numeric columns. Below, it aggregates GDP per capita, life expectancy, and country name by World Bank income group, with population weights.¹⁷ This yields population-weighted statistics, the largest country, and each income group's total population (sum of weights) for each year, preserving (default keep.col.order = TRUE) the order of columns.

```
R> collap(wlddev, country + PCGDP + LIFEEX ~ year + income, w = ~ POP) |>
+ head(4)
```

	country	year			income	PCGDP	LIFEEX	POP
1	United States	1960		High	income	12768.7	68.59	7.495e+08
2	Ethiopia	1960		Low	income	658.5	38.33	1.474e+08
3	India	1960	Lower	middle	income	500.8	45.27	9.280e+08
4	China	1960	Upper	${\tt middle}$	income	1166.1	49.86	1.184e+09

4. Time series and panel data

collapse also provides a flexible high-performance architecture to perform (time aware) computations on time series and panel series. In particular, the user enjoys great flexibility in deciding the desired degree of indexation and mode of computation. It is possible to apply time series and panel data transformations without any indexation by passing individual and/or time identifiers to the respective functions in an ad-hoc fashion, or by using 'indexed_frame' and 'indexes_series' classes, which implement full and deep indexation. Table 2 summarizes **collapse**'s time series and panel data architecture.

4.1. Ad-hoc computations

Time series functions such as fgrowth() (to compute growth rates) are S3 generic and can be applied to most time series classes. In addition to a g argument for grouped computation, these functions also have a t argument for indexation. If t is a plain numeric vector or a factor, it is coerced to integer and interpreted as time steps.¹⁸ If t is a numeric time object (e.g., 'Date', 'POSIXct', etc.), then it is internally passed through timeid() which computes the greatest common divisor (GCD) and generates an integer time-id. For the GCD approach to work, t must have an appropriate class, e.g., for monthly/quarterly data, zoo::yearmon()/zoo::yearqtr() should be used instead of 'Date' or 'POSIXct'.

```
R> fgrowth(airmiles) |> round(2)
```

¹⁶Use set_collapse(nthreads = #) or the nthreads arguments to fnth/fmedian/fmode (default 1).

¹⁷wlddev is a dataset supplied by collapse, extracted from the World Bank World Development Indicators.

¹⁸This is premised on the observation that the most common form of temporal identifier is a numeric variable denoting calendar years. Users need to manually call timeid() on plain numeric vectors with decimals to yield an appropriate integer representation.

```
Classes, constructors and utilities
findex_by(), findex(), unindex(), reindex(), timeid(), is_irregular(),
to_plm() + S3 methods for 'indexed_frame', 'indexed_series' and 'index_df'
```

```
Core time-based functions
flag(), fdiff(), fgrowth(), fcumsum(), psmat()
psacf(), pspacf(), psccf()
```

Data transformation functions with supporting methods fscale(), f[hd]between(), f[hd]within()

Data manipulation functions with supporting methods fsubset(), funique(), roworder[v]() (internal), na_omit() (internal)

Summary functions with supporting methods
varying(), qsu()

Table 2: Time series and panel data architecture.

Time Series: Start = 1937 End = 1960 Frequency = 1 [1] NA 16.50 42.29 54.03 31.65 2.38 15.23 33.29 54.36 76.92 2.71 -2.10 [13] 12.91 18.51 32.03 18.57 17.82 13.61 18.19 12.83 13.32 0.01 15.49 4.25

The following code creates an irregular series by removing the 3rd and 15th observation and shows how indexation with the t argument accounts for this.

R> am_ir <- airmiles[-c(3, 15)]
R> t <- time(airmiles)[-c(3, 15)]
R> fgrowth(am_ir, t = t) |> round(2)

[1] NA 16.50 NA 31.65 2.38 15.23 33.29 54.36 76.92 2.71 -2.10 12.91 [13] 18.51 NA 17.82 13.61 18.19 12.83 13.32 0.01 15.49 4.25

 $R > fgrowth(am_ir, -1:3, t = t) | > head(4)$

FG1 ___ G1 L2G1 L3G1 [1,] -14.167 412 NA NΑ NΑ [2,] NA 480 16.50 NA NΔ [3,] -24.043 1052 NA 119.2 155.3 [4,] -2.327 1385 31.65 NA 188.5

For these functions, there also exists shorthands in the form of statistical operators, e.g., L()/D()/G() are shorthands for flag()/fdiff()/fgrowth(), which facilitate their use inside

formulas and also provide enhanced data frame interfaces for convenient ad-hoc computations. With panel data, t can be omitted, but this requires sorted data with consecutive groups.¹⁹

R > G(wlddev, c(1, 10), by = POP + LIFEEX ~ iso3c, t = ~ year) | > head(3)iso3c year G1.POP L10G1.POP G1.LIFEEX L10G1.LIFEEX AFG 1960 NA NA NA NA 1 AFG 1961 NA 1.590 NA 2 1.917 3 AFG 1962 1.985 NA 1.544 NA R> settransform(wlddev, POP_growth = G(POP, g = iso3c, t = year)) These functions and operators are also integrated with fsummarise() and fmutate() for vectorized grouped computations. R> wlddev |> fgroup_by(iso3c) |> fselect(iso3c, year, POP, LIFEEX) |> fmutate(across(c(POP, LIFEEX), G, t = year)) |> head(2)

iso3c year POP LIFEEX G1.POP G1.LIFEEX 1 AFG 1960 8996973 32.45 NA NA 2 AFG 1961 9169410 32.96 1.917 1.59

Similarly, functions to scale, center, and average data have groups (g) and also weights (w) arguments, and corresponding operators STD(), [HD]W(), [HD]B() to facilitate ad-hoc transformations. Below, two ways to perform grouped scaling are demonstrated. The operator version is slightly faster and renames the transformed columns by default (stub = TRUE).

```
R> iris |> fgroup_by(Species) |> fscale() |> head(2)
```

Species Sepal.Length Sepal.Width Petal.Length Petal.Width setosa 0.2667 0.1899 -0.357-0.43651 2 setosa -0.3007 -1.1291 -0.357 -0.4365R> STD(iris, ~ Species) |> head(2) Species STD.Sepal.Length STD.Sepal.Width STD.Petal.Length STD.Petal.Width setosa 0.2667 0.1899 -0.357-0.43651 -0.3007-1.1291-0.357-0.43652 setosa

The following example demonstrates a fixed-effects regression à la Mundlak (1978).

R> lm(mpg ~ carb + B(carb, cyl), data = mtcars) |> coef()

(Intercept)	carb	B(carb,	cyl)
34.8297	-0.4655	-4	.7750

¹⁹This is because a group-lag is computed in a single pass, requiring all group elements to be consecutive.

collapse also offers higher-dimensional between and within transformations, powered by C++ code conditionally imported (and accessed directly) from **fixest**. The following detrends GDP per Capita and Life Expectancy at Birth using country-specific cubic polynomials.

R> HDW(wlddev, PCGDP + LIFEEX ~ iso3c * poly(year, 3), stub = F) /> head(2)
PCGDP LIFEEX
1 8.885 0.023614

4.2. Indexed series and frames

2 13.685 0.006724

For more complex use cases, indexation is very convenient. **collapse** supports **plm**'s '**pseries**' and '**pdata.frame**' classes through dedicated methods. Flexibility and performance considerations lead to the creation of new classes 'indexes_series' and 'indexed_frame' which inherit from the former. Any data frame-like object can be an 'indexed_frame' with any number of individual and/or time identifiers (e.g., an indexed 'data.table' is fully functional for other operations). The technical implementation of these classes is described in the vignette on object handling and, in more detail, in the documentation. The basic syntax is:

```
data_ix <- findex_by(data, id1, ..., time)
data_ix$indexed_series; with(data, indexed_series)
index_df <- findex(data_ix)</pre>
```

Data can be indexed using one or more indexing variables. Unlike 'pdata.frame', an 'indexed_frame' is a deeply indexed structure, i.e., every series inside the frame is already an 'indexes_series' and contains, in its 'index_df' attribute, an external pointer to the 'index_df' attribute of the frame (to avoid duplication in memory). A comprehensive set of methods for subsetting and manipulation, and applicable 'pseries' and 'pdata.frame' methods for time series and transformation functions like flag()/L(), ensure that these objects behave in a time-/panel-aware manor in any caller environment (created by with(), lm() etc.). Indexation can be undone using unindex() and redone with reindex() and a suitable 'index_df'. 'indexes_series' can be atomic vectors or matrices (including objects such as 'ts' or 'xts') and can also be created directly using reindex().

```
data <- unindex(data_ix)
data_ix <- reindex(data, index = index_df)
indexed_series <- reindex(vec/mat, index = vec/index_df)</pre>
```

An example using the wlddev data follows:

```
R> wldi <- wlddev |> findex_by(iso3c, year)
R wldi |> fsubset(-3, iso3c, year, PCGDP:POP) |> G() |> head(4)
  iso3c year G1.PCGDP G1.LIFEEX G1.GINI G1.ODA G1.POP
    AFG 1960
1
                   NA
                             NA
                                     NA
                                            NA
                                                    NA
2
    AFG 1961
                   NA
                          1.590
                                     NA
                                        98.75 1.917
```

 3
 AFG 1963
 NA
 NA
 NA
 NA
 NA
 NA

 4
 AFG 1964
 NA
 1.448
 NA
 24.48
 2.112

Indexed by: iso3c [1] | year [4 (61)]

The index statistics are: [N. ids] | [N. periods (total periods: (max-min)/GCD)]. This creates an 'indexes_series' of life expectancy and demonstrates its properties:

```
R> LIFEEXi <- wldi$LIFEEX; str(LIFEEXi, width = 70, strict = "cut")
```

'indexed_series' num [1:13176] 32.4 33 33.5 34 34.5 ...
- attr(*, "label")= chr "Life expectancy at birth, total (years)"
- attr(*, "index_df")=Classes 'index_df', 'pindex' and 'data.frame'..
..\$ iso3c: Factor w/ 216 levels "ABW","AFG","AGO",..: 2 2 2 2 2 2 ..
...- attr(*, "label")= chr "Country Code"
..\$ year : Ord.factor w/ 61 levels "1960"<"1961"<..: 1 2 3 4 5 6 7..
...- attr(*, "label")= chr "Year"</pre>

```
R> c(is_irregular(LIFEEXi), is_irregular(LIFEEXi[-5]))
```

[1] FALSE TRUE

R> G(LIFEEXi[c(1:5, 7:10)])

[1] NA 1.590 1.544 1.494 1.448 NA 1.366 1.362 1.365

Indexed by: iso3c [1] | year [9 (61)]

The transformation and estimation below demonstrate the deep indexation of 'indexed_frame"s, allowing correct computations in arbitrary data masking environments.

```
R> settransform(wldi, PCGDP_ld = Dlog(PCGDP))
R> lm(D(LIFEEX) ~ L(PCGDP_ld, 0:5) + B(PCGDP_ld), wldi) |>
+ summary() |> coef() |> round(3)
```

		Estimate	Std.	Error	t value	Pr(> t)
(Intercept)		0.299		0.007	44.412	0.000
L(PCGDP_ld,	0:5)	0.300		0.080	3.735	0.000
L(PCGDP_ld,	0:5)L1	0.269		0.081	3.332	0.001
L(PCGDP_ld,	0:5)L2	0.227		0.079	2.854	0.004
L(PCGDP_ld,	0:5)L3	0.200		0.078	2.563	0.010
L(PCGDP_ld,	0:5)L4	0.143		0.076	1.871	0.061
L(PCGDP_ld,	0:5)L5	0.095		0.073	1.301	0.193
B(PCGDP_1d)		-1.021		0.316	-3.234	0.001

In comparison with existing solutions, the flexibility of this architecture is new to the R ecosystem: A 'pdata.frame' or 'fixest_panel' only works inside plm/fixest estimation functions.²⁰ Time series classes like 'xts' and 'tsibble' also do not provide deeply indexed structures for time series operations or native handling of irregularity in basic operations. 'indexed_series' and 'indexed_frame', on the other hand, work anywhere and can be superimposed on any suitable object (such as 'sf' to create a spatiotemporal panel), as long as collapse's functions (flag()/L() etc.) are used to perform the time-based computations. The 'index_df' attached to these objects can be used with other general tools such as collapse::BY() to perform grouped computations using 3rd-party functions. An example of calculating a 5-year rolling average is given below. Last but not least, the performance of these classes is second to none, as demonstrated in the useR 2022 presentation on slide 40.

R> BY(LIFEEXi, findex(LIFEEXi)\$iso3c, data.table::frollmean, 5) |> head(10)

[1] NA NA NA NA 33.46 33.96 34.46 34.95 35.43 35.92 Indexed by: iso3c [1] | year [10 (61)]

5. Table joins and pivots

While **collapse** has a broad set of data manipulation functions, its implementations of table joins and pivots is particularly noteworthy since they offer several new features, including rich verbosity for table joins, pivots supporting variable labels, and 'recast' pivots. Both implementations provide outstanding computational performance and memory efficiency.

5.1. Joins

Compared to commercial environments such as STATA, the implementation of joins in most open-source software, including R, is non-verbose, i.e., provides no information on how many and which records were joined from both tables. This is somewhat unsatisfying and often provokes manual efforts to validate the join operation. collapse::join provides a rich set of options to make table join operations intelligible. Its syntax is:

```
join(x, y, on = NULL, how = "left", suffix = NULL, validate = "m:m",
multiple = FALSE, sort = FALSE, keep.col.order = TRUE,
drop.dup.cols = FALSE, verbose = 1, column = NULL, attr = NULL, ...)
```

By default (verbose = 1), it prints information about the join operation and number of records joined. Users can request the generation of a .join column (column = "name"/TRUE), akin to STATA's _merge column, indicating the origin of records in the joined table.

 $^{^{20}\}mathrm{And},$ in the case of $\mathbf{fixest},$ inside $\mathbf{data.table}$ due to dedicated methods.

```
R> df1 <- data.frame(id1 = c(1, 1, 2, 3), id2 = c("a", "b", "b", "c"),
     name = c("John", "Jane", "Bob", "Carl"), age = c(35, 28, 42, 50))
+
R> df2 <- data.frame(id1 = c(1, 2, 3, 3), id2 = c("a", "b", "c", "e"),
+
     salary = c(60000, 55000, 70000, 80000),
     dept = c("IT", "Marketing", "Sales", "IT"))
+
R join(df1, df2, on = c("id1", "id2"), how = "full", column = TRUE)
full join: df1[id1, id2] 3/4 (75%) <m:m> df2[id1, id2] 3/4 (75%)
  id1 id2 name age salary
                               dept
                                       .join
                    60000
1
    1
        a John 35
                                 IT matched
2
    1
        b Jane
                28
                       NA
                               <NA>
                                        df1
3
    2
                42
                   55000 Marketing matched
        b Bob
4
    3
        c Carl
                50
                    70000
                              Sales matched
                                 IT
5
    З
        e <NA>
                NA
                    80000
                                        df2
```

An alternative to the join column is to request an attribute (attr = "name"/TRUE) that also summarizes the join operation, including the output of fmatch() (the workhorse of join() if sort = FALSE). Users can also invoke the validate argument to check the uniqueness of the join keys in either table: passing a '1' for a non-unique key produces an error.

```
R> join(df1, df2, on = c("id1", "id2"), validate = "1:1", attr = "join") |>
+ attr("join") |> str(width = 70, strict = "cut")
```

```
left join: df1[id1, id2] 3/4 (75%) <1:1> df2[id1, id2] 3/4 (75%)
List of 3
$ call : language join(x = df1, y = df2, on = c("id1", "id2"), v"..
$ on.cols:List of 2
...$ x: chr [1:2] "id1" "id2"
...$ y: chr [1:2] "id1" "id2"
$ match : 'qG' int [1:4] 1 NA 2 3
... attr(*, "N.nomatch")= int 1
... attr(*, "N.groups")= int 4
... attr(*, "N.distinct")= int 3
```

A few further particularities are worth highlighting. First, collapse::join is also classagnostic and preserves the attributes of x. It supports 6 different join operations ("left", "right", "inner", "full", "semi", or "anti") and defaults to "left", so the default behavior simply adds columns to x. By default (sort = FALSE), the order of rows in x is also preserved. Setting sort = TRUE sorts all records in the joined table by the keys.²¹ Additionally, by default (multiple = FALSE), only the first matches from y are joined to avoid silent cartesian duplication of records. In multi-match settings, this will be reflected by few records from y being used. fmatch() also has a built-in overidentification check, which issues a warning if more key columns than necessary to identify the records are provided:

 $^{^{21}}$ This is done using a separate sort-merge-join algorithm, so it is faster than performing a hash join (using fmatch()) followed by sorting, particularly if the data is already sorted on the keys.

```
R> df2$name = df1$name
R> join(df1, df2) |> capture.output(type = "m") |>
     strwrap(77) \mid > cat(sep = "\n")
left join: df1[id1, id2, name] 1/4 (25%) <m:m> df2[id1, id2, name] 1/4 (25%)
  id1 id2 name age salary dept
        a John 35
                    60000
1
    1
                            TT
2
                       NA <NA>
    1
        b Jane 28
                       NA <NA>
3
    2
        b Bob 42
4
    3
        c Carl 50
                       NA <NA>
Warning in fmatch(x[ixon], y[iyon], nomatch = NA_integer_, count = count, :
Overidentified match/join: the first 2 of 3 columns uniquely match the
records. With overid > 0, fmatch() continues to match columns. Consider
removing columns or setting overid = 0 to terminate the algorithm after 2
columns (the results may differ, see ?fmatch). Alternatively set overid = 2
to silence this warning.
```

A final noteworthy feature is the handling of duplicate non-id columns in both tables:

```
R> join(df1, df2, on = c("id1", "id2"))
```

1	eft j	join	df1	[id1,	, id2] 3	3/4 (75%)	<m:m></m:m>	df2[id1,	id2]	3/4	(75%)
ď	uplic	cate	colur	nns:	name =>	> renamed	using	suffix '	_df2'	for	У
	id1	id2	name	age	salary	dept	name	_df2			
1	1	a	John	35	60000	IT		John			
2	1	b	Jane	28	NA	<na></na>	· · ·	<na></na>			
3	2	b	Bob	42	55000	Marketing		Jane			
4	3	с	Carl	50	70000	Sales		Bob			

By default (suffix = NULL), join() extracts the name of the y table and appends y-columns with it. x-columns are not renamed. This is congruent to the principle of adding columns to x and altering this table as little as possible. Another option, drop.dup.cols = "x"/"y", can be used to simply drop duplicate columns from x or y before the join operation.

5.2. Pivots

The reshaping/pivoting functionality of both commercial and open source software is also unsatisfying for complex datasets such as surveys or disaggregated production, trade, or financial sector data, where variable names resemble codes and variable labels are essential to making sense of the data. Such datasets can presently only be reshaped by losing these labels or additional manual efforts to retain them. Modern R packages also offer different functions for different reshaping operations, such as data.table::melt/tidyr::pivot_longer to combine columns and data.table::dcast/tidyr::pivot_wider to expand them, requiring users to learn both. Since the depreciation of reshape(2) (Wickham 2007), there is also no modern replacement for reshape2::recast(), requiring R users to consecutively call two reshaping functions, incurring a high cost in terms of syntax and memory. collapse::pivot provides a modern class-agnostic implementation of reshaping for R that addresses these shortcomings: it has a single intuitive syntax to perform 'longer', 'wider', and 'recast' pivots, and supports complex labelled data without loss of information. Its syntax is:

```
pivot(data, ids = NULL, values = NULL, names = NULL, labels = NULL,
how = "longer", na.rm = FALSE, factor = c("names", "labels"),
check.dups = FALSE, nthreads = 1, fill = NULL, drop = TRUE,
sort = FALSE, transpose = FALSE)
```

The demonstration below employs a generated dataset about fruits. We could equivalently think about a survey with households and individuals, or sectors and firms. Variable labels are stored in attr(column, "label"). The documentation provides more elaborate examples.

```
R> data <- data.frame(type = rep(c("A", "B"), each = 2),
+ type_name = rep(c("Apples", "Bananas"), each = 2),
+ id = rep(1:2, 2), r = abs(rnorm(4)), h = abs(rnorm(4)*2))
R> setrelabel(data, id = "Fruit Id", r = "Fruit Radius", h = "Fruit Height")
R> print(data)
```

	type	type_name	id	r	h
1	А	Apples	1	0.3139	2.983
2	А	Apples	2	0.4095	1.572
3	В	Bananas	1	0.4302	2.220
4	В	Bananas	2	0.1851	2.380

R> vlabels(data)

type	type_name	id	r	h
NA	NA	"Fruit Id" "H	Fruit Radius" "Fruit	Height"

To reshape this dataset into a longer format, it suffices to call pivot(data, ids = c(...)). If labels = "lab_name" is specified, variable labels are saved to an additional column named lab_name. In addition, names = list(variable = "var_name", value = "val_name") can be passed to assign alternative names to the variable and value columns, respectively.

R> (dl <- pivot(data, ids = c("type", "type_name", "id"), labels = "label"))</pre>

	type	type_name	id	variable		label	value
1	А	Apples	1	r	Fruit	Radius	0.3139
2	А	Apples	2	r	Fruit	Radius	0.4095
3	В	Bananas	1	r	Fruit	Radius	0.4302
4	В	Bananas	2	r	Fruit	Radius	0.1851
5	А	Apples	1	h	Fruit	Height	2.9829
6	А	Apples	2	h	Fruit	Height	1.5722
7	В	Bananas	1	h	Fruit	Height	2.2203
8	В	Bananas	2	h	Fruit	Height	2.3797

R> vlabel	s(dl)					
typ	e typ	e_name	id	l variable	label	value
N	A	NA	"Fruit Id'	' NA	NA	NA

pivot() only requires essential information and intelligently guesses the rest. For example, the same result could have been obtained by pivot(data, values = c("r", "h"), labels = "label"). An exact reverse operation can also be performed by specifying as little as pivot(dl, labels = "label", how = "w").

The second option is a wider pivot with how = "wider". Here, names and labels can be used to select columns containing the names of new columns and their labels.²² Note how the labels are combined with existing labels such that also this operation is without loss of information. It is, however, a destructive operation, i.e., with 2 or more columns selected through values, pivot() is not able to reverse it. Further arguments like na.rm, fill, sort, and transpose can be used to control the casting process.

```
R> (dw <- pivot(data, "id", names = "type", labels = "type_name", how = "w"))</pre>
```

```
id r_A r_B h_A h_B
1 1 0.3139 0.4302 2.983 2.22
2 2 0.4095 0.1851 1.572 2.38
```

R> namlab(dw)

	Variable	Label
1	id	Fruit Id
2	r_A	Fruit Radius - Apples
3	r_B	Fruit Radius - Bananas
4	h_A	Fruit Height - Apples
5	h_B	Fruit Height - Bananas

For the recast pivot (how = "recast"), unless a column named variable exists in the data, the source and (optionally) destination of variable names need to be specified using a list passed to names, and similarly for labels. Again, taking along labels is optional, and omitting either the list's from or to elements will omit the respective operations.

```
R> (dr <- pivot(data, ids = "id", names = list(from = "type"),</pre>
+
                labels = list(from = "type name", to = "label"), how = "r"))
  id variable
                     label
                                 A
                                        B
1
  1
            r Fruit Radius 0.3139 0.4302
2
   2
            r Fruit Radius 0.4095 0.1851
3 1
            h Fruit Height 2.9829 2.2203
4
   2
            h Fruit Height 1.5722 2.3797
```

 $^{^{22}{\}rm multiple}$ columns with names and labels could be selected, which would be combined using "_" for names and " – " for labels.

```
R> vlabels(dr)
```

id	variable	label	А	В
"Fruit Id"	NA	NA	"Apples"	"Bananas"

As with the other pivots, this operation does not incur any loss of information. A suitable reverse operation also exists: pivot(dr, "id", names = list(to = "type"), labels = list(from = "label", to = "type_name"), how = "r"). More features of pivot() are demonstrated in the documentation examples. Notably, it is also possible to perform longer and recast pivots without id variables. The recast pivot without ids resembles a generalization of data.table::transpose(), albeit slightly less efficient.

6. List processing

Often in programming, nested structures are needed. A typical use case involves running statistical procedures for multiple configurations of variables and parameters and saving multiple objects (such as a model object, performance statistics, and predictions) in a list. Nested data is also often the result of web scraping or web APIs. A typical use case in development involves serving different data according to user choices, e.g., in response to nested user inputs in shiny apps. Except for certain recursive functions found in packages such as **purr**, **tidyr**, or **rrapply**, R lacks a general recursive toolkit to create, query, and tidy nested data. **collapse**'s list processing functions attempt to provide a basic toolkit.

To create nested data, rsplit() generalizes split() and (recursively) splits up data framelike objects into a (nested) list.

R> (dl <- mtcars |> rsplit(mpg + hp + carb ~ vs + am)) |> str(max.level = 2)

```
List of 2

$ 0:List of 2

..$ 0:'data.frame': 12 obs. of 3 variables:

..$ 1:'data.frame': 6 obs. of 3 variables:

$ 1:List of 2

..$ 0:'data.frame': 7 obs. of 3 variables:

..$ 1:'data.frame': 7 obs. of 3 variables:
```

If a nested structure is not wanted, argument flatten = TRUE lets rsplit() operate like a faster version of split(). With a single column on the LHS of the formula, the default (simplify = TRUE) returns a nested list of atomic vectors. Having created a nested list, rapply2d() is used to fit a linear model on each frame,²³ followed by get_elem() to obtain the coefficient matrices. get_elem() offers several options for filtering lists but, by default, simplifies the list tree as much as possible while maintaining existing hierarchies. In this case, it returns the same nested list with coefficient matrices in all final nodes.

²³rapply2d() is just a recursive wrapper around lapply(), with different defaults than rapply(). Notably, by default, it excludes data frames from being considered as sub-lists and does not simplify the result.

```
R> nest_lm_coef <- dl /> rapply2d(lm, formula = mpg ~ .) />
+ rapply2d(summary, classes = "lm") /> get_elem("coefficients")
R> nest_lm_coef /> str(give.attr = FALSE, strict = "cut")
List of 2
$ 0:List of 2
...$ 0: num [1:3, 1:4] 15.8791 0.0683 -4.5715 3.655 0.0345 ...
...$ 1: num [1:3, 1:4] 26.9556 -0.0319 -0.308 2.293 0.0149 ...
$ 1:List of 2
...$ 0: num [1:3, 1:4] 30.896903 -0.099403 -0.000332 3.346033 0.03587 ...
...$ 1: num [1:3, 1:4] 37.0012 -0.1155 0.4762 7.3316 0.0894 ...
```

At last, unlist2d() is applied to unlist the nested list to a data frame. This function can create a data frame (or 'data.table') representation of any nested list containing data using recursive row-binding and coercion operations while generating (optional) id variables representing the list tree and (optionally) saving row names of matrices or data frames.

```
R> nest_lm_coef |> unlist2d(c("vs", "am"), row.names = "variable") |> head(2)
vs am variable Estimate Std. Error t value Pr(>|t|)
1 0 0 (Intercept) 15.87915 3.65495 4.345 0.001865
2 0 0 hp 0.06832 0.03449 1.981 0.078938
```

This example does not represent an optimal workflow for this specific task²⁴ but exemplifies the power of these tools to create, query, and combine nested data in very general ways. **collapse**'s list processing toolkit provides further useful functions such as t_list() to turn lists of lists inside out, has_elem() to check for the existence of elements, ldepth() to return the maximum level of recursion, and is_unlistable() to check whether a list has atomic elements in all final nodes. A non-recursive and class-agnostic rowbind() function also exists to efficiently bind lists of data frame-like objects (like data.table::rbindlist()).

7. Summary statistics

collapse's summary statistics functions offer a parsimonious and powerful toolset to examine complex datasets. A particular focus has been on providing tools for examining longitudinal (panel) data. Recall the indexed world development panel (wldi) from Section 4. The function varying() indicates which of these variables are time-varying:

R> varying(wldi)

country	date	year	decade	region	income	OECD	PCGDP	LIFEEX
FALSE	TRUE	TRUE	TRUE	FALSE	FALSE	FALSE	TRUE	TRUE
GINI	ODA	POP						
TRUE	TRUE	TRUE						

²⁴A better way of achieving the same result would be mtcars |> fgroup_by(vs, am) |> fsummarise(qDF(lmtest::coeftest(lm(mpg hp + carb)), "variable")).

```
R> varying(wldi, any_group = FALSE) |> head(3)
```

country date year decade region income OECD PCGDP LIFEEX GINI ODA POP ABW FALSE TRUE TRUE TRUE FALSE FALSE FALSE TRUE TRUE NA TRUE TRUE AFG FALSE TRUE TRUE TRUE FALSE FALSE FALSE TRUE TRUE NA TRUE TRUE FALSE TRUE TRUE FALSE FALSE FALSE TRUE TRUE TRUE TRUE AGO TRUE TRUE

Country-variance can be examined using varying(wldi, effect = "year"). For non-indexed data, varying() also has a g argument. A related exercise is to decompose the variance of a panel series into a component due to variation between countries and one capturing variance within countries over time. Using the W()/B() operators and the LIFEEXi 'indexed_series' from Section 4, this is easily demonstrated:

```
R> all.equal(fvar(W(LIFEEXi)) + fvar(B(LIFEEXi)), fvar(LIFEEXi))
```

[1] TRUE

The function qsu() (quick-summary) provides an efficient method to approximately compute this decomposition, considering the group-means instead of the between transformation²⁵ and adding the mean back to the within transformation to preserve the scale of the data.

R> qsu(LIFEEXi)

	N/T	Mean	SD	Min	Max
Overall	11670	64.2963	11.4764	18.907	85.4171
Between	207	64.9537	9.8936	40.9663	85.4171
Within	56.3768	64.2963	6.0842	32.9068	84.4198

This decomposition shows more variation in life expectancy between countries than within countries over time. It can also be computed for different subgroups, such as OECD members and non-members, and with sampling weights, such as population. qsu() can also return Pearson's measures of higher-order statistics.

```
R> qsu(LIFEEXi, g = wlddev$OECD, w = wlddev$POP, higher = TRUE) |> aperm()
```

, , FALSE

	N/T	Mean	SD	Min	Max	Skew	Kurt
Overall	9503	63.5476	9.2368	18.907	85.4171	-0.7394	2.7961
Between	171	63.5476	6.0788	43.0905	85.4171	-0.8041	3.082
Within	55.5731	65.8807	6.9545	30.3388	82.8832	-1.0323	4.0998
, , TRUE							
	N/T	Mean	SD	Min	Max	Skew	Kurt
Overall	2156	74.9749	5.3627	45.369	84.3563	-1.2966	6.5505
Between	36	74.9749	2.9256	66.2983	78.6733	-1.3534	4.5999
Within	59.8889	65.8807	4.4944	44.9513	77.2733	-0.627	3.9839

 25 This is more efficient and equal to using the between transformation if the panel is balanced.

The output shows that the variation in life expectancy is significantly larger for non-OECD countries and that for these countries, the between- and within-country variation is approximately equal in magnitude.²⁶ For more detailed (grouped, weighted) statistics, descr() provides a rich statistical description of variables in a dataset.

```
R> descr(wlddev, LIFEEX ~ OECD, w = ~ replace_na(POP))
```

```
Dataset: wlddev, 1 Variables, N = 13176, WeightSum = 313233706778
Grouped by: OECD [2]
           Ν
              Perc
                         WeightSum
                                    Perc
       10980 83.33
                    2.49344474e+11
FALSE
                                    79.6
TRUE
        2196 16.67
                    6.38892329e+10
                                    20.4
         _____
LIFEEX (numeric): Life expectancy at birth, total (years)
Statistics (N = 11659, 11.51% NAs)
             Perc Ndist
                                   SD
                                                            Kurt
         Ν
                           Mean
                                         Min
                                                Max
                                                      Skew
FALSE
      9503
            81.51
                    8665
                          63.55
                                 9.24
                                       18.91
                                              85.42
                                                     -0.74
                                                             2.8
TRUE
       2156
            18.49
                     2016
                          74.97 5.36
                                       45.37
                                              84.36
                                                      -1.3
                                                            6.55
Quantiles
          1%
                5%
                      10%
                             25%
                                    50%
                                           75%
                                                  90%
                                                         95%
                                                                99%
     41.39
             45.78
                    49.08
                           57.51
                                  65.98
                                         70.14
                                                74.12
                                                       75.63
                                                              76.91
FALSE
                                                       82.43
TRUE
       56.65
              65.98
                      69.7
                           71.85
                                  75.38
                                         78.64
                                                81.26
                                                               83.6
```

While descr() does not support panel-variance decompositions like qsu(), it also computes detailed (grouped, weighted) frequency tables for categorical data and is thus very utile with complex surveys. A stepwise argument toggles describing one variable at a time, allowing users to naturally 'click-through' a large dataset rather than printing a massive output to the console. More details and examples are in the documentation. Both qsu() and descr() provide an as.data.frame() method for efficient tidying and further analysis.

A final noteworthy function from **collapse**'s descriptive statistics toolkit is qtab(), an enhanced drop-in replacement for base::table. It is enhanced both in a statistical and computational sense, providing a remarkable performance boost, an option (sort = FALSE) to preserve the first-appearance-order of vectors being cross-tabulated, support for frequency weights (w), and the ability to compute different statistics representing table entries using these weights - vectorized when using *Fast Statistical Functions*, as demonstrated below.

```
R> library("magrittr")
R> wlda15 <- wlddev |> fsubset(year >= 2015) |> fgroup_by(iso3c) |> flast()
R> wlda15 %$% qtab(OECD, income)
```

```
income
OECD High income Low income Lower middle income Upper middle income
```

 $^{^{26}}$ qsu() also has a convenient formula interface to perform these transformations in an ad-hoc fashion, e.g., the above can be obtained using qsu(wlddev, LIFEEX OECD, iso3c, POP, higher = TRUE), without prior indexation.

collapse: Advanced and Fast Data Transformation in R

FALSE	45	30	47	58
TRUE	34	0	0	2

This shows the total population (latest post-2015 estimates) in millions.

R> wlda15 %\$% qtab(OECD, income, w = POP) %>% divide_by(1e6)

	income	Э								
OECD	High	income	Low	income	Lower	middle	income	Upper	middle	income
FALSE		93.01		694.89		:	3063.54			2459.71
TRUE	-	1098.75		0.00			0.00			211.01

This shows the average life expectancy in years. The use of fmean() toggles an efficient vectorized computation of the table entries (i.e., fmean() is only called once).

R> wlda15 %\$% qtab(OECD, income, w = LIFEEX, wFUN = fmean) %>% replace_na(0)

:	income	e								
OECD	High	income	Low	income	Lower	middle	income	Upper	middle	income
FALSE		78.75		62.81			68.30			73.81
TRUE		81.09		0.00			0.00			76.37

Finally, this calculates a population-weighted average of life expectancy in each group.

R> wlda15 %\$% qtab(OECD, income, w = LIFEEX, wFUN = fmean, + wFUN.args = list(w = POP)) %>% replace_na(0)

	income	Э								
OECD	High	income	Low	income	Lower	middle	income	Upper	middle	income
FALSE		77.91		63.81			68.76			75.93
TRUE		81.13		0.00			0.00			76.10

'qtab' objects inherit the 'table' class, thus all 'table' methods apply. Apart from the above functions, collapse also provides functions pwcor, pwcov, pwnobs for convenient (pairwise, weighted) correlations, covariances, and observations counts, and also functions psacf, pspacf and psccf for auto- and cross-covariance and correlation function estimation on panel series.

8. Global options

collapse is globally configurable to an extent few packages are: the default value of key function arguments governing the behavior of its algorithms, and the exported namespace, can be adjusted interactively through the **set_collapse()** function. These options are saved in an internal environment called .op (for safety and performance reasons) visible in the documentation of some functions. Its contents can be accessed using get_collapse().

The current set of options comprises the default behavior for missing values (na.rm arguments in all statistical functions and algorithms), sorted grouping (sort), multithreading and algorithmic optimizations (nthreads, stable.algo), presentational settings (stub, digits, verbose), and, surpassing all else, the package namespace itself (mask, remove).

As evident from previous sections, **collapse** provides performance-improved or otherwise enhanced versions of functionality already present in base R (like the *Fast Statistical Functions*, funique(), fmatch(), fsubset(), ftransform(), etc.) and other packages (esp. dplyr (Wickham *et al.* 2023a): fselect(), fsummarise(), fmutate(), frename(), etc.). The objective of being namespace compatible warrants such a naming convention, but this has a syntactical cost, particularly when **collapse** is the primary data manipulation package.

To reduce this cost, **collapse**'s **mask** option allows masking existing R functions with the faster **collapse** versions by creating additional functions in the namespace and instantly exporting them. All **collapse** functions starting with 'f' can be passed to the option (with or without the 'f'), e.g., set_collapse(mask = c("subset", "transform")) creates subset <- fsubset and transform <- ftransform and exports them. Special functions are "n", "table"/"qtab", and "%in%", which create n <- GRPN (for use in (f)summarise/(f)mutate), table <- qtab, and replace %in% with a fast version using fmatch, respectively. There are also several convenience keywords to mask related groups of functions. The most powerful of these is "all", which masks all f-functions + specials, as shown below.

The above is now 100% **collapse** code. Similarly, using this option, all code in this article could have been written without f-prefixes. Thus, **collapse**, together with namespace masking, is able to provide a fast and syntactically clean experience of R - without the need to even restart the session. Masking is completely interactive and reversible within the active session: calling set_collapse(mask = NULL) instantly removes the additional functions. Option remove can further be used to remove any collapse function from the list of exported functions, allowing manual conflict management. Function fastverse::fastverse_conflicts() from the related fastverse project²⁷ can be used to display namespace conflicts with collapse. Invoking

²⁷Website: https://fastverse.github.io/fastverse/

either mask or remove detaches collapse and reattaches it at the top of the search path, letting its namespace to take precedence over other packages.

9. Benchmark

This section offers a small benchmark to demonstrate that **collapse** provides best-in-R performance for many basic statistical and data manipulation tasks. They are executed on an Apple M1 MacBook Pro with 16 GB unified memory. The DuckDB Benchmarks compare more software packages on larger datasets, using a large server with many (slow) cores.²⁸

```
expr
           min
                  lq
                       mean median
                                             max neval
                                       uq
       R 9.827 9.858 10.061
                             9.885 9.970 16.701
                                                   100
  Rfast 1.349 1.819
                      2.135
                             1.877 2.009 11.236
                                                   100
collapse 1.321 1.475
                      1.728
                             1.521 1.701 5.502
                                                   100
```

 28 A lot may be said about benchmarking **collapse**, which would be beyond the scope of this article. Users should note, however, that its defaults (na.rm = TRUE, sort = TRUE, stable.algo = TRUE, nthreads = 1) cater to convenience rather than maximum performance. For maximum performance, set these 3 settings to FALSE and increase the number of threads. To also provide a minimalistic guide for R users seeking to understand the relative performance of collapse and data.table, reflecting current (spring 2024) developments: collapse has highly efficient algorithms for grouping and computing statistics, but presently does not provide sub-column level parallel grouping architecture. Simple statistics like fmean() are parallelized across columns and perform grouped computations in a single pass. More complex ones fmedian(), fmode() have group-level parallelism. data.table, on the other hand, has sub-column parallel grouping and also group-level parallel implementations for simple statistics such as mean(), but no parallelism for complex statistics such as median(). data.table's GForce optimization also only applies to simple statistics. not complex expressions or weighted statistics - as can be vectorized using Fast Statistical Functions in collapse. Thus, if your data is moderately sized (≤ 100 mio. obs.), you have more than 1 column to compute on, you want to do complex statistical things, or if your processor is very fast (high single core speed), collapse is a great choice. On the other hand, if your data is really long (>100mio. obs.), you have only a few columns to compute on, you are computing simple statistics that **data.table** optimizes, and you have massive parallel compute, then **data.table** is a great choice. My recommendation: use both, just need to call library(fastverse). Finally, let me note that polars uses optimized memory buffers based on Apache Arrow, multithreaded hash-based grouping, SIMD instructions and multithreading at the group-level, and \mathbf{a} query optimizer - all implemented in Rust, a thread-safe programming language. While some of these parallel algorithms could be ported to collapse, this is more challenging since C, and particularly R's C API, is not thread safe - and it would still be lacking the benefits of Arrow memory buffers. At core, R is a 30-year old statistical language and not intended to work like an optimized database. collapse seamlessly integrates with R's data structures; polars, at present, has nothing to do with them (and is therefore also not part of this benchmark).

```
R> microbenchmark(R = rowsum(data, g, reorder = FALSE),
                 data.table = data[, lapply(.SD, sum), by = g],
+
                 collapse = fsum(data, g))
+
Unit: milliseconds
      expr
                      lq mean median
                                         uq
                                                max neval
             min
         R 11.002 11.331 12.255 11.516 11.946 24.269
                                                      100
 data.table 13.918 19.036 21.956 19.746 21.676 64.273
                                                      100
   collapse 1.911 2.743 3.408 3.136 3.702 6.514 100
R> add_vars(data) <- g
R> microbenchmark(data.table = data[, lapply(.SD, median), by = g],
                 collapse = data |> fgroup_by(g) |> fmedian())
+
Unit: milliseconds
      expr min lq mean median uq max neval
 data.table 136.94 137.72 141.04 138.48 140.01 265.1
                                                     100
   collapse 70.48 76.56 81.03 79.72 82.17 191.9
                                                     100
R > d <- data.table(g = unique(g), x = 1, y = 2, z = 3)
R> microbenchmark(data.table = d[data, on = "g"],
                 collapse = join(data, d, on = "g", verbose = 0))
+
Unit: milliseconds
      expr min
                    lq mean median
                                               max neval
                                         uq
 data.table 9.153 12.140 24.382 14.118 20.849 66.701
                                                     100
   collapse 1.220 1.391 1.472 1.424 1.466 2.948
                                                     100
R> microbenchmark(data.table = melt(data, "g"),
                 collapse = pivot(data, "g"))
Unit: milliseconds
      expr min
                    lq mean median uq max neval
 data.table 11.96 15.34 22.6 16.63 18.41 75.20 100
   collapse 11.74 15.01 22.0 16.32 18.28 63.01
                                               100
R> settransform(data, id = rowid(g))
R> cols = grep("^V", names(data), value = TRUE)
R> microbenchmark(data.table = dcast(data, g ~ id, value.var = cols),
            collapse = pivot(data, ids = "g", names = "id", how = "w"))
+
Unit: milliseconds
                     lq mean median
      expr min
                                         uq max neval
 data.table 72.48 116.74 119.65 119.7 123.68 142.7 100
   collapse 55.83 87.97 92.83 90.6 93.19 200.7 100
```

The benchmark below further shows that **collapse** provides faster algorithms for basic computationally intensive operations such as unique values and matching. These algorithms power much of its functionality, such as efficient factor generation with qF(), cross-tabulation with qtab(), join()'s, pivot()'s, etc.

```
R> set.seed(101)
R> g_int <- sample.int(1e3, 1e7, replace = TRUE)</pre>
R> char <- c(letters, LETTERS, month.abb, month.name)
R> char <- outer(char, char, paste0)
R> g_char <- sample(char, 1e7, replace = TRUE)</pre>
R> microbenchmark(base_int = unique(g_int), collapse_int = funique(g_int),
               base_char = unique(g_char), collapse_char = funique(g_char))
+
Unit: milliseconds
                          lq mean median
          expr
                  min
                                                     max neval
                                               uq
      base_int 60.294 63.508 65.73 65.251
                                            66.62 110.97
                                                           100
  collapse_int 8.677 9.347 10.49 9.595
                                           10.91
                                                   15.83
                                                           100
     base_char 92.569 95.032 99.15 98.483 100.67 141.98
                                                           100
 collapse_char 21.756 23.128 24.91 23.691 24.46 88.37
                                                           100
R> microbenchmark(base_int = match(g_int, 1:1000),
                  collapse_int = fmatch(g_int, 1:1000),
+
                  base_char = match(g_char, char),
+
+
                  data.table_char = chmatch(g_char, char),
+
                  collapse_char = fmatch(g_char, char), times = 10)
Unit: milliseconds
            expr
                   min
                           lq
                                mean median
                                                        max neval
                                                  uq
        base_int 27.24 27.502 29.085 28.093
                                              30.789
                                                      32.41
                                                               10
    collapse int 8.78 8.867 9.429 8.891
                                               9.185
                                                      13.29
                                                               10
       base_char 94.72 96.474 99.857 97.048 101.644 110.06
                                                               10
 data.table_char 42.21 42.412 44.063 42.758
                                              43.287
                                                      51.68
                                                               10
   collapse_char 36.61 36.769 37.592 36.959 37.667 41.62
                                                               10
```

Apart from the raw algorithmic efficiency demonstrated here, **collapse** is often more efficient than other solutions by simply doing less. For example, if grouping columns are factor variables, **collapse**'s algorithms in funique(), group() or fmatch(), etc., use the values as hashes without checking for collisions. Similarly, if data is already sorted/unique, it is directly returned by functions like roworder()/funique().

10. Conclusion

It is coming close to 4 years since the first CRAN release of **collapse** in March 2020, and since then, the package has grown and matured considerably. At the time of writing this article in early 2024, it has been downloaded >1.5 million times off CRAN. In this article, I have articulated key ideas and design principles and demonstrated some core features of the package. In summary, my work with R as an applied economist has led me to believe that there should be a new foundation package for statistical computing and data manipulation in R that is statistically advanced, class-agnostic, flexible, fast, lightweight, stable, and able to manipulate complex scientific data with ease. **collapse** is my attempt at providing such a package, and the feedback I have received over the years, particularly from users in academia, government, and international organizations, is a strong indication that I have responded to a need felt in larger parts of the R community. As mentioned, a single article cannot comprehensively introduce **collapse**, but there is a modern website with comprehensive documentation resources.

Computational details

The results in this paper were obtained using R (R Core Team 2023) 4.3.0 with collapse 2.0.10, data.table 1.15.0, Rfast 2.1.0, fixest 0.11.3, magrittr (Bache and Wickham 2022) 2.0.3 and microbenchmark (Mersmann 2023) 1.4.10. All packages used are available from the Comprehensive R Archive Network (CRAN) at https://CRAN.R-project.org/. The benchmark was run on an Apple M1 MacBook Pro (2020) with 16GB unified memory. Packages were compiled from source using Homebrew Clang version 16.0.4 with OpenMP enabled and the -O3 optimization flag.

Acknowledgments

The source code of **collapse** has been heavily inspired by (and partly copied from) **data.table** (Matt Dowle and Arun Srinivasan), R's source code (R Core Team and contributors worldwide), the **kit** package (Morgan Jacob), and **Rcpp** (Dirk Eddelbuettel). Packages **plm** (Yves Croissant, Giovanni Millo, and Kevin Tappe) and **fixest** (Laurent Berge) have also provided a lot of inspiration (and a port to its demeaning algorithm in the case of **fixest**). I also thank many people from diverse fields for helpful answers on Stackoverflow and many other people for encouragement, feature requests, and helpful issues and suggestions.

References

- Bache SM, Wickham H (2022). magrittr: A Forward-Pipe Operator for R. R package version 2.0.3, URL https://CRAN.R-project.org/package=magrittr.
- Bengtsson H (2023). matrixStats: Functions that Apply to Rows and Columns of Matrices (and to Vectors). R package version 1.0.0, URL https://CRAN.R-project.org/package=matrixStats.
- Bergé L (2018). "Efficient Estimation of Maximum Likelihood Models with Multiple Fixed-Effects: the R Package **FENmlm**." *CREA Discussion Papers*, (13).
- Bouchet-Valat M, Kamiński B (2023). "DataFrames.jl: Flexible and Fast Tabular Data in Julia." Journal of Statistical Software, 107(4), 1-32. doi:10.18637/jss.v107.i04. URL https://www.jstatsoft.org/index.php/jss/article/view/v107i04.
- Chau J (2022). *rrapply:* Revisiting Base Rapply. R package version 1.2.6, URL https://CRAN.R-project.org/package=rrapply.
- Croissant Y, Millo G (2008). "Panel Data Econometrics in R: The **plm** Package." Journal of Statistical Software, **27**(2), 1–43. doi:10.18637/jss.v027.i02.
- Dowle M, Srinivasan A (2023). *data.table:* Extension of 'data.frame'. R package version 1.14.8, URL https://CRAN.R-project.org/package=data.table.
- Harris CR, et al. (2020). "Array programming with **NumPy**." Nature, **585**, 357–362. doi:10.1038/s41586-020-2649-2.
- Hyndman RJ, Fan Y (1996). "Sample Quantiles in Statistical Packages." American Statistician, pp. 361–365.
- JuliaStats (2023). "StatsBase.jl: Julia Package for Basic Statistics." URL https://github.com/JuliaStats/StatsBase.jl.
- Larmarange J (2023). *labelled:* Manipulating Labelled Data. R package version 2.12.0, URL https://CRAN.R-project.org/package=labelled.
- Lumley T (2004). "Analysis of Complex Survey Samples." Journal of Statistical Software, **9**(1), 1–19. R package verson 2.2.
- Mersmann O (2023). microbenchmark: Accurate Timing Functions. R package version 1.4.10, URL https://CRAN.R-project.org/package=microbenchmark.
- Mundlak Y (1978). "On the Pooling of Time Series and Cross Section Data." *Econometrica:* Journal of the Econometric Society, pp. 69–85.
- Müller K, Wickham H (2023). *tibble: Simple Data Frames.* R package version 3.2.1, URL https://CRAN.R-project.org/package=tibble.
- pandas Development Team (2023). "pandas-dev/pandas: pandas." doi:10.5281/zenodo.10426137. URL https://doi.org/10.5281/zenodo.10426137.

- Papadakis M, et al. (2023). Rfast: A Collection of Efficient and Extremely Fast R Functions. R package version 2.1.0, URL https://CRAN.R-project.org/package=Rfast.
- Pebesma E (2018). "Simple Features for R: Standardized Support for Spatial Vector Data." The R Journal, 10(1), 439–446. doi:10.32614/RJ-2018-009. URL https://doi.org/10.32614/RJ-2018-009.
- R Core Team (2023). R: A Language and Environment for Statistical Computing. R Foundation for Statistical Computing, Vienna, Austria. URL https://www.R-project.org/.
- Ryan JA, Ulrich JM (2023). **xts**: eXtensible Time Series. R package version 0.13.1, URL https://CRAN.R-project.org/package=xts.
- Signorell A (2023). **DescTools**: Tools for Descriptive Statistics. R package version 0.99.52, URL https://CRAN.R-project.org/package=DescTools.
- StataCorp LLC (2023). STATA Statistical Software: Release 18. College Station, TX. URL https://www.stata.com.
- Vink R, et al. (2023). "pola-rs/polars: Python polars 0.20.2." doi:10.5281/zenodo.10413093. URL https://doi.org/10.5281/zenodo.10413093.
- Wang E, et al. (2020). "A New Tidy Data Structure to Support Exploration and Modeling of Temporal Data." Journal of Computational and Graphical Statistics, 29(3), 466–478. doi:10.1080/10618600.2019.1695624. URL https://doi.org/10.1080/10618600.2019.1695624.
- Wes McKinney (2010). "Data Structures for Statistical Computing in Python." In Stéfan van der Walt, Jarrod Millman (eds.), *Proceedings of the 9th Python in Science Conference*, pp. 56 61. doi:10.25080/Majora-92bf1922-00a.
- Wickham H (2007). "Reshaping Data with the reshape Package." Journal of Statistical Software, 21(12), 1-20. URL http://www.jstatsoft.org/v21/i12/.
- Wickham H (2014). "Tidy Data." Journal of Statistical Software, **59**(10), 1-23. doi:10.18637/jss.v059.i10. URL https://www.jstatsoft.org/index.php/jss/article/view/v059i10.
- Wickham H, Henry L (2023). purr: Functional Programming Tools. R package version 1.0.1, URL https://CRAN.R-project.org/package=purr.
- Wickham H, et al. (2019). "Welcome to the tidyverse." Journal of Open Source Software, 4(43), 1686. doi:10.21105/joss.01686.
- Wickham H, et al. (2023a). dplyr: A Grammar of Data Manipulation. R package version 1.1.2, URL https://CRAN.R-project.org/package=dplyr.
- Wickham H, et al. (2023b). tidyr: Tidy Messy Data. R package version 1.3.0, URL https://CRAN.R-project.org/package=tidyr.

Affiliation:

Sebastian Krantz Kiel Institute for the World Economy Haus Welt-Club Düsternbrooker Weg 148 24105 Kiel, Germany E-mail: sebastian.krantz@ifw-kiel.de