Low-Cost Privacy-Preserving Decentralized Learning

Sayan Biswas*, Davide Frey[†], Romaric Gaudel[†], Anne-Marie Kermarrec*,

Dimitri Lerévérend[†], Rafael Pires^{*}, Rishi Sharma^{*}, François Taïani[†]

*EPFL, Switzerland.

Email: <first_name>.<last_name>@epfl.ch [†]Univ Rennes, Inria, CNRS, IRISA Email: <first name>.<last name>@irisa.fr

Abstract—This paper introduces ZIP-DL, a novel privacy-aware decentralized learning (DL) algorithm that exploits correlated noise to provide strong privacy protection against a local adversary while yielding efficient convergence guarantees for a low communication cost. The progressive neutralization of the added noise during the distributed aggregation process results in ZIP-DL fostering a high model accuracy under privacy guarantees. ZIP-DL further uses a single communication round between each gradient descent, thus minimizing communication overhead. We provide theoretical guarantees for both convergence speed and privacy guarantees, thereby making ZIP-DL applicable to practical scenarios. Our extensive experimental study shows that ZIP-DL significantly outperforms the state-of-the-art in terms of vulnerability/accuracy trade-off. In particular, ZIP-DL (i) reduces the efficacy of linkability attacks by up to 52 percentage points compared to baseline DL, (ii) improves accuracy by up to 37 percent w.r.t. the state-of-the-art privacy-preserving mechanism operating under the same threat model as ours, when configured to provide the same protection against membership inference attacks, and (iii) reduces communication by up to $10.5 \times$ against the same competitor for the same level of protection.

1. Introduction

Decentralized learning (DL) allows a collection of machines to train a global model collaboratively without sharing raw training data. This approach has drawn increasing attention from both academia [1] and industry, showcasing its potential across various sectors, including healthcare [2], [3] and autonomous vehicles [4]. In DL, each device (henceforth node) (i) trains a local model using its own data; (ii) exchanges this model with those of its neighbors according to the underlying communication topology; and *(iii)* averages its current local model with the models received from neighbors. This iterative process repeats until convergence is reached [5], [6]. Although training data never leaves participating nodes in DL, the models that nodes exchange still leak information. Exploiting these leaks, an honest-but-curious attacker can launch privacy attacks against participants, including Membership-Inference Attacks (MIAs) [7], which reveal whether a particular sample

belongs to the training set of a node, and gradient-inversion attacks [8], [9], aimed at recreating training samples from model updates.

Differential Privacy (DP) [12] is a widely-used measure of formal privacy guarantees that has been applied to the design of privacy-preserving DL [13]. DP strategically adds noise to data so that the inclusion or exclusion of a data point becomes much harder to detect. However, DP typically assumes a worst-case threat model in which an attacker can access all messages transiting on the network. As a result, and although it provides robust privacy guarantees, DP tends to require high noise levels that disrupt the learning process and severely impair the system's utility.

Following existing literature [10], [11], we assume a weaker yet representative threat model in which local honestbut-curious attackers can only observe the messages they receive. An attack is furthermore considered successful only if the obtained information can be linked to its contributing participant. This model covers a wide range of scenarios in which network communication is protected, but nodes participating in the distributed learning process can exploit their partial knowledge of the system to breach the privacy of other participants. To specifically address this threat model, Muffliato [11] introduces Pairwise Network Differential Privacy (PNDP). In contrast to DP that captures a global privacy measure, PNDP tracks privacy loss at a finer level, between pairs of nodes. As a result, PNDP lends itself to lower noise levels, faster convergence, and better accuracy. Unfortunately, its use so far requires multiple rounds of averaging [11], leading to high network costs.

This paper explores the use of correlated noise to achieve PNDP without significant network costs. Correlated noise—a natural evolution of noise-based privacy methods—protects individual node inputs while minimizing the impact on model accuracy. Although systems using correlated noise show promising convergence [10], their privacy implications remain underexplored. Several approaches using correlated noise have been formulated [13], [14], [15], but most of them either rely on a trusted aggregator to cancel out the noises [13], [14] or on pair-wise coordination between nodes, which comes at a cost either in communication or in utility [15].

We introduce ZIP-DL (zero-sum-noise privacy-

TABLE 1. POSITION OF OUR WORK COMPARED TO PREVIOUS APPROACHES.

Approach	Masking (RSS-NB)	RSS-LB	MUFFLIATO	ZIP-DL
	[10]	[10]	[11]	(ours)
Formal privacy guarantees No P2P coordination One averaging round Communication cost Impact on Converge Rate	X X Moderate None	× ✓ Low High	✓ ✓ High High	✓ ✓ Low Low

preserving decentralized learning), a privacy-preserving algorithm that leverages correlated noise in a single communication round while offering formal privacy guarantees. ZIP-DL (see Table 1) is the only approach (*i*) with formal guarantees that (*ii*) requires no prior pair-wise coordination between nodes, and (*iii*) only requires a single averaging round per gradient step. In addition to ZIP-DL, we make the following contributions:

- We prove that our approach converges even though it uses a single communication round per gradient step. This powerful property results from the fact that the sum of the noises added to the communication rounds is zero. Moreover, our analysis shows that the impact of the noise on the convergence rate is minimal compared to the state-of-the-art.
- We provide a formal privacy guarantee of our approach in terms of PNDP, including in the context of colluding attackers.
- We conduct an extensive evaluation study comparing ZIP-DL to Muffliato and standard DL under thresholdbased membership inference attacks on the CIFAR-10 dataset partitioned in a non independent-and-identicallydistributed (non-IID) manner. Our results show that ZIP-DL provides the best trade-off between accuracy and privacy while maintaining low communication overhead. In particular, ZIP-DL reduces the success rate of linkability attacks by up to 52 percentage points while only entailing a loss of 4 percentage points in test accuracy by up to 37 percent and reduces communication costs by up to 10.5× w.r.t. Muffliato when configured to provide the same protection.

The rest of the paper is organized as follows: Section 2 presents related work with similar objectives as this paper. Section 3 provides the necessary background and threat model. Section 4 presents the design of ZIP-DL and its core properties. Sections 5 and 6 present the theoretical guarantees of our privacy-preserving algorithm, in terms of convergence rate and privacy. We present the results of our experimental study in Section 7 before concluding (Section 8).

2. Related work

Privacy attacks. Many privacy attacks have been proposed that target the models and gradients of Machine Learning systems [7], [8], [9], [16], [17]. A large part of this literature, however, focuses on attacking a single model

or gradient. As a result, attacks that exploit the many model releases produced by DL tend to be less understood and remain an evolving field [18].

Criteria of Differential Privacy. In a decentralized scenario, DP can be instantiated in different ways. The most well-studied variants are *local differential privacy* (LDP) [19] and *central differential privacy* (CDP). The former assumes all other nodes to be an attacker, whereas the latter only provides guarantees on a final, averaged model. It has been shown that the optimal tradeoff in both cases differs by a factor of n, the number of nodes [20]. To bridge this gap, relaxations of the strict scenario of LDP have been proposed [11], [15]. These relaxations include PNDP, which we consider in this work.

Correlated noises. Correlated noises are a natural choice when seeking to reduce the utility cost of privacy. However, most of the literature focuses on a correlation across nodes [13], [14], [15]. In order to perform such correlation, participating nodes need to rely either on a trusted aggregator, so that the noise can cancel out [13], [14], or on an agreement between nodes [13], [15]. We argue that the former is not always achievable, nor desirable, and the latter comes at a cost in terms of communication or utility [15].

A recent approach also leveraging correlated noises, DECOR [15], assumes that the channels between nodes may get compromised, and considers an adversary with access to every message transmitted on the network. Under this strong threat model, DECOR leverages shared secrets and introduces a novel privacy criterion, *secret-based local differential privacy* (SecLDP), that is orthogonal to PNDP, which we consider here. In particular, SecLDP is conditioned on the number of pair-wise secrets compromised by the attacker. To counter such a strong adversary, DECOR injects a combination of independent and correlated noises that require pair-wise coordination between nodes. This strategy comes at a cost in terms of convergence and accuracy, a point we revisit in Section 5.2.

Secret sharing. Other variants of correlated noise, such as *secret sharing* [21] can be used in the context of DL [22]. In a decentralized context, while additive secret sharing does not necessarily involve coordination among nodes or a trusted aggregator, it requires multiple averaging rounds to reconstruct the shared secret. Thus, additional operations such as gradient descent cannot be mixed together with the communication process, leading to prohibitive communication costs.

Other notions of privacy. Other cryptographic approaches include *secure multiparty computation* [23] and *secure aggregation* [24]. In these techniques, nodes agree on masks that conceal local models during the averaging process. Despite providing exact solutions to model averaging, they impose a significant drawback by requiring nodes to coordinate in order to set up and remove the masking. In large and dynamic distributed systems, this requirement may prove infeasible, especially in real-world scenarios involving mobile devices.

3. Preliminaries

3.1. Decentralized learning

We consider a set of n nodes $\mathcal{V} = \llbracket 1, n \rrbracket$ whose aim is to solve a DL problem without sharing raw training data. While each node $a \in \mathcal{V}$ stores a local data distribution \mathcal{D}_a , the goal is to determine the model parameters $x^* \in \mathbb{R}^d$ that optimize the learning problem over all local datasets. This is done by minimizing an average loss function:

$$\underset{x \in \mathbb{R}^d}{\operatorname{argmin}} \left[f(x) = \frac{1}{n} \sum_{a=1}^{n} \underbrace{\mathbb{E}_{\xi \sim \mathcal{D}_a} \left[F_a(x;\xi) \right]}_{f_a(x)} \right], \qquad (1)$$

where $f_a(x)$ represents the local objective function associated with the node a, and $F_a(x;\xi)$ quantifies the prediction loss associated with the model parameters x for the sample ξ , potentially encompassing non-convex characteristics.

To solve Equation (1) we proceed in T successive iterations, with each node a keeping its own local model $x_a^{(t)}$ for each iteration $t \in [\![0,T]\!]$. The goal is to make the averaged model $\bar{x}^{(t)} := \frac{1}{n} \sum_{a=1}^{n} x_a^{(t)}$ converge to x^* .

Specifically, the corresponding learning process involves collaborative interactions between nodes, which are connected by an evolving communication topology. At each iteration t, each node first trains its model on its local data and then aims to average it with the models of other nodes. During the averaging step, each node restricts its communication to its neighbors in the communication topology using gossip averaging (Section 3.2). Yet, sharing only model parameters may still leak sensitive information, thus hurting privacy.

3.2. Gossip averaging

Many DL algorithms rely on gossip averaging to estimate and share the average model $\bar{x}^{(t)} := \frac{1}{n} \sum_{a=1}^{n} x_a^{(t)}$ at each iteration t [25], [26]. A gossip averaging can consist of multiple successive rounds, where in each round s the nodes communicate according to a gossip matrix $W^{(t,s)}$ in the following manner: each node a sends a message $m_{a\to v}^{(t,s)} \in \mathbb{R}^d$ to each neighbor v, and $W_{a,v}^{(t,s)}$ denotes the weight that node a gives to the received message $m_{v\to a}^{(t,s)}$. In the simplest setting, $m_{a\to v}^{(t,s)}$ corresponds to the current local estimate of $\bar{x}^{(t)}$, this estimate is updated to $\sum_{v\in\mathcal{V}} W_{a,v}^{(t,s)} m_{v\to a}^{(t,s)}$, and it converges to $\bar{x}^{(t)}$ as s tends to infinity. We make the following assumption on $W^{(t,s)}$:

Assumption 1. All gossip matrices are stochastic, $\forall a \in \mathcal{V}, \sum_{v \in \mathcal{V}} W_{a,v}^{(t,s)} = 1$, and symmetric, ${}^{\mathsf{T}}W^{(t,s)} = W^{(t,s)}$.

While the symmetry assumption is not always necessary [25], [26], it is a common assumption for complexity proofs that enables tighter bounds [11], [27]. In our case, it enables convergence and privacy analysis. However, this assumption could be removed by adding an exchange of weights between neighboring nodes prior to noise generation.

We also denote by $\Gamma_a^{(t,s)}$ the set of neighbors to which node *a* sends its model, and $d_a^{(t,s)}$ the corresponding degree of *a*. Formally, we have $\Gamma_a^{(t,s)} := \{v \in \mathcal{V} \mid W_{v,a}^{(t,s)} \neq 0\}$, where node *a* can be in $\Gamma_a^{(t,s)}$. Note that, due to Assumption 1 the networks are symmetric: $v \in \Gamma_a^{(t,s)} \iff a \in \Gamma_v^{(t,s)}$.

Finally, several averaging approaches add a mask [24] or noise [11] to the messages to protect the privacy of the nodes' data. In this paper, we focus on noise-based approaches as they require less coordination and are more resilient to collusion between attackers.

Remark 1. In DL, the averaging step does not need to reach exactly the same model at each node. Therefore, the rounds can be stopped before full convergence. In ZIP-DL, even one round is sufficient (s = 1). Thus, in the rest of the paper, we will omit s in notations related to the aggregation.

3.3. Threat model

We aim to protect the privacy of user data against *honest-but-curious* participating nodes during the training. This scenario is in line with related work [8], [11], where the attacker can observe information about a victim node during training but does not deviate from the algorithm. We consider the attacker to be a node (or a set of nodes) of the training algorithm, but this can be extended to an attacker eavesdropping on a node's communication. The attacker's goal is to gain some information about the victim's data distribution, which we quantify in terms of PNDP (see. Section 6 for a formal definition).

What drives this privacy definition is the observation that privacy loss is not equal between all nodes in a distributed algorithm: close neighbors in the communication topology will receive more information from a node than nodes that are further away.

To empirically evaluate the approaches, we conduct two types of Membership-Inference Attack (MIA) that consider a strong attacker with knowledge of the global training set, its elements, and how it is partitioned. The only thing the attacker does not know is which partition nodes are given. The goal is to use a victim's message to (i) infer whether a particular training sample was used to train the victim's model, and (ii) infer which partition of the global training set the node has been given. More details are given in Section 7.1.

Symbol	Usage
\mathcal{V}	Set of all the nodes that participate in the training.
n	Number of nodes in \mathcal{V} .
a, u, v	Nodes in \mathcal{V} .
$\Gamma_a^{(t,s)}$	Neighbors of node a at averaging round s , after learning iteration t .
$d_a^{(t,s)}$	Degree of node a at averaging round s , after learning iteration t .
d_a	Maximum degree of node a, over learning iterations and averaging rounds.
$W^{(t,s)}$	Gossip matrix at averaging round s , after learning iteration t .
p	Mixing parameter of the gossip matrices (Assumption 1).
$x_a^{(t)}$	Model of node a at learning iteration t .
$\bar{x}^{(t)}$	Average model at learning iteration t .
$x_a^{(t+1/2)}$	Model of node a at learning iteration t after the gradient step.
$\bar{x}^{(t+1/2)}$	Average model at learning iteration t after the gradient step.
x^*	Optimal model.
f^*	Minimum of the global loss function.
\mathcal{D}_a	Data distribution of node a.
$\xi_a^{(t)}$	Data sample drawn from \mathcal{D}_a .
F_a	Loss function of node a.
f_a	Sampled (or expected) loss of node a (Equation (1)).
f	Globally sampled loss (Equation (1)).
μ	Convexity constant (Assumption 2).
L	Smoothness constant (Assumption 2).
ϑ_i^2	Noise level at the optimum (Assumption 4).
ω_i^2	Diversity of the data distribution at the optimum (Assumption 4).
γ	Stepsize of the gradient descent.
$Y_{a \to v}^{(t)}$	Intermediate noise generated by node a destined to v at learning iteration t .
$Z_{a \to v}^{(t)}$	ZIP-DL-averaging noise from node a to node v at learning iteration t .
ς_a^2	Variance of $Y_{a \to v}^{(t)}$.
$(\sigma_{a \to v}^{(t)})^2$	Variance of $Z_{a \to v}^{(t)}$.
Δ	Adjacent datasets bound (Assumption 6).
$g^{(T)}(a,v)$	Privacy bound from node a to node v at timestamp T (Definition 2).
$\hat{X}^{(t)}$	Virtual models vector at time t.
$\hat{\chi}^{(t)}$	Unnoised virtual execution (with the same graphs and batches, but no noise) at time t .
Ŵ	(Virtual) Mixing matrix (Equation (8))

TABLE 2. LIST OF THE MAIN SYMBOLS USED IN THIS WORK.

Algorithm	1	ZIP-DL-averaging	for	a	node	<i>a</i> .

Input: local model x_a , stepsize γ , privacy parameter ς_a . **Output**: Localized model average with correlated noise.

- 1: Get the gossip weights W_a , $d_a \leftarrow |\Gamma_a|$ 2: Draw $Y_{a \to v} \sim \mathcal{N}(0, \gamma^2 \varsigma_a^2)$ for $v \in \Gamma_a$ 3: $Z_{a \to v} = Y_{a \to v} - \frac{1}{d_a W_{a,v}} \sum_{j \in \Gamma_a} W_{a,j} Y_{a \to j}$ 4: for all $v \in \Gamma_a$ do 5: Send $x_a + Z_{a \to v}$ to v6: Receive $x_v + Z_{v \to a}$ from v7: end for
- 8: return $\sum_{v \in \Gamma_a} W_{a,v}(x_v + Z_{v \to a})$

4. ZIP-DL: Locally-Correlated Noise

4.1. ZIP-DL in a nutshell

Gossip averaging typically requires multiple averaging rounds to provide a good estimate of the average of nodes' individual inputs [28]. Unfortunately, in DL, since averaging is required at each learning iteration, these averaging rounds add up to a substantial network cost. We drastically reduce this overhead by performing a single averaging round per learning iteration. Without noise, the cumulative effect of one-round averaging between each descent step is enough to ensure convergence [25], [26], [29].

ZIP-DL adds noise to this process to provide PNDP. Because one-round averaging is limited to a node's neighbors, the residual noise in partially averaged models remains high, which may disrupt learning. We mitigate this effect by *correlating* the injected noise such that it sums to zero over each node's neighborhood. The correlation is local and eschews any coordination between neighbors.

In the following, we first detail the one-round localized averaging that lies at the core of ZIP-DL (Algorithm 1), before moving on to the resulting decentralized SGD learning algorithm (Algorithm 2). We then state some fundamental properties of ZIP-DL's global average model in Section 4.3.

4.2. Detailed description of ZIP-DL

ZIP-DL's model-averaging procedure is described in Algorithm 1. It relies on a stochastic communication topology [25] captured by the gossip matrix $W^{(t)}$, where t denotes

Algorithm	2	Zip-DL	for	а	node	a.
-----------	---	--------	-----	---	------	----

Input $x_a^{(0)}$ the initial model, T the number of iterations. 1: for t = 0 to T - 1 do 2: Draw $\xi_a^{(t)} \sim \mathcal{D}_a$, compute $g_a^{(t)} := \nabla F_a(x_a^{(t)}, \xi_a^{(t)})$ 3: $x_a^{(t+1/2)} = x_a^{(t)} - \gamma g_a^{(t)}$ 4: $x_a^{(t+1)} = \text{ZIP-DL-averaging}(x_a^{(t+1/2)}, \gamma, \varsigma_a)$ 5: end for

the current learning iteration (Section 3.2). Node *a* first determines its neighborhood $\Gamma_a^{(t)}$ and the weights $W_a^{(t)}$ that its neighbors apply. Then, to protect its local data, a node *a* adds a noise $Z_{a\to v}^{(t)}$ to its model $x_a^{(t)}$ before sending it to each of its neighbors $v \in \Gamma_a^{(t)}$. By construction, these noises sum to zero (Lines 2-3) to discard their contribution to the global average. A node adapts how it protects its data by picking its own privacy parameter ς_a , which itself drives the variance $\gamma^2 \varsigma_a^2$ of the injected noises.

In contrast to [10], Algorithm 1 uses a *closed neighborhood* that includes the local node a (*i.e.*, $a \in \Gamma_a$). Hence, even if a is surrounded by attackers after an eclipse attack [30], a's model remains protected to some extent as the noises of the models sent to $\Gamma_a \setminus \{a\}$ do not cancel out.

ZIP-DL's main algorithm (Algorithm 2) is a DL algorithm. At each iteration t, each node a first performs a local gradient step on its local model $x_a^{(t)}$ to produce an intermediate model $x_a^{(t+1/2)}$ (Lines 2-3). The local model for the next iteration, $x_a^{(t+1)}$, is then obtained by applying ZIP-DL's averaging procedure (Algorithm 1) to this model $x_a^{(t+1/2)}$.

4.3. ZIP-DL's core properties

The following results pave the way for the formal analysis of ZIP-DL in Section 5. If there is no influence of the time factor, we remove the (t) superindex to alleviate the notation (e.g. when a lemma is true for all $t \in [0, T]$). Proofs that are not provided in this section can be found in Appendix B.

First, we state a property that summarizes the effect of the noise generated by a node on the network:

Lemma 1. Noise cancellation on the global model: for every node $a \in \mathcal{V} = [\![1, n]\!]$, it holds that

$$\sum_{v=1}^{n} W_{a,v} Z_{a \to v} = \sum_{v=1}^{n} W_{v,a} Z_{a \to v} = 0.$$

Sketch of proof. This immediately follows from unrolling the definition of $Z_{a \rightarrow v}$.

This lemma states that a node does not add noise to the overall network, and leads to the following crucial corollary.

Corollary 2. Impact on the global average model:

$$\forall t \in [0, T], \bar{x}^{(t+1)} = \bar{x}^{(t+1/2)}.$$

While simple, this corollary is pivotal in our convergence analysis of $\bar{x}^{(t)}$. Without this property, the bound on the expectation of $\|\bar{x}^{(t+1)} - x^*\|^2$ suffers from an extra term.

Finally, Lemma 3 describes the behavior of the noise generated by ZIP-DL: it follows a Gaussian distribution, which is standard for deriving formal privacy guarantees.

Lemma 3. Noise characterization for Algorithm 1: Consider that for node a, for all $v \in \Gamma_a^{(t)}$, $Y_{a \to v}^{(t)} \sim \mathcal{N}(0, \gamma^2 \varsigma_a^2)$, for a fixed topology $W^{(t)}$. Then, using the definition of Algorithm 1, we have:

$$\forall a, v \in \llbracket 1, n \rrbracket, Z_{a \to v}^{(t)} \sim \mathcal{N}\left(0, (\sigma_{a \to v}^{(t)})^2\right)$$

with

$$(\sigma_{a \to v}^{(t)})^2 = \left(\frac{(d_a - 1)^2}{d_a^2} + \frac{\sum_{j \in \Gamma_a^{(t)}, j \neq v} (W_{a,j}^{(t)})^2}{(d_a W_{a,v}^{(t)})^2}\right) \gamma^2 \varsigma_a^2.$$

Note that Lemma 3 entails that the variance of the noise added to sent messages is strongly linked to the communication topology. This means that the chosen communication topology also has a deep influence on privacy.

Remark 2. When considering an k-regular topology or even a topology where only the incoming degree is fixed at k for all the nodes with a uniform weight distribution [25], then $(\sigma_{a\to\nu}^{(t)})^2 = \frac{k-1}{k}\gamma^2\varsigma_a^2$. If in addition, we chose an equal privacy parameter ς_a^2 for all nodes, the noise variance becomes independent from the nodes that are considered. This means that all the noises on the network will follow the exact same distribution, meaning the attacker won't gain any advantage by knowing the topology. This also means that if we were to compare it to another method, we could artificially increase the privacy parameter ς_a^2 to match the exact noise variance of another approach.

5. Convergence of ZIP-DL

We now analyze the convergence rate of ZIP-DL. The proof of the results stated in this section follows a similar structure to that of [27]. Detailed versions of some proofs related to this section can be found in Appendix C.

5.1. Assumptions

To ensure convergence, we define some assumptions that are common in the literature, and that mostly follow those of [27]. First, we make assumptions about the smoothness and convexity of the loss functions:

Assumption 2. (L-smoothness). The functions $F_i : \mathbb{R}^d \times \Omega \rightarrow \mathbb{R}$ are differentiable for each $i \in \mathcal{V}$ and $\xi \in supp(\mathcal{D}_i)$, and there exists a constant $L \geq 0$ such that for each $x, x' \in \mathbb{R}^d$ and $\xi \in supp(\mathcal{D}_i)$:

$$\|\nabla F_i(x',\xi) - \nabla F_i(x,\xi)\| \le L \|x - x'\|.$$
(2)

Assumption 3. (μ -convexity) Each function f_i is μ -convex for a constant $\mu \ge 0$. For all $x, x' \in \mathbb{R}^d$:

$$f_i(x) - f_i(x') + \frac{\mu}{2} ||x - x'||_2^2 \le \langle \nabla f_i(x), x - x' \rangle$$

We also assume the noise caused by stochastic gradient descent (SGD) is bounded. This is particularly important since we consider a possible non-IID data distribution:

Assumption 4. (Bounded noise at the optimum) Let $x^* := \operatorname{argmin} f(x)$ and define

$$\vartheta_i^2 := \|\nabla f_i(x^*)\|^2, \qquad \bar{\vartheta}^2 := \frac{1}{n} \sum_{i=1}^n \vartheta_i^2.$$
 (3)

In addition, define

$$\omega_i^2 := \mathbb{E}_{\xi_i} \left[\|\nabla F_i(x^*, \xi_i) - \nabla f_i(x^*)\|_2^2 \right]$$
(4)

and $\bar{\omega}^2 := \frac{1}{n} \sum_{i=1}^n \omega_i^2$. Then $\bar{\vartheta}^2$ and $\bar{\omega}^2$ are bounded.

Intuitively, $\bar{\vartheta}^2$ measures the noise level and $\bar{\omega}^2$ the diversity of the locally sampled functions f_i . It is important to note that $\bar{\omega}^2$ is strongly linked to the data distribution. In particular, it will tend to be larger in a non-IID setting.

Finally, we state the assumption on the mixing matrix:

Assumption 5. (Expected consensus rate) There exists $p \in [0, 1]$ such that for all matrices $X \in \mathbb{R}^{d \times n}$ and all iteration $t \in [\![0, T]\!]$, if we define $\overline{X} := \frac{1}{n} X \mathbf{1}_{n \times n}$ where $\mathbf{1}_{n \times n} \in \mathbb{R}^{n \times n}$ is the matrix composed of ones, we have

$$\mathbb{E}_{W^{(t)}}\left[\left\|W^{(t)}X - \bar{X}\right\|_{F}^{2}\right] \le (1-p)\left\|X - \bar{X}\right\|_{F}^{2}.$$

This assumption is standard in the decentralized consensus literature, with p a value linked to the spectrum of $\mathbb{E}\left[{}^{\mathsf{T}}W^{(t)}W^{(t)}\right]$ [31].

5.2. Convergence rates of ZIP-DL

We now state the formal convergence of ZIP-DL in the strongly convex case:

Theorem 4 (Convergence rate of ZIP-DL). For any number of iterations T, there exists a constant stepsize γ s.t. for Algorithm 2, it holds that $\frac{1}{2W_T} \sum_{t=0}^T w_t(\mathbb{E}\left[f(\bar{x}^{(t)})\right] - f^*) + \frac{\mu}{2}r_{T+1}$ is bounded by:

$$\mathcal{O}\left(\frac{\bar{\omega}^2}{n\mu T} + \frac{LA'}{\mu^2 T^2} + \frac{r_0 L}{p} \exp\left[-\frac{\mu p(T+1)}{192\sqrt{3}L}\right]\right)$$

where $f^* = f(x^*)$, $r_t = \mathbb{E}\left[\left\|\bar{x}^{(t)} - x^*\right\|^2\right]$, $w_t = (1 - \frac{\mu}{2}\gamma)^{-(t+1)}$, $W_T = \frac{1}{T}\sum_{t=1}^T w_t$ and $A' = \frac{16-4p}{2(16-7p)}(\bar{\omega}^2 + \frac{18}{p}\bar{\vartheta}^2) + \frac{d}{n}\frac{16-4p}{16-7p}\sum_{a,v=1}^n d_a\frac{(d_v-1)^2}{d_v}\varsigma_v^2$.

Or, if we prefer a formulation to reach a desired accuracy:

Corollary 5. Setting all the constants to be the same as in Theorem 4, for any target accuracy $\rho > 0$, there exists a

constant stepsize γ such that Algorithm 2 reaches the target accuracy after at most

$$\frac{3\kappa\bar{\omega}^2}{n\mu\rho} + \sqrt{\frac{3\kappa LA'}{\rho\mu^2} + \frac{192\sqrt{3}L}{\mu p}\ln\left[\frac{3\kappa r_0L}{\rho p}\right]}$$

training iterations, where κ is the constant that arises when upper bound $\mathcal{O}\left(\frac{\bar{\omega}^2}{n\mu T} + \frac{LA'}{\mu^2 T^2} + \frac{r_0 L}{p} \exp\left[-\frac{\mu p(T+1)}{192\sqrt{3}L}\right]\right)$ is expanded out.

This bound is similar to the one of [27]. The first and last terms are the same, except for the constants in the logarithm, which do not influence overall convergence since the logarithmic term is the slowest to grow. The second term however contains the additional complexity of our approach, in particular in the definition of A'. Our additional term is of the form $\sqrt{\frac{3\kappa Ld(16-4p)}{2n(16-7p)\mu^2\rho}}\sum_{a,v=1}^n d_a \frac{(d_v-1)^2}{d_v}\varsigma_v^2$. This term is weighted by $\rho^{-\frac{1}{2}}$ and is not the one that grows fastest as ρ goes to 0, proving the limited impact of our approach on convergence. We observe that this term contains a weighted average of the noise propagated by every node, showing the intuitive behavior of slowing down convergence if the noise ς_a^2 becomes too big. Interestingly, this term grows as the network size or density grows. Indeed, the higher the degree, the more the noise injected at each iteration, and the larger the network, the longer it takes for the noise to propagate and cancel out.

We can also compare this bound to a recent noisy approach [15], even if their privacy setting is different from ours. While they do not consider a strongly-convex scenario like us and assume a weaker assumption that is implied by a strongly-convex property, we observe that the noise variance appears on their leading term, in $\mathcal{O}(\frac{1}{T})$. The analysis we performed here on an algorithm without noise cancellation would also have yielded similar results. On the other hand, our approach delegates the impact of the noise to the second leading term, yielding faster convergence rates.

Sketch of proof. (*Theorem 4*). We mostly follow the proof of [27]. The main challenge lies in adapting the set of lemmas to our noisy approach. The mini-batch variance (Proposition 1) is unchanged, as it only relies on hypotheses on the loss function, which are identical to ours. The descent lemma (Lemma 6) is where Corollary 2 comes into play, since canceling noises have no impact on the averaged model. Without noise cancellation, an additional term would have been added here, which would have propagated to the leading term of the convergence rate in $\frac{1}{T}$.

Finally, the recursion for consensus distance (Lemma 7) is modified because of the noise addition, which becomes an extra term. In addition to this extra term, our main recursion is slightly altered, with an additional factor to the recursive term. While this additional factor prevents solving the main recursion directly, a manipulation leads to a term that can be solved, yielding the desired result. \Box

For the sake of completeness, we present the three adapted lemmas used in the proof below. We defer their

proofs to Appendix C, as they are adaptations from already existing work to our system. Moreover, Appendix C also presents a more detailed proof of Theorem 4.

Proposition 1. Mini-batch variance Proposition 5 in [27] Assume that F_i is L-smooth (Assumption 2) with bounded noise at the optimum (Assumption 4). Then, for any $i \in [\![1, n]\!]$, we have:

$$\mathbb{E}_{\xi_1,\dots,\xi_n} \left[\left\| \frac{1}{n} \sum_{i=1}^n (\nabla f(x_i) - \nabla F_i(x_i,\xi_i)) \right\|^2 \right] \\ \leq \frac{3L^2}{n} \sum_{i=1}^n \|x_i - \bar{x}\|^2 + 6L(f(\bar{x}) - f(x^*)) + 3\bar{\omega}^2$$

Lemma 6. Descent lemma for convex cases. (*Lemma 8 of* [27]) Under Assumptions 2 to 5, with stepsize $\gamma \leq \frac{1}{12L}$ we have:

$$\begin{split} \mathbb{E}_{\xi_{1}^{(t)},\dots,\xi_{n}^{(t)}} \left[\left\| \bar{x}^{(t+1)} - x^{*} \right\|^{2} \right] &\leq (1 - \frac{\gamma\mu}{2}) \left\| \bar{x}^{(t)} - x^{*} \right\|^{2} \\ &+ \frac{\gamma^{2}\bar{\omega}^{2}}{n} - \gamma(f(\bar{x}^{(t)}) - f(x^{*})) \\ &+ \gamma \frac{3L}{n} \sum_{i=1}^{n} \left\| \bar{x}^{(t)} - x_{i}^{(t)} \right\|^{2} \end{split}$$

Lemma 7. (Recursion for consensus distance) Under Assumptions 2 to 5, if stepsizes $\gamma \leq \frac{p}{96\sqrt{3}L}$, then for any $\beta > 0$:

$$\begin{split} \Xi_t &\leq (1+\beta) \left(1 - \frac{7p}{16} \right) \Xi_{t-1} \\ &+ (1+\beta) \frac{36L}{p} \left(f(\bar{x}^{(t-1)}) - f(x^*) \right) \\ &+ \gamma^2 (1+\beta) \left(\bar{\omega}^2 + \frac{18}{p} \bar{\vartheta}^2 \right) \\ &+ \gamma^2 (1+\beta^{-1}) \frac{d}{n} \sum_{i=1}^n d_i \sum_{v=1}^n \left(\frac{(d_v - 1)^2}{d_v} \varsigma_v^2 \right) \end{split}$$

where $\Xi_t = \frac{1}{n} \sum_{i=1}^n \mathbb{E}_t \left[\left\| x_i^{(t)} - \bar{x}^{(t)} \right\|^2 \right]$ is the consensus distance

6. Pairwise Network Differential Privacy

We now formalize the privacy guarantees of ZIP-DL in terms of *pairwise-network differential privacy (PNDP)*, a graph-based variant of DP introduced by Cyffers et al. in [11] to capture the unique threats to privacy introduced by the DL framework. This section establishes the formal PNDP guarantees that ZIP-DL provides and dissects further its analytical properties.

More concretely, we first present the additional assumption and privacy definition used in the analysis (Section 6.1), before defining an equivalent formulation of our algorithm (Section 6.2). Section 6.3 will then exploit this formulation to express the evolution fo the system, wich is pivotal to our privacy analysis of ZIP-DL presented in Section 6.4. We finally consider the simpler case Algorithm 1 (Section 6.5), and link our result to those of [11].

6.1. Assumptions & definitions

When discussing PNDP, we use the same notations and definitions as [11]. Specifically, with $\mathcal{D} = (\mathcal{D}_a)_{a \in \mathcal{V}}$ denoting set of datasets across all the nodes, we call a pair of (entire) datasets \mathcal{D} and \mathcal{D}' adjacent, denoted by $\mathcal{D} \sim_a \mathcal{D}'$, if there is some node and only one node $a \in \mathcal{V}$ for which \mathcal{D}_a and \mathcal{D}'_a differ.

We are interested in analyzing how ZIP-DL guarantees PNDP for an input dataset \mathcal{D} (a given initial data distribution between the nodes). To this purpose, we require two additional assumptions, in addition to those highlighted in Section 5.1. First, we need the distance between the models trained on two adjacent datasets to bounded, which aligns with Assumption 1 in [11].

Assumption 6. There exists some constant $\Delta > 0$ such that)) for any adjacent datasets $\mathcal{D} \sim_a \mathcal{D}'$, we have

$$\sup_{x \in \mathbb{R}^d} \sup_{\xi, \dot{\xi} \in \mathcal{D} \times \mathcal{D}'} \left\| \nabla F(x,\xi) - \nabla F(x,\dot{\xi}) \right\|^2 \le \Delta^2.$$
 (5)

This is a standard assumption when considering differentially private algorithms: we use a bound on the original perturbation and observe how this perturbation can be scaled by the algorithm.

For a pair of adjacent datasets, é [11] introduces the notion of *privacy view* on two such datasets:

Definition 1. [11] The privacy view of a node v after T steps for a dataset D is:

$$\mathcal{O}_v(\mathcal{A}^{(T)}(\mathcal{D})) = \{m_{v \to w}^{(t)} \mid t \in \llbracket 1, T \rrbracket, v \in \Gamma_w^{(t)}\} \cup \{x_v\},$$

with $\mathcal{A}^{(T)}$ a state-sharing algorithm iterated T times such as Algorithm 1 or Algorithm 2, and $\mathcal{A}^{(T)}(\mathcal{D})$ the set of all messages sent by neighboring nodes on the network during the execution of the algorithm.

The privacy view represents a projection from the set of all the messages in an execution $\mathcal{A}^{(T)}$ to the set of messages that v receives during the algorithm's execution.

When considering this privacy view $\mathcal{O}_v(\mathcal{A}^{(T)}(\mathcal{D}))$, we consider the scenario where node v would be an *honest-but-curious* attacker and tries to infer information from it's observations - the privacy view. This view is then used to define PNDP [11], by leveraging the definition of Rényi-DP [32].

Definition 2. (Pairwise Network Differential Privacy) For $g: \mathcal{V}^2 \to \mathbb{R}^+$ and $\alpha > 1$, a mechanism $\mathcal{A}^{(T)}$ satisfies (α, g) -Pairwise Network Differential Privacy (PNDP) if, for all pairs of distinct nodes $a, v \in \mathcal{V}$ and adjacent datasets $\mathcal{D} \sim_a \mathcal{D}'$, we have

$$D_{\alpha}\left(\mathcal{O}_{v}(\mathcal{A}^{(T)}(\mathcal{D})) \| \mathcal{O}_{v}(\mathcal{A}^{(T)}(\mathcal{D}'))\right) \leq g^{(T)}(a,v),$$

where $D_{\alpha}(P||Q)$ is the Rényi divergence [33] between probability distributions P and Q:

$$D_{\alpha}\left(X\|Y\right) = \frac{1}{\alpha - 1} \ln \int \left(\frac{\mu_X(z)}{\mu_Y(z)}\right)^{\alpha} \mu_Y(z) dz$$

with μ_X and μ_Y the densities of X and Y.

Therefore, $g^{(T)}(a, v)$ quantifies the *privacy leaked* from *a* to *v*, and our goal is to constrain it to a minimal value. This decentralized approach harnesses communication topology, in contrast to DP or Renyi-DP, thus fully exploiting the specificity of a decentralized context.

The choice of this privacy guarantee is further motivated by the synergy between Rényi-DP and Gaussian noise [32], as the following lemma underlines:

Lemma 8. [33] Suppose that $X \sim \mathcal{N}(\mu_X, \Sigma)$ and $Y \sim \mathcal{N}(\mu_Y, \Sigma)$. Then for all $\alpha > 1$, we have:

$$D_{\alpha}(X||Y) = \frac{\alpha}{2} {}^{\mathsf{T}}(\mu_X - \mu_Y) \Sigma^{-1}(\mu_X - \mu_Y)$$
(6)

This lemma shows Gaussian noises are crucial to our algorithm to properly generate cancelling noises. Most other distributions with link to differential privacy do not have the additivity property that Gaussian distribution has, and which is at the core of our approach.

Rényi-divergence usually provides important properties when considering privacy concerns. Most notably, the *composition theorem* and the preservation by *post-processing* [32]. Of those two, the former allows for an easy way to derive the privacy guarantee of the composition of differentially private algorithms. When considering a process with multiple rounds, this makes it practical to compose privacy guarantees between rounds and significantly alleviates the analysis.

Remark 3. Since we consider a projection of the set of all messages $\mathcal{A}^{(T)}(\mathcal{D})$ on the view of the attacker, we cannot naively apply composition theorems on $\mathcal{O}_v(\mathcal{A}^{(t)}(\mathcal{D}))$ to this approach directly. That is because here, the composition would rely on external information, that was not in the view of the attacker. To circumvent this, the original paper [11] considers a full averaging algorithm, meaning composition can be performed by using the (common) final state of the averaging algorithm.

However, we want a more usual view of DL, where we alternate between one round of averaging and one round of gradient descent. To avoid using composition, we must be able to analyze the behavior of the noise through the gradient. To this end, we consider the following assumption:

Assumption 7. For all $i \in \mathcal{V}$, for all data sample ξ_i and model x, if we consider a noise $Z \sim \mathcal{N}(0, \Sigma)$, then we have:

$$\nabla F_i(x+Z,\xi_i) \sim \mathcal{N}(\nabla F_i(x,\xi_i),L\Sigma)$$

In essence, Assumption 7 implies that the gradient of a model perturbed with Gaussian noise stays close to the unnoised (original) gradient while following a Gaussian distribution around this unnoised gradient. The range of the standard deviation is bounded by the smoothness constant L (Assumption 2), which comes from the remark that $\|\nabla F_i(x+Z,\xi_i) - \nabla F_i(x,\xi_i)\|^2 \leq L \|Z\|^2$. This assumption will allow us to simplify privacy expressions without resorting to a composition theorem. Most notably, Lemma 10 links an execution of ZIP-DL to an execution of decentralized learning without any noise. This link will be pivotal to the privacy proof.

6.2. Equivalent system formulation

Gossip matrices (Section 3.2) are a natural tool to analyze how information propagates in a communication graph over several communication rounds. Unfortunately, they cannot be directly applied to Algorithm 2, as they assume that each node sends the same information to all its neighbors in a given round. This assumption does not hold for Algorithm 2, where the noise $Z_{a \rightarrow v}$ added by each node *a* to its model during the ZIP-DL-averaging step (line 5 of Algorithm 1) is different for each of *a*'s neighbors.

We overcome this difficulty by considering an equivalent virtual communication graph of n^2 nodes that emulate the behavior of the *n* nodes executing Algorithm 2. In this construction, each original node $a \in \mathcal{V}$ is replaced by *n* virtual nodes $a_1, ..., a_n \in \hat{\mathcal{V}}$ connected in a clique. Each virtual node a_v is then connected to v_a in the virtual communication graph if *a* is connected to *v*.

This emulated network makes it possible to track the privacy loss incurred by our algorithm, whose behavior can be interpreted as a sequence of linear matrix operations on the states of the virtual nodes. Because each virtual node replicates the state of its real node, the system's state is encoded in a matrix of dimension $n^2 \times d$, while message exchanges and state updates are captured by matrices of size $n^2 \times n^2$ (since the virtual communication topology contains n^2 nodes). For simplicity, we focus in the following on the case d = 1 to introduce the notations, but the approach generalizes seamlessly to higher dimensions.

In the remainder of this section, we present in more detail the entities we use to analyze the privacy loss of Algorithm 2 using virtualization. Virtual entities are decorated with the symbol $\hat{}$: if A describes an object in the original "real" system, then \hat{A} represents its counterpart in the virtual topology. We note $\hat{\mathcal{V}} = [\![1, n^2]\!]$ the set of virtual nodes, where the real node i is represented by the virtual nodes ranging from n(i-1) + 1 to ni. $\hat{X}^{(t)}$ represents the stacking of virtual models at time t, *i.e.*,

$$\hat{X}^{(t)} = {}^{\mathsf{T}} \Big({}^{\mathsf{T}} x_1^{(t)}, \dots, {}^{\mathsf{T}} x_1^{(t)}, {}^{\mathsf{T}} x_2^{(t)}, \dots, {}^{\mathsf{T}} x_n^{(t)} \Big),$$

in which the local model $x_a^{(t)} \in \mathbb{R}^d$ is duplicated n times across all the virtual nodes associated with node a. $\hat{X}^{(t)} \in \mathbb{R}^{n^2 \times d}$ in the general case, but collapses to a simple vector of dimension n^2 for d = 1, which we assume in the rest of this section.

The noises generated in Algorithm 1 are captured by two random vectors $\hat{Y}^{(t)}$ and $\hat{Z}^{(t)}$ of dimension n^2 , defined component-wise by

$$\begin{split} \hat{Y}_{n(i-1)+j}^{(t)} &\coloneqq Y_{i \to j}^{(t)}, \qquad \quad \forall i, j \in \mathcal{V}, \\ \hat{Z}_{n(i-1)+j}^{(t)} &\coloneqq Z_{i \to j}^{(t)}, \qquad \quad \forall i, j \in \mathcal{V}. \end{split}$$

Due to Line 3 of Algorithm 1, $\hat{Z}^{(t)}$ results from a linear combination of $\hat{Y}^{(t)}$:

$$\hat{Z}^{(t)} = \hat{C}^{(t)} \hat{Y}^{(t)},\tag{7}$$

where, $\hat{C}^{(t)}$ is the block-diagonal matrix filled with 0 values, except in the following positions when a, v, j range over \mathcal{V} :

$$\hat{C}_{n(a-1)+v,n(a-1)+j}^{(t)} := \begin{cases} \frac{d_a - 1}{d_a} & \text{if } j = v \land v \in \Gamma_a^{(t)}, \\ -\frac{W_{a,j}^{(t)}}{d_a W_{a,v}^{(t)}} & \text{if } j \neq v \land v \in \Gamma_a^{(t)}, \\ 0 & \text{Otherwise.} \end{cases}$$

The covariance matrix of \hat{Y} is the diagonal matrix in which each node's variance (ς_a^2) is repeated *n* times. The covariance matrix of \hat{Z} is $\Sigma_{\hat{Z}}^{(t)} = \hat{C}^{(t)} \Sigma_{\hat{Y}}^{\mathsf{T}} \hat{C}^{(t)}$ due to Equation (7).

From a given gossip matrix $W^{(t)}$, we construct $\hat{W}^{(t)}$ as the communication matrix where each virtual node only communicates with one fixed node. We also introduce \hat{M} , which mixes information between the virtual nodes afterward.

$$\hat{W}_{\hat{i},\hat{j}}^{(t)} := \begin{cases} W_{i,j}^{(t)}, & \text{if } \hat{i} = n(i-1) + j, \hat{j} = n(j-1) + i \\ 0, & \text{Otherwise} \end{cases}$$
$$\hat{M} := \begin{pmatrix} \mathbf{1}_n & \mathbf{0}_n & \mathbf{0}_n & \dots & \mathbf{0}_n \\ \mathbf{0}_n & \mathbf{1}_n & \mathbf{0}_n & \dots & \mathbf{0}_n \\ \dots & \dots & \dots & \dots & \dots \\ \mathbf{0}_n & \mathbf{0}_n & \mathbf{0}_n & \dots & \mathbf{1}_n \end{pmatrix} \in \mathbb{R}^{n^2 \times n^2}, \qquad (8)$$

where $\mathbf{1}_n = [1]_{i,j \in [1..n]}$ and $\mathbf{0}_n = [0]_{i,j \in [1..n]}$ represent the matrices of dimension $n \times n$ full of ones or zeros, respectively. \hat{M} creates a fully connected network between the virtual nodes of a given real node. In doing so it captures how each local node averages the individual models it receives through $\hat{W}^{(t)}$.

Using this matrix, we obtain the following virtual gossip round:

$$\hat{X}^{(t+1)} = \hat{M}\hat{W}^{(t)}(\hat{X}^{(t+1/2)} + \hat{Z}^{(t)})$$
(9)

The following lemma ensures that the update rule stays the same as Line 8 of Algorithm 1, proving we have constructed something equivalent to the non-virtual update rule:

Lemma 9. Consider $i \in \mathcal{V}$ and $t \in \mathbb{N}$. Then we have:

$$\forall k \in \mathcal{V}, \hat{X}_{ni+k}^{(t)} = X_i^{(t)}$$

Sketch of proof. This is proved by induction over $t \in \mathbb{N}$, using (9) and unrolling the matrix multiplication. The idea is to remove indexes in the virtual domain by exploiting the properties of the matrices.

- $\hat{M}_{n(i-1)+k,\hat{j}} \neq 0 \iff \hat{j} \in [n(i-1)+1, ni]$ and $\hat{M}_{n(i-1)+k,\hat{j}} = 1$ in this case in such case, which simplifies the sum by removing \hat{M} .
- $\hat{W}_{j+n(i-1),u}^{(t)} \neq 0 \iff u = n(j-1) + i$, in which case $\hat{W}_{j+n(i-1),u}^{(t)} = W_{i,j}^{(t)}$, which simplifies the sum further, by removing indexes and rewriting in terms of $W^{(t)}$.

Finally, some variables changes allow to obtain a direct sum over indexes in \mathcal{V} , yielding to the desired result.

6.3. Accounting for noises over time

In order to track how privacy losses propagate from one SGD round to the next without using a composition theorem (see Remark 3), we further consider T successive rounds of Algorithm 2. These T rounds incur the generation of Tn^2 individual noise values at Line 2 of Algorithm 1, and the same number of noise values at Line 3 just afterward. We track the correlation between these noises and the model parameters to which they are applied in the virtual system through covariance matrices of size tn^2 , for $t \in [1, T]$.

To track those $n^2 \times t$ noises, we consider matrices that aggregate data through time for notation purposes. Those matrices will be denoted by a $\tilde{}$ notation. Similarly to before, we consider $\tilde{Y}^{(t)} \in \mathbb{R}^{tn^2}$ a matrix stacking all the noises generated on the network.

Even if the noises at time t + 1 are independent from the noises at time t, meaning the covariance matrix will be block-diagonal, we reach a simpler expression with time matrices. Formally, we have:

$$\Sigma_{\tilde{Y}^{(t)}} := \begin{pmatrix} \Sigma_{\hat{Y}} & \mathbf{0}_{n^2} & \dots & \mathbf{0}_{n^2} \\ \mathbf{0}_{n^2} & \Sigma_{\hat{Y}} & \dots & \mathbf{0}_{n^2} \\ \dots & \dots & \dots & \dots \\ \mathbf{0}_{n^2} & \mathbf{0}_{n^2} & \dots & \Sigma_{\hat{Y}} \end{pmatrix} \in \mathbb{R}^{tn^2 \times tn^2}$$
(10)

where $\Sigma_{\hat{Y}} \in \mathbb{R}^{n \times n}$ corresponds to the covariance matrix of the uncorrelated noises. This is a diagonal matrix. In the special case where all nodes have the same privacy parameter ζ^2 , then we have $\Sigma_{\tilde{Y}^{(t)}} = \zeta^2 I_{tn^2 \times tn^2}$.

Using this and the decomposition $\hat{Z}^{(t)} = \hat{C}^{(t)}\hat{Y}^{(t)}$ (Equation (7)), where $\hat{Y}^{(t)} \sim \mathcal{N}(0, \Sigma_{\hat{Y}})$, we also create a decomposition $\tilde{Z}^{(t)} = \tilde{C}^{(t)}\tilde{Y}^{(t)}$, where $\tilde{C}^{(t)}$ a block diagonal matrix of all the $\hat{C}^{(t)}$.

For ease of notation, when considering matrices that aggregate through time, we will consider a constant communication matrix $W^{(t)} = W$. Our notations could be generalized at the expense of matrix product notations. For the temporal gossip matrix, we define the following:

$$\tilde{W}^{(T)} := \begin{pmatrix} (1 - \gamma L)^T \\ \dots, \\ (1 - \gamma L) \end{pmatrix} \left((\hat{M}\hat{W})^T, \dots, \hat{M}\hat{W} \right)$$
(11)

In particular, we have $\tilde{W}^{(T)} \in \mathbb{R}^{n^2 \times Tn^2}$. This matrix will appear in Theorem 11 and can be used to compute the propagation of the noise through the system after T steps.

This notation finally allows us to leverage Assumption 7. Using the equivalent formulation defined in Section 6.2, we now progress toward the privacy analysis. First, we derive the distribution of the model vectors:

Lemma 10. Using Assumption 7, consider $\hat{\chi}^{(T)}$ a virtual execution without any noise, and every other source of randomness is the same. Then, we have:

$$\hat{X}^{(T)} \sim \mathcal{N}\left(\hat{\chi}^{(T)}, L\hat{W}^{(T)}\tilde{C}^{(t)}\Sigma_{\tilde{Y}^{(t)}}^{\mathsf{T}}(\hat{W}^{(T)}\tilde{C}^{(t)})\right)$$

This lemma draws a parallel between an execution of Algorithm 2 and an unnoised execution and is at the core of our privacy analysis. Lemma 10 offers a structure to bound the Rényi divergence between $\hat{X}^{(T)}$ on two executions on adjacent datasets. Its proof is deferred to Appendix A.

6.4. ZIP-DL privacy analysis

We now focus on analyzing the formal privacy guarantees of Algorithm 2.

Theorem 11 (Privacy of ZIP-DL). *T* iterations of ZIP-DL (Algorithm 2) satisfies $(\alpha, \epsilon^{(T)}(a, v))$ -PNDP, where $\epsilon^{(T)}(a, v)$ is bounded for any two nodes $a, v \in \mathcal{V}$ by:

$$\frac{2\alpha\gamma^2\Delta^2}{L+4\gamma^2L^2}\sum_{t=0}^{T-1}\sum_{\substack{\hat{v}\in\hat{V}\\\hat{w}\in\hat{\Gamma}_{\hat{v}}^{(t)}}}\frac{(2+4\gamma^2L)^t-1}{\left(\left(\tilde{W}\tilde{C}\right)^{(t)}\tilde{\Sigma}_{\tilde{Y}^{(t)}}^{\mathsf{T}}\left(\tilde{W}\tilde{C}\right)^{(t)}\right)_{\tilde{w},\tilde{w}}}$$

where $\tilde{\Sigma}_{\tilde{Y}^{(t)}}$ is a diagonal matrix representing the noise variances of all noises generated by the algorithm up to time T, $\tilde{C}^{(t)}$ is a block-diagonal matrix representing the correlation factor at each iteration t, and $\tilde{W}^{(t)}$ is the accumulation of all the powers of the gossip matrix defined in Section 6.2.

In essence, a node's privacy loss increases over time, and the influence of the privacy mechanism is denoted by the denominator: this term accounts for all the noises received by the virtual node \hat{w} . On the other hand, the numerator accounts for how models drift away from each other.

If we consider that all nodes have the same privacy parameter ς^2 , then the denominator becomes akin to the norm of $(\tilde{W}\tilde{M})^{(t)}_{\hat{w}}$, which is similar to [11].

norm of $(\tilde{W}\tilde{M})^{(t)}_{\hat{w}}$, which is similar to [11]. This result is a double sum over time and the attacker's neighbors, since in our notation $\hat{\Gamma}^{(t)}_{\hat{w}}$ is a set containing at most one value that translates whether w is in $\Gamma^{(t)}_{v}$ or not.

Remark 4. This result naturally extends to colluding nodes if we consider $\hat{V} = \bigcup_{v \in V} \{n(v-1) + k \mid k \in V\}$ to be the set of colluding nodes. We can thus have a similar bound of $\epsilon^{(T)}(a, V)$, for $V \subset V$ a set of colluding nodes.

Even if the matrices considered here are of large dimensions, this bound can be computed in practice since their underlying matrices are sparse: either they are diagonal by block, or some have only one element by line. For instance, both \tilde{M} and $\tilde{\Sigma}_{\tilde{Y}(t)}$ are diagonal by block since the noises generated at each iteration are independent.

Sketch of proof. (Theorem 11) - We first consider two adjacent datasets distributions $\xi^{(t)} \sim_u \dot{\xi}^{(t)}$. For a given set of nodes $V \subset \mathcal{V}$, we denote $\hat{\mathcal{V}} \subset \hat{\mathcal{V}}$ the corresponding set of virtual nodes. We have:

$$D_{\alpha}\left(\mathcal{O}_{V}(\mathcal{A}^{(T)}(\mathcal{D})) \| \mathcal{O}_{V}(\mathcal{A}^{(T)}(\dot{\mathcal{D}}))\right)$$

$$\leq \sum_{t=0}^{T-1} \sum_{\hat{v} \in \hat{V}} \sum_{\hat{w} \in \hat{\Gamma}_{\hat{v}}^{(t)}} D_{\alpha}\left(\hat{X}_{\hat{w}}^{(t)} \| \hat{X}_{\hat{w}}^{(t)}\right) \qquad (12)$$

Using Lemma 10 on both $\hat{X}_{\hat{w}}^{(t)}$ and $\hat{\hat{X}}_{\hat{w}}^{(t)}$, we can consider *adjacent* unnoised executions $\hat{\chi}_{\hat{w}}^{(t)}$ and $\hat{\chi}_{\hat{w}}^{(t)}$. They are two executions with slightly altered trajectories. We obtain:

$$\hat{X}_{\hat{w}}^{(t)} \sim \mathcal{N}(\hat{\chi}_{\hat{w}}^{(t)}, L(\Sigma_t)_{\hat{w}, \hat{w}}), \quad \hat{X}_{\hat{w}}^{(t)} \sim \mathcal{N}(\hat{\chi}_{\hat{w}}^{(t)}, L(\Sigma_t)_{\hat{w}, \hat{w}}),$$

with

$$\Sigma_t = \left(\tilde{W}\tilde{C}\right)^{(t)}\tilde{\Sigma}_{\tilde{Y}^{(t)}}^{\mathsf{T}}\left(\tilde{W}\tilde{C}\right)^{(t)}$$
(13)

Considering (11),(13) along with Lemma 8, we obtain:

$$D_{\alpha}\left(\hat{X}_{\hat{w}}^{(t)}\|\hat{X}_{\hat{w}}^{(t)}\right) \leq \frac{\alpha}{2L} \frac{\left\|\hat{\chi}_{\hat{w}}^{(t)} - \hat{\chi}_{\hat{w}}^{(t)}\right\|^{2}}{\left(\tilde{W}^{(T)}\tilde{M}\Sigma_{\tilde{Y}}^{\mathsf{T}}(\tilde{W}^{(T)}\tilde{M})\right)_{\tilde{w},\tilde{w}}}$$

Finally, we bound $\|\hat{\chi}_{\hat{w}}^{(t)} - \hat{\chi}_{\hat{w}}^{(t)}\|^2$ using Lemma 12. Putting it all together in (12), we obtain the desired

Putting it all together in (12), we obtain the desired result. \Box

To truly complete the proof, a bound between two adjacent inputs is derived using the following lemma, whose proof is deferred to the appendix.

Lemma 12. Consider two unnoised executions. Then,

$$\left\|\hat{\chi}^{(t)} - \hat{\chi}^{(t)}\right\|_{\infty}^{2} \leq \frac{4\gamma^{2}\Delta^{2}}{1 + 4\gamma^{2}L}((2 + 4\gamma^{2}L)^{t} - 1)$$

This lemma bounds the maximal difference between local models of two adjacent unnoised executions. One limitation of this lemma is that it bounds over a maximum. This is because the gradient must be isolated from the recursive term in the proof. To show this, Section 6.5 focuses on the case where only averaging is performed. In this scenario, the equivalent of the above lemma is much tighter, and we derive a generalization of previous results to our case of correlated noises.

6.5. ZIP-DL-avg privacy analysis

We also focus on the privacy of Algorithm 1 as a pure averaging algorithm. This removes gradient from the proof of Theorem 11, and thus Assumption 7 is not needed. By following the same proof with a simpler update rule, we can derive a more tractable term, **Theorem 13.** *T* iterations of Algorithm 1 satisfy $(\alpha, \epsilon^{(T)}(a, v))$ -PNDP, where $\epsilon^{(T)}(a, v)$ is bounded for any two nodes $a, v \in \mathcal{V}$ by:

$$\frac{\alpha\Delta^2}{2} \sum_{t=0}^{T-1} \sum_{\hat{v}\in\hat{V}} \sum_{\hat{w}\in\hat{\Gamma}_{\hat{v}}^{(t)}} \frac{\left((\hat{M}\hat{W})^T\right)_{\hat{w},\hat{a}}}{\left((\tilde{W}\tilde{C})^{(t)}\Sigma_{\tilde{Y}}{}^{\mathsf{T}}(\tilde{W}\tilde{C})^{(t)}\right)_{\tilde{w},\tilde{w}}}$$

where

$$\tilde{W}^{(T)} := \begin{pmatrix} (\hat{M}\hat{W})^T, & \dots, & \hat{M}\hat{W} \end{pmatrix}$$

Remark 5. This theorem generalizes the result of [11] by introducing the correlation matrix between all the generated noises $\tilde{C}^{(t)}$. Applied to the algorithm presented in [11], the correlation matrix $\tilde{C}^{(t)}$ in the above expression would instead be the identity matrix. Additionally, the numerator is also the same as the one of the original work, as we have $\left((\hat{M}\hat{W})^T\right)_{\hat{w},\hat{a}} = (W)_{w,a}^T$ where w, a are the nodes associated to the virtual nodes \hat{w}, \hat{a} .

7. Evaluation

In this section, we compare ZIP-DL's performance on a practical learning task with that of baseline decentralized parallel stochastic gradient descent (D-PSGD) and the privacypreserving DL algorithm Muffliato [11]. The comparison focuses on two aspects: (i) the tradeoff between model utility (top-1 accuracy) and privacy, and (ii) the cost of such privacy in terms of the communication overhead. The next section explains all the experimental details, and the following ones are dedicated to the performance against a passive attacker described in Section 3.3.

7.1. Experimental setup

Topology. Throughout the evaluation, we use 128 nodes connected in a 6-regular communication topology. We assess two settings: (*i*) static topology: D-PSGD [34] over a fixed topology generated at the start of the experiment, and (*ii*) dynamic topology: EL-Oracle [25] where the positions of the nodes in the topology are randomized before each communication round.

Baselines. We compare ZIP-DL to two baselines: the basic version of the DL algorithm without privacy guarantees (*No noise*) and Muffliato, a state-of-the art privacy-preserving DL algorithm. For Muffliato, we allow 10 averaging rounds per training iteration, as recommended by the authors [11]. This produces a nearly-exact average across the network (see Figure 5 for details).

Learning task - CIFAR-10. We evaluate ZIP-DL and the baselines over the image classification task of CIFAR-10 [35] using a convolutional neural network GN-LeNet [36]. The training set comprises 50 000 data samples and the test set 10 000 data samples. The neural network has 89 834 trainable parameters. Nodes perform a fixed number of local gradient steps with tuned learning between communication rounds. Data partition. Data is split among nodes in the following manner [22], [37], [38]:

- The entire training dataset is sorted by class.
- Each node takes two slices, or *shards*, of equal length of this dataset one after the other.

This ensures that the data is non-IID, while each node obtains an equal amount of data. In our case, each node has around 390 training elements, with most nodes having only elements of two classes.

Noise levels. To show the effectiveness of ZIP-DL, we evaluate its performance under different noise levels: $k\sigma$, for $k \in \{1, 2, 4, 8, 16, 32, 64, 128, 256\}$. We choose σ empirically by measuring the value of the average gradient norm during a *No noise* run: 128σ corresponds to a noise of the same magnitude as the typical gradient. For a fair comparison, we amplify the noise of ZIP-DL to have the same variance as the noise generated by Muffliato (Remark 2). In other words, we compare ZIP-DL and Muffliato using *equivalent* noise levels. To select the value for σ ; we evaluate that the typical gradient on the CIFAR-10 task for our model is around 0.225. Since our focus is the tradeoff between accuracy and privacy, we craft our noise level 128σ so that the generated noise has a standard deviation $(128\gamma\sigma)$ equal to this typical gradient. Then, we consider multiple noise levels around this value. For reference, the lowest noise level generated has a standard deviation of 1.76×10^{-3} , whereas the highest one for ZIP-DL is 0.9.

Privacy attack and metrics. We evaluate the privacy of the algorithms against an honest-but-curious attacker described in Section 3.3. Empirically, we apply (i) a thresholdbased membership inference attack [7], [17], and (ii) a linkability attack [39] to transmitted models. The objective of the threshold attack is to identify whether a particular data point was used during the training of a machine learning (ML) model. While simple, this approach serves as a lower bound to privacy vulnerability: if such an attack is successful, more sophisticated ones will also be [17]. The attack is quantified using the Area Under the Curve (AUC) of the TPR (true positive rate) vs. FPR (false positive rate). The linkability attack, in turn, is quantified through the attack accuracy, whose objective is to identify which node's local training set produced a particular model. Linkability attack is based on the loss of the given model on each local training set.

In addition to the privacy of each algorithm, we also evaluate the utility of its trained models using top-1 accuracy on the test set, and the communication cost of the entire training process. This provides a measure of the cost of privacy and the tradeoff between communication cost, model utility, and privacy. Moreover, since Muffliato and ZIP-DL are parameterized by noise, we show a *privacy-accuracy trade-off* over multiple noise levels.

7.2. ZIP-DL privacy-utility tradeoff

We assess the privacy vs. utility tradeoff of ZIP-DL by plotting the maximum top-1 test accuracy reached (utility for nodes) against the average attack success (privacy vulnerability for nodes) throughout the learning process for increasing



Figure 1. Maximum accuracy reached as a function of the average linkability attack success rate.



Figure 2. Threshold attack AUC and accuracy with the threshold attack at different noise levels.

noise levels. Ideally, we strive for an accuracy close to that of *No noise* while a keeping low attack success.

Figure 1 shows the tradeoff over the linkability attack for decreasing noise (color intensity) from left to right for both static and dynamic topologies. ZIP-DL achieves similar utility to No noise for significantly lower linkability attack accuracy. For instance, with a noise level of 32σ , ZIP-DL achieves a 52 percentage points decrease in the linkability attack success rate while limiting the utility loss to 4 percentage points. Moreover, if we observe the domain of low linkability attack accuracy ($\leq 30\%$), ZIP-DL consistently beats Muffliato in terms of the privacy-utility tradeoff, exhibiting lower linkability attack accuracy with better test accuracy. The same trend appears in dynamic topologies. Note that for very low noise level (σ), Muffliato shows better utility than both ZIP-DL and No noise in the static topology. This is due to the near-perfect averaging achieved in Muffliato with 10 averaging rounds between gradient steps compared to 1 averaging round fot ZIP-DL and *No noise*. While this results in a $10 \times$ communication cost for Muffliato compared to ZIP-DL and No noise, Muffliato's advantage wears off in dynamic topologies, as apparent on the right-hand side of Figure 1.

Figure 2 shows the privacy vs. utility tradeoff under the threshold attack. The noise decreases from left to right in ZIP-DL and is represented by the decreasing intensity of the



Figure 3. Accuracy at different noise levels on CIFAR-10.



Figure 4. Data exchanged to reach 50% accuracy for CIFAR-10. Muffliato fails to reach this target for higher noise.

color of the data points. As in the linkability attack, ZIP-DL consistently beats Muffliato by delivering higher utility for the same threshold attack AUC. Although it is simple, the threshold attack remains fairly robust to the noise added to models in DL. In both static and dynamic topologies, the models in Muffliato show extremely low model utility (< 20%) up to high levels of attack success (80%). Finally, Muffliato shows a strange behavior of decreasing threshold attack AUC for decreasing noise at low noise levels. We conjecture this happens because, at the inflection point, the models start to generalize beyond the local training set, hence, decreasing the attack success.

Figure 3 compares the best accuracy reached by ZIP-DL and Muffliato for various noise levels. In contrast to Muffliato, the accuracy of ZIP-DL is less sensitive to noise in the region of high test accuracy, *i.e.*, ZIP-DL with noise 64σ achieves better test accuracy than Muffliato with a noise of 4σ in the static topology. Furthermore, for dynamic topology, ZIP-DL converges to the accuracy of *No noise* at the noise level of 16σ , while Muffliato never converges to the same accuracy even for the smallest noise of 2σ . In conclusion, ZIP-DL demonstrates better convergence when compared to Muffliato for similar privacy vulnerabilities.

7.3. Communication overhead

While basic DL and ZIP-DL limit themselves to a single averaging communication per gradient step, Muffliato should



Figure 5. Muffliato test accuracy with different numbers of averaging rounds for a noise level of 8σ (left) and 32σ (right), compared to ZIP-DL (1-round). For Muffliato, there is little difference between 10 and 20 rounds. However, 1 round greatly degrades the accuracy even with the smallest amount of noise, forcing the use of 10 averaging rounds, which is costly in terms of network usage, communication time, and privacy loss.

perform several of them to ensure the convergence of the averaging. The exact number of communications required depends on both the variance of the models at the nodes and on the spectral analysis of the communication graph. Since the variance of all the models should be unknown from each individual model, we test Muffliato with 1, 10, and 20 rounds of communication to find the right number of communications rounds.

Figure 5 shows the evolution of the test accuracy w.r.t. the number of iterations for basic DL, Muffliato (with 1, 10, and 20 communication rounds), and ZIP-DL for two different settings. For both settings, we observe that Muffliato-10 is as accurate or more accurate than Muffliato-1, and has the same accuracy as Muffliato-20. Therefore, 10 rounds of communication are sufficient for Muffliato to achieve proper averaging while minimizing communication costs.

The paper [11] also uses rescaled Chebyshev polynomials. However, this is only partially reduces the number of averaging rounds required. Instead, we pick the smallest number of standard averaging rounds that is high enough to ensure accuracy convergence, since we are interested in the accuracy and attack results, while Muffliato's communication results are compromised anyway by the its requirement for multiple averaging rounds.

The addition of noise in both ZIP-DL and Muffliato not only affects the final utility of the models, but in some cases increases the number of learning iterations required for the accuracy to converge. We measure this communication overhead using the total number of bytes transferred to reach 50% top-1 accuracy for both ZIP-DL and Muffliato. Figure 4 shows the communication overhead in TiB for increasing noise levels. Performing 10 communication rounds per averaging step, Muffliato transfers $10 \times$ more data compared to ZIP-DL in one training iteration. Additionally, being sensitive to the noise, Muffliato does not even converge to an accuracy of 50% for noise levels beyond 8σ for both static and dynamic topologies. In contrast, ZIP-DL attains 72% accuracy (Figure 3), even for a noise level of 32σ , while having similar communication cost to No noise for noise levels up to 8σ . ZIP-DL, therefore provides better privacy guarantees while keeping the communication overhead in check.

Linking Figure 4 to Figure 1, we can compare the communication costs under an equivalent attacker advantage. If we consider a noise of 32σ for ZIP-DL, and 4σ for Muffliato, Muffliato requires $10.5\times$ more communication than ZIP-DL to reach the 50% accuracy bar.

The trend is replicated in the dynamic topology experiments where ZIP-DL consistently has a lower communication overhead of privacy as opposed to Muffliato.

8. Conclusion

DL addresses privacy in collaborative learning by preventing raw data sharing. Despite that, models shared between nodes still leak private information. We introduce ZIP-DL, which enhances privacy in DL by injecting correlated noise into shared models. ZIP-DL does not introduce additional messages or any sort of coordination across nodes, hence having minimal impact on communication cost while keeping convergence rates on par with the state-of-the-art. In particular, the noise introduced by ZIP-DL has a provably minimal impact on the convergence rate of the system compared to other similar approaches, meaning ZIP-DL can be used as a basic privacy addition even in high-performance regimes where traditional privacy-preserving mechanisms may be intractable to use because of utility degradation. In addition, we provide formal privacy guarantees in the form of PNDP, bounding the privacy leakage of a node. Experimental results confirm ZIP-DL's superior privacy-accuracy tradeoff under Linkability and Membership Inference Attacks. ZIP-DL performs particularly well on attacks that do not require crossing information across iterations, which are the most studied practical attack scenarios. Future work will explore broader scenarios beyond the initial assumptions of symmetric gossip matrices and behavior of a noisy gradient, aiming to extend ZIP-DL's applicability and robustness guarantees.

References

- [1] E. T. M. Beltrán, M. Q. Pérez, P. M. S. Sánchez, S. L. Bernal, G. Bovet, M. G. Pérez, G. M. Pérez, and A. H. Celdrán, "Decentralized federated learning: Fundamentals, state-of-the-art, frameworks, trends, and challenges," 2022. [Online]. Available: https://arxiv.org/abs/2211.08413
- [2] S. Lu, Y. Zhang, and Y. Wang, "Decentralized federated learning for electronic health records," in 2020 54th Annual Conference on Information Sciences and Systems (CISS). IEEE, 2020, pp. 1–5.
- [3] Y. Tian, S. Wang, J. Xiong, R. Bi, Z. Zhou, and M. Z. A. Bhuiyan, "Robust and privacy-preserving decentralized deep federated learning training: Focusing on digital healthcare applications," *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 2023.
- [4] J.-H. Chen, M.-R. Chen, G.-Q. Zeng, and J.-S. Weng, "BDFL: A byzantine-fault-tolerance decentralized federated learning method for autonomous vehicle," *IEEE Transactions on Vehicular Technology*, vol. 70, no. 9, pp. 8639–8652, 2021.
- [5] R. Ormándi, I. Hegedüs, and M. Jelasity, "Gossip Learning with Linear Models on Fully Distributed Data," *Concurrency and Computation: Practice and Experience*, vol. 25, no. 4, pp. 556–571, Feb. 2013.
- [6] X. Lian, W. Zhang, C. Zhang, and J. Liu, "Asynchronous decentralized parallel stochastic gradient descent," in *Proceedings of the 35th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 80. PMLR, 10–15 Jul 2018, pp. 3043–3052.
- [7] R. Shokri, M. Stronati, C. Song, and V. Shmatikov, "Membership Inference Attacks Against Machine Learning Models," in 2017 IEEE Symposium on Security and Privacy, SP 2017, San Jose, CA, USA, May 22-26, 2017. IEEE Computer Society, 2017, pp. 3–18.
- [8] J. Geiping, H. Bauermeister, H. Dröge, and M. Moeller, "Inverting Gradients - How easy is it to break privacy in federated learning?" in *Advances in Neural Information Processing Systems*, vol. 33. Curran Associates, Inc., 2020, pp. 16937–16947.
- [9] H. Yin, A. Mallya, A. Vahdat, J. M. Alvarez, J. Kautz, and P. Molchanov, "See through Gradients: Image Batch Recovery via GradInversion," in 2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). Nashville, TN, USA: IEEE, Jun. 2021, pp. 16332–16341.
- [10] S. Gade and N. H. Vaidya, "Private Optimization on Networks," in 2018 Annual American Control Conference (ACC). Milwaukee, WI: IEEE, Jun. 2018, pp. 1402–1409.
- [11] E. Cyffers, M. Even, A. Bellet, and L. Massoulié, "Muffliato: Peerto-Peer Privacy Amplification for Decentralized Optimization and Averaging," in Advances in Neural Information Processing Systems, 2022.
- [12] C. Dwork, F. McSherry, K. Nissim, and A. Smith, "Calibrating noise to sensitivity in private data analysis," in *Theory of Cryptography*. Berlin, Germany: Springer Berlin Heidelberg, 2006, pp. 265–284.
- [13] C. Sabater, A. Bellet, and J. Ramon, "An accurate, scalable and verifiable protocol for federated differentially private averaging," *Machine Learning*, vol. 111, no. 11, pp. 4249–4293, Nov. 2022.
- [14] H. Imtiaz, J. Mohammadi, R. Silva, B. Baker, S. M. Plis, A. D. Sarwate, and V. D. Calhoun, "A Correlated Noise-Assisted Decentralized Differentially Private Estimation Protocol, and its Application to fMRI Source Separation," *IEEE Transactions on Signal Processing*, vol. 69, pp. 6355–6370, 2021.
- [15] Y. Allouah, A. Koloskova, A. E. Firdoussi, M. Jaggi, and R. Guerraoui, "The Privacy Power of Correlated Noise in Decentralized Learning," May 2024. [Online]. Available: https://arxiv.org/abs/2405.01031
- [16] L. Zhu, Z. Liu, and S. Han, "Deep Leakage from Gradients," in Advances in Neural Information Processing Systems (NeurIPS), H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, Eds., vol. 32. Curran Associates, Inc., 2019.

- [17] N. Carlini, S. Chien, M. Nasr, S. Song, A. Terzis, and F. Tramèr, "Membership Inference Attacks From First Principles," in 2022 IEEE Symposium on Security and Privacy (SP), May 2022, pp. 1897–1914.
- [18] A. E. Mrini, E. Cyffers, and A. Bellet, "Privacy Attacks in Decentralized Learning," Feb. 2024. [Online]. Available: https://arxiv.org/abs/2402.10001
- [19] S. P. Kasiviswanathan, H. K. Lee, K. Nissim, S. Raskhodnikova, and A. Smith, "What Can We Learn Privately?" *SIAM Journal on Computing*, vol. 40, no. 3, pp. 793–826, Jan. 2011.
- [20] J. C. Duchi, M. I. Jordan, and M. J. Wainwright, "Minimax Optimal Procedures for Locally Private Estimation," *Journal of the American Statistical Association*, vol. 113, no. 521, pp. 182–201, Jan. 2018.
- [21] A. Shamir, "How to share a secret," Communications of the ACM, vol. 22, no. 11, pp. 612–613, Nov. 1979.
- [22] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y. Arcas, "Communication-efficient learning of deep networks from decentralized data," in *AISTATS*, 2017.
- [23] R. Kanagavelu, Q. Wei, Z. Li, H. Zhang, J. Samsudin, Y. Yang, R. S. M. Goh, and S. Wang, "Ce-fed: Communication efficient multiparty computation enabled federated learning," *Array*, vol. 15, p. 100207, 2022.
- [24] K. Bonawitz, V. Ivanov, B. Kreuter, A. Marcedone, H. B. McMahan, S. Patel, D. Ramage, A. Segal, and K. Seth, "Practical secure aggregation for privacy-preserving machine learning," in *proceedings of the* 2017 ACM SIGSAC Conference on Computer and Communications Security, 2017, pp. 1175–1191.
- [25] M. De Vos, S. Farhadkhani, R. Guerraoui, A.-m. Kermarrec, R. Pires, and R. Sharma, "Epidemic Learning: Boosting Decentralized Learning with Randomized Communication," *Advances in Neural Information Processing Systems*, vol. 36, pp. 36132–36164, Dec. 2023.
- [26] B. Le Bars, A. Bellet, M. Tommasi, E. Lavoie, and A.-M. Kermarrec, "Refined convergence and topology learning for decentralized SGD with heterogeneous data," in *Proceedings of The 26th International Conference on Artificial Intelligence and Statistics*, ser. Proceedings of Machine Learning Research, vol. 206. PMLR, 25–27 Apr 2023, pp. 1672–1702.
- [27] A. Koloskova, N. Loizou, S. Boreiri, M. Jaggi, and S. Stich, "A unified theory of decentralized SGD with changing topology and local updates," in *Proceedings of the 37th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 119. PMLR, 13–18 Jul 2020, pp. 5381–5393.
- [28] M. Jelasity, A. Montresor, and Ö. Babaoglu, "Gossip-based aggregation in large dynamic networks," ACM Trans. Comput. Syst., vol. 23, no. 3, pp. 219–252, 2005.
- [29] V. Zantedeschi, A. Bellet, and M. Tommasi, "Fully decentralized joint learning of personalized models and collaboration graphs," in *AISTATS*, ser. Proceedings of Machine Learning Research, vol. 108. PMLR, 2020, pp. 864–874.
- [30] A. Singh, T.-W. Ngan, P. Druschel, and D. S. Wallach, "Eclipse Attacks on Overlay Networks: Threats and Defenses," in *Proceedings IEEE INFOCOM 2006. 25TH IEEE International Conference on Computer Communications.* Barcelona, Spain: IEEE, 2006, pp. 1–12.
- [31] S. Boyd, A. Ghosh, B. Prabhakar, and D. Shah, "Randomized gossip algorithms," *IEEE Transactions on Information Theory*, vol. 52, no. 6, pp. 2508–2530, Jun. 2006.
- [32] I. Mironov, "Renyi Differential Privacy," in 2017 IEEE 30th Computer Security Foundations Symposium (CSF), Aug. 2017, pp. 263–275.
- [33] M. Gil, F. Alajaji, and T. Linder, "Rényi divergence measures for commonly used univariate continuous distributions," *Information Sciences*, vol. 249, pp. 124–131, Nov. 2013.
- [34] X. Lian, C. Zhang, H. Zhang, C.-J. Hsieh, W. Zhang, and J. Liu, "Can decentralized algorithms outperform centralized algorithms? a case study for decentralized parallel stochastic gradient descent," in *NIPS*, 2017.

- [35] A. Krizhevsky, V. Nair, and G. Hinton, "The cifar-10 dataset," vol. 55, no. 5, 2014. [Online]. Available: https://www.cs.toronto.edu/~kriz/ cifar.html
- [36] K. Hsieh, A. Phanishayee, O. Mutlu, and P. B. Gibbons, "The non-IID data quagmire of decentralized machine learning," in *ICML*, 2020.
- [37] A. Dhasade, A.-M. Kermarrec, R. Pires, R. Sharma, and M. Vujasinovic, "Decentralized Learning Made Easy with DecentralizePy," in *Proceedings of the 3rd Workshop on Machine Learning and Systems*, ser. EuroMLSys '23. New York, NY, USA: Association for Computing Machinery, May 2023, pp. 34–41.
- [38] A. Dhasade, A.-M. Kermarrec, R. Pires, R. Sharma, M. Vujasinovic, and J. Wigger, "Get more for less in decentralized learning systems," in 43rd IEEE International Conference on Distributed Computing Systems (ICDCS'23), 2023.
- [39] T. Lebrun, A. Boutet, J. Aalmoes, and A. Baud, "MixNN: protection of federated learning against inference attacks by mixing neural network layers," in *Proceedings of the 23rd ACM/IFIP International Middleware Conference*, 2022, pp. 135–147.

Appendix A. **Proof of Theorem 11**

A.1. Assumptions and lemmas

Proof. (Lemma 10) We proceed by induction on T for the expected value, and note $\Sigma_T \sum_{t=1}^T (1 - \gamma L)^t (\hat{M}\hat{W})^t \Sigma_Z^{(t) \mathsf{T}} (\hat{M}\hat{W})^t$. We have the following two update rules: =

$$\hat{X}^{(T+1)} = \hat{M}\hat{W}^{(T)} \left(\hat{X}^{(T)} - \gamma \nabla F(\hat{X}^{(T)}, \xi^{(T)}) + \hat{Z}^{(t)} \right)$$
$$\hat{\chi}^{(T+1)} = \hat{M}\hat{W}^{(T)} \left(\hat{\chi}^{(T)} - \gamma \nabla F(\hat{\chi}^{(T)}, \xi^{(T)}) \right).$$

First, we can show by another induction that this is a linear combination of Gaussian random variables. Then, let us look at the expected value for $\hat{X}^{(T+1)}$: if we assume that the expected value of $\hat{X}^{(T)}$ is $\hat{\chi}^{(T)}$, Assumption 7 guarantees that the expected value of $\hat{X}^{(T+1)}$ is $\hat{\chi}^{(T+1)}$. Finally, using Assumption 7, we have:

$$\hat{X}^{(T+1)} \sim \mathcal{N}\left(\hat{\chi}^{(T+1)}, L(1-\gamma L)\hat{M}\hat{W}^{(T)}\Sigma_T^{\mathsf{T}}(\hat{M}\hat{W}^{(T)}) + L(\hat{M}\hat{W}^{(T)})\Sigma_Z^{\mathsf{T}}(\hat{M}\hat{W}^{(T)})\right)$$

Thus, we obtain the update rule:

$$L\Sigma_{T+1} = (1 - \gamma L) \hat{M} \hat{W}^{(T)} (L\Sigma_T)^{\mathsf{T}} (\hat{M} \hat{W}^{(T)}) + L(\hat{M} \hat{W}^{(T)}) \Sigma_Z^{\mathsf{T}} (\hat{M} \hat{W}^{(T)}).$$

This yields the following:

$$L\Sigma_T = L \sum_{t=1}^T (1 - \gamma L)^t (\hat{M}\hat{W})^t \Sigma_Z^{(t) \mathsf{T}} (\hat{M}\hat{W})^t$$
$$= L \tilde{W}^{(T)} \Sigma_Z^{(t) \mathsf{T}} \tilde{W}^{(T)}$$

Proof. We know that
$$\left\|\hat{M}\hat{W}\right\|_{\infty} = 1.$$

$$\left\|\hat{\chi}^{(t)} - \hat{\chi}^{(t)}\right\|_{\infty}^{2} \leq \left\|\hat{M}\hat{W}^{(t)}\left(\hat{\chi}^{(t-1)} - \hat{\chi}^{(t-1)} - \gamma(\nabla F(\hat{\chi}^{(t-1)}, \xi^{(t-1)}) - \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)}))\right)\right\|_{\infty}^{2}$$

$$\leq \left\|\hat{\chi}^{(t-1)} - \hat{\chi}^{(t-1)} - \gamma(\nabla F(\hat{\chi}^{(t-1)}, \xi^{(t-1)}) - \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)}))\right\|_{\infty}^{2}$$

$$\leq 2\left\|\hat{\chi}^{(t-1)} - \hat{\chi}^{(t-1)}\right\|_{\infty}^{2} + 2\gamma^{2}\left\|\nabla F(\hat{\chi}^{(t-1)}, \xi^{(t-1)}) - \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)})\right\|_{\infty}^{2}.$$

$$:=C_{1}^{(T)}$$

We focus on the left term, and notice that:

$$\begin{split} C_1^{(T)} &= \left\| \nabla F(\hat{\chi}^{(t-1)}, \xi^{(t-1)}) - \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)}) + \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)}) - \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)}) \right\|_{\infty}^2 \\ &\leq 2 \left\| \nabla F(\hat{\chi}^{(t-1)}, \xi^{(t-1)}) - \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)}) \right\|_{\infty}^2 + 2 \left\| \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)}) - \nabla F(\hat{\chi}^{(t-1)}, \dot{\xi}^{(t-1)}) \right\|_{\infty}^2 \\ &\leq 2 \Delta^2 + 2L \left\| \hat{\chi}^{(t-1)} - \hat{\chi}^{(t-1)} \right\|_{\infty}^2 \end{split}$$

Thus, we get:

$$\left\| \hat{\chi}^{(t)} - \hat{\chi}^{(t)} \right\|_{\infty}^{2} \le (2 + 4\gamma^{2}L) \left\| \hat{\chi}^{(t-1)} - \hat{\chi}^{(t-1)} \right\|_{\infty}^{2} + 4\gamma^{2}\Delta^{2}$$

Unrolling the recursion, we obtain:

$$\left\|\hat{\chi}^{(t)} - \hat{\chi}^{(t)}\right\|_{\infty}^{2} \le \frac{4\gamma^{2}\Delta^{2}}{1+4\gamma^{2}L}((2+4\gamma^{2}L)^{t}-1).$$

A.2. Proof of Theorem 11

Theorem 11 (Privacy of ZIP-DL). T iterations of ZIP-DL (Algorithm 2) satisfies $(\alpha, \epsilon^{(T)}(a, v))$ -PNDP, where $\epsilon^{(T)}(a, v)$ is bounded for any two nodes $a, v \in \mathcal{V}$ by:

$$\frac{2\alpha\gamma^2\Delta^2}{L+4\gamma^2L^2}\sum_{t=0}^{T-1}\sum_{\substack{\hat{v}\in\hat{V}\\\hat{w}\in\hat{\Gamma}_{\hat{v}}^{(t)}}}\frac{(2+4\gamma^2L)^t-1}{\left(\left(\tilde{W}\tilde{C}\right)^{(t)}\tilde{\Sigma}_{\tilde{Y}^{(t)}}^{\mathsf{T}}\left(\tilde{W}\tilde{C}\right)^{(t)}\right)_{\tilde{w},\tilde{w}}},$$

where $\tilde{\Sigma}_{\tilde{Y}^{(t)}}$ is a diagonal matrix representing the noise variances of all noises generated by the algorithm up to time T, $\tilde{C}^{(t)}$ is a block-diagonal matrix representing the correlation factor at each iteration t, and $\tilde{W}^{(t)}$ is the accumulation of all the powers of the gossip matrix defined in Section 6.2.

Proof. We want to bound the privacy loss that emerges from the view of nodes V. To this end, we will use the matrix notations defined in Section 6.2, with a virtual network.

For simplicity of notation, we assume that the communication matrix is fixed through time. The proof generalizes to arbitrary communication matrix at time t at the expense of product notations. We obtain the following update rule for a given averaging round t:

$$\hat{X}^{(t+1)} = \hat{M}\hat{W}\left(\hat{X}^{(t)} - \gamma\nabla F(\hat{X}^{(t)}, \xi^{(t)}) + \hat{Z}^{(t)}\right)$$
(14)

We now want to focus on two distinct executions on datasets $\xi^{(t)} \sim_u \dot{\xi}^{(t)}$. The dot notation will correspond to the execution of the algorithm on an adjacent dataset.

If we now consider some set of nodes $V \subseteq \mathcal{V}$, we denote $\hat{V} \subseteq \hat{\mathcal{V}}$ the set of corresponding virtual nodes. We want to bound:

$$D_{\alpha}\left(\mathcal{O}_{V}(\mathcal{A}^{(T)}(\mathcal{D})) \| \mathcal{O}_{V}(\mathcal{A}^{(T)}(\dot{\mathcal{D}}))\right) = D_{\alpha}\left(\mathcal{O}_{\hat{V}}(\mathcal{A}^{(T)}(\mathcal{D})) \| \mathcal{O}_{\hat{V}}(\mathcal{A}^{(T)}(\dot{\mathcal{D}}))\right)$$
$$\leq \sum_{t=0}^{T-1} \sum_{\hat{v} \in \hat{V}} \sum_{\hat{w} \in \hat{\Gamma}_{\hat{v}}^{(t)}} D_{\alpha}\left(\hat{X}_{\hat{w}}^{(t)} \| \hat{X}_{\hat{w}}^{(t)}\right)$$
(15)

Our main focus is thus to bound $D_{\alpha}\left(\hat{X}_{\hat{w}}^{(t)}\|\hat{X}_{\hat{w}}^{(t)}\right)$. To this end, we want to apply Lemma 10 to both $\hat{X}_{\hat{w}}^{(t)}$ and $\hat{X}_{\hat{w}}^{(t)}$. One key remark is that both their distributions are centered on slightly altered trajectories, corresponding to the two adjacent datasets. Thus, we apply Lemma 10, and obtain:

with $\Sigma_T = \sum_{t=1}^T (1 - \gamma L)^t (\hat{M}\hat{W})^t \Sigma_Z^{\mathsf{T}} (\hat{M}\hat{W})^t$. One last thing we may want to do is factorize the noise expression: We now consider the matrix of all the noises $\tilde{Z}^{(T)} \in \mathbb{R}^{Tn^2}$, where $\tilde{Z}[tn^2 + \hat{w}] := \hat{Z}^{(t)}_{\hat{w}}$ for $0 \le \hat{w} < n^2$. We can express the term by considering the temporal matrix notations of Section 6.2. This leads to:

$$\Sigma_T = \tilde{W}^{(T)} \tilde{M} \Sigma_{\tilde{Y}}^{\mathsf{T}} (\tilde{W}^{(T)} \tilde{M})$$
(16)

Considering (11),(16) along with Lemma 8, we obtain:

$$D_{\alpha}\left(\hat{X}_{\hat{w}}^{(t)}\|\hat{X}_{\hat{w}}^{(t)}\right) \leq \frac{\alpha}{2L} \frac{\left\|\hat{\chi}_{\hat{w}}^{(t)} - \hat{\chi}_{\hat{w}}^{(t)}\right\|^{2}}{\left(\tilde{W}^{(t)}\tilde{M}\Sigma_{\tilde{Y}}^{\mathsf{T}}(\tilde{W}^{(t)}\tilde{M})\right)_{\tilde{w},\tilde{w}}}$$

Finally, we need to bound the difference between the two unnoised executions $\left\|\hat{\chi}_{\hat{w}}^{(t)} - \hat{\chi}_{\hat{w}}^{(t)}\right\|^2$ using Lemma 12. Putting it all together in (15), we get:

$$D_{\alpha}\left(\mathcal{O}_{V}(\mathcal{A}^{(T)}(\mathcal{D})) \| \mathcal{O}_{V}(\mathcal{A}^{(T)}(\dot{\mathcal{D}}))\right) \leq \frac{2\alpha\gamma^{2}\Delta^{2}}{L+4\gamma^{2}L^{2}} \sum_{t=0}^{T-1} \sum_{\hat{v}\in\hat{V}} \sum_{\hat{w}\in\hat{\Gamma}_{\hat{v}}^{(t)}} \frac{(2+4\gamma^{2}L)^{t}-1}{\left(\tilde{W}^{(t)}\tilde{M}\Sigma_{\tilde{Y}}^{-\mathsf{T}}(\tilde{W}^{(t)}\tilde{M})\right)_{\tilde{w},\tilde{w}}}.$$

$$(17)$$

A.3. Proof of Section 6.5

Sketch of proof. (Theorem 13) We can follow the same proof concept for the averaging algorithm presented in Algorithm 1. In this case, the notion of adjacent dataset is slightly different, as it concerns the original data itself $X^{(0)}$. We will obtain a simpler update rule:

$$\hat{X}^{(T+1)} = \hat{M}\hat{W}^{(T)} \left(\hat{X}^{(T)} + \hat{Z}^{(T)} \right)$$

Unrolling the model updates, and following a similar reasoning, we obtain that:

$$\hat{X}^{(T+1)} \sim \mathcal{N}((\hat{M}\hat{W})^T \hat{X}^{(0)}, \tilde{W}^T \tilde{M} \Sigma_Y^{\mathsf{T}}(\tilde{W}^T \tilde{M}))$$

where $\tilde{W}^{(T)} := ((\hat{M}\hat{W})^T, \ldots, \hat{M}\hat{W}) \in \mathbb{R}^{n^2 \times Tn^2}$

Then, using the same decomposition and Lemma 8, we observe the sensitivity is:

$$\left\| \left((\hat{M}\hat{W})^T \left(\hat{X}^{(0)} - \hat{X}^{(0)} \right) \right)_{\hat{w}} \right\|^2 \le \left((\hat{M}\hat{W})^T \right)_{\hat{w},\hat{u}} \Delta^2,$$

with Δ the bound on two adjacent datasets, since $\hat{X}^{(0)}$ and $\hat{X}^{(0)}$ are only different in component u. We can derive the desired result from this.

Appendix B. Proofs of Section 4

Lemma 1. Noise cancellation on the global model: for every node $a \in \mathcal{V} = [\![1, n]\!]$, it holds that

$$\sum_{v=1}^{n} W_{a,v} Z_{a \to v} = \sum_{v=1}^{n} W_{v,a} Z_{a \to v} = 0.$$

Proof. Using the notation in Algorithm 1, and since the matrix is symmetric, we have for a fixed node a:

$$\begin{split} \sum_{v \in \Gamma_a} W_{a,v} Z_{a \to v} &= \sum_{v \in \Gamma_a} W_{a,v} [Y_{a \to v} - \frac{1}{d_a W_{a,v}} \sum_{j \in \Gamma_a} W_{a,j} Y_{a \to j}] \\ &= \sum_{v \in \Gamma_a} W_{a,v} Y_{a \to v} - \sum_{v \in \Gamma_a} \frac{1}{d_a} (\sum_{j \in \Gamma_a} W_{a,j} Y_{a \to j}) \\ &= \sum_{v \in \Gamma_a} W_{a,v} Y_{a \to v} - \sum_{j \in \Gamma_a} W_{a,j} Y_{a \to j} \\ &= 0. \end{split}$$

Corollary 2. Impact on the global average model:

$$\forall t \in [0, T], \bar{x}^{(t+1)} = \bar{x}^{(t+1/2)}.$$

Proof.

$$\bar{x}^{(t+1)} = \frac{1}{n} \sum_{a=1}^{n} x_{a}^{(t+1)} = \frac{1}{n} \sum_{a=1}^{n} \sum_{v \in \Gamma_{a}} W_{a,v}^{(t)} (x_{v}^{(t+1/2)} + Z_{v \to a}^{(t)})$$
$$= \frac{1}{n} \sum_{a=1}^{n} \sum_{v \in \Gamma_{a}} W_{a,v}^{(t)} x_{v}^{(t+1/2)} + \frac{1}{n} \sum_{a=1}^{n} \sum_{v \in \Gamma_{a}} W_{a,v}^{(t)} Z_{v \to a}^{(t)}$$
(18)

For the first term:

$$\begin{split} \frac{1}{n} \sum_{a=1}^{n} \sum_{v \in \Gamma_a} W_{a,v}^{(t)} x_v^{(t+1/2)} &= \frac{1}{n} \sum_{a=1}^{n} W_a^{(t)} x^{(t+1/2)} \\ &= \frac{1}{n} \operatorname{T} \mathbf{1} x^{(t+1/2)} \\ &= \bar{x}^{(t+1/2)} \end{split}$$

Where we used the properties of the mixing matrix.

Focusing on the second term in (18), we obtain:

$$\frac{1}{n} \sum_{a=1}^{n} \sum_{v \in \Gamma_a} W_{a,v}^{(t)} Z_{v \to a}^{(t)} = \frac{1}{n} \sum_{a=1}^{n} \sum_{v=1}^{n} W_{a,v}^{(t)} Z_{v \to a}^{(t)}$$
$$= \frac{1}{n} \sum_{v=1}^{n} \sum_{a=1}^{n} W_{a,v}^{(t)} Z_{v \to a}^{(t)}$$
$$= 0.$$

Plugging this into (18) yields the desired result:

$$\bar{x}^{(t+1)} = \frac{1}{n} \sum_{a=1}^{n} x_a^{(t+1)} = \bar{x}^{(t+1/2)}$$

Lemma 3. Noise characterization for Algorithm 1: Consider that for node a, for all $v \in \Gamma_a^{(t)}$, $Y_{a \to v}^{(t)} \sim \mathcal{N}(0, \gamma^2 \varsigma_a^2)$, for a fixed topology $W^{(t)}$. Then, using the definition of Algorithm 1, we have:

$$\forall a, v \in \llbracket 1, n \rrbracket, Z_{a \to v}^{(t)} \sim \mathcal{N}\left(0, (\sigma_{a \to v}^{(t)})^2\right)$$

with

$$(\sigma_{a\to v}^{(t)})^2 = \left(\frac{(d_a - 1)^2}{d_a^2} + \frac{\sum_{j\in\Gamma_a^{(t)}, j\neq v}(W_{a,j}^{(t)})^2}{(d_a W_{a,v}^{(t)})^2}\right)\gamma^2\varsigma_a^2.$$

Proof. First, looking at the definition of $Z_{a \rightarrow v}$, we obtain that:

$$Z_{a \to v} = Y_{a \to v} - \frac{1}{d_a W_{a,v}} \sum_{j \in \Gamma_a} W_{a,j} Y_{a \to j}$$
$$= \frac{d_a - 1}{d_a} Y_{a \to v} - \frac{1}{d_a W_{a,v}} \sum_{\substack{j \in \Gamma_a \\ i \neq v}} W_{a,j} Y_{a \to j}$$
(19)

Thus, $Z_{a \to v}$ is a linear combination of independent Gaussian noises. This means that $Z_{a \to v}$ also follows a Gaussian distribution. Since the mean of all $Y_{a \to v}$ is 0, so is the mean of $Z_{a \to v}$. To obtain the desired result, we only need to look at the variance. Using (19), we obtain:

$$\begin{split} \mathbb{V}(Z_{a \to v}) &= \mathbb{V}(\frac{d_a - 1}{d_a} Y_{a \to v} - \frac{1}{d_a W_{a,v}} \sum_{\substack{j \in \Gamma_a \\ j \neq v}} W_{a,j} Y_{a \to j}) \\ &= (\frac{d_a - 1}{d_a})^2 \, \mathbb{V}(Y_{a \to v}) + (\frac{1}{d_a W_{a,v}})^2 \, \mathbb{V}\left(\sum_{\substack{j \in \Gamma_a \\ j \neq v}} W_{a,j} Y_{a \to j}\right) \\ &= (\frac{d_a - 1}{d_a})^2 \gamma^2 \varsigma_a^2 + (\frac{1}{d_a W_{a,v}})^2 \sum_{\substack{j \in \Gamma_a \\ j \neq v}} (W_{a,j})^2 \gamma^2 \varsigma_a^2 \\ &= \left(\frac{(d_a - 1)^2}{d_a^2} + \frac{\sum_{\substack{j \in \Gamma_a \\ j \neq v}} (W_{a,j})^2}{(d_a W_{a,v})^2}\right) \gamma^2 \varsigma_a^2 \end{split}$$

Lemma 14. For all $a \in \mathcal{V}, v, v' \in \Gamma_a$ such that $v \neq v'$, we have

$$\operatorname{Covar}(Z_{a \to v}, Z_{a \to v'}) = \frac{\sum_{k \in \Gamma_a} (W_{a,k})^2 - d_a \left[(W_{a,v})^2 + (W_{a,v'})^2 \right]}{d_a W_{a,v} W_{a,v'}} \frac{\gamma^2 \varsigma_a^2}{d_a}$$

Notably, in the case of uniform weights $(W_{a,v'} = W_{a,v}$ for all $v, v' \in \Gamma_a$), then the first fraction becomes -1, yielding to a covariance of $-\frac{\varsigma_a^2}{d_a}$.

Proof.

$$\begin{aligned} \operatorname{Covar}(Z_{a \to v}, Z_{a \to v'}) &= \mathbb{E}\left[Z_{a \to v} Z_{a \to v'}\right] \\ &= \mathbb{E}\left[\left(Y_{a \to v} - \frac{1}{d_a W_{a,v}} \sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right) \left(Y_{a \to v'} - \frac{1}{d_a W_{a,v'}} \sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right)\right] \\ &= \mathbb{E}\left[Y_{a \to v} Y_{a \to v'} - \frac{1}{d_a W_{a,v'}} Y_{a \to v} \sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k} - \frac{1}{d_a W_{a,v}} Y_{a \to v'} \sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right] \\ &+ \mathbb{E}\left[\frac{1}{d_a^2 W_{a,v} W_{a,v'}} \left(\sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right)^2\right] \\ &= 0 - \frac{1}{d_a W_{a,v'}} \mathbb{E}\left[Y_{a \to v} \sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right] - \frac{1}{d_a W_{a,v}} \mathbb{E}\left[Y_{a \to v'} \sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right] \\ &+ \frac{1}{d_a^2 W_{a,v} W_{a,v'}} \mathbb{E}\left[\left(\sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right)^2\right] \end{aligned}$$

Where we used that $Y_{a \to v}$ is independent from $Y_{a \to v'}$ because $v \neq v'$. The two middle terms are handled similarly, by symmetry between v and v':

$$\begin{split} \frac{1}{d_a W_{a,v'}} \mathbb{E}\left[Y_{a \to v} \sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right] &= \frac{W_{a,v}}{d_a W_{a,v'}} \mathbb{E}\left[(Y_{a \to v})^2\right] + \frac{1}{d_a W_{a,v'}} \mathbb{E}\left[Y_{a \to v} \sum_{k \in \Gamma_a, k \neq v} W_{a,k} Y_{a \to k}\right] \\ &= \frac{W_{a,v}}{W_{a,v'}} \frac{\gamma^2 \varsigma_a^2}{d_a} + \frac{1}{d_a W_{a,v'}} \mathbb{E}\left[Y_{a \to v}\right] \mathbb{E}\left[\sum_{k \in \Gamma_a, k \neq v} W_{a,k} Y_{a \to k}\right] \\ &= \frac{W_{a,v}}{W_{a,v'}} \frac{\gamma^2 \varsigma_a^2}{d_a}. \end{split}$$

Where we used the fact that $Y_{a \to v}$ is independent from $Y_{a \to v'}$, and that $\mathbb{E}[Y_{a \to v}] = 0$. By symmetry between v and v', we obtain the third term:

$$\frac{1}{d_a W_{a,v}} \mathbb{E}\left[Y_{a \to v'} \sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right] = \frac{W_{a,v'}}{W_{a,v}} \frac{\gamma^2 \varsigma_a^2}{d_a}.$$

Finally, the last term is the variance of a weighted sum of independent Gaussian variables. This yields:

$$\frac{1}{d_a^2 W_{a,v} W_{a,v'}} \mathbb{E}\left[\left(\sum_{k \in \Gamma_a} W_{a,k} Y_{a \to k}\right)^2\right] = \frac{\sum_{k \in \Gamma_a} (W_{a,k})^2}{d_a W_{a,v} W_{a,v'}} \frac{\gamma^2 \varsigma_a^2}{d_a}$$

Plugging this all into the main equation:

$$\begin{aligned} \operatorname{Covar}(Z_{a \to v}, Z_{a \to v'}) &= -\frac{W_{a,v}}{W_{a,v'}} \frac{\gamma^2 \varsigma_a^2}{d_a} - \frac{W_{a,v'}}{W_{a,v}} \frac{\gamma^2 \varsigma_a^2}{d_a} + \frac{\sum_{k \in \Gamma_a} (W_{a,k})^2}{d_a W_{a,v} W_{a,v'}} \frac{\gamma^2 \varsigma_a^2}{d_a} \\ &= -\frac{(W_{a,v})^2 + (W_{a,v'})^2}{W_{a,v} (W_{a,v'})^2} \frac{\gamma^2 \varsigma_a^2}{d_a} + \frac{\sum_{k \in \Gamma_a} (W_{a,k})^2}{d_a W_{a,v} W_{a,v'}} \frac{\gamma^2 \varsigma_a^2}{d_a} \\ &= \frac{\sum_{k \in \Gamma_a} (W_{a,k})^2 - d_a \left[(W_{a,v})^2 + (W_{a,v'})^2 \right]}{d_a W_{a,v} W_{a,v'}} \frac{\gamma^2 \varsigma_a^2}{d_a} \end{aligned}$$

This is the desired result.

Appendix C. Convergence rate of ZIP-DL

C.1. Useful inequalities

Lemma 15. For any set of n vectors $(a_i)_{i=1}^n, a_i \in \mathbb{R}^d$:

$$\left\|\sum_{i=1}^{n} a_{i}\right\|^{2} \le n \sum_{i=1}^{n} \|a_{i}\|^{2}$$

Lemma 16. For any vectors $\mathbf{a}, \mathbf{b} \in \mathbb{R}^d$, for any $\beta > 0$, we have:

$$\|\mathbf{a} + \mathbf{b}\|^2 \le (1 + \beta) \|\mathbf{a}\|^2 + (1 + \beta^{-1}) \|\mathbf{b}\|$$

C.2. Convergence rate results

Theorem 4 (Convergence rate of ZIP-DL). For any number of iterations T, there exists a constant stepsize γ s.t. for Algorithm 2, it holds that $\frac{1}{2W_T} \sum_{t=0}^T w_t (\mathbb{E} \left[f(\bar{x}^{(t)}) \right] - f^*) + \frac{\mu}{2} r_{T+1}$ is bounded by:

$$\mathcal{O}\left(\frac{\bar{\omega}^2}{n\mu T} + \frac{LA'}{\mu^2 T^2} + \frac{r_0 L}{p} \exp\left[-\frac{\mu p (T+1)}{192\sqrt{3}L}\right]\right)$$

where $f^* = f(x^*)$, $r_t = \mathbb{E}\left[\left\|\bar{x}^{(t)} - x^*\right\|^2\right]$, $w_t = (1 - \frac{\mu}{2}\gamma)^{-(t+1)}$, $W_T = \frac{1}{T}\sum_{t=1}^T w_t$ and $A' = \frac{16-4p}{2(16-7p)}(\bar{\omega}^2 + \frac{18}{p}\bar{\vartheta}^2) + \frac{d}{n}\frac{16-4p}{16-7p}\sum_{a,v=1}^n d_a\frac{(d_v-1)^2}{d_v}\varsigma_v^2$.

Proof. (Theorem 4) We used a similar situation to [27] with $\tau = 1$ and a fixed communication matrix sampling distribution. The proof follows the same structure as in their paper. Our algorithm only induces some changes in some of the intermediary lemmas that need to be adapted to obtain the main result.

To this end, we restate Proposition 1 and Lemmas 6 and 7 in our setting. We can then solve the main equation in the following manner:

- We bound the distance of the averaged model to the optimum Lemma 6. It is the case $r_t = \mathbb{E} \left[\left\| \bar{x}^{(t)} x^* \right\|^2 \right]$,
- $e_t = f(\bar{x}^{(t)}) f(x^*), a = \frac{\mu}{2}, b = 1, c = \frac{\bar{\omega}^2}{n}$ and B = 3L• We also bound the consensus distance with a recursive bound using Lemma 7. The next step is to determine the precise constants to continue the proof.

The equation of the consensus distance (Lemma 7) is of the following form:

$$\Xi_t \le (1+\beta)(1-\frac{7p}{16})\Xi_{t-1} + (1+\beta)D\gamma^2 e_{t-1} + \left((1+\beta)A + (1+\beta^{-1})\frac{d}{n}\sum_{i=1}^n d_i\sum_{v=1}^n \frac{(d_v-1)^2}{d_v}\varsigma_v^2\right)\gamma^2$$

with $e_t = f(\bar{x}^{(t)}) - f(x^*)$, $D = \frac{36L}{p}$ and $A = \bar{\omega}^2 + \frac{18}{p}\bar{\vartheta}^2$ Because of the $1 + \beta$ factor, we cannot directly apply the recursion-solving Lemma to our scenario (Lemma 12 in [27]). We can however modify our current equation to match the beginning of their proof of this Lemma. This is mostly possible

because we are in the case $\tau = 1$, meaning that we require a slightly stronger property on the matrices' distribution. We can now rewrite the previous equation by setting $\beta = \frac{3p}{16-7p}$ (rq: we only require $\beta > 0$, which is satisfied since $0 \le p \le 1$),

$$(1+\beta) = \frac{16-7p+3p}{16-7p} = \frac{16-4p}{16-7p}$$

and

$$(1+\beta)(1-\frac{7p}{16}) = \frac{16-4p}{16-7p}\frac{16-7p}{16} = \frac{16-4p}{16} = 1-\frac{p}{4}$$

Putting these inside the main equation, and setting $A' = \left((1+\beta)A + (1+\beta^{-1})\frac{d}{n}\sum_{i=1}^{n}d_i\sum_{v=1}^{n}\frac{(d_v-1)^2}{d_v}\varsigma_v^2\right)\gamma$ and $D' = \frac{1}{2}\sum_{i=1}^{n}d_i\sum_{v=1}^{n}\frac{(d_v-1)^2}{d_v}\varsigma_v^2$ $\frac{1}{2}(1+\beta)D = \frac{16-4p}{2(16-7p)}\frac{36L}{p}$:

$$\Xi_t \le (1 - \frac{p}{4})\Xi_{t-1} + 2D'\gamma^2 e_{t-1} + 2A'\gamma^2$$

This is exactly the term obtained in [27]'s Lemma 12 after unrolling the different terms, which is only needed when $\tau > 1$. Thus, in our case, we can fall back to their proof using this approach. We just need to ensure Lemma 12's hypothesis are verified:

- 0

- 0
 τ = 1 ≥ 1
 A', D' ≥ 0
 {γ²}_{t≤0} is a ⁸/_p-slow decreasing sequence since it is a constant.
 {w_t := (1 aγ)^{-(t+1)}} is a ¹⁶/_p-slow increasing sequence of weights

Thus, we can have the same reasoning as the proof of Lemma 12 in [27], and obtain the lemma's result with the following equation:

$$B\sum_{t=0}^{T} w_t \Xi_t \le \frac{b}{2} \sum_{t=0}^{T} w_t e_t + 64A' B\gamma^2 \sum_{t=0}^{T} w_t$$
(20)

for some constant E and stepsize $\gamma \leq \frac{1}{16} \sqrt{\frac{pb}{D'B}}$ From this point on, we can follow the exact ending of the proof, the only difference are our new constants A' and D'. We thus obtain:

$$\frac{1}{2W_T} \sum_{t=0}^T bw_t e_t \le \frac{1}{W_T} \sum_{t=0}^T \left(\frac{(1-a\gamma)w_t}{\gamma} r_t - \frac{w_t}{\gamma} r_{t+1} \right) + \frac{c}{W_T} \sum_{t=0}^T w_t \gamma + \frac{64BA'}{W_T} \sum_{t=0}^T w_t \gamma^2$$

(with $W_T = \sum_{t=0}^T w_t$). Finally, we use Lemma 13 of [27] to obtain the final result, since we verify the following hypothesis: $a, b > 0, c, A', B \ge 0$ Thus, we obtain that $\frac{1}{2W_T} \sum_{t=0}^T be_t w_t + ar_{T+1} \le \mathcal{O}\left(r_0 d\exp\left[-\frac{a(T+1)}{d}\right] + \frac{c}{aT} + \frac{BA'}{a^2T^2}\right)$ for a well chosen γ , and plugging in the values yields the result for Theorem 4.

From the previous result, we also prove the convergence rate to an arbitrary ρ accuracy:

Corollary 5. Setting all the constants to be the same as in Theorem 4, for any target accuracy $\rho > 0$, there exists a constant stepsize γ such that Algorithm 2 reaches the target accuracy after at most

$$\frac{3\kappa\bar{\omega}^2}{n\mu\rho} + \sqrt{\frac{3\kappa LA'}{\rho\mu^2} + \frac{192\sqrt{3}L}{\mu p}\ln\left[\frac{3\kappa r_0L}{\rho p}\right]}$$

training iterations, where κ is the constant that arises when upper bound $\mathcal{O}\left(\frac{\bar{\omega}^2}{n\mu T} + \frac{LA'}{\mu^2 T^2} + \frac{r_0L}{p}\exp\left[-\frac{\mu p(T+1)}{192\sqrt{3}L}\right]\right)$ is expanded out.

Proof. For Algorithm 2 to reach the target accuracy ρ , we need to have:

$$\frac{1}{2W_T} \sum_{t=0}^T w_t \left(\mathbb{E}\left[f(\bar{x}^{(t)}) \right] - f^* \right) + \frac{\mu}{2} r_{T+1} \le \rho$$
(21)

However, from Theorem 4, we know that

$$\frac{1}{2W_T} \sum_{t=0}^T w_t \left(\mathbb{E} \left[f(\bar{x}^{(t)}) \right] - f^* \right) + \frac{\mu}{2} r_{T+1}$$

$$\leq \kappa \left(\frac{r_0 L}{p} \exp \left[-\frac{\mu p (T+1)}{192 \sqrt{3}L} \right] + \frac{\bar{\omega}^2}{n \mu T} + \frac{LA'}{\mu^2 T^2} \right)$$

for some constant $\kappa > 0$.

Thus, in order to satisfy (21), it suffices to simultaneously have:

$$\kappa \frac{r_0 L}{p} \exp\left[-\frac{\mu p(T+1)}{192\sqrt{3}L}\right] \leq \frac{\rho}{3}$$
$$\iff \exp\left[\frac{\mu p(T+1)}{192\sqrt{3}L}\right] \geq \frac{3\kappa r_0 L}{\rho p}$$
$$\iff T \geq \frac{192\sqrt{3}L}{\mu p} \ln\left[\frac{3\kappa r_0 L}{\rho p}\right] - 1$$
(22)

$$\kappa \frac{\bar{\omega}^2}{n\mu T} \le \frac{\rho}{3} \iff T \ge \frac{3\kappa \bar{\omega}^2}{n\mu\rho}$$
(23)

$$\kappa \frac{LA'}{\mu^2 T^2} \le \frac{\rho}{3} \iff T \ge \sqrt{\frac{3\kappa LA'}{\rho\mu^2}}$$
(24)

Therefore, in order to simultaneously satisfy the inequalities in (22),(23), and (24), it suffices to have

$$T \ge \frac{192\sqrt{3}L}{\mu p} \ln\left[\frac{3\kappa r_0 L}{\rho p}\right] - 1 + \frac{3\kappa \bar{\omega}^2}{n\mu\rho} + \sqrt{\frac{\kappa L A'}{3\mu^2}}$$
$$\implies T > \frac{192\sqrt{3}L}{\mu p} \ln\left[\frac{3\kappa r_0 L}{\rho p}\right] + \frac{3\kappa \bar{\omega}^2}{n\mu\rho} + \sqrt{\frac{3\kappa L A'}{\rho\mu^2}}$$

-			
ſ			I.
н			L
L.	_	_	

C.3. Intermediary lemmas proofs

Proof. (Proposition 1) Nothing changes in this proof, since only the gradient and the loss functions are needed. \Box

Proof. (Lemma 6) Because of ZIP-DL's properties (in particular Corollary 2), this property holds almost immediately from Lemma 8 of [27]. Using Corollary 2, we have:

$$\begin{aligned} \left\| \bar{x}^{(t+1)} - x^* \right\|^2 &= \left\| \bar{x}^{(t+1/2)} - x^* \right\|^2 \\ &= \left\| \bar{x}^{(t)} - \frac{\gamma}{n} \sum_{i=1}^n \nabla F_i(x_i^{(t)}, \xi_i^{(t)}) - x^* \right\|^2 \end{aligned}$$

This corresponds to the first line of Lemma 8, so following the proof will yield the same result. More generally, this property would not hold as it stands for a method that only cancels the noise in expectation: because we consider a norm here, this will lead to an additional term equal to the variance of the residual noise on the network, e.g. the variance of the sum of all the noises. If the noises are not correlated, this is an estimator of the original distribution, yielding an additional term. In our case, this term is exactly zero.

Proof. (Lemma 7)

$$n\Xi_{t} = \sum_{i=1}^{n} \mathbb{E}_{t} \left[\left\| x_{i}^{(t)} - \bar{x}^{(t)} \right\|^{2} \right]$$
$$= \sum_{i=1}^{n} \mathbb{E}_{t} \left[\left\| (x_{i}^{(t)} - \bar{x}^{(t-1)}) - (\bar{x}^{(t)} - \bar{x}^{(t-1)}) \right\|^{2} \right]$$
$$\leq \sum_{i=1}^{n} \mathbb{E}_{t} \left[\left\| (x_{i}^{(t)} - \bar{x}^{(t-1)}) \right\|^{2} \right]$$

Where we used that $\sum_{i=1}^{n} \|a_i - \bar{a}\|^2 \le \sum_{i=1}^{n} \|a_i\|^2$. Unrolling the model update:

$$\begin{split} x_i^{(t)} &= \sum_{v \in \Gamma_i^{(t-1)}} W_{i,v}^{(t-1)}(x_v^{(t-1/2)} + Z_{v \to i}^{(t-1)}) \\ &= \sum_{v \in \Gamma_i^{(t-1)}} W_{i,v}^{(t-1)}((x_v^{(t-1)} - \gamma \nabla F_v(x_v^{(t-1)}, \xi_v^{(t-1)})) + Z_{v \to i}^{(t-1)}) \\ &= \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)}(x_v^{(t-1)})) - \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)} \gamma \nabla F_v(x_v^{(t-1)}, \xi_v^{(t-1)})) + \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)} Z_{v \to i}^{(t-1)}) \end{split}$$

This yields, after expanding the recursion and using Lemma 16, for any $\beta > 0$:

$$\begin{split} n\Xi_t &\leq \sum_{i=1}^n \mathbb{E}_t \left[\left\| \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)} x_v^{(t-1)}) - \bar{x}^{(t-1)} - \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)} \gamma \nabla F_v(x_v^{(t-1)}, \xi_v^{(t-1)})) + \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)} Z_{v \to i}^{(t-1)}) \right\|^2 \right] \\ &\leq (1+\beta) \underbrace{\sum_{i=1}^n \mathbb{E}_t \left[\left\| \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)} x_v^{(t-1)}) - \bar{x}^{(t-1)} - \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)} \gamma \nabla F_v(x_v^{(t-1)}, \xi_v^{(t-1)})) \right\|^2 \right] \\ &+ (1+\beta^{-1}) \underbrace{\sum_{i=1}^n \mathbb{E}_t \left[\left\| \sum_{v \in \Gamma_i^{(t-1)}} (W_{i,v}^{(t-1)} Z_{v \to i}^{(t-1)}) \right\|^2 \right]}_{:=T_2} \end{split}$$

Looking at the second term, and using Lemma 15:

$$\begin{split} T_{2} &\leq \sum_{i=1}^{n} d_{i} \sum_{v \in \Gamma_{i}^{(t-1)}} \mathbb{E}_{t} \left[\left\| W_{i,v}^{(t-1)} Z_{v \to i}^{(t-1)} \right\|^{2} \right] \\ &\leq \sum_{i=1}^{n} d_{i} \sum_{v \in \Gamma_{i}^{(t-1)}} \mathbb{E}_{t} \left[(W_{i,v}^{(t-1)})^{2} \left\| Z_{v \to i}^{(t-1)} \right\|^{2} \right] \\ &\leq \sum_{i=1}^{n} d_{i} \sum_{v \in \Gamma_{i}^{(t-1)}} \mathbb{E}_{t,i \in \Gamma_{v}^{(t-1)}} \left[(W_{i,v}^{(t-1)})^{2} \left\| Z_{v \to i}^{(t-1)} \right\|^{2} \right] \\ &\leq \sum_{i=1}^{n} d_{i} \sum_{v \in \Gamma_{i}^{(t-1)}} \mathbb{E}_{t,i \in \Gamma_{v}^{(t-1)}} \left[(W_{i,v}^{(t-1)})^{2} \mathbb{E}_{W^{(t-1)}} \left[\left\| Z_{v \to i}^{(t-1)} \right\|^{2} \right] \right] \end{split}$$

Using Lemma 3 for a fixed gossip matrix, and leveraging $W_{i,v}^{(t)} = W_{v,i}^{(t)}$ since we assume symmetric matrices, we obtain:

$$\begin{split} T_2 &\leq \sum_{i=1}^n d_i \sum_{v=1}^n \mathbb{E}_{t,i \in \Gamma_v^{(t-1)}} \left[(W_{v,i}^{(t-1)})^2 d(\sigma_{v \to i}^{(t-1)})^2 \right] \\ &\leq d \sum_{i=1}^n d_i \sum_{v=1}^n \mathbb{E}_{t,i \in \Gamma_v^{(t-1)}} \left[(W_{i,v}^{(t-1)})^2 \left(\frac{(d_v - 1)^2}{d_v^2} + \frac{\sum_{j \in \Gamma_v^{(t)}, j \neq v} (W_{v,j}^{(t)})^2}{(d_v W_{v,i}^{(t)})^2} \right) \gamma^2 \varsigma_v^2 \right] \\ &\leq d\gamma^2 \sum_{i=1}^n d_i \sum_{v=1}^n \mathbb{E}_{t,i \in \Gamma_v^{(t-1)}} \left[\left(\frac{(d_v - 1)^2 (W_{i,v}^{(t-1)})^2}{d_v^2} + \frac{\sum_{j \in \Gamma_v^{(t)}, j \neq v} (W_{j,v}^{(t)})^2}{d_v^2} \right) \varsigma_v^2 \right] \\ &\leq d\gamma^2 \sum_{i=1}^n d_i \sum_{v=1}^n \left(\frac{(d_v - 1)^2}{d_v^2} + \frac{d_v - 1}{d_v^2} \right) \varsigma_v^2 \end{split}$$

$$\leq d\gamma^2 \sum_{i=1}^n d_i \sum_{v=1}^n \left(\frac{(d_v - 1)^2}{d_v}\right) \varsigma_v^2$$

Where we used that $(W_{i,v})^2 \leq 1$ for all $i, v \in \mathcal{V}$ For T_1 , we obtain that:

$$T_{1} = \mathbb{E}_{t} \left[\left\| W^{(t-1)} \left(x^{(t-1)} - \gamma \nabla F(x^{(t-1)}, \xi^{(t-1)}) \right) - \bar{x}^{(t-1)} \right\|_{F}^{2} \right]$$

This is the exact notation from [27], in the proof of the corresponding Lemma (Lemma 9), with the notation $\tau = 1$ (our matrix notation are transposed to theirs). By following the same steps, we obtain:

$$T_1 \le n \left((1 - \frac{p}{2}) \Xi_{t-1} + \frac{p}{16} \Xi_{t-1} + \frac{36L}{p} \gamma^2 (f(\bar{x}^{(t-1)}) - f(x^*)) + (\bar{\omega}^2 + \frac{18}{p} \bar{\vartheta}^2) \gamma^2 \right)$$

Plugging T_1 and T_2 back into the original term, we obtain:

$$\begin{split} \Xi_t &\leq (1+\beta) \left((1-\frac{7p}{16}) \Xi_{t-1} + \frac{36L}{p} \gamma^2 (f(\bar{x}^{(t-1)}) - f(x^*)) + (\bar{\omega}^2 + \frac{18}{p} \bar{\vartheta}^2) \gamma^2 \right) \\ &+ (1+\beta^{-1}) \frac{d\gamma^2}{n} \sum_{i=1}^n d_i \sum_{v=1}^n \left(\frac{(d_v-1)^2}{d_v} \right) \varsigma_v^2 \\ &\leq (1+\beta) (1-\frac{7p}{16}) \Xi_{t-1} + (1+\beta) \frac{36L}{p} \gamma^2 (f(\bar{x}^{(t-1)}) - f(x^*)) \\ &+ \left((1+\beta) (\bar{\omega}^2 + \frac{18}{p} \bar{\vartheta}^2) + (1+\beta^{-1}) \frac{d}{n} \sum_{i=1}^n d_i \sum_{v=1}^n \left(\frac{(d_v-1)^2}{d_v} \varsigma_v^2 \right) \right) \gamma^2 \end{split}$$

For any $\beta > 0$, which is the desired result.