# Desiderata of evidence for representation in neuroscience

Stephan POHL<sup>§</sup>, Department of Philosophy, New York University, stephan.pohl@nyu.edu

Edgar Y WALKER, Department of Physiology and Biophysics, Computational Neuroscience Center, University of Washington, Seattle, WA, <u>eywalker@uw.edu</u>

David L BARACK, Departments of Neuroscience and Philosophy, University of Pennsylvania, Philadelphia, PA, <u>dbarack@gmail.com</u>

Jennifer LEE, Center for Neural Science, New York University, jll616@nyu.edu

Rachel N DENISON, Department of Psychological & Brain Sciences, Boston University, Boston, MA, <u>rdenison@bu.edu</u>

Ned BLOCK, Department of Philosophy, New York University, ned.block@nyu.edu

Florent MEYNIEL<sup>#</sup>, Cognitive Neuroimaging Unit, INSERM, CEA, CNRS, Université Paris-Saclay, NeuroSpin center, Gif/Yvette, France & Institute for Neuromodulation, GHU Paris psychiatrie et neuroscience, Sainte Anne Hospital, Paris, France, <u>florent.meyniel@cea.fr</u>

Wei Ji MA<sup>#</sup> Center for Neural Science and Department of Psychology, New York University, <u>weijima@nyu.edu</u>

*\**: co-senior authors; *§*: corresponding author

#### Short abstract

When claiming that a neural response represents a feature of the world, scientists try to establish that the neural response is (1) sensitive and (2) specific to the feature, (3) invariant to other features, and (4) functional downstream in the brain. We formalize these desiderata in information-theoretic terms, permitting their precise statement while unifying the different analysis methods used in neuroscience under one framework, thereby, providing a common terminology to researchers. We discuss how common analysis methods are used to evaluate the desiderata and present canonical examples to illustrate the desiderata at work in research practice.

#### Long abstract

This paper develops a systematic framework for the evidence neuroscientists use to establish whether a neural response represents a feature. Researchers try to establish that the neural response is (1) sensitive and (2) specific to the feature, (3) invariant to other features, and (4) functional, which means that it is used downstream in the brain. We formalize these desiderata in information-theoretic terms. This formalism allows us to precisely state the desiderata while unifying the different analysis methods used in neuroscience under one framework. We discuss how common methods such as correlational analyses, decoding and encoding models, representational similarity analysis, and tests of statistical dependence are used to evaluate the desiderata. In doing so, we provide a common terminology to researchers that helps to clarify disagreements, to compare and integrate results across studies and research groups, and to identify when evidence might be missing and when evidence for some representational conclusion is strong. We illustrate the framework with several canonical examples, including the representation of orientation, numerosity, faces, and spatial location. We end by discussing how the framework can be extended to cover models of the neural code, multi-stage models, and other domains.

#### Keywords

computation, decoding, encoding, information, mutual information, neural code, neuroscience, representation, representational similarity analysis

## 1. Introduction

Humans and other animals perceive their environment, reason about how their goals can be achieved, and then, in coordination with the environment, behave to achieve those goals. Neuroscience aims to explain how the brain brings about these abilities. In a common explanatory framework, sensory inputs are transformed into representations, while computations transform these representations through multiple steps and integrate them into various cognitive processes including reasoning, planning, learning, and memory (Marr, 1982). When it is decided that a behavioral response is appropriate, representations are transformed into motor commands (Barack & Krakauer, 2021; Perkel & Bullock, 1968).

Neuroscientists tend to agree that the notion of representation is an important component in their explanatory practices (Baker, Lansdell, & Kording, 2022; Favela & Machery, 2023). Appeals to representations appear frequently. Marr (1982) discusses the transformation of representations of local retinotopic properties to representations of shape properties that are used for object recognition in vision. Salzman, Britten, and Newsome (1990) find that stimulation with microelectrodes enhances the sensory representations of motion direction. Haxby et al. (2001) suggest that the representations of faces and objects are distributed and overlapping. Kriegeskorte and Diedrichsen (2019) discuss models of the representational geometry of neural responses. Yet, despite this widespread use of representational terminology, neuroscientists report high uncertainty about what counts as evidence for representation (Favela & Machery, 2023). As a result, the epistemological status of representational claims made by neuroscientists and how to compare these claims across studies and research groups remain unclear. When two researchers disagree over whether an area represents a feature, do they disagree over methodology or do they disagree over a property of the brain? We aim to clarify the use of representational terminology in neuroscience by providing a systematic framework for what evidence neuroscientists use to establish whether a neural response represents a feature.

We are not proposing a new approach to studying representation in neuroscience, but rather, we are explicitly formalizing what neuroscientists have been doing all along. Previous analyses of the notion of representation in neuroscience have been framed in terms of decoding or reconstruction models (deCharms & Zador, 2000; Zhang, Ginzburg, McNaughton, & Sejnowski, 1998), brain signatures (Kragel, Koban, Barrett, & Wager, 2018), or representational similarity (Haxby, Connolly, & Guntupalli, 2014; Kriegeskorte & Diedrichsen, 2019). By contrast, we do not focus on one particular analysis technique; instead, we aim to unify these approaches by identifying the core desiderata that all methods aim to establish.

For ease of exposition, we focus on representations that carry information about the state of the world, whether past, present, or future. Not all representations do. Imaginings, hypothetical reasoning, and representations of goals can occur independently of what the state of the world is. Some extensions of our framework beyond this restriction are discussed in section 5.6.

We formulate four desiderata for evidence supporting claims about representation. In order to show that some neural response is a representation of a feature, for instance that the fusiform face area (FFA) represents faces (Kanwisher, McDermott, & Chun, 1997), scientists seek

evidence that, we believe, falls under four desiderata: First, the neural response is *sensitive* to the feature, that is it carries information about the feature. Second, the neural response is *specific* to the feature, that is most variations of the neural response occur only when the feature is changed. Third, the neural response is *invariant* to other features; a representation of a face, for instance, responds to faces irrespective of features such as position or lighting. Fourth, the neural response is *functional*, that is it not only carries information about the feature, but it also makes that information available to other cognitive processes, for instance in the form of a behavioral response.

We suggest information-theoretic quantities that formalize the desiderata. These quantities make our framework precise while being agnostic to the details of the methodology. We thereby develop a common terminology that researchers can use to integrate results across studies. Our information-theoretic analysis builds on a long line of previous work. After its development in an engineering context (Shannon, 1948), information theory has been used to analyze the notion of representation in philosophy (Dretske, 1981; Usher, 2001), it has been used to characterize the information captured by decoding models (Quiroga & Panzeri, 2009), and the efficiency with which spike trains represent stimulus features (Bialek, Rieke, de Ruyter van Steveninck, & Warland, 1991; Bialek, DeWeese, Rieke, & Warland, 1993; Laughlin, 2001; Rieke, Warland, & Bialek, 1993).

We begin by defining sensitivity, specificity, invariance, and functionality in information-theoretic and causal terms. With these formal definitions at hand, we discuss more common measures and show how they are used to approximate the information-theoretic quantities. We then review several canonical examples of representations: orientation in V1, numerosity in the parietal cortex, faces in FFA, and spatial location in the hippocampus. We show how arguments both for and against the existence of representations in these canonical studies have been made on the basis of one or multiple of the desiderata. Finally, we discuss ways in which the application of our framework can be extended.

### 2. Definition of the desiderata

We introduce the desiderata using a toy example. Let us assume that we are interested in how the ripeness of an apple is represented in the brain. The ripeness of an apple presented to a subject is the stimulus feature s of interest. Depending on the context, we may consider s to be a continuous variable ranging gradually from not ripe to ripe, or we consider s to be a binary variable that only takes the discrete values of ripe or not ripe. We are looking for an activity pattern in the brain, a neural response r, that represents whether the apple is ripe. n is the color of the apple, which is one cue the subject uses to infer ripeness (see Figure 1).



**Figure 1. Generative model of our toy example**. *s* is the ripeness of an apple, *n* is the color of the apple, *r* is a neural response that might be a representation of *s*, and *b* is a behavioral response; here our subject eats or does not eat the apple depending on whether they perceive it to be ripe. The causal structure in this model is simplified and just one possible structure. Here, *n* is causally intermediate between *s* and *r*, but other features *n* may also be causes of *s*, or *n* and *s* may cause *r* together. There may also be other causal routes from *s* to *r* that bypass *n*, or *n* may not be causally related to the other variables.

In typical experimental contexts, *s* could be any feature of interest like the orientation of a grating, the category of an object, or a more abstract feature such as the probability with which another feature changes its value. Similarly, *n* could be a confounding feature like the contrast of an image, the perspective from which an object is viewed, or, as discussed in section 2.1.3, the modality of a stimulus or the task context. If researchers investigate multiple features, *s* or *n* could be multi-dimensional. *r* could be any aspect of the brain that is hypothesized to represent a stimulus feature. Typically, *r* is a high-dimensional vector reflecting the activity pattern of a population of neurons as measured for example with fMRI, EEG, or implanted electrodes. Finally, *b* could be any behavioral response to *s*, such as an eye movement or a button press.

Some work is not framed in terms of the representation of features, but in terms of representations that are selective for a single kind of thing. A neural event may indicate the presence of some kind of thing, e.g. the firing of neurons in the fusiform face area indicates the presence of faces (Kanwisher et al., 1997). Note that a population of neurons that is selectively responsive to the presence of a single kind of thing, thereby is also sensitive and specific to the binary feature that can take as its value either that the thing is present or absent. Yet the framing in terms of features can easily be extended to many-valued categorical features, like object category, or to features with a graded scale, like orientation. For such many valued features, it does not make sense to speak of the presence or absence of a thing, which is why we prefer the more general framing in terms of features.

In order to show that a neural response r is a representation of stimulus feature s, scientists seek evidence for four desiderata: (1) r is *sensitive* to s; (2) r is *specific* to s; (3) the dependence of r on s is *invariant* to other features n; (4) r is *functional*, that is, it provides information about s to downstream processes, e.g. by causing a behavioral response b to s.

Often, experiments start with a feature *s* and an experimental setup in which *s* and other parameters *n* are modulated in order to search for a neural response *r* that represents *s*. However, some experiments also start with a neural response *r* and try to establish which feature *s* is represented by *r*.

The choice of which variable and which values of the variables to include in one's analysis is crucial. In a case where one fails to include a relevant parameter n, the desiderata might suggest that some neural response r is a representation of s, when, actually, r is rather a representation of some other feature. Say we are looking for a representation of ripeness, but we do not consider color as an additional parameter. We test our hypothesis with a species of apple where red apples tend to be ripe but green apples are not. In that context, we might mistake a mere representation of color for a representation of ripeness. Yet, once apples that are green even when ripe are included in the analysis, we see that the representation of color no longer tracks ripeness.

## 2.1. Desiderata about the relationship between stimulus and neural response

We begin by spelling out the desiderata of sensitivity, specificity, and invariance in information-theoretic terms (see Figure 2). These desiderata are about the relation between features of the world state s, n, and the neural response r. Functionality, which is about the causal role of r, will be discussed subsequently.

Box 1 summarizes basic notions of information theory. Information-theoretic desiderata have been used to analyze the notion of representation in philosophy (Dretske, 1981; Usher, 2001). One of our desiderata, specificity, has been used under the label 'coding efficiency' in work on the neural code of spike trains (Bialek et al., 1991, 1993; Rieke et al., 1993). Yet, to our knowledge, ours is the first use of information theory to systematize the evidence that neuroscientists take to support claims about representation.

#### **Box 1: Information theory**

Here we provide a brief introduction to the central concepts of information theory. See (Cover & Thomas, 2006) for a more extensive treatment. Information theory was first developed in an engineering context for studying communication systems (Shannon, 1948). The brain can also be framed as an information processing system, which motivates the application of information theory in neuroscience (Bialek et al., 1991; Perkel & Bullock, 1968; Rieke et al., 1993).

We assume that variables are discrete; continuous variables are often discretized in practice. We write random variables as lower case letters (e.g., x). Values of the variables are written with an index (e.g.,  $x_i$ ).  $x_i$  also abbreviates the event  $x = x_i$ .

#### Entropy

Entropy measures the uncertainty about a random variable, which can also be understood as the amount of variability or randomness associated with a variable. Entropy is high when a variable has many possible values with equally high probabilities.

**Definition:** 
$$H(x) = -\sum_{i} p(x_i) \log p(x_i)$$

#### **Conditional entropy**

The conditional entropy measures how much uncertainty there is on average about some variable conditioned on another variable—that is, it measures the average uncertainty about the first variable that remains after the value of the second variable is specified.

**Definition:** 
$$H(x|y) = -\sum_{i} p(y_i) \sum_{j} p(x_j|y_i) \log p(x_j|y_i)$$

#### **Mutual information**

The mutual information between two variables measures how much information one variable provides about the other variable. That is, it measures how much less information is needed in order to specify the value of the first variable, conditioned on the second variable, or equivalently, it measures the reduction in uncertainty about one variable by conditioning on the other variable. Mutual information is symmetric.

**Definition:** 
$$I(x; y) = H(x) - H(x|y) = H(y) - H(y|x)$$

Mutual information can also be understood as a measure of the statistical dependence between two variables. When *x* and *y* are statistically independent, then I(x; y) = 0. When there is some statistical dependence between *x* and *y*, then I(x; y) > 0.

#### Joint entropy

The entropy of a joint distribution is calculated as follows.

**Definition:** 
$$H(x, y) = -\sum_{i,j} p(x_i, y_j) \log p(x_i, y_j)$$

#### **Conditional mutual information**

Conditional mutual information measures the mutual information between two variables conditioned on a third variable. That is, it measures how much, on average, uncertainty about a first variable is reduced by conditioning on a second variable, given that the value of the third variable is already specified.

**Definition:** 
$$I(x; y|z) = H(x|z) - H(x|y,z) = H(x,z) + H(y,z) - H(x, y, z) - H(z)$$



Figure 2. Information-theoretic characterization of sensitivity, specificity, and invariance. The variables s, n, and r correspond to the stimulus feature of interest, other features, and the neural response. Circles in the Venn diagram to the left represent the total variability associated with a given variable measured in terms of the entropy H of that variable. Overlapping areas represent the mutual information I between variables. The desiderata of sensitivity, specificity, invariance, and the conditional forms of sensitivity and specificity are defined in terms of the equations on the right. The shapes in the middle depict the same quantities in terms of the respective areas in the Venn diagram to the left. The numeric values of the desiderata range from 0 to 1, with 1 indicating maximal satisfaction and 0 indicating no satisfaction of a desideratum.

#### 2.1.1. Sensitivity

The neural response *r* is sensitive to *s* given that *r* is highly informative about *s*. In our ripeness example, *r* is sensitive to the ripeness of an apple given that ripeness can be predicted from *r*, e.g. because the neural response rate is higher for ripe apples than for non-ripe apples. Another example would be the sensitivity of neurons in V1 to the orientation of a stimulus (Hubel & Wiesel, 1959).

#### **Mutual Information**



**Figure 3. Examples illustrating mutual information**. In A, there is no mutual information between *r* and *s*; they are statistically independent. In B, there is high mutual information; the value of *r* depends on the value of *s*.

In order for *r* to be sensitive to *s*, there has to be high mutual information between *r* and *s* (see Figure 3). However, the absolute amount of mutual information is not very informative because it depends on how many values each variable can take, or more precisely, their entropies (see Box 1). What matters for sensitivity is not the absolute amount of mutual information, but that the mutual information between *r* and *s* captures a large proportion of the information about *s*. If *r* captures the total information about *s* (i.e. I(s;r) = H(s)) it is possible to predict the value of *s* from *r* without error (see Figure 4). A quantity that satisfies this constraint is the mutual information between *s* and *r*, normalized by the entropy of *s*:

sensitivity: = 
$$\frac{I(s;r)}{H(s)}$$

That *r* is highly sensitive to *s* therefore means that the information *r* carries about *s* captures a large proportion of the variability of *s*. Because of the normalization, sensitivity takes a value between 0 (no sensitivity) and 1 (perfect sensitivity).



**Figure 4. Example illustrating sensitivity**. In A, sensitivity of *r* to *s* is low, in B it is high. However, the same values of *r* and *s* underlie both plots. In A, *r* is related to a continuous degree of ripeness *s*. In B, ripeness has been collapsed into the binary variable *s*' of whether an apple is ripe enough to eat. In the given example, the mutual information between *r* and *s* and the mutual information between *r* and *s* is the same, but *r* is much more sensitive to the binary variable *s*' than to the continuous variable *s*, because the value of *s*' can be predicted perfectly from *r*, whereas most of the variability of *s* is more fine-grained than the categories of *s*' and is unrelated to *r*.

We cannot generally expect a sensitivity of 1. Representations may be inaccurate. For instance, many people are inexperienced in telling species of trees apart. One may represent a tree as being a beech, however, such a representation is often inaccurate, i.e. its sensitivity to the presence of beeches is low. It might still be the case that being a beech tree is the feature to which the representation is most sensitive.

#### 2.1.2. Specificity

The neural response *r* is specific to *s* if many of the changes in *r* are explained by changes in *s*. In other words, *s* explains a large proportion of the variability of *r*, or, conditioned on *s*, *r* remains mostly constant. In our ripeness example, the neural response *r* is specific to the ripeness of an apple when many of the changes in *r* are explained by changes in ripeness (see Figure 5). Recall that *s* can be multi-dimensional. A representation that is sensitive to multiple features—displaying mixed selectivity (Fusi, Miller, & Rigotti, 2016; Rigotti et al., 2013)—will be specific only to the combination of these features.



**Figure 5. Examples illustrating specificity.** Here, the mutual information between s' and r is the same for A and B. However, in B, r is more specific to s' than in A, because s' explains a larger proportion of the variability of r, in A, conditioned on s', there is more remaining variability of r (in B, the distributions are more narrow along the r-axis than in A).

Formally, specificity is defined as the mutual information between *s* and *r*, normalized by the entropy of *r*.

specificity: = 
$$\frac{I(s;r)}{H(r)}$$

That *r* is highly specific to *s* therefore means that a large proportion of the variability of *r* carries information about *s*. An equivalent expression of specificity is as follows:

$$1 - \frac{H(r|s)}{H(r)}$$

That is, we can also think of specificity as the proportion of the variability of *r* that is explained by *s*. The desideratum of specificity has also been used under the label 'coding efficiency' (Bialek et al., 1993; Rieke et al., 1993). This work evaluated what proportion of the variability of spike trains carries information about the stimulus; the larger the proportion of the variability of spike trains that carries information about the stimulus, the more efficient the neural code is for transmitting information about the stimulus.

Sensitivity and specificity both depend on the mutual information between *r* and *s*; they differ only in the normalizing factor. High sensitivity means that *s* can be predicted from *r* with high

accuracy. High specificity means that *r* can be predicted from *s* with high accuracy. Often, sensitivity is approximated by the performance of decoding models, specificity is approximated by the performance of encoding models (see section 3). Confusing sensitivity with specificity has been argued to underlie faulty interpretations in neuroimaging (Poldrack, 2006, 2011).

The notions of sensitivity and specificity in our framework should not be confused with sensitivity and specificity in a binary decision or test context. In that context, 'sensitivity' refers to the true positive rate, i.e. the proportion of positive instances truly detected as positive, and 'specificity' refers to the true negative rate, i.e. the proportion of negative instances truly detected as negative. There is a high level analogy between the two; in both contexts, sensitivity indicates that a test or representation is responsive to its target while specificity indicates that it is not responsive to other things. Yet, mathematically, these notions are quite different.

We should not usually expect to find a perfect specificity of 1. There are factors unrelated to the world state of interest that affect the neural response. These include neural noise (Faisal, Selen, & Wolpert, 2008) and internal processing reflecting brain states such as arousal, motivation, or mind wandering.

#### 2.1.3. Invariance

The representation of *s* by *r* is invariant to another feature *n* if *r* does not depend on *n* for a given value of *s*, i.e. if *r* is not sensitive to *n*, conditioned on *s*. In our ripeness example, in order to show that the representation of ripeness by *r* is invariant to the color of the apple, one would have to show that the neural response to ripeness stays the same independent of the color of the apple. Say a population of neurons responds to ripe apples with a high firing rate. This would have to be the same for ripe apples whether they are red or green. Another common example is the invariance of representations of object categories in the primate inferior temporal cortex to the orientation of the object (Logothetis, Pauls, & Poggio, 1995; Quiroga, Reddy, Kreiman, Koch, & Fried, 2005).

Trivially, *r* is invariant to *n* when *r* is not sensitive to *n*. However, *s* and *n* may be statistically related. If they are, then, when *r* is sensitive to *s*, it will also be somewhat sensitive to *n*. In such a case, *r* can still be invariant to *n* as long as all of the dependence of *r* on *n* is accounted for by *r*'s dependence on *s*. In other words, *r* is invariant to *n*, if, at least conditioned on *s*, *n* does not account for any of the variability of *r* (see Figure 6).



**Figure 6. Example illustrating invariance.** Both in A and B, the neural response *r* depends both on the ripeness *s* and the color *n*. Yet, in A, *r* fails to be invariant to *n*; even conditioned on *s*, *r* tends to be larger for n = red, than for n = green. In B, *r* is invariant to *n*; overall, *r* tends to be larger for n = red than for n = green; yet, conditioned on *s*, this dependence of *r* on *n* disappears.

Formally, invariance is defined as follows:

invariance: = 
$$1 - \frac{I(n;r|s)}{H(r|s)}$$

Which, equivalently, can be expressed as follows:

$$\frac{H(r|n,s)}{H(r|s)}$$

An invariance of 1 means that no more of the variability of r can be accounted for by the combination of s and n than by s alone. An invariance below 1 means that some of the variability of r that is unrelated to s (i.e. conditioned on s) can be explained by n.

Two applications of the desideratum of invariance are of particular interest. The parameter n may reflect the modality of the stimulus. A representation r of location s might for instance be invariant to whether the location of an event is presented to a subject in terms of a visual cue or an auditory cue. r is invariant to modality n when r represents s both in the condition n = auditory and when n = visual. Invariance to modality is great evidence for the claim that r is a representation of s. However, lack of invariance to modality is more difficult to interpret. It might

be that the same features are independently represented in the perceptual systems specialized for different modalities.

Another kind of invariance is task invariance; here *n* stands for the task. *r* is task-invariant when it is sensitive to *s* irrespective of the task. Some populations of neurons may only respond to some stimulus feature *s* when it is relevant under a task, in which case *r* is not invariant to the task. Such a lack of task invariance does not need to indicate that *r* is a poor candidate for a representation of *s*; it might simply be that the brain only represents *s* when it has to. That a neural response is particularly sensitive or specific only in conditions where it is task relevant may even suggest that it is used in the response to the task, i.e. that it is functional. It has, for instance, been shown that the sensitivity and specificity of parietal areas to numerosity is increased in numerosity-related tasks (Castaldi, Piazza, Dehaene, Vignaud, & Eger, 2019).

Both the invariance and specificity of the neural response for complex features tends to increase along hierarchies of perceptual processing. By the data processing inequality (Cover & Thomas, 2006), sensitivity can only stay the same or decrease from early processing stages to later processing stages. However, later areas tend to be more specific to complex features and invariant to low-level features as they disentangle representations of the complex features from low-level features (DiCarlo & Cox, 2007). Object category, for instance, can be decoded already from early visual areas using sophisticated models; however, in inferotemporal cortex there are populations of neurons that are highly specific to object category and invariant to low-level features such as the orientation of the object.

#### 2.1.4. Conditional sensitivity/specificity

Sensitivity and specificity can be evaluated conditioned on some other parameter n. A common goal for testing conditional sensitivity and conditional specificity is to rule out that r depends on s merely because r depends on n—and s happens to also depend on n. This can be ruled out by showing that, even after conditioning on n, r continues to depend on s—that is the mutual information between r and s is high even conditioned on n (see Figure 7).

In our ripeness example, we may for instance test whether even just for green apples, *r* continues to depend on the ripeness of the apple, i.e. whether *r* differs between green apples that are ripe and green apples that are not ripe. If *r* were not a representation of ripeness, but just of the color of the apple, it would also depend on ripeness, given that red apples tend to be ripe and green apples do not tend to be ripe. However, conditioned on the color, there would be no mutual information left between *r* and ripeness.

#### **Conditional Mutual Information**



**Figure 7. Example illustrating conditional mutual information.** In A and B, there is mutual information between r and both the ripeness s and color n of an apple. In A, the dependence of r on s is broken by conditioning on n. Conditioned on color, r no longer carries information about ripeness. In B, there still is high mutual information between r and s, conditioned on n. Even conditioned on color, r is informative about ripeness.

As their unconditional analogues, conditional sensitivity and conditional specificity are defined as different normalizations of the mutual information between *s* and *r*, but conditioned on *n*:

conditional sensitivity: = 
$$\frac{I(s;r|n)}{H(s|n)}$$
 conditional specificity: =  $\frac{I(s;r|n)}{H(r|n)}$ 

That *r* is sensitive to *s*, conditioned on *n*, means that the information *r* carries about *s*, even after conditioning on *n*, captures a large proportion of the variability of *s*. That *r* is specific to *s*, conditioned on *n*, means that, even after conditioning on *n*, a large proportion of the variability of *r* carries information about *s*.

In practice, sensitivity and specificity are always evaluated conditioned on the experimental setup. In order to test these desiderata in their unconditional form, one can reduce the dependence on the experimental setup for instance by varying conditions as much as possible and randomizing them.

#### 2.2. Functionality

In order for a neural response *r* to be a representation of the feature *s* it does not only have to carry information about *s*, but that information also has to be used in the brain (Baker et al.,

2022; deCharms & Zador, 2000; Perkel & Bullock, 1968; Ritchie, Kaplan, & Klein, 2019; Shadlen & Newsome, 1994). A representation of *s*, for instance, may be used in reasoning about *s*. Generally, when *r* is used as a representation of *s*, subsequent processes that rely on information about *s* receive that information from *r*. In our ripeness example, *r* may be used as a representation of ripeness when the subject makes the decision to either eat an apple or not to eat it on the basis of whether *r* represents the apple to be ripe or not.

In experiments, functionality is most commonly evaluated by testing whether there is a behavioral response *b* that depends on *s* because it is caused by *r*. The behavioral response may be a report of *s*, or a response that takes *s* into account more indirectly, like a decision made on the basis of *s*. As an example, Salzman et al. (1990) showed that when neurons with a specific preferred motion direction are stimulated, the behavioral report of the perceived motion direction is biased towards the preferred direction of the stimulated neurons. Hereafter, we restrict our discussion of functionality to tests that relate *r* to a behavioral response *b*. More complex models that consider processes between *r* and *b* are discussed in section 5.3.

Functionality is a causal desideratum. In behavioral tests of functionality, r is functional as a representation of s when r causes s-related behavior b (Brette, 2019; Jones & Kording, 2019). Causal claims can be established with experimental interventions (Pearl, 2009; Woodward, 2003). In order to show that r causes b one can intervene on r and demonstrate that this intervention leads to changes in b.

In the case of the world-related desiderata of sensitivity, specificity, and invariance interventions are easy. Stimulus parameters s and n, typically, are under the control of the experimenter. Causality is therefore not usually an issue for these desiderata. Many experiments used primarily to evaluate the information-theoretic desiderata also establish causal dependencies because they perform interventions on s and/or n by changing the stimulus.

In the case of functionality, establishing causal claims is more difficult because it is more difficult to intervene on the neural response *r*. Many methods can only knock out populations of neurons and cannot induce specific activity patterns. It is therefore useful to also have non-interventionist tests for functionality.

## 2.2.1. Information-theoretic desiderata of functionality

Even in the absence of interventions, statistical methods can provide important clues for causal dependencies (Pearl, 2009). The central challenge is to show that a statistical dependence between *b* and *r* obtains because *r* causes *b* and not because of some other causal connection. Figure 8 depicts causal structures in which there is a statistical dependence between *b* and  $r_1$ ; but only in Figure 8A is  $r_1$  functional.



**Figure 8. Examples illustrating causal relations of functionality.** A depicts a causal graph in which  $r_1$  is functional as a representation because it causes *b*; the causal effect is mediated by a further neural response  $r_2$ . B depicts two causal graphs in which  $r_1$  is not functional. Either *b* is statistically related to  $r_1$  merely because both are caused by *s*; however, *b* is caused by some other neural response  $r_2$  and not by  $r_1$ . Or *b* is statistically related to  $r_1$  might for instance be a neural response involved in monitoring performance.

Information-theoretic desiderata can also be used to test for functionality (see Figure 9). These are analogous to the desiderata discussed in section 2.1, except that they characterize how the behavioral response *b* depends on the neural response *r* and the target feature *s* rather than how *r* depends on the stimulus parameters *s* and *n*.



**Figure 9. Information-theoretic characterization of functionality.** Circles in the Venn diagram to the left represent the total variability associated with a given variable measured in terms of the entropy *H* of that variable. Overlapping areas represent the mutual information *I* between variables. The desiderata of functional sensitivity, functional specificity, functional invariance, and the functional conditional forms of sensitivity and specificity are defined in terms of the equations on the right. The shapes in the middle depict the same quantities in terms of the respective areas in the Venn diagram to the left. The numeric values of the desiderata range from 0 to 1, with 1 indicating maximal satisfaction and 0 indicating no satisfaction of a desideratum.

**Functional sensitivity and functional specificity** offer the most basic test of functionality by showing that *b* and *r* are statistically related. *r* is functionally specific to *b* when *b* can be decoded or predicted from *r*. In our ripeness example, *r* is functionally specific when one can use *r* to predict whether or not the subject will eat the apple. A common measure of functional specificity is the probability that a model correctly predicts *b* from *r* (Britten, Newsome, Shadlen, Celebrini, & Movshon, 1996). *r* is functionally sensitive to *b* when an encoding model of *b* predicts a large proportion of the variability of *r*. Such encoding models are common in research about representations in motor areas; in other contexts, it is often more natural to evaluate functional specificity and to predict *b* from *r*—usually, *r* is very high dimensional whereas *b*, often, only has one binary dimension (e.g. left vs right button pressed) so that *b* can be

predicted from *r* much better than *r* from *b*. Establishing functional sensitivity and functional specificity, however, does not establish that it is indeed *r* and not some other neural response that causes the behavior.

**Functional invariance** is more interesting. *b* is functionally invariant to *s* if additional variability of *s*, that is unrelated to *r*, does not change *b*. In other words, no information in *b* about *s* bypasses *r*. This suggests that *b* receives its information about *s* from *r*, i.e. that the causal impact of *s* on *b* is mediated by *r*. In our ripeness example, functional invariance is demonstrated if—while holding fixed whether *r* represents the apple to be ripe or not—it is no longer possible to predict whether the subject will eat the apple based on whether the apple is actually ripe; that is, *s* does not provide more information about *b* than *r*.

**Functional conditional specificity** allows drawing similar conclusions. *b* is functionally specific to *r*, conditioned on *s*, if variability of *r*, that is unrelated to *s*, predicts *b*. Error trials are trials in which some disturbance unrelated to *s* caused *b*. That such errors can be predicted from *r* demonstrates functional conditional specificity. In our ripeness example, *r* is functionally conditionally specific if—while holding fixed whether the apple is actually ripe or not—one can predict from *r* whether the subject will eat the apple. Functional conditional specificity has been evaluated for instance for perceived motion direction in area MT; researchers showed that the reported motion direction changes spontaneously—could be predicted from neural activity in area MT (Bradley, Chang, & Andersen, 1998).

**Functional conditional sensitivity** is evaluated by testing whether an encoding model of *b* predicts a large proportion of the variability of *r* that is unrelated to *s*. It is therefore closely related to functional conditional specificity. However, analogous to the case of unconditional functional sensitivity and specificity, in many contexts, it is more natural to evaluate functional conditional specificity than functional conditional sensitivity. It is usually easier to predict *b* (commonly a binary variable) from the high dimensional neural response that caused it than making a prediction the other way around.

When functional invariance and functional conditional specificity are well established, the only salient alternative to r being a cause of b is that b is a cause of r or that r is caused by some other neural response involved in the preparation of b. r may for instance be involved in a feedback loop that plays a role in controlling behavior. These alternatives can sometimes be ruled out on anatomical grounds. It is plausible, for instance, that neural populations in perceptual areas are not involved in controlling behavior. In other cases, these alternatives can only be ruled out with interventions that show, for instance, that one can stop b from being responsive to s by inactivating r.

## 3. Comparison to practical measures

We have formalized the desiderata of evidence for representation in information-theoretic terms. This formalization allows us to state the desiderata in a systematic and precise manner while being agnostic with respect to analysis technique. In practice, however, neuroscientists rarely compute these information-theoretic quantities from actual measurements. Many datasets are too small to allow for a robust approximation of the entropy of the neural response or of the mutual information between neural response and stimulus features or behavioral response. That being said, the analysis methods used by neuroscientists to find evidence for representation are conceptually closely related to these desiderata. Here, we discuss how common methods approximate the information-theoretic quantifications of the desiderata.

#### 3.1. Linear correlation

A very common quantitative measure of the relationship between two variables is their linear Pearson correlation, defined as the normalized covariance. Notably, two variables that are correlated must have above zero mutual information. This follows from the fact that zero mutual information implies that the two variables are statistically independent, which in turn implies that they have zero linear correlation. Establishing that *r* and *s* are correlated, therefore also establishes that they have above zero mutual information and that sensitivity and specificity are larger than zero.

The strength of a correlation can be measured with the correlation coefficient  $\rho$ . However, it is not generally the case that when *r* is more strongly correlated with *s* than with *n*, that the mutual information between *r* and *s* is also higher than the mutual information between *r* and *n*, or that *r* is more sensitive to *s* than to *n*. The dependence of *r* on *s* may for instance be U-shaped such that there is high mutual information but no linear correlation (Reshef et al., 2011) (see Figure 10). In this case, mutual information is the superior measure.



**Figure 10. Example illustrating a nonlinear relationship between** *s* **and** *r*. *r* depends on *s* by a quadratic function. There is high mutual information between *s* and *r*, but *s* and *r* are not correlated.

Comparisons of mutual information can be made on the basis of correlation strength only when the dependence between *r* and *s* is linear and of known forms of distribution. If the dependence

between *r* and *s* is linear with added Gaussian noise, the mutual information depends on  $\rho$  as follows (Cover & Thomas, 2006):

$$I(s; r) = -\frac{1}{2} \log \left(1 - \rho_{s,r}^{2}\right)$$

That is, given that the dependencies between r and s and between r and n are linear, when r is more strongly correlated with s than with n, then the mutual information between r and s is larger than between r and n.

#### 3.2. Decoding models

The most common measures of sensitivity are measures of the performance of a decoding model, that is, a model that predicts *s* from *r*. Such models have been used to decode faces (Abbott, Rolls, & Tovee, 1996) and object identity (Hung, Kreiman, Poggio, & DiCarlo, 2005) from the monkey temporal cortex, to decode spatial location from the human hippocampus (Hassabis et al., 2009), auditory location from the monkey auditory cortex (Miller & Recanzone, 2009), and orientation from the monkey V1 (Graf, Kohn, Jazayeri, & Movshon, 2011).

A good measure of sensitivity is the accuracy of a decoding model, because it has an easy to interpret lower and upper bound. When the decoding accuracy is at the chance level, this means that the given decoding model cannot extract any information about *s* from *r*, suggesting that the sensitivity is 0. The higher the decoding accuracy is above the chance level, the higher the sensitivity. 100% decoding accuracy means one can perfectly predict *s* from *r*, i.e. the sensitivity of *r* to *s* is 1.

However, accuracy only measures whether an estimate of a decoding model is exactly true or not. A more general measure of sensitivity can be derived from the expected logarithmic loss of a decoding model. Consider a decoding model  $p_{\theta}(s|r)$  with parameters  $\theta$ . The expected logarithmic loss of this model is E[-log  $p_{\theta}(s|r)$ ]. If the decoding model is fitted well and  $p_{\theta}(s|r)$  is identical to the true probability p(s|r), then E[-log  $p_{\theta}(s|r)$ ] = H(s|r), that is, the expected logarithmic loss of a decoding model is an estimate of the entropy H(s|r). The case where  $p_{\theta}(s|r)$ and p(s|r) mismatch is discussed below. An expected logarithmic loss of 0 means that the sensitivity of *r* to *s* is 1; *s* can perfectly be decoded from *r*. That is, the lower bound on the expected logarithmic loss of a decoding model corresponds to the upper bound on sensitivity. The lower bound on sensitivity corresponds to the chance level. When the sensitivity is 0, the expected logarithmic loss of a decoding model is equal to the loss of a model based on the prior distribution p(s) alone, i.e. E[-log p(s)]. Sensitivity can be estimated as follows:

sensitivity: 
$$\frac{I(s;r)}{H(s)} = \frac{H(s) - H(s|r)}{H(s)} = \frac{\mathbb{E}[-\log p(s)] - \mathbb{E}\left[-\log p_{\theta}(s|r)\right]}{\mathbb{E}[-\log p(s)]}$$

Any measure of the performance of a decoding model that covaries with the logarithmic loss can be used as a measure of sensitivity in an analogous manner. This includes, for instance, decoder accuracy, mean squared error, or absolute error.

When  $p_{\theta}(s|r)$  and p(s|r) mismatch, then the expectation of the logarithmic loss of a decoder under the true joint probability distribution p(s,r) merely offers an upper bound for the true entropy H(s|r). That is, the estimate of the mutual information with the decoder is merely a lower bound on the true mutual information. There are two main reasons for why a decoding model  $p_{\theta}(s|r)$  may not fit the true probability p(s|r). First, the available dataset may mismatch the underlying distribution because it is too small or biased. Secondly, the decoding model may not be sufficiently complex to fit the true relationship between *s* and *r*. A linear model, for instance, will not pick up on non-linear relationships. Since the mutual information estimated with a decoding model is a lower bound on the true mutual information, estimates of sensitivity made with decoding models are also lower bounds on the true sensitivity. By showing that a decoding model performs better than chance (e.g. E[-log  $p_{\theta}(s|r)] < E[-log <math>p(s)]$ ), one shows that the sensitivity of *r* to *s* has to be larger than zero. However, comparative claims are more difficult to interpret. Even when the sensitivity of *r* to *s*, estimated with some decoding model, is larger than the sensitivity of *r* to *n*, this does not mean that *r* truly has to be more sensitive to *s* than to *n* because one might have underestimated the sensitivity of *r* to *n*.

Usually, as long as one has enough training data, estimates of sensitivity made with decoding models are better the more complex the decoding model is. Given the greater amount of neural data that is available with more recent recording techniques, this motivates the use of complex machine learning tools like support vector machines (Cortes & Vapnik, 1995) or more unconstrained deep neural networks (Livezey & Glaser, 2021). Sometimes, the complexity of decoding models is deliberately restricted, for instance to linear models, because it is assumed that linearly decodable features can be used by a single downstream neuron or layer (DiCarlo & Cox, 2007; Kriegeskorte & Diedrichsen, 2019). When decoding models are constrained by biological considerations, then the research does not merely aim to establish claims about sensitivity, but it aims to uncover the neural code that is being used in the brain. We discuss such models in section 5.2.

#### 3.3. Encoding models

An encoding model is a model that predicts *r* from stimulus parameters. Encoding models can be used to estimate specificity analogously to how decoding models are used to estimate sensitivity. Examples of encoding models include models of the receptive fields of neurons in the cat visual cortex (Hubel & Wiesel, 1959, 1962), the encoding of shape in populations of neurons in monkey V4 (Pasupathy & Connor, 2002), and population receptive field models with fMRI of the human visual cortex (Dumoulin & Wandell, 2008). General linear models in fMRI analysis (Friston, Jezzard, & Turner, 1994; Friston et al., 1995) are also encoding models, as are generalized linear models (Paninski, Pillow, & Lewi, 2007) and linear-nonlinear models (Aljadeff, Lansdell, Fairhall, & Kleinfeld, 2016) in the analysis of electrophysiology data.

Analogous to decoding models, the expected logarithmic loss of an encoding model that predicts *r* from *s*, i.e. E[-log  $p_{\theta}(r|s)$ ], can be used to estimate the specificity of *r* to *s*.

specificity: 
$$\frac{I(s;r)}{H(r)} = \frac{H(r) - H(r|s)}{H(r)} = \frac{\mathbb{E}[-\log p(r)] - \mathbb{E}\left[-\log p_{\theta}(r|s)\right]}{\mathbb{E}[-\log p(r)]}$$

The lower bound on the expected logarithmic loss of the encoding model corresponds to the upper bound on specificity; when *r* can perfectly be predicted from *s*—i.e. E[-log  $p_{\theta}(r|s)$ ] = 0—then specificity is 1. When the expected loss is above the baseline predictability, i.e. E[-log  $p_{\theta}(r|s)$ ] > E[-log p(r)], then specificity is larger than 0. The baseline predictability of the neural population without knowledge of the stimulus E[-log p(r)] is often assessed by shuffling the relationship between *r* and *s*, thereby setting the shuffled *r* and *s* to be independent, and therefore removing any mutual information in the dataset.

As in the case of decoding models, encoding models can take many forms, from linear models with Gaussian noise to much more complex deep neural network (DNN) based models (Kriegeskorte, 2015). So called linearized encoding models first find a model of a feature space, based potentially on non-linear transformations of stimulus parameters, and then fit a linear combination of these features to the neural data (Naselaris, Kay, Nishimoto, & Gallant, 2011). And, as in the case of decoding models, measures of mutual information and specificity established with encoding models are merely lower bounds on the true measures. The higher the complexity of the model and the more data is available to fit the model, the closer the estimates of mutual information and specificity can be expected to be to the true measures. Comparisons of estimates of specificity, such as the claim that the specificity of *r* to *s* is larger than the specificity of *r* to *n*, are only as well supported as the assumption that one's encoding model captures all of the dependencies between *r* and *s* and between *r* and *n*.

The performance of an encoding model can be measured with all the measures that are also available for decoding models. A measure that is common particularly for encoding models is the proportion of variance explained, which is similar to specificity, except that the variability unexplained by *s* is measured with the variance of the residual of a model of *r* given *s* rather than the entropy:

specificity:  $\frac{I(s;r)}{H(r)} = \frac{H(r) - H(r|s)}{H(r)} = 1 - \frac{H(r|s)}{H(r)}$ 

proportion of variance explained:  $1 - \frac{var(r-m(r;s))}{var(r)}$ ,

where m(r,s) is a model that predicts *r* from *s*.

Variance is a computationally convenient measure of variability that can be estimated from small datasets more robustly than entropy, but it has limitations; it, for instance, is not sensitive to the shape of probability distributions, e.g. whether they are skewed or multi-modal.

#### 3.4. Representational geometry analysis

Representational geometry analysis seeks to build an understanding of low-dimensional geometric properties of high-dimensional neural population activities and their dependence on

stimulus features. Of these, representational similarity analysis (RSA) has proven to be a powerful and popular approach (Kriegeskorte, Mur, & Bandettini, 2008a).

In RSA, the geometry of the neural representations is captured by computing a representational dissimilarity matrix (RDM). The RDM is constructed by computing dissimilarity in population responses to distinct sets of stimuli. Specifically, given a set of *N* probing stimuli, an *N* x *N* dissimilarity matrix can be constructed, where each entry  $d_{ij}$  is calculated by computing the dissimilarity in the neural population response to stimuli  $s_i$  and  $s_j$  (Kriegeskorte et al., 2008a). The resultant RDM is symmetric along the main diagonal at which dissimilarities are zero because they indicate the dissimilarity of a neural response from itself (see Figure 3). RDMs depend heavily on the definition of the dissimilarity measure used to construct the matrix (Walther et al., 2016). The most commonly used dissimilarity measure is the correlation distance, defined as 1 minus the correlation between the two population responses, computed across neurons or voxels.

Typically, when computing the RDM, each stimulus is presented multiple times and the average population response to each stimulus is used to compute neural dissimilarity. This stimulus-conditioned averaging of the neural population response has the effect of averaging out the non-stimulus dependent variability in the neural population activity. As a result, RDMs tend to poorly reflect the specificity of the neural population response to the stimulus set, and more closely reflect its sensitivity.



**Figure 11. Example illustrating the interpretation of representational dissimilarity matrices (RDMs).** In this hypothetical example, thirty ripe apples and thirty apples that are not ripe were presented to a subject. Neural responses were recorded from different brain areas (A and B) and correlations of neural

responses were computed for all pairs of stimuli in order to construct RDMs. In A, we see the RDM for brain area A. There is no difference between dissimilarity for ripe and unripe apples; the neural response is not sensitive to the category distinction. In B, we see the RDM for brain area B. There is high dissimilarity across the category boundary of ripe vs. unripe; the neural response is sensitive to this distinction. Yet there is little dissimilarity between exemplars within categories; hence the neural response appears to be invariant to within category distinctions.

RDMs can be used to evaluate sensitivity and invariance. If the neural response carries no information about the stimulus—i.e. is independent of the stimulus—the dissimilarity of neural activity patterns will be the same, independently of the stimulus in response to which they were measured. The resultant RDM would be unstructured, and uniformly dominated by noise (see Figure 11A). Since such an unstructured RDM suggests zero mutual information between *r* and *s* it also suggests that sensitivity is zero. Conversely, if a neural population carries information about the stimuli, we would expect the RDM to display a structure reflecting the dissimilarity of stimuli. Often, stimuli are drawn from categories with multiple example stimuli present from each category. Dissimilarity of stimuli across category boundaries (e.g. houses vs. faces) indicates sensitivity to the category distinction. Low dissimilarity of stimuli within categories indicates invariance to within-category distinctions (e.g. variations of the orientation of a face) (see Figure 11B).

However, RDMs are often computed with relatively few stimuli that vary along many dimensions. When the number of stimuli is small compared to the number of dimensions of variation, one cannot tell which dimensions of variation account for the variation of neural responses. The interpretation of RDMs also depends on the dissimilarity measure. Analogous to what has been discussed in previous sections, the correlation distance, for instance, does not pick up on non-linear relationships between activation patterns; neither does it reflect differences in the average activity level between stimuli (Walther et al., 2016). The choice of dissimilarity measure is analogous to the choice of complexity of the model class in decoding or encoding analyses.

Perhaps the most powerful application of RSA lies in comparisons across systems, such as brains of different individuals, different brain areas, brains of different species (Kriegeskorte et al., 2008b), or even brains and artificial neural networks (Li et al., 2019; Yamins, Hong, Cadieu, & DiCarlo, 2013). Yet such comparisons are not primarily concerned with what evidence establishes that a feature is represented—which is the focus of this paper—but with studying how structures of representations compare across systems. Similarity of RDMs computed from neural responses and RDMs computed from behavioral responses can also provide evidence for the functionality of the neural response.

#### 3.5. Tests of statistical dependence

Some analyses do not estimate the amount of information a neural response carries about the stimulus and, therefore, do not offer degreed estimates of sensitivity, specificity, or invariance. Rather they test hypotheses about relations of statistical dependence between stimulus, neural

response, and behavior, which imply that respective desiderata have to be greater than zero. Initial work demonstrating that the fusiform face area (FFA) is sensitive to faces, for instance, showed that fMRI measurements of activity in FFA were significantly higher in conditions in which an image of a face was shown to a subject compared to conditions in which another object like a house was shown (Kanwisher et al., 1997). This establishes that FFA carries information about faces without quantifying how much information. Establishing that there is mutual information between *r* and *s* also establishes that *r* has larger than zero sensitivity and specificity; they showed that FFA activity was greater for intact faces than for images of scrambled face parts, indicating sensitivity and specificity conditional on low level visual features shared between intact and scrambled faces.

Invariance can be tested by determining whether other parameters have an effect on r. Pinel et al. (1999) for instance showed that inferior parietal activity depends on numerosity, but no dependence was found on whether numbers were written with a word or arabic numerals, suggesting invariance to the notation. However, since such interpretations rest on null findings, they are only suggestive. There are many reasons for why one might not find a significant dependence of r on n even though there is notable mutual information between these variables. Measurements of neural activity might be too coarse grained in spatial or temporal resolution, the dependence might be too complex to be picked up on by a test that relies on simplifying assumptions about the distributions of variables, or there may be other factors limiting the statistical power of a test. Functionality can be tested by determining whether a behavioral response b depends on r.

Many tests for relations of statistical dependence merely look for a dependence between stimulus or behavior and the mean neural response of an isolated element (e.g. an individual neuron or a voxel in a fMRI analysis) in a so-called univariate analysis. Such tests cannot pick up on distributed activity patterns that may carry information about stimulus or behavior. In order to pick up on such patterns, a multivariate pattern analysis (MVPA) in terms of correlation or more complex encoding or decoding models is needed (Haxby et al., 2001, 2014).

#### 3.6. Adaptation

A phenomenon that has received significant attention in research about representations is adaptation. Upon repeated presentation of a feature, the response magnitude of neurons (Baylis & Rolls, 1987; Sobotka & Ringo, 1994) or brain regions (Grill-Spector et al., 1999; Weigelt, Muckli, & Kohler, 2008) that are sensitive to the feature decreases. This adaptation is disrupted when a stimulus is presented that has a different feature. Hence, adaptation can be used to show which features of a stimulus a neural response r is sensitive to. When adaptation is disrupted by changes in a feature s, r is sensitive to s. When adaptation persists across changes of a feature n, r is invariant to n; as far as r is concerned, stimuli that differ in n are still equivalent.

To illustrate, fMRI activity in the lateral occipital complex (LOC) adapts to presentations of the same object (Grill-Spector et al., 1999). This adaptation was more strongly disrupted by

changes in illumination or viewpoint than by changes in position or size of the object. That is, LOC shows some invariance to the position or size of an object, but it is less invariant (i.e. more sensitive) to its illumination and viewpoint.

#### Box 2: Synopsis of the desiderata of evidence for representation in neuroscience.

Here we summarize our desiderata and typical tests for them.

**Sensitivity:** *r* carries information about *s*.  $\frac{I(s;r)}{H(s)}$ 

*Typical test:* Decode *s* from *r*. Sensitivity can be evaluated in terms of the decoder accuracy, decoder loss, correlation coefficient, mean squared error, etc.

**Specificity:** *s* explains a large proportion of the variability of *r*.  $\frac{I(s;r)}{H(r)}$ 

*Typical test:* Predict *r* from *s*. Specificity can be evaluated in terms of the loss of an encoding model, the proportion of variance of *r* explained by *s*, etc.

**Invariance:** *r*'s response to *s* is independent of *n*. 1  $-\frac{I(n;r|s)}{H(r|s)}$ 

Most straightforwardly, one can show that r is invariant to n by showing that r is not sensitive to n. Given that r is sensitive to n, one can demonstrate invariance by showing that, conditioned on s, r is independent of n. That is, r covaries with n only insofar as s covaries with n.

Conditional sensitivity: 
$$\frac{I(s;r|n)}{H(s|n)}$$
 Conditional specificity:  $\frac{I(s;r|n)}{H(r|n)}$ 

*Typical tests:* Decode *s* from *r*, or predict *r* from *s*, conditioned on *n*. In practice, sensitivity and specificity are always tested conditioned on the experimental conditions. If one wants to test them in the unconditional form, one has to reduce the dependence on confounding factors by varying experimental conditions and randomization.

Functionality: r is used as a representation of s.

Most research focuses on behavioral tests that show that r causes a behavioral response b that is sensitive to s.

*Typical interventionist test:* Show that r mediates the flow of information from s to b; e.g., by showing that inhibiting r breaks the dependence of b on s.

*Information-theoretic measures:* Functionality can also be tested in information-theoretic terms by showing that b is sensitive to r, that b is specific to r, that b is invariant to s, and that b is sensitive to r and specific to r, conditioned on s.

Of particular relevance are tests for functional conditional specificity. Showing that even conditioned on *s*, *r* explains a large proportion of the variability of *b*—e.g., because errors can be predicted from *r*—suggests that *b* receives its information about *s* from *r*.

## 4. Canonical examples

In our view, neuroscientific research about representations has always been guided implicitly by the desiderata summarized in Box 2. The framework we develop is not meant to be revolutionary. Rather, it is supposed to capture, in a systematic and unified way, what researchers have been doing all along. To see the framework employed in practice, we look at a few examples of lines of research about neural representations. These were chosen arbitrarily as examples that have received high attention from researchers and that have been involved in developing and shaping the tools and analyses with which representations in the brain are being studied. We show how these central case studies involve our desiderata.

#### 4.1. Orientation of visual elements

In their series of pioneering works, Hubel and Wiesel (1959, 1961, 1962, 1968) identified that the activities of cat and macaque V1 neurons are strongly modulated by the orientation of a moving edge as the edge slides in and out of the spatial receptive field of the neurons. By establishing that many V1 neurons have a preferential response to specific orientations, as commonly characterized by their orientation tuning curves, their work showed that V1 carries information about the stimulus orientation, thereby establishing sensitivity and specificity. Furthermore, their work established two distinct types of orientation-sensitive neurons in V1—simple cells and complex cells—by showing that the responses of complex cells demonstrated invariance to the spatial phase of an oriented stimulus within the cell's receptive field.

Orientation tuning curves—the average response of a neuron to each stimulus orientation-have been one of the earliest and most influential encoding models in which the variability of V1 neuron responses is explained in terms of the variability in the stimulus orientation (Sompolinsky & Shapley, 1997; Victor, Purpura, Katz, & Mao, 1994); the performance of such models has been evaluated based on the total variance explained, an approximate measure of specificity. Sensitivity of V1 has been characterized further with decoding models (both linear and nonlinear) in order to establish the decodability of stimulus orientation from the V1 population activity (Berens et al., 2012; Chen, Geisler, & Seidemann, 2006, 2008). By manipulating additional variables, such work has also shown that V1 exhibits conditional sensitivity and conditional specificity to orientation, as conditioned on contrast (Anderson, Lampl, Gillespie, & Ferster, 2000; Berens et al., 2012; Hansel & van Vreeswijk, 2002; Nowak & Barone, 2009), temporal frequency (Moore, Alitto, & Usrey, 2005), and spatial frequency (Jeon, Swain, Good, Chase, & Kuhlman, 2018). However, while V1 demonstrates a high degree of sensitivity, both conditioned and unconditioned, most V1 neurons exhibit low invariance to contrast, spatial frequency and temporal frequency. Hence in the face of variations in orientation along with other variables, V1 will typically exhibit low specificity to the stimulus orientation.

The functionality of V1 for orientation has been tested in the context of orientation discrimination tasks. When the animal is presented with ambiguous orientation stimuli, apparently random activity in V1 has been shown to be predictive of the animal's decision above chance—a phenomenon known as choice probability (Nienborg & Cumming, 2014). While this work does not clearly establish a causal connection, being able to predict behavior from the neural response at least establishes functional specificity. More recently, deep neural network models have been used to predict the animal's orientation-based decision from V1 activity even when conditioned on the stimulus, again helping to establish functional conditional specificity (Walker, Cotton, Ma, & Tolias, 2020).

#### 4.2. Numerosity

The numerosity of a collection of things is the number or cardinality of how many things there are in a collection. Lesion studies have long indicated that spatial computational resources in the parietal lobe of the brain are functional, i.e. play a causal role in the processing of numerosities; lesions of parietal areas lead to deficits in the processing of numerosities (Dehaene & Cohen, 1995); because these representations treat numerosity analogously to continuous magnitudes like size they have been termed analog representations of numerosity. Early fMRI work confirmed that parietal areas are activated during the processing of numerical tasks (Dehaene, Spelke, Pinel, Stanescu, & Tsivkin, 1999). However, these findings do not yet show that there are neural activity patterns that are sensitive to specific numerosities. Evidence for sensitivity of parietal areas was first provided by Pinel et al. (1999) who showed a difference in activity dependent on numerical distance in a number comparison task. Individual neurons correlated with numerosity were found in the monkey's parietal cortex (Sawamura, Shima, & Tanii, 2002). Prefrontal neurons were also shown to be tuned to numerosities (Nieder. Freedman, & Miller, 2002), indicating specificity. The first parietal neurons of which the activity is modulated by the numerosity of dot clouds in a perceptual context were reported by (Nieder & Miller, 2004). Many of these findings only indicate that neural responses carry information about numerosity and thereby do not clearly distinguish between sensitivity and specificity.

These studies also tested for invariance, for instance by showing that while neural responses are modulated by numerosity, low level visual features have no effect (Nieder et al., 2002; Nieder & Miller, 2004). The desideratum of invariance is especially central to the study of representations of numerosity because a number of other features co-vary necessarily with the numerosity of a stimulus. Consider two dot clouds that differ in numerosity; necessarily, the more numerous cloud either has to cover a larger surface area or has to have a higher density of dots (DeWind, Adams, Platt, & Brannon, 2015). Pinel et al. (1999) found that the brain areas sensitive to numerosity were invariant to whether numerosities were presented with number symbols or words spelling out numbers. Nieder (2012) showed that numerosity sensitive neurons are invariant to whether numerosities are presented with sequences of tones in the auditory domain or instantaneously with dot clouds in the visual domain.

However, other studies report a lack of invariance. Pinel, Piazza, Le Bihan, and Dehaene (2004) show that parietal neural responses are modulated by the numerosity, size, and luminosity of

the stimulus. Numerosity sensitive areas overlapped with size sensitive areas, but did not overlap with luminosity sensitive areas. These findings were mirrored by interference between behavioral responses to size and numerosity, but no behavioral interference between numerosity and luminosity, indicating that numerosity representations are invariant to luminosity, but not invariant to the size of a stimulus. In the monkey parietal cortex, both numerosity sensitive neurons of which the tuning is invariant to the length of a line and neurons that lack this invariance were found (Tudusciuc & Nieder, 2007), suggesting a distributed population code for a number of related quantities. Harvey, Klein, Petridou, and Dumoulin (2013) find, with fMRI, that parietal areas in humans are highly specific to numerosity—evaluated in terms of the variance explained by a Gaussian tuning model—but report limited invariance to some features, e.g. the circumference of a dot cloud.

More recent decoding models show that the whole dorsal visual stream up to the parietal cortex is sensitive to numerosity (Castaldi et al., 2019). Yet it can also be shown that the degree to which the neural code is mixed between quantities depends on the task context; during a numerosity related task—in contrast to a size related task—decoding accuracy for numerosity in the parietal cortex increases, indicating an increase in sensitivity, and the proportion of variance explained by numerosity increases as well, indicating an increase in specificity; these task related boosts to sensitivity and specificity were not found in early visual areas, increased throughout the dorsal stream, and were strongest in parietal areas (Castaldi et al., 2019).

Finally, during error trials, the decoding accuracy of numerosity is decreased compared to non-error trials (Tudusciuc & Nieder, 2007). This suggests that the error occurred because parietal activity did not carry information about numerosity in such trials. Yet a more straightforward test for functionality would not have been conditioned on the error but would have shown that behavioral errors can be predicted from the neural response. Evidence for functionality in causal terms is provided by intervention studies. The repetitive stimulation of parietal areas with TMS impairs the processing of numerosity (Dormal, Andres, & Pesenti, 2008). Pharmacological inactivation of numerosity sensitive neurons in the monkey's parietal cortex stops the monkey from behaviorally responding to numerosity (Sawamura, Shima, & Tanji, 2010).

#### 4.3. Faces

Kanwisher et al. (1997) was the first paper to identify and name the Fusiform Face Area (FFA) using fMRI. They discovered that FFA is significantly more active when subjects viewed images of faces compared to other objects. These results were in line with findings from lesion studies suggesting that this area is involved in recognizing faces, i.e. that it is functional. One problem with the contrastive analysis by Kanwisher et al. (1997) is that many features besides the presence of faces differ between images of faces and the control stimuli. As controls, Kanwisher et al. also tested whether FFA is more active in response to faces even when control stimuli have higher contrast, when contrast stimuli are drawn from the homogenous category of houses, when contrast stimuli are other body parts like hands, or scrambled arrangements of face parts. These tests are indicative for multiple desiderata. One can interpret them as tests of

conditional specificity; while holding fixed some other parameters—e.g. low level visual features of faces in the face vs. scrambled face contrast—one tests whether the presence of faces makes a significant difference for the neural responses. These tests are also interpreted as tests for sensitivity; FFA is taken to carry information about faces, but it is not taken to carry information about other features like luminosity. Saying that FFA is sensitive to faces and no other features is sometimes put by saying that FFA is face selective. Some tests are also indicative of invariance. Kanwisher et al., for instance, showed that FFA also responds to three-quarter views of faces, indicating invariance to viewing angle.

Previously, a posterior-temporal event related potential ca. 170 ms after stimulus onset (N170) was thought to signify face-selective responses (Bentin, Allison, Puce, Perez, & McCarthy, 1996; Jeffreys, 1996); but later findings alternatively suggested a more general role of the N170 in the processing of stimuli over which observers had discriminatory expertise (e.g. car identification in car experts) (Tanaka & Curran, 2001)—suggesting that the N170 might lack specificity to faces. The face selectivity of FFA responses was confirmed again by later studies (Halgren, 2000; Liu, Harris, & Kanwisher, 2002; Xu, Liu, & Kanwisher, 2005); the central findings are that faces but not other objects of expertise predict high neural responses as measured by MEG, indicating sensitivity and specificity to faces, and that the accuracy of behavioral responses to faces, but not behavioral responses to other objects predicts differences in the neural response, indicating functional sensitivity. A causal test of functionality is possible in patients with electrodes implanted in FFA; Parvizi et al. (2012) report that stimulations of FFA but not at other sites induced distortions to face percepts in one patient.

After identifying face-sensitive cortical patches with fMRI, electrophysiology in analogous face-selective neurons in macague monkeys offered further refinements to representational hypotheses, providing evidence for patches of cortex that are either sensitive to faces only conditioned on a specific head orientation, or are invariant to the orientation of the face (Freiwald & Tsao, 2010). Further research tried to identify which dimensions of variation in a parametrized space of face images accounts for responses in macaque face patches (Chang & Tsao, 2017); they found neurons that were tuned to low numbers of distinct dimensions. Sensitivity to dimensions of variation of faces was evaluated in terms of decoding accuracy and the proportion of variance of the facial features explained by a decoding model. However, the controversies about face selective responses versus responses involved in recognition of complex objects more generally reemerges for these more detailed analyses. Vinken, Prince, Konkle, and Livingstone (2023) report that the face selectivity of face patch neurons can be explained by tuning to non-face-specific latent features that units in deep neural networks trained for general object recognition learn to pick up on. They show that general object features explain a large proportion of the variance of neural responses, indicating specificity to these features.

#### 4.4. Spatial Location

Place cells are cells in the hippocampus (HC) that respond with increases in spiking activity when the animal is in a particular location in the environment. Place cells were discovered in

1971 when O'Keefe and Dostrovsky observed spiking of single HC neurons when the rat was placed in a particular location facing a particular direction (O'Keefe & Dostrovsky, 1971); these neurons were shown to be sensitive to the location and heading of the animal. Wilson and McNaughton (1993) showed that, across the whole HC population, the animal's position for all investigated locations can be inferred. Specificity was tested by rotating the platform to control for proximal olfactory or tactile cues, removing various sound sources like fans and polygraph machines, and changing the visual field's lighting or occlusion. These experiments revealed that a large proportion of the variability of place cells is driven by location and that the activity remains unchanged by variations in such contextual cues (Muller & Kubie, 1987; O'Keefe & Speakman, 1987).

Subsequent research has provided evidence for invariance to a range of environmental cues: place fields have asymmetric place preferences in an environment with a symmetric cue configuration (Sharp, Kubie, & Muller, 1990); place fields dynamically shift between reference frames, such as between a frame defined by a reward box that moved relative to the laboratory reference frame and the lab reference frame itself (Gothard, Skaggs, Moore, & McNaughton, 1996b; Gothard, Skaggs, & McNaughton, 1996a); the location and orientation of place fields follow rotated rats independently of the environment (Jeffery & O'Keefe, 1999); and the size of place fields is independent of local cue density, spatial frequency, or salience (Battaglia, Sutherland, & McNaughton, 2004).

O'Keefe & Dostrovsky (1971) also showed that the tuning of place cells for their preferred place persists conditioned on a variety of parameters, e.g. when lights were turned on or off or when their color changed, when olfactory and tactile cues were manipulated, when reorienting the rat (which left untouched the neural responses in about half of cells), when rotating the maze (which after a trial or two resulted in the cell responding to the original position, but after further rotations, the cell only responded to the location in the room, regardless of maze rotation), and finally when changing the experimenters location in the room. In these tests, the mutual information between neural response and location is evaluated conditional sensitivity and conditional specificity. However, place cells shut off completely when animals are restrained from locomotion (Foster, Castro, & McNaughton, 1989), suggesting that self-movement variables are important for coding of location.

Functionality has been extensively tested in the place cell system. For example, selective manipulation of place cells that code for starting places or rewarding places can induce behavior appropriate to the initiation of navigation or to reward gathering even when the animal is not at the corresponding locations (Robinson et al., 2020). In a clever manipulation, place cell activity during the animal's sleep was used as a trigger to stimulate the medial forebrain bundle, which codes a reward signal (De Lavilléon, Lacroix, Rondi-Reig, & Benchenane, 2015). Animals subsequently showed goal-directed behavior toward the corresponding location in the environment.

## 5. Extensions of the framework

The discussion so far has focused on the core case of what evidence supports claims of the form that some neural response represents some feature of the stimulus. In this section we consider some of the ways in which the framework can be applied beyond the contexts that have been discussed so far.

#### 5.1. Reducing *r* to its relevant aspect

We may wonder what *aspect* of a neural response represents a stimulus feature. A classic question is what *aspect* of spike trains carries information about the stimulus—only firing rate or also the timing of spikes (Bialek et al. 1991; London et al. 2010; Rieke et al. 1999). Let r be the spike train of some neuron that represents stimulus feature s. We denote by f a mapping that reduces r to its relevant *aspect*. According to the rate coding hypothesis, f maps r—which still contains information about the timing of spikes—to just a single scalar that corresponds to the neuron's firing rate. That is, f(r) disregards the timing of spikes. When considering population responses, often, the mapping f is a dimensionality reduction or a mapping from r to a subspace of r, that gives a reduced set of dimensions such that only variations of r along those dimensions carry information about s.

Finding dimensions of variation of *r* that represent stimulus features is constrained by what dimensions of variation of the stimulus we hypothesize to be represented. Often, our models of the mapping *f* and of dimensions of variation of the stimulus co-evolve. Consider the search for the neural code for faces; Chang & Tsao (2017) find that neurons in different parts of the macaque brain are sensitive and specific to small numbers of dimensions of variation either of the appearance or the shape of faces.

With the slight modification of substituting f(r) for r, the desiderata of evidence for representation also guide the search for the mapping f; that is, we try to find some mapping f such that f(r) is *sensitive* to *s*, *specific* to *s*, *invariant* to other parameters *n*, and *functional*. As an example, for the desideratum of specificity we get the following information-theoretic definition by substituting f(r) for *r*.

$$\frac{I(s;f(r))}{H(f(r))}$$

A central advantage we get out of this substitution is an increase in specificity: the specificity of f(r) to s will be greater than the specificity of r to s. This is because, usually, there will be much more variability in r than in f(r), i.e.  $H(r) \ge H(f(r))$ , and specificity is normalized by the entropy of r or f(r) respectively. f abstracts away from variability of r that is unrelated to s. As a result, s explains a larger proportion of the variability of f(r) than of r, we may even hope that most of the variability of f(r) can be explained by s. The specificity of r to s, on the other hand, cannot usually be expected to be too close to 1.

For similar reasons, f(r) should be more invariant than r to features other than s. Even when a population of neurons displays mixed selectivity and is sensitive to multiple features, as long as these features are separable in the activity patterns of r, f(r) can be perfectly invariant and specific to s by abstracting away from variability related to other features (DiCarlo & Cox, 2007).

Finally, in order to satisfy functionality, f(r) cannot merely be a simplifying description of r that accounts for all or most of the mutual information between s and r. In order to be functional, the mapping f has to capture which variations of r are used downstream in the brain, e.g. in the production of behavior.

#### 5.2. Reading the neural code

One shortcoming of information-theoretic analyses is that they only tell us *that* the response of a population of neurons carries information about the stimulus; knowledge that r carries information about s does not by itself tell us *how* to extract the information about s from r. In order to understand the latter, we need to be able to read the neural code, that is, we need to be able to tell what stimulus value is being represented by a particular neural activity pattern.

Reading the neural code involves finding a mapping *g* from neural responses to estimates of a stimulus feature. *g* may for instance map *r* to a point estimate of the represented feature, i.e.  $g(r) = \hat{s}$  (Bialek et al., 1991), or, in a probabilistic population code, *g* may map *r* to a probability distribution over possible values of the represented feature, i.e.  $g(r) = p(\hat{s}|r)$  (Jazayeri & Movshon, 2006; Ma, Beck, Latham, & Pouget, 2006). In light of the discussion of the previous section, we may decompose the mapping *g* into, first, a mapping *f* from *r* to its relevant aspect, and secondly, a mapping *g'* that assigns a stimulus estimate  $\hat{s}$  or  $p(\hat{s}|r)$  to f(r), i.e. g(r) = g'(f(r)). Here *g'* may be understood as an interpretation function, or a content assignment that assigns a content—an estimate of a stimulus feature—to f(r).

A model of the mapping *g* affords crucial tests of functionality. If, in a particular trial, the orientation of a stimulus is represented by *r* to be thirty degrees right of vertical, i.e.  $g(r_i) = 30^\circ$ , then we expect the subject to also report it to be thirty degrees right of vertical. On the other hand, when the subject makes an error and reports the orientation to be 25 degrees when, actually, it is 30 degrees right of vertical, we expect to be able to explain the error in this particular trial either in terms of a misrepresentation of the orientation, i.e.  $g(r_i) = 25^\circ$ , or in terms of some interference by a process downstream of the representation (see the discussion of multi-stage process models in the next subsection).

Short of building an exact model of the mapping g, we may constrain the class of models that are plausible. Constraints on biologically plausibility derive from anatomical and other biological considerations. Further constraints are derived from the successes and failures of encoding or decoding. For instance, when models are successful only with a certain kind of structure—e.g. multivariate linear models—then the neural code also has to have that kind of structure.

One salient family of constraints are constraints on the complexity of the neural code. It has for instance been suggested that representations—or at least explicit representations—have to be

linearly decodable (DiCarlo & Cox, 2007; Kriegeskorte & Diedrichsen, 2019). Such a constraint may be motivated by the observation that a linear code is easily readable by an individual neuron.

We are skeptical of a priori constraints on the complexity of the neural code. Simple neural codes like linear ones are useful because they are easily readable. So we may find that some features, especially features that are evolutionarily important to an organism, may be represented in terms of linear codes. However, the brain is a deep neural network and can approximate codes of arbitrary complexity. Populations of neurons can perform computations over features that are not linearly decodable; already individual neurons compute nonlinear functions of their inputs. Constraints on the complexity of neural codes have to be discovered empirically.

#### 5.3. Multi-stage process models

A representation is functional when it is used in downstream operations as a representation of the feature it represents. Most empirical tests of functionality focus on the role a representation plays in the production of behavioral responses to the feature. The discussion of functionality in section 2.2 is restricted to such behavioral tests of functionality. This restriction is useful because behavior is easily observable and behavioral tests are at least a good sufficient test; showing that a representation is used in the production of behavior is sufficient for showing that the representation is functional in some way.

However, representations may be used in many ways that are more or less closely or may even not at all be related to behavior. One may for instance see a flower and silently think to oneself that this flower is beautiful without behaviorally responding to the flower in any way. And even when a representation is used in the production of behavior, this involves many processing steps. Minimally, a representation of the stimulus has to be compared against a representation of the task demands in order to reach a decision. This decision has to be transformed into motor commands that control the behavioral response.

A full understanding of functionality in terms of multi-stage process models will require going beyond modeling how stimulus features cause a single neural response and how this neural response causes behavior. Multi-stage process models include transformations with which multiple distinct representations interact. As an example, Wilming, Murphy, Meyniel, and Donner (2020) studied how early visual, parietal, and motor areas interact in order to produce a behavioral response to stimulus contrast. They found evidence suggesting that early visual areas represent contrast of the current stimulus, parietal areas integrate information about contrast over sequences of stimuli, and motor areas reflect the choice made by the subject. However, they also showed how choice reflective motor activity feeds back into early visual areas where it seems to modulate how much early visual representations are integrated into the decision process.

#### 5.4. Models based on behavioral data

This paper focuses on neural evidence for representational claims. However, neural data is difficult to come by. Much research about representations in the brain proceeds on the basis of behavioral data. In some domains, where neural data is particularly difficult to collect, for instance in research about social cognition, which focuses on humans and other great apes, or developmental psychology, which focuses on human babies and children, most research is based on behavioral data alone. Models based on behavioral data are also common where complex functional roles of representations are being investigated, but neural data of the complex interactions of mental states is not available, e.g. in research about conceptual thought.

Historically, behavioral psychological research has preceded neural investigations of the representations of many features. Neuroscientists study which neural responses represent world features. However, what are the world features represented by the brain? Psychological work identifies such features—after which neuroscientific work may identify which populations of neurons represent the given features. Hering (1878) for instance developed a model of opponent processing of color in terms of blue-yellow, red-green, and black-white channels on the basis of similarity judgments between colors; many decades later, cells corresponding to these opponent processing channels were found in the thalamus (De Valois, Smith, Kitai, & Karoly, 1958) and retina (Hubel & Wiesel, 1960).

The desiderata of evidence for representation also guide models based on behavioral data. Such models aim to identify representations that are sensitive to a feature, they reveal interferences between representations, i.e. failures of invariance, and, inherently, they also show that a representation is functional by being used in the production of behavior. Only the desideratum of specificity is not straightforwardly applied in behavioral research, since behavioral data does not afford estimates of neural variability.

## 5.5. Quantitative comparisons of the desiderata

A typical finding is that some desideratum is satisfied in the case of some representation, e.g. that FFA is sensitive to facial features, or that it is functional. Yet our information-theoretic framework also lends itself to quantitative comparisons of the desiderata; that is, one can also establish claims of the form that  $r_1$  is twice as sensitive to *s* than  $r_2$ , or that *r*'s specificity to *s* is exactly the same conditioned on *n* and unconditioned.

Such comparative claims have become more common in more recent research. We have for instance discussed a study by Castaldi et al. (2019) in which it is shown that the specificity to numerosity increases from early to later areas in the dorsal visual stream and that late areas are more specific to numerosity in task contexts in which numerosity is relevant. However, such comparative claims are still not very common and in this paper, so far, we have not had a general discussion of such comparative claims. This is because much of such a discussion has

to happen on a case by case basis. Many quantitative estimates of the desiderata heavily depend on data recording techniques and analysis tools used; it is therefore difficult to compare them across studies. Yet, as larger datasets become more readily available, information-theoretic quantities can be estimated more robustly. Our quantification of the desiderata in information-theoretic terms allows to formulate and test more fine-grained hypotheses about representations and to compare them across studies. We hope that researchers will report more quantitative estimates of the desiderata. The more such estimates become available, the more it will be possible to integrate results across recording techniques and data analysis pipelines.

#### 5.6. Natural statistics

The mutual information between two variables is determined by their joint probability distribution. Thus mutual information is determined by the dependence between these variables, but also by the distributions of the variables in isolation. The desiderata of representation we discuss, therefore, also depend on the distributions of these variables.

As an example, consider how we might study the perception of three dimensional shapes. One process for computing shapes depends on the assumption that light comes from above, which allows the use of shadows and highlights as cues for three dimensional shape. If we were to study this process in an environment where light does not happen to come from above, a representation that, under normal conditions, is sensitive to three dimensional shape might fail to be sensitive in this abnormal environment. On the other hand, in the constrained environment of an experimental setup, there may be spurious correlations between features, suggesting statistical dependencies that do not hold in the natural environment.

A less extreme finding is that the processing of information in the brain is optimized for natural statistics. It was for instance shown that the specificity, i.e. efficiency of the neural code, of spike trains coding for auditory stimuli is greater for stimuli selected from natural ensembles than for unnatural stimuli (Rieke, Bodnar, & Bialek, 1995).

However, there are also benefits to choosing stimulus distributions that are deliberately unnatural; such distributions are helpful for teasing apart features that normally covary. Take the study of numerosity. In natural conditions, the numerosity of a collection of things covaries with many other features like the size of the space occupied by the collection. In order to determine whether a representation is of numerosity specifically, and whether it is invariant to other features like size, one needs an experimental setup in which these features vary independently of each other (Nieder et al., 2002). Such an experimental setup is often unnatural.

It therefore seems to be important to evaluate the desiderata under natural statistics in order to understand how information processing in the brain is optimized for the natural environment. However, it is not generally the case that the desiderata are more informative about representations when evaluated under natural statistics.

## 5.7. Extending the framework to other representations

In the discussion so far, the desiderata of sensitivity, specificity, and invariance are about what information a representation carries about the state of the world. Prototypical representations that carry such information are perceptual representations, which carry information about the current state of the world, memories, which carry information about a past state of the world, and predictions of future states. The desiderata discussed in this paper straightforwardly apply to representations of these kinds.

Yet not all representations carry information about the state of the world. For instance, representations of goals and desires, representations of motor commands, or representations in mental simulations, planning, mental imagery and hypothetical reasoning may only carry little or no information about what the world is like. In order to apply our framework to the study of such representations, the interpretation of the desiderata has to be amended.

One line of research concerns representations involved in planning, e.g. when anticipating and deciding on a travel route, a sequence of moves in a game, or the structure of a paper. In order to solve such tasks, an agent may mentally simulate possible states of the world. Johnson and Redish (2007), for instance, found activity of place cells that corresponded to a forward sweep along potential pathways for a rat at critical choice points; this activity could be involved in predicting which of multiple possible actions will have the most beneficial consequences. Kurth-Nelson, Economides, Dolan, and Dayan (2016) found MEG signals corresponding to sequences of states in a non-spatial planning task in humans. Representations in such mental simulations are not sensitive to the actual world, but sensitive to possible variations of the actual world and sensitive to the consequences actions would have in such possible worlds. Specificity and invariance, similarly, have to be reinterpreted to be about possible states of the world.

Elsewhere, we have discussed how our desiderata apply to the representation of uncertainty (Walker et al., 2023). This is an extension of the current framework because uncertainty is not a feature of the state of the world, but a feature of a belief or representation an observer has about the world. When applied to the study of uncertainty, sensitivity is evaluated by relating *r* to proxies of uncertainty derived from the stimulus alone, e.g. the ideal observer uncertainty that an observer would have were they to compute an optimal Bayesian inference. Conditional specificity is evaluated by testing whether *r* responds to proxies of uncertainty even while holding fixed some particular confounding variable of uncertainty like the contrast of the stimulus in a visual task. Invariance is evaluated, for instance, by testing whether uncertainty is represented for different perceptual features. Finally, functionality takes a center stage because of the observer-dependent nature of uncertainty. That an observer is uncertain about some feature manifests itself in them giving less weight to that representation and relying more on other sources of information in their responses.

We leave it to future work to determine more thoroughly whether and how our framework can be extended to apply to research about representations that do not paradigmatically fall under our framework.

## 6. Concluding remarks

We believe that there is implicit agreement in neuroscience on what evidence is needed in order to substantiate claims about representation. Our formal framework aims to make that agreement explicit. It does so by disambiguating and formalizing different ways that evidence can support the presence of representations that, previously, have not been teased apart systematically. There are many more analysis methods than could be considered in a single paper; how exactly those methods relate to our desiderata and how they should be applied to different cases of representations has to be discussed on a case by case basis. We propose that researchers investigating representations make explicit which of the desiderata they take to be supported by the evidence they provide—and to explain how the analysis methods they use support these desiderata. If they study a particular aspect of the neural response, they should make explicit the function f(r) they use. Using a common terminology in this way would facilitate communication across research groups, would make it easier to see how different research approaches combine, and would afford easier meta-analyses. Few studies provide evidence for all of the desiderata; strong evidence for representation emerges only out of a combination of studies. Following the framework we present here makes more salient which evidence is missing from a line of research; it also allows researchers to determine when strong evidence for a representation has emerged in a field.

As measurement techniques develop, datasets get larger, and analysis methods get more complex, information-theoretic quantities can be estimated more robustly. As we explain in sections 3.2 and 3.3 on decoding and encoding models, deep neural networks are a particularly useful tool for estimating conditional entropies and the desiderata that derive from these. Quantifying the desiderata allows for richer comparisons of different types of evidence.

How does our framework relate to philosophical discussions of representation? The framework is intended to systematize how representations are studied in neuroscience. It is not designed to address philosophical questions about what a representation is. But, of course, how representations are studied is very relevant for what we think representations are. It will therefore be relevant to consider how philosophical accounts of representations interface with our framework for evidence for representation in neuroscience.

Finally, interest has recently arisen in explaining artificial neural networks in representational terms. Neuroscience benefits from developments in artificial intelligence research because that research provides new analysis and modeling tools for neuroscience. On the other hand, analysis tools for understanding artificial neural networks are being compared to neuroscientific methodology (Ivanova, Hewitt, & Zaslavsky, 2021; Lindsay & Bau, 2023). Our framework is a natural starting point for such a discussion because it encapsulates the methodology that has

developed over more than hundred years in neuroscience and the information-theoretic formalism lends itself naturally to an application to artificial neural networks.

### 7. Funding Statement

None.

### 8. Conflict of Interest Statement

Competing interests: The authors declare none.

### 9. References

- Abbott, L. F., Rolls, E. T., & Tovee, M. J. (1996). Representational Capacity of Face Coding in Monkeys. *Cerebral Cortex*, 6(3), 498–505. doi:10.1093/cercor/6.3.498
- Aljadeff, J., Lansdell, B. J., Fairhall, A. L., & Kleinfeld, D. (2016). Analysis of Neuronal Spike Trains, Deconstructed. *Neuron*, *91*(2), 221–259. doi:10.1016/j.neuron.2016.05.039
- Anderson, J. S., Lampl, I., Gillespie, D. C., & Ferster, D. (2000). The Contribution of Noise to Contrast Invariance of Orientation Tuning in Cat Visual Cortex. *Science*, 290, 1968–1972. doi:10.1126/science.290.5498.1968
- Baker, B., Lansdell, B., & Kording, K. P. (2022). Three aspects of representation in neuroscience. *Trends in Cognitive Sciences*, *26*(11), 942–958. doi:10.1016/j.tics.2022.08.014
- Barack, D. L., & Krakauer, J. W. (2021). Two views on the cognitive brain. *Nature Reviews Neuroscience*, 22(6), 359–371. doi:10.1038/s41583-021-00448-6
- Battaglia, F. P., Sutherland, G. R., & McNaughton, B. L. (2004). Local Sensory Cues and Place Cell Directionality: Additional Evidence of Prospective Coding in the Hippocampus. *The Journal of Neuroscience*, *24*(19), 4541–4550. doi:10.1523/JNEUROSCI.4896-03.2004
- Baylis, G. C., & Rolls, E. T. (1987). Responses of neurons in the inferior temporal cortex in short term and serial recognition memory tasks. *Experimental Brain Research*, 65(3), 614–622. doi:10.1007/BF00235984
- Bentin, S., Allison, T., Puce, A., Perez, E., & McCarthy, G. (1996). Electrophysiological Studies of Face Perception in Humans. *Journal of Cognitive Neuroscience*, 8(6), 551–565. doi:10.1162/jocn.1996.8.6.551

Berens, P., Ecker, A. S., Cotton, R. J., Ma, W. J., Bethge, M., & Tolias, A. S. (2012). A Fast and

Simple Population Code for Orientation in Primate V1. *Journal of Neuroscience*, *32*(31), 10618–10626. doi:10.1523/JNEUROSCI.1335-12.2012

- Bialek, W., DeWeese, M., Rieke, F., & Warland, D. (1993). Bits and brains: Information flow in the nervous system. *Physica A: Statistical Mechanics and Its Applications*, 200(1–4), 581–593. doi:10.1016/0378-4371(93)90563-J
- Bialek, W., Rieke, F., de Ruyter van Steveninck, R., & Warland, D. (1991). Reading a neural code. Science, 252(5014), 1854–1857. doi:10.1126/science.2063199
- Bradley, D. C., Chang, G. C., & Andersen, R. A. (1998). Encoding of three-dimensional structure-from-motion by primate area MT neurons. *Nature*, 392(6677), 714–717. doi:10.1038/33688
- Brette, R. (2019). Is coding a relevant metaphor for the brain? *Behavioral and Brain Sciences*, 42, e215. doi:10.1017/S0140525X19000049
- Britten, K. H., Newsome, W. T., Shadlen, M. N., Celebrini, S., & Movshon, J. A. (1996). A relationship between behavioral choice and the visual responses of neurons in macaque MT. *Visual Neuroscience*, *13*(1), 87–100. doi:10.1017/S095252380000715X
- Castaldi, E., Piazza, M., Dehaene, S., Vignaud, A., & Eger, E. (2019). Attentional amplification of neural codes for number independent of other quantities along the dorsal visual stream. *eLife*, *8*, e45160. doi:10.7554/eLife.45160
- Chang, L., & Tsao, D. Y. (2017). The Code for Facial Identity in the Primate Brain. *Cell*, *169*(6), 1013-1028.e14. doi:10.1016/j.cell.2017.05.011
- Chen, Y., Geisler, W. S., & Seidemann, E. (2006). Optimal decoding of correlated neural population responses in the primate visual cortex. *Nature Neuroscience*, 9(11), 1412–1420. doi:10.1038/nn1792
- Chen, Y., Geisler, W. S., & Seidemann, E. (2008). Optimal Temporal Decoding of Neural Population Responses in a Reaction-Time Visual Detection Task. *Journal of Neurophysiology*, 99(3), 1366–1379. doi:10.1152/jn.00698.2007
- Cortes, C., & Vapnik, V. (1995). Support-vector networks. *Machine Learning*, *20*(3), 273–297. doi:10.1007/BF00994018
- Cover, T. M., & Thomas, J. A. (2006). *Elements of Information Theory*. John Wiley & Sons.
- De Lavilléon, G., Lacroix, M. M., Rondi-Reig, L., & Benchenane, K. (2015). Explicit memory creation during sleep demonstrates a causal role of place cells in navigation. *Nature Neuroscience*, *18*(4), 493–495. doi:10.1038/nn.3970
- De Valois, R. L., Smith, C. J., Kitai, S. T., & Karoly, A. J. (1958). Response of Single Cells in Monkey Lateral Geniculate Nucleus to Monochromatic Light. *Science*, *127*(3292),

238–239. doi:10.1126/science.127.3292.238

- deCharms, R. C., & Zador, A. (2000). Neural Representation and the Cortical Code. *Annual Review of Neuroscience*, *23*(1), 613–647. doi:10.1146/annurev.neuro.23.1.613
- Dehaene, S., & Cohen, L. (1995). Towards an Anatomical and Functional Model of Number Processing. *Mathematical Cognition*, *1*, 83–120.
- Dehaene, S., Spelke, E., Pinel, P., Stanescu, R., & Tsivkin, S. (1999). Sources of Mathematical Thinking: Behavioral and Brain-Imaging Evidence. *Science*, *284*(5416), 970–974. doi:10.1126/science.284.5416.970
- DeWind, N. K., Adams, G. K., Platt, M. L., & Brannon, E. M. (2015). Modeling the approximate number system to quantify the contribution of visual stimulus features. *Cognition*, *142*, 247–265. doi:10.1016/j.cognition.2015.05.016
- DiCarlo, J. J., & Cox, D. D. (2007). Untangling invariant object recognition. *Trends in Cognitive Sciences*, *11*(8), 333–341. doi:10.1016/j.tics.2007.06.010
- Dormal, V., Andres, M., & Pesenti, M. (2008). Dissociation of numerosity and duration processing in the left intraparietal sulcus: A transcranial magnetic stimulation study. *Cortex*, *44*(4), 462–469. doi:10.1016/j.cortex.2007.08.011
- Dretske, F. (1981). Knowledge and the flow of information. The MIT Press.
- Dumoulin, S. O., & Wandell, B. A. (2008). Population receptive field estimates in human visual cortex. *NeuroImage*, *39*(2), 647–660. doi:10.1016/j.neuroimage.2007.09.034
- Faisal, A. A., Selen, L. P. J., & Wolpert, D. M. (2008). Noise in the nervous system. *Nature Reviews Neuroscience*, *9*(4), 292–303. doi:10.1038/nrn2258
- Favela, L. H., & Machery, E. (2023). Investigating the concept of representation in the neural and psychological sciences. *Frontiers in Psychology*, *14*, 1165622. doi:10.3389/fpsyg.2023.1165622
- Foster, T. . C., Castro, C. A., & McNaughton, B. L. (1989). Spatial Selectivity of Rat Hippocampal Neurons: Dependence on Preparedness for Movement. *Science*, 244(4912), 1580–1582. doi:10.1126/science.2740902
- Freiwald, W. A., & Tsao, D. Y. (2010). Functional Compartmentalization and Viewpoint Generalization Within the Macaque Face-Processing System. *Science*, *330*(6005), 845–851. doi:10.1126/science.1194908
- Friston, K. J., Holmes, A. P., Poline, J.-B., Grasby, P. J., Williams, S. C. R., Frackowiak, R. S. J.,
  & Turner, R. (1995). Analysis of fMRI Time-Series Revisited. *NeuroImage*, 2(1), 45–53.
  doi:10.1006/nimg.1995.1007

Friston, K. J., Jezzard, P., & Turner, R. (1994). Analysis of functional MRI time-series. Human

Brain Mapping, 1(2), 153–171. doi:10.1002/hbm.460010207

- Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: high dimensionality for higher cognition. *Current Opinion in Neurobiology*, 37, 66–74. doi:10.1016/j.conb.2016.01.010
- Gothard, K. M., Skaggs, W. E., & McNaughton, B. L. (1996a). Dynamics of Mismatch Correction in the Hippocampal Ensemble Code for Space: Interaction between Path Integration and Environmental Cues. *The Journal of Neuroscience*, *16*(24), 8027–8040. doi:10.1523/JNEUROSCI.16-24-08027.1996
- Gothard, K., Skaggs, W., Moore, K., & McNaughton, B. (1996b). Binding of hippocampal CA1 neural activity to multiple reference frames in a landmark-based navigation task. *The Journal of Neuroscience*, *16*(2), 823–835. doi:10.1523/JNEUROSCI.16-02-00823.1996
- Graf, A. B. A., Kohn, A., Jazayeri, M., & Movshon, J. A. (2011). Decoding the activity of neuronal populations in macaque primary visual cortex. *Nature Neuroscience*, *14*(2), 239–245. doi:10.1038/nn.2733
- Grill-Spector, K., Kushnir, T., Edelman, S., Avidan, G., Itzchak, Y., & Malach, R. (1999).
  Differential Processing of Objects under Various Viewing Conditions in the Human Lateral Occipital Complex. *Neuron*, *24*(1), 187–203. doi:10.1016/S0896-6273(00)80832-6
- Halgren, E. (2000). Cognitive Response Profile of the Human Fusiform Face Area as Determined by MEG. *Cerebral Cortex*, *10*(1), 69–81. doi:10.1093/cercor/10.1.69
- Hansel, D., & van Vreeswijk, C. (2002). How Noise Contributes to Contrast Invariance of
  Orientation Tuning in Cat Visual Cortex. *The Journal of Neuroscience*, *22*, 5118–5128.
  doi:10.1523/JNEUROSCI.22-12-05118.2002
- Harvey, B. M., Klein, B. P., Petridou, N., & Dumoulin, S. O. (2013). Topographic Representation of Numerosity in the Human Parietal Cortex. *Science*, *341*(6150), 1123–1126. doi:10.1126/science.1239052
- Hassabis, D., Chu, C., Rees, G., Weiskopf, N., Molyneux, P. D., & Maguire, E. A. (2009).
  Decoding Neuronal Ensembles in the Human Hippocampus. *Current Biology*, *19*, 546–554. doi:10.1016/j.cub.2009.02.033
- Haxby, J. V., Connolly, A. C., & Guntupalli, J. S. (2014). Decoding Neural Representational Spaces Using Multivariate Pattern Analysis. *Annual Review of Neuroscience*, 37(1), 435–456. doi:10.1146/annurev-neuro-062012-170325
- Haxby, J. V., Gobbini, M. I., Furey, M. L., Ishai, A., Schouten, J. L., & Pietrini, P. (2001).
  Distributed and Overlapping Representations of Faces and Objects in Ventral Temporal Cortex. *Science*, *293*(5539), 2425–2430. doi:10.1126/science.1063736

- Hering, E. (1878). Zur Lehre vom Lichtsinne: Sechs Mittheilungen an die Kaiserl. Akademie der Wissenschaften in Wien. Carl Gerold's Sohn.
- Hubel, D. H., & Wiesel, T. N. (1959). Receptive fields of single neurones in the cat's striate cortex. *The Journal of Physiology*, *148*(3), 574–591. doi:10.1113/jphysiol.1959.sp006308
- Hubel, D. H., & Wiesel, T. N. (1960). Receptive fields of optic nerve fibres in the spider monkey. *The Journal of Physiology*, *154*(3), 572–580. doi:10.1113/jphysiol.1960.sp006596
- Hubel, D. H., & Wiesel, T. N. (1961). Integrative action in the cat's lateral geniculate body. *The Journal of Physiology*, *155*(2), 385–398. doi:10.1113/jphysiol.1961.sp006635
- Hubel, D. H., & Wiesel, T. N. (1962). Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *The Journal of Physiology*, *160*(1), 106–154. doi:10.1113/jphysiol.1962.sp006837
- Hubel, D. H., & Wiesel, T. N. (1968). Receptive fields and functional architecture of monkey striate cortex. *The Journal of Physiology*, *195*(1), 215–243. doi:10.1113/jphysiol.1968.sp008455
- Hung, C. P., Kreiman, G., Poggio, T., & DiCarlo, J. J. (2005). Fast Readout of Object Identity from Macaque Inferior Temporal Cortex. *Science*, *310*(5749), 863–866. doi:10.1126/science.1117593
- Ivanova, A. A., Hewitt, J., & Zaslavsky, N. (2021). *Probing artificial neural networks: insights from neuroscience* (arXiv:2104.08197). doi:10.48550/arXiv.2104.08197
- Jazayeri, M., & Movshon, J. A. (2006). Optimal representation of sensory information by neural populations. *Nature Neuroscience*, *9*(5), 690–696. doi:10.1038/nn1691
- Jeffery, K. J., & O'Keefe, J. M. (1999). Learned interaction of visual and idiothetic cues in the control of place field orientation. *Experimental Brain Research*, 127(2), 151–161. doi:10.1007/s002210050785
- Jeffreys, D. A. (1996). Evoked Potential Studies of Face and Object Processing. *Visual Cognition*, *3*(1), 1–38. doi:10.1080/713756729
- Jeon, B. B., Swain, A. D., Good, J. T., Chase, S. M., & Kuhlman, S. J. (2018). Feature selectivity is stable in primary visual cortex across a range of spatial frequencies. *Scientific Reports*, *8*, 15288. doi:10.1038/s41598-018-33633-2
- Johnson, A., & Redish, A. D. (2007). Neural Ensembles in CA3 Transiently Encode Paths Forward of the Animal at a Decision Point. *The Journal of Neuroscience*, *27*(45), 12176–12189. doi:10.1523/JNEUROSCI.3761-07.2007
- Jones, I. S., & Kording, K. P. (2019). Quantifying the role of neurons for behavior is a mediation question. *Behavioral and Brain Sciences*, *42*, e233. doi:10.1017/S0140525X19001444

- Kanwisher, N., McDermott, J., & Chun, M. M. (1997). The Fusiform Face Area: A Module in Human Extrastriate Cortex Specialized for Face Perception. *The Journal of Neuroscience*, *17*(11), 4302–4311. doi:10.1523/JNEUROSCI.17-11-04302.1997
- Kragel, P. A., Koban, L., Barrett, L. F., & Wager, T. D. (2018). Representation, Pattern Information, and Brain Signatures: From Neurons to Neuroimaging. *Neuron*, 99(2), 257–273. doi:10.1016/j.neuron.2018.06.009
- Kriegeskorte, N. (2015). Deep Neural Networks: A New Framework for Modeling Biological Vision and Brain Information Processing. *Annual Review of Vision Science*, 1(1), 417–446. doi:10.1146/annurev-vision-082114-035447
- Kriegeskorte, N., & Diedrichsen, J. (2019). Peeling the Onion of Brain Representations. *Annual Review of Neuroscience*, *42*(1), 407–432. doi:10.1146/annurev-neuro-080317-061906
- Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008a). Representational similarity analysis connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2(4). doi:10.3389/neuro.06.004.2008
- Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., Tanaka, K., & Bandettini, P. A. (2008b). Matching Categorical Object Representations in Inferior Temporal Cortex of Man and Monkey. *Neuron*, *60*(6), 1126–1141. doi:10.1016/j.neuron.2008.10.043
- Kurth-Nelson, Z., Economides, M., Dolan, R. J., & Dayan, P. (2016). Fast Sequences of Non-spatial State Representations in Humans. *Neuron*, *91*(1), 194–204. doi:10.1016/j.neuron.2016.05.028
- Laughlin, S. (2001). Energy as a constraint on the coding and processing of sensory information. *Current Opinion in Neurobiology*, *11*(4), 475–480. doi:10.1016/S0959-4388(00)00237-3
- Li, Z., Brendel, W., Walker, E., Cobos, E., Muhammad, T., Reimer, J., Bethge, M., Sinz, F., Pitkow, Z., & Tolias, A. (2019). Learning from brains how to regularize machines. *Advances in Neural Information Processing Systems*, *32*. Retrieved from https://proceedings.neurips.cc/paper\_files/paper/2019/file/70117ee3c0b15a2950f1e82a2 15e812b-Paper.pdf
- Lindsay, G. W., & Bau, D. (2023). Testing methods of neural systems understanding. *Cognitive Systems Research*, *82*, 101156. doi:10.1016/j.cogsys.2023.101156
- Liu, J., Harris, A., & Kanwisher, N. (2002). Stages of processing in face perception: an MEG study. *Nature Neuroscience*, *5*(9), 910–916. doi:10.1038/nn909
- Livezey, J. A., & Glaser, J. I. (2021). Deep learning approaches for neural decoding across

architectures and recording modalities. *Briefings in Bioinformatics*, *22*(2), 1577–1591. doi:10.1093/bib/bbaa355

- Logothetis, N. K., Pauls, J., & Poggio, T. (1995). Shape representation in the inferior temporal cortex of monkeys. *Current Biology*, *5*(5), 552–563. doi:10.1016/S0960-9822(95)00108-4
- Ma, W. J., Beck, J. M., Latham, P. E., & Pouget, A. (2006). Bayesian inference with probabilistic population codes. *Nature Neuroscience*, *9*(11), 1432–1438. doi:10.1038/nn1790
- Marr, D. (1982). Vision: a computational investigation into the human representation and processing of visual information. MIT Press.
- Miller, L. M., & Recanzone, G. H. (2009). Populations of auditory cortical neurons can accurately encode acoustic space across stimulus intensity. *Proceedings of the National Academy* of Sciences, 106(14), 5931–5935. doi:10.1073/pnas.0901023106
- Moore, B. D., Alitto, H. J., & Usrey, W. M. (2005). Orientation Tuning, But Not Direction Selectivity, Is Invariant to Temporal Frequency in Primary Visual Cortex. *Journal of Neurophysiology*, 94(2), 1336–1345. doi:10.1152/jn.01224.2004
- Muller, R., & Kubie, J. (1987). The effects of changes in the environment on the spatial firing of hippocampal complex-spike cells. *The Journal of Neuroscience*, 7(7), 1951–1968. doi:10.1523/JNEUROSCI.07-07-01951.1987
- Naselaris, T., Kay, K. N., Nishimoto, S., & Gallant, J. L. (2011). Encoding and decoding in fMRI. *NeuroImage*, *56*(2), 400–410. doi:10.1016/j.neuroimage.2010.07.073
- Nieder, A. (2012). Supramodal numerosity selectivity of neurons in primate prefrontal and posterior parietal cortices. *Proceedings of the National Academy of Sciences*, *109*(29), 11860–11865. doi:10.1073/pnas.1204580109
- Nieder, A., Freedman, D., & Miller, E. K. (2002). Representation of the Quantity of Visual Items in the Primate Prefrontal Cortex. *Science*, *297*(5587), 1708–1711. doi:10.1126/science.1072493
- Nieder, A., & Miller, E. K. (2004). A parieto-frontal network for visual numerical information in the monkey. *Proceedings of the National Academy of Sciences*, *101*(19), 7457–7462. doi:10.1073/pnas.0402239101
- Nienborg, H., & Cumming, B. G. (2014). Decision-Related Activity in Sensory Neurons May Depend on the Columnar Architecture of Cerebral Cortex. *The Journal of Neuroscience*, 34(10), 3579–3585. doi:10.1523/JNEUROSCI.2340-13.2014
- Nowak, L. G., & Barone, P. (2009). Contrast Adaptation Contributes to Contrast-Invariance of Orientation Tuning of Primate V1 Cells. *PLoS ONE*, *4*(3), e4781.

doi:10.1371/journal.pone.0004781

- O'Keefe, J., & Dostrovsky, J. (1971). The hippocampus as a spatial map. Preliminary evidence from unit activity in the freely-moving rat. *Brain Research*, *34*(1), 171–175. doi:10.1016/0006-8993(71)90358-1
- O'Keefe, J., & Speakman, A. (1987). Single unit activity in the rat hippocampus during a spatial memory task. *Experimental Brain Research*, 68, 1–27. doi:10.1007/BF00255230
- Paninski, L., Pillow, J., & Lewi, J. (2007). Statistical models for neural encoding, decoding, and optimal stimulus design. In *Progress in Brain Research* (Vol. 165, pp. 493–507). Elsevier. doi:10.1016/S0079-6123(06)65031-0
- Parvizi, J., Jacques, C., Foster, B. L., Withoft, N., Rangarajan, V., Weiner, K. S., & Grill-Spector, K. (2012). Electrical Stimulation of Human Fusiform Face-Selective Regions Distorts
  Face Perception. *The Journal of Neuroscience*, *32*(43), 14915–14920.
  doi:10.1523/JNEUROSCI.2609-12.2012
- Pasupathy, A., & Connor, C. E. (2002). Population coding of shape in area V4. *Nature Neuroscience*, *5*(12), 1332–1338. doi:10.1038/972
- Pearl, J. (2009). Causality: models, reasoning, and inference. Cambridge University Press.
- Perkel, D. H., & Bullock, T. H. (1968). Neural Coding. *Neuroscience Research Program Bulletin*, 6(3), 221–348.
- Pinel, P., Le Clec'H, G., van de Moortele, P.-F., Naccache, L., Le Bihan, D., & Dehaene, S. (1999). Event-related fMRI analysis of the cerebral circuit for number comparison: *NeuroReport*, *10*(7), 1473–1479. doi:10.1097/00001756-199905140-00015
- Pinel, P., Piazza, M., Le Bihan, D., & Dehaene, S. (2004). Distributed and Overlapping Cerebral Representations of Number, Size, and Luminance during Comparative Judgments. *Neuron*, *41*(6), 983–993. doi:10.1016/S0896-6273(04)00107-2
- Poldrack, R. (2006). Can cognitive processes be inferred from neuroimaging data? *Trends in Cognitive Sciences*, *10*(2), 59–63. doi:10.1016/j.tics.2005.12.004
- Poldrack, R. A. (2011). Inferring Mental States from Neuroimaging Data: From Reverse Inference to Large-Scale Decoding. *Neuron*, 72(5), 692–697. doi:10.1016/j.neuron.2011.11.001
- Quiroga, R. Q., & Panzeri, S. (2009). Extracting information from neuronal populations: information theory and decoding approaches. *Nature Reviews Neuroscience*, *10*(3), 173–185. doi:10.1038/nrn2578
- Quiroga, R. Q., Reddy, L., Kreiman, G., Koch, C., & Fried, I. (2005). Invariant visual representation by single neurons in the human brain. *Nature*, *435*(7045), 1102–1107.

doi:10.1038/nature03687

- Reshef, D. N., Reshef, Y. A., Finucane, H. K., Grossman, S. R., McVean, G., Turnbaugh, P. J., Lander, E. S., Mitzenmacher, M., & Sabeti, P. C. (2011). Detecting Novel Associations in Large Data Sets. *Science*, *334*(6062), 1518–1524. doi:10.1126/science.1205438
- Rieke, F., Bodnar, D. A., & Bialek, W. (1995). Naturalistic stimuli increase the rate and efficiency of information transmission by primary auditory afferents. *Proceedings of the Royal Society of London. Series B: Biological Sciences*, 262(1365), 259–265. doi:10.1098/rspb.1995.0204
- Rieke, F., Warland, D., & Bialek, W. (1993). Coding Efficiency and Information Rates in Sensory Neurons. *Europhysics Letters (EPL)*, *22*(2), 151–156. doi:10.1209/0295-5075/22/2/013
- Rigotti, M., Barak, O., Warden, M. R., Wang, X.-J., Daw, N. D., Miller, E. K., & Fusi, S. (2013). The importance of mixed selectivity in complex cognitive tasks. *Nature*, *497*(7451), 585–590. doi:10.1038/nature12160
- Ritchie, J. B., Kaplan, D. M., & Klein, C. (2019). Decoding the Brain: Neural Representation and the Limits of Multivariate Pattern Analysis in Cognitive Neuroscience. *The British Journal for the Philosophy of Science*, *70*(2), 581–607. doi:10.1093/bjps/axx023
- Robinson, N. T. M., Descamps, L. A. L., Russell, L. E., Buchholz, M. O., Bicknell, B. A., Antonov, G. K., Lau, J. Y. N., Nutbrown, R., Schmidt-Hieber, C., & Häusser, M. (2020). Targeted Activation of Hippocampal Place Cells Drives Memory-Guided Spatial Behavior. *Cell*, *183*(6), 1586-1599.e10. doi:10.1016/j.cell.2020.09.061
- Salzman, C. D., Britten, K. H., & Newsome, W. T. (1990). Cortical microstimulation influences perceptual judgements of motion direction. *Nature*, *346*(6280), 174–177. doi:10.1038/346174a0
- Sawamura, H., Shima, K., & Tanji, J. (2002). Numerical representation for action in the parietal cortex of the monkey. *Nature*, *415*(6874), 918–922. doi:10.1038/415918a
- Sawamura, H., Shima, K., & Tanji, J. (2010). Deficits in Action Selection Based on Numerical Information After Inactivation of the Posterior Parietal Cortex in Monkeys. *J Neurophysiol*, *104*, 902–910. doi:10.1152/jn.01014.2009
- Shadlen, M. N., & Newsome, W. T. (1994). Noise, neural codes and cortical organization. *Current Opinion in Neurobiology*, *4*(4), 569–579. doi:10.1016/0959-4388(94)90059-0
- Shannon, C. (1948). A Mathematical Theory of Communication. *The Bell System Technical Journal*, *27*(3), 379–423. doi:10.1002/j.1538-7305.1948.tb01338.x
- Sharp, P., Kubie, J., & Muller, R. (1990). Firing properties of hippocampal neurons in a visually symmetrical environment: contributions of multiple sensory cues and mnemonic

processes. *The Journal of Neuroscience*, *10*(9), 3093–3105. doi:10.1523/JNEUROSCI.10-09-03093.1990

- Sobotka, S., & Ringo, J. L. (1994). Stimulus specific adaptation in excited but not in inhibited cells in inferotemporal cortex of Macaque. *Brain Research*, *646*(1), 95–99. doi:10.1016/0006-8993(94)90061-2
- Sompolinsky, H., & Shapley, R. (1997). New perspectives on the mechanisms for orientation selectivity. *Current Opinion in Neurobiology*, 7, 514–522. doi:10.1016/S0959-4388(97)80031-1
- Tanaka, J. W., & Curran, T. (2001). A Neural Basis for Expert Object Recognition. *Psychological Science*, *12*(1), 43–47. doi:10.1111/1467-9280.00308
- Tudusciuc, O., & Nieder, A. (2007). Neuronal population coding of continuous and discrete quantity in the primate posterior parietal cortex. *Proceedings of the National Academy of Sciences*, *104*(36), 14513–14518. doi:10.1073/pnas.0705495104
- Usher, M. (2001). A Statistical Referential Theory of Content: Using Information Theory to Account for Misrepresentation. *Mind and Language*, *16*(3), 311–334. doi:10.1111/1468-0017.00172
- Victor, J. D., Purpura, K., Katz, E., & Mao, B. (1994). Population encoding of spatial frequency, orientation, and color in macaque V1. *Journal of Neurophysiology*, 72(5), 2151–2166. doi:10.1152/jn.1994.72.5.2151
- Vinken, K., Prince, J. S., Konkle, T., & Livingstone, M. S. (2023). The neural code for "face cells" is not face-specific. *Science Advances*, 9, eadg1736. doi:10.1126/sciadv.adg1736
- Walker, E. Y., Cotton, R. J., Ma, W. J., & Tolias, A. S. (2020). A neural basis of probabilistic computation in visual cortex. *Nature Neuroscience*, 23(1), 122–129. doi:10.1038/s41593-019-0554-5
- Walker, E. Y., Pohl, S., Denison, R. N., Barack, D. L., Lee, J., Block, N., Ma, W. J., & Meyniel, F. (2023). Studying the neural representations of uncertainty. *Nature Neuroscience*, 26, 1857–1867. doi:10.1038/s41593-023-01444-y
- Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016). Reliability of dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*, *137*, 188–200. doi:10.1016/j.neuroimage.2015.12.012
- Weigelt, S., Muckli, L., & Kohler, A. (2008). Functional Magnetic Resonance Adaptation in Visual Neuroscience. *Reviews in the Neurosciences*, 19(4–5), 363–380. doi:10.1515/REVNEURO.2008.19.4-5.363

Wilming, N., Murphy, P. R., Meyniel, F., & Donner, T. H. (2020). Large-scale dynamics of

perceptual decision information across human cortex. *Nature Communications*, *11*(1), 5109. doi:10.1038/s41467-020-18826-6

- Wilson, M. A., & McNaughton, B. L. (1993). Dynamics of the Hippocampal Ensemble Code for Space. *Science*, *261*(5124), 1055–1058. doi:10.1126/science.8351520
- Woodward, J. (2003). *Making things happen: A theory of causal explanation*. Oxford University Press.
- Xu, Y., Liu, J., & Kanwisher, N. (2005). The M170 is selective for faces, not for expertise. *Neuropsychologia*, *43*(4), 588–597. doi:10.1016/j.neuropsychologia.2004.07.016
- Yamins, D. L., Hong, H., Cadieu, C., & DiCarlo, J. J. (2013). Hierarchical Modular Optimization of Convolutional Networks Achieves Representations Similar to Macaque IT and Human Ventral Stream. Advances in Neural Information Processing Systems, 26. Retrieved from https://proceedings.neurips.cc/paper\_files/paper/2013/file/9a1756fd0c741126d7bbd4b69 2ccbd91-Paper.pdf
- Zhang, K., Ginzburg, I., McNaughton, B. L., & Sejnowski, T. J. (1998). Interpreting Neuronal Population Activity by Reconstruction: Unified Framework With Application to Hippocampal Place Cells. *Journal of Neurophysiology*, 79(2), 1017–1044. doi:10.1152/jn.1998.79.2.1017