# On the Power of Quantum Distributed Proofs

Atsuya Hasegawa<sup>\*1</sup>, Srijita Kundu<sup>†2</sup>, and Harumichi Nishimura<sup>‡3</sup>

<sup>1</sup>Graduate School of Information Science and Technology, The University of Tokyo, Japan

<sup>2</sup>Institute for Quantum Computing and Department of Combinatorics and Optimization,

University of Waterloo, Canada

<sup>3</sup>Graduate School of Informatics, Nagoya University, Japan

#### Abstract

Quantum nondeterministic distributed computing was recently introduced as dQMA (distributed quantum Merlin-Arthur) protocols by Fraigniaud, Le Gall, Nishimura and Paz (ITCS 2021). In dQMA protocols, with the help of quantum proofs and local communication, nodes on a network verify a global property of the network. Fraigniaud et al. showed that, when the network size is small, there exists an exponential separation in proof size between distributed classical and quantum verification protocols, for the equality problem, where the verifiers check if all the data owned by a subset of them are identical. In this paper, we further investigate and characterize the power of the dQMA protocols for various decision problems.

First, we give a more efficient dQMA protocol for the equality problem with a simpler analysis. This is done by adding a symmetrization step on each node and exploiting properties of the permutation test, which is a generalization of the SWAP test. We also show a quantum advantage for the equality problem on path networks still persists even when the network size is large, by considering "relay points" between extreme nodes.

Second, we show that even in a general network, there exist efficient dQMA protocols for the ranking verification problem, the Hamming distance problem, and more problems that derive from efficient quantum one-way communication protocols. Third, in a line network, we construct an efficient dQMA protocol for a problem that has an efficient two-party QMA communication protocol.

Finally, we obtain the first lower bounds on the proof and communication cost of dQMA protocols. To prove a lower bound on the equality problem, we show any dQMA protocol with an entangled proof between nodes can be simulated with a dQMA protocol with a separable proof between nodes by using a QMA communication-complete problem introduced by Raz and Shpilka (CCC 2004).

 $<sup>^*</sup>atsuyahasegawa@is.s.u-tokyo.ac.jp$ 

<sup>&</sup>lt;sup>†</sup>srijita.kundu@uwaterloo.ca

<sup>&</sup>lt;sup>‡</sup>hnishimura@i.nagoya-u.ac.jp

# Contents

| 1        | Introduction  | 3         |  |  |  |  |
|----------|---|-----------|--|--|--|--|
|          | 1.1 Background  | 3         |  |  |  |  |
|          | 1.2 Our results   | 4         |  |  |  |  |
|          | 1.3 Overview of our techniques                                    | 8         |  |  |  |  |
|          | 1.4 Related works   | 10        |  |  |  |  |
|          | 1.5 Discussion and open problems                                  | 10        |  |  |  |  |
|          | 1.6 Organization  | 11        |  |  |  |  |
| <b>2</b> | Preliminaries   | 11        |  |  |  |  |
|          | 2.1 Quantum computation and information                           | 12        |  |  |  |  |
|          | 2.2 Computational models  | 13        |  |  |  |  |
|          | 2.2.1 Communication complexity                                    | 13        |  |  |  |  |
|          | 2.2.2 QMA communication protocols and its variants                | 14        |  |  |  |  |
|          | 2.2.3 Distributed verification                                    | 15        |  |  |  |  |
| 3        | Improved dQMA protocol for EQ with the permutation test           | 17        |  |  |  |  |
|          | 3.1 Property and application of the permutation test              | 17        |  |  |  |  |
|          | 3.2 Protocol on paths   | 20        |  |  |  |  |
|          | 3.3 Protocol on general graphs                                    | 22        |  |  |  |  |
| <b>4</b> | Robust quantum advantage for EQ on a path                         | <b>24</b> |  |  |  |  |
|          | 4.1 Quantum upper bound   | 24        |  |  |  |  |
|          | 4.2 Classical lower bound   | 25        |  |  |  |  |
| 5        | Protocol for comparing the values of inputs                       |           |  |  |  |  |
|          | 5.1 Protocol for the greater-than problem                         | 26        |  |  |  |  |
|          | 5.2 Application for ranking verification                          | 28        |  |  |  |  |
| 6        | Protocol for the Hamming distance and beyond on general graphs    |           |  |  |  |  |
|          | 6.1 Protocol for the Hamming distance                             | 29        |  |  |  |  |
|          | 6.2 Extended results  | 31        |  |  |  |  |
| 7        | Construction of $dQMA^{sep}$ protocols from $dQMA$ protocols      | <b>34</b> |  |  |  |  |
| 8        | Lower bounds for dQMA protocols                                   |           |  |  |  |  |
|          | 8.1 By a counting argument over quantum states for fooling inputs | 37        |  |  |  |  |
|          | 8.2 By a reduction to lower bounds of QMA communication protocols | 41        |  |  |  |  |

# 1 Introduction

# 1.1 Background

#### Quantum distributed computing

Quantum distributed computing is the quantum analog of distributed computing where parties are quantum computers and communication in a network is done via qubits. A few early works initiated the study of quantum distributed computing [BOH05, TKM12, GKM09, EKNP14]. See also [BT08, DP08, AF14] for general discussions.

Recently, the quantum distributed computing model has been intensively studied to identify quantum advantages in the number of rounds and the amount of communication in distributed computing. The major models in classical distributed computing have been explored since the seminal work by Le Gall and Magniez [GM18]; CONGEST model [GM18, IGM20, MN22, CHFG<sup>+</sup>22, vAdV22, WY22], CONGEST-CLIQUE model [IG19] and LOCAL model [GNR19, GR22, CRdG<sup>+</sup>23].

#### Nondeterministic distributed computing

For both theoretical and application reasons, on distributed networks, it is quite important to efficiently verify some global properties of the network with local (i.e., constant-round) communication. The most widely accepted and studied criteria for distributed verification is as follows [Fra10]:

- (completeness) For a *yes*-instance, all the nodes must accept.
- (soundness) For a *no*-instance, at least one node must reject.

Intuitively, if the global property of the graph is appropriate, all the nodes are satisfied, and otherwise, at least one node raises an alarm to all the other nodes.

On the other hand, many properties cannot be checked with such local communication, and usually require many rounds on the networks. A possible extension is to give information to the nodes on the network. Such a scheme was introduced as proof-labelling schemes [KKP10] and locally checkable proofs [GS16], which are considered distributed NP protocols. More recently, randomized proof-labeling schemes were introduced [FPSP19], and these protocols are considered as *distributed Merlin-Arthur* (dMA) protocols. In a dMA protocol, an untrusted prover sends a classical proof to all the nodes on a network. Based on their part of the proof, each node, who can use a randomized algorithm, on the network simultaneously sends messages to its neighbors and receives messages from its neighbors in constantly many rounds. Finally each node outputs accept or reject in a probabilistic manner so that completeness is high, i.e., the completeness condition holds with probability at least, say,  $\frac{2}{3}$  (completeness  $\frac{2}{3}$ ) and soundness error is low, i.e., the soundness condition does not hold with probability at most, say,  $\frac{1}{3}$  (soundness  $\frac{1}{3}$ ).

While a dMA protocol is more powerful than usual deterministic distributed computing, unfortunately, there are still limits on this model for some predicates [FGNP21].

#### Distributed quantum Merlin-Arthur (dQMA) protocols

Fraigniaud, Le Gall, Nishimura, and Paz [FGNP21] introduced the setting where a prover and nodes are *quantum* computers and communicate with *quantum* messages, and named such the protocols distributed *quantum* Merlin-Arthur (dQMA) protocols.

The global property they considered was the problem EQ of deciding whether all the distributed data (*n*-bit binary strings) on the network are the same or not. The basic idea behind their dQMA protocol is to make the prover send quantum fingerprints for the input data [BCWdW01] to all the nodes; subsequently, each node sends the fingerprint it receives to its neighbor, and they do the SWAP test [BCWdW01], a quantum procedure for checking whether two quantum fingerprints are the same or not. Their dQMA protocol needs local proof size  $O(tr^2 \log n)$ , namely, each node receives an  $O(tr^2 \log n)$ -qubit proof, where r is the radius of the network and t is the number of distributed inputs. As a complementary result to their dQMA upper bound, they showed that any dMA protocol with high completeness and low soundness error requires an  $\Omega(n)$  size classical proof for at least one node. As a consequence, they gave an exponential gap in the proof size between dMA protocols and dQMA protocols for the equality problem.

They also derive an efficient dQMA protocol on a path, for any function that has an efficient quantum one-way communication protocol with bounded error in the communication complexity setting. As a corollary, they have an efficient dQMA protocol on a path for the Hamming distance problem since it has an efficient quantum one-way communication protocol [Yao03].

The results of [FGNP21] are summarized in Table 1, where #Terminals represents the number of terminals, the nodes that have distributed inputs. For a function  $f: (\{0,1\}^n)^2 \to \{0,1\}$ , let us denote by  $\mathsf{BQP}^1(f)$  the quantum one-way communication complexity of f.

| Protocol  | Problem | #Terminals | Round Number | Local Proof Size            |
|-----------|---------|------------|--------------|-----------------------------|
| Quantum   | EQ      | t          | 1            | $O(tr^2\log n)$             |
| Quantum   | f       | 2          | 1            | $O(r^2 BQP^1(f) \log(n+r))$ |
| Classical | EQ      | 2          | u            | $\Omega(\frac{n}{\nu})$     |

Table 1: Summary of the results by Fraigniaud, Le Gall, Nishimura, and Paz [FGNP21]

# 1.2 Our results

In this work, we further investigate the power and limits of dQMA protocols, and give a comprehensive characterization for various decision problems.

#### Improved dQMA protocols for EQ

We derive a more efficient dQMA protocol for EQ on a general graph with multiple input terminals, by a simpler analysis of soundness. Our protocol and analysis are simpler than the ones in [FGNP21] and the proof size of our dQMA protocol does not depend on the number of the terminals and matches the size of the path case with two terminals.

**Theorem 1** (Theorem 19). There exists a dQMA protocol for EQ between t terminals, on a network of radius r, with perfect completeness (i.e., completeness 1) and sufficiently low soundness error, using local proof and message of size  $O(r^2 \log n)$ .

The result of [FGNP21] implies that there is an exponential difference in proof size between dMA and dQMA for EQ on a path. However, such a big difference holds only when the network size is much smaller than the input size, i.e.,  $r \ll n$ . Since there exists a trivial classical protocol with *n*-bit proofs (the prover sends the whole *n*-bit string to all the nodes, and each node checks if

the proofs of its neighbors are identical to its own or not), the quantum strategy can be even worse than the trivial classical strategy when the network size is not so small.

In this paper, we show that even when the network size is not so small, a provable quantum advantage still persists. To claim the quantum advantage, we consider the complexity measure of the total size of proofs to all the nodes rather than the size of respective proofs to each node.

**Theorem 2** (Informal version of Theorem 22 and Corollary 25). There exists a dQMA protocol for EQ on the path of length r, with 1-round communication, perfect completeness and sufficiently low soundness error, and with  $\tilde{O}(rn^{\frac{2}{3}})$  qubits as proofs in total. In contrast, any dMA protocol for EQ with constant-round communication, sufficiently high completeness and low soundness error, requires  $\Omega(rn)$  bits as proofs in total.

#### The power of dQMA protocols for various problems

Checking how large an input is among all inputs held by the terminals in a network is a fundamental problem. We name this problem the ranking verification (RV) problem, and show that there exists an efficient dQMA protocol for it.

**Definition 1** (Ranking verification problem, informal version of Definition 9). For  $i, j \in [1, t]$ ,  $\mathsf{RV}_t^{i,j}(x_1, \ldots, x_t) = 1$  if and only if  $x_i$ , which is held by the *i*-th terminal, is the *j*-th largest input among t n-bit integers  $x_1, \ldots, x_t$ .

**Theorem 3** (Informal version of Theorem 29). There exists a dQMA protocol for RV between t terminals on a network of radius r, with perfect completeness and sufficiently low soundness error, using local proof and messages of size  $O(tr^2 \log n)$ .

To prove this statement, we derive an efficient dQMA protocol on a path to solve the greaterthan function. The greater-than function (GT) is defined as GT(x, y) = 1 if and only if x > y, where x and y are n-bit integers.

**Theorem 4** (Theorem 26). There exists a dQMA protocol for GT on the path of length r with 1round communication, perfect completeness, and sufficiently low soundness error, using local proof and message of size  $O(r^2 \log n)$ .

We can show that any dMA protocol for GT with high completeness and low soundness error requires  $\Omega(nr)$  size classical proofs in total. Thus, this provides us another fundamental problem that exhibits an exponential quantum advantage in distributed verification.

The result of [FGNP21] on converting a quantum one-way communication protocol to a dQMA protocol only works on a path with two inputs, and no efficient dQMA protocol was known for three or more inputs over general networks. We construct an efficient dQMA protocol on a general graph with multiple terminals, for any function which has an efficient quantum one-way communication protocol with bounded error. For a function  $f: (\{0,1\}^n)^2 \to \{0,1\}$ , we define the multi-input function  $\forall_t f: (\{0,1\}^n)^t \to \{0,1\}$  where  $\forall_t f(x_1,\ldots,x_t) = 1$  iff  $f(x_i,x_j) = 1$  for any  $i, j \in [1,t]$ .

**Theorem 5** (Theorem 32). For a function  $f : (\{0,1\}^n)^2 \to \{0,1\}$ , there exists a 1-round dQMA protocol for  $\forall_t f$  on a network of radius r, with sufficiently high completeness and low soundness error, using local proof and message of size  $O(t^2r^2\mathsf{B}\mathsf{Q}\mathsf{P}^1(f)\log(n+t+r))$ .

We also construct an efficient dQMA protocol for a function which has an efficient QMA communication protocol (introduced by Raz and Shpilka [RS04]) rather than an efficient quantum one-way communication protocol. Let us denote by QMAcc(f) the sum of the proof and communication amount of QMA communication protocols for f.

**Theorem 6** (Informal version of Proposition 47). There exists a dQMA protocol to solve f on the path of length r with sufficiently high completeness and low soundness error, using local proof and message of size  $O(r^2 \log(r) \operatorname{poly}(\mathsf{QMAcc}(f)))$ .

In addition, we show that any dQMA protocol in which entangled proofs are given to the nodes can be simulated with a dQMA protocol with "separable" proofs, in which the local part of the proof at each node is not entangled with the other nodes, with some overheads. A  $dQMA^{sep}$  protocol is a dQMA protocol whose completeness holds with a proof that is separable between nodes.

**Theorem 7** (Informal version of Theorem 46). For a function f which has a constant-round efficient dQMA protocol on a path (with entangle proofs), there exists a 1-round efficient dQMA<sup>sep</sup> protocol for f.

Our results on quantum upper bounds and classical lower bounds are summarized in Table 2. As seen in the table, all the dQMA protocols constructed in this paper are actually dQMA<sup>sep</sup> ones. Let dQMA(f) denote the sum of the total proof size and the communication size of a dQMA protocol for f.

| Protocol            | Problem       | #Terminals | Local Proof Size                               | Total Proof Size            | Ref              |
|---------------------|---------------|------------|--|-----------------------------|------------------|
| dQMA <sup>sep</sup> | EQ            | t          | $O(r^2 \log n)$                                | _                           | § <mark>3</mark> |
| $dQMA^{sep}$        | EQ            | 2          | $n \text{ or } O(r^2 \log n)$                  | $	ilde{O}(rn^{rac{2}{3}})$ | § <b>4.1</b>     |
| dMA                 | EQ,GT         | 2          |  | $\Omega(rn)$                | $\S{4.2}$        |
| dQMA <sup>sep</sup> | GT            | 2          | $O(r^2 \log n)$                                |                             | $\S{5.1}$        |
| $dQMA^{sep}$        | RV            | t          | $O(tr^2\log n)$                                |                             | $\S{5.2}$        |
| dQMA <sup>sep</sup> | $\forall_t f$ | t          | $O(t^2 r^2 BQP^1(f) \log(n+t+r))$              |                             | § <mark>6</mark> |
| dQMA <sup>sep</sup> | f             | 2          | $O(r^2 \log(r) \operatorname{poly}(QMAcc(f)))$ |                             | § 7              |
| dQMA <sup>sep</sup> | f             | 2          | $	ilde{O}(r^2(dQMA(f))^2)$                     |                             | § 7              |

Table 2: Summary of our results on quantum upper bounds and classical lower bounds

#### Lower bounds for dQMA protocols

In this paper, we derive the first lower bounds on the proof and communication cost of dQMA protocols. We introduce a dQMA<sup>sep,sep</sup> protocol as another variant of dQMA protocols where a prover can only send separable proofs between nodes (and thus soundness holds only with respect to separable proofs). When we restrict the power of the prover, we obtain the following strong lower bound (note that it implies the matching lower bounds for EQ and GT with respect to the order of the input size n as their sizes of 1-fooling sets are  $2^n$ ).

**Theorem 8** (Informal version of Theorem 51). Let  $\nu \in \mathbb{N}$  be a constant and  $f : (\{0,1\}^n)^2 \to \{0,1\}$  be a Boolean function with a 1-fooling set of size  $2^n$  (the definition of 1-fooling sets is given in Section 2.2.1). Let  $\mathcal{P}$  be a dQMA<sup>sep,sep</sup> protocol for f on the path of length r with  $\nu$ -round

communication, sufficiently high completeness and low soundness error. Then, the total proof size is  $\Omega(r \log n)$ .

It is notoriously hard to prove lower bounds when dealing with entanglement between parties, and the seminal example is the case of MIP<sup>\*</sup> [CHTW04, IV12, NW19, JNV<sup>+</sup>21]. In dQMA protocols, nodes on a network might exploit the power of entangled proofs from a prover by clever local communication and computations. Despite this difficulty, we prove several lower bounds of dQMA protocols. The main result is as follows.

**Theorem 9** (Informal version of Theorem 56). Let  $f : (\{0,1\}^n)^2 \to \{0,1\}$  be a Boolean function with a 1-fooling set of size  $2^n$  (including EQ and GT). Let  $\mathcal{P}$  be a dQMA protocol for f on the path of length r with constant-round communication, sufficiently high completeness and low soundness error. Then, the total proof and communication size of  $\mathcal{P}$  is  $\Omega((\log n)^{1/4-\epsilon})$  for a sufficiently small constant  $\epsilon > 0$ .

Additionally, we prove a dQMA lower bound for functions which are hard for QMA communication protocols, in terms of the one-sided smooth discrepancy [Kla11]. Let us denote by  $sdisc^{1}(f)$ the one-sided smooth discrepancy of a function f; it was shown in [Kla11] that  $sdisc^{1}$  is a lower bound on QMA communication complexity.

**Theorem 10** (Informal version of Theorem 63). Assume that  $\mathcal{P}$  is a dQMA protocol on a line of length r with arbitrary rounds to solve f with sufficiently high completeness and low soundness error. Then, the total proof and communication size of  $\mathcal{P}$  is  $\Omega(\sqrt{\log \operatorname{sdisc}^1(f)})$ .

Note that the above theorem does not give a nontrivial lower bound for the equality function, since this function has a constant-cost classical randomized communication protocol, and therefore  $sdisc^{1}(EQ)$  is at most constant. Theorem 9 thus outperforms Theorem 10 for the EQ function.

Our results on lower bounds (including other ones than the above three theorems) are summarized in the following Table 3. In the table,  $\epsilon > 0$  is any small constant and  $f^+$  is any non-constant Boolean function f. As functions which are hard for QMA communication protocols [Kla11], let us denote by DISJ the disjointness function, by IP the inner product function, by  $P_{AND}$  the pattern matrix [She11] of the AND function. These lower bounds will be formally stated and proved in Section 8.

| Protocol                | Problem   | Round Number | Lower Bound   |
|-------------------------|-----------|--------------|---|
| dQMA <sup>sep,sep</sup> | EQ,GT     | constant     | total proof size $\Omega(r \log n)$   |
| dQMA                    | EQ,GT     | constant     | total proof & communication size $\Omega(\frac{(\log n)^{\frac{1}{2}-\epsilon}}{r^{1+\epsilon}})$ |
| dQMA                    | $f^+$     | constant     | total proof size $\Omega(r)$  |
| dQMA                    | EQ,GT     | constant     | total proof & communication size $\Omega((\log n)^{\frac{1}{4}-\epsilon})$                        |
| dQMA                    | DISJ      | arbitrary    | total proof & communication size $\Omega(n^{\frac{1}{3}})$  |
| dQMA                    | IP        | arbitrary    | total proof & communication size $\Omega(n^{\frac{1}{2}})$  |
| dQMA                    | $P_{AND}$ | arbitrary    | total proof & communication size $\Omega(n^{\frac{1}{3}})$  |

Table 3: Summary of our results on quantum lower bounds

### 1.3 Overview of our techniques

#### Improved protocol for EQ with a simpler analysis and the permutation test

In [FGNP21], they designed a protocol on a path where each node sends the received proof (quantum fingerprint) to its left neighbor with probability  $\frac{1}{2}$ , and thus the conditional probability that the SWAP test occurs is needed to analyze. To simplify the analysis of the soundness of the protocol, we add an extra step called the symmetrization step for each node. With this step, we can avoid using conditional probability because each node conducts the SWAP test with certainty.

In the [FGNP21] protocol for EQ with three or more terminals, every non-terminal node performs the SWAP test on the state that consists of the state received from the prover and a state randomly chosen from states received from the children. Every node discards the other states received from the children and are not used for the SWAP test. To improve the proof size of the protocol for general graphs from  $O(tr^2 \log n)$  to  $O(r^2 \log n)$ , we make each node perform the permutation test [BBD+97, BCWdW01, KNY08] on all the states from its children.

The permutation test is a generalization of the SWAP test from 2-partite systems to k-partite systems for any integer  $k \ge 2$ . We identify the permutation test with a projector to the symmetric subspace of multiple systems as a special case of weak Schur Sampling [BCH06]. Using properties of Schur sampling, we show that, by using the permutation test, we can test how close the subspace is to given states.

#### Robust quantum advantage for EQ on a path

To prove a universal quantum advantage for EQ, we consider inserting multiple "relay points" per  $O(n^{\frac{1}{3}})$  nodes between extreme nodes that receive *n*-qubit proofs. Based on the *n*-bit measurement results, nodes between relay points conduct the SWAP test-based quantum strategy. This makes for a dQMA protocol in which all the nodes receive  $\tilde{O}(rn^{\frac{2}{3}})$  qubits in total and has high completeness and low soundness error.

To complement this result, we claim any dMA protocol for EQ with high completeness and low soundness error has to receive  $\Omega(rn)$  bits in total by a finer observation of the classical lower bound in [FGNP21].

#### Protocol for the greater-than problem and the ranking verification problem

It was shown that the quantum one-way communication complexity of GT is maximal, i.e.,  $BQP^1(GT) = \Theta(n)$  by Zhang [Appendix B in [Zha11]]. Therefore, one cannot apply the technique from [FGNP21], and no efficient dQMA protocol for GT was previously known. In this paper, we derive a new way to use quantum fingerprints with classical indexes, and construct an efficient dQMA protocol for GT.

To construct a dQMA protocol for the greater-than (GT) problem, we first observe that for  $x, y \in \{0, 1\}^n$ , GT(x, y) = 1 if and only if there exists an index *i* such that a part of *x* and *y* from the 1st bit to the (i - 1)th bit are the same and the *i*th bit of *x* is 1 and the *i*th bit of *y* is 0. Therefore, we can run the protocol for the equality problem for a part of the inputs, and make the prover send the classical index *i*.

To prove the soundness for the ranking verification problem, we consider to make the prover send a direction bit indicating which input is larger and add a step for a root node to count the directions. We then have an efficient protocol for the ranking verification problem by running the protocol for GT between multiple terminals in parallel.

#### Protocol from a quantum one-way communication protocol on general graphs

To derive a dQMA protocol for a function that has an efficient quantum one-way communication protocol with multiple terminals, one difficulty is that we need to run the operation of Bob, a party that receives a message from the other party Alice, in the one-way protocol for the function on every leaf. Therefore, we consider a protocol from root to leaves, which is the reverse of the direction of messages in the protocol for EQ.

The other caveat is that a protocol on one tree is not enough to prove soundness. This is because even if  $f(x_i, x_{i+1}) = 1$  and  $f(x_i, x_{i+2}) = 1$ , the value of  $f(x_{i+1}, x_{i+2})$  can be 0. To overcome this, we consider running the protocols in parallel for all the t spanning trees whose roots are the t terminals.

#### Construction of a dQMA protocol with separable proofs from any dQMA protocol

To construct a dQMA protocol with separable proofs from any dQMA protocol, we use a QMA communication complete problem introduced by Raz and Shpilka [RS04].

QMA communication protocols are two-party communication protocols with a prover who can send a proof to one party Alice. Raz and Shpilka [RS04] defined the Linear Subspace Distance (LSD) problem as a QMA communication complete problem, i.e., any QMA communication protocol can be reduced to the LSD problem. The LSD problem is a problem to decide whether two subspaces held respectively by the two parties Alice and Bob are close or not.

A useful property of the LSD problem is that it can be solved with a QMA one-way communication protocol with a proof to Alice. Exploiting this property and the SWAP test strategy [FGNP21], we construct a  $dQMA^{sep}$  protocol for any function that has a QMA communication protocol.

In addition, we observe that any dQMA protocol can be viewed as a QMA communication protocol when we split the total nodes into two groups of nodes and consider Alice and Bob to simulate the protocol of the nodes. This leads us to get a  $dQMA^{sep}$  protocol from any dQMA protocol.

#### Lower bounds for dQMA

We obtain some lower bounds by counting arguments over quantum states for fooling inputs. To prove our bounds, we use a result from [BCWdW01, dW01], which states that in order to keep non-trivial distances between each pair of a set of  $2^n$  states, at least  $\Omega(\log n)$  qubits are required. From this we can prove that, to answer correctly on  $2^n$  fooling inputs for EQ and GT, local nodes in a dQMA protocol must receive at least  $\Omega(\log n)$  qubits. Then, by the pigeonhole principle, we show that at least  $\Omega(r \log n)$  qubits are required as a quantum proof in total. This lower bound and proof strategy can be regarded as a quantum analog of the classical lower bound in [FGNP21].

In order for the above proof strategy to be applicable, proofs between nodes are required to be separable, since entanglement between nodes might fool the verifiers. However, by combining our result on the simulation of any dQMA protocol with a dQMA<sup>sep</sup> protocol, we show a lower bound even for entangled proofs and communications, where the order of the bound is an inverse of a polynomial in r, due to the overhead of the simulation.

For entangled proofs, we can also show a simpler lower bound. Let us suppose that there are consecutive nodes which receive no proof from a prover. Then, even for a function that has only two fooling inputs, the verifiers are easily fooled by the two inputs, because the information the nodes have is separated between the two parts. To deliver quantum proofs to each local node, it can be shown that  $\Omega(r)$  qubits are required as a quantum proof in total. By combining the two lower bounds for entangled proofs, for EQ and GT we can obtain a lower bound which does not depend on r which is the main result of our lower bounds.

We obtain other lower bounds by a reduction to QMA communication lower bounds by Klauck [Kla11]. To make a reduction, we first introduce  $QMA^*$  communication protocols where proofs are sent to the two parties and they might be entangled. Then, we observe that a dQMA protocol can be used to give a QMA<sup>\*</sup> communication protocol, and then the results of [Kla11] can be applied.

#### 1.4 Related works

Raz and Shpilka [RS04] introduced the Linear Subspace Distance problem as a complete problem for QMA communication protocols, and showed that there exists an efficient QMA (two-party) communication protocol and no efficient quantum communication protocol and MA communication protocol for the problem. To prove the completeness, they considered a superposition of each step of QMA communication protocols similar to Kitaev's circuit-to-Hamiltonian construction [KSV02].

Klauck [Kla11] proved the first lower bounds for the QMA communication protocols. To derive the lower bounds, Klauck introduced a new technique named one-sided discrepancy, and showed separations between AM communication complexity and PP communication complexity, and between AM communication complexity and QMA communication complexity.

In [GMN23a], Le Gall, Miyamoto, and Nishimura considered the state synthesis [Aar16] on the dQMA protocols. They introduced the state generation on distributed inputs (SGDI) and gave a dQMA protocol for the task. As an application, they constructed an efficient dQMA protocol for the Set Equality problem introduced by [NPY20]. They also showed that from any dQMA protocol, we can replace quantum communications with classical communications between verifiers on the network and construct an LOCC (Local Operation and Classical Communication) dQMA protocol to simulate the original dQMA protocol.

In [GMN23b], Le Gall, Miyamoto, and Nishimura introduced distributed quantum interactive proofs (dQIP) as a quantum analog of the distributed interactive proofs (dAM) introduced by [KOS18]. They proved that any dAM protocols with constant turns communication between verifiers and a prover can be converted into dQIP protocols with 5 turns if no shared randomness on the network and 3 turns if the shared randomness is allowed.

#### 1.5 Discussion and open problems

In this paper, we investigate the power of the dQMA protocols and show the protocols are indeed useful for many problems but have limits for some functions.

Here we list some problems that are left open by our work.

1. There are many variants of QMA (see [Gha24] for a comprehensive survey on QMA and its variants) and we can define more variants of dQMA protocols. For example, we can define a dQCMA protocol if we allow only classical proofs from a prover while the verifier can communicate with qubits. Another example is a dQMA(k) protocol for  $k \in \mathbb{N}$  if we allow k

provers who send quantum proofs to the nodes independently and whose proofs are promised to be separable. Can we find a new relationship between dQMA protocols and their variants?

Note that some relations are known. In [GMN23a], the authors showed that any dQMA protocol can be simulated by an LOCC dQMA protocol with some overheads. This paper shows that any dQMA protocol can be simulated by a dQMA<sup>sep</sup> protocol with some overheads.

- 2. In our paper and relevant papers about dQMA protocols, a quantum advantage on the input size is the focus. In [GS16], Göös and Suomela classified graph properties according to their proof size complexity with local verification based on the graph size. Can we have a quantum advantage in distributed verification concerning the graph size? Can we give an efficient quantum verification protocol for a graph property that is shown to be hard in [GS16]?
- 3. There are gaps between upper and lower bounds for EQ and GT. Can we fill the gaps by providing stronger upper or lower bounds?

#### 1.6 Organization

In Section 2, we give some preliminaries for this paper. In Section 3, we apply the permutation test to obtain our improved dQMA protocol for EQ. In Section 4, we prove a quantum advantage on distributed verification protocols on a path for EQ still persists even when there is no condition on the size of the path networks. In Section 5, we derive an efficient dQMA protocol for GT and the ranking verification problem. In Section 6, we present an efficient dQMA protocol for the Hamming distance problem with multiple terminals and its applications. In Section 7, we show how to convert a QMA communication protocol and a dQMA protocol to a dQMA<sup>sep</sup> protocol. In Section 8, we derive some lower bounds for dQMA protocols.

# 2 Preliminaries

Proof.  $n\Pr[A_1 \lor A_2]$ 

When we do not care about constant factors, we use the asymptotic notations. We say T(n) = O(f(n)) if there exist constants c and  $n_0$  such that for all the integers  $n \ge n_0$ , we have  $T(n) \le cf(n)$ . We say  $T(n) = \Omega(f(n))$  if there exist constants c and  $n_0$  such that for all the integers  $n \ge n_0$ , we have  $T(n) \ge cf(n)$ .  $T(n) = \Theta(f(n))$  means that T(n) = O(f(n)) and  $T(n) = \Omega(f(n))$  hold simultaneously. We also say  $T(n) = \tilde{O}(f(n))$  if there exists a constant c such that  $T(n) = O(f(n) \cdot \log^c(f(n)))$ .

This paper considers simple connected graphs as the underlying graph of networks and identifies a network with its underlying graph. The radius r of a network G = (V, E) is defined as  $r := \min_{u \in V} \max_{v \in V} \operatorname{dist}_G(u, v)$ , where  $\operatorname{dist}_G(u, v)$  denotes the distance between u and v in G.

For any event A and B, let us denote the complement of A by  $\neg A$ , the intersection of A and B by  $A \land B$ , the union of A and B by  $A \lor B$ . We will need the following basic property on probability.

**Lemma 11.** Let  $A_j$  be an event for  $j = 1, 2, \ldots, n$ .<sup>1</sup> Then,

$$\Pr[A_1 \lor A_2 \lor \dots \lor A_n] \ge \frac{1}{n} \sum_{j=1}^n \Pr[A_j].$$
$$\lor \dots \lor A_n] = \sum_{j=1}^n \Pr[A_1 \lor A_2 \lor \dots \lor A_n] \ge \sum_{j=1}^n \Pr[A_j]$$

<sup>1</sup>Note that these events are not necessarily independent.

#### 2.1 Quantum computation and information

We assume that readers are familiar with basic notations of quantum computation and information. We refer to [NC10, Wat18, dW19] for standard references.

For a Hilbert (finite-dimensional complex Euclidean) space  $\mathcal{H}, \mathcal{B}(\mathcal{H})$  and  $\mathcal{D}(\mathcal{H})$  denote the sets of pure and mixed states over  $\mathcal{H}$  respectively. Let us consider Hilbert spaces  $\mathcal{H}_1, \ldots, \mathcal{H}_n$  and a matrix M on  $\mathcal{H}_1 \otimes \cdots \otimes \mathcal{H}_n$ . We will denote by  $|b_y^x\rangle$  a *y*th orthonormal basis vector of  $\mathcal{H}_x$ . Then, let us define the reduced matrix  $\operatorname{tr}_{\overline{i}}(M)$  on  $\mathcal{H}_i$  obtained by tracing out  $\mathcal{H}_1, \ldots, \mathcal{H}_{i-1}, \mathcal{H}_{i+1}, \ldots, \mathcal{H}_n$ as

$$\operatorname{tr}_{\overline{i}}(M) = \sum_{j_1, \dots, j_{i-1}, j_{i+1}, \dots, j_n} (\langle b_{j_1}^1 | \otimes \dots \otimes \langle b_{j_{i-1}}^{i-1} | \otimes I \otimes \langle b_{j_{i+1}}^{i+1} | \otimes \dots \otimes \langle b_{j_n}^n | ) M(|b_{j_1}^1 \rangle \otimes \dots \otimes |b_{j_{i-1}}^{i-1} \rangle \otimes I \otimes |b_{j_{i+1}}^{i+1} \rangle \otimes \dots \otimes |b_{j_n}^n \rangle).$$

We also define the reduced matrix  $\operatorname{tr}_i(M)$  on  $\mathcal{H}_1 \otimes \cdots \otimes \mathcal{H}_{i-1} \otimes \mathcal{H}_{i+1} \otimes \cdots \otimes \mathcal{H}_n$  obtained by tracing out  $\mathcal{H}_i$  as

$$\operatorname{tr}_i(M) = \sum_j (I \otimes \cdots \otimes I \otimes \langle b_j^i | \otimes I \otimes \cdots \otimes I) M (I \otimes \cdots \otimes I \otimes | b_j^i \rangle \otimes I \otimes \cdots \otimes I).$$

One common measure of distance between quantum states is the trace distance, which is defined as half of the trace norm of the difference of the matrices:

$$D(\rho,\sigma) := \frac{1}{2} \|\rho - \sigma\|_1,$$

where  $||A||_1 \equiv \text{tr}\sqrt{A^{\dagger}A}$  is the trace norm of A, and  $\sqrt{A}$  is the unique semidefinite B such that  $B^2 = A$  (which is always defined for positive semidefinite A). The trace distance can be regarded as a maximum probability to distinguish the two states by POVM measurements since

$$D(\rho, \sigma) = \max_{M} \operatorname{tr}(M(\rho - \sigma)),$$

where the maximization is taken over all positive operators  $M \leq I$ . The other common measure of the distance is the fidelity, which is defined as

$$F(\rho,\sigma) := \operatorname{tr}\sqrt{\sqrt{\rho}\sigma\sqrt{\rho}}.$$

The relation between the trace distance and the fidelity is known as follows.

**Fact 1** (Fuchs-van de Graaf inequalities [FvdG99]). For any quantum states  $\rho$  and  $\sigma$ ,

$$1 - F(\rho, \sigma) \le D(\rho, \sigma) \le \sqrt{1 - F(\rho, \sigma)^2}.$$

Here is a useful lemma to connect the trace norm and the fidelity as a corollary of the Uhlmann theorem [Uhl76].

**Lemma 12** (Corollary 3.23 in [Wat18]). Let  $|\psi\rangle$  and  $|\phi\rangle$  be two pure states on  $\mathcal{X} \otimes \mathcal{Y}$  where  $\mathcal{X}$  and  $\mathcal{Y}$  are finite-dimensional complex Euclidean spaces. Then,

$$\|\operatorname{tr}_{\mathcal{X}}(|\psi\rangle\langle\phi|)\|_{1} = F(\operatorname{tr}_{\mathcal{Y}}(|\psi\rangle\langle\psi|), \operatorname{tr}_{\mathcal{Y}}(|\phi\rangle\langle\phi|)).$$

We will also need some mathematical facts.

**Fact 2** (Schmidt decomposition, e.g., Theorem 2.7 in [NC10]). Suppose  $|\psi\rangle$  is a pure state of a composite system AB. Then there exist orthonormal states  $|i_A\rangle$  for system A, and orthonormal states  $|i_B\rangle$  of system B such that

$$\ket{\psi} = \sum_{i} \lambda_i \ket{i_A} \ket{i_B}$$

where  $\lambda_i$  are non-negative numbers satisfying  $\sum_i \lambda_i^2 = 1$ .

**Fact 3.** For any two mixed states  $\rho$  and  $\sigma$ , any quantum algorithm A and any classical string s,

$$\left|\Pr[\mathcal{A}(\rho) = s] - \Pr[\mathcal{A}(\sigma) = s]\right| \le D(\rho, \sigma).$$

**Fact 4.** The trace distance is contractive under completely positive and trace preserving (CPTP) maps, i.e., if  $\Phi$  is a CPTP map, then  $D(\Phi(\rho), \Phi(\sigma)) \leq D(\rho, \sigma)$  for any states  $\rho$  and  $\sigma$ .

### 2.2 Computational models

In this subsection, we recall definitions of several important computational models and related concepts.

#### 2.2.1 Communication complexity

As standard references, we refer to [KN96, RY20] for classical communication complexity and [dW02, BCMdW10] for quantum communication complexity and the simultaneous message passing (SMP) model.

The goal in communication complexity is for Alice and Bob to compute a function  $F : \mathcal{X} \times \mathcal{Y} \rightarrow \{0, 1, \bot\}$ . We interpret 1 as "accept" and 0 as "reject" and we mostly consider  $\mathcal{X} = \mathcal{Y} = \{0, 1\}^n$ . In the computational model, Alice receives an input  $x \in \mathcal{X}$  (unknown to Bob) and Bob receives an input  $y \in \mathcal{Y}$  (unknown to Alice) promised that  $(x, y) \in \text{dom}(F) = F^{-1}(\{0, 1\})$ . In a one-way communication protocol, Alice sends a single message to Bob, and he is required to output F(x, y). In a two-way communication protocol, Alice and Bob can exchange messages with multiple rounds. The cost of a classical (resp. quantum) communication protocol is the number of bits (resp. qubits) communicated. The (bounded-error) communication complexity (resp. one-way communication complexity) of F is defined as the minimum cost of two-way (resp. one-way) classical or quantum communication protocols to compute F(x, y) with high probability, say  $\frac{2}{3}$ .

The simultaneous message passing (SMP) model is a specific model of communication protocols. In this model, Alice and Bob each send a single (possibly quantum or randomized) message to a referee Charlie. The goal for Charlie is to output F(x, y) with high probability, say at least  $\frac{2}{3}$ . The complexity measure of the protocol is the total amount of messages Charlie receives from Alice and Bob.

In this paper,  $\mathsf{BQP}^1(f)$  and  $\mathsf{BQP}^{||}(f)$  denote the quantum one-way and SMP communication complexity of f, respectively. Note that  $\mathsf{BQP}^1(f) \leq \mathsf{BQP}^{||}(f)$  for any f since any SMP protocol can be efficiently simulated by a one-way communication protocol where Charlie is simulated by Bob.

A basic function considered in communication complexity is the equality function  $\mathsf{EQ}_n : \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$ , which is defined as  $\mathsf{EQ}_n(x,y) = 1$  if x = y and 0 otherwise. This paper frequently uses the fact that  $\mathsf{EQ}_n$  can be solved by a one-way quantum protocol of cost  $c \log n$  with one-sided error for some constant c > 0; the protocol outputs 1 if x = y with probability 1, and outputs 0 with

probability 2/3. In what follows, such the protocol is called  $\pi$ , let  $|h_x\rangle$  be the  $c \log n$ -qubit state from Alice to Bob (fingerprint of x), and let  $\{M_{y,1}, M_{y,0}\}$  be the POVM measurement performed by Bob on  $|h_x\rangle$ , where  $M_{y,1}$  corresponds to the measurement result 1 (accept) and  $M_{y,0}$  to the measurement result 0 (reject).

For any Boolean function  $f : \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$ , a set  $S \subseteq \{0,1\}^n \times \{0,1\}^n$  is a 1-fooling set for f if f(x,y) = 1 for any  $(x,y) \in S$ , and  $f(x_1,y_2) = 0$  or  $f(x_2,y_1) = 0$  for any two pairs  $(x_1,y_1) \neq (x_2,y_2) \in S \times S$ .

### 2.2.2 QMA communication protocols and its variants

Let us recall the definition of QMA communication protocols.

**Definition 2** (QMA communication protocol and QMAcc(f), Definition 3 in [Kla11] and Definition 4 in [RS04]). In a QMA communication protocol for an input (x, y), Alice has a part of the input x and Bob has the other part of the input y, and Merlin produces a quantum state  $\rho$  (the proof) on some  $\gamma$  qubits, which he sends to Alice. Alice and Bob then communicate using a quantum protocol of  $\mu$  qubits in total with multiple rounds, and either accept or reject the input (x, y). We say that a QMA communication protocol computes a Boolean function  $f : \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$ , if for all inputs (x, y) such that f(x, y) = 1, there exists a quantum proof such that the protocol accepts with probability at least  $\frac{2}{3}$ , and for all inputs (x, y) such that f(x, y) = 0, and all quantum proofs, the protocol accepts with probability at most  $\frac{1}{3}$ . The cost of a QMA communication protocol is the sum of the proof size  $\gamma$  and the length of the communication  $\mu$  between Alice and Bob. We define QMAcc(f) as the minimum cost of the protocol that computes f.

We say for a function f,  $QMAcc(f) = \gamma + \mu$  if there exists a QMA communication protocol whose proof size is  $\gamma$  and communication amount is  $\mu$ .

Next, let us define a QMA one-way communication protocol and a QMA<sup>\*</sup> communication protocol as two variants of the QMA communication protocol. In the QMA one-way communication protocol, Alice can send a message once to Bob and no more communication is prohibited.

**Definition 3** (QMA one-way communication protocol and  $QMAcc^1(f)$ ). In a QMA one-way communication protocol for an input (x, y), Alice has a part of the input x and Bob has the other part of the input y, and Merlin produces a quantum state  $\rho$  (the proof) on some  $\gamma$  qubits, which he sends to Alice. Alice applies some quantum operations on the proof depending on her input x and sends  $\mu$  qubits to Bob. Bob applies some quantum operations depending on his input y and outputs accept or reject. We say that a QMA one-way communication protocol computes a Boolean function  $f: \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$ , if for all inputs (x,y) such that f(x,y) = 1, there exists a quantum proof such that the protocol accepts with probability at least  $\frac{2}{3}$ , and for all inputs (x,y) such that f(x,y) = 0, the protocol accepts with probability at most  $\frac{1}{3}$  for any quantum proof. The cost of a QMA one-way communication protocol is the sum of the proof size  $\gamma$  and the length of the one-way communication  $\mu$  from Alice to Bob. We define QMAcc<sup>1</sup>(f) as the minimum cost of the protocol that computes f.

In the QMA<sup>\*</sup> communication protocol, Alice and Bob can receive proofs respectively from Merlin and the proofs might be entangled.

**Definition 4** (QMA<sup>\*</sup> communication protocol and QMAcc<sup>\*</sup>(f)). In a QMA<sup>\*</sup> communication protocol for an input (x, y), Alice has a part of the input x and Bob has the other part of the input

y, and Merlin produces a quantum state  $\rho$  (the proof) on some  $(\gamma_1 + \gamma_2)$  qubits, which he sends  $\gamma_1$ qubits to Alice and  $\gamma_2$  qubits to Bob. Alice and Bob then communicate using a quantum protocol of  $\mu$  qubits in total with multiple rounds, and either accept or reject the input (x, y). We say that a QMA<sup>\*</sup> communication protocol computes a Boolean function  $f : \{0,1\}^n \times \{0,1\}^n \rightarrow \{0,1\}$ , if for all inputs (x, y) such that f(x, y) = 1, there exists a quantum proof such that the protocol accepts with probability at least  $\frac{2}{3}$ , and for all inputs (x, y) such that f(x, y) = 0, and all quantum proofs, the protocol accepts with probability at most  $\frac{1}{3}$ . The cost of a QMA<sup>\*</sup> communication protocol is the sum of the total proof size  $\gamma_1 + \gamma_2$  and the length of the communication  $\mu$  between Alice and Bob. We define QMAcc<sup>\*</sup>(f) as the minimum cost of the protocol that computes f on all the inputs.

We say for a function f,  $\mathsf{QMAcc}^1(f) = \gamma + \mu$  and  $\mathsf{QMAcc}^*(f) = \gamma_1 + \gamma_2 + \mu$  similar to  $\mathsf{QMAcc}(f) = \gamma + \mu$ . There are (trivial) relationships between them. First, for any f,  $\mathsf{QMAcc}(f) \leq \mathsf{QMAcc}^1(f)$  by their definitions. Second, for any f for which  $\mathsf{QMAcc}^*(f) = \gamma_1 + \gamma_2 + \mu$ ,

$$\mathsf{QMAcc}(f) \le \gamma_1 + 2\gamma_2 + \mu. \tag{1}$$

This is because any QMA<sup>\*</sup> communication protocol  $\mathcal{P}$  such that Merlin sends  $\gamma_1$  qubits to Alice and  $\gamma_2$  qubits to Bob can be simulated by a QMA communication protocol where Merlin sends Alice the  $(\gamma_1 + \gamma_2)$  qubits sent by Merlin in  $\mathcal{P}$ , Alice sends the Bob-part in  $\mathcal{P}$  ( $\gamma_2$  qubits) to Bob, and Alice and Bob conduct the subsequent communication protocol in  $\mathcal{P}$ .

#### 2.2.3 Distributed verification

Let us recall the definition of classical distributed verification protocols called distributed Merlin-Arthur protocols (dMA protocols).

In a  $\nu$ -round dMA protocol for a binary-valued function f, the prover (Merlin) first sends a message called a proof (or certificate) to the verifier (Arthur) that consists of the nodes of a network G = (V, E). More precisely, the prover sends a c(u)-bit string to each  $u \in V$ . Then, the nodes of Grun a  $\nu$ -round verification algorithm, namely, a randomized algorithm (or protocol) using  $\nu$ -round communication among the nodes. Here, t nodes  $u_i$  called *terminals* have own input string  $x_i$ . Then, the condition that the dMA protocol should satisfy for verifying whether  $f(x_1, \ldots, x_t) = 1$  or not is as follows.

**Definition 5.** On a network G = (V, E), a  $\nu$ -round dMA protocol  $\pi$  of c(u) bits proof for  $u \in V$ and m(v, w) bits communication for  $\{v, w\} \in E$  has completeness a and soundness b for a function  $f : (\{0, 1\}^n)^t \to \{0, 1\}$  if there exists a  $\nu$ -round verification algorithm with messages of m(u, v) bits in total between nodes v and w for  $\{v, w\} \in E$  respectively such that for all the inputs  $(x_1, \ldots, x_t) \in$  $(\{0, 1\}^n)^t$ :

- Completeness: if  $f(x_1, \ldots, x_t) = 1$ , then there exists a  $(\sum_{u \in V} c(u))$ -bit proof to the nodes such that  $\Pr[all \text{ the nodes accept}] \geq a$ ;
- Soundness: if  $f(x_1, \ldots, x_t) = 0$ , then  $\Pr[all \text{ the nodes accept}] \leq b$  for any  $(\sum_{u \in V} c(u))$ -bit proof.

In particular, we say that the protocol  $\pi$  has perfect completeness if a = 1. The sum  $\sum_{u \in V} c(v)$ (resp.  $\sum_{\{v,w\} \in E} m(v,w)$ ) is called the total proof (resp. message) size of  $\pi$ , and  $\max_{u \in V} c(v)$ (resp.  $\max_{\{u,w\} \in E} m(v,w)$ ) is called the local proof (resp. message) size of  $\pi$ . Let us next recall the definition of quantum verification protocols called distributed quantum Merlin-Arthur protocols (dQMA protocols). A dQMA protocol is defined similarly to dMA protocols except that the message from the prover is a quantum state and the algorithm of each node and the communication among the nodes are also quantum (and thus the complexity is measured by the number of qubits). The condition that the dQMA protocol should satisfy for verifying whether  $f(x_1, \ldots, x_n) = 1$  or not is as follows; let  $\mathcal{H}_v$  denote the Hilbert space associated with the quantum register  $R_v$  sent from the prover to the node v.

**Definition 6.** On a network G = (V, E), a  $\nu$ -round dQMA protocol of c(u) qubits proof for  $u \in V$ and m(v, w) qubits communication for  $\{v, w\} \in E$  has completeness a and soundness b for a function  $f : (\{0, 1\}^n)^t \to \{0, 1\}$  if there exists a  $\nu$ -round quantum verification algorithm with messages of m(v, w) qubits in total between nodes v and w for  $\{v, w\} \in E$  respectively such that for all the inputs  $(x_1, \ldots, x_t) \in (\{0, 1\}^n)^t$ :

- Completeness: if  $f(x_1, \ldots, x_t) = 1$ , then there exists a  $(\sum_{u \in V} c(u))$ -qubit proof  $|\xi\rangle$  on the Hilbert space  $\bigotimes_{u \in V} \mathcal{H}_u$  to the nodes such that  $\Pr[all \text{ the nodes accept}] \ge a$ ;
- Soundness: if  $f(x_1, \ldots, x_t) = 0$ , then for any  $(\sum_{u \in V} c(u))$ -qubit proof  $|\xi\rangle$  on  $\bigotimes_{u \in V} \mathcal{H}_u$ , Pr[all the nodes accept]  $\leq b$ .

In the definition above, we consider quantum proofs that are only pure states. Since mixed states are convex combinations of pure states, this restriction does not affect the completeness and soundness parameters and lose generality as in the case for QMA.

Let us define some variants of the dQMA protocol. For  $dQMA^{sep}$  protocols, the completeness holds with a separable proof between nodes and the soundness holds against any entangled proof. Actually, the dQMA protocols in [FGNP21] as well as the dQMA protocols in this paper are  $dQMA^{sep}$  protocols while we do not state it in some of the theorems for the simplicity of their statements.

**Definition 7.** On a network G = (V, E), a  $\nu$ -round dQMA<sup>sep</sup> protocol of c(u) qubits proof for  $u \in V$  and m(v, w) qubits communication for  $\{v, w\} \in E$  has completeness a and soundness b for a function  $f : (\{0,1\}^n)^t \to \{0,1\}$  if there exists a  $\nu$ -round quantum verification algorithm with messages of m(v, w) qubits between nodes v and w for  $\{v, w\} \in E$  respectively such that for all the inputs  $(x_1, \ldots, x_t) \in (\{0,1\}^n)^t$ :

- Completeness: if  $f(x_1, \ldots, x_t) = 1$ , then there is a  $(\sum_{u \in V} c(u))$ -qubit proof  $\bigotimes_{u \in V} |\xi_u\rangle$ , where  $|\xi_u\rangle$  is a state on  $\mathcal{H}_u$  for  $u \in V$ , to the nodes such that  $\Pr[all \text{ the nodes accept}] \geq a$ ;
- Soundness: if  $f(x_1, \ldots, x_t) = 0$ , then for any  $(\sum_{u \in V} c(u))$ -qubit proof  $|\xi\rangle$  on  $\bigotimes_{u \in V} \mathcal{H}_u$ , Pr[all the nodes accept]  $\leq b$ .

For  $dQMA^{sep,sep}$  protocols, the completeness holds with a separable proof and the soundness holds against only separable proofs. In other words, a  $dQMA^{sep,sep}$  protocol is a dQMA protocol where a prover can send only separable proofs over nodes.

**Definition 8.** On a network G = (V, E), a  $\nu$ -round dQMA<sup>sep,sep</sup> protocol of c(u) qubits proof for  $u \in V$  and m(v, w) qubits communication for  $\{v, w\} \in E$  has completeness a and soundness b for a function  $f : (\{0,1\}^n)^t \to \{0,1\}$  if there exists a  $\nu$ -round quantum verification algorithm with messages of m(v, w) qubits between nodes v and w for  $\{v, w\} \in E$  respectively such that for all the inputs  $(x_1, \ldots, x_t) \in (\{0,1\}^n)^t$ :

- Completeness: if  $f(x_1, \ldots, x_t) = 1$ , then there is a  $(\sum_{u \in V} c(u))$ -qubit proof  $\bigotimes_{u \in V} |\xi_u\rangle$ , where  $|\xi_u\rangle$  is a state on  $\mathcal{H}_u$  for  $u \in V$ , to the nodes such that  $\Pr[all \text{ the nodes accept}] \geq a$ ;
- Soundness: if  $f(x_1, \ldots, x_t) = 0$ , then for any  $(\sum_{u \in V} c(u))$ -qubit proof  $\bigotimes_{u \in V} |\xi_u\rangle$ , where  $|\xi_u\rangle$  is a state on  $\mathcal{H}_u$  for  $u \in V$ ,  $\Pr[all$  the nodes  $accept| \leq b$ .

Note that if a protocol  $\mathcal{P}$  is a dQMA<sup>sep</sup> protocol, then  $\mathcal{P}$  is also a dQMA<sup>sep,sep</sup> protocol from the definitions.

In what follows, a distributed verification protocol is a 1-round one when we do not mention the number of rounds explicitly.

# 3 Improved dQMA protocol for EQ with the permutation test

In this section, we derive a dQMA protocol for the equality function exploiting the property of the permutation test.

# 3.1 Property and application of the permutation test

The permutation test [BBD+97, BCWdW01, KNY08] is a generalization of the SWAP test. In this subsection, we identify the property of the permutation test as a special case of the weak Schur sampling and the generalized phase estimation [Har05, CHW07]. We refer to Section 4.2.2 in [MdW16] for a comprehensive summary. We then apply the property of the permutation test to check how the reduced states on subsystems are close.

First, let us recall the SWAP test. The test is a protocol with a given input state on  $\mathcal{H} = \mathcal{H}_1 \otimes \mathcal{H}_2$ where  $\mathcal{H}_1$  and  $\mathcal{H}_2$  are Hilbert spaces. We here consider  $\mathcal{H}_1$  and  $\mathcal{H}_2$  are corresponding to registers  $R_1$  and  $R_2$ .

# **Algorithm 1** The SWAP test

**Input:**  $\rho \in \mathcal{D}(\mathcal{H}_1 \otimes \mathcal{H}_2)$  on registers  $R_1$  and  $R_2$ .

- 1: Prepare an ancilla qubit and initialize the state with  $|0\rangle$ .
- 2: Apply the Hadamard gate  $H = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}$  on the state and obtain the state  $|+\rangle = \frac{1}{\sqrt{2}} (|0\rangle + |1\rangle)$ .
- 3: Apply the controlled swap  $|0\rangle \langle 0|\otimes I+|1\rangle \langle 1|\otimes SWAP$  where SWAP is defined by SWAP  $|i_1\rangle |i_2\rangle = |i_2\rangle |i_1\rangle$  for  $|i_1\rangle \in \mathcal{B}(\mathcal{H}_1)$  and  $|i_2\rangle \in \mathcal{B}(\mathcal{H}_2)$ .
- 4: Apply the Hadamard gate again on the ancilla qubit and measure it in the computational basis. If the measurement result is |0⟩, the test accepts. Else, it rejects.

It is well known that when pure states  $|\psi_1\rangle$  and  $|\psi_2\rangle$  on  $R_1$  and  $R_2$  are given, the SWAP test accepts with probability  $\frac{1}{2} + \frac{1}{2} |\langle \psi_1 | \psi_2 \rangle|^2$ . In particular, the SWAP test accepts with probability 1 when  $|\psi_1\rangle = |\psi_2\rangle$ .

For completeness, we rewrite the lemmas about the property and application of the SWAP test from [FGNP21], which will be used in Section 3.2. Let  $\mathcal{H}_S^2$  denote the symmetric subspace of  $\mathcal{H}_1 \otimes \mathcal{H}_2$  and let  $\mathcal{H}_A$  denote the anti-symmetric subspace in  $\mathcal{H}_1 \otimes \mathcal{H}_2$ . Note that any state in  $\mathcal{H}_1 \otimes \mathcal{H}_2$  can be represented as a superposition of a state in  $\mathcal{H}_S^2$  and a state in  $\mathcal{H}_A$ , i.e.,  $\mathcal{H}_1 \otimes \mathcal{H}_2 = \mathcal{H}_S^2 \oplus \mathcal{H}_A$  since SWAP is a Hermitian matrix which has only +1 and -1 eigenvalues.

**Lemma 13** (Lemma 4 in [FGNP21]). Assume that  $|\psi\rangle = \alpha |\psi_S\rangle + \beta |\psi_A\rangle$  where  $|\psi_S\rangle \in \mathcal{B}(\mathcal{H}_S^2)$  and  $|\psi_A\rangle \in \mathcal{B}(\mathcal{H}_A)$ . Then, the SWAP test on input  $|\psi\rangle$  accepts with probability  $|\alpha|^2$ .

**Lemma 14** (Lemma 5 in [FGNP21]). Let  $0 \le \epsilon \le 1$ , and assume that the SWAP test on input  $\rho$  in the input register  $(R_1, R_2)$  accepts with probability  $1 - \epsilon$ . Then,  $D(\rho_1, \rho_2) \le 2\sqrt{\epsilon} + \epsilon$ , where  $\rho_j$  is the reduced state on  $R_j$  of  $\rho$ . Moreover, if the SWAP test on input  $\rho$  accepts with probability 1, then  $\rho_1 = \rho_2$  (and hence  $D(\rho_1, \rho_2) = 0$ ).

The SWAP test can be considered as a test to estimate the absolute value of the amplitude in the symmetric subspace of a bipartite system. We will next generalize the test to k-partite systems for any integer k. Let  $S_k$  denote the symmetric group on k elements and define a unitary operator  $U_{\pi}$  which acts by permuting k-partite systems according to  $\pi$  as

$$U_{\pi} |i_1\rangle \cdots |i_k\rangle = |i_{\pi^{-1}(1)}\rangle \cdots |i_{\pi^{-1}(k)}\rangle.$$

Let  $\lambda$  denote a partition of  $\{1, \ldots, k\}$  that corresponds to an irreducible representation (irrep) of  $S_k$ . We denote  $d_{\lambda}$  the dimension of the corresponding irreducible representation  $V_{\lambda}$  of  $S_k$ , which associates a  $d_{\lambda}$ -dimensional square matrix with each permutation  $\pi \in S_k$ . The quantum Fourier transform (QFT) over  $S_k$  is a unitary operator that performs a change of bases from  $\{|\pi\rangle : \pi \in S_k\}$  to  $\{|\lambda, i, j\rangle : 1 \leq i, j \leq d_{\lambda}\}$ . Then, the algorithm of the permutation test can be described as Algorithm 2.

# Algorithm 2 The permutation test

**Input:**  $\rho \in \mathcal{D}(\mathcal{H}_1 \otimes \cdots \otimes \mathcal{H}_k)$  on registers  $R_1, \ldots, R_k$ .

- 1: Prepare a (k!)-dimensional ancilla register whose basis states correspond to  $|\lambda, i, j\rangle$ .
- 2: Initialize the ancilla register in the state  $|(k), 1, 1\rangle$  where (k) is corresponding to the trivial irrep.
- 3: Apply the inverse quantum Fourier transform over  $S_k$  to the ancilla qubits and obtain the state  $\frac{1}{\sqrt{k!}}\sum_{\pi \in S_k} |\pi\rangle$ .
- 4: Apply the controlled permutation  $\sum_{\pi \in S_k} |\pi\rangle \langle \pi| \otimes U_{\pi}$ .
- 5: Apply the quantum Fourier transform over  $S_k$  to the ancilla and measure it in the computational basis.
- 6: If the measurement result of the partition  $\lambda$  is (k), the test accepts. Else, it rejects.

The probability that  $\lambda$  is output is tr( $P_{\lambda}\rho$ ) [BCH06, Har05]. The projector  $P_{\lambda}$  is defined by

$$P_{\lambda} := \frac{d_{\lambda}}{k!} \sum_{\pi \in S_k} \chi_{\lambda}(\pi) U_{\pi},$$

where  $\chi_{\lambda}$  is the corresponding character  $\operatorname{tr}(V_{\lambda})$ . In this paper, we concentrate on the case where  $\lambda$  is the trivial irrep (k) which maps  $\pi \mapsto 1$  for all  $\pi \in S_k$ . In the case,  $d_{\lambda} = 1$  and  $\chi_{\lambda}(\pi) = 1$  for all  $\pi \in S_k$ . Therefore,  $P_{\lambda} = \frac{1}{k!} \sum_{\pi \in S_k} U_{\pi}$ . This is equal to  $\binom{d+k-1}{k} \int d\psi |\psi\rangle^{\otimes k} \langle \psi|^{\otimes k}$ , which is the projector  $\Pi_{\text{sym}}$  to the symmetric subspace  $\mathcal{H}_S^k := \{|\Phi\rangle \in \mathcal{B}((\mathbb{C}^d)^{\otimes k}) : U_{\pi} |\Phi\rangle = |\Phi\rangle\}$ . See e.g., Lemma 1.7 in [Chr06] and Lemma 1 in [Sco06] for the reference of this fact.

The following lemma is an analog of Lemma 13 for the k-partite case using the permutation test. We will denote by  $\mathcal{H}_N$  the orthogonal subspace of  $\mathcal{H}_1 \otimes \cdots \otimes \mathcal{H}_k$  to the symmetric subspace  $\mathcal{H}_S^k$ , i.e.,  $\mathcal{H}_1 \otimes \cdots \otimes \mathcal{H}_k = \mathcal{H}_S^k \oplus \mathcal{H}_N$ .

**Lemma 15.** Assume that  $|\psi\rangle = \Pi_{\text{sym}}(|\psi\rangle) + (I - \Pi_{\text{sym}})(|\psi\rangle) = \alpha |\psi_S\rangle + \beta |\psi_N\rangle$  where  $|\psi_S\rangle \in \mathcal{B}(\mathcal{H}_S^k)$ and  $|\psi_N\rangle \in \mathcal{B}(\mathcal{H}_N)$ . Then, the permutation test on input  $|\psi\rangle$  accepts with probability  $|\alpha|^2$ . In particular, the test accepts with probability 1 if  $|\psi\rangle = |\varphi\rangle^{\otimes k}$  for some  $|\varphi\rangle$ .

The following lemma is also an analog of Lemma 14 for the k-partite case using the permutation test. Note that a similar analysis was first done by Rosgen (Lemma 5.1 in [Ros08]) with the fidelity as a measure between quantum states.

**Lemma 16.** Let  $0 \le \epsilon \le 1$ , and assume the permutation test on input  $\rho$  in the registers  $R_1, \ldots, R_n$ accepts with probability  $1 - \epsilon$ . Then, for any  $i, j \in [n]$ ,  $D(\rho_i, \rho_j) \le 2\sqrt{\epsilon} + \epsilon$  where  $\rho_i$  and  $\rho_j$  are the reduced states of  $R_i$  and  $R_j$  respectively. Moreover, if the permutation test on input  $\rho$  accepts with probability 1, then, for any  $i, j \in [n]$ ,  $\rho_i = \rho_j$  (and hence  $D(\rho_i, \rho_j) = 0$ ).

*Proof.* The mixed state  $\rho$  can be decomposed into an ensemble of pure states as  $\sum_k p_k |\psi_k\rangle \langle \psi_k|$ . In addition, each pure state is a superposition of a state in the symmetric subspace and a state in the orthogonal subspace, namely  $|\psi_k\rangle = \alpha_k |\psi_k^S\rangle + \beta_k |\psi_k^N\rangle$ . By Lemma 15 and the assumption of the acceptance probability,  $\sum_k p_k |\alpha_k|^2 \ge 1 - \epsilon$ . Then,

$$\sum_{k} p_k |\beta_k|^2 \le \epsilon.$$
<sup>(2)</sup>

The state  $\rho$  can be moreover represented as

$$\rho = \sum_{k} p_{k}(|\alpha_{k}|^{2} |\psi_{k}^{S}\rangle \langle \psi_{k}^{S}| + \alpha_{k}\beta_{k}^{*} |\psi_{k}^{S}\rangle \langle \psi_{k}^{N}| + \alpha_{k}^{*}\beta_{k} |\psi_{k}^{N}\rangle \langle \psi_{k}^{S}| + |\beta_{k}|^{2} |\psi_{k}^{N}\rangle \langle \psi_{k}^{N}|).$$

Let us denote  $\psi_k^s = |\psi_k^S\rangle \langle \psi_k^S|$ ,  $\psi_k^{sn} = |\psi_k^S\rangle \langle \psi_k^N|$ ,  $\psi_k^{ns} = |\psi_k^N\rangle \langle \psi_k^S|$  and  $\psi_k^n = |\psi_k^N\rangle \langle \psi_k^N|$ . Using the notations, the subsystems  $\rho_i$  and  $\rho_j$  can be described as follows.

$$\rho_i = \sum_k p_k (|\alpha_k|^2 \operatorname{tr}_{\bar{i}}(\psi_k^s) + \alpha_k \beta_k^* \operatorname{tr}_{\bar{i}}(\psi_k^{sn}) + \alpha_k^* \beta_k \operatorname{tr}_{\bar{i}}(\psi_k^{ns}) + |\beta_k|^2 \operatorname{tr}_{\bar{i}}(\psi_k^n)),$$
  
$$\rho_j = \sum_k p_k (|\alpha_k|^2 \operatorname{tr}_{\bar{j}}(\psi_k^s) + \alpha_k \beta_k^* \operatorname{tr}_{\bar{j}}(\psi_k^{sn}) + \alpha_k^* \beta_k \operatorname{tr}_{\bar{j}}(\psi_k^{ns}) + |\beta_k|^2 \operatorname{tr}_{\bar{j}}(\psi_k^n)).$$

From the definition of the symmetric subspace,  $\operatorname{tr}_{\overline{i}}(\psi_k^s) = \operatorname{tr}_{\overline{i}}(\psi_k^s)$ . We then get

$$\rho_i - \rho_j = \sum_k p_k (\alpha_k \beta_k^* (\operatorname{tr}_{\bar{i}}(\psi_k^{sn}) - \operatorname{tr}_{\bar{j}}(\psi_k^{sn})) + \alpha_k^* \beta_k (\operatorname{tr}_{\bar{i}}(\psi_k^{ns}) - \operatorname{tr}_{\bar{j}}(\psi_k^{ns})) + |\beta_k|^2 (\operatorname{tr}_{\bar{i}}(\psi_k^{n}) - \operatorname{tr}_{\bar{j}}(\psi_k^{n}))).$$

From the positive scalability and the triangle inequality of the trace norm, we obtain

$$D(\rho_{i},\rho_{j}) = \frac{1}{2} \|\rho_{i} - \rho_{j}\|_{1}$$

$$\leq \frac{1}{2} \sum_{k} p_{k}(|\alpha_{k}||\beta_{k}|\|\mathrm{tr}_{\bar{i}}(\psi_{k}^{sn}) - \mathrm{tr}_{\bar{j}}(\psi_{k}^{sn})\|_{1} + |\alpha_{k}||\beta_{k}|\|\mathrm{tr}_{\bar{i}}(\psi_{k}^{ns}) - \mathrm{tr}_{\bar{j}}(\psi_{k}^{ns})\|_{1} + |\beta_{k}|^{2}\|\mathrm{tr}_{\bar{i}}(\psi_{k}^{n}) - \mathrm{tr}_{\bar{j}}(\psi_{k}^{n})\|_{1})$$

Since  $\operatorname{tr}_{\overline{i}}(\psi_k^n)$  and  $\operatorname{tr}_{\overline{j}}(\psi_k^n)$  are quantum states, their trace norms are 1. We thus have

$$\|\operatorname{tr}_{\bar{i}}(\psi_k^n) - \operatorname{tr}_{\bar{j}}(\psi_k^n)\|_1 \le \|\operatorname{tr}_{\bar{i}}(\psi_k^n)\|_1 + \|\operatorname{tr}_{\bar{j}}(\psi_k^n)\|_1 = 1 + 1 = 2.$$

With Lemma 12 and the fact that the fidelity between any quantum states can be bounded by 1,

$$\begin{aligned} \|\operatorname{tr}_{\overline{i}}(\psi_k^{sn})\|_1 &= F(\operatorname{tr}_i(\psi_k^s), \operatorname{tr}_i(\psi_k^n)) \leq 1, \\ \|\operatorname{tr}_{\overline{j}}(\psi_k^{sn})\|_1 &= F(\operatorname{tr}_j(\psi_k^s), \operatorname{tr}_j(\psi_k^n)) \leq 1. \end{aligned}$$

We hence have

$$\|\mathrm{tr}_{\bar{i}}(\psi_k^{sn}) - \mathrm{tr}_{\bar{j}}(\psi_k^{sn})\|_1 \le \|\mathrm{tr}_{\bar{i}}(\psi_k^{sn})\|_1 + \|\mathrm{tr}_{\bar{j}}(\psi_k^{sn})\|_1 = 1 + 1 = 2.$$

A similar argument holds as  $\|\operatorname{tr}_{\overline{i}}(\psi_k^{ns}) - \operatorname{tr}_{\overline{j}}(\psi_k^{ns})\|_1 \leq 2$ . Therefore, we have

$$D(\rho_i, \rho_j) \le \sum_k p_k 2|\alpha_k| |\beta_k| + \sum_k p_k |\beta_k|^2.$$

From Eq. (2), the Cauchy-Schwarz inequality and  $|\alpha_k| \leq 1$ ,

$$\sum_{k} p_{k} 2|\alpha_{k}||\beta_{k}| + \sum_{j} p_{k}|\beta_{k}|^{2} \leq 2\sum_{k} p_{k}|\beta_{k}| + \epsilon$$

$$= 2\sum_{k} \sqrt{p_{k}} \sqrt{p_{k}}|\beta_{k}| + \epsilon$$

$$\leq 2\left(\sum_{k} p_{k}\right)^{\frac{1}{2}} \left(\sum_{k} p_{k}|\beta_{k}|^{2}\right)^{\frac{1}{2}} + \epsilon$$

$$\leq 2\sqrt{\epsilon} + \epsilon,$$

which concludes the proof.

## 3.2 Protocol on paths

In this subsection, we focus on the case where the verifier  $v_0, \ldots, v_r$  are arranged in a row and the two extremities  $v_0$  and  $v_r$  have inputs. Let  $x \in \{0,1\}^n$  be the input string owned by  $v_0$ , and  $y \in \{0,1\}^n$  be the input string owned by  $v_r$ . We are going to derive a dQMA protocol for the equality function EQ.

Our dQMA protocol  $\mathcal{P}_{\pi}$  is described in Algorithm 3 (recall that  $\pi$ ,  $|h_x\rangle$ , and  $\{M_{y,1}, M_{y,0}\}$  are defined in Section 2.2.1).

**Algorithm 3** Protocol  $\mathcal{P}_{\pi}$  for EQ on an input pair (x, y) in a path  $v_0, \ldots, v_r$ 

- 1: The prover sends two  $c \log n$ -qubit registers  $R_{j,0}, R_{j,1}$  to each of the intermediate nodes  $v_j$  for  $j \in \{1, \ldots, r-1\}$ .
- 2: The left-end node  $v_0$  prepares the state  $\rho_0 = |h_x\rangle \langle h_x|$  in the register  $R_0$  by itself, and sends  $R_0$  to the right neighbor  $v_1$ .
- 3: Each intermediate node  $v_j$  swaps the states between  $R_{j,0}$  and  $R_{j,1}$  with probability  $\frac{1}{2}$ , i.e., symmetrizes the states on  $R_{j,0}$  and  $R_{j,1}$ .
- 4: Each intermediate node  $v_j$  sends  $R_{j,1}$  to the right neighbor  $v_{j+1}$ .
- 5: Each intermediate node  $v_j$  receives  $R_{j-1,1}$  from its left neighbor  $v_{j-1}$ . Then  $v_j$  performs the SWAP test on the registers  $(R_{j-1,1}, R_{j,0})$  and accepts or rejects accordingly.
- 6: The right-end node  $v_r$  receives  $R_{r-1,1}$  from its left neighbor  $v_{r-1}$ . Then,  $v_r$  performs the POVM measurement  $\{M_{y,0}, M_{y,1}\}$  corresponding to  $\pi$  applied to the state  $R_{r-1,1}$  and accepts or rejects accordingly.

| - |  |   |
|---|--|---|
|   |  | L |
|   |  | L |
|   |  | L |
|   |  |   |

In the above protocol  $\mathcal{P}_{\pi}$ , the size of the quantum proof that each node receives from the prover is  $2c \log n$ , and the length of the quantum message that each node sends to the neighbor is  $c \log n$ . We next show that the above protocol has perfect completeness and soundness  $\frac{4}{81r^2}$ .

#### Completeness

Let us assume inputs x and y are satisfying EQ(x, y) = 1, i.e., x = y. The prover sends  $|h_x\rangle |h_x\rangle$  to all the intermediate nodes. In step 3, as the state is already symmetric, the state does not change by the symmetrization. Therefore, in step 5, all the SWAP tests accept with certainty. Furthermore, the right end node  $v_r$  accepts with certainty. Then, from the definition of completeness, the protocol has perfect completeness.

#### Soundness

Let us assume inputs x and y are satisfying EQ(x, y) = 0, i.e.,  $x \neq y$ . Then, the following lemma holds.

**Lemma 17.** For  $j \in \{1, ..., r\}$ , let  $E_j$  be the event that the local test  $v_j$  performs (the SWAP test or the POVM measurement) accepts. Then,  $\sum_{j=1}^{r} \Pr[\neg E_j] \ge \frac{4}{81r}$ .

*Proof.* For conciseness, let us denote  $p_j = \Pr[\neg E_j]$ . By Lemma 14, the trace distance between the reduced states  $\rho_{j-1,1}$  on  $R_{j-1,1}$  and  $\rho_{j,0}$  on  $R_{j,0}$  can be bounded as

$$D(\rho_{j-1,1}, \rho_{j,0}) \le 2\sqrt{p_j} + p_j.$$

We thus have  $D(\rho_{j-1,1}, \rho_{j,0}) \leq 3\sqrt{p_j}$ . By the symmetrization step of the protocol,  $\rho_{j,0} = \rho_{j,1}$  for  $j = 1, \ldots, r-1$ . Therefore, with the triangle inequality of the trace norm, we have

$$D(\rho_0, \rho_{r-1,1}) \le 3\sum_{j=1}^{r-1} \sqrt{p_j}$$

From the assumption of the soundness,  $tr(M_{y,0}\rho_0) \geq \frac{2}{3}$ . Then, by the linearity of the trace and the property of the trace norm, an inequality follows as

$$p_r = \operatorname{tr}(M_{y,0}\rho_{r-1,1}) = \operatorname{tr}(M_{y,0}\rho_0) - \operatorname{tr}(M_{y,0}(\rho_0 - \rho_{r-1,1})) \ge \frac{2}{3} - \|\rho_0 - \rho_{r-1,1}\|_1 \ge \frac{2}{3} - 3\sum_{j=1}^{r-1}\sqrt{p_j}.$$

Since  $0 \le p_j \le 1$ , we have

$$3\sum_{j=1}^{r}\sqrt{p_j} = 3\sqrt{p_r} + 3\sum_{j=1}^{r-1}\sqrt{p_j} \ge \sqrt{p_r} + 3\sum_{j=1}^{r-1}\sqrt{p_j} \ge p_r + 3\sum_{j=1}^{r-1}\sqrt{p_j} \ge \frac{2}{3}$$

From the Cauchy-Schwarz inequality, we get

$$\sqrt{r}\sqrt{\sum_{j=1}^r p_j} \ge \sum_{j=1}^r \sqrt{p_j}.$$

We thus conclude

$$\sum_{j=1}^{r} p_j \ge \left(\frac{1}{\sqrt{r}} \sum_{j=1}^{r} \sqrt{p_j}\right)^2 \ge \left(\frac{2}{3 \cdot 3\sqrt{r}}\right)^2 = \frac{4}{81r}$$

as claimed.

By Lemma 11, we have

$$\Pr[\neg E_1 \lor \neg E_2 \lor \cdots \lor \neg E_r] \ge \frac{1}{r} \sum_{j=1}^r \Pr[\neg E_j].$$
$$\ge \frac{4}{81r^2},$$

which implies that the protocol  $\mathcal{P}_{\pi}$  has soundness  $1 - \frac{4}{81r^2}$ .

#### Full protocol

Let us consider a k-times repetition of the protocol  $\mathcal{P}_{\pi}$  to reduce the soundness error which is a standard technique for QMA as in [AN02, KSV02]. The protocol  $\mathcal{P}_{\pi}[k]$  described in Algorithm 4 has soundness  $(1 - \frac{4}{81r^2})^k$ . Let us set  $k = \lceil 2\frac{81r^2}{4} \rceil$  and then the protocol has soundness  $(\frac{1}{e})^2 < \frac{1}{3}$ . The proof size is  $O(r^2 \log n)$  qubits for each node and the communication amount between nodes is  $O(r^2 \log n)$  respectively.

# Algorithm 4 Protocol $\mathcal{P}_{\pi}[k]$

- 1: The prover sends 2k quantum registers  $R_{j,0,i}, R_{j,1,i}$  for  $i \in \{1, \ldots, k\}$ , which are  $c \log n$  qubits respectively, as proofs to each of the intermediate nodes  $v_j$  for  $j \in \{1, \ldots, r-1\}$ .
- 2: The left-end node  $v_0$  prepares k states  $(|h_x\rangle \langle h_x|)^{\otimes k}$  in the registers  $R_{0,1,i}$  for  $i \in \{1, \ldots, k\}$  by itself. Then  $v_0$  sends their registers to  $v_1$ .
- 3: Each intermediate node  $v_j$  swaps the states between  $R_{j,0,i}$  and  $R_{j,1,i}$  with probability  $\frac{1}{2}$ , i.e., symmetrizes the states on  $R_{j,0,i}$  and  $R_{j,1,i}$ .
- 4: Each intermediate node  $v_j$  sends  $R_{j,1,i}$  to the right neighbor  $v_{j+1}$  for all  $i \in \{1, \ldots, k\}$ .
- 5: Each intermediate node  $v_j$  receives k quantum registers  $R_{j-1,1,i}$  from its left neighbor  $v_{j-1}$ . Then  $v_j$  performs the SWAP test on the registers  $(R_{j-1,1,i}, R_{j,0,i})$  for each  $i \in \{1, \ldots, k\}$ . The node  $v_j$  rejects if at least one of the performed SWAP tests rejects, and accepts otherwise.
- 6: The right-end node  $v_r$  receives k registers  $R_{r-1,1,i}$  from its left neighbor. Then,  $v_r$  performs the POVM measurement  $\{M_{y,0}, M_{y,1}\}$  corresponding to  $\pi$  applied to the states  $R_{r-1,1,i}$ . The node  $v_r$  rejects if at least one of the performed POVM measurements rejects, and accepts otherwise.

#### 3.3 Protocol on general graphs

Let G = (V, E) be a network of radius r with terminals  $u_1, \ldots, u_t$ . Let us assume, without loss of generality, that  $u_1$  is the most central node among them, i.e., it satisfies  $\max_{i=1,\ldots,t} \operatorname{dist}_G(u_1, u_i) = \min_{j=1,\ldots,t} \max_{i=1,\ldots,t} \operatorname{dist}_G(u_j, u_i)$ . Let us construct a tree T rooted at  $u_1$ , with the other terminals as leaves, maximum degree t, and depth at most r + 1. To do this, we start with the breadth-first search from  $u_i$  and find a tree T'. Then, we truncate T' at each terminal  $u_i$  that does not have any terminal as successors, which limits the depth of the tree to r and the maximum degree to t.

For every terminal  $u_i$  that is not a leaf, replace  $u_i$  and connect  $u_i$  to  $u'_i$  as a leaf, where  $u_i$  keeps the input  $x_i$ . By this construction, we ensure all the terminals have degree 1 and the depth can be increased by at most 1. See Figure 1 in [FGNP21] for an illustration of the construction. Any protocol of  $u_i$  and  $u'_i$  over T is simulated on the node  $u_i$  over T', which does not affect the soundness and completeness of dMA and dQMA protocols from their definitions.

It is also known that there exists a deterministic dMA protocol that checks if a tree T satisfies the condition.

**Lemma 18** ([Pel00, KKP10]). For any network G = (V, E) with nodes IDs taken in a range polynomial in |V|, there is a deterministic dMA protocol (i.e., with completeness 1 and soundness 0) for the tree T using a proof of  $O(\log |V|)$  bits for each node.

Based on the tree construction and the deterministic dMA protocol above, we can focus on a protocol over the tree T since if any malicious prover tells a fake tree construction over nodes, at least one node can detect it with certainty.

Now we present a dQMA protocol for the equality function  $\mathsf{EQ}_n^t$ , which is a function from  $(\{0,1\}^n)^t$  to  $\{0,1\}$  defined as  $\mathsf{EQ}_n^t(x_1,\ldots,x_t) = 1$  if  $x_1 = \cdots = x_t$  and 0 otherwise.

**Theorem 19.** There exists a dQMA protocol for  $EQ_n^t$  on a network G of radius r with perfect completeness and soundness  $\frac{1}{3}$ , using local proof and message of size  $O(r^2 \log n)$ .

*Proof.* Our protocol assuming a spanning tree T rooted at  $u_1$  guaranteed by Lemma 18 is described as Algorithm 5.

**Algorithm 5** Protocol  $\mathcal{P}(\mathsf{EQ}_n^t)$  on a spanning tree T

- 1: The prover sends two  $c \log n$ -qubit states in registers  $R_{v,0}$  and  $R_{v,1}$  to each of the nodes v which has no input. Then, v symmetrizes the two  $c \log n$ -qubit states on  $R_{v,0}$  and  $R_{v,1}$ .
- 2: For every  $i \in \{1, \ldots, t\}$ , the node  $u_i$  prepares the  $c \log n$ -qubit state  $|h_{x_i}\rangle$  in register  $R_{u_i,1}$ .
- 3: Every non-root node v of the tree sends its  $c \log n$ -qubit state in  $R_{v,1}$  to its parent in T.
- 4: Every non-terminal node v receives some  $c \log n$ -qubit states from the children. Then, it performs the permutation test on states that consist of the  $c \log n$ -qubit state received from the prover and the  $c \log n$ -qubit states received from the children. Then, it accepts or rejects accordingly.
- 5: The root node  $u_1$  receives some  $c \log n$ -qubit states form its children. Then  $u_1$  performs the permutation test on the state that consist of  $|h_{x_1}\rangle$  and the states from the children. Then, accept or reject accordingly.

The perfect completeness follows from Lemma 15 since fingerprints  $|h_{x_i}\rangle$  for  $i = 1, \ldots, t$  are the same. For the soundness, let us assume  $\mathsf{EQ}_n^t(x_1, \ldots, x_t) = 0$ , i.e., there is a leaf  $u_i$  whose input  $x_i$  is not equal to  $x_1$ . Then, a similar analysis holds as in Section 3.2 for the path connecting  $u_1$  and  $u_i$ . This is because the analysis of Lemma 17 holds even if some of the nodes on the path conduct the permutation test instead of the SWAP test due to Lemma 16. Therefore,  $\mathcal{P}(\mathsf{EQ}_n^t)$  has soundness  $1 - O(\frac{1}{r^2})$ . By the parallel  $O(r^2)$  repetitions of  $\mathcal{P}(\mathsf{EQ}_n^t)$  similar to the protocol  $\mathcal{P}_{\pi}$ , the soundness error can be reduced to  $\frac{1}{3}$  and thus the proof of Theorem 19 is completed.

Finally, we can combine the technique to replace quantum communication with classical communication by [GMN23a] with our result. If the communication at the verification stage (i.e., the communication among the nodes) of a dQMA protocol is classical, [GMN23a] named it an LOCC (Local Operation and Classical Communication) dQMA protocol. In [GMN23a], the following result was obtained.

**Lemma 20** (Theorem 5 in [GMN23a]). For any constant  $p_c$  and  $p_s$  such that  $0 \le p_s < p_c \le 1$ , let  $\mathcal{P}$  be a dQMA protocol for some problem on a network G with completeness  $p_c$ , soundness  $p_s$ , local proof size  $s_c^{\mathcal{P}}$  and local message size  $s_m^{\mathcal{P}}$ . For any small enough constant  $\gamma > 0$ , there exists an LOCC dQMA protocol  $\mathcal{P}'$  for the same problem on G with completeness  $p_c$ , soundness  $p_s + \gamma$ , local proof size  $s_c^{\mathcal{P}} + O(d_{max} s_m^{\mathcal{P}} s_{tm}^{\mathcal{P}})$ , and local message size  $O(s_m^{\mathcal{P}} s_{tm}^{\mathcal{P}})$ , where  $d_{max}$  is the maximum degree of G, and  $s_{tm}^{\mathcal{P}}$  is the total number of qubits sent in the verification stage of  $\mathcal{P}$ .

Theorem 19 and Lemma 20 lead to the following corollary, which shows a more efficient LOCC dQMA protocol for the equality function than Corollary 1 in [GMN23a].

**Corollary 21.** For any small constant  $\epsilon > 0$ , there is an LOCC dQMA protocol for EQ<sup>t</sup><sub>n</sub> on a network G = (V, E) of radius r with completeness 1, soundness  $\epsilon$ , local proof size  $O(d_{max}|V|r^4 \log^2(n))$ and message size  $O(|V|r^4 \log^2(n))$ .

# 4 Robust quantum advantage for EQ on a path

In this section, we consider the path  $v_0, \ldots, v_r$  as a network topology, and  $v_0$  and  $v_r$  have *n*-bit input strings x and y, respectively. We will show that a quantum advantage of distributed verification protocols for the equality problem (EQ) still persists even when the size of the network r is not so small compared with the size of the inputs n.

#### 4.1 Quantum upper bound

In this subsection, we give a dQMA protocol that is efficient even when the network size is not small.

**Theorem 22.** There exists a dQMA protocol to solve EQ on the path of length r with total proof size  $\sum_i c(v_i) = \tilde{O}(rn^{\frac{2}{3}})$ , perfect completeness and soundness  $\frac{1}{3}$ .

*Proof.* Let us denote by S a set of nodes such that the indexes can be divided by  $\lceil n^{\frac{1}{3}} \rceil$ , i.e.,  $S = \left\{ v_{\lceil n^{\frac{1}{3}} \rceil}, v_{2\lceil n^{\frac{1}{3}} \rceil}, \dots, v_{\lfloor \frac{r}{\lceil n^{\frac{1}{3}} \rceil} \rfloor \lceil n^{\frac{1}{3}} \rceil} \right\}$ . Let us call nodes of S relay points. Then, the protocol can

be described as Algorithm 6.

The total size of the proof is

$$O(n^{\frac{2}{3}}\log n) \times (\lceil n^{\frac{1}{3}} \rceil - 1) \times \left(\frac{r}{\lceil n^{\frac{1}{3}} \rceil} + 1\right) + n \times \left\lfloor \frac{r}{\lceil n^{\frac{1}{3}} \rceil} \right\rfloor = \tilde{O}(rn^{\frac{2}{3}}).$$

To show completeness, let us assume x = y. Then, when the proofs for  $v_i \in S$  are  $|x\rangle$  and the proofs for  $v_i \notin S$  are  $|h_x\rangle^{\otimes 42(\lceil n^{\frac{1}{3}} \rceil)^2}$ , all the SWAP tests accept. To show soundness, let us assume  $x \neq y$ . Then, for any quantum proof, *n*-bit measurement results of at least one adjacent pair of the relay points differ. Then, between the two relay points, at least one node outputs reject from the soundness of the protocol  $\mathcal{P}_{\pi}[42r^2]$  in Algorithm 4 with probability  $\frac{2}{3}$  as claimed.

# Algorithm 6 Protocol for EQ with "relay points"

- 1: The prover sends an *n*-qubit state to the relay points  $v_i \in S$ .
- 2: The prover sends two  $42(\lceil (n^{\frac{1}{3}})\rceil)^2 c \log n$ -qubit states to each of the intermediate nodes  $v_i \notin S$ . Then, the nodes symmetrize the states.
- 3: On the relay points, the node  $v_i \in S$  measures the proof in the computational basis. Based on the *n*-bit measurement results, the nodes create  $2 \times 42(\lceil n^{\frac{1}{3}} \rceil)^2$  fingerprints (see Section 2.2.1 for a formal definition of the quantum fingerprints).
- 4: The left-end node creates  $42(\lceil n^{\frac{1}{3}}\rceil)^2$  fingerprints  $|h_x\rangle$ . The right-end node creates  $42(\lceil n^{\frac{1}{3}}\rceil)^2$  fingerprints  $|h_y\rangle$ .
- 5: Each node except the right-end node sends a  $42(\lceil n^{\frac{1}{3}}\rceil)^2 c \log n$ -qubit state to the right neighbor. Then, each node except the left-end node conducts the SWAP test  $42(\lceil n^{\frac{1}{3}}\rceil)^2$  times on the own fingerprints and the fingerprints from the left neighbor. If even at least one the SWAP test rejects, each node rejects. Otherwise, each node accepts.

### 4.2 Classical lower bound

In this subsection, we show that a stronger lower bound of the proof size of dMA protocols with 1-round verification for EQ.

Let us first show that a linear size proof is required for each local 2 nodes. This is a corollary of Theorem 9 in [FGNP21] but we give a proof for completeness.

**Lemma 23.** Let f(x, y) be any Boolean function with a 1-fooling set of size at least k. Let  $\mathcal{P}$  be a dMA protocol for f on the path of length r, with  $\nu$ -round of communication among the nodes, shared randomness. Suppose that the proof of size satisfying  $\sum_{j=i-\nu+1}^{i+\nu} c(v_j) = \lfloor \frac{1}{2} \log(k-1) \rfloor$  bits for  $i \in [\nu, r - \nu - 1]$ , and  $\mathcal{P}$  has completeness 1 - p. Then,  $\mathcal{P}$  has soundness error at least 1 - 2p.

*Proof.* For conciseness, we show only the case that  $\mathcal{P}$  is a 1-round communication protocol (we can easily modify the following proof to the  $\nu$ -round case). Since f has a large 1-fooling set and the proof size is small, there exist two distinct pairs of fooling inputs that have the same assignment of proofs on  $v_i$  and  $v_{i+1}$ . Let us fix such two inputs pairs (x, y) and (x', y') such that f(x, y) = f(x', y') = 1 and f(x, y') = 0 with corresponding assignment of proofs w and w' such that  $w(v_i) = w'(v_i)$  and  $w(v_{i+1}) = w'(v_{i+1})$ , where  $w(v_j)$  is the  $v_j$ 's part of w.

We denote by  $\operatorname{out}_i(x, y, w)$  the output of  $v_i$  when the inputs are x and y and the proof assignment is w. Since  $\mathcal{P}$  has completeness 1 - p, we have

$$\Pr_s \big[ \bigwedge_{j:j \leq i} \mathsf{out}_j(x,y,w) = 1 \land \bigwedge_{j:j \geq i+1} \mathsf{out}_j(x,y,w) = 1 \big] \geq 1-p,$$

where s denotes the random string taken in  $\mathcal{P}$ . The same holds for (x', y', w'). Hence,

$$\Pr_{s} \left[ \bigwedge_{j:j \leq i} \operatorname{out}_{j}(x, y, w) = 1 \right] \geq 1 - p,$$
  
$$\Pr_{s} \left[ \bigwedge_{j:j \geq i+1} \operatorname{out}_{j}(x', y', w') = 1 \right] \geq 1 - p.$$

Let w'' be the proof assignment defined by  $w''(v_j) = w(v_j)$  for  $j \in [0, i-1]$ ,  $w''(v_j) = w(v_j) = w'(v_j)$ for j = i, i+1 and  $w''(v_j) = w'(v_j)$  for  $j \in [i+2, r]$ . Consider the input assignment (x, y') combined with the proof assignment w''. Then, the nodes  $v_j$  for  $j \leq i$  receive the same partial inputs and proof when the total inputs and proof are (x, y', w'') and (x, y, w) and the nodes  $v_j$  for  $j \geq i + 1$  receive the same partial inputs and proof when the total inputs and proof are (x, y', w'') and (x', y', w'). Therefore, by a union bound, we have

$$\begin{split} &\Pr_{s}\left[\bigwedge_{j:j\leq i}\operatorname{out}_{j}(x,y',w'')=1\wedge\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(x,y',w'')=1\right]\\ &\geq 1-\Pr_{s}\left[\neg\bigwedge_{j:j\leq i}\operatorname{out}_{j}(x,y',w'')=1\right]-\Pr_{s}\left[\neg\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(x',y',w'')=1\right]\\ &= 1-\Pr_{s}\left[\neg\bigwedge_{j:j\leq i}\operatorname{out}_{j}(x,y,w)=1\right]-\Pr_{s}\left[\neg\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(x',y',w')=1\right]\\ &\geq 1-2p, \end{split}$$

which implies the soundness error is at least 1 - 2p.

**Proposition 24.** Let f(x, y) be any Boolean function with a 1-fooling set of size at least k. Let  $\mathcal{P}$  be a dMA protocol for f on the path of length r, with  $\nu$ -round of communication among the nodes, shared randomness, total proof size  $\sum_{j=0}^{r} c(v_j) \leq \lfloor \frac{r-1}{2\nu} \rfloor \lfloor \frac{1}{2} \log(k-1) \rfloor$ , and completeness 1 - p. Then,  $\mathcal{P}$  has soundness error at least 1 - 2p.

*Proof.* By the pigeonhole principle, there exists  $i \in [\nu, r-\nu-1]$  such that  $\sum_{j=i}^{i+1} c(v_j) \leq \lfloor \frac{1}{2} \log(k-1) \rfloor$ . Then, Lemma 23, the protocol  $\mathcal{P}$  has soundness error at least 1-2p.

Since EQ has a 1-fooling set of size  $2^n$ , the corollary below directly follows from Proposition 24.

**Corollary 25.** Let  $\mathcal{P}$  be any dMA protocol for EQ with  $\nu$ -round of communication between the nodes on the path of length r with total proof size  $\sum_{j=0}^{r} c(v_j) \leq \lfloor \frac{r-1}{2\nu} \rfloor \lfloor \frac{1}{2}(n-1) \rfloor$ , and completeness 1-p. Then,  $\mathcal{P}$  has soundness error at least 1-2p.

Corollary 25 implies that any dMA protocol with constant-round, sufficiently high completeness and low soundness error has to receive  $\Omega(rn)$  bits as proofs in total.

# 5 Protocol for comparing the values of inputs

In this section, we give dQMA protocols to compare the values of inputs regarded as integers.

#### 5.1 Protocol for the greater-than problem

In this subsection, we construct an efficient dQMA protocol for the greater-than function (GT).

The function  $\mathsf{GT}: \{0, 1, \dots, 2^n - 1\} \times \{0, 1, \dots, 2^n - 1\} \rightarrow \{0, 1\}$  is defined as  $\mathsf{GT}(x, y) = 1$  if and only if x > y. We identify

$$x = x_0 \times 2^{n-1} + x_1 \times 2^{n-2} + \dots + x_{n-2} \times 2^1 + x_{n-1} \times 2^0,$$
  

$$y = y_0 \times 2^{n-1} + y_1 \times 2^{n-2} + \dots + y_{n-2} \times 2^1 + y_{n-1} \times 2^0$$

by the *n*-bit strings  $x = x_0 x_1 \cdots x_{n-2} x_{n-1}$  and  $y = y_0 y_1 \cdots y_{n-2} y_{n-1}$ .

We first observe GT(x, y) = 1 if and only if there exists an index  $i \in [0, n-1]$  such that  $x_i = 1$ ,  $y_i = 0$  and x[i] = y[i], where  $x[i] := x_0 \cdots x_{i-1}$  and  $y[i] := y_0 \cdots y_{i-1}$ . Then, we construct a dQMA protocol for GT using the protocol for EQ as a subroutine.

**Theorem 26.** There exists a dQMA protocol for GT on the path of length r with perfect completeness and soundness  $\frac{1}{3}$ , using local proof and message of size  $O(r^2 \log n)$ .

*Proof.* The protocol before the parallel repetition can be described in Algorithm 7.

**Algorithm 7** Protocol for GT on an input pair (x, y) in a path  $v_0, \ldots, v_r$ 

- 1: The prover sends two  $O(\log n)$ -qubit registers  $R_{j,0}, R_{j,1}$  called fingerprint registers to each of the intermediate nodes  $v_j$  for  $j \in \{1, \ldots, r-1\}$ . The prover also sends a  $\lceil \log n \rceil$ -qubit register, called an index register, to each of all the nodes.
- 2: The node  $v_0$  measures the index register in the computational basis and let us denote by  $i_0 \in \{0,1\}^{\lceil \log n \rceil}$  the measurement result. If  $x_{i_0} = 0$ ,  $v_0$  rejects. Then,  $v_0$  prepares the state  $\rho_0 = |h_{x[i_0]}\rangle \langle h_{x[i_0]}|$  in register  $R_0$  as the fingerprint of the binary string  $x[i_0] := x_0 \cdots x_{i_0-1}$ . If  $i_0 = 0$ , it prepares  $|\perp\rangle$ .
- 3: Each intermediate node  $v_j$  measures the index register in the computational basis. It also swaps the states between  $R_{j,0}$  and  $R_{j,1}$  with probability  $\frac{1}{2}$ , i.e., symmetrizes the states on  $R_{j,0}$  and  $R_{j,1}$ .
- 4: The node  $v_r$  measures the index register in the computational basis and let us denote by  $i_r \in \{0,1\}^{\lceil \log n \rceil}$  the measurement result. If  $y_{i_r} = 1$ ,  $v_r$  rejects. Then,  $v_r$  prepares the state  $\rho_r = |h_{y[i_r]}\rangle \langle h_{y[i_r]}|$  in register  $R_r$  as the fingerprint of the binary string  $y[i_r] := y_0 \cdots y_{i_r-1}$ . If  $i_r = 0$ , it prepares  $|\perp\rangle$ .
- 5: The node  $v_0$  sends  $R_0$  and a register  $R'_0$  that encodes the measurement result of the index register to the right neighbor  $v_1$ . Each intermediate node  $v_j$  sends  $R_{j,1}$  and a register  $R'_j$  that encodes the measurement result of the index register to the right neighbor  $v_{j+1}$ .
- 6: Each intermediate node  $v_j$  receives  $R_{j-1,1}$  from its left neighbor  $v_{j-1}$ . The node  $v_j$  also receives  $R'_{j-1}$  from  $v_{j-1}$  and measures them in the computational basis to check if the measurement result is the same as the own index register or not. If they are different,  $v_j$  rejects. Otherwise,  $v_j$  performs the SWAP test on the registers  $(R_{j-1,1}, R_{j,0})$  and accepts or rejects accordingly.
- 7: The node  $v_r$  receives  $R_{r-1,1}$  and  $R'_{r-1}$  from its left neighbor  $v_{r-1}$ . Then,  $v_r$  measures  $R'_{r-1}$  in the computational basis and checks if the measurement result is the same as the own index register. If they are different,  $v_r$  rejects. Otherwise,  $v_r$  performs the SWAP test on  $(R_{r-1,1}, R_r)$ , and accepts or rejects accordingly.

### Completeness

Let us assume GT(x, y) = 1, i.e., x > y. Then, there exists an index *i* such that  $x_i = 1$ ,  $y_i = 0$ , and x[i] = y[i]. To achieve perfect completeness, the honest prover can send the index *i* in the index register and  $|h_{x[i]}\rangle = |h_{y[i]}\rangle$  in the fingerprint register to all the nodes. If i = 0, the prover sends the index 0 in the index register and  $|\bot\rangle$  in the fingerprint register. Then, all the nodes accept since  $x_i = 1$ ,  $y_i = 0$ , and all the index comparisons and the SWAP tests are accepted.

#### Soundness

From the index comparisons in the protocol, the prover must send the same index in all the index registers to maximize the acceptance probability. Thus we assume the prover sends the same index i in all the index registers.

Let us assume  $\mathsf{GT}(x, y) = 0$ , i.e.,  $x \leq y$ . If  $x_i = 0$  or  $y_i = 1$ ,  $v_0$  or  $v_r$  rejects. Thus the prover must choose *i* such that  $x_i = 1$  and  $y_i = 0$ . Then  $x[i] \neq y[i]$  as otherwise x > y, which contradicts  $\mathsf{GT}(x, y) = 0$ . (Note that when i = 0,  $x_0 = 0$  or  $y_0 = 1$  holds from  $x \leq y$  and thus  $v_0$  or  $v_r$  rejects. Hence we can assume  $i \geq 1$ .) Then, by the soundness analysis of the dQMA protocol for EQ, at least one node rejects with probability  $O(\frac{1}{r^2})$ .

By the parallel repetition of Algorithm 7 with  $O(r^2)$  times, the protocol has a sufficiently low constant soundness error. This completes the proof.

Since the size of the 1-fooling set of GT is  $2^n$ , a lower bound of dMA protocols can be shown from Proposition 24.

**Corollary 27.** Let  $\mathcal{P}$  be any  $\nu$ -round dMA protocol for GT on the path of length r with total proof size  $\sum_{j=0}^{r} c(v_j) \leq \lfloor \frac{r-1}{2\nu} \rfloor \lfloor \frac{1}{2}(n-1) \rfloor$  and completeness 1-p. Then,  $\mathcal{P}$  has soundness error at least 1-2p.

We can define three functions from  $\{0, 1, \ldots, 2^n - 1\} \times \{0, 1, \ldots, 2^n - 1\}$  to  $\{0, 1\}$ ,  $\mathsf{GT}_{<}$ ,  $\mathsf{GT}_{\geq}$ , and  $\mathsf{GT}_{\leq}$  as follows:  $\mathsf{GT}_{<}(x, y) = 1$  iff x < y,  $\mathsf{GT}_{\geq}(x, y) = 1$  iff  $x \ge y$ , and  $\mathsf{GT}_{\leq}(x, y) = 1$  iff  $x \le y$ .<sup>2</sup> By modifying our protocol for  $\mathsf{GT}$ , we also obtain dQMA protocols for these functions.

**Corollary 28.** There are dQMA protocols for  $GT_{\leq}$ ,  $GT_{\geq}$ , and  $GT_{\leq}$  on the path of length r with perfect completeness and soundness  $\frac{1}{3}$  and using local proof and message of size  $O(r^2 \log n)$ .

#### 5.2 Application for ranking verification

In this subsection, we apply the dQMA protocol for GT for verifying the ranking of a terminal in a network.

Let us define the ranking verification problem, which asks whether the input  $x_i$  of the *i*-th terminal is the *j*-the largest over all the inputs over the network.

**Definition 9** (ranking verification). For  $i, j \in [1, t]$ ,  $\mathsf{RV}_{t,n}^{i,j}(x_1, \ldots, x_t) = 1$  if and only if

$$\sum_{k \in [1,t] \setminus \{i\}} \mathsf{GT}_{\geq}(x_i, x_k) = t - j + 1.$$

By running the dQMA protocol for  $GT_{\geq}$  (and  $GT_{<}$ ) in parallel on a spanning tree rooted at  $u_i$ , we obtain a dQMA protocol for RV.

**Theorem 29.** For  $i, j \in [1, t]$ , there exists a dQMA protocol for  $\mathsf{RV}_{t,n}^{i,j}$  with t terminals and radius r, with perfect completeness and soundness  $\frac{1}{3}$ , using local proof and message size  $O(tr^2 \log n)$ .

*Proof.* Let  $u_1, \ldots, u_t$  be the t terminals where  $x_k$  is owned by  $u_k$ . The protocol is described as Algorithm 8.

 $<sup>^{2}</sup>GT$  can be regarded as  $GT_{>}$  in this notation.

# **Algorithm 8** Protocol for $\mathsf{RV}_{t,n}^{i,j}$

- 1: An honest prover tells a spanning tree T whose root is  $u_i$  and leaves are the other terminals.
- 2: For every leaf terminal  $u_k$  and every node on the path between  $u_i$  and  $u_k$  in T, a 1-qubit register called a direction register is sent from the prover, where 0 and 1 in the direction register represent " $\geq$ " (which means  $x_i \geq x_k$ ) and "<" (which means  $x_i < x_k$ ), respectively. Moreover, the prover sends a proof  $\rho$  to the nodes on the path according to the protocol for  $\mathsf{GT}_>$  (when  $x_i \geq x_k$ ) or  $\mathsf{GT}_<$  (when  $x_i < x_k$ ).
- 3: For the node  $u_i$  and each of the other terminals  $u_k$ , the following steps are done: (i) Check whether all the contents of the direction registers on the path between  $u_i$  and  $u_k$  are the same or not using 1-bit information obtained by measuring each direction register in the computational basis. (ii) If all the contents are " $\geq$ " (resp. "<"), the nodes on the path conduct the protocol for  $\mathsf{GT}_>$  (resp.  $\mathsf{GT}_<$ ) using the proof  $\rho$  from the prover.
- 4: The root node  $v_i$  counts the number of " $\geq$ " in the t-1 direction registers from the prover, and rejects if  $\sum_{k \in [1,t] \setminus \{i\}} \mathsf{GT}_{\geq}(x_i, x_k) \neq t-j+1$ . Otherwise,  $v_i$  accepts.

The local proof and message sizes are  $O(tr^2 \log n)$  as every node receives at most t-1 fingerprint registers whose size is guaranteed by Corollary 28.

In the following analysis, we can assume that all nodes on the path between  $u_1$  and any leaf  $u_k$  receive the same direction ( $\geq$  or <) in the direction registers as otherwise the prover is rejected with probability 1.

The completeness holds because the honest prover can send the true direction for each path, namely,  $\geq$  (resp. <) is chosen when  $x_i \geq x_k$  (resp.  $x_i < x_k$ ). Then all the protocols for  $\mathsf{GT}_{\geq}$  or  $\mathsf{GT}_{<}$  accept and the root node  $u_i$  also accepts at the final step since the number of " $\geq$ " is exactly t - j + 1.

To show the soundness, let us assume that  $\mathsf{RV}_{t,n}^{i,j}(x_1,\ldots,x_t) = 0$ . If the prover sends the true direction and follows the corresponding protocol for  $\mathsf{GT}_{\geq}$  (resp.  $\mathsf{GT}_{<}$ ) according to  $x_i \geq x_k$  (resp.  $x_i < x_k$ ) for every leaf  $x_k$ , the root node  $u_i$  rejects at the final step since  $\sum_{k \in [1,t] \setminus \{i\}} \mathsf{GT}_{\geq}(x_i, x_k) \neq t-j+1$ . Thus, the prover must send a false direction and cheat the protocol for  $\mathsf{GT}_{\geq}$  or  $\mathsf{GT}_{<}$  on some path. However, from the soundness of the protocol for  $\mathsf{GT}_{\geq}$  or  $\mathsf{GT}_{<}$  (by Corollary 28), the probability that at least one node on the path rejects is at least  $\frac{2}{3}$ .

# 6 Protocol for the Hamming distance and beyond on general graphs

In this section, we derive dQMA protocols for the Hamming distance and more extended functions on general graphs.

## 6.1 Protocol for the Hamming distance

 $\mathsf{HAM}_n^{\leq d}(x,y) = 1$  if and only if the Hamming distance between *n*-bit strings *x* and *y* is at most *d*. The SMP (and hence one-way) quantum communication complexity of  $\mathsf{HAM}_n^{\leq d}(x,y)$  is  $O(d \log n)$  [LZ13], improving the previous works [Yao03, GKdW04]. Let *c'* be an enough large constant independent with *n*, *r* and *d*, and let  $\pi'$  be a quantum one-way communication protocol for the Hamming distance transmitting  $c'd \log n$  qubits from [LZ13], such that, for all input pairs (x, y), if  $\mathsf{HAM}_n^{\leq d}(x, y) = 1$  then  $\pi'$  outputs 1 with probability at least  $\frac{2}{3}$ , and if  $\mathsf{HAM}_n^{\leq d}(x, y) = 0$ , then  $\pi'$ 

output 0 with probability at least  $\frac{2}{3}$ . Let  $|\psi(x)\rangle$  be the  $c'd\log n$ -qubit (pure) state sent from Alice to Bob in  $\pi'$  when x is an input for Alice.

As a previous work, there is a  $\mathsf{dQMA}$  protocol for the Hamming distance problem on a path network.

**Fact 5** (Corollary 3 in [FGNP21]). For any c > 0 and  $d \in \mathbb{Z}$ , there exists a dQMA protocol for  $\mathsf{HAM}_n^{\leq d}$  on the path of length r with completeness  $1 - \frac{1}{n^c}$ , soundness  $\frac{1}{3}$ , and using local proof and message of size  $O(r^2d(\log n)\log(n+r))$ .

We generalize the dQMA protocol for the Hamming distance between multiple inputs over apart nodes on a network. As in the case of the equality function, let r be the radius and t be the number of the terminals. The function of Hamming distance for t terminals  $u_1, \ldots, u_t$  where  $u_j$  has an n-bit string  $x_j$  can be defined as follows;  $\mathsf{HAM}_{t,n}^{\leq d}(x_1, \ldots, x_t) = 1$  if and only if the Hamming distance between any two n-bit strings  $x_i$  and  $x_j$  is at most d. Then, we show the following theorem.

**Theorem 30.** For any c > 0 and  $d \in \mathbb{Z}$ , there exists a dQMA protocol for  $\mathsf{HAM}_{t,n}^{\leq d}$  on a network of radius r with completeness  $1 - \frac{1}{n^c}$  and soundness  $\frac{1}{3}$ , using local proof and message of size  $O(t^2r^2d(\log n)\log(n+t+r))$ .

*Proof.* Let us first consider a two-sided error one-way protocol  $\pi''$  that repeats the one-way communication protocol  $\pi'$  for  $O(\log(n + t + r))$  times and takes a majority of the outcomes to reduce the error probability. The protocol  $\pi''$  on input (x, y) accepts with probability at least  $1 - \frac{1}{42n^{c}t^{2}r^{2}}$  when  $\mathsf{HAM}_{n}^{\leq d}(x, y) = 1$  and accepts with probability at most  $\frac{1}{3}$  when  $\mathsf{HAM}_{n}^{\leq d}(x, y) = 0.^{3}$  Note that  $|\psi''(x)\rangle := |\psi(x)\rangle^{\otimes O(\log(n+t+r))}$  is the state from Alice on input x to Bob in  $\pi''$ .

As our dQMA protocol for EQ, we assume that the network can know the construction of the spanning tree whose root and leaves are terminals from the prover. In the EQ protocol, we considered a protocol where messages are sent from the leaves to the root. In contrast, let us consider a protocol where messages are sent from the root to the leaves to show the completeness of the protocol. We also consider running the protocols in parallel for all the t spanning trees whose roots are the t terminals to show the soundness of the protocol. The total verification algorithm can be described in Algorithm 9.

Let  $k = 42r^2$ . The total size of the quantum registers  $R_{j,v,1}, \ldots, R_{j,v,\delta}$  is  $O(td \log(n) \log(n+t+r))$ because  $\delta$  can be bounded by t-1. By the for-loop at Step 2 and the k parallel repetitions at Step 7, the local proof and message sizes are  $O(t^2r^2d\log(n)\log(n+t+r))$ .

To show the completeness, let us assume that  $\mathsf{HAM}_{t,n}^{\leq d}(x_1, \ldots, x_t) = 1$ . The operations of Bob in the protocol  $\pi''$  are done  $42r^2t(t-1)$  times in total. Therefore the protocol has completeness  $(1 - \frac{1}{42t^2r^2n^c})^{42r^2t(t-1)} \geq 1 - \frac{1}{n^c}$ .

To show the soundness, let us assume that  $\mathsf{HAM}_{t,n}^{\leq d}(x_1, \ldots, x_t) = 0$ . Then there exist *i* and *j* such that  $\mathsf{HAM}_n^{\leq d}(x_i, x_j) = 0$ . Over the path on  $T_j$  whose extremities are  $u_i$  and  $u_j$  with input  $x_i$  and  $x_j$  respectively, the probability that all nodes on the path accept is at most  $\left(1 - \frac{4}{81r^2}\right)^k < \frac{1}{3}$  by a similar analysis of the EQ protocol in Section 3.

Since EQ is a spacial case of  $\mathsf{HAM}_n^{\leq d}$  when d = 0, it can be shown that a similar lower bound of dMA to Corollary 25 holds for  $\mathsf{HAM}_n^{\leq d}$ .

<sup>&</sup>lt;sup>3</sup>Actually, it is at most  $\frac{1}{42n^{c}t^{2}r^{2}}$ , which is smaller than  $\frac{1}{3}$ .

#### Algorithm 9 Protocol for the Hamming distance on general graphs

1: The (honest) prover sends t spanning trees  $T_1, \ldots, T_t$  to the nodes: the root of the jth one is the jth terminal  $u_j$ , and the leaves are the other terminals.

- 3: The honest prover sends  $(\delta + 1)$  quantum registers  $\mathsf{R}_{j,v,1}, \ldots, \mathsf{R}_{j,v,\delta+1}$  to a node v which is neither a root nor a leaf and whose number of its children is  $\delta$ . The contents of the registers are assumed to be the fingerprint  $|\psi''(x_r)\rangle$  of the root  $u_r$ . Then, v permutes  $(\delta + 1)$  registers by a permutation on  $S_{\delta+1}$  chosen uniformly at random. Then v keeps  $\mathsf{R}_{j,v,\delta+1}$  (renamed by the permutation), and sends  $\mathsf{R}_{j,v,\mu}$  to the  $\mu$ th child of v.
- 4: The root node  $u_r$  with input  $x_r$  sends the fingerprint  $|\psi''(x_r)\rangle$  to each of the children.
- 5: Each of non-root nodes, v, implements the SWAP test on  $\mathsf{R}_{j,v,\delta+1}$  and the register sent from the parent. Then, v accepts or rejects based on the result of the SWAP test.
- 6: Each leaf  $u_l$  with input  $x_l$  does the POVM operation of Bob in the one-way communication protocol  $\pi''$  on the register sent from the parent. Then,  $u_l$  accepts or rejects based on the result of the POVM operation.
- 7: To reduce the soundness error, do the parallel repetition of Steps 3 to 6 with k times similarly to Algorithm 4. Each node rejects if at least one of the performed SWAP tests or the operation of Bob in the one-way communication protocol  $\pi''$  rejects, and accepts otherwise.

8: end for

**Corollary 31.** Let  $\mathcal{P}$  be any  $\nu$ -round dMA protocol for  $\mathsf{HAM}_n^{\leq d}$  on the path of length r with total proof size  $\sum_{j=0}^r c(v_j) \leq \lfloor \frac{r-1}{2\nu} \rfloor \lfloor \frac{1}{2}(n-1) \rfloor$  and completeness 1-p. Then,  $\mathcal{P}$  has soundness error at least 1-2p.

### 6.2 Extended results

In this subsection, we extend Theorem 30 to other problems than the Hamming distance and LOCC dQMA protocols.

From a function  $f: (\{0,1\}^n)^2 \to \{0,1\}$ , let us denote a multi-input function  $\forall_t f: (\{0,1\}^n)^t \to \{0,1\}$  where  $\forall_t f(x_1,\ldots,x_t) = 1$  iff  $f(x_i,x_j) = 1$  for any  $i,j \in [1,t]$ . Similarly to the proof of Theorem 30, we obtain the following theorem that converts any one-way two-party quantum communication complexity protocol to dQMA protocols over a network.

**Theorem 32.** For a function  $f: (\{0,1\}^n)^2 \to \{0,1\}$  such that  $\mathsf{BQP}^1(f) = s$ , there exists a dQMA protocol for  $\forall_t f$  on a network of radius r with t terminals, completeness  $1 - \frac{1}{\mathsf{poly}(n)}$  and soundness  $\frac{1}{3}$ , using local proof and message of size  $O(t^2r^2s\log(n+t+r))$ .

We give a number of applications of Theorem 32. First, we apply the techniques of [DM18]. Let us introduce some definitions of  $l_1$ -graphs. Let V(H) denote the set of nodes of a graph H.

**Definition 10** ( $l_1$ -graph [DL97]). A graph H is an  $l_1$ -graph if its path metric dist<sub>H</sub> is  $l_1$ -embeddable, i.e., there is a map f between V(H) and  $\mathbb{R}^m$ , for some m, such that dist<sub>H</sub> $(v, w) = ||f(v) - f(w)||_1$ .

**Definition 11** (k-scale embedding [Shp93, BC08]). Given two connected and undirected graphs Hand H', we say that H is a k-scale embedding of H' if there exists a mapping  $f : V(H) \to V(H')$ such that  $\operatorname{dist}_{H'}(f(a), f(b)) = k \cdot \operatorname{dist}_{H}(a, b)$  for all the vertices  $a, b \in V(H)$ .

<sup>2:</sup> for j = 1, ..., t do

**Lemma 33** (Proposition 8.4 in [BC08]). A graph H is an  $l_1$ -graph if and only if it admits a constant scale embedding into a hypercube.

Examples of  $l_1$ -graphs are Hamming graphs [Che88], half cubes (the half-square of the hyper cubes) and Johnson graphs [Che17] are 2-embeddable into a hypercube [BC08]. Using the Johnson-Lindenstrauss lemma [JL84, GKdW06] to reduce the protocol complexity, Driguello and Montanaro showed the following statement as a subroutine of Protocol 2 in [DM18].

**Lemma 34** ([DM18]). Let H = (V, E) be an  $\ell_1$ -graph with |V| vertices, and let  $u, v \in V$ . There exists a quantum protocol in the SMP model with private randomness which communicates  $O(d^2 \log \log |V|)$  qubits and decide  $\mathsf{dist}_H(u, v) \leq d$  or  $\mathsf{dist}_H(u, v) \geq d+1$  with arbitrary high constant probability<sup>4</sup>.

We define a *t*-party version of the above problem.

**Definition 12.** For an  $\ell_1$ -graph H,  $\operatorname{dist}_{t,H}^{\leq d}(v_1, \ldots, v_t) = 1$  if  $\operatorname{dist}_H(v_i, v_j) \leq d$  for any distinct  $v_i$  and  $v_j$  in H, and  $\operatorname{dist}_{t,H}^{\leq d}(v_1, \ldots, v_t) = 0$  if  $\operatorname{dist}_H(v_i, v_j) \geq d + 1$  for some distinct  $v_i$  and  $v_j$  in H.

Then we have the following result from Theorem 32.

**Corollary 35.** For any  $d \in \mathbb{N}$ ,  $\ell_1$ -graph H, and network G whose radius is r and number of terminals is t, there exists a dQMA protocol for dist $\overset{\leq d}{\underset{t,H}{\leq}}(v_1,\ldots,v_t)$  over G with completeness  $1 - \frac{1}{\text{poly}(\log |V(H)|)}$  and soundness  $\frac{1}{3}$ , using local proof and message of size  $O(t^2r^2d^2\log \log |V(H)|\log(\log(|V(H)|) + t + r)).$ 

Driguello and Montanaro also showed an efficient quantum protocol of the SMP model to distinguish  $l_1$ -distances between vectors. A special case of the distance is the total variation distance of probabilistic distributions.

**Lemma 36** (Section IV in [DM18]). Let  $x, y \in [-1, 1]^n$  such that each entry of x and y is specified by a O(n)-bit string. For any d > 0, there is a quantum protocol in the SMP model which communicate  $O(\frac{\log n}{\epsilon^2})$  qubits and decide  $||x - y||_1 \leq d$  or  $||x - y||_1 \geq d(1 + \epsilon)$  for any  $\epsilon = \Omega(\frac{1}{\log n})$  with failure probability bounded by an arbitrarily small constant.

We can also define a t-party version.

**Definition 13.** For vectors  $x_1, \ldots, x_t \in [-1, 1]^n$  such that each entry of a vector is specified by a O(n)-bit string, d > 0 and  $\epsilon = \Omega(\frac{1}{\log n})$ ,  $\operatorname{dist}_{\mathbb{R}^n}^{\leq d, \epsilon}(x_1, \ldots, x_t) = 1$  if  $||x_i - x_j||_1 \leq d$  for any distinct i and j and  $\operatorname{dist}_{\mathbb{R}^n}^{\leq d, \epsilon}(x_1, \ldots, x_t) = 0$  if  $||x_i - x_j||_1 \geq d(1 + \epsilon)$  for at least one pair of distinct i and j.

By Theorem 32, the following result is obtained.

**Corollary 37.** There exists a dQMA protocol for dist $_{\mathbb{R}^n}^{\leq d,\epsilon}$  on a network of radius r with t terminals, completeness  $1-\frac{1}{\text{poly}(n)}$  and soundness  $\frac{1}{3}$ , using local proof and message of size  $O(t^2r^2\epsilon^{-2}\log n\log(n+r+t))$ .

<sup>&</sup>lt;sup>4</sup>Each party knows H in this problem.

A function F(x, y) on  $\{0, 1\}^n \times \{0, 1\}^n$  is an XOR function if  $F(x, y) = f(x \oplus y)$  for some function f on n-bit strings, where  $x \oplus y$  is the bit-wise XOR of x and y. An XOR function is symmetric if f is symmetric, i.e., f(z) depends only on the Hamming weight of z. The Hamming distance function is indeed an important symmetric XOR function, which can be also defined as follows.

$$\mathsf{HAM}_n^{\leq d}(x,y) = \begin{cases} 1 & \text{if } |x \oplus y| \leq d \\ 0 & \text{if } |x \oplus y| > d \end{cases}$$

Let us consider more general classes of the XOR function. A linear threshold functions (LTF) f is defined by

$$f(z) = \begin{cases} 1 & \text{if } \sum_{i} w_i z_i \leq \theta \\ 0 & \text{if } \sum_{i} w_i z_i > \theta \end{cases}$$

where  $\{w_i\}$  are the weights and  $\theta$  is the threshold. We define

$$W_0 = \max_{z:f(z)=0} \sum_i w_i z_i$$
 and  $W_1 = \min_{z:f(z)=1} \sum_i w_i z_i$ ,

and define  $m_0 = \theta - W_0$  and  $w_1 = W_1 - \theta$ . The margin of f is  $m = \max\{m_0, m_1\}$ . Note that the function remains the same if  $\{w_i\}$  are fixed and  $\theta$  varies in  $(W_0, W_1]$ . Thus, without loss of generality, we assume that  $\theta = \frac{W_0 + W_1}{2}$ , in which case  $m_0 = m_1 = m$ .

**Lemma 38** (Theorem 3 in [LZ13]). For any linear threshold function f whose threshold is  $\theta$  and margin is m and a function g such that  $g(x, y) = f(x \oplus y)$ ,  $\mathsf{BQP}^{||}(g) = O(\frac{\theta}{m} \log n)$ .

Our multiparty problem and the result induced from Theorem 32 are given in the following.

**Definition 14.** For any linear threshold function f whose threshold is  $\theta$  and margin is m and t n-bit inputs  $(x_1, \ldots, x_t)$ ,  $\mathsf{LTF}_n^{\leq \theta, m}(x_1, \ldots, x_t) = 1$  if and only if  $f(x_i \oplus x_j) = 1$  for any distinct i and j.

**Corollary 39.** There exists a dQMA protocol for  $LTF_n^{\leq \theta,m}$  on a network of radius r with t terminals, completeness  $1 - \frac{1}{\text{poly}(n)}$  and soundness  $\frac{1}{3}$ , using local proof and message of size  $O(t^2r^2\frac{\theta}{m}\log n\log(n+r+t))$ .

Let us next consider a function  $\mathbb{F}_q$ -rank $_n^r : \mathbb{F}_q^{n \times n} \times \mathbb{F}_q^{n \times n} \to \{0, 1\}$ . We define  $\mathbb{F}_q$ -rank $_n^r(X, Y) = 1$  if and only if the matrix X + Y has rank less than r, where the rank and the summation X + Y are both over  $\mathbb{F}_q$ .

**Lemma 40** (Theorem 4 in [LZ13]). For  $f = \mathbb{F}_q$ -rank<sup>r</sup><sub>n</sub>,  $\mathsf{BQP}^{||}(f) = \min\{q^{O(r^2)}, O(nr\log q + n\log n)\}$ .

Our multiparty problem and the result induced from Theorem 32 are given in the following.

**Definition 15.**  $\mathbb{F}_q$ -rank $_{t,n}^{\leq r}(X_1, \ldots, X_t) = 1$  if and only if  $\mathbb{F}_q$ -rank $_n^r(X_i, X_j) = 1$  for any distinct i and j.

**Corollary 41.** There exists a dQMA protocol for  $\mathbb{F}_q$ -rank $_{t,n}^{\leq r}(X_1, \ldots, X_t)$  on a network of radius r with t terminals, completeness  $1 - \frac{1}{poly(n)}$  and soundness  $\frac{1}{3}$ , using local proof and message of size  $O(t^2r^2\min\{q^{O(r^2)}, O(nr\log q + n\log n)\}\log(n + r + t)).$ 

# 7 Construction of dQMA<sup>sep</sup> protocols from dQMA protocols

In this section, we prove that any function which can be efficiently solved in a dQMA protocol has an efficient  $dQMA^{sep}$  protocol with some overheads.

We first show that any QMA one-way communication protocol can be transformed into a dQMA protocol on a path with some overheads.

**Theorem 42.** Suppose that, for a Boolean function  $f : \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$ , there exists a QMA one-way communication protocol with a  $\gamma$ -qubit proof and  $\mu$ -qubit communications, completeness  $\frac{2}{3}$  and soundness  $\frac{1}{3}$ . Then, there exists a dQMA protocol for f on a path  $v_0, \ldots, v_r$  with completeness  $1 - \frac{1}{\text{poly}(n)}$  and soundness  $\frac{1}{3}$ , proof size  $c(v_0) = O(r^2\gamma \log(n+r)), c(v_1), c(v_2), \ldots, c(v_{r-1}) = O(r^2(\gamma + \mu)\log(n + r))$ , and message size  $m(v_i, v_{i+1}) = O(r^2(\gamma + \mu)\log(n + r))$  for  $i \in [0, r - 1]$ .

*Proof.* Let us consider a  $O(\log(n+r))$  times repetition of the QMA one-way communication protocol for f in a standard way as in [AN02, KSV02]. The repeated protocol requires a  $O(\gamma \log(n+r))$ qubit proof and a  $O(\mu \log(n+r))$ -qubit communication from Alice to Bob and has completeness at least  $1 - \frac{1}{42n^c r^2}$  and soundness at most  $\frac{1}{42n^c r^2}$ .

Let us describe the above QMA one-way communication protocol as follows. Note that this formalization holds for any QMA one-way communication protocol. Merlin produces a quantum state  $\rho$  on  $\gamma' = O(\gamma \log(n+r))$  qubits, which he sends to Alice. Then, Alice applies some quantum operation on  $\rho$  depending on her input  $x \in \{0,1\}^n$  and sends Bob a quantum state  $\sigma$  on  $\mu' = O(\mu \log(n+r))$  qubits. Then, Bob conducts a POVM measurement  $\{M_{y,0}, M_{y,1}\}$  on the state  $\sigma$  depending on his input  $y \in \{0,1\}^n$ .

To make a quantum message from Alice to Bob in the case of completeness a pure state rather than a mixed state, we consider a variant of the original protocol as follows. Not to confuse readers, let us call two parties Carol and Dave which have an input x and y respectively rather than Alice and Bob. Merlin produces a quantum state  $\rho$  on  $\gamma'$  qubits, which he sends to Carol. Then, Carol applies some unitary operation  $U_x$  on  $\rho$  and her  $(\gamma' + \mu')$  ancilla qubits and sends Dave a  $(2\gamma' + \mu')$ qubit state  $\sigma' = U_x(\rho \otimes |0\rangle^{\otimes (\gamma' + \mu')} \langle 0|^{\otimes (\gamma' + \mu')}) U_x^{\dagger}$ . Then, Dave obtains  $\sigma$  by tracing out the last  $2\gamma'$ qubits of  $\sigma'$  and conducts the POVM measurement  $\{M_{y,0}, M_{y,1}\}$  on the state  $\sigma$  depending on his input  $y \in \{0,1\}^n$ . Let us denote by a POVM measurement  $\{M'_{y,0}, M'_{y,1}\}$  the whole operations of Dave. This modification can be done from the fact that for any quantum operation (CPTP map) from *n*-qubit to *m*-qubit, there exists an equivalent operation of a unitary matrix on (2n+m)-qubit (see, e.g., Lemma 1 in [AKN98]). This modified protocol has the same completeness and soundness to the original protocol.

Let us next analyze the completeness and soundness of the protocol  $\mathcal{P}_{QMAcc}$  described in Algorithm 10. Note that the analysis is quite close to the analysis of the dQMA protocol for EQ on paths.

#### Completeness

Let us assume that an input (x, y) satisfies f(x, y) = 1. Then, there exists a quantum proof  $|\xi\rangle$ such that  $\operatorname{tr}(M'_{y,1}(U_x(|\xi\rangle \langle \xi| \otimes |0 \cdots 0\rangle \langle 0 \cdots 0|)U_x^{\dagger}))) = 1$  with probability at least  $1 - \frac{1}{42n^c r^2}$ . The prover sends  $\sigma = |\xi\rangle \langle \xi|$  to  $v_0$  and  $U_x(|\xi\rangle \langle \xi| \otimes |0 \cdots 0\rangle \langle 0 \cdots 0|)U_x^{\dagger} \otimes U_x(|\xi\rangle \langle \xi| \otimes |0 \cdots 0\rangle \langle 0 \cdots 0|)U_x^{\dagger}$ to all the intermediate nodes. Then, all the SWAP tests accept with certainty. Furthermore, the right-end node  $v_r$  accepts with probability at least  $1 - \frac{1}{42n^c r^2}$ . Then, from the definition of the completeness of dQMA protocols, the protocol  $\mathcal{P}_{\mathsf{QMAcc}}$  has completeness at least  $1 - \frac{1}{42n^c r^2}$ . **Algorithm 10** dQMA protocol  $\mathcal{P}_{QMAcc}$  for a function f such that  $QMAcc^{1}(f) = \gamma + \mu$ .

- 1: The prover sends a state  $\rho$  on the quantum register  $R_{0,0}$ , whose size is  $O(\gamma \log(n+r))$ , to the left-end node  $v_0$  as a proof.
- 2: The prover sends the quantum registers  $R_{j,0}, R_{j,1}$ , which are  $O((\gamma + \mu) \log(n + r))$  qubits respectively, as proofs to each of the intermediate nodes  $v_j$  for  $j \in \{1, \ldots, r-1\}$ .
- 3: The left-end node  $v_0$  applies the unitary operation  $U_x$  to  $\rho$  and  $O((\gamma + \mu) \log(n + r))$  ancilla qubits and sends a state  $U_x(\rho \otimes |0 \cdots 0\rangle \langle 0 \cdots 0|) U_x^{\dagger}$  in the register  $R_{0,1}$  to  $v_1$ .
- 4: Each intermediate node  $v_j$  swaps the states between  $R_{j,0}$  and  $R_{j,1}$  with probability  $\frac{1}{2}$ , i.e., symmetrizes the states on  $R_{j,0}$  and  $R_{j,1}$ .
- 5: Each of the nodes sends its quantum register  $R_{j,1}$  to the right neighbor  $v_{j+1}$ .
- 6:  $v_j$  receives a quantum register from its left neighbor  $v_{j-1}$ . The node then performs the SWAP test on the registers  $(R_{j-1,1}, R_{j,0})$  and accepts or rejects accordingly.
- 7: The right-end node  $v_r$  receives a state on a register  $R_{r-1,1}$  from its left neighbor. Then,  $v_r$  performs the POVM measurement  $\{M'_{y,0}, M'_{y,1}\}$  on the state of  $R_{r-1,1}$  and accepts or rejects accordingly.

#### Soundness

Let us assume that an input (x, y) satisfies f(x, y) = 0 and, for any quantum proof  $|\xi\rangle$ ,  $\operatorname{tr}(M'_{y,0}(U_x(|\xi\rangle \langle \xi| \otimes |0 \cdots 0\rangle \langle 0 \cdots 0|)U_x^{\dagger}))) \geq 1 - \frac{1}{42n^c r^2} \geq \frac{2}{3}$ . Then, a lemma similar to Lemma 17 is shown.

**Lemma 43.** For  $j \in \{1, ..., r\}$ , let  $E_j$  be the event that the local test  $v_j$  performs (the SWAP test or the POVM measurement) accepts. Then,  $\sum_{j=1}^{r} \Pr[\neg E_j] \ge \frac{4}{8!r}$ .

*Proof.* For conciseness, let us denote  $p_j = \Pr[\neg E_j]$ . By the same discussion to Lemma 17, we have

$$D(\rho_{0,1}, \rho_{r-1,1}) \le 3\sum_{j=1}^{r-1} \sqrt{p_j},$$

where  $\rho_{0,1}$  is a reduced state on the register  $R_{0,1}$  and  $\rho_{r-1,1}$  is a reduced state on the register  $R_{r-1,1}$ . From the assumption of the soundness,  $\operatorname{tr}(M'_{y,0}(\rho_{0,1})) \geq \frac{2}{3}$ . Then, by the same discussion to Lemma 17, we conclude

$$\sum_{j=1}^r p_j \ge \frac{4}{81r}.$$

Using Lemma 11, the protocol  $\mathcal{P}_{\mathsf{QMAcc}}$  has soundness  $\frac{4}{81r^2}$ . Let us again consider a parallel repetition with  $O(r^2)$  times as the protocol  $P_{\pi}[k]$  in Algorithm 4, which completes the proof of Theorem 42.

We next show any dQMA protocol can be simulated by a dQMA<sup>sep</sup> protocol with some overhead. To do it, let us restate the definition of the Linear Space Distance (LSD) problem from [RS04] as a complete problem for QMA communication protocols. For a subspace  $V \subset \mathbb{R}^m$ , let us define  $S(V) = \{v \in V | ||v|| = 1\}$ , the unit sphere in V where  $||\cdot||$  is the Euclidean norm. For two subspaces  $V_1, V_2 \subset \mathbb{R}^m$ , let us define

$$\Delta(V_1, V_2) = \min_{v_1 \in S(V_1)} \min_{v_2 \in S(V_2)} \|v_1 - v_2\|$$

as the distance between  $V_1$  and  $V_2$ .

**Definition 16** (The Linear Space Distance (LSD) problem [RS04]). Given two subspaces  $V_1$  and  $V_2$  of  $\mathbb{R}^m$  under the promise that  $\Delta(V_1, V_2) \leq 0.1 \cdot \sqrt{2}$  or  $\Delta(V_1, V_2) \geq 0.9 \cdot \sqrt{2}$ , decide if the distance is small or not.

**Lemma 44** (Theorem 7 in [RS04]). Suppose  $f : \mathcal{X} \times \mathcal{Y} \to \{0, 1\}$  has a  $\nu$ -round QMA communication protocol with a  $\gamma$ -qubit proof and  $\mu$ -qubit communications. Then, there exists a mapping from  $\mathcal{X}$ and  $\mathcal{Y}$  to subspaces of  $\mathbb{R}^{2(\gamma+\mu)\mathrm{poly}(\nu)}$ ,  $x \mapsto A_x$ ,  $y \mapsto B_y$ , such that if f(x, y) = 1,  $\Delta(A_x, B_y) \leq 0.1 \cdot \sqrt{2}$ and if f(x, y) = 0,  $\Delta(A_x, B_y) \geq 0.9 \cdot \sqrt{2}$ .

**Lemma 45** (Theorem 16 in [RS04]). There exists a QMA one-way communication protocol of cost  $O(\log m)$  to solve the LSD problem <sup>6</sup>.

In the definition of the LSD problem, the input precision is infinite. We can define LSD as the finite precision version where  $\mathbb{R}^m$  are approximated with  $O(m^2)$  variables and each variable is described with  $O(\log m)$  bits. The input size of the problem is  $O(m^2 \log m)$  and the above two results hold for the finite precision analog [RS04]. Therefore we assume that the input size for the LSD problem is  $O(m^2 \log m)$  without loss of generality.

Using the property of the LSD problem as a QMA communication complete problem, we prove that any dQMA protocol can be simulated by a  $dQMA^{sep}$  protocol with some overheads.

**Theorem 46.** Suppose  $f : \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$  has a constant-round dQMA protocol on a path  $v_0, \ldots, v_r$ , completeness  $\frac{2}{3}$ , and soundness  $\frac{1}{3}$ . Let  $C := \sum_{j \in [0,r]} c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1})$ . Then, there exists a 1-round dQMA<sup>sep</sup> protocol for f on the path of length r with completeness  $1 - \frac{1}{\text{poly}(C2^C)}$ , soundness  $\frac{1}{3}$ , using local proof and message of size  $\tilde{O}(r^2C^2)$ .

*Proof.* Let us denote  $j = \operatorname{argmin} m(v_i, v_{i+1})$ . Let us divide r+1 nodes into the two groups  $v_0, \ldots, v_j$ 

and  $v_{j+1}, \ldots, v_r$ . From the original dQMA protocol, let us consider Alice simulates the protocols of  $v_{0}, \ldots, v_{j}$  and she accepts iff all the parties accept, and Bob simulates the protocols of  $v_{j+1}, \ldots, v_r$  and he accepts iff all the parties accept. This protocol is a QMA<sup>\*</sup> communication protocol whose complexity is at most C to solve f. From the inequality (1) in Section 2.2.2, QMAcc(f) is at most 2C. By Lemma 44 and Lemma 45, there exists a QMA one-way communication protocol of complexity O(C) to solve the LSD problem to which f reduces. Note that the dimension m of the subspaces of the LSD instance is  $m = 2^{O(C)}$ . Since the input size of the LSD is  $O(m^2 \log m) = O(C2^{O(C)})$ , Theorem 42 implies that there exists a dQMA<sup>sep</sup> protocol for the LSD problem (and hence for f) on the path of length r with 1-round communication, and completeness  $1 - \frac{1}{\Omega(\text{poly}(C2^C))}$ , soundness  $\frac{1}{3}$ , using local proof and message sizes  $O(r^2(C) \log(2^{O(C \log(C))} + r)) = \tilde{O}(r^2C^2)$ .

<sup>&</sup>lt;sup>5</sup>The dimension of the vector space is different from Theorem 7 in [RS04], while it is observed by the analysis of the proof. A similar analysis is also considered in [KP14].

<sup>&</sup>lt;sup>6</sup>Soundness and completeness do not change in the complex setting of quantum proofs [McK13].

We also show that there exists an efficient dQMA protocol for a function which has an efficient  $QMA^*$  communication protocol with some overhead costs.

**Proposition 47.** Suppose  $f : \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$  has a QMA<sup>\*</sup> communication protocol with cost C, i.e., QMAcc<sup>\*</sup>(f) = C. Then, there exists a dQMA<sup>sep</sup> protocol for f on the path of length r with completeness  $1 - \frac{1}{\text{poly}(n)}$ , soundness  $\frac{1}{3}$ , using local proof and message of size  $O(r^2 \log(r) \text{poly}(C))$ .

*Proof.* From the inequality (1) in Section 2.2.2, QMAcc(f) is at most 2*C*, and from Lemma 44 and Lemma 45, there exist a QMA one-way communication protocol of complexity O(poly(C)) to solve the LSD problem to which *f* reduces, where the dimension *m* of the subspaces of the LSD instance is  $m = 2^{poly(C)}$ . Since the input size of the LSD is  $O(m^2 \log m)$ , Theorem 42 implies the claim described.

# 8 Lower bounds for dQMA protocols

In this section, we will obtain lower bounds for the size of proofs and communication of dQMA protocols. In this section, we also focus on the case where the verifier  $v_0, \ldots, v_r$  are arranged in a row and the two extremities  $v_0$  and  $v_r$  have inputs. Let  $x \in \{0,1\}^n$  be the input owned by  $v_0$ , and  $y \in \{0,1\}^n$  be the input owned by  $v_r$ .

#### 8.1 By a counting argument over quantum states for fooling inputs

In this subsection, we will obtain a lower bound of the proof size by a counting argument of quantum states for fooling inputs.

A lower bound for the size of quantum fingerprints of n-bits was shown by a reduction to the lower bound of quantum one-way communication complexity for EQ [BdW01].

**Lemma 48** (Theorem 8.3.2 in [dW01]). Let  $\delta \geq 2^{-n}$ . Suppose that a family of pure states  $\{|h_x\rangle\}_{x\in\{0,1\}^n}$  of b-qubit satisfies  $|\langle h_i|h_j\rangle| \leq \delta$  for any distinct i, j. Then,  $b = \Omega(\log(\frac{n}{\delta^2}))$ .

**Claim 49.** For any family of sets  $S_n$  where  $|S_n| \ge s(n)$  and any constant  $0 \le \delta < 1$ , there exist a sufficiently small constant c > 0 and large integer n such that, for any family of  $c \log \log s(n)$ -qubit pure states  $\{|h_x\rangle\}_{x \in S_n}$ , there exist i and j such that  $|\langle h_i|h_j\rangle| > \delta$ .

Proof. Let us choose a family of sets  $S'_n$  so that for all n, each set is an arbitrary subset of the set  $S_n$  and  $|S'_n| = 2^{\lfloor \log s(n) \rfloor}$ , and let us correspond an element of  $S'_n$  with an element of  $\{0,1\}^{\lfloor \log s(n) \rfloor}$  one by one. Then, from Lemma 48, if there exists a family of pure states  $\{|h_x\rangle\}_{x \in S'_n}$  of b-qubit satisfies  $|\langle h_i | h_j \rangle| \leq \delta$  for any distinct elements  $i, j \in S'_n, b = \Omega(\log \log s(n))$ , i.e., for sufficient large n and a constant  $c', b \geq c' \log \log s(n)$ . Then, for a constant c < c', the claim holds.

By a counting argument for fooling inputs, we have a lower bound of the proof size of  $\mathsf{dQMA}^{\mathsf{sep},\mathsf{sep}}$  protocols.

**Proposition 50.** Let  $p \ge 0, \delta > 0, \nu \in \mathbb{N}$  be constants and f be a Boolean function with a 1fooling set of size at least k. Let  $\mathcal{P}$  be a dQMA<sup>sep,sep</sup> protocol for f on the path of length r with  $\nu$ -round communication, completeness 1 - p and soundness error less than  $1 - 2p - \delta$ . Then, for any  $i \in [\nu, r - \nu - 1]$  and a sufficiently small constant  $c, \sum_{j=i-\nu+1}^{i+\nu} c(v_j) > c \log \log k$ . *Proof.* For conciseness, we prove the case that  $\mathcal{P}$  is a 1-round communication protocol (we can easily modify the following proof to the  $\nu$ -round case).

Let us denote by  $S_n$  the 1-fooling set for  $f : \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$  where  $|S_n| \ge k$ . For  $x_1, x_2 \in \{0,1\}^n$ , let  $|\psi_x\rangle$  be a proof with the input  $x = (x_1, x_2)$  for all the nodes  $v_0, \ldots, v_r$ , where  $x_1$  is owned by  $v_0$  and  $x_2$  is owned by  $v_r$ , and let  $|\psi_x\rangle_j$  be a part of the proof for the node  $v_j$  where  $j = 0, \ldots, r$ .

To reach a contradiction, let us assume that  $\sum_{j=i}^{i+1} c(v_j) \leq c \log \log k$  for some  $i \in [1, r-2]$ . Let us consider a family of states  $\{|\psi_x\rangle_i \otimes |\psi_x\rangle_{i+1}\}_{(x_1,x_2)\in S_n}$ . From Claim 49, since the qubit size of the family is less than or equal to  $c \log \log k$  where c is chosen a sufficiently small constant, there exist  $y = (y_1, y_2)$  and  $z = (z_1, z_2)$  in  $S_n$  such that  $f(y_1, y_2) = f(z_1, z_2) = 1$  and  $|\langle \psi_y|_i \otimes \langle \psi_y|_{i+1} |\psi_z\rangle_i \otimes$  $|\psi_z\rangle_{i+1}| > 1 - \frac{\delta^2}{8}$ . From Fact 1 and Fact 4 and since the partial trace is a quantum operation, we have

$$\begin{split} D(|\psi_y\rangle_i, |\psi_z\rangle_i) &\leq D(|\psi_y\rangle_i \otimes |\psi_y\rangle_{i+1}, |\psi_z\rangle_i \otimes |\psi_z\rangle_{i+1}) \\ &\leq \sqrt{1 - F(|\psi_y\rangle_i \otimes |\psi_y\rangle_{i+1}, |\psi_z\rangle_i \otimes |\psi_z\rangle_{i+1})^2} \\ &= \sqrt{1 - |\langle\psi_y|_i \otimes \langle\psi_y|_{i+1} |\psi_z\rangle_i \otimes |\psi_z\rangle_{i+1}|^2} \\ &< \sqrt{1 - \left(1 - \frac{\delta^2}{8}\right)^2} \\ &= \sqrt{\frac{\delta^2}{4} - \frac{\delta^4}{16}} \\ &< \frac{\delta}{2}. \end{split}$$

We also have  $D(|\psi_y\rangle_{i+1}, |\psi_z\rangle_{i+1}) < \frac{\delta}{2}$  by the same discussion.

Let L be a register of a part of the proof for  $v_0, \ldots, v_i$  and R be a register of the other part (namely, for  $v_{i+1}, \ldots, v_r$ ). Let us denote by  $\mathsf{out}_j(s, t, |\phi\rangle)$  the output of  $v_j$  when the input is (s, t) (where s is owned by  $v_0$  and t is owned by  $v_r$ ) and the proof is  $|\phi\rangle$ . From the assumption of the completeness, we have

$$\Pr\left[\bigwedge_{j:j\leq i}\operatorname{out}_{j}(y_{1}, y_{2}, |\psi_{y}\rangle_{LR}) = 1 \land \bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(y_{1}, y_{2}, |\psi_{y}\rangle_{LR}) = 1\right] \ge 1 - p,$$
  
$$\Pr\left[\bigwedge_{j:j\leq i}\operatorname{out}_{j}(z_{1}, z_{2}, |\psi_{z}\rangle_{LR}) = 1 \land \bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(z_{1}, z_{2}, |\psi_{z}\rangle_{LR}) = 1\right] \ge 1 - p.$$

We thus have

$$\Pr\left[\bigwedge_{j:j\leq i}\operatorname{out}_{j}(y_{1}, y_{2}, |\psi_{y}\rangle_{LR}) = 1\right] \geq 1 - p,$$
  
$$\Pr\left[\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(z_{1}, z_{2}, |\psi_{z}\rangle_{LR}) = 1\right] \geq 1 - p.$$

Let us consider the input assignment  $(y_1, z_2)$  combined with the proof assignment  $|\psi_y\rangle_L \otimes |\psi_z\rangle_R$ . By the definition of the 1-fooling set,  $f(y_1, z_2) = 0$  without loss of generality. Since the protocol  $\mathcal{P}$  has 1-round in the verification algorithm and the proofs are separable, we have

$$\Pr\left[\bigwedge_{j:j\leq i-1}\mathsf{out}_j(y_1,y_2,|\psi_y\rangle_{LR})=1\right]=\Pr\left[\bigwedge_{j:j\leq i-1}\mathsf{out}_j(y_1,z_2,|\psi_y\rangle_{L}\otimes|\psi_z\rangle_{R})=1\right],$$

$$\Pr\left[\bigwedge_{j:j\geq i+2}\mathsf{out}_j(z_1,z_2,|\psi_z\rangle_{LR})=1\right]=\Pr\left[\bigwedge_{j:j\geq i+2}\mathsf{out}_j(y_1,z_2,|\psi_y\rangle_L\otimes|\psi_z\rangle_R)=1\right].$$

The output of the node  $v_i$  can be only affected by  $|\psi_y\rangle_{i-1} \otimes |\psi_y\rangle_i \otimes |\psi_z\rangle_{i+1}$  and the binary string  $y_1$ . Similarly the output of the node  $v_{i+1}$  can be affected by  $|\psi_y\rangle_i \otimes |\psi_z\rangle_{i+1} \otimes |\psi_z\rangle_{i+2}$  and the binary string  $z_2$ . With Fact 3, we thus have

$$\begin{split} |\Pr[\mathsf{out}_{i}(y_{1}, y_{2}, |\psi_{y}\rangle_{LR}) = 1] - \Pr[\mathsf{out}_{i}(y_{1}, z_{2}, |\psi_{y}\rangle_{L} \otimes |\psi_{z}\rangle_{R}) = 1]| \\ &\leq D(|\psi_{y}\rangle_{i-1} \otimes |\psi_{y}\rangle_{i} \otimes |\psi_{y}\rangle_{i+1}, |\psi_{y}\rangle_{i-1} \otimes |\psi_{y}\rangle_{i} \otimes |\psi_{z}\rangle_{i+1}) = D(|\psi_{y}\rangle_{i+1}, |\psi_{z}\rangle_{i+1}) < \frac{\delta}{2}, \\ |\Pr[\mathsf{out}_{i+1}(z_{1}, z_{2}, |\psi_{z}\rangle_{LR}) = 1] - \Pr[\mathsf{out}_{i+1}(y_{1}, z_{2}, |\psi_{y}\rangle_{L} \otimes |\psi_{z}\rangle_{R}) = 1]| \\ &\leq D(|\psi_{y}\rangle_{i} \otimes |\psi_{z}\rangle_{i+1} \otimes |\psi_{z}\rangle_{i+2}, |\psi_{z}\rangle_{i} \otimes |\psi_{z}\rangle_{i+1} \otimes |\psi_{z}\rangle_{i+2}) = D(|\psi_{y}\rangle_{i}, |\psi_{z}\rangle_{i}) < \frac{\delta}{2}. \end{split}$$

Combining the inequalities and the union bound, we have

$$\begin{split} & \Pr\left[\bigwedge_{j:j \leq i} \operatorname{out}_{j}(y_{1}, z_{2}, |\psi_{y}\rangle_{L} \otimes |\psi_{z}\rangle_{R}) = 1 \wedge \bigwedge_{j:j \geq i+1} \operatorname{out}_{j}(y_{1}, z_{2}, |\psi_{y}\rangle_{L} \otimes |\psi_{z}\rangle_{R}) = 1\right] \\ &= \Pr\left[\left(\bigwedge_{j:j \leq i-1} \operatorname{out}_{j}(y_{1}, y_{2}, |\psi_{y}\rangle) = 1 \wedge \operatorname{out}_{i}(y_{1}, z_{2}, |\psi_{y}\rangle_{L} \otimes |\psi_{z}\rangle_{R}) = 1\right) \wedge \left(\operatorname{out}_{i+1}(y_{1}, z_{2}, |\psi_{y}\rangle_{L} \otimes |\psi_{z}\rangle_{R}) = 1 \wedge \bigwedge_{j:j \geq i+2} \operatorname{out}_{j}(z_{1}, z_{2}, |\psi_{z}\rangle) = 1\right)\right] \\ &\geq 1 - \Pr\left[\neg\left(\bigwedge_{j:j \leq i-1} \operatorname{out}_{j}(y_{1}, y_{2}, |\psi_{y}\rangle) = 1 \wedge \operatorname{out}_{i}(y_{1}, z_{2}, |\psi_{y}\rangle_{L} \otimes |\psi_{z}\rangle_{R}) = 1\right)\right] \\ &- \Pr\left[\neg\left(\operatorname{out}_{i+1}(y_{1}, z_{2}, |\psi_{y}\rangle_{L} \otimes |\psi_{z}\rangle_{R}) = 1 \wedge \bigwedge_{j:j \geq i+2} \operatorname{out}_{j}(z_{1}, z_{2}, |\psi_{z}\rangle) = 1\right)\right] \\ &\geq 1 - \delta - \Pr\left[\neg\left(\operatorname{out}_{i+1}(z_{1}, z_{2}, |\psi_{y}\rangle) = 1 \wedge \operatorname{out}_{i}(y_{1}, y_{2}, |\psi_{y}\rangle) = 1\right) \\ &- \Pr\left[\neg\left(\operatorname{out}_{i+1}(z_{1}, z_{2}, |\psi_{z}\rangle) = 1 \wedge \bigwedge_{j:j \geq i+2} \operatorname{out}_{j}(z_{1}, z_{2}, |\psi_{z}\rangle) = 1\right)\right] \\ &\geq 1 - 2p - \delta, \end{split}$$

which contradicts the condition of the soundness. Therefore, we conclude  $\sum_{j=i}^{i+1} c(v_j) > c \log \log k$  for any  $i \in [1, r-2]$ .

The proposition above implies that any  $dQMA^{sep,sep}$  protocol for EQ and GT with sufficiently high completeness and low soundness error requires  $\Omega(r \log n)$ -qubit quantum proofs.

**Theorem 51.** Let  $p \ge 0, \delta > 0, \nu \in \mathbb{N}$  be constants and  $f : (\{0,1\}^n)^2 \to \{0,1\}$  be a Boolean function with a 1-fooling set of size  $2^n$  (including EQ and GT). Let  $\mathcal{P}$  be a dQMA<sup>sep,sep</sup> protocol for f on the path of length r with  $\nu$ -round communication, completeness 1-p and soundness error less than  $1-2p-\delta$ . Then,  $\sum_{j=0}^r c(v_j) = \Omega(r \log n)$ .

*Proof.* Assume that  $\sum_{j=0}^{r} c(v_j) \leq \lfloor \frac{r-1}{2\nu} \rfloor \lfloor c \log n \rfloor$  for a sufficiently small constant c. Then, by the pigeonhole principle, there exists  $i \in [\nu, r - \nu - 1]$  such that  $\sum_{j=i-\nu+1}^{i+\nu} c(v_j) \leq c \log n$ , which contradicts Proposition 50. Therefore,  $\sum_{j=0}^{r} c(v_j) = \Omega(r \log n)$ .

Even for entangled proofs, we obtain the following lower bound by combining Theorem 51 with Theorem 46.

**Theorem 52.** Let  $f : (\{0,1\}^n)^2 \to \{0,1\}$  be a Boolean function with a 1-fooling set of size  $2^n$  (including EQ and GT). Let  $\mathcal{P}$  be a dQMA protocol for f on the path of length r with constant-round communication, completeness  $\frac{2}{3}$  and soundness  $\frac{1}{3}$ . Let  $C := \sum_j c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1})$ . Then,  $\mathcal{P}$  satisfies  $C = \Omega(\frac{(\log n)^{1/2-\epsilon}}{r^{1+\epsilon'}})$  for any constants  $\epsilon, \epsilon' > 0$ .

*Proof.* Assume that  $\mathcal{P}$  satisfies  $C = o(\frac{(\log n)^{1/2-\epsilon}}{r^{1+\epsilon'}})$ . Then, from Theorem 46, there exists a dQMA<sup>sep</sup> (and hence dQMA<sup>sep,sep</sup>) protocol for f on the path of length r with 1-round communication, completeness  $\frac{3}{4}$  and soundness  $\frac{1}{3}$  and total proof size

$$\sum_{j=0}^{r} c(v_j) = \tilde{O}\left(r^3 \left(\frac{(\log n)^{1/2-\epsilon}}{r^{1+\epsilon'}}\right)^2\right) = \tilde{O}(r^{1-2\epsilon'}(\log n)^{1-2\epsilon}) = o(r\log n),$$

which contradicts Theorem 51.

For entangled proofs, we can have another lower bound.

**Lemma 53.** Let  $\nu \in \mathbb{N}$  be a constant and f be a function which has a 1-fooling set of size at least 2. Let  $\mathcal{P}$  be a  $\nu$ -round dQMA protocol for f on the path of length r with a proof of size satisfying  $\sum_{j=i-\nu+1}^{i+\nu} c(v_j) = 0$  for  $i \in [\nu, r-\nu-1]$ , and completeness 1-p. Then,  $\mathcal{P}$  has soundness error at least 1-2p.

*Proof.* For conciseness, we prove the case that  $\mathcal{P}$  is a 1-round communication protocol (we can easily modify the following proof to the  $\nu$ -round case).

Let (x, y) and (x', y') be in the 1-fooling set for f, i.e., f(x, y) = 1, f(x', y') = 1 and f(x, y') = 0without loss of generality. Let  $|\psi\rangle$  be a proof with the input (x, y) for all the nodes  $v_0, \ldots, v_r$  and let  $|\psi'\rangle$  be a proof with the input (x', y') for all the nodes  $v_0, \ldots, v_r$ .

From the assumption of the completeness, we have

$$\Pr\left[\bigwedge_{j:j\leq i}\operatorname{out}_{j}(x,y,|\psi\rangle_{LR})=1\wedge\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(x,y,|\psi\rangle_{LR})=1\right]\geq 1-p,$$
  
$$\Pr\left[\bigwedge_{j:j\leq i}\operatorname{out}_{j}(x',y',|\psi'\rangle_{LR})=1\wedge\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(x',y',|\psi'\rangle_{LR})=1\right]\geq 1-p.$$

From Fact 2,  $|\psi\rangle_{LR} = \sum_j \sqrt{p_j} |\psi_j\rangle_L |\phi_j\rangle_R$  and  $|\psi'\rangle_{LR} = \sum_j \sqrt{p'_j} |\psi'_j\rangle_L |\phi'_j\rangle_R$ . Let  $\rho = \operatorname{tr}_R |\psi\rangle \langle\psi|_{LR} = \sum_j p_j |\psi_j\rangle \langle\psi_j|$ ,  $\sigma = \operatorname{tr}_L |\psi\rangle \langle\psi|_{LR} = \sum_j p_j |\phi_j\rangle \langle\phi_j|$ ,  $\rho' = \operatorname{tr}_R |\psi'\rangle \langle\psi'|_{LR} = \sum_j p'_j |\psi'_j\rangle \langle\psi'_j|$  and  $\sigma' = \operatorname{tr}_L |\psi'\rangle \langle\psi'|_{LR} = \sum_j p'_j |\phi'_j\rangle \langle\phi'_j|$ . Let us consider the case where the input are distinct x and y' and the proof  $\rho \otimes \sigma'$ . Since  $\sum_{j=i}^{i+1} c(v_j) = 0$  and the protocol  $\mathcal{P}$  has only 1-round communication,

$$\Pr\left[\bigwedge_{j:j\leq i}\mathsf{out}_j(x,y,|\psi\rangle_{LR})=1\right]=\Pr\left[\bigwedge_{j:j\leq i}\mathsf{out}_j(x,y,\rho\otimes\sigma)=1\right]=\Pr\left[\bigwedge_{j:j\leq i}\mathsf{out}_j(x,y',\rho\otimes\sigma')=1\right]$$

$$\Pr\left[\bigwedge_{j:j\geq i+1}\mathsf{out}_j(x',y',|\psi'\rangle_{LR})=1\right]=\Pr\left[\bigwedge_{j:j\geq i+1}\mathsf{out}_j(x',y',\rho'\otimes\sigma')=1\right]=\Pr\left[\bigwedge_{j:j\geq i+1}\mathsf{out}_j(x,y',\rho\otimes\sigma')=1\right]$$

Therefore, we have

$$\begin{aligned} &\Pr\left[\bigwedge_{j:j\leq i}\operatorname{out}_{j}(x,y',\rho\otimes\sigma')=1\wedge\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(x,y',\rho\otimes\sigma')=1\right]\\ &\geq 1-\Pr\left[\neg\bigwedge_{j:j\leq i}\operatorname{out}_{j}(x,y',\rho\otimes\sigma')=1\right]-\Pr\left[\neg\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(x,y',\rho\otimes\sigma')=1\right]\\ &= 1-\Pr\left[\neg\bigwedge_{j:j\leq i}\operatorname{out}_{j}(x,y,|\psi\rangle)=1\right]-\Pr\left[\neg\bigwedge_{j:j\geq i+1}\operatorname{out}_{j}(x',y',|\psi'\rangle)=1\right]\\ &\geq 1-2p,\end{aligned}$$

as claimed.

**Proposition 54.** Let f be a function which has a 1-fooling set of size at least 2. Let  $\mathcal{P}$  be a  $\nu$ -round dQMA protocol for f on the path of length r with a proof of size satisfying  $\sum_{j=0}^{r} c(v_j) \leq \lfloor \frac{r-1}{2\nu} \rfloor - 1$ , and completeness 1 - p. Then,  $\mathcal{P}$  has soundness error at least 1 - 2p.

*Proof.* From the pigeonhole principle, if  $\sum_{j=i}^{i+1} c_j \leq \lfloor \frac{r-1}{2\nu} \rfloor - 1$ , there exists  $i \in [1, r-2]$  such that  $\sum_{j=i}^{i+1} c(v_j) = 0$ . Then, from Lemma 53, we have the claim.

**Corollary 55.** Let  $f^+: (\{0,1\}^n)^2 \to \{0,1\}$  be any non-constant Boolean function. Let  $\mathcal{P}$  be a constant-round dQMA protocol for  $f^+$  on the path of length r with completeness 1-p and soundness error at least 1-2p. Then  $\mathcal{P}$  satisfies  $\sum_{j=0}^r c(v_j) = \Omega(r)$ .

Combining the two lower bounds on entangled proofs, we have a lower bound below.

**Theorem 56.** Let  $f : (\{0,1\}^n)^2 \to \{0,1\}$  be a Boolean function with a 1-fooling set of size  $2^n$  (including EQ and GT). Let  $\mathcal{P}$  be a constant-round dQMA protocol for f on the path of length r with completeness  $\frac{3}{4}$  and soundness  $\frac{1}{4}$ . Then,  $\mathcal{P}$  satisfies  $\sum_{j=0}^r c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1}) = \Omega((\log n)^{1/4-\epsilon})$  for any constant  $\epsilon > 0$ .

 $\begin{array}{l} Proof. \text{ From Theorem 52 and Corollary 55}, \ \sum_{j=0}^{r} c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1}) \geq \sum_{j=0}^{r} c(v_j) = \\ \Omega(r) \text{ and } \sum_{j=0}^{r} c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1}) = \Omega(\frac{(\log n)^{1/2-\epsilon}}{r^{1+\epsilon'}}) \text{ for any constants } \epsilon, \epsilon' > 0. \text{ Since for any constant } \epsilon'' > 0, \text{ there exist } \epsilon, \epsilon' > 0 \text{ such that } \max\{r, \frac{(\log n)^{1/2-\epsilon}}{r^{1+\epsilon'}}\} \geq (\log n)^{1/4-\epsilon''} \text{ for any } r, \text{ we have } \sum_{j=0}^{r} c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1}) = \Omega((\log n)^{1/4-\epsilon''}) \text{ for any constant } \epsilon'' > 0. \end{array}$ 

### 8.2 By a reduction to lower bounds of QMA communication protocols

In this subsection, we prove lower bounds of dQMA protocols by a reduction to a lower bound of the two nodes case.

Klauck [Kla11] derived lower bounds on QMA communication protocols for some predicates. To prove the lower bounds, he first observed the proof efficient error reduction for QMA [MW05] works for the QMA communication protocols as well. Then, after the error reduction, he considered to replace a proof with a maximally entangled state (which can be generated by Alice) and have an unbounded error communication protocol. Klauck finally derived a quantum communication

lower bound for such the unbounded-error communication protocol exploiting the one-sided smooth discrepancy [Kla11].

Let us denote by  $sdisc^{1}(f)$  the one-sided smooth discrepancy of a function f and see Definition 8 and 9 in [Kla11] for the definition of the one-sided smooth discrepancy.

**Lemma 57** (Theorem 2 in [Kla11]).  $QMAcc(f) = \Omega\left(\sqrt{\log sdisc^1(f)}\right)$ .

**Definition 17** (Disjointness). The disjoint function DISJ receives two n-bit strings x and y as inputs. DISJ $(x, y) := \bigwedge_{i=1,\dots,n} (\neg x_i \lor \neg y_i).$ 

Corollary 58 (Theorem 1 in [Kla11]).  $QMAcc(DISJ) = \Omega(n^{\frac{1}{3}}).$ 

**Definition 18.** The inner product function receives two n-bit strings x and y as inputs.  $\mathsf{IP}_2(x, y) = \bigoplus_{i=1,...,n} (x_i \wedge y_i).$ 

Lemma 59 (Corollary 1 in [Kla11]).  $QMAcc(IP_2) = \Omega(n^{\frac{1}{2}}).$ 

Sherstov [She11] introduced the pattern matrices, which is a method to convert a Boolean function into a hard communication problem.

**Definition 19** (Pattern Matrices, Definition 5 in [Kla11]). For a function  $f : \{0,1\}^n \to \{0,1\}$ , the pattern matrix  $P_f$  is the communication matrix of the following problem: Alice receives a bit string x of length 2n, Bob receives two bit strings y, z of length n each. The output of the function described by  $P_f$  on inputs x, y, z is  $f(x(y) \oplus z)$ , where  $\oplus$  is the bitwise xor, and x(y) denotes the n bit string that contains  $x_{2i-y_i}$  in position i = 1, ..., n.

AND function is defined by  $AND(x_1, \ldots, x_n) = x_1 \wedge \cdots \wedge x_n$ .

Lemma 60 (Corollary 2 in [Kla11]).  $QMAcc(P_{AND}) = \Omega(n^{\frac{1}{3}}).$ 

We observe that the result and proof strategy of [Kla11] still hold for QMA<sup>\*</sup> communication protocols. One reason is that a maximally mixed state over Alice and Bob is a separable state between Alice and Bob and it can be produced by Alice and Bob with no communication. Another reason is the proof-efficient error reduction of the QMA communication protocols from [MW05] also holds for the QMA<sup>\*</sup> communication protocols. Moreover, the rest of the proof is the same for such an unbounded-error communication protocol, obtaining a quantum lower bound.

**Fact 6.** Assume that there exists a QMA<sup>\*</sup> communication protocol with proof length  $\gamma_1$  and  $\gamma_2$  and communication length  $\mu$  with bounded error. Then, there exists a QMA<sup>\*</sup> communication protocol with proof length  $\gamma_1$  and  $\gamma_2$  and communication length  $O(\mu \cdot k)$  and error  $\frac{1}{2k}$ .

Claim 61. QMAcc<sup>\*</sup>(
$$f$$
) =  $\Omega\left(\sqrt{\log \mathsf{sdisc}^1(f)}\right)$ 

 $\textbf{Corollary 62. } \mathsf{QMAcc}^*(\mathsf{DISJ}) = \Omega(n^{\frac{1}{3}}), \ \mathsf{QMAcc}^*(\mathsf{IP}_2) = \Omega(n^{\frac{1}{2}}), \ \mathsf{QMAcc}^*(P_{\mathsf{AND}}) = \Omega(n^{\frac{1}{3}}).$ 

Then, we obtain a lower bound of dQMA by a reduction to the lower bound of Claim 61.

**Theorem 63.** Assume that  $\mathcal{P}$  is a dQMA protocol on the path of length r with arbitrary rounds to solve f with completeness  $\frac{2}{3}$  and soundness  $\frac{1}{3}$ . Then,  $\mathcal{P}$  satisfies  $\sum_{j=0}^{r} c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1}) = \Omega(\sqrt{\log \operatorname{sdisc}^1(f)}).$ 

Proof. Let us consider reductions from a dQMA protocol to a QMA<sup>\*</sup> communication protocol in (slightly) different ways depending on how we split all the nodes into two groups. Let us name each reduction an *i*-th reduction when we consider that  $v_0, \ldots, v_i$  is one set of nodes and  $v_{i+1}, \ldots, v_r$  is the other set for  $i \in \{0, \ldots, r-1\}$  and the reductions can be described as Algorithm 11. The QMA<sup>\*</sup> communication protocol after the reductions has completeness  $\frac{2}{3}$  and soundness  $\frac{1}{3}$  and its complexity is  $\sum_{j=0}^{r} c(v_j) + m(v_i, v_{i+1})$ . The complexity must be  $\Omega\left(\sqrt{\log \operatorname{sdisc}^1(f)}\right)$  for all *i* from Claim 61, which implies the claim.

#### Algorithm 11 *i*-th reduction from a dQMA protocol to a QMA<sup>\*</sup> communication protocol

- 1: Alice receives a  $\left(\sum_{j=0}^{i} c(v_j)\right)$ -qubit state and Bob receives a  $\left(\sum_{j=i+1}^{r} c(v_j)\right)$ -qubit state from a prover (Merlin).
- 2: Alice simulates the computation and communication of the nodes  $v_0, \ldots, v_i$  communicating with Bob by  $m(v_i, v_{i+1})$  qubits. Bob simulates the computation and communication of the nodes  $v_{i+1}, \ldots, v_r$  communicating with Alice by  $m(v_i, v_{i+1})$ .
- 3: Alice accepts if and only if all the nodes  $v_0, \ldots, v_i$  accept. Bob accepts if and only if all the nodes  $v_{i+1}, \ldots, v_r$  accept.

For concrete functions, we have lower bounds from Theorem 63.

**Corollary 64.** Assume that  $\mathcal{P}$  is a dQMA protocol on the path of length r with arbitrary rounds to solve DISJ with completeness  $\frac{2}{3}$  and soundness  $\frac{1}{3}$ . Then,  $\mathcal{P}$  satisfies  $\sum_{j=0}^{r} c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1}) = \Omega(n^{\frac{1}{3}})$ .

**Corollary 65.** Assume that  $\mathcal{P}$  is a dQMA protocol on the path of length r with arbitrary rounds to solve IP<sub>2</sub> with completeness  $\frac{2}{3}$  and soundness  $\frac{1}{3}$ . Then,  $\mathcal{P}$  satisfies  $\sum_{j=0}^{r} c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1}) = \Omega(n^{\frac{1}{2}})$ .

**Corollary 66.** Assume that  $\mathcal{P}$  is a dQMA protocol on the path of length r with arbitrary rounds to solve  $P_{\text{AND}}$  with completeness  $\frac{2}{3}$  and soundness  $\frac{1}{3}$ . Then,  $\mathcal{P}$  satisfies  $\sum_{j=0}^{r} c(v_j) + \min_{j \in [0,r-1]} m(v_j, v_{j+1}) = \Omega(n^{\frac{1}{3}})$ .

# Acknowledgements

Part of the work was done while AH was visiting Nagoya University and the Institute for Quantum Computing, University of Waterloo, and AH is grateful to their hospitality. AH would like to thank Richard Cleve, François Le Gall, Masayuki Miyamoto, Yuki Takeuchi, Seiichiro Tani and Eyuri Wakakuwa for helpful discussions.

AH is supported by JSPS KAKENHI grants Nos. JP22J22563 and NICT Quantum Camp 2023. SK is funded by the Natural Sciences and Engineering Research Council of Canada (NSERC) Discovery Grants Program and Fujitsu Labs America. Research at the Institute for Quantum Computing (IQC) is supported by Innovation, Science and Economic Development (ISED) Canada. HN is supported by the JSPS KAKENHI grants JP19H04066, JP20H05966, JP21H04879, JP22H00522 and by the MEXT Q-LEAP grants JPMXS0120319794.

# References

| [Aar16]   | Scott Aaronson. The complexity of quantum states and transformations: from quantum money to black holes. arXiv preprint arXiv:1607.05256, 2016. $10$  |  |  |  |  |
|-----------|---|--|--|--|--|
| [AF14]    | Heger Arfaoui and Pierre Fraigniaud. What can be computed without communications? ACM SIGACT News, $45(3)$ :82–104, 2014. 3   |  |  |  |  |
| [AKN98]   | Dorit Aharonov, Alexei Kitaev, and Noam Nisan. Quantum circuits with mixed states. In <i>Proceedings of the 30th annual ACM symposium on Theory of computing (STOC 1998)</i> , pages 20–30, 1998. 34                            |  |  |  |  |
| [AN02]    | Dorit Aharonov and Tomer Naveh. Quantum NP - A Survey. $arXiv\ preprint\ quant-ph/0210077,\ 2002.$ 22, 34   |  |  |  |  |
| [BBD+97]  | Adriano Barenco, André Berthiaume, David Deutsch, Artur Ekert, Richard Jozsa, and Chiara Macchiavello. Stabilization of quantum computations by symmetrization. <i>SIAM Journal on Computing</i> , 26(5):1541–1557, 1997. 8, 17 |  |  |  |  |
| [BC08]    | Hans-Jurgen Bandelt and Victor Chepoi. Metric graph theory and geometry: a survey. <i>Contemporary Mathematics</i> , 453:49–86, 2008. <b>31</b> , <b>32</b>   |  |  |  |  |
| [BCH06]   | Dave Bacon, Isaac L. Chuang, and Aram W. Harrow. Efficient Quantum Circuits for Schur and Clebsch-Gordan Transforms. <i>Phys. Rev. Lett.</i> , 97:170502, 2006. 8, 18   |  |  |  |  |
| [BCMdW10] | Harry Buhrman, Richard Cleve, Serge Massar, and Ronald de Wolf. Nonlocality and communication complexity. <i>Reviews of Modern Physics</i> , 82(1):665, 2010. 13  |  |  |  |  |
| [BCWdW01] | Harry Buhrman, Richard Cleve, John Watrous, and Ronald de Wolf. Quantum fingerprinting. <i>Phys. Rev. Lett.</i> , 87:167902, 2001. 4, 8, 9, 17  |  |  |  |  |
| [BdW01]   | Harry Buhrman and Ronald de Wolf. Communication complexity lower bounds by polynomials. In <i>Proceedings 16th Annual IEEE Conference on Computational Complexity (CCC 2001)</i> , pages 120–130, 2001. 37                      |  |  |  |  |
| [BOH05]   | Michael Ben-Or and Avinatan Hassidim. Fast quantum byzantine agreement. In <i>Proceedings of the thirty-seventh annual ACM symposium on Theory of computing</i> (STOC 2005), pages 481–485, 2005. 3                             |  |  |  |  |
| [BT08]    | Anne Broadbent and Alain Tapp. Can quantum mechanics help distributed computing? ACM SIGACT News, 39(3):67–76, 2008. 3  |  |  |  |  |

- [Che88] Victor Chepoi. Isometric subgraphs of hamming graphs and d-convexity. *Cybernetics*, 24(1):6–11, 1988. 32
- [Che17] Victor Chepoi. Distance-preserving subgraphs of johnson graphs. *Combinatorica*, 37(6):1039–1055, 2017. 32
- [CHFG<sup>+</sup>22] Keren Censor-Hillel, Orr Fischer, François Le Gall, Dean Leitersdorf, and Rotem Oshman. Quantum Distributed Algorithms for Detection of Cliques. In Proceedings of 13th Innovations in Theoretical Computer Science Conference (ITCS 2022), volume 215 of LIPIcs, pages 35:1–35:25, 2022. 3
- [Chr06] Matthias Christandl. The Structure of Bipartite Quantum States Insights from Group Theory and Cryptography. PhD thesis, University of Cambridge, 2006. 18
- [CHTW04] Richard Cleve, Peter Hoyer, Benjamin Toner, and John Watrous. Consequences and limits of nonlocal strategies. In *Proceedings. 19th IEEE Annual Conference on Computational Complexity (CCC 2004)*, pages 236–249, 2004.
- [CHW07] Andrew M. Childs, Aram W. Harrow, and Paweł Wocjan. Weak fourier-schur sampling, the hidden subgroup problem, and the quantum collision problem. In Proceedings of 24th Symposium on Theoretical Aspects of Computer Science (STACS 2007), pages 598–609, 2007. 17
- [CRdG<sup>+</sup>23] Xavier Coiteux-Roy, Francesco d'Amore, Rishikesh Gajjala, Fabian Kuhn, François Le Gall, Henrik Lievonen, Augusto Modanese, Marc-Olivier Renou, Gustav Schmid, and Jukka Suomela. No distributed quantum advantage for approximate graph coloring. arXiv preprint arXiv:2307.09444, 2023. 3
- [DL97] Michel Marie Deza and Monique Laurent. *Geometry of cuts and metrics*, volume 15 of *Algorithms and combinatorics*. Springer, 1997. **31**
- [DM18] João F Doriguello and Ashley Montanaro. Quantum sketching protocols for hamming distance and beyond. *arXiv preprint arXiv:1810.12808*, 2018. **31**, 32
- [DP08] Vasil S Denchev and Gopal Pandurangan. Distributed quantum computing: A new frontier in distributed systems or science fiction? ACM SIGACT News, 39(3):77–95, 2008. 3
- [dW01] Ronald de Wolf. *Quantum Computing and Communication Complexity*. PhD thesis, University of Amsterdam, 2001. 9, 37
- [dW02] Ronald de Wolf. Quantum communication and complexity. *Theoretical computer* science, 287(1):337–353, 2002. 13
- [dW19] Ronald de Wolf. Quantum computing: Lecture notes. *arXiv preprint arXiv:1907.09415*, 2019. 12
- [EKNP14] Michael Elkin, Hartmut Klauck, Danupon Nanongkai, and Gopal Pandurangan. Can quantum communication speed up distributed computation? In Proceedings of the 2014 ACM symposium on Principles of distributed computing (PODC 2014), pages 166–175, 2014. 3

- [FGNP21] Pierre Fraigniaud, François Le Gall, Harumichi Nishimura, and Ami Paz. Distributed Quantum Proofs for Replicated Data. In Proceedings of 12th Innovations in Theoretical Computer Science Conference (ITCS 2021), volume 185 of LIPIcs, pages 28:1–28:20, 2021. 3, 4, 5, 8, 9, 16, 17, 18, 23, 25, 30
- [FPSP19] Pierre Fraigniaud, Boaz Patt-Shamir, and Mor Perry. Randomized proof-labeling schemes. *Distributed Computing*, 32:217–234, 2019. **3**
- [Fra10] Pierre Fraigniaud. Distributed computational complexities: are you volvo-addicted or nascar-obsessed? In Proceedings of the 29th ACM SIGACT-SIGOPS symposium on Principles of distributed computing (PODC 2010), pages 171–172, 2010. 3
- [FvdG99] Christopher A Fuchs and Jeroen van de Graaf. Cryptographic distinguishability measures for quantum-mechanical states. *IEEE Transactions on Information Theory*, 45(4):1216–1227, 1999. 12
- [Gha24] Sevag Gharibian. Guest column: The 7 faces of quantum NP. ACM SIGACT News, 54(4):54–91, 2024. 10
- [GKdW04] Dmytro Gavinsky, Julia Kempe, and Ronald de Wolf. Quantum communication cannot simulate a public coin. arXiv preprint quant-ph/0411051, 2004. 29
- [GKdW06] Dmitry Gavinsky, Julia Kempe, and Ronald de Wolf. Strengths and weaknesses of quantum fingerprinting. In *Proceedings of 21st Annual IEEE Conference on Computational Complexity (CCC 2006)*, pages 288–295, 2006. 32
- [GKM09] Cyril Gavoille, Adrian Kosowski, and Marcin Markiewicz. What can be observed locally? round-based models for quantum distributed computing. In Proceedings of International Symposium on Distributed Computing (DISC 2009), pages 243–257, 2009. 3
- [GM18] François Le Gall and Frédéric Magniez. Sublinear-time quantum computation of the diameter in CONGEST networks. In *Proceedings of the 2018 ACM Symposium on Principles of Distributed Computing (PODC 2018)*, pages 337–346, 2018. **3**
- [GMN23a] François Le Gall, Masayuki Miyamoto, and Harumichi Nishimura. Distributed Merlin-Arthur Synthesis of Quantum States and Its Applications. In Proceedings of 48th International Symposium on Mathematical Foundations of Computer Science (MFCS 2023), volume 272 of LIPIcs, pages 63:1–63:15, 2023. 10, 11, 23, 24
- [GMN23b] François Le Gall, Masayuki Miyamoto, and Harumichi Nishimura. Distributed Quantum Interactive Proofs. In *Proceedings of 40th International Symposium on Theoretical Aspects of Computer Science (STACS 2023)*, volume 254 of *LIPIcs*, pages 42:1–42:21, 2023. 10
- [GNR19] François Le Gall, Harumichi Nishimura, and Ansis Rosmanis. Quantum Advantage for the LOCAL Model in Distributed Computing. In 36th International Symposium on Theoretical Aspects of Computer Science (STACS 2019), volume 126 of LIPIcs, pages 49:1–49:14, 2019. 3

- [GR22] François Le Gall and Ansis Rosmanis. Non-trivial lower bound for 3-coloring the ring in the quantum LOCAL model. *arXiv preprint arXiv:2212.02768*, 2022. 3
- [GS16] Mika Göös and Jukka Suomela. Locally checkable proofs in distributed computing. *Theory of Computing*, 12(19):1–33, 2016. 3, 11
- [Har05] Aram W. Harrow. Applications of coherent classical communication and the Schur transform to quantum information theory. PhD thesis, Massachusetts Institute of Technology, 2005. 17, 18
- [IG19] Taisuke Izumi and François Le Gall. Quantum distributed algorithm for the allpairs shortest path problem in the CONGEST-CLIQUE model. In Proceedings of the 2019 ACM Symposium on Principles of Distributed Computing (PODC 2019), pages 84–93, 2019. 3
- [IGM20] Taisuke Izumi, François Le Gall, and Frédéric Magniez. Quantum Distributed Algorithm for Triangle Finding in the CONGEST Model. In 37th International Symposium on Theoretical Aspects of Computer Science (STACS 2020), volume 154 of LIPIcs, pages 23:1–23:13, 2020. 3
- [IV12] Tsuyoshi Ito and Thomas Vidick. A multi-prover interactive proof for NEXP sound against entangled provers. In 2012 IEEE 53rd Annual Symposium on Foundations of Computer Science (FOCS 2012), pages 243–252, 2012. 7
- [JL84] William B Johnson and Joram Lindenstrauss. Extensions of lipschitz mappings into a hilbert space. In *Conference on Modern Analysis and Probability*, volume 26, pages 189–206. American Mathematical Society, 1984. 32
- [JNV<sup>+</sup>21] Zhengfeng Ji, Anand Natarajan, Thomas Vidick, John Wright, and Henry Yuen. MIP<sup>\*</sup>= RE. Communications of the ACM, 64(11):131–138, 2021. 7
- [KKP10] Amos Korman, Shay Kutten, and David Peleg. Proof labeling schemes. *Distributed Computing*, 22(4):215–233, 2010. 3, 23
- [Kla11] Hartmut Klauck. On Arthur Merlin games in communication complexity. In Proceedings of 26th Annual IEEE Conference on Computational Complexity (CCC 2011), pages 189–199, 2011. 7, 10, 14, 41, 42
- [KN96] Eyal Kushilevitz and Noam Nisan. *Communication Complexity*. Cambridge University Press, 1996. 13
- [KNY08] Masaru Kada, Harumichi Nishimura, and Tomoyuki Yamakami. The efficiency of quantum identity testing of multiple states. *Journal of Physics A: Mathematical and Theoretical*, 41(39):395309, 2008. 8, 17
- [KOS18] Gillat Kol, Rotem Oshman, and Raghuvansh R Saxena. Interactive distributed proofs. In Proceedings of the 2018 ACM Symposium on Principles of Distributed Computing (PODC 2018), pages 255–264, 2018. 10

[KP14] Hartmut Klauck and Supartha Podder. Two results about quantum messages. In International Symposium on Mathematical Foundations of Computer Science (MFCS 2014), pages 445–456. Springer, 2014. 36 [KSV02] Alexei Yu Kitaev, Alexander Shen, and Mikhail N Vyalyi. Classical and quantum computation. Number 47. American Mathematical Soc., 2002. 10, 22, 34 [LZ13] Yang Liu and Shengyu Zhang. Quantum and randomized communication complexity of XOR functions in the SMP model. *Electronic Colloquium on Computational* Complexity (ECCC), TR13-010, 2013. 29, 33 [McK13] Matthew McKague. On the power quantum computation over real Hilbert spaces. International Journal of Quantum Information, 11(01):1350001, 2013. 36 [MdW16]Ashley Montanaro and Ronald de Wolf. A Survey of Quantum Property Testing. Number 7 in Graduate Surveys. Theory of Computing Library, 2016. 17 [MN22] Frédéric Magniez and Ashwin Nayak. Quantum distributed complexity of set disjointness on a line. ACM Transactions on Computation Theory (TOCT), 14(1):1–22, 2022. **3** [MW05] Chris Marriott and John Watrous. Quantum Arthur–Merlin games. computational complexity, 14:122–152, 2005. 41, 42 [NC10] Michael A. Nielsen and Isaac L. Chuang. Quantum Computation and Quantum Information: 10th Anniversary Edition. Cambridge University Press, 2010. 12, 13 [NPY20] Moni Naor, Meray Parter, and Eylon Yogey. The power of distributed verifiers in interactive proofs. In Proceedings of the Fourteenth Annual ACM-SIAM Symposium on Discrete Algorithms (SODA 2020), pages 1096–1115, 2020. 10 [NW19] Anand Natarajan and John Wright. NEEXP is contained in MIP<sup>\*</sup>. In 2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS 2019), pages 510-518, 2019. 7 [Pel00] David Peleg. Distributed computing: a locality-sensitive approach. SIAM, 2000. 23 [Ros08]Bill Rosgen. Distinguishing Short Quantum Computations. In 25th International Symposium on Theoretical Aspects of Computer Science (STACS 2008), volume 1 of LIPIcs, pages 597–608, 2008. 19 [RS04] Ran Raz and Amir Shpilka. On the power of quantum proofs. In Proceedings 19th Annual IEEE Conference on Computational Complexity (CCC 2004), pages 260–274, 2004. Full version is available from the following URL: https://www.cs.tau.ac.il/~shpilka/publications/RazShpilka\_QMA.pdf. Last visited on 2024/01/03. 6, 9, 10, 14, 35, 36 [RY20] Anup Rao and Amir Yehudayoff. Communication Complexity: and Applications. Cambridge University Press, 2020. 13

- [Sco06] Andrew J Scott. Tight informationally complete quantum measurements. Journal of Physics A: Mathematical and General, 39(43):13507, 2006. 18
- [She11] Alexander A Sherstov. The pattern matrix method. SIAM Journal on Computing, 40(6):1969–2000, 2011. 7, 42
- [Shp93] Sergey V Shpectorov. On scale embeddings of graphs into hypercubes. *European Journal of Combinatorics*, 14(2):117–130, 1993. **31**
- [TKM12] Seiichiro Tani, Hirotada Kobayashi, and Keiji Matsumoto. Exact quantum algorithms for the leader election problem. *ACM Transactions on Computation Theory (TOCT)*, 4(1):1–24, 2012. **3**
- [Uhl76] Armin Uhlmann. The "transition probability" in the state space of a \*-algebra. Reports on Mathematical Physics, 9(2):273–279, 1976. 12
- [vAdV22] Joran van Apeldoorn and Tijn de Vos. A framework for distributed quantum queries in the congest model. In Proceedings of the 2022 ACM Symposium on Principles of Distributed Computing (PODC 2022), pages 109–119, 2022. 3
- [Wat18] John Watrous. The Theory of Quantum Information. Cambridge University Press, 2018. 12
- [WY22] Xudong Wu and Penghui Yao. Quantum complexity of weighted diameter and radius in congest networks. In Proceedings of the 2022 ACM Symposium on Principles of Distributed Computing (PODC 2022), pages 120–130, 2022. 3
- [Yao03] Andrew Chi-Chih Yao. On the power of quantum fingerprinting. In *Proceedings of the* 34th annual ACM symposium on Theory of computing (STOC 2003), pages 77–81, 2003. 4, 29
- [Zha11] Shengyu Zhang. On the power of lower bound methods for one-way quantum communication complexity. In International Colloquium on Automata, Languages, and Programming (ICALP 2011), pages 49–60, 2011. 8