# CODA: A COst-efficient Test-time Domain Adaptation Mechanism for HAR

Minghui Qiu

DSA, Hong Kong University of Science and Technology (Guangzhou) Guangzhou, China mqiu585@connect.hkust-gz.edu.cn Yandao Huang CSE, Hong Kong University of Science and Technology Hong Kong, China yhuangfg@connect.ust.hk

Lu Wang CSSE, Shenzhen University Shenzhen, China wanglu@szu.edu.cn

# ABSTRACT

In recent years, emerging research on mobile sensing has led to novel scenarios that enhance daily life for humans, but dynamic usage conditions often result in performance degradation when systems are deployed in real-world settings. Existing solutions typically employ one-off adaptation schemes based on neural networks, which struggle to ensure robustness against uncertain drifting conditions in human-centric sensing scenarios. In this paper, we propose CODA, a COst-efficient Domain Adaptation mechanism for mobile sensing that addresses real-time drifts from the data distribution perspective with active learning theory, ensuring cost-efficient adaptation directly on the device. By incorporating a clustering loss and importance-weighted active learning algorithm, CODA retains the relationship between different clusters during cost-effective instance-level updates, preserving meaningful structure within the data distribution. We also showcase its generalization by seamlessly integrating it with Neural Network-based solutions for Human Activity Recognition tasks. Through meticulous evaluations across diverse datasets, including phone-based, watch-based, and integrated sensor-based sensing tasks, we demonstrate the feasibility and potential of online adaptation with CODA. The promising results achieved by CODA, even without learnable parameters, also suggest the possibility of realizing unobtrusive adaptation through specific application designs with sufficient feedback.

# **CCS CONCEPTS**

• Human-centered computing  $\rightarrow$  Ubiquitous and mobile computing systems and tools.

### **KEYWORDS**

Human activity recognition; Mobile sensing; Active learning; Model adaptation

### **1** INTRODUCTION

Human Activity Recognition (HAR) is a pivotal focus in humancentric mobile sensing, with diverse applications including gesture recognition [5, 11], cardiovascular monitoring [4, 12], sleep quality monitoring [9, 22], and inference on daily habits [2, 17]. HAR plays a crucial role in physical and mental healthcare, detecting human falls Lin Chen

DSA, Hong Kong University of Science and Technology (Guangzhou) Guangzhou, China Ichen297@connect.hkust-gz.edu.cn

Kaishun Wu DSA & IoT, Hong Kong University of Science and Technology (Guangzhou) Guangzhou, China wuks@hkust-gz.edu.cn



Figure 1: Unexpected degradations of the system in the wild probably result from the uncertain drifting of the data distribution (in both durations and directions).

[14, 31], monitoring exercise performance [10, 20], and predicting emotional states [16, 19].

While Human Activity Recognition (HAR) has yielded promising outcomes, the adaptability of proposed systems can be hindered in practical scenarios, leading to performance degradation or failure under changing usage conditions [21, 26, 30]. From a user perspective, pretrained HAR models may lack generalization for unseen users due to substantial variations in behavioral habits and physiological characteristics among individuals.

Consider, for instance, gesture recognition with a smartwatch, where users may exhibit different starting positions, writing speeds, and ranges when forming characters in the air (e.g., the number "8"). From the device perspective, diverse sensor specifications, device types, positions, and orientations introduce variability in signal patterns for the same action. Consequently, users may be compelled to undergo a cumbersome instance collection process for model calibration, posing challenges to the large-scale deployment of HAR on mobile devices.

To address these challenges, various adaptation techniques from machine learning theory have been introduced. Suzuki et al. [27] propose a generative adversarial network (GAN)-based style transformation to synthesize personal data, alleviating users' efforts in model calibration. Additionally, studies [1, 13, 18, 23] adopt transfer learning principles, aligning data distribution across different domains to obviate the need for model retraining. Some approaches Conference'17, July 2017, Washington, DC, USA



Figure 2: We observe the driftings at time  $T_1$  comparing to the initialization phase at time  $T_0$  with hand-tune features.

[7, 8] incorporate meta-learning ideas to facilitate faster adaptation with minimal training data. Despite these innovative mechanisms, ensuring long-term performance in mobile sensing scenarios, particularly for human-centric applications, remains a persistent challenge. One concern arises from the dynamic nature of practical scenarios where controlling user behaviors is challenging for service providers. Users can change their behaviors at will, and strenuous motions may alter the orientation or displacement of a mobile device mounted on the user. A one-off adaptation approach proves insufficient for the practical deployment of mobile sensing. Another challenge lies in the scarcity of real-world data, exacerbated by the limited volume of available data. The contingency of changes further restricts the availability of specific problem-related data in real-world scenarios.

To address these challenges, illustrated in Figure 1, we attribute system degradation to changes in data distribution and propose leveraging instances as direct indicators. Specifically, we explore the potential of adaptation with nearest neighbors, functioning akin to a 'cache' by predicting through pairing with cached candidates. Building on the understanding of class relationships, we introduce CODA, a COst-efficient test-time Domain Adaptation mechanism for mobile sensing. CODA integrates importance-weighted active learning [3] and a necessary retentive reweighting strategy, enabling robust adaptation to uncertainty, even without trainable parameters.

The evaluation incorporates two public and two self-collected datasets, featuring diverse devices such as integrated sensors, smartphones, and smartwatches, as well as varying user profiles. After specifying the recognition pipeline for each dataset, we conduct a pilot study for baseline comparison, demonstrating the general performance of CODA.

The contributions of this paper are outlined as follows:

- We tackle adaptation challenges through a straightforward Nearest Neighbor idea and introduce CODA, marking it as the first continual test-time domain adaptation framework integrated with active learning for mobile sensing, to the best of our knowledge.
- We conduct a comprehensive evaluation of CODA on two common tasks: activity of daily living recognition and gesture recognition in Human Activity Recognition (HAR) scenarios. Across experiments on four datasets (two public and

Minghui Qiu, Yandao Huang, Lin Chen, Lu Wang, and Kaishun Wu



Figure 3: The drifting at time  $T_1$  could not be resolved with few-shot adaptation (by MetaSense[8]).

two self-collected datasets, captured with three different models), we validate CODA's designs and demonstrate its generality through performance in diverse settings. Augmented feature experiments also suggest potential improvements with additional deep learning mechanisms.

# 2 BACKGROUND AND MOTIVATION

# 2.1 Domain Drifting in Human Activity

Recently, researchers have utilized mobile devices (smart phones and watches .etc) to implement many interesting HAR applications. These HAR applications are built upon the essential assumption [25] that different activities have unique and stable patterns that can be characterized using sensor data (e.g., inertial measurement unit (IMU), electromyography (EMG), electrocardiography (ECG), and PPG data). However, the patterns are distorted when the usage conditions change. The literature [21, 26, 30] has empirically proven that condition changes cause HAR system performance to degrade in practical scenarios. To further address the challenge of drifting in practical usage, we have the data collected with minimum control on the user behaviors for two different types of scenarios (TAPRINT for gesture recognition, and WHAR for human activity recognition) . We further inspect the data distributions by adopting Isomap [28], a visualization technique that helps retain the global structure of data in the high dimensional space, and observe the driftings along the time on both datasets. The figures 2 show two typical drifting that could appear within the same trace of collection. We also reimplement MetaSense[8], which is a domain adaptation technique for HAR scenes. And the drifting remains obvious regardless of the simple or extracted feature space.

# 2.2 Domain Adaptation for Human Activity Recognition.

To alleviate the degradation of system performance caused by drift, many domain adaptation solutions from machine learning theory have been proposed in recent years. Broadly, they can be divided into three main approaches. Firstly, an intuitive solution is to collect or generate the related dataset that is sufficient to cover the drifting influence. Suzuki et al. [27] integrates the CycleGAN to generate personal sensory data with only partial observations. Similarly, Kwon et al. [15] explore the idea of generating sensor data from videos to enhance the performance of pre-trained model. The CODA: A COst-efficient Test-time Domain Adaptation Mechanism for HAR



second kind of solutions[1, 13, 18, 23] supposes the variance could be mitigated by aligning the data distribution, and integrates series of transfer learning techniques. The other solutions [7, 8] focus on enhancing the learning efficiency and propose to deploy the system with meta-learning. The mentioned solutions have made progress towards practical deployment with uncertainty in the wild. However, it could be still challenging for these domain adaptation solution due to the fact that the dynamicity in practice. In response, we propose a simple mechanism that uses a Nearest Neighbor as the downstream predictor and allows continuously adapting to the human activity scenarios with a low cost and limited users collaboration.

### 2.3 Active Learning for Candidates Evaluation.

Active learning is a machine learning approach where the algorithm interactively selects the most informative data points to be labeled by a human oracle. This minimizes the amount of labeled data required for model training, making it useful in scenarios where labeled data is expensive or time-consuming to obtain. It has applications in various domains such as document classification, image recognition, and bioinformatics. In CODA, we adopt an Active Learning technique, Importance Weighted Active Learning, to guarantee the consistent performance during the test-time domain adaptation with the Nearest Neighbor Model.

# 3 ONLINE ADAPTATION WITH ACTIVE LEARNING

CODA functions as a 'cache' for human activity recognition using an instance-based model as the predictor. The framework comprises three main routines, shown in figure 4. The first routine involves classification (Step 1), where an instance undergoes detection, preprocessing, and feature extraction before being paired with other instances in the caches for prediction. The interface provides feedback (Step 2) triggering the agent to evaluate and update the 'caches' (Step 3). The agent, essential for enabling adaptation, operates on an Importance Weighted Active Learning (IWAL) algorithm. At each timestep, the agent assesses the instance's importance using the 'Rejection-Threshold' subroutine and updates the caches through Weighted Empirical Risk Minimization. This section introduces the IWAL algorithm's framework and elaborates on the agent design for human activity recognition, incorporating the instance-based model hypotheses, clustering loss function, and retentive reweighting strategy.

Algorithm 1 Importance-Weighted Active Learning						
1: Set $S_0 = \emptyset$						
2: <b>for</b> t in 1, 2, 3, <b>do</b>						
3: Receive $(x_t, \hat{y}_t)$						
$p_t, H_t = $ <b>Rejection-Threshold</b> $(x_t, \hat{y}_t, S_{t-1}) $ $> $ §3.1.3						
5: Flip a coin $Q_t \in \{0, 1\}$ with $E[Q_t] = p_t$						
6: <b>if</b> $Q_t = 1$ , <b>then</b> set $S_t = S_{t-1} \cup \{(x_t, \hat{y}_t, w_t, t)\}$ ; <b>else</b> $S_t = S_{t-1}$						
7: $h_t \leftarrow \arg\min_{h \in H_t} \mathcal{L}_t(h, S_t)$	▷ Weighted ERM					
8: end for						
Algorithm 2 Rejection-Threshold						
Input:						
$x_t, y_t$ : Instance and feedback						
$S_{t-1} = \{(x_i, y_i, w_i, Q_i, t_i) : 1 \le t_i \le t-1\}$						
Output:						

Jul:

- $p_t : \Pi(h(x_t) \neq y_t^*)$   $\triangleright y_t^*$  refers to the ground truth  $H_t \leftarrow$  The pruned hypothesis space 1: Initialize  $H_{t-1}$   $\triangleright$  §3.2.1
- 2: Update  $\mathcal{L}_{t-1}^* = \min_{h \in H_{t-1}} \mathcal{L}_{t-1}(h, S_{t-1})$ 3:  $H_t \leftarrow \left\{ h \in H_{t-1} : \mathcal{L}_{t-1}(h, S_{t-1}) \leq \mathcal{L}_{t-1}^* + \Delta_{t-1} \right\}$ 4:  $p_t \leftarrow \max_{f,g \in H_t, y \in Y} \left[ \ell\left(f(x_t), y\right) - \ell\left(g(x_t), y\right) \right]$ 5: Return  $p_t, H_t$

### 3.1 Importance-Weighted Active Learning

In active learning, the system actively queries oracles, and researchers have proposed metrics to reduce query frequency and select helpful instances. IWAL is a disagreement-based active learning algorithm that evaluates instance disagreement in the hypothesis space with a customized bounded loss. We integrate IWAL into our framework and modify it for passive adaptation. Before detailing our proposed framework, we will present the preliminaries.

3.1.1 Preliminaries. The input space X and output space Y are defined. Sensor data is continuously fed into the adaptation framework as a stream. At each time step t, the agent observes an instance  $x_t \in X$  and its feedback  $\hat{y}_t \in Y$ . The agent then determines the instance's representativeness using a probability  $p_t$ , calculated based on the customized loss function  $\ell : Z \times Y \rightarrow [0, \infty)$  in the current hypothesis space  $H_t = h : X \rightarrow Z$ . In the context of IWAL, a bounded loss  $\ell$  is normalized to a real value in [0, 1]. Further details about the loss function are provided in Section 3.2.

3.1.2 Skeleton of IWAL. Algorithm 1 outlines the IWAL process. At time *t*, the agent receives an instance  $x_t$  and feedback  $\hat{y}_t$ , triggering the *Rejection-Threshold* subroutine (line 4, detailed in algorithm 2). This subroutine considers the past history  $S_{t-1}$  and returns a pruned hypothesis  $H_t$  and a probability  $p_t$ , indicating the instance's importance. An important instance is added to the instance set  $S_t$  with weight  $w = 1/p_t$  (lines 5-6). The final step is empirical risk minimization with a loss function  $\mathcal{L}(h, S_t)$ , where a new hypothesis

 $h_t$  (i.e., the adapted model) is learned based on  $S_t$ . The loss estimate  $\mathcal{L}_t(h, S_t)$  based on the hypothesis regarding the set  $S_t$  is defined as:

$$\mathcal{L}_t(h, St) = \frac{1}{|S_t|} \sum_{(x, y, w, Q) \in S_t} Q \cdot w \cdot \ell(h(x), y)$$
(1)

where the random variable Q (with a Bernoulli distribution and parameter  $p_t$ ) is as defined in algorithm 1.

3.1.3 Rejection Threshold. In passive mode, where feedback knowledge is available, the Rejection-Threshold subroutine first generates the hypothesis space based on prior knowledge (line 1). The minimum loss in  $H_{t-1}$  is  $\mathcal{L}_{t-1}^*$ , as defined on line 2. The subset of Ht - 1 for which the loss is not significantly worse than  $\mathcal{L}_{t-1}^*$  is assigned to  $H_t$  using a slack derived from a standard sample complexity bound to ensure shrinkage following learning theory [29]. This process results in the initial hypothesis space shrinking to a smaller space, with any optimal hypothesis always in  $H_t$ . With the shrunken hypothesis space  $H_t$ , the probability  $p_t$  is calculated as follows:

$$p_t = \max_{f,g \in H_t; y \in Y} \ell(f(x_t), y) - \ell(g(x_t), y)$$
(2)

where the value of  $p_t$  represents the greatest disagreement in  $H_t$  with respect to the instance  $(x_t, y)$  and can be seen as the error probability of the new hypothesis space given the current instance at time t. A higher  $p_t$  indicates higher importance of the current instance. Therefore, the importance weight w is set to  $1/p_t$ , which corrects the instance bias when calculating  $L_t(h, S_t)$ .

### 3.2 IWAL for Nearest Neighbor Model

In traditional IWAL, actively querying an oracle for instances with high  $p_t$  is necessary, and the feedback  $\hat{y}_t$  is not included in the input to the Rejection-Threshold subroutine. In response to this limitation, we propose a revised IWAL algorithm that incorporates feedback in a passive manner. Specifically, we tailor IWAL for an instance-based model, utilizing a distance-based loss function constrained by a flexible kernel. In the following section, we provide detailed insights into this revision and elucidate its effectiveness. To achieve lightweight and adaptable adaptation, we employ learning theory to manage the 'cache' and facilitate online adaptation while upholding memory efficiency and leveraging the adaptability of the instance-based model. This approach is driven by the necessity for a lightweight and flexible online adaptation framework, especially in resource-constrained mobile applications. Our adaptation framework centers on an instance-based model (e.g., K-Nearest Neighbors) instead of a neural-network-based model, and we allocate a fixed cache size N for each class to efficiently manage memory usage.

3.2.1 Clustering Loss Function. We operate under the assumption that instances with a shared label (e.g., walking) should exhibit greater similarity to each other and therefore should form a cluster. Consequently, in this paper, we propose a bounded and similarity-based loss function, known as the clustering loss, which is well-suited for implementation with the instance-based model. More specifically, the soft clustering loss function  $\ell_c$  is defined as follows:

$$\ell_{c}(h(x), y) = \max\left\{0, \hat{E}\left[d(\mathbf{X}_{y}, x)\right] - \min(d(\overline{\mathbf{X}}_{y}, x))\right\}$$
(3)

where the  $\tilde{E}[\mathbf{D}]$  represents the expectation of the vector **D**. The set of instances with class label y is denoted as  $X_y$ , while the remaining instances in the cache are represented by  $\overline{X}_y$ . The term  $d(X_y, x)$ refers to the vector of distances calculated between instance  $u \in X_y$ and x. It's worth noting that the efficiency of this loss stems from the fact that the distances referenced in the components are computed during the classification process.

3.2.2 *Bounded Kernel.* As mentioned previously, the clustering loss we proposed aids in evaluating the instance-based hypotheses while ensuring the bounded attribute required by learning theory. Specifically, the loss is bounded by constructing the distance with a cosine normalized kernel. The distance function is defined as follows:

$$d(u,v) = \sqrt{2 \times \left(1 - \frac{\mathcal{K}(u,v)}{\sqrt{\mathcal{K}(u,u)\mathcal{K}(v,v)}}\right)}$$
(4)

where u and v represent two instances in X, and  $\mathcal{K}$  is a positivedefinite kernel. The selection of the kernel  $\mathcal{K}$  depends on the practical application scenario of interest. It is important to note that different kernel selections will also result in different decision boundaries.

*3.2.3 Retentive Weights.* We also try to enhance the temporal sensitivity and propose to control the adaptation with reweighting function as follows,

$$\ell_t(h(x), y; \Delta t_x) = \mathcal{E}_t(\Delta t_x) \cdot \ell_c(h(x), y)$$
(5)

where the  $\ell_c$  term is defined in Eq. (3). And the  $\mathcal{E}_t$  is a weighting function reflects the temporal importance of the candidate x, parameterized with the timesteps ( $\Delta t_x = t - t_x$ ) since arrival. Particularly, a monotonically decreasing function is empirically adopted in CODA to address the retentive feature, as follows,

$$\mathcal{E}_t(\Delta t_x) = e^{-\Delta t_x} \in (0, 1] \tag{6}$$

where  $\Delta t_x$  refers to the length of the timesteps since the sample *x* presents.

### **4 EVALUATION**

As for the evaluation, we adopt the continual test-time domain adaptation setting. Particularly, the instances with annotations from the predictions or contextual feedback arrive in time order. In this section, we would first have a brief introduction regarding the datasets we use to evaluate the performance of CODA. Then we would present the baselines we compares and the according results.

### 4.1 Datasets And Baselines

In this paper, we evaluate online adaptation performance for two common tasks: Activity for Daily Living (ADLs) recognition and

**Table 1: Summary of Datasets** 

Task	Dataset	#-Subjects	Model(s)	Sample Rate (in Hz)		
				AC	CE.	GYRO.
ADLs	PAMAP2[24]	5	-	100	100	100
	HHAR[26]	8	nexus4	200		
			s3	100 93		-
			sumsungold			
	WHAR <sup>†</sup>	12	LG	200		200
			HW	100		100
			TW	10	)3	103
GR	TAPRINT <sup>†</sup>	9	LG/HW/TW	Same As WHAR		

CODA: A COst-efficient Test-time Domain Adaptation Mechanism for HAR



Figure 5: Illustrations of structures. The output of 1D-CNN is flatterned as the augmented feature in section 4.1.

Gesture Recognition (GR). ADLs involve recognizing the user's state/motion to support applications like health care monitoring, while GR recognizes predefined activities, often groups of gestures.

4.1.1 Datasets Discriptions. We conducted experiments on four datasets covering various devices: PAMAP2, HHAR, WHAR, and TAPRINT. PAMAP2[24] and HHAR[26] were publicly available, while we collected WHAR and TAPRINT data. The datasets encompassed different sensors and devices, providing diverse data for evaluation. We utilized specific signal detection, preprocessing, and feature extraction pipelines (the feature extracted without Neural Network Model is referred to as 'simple feature') tailored to each dataset and task, reflecting real-world scenarios. By default, we implement the CODA with linear kernel. While we adopt the GAK[6] for simple feature in time domain appears to be the most consistent on TAPRINT dataset and Global Alignment Kernel appears to be a feasible kernel that could help retain the performance through solving the alignment issue.

4.1.2 *Baselines.* To further validate the CODA's performance, we propose to compare the performance with the following baselines: *RND*: We compare the baselines with random strategy, where we ask the system to randomly update the hypothesis. For 10-shot setting, that is to randomly replace one out of ten instances with the latest one. To some extend, under fruitful feedback condition, the random strategy represents the least available improvements by online feedback.

*TH*: Time Heuristic strategy is the other trivial strategy. Following the retentive intuition, TH functions as the LRU strategy, where the earliest instance get replaced by the latest one.

**CODA-P:** As the backbone of the CODA strategy, CODA-P refers to the algorithm backbone of IWAL. It evaluates the instance from the model perspective, utilizing all of the historic instances regradless of the temporal information.

**CODA-L:** In CODA, one of the key designs to gather accurate information is the monotonically decreasing function for retentive reweighting. CODA-L refers to the strategy that updates the hypothesis based on the loss function regardless of the historic information. In other words, the strategy flushes away the most dissimilar instance at that time.



Figure 6: Practical online domain adaptation. The underlined ratios are taken for later experiments as Minimum Feedback Ratio.



Figure 7: Practical Online Domain Adaptation (Augmented with MetaSense). The size of a marker only represents the relative value of standard deviation.



Figure 8: Comparison of Latency (ms) by prediciton and adaptation. The models of the smartwatch are marked with the release date.

In addition, we also implement one SOTA meta-learning based domain adaptation technique, **MetaSense**[8]. Precisely, we further tailor the Neural Network model for each datasets to achieve a good performance with MetaSense. The inputs are the simple features and the outputs of the feature extractor of the Neural Network Model are used as the extracted feature.

### 4.2 Experimental Results.

We adopt the test-time domain adaptation setting, that is the instances present one by one along with annotation from the context (either prediction itself or the feedback from the user). In addition, we diverse the frequency of the feedback to inspect the performance when there is a lack of ground truth. And we select the macro  $F_1$ score as the major performance indicator, as it mitigates the impact by imbalanced data.

4.2.1 Practical Continual Test-time Domain Adaptation. As is shown in figure 6 and figure 7, benefiting from the IWAL algorithm, the CODA presents remarkable and consistent performance among the baselines against partially feedback situations. Here we denote the Minimum Feedback Ratio as the point that indicates the prerequisite feedback ratio for the advancing performance by continuous adaptation<sup>1</sup>. The alleviation of the feedback ratio after applying the novel feature extractor trained by MetaSense (i.e. the decreases of the MFR on the datasets ranging from 2.94% to 37.30%) further verifies the claim that the better feature space the less reliance on the feedback.

<sup>&</sup>lt;sup>1</sup>Here we locate the MFR with the performance of MetaSense for its special meaning for domain adaptation, motioned in section 4.1.

Minghui Qiu, Yandao Huang, Lin Chen, Lu Wang, and Kaishun Wu

4.2.2 System Implementation. In this section, we explore the cost of implementing the CODA and RND strategies on Commercial Off-The-Shelf smartwatches for the Taprint scenario. We specifically focused on the computational efficacy of these strategies. For the RND implementation, we streamlined the distance calculation process for fair comparison. In the CODA implementation, we introduced caching of necessary values for importance evaluation and weighted empirical risk minimization. By simulating the typing task on different smartwatch brands, we observed that the CODA strategy demonstrated greater efficacy compared to RND, with minimal impact on computational resources. Despite hardware variations, the median latency with CODA increased by 7ms on LG, 2ms on HW, and decreased by 1ms on TW. These results indicate the low cost in computational resources traded for more robust adaptation.

## 5 CONCLUSION

In this paper, we presented CODA, a continuous online adaptation framework that adjusts the mobile sensing system to uncertain conditions. The key innovation is treating online drifting conditions as a result of changes in data distribution. Integrated with IWAL and a retentive reweighting strategy, CODA achieves robust adaptation with a simple cache-like structure, even without learnable parameters. Comprehensive experiments on four datasets (two of which were self-collected) demonstrate the feasibility and potential of online adaptation. As we propose to commit to online adaptation, our subsequent research will aim to address the feedback requirements by specifying the application design.

#### REFERENCES

- [1] Ali Akbari and Roozbeh Jafari. 2019. Transferring Activity Recognition Models for New Wearable Sensors with Deep Generative Domain Adaptation. In Proceedings of the 18th International Conference on Information Processing in Sensor Networks (IPSN'19). Association for Computing Machinery, New York, NY, USA, 85–96. https://doi.org/10.1145/3302506.3310391 event-place: Montreal, Quebec, Canada.
- [2] Sayma Akther, Nazir Saleheen, Shahin Alan Samiei, Vivek Shetty, Emre Ertin, and Santosh Kumar. 2019. mORAL: An mHealth model for inferring oral hygiene behaviors in-the-wild using wrist-worn inertial sensors. *Proceedings of the ACM* on Interactive, Mobile, Wearable and Ubiquitous Technologies 3, 1 (2019), 1–25.
- [3] Alina Beygelzimer, Sanjoy Dasgupta, and John Langford. 2009. Importance weighted active learning. In Proceedings of the 26th Annual International Conference on Machine Learning - ICML '09. ACM Press, Montreal, Quebec, Canada, 1–8. https://doi.org/10.1145/1553374.1553381
- [4] Nam Bui, Nhat Pham, Jessica Jacqueline Barnitz, Zhanan Zou, Phuc Nguyen, Hoang Truong, Taeho Kim, Nicholas Farrow, Anh Nguyen, Jianliang Xiao, Robin Deterding, Thang Dinh, and Tam Vu. 2019. EBP: A Wearable System For Frequent and Comfortable Blood Pressure Monitoring From User's Ear. In *The 25th Annual International Conference on Mobile Computing and Networking (MobiCom '19)*. Association for Computing Machinery, New York, NY, USA. https://doi.org/10. 1145/3300061.3345454 event-place: Los Cabos, Mexico.
- [5] Wenqiang Chen, Lin Chen, Yandao Huang, Xinyu Zhang, Lu Wang, Rukhsana Ruby, and Kaishun Wu. 2019. Taprint: Secure text input for commodity smart wristbands. In The 25th Annual International Conference on Mobile Computing and Networking. 1–16.
- [6] Marco Cuturi. 2011. Fast Global Alignment Kernels. In Proceedings of the 28th International Conference on Machine Learning, ICML 2011, Bellevue, Washington, USA, June 28 - July 2, 2011.
- [7] Shuya Ding, Zhe Chen, Tianyue Zheng, and Jun Luo. 2020. RF-Net: A Unified Meta-Learning Framework for RF-Enabled One-Shot Human Activity Recognition. In Proceedings of the 18th Conference on Embedded Networked Sensor Systems (SenSys '20). Association for Computing Machinery, New York, NY, USA, 517-530. https://doi.org/10.1145/3384419.3430735 event-place: Virtual Event, Japan.
- [8] Taesik Gong, Yeonsu Kim, Jinwoo Shin, and Sung-Ju Lee. 2019. MetaSense: fewshot adaptation to untrained conditions in deep mobile sensing. In Proceedings of the 17th Conference on Embedded Networked Sensor Systems (SenSys'19). ACM, 110–123. https://doi.org/10.1145/3356250.3360020
- [9] Weixi Gu, Longfei Shangguan, Zheng Yang, and Yunhao Liu. 2015. Sleep hunter: Towards fine grained sleep stage tracking with smartphones. *IEEE Transactions*

on Mobile Computing 15, 6 (2015), 1514-1527.

- [10] Xiaonan Guo, Jian Liu, and Yingying Chen. 2017. FitCoach: Virtual fitness coach empowered by wearable mobile devices. In IEEE INFOCOM 2017-IEEE Conference on Computer Communications. IEEE, 1–9.
- [11] Jiahui Hou, Xiang-Yang Li, Peide Zhu, Zefan Wang, Yu Wang, Jianwei Qian, and Panlong Yang. 2019. Signspeaker: A real-time, high-precision smartwatch-based sign language translator. In *The 25th Annual International Conference on Mobile Computing and Networking*. 1–15.
- [12] Sinh Huynh, Rajesh Krishna Balan, JeongGil Ko, and Youngki Lee. 2019. VitaMon: Measuring heart rate variability using smartphone front camera. In Proceedings of the 17th Conference on Embedded Networked Sensor Systems. 1–14.
- [13] Jeya Vikranth Jeyakumar, Liangzhen Lai, Naveen Suda, and Mani Srivastava. 2019. SenseHAR: A Robust Virtual Activity Sensor for Smartphones and Wearables. In Proceedings of the 17th Conference on Embedded Networked Sensor Systems (SenSys '19). Association for Computing Machinery, New York, NY, USA, 15–28. https://doi.org/10.1145/3356250.3360032 event-place: New York, New York.
- [14] Lih-Jen Kau and Chih-Sheng Chen. 2014. A smart phone-based pocket fall accident detection, positioning, and rescue system. *IEEE journal of biomedical* and health informatics 19, 1 (2014), 44–56.
- [15] Hyeokhyen Kwon, Catherine Tong, Harish Haresamudram, Yan Gao, Gregory D. Abowd, Nicholas D. Lane, and Thomas Plötz. 2020. IMUTube: Automatic Extraction of Virtual on-Body Accelerometry from Video for Human Activity Recognition. Proc. ACM Interact. Mob. Wearable Ubiquitous Technol. 4, 3 (2020). https://doi.org/10.1145/3411841 Place: New York, NY, USA Publisher: Association for Computing Machinery.
- [16] Jin Lu, Chao Shang, Chaoqun Yue, Reynaldo Morillo, Shweta Ware, Jayesh Kamath, Athanasios Bamis, Alexander Russell, Bing Wang, and Jinbo Bi. 2018. Joint modeling of heterogeneous sensing data for depression assessment via multi-task learning. Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies 2, 1 (2018), 1-21.
- [17] Chengwen Luo, Xingyu Feng, Junliang Chen, Jianqiang Li, Weitao Xu, Wei Li, Li Zhang, Zahir Tari, and Albert Y Zomaya. 2019. Brush like a dentist: accurate monitoring of toothbrushing via wrist-worn gesture sensing. In *IEEE INFOCOM* 2019-IEEE Conference on Computer Communications. IEEE, 1234–1242.
- [18] Akhil Mathur, Anton Isopoussu, Nadia Berthouze, Nicholas D. Lane, and Fahim Kawsar. 2019. Unsupervised Domain Adaptation for Robust Sensory Systems. In Adjunct Proceedings of the 2019 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2019 ACM International Symposium on Wearable Computers (UbiComp/ISWC '19 Adjunct). Association for Computing Machinery, New York, NY, USA, 505-509. https: //doi.org/10.1145/3341162.3345609 event-place: London, United Kingdom.
- [19] Abhinav Mehrotra and Mirco Musolesi. 2018. Using autoencoders to automatically extract mobility features for predicting depressive states. Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies 2, 3 (2018), 1-20.
- [20] Fen Miao, Yi He, Jinlei Liu, Ye Li, and Idowu Ayoola. 2015. Identifying typical physical activity on smartphone with varying positions and orientations. *Biomedical engineering online* 14, 1 (2015), 1–15.
- [21] Chulhong Min, Akhil Mathur, Alessandro Montanari, and Fahim Kawsar. 2019. An Early Characterisation of Wearing Variability on Motion Signals for Wearables. In Proceedings of the 23rd International Symposium on Wearable Computers (ISWC '19). Association for Computing Machinery, New York, NY, USA, 166–168. https: //doi.org/10.1145/3341163.3347716 event-place: London, United Kingdom.
- [22] Rajalakshmi Nandakumar, Shyamnath Gollakota, and Nathaniel Watson. 2015. Contactless sleep apnea detection on smartphones. In Proceedings of the 13th annual international conference on mobile systems, applications, and services. 45– 57.
- [23] Xin Qin, Yiqiang Chen, Jindong Wang, and Chaohui Yu. 2019. Cross-Dataset Activity Recognition via Adaptive Spatial-Temporal Transfer Learning. Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies 3, 4 (Dec. 2019), 1–25. https://doi.org/10.1145/3369818
- [24] Attila Reiss and Didier Stricker. 2012. Creating and benchmarking a new dataset for physical activity monitoring. In Proceedings of the 5th International Conference on PErvasive Technologies Related to Assistive Environments - PETRA '12. ACM Press, Heraklion, Crete, Greece, 1. https://doi.org/10.1145/2413097.2413148
- [25] Daniel Roggen, Stéphane Magnenat, Markus Waibel, and Gerhard Tröster. 2011. Wearable Computing. IEEE Robotics & Automation Magazine 18, 2 (2011), 83–95. https://doi.org/10.1109/MRA.2011.940992
- [26] Allan Stisen, Henrik Blunck, Sourav Bhattacharya, Thor Siiger Prentow, Mikkel Baun Kjærgaard, Anind Dey, Tobias Sonne, and Mads Møller Jensen. 2015. Smart Devices Are Different: Assessing and MitigatingMobile Sensing Heterogeneities for Activity Recognition. In Proceedings of the 13th ACM Conference on Embedded Networked Sensor Systems (SenSys '15). Association for Computing Machinery, New York, NY, USA, 127–140. https://doi.org/10.1145/2809695.2809718 event-place: Seoul, South Korea.
- [27] Noeru Suzuki, Yuki Watanabe, and Atsushi Nakazawa. 2020. GAN-Based Style Transformation to Improve Gesture-Recognition Accuracy. Proc. ACM Interact. Mob. Wearable Ubiquitous Technol. 4, 4 (2020). https://doi.org/10.1145/3432199

CODA: A COst-efficient Test-time Domain Adaptation Mechanism for HAR

Place: New York, NY, USA Publisher: Association for Computing Machinery.

- [28] Joshua B. Tenenbaum, Vin de Silva, and John C. Langford. 2000. A Global Geometric Framework for Nonlinear Dimensionality Reduction. Science 290, 5500 (2000), 2319–2323. https://doi.org/10.1126/science.290.5500.2319 arXiv:https://www.science.org/doi/pdf/10.1126/science.290.5500.2319
- [29] Shuaiqiang Wang, Xiaoming Xi, and Yilong Yin. 2012. Importance Weighted Passive Learning. In Proceedings of the 21st ACM International Conference on Information and Knowledge Management (CIKM '12). Association for Computing Machinery, New York, NY, USA, 2243-2246. https://doi.org/10.1145/2396761.

2398611 event-place: Maui, Hawaii, USA.

- [30] Gary Weiss and Jeffrey Lockhart. 2012. The Impact of Personalization on Smartphone-Based Activity Recognition. https://aaai.org/ocs/index.php/WS/ AAAIW12/paper/view/5203
- [31] Waskitho Wibisono, Dedy Nur Arifin, Baskoro Adi Pratomo, Tohari Ahmad, and Royyana M Ijtihadie. 2013. Falls detection and notification system using tri-axial accelerometer and gyroscope sensors of a smartphone. In 2013 Conference on Technologies and Applications of Artificial Intelligence. IEEE, 382–385.