An Experiment with the Use of ChatGPT for LCSH Subject

Assignment on Electronic Theses and Dissertations

Eric H. C. Chow^a*, TJ Kao^b and Xiaoli Li^b

^aHong Kong Baptist University, Hong Kong, China; ^bUniversity of California Davis, U.S.A.

Address correspondence to Eric H. C. Chow, Digital Scholarship Manager, Au Shue Hung Memorial Library, Hong Kong Baptist University, 34 Renfrew Road, Kowloon Tong, Kowloon, Hong Kong. Email: choweric@hkbu.edu.hk*

Abstract

This study delves into the potential use of Large Language Models (LLMs) for generating Library of Congress Subject Headings (LCSH). The authors employed ChatGPT to generate subject headings for electronic theses and dissertations (ETDs) based on their titles and summaries. The results revealed that although some generated subject headings were valid, there were issues regarding specificity and exhaustiveness. The study showcases that LLMs can serve as a strategic response to the backlog of items awaiting cataloging in academic libraries, while also offering a cost-effective approach for promptly generating LCSH. Nonetheless, human catalogers remain essential for verifying and enhancing the validity, exhaustiveness, and specificity of LCSH generated by LLMs.

Keywords: Large Language Models; Library of Congress Subject Headings; Subject analysis; Electronic Theses and Dissertations

Introduction

MARC and LCSH Systems

Library metadata practitioners usually produce bibliographic records for library resources in the form of MARC (Machine-Readable Cataloging) records. MARC is a data format that organizes information about books and other materials in a library collection. One important part of the data is the MARC 6XX Subject Access Fields, which are used to input subject access entries and terms (e.g., topical terms, personal names, places, and time periods) covered by each book or resource. Most of these fields contain subject terms based on controlled vocabularies, one of which is the Library of Congress Subject Headings (LCSH).

The LCSH vocabulary has a rich history going back to 1898.¹ Initially a mere list of subject headings, the LCSH vocabulary was designed to meet the specific cataloging needs of the Library of Congress. Today, the LCSH acts as a sophisticated filter that categorizes books into specific subjects for improved searchability. This system ensures that a search in a library's catalog returns all relevant books, even when the search terms that are used do not match the exact title or author, thereby facilitating the discovery of relevant resources. Moreover, the LCSH aids in understanding the broader context of a given publication by including related subjects. This not only directs users to their desired sources, but also suggests additional areas of interest. As the collection and variety of the Library of Congress materials grew, so too did the LCSH, expanding in scope and complexity to accommodate new genres and topics. This expansion was not just a matter of adding more terms – rather, it additionally involved standardizing the headings to ensure consistency across the library's vast collection. By the mid-20th century, the influence of the LCSH had extended well beyond the walls of the Library of Congress,² with libraries across the United States and other English-speaking countries adopting the LCSH for their own cataloging needs. At present, the LCSH provides

consistency across libraries worldwide, offering a standardized method for subject search. This uniformity is particularly useful for users accessing multiple libraries, as it maintains a consistent approach to finding publications on specific topics.

However, the LCSH system has several limitations. One of the criticisms of the LCSH system concerns its complexity and extensive training required for catalogers to effectively apply it. As reported in several previous studies,^{3,4} when using the LCSH system, library catalogers have to manually combine various elements into a single, complex subject heading string by adhering to elaborate and often intricate rules for heading construction. Complexity of these rules presupposes that catalogers have a comprehensive understanding of the LCSH structure and principles. Yet, it takes a considerable amount of time and effort to train new catalogers to correctly apply these rules. Accordingly, catalogers would undergo years of training before they can independently create complex strings; in many cases, training is not provided at all, leaving catalogers to rely on existing bibliographic records as examples.

This complexity is not just a barrier for the enrolment of new catalogers, but also an ongoing challenge for the already trained professionals. With the evolution of the system and incorporation of new terms, constructing accurate and relevant subject strings demands a yet higher level of expertise and continuous learning. In addition, the intricate nature of the LCSH system, which requires significant human intervention and judgment, makes it difficult to automate the system using rule-based computer programs. This reliance on manual labor not only increases the time and resources needed for cataloging, but also increases the risk of inconsistencies and errors entering the system, especially in large and diverse collections.

Automatic Cataloging Record Generation

To date, several previous studies have attempted using machine learning in automatic assignment of subject headings on library collections. For instance, Wartena et al.⁵ focused on creating classifiers for frequently used terms in abstracts and extracting headings directly from texts. However, despite achieving acceptable levels of precision, the classifiers had limited recall due to the inability to train on a vast number of LCSH terms. Drawing conclusions based on these findings, the authors highlighted the challenges in categorizing documents with the LCSH due to the vast number of headings and specificity of many terms. In another relevant study, Kazi et al.⁶ explored the LCSH assignment task by formulating it as a multi-label classification problem and developing predictive models using a gold-standard dataset. The results revealed the viability of predicting the LCSH for scholarly articles using models like Decision Trees and Artificial Neural Networks.

In recent years, the surge in the development of large language models (LLM) has fueled their use in various machine learning applications, including label assignment on a given text input. LLMs such as OpenAI's ChatGPT are AI tools built upon multi-layer recurrent neural networks trained on vast amounts of text data⁷ to generate human-like text output. LLMs use transformer-based architectures and statistical methods to predict subsequent words given a textual input.⁸ LLMs also display remarkable proficiency in composing computer programming code, simulating scientific discourse, and even creating literary works such as prose and poetry. Similarly remarkable is LLMs' current performance on labeling and classification tasks on a given textual input, such as sentiment analysis,⁹ political social media posts classification,¹⁰ and topic classification.¹¹At the time of this writing, both OpenAI and Google have released multimodal versions of their LLMs, which can take image, video, and text as inputs to produce generative text output.

Recently, LLMs have also come to be used in the area of library cataloging, which marked a significant shift from previous methods by eliminating the need for machine learning model training. In one of these recent studies, Brzustowicz¹² tested ChatGPT's ability to generate MARC records. The experiment involved using ChatGPT to create MARC records for a variety of items, including books and sound recordings, in different languages. In order to test ChatGPT's ability to generate an original record, the selected items included both those with existing MARC records in OCLC's WorldCat and those without a corresponding entry. The results revealed that ChatGPT successfully produced MARC records closely resembling those created by professional human catalogers. The findings also demonstrated ChatGPT's proficiency in extracting essential metadata, such as title and authors. However, discrepancies were noted in subject headings assignment. An interesting finding in Brzustowicz's study was that ChatGPT managed to generate original MARC records when no existing WorldCat entry was available, showing its potential for creating new catalog entries.

Furthermore, Zhang et al.¹³ specifically tackled the problem of subject heading assignment using ChatGPT. The authors designed a prompt that included a list of 22 subject heading (such as "chemical science," "engineering," "law and legal studies") from the Australian and New Zealand Standard Research Classification (ANZSRC) scheme, along with instructions on the use of this scheme and several demonstration examples (known as few-shot prompting technique). The results showed that, while ChatGPT demonstrated high precision in certain subject disciplines, lower performance was observed in others. This variation in performance highlights the challenges in assigning labels to multidisciplinary research datasets, as well as the limitations of in-context learning methods in applying discipline-specific classification rules.

Yet, a limitation of Zhang et al.'s study¹⁴ is that may not have capitalized the internal knowledge of a LLM – specifically, MARC records and the LCSH that may

have already been internalized in an LLM – for library cataloging functions. In fact, LLMs such as ChatGPT are trained on text data publicly available from the Internet.¹⁵ The LCSH and MARC records are readily available on the Internet's public domain. At the time of this writing, a total of 459,624 records of authorized LCSH topical vocabulary are freely and openly accessible on the Library of Congress website.¹⁶ For instance, the LCSH *Hong Kong Sign Language* and related information such as variant terms, broader terms, and associated book titles are made readily available on the Library of Congress website.¹ Moreover, many academic libraries and commercial publishers have made the MARC 21 records of their collections open-access.

These records frequently contain detailed bibliographic metadata, including title, abstract, and the associated LCSH subject headings. Therefore, it is highly plausible that LLMs such as ChatGPT have already ingested from the public domain a vast amount of metadata encoding the relationships between thousands of LCSH vocabularies and bibliographic elements from millions of existing MARC 21 records.

Subject Analysis for Theses and Dissertations

Theses and dissertations are original research outputs that not only reflect the quality of students' and faculty members' scholarly work, but also represent a body of knowledge and history of the corresponding degree-granting institution.¹⁷

In this context, it is important for research institutions to properly catalog theses and dissertations, making them discoverable by future researchers. Unfortunately, such a task is frequently highly time-consuming even for experienced catalogers, as it involves a highly complex subject analysis of writings on sometimes very narrow and specialized subject areas. To reduce processing time, it is not uncommon for academic library catalogers to input author-supplied keywords into the 653 fields for uncontrolled index

¹ See https://id.loc.gov/authorities/subjects/sh2007020076.html

terms.¹⁸ Yet, these author-supplied keywords are often unhelpful for the LCSH assignment,¹⁹ as students are not professionally trained on subject analysis, and the keywords are most likely non-conformant to the LCSH controlled vocabularies that can be used directly in the 600, 610, 630, 650, and 651 fields in a MARC record. Furthermore, although most theses and dissertations nowadays are born-digital (Electronic Theses and Dissertations, or ETD), in which case many fields of the MARC record can be populated automatically, subject heading assignments in 6XX fields, especially using LCSH controlled vocabularies, still remain untouched, which results in a demanding task for cataloging librarians. Aiming to address this concern, in the present study, we specifically examine the use of ChatGPT for subject heading assignment for theses and dissertations, as the prospective results would be highly informative and beneficial not only for catalogers of research institutions, but also for entire research communities.

Methodology

In this study, we attempted to use ChatGPT's internalized knowledge of the LCSH, supplemented by three examples to describe the output in MARC 21 format. To address the shortcoming discovered in Brzustowicz's²⁰ work, we focus specifically on LC Subject Headings assignment. Furthermore, unlike Zhang et al.,²¹ we did not include explicit heuristics and list of subject headings in the prompt. The prompt used in this study was as follows:

As a library cataloguer, please provide the appropriate Library of Congress (LC) subject heading(s) that best match the abstract and title of the given work. The detail of the output is as follows:

- Format the subject headings in MARC 21 (fields 650, 600, 610, 651, 630) without using field 880.

- Assign subject headings that best summarizes the overall contents of the work, and as specific as possible on the topics being covered.

- Include multiple subject headings if the book covers various topics.
- Limit the number of subject headings between one to four.
- Provide the MARC fields only, without explanations or notes or greetings.

--- Start of Examples ---

Example 1:

Title: Composite property rights and boundary-treading resistance : a case study of County in Eastern Sichuan Summary: This thesis studies land expropriation disputes from the angle of property

right, exploring its origins from the relationships between township (town) government and villagers, village collective and villagers, and different villagers, focusing on peasants' resisting low land expropriation.

- 650 \$aLand tenure \$zChina.
- 650 \$aRight of property \$zChina.

Example 2:

Title: Determinants of expertise of Olympic style Taekwondo performance Summary: The purpose of this study was to identify the determinants of expertise and the contributory effect of domains to the Olympic style Taekwondo performance. Eighty-seven Taekwondo athletes with different levels of expertise, namely elite, sub-elite and practitioner were recruited.

- 650 \$aAthletes \$xPsychological aspects.
- 650 \$aAthletes \$xResearch.
- 650 \$aTae kwon do.

Example 3:

Title: An ADMM approach to the numerical solution of state constrained optimal control problems for systems modeled by linear parabolic equations Summary: We address in this thesis the numerical solution of state constrained optimal control problems for systems modeled by linear parabolic equations. For the unconstrained or control-constrained optimal control problem, the first order optimality condition can be obtained in a general way.

- 650 \$aFinite differences.
- 650 \$aMultipliers (Mathematical analysis)
- 650 \$aNumerical analysis.
- --- End of Examples ---

With the growing popularity of LLMs, researchers and practitioners alike have experimented and discovered general rules and best practices in crafting LLM prompts that would produce meaningful results. Accordingly, in crafting our prompt, we took into account the following considerations. A good prompt should contain four main components: context, instruction, output indicator and input data.²² Therefore, our prompt design captured the first three elements – context ("As a library cataloger..."), instruction ("...provide the appropriate Library of Congress Subject Headings..."), and output indicator (the examples demonstrating how the output should look like). The input data, which consisted of the title and summary of the ETD in question, was then appended to context, instruction, and output indicators. We also took into account available evidence showing that, by repetitively providing several examples of the desired output, LLMs could produce better and more accurate output.²² Accordingly, our prompt included three examples of the desired output in the MARC format. Furthermore, an effective prompt should be specific and include constraints whenever necessary (e.g., "Provide the MARC fields only, without explanations or notes or greetings"). During the experimentation in crafting the prompt, non-Latin input data (e.g., Chinese title and summary) were used, and the prompt resulted in the creation of the 880 field, which was used as linkage to the 6XX field for subjects in non-Latin scripts. As the ETD records examined in our experiment were in English (Latin scripts) only, the specific instruction of "...without using the 880 field" was included in the prompt.

The experiment was conducted on January 17, 2024 using ChatGPT-3.5 through Microsoft Azure OpenAI API. To ensure a wider applicability of our findings, we conducted the experiment using ChatGPT-3.5, which can be freely accessed from OpenAI, rather than ChatGPT-4 which is still a paid service at the time of this writing. In order to reduce randomness in the responses, the LLM "temperature" setting was set to 0 (zero). The MARC records of 30 ETDs were randomly selected from the WorldCat and UC Davis Library catalog. The ETDs covered various disciplines and subject matters. A Python programming script² was written to feed the prompt presented above, appended sequentially by the title and abstract of each ETD record into ChatGPT. The total processing time for the 30 records amounted to approximately 3 minutes.

Results

ChatGPT produced between three to five subject headings (mostly with subdivisions) for each of the ETD records. The results were tabulated into an Excel spreadsheet³ for a subsequent analysis by an experienced professional cataloger with respect to the following three principles described in *Basic Subject Cataloging Using LCSH - Instructor Manual* published by the Library of Congress:²³

- 1. Is the MARC coding correct?
- Is the heading string valid? (e.g., are the elements authorized by authority records or by the Subject Heading Manual? Is the order and placement of subdivisions appropriate?)
- 3. Do the headings assigned reflect the content of the work being cataloged?

² See https://github.com/choweric/llm-lcsh-experiment/

³See https://github.com/choweric/llm-lcsh-experiment/raw/main/results.xlsx

Correctness of MARC coding

Among the 30 analyzed ETD records, ChatGPT's outputs of MARC coding were mostly correct (90%), with only three records containing incorrect codes. Specifically, these three erroneous records contained subject headings that were assigned to 650 fields where it was supposed to be 600 or 610.

Validity of LCSH assignment

ChatGPT produced LCSH for seven ETD records, or 23.3%, without any issue; in the remaining 23 ETD records, the assigned LCSH had varying degrees of accuracy. In what follows, we provide a qualitative summary of the results.

- a. Topical terms that were clearly not from the LCSH controlled vocabulary:
 Abuse, Adaptations, Environmental regulation, Ethnohydrology, Freezing
 resistance of plants, Growth mindset, Infidelity in motion pictures, Laser
 annealing, Princess Nourah bint Abdulrahman University, Socioeconomic
 factors, Women in sports administration.
- b. Topical terms that closely matched the existing LCSH controlled vocabulary. For example:

ChatGPT Output	LCSH Controlled Vocabulary
College personnel	College personnel management
Doping (Semiconductor technology)	Semiconductor doping
High-frequency ventilation	High-frequency ventilation (Therapy)
Urea cycle	Urea

c. Subject headings from the LCSH controlled vocabulary, but in their variant form, rather than the preferred terms. For example:

ChatGPT Output	LCSH Controlled Vocabulary
	(Preferred Terms)
Animal translocation	Animal introduction
Personal growth	Maturation (Psychology)
Psychoanalytic criticism	Psychoanalysis and literature
Zooarchaeology	Animal remains (Archaeology)

d. Topical terms that were not LCSH, but provided a more precise or nuanced description than those available in the LCSH controlled vocabulary for the specific topic of the ETD being examined. For example:

ChatGPT Output	LCSH Controlled Vocabulary
Group counseling for men	Group counseling for teenagers
	Group counseling for children
	Group counseling for girls
	Group counseling for teenage girls
Respiratory distress syndrome,	Respiratory distress syndrome
Newborn	Respiratory distress syndrome, Adul

e. Subdivision terms that did not conform to the LCSH subdivision rules. For example:

ChatGPT Output	Reason for non-LCSH conformant
\$a Press coverage \$x Political	Press coverage is a subdivision and
aspects.	cannot be used as a main topical
	subject.
\$a Cardiovascular system \$x Risk	Risk factors cannot be used as
factors.	subdivision of Cardiovascular

systems. It can only be appended to individual diseases and types of diseases.

\$a English language \$x Lexicography cannot be geographical Lexicography subdivided *\$z Great Britain \$x History \$y 18th century. \$a Women composers \$z France* Chronological subdivisions, such as *\$y 20th century \$y 20th century*, can only be *\$a Women musicians \$z France* appended to topical subjects of *\$y 20th century* historical nature or form / genre headings. Literary collections is a *\$a Middle Ages \$x Literary* collections form subdivision, but not a topical subdivision Invalid subdivision term *\$x Career development \$x Factors* \$x Men *\$x Sexual orientation*

Specificity and Exhaustiveness of LCSH assignment

To find out whether the headings assigned by ChatGPT reflected the content of the work being cataloged, we focused on two key principles of cataloging specified in the Library of Congress' *Subject Heading Manuals (SHM) H 180 – Assigning and Constructing Subject Headings*: specificity and exhaustiveness. The principle of specificity guides catalogers to assign subject headings that are as precise as the content they represent, while the principle of exhaustiveness directs them to assign subject headings that encapsulate the overall content of the work and highlight its significant topics. Accordingly, we initiated the process by scrutinizing titles and abstracts, comparing subject headings from the original 30 MARC records and those by ChatGPT.

Out of the 30 ETDs records being reviewed, 17 (56.6%) were evaluated as acceptable in specificity and 22 (73.3%) for exhaustiveness.⁴

Discussion

A notable outcome of the present study is the high level of correctness ChatGPT demonstrated in MARC field coding, indicating that catalogers can generally depend on ChatGPT for this task, albeit with the understanding that occasional errors may require manual correction through spot checks. Catalogers can also rely on Integrated Library Systems (ILS) or other authority control services to routinely check and identify records with field coding errors, flagging those errors for subsequent corrective action.

When addressing the issue of validity of the LCSH generated by ChatGPT, catalogers have the following four solutions at their disposal:

- Manually search for alternative or broader subject heading terms through additional research into LCSH controlled vocabularies and authority records;
- 2. Use existing software for rectification. Reconciliation tools can assess ChatGPT-generated subject strings, distinguishing correct LCSH from invalid ones. This method is particularly effective for addressing the five aforementioned categories of validity issues. Again, ILS can be used for a routine check for errors in MARC records that have been enriched with these subjects.
- 3. Employ faceted vocabularies that do not require intricate rule interpretation and application for subject assignment. A faceted vocabulary term represents only a single concept. While some faceted subject strings include subdivisions, e.g., *Sports--Political aspects* from FAST (Faceted Application of Subject Terminology), all components are in the same subject category. To express

⁴ See Columns H and I in https://github.com/choweric/llm-lcsh-experiment/raw/main/results.xlsx

multiple concepts, multiple faceted vocabulary terms are to be assigned. Therefore, there is no need for rule interpretation and application. This will certainly make subject assignment much more straightforward and yield better results. These terms may still be input directly in the 653 (uncontrolled index term) field in a MARC record.

4. Propose new subject authority records through the Subject Authority Cooperative (SACO) of the Program for Cooperative Cataloging. While proposals require adherence to the SHM rules and guidelines, individuals can seek support from a SACO funnel with relevant expertise.

Although the LLM we used in the present study was ChatGPT, which is not an open-source LLM, so its exact training data are not known, our results provide strong evidence that ChatGPT has been trained on LCSH vocabularies scraped from the Library of Congress website and MARC records from websites of libraries and publishers around the world. While the model cannot be retrained, recent development of Retrieval-Augmented Generation (RAG) in LLM applications may offer potential for improving ChatGPT's performance by incorporating the official LCSH vocabularies as a reference source of information when querying the LLM. Furthermore, the emergence of open-source LLMs, such as Llama 2 and Mistral, presents an opportunity to train custom models using a large number of quality bibliographic data from diverse disciplines as training data. Bibliographic records with the Program for Cooperative Cataloging (PCC) authentication are considered quality data.²⁴ PCC contributors are required to go through a rigorous training and review process before being approved to create PCC authenticated records on their own. In addition, PCC records cover a broad range of disciplines and topics, even though the content of resources represented by these records tends to be more academic. Using these records to train an open-source LLM might significantly increase the quality of subject assignment.

With respect to specificity and exhaustiveness, it is worth noting that, unlike MARC coding accuracy and LCSH validity that can be checked against the rigid rules and controlled vocabularies, these two dimensions are highly subjective. Our results on specificity and exhaustiveness are based solely on our own assessment. Subject analysis is not an exact science, but rather a blend of activities prone to subjectivity, such as comprehension, interpretation, and even translation. It is not uncommon for two catalogers to assign different subjects headings to the same resource due to their unique perspectives. Indeed, as previously demonstrated by Tonta,²⁵ the subject headings assigned by catalogers from the Library of Congress and the British Library to a set of identical books were mostly inconsistent with each other. Last but not least, specificity and exhaustiveness of subject headings are also affected by external factors, such as institutional policies, practices, and time constraints.

Conclusion

This study presents a promising exploration of using Large Language Models, specifically ChatGPT, in the generation of Library of Congress Subject Headings (LCSH). The results revealed that ChatGPT's internalized knowledge of the LCSH and MARC 21 format is sufficient to produce a decent list of LCSH when presented with a title and summary of an ETD through a prompt. While some subject headings generated by our model had validity, specificity, or exhaustiveness issues, there are ways and tools using which catalogers can remedy those issues.

In present-day context, the use of LLMs like ChatGPT in academic libraries cataloging can be a strategic response to the fact that many libraries are inundated with new electronic resources, which by far outpaces the cataloging capacity of human staff. With the help of LLMs, the cataloging process can be expedited, effectively reducing the backlog of items to be cataloged. LLMs' role in this context is to assist in automating initial classification tasks, thereby allowing experienced catalogers to focus on critical aspects of quality control. This symbiotic relationship can enhance productivity without replacing the invaluable expertise of human catalogers. Even for junior catalogers, it is much easier to learn to identify and refine invalid LCSH generated by ChatGPT than to create LCSH from scratch.

The results of the present study also present an economical approach for the immediate generation of the LCSH. The cost associated with using Microsoft's OpenAI API in the present study amounted to approximately USD \$0.25. This having been said, LLMs are proposed as tools to aid in reducing cataloging cost and time, rather than as substitutes of professional catalogers. Human catalogers are still needed to check and improve the validity, exhaustiveness, and specificity of the LCSH generated by LLMs. Considering that the internalized knowledge base of ChatGPT is being continuously updated, it is to be expected that the results of the present study may differ over time. Therefore, human catalogers are still needed to continuously monitor the quality of ChatGPT output as time goes on.

Finally, considering that, in the present study, we focused exclusively on the generation of the LCSH, future experiments could explore subject assignment in other frameworks, such as FAST (Faceted Application of Subject Terminology), as well as in other types of works (books, audio-visual materials, etc.), which will provide further insights into the applicability of LLMs in library cataloging.

References

- Alva T. Stone, "The LCSH Century: A Brief History of the Library of Congress Subject Headings, and Introduction to the Centennial Essays," *Cataloging & Classification Quarterly* 29, no. 1-2 (2000): 1–15.
- 2. Stone, "The LCSH Century."
- Beacher Wiggins, "Library of Congress Subject Headings: Pre-vs Post-Coordination and Related Issues," March 15, 2007, https://www.loc.gov/catdir/cpso/pre_vs_post.pdf (accessed January 29, 2024).
- Nancy Cooey and Amy Phillips, "Library of Congress Subject Headings: A Post-Coordinated Future," *Cataloging & Classification Quarterly* 61, no. 5-6 (2023): 491–505.
- Christian Wartena and Michael Franke-Maier, "A Hybrid Approach to Assignment of Library of Congress Subject Headings," *Archives of Data Science* 4, no. 1 (2018): 1–13.
- Nazmul Kazi, Lane Nathaniel, and Kahanda Indika, "Automatically Cataloging Scholarly Articles Using Library of Congress Subject Headings," in *Proceedings* of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Student Research Workshop (Association for Computational Linguistics, 2021), 43–9.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D. Kaplan, Prafulla Dhariwal, Arvind Neelakantan, et al., "Language Models Are Few-Shot Learners," *Advances in Neural Information Processing Systems* 33 (2020): 1877–901.
- Ian L. Alberts, Lorenzo Mercolli, Thomas Pyka, George Prenosil, Kuangyu Shi, Axel Rominger, and Ali Afshar-Oromieh, "Large Language Models (LLM) and ChatGPT: What Will the Impact on Nuclear Medicine Be?" *European Journal of Nuclear Medicine and Molecular Imaging* 50, no. 6 (2023): 1549–52.
- Yiming Zhu, Peixian Zhang, Ehsan-Ul Haq, Pan Hui, and Gareth Tyson, "Can ChatGPT Reproduce Human-Generated Labels? A Study of Social Computing Tasks," arXiv preprint arXiv:2304.10145 (2023).

- Petter Törnberg, "ChatGPT-4 Outperforms Experts and Crowd Workers in Annotating Political Twitter Messages with Zero-Shot Learning," arXiv preprint arXiv:2304.06588 (2023).
- Shuohang Wang, Yang Liu, Yichong Xu, Chenguang Zhu, and Michael Zeng,
 "Want to Reduce Labeling Cost? GPT-3 Can Help," arXiv preprint arXiv:2108.13487 (2021).
- Richard Brzustowicz, "From ChatGPT to CatGPT: The Implications of Artificial Intelligence on Library Cataloging," *Information Technology and Libraries* 42, no. 3 (2023): 1–22.
- Shiwei Zhang, Mingfang Wu, and Xiuzhen Zhang, "Utilising a Large Language Model to Annotate Subject Metadata: A Case Study in an Australian National Research Data Catalogue," arXiv preprint arXiv:2310.11318 (2023).
- 14. Zhang et al., "Utilising a Large Language Model to Annotate Subject Metadata."
- 15. Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever,"Improving Language Understanding by Generative Pre-Training," (2018).
- "Library of Congress Linked Data Service: Authorities and Vocabularies," *Library of Congress*, http://id.loc.gov/authorities/subjects/collection_LCSHAuthorizedHeadings. (accessed February 15, 2024).
- Cedar C. Middleton, Jason Dean, and Mary A. Gilbertson. "A process for the original cataloging of theses and dissertations." *Cataloging & Classification Quarterly* 53, no. 2 (2015): 234–246.
- Ken Robinson, Jeff Edmunds, and Stephen C. Mattes. "Leveraging author-supplied metadata, OAI-PMH, and XSLT to Catalog ETDs: A case study at a large research library." *Library Resources & Technical Services* 60, no. 3 (2016): 191-203.
- Myung-Ja K. Han, Patrick Harrington, Andrea Black, and Deren Kudeki, "Aligning Author-Supplied Keywords for ETDS with Domain-Specific Controlled Vocabularies," In *Satellite Meeting - Subject Access: Unlimited Opportunities* (State Library of Ohio, 2016), 1–10.
- 20. Brzustowicz, "From ChatGPT to CatGPT."
- 21. Zhang et al., "Utilising a Large Language Model to Annotate Subject Metadata."
- 22. Louie Giray, "Prompt Engineering with ChatGPT: A Guide for Academic Writers," *Annals of Biomedical Engineering* 51, no. 12 (2023): 2629–33.

- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, et al., "Llama: Open and Efficient Foundation Language Models," arXiv preprint arXiv:2302.13971 (2023).
- 24. "Basic Subject Cataloging using LCSH Instructor Manual," *Library of Congress*, last updated April, 2011, https://www.loc.gov/catworkshop/courses/basicsubject/pdf/LCSH_Instructor_20 11.pdf (accessed March 21, 2024).
- Magda El-Sherbini, "Program for Cooperative Cataloging: BIBCO Records: Analysis of Quality," *Cataloging & Classification Quarterly* 48, no. 2-3 (2010): 221–36.
- Yaşar Tonta, "A Study of Indexing Consistency Between Library of Congress and British Library Catalogers," *Library Resources & Technical Services* 35, no. 2 (1991): 177–85.