

Minimum Sum Vertex Cover: Kernelization and Parameterized Algorithms

Yixin Cao^{*†}

Jingyi Liu^{*}

Jianxin Wang^{*}

Abstract

Given an ordering of the vertices of a graph, the cost of covering an edge is the smaller number of its two ends. The minimum sum vertex cover problem asks for an ordering that minimizes the total cost of covering all edges. We consider parameterized complexity of this problem, using the largest cost k of covering a single edge as the parameter. Note that the first k vertices form a (not necessarily minimal) vertex cover of the graph, and ordering of vertices after k is irrelevant. We present a $(2k^2 + 3k)$ -vertex kernel and an $O(|E(G)| + 2^k k! k^4)$ -time algorithm for the minimum sum vertex cover problem.

1 Introduction

A *vertex cover* of a graph G is a set of vertices such that every edge has at least one end in the set. In other words, this vertex set “covers” all the edges of the graph. There are many variations of this fundamental concept. In the temporal setting, e.g., we take the vertices in a vertex cover one by one, and assign the number to all uncovered edges incident to this vertex, which are then covered. The objective is to minimize the sum of the numbers assigned to all edges. Given a graph G , the *minimum sum vertex cover* problem asks for an ordering of the vertices of G to minimize the total cost of all edges in $E(G)$, where the cost of an edge is the smaller number of its two ends in the ordering.

This problem was formally introduced by Feige et al. [5]. They considered a more general problem, called the *minimum sum set cover*, of which our problem is a special case. They proved that the minimum sum vertex cover problem is APX-hard and admits a 2-approximation, which was improved to $16/9$ recently by Bansal et al. [2]. Stanković [6] showed that the MSVC problem cannot be approximated within 1.014, assuming the Unique Games Conjecture.

In comparison, there was not much study on the parameterized complexity of the minimum sum vertex cover problem, and one explanation is about the parameter. Note that to make a decision problem, the input has an additional integer w , and the question becomes whether the input graph admits a solution with total cost at most w . The standard parameterization is uninteresting because in a yes-instance, w cannot be smaller than the size of the graph. One option, taken by Aute and Panolan [1], is to use the vertex cover number τ , i.e., the size of a minimum vertex cover. They presented an algorithm running in time $\tau!(\tau + 1)^{2^\tau} n^{O(1)}$, where n is the order of the input graph. It starts with finding a minimum vertex cover S and guessing the ordering of the vertices in S . The vertices in $V(G) \setminus S$ is an independent set, and they can be partitioned into at most 2^τ sets with respect to their neighborhoods in S . The key observation is that vertices in the same set (which are twins) appear consecutively in an optimal ordering. The astronomical factor in the running time is for guessing the relative order of these sets. Aute and Panolan [1] also considered parameterization by the size of a minimum vertex cover of the complement of the input graph.

We take a natural alternative. Let σ be an optimal ordering of $V(G)$. Taking the ends of all edges that are assigned the smaller number by σ , we end with a vertex cover S . This vertex cover may or may not be minimal; e.g., consider the 19-vertex graph obtained from six disjoint claws by identifying one leaf from each claw. On the other hand, one may show that the vertices in S are at the beginning of σ . Indeed, what matters in σ is the ordering of vertices in S , and other vertices can be appended to that in an arbitrary order. We are thus motivated to use the size k of S as the parameter.

^{*}School of Computer Science and Engineering, Central South University, Changsha, China. jingyiliu@csu.edu.cn, jxwang@mail.csu.edu.cn

[†]Department of Computing, Hong Kong Polytechnic University, Hong Kong, China. yixin.cao@polyu.edu.hk.

The parameters k and τ are related. On the one hand, the vertex cover number τ of the input graph is a trivial lower bound for k . On the other hand, a straightforward counting argument shows that $k \leq 2\tau^2$. We conjecture that every graph has a minimum sum vertex cover such that $k < \tau + O(\log \tau)$.

Lemma 1.1. *In any optimal ordering, $k < \tau^2 + 2\tau$.*

Our first result is a polynomial kernel. Given an instance (G, w, k) , a *kernelization algorithm* produces in time polynomial in $n + k$ an equivalent instance (G', w', k') such that $k' \leq k$ and the order of G' is bounded by a computable function of k' .

Theorem 1.2. *The minimum sum vertex cover problem has a $(2k^2 + 3k)$ -vertex kernel, and it can be computed in linear time.*

Similar to the classic Buss reduction, we try to dispose of isolated vertices and vertices with degree higher than k . However, we cannot simply delete a vertex that has been known to be in S or not in S , unless it is isolated. Since each vertex of degree greater than k has to be in S , there are at most k of them. Let $V_{>k}$ denote them. We can use Buss' argument to bound non-isolated vertices in $G - V_{>k}$. It remains to deal with isolated vertices in $G - V_{>k}$, for which we take two steps.

The first is to bound the maximum degree of the graph. If the degrees of two vertices differ by more than k , i.e., $d(u) > d(v) + k$, then u must appear before v in any solution of (G, w, k) . We sort the vertex degrees non-increasingly. If the degrees of two consecutive vertices differ by more than k , then we can partition $V(G)$ into V_1 and V_2 such that $d(u) > d(v) + k$ for every pair of $u \in V_1$ and $v \in V_2$. For each vertex in V_1 , we remove the same number of edges, chosen arbitrarily, between it and V_2 . This operation is safe because once the order between the two partitions is fixed, only the numbers matter. Together with $|V_{>k}| \leq k$, we have a bound $k^2 + k$ on the maximum degree of the graph. The second is to bound the number of isolated vertices of $G - V_{>k}$, denoted as I . We observe that S can always be taken to be disjoint from I . Thus, we can assume that vertices in I are placed at the end of the ordering. Again, the purpose of the edges between $V_{>k}$ and I is for their ends in $V_{>k}$. More specifically, what matters is the number of edges between each vertex in $V_{>k}$ and I . We can then condense I into a small set of vertices and move all the edges between $V_{>k}$ and I to be incident to this set. Its size is at most the maximum degree of the graph.

It is worth stressing that we only conduct each reduction once, and thus the algorithm can be carried out in linear time.

Our second result is a parameterized algorithm. We may start with the kernel. Note that once we know the vertex set S , a straightforward adaptation of the Held–Karp algorithm can produce a feasible ordering. A trivial approach is thus to enumerate all k -vertex subsets of $V(G)$, followed by the Held–Karp algorithm to find an ordering. The running time is $(2k)^{2k} k^{O(1)}$, which already improves [1]. We show an even better result.

Theorem 1.3. *There is an $O(|E(G)| + 2^k k! k^4)$ -time algorithm for minimum sum vertex cover.*

Suppose that (G, w, k) is a yes-instance of the minimum sum vertex cover problem, with a solution σ . Since S is a vertex cover of G , there must be a subset S' of S that is a minimal vertex cover of G . Damaschke [4] showed how to enumerate in $O(|E(G)| + k^2 2^k)$ time all minimal vertex covers of size at most k . We can thus start with guessing the set S' of vertices and their positions in σ . It remains to fill in the empty positions in the first k , by vertices from $S \setminus S'$. We show that it suffices to try a small number of candidates for each of them.

Before we conclude this section, let us mention that the problem is significantly easier on regular graphs. For example, it admits an approximation ratio of 1.225 [5, 6], compared to 16/9 on general graphs. This is also the case for parameterized algorithms. For a nontrivial regular graph, where the degree is three or more, $\tau \geq n/2$. Thus, we can find the set S in $O(2^{2k} k^2)$ time, and then use the Held–Karp algorithm to find the ordering in the same time.

2 Preliminaries

All the graphs discussed in this paper are finite and simple. The vertex set and edge set of a graph G are denoted by, respectively, $V(G)$ and $E(G)$, and $n = |V(G)|$ and $m = |E(G)|$. The set of *neighbors* of

a vertex v in G is denoted as $N_G(v)$, and $d_G(v) = |N_G(v)|$. We drop the subscript when the graph is clear from context. For a subset S of vertices, $N(S) = \bigcup_{x \in S} N(x)$. Let $G[S]$ be the subgraph induced by S , whose vertex set is S and whose edge set consists of edges of G with both ends in S . We use $G - S$ as a shorthand for $G[V(G) \setminus S]$, which is further shortened to $G - v$ when S consists of a single vertex v .

A *solution* of a graph G is a bijection $\sigma : V(G) \rightarrow \{1, 2, \dots, n\}$. Under the solution σ , the *cost* of an edge uv is $\min(\sigma(u), \sigma(v))$. The *maximum cost* and the *total cost* of the solution are, respectively,

$$\max_{uv \in E(G)} \min(\sigma(u), \sigma(v)), \quad \sum_{uv \in E(G)} \min(\sigma(u), \sigma(v)).$$

We are now ready to formally define the problem.

Input: a graph G , two nonnegative integers k and w .

Output: whether there exists a solution σ of G such that the maximum cost is at most k and the total cost is at most w .

We say that a solution σ is *feasible* if its maximum cost is at most k and the total cost is at most w , and *optimal* if its maximum cost is at most k and the total cost is minimized. Note that G might admit a solution with a smaller total cost and a greater maximum cost than an optimal solution. If σ is a feasible solution, then the first k vertices in σ form a vertex cover of G .

Proposition 2.1. *Let (G, w, k) be a yes-instance and v a vertex of G . If $d(v) > k$, then $\sigma(v) \leq k$ for any feasible solution σ of (G, w, k) .*

Proof. If $\sigma(v) > k$, then $\sigma(x) \leq k$ for all $x \in N(v)$. This is impossible because $d(v) > k$. □

We use $r_\sigma(i)$ to denote the number of edges with cost i , i.e.,

$$r_\sigma(i) = |\{x \in N(\sigma^{-1}(i)) \mid \sigma(x) > i\}|.$$

In an optimal solution, this number is non-increasing.

Lemma 2.2. *Let (G, w, k) be a yes-instance and σ an optimal solution of (G, w, k) . For any pair of vertices u and v of G ,*

- i) *if $\sigma(u) < \sigma(v)$, then $r_\sigma(\sigma(u)) \geq r_\sigma(\sigma(v))$; and*
- ii) *if $d(u) \geq k + \max\{1, d(v)\}$, then $\sigma(u) < \sigma(v)$.*

Proof. (i) It suffices to show that if $\sigma(u) = \sigma(v) - 1$, then $r_\sigma(\sigma(u)) \geq r_\sigma(\sigma(v))$. Let σ' be obtained from σ by switching u and v . For each edge ux with $\sigma(x) > \sigma(v)$, the cost is $\sigma(u)$ in σ and $\sigma(v)$ in σ' . For each edge vx with $\sigma(x) > \sigma(v)$, the cost is $\sigma(v)$ in σ and $\sigma(u)$ in σ' . All the other edges have the same cost in σ and σ' . By the optimality of σ , we have $r_\sigma(\sigma(u)) - r_\sigma(\sigma(v)) \leq 0$.

(ii) Noting that $\sigma(u) \leq k$ by Proposition 2.1, we have

$$r_\sigma(\sigma(u)) \geq d(u) - (\sigma(u) - 1) > d(u) - k \geq d(v) \geq r_\sigma(\sigma(v)).$$

Thus, $\sigma(u) < \sigma(v)$. □

We are now ready to prove Lemma 1.1.

Proof of Lemma 1.1. Let σ be a solution of G that has the minimum total cost, and let k be the maximum cost of an edge in σ . Suppose for contradiction that $k \geq \tau^2 + 2\tau$. We take a minimum vertex cover S^* of G . We may number the vertices such that $\sigma(v_i) = i$, and assume that $v_1 \notin S^*$: otherwise we consider the subgraph $G - v_1$, where v_2, v_3, \dots, v_n is an optimal solution. As a result, for each vertex $x \in S^*$, we have

$$d(x) < k + d(v_1) \leq k + \tau,$$

where the first inequality follows from Lemma 2.2(ii), and the second that $N(v_1) \subseteq S^*$.

Let π be an ordering of $V(G)$ such that $\pi(x) \leq \tau$ if and only if $x \in S^*$. Then

$$\begin{aligned}
& \sum_{i=1}^n r_{\pi(i)} \cdot i - \sum_{i=1}^n r_{\sigma(i)} \cdot i \\
&= \sum_{i=1}^{\tau} (r_{\pi(i)} - r_{\sigma(i)}) \cdot i - \sum_{i=\tau+1}^k r_{\sigma(i)} \cdot i \\
&< \sum_{i=1}^{\tau} (k + \tau) \cdot i - \sum_{i=\tau+1}^k i \\
&= \frac{1}{2} \tau(\tau + 1)(k + \tau) - \frac{1}{2} (k + \tau + 1)(k - \tau) \\
&< 0,
\end{aligned}$$

which contradicts the optimality of σ . \square

The Held–Karp algorithm can be adapted to solve the problem in $O(2^n n^2)$ time.

Theorem 2.3. *There is an $O(4^k k^2)$ -time algorithm for the minimum sum vertex cover problem on regular graphs.*

Proof. The problem is trivial when the degree is 0 or 1. Otherwise, $k \geq \tau \geq n/2$. Thus, the problem can be solved in $O(4^k k^2)$ time. \square

3 Kernelization

We number the vertices of the input graph as v_1, v_2, \dots, v_n such that $d(v_i) \geq d(v_{i+1})$ for all $i = 1, \dots, n-1$. We start with dealing with vertices with high degrees. The safeness of our first rule follows immediately from Proposition 2.1.

Rule 1. *If $d(v_{k+1}) > k$, then return a trivial no-instance.*

For $i = 1, \dots, n-1$, let $\delta_i = d(v_i) - d(v_{i+1})$. The safeness of our second rule is ensured by Lemma 2.2.

Rule 2. *If there exists t such that $\delta_t \geq k$, then for each $i = 1, \dots, t$, remove $\delta_t - k$ edges between v_i and $\{v_{t+1}, \dots, v_n\}$, and decrease w by $(t^2 + t)(\delta_t - k)/2$.*

Safeness of Rule 2. Denote by G' the resulting graph obtained after applying Rule 2, and let $w' = w - (t^2 + t)(\delta_t - k)/2$. We show that (G, w, k) is a yes-instance if and only if (G', w', k) is a yes-instance.

Suppose that (G, w, k) is a yes-instance, and let σ be an optimal solution. Note that G' is a subgraph of G , and the costs of remaining edges remain the same. By the ordering of the vertices, for every pair of i and j with $i \leq t < j$, we have

$$d(v_i) \geq d(v_t) = d(v_{t+1}) + \delta_t \geq d(v_{t+1}) + k \geq d(v_j) + k.$$

Since $d(v_{t+1}) > 0$, we have $\sigma(v_i) < \sigma(v_j)$ by Lemma 2.2(ii). Thus, $\sigma(v_i) \leq t$ if and only if $i \leq t$. The cost of the solution σ of G' is at most

$$w - 1(\delta_t - k) - 2(\delta_t - k) - \dots - t(\delta_t - k) = w - \frac{(t^2 + t)(\delta_t - k)}{2} = w'.$$

Therefore, σ is a feasible solution of (G', w', k) .

Now suppose that (G', w', k) is a yes-instance, and let σ' be an optimal solution. Note that $d_{G'}(v_i) \leq d_G(v_i)$ for all $i = 1, \dots, n$. By construction, for all $i = 1, \dots, t$,

$$d_{G'}(v_i) = d_G(v_i) - (\delta_t - k) \geq d_G(v_t) - (\delta_t - k) = d_G(v_{t+1}) + k \geq \max_{j=t+1}^n d_{G'}(v_j) + k.$$

Thus, we again have $\sigma'(v_i) \leq t$ if and only if $i \leq t$. For the maximum cost, we only need to consider edges in $E(G) \setminus E(G')$. Since they are all incident to $\{v_1, \dots, v_t\}$, their cost is at most t . The cost of σ' on G is at most $w' + (t^2 + t)(\delta_t - k)/2 = w$. \square

Rules 1 and 2 bound the maximum degree of the graph.

Lemma 3.1. *If neither of Rules 1 and 2 can be applied, then $d(v_1) \leq k^2 + k$.*

Proof. It is trivial when $n < k^2 + k$, and hence we assume otherwise. By assumption, $d(v_1) = \sigma_1 + \dots + \sigma_k + d(v_{k+1}) \leq k(k+1)$. \square

We now turn to vertices of degrees at most k . Let $V_{>k}$ denote the set of vertices of degrees greater than k , and I denote the set of isolated vertices of the subgraph $G - V_{>k}$. Note that $N(v) \subseteq V_{>k}$ for all vertices $v \in I$. We can use Buss' observation to bound the number of vertices that are not isolated in $G - V_{>k}$.

Rule 3 ([3]). *If $|V(G) \setminus (V_{>k} \cup I)| > k^2 + k$, then return a trivial no-instance.*

Safeness of Rule 3. *If $|V(G) \setminus (V_{>k} \cup I)| > k^2 + k$, then we must assign at least $k+1$ vertices from them to a position no later than k , which is not possible.* \square

The next rule is our main tool to get rid of most vertices.

Rule 4. *If $|I| > d(v_1)$, then*

- i) *add $d(v_1)$ new vertices $x_1, \dots, x_{d(v_1)}$ to G ;*
- ii) *for each vertex $v \in V_{>k}$, add edges $\{vx_i \mid 1 \leq i \leq |N(v) \cap I|\}$; and*
- iii) *delete all the vertices in I from G .*

For the safeness of Rule 4, we need the following lemma.

Lemma 3.2. *Let (G, w, k) be a yes-instance and v a vertex of G . If $d(x) > k$ for all the neighbors x of v , then $\sigma(v) > \sigma(x)$ in any optimal solution σ of (G, w, k) .*

Proof. Suppose for contradiction that $X = \{x \in N(v) \mid \sigma(v) < \sigma(x)\}$ is not empty. We take the vertex u from X such that $\sigma(u)$ is minimized. By the selection of u , precisely $r_\sigma(\sigma(v)) - 1$ neighbors of v appear after u in σ . On the other hand, by Lemma 2.2(i), $r_\sigma(\sigma(u)) \leq r_\sigma(\sigma(v))$. Thus, at least $d(u) - r_\sigma(\sigma(v))$ neighbors of u appear earlier than u in σ . Thus, the position of the last neighbor of v in σ is at least $d(u) - r_\sigma(\sigma(v)) + 1 + r_\sigma(\sigma(v)) - 1 = d(u) > k$, a contradiction to Proposition 2.1. \square

Safeness of Rule 4 Denote by G' the resulting graph obtained after applying Rule 4. Each vertex in $V_{>k}$ has the same degree in G and G' . Thus, in any feasible solution σ of either instance, $\sigma(x) \leq k$ for all $x \in V_{>k}$ by Proposition 2.1. We can build a bijection between $E(G) \setminus E(G')$ and $E(G') \setminus E(G)$. Each feasible solution σ of (G, w, k) has the same cost in G' , and the same holds for each feasible solution of (G', w, k) . Thus, (G, w, k) and (G', w, k) are equivalent. \square

We now summarize our kernelization algorithm in Figure 1. Note that it does not change the value of k , and after a rule is not applicable, we do not need to check it again. Thus, it can be carried out in linear time.

-
1. **if $k < 0$ then return** a no-instance;
 2. number the vertices such that $d(v_1) \geq d(v_2) \geq \dots \geq d(v_n)$;
 3. **if $d(v_{k+1}) \geq k$ then return** a no-instance;
 4. **if $d(v_1) > k^2 + k$ then apply** Rule 2;
 5. apply Rule 3 and Rule 4;
 6. **then return** (G, w, k) .
-

Figure 1: The kernelization algorithm for minimum sum vertex cover.

Proof of Theorem 1.2. We use the algorithm described in Figure 1. The correctness of step 1 is trivial. We have seen the safeness of the reduction rules, applied in steps 3–5. Note that Rule 2 must be applicable in step 4 by Lemma 3.1. After step 5, the number of vertices is at most $k + k^2 + k + d(v_1) \leq 2k^2 + 3k$. Since we process each edge once, the algorithm can be carried out in $O(n + m)$ time. \square

4 A parameterized algorithm

We present a simple branching algorithm for the minimum sum vertex cover problem. Suppose that (G, w, k) is a yes-instance, with a solution σ . By definition, the set of first k vertices in σ is a vertex cover of G , and there must be a subset S of it is a minimal vertex cover of G . We use branching to find vertices in this minimal vertex cover and their positions in σ , followed by other vertices. Damaschke [4] showed how to enumerate in $O(m + k^2 2^k)$ time all minimal vertex covers of size at most k .

Lemma 4.1 ([4]). *A graph has at most 2^k minimal vertex covers of size at most k , and we can enumerate them in $O(m + k^2 2^k)$ time.*

For each minimal vertex cover of G , we use branching to find positions of these vertices. In one of the branchings, the minimal vertex cover is S , and the position of a vertex $v \in S$ is $\sigma(v)$. It remains to fill in the gaps with vertices from $V(G) \setminus S$. Let i be such a position. The purpose of including a vertex $v \in V(G) \setminus S$ in position i is that it decreases the costs of edges between v and vertices in later positions. Note that there are no edges among $V(G) \setminus S$, the ends of all these edges are already in position. For each vertex in $V(G) \setminus S$, we can calculate how much the total cost decreases with perching it at position i . We choose the $k - |S|$ ones with the top scores, and we show that it is always safe to use one of them. We need $k - |S|$ here because these vertices may be needed by other gaps.

We are now ready to summarize the algorithm in Figure 2 and use it to prove Theorem 1.3.

-
1. guess a minimal vertex cover S of G with $|S| \leq k$;
 2. guess an injective mapping $\sigma : S \rightarrow \{1, 2, \dots, k\}$;
 3. **for each** unoccupied position $p < k$ of σ **do**
 - 3.1. **for each** $u \in V(G) \setminus S$ **do**
 - 3.1.1. calculate $s(u) = \sum \{j - p \mid \sigma^{-1}(j) \in N(u), j > p\}$;
 - 3.2. $C \leftarrow k - |S|$ vertices maximizing $s(\cdot)$, breaking ties arbitrarily;
 - 3.3. guess a vertex $x \in C$, add x to S , and set $\sigma(x) = p$;
 4. **if** the cost of σ is $\leq w$ **then return** “yes”;
else return “no.”
-

Figure 2: The parameterized algorithm for minimum sum vertex cover.

Proof of Theorem 1.3. We use the algorithm described in Figure 2. Since the algorithm returns “yes” only when a solution is identified, it suffices to show a solution must be returned for a yes-instance. We fix an optimal solution σ^* , and we may number the vertices such that $\sigma^*(v_i) = i$. Let $S^* = \{v_1, \dots, v_k\}$. Since σ^* is feasible, S^* is a vertex cover of G . Step 1 finds a minimal vertex cover S of G that is a subset of S^* , and step 2 finds $\sigma(v)$ of each vertex $v \in S$. Note that $\sigma^* = \sigma$ when $|S| = k$, and we are already done. Otherwise, for each unoccupied position p , step 3 select a vertex u from $V(G) \setminus S$ and assign u to p .

Step 3.3 finds the vertex v_p if it is in C . Now suppose that $v_p \notin C$. By the selection of vertices in C , it contains a vertex v_i with $i > k$ and $s(v_i) \geq s(v_p)$. Let σ' be the solution obtained from σ^* by switching v_i and v_p . We argue that σ' has the same cost as σ^* , hence also an optimal solution. Between σ' and σ^* , only the costs of edges incident to v_i and v_p can be different. The cost of the edge $v_i v_j$ or $v_p v_j$ remains j if $j < p$. There is no edge between v_i and v_j or between v_p and v_j for $j > k$ (because S is a vertex cover). Thus, the difference between the total costs of σ' and σ^* is $s(v_p) - s(v_i) \leq 0$. Thus, the algorithm always ends with a solution with the same total cost as σ^* (note that $s(v_p) - s(v_i) \geq 0$ since σ^* is an optimal solution).

We now analyze the running time. We may preprocess the instance with the kernelization algorithm, and hence G has at most $O(k^2)$ vertices. We can use the algorithm of Damaschke [4] to find all the required minimal vertex covers in $O(m + k^2 2^k)$ time. For each of them, the number of injective mappings is $k! / (k - |S|)!$. Steps 3.1 and 3.2 can be done in $O(k^4)$ time. Step 3.3 makes $k - |S|$ branches. Note that $|S|$ increases by one with each iteration, and thus the total number of branching is $(k - |S|)!$. Step 4 takes $O(k^4)$ time. The total time is thus $O(m + 2^k k! k^4)$. \square

References

- [1] Shubhada Aute and Fahad Panolan. Parameterized algorithms for minimum sum vertex cover. In *Proceedings of the 16th Latin American Symposium on Theoretical Informatics, Part II*, volume 14579 of *Lecture Notes in Computer Science*, pages 193–207, 2024. doi:10.1007/978-3-031-55601-2_13.
- [2] Nikhil Bansal, Jatin Batra, Majid Farhadi, and Prasad Tetali. On min sum vertex cover and generalized min sum set cover. *SIAM Journal on Computing*, 52(2):327–357, 2023. doi:10.1137/21M1434052.
- [3] Jonathan F. Buss and Judy Goldsmith. Nondeterminism within P. *SIAM Journal on Computing*, 22(3):560–572, 1993. doi:10.1137/0222038.
- [4] Peter Damaschke. Parameterized enumeration, transversals, and imperfect phylogeny reconstruction. *Theoretical Computer Science*, 351(3):337–350, 2006. doi:10.1016/J.TCS.2005.10.004.
- [5] Uriel Feige, László Lovász, and Prasad Tetali. Approximating min sum set cover. *Algorithmica*, 40(4):219–234, 2004. doi:10.1007/S00453-004-1110-5.
- [6] Aleksa Stanković. Some results on approximability of minimum sum vertex cover. In *Proceedings of the 25th Approximation, Randomization, and Combinatorial Optimization*, volume 245 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 50:1–50:16, 2022. doi:10.4230/LIPICs.APPROX/RANDOM.2022.50.