

Optimal Resource Efficiency with Fairness in Heterogeneous GPU Clusters

Zizhao Mo
University of Macau
Macau SAR, China
yc17461@um.edu.mo

Huanle Xu*
University of Macau
Macau SAR, China
huanlexu@um.edu.mo

Wing Cheong Lau
The Chinese University of Hong Kong
Hong Kong
wclau@ie.cuhk.edu.hk

ABSTRACT

Ensuring the highest training throughput to maximize resource efficiency, while maintaining fairness among users, is critical for deep learning (DL) training in heterogeneous GPU clusters. However, current DL schedulers provide only limited fairness properties and suboptimal training throughput, impeding tenants from effectively leveraging heterogeneous resources. The underlying design challenge stems from inherent conflicts between efficiency and fairness properties.

In this paper, we introduce OEF, a new resource allocation framework specifically developed for achieving optimal resource efficiency and ensuring diverse fairness properties in heterogeneous GPU clusters. By integrating resource efficiency and fairness within a global optimization framework, OEF is capable of providing users with maximized overall efficiency, as well as various guarantees of fairness, in both cooperative and non-cooperative environments. We have implemented OEF in a cluster resource manager and conducted large-scale experiments, showing that OEF can improve the overall training throughput by up to 32% while improving fairness compared to state-of-the-art heterogeneity-aware schedulers.

CCS CONCEPTS

• **Computer systems organization** → **Cloud computing.**

KEYWORDS

Heterogeneous GPU cluster, fairness, scheduling, deep learning training

ACM Reference Format:

Zizhao Mo, Huanle Xu, and Wing Cheong Lau. 2024. Optimal Resource Efficiency with Fairness in Heterogeneous GPU Clusters. In *25th International Middleware Conference (Middleware '24)*, December 2–6, 2024, Hong Kong, Hong Kong. ACM, New York, NY, USA, 13 pages. <https://doi.org/10.1145/3652892.3654792>

1 INTRODUCTION

Modern deep-learning (DL) tasks are rapidly being applied across various domains, including object detection [1], natural language

processing [2], and video processing [3]. To meet the increasing demand for training DL tasks, major companies have established multi-tenant GPU clusters where multiple users need to share GPU resources. Additionally, production clusters today feature a variety of accelerator types due to the rapid pace of accelerator updates. For example, in Google Cloud Platform [4], seven types of GPUs coexist: A100, V100, P100, K80, T4, P4, and L4. While heterogeneous clusters provide users with more choices in terms of pricing and efficiency trade-offs for DL training, the complex runtime profiles of users—specifically, diverse training throughput across GPU devices—pose significant challenges in achieving high resource efficiency [5–8] and ensuring fairness [8–10] in resource allocation among users.

From an operator’s perspective, it is always imperative to provide users with the highest overall training throughput for the best resource efficiency. DL jobs typically have significantly different speedups of training throughput between GPU devices [7–9]. Specifically, the speedup ranges from almost no speedup to several times due to architectural differences between DL models. For high resource efficiency, it is desirable to allocate jobs with the most speedup on high-end GPUs to produce the highest training throughput. However, this can easily lead to extremely unbalanced efficiency, i.e., jobs with great speedup monopolize the fast GPU whereas other jobs have to be starved or assigned to low-end devices. As a consequence, simply optimizing resource efficiency grants negative *sharing incentive* to jobs with low speedup, and encourages users to cheat on their job speedup rate to win allocations on fast GPUs. In this sense, pure efficiency maximization shall violate *strategy-proofness*, which is an important fairness requirement as it can prevent users from lying about their requirements to improve their training performance.

From a user’s perspective, fairness has always been an important issue. A big challenge herein is that existing fairness schedulers are no-longer suitable for heterogeneous GPU clusters. First, the widely adopted fairness principle *max-min fairness* [11–13] and its variants in operating system [14–16] and network domains [17, 18] are tailored for resources of the same type. While this principle aims to equitably distribute resources, it can have an adverse impact on overall resource efficiency due to variations in speedup levels among different jobs. Second, GPUs are considered *interchangeable* resources for DL jobs, as explained in § 2.2. Therefore, we cannot directly apply existing multi-resource fairness schedulers [19–25] that allocate non-interchangeable resources (such as CPU, memory, or network) to heterogeneous GPU scheduling. In GPU clusters, it remains an open problem to design an efficient and fair policy that can offer users multiple fairness properties, including *envy-freeness* (where users do not prefer others’ allocations over their own) and

*Corresponding author

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Middleware '24, December 2–6, 2024, Hong Kong, Hong Kong

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 979-8-4007-0623-3/24/12

<https://doi.org/10.1145/3652892.3654792>


sharing-incentive (which incentivizes users to share resources), in addition to *strategy-proofness* [8].

In this paper, our focus is to address a fundamental problem: maximizing overall resource efficiency while meeting various fairness requirements for scheduling with heterogeneous GPUs. Existing researches have proposed efficient scheduling methods in this area [7–9], but these approaches primarily focus on training efficiency, leading to fairness violations. Furthermore, even schedulers that prioritize fairness can only guarantee *sharing-incentive* and *pareto-efficiency* [8, 9]. Among them, Gandiva_{fair} shares a similar objective to ours [9]. Specifically, it aims to strike a balance between efficiency and fairness by implementing a trading mechanism based on *max-min* fairness [26]. However, Gandiva_{fair} is far from optimal as it fails to address cheating or ensure *envy-freeness*.

We have identified the underlying reasons why current schedulers fall short in delivering adequate fairness properties and optimal efficiency. First, from a methodological perspective, these schedulers tightly couple their allocation schemes to specific fairness properties, attempting to integrate other properties in a best-effort manner without global coordination. Second, in principle, our analysis reveals inherent conflicts among different fairness properties in heterogeneous GPU scheduling. Pursuing high efficiency, for instance, proves incompatible with achieving *strategy-proofness*, *envy-freeness*, and *sharing-incentive*. Simply prioritizing the latter two fairness properties can, in fact, result in more harm than good.

Based on the identification, we present OEF, a resource allocation framework capable of globally coordinating multiple fairness properties and maximum resource efficiency in the context of heterogeneity. At its core, OEF explicitly quantifies efficiency and fairness, and formulates optimization problems to explore the best coordination between them in both cooperative and non-cooperative environments. These environments have been extensively studied in the scheduling literature to address fairness concerns [22]. In non-cooperative environments, such as multi-tenant platforms where individuals or entities need to compete for limited resources without a pricing mechanism, ensuring *strategy proofness* is imperative. Non-cooperative OEF incentivizes users to reveal the true training throughput in their DL jobs across various devices, facilitating optimized resource efficiency concurrently. In cooperative environments where *strategy-proofness* might not be a rigid requirement, OEF simultaneously achieves *envy-freeness* and *sharing-incentive* while guaranteeing optimal efficiency.

Moreover, OEF demonstrates its extensibility by supporting complex scheduling scenarios, such as accommodating users with varying priorities and enabling a user to run multiple types of DL tasks simultaneously. Furthermore, OEF only assigns GPUs with adjacent speedups to each user, thereby mitigating the adverse effect of skewed training speed across GPU types. We implemented a prototype system of OEF in a local cluster comprising 24 heterogeneous GPU devices to assess its performance. The results demonstrate that OEF successfully achieves desired fairness properties while outperforming state-of-the-art baselines. It provides users with a higher overall training throughput in both non-cooperative and cooperative settings, with improvements of up to 32%. Additionally, OEF significantly reduces the overall job completion time in the long term, achieving reductions of up to 19%. In summary, we have made the following contributions in this paper:



(a) Diverse speedup for users with different DL training jobs (b) Diverse speedup for users under different fair schedulers

Figure 1: The effect of GPU heterogeneity in DL training clusters, speedup denotes the training throughput normalized by that on the slowest GPU type. In this illustration, user-1 executes a VGG model, while user-2 engages in running an LSTM model.

- We identify the limitations of existing fairness frameworks tailored specifically for heterogeneous GPU clusters and highlight the inherent conflicts between resource efficiency and diverse fairness properties in the context of heterogeneous GPU scheduling.
- We design OEF, the first heterogeneity-aware resource allocation framework that can achieve *strategy-proofness* and *envy-freeness* while pursuing high resource efficiency. Additionally, OEF exhibits flexibility by accommodating users with varying priorities and multiple types of training workloads.
- We demonstrate that OEF exhibits high resource efficiency, excellent scalability and introduces minimal computational overhead when identifying the optimal allocation in large-scale clusters.

2 BACKGROUND AND MOTIVATION

2.1 Multi-tenant GPU Clusters

Today, GPU clusters are often shared among multiple tenants to reduce the operating costs and in the meanwhile, improve resource utilization [9]. To this end, a large number of DL jobs from tenants need to be served in production GPU clusters [27, 28]. As a representative use case, to train an accurate model for a given task, one may first run a large number of related training jobs with different combinations of hyper-parameters, e.g., learning rate, batch size, or dropout rate, to explore the best combination that can yield the highest accuracy. Since these jobs are of similar model structure, they are (almost) equally accelerated given the same GPU. As reported by [27], approximately 90% of jobs in Alibaba clusters are recurring hyperparameter search jobs. Furthermore, tenants may concurrently experiment with different DL models for the same tasks, where the acceleration effect of jobs may vary significantly due to architectural differences. Therefore, schedulers should be adaptable to such situations and function effectively to maximize efficiency.

2.2 Diverse Speedup under GPU Heterogeneity

The GPU heterogeneity in production clusters complicates scheduling among tenants. Specifically, DL training models typically show heterogeneous acceleration performance across GPU types due

to architectural differences between models. Fig. 1(a) exhibits the skewed acceleration effect across jobs normalized by the training speed on the slowest GPU type. We can observe that VGG achieves $1.39\times$ speedup on RTX 3090. By contrast, LSTM achieves much higher speedups on more advanced GPUs, i.e., $2.15\times$ speedup on 3090.

2.3 Fair Allocation in Heterogeneous Environment

Given k types of GPUs with m_k devices each, and the training throughput of DL jobs on these k types from n different tenants (users), the cluster manager must use a scheme \mathcal{S} to determine the allocation matrix X , which specifies the number of each type of GPU devices assigned to each tenant:

$$\mathcal{S}(\{\vec{W}_1; \vec{W}_2; \dots; \vec{W}_n\}) = X = \{\vec{x}_1; \vec{x}_2; \dots; \vec{x}_n\}.$$

$\vec{w}_l = \langle w_l^1, w_l^2, \dots, w_l^k \rangle$ represents the vector of training throughput for the l -th tenant. $\vec{x}_l = \langle x_l^1, x_l^2, \dots, x_l^k \rangle$ is the allocation vector, here, x_l^j denotes the number of devices of type j . To better formulate fairness, we normalize the throughput vector to the training throughput on the slowest GPUs, i.e., $w_l^1 = 1$ for all tenants¹. In this sense, \vec{W}_l captures the speedup of different GPU types relative to the slowest type, also known as the speedup vector, and $W = \{\vec{W}_1; \vec{W}_2; \dots; \vec{W}_n\}$ is the speedup matrix capturing all speedup information for all users.

2.3.1 Fairness requirements. As defined in previous works [10, 19, 22], a fair allocation scheme needs to meet four requirements:

- (1) **Strategy-proofness (SP):** Tenants should not be able to benefit by lying about their speedups. In this sense, when the l -th tenant reports a fake vector \vec{W}_l where each element is no less than that in the groundtruth, his attained normalized training throughput will decrease. This property serves as a deterrent, effectively preventing tenants from engaging in cutthroat competition for precious high-end GPU resources.
- (2) **Envy-freeness (EF):** A tenant should not prefer the allocation of another tenant, thereby ensuring equitable treatment for all tenants.
- (3) **Sharing-incentive (SI):** A tenant should obtain higher training throughput in a cluster partition consisting of $\frac{1}{n}$ of all types of GPU devices. Without this attribute, tenants would rather prefer an exclusive GPU cluster.
- (4) **Pareto-efficiency (PE):** It should not be possible to increase the training throughput of a user without decreasing the throughput of at least another user².

2.3.2 Optimal resource efficiency. As demonstrated in extensive real-world studies [27, 29], it is well-established that DL training jobs often span hours or even days, presenting significant opportunities for acceleration. This emphasizes the critical need to integrate

¹Due to hardware evolution, the slowest GPU type for different DL jobs is consistent, i.e. RTX 3070 is always slower than RTX 3090 when training various DL jobs.

²We follow the original definition of PE given by DRF [19]. This definition is stronger than the one introduced in Gavel [8], where the allocation is work conserving but throughput improvement can still be achieved via trading GPU shares among users.

resource efficiency in order to achieve optimized training throughput. In light of this requirement, the co-optimization of efficiency and fairness has the potential to further bolster the effectiveness of a scheduling scheme solely focused on fairness.

In particular, it is desirable to strive for the highest overall training throughput, referred to as *optimal efficiency* while also taking various fairness considerations into account. It is important to clarify that this concept differs from *pareto-efficiency*, as *pareto-efficiency* allocations may not always lead to *optimal efficiency*.

2.3.3 Why need new fair schedulers? While Max-Min based schedulers excel in offering users various fairness attributes, they fall short in delivering satisfactory throughput performance to tenants in heterogeneous clusters, resulting in diminished overall resource efficiency. Illustrated in Fig. 1(b), User-2 experiences a training throughput decline of $1.18\times$ compared to that achieved under our proposed scheduler OEF, which concurrently maintains various fairness properties in a heterogeneity environment (elaborated in § 5). In aggregate, the cluster's overall efficiency contracts by approximately 10%. This inefficiency arises because Max-Min fairness treats DL training jobs from tenants equally, inadequately leveraging high-end resources.

Another widely-adopted fairness schedulers, i.e., Dominant Resource Fairness (DRF) [19] and its variants [20–25], are also unfit for heterogeneous clusters. They primarily allocate resources proportionally to a user's requested resources, such as computation, storage, and networking. However, there is a significant distinction between our scenario and the multi-resource setting: GPUs of various types actually belong to the same category, namely computation resources. In other words, DL jobs can be executed on any type of GPU device, regardless of differences in training performance—an attribute known as *interchangeability* [7]. On the contrary, a job that requires network resources cannot function if no network bandwidth is granted. Consequently, DRF-based schemes are not suitable for this new scenario, necessitating the development of innovative fairness solutions.

2.4 Limitation of Existing Heterogeneous Schedulers

Gandiva_{fair} designs a trading mechanism on top of max-min fairness. Specifically, Gandiva_{fair} first equally divides GPU resources to users according to max-min fairness. Then, it performs greedy trading between users, that is, during the trading process, the fastest-accelerating users on high-end GPUs use a second-price auction mechanism to trade their shares of slow GPUs for shares of fast GPUs using the second price auction mechanism [30], where the second price denotes the speedup rate on fast GPUs of the second most accelerated user. Since this trading mechanism can only increase each user's training throughput, Gandiva_{fair} satisfies *sharing-incentive*. In addition, the second-price auction mechanism also prevents the fastest-accelerating user from lying about his speedup on fast GPUs. Consider an example where we have three users u_1 , u_2 , and u_3 . The speedup matrix indicating the acceleration effect on diverse GPU types among jobs and the allocation matrix

are presented as W and X respectively:

$$W = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 2 \\ 1 & 3 \\ 1 & 4 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_3 \end{matrix}, X = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 0.09 \\ 0 & 0.47 \\ 0 & 0.44 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_3 \end{matrix}. \quad (1)$$

And the achieved efficiency vector for users are denoted as $E = \langle 1.18; 1.41; 1.76 \rangle$. The trading mechanism benefits all three users, leading to a much higher overall resource efficiency than the original max-min fairness scheduler. $\text{Gandiva}_{\text{fair}}$ is *pareto-efficient*, however, it violates *envy-freeness*, as the algorithm proceeds greedily, regardless of inter-user constraints. In this example, u_3 prefers u_2 's allocation.

Another limitation of $\text{Gandiva}_{\text{fair}}$ is that it cannot completely prevent all users from lying. Suppose u_1 artificially increases the speedup value on GPU_2 from 2 to 2.8. In this case, the price in the second-round trading changes from 2.5 to 2.9, so u_1 successfully wins more portions on GPU_2 and improves his efficiency, violating *strategy-proofness*, as shown below:

$$W^f = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 2.8 \\ 1 & 3 \\ 1 & 4 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_3 \end{matrix}, X^f = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 0.11 \\ 0 & 0.45 \\ 0 & 0.44 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_3 \end{matrix}.$$

In this case, the achieved efficiency vector becomes $E^f = \langle 1.22; 1.35; 1.76 \rangle$. Moreover, one can simply construct a more resource-efficient allocation that satisfies both *envy-freeness* and *sharing-incentive* properties, i.e.:

$$X^* = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 0 \\ 0 & 0.5 \\ 0 & 0.5 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_3 \end{matrix}, E^* = \begin{pmatrix} 1 \\ 1.5 \\ 2 \end{pmatrix}. \quad (2)$$

Without cheating, this allocation achieves much higher resource efficiency than $\text{Gandiva}_{\text{fair}}$, indicating $\text{Gandiva}_{\text{fair}}$ fails to provide optimal resource efficiency under *sharing-incentive* constraints.

Gavel proposes a completely different approach by trying to speed up the least incentivized users in the cluster. In this sense, the ratio of efficiency obtained from Gavel to that under a max-min fair share is equalized across users. This policy is naturally *sharing-incentive*. However, Gavel falls short to provide high resource efficiency and *envy-freeness*. To be specific, consider the same speedup matrix as in Expression (1), the allocation and the related efficiency under Gavel is given by:

$$X = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 0.91 & 0.09 \\ 0.09 & 0.45 \\ 0 & 0.45 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_3 \end{matrix}, E = \begin{pmatrix} 1.09 \\ 1.44 \\ 1.8 \end{pmatrix}, \quad (3)$$

where u_3 prefers u_2 's allocation and the total resource efficiency attained is even lower than that under $\text{Gandiva}_{\text{fair}}$. Similarly, users

Table 1: Properties guaranteed by existing schedulers.

	PE	EF	SI	SP	<i>optimal efficiency</i>
Gavel [8]	✗	✗	✓	✗	✗
$\text{Gandiva}_{\text{fair}}$ [9]	✓	✗	✓	✗	✗
OEF	✓	✓	✓	✓	✓

under Gavel also have incentive to cheat on their speedup rate. For example, when u_1 increase his speedup rate on GPU_2 to 2.5, his resulted share vector become $\langle 0.85, 0.15 \rangle$, leading to higher resource efficiency. In this sense, Gavel does not achieve *strategy-proofness* either. Moreover, u_2 can trade with u_1 to obtain higher efficiency without hurting anyone, that is, $x'_1 = \langle 1, 0.045 \rangle$ and $x'_2 = \langle 0, 0.0495 \rangle$. This demonstrates the *pareto-inefficiency* and non-optimal resource efficiency under Gavel.

Upon examining existing schedulers, we find that, in addition to not achieving optimal efficiency, they fail to ensure various critical fairness properties outlined in Tab 1. One key reason is the tight coupling of these schedulers with a single fairness objective, such as Gavel and $\text{Gandiva}_{\text{fair}}$, aim to make their scheme sharing-incentive. These schedulers then try to enhance resource efficiency on a best-effort basis by introducing a second-stage optimization. However, due to the absence of global coordination between resource efficiency and fairness within a unified framework, they are far from effective. Additionally, as these schedulers assume jobs of each user can be represented by a speedup vector, they are not compatible with cases where multiple types of jobs are simultaneously trained by the same user, which consequently reduces their practicality.

3 OEF OVERVIEW

3.1 Design Challenges

3.1.1 Conflicts between efficiency and fairness. The first challenges arise from the inherent conflicts between maximizing resource efficiency and maintaining fairness.

- *Merely maximizing resource efficiency is detrimental.* Maximizing the overall training throughput within the cluster can be formulated as the following objective:

$$\max \sum_{j=1}^k \sum_{l=1}^n w_l^j \cdot x_l^j, \quad \text{s.t.}, \sum_{l=1}^n x_l^j \leq m_j, \quad \text{for all } j. \quad (4)$$

However, optimizing this objective alone yields an outcome that consistently assigns the highest scheduling priority to jobs with the greatest speedup on a fast GPU, which is inherently unfair to users with slower speedups. As an example, consider three users (u_1, u_2, u_3) with different speedups sharing a cluster of two different GPUs as follows:

$$W = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 2 \\ 1 & 3 \\ 1 & 4 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_3 \end{matrix}, X = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 0 \\ 0 & 0 \\ 0 & 1 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_3 \end{matrix}. \quad (5)$$

It is straightforward to show that the best allocation result that produces the highest overall efficiency is to assign GPU_2 to u_3 and assign GPU_1 to u_1 or u_2 . However, this allocation totally neglects

the resource demand of u_2 (or u_1), which is not *sharing-incentive* since u_2 does not get $\frac{1}{3}$ of all resources in the cluster. This allocation is also not *envy-free* as both u_1 and u_2 prefer u_3 's allocation. Moreover, such scheme encourages u_1 and u_2 to lie, as jobs with greater speedup would be more likely to be placed on fast GPUs. Therefore, such scheme does not satisfy *strategy-proofness*. In this sense, purely maximizing resource efficiency is completely unfair to users with slow speedup. Additionally, since users have incentive to lie on their speedup profiles, the resource allocation process will eventually behave like max-min fairness, thereby greatly degrading the overall resource efficiency that can be achieved in the cluster.

• *Naively maintaining fairness properties reduces resource efficiency.* Placing excessive emphasis on fairness attributes such as *envy-freeness* can actually hinder resource efficiency, leading to a situation akin to the classic prisoner's dilemma problem [22]. To demonstrate this, let's consider an example where two users share a cluster comprising two distinct GPUs, characterized by a speedup matrix represented by the following matrix, labeled as W . When attempting to optimize resource efficiency and maintain *envy-freeness* simultaneously, it results in the allocation X as follows:

$$W = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 2 \\ 1 & 5 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \end{matrix}, X = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 0.25 \\ 0 & 0.75 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \end{matrix}, \quad (6)$$

by following the envy-freeness constraints for u_1 and u_2 listed as below:

$$x_1^1 + 2x_1^2 \geq x_2^1 + 2x_2^2, \text{ and } x_2^1 + 5x_2^2 \geq x_1^1 + 5x_1^2.$$

The above allocation X yields a total resource efficiency of 5.25. In contrast, when the first user cheats the cluster manager and lies about his speedup on GPU₂ up to 4, the resulted allocation will become X^l listed below, which leads to a total throughput of 1.75 for u_1 and is 16.7% higher than his original throughput. However, the overall efficiency will decrease from 5.25 to 4.875, implying that naively preserving *envy-freeness* can do more harm than good. This example further suggests that after u_1 lies, another user u_2 also has the incentive to lie to increase his throughput. Finally, the result X^f will be equivalent to the allocation under max-min fairness as shown below, which results in no better throughput for both users, that is, with u_1 obtaining 1.5 and u_2 achieving 3.

$$X^l = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 0.375 \\ 0 & 0.625 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \end{matrix}, X^f = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 0.5 & 0.5 \\ 0.5 & 0.5 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \end{matrix},$$

Under the same speedup matrix, *sharing-incentive* requires the allocation to matrix satisfy:

$$x_1^1 + 2x_1^2 \geq 1.5, \text{ and } x_2^1 + 4x_2^2 \geq 3.$$

When u_1 lies about his speedup on GPU₂ to 4, his own efficiency improves whereas the overall resource efficiency drops by 8%.

3.1.2 Conflicts between various fairness properties. The second challenge stems from the inherent conflicts between *strategy-proofness* and other fairness properties when striving to maximize resource




Figure 2: An example shows the conflicts between various fairness properties. The blue and yellow space represent the allocation for the first and second user, respectively.

efficiency in a heterogeneous context. These conflicts are illuminated through the following theorems. This highlights that it is not feasible to provide users with both properties at the same time. Therefore, we need to carefully integrate fairness properties with resource efficiency when designing resource allocation schemes.

LEMMA 3.1. *To achieve optimal efficiency, in \vec{x}_1 , which represents the allocation for the user with the slowest speedup, all non-zero elements are positioned at the leftmost positions and have a value of m_j , except for the right-most element.*

PROOF. In order to maximize the overall efficiency, the lowest-end GPU quotas must be allocated user 1 who possesses the lowest speedup among all users. Referring to the definition of speedup in § 2.3, it is evident that $w_1^j = \min_l w_l^j, \forall j \in [1, \dots, k]$, and $w_1^p < w_1^q, \forall 1 \leq p < q \leq k$. These inequalities imply that the non-zero elements in \vec{x}_1 are filled from left to right, and $x_1^q > 0$ holds only when $x_1^p = m_p, \forall p < q$. \square

THEOREM 3.2. *No sharing mechanism providing optimal resource efficiency can simultaneously guarantee envy-freeness and strategy-proofness.*

PROOF. To achieve optimal efficiency, we should have stringent *envy-free* constraints on \vec{x}_1 and another user \vec{x}_l such that:

$$\vec{W}_1 \cdot \vec{x}_1 - \vec{W}_l \cdot \vec{x}_l = 0, l \neq 1, \quad (7)$$

otherwise, allocating a larger GPU share to users with higher speedup values could enhance the overall resource efficiency. Let us examine a scenario where user 1 manipulates and marginally increases the speedup vector, while ensuring it remains below the speedup of the second slowest user, i.e.,

$$\vec{W}_2 \geq \vec{W}_1' = \langle 1, w_1^2 + \epsilon_1^2, \dots, w_1^k + \epsilon_1^k \rangle \geq \vec{W}_1, \text{ and } \epsilon_1^j > 0, \forall j.$$

If the rightmost non-zero element x_1^j does not reach the limit m_j , it becomes apparent that the inequality $x_1^{j'} > x_1^j$ holds by utilizing Lemma 3.1. Consequently, we have $\vec{W}_1 \cdot \vec{x}_1' > \vec{W}_1 \cdot \vec{x}_1$. In another scenario, it is evident that the leftmost zero element $x_1^{(j+1)'}$ improves. Both of these results contradict *strategy-proofness*. This completes the proof. \square

THEOREM 3.3. *No sharing mechanism providing optimal resource efficiency can guarantee sharing-incentive and strategy-proofness at the same time.*

PROOF. In this scenario, user 1 is also subjected to a stringent *sharing-incentive* constraint on the allocation vector \vec{x}_1 :

$$\vec{W}_1 \cdot \vec{x}_1 - \vec{W}_1 \cdot \frac{\vec{m}}{n} = 0, \quad \vec{m} = \langle m_1, \dots, m_k \rangle, \quad (8)$$

We construct a fake speedup vector, $\vec{W}'_1 = \langle 1, w_1^2, \dots, w_1^k + \epsilon_1^k \rangle$, where only the last value is augmented. Under the real speedup, we assert that $x_1^k < \frac{m^k}{n}$, as having $x_1^k \geq \frac{m^k}{n}$ would lead to $x_1^j = m_j, \forall j \neq k$. This condition would imply $\vec{W}_1 \cdot \vec{x}_1 > \vec{W}_1 \cdot \frac{\vec{m}}{n}$, which contradicts Equation (8). Therefore, we can conclude that $\vec{W}_1 \cdot \vec{x}_1 \leq \vec{W}'_1 \cdot \vec{x}_1 < \vec{W}'_1 \cdot \frac{\vec{m}}{n}$. This implies that $\vec{x}'_1 \geq \vec{x}_1$ by utilizing Lemma 3.1, violating *strategy-proofness*. This completes the proof. \square

Moreover, we provide an intuitive example depicted in Fig. 2 to better explain these two theorems. For the first theorem, consider the scenario where two users with a speedup matrix of $\langle 1, 2; 1, 4 \rangle$. In this case, the allocation that provides the optimal efficiency and *envy-freeness* is $\langle 1, 0.25; 0, 0.75 \rangle^3$. When the first user lies and reports the speedup to be $\langle 1, 3 \rangle$, the original allocation is no longer *envy-free*⁴, and the new allocation with the same goal becomes $\langle 1, 0.33; 0, 0.67 \rangle$, thus violating *strategy-proofness*.

3.2 Architecture & Workflow

In light of the conflicts that arise from different fairness properties, our primary objective is to develop allocation schemes for diverse scheduling scenarios, with the aim of improving resource efficiency while maintaining fairness properties to the greatest extent possible. Specifically, OEF prioritizes *strategy-proofness* while maximizing resource efficiency in non-cooperative environments where multiple tenants may cheat to compete for limited resources. In cooperative environments where cheating is a non-issue, it ensures *envy-freeness* and *sharing-incentive* while maximizing the resource efficiency. Distinct scheduling mechanisms are adopted based on the selection of the cluster administrator. Moreover, the *pareto-efficiency* are always maintained in both environments. The complete system architecture of OEF, along with its scheduling workflow, is depicted in Fig. 3.

Once a tenant enters the cluster, OEF takes charge of the submitted DL jobs. First, OEF provides tenants with an profiling agent, to which users submit one of their DL training tasks for throughput estimation. Subsequently, the agent delivers the profiled throughput to the scheduler module, which is responsible for generating optimal resource allocation schemes. At its core, a fair share evaluator (① in Fig. 3) first computes the fair share among users based on the algorithm specifically tailored for a selected scheduling environment. Importantly, the preservation of *strategy-proofness* in the non-cooperative environment is guaranteed through the enforcement of OEF's allocation mechanism. The placer component (② in




Figure 3: The system architecture of OEF.

Fig.3) then allocates GPUs to users, enforcing efficient allocation in the long run. Specifically, we design a rounding based placement policy to approximate the fractional ideal GPU shares among tenants in multiple rounds, and address the straggler effect incurred by cross-type placement of DL training jobs.

4 OEF DESIGN

4.1 Profiling

In OEF, tenants have the flexibility to submit multiple DL training jobs of the same type or diverse types. To facilitate this, the profiling agent offers tenants a profiling interface, allowing them to collect throughput information for their DL training jobs on each type of GPU. Specifically, tenants are responsible for selecting a representative profiling task for each job type they have. The profiling mechanism is lightweight, incurring minimal profiling overhead by executing a short run (few mini-batches in our setting). This makes sense since the execution time of each iteration almost keeps constant over time. Upon the completion of the profiling process, the final speedup vector is generated and provided to OEF scheduler, which will then makes allocation decisions to each tenant.

4.2 Allocation Mechanisms

4.2.1 OEF in non-cooperative environments. In contrast to the requirements of *envy-freeness* or *sharing-incentive*, expressing *strategy-proofness* directly through a formulation is challenging. This difficulty arises from the fact that if a user misrepresents the speedup vector, the speedup matrix W and allocation matrix X change accordingly, making it difficult to compare the efficiency between before and after cheating among users. Fortunately, we have discovered that ensuring all users achieve identical (normalized) throughput can guarantee *strategy-proofness*. We formally design the allocation scheme based on the optimal solution to the following optimization problem:

$$\max \sum_{l=1}^n \sum_{j=1}^k w_l^j \cdot x_l^j \quad (9a)$$

$$\text{s.t.}, \sum_{l=1}^n x_l^j \leq m_j, \quad \forall j, \quad (9b)$$

$$\sum_{j=1}^k w_l^j \cdot x_l^j = \sum_{j=1}^k w_i^j \cdot x_i^j, \quad \forall 1 \leq i, l \leq n. \quad (9c)$$

³As the second user has the highest speedup rate, giving more high-end GPU devices to her benefits the overall efficiency most. However, to maintain *envy-freeness*, the user with speedup $\langle 1, 2 \rangle$ should not envy the share of another user barely.

⁴Since $\langle 1, 3 \rangle \cdot \langle 1, 0.25 \rangle < \langle 1, 3 \rangle \cdot \langle 0, 0.75 \rangle$, the user with false speedup will envy the share of another one.

The key idea behind this optimization is that attempting to cheat will lead to a new allocation that still maintains the same overall speedup across all users. If the efficiency of honest users decreases under the new allocation, it follows that the efficiency of the cunning user under their actual speedup should also decrease due to the equality constraint (9c). Conversely, if honest users receive more resources because of improved efficiency, it indicates that cunning users must be allocated fewer resources than they had received before.

4.2.2 OEF in cooperative environments. As *strategy-proofness* is not a major concern in cooperative environments, we get rid of the conflicts identified in § 3.1.2 and are able to incorporate *envy-freeness* and *sharing-incentive* into a unified framework. To be more precise, we formulate the cooperative OEF framework as follows:

$$\max \sum_{l=1}^n \sum_{j=1}^k w_l^j \cdot x_l^j \quad (10a)$$

$$\text{s.t.}, \sum_{l=1}^n x_l^j \leq m_j, \quad \forall j, \quad (10b)$$

$$\sum_{j=1}^k w_l^j \cdot x_l^j \geq \sum_{j=1}^k w_l^j \cdot x_l^j, \quad \forall 1 \leq i, l \leq n. \quad (10c)$$

In this framework, we address the need for *envy-freeness* by directly incorporating it as optimization constraints. However, we do not include explicit constraints for expressing *sharing-incentive*. This is because, as we will demonstrate in Theorem 5.1, the pursuit of *envy-freeness* inherently leads to *sharing-incentive* when we maximize the overall resource efficiency.

4.2.3 Weighted OEF. Currently, administrators frequently assign varying levels of priority to users. Surprisingly, it is possible to extend OEF to accommodate this scenario by allocating additional resources to users engaged in more critical tasks or those with higher resource quotas [9].

In the weighted OEF framework, each tenant j is assigned a weight π_j that represents their level of importance. Specifically, if $\pi_2 = 2$ and $\pi_1 = 1$, it implies that the second user u_2 should receive an allocation resulting in twice the total training throughput compared to the first user u_1 . OEF introduces a novel approach to achieve this while ensuring fairness. The key concept involves replicating the speedup vector multiple times for users with higher weights. For instance, consider the speedup matrix in Eq. (6) with $\pi_2 = 2$, OEF will modify the speedup matrix and produce an allocation in a non-cooperative environment as follows:

$$W = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 2 \\ 1 & 5 \\ 1 & 5 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_2 \end{matrix}, \quad X = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 1/3 \\ 0 & 1/3 \\ 0 & 1/3 \end{pmatrix} \begin{matrix} u_1 \\ u_2 \\ u_2 \end{matrix}.$$

In this scenario, if there is only one worker available for two types of GPUs, u_2 will be allocated 2/3 fraction of the second type of GPU. This replication approach employed by Weighted OEF ensures that all the fairness properties achieved by OEF are perfectly maintained.

More importantly, it enables a user to run multiple DL jobs with varying speedups, as explained in § 4.2.4. However, conventional solutions that directly incorporate user weights into optimization problems are unable to handle such cases.

4.2.4 Compatible with different job types. In certain situations, a user may have the need to train multiple different types of DL jobs concurrently. However, representing these distinct jobs within a single speedup vector can be challenging. Fortunately, the framework of Weighted OEF allows us to effectively address this scenario.

When a user submits different types of DL jobs to a cluster, OEF treats each job type as a separate virtual user. This allows us to handle the different job types individually. However, it is worth noting that simply creating virtual users may result in an unfair increase in a user's overall throughput. To address this, we divide the weight of a user equally among their job types and assign a corresponding weight to each virtual user.

Once again, we will use the speedup matrix in Eq. (6), as an example to demonstrate the allocation process. Consider that both users have equal weights and the first user wishes to train a new DL job with a speedup vector of $\langle 1, 3 \rangle$ in addition to the original job, the resulting new speedup matrix and the allocation in a non-cooperative environment are as follows:

$$W = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 2 \\ 1 & 3 \\ 1 & 5 \\ 1 & 5 \end{pmatrix} \begin{matrix} u_1 \\ u_1 \\ u_2 \\ u_2 \end{matrix}, \quad X = \begin{pmatrix} \text{GPU}_1 & \text{GPU}_2 \\ 1 & 0.11 \\ 0 & 0.41 \\ 0 & 0.24 \\ 0 & 0.24 \end{pmatrix} \begin{matrix} u_1 \\ u_1 \\ u_2 \\ u_2 \end{matrix}.$$

By this design, OEF is also able to support different priorities of jobs within the same tenant.

4.3 Placement Optimization

Given the substantial interference caused by multiplexing [31], it proves more advantageous for the placer in OEF to allocate the entire GPU to a single user in each scheduling round. However, there is a possibility that the fair share evaluator may yield fractional share values. To mitigate this, we have developed a rounding policy that converts the fractional value assigned to each user into an integral share, ensuring fairness and efficiency in the long run. During each round t , the placer tracks the cumulative deviation $\text{dev}_j(t)$ for every user j from their ideal share $\text{ideal}_j(t)$. Utilizing this deviation, OEF assigns each user j a share, represented as $\text{real}_j(t) = \text{round}(\text{ideal}_j(t) + \text{dev}_j(t))$. The deviation is updated based on the formula $\text{dev}_j(t+1) = \text{dev}_j(t) + (\text{ideal}_j(t) - \text{real}_j(t))$, allowing the actual share for each job to gradually approximate the assigned value over time.

In situations where a user is allocated only a small GPU share, insufficient to meet the requirements of any job, we have refined the rounding strategy. Specifically, the placer adjusts $\text{real}_j(t)$ to 0 if it falls below $\min_k \text{demand}_k$, where demand_k represents the required worker size of job k under user j . By progressively accumulating the deviation value over time, tenants who experience resource

starvation are assured a $\text{real}_j(t)$ greater than $\min_k \text{demand}_k$. Consequently, these tenants will inevitably have the opportunity to execute at least one job.

To further alleviate network contention within the cluster, OEF optimizes the placement scheme for DL workloads. Notably, the placer grants placement priority to jobs with more workers, as the collective communication overhead—a primary contributor to network congestion—escalates with the number of workers. Consequently, under OEF, these jobs are prioritized for placement on a host whenever feasible.

4.4 Alleviating the Straggler Effect

It is possible for users to possess multiple types of GPUs, requiring the distribution of their jobs across different GPU types under OEF. In such cases, the occurrence of the *straggler effect* is a concern, where the slowest GPU type limits the overall speed of DL training, outweighing the advantages provided by faster GPUs. However, OEF's optimization ensures that the allocated GPUs for each user are limited to a small range, as proven in Theorem 5.2. This advantage greatly mitigates the impact of the straggler effect.

Furthermore, we provide a theoretical finding that, with OEF, only a few users and their respective jobs will experience the straggler effect. According to the Extreme Point Theorem [32], the allocation matrix produced by OEF contains a maximum of $(n + m - 1)$ nonzero elements. Hence, when the number of GPU types is smaller than the number of tenants, most tenants will be allocated only one type of GPU. This observation highlights the effectiveness of OEF in minimizing the impact of the straggler effect.

4.5 Implementation Details

We have developed a prototype system for OEF using Python 3. The current implementation supports DL training jobs written in PyTorch.

Fair share evaluation. Given the linearity inherent in our algorithm formulation, we have implemented the fair share evaluator in OEF utilizing *cvxpy*, an effective tool for solving convex optimization problems. In this context, resource allocation is defined as a *variable*, and fairness constraints are articulated as *constraints*. We employ the *ECOS* solver to efficiently generate the allocation.

Control and data plane. Within OEF, inter-module communication is established through Restful interfaces. Additionally, the seamless transfer of checkpoint files between hosts is facilitated by *rsync*, ensuring an imperceptible training process for the user.

5 PROPERTIES OF OEF

In this section, we present the main properties achieved by the OEF framework.

- (1) OEF satisfies *pareto-efficiency* (Theorem 5.3).
- (2) In non-cooperative environments, OEF ensures *strategy-proofness* (Theorem 5.4). To our knowledge, OEF is the first resource allocation framework that can achieve *strategy-proofness* for heterogeneous GPU clusters.
- (3) In cooperative environments, OEF achieves the optimal resource efficiency and ensures *sharing-incentive* and *envy-freeness* (Theorem 5.1).

- (4) OEF only assigns GPUs of adjacent types to the same user (Theorem 5.2). OEF can benefit from this property to better support alleviating the potential straggler effect in distributed DL training (§ 4.4).

THEOREM 5.1. *Cooperative OEF achieves the optimal resource efficiency, while ensuring sharing-incentive and envy-freeness.*

PROOF. As discussed above, envy-freeness denotes that the GPU share assigned to each user is already the best-fit one in contrast to that of others, i.e., $\sum_{j=1}^k w_l^j \cdot x_l^j \geq \sum_{j=1}^k w_l^j \cdot x_i^j, \forall 1 \leq i, l \leq n$. Summing up all constraints for a user l , including a constraint that user l should not envy the share he has already obtained, we have:

$$n \cdot \sum_{j=1}^k w_l^j \cdot x_l^j \geq \sum_{i=1}^n \sum_{j=1}^k w_i^j \cdot x_i^j.$$

Note that we also have $\sum_{i=1}^n x_i^j = m_j$ for each type j of GPU resources. In this sense, by moving n to the left side, we can obtain:

$$\sum_{j=1}^k w_l^j \cdot x_l^j \geq \sum_{j=1}^k \frac{m_j}{n} \cdot w_l^j,$$

which directly implies *sharing-incentive*. As in cooperative environments OEF explicitly formulates *envy-freeness* constraint, these two properties are automatically achieved. Furthermore, the OEF framework guarantees the best resource efficiency, since linear optimization yields a globally optimal solution. This completes the proof. \square

THEOREM 5.2. *Under OEF, users are allocated adjacent GPU types.*

PROOF. In this part, we prove that OEF can allocate adjacent GPU types only in cooperative and non-cooperative environments respectively.

First, in the non-cooperative setting, we first demonstrate that OEF does not assign a non-zero value to the lower left corner of another non-zero value. To achieve this, we construct a counter-example as follows:

$$X = \begin{pmatrix} x_1 & \cdots & y_1 \\ \vdots & \ddots & \vdots \\ x_2 & \cdots & y_2 \end{pmatrix}, \quad W = \begin{pmatrix} a_1 & \cdots & a_1 \cdot b_1 \\ \vdots & \ddots & \vdots \\ a_2 & \cdots & a_2 \cdot b_2 \end{pmatrix},$$

where y_1 and x_2 are non-zero, $a_2 > a_1$, and $b_2 > b_1$. Note that two users should have the same efficiency according to the formulation of non-cooperative OEF. However, if we modify the allocation matrix X to be as follows:

$$\begin{pmatrix} x_1 + x_2 & \cdots & y_1 - \epsilon_1 \\ \vdots & \ddots & \vdots \\ 0 & \cdots & y_2 + \epsilon_2 \end{pmatrix}, \quad \text{or} \quad \begin{pmatrix} x_1 + \epsilon_3 & \cdots & 0 \\ \vdots & \ddots & \vdots \\ x_2 - \epsilon_4 & \cdots & y_1 + y_2 \end{pmatrix},$$

we can keep the efficiency of each user unchanged while leaving spare resources in x or y column, which can be utilized to improve the efficiency of all users to the same extent. To be specific, in the first case, we have $a_1 x_1 + a_1 b_1 y_1 = a_1(x_1 + x_2) + (y_1 - \epsilon_1)a_1 b_1$ and $a_2 x_2 + a_2 b_2 y_2 = a_2 b_2(y_2 + \epsilon_2)$. Spare resources exist because $\epsilon_1 - \epsilon_2 = \frac{x_2}{b_1} - \frac{x_2}{b_2} > 0$. In this sense, maximum resource efficiency is not achieved under allocation X , violating the optimality of OEF. This indicates that it is impossible for OEF to produce allocations

like X . As such, an allocation that has a zero value between non-zero values with the following pattern:

$$X = \begin{pmatrix} & & x_1 & & \\ & & \vdots & & \\ x_2^1 & \cdots & 0 & \cdots & x_2^2 \\ & & \vdots & & \\ & & x_3 & & \end{pmatrix},$$

will not exist, as either x_1 or x_3 is non-zero, it will locate on the lower left corner of another non-zero entry. Therefore, users are allocated adjacent GPU types only.

We proceed to prove the theorem under cooperative OEF. Note that in cooperative OEF, no inter-user efficiency equalization is enforced and each user is only required to have an efficiency greater than a certain value (for *envy-freeness* constraints, this value is $\min_l w_i \cdot x_l, \forall l$ given a user i). In this sense, we can directly trade between the first and the second column, or trade between the second and the third column within X to generate higher efficiency without hurting anyone, thus contradicting the optimality of OEF. This completes the proof. \square

THEOREM 5.3. *OEF achieves pareto-efficiency.*

PROOF. Assuming that the allocation produced by OEF is "pareto-inefficient", which means that it is possible to perform effective trading to improve overall efficiency without negatively impacting anyone. In this sense, there must exist another allocation, denoted as X' , that results in a greater overall efficiency than the OEF allocation X , while still satisfying the same constraints, i.e., $\sum_{j=1}^k \sum_{l=1}^n w_l^j \cdot x_l^j > \sum_{j=1}^k \sum_{l=1}^n w_l^j \cdot x_l^j$. However, this contradicts the fact that X is the globally optimal solution within the same feasible domain in linear optimization. This completes the proof. \square

THEOREM 5.4. *Non-cooperative OEF ensures strategy proofness.*

PROOF. We establish the proof by examining the new allocation, denoted as X' , that occurs after someone cheats. If the efficiency of honest users decreases, the cunning user i will also be penalized due to the constraint of efficiency equality between users, i.e., $\vec{w}_i \cdot \vec{x}_i' < \vec{w}_i' \cdot \vec{x}_i = \vec{w}_k \cdot \vec{x}_k'$ where k denotes the honest user. This inequality ensures the property of being *strategy-proof*. In another scenario, where the efficiency of honest users increases, we only have to analyze the case where user i increases a small amount of acceleration rate and still does not exceed any speedup rates of others. Without loss of generality, assume user i increases his speedup rate from \vec{w}_i to \vec{w}_i' , which satisfies $\vec{w}_{i+1}' \geq \vec{w}_i' \geq \vec{w}_i$. Following Theorem 5.2, the allocation undergoes the following changes:

$$W = \begin{pmatrix} a_i & b_i \\ a_{i+1} & b_{i+1} \end{pmatrix} X = \begin{pmatrix} x_i & y_i \\ 0 & y_{i+1} \end{pmatrix} X' = \begin{pmatrix} x_i' & y_i' \\ 0 & y_{i+1}' \end{pmatrix},$$

where the bottom-left zero value in X will remain unchanged in X' , otherwise the optimal resource efficiency cannot be attained. Although there are various possible structures for the allocation matrix before and after cheating, we can employ the same method to demonstrate the satisfaction of *strategy-proofness* in all cases. Specifically, in the aforementioned scenario, when user i cheats a bit on his speedup vector, the benefits for honest users should solely

arise from changes in the x and y components (corresponding to two columns in X). Consequently, we have $y_{i+1}' > y_{i+1}$. Furthermore, let us define $x_i' = x_i - \epsilon_x$, and $y_i' = y_i - (y_{i+1}' - y_{i+1}) - \epsilon_y$, where ϵ_x and ϵ_y represent the change in allocation to benefit honest users, except for user $i + 1$. Based on these definitions, we deduce that $a_i \cdot x_i' + b_i \cdot y_i' < a_i \cdot x_i + b_i \cdot y_i$, implying the cunning user must be penalized. This completes the proof. \square

6 EVALUATION

In this section, we present the evaluation results of the OEF system. We begin by exploring the attainment of fairness properties and the enhanced resource efficiency offered by OEF throughout the entire scheduling period, considering both non-cooperative and cooperative scenarios in comparison to various baselines. To illustrate the realization of fairness properties, we conducted a small-scale experiment involving four tenants. Additionally, we employed a large-scale experiment encompassing a more extensive array of tenants and jobs to showcase the advantages in training throughput and job completion time (JCT) reduction. Furthermore, we shed light on the system overhead of OEF, illustrating its seamless integration into large-scale clusters.

6.1 Experiment Setup

6.1.1 Environment. We conducted experiments on a real cluster consisting of eight RTX 3070 GPUs, eight 3080 GPUs, and eight 3090 GPUs, where four GPUs of the same type co-locate on the same host. Without special mention, we set 5 minutes as the length of the scheduling round by default.

6.1.2 Workloads. To validate our scheme in real world, we picked several popular DL jobs from different domains. For image classification, we utilized VGG, ResNet, and DenseNet models on the CIFAR-100 dataset. In contrast, for language modeling tasks, we implemented LSTM, RNN, and Transformer models using the WikiText-2 dataset. To ensure consistency with real-world scenarios, each job was assigned a random combination of hyperparameters, including batch size and learning rate, within a reasonable range.

To more accurately mimic real-world scheduling scenarios when assessing JCT and throughput performance, we maintained cluster contention levels consistent with those observed in Microsoft's Philly trace [29].

6.1.3 Baselines. To demonstrate the superiority of OEF, we compare it to the following schedulers:

- **Gandiva_{fair}** [9]. Gandiva_{fair} applies a trading-based algorithm to guarantee *sharing-incentive* and improve the overall resource efficiency. Specifically, it conducts trading in a greedy way, i.e., always trades between shares with the greatest speedup gap. However, the second-price trading mechanism introduced in this user prevents users from obtaining the highest overall efficiency and also incentives users to lie.
- **Gavel** [8]. Gavel formulates a max-min optimization problem, which tries to maximize the throughput of the user with the least speedup. In this sense, Gavel can also provide users with *sharing-incentive*.




Figure 4: OEF penalizes lying users. User 4 exits at the 40-th minute.

In order to ensure a fair evaluation, we employ a consistent round-robin scheduling strategy for jobs within each tenant across all baselines. More precisely, scheduling priority is assigned to jobs with the longest starvation time.

6.1.4 Metrics. To measure fairness and efficiency, we employed normalized throughput as our primary performance metric. This involves normalizing the training throughput of users based on the allocation provided by the scheduler at a specific time unit, using the throughput of the same number of the slowest GPU devices as a reference. This normalization process is intended to eliminate the effect of diverse training speeds across different jobs. Furthermore, we performed ablation studies on the evaluation of throughput performance to showcase the individual contributions of the fair share evaluator and placer. We specifically designate the throughput estimate assessed by the OEF fair share evaluator as 'estimated' to demonstrate the algorithmic perspective's throughput advantage. Additionally, we label the tangible training throughput as 'actual', encompassing the throughput benefit from both algorithm design and placement scheme.

6.2 Evaluation on Fairness Properties

In this part, we present the attainment of fairness properties under OEF in both cooperative and non-cooperative environments.

6.2.1 The power of strategy-proofness. We examined the throughput across users in two scenarios: when no one cheats and when User-1 cheats, while maintaining the same speedup profile. As shown in Fig. 4(a), when no one cheats on the speedup vector, four users achieve almost identical normalized progress under the non-cooperative OEF, despite some variations due to profiling errors and context switching costs. Moreover, even after the User-4 who executes a batch of VGG11 jobs quits the cluster at the 40th minute, other three users still obtain the same throughput. In Fig. 4(b), we consider User-1 tuning LSTM jobs artificially increases his speedup rate. In this scenario, we observe that the deceptive user has been penalized, receiving less throughput than before cheating. This demonstrates the effectiveness of *strategy-proofness* under OEF, which prevents a decrease in throughput performance when dealing with shrewd users. At the same time, we also notice that the throughput of honest users improves after someone cheats. Furthermore, it also shows that the throughput disadvantage of User-1 persists even after a user quits the cluster, and cheating reduces the overall training throughput by around 10%.




Figure 5: Provision of sharing incentive and adaptation to multiple job types under OEF.

Figure 5: Provision of sharing incentive and adaptation to multiple job types under OEF.

6.2.2 Effectiveness of sharing incentive. We assessed the *sharing incentive* property of OEF in a cooperative environment by comparing the training throughput of four users when training different types of jobs under OEF. As depicted in Fig. 5(a), the fair share evaluator in OEF consistently produces higher or equal estimated throughput in comparison to the Max-Min approach. Notably, OEF demonstrates its capacity to expedite User-4 the most, achieving up to a 1.16× improvement in estimated training throughput. This acceleration is attributed to the cooperative nature of OEF, which prioritizes the training jobs of tenants with the highest speedup rate, thus maximizing the overall throughput improvement. Furthermore, the placer component in OEF introduces network contention alleviation, resulting in an additional training throughput improvement of 1.24×.

6.2.3 Different speedups within a tenant. To show the effective support for users to train different types of DL jobs under OEF, we conducted experiments on a dynamic trace, where User-1 adds another type of DL jobs on the fly. As shown in Fig. 5(b), we observe that before introducing the new job type, User-1 receives almost the same throughput as others. After introducing a new type of jobs at 40 minutes, we investigate the throughput of these two types of User-1 separately. It is clear that these two types receive almost equal throughput. Additionally, each job from User-1 obtain half the training throughput of other users.

6.2.4 Effectiveness of envy freeness. We proceed to investigate the effectiveness of *envy-freeness* under cooperative OEF. To be specific, we compared the progress obtained by each user to that generated by having resource allocation from others. As illustrated in Fig. 6, users under cooperative OEF are all provided with the most suitable allocation that yields the highest throughput, i.e., no allocation vector from other users results in higher throughput. For instance, User-4 exhibits an estimated throughput that is 1.58× greater than that achieved using the allocation assigned to User-1. To this end, it is unnecessary for users to envy others under the cooperative OEF.

6.3 Resource Efficiency

6.3.1 Throughput evaluation. We conducted an evaluation involving 20 tenants, each owning DL training jobs of the same type. This ensures a fair comparison with Gavel and Gandiva_{fair}, which do not support multiple job types within a tenant. As depicted in




Figure 6: Estimated training throughput of allocation for each user from other's perspective under cooperative OEF, which demonstrates that one wouldn't prefer the allocation of others, achieving the *envy-freeness*.




Figure 7: Training throughput improvement under non-cooperative setting.




Figure 8: Training throughput improvement under cooperative setting.

Fig. 7, the non-cooperative OEF attains efficiency levels comparable to baselines, while maintaining a *strategy-proofness* property. Through meticulous placement design in the placer, OEF enhances training throughput, achieving up to a 10% actual increase in training throughput compared to Gavel and *Gandiva_{fair}*, both of which lack optimization strategies for placement, including network contention alleviation and mechanisms to prevent excessive GPU allocation across diverse types.

In Fig. 8, the throughput advantage of cooperative OEF over other baselines is evident, primarily attributed to the effective efficiency optimization within the OEF framework. Specifically, OEF outperforms baselines by 20% in terms of estimated throughput due to the algorithm design. This significant improvement is further amplified to a 32% actual throughput increase, underscoring the impact of OEF's meticulous placement design.




Figure 9: OEF can reduce overall JCT by 17% and 19%, in contrast to *Gandiva_{fair}* and Gavel.

6.3.2 *JCT evaluation*. We conducted a three-day-long evaluation to showcase the efficacy of reducing JCT in our GPU cluster. The experiment involved jobs from 50 tenants, with each tenant averaging 20 jobs of the same type. Tenants exited the cluster upon the completion of all their jobs. As illustrated in Fig. 9, OEF surpasses its counterparts, *Gandiva_{fair}* and Gavel, in reducing job training time by 17% and 19%, respectively. This JCT advantage is attributed not only to throughput improvements but also to the advanced rounding strategy implemented in the placer. The latter enables tenants to progress jobs even when allocated GPU resources are less than their job expectations, thereby diminishing starvation time and resulting in overall JCT reduction.

6.3.3 *Straggler effect alleviation*. We performed an ablation study to demonstrate the extent to which OEF can alleviate the straggler effect. Specifically, we tracked the occurrences of cross-GPU-type placement events across different baselines, where higher-end GPU resources remain idle during periodic data synchronizations with lower-end GPUs. In comparison to *Gandiva_{fair}* and Gavel, OEF reduces the number of workers impacted by the straggler effect by 14% and 26%, respectively.

6.4 System Overhead

6.4.1 *Computation overhead*. As scalability is a major concern in large-scale cluster scheduling, we demonstrated that OEF will not block scheduling given a large cluster size. In particular, because solving the optimization problem is of the most time-consuming part under OEF, we carefully investigated its computation overhead at different cluster sizes. Specifically, we fix the number of GPU types to ten, which is sufficient for most production clusters. As shown in Fig. 10(a), we can see that cooperative OEF consumes more time than the non-cooperative version. The reason is that cooperative OEF has $O(n^2)$ constraints while the non-cooperative version has only $O(n)$ constraints, where n is the number of users. Considering that scheduling rounds are several minutes long, this scheduling overhead is negligible.

6.4.2 *Sensitivity analysis*. As profiling cannot always provide users with strictly accurate runtime information about their jobs, schedulers should be less sensitive to the profiling errors. To this end, we investigated the efficiency deviation, i.e., the gap between the throughput OEF should achieve based on the speedup profile reported by the users and the throughput OEF has actually achieved in the cluster. As shown in Fig. 10(b), even given a profiling error up to 20%, OEF only yields a deviation about 3%, demonstrating its robustness in the presence of profiling error.




Figure 10: The scalability of OEF and robustness in the presence of profiling errors.

7 RELATED WORKS

Heterogeneous DL schedulers. As for heterogeneity-aware scheduling, AlloX [7] designs an efficient scheduling algorithm based on bipartite matching to reduce the overall JCT in an offline setting. To systematically deal with the effect introduced by performance heterogeneity, Gavel [8] proposes an optimization framework to yield good efficiency or fairness. By contrast, Gandiva_{fair} focuses on fair scheduling in heterogeneous GPU clusters, and provides several fairness properties. In addition to GPU resources, several works also take other resources such as CPU and memory into consideration when improving job training performance [33, 34].

Fair schedulers. Many schedulers have been designed to improve and extend max-min fairness in the literature [14–18, 35–40]. These studies primarily focus on the single-resource-type environment, commonly applied in operating system and network-related contexts. As for multi-resource fairness, DRF [19] and its variants [21–25, 41] becomes the mainstream manner to provide fairness for tenants. However, all of these schedulers do not well fit into heterogeneous GPU scheduling setting. Themis [10] propose a *finish-time* fair scheduler for homogeneous GPU cluster, where jobs are provided *sharing incentive* in best-effort manner. Gandiva_{fair} and Gavel [8, 9] are the only two schedulers that has similar targets with OEF, with few fairness properties and non-optimal efficiency provided.

8 CONCLUSION AND REMARKS

In this paper, we have identified the inherent conflicts between resource efficiency and various fairness properties in the context of heterogeneous GPU scheduling. Based on this recognition, we design a framework OEF to explore the optimal balance between these conflicting objectives. To the best of our knowledge, OEF is the first solution capable of achieving *strategy-proofness* while utilizing interchangeable resources. Furthermore, OEF not only significantly enhances training throughput but also demonstrates strong scalability for supporting distributed DL training in large-scale clusters.

OEF can be extended to support job-level fairness. With the increasing popularity of elastic DL training [42], OEF can leverage this training paradigm to dynamically assign GPU resources to each job, while simultaneously ensuring fairness in the allocation process.

ACKNOWLEDGMENTS

We thank the anonymous reviewers, and our shepherd, Prof. Robert Birke for their helpful comments. This work is supported in part by the Science and Technology Development Fund of Macau (0024/2022/A1, 0071/2023/ITP2), the Multi-Year Research Grant of University of Macau (MYRG2022-00119-FST, MYRG-GRG2023-00019-FST-UMDF).

REFERENCES

- [1] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of CVPR*, 2017.
- [2] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, 2017.
- [3] Mohammad Javad Shafiee, Brendan Chywł, Francis Li, and Alexander Wong. Fast yolo: A fast you only look once system for real-time embedded object detection in video. *arXiv preprint arXiv:1709.05943*, 2017.
- [4] Google cloud platform. <https://cloud.google.com/gpu>, 2022-10-20.
- [5] Juncheng Gu, Mosharaf Chowdhury, Kang G Shin, Yibo Zhu, Myeongjae Jeon, Junjie Qian, Hongqiang Liu, and Chuanxiong Guo. Tiresias: A GPU cluster manager for distributed deep learning. In *Proceedings of NSDI*, 2019.
- [6] Yanghua Peng, Yixin Bao, Yangrui Chen, Chuan Wu, and Chuanxiong Guo. Optimus: An efficient dynamic resource scheduler for deep learning clusters. In *Proceedings of Eurosys*, 2018.
- [7] Tan N Le, Xiao Sun, Mosharaf Chowdhury, and Zhenhua Liu. AlloX: compute allocation in hybrid clusters. In *Proceedings of Eurosys*, 2020.
- [8] Deepak Narayanan, Keshav Santhanam, Fiodar Kazhamiaka, Amar Phanishayee, and Matei Zaharia. Heterogeneity-aware cluster scheduling policies for deep learning workloads. In *Proceedings of OSDI*, 2020.
- [9] Shubham Chaudhary, Ramachandran Ramjee, Muthian Sivathanu, Nipun Kwatra, and Srinidhi Viswanatha. Balancing efficiency and fairness in heterogeneous gpu clusters for deep learning. In *Proceedings of Eurosys*, 2020.
- [10] Kshiteej Mahajan, Arjun Balasubramanian, Arjun Singhvi, Shivaram Venkataraman, Aditya Akella, Amar Phanishayee, and Shuchi Chawla. Themis: Fair and efficient GPU cluster scheduling. In *Proceedings of NSDI*, 2020.
- [11] A. Demers, S. Keshav, and S. Shenker. Analysis and simulation of a fair queueing algorithm. In *Proceedings of ACM Sigcomm*, 1989.
- [12] Chung Laung Liu and James W Layland. Scheduling algorithms for multiprogramming in a hard-real-time environment. *Journal of the ACM (JACM)*, 1973.
- [13] Dror G Feitelson. *Workload modeling for computer systems performance evaluation*. 2015.
- [14] Proportionate progress: A notion of fairness in resource allocation. In *Proceedings of the twenty-fifth annual ACM symposium on Theory of computing*, pages 345–354, 1993.
- [15] Sanjoy K Baruah, Johannes E Gehrke, and C Greg Plaxton. Fast scheduling of periodic tasks on multiple resources. In *Proceedings of 9th International Parallel Processing Symposium*, pages 280–288. IEEE, 1995.
- [16] Dakai Zhu, Daniel Mossé, and Rami Melhem. Multiple-resource periodic scheduling problem: how much fairness is necessary? In *RTSS 2003. 24th IEEE Real-Time Systems Symposium, 2003*, pages 142–151. IEEE, 2003.
- [17] Josep M Blanquer and Banu Özden. Fair queuing for aggregated multiple links. *ACM SIGCOMM Computer Communication Review*, 31(4):189–197, 2001.
- [18] Jon Kleinberg, Yuval Rabani, and Éva Tardos. Fairness in routing and load balancing. In *40th Annual Symposium on Foundations of Computer Science (Cat. No. 99CB37039)*, pages 568–578. IEEE, 1999.
- [19] Ali Ghodsi, Matei Zaharia, Benjamin Hindman, Andy Konwinski, Scott Shenker, and Ion Stoica. Dominant resource fairness: Fair allocation of multiple resource types. In *Proceedings of NSDI*, 2011.
- [20] M. Isard, V. Prabhakaran, J. Currey, U. Wieder, K. Talwar, and A. Goldberg. Quincy: Fair scheduling for distributed computing clusters. In *Proceedings of SOSP*, 2009.
- [21] Robert Grandl, Mosharaf Chowdhury, Aditya Akella, and Ganesh Ananthanarayanan. Altruistic scheduling in multi-resource clusters. In *Proceedings of OSDI*, 2016.
- [22] Mosharaf Chowdhury, Zhenhua Liu, Ali Ghodsi, and Ion Stoica. {HUG}: {Multi-Resource} fairness for correlated and elastic demands. In *Proceedings of NSDI*, 2016.
- [23] Jalal Khamse-Ashari, Ioannis Lambadaris, George Kesidis, Bhuvan Urganakar, and Yiqiang Zhao. Per-server dominant-share fairness (ps-dsf): A multi-resource fair allocation mechanism for heterogeneous servers. In *2017 IEEE International Conference on Communications (ICC)*, 2017.
- [24] Wei Wang, Ben Liang, and Baochun Li. Multi-resource fair allocation in heterogeneous cloud computing systems. *IEEE Transactions on Parallel and Distributed Systems*, 26(10):2822–2835, 2014.
- [25] Wei Wang, Baochun Li, Ben Liang, and Jun Li. Multi-resource fair sharing for datacenter jobs with placement constraints. In *Proceedings of SC*, 2016.

- [26] Jeffrey Jaffe. Bottleneck flow control. *IEEE Transactions on Communications*, 1981.
- [27] Qizhen Weng, Wencong Xiao, Yinghao Yu, Wei Wang, Cheng Wang, Jian He, and Yong Li. Mlaas in the wild: Workload analysis and scheduling in large-scale heterogeneous GPU clusters. In *Proceedings of NSDI*, 2022.
- [28] Qinghao Hu, Peng Sun, Shengen Yan, Yonggang Wen, and Tianwei Zhang. Characterization and prediction of deep learning workloads in large-scale gpu data-centers. In *Proceedings of SC*, 2021.
- [29] Myeongjae Jeon, Shivaram Venkataraman, Amar Phanishayee, Junjie Qian, Wencong Xiao, and Fan Yang. Analysis of large-scale multi-tenant GPU clusters for DNN training workloads. In *Proceedings of ATC*, 2019.
- [30] Lawrence M Ausubel, Paul Milgrom, et al. The lovely but lonely vickrey auction. *Combinatorial auctions*, 2006.
- [31] Wencong Xiao, Shiru Ren, Yong Li, Yang Zhang, Pengyang Hou, Zhi Li, Yihui Feng, Wei Lin, and Yangqing Jia. Antman: Dynamic scaling on GPU clusters for deep learning. In *Proceedings of OSDI*, 2020.
- [32] Lester E. Dubins. On extreme points of convex sets. *Journal of mathematical analysis and applications*, 1962.
- [33] Jayashree Mohan, Amar Phanishayee, Janardhan Kulkarni, and Vijay Chidambaram. Looking beyond {GPUs} for {DNN} scheduling on {Multi-Tenant} clusters. In *Proceedings of OSDI*, 2022.
- [34] Xiao Sun, Tan N Le, Mosharaf Chowdhury, and Zhenhua Liu. Fair allocation of heterogeneous and interchangeable resources. *ACM SIGMETRICS Performance Evaluation Review*, 2019.
- [35] Alan Demers, Srinivasan Keshav, and Scott Shenker. Analysis and simulation of a fair queueing algorithm. *ACM SIGCOMM Computer Communication Review*, 1989.
- [36] Abhay K Parekh and Robert G Gallager. A generalized processor sharing approach to flow control in integrated services networks-the single node case. In *Proceedings of INFOCOM*, 1992.
- [37] Hui Zhang and Jon CR Bennett. Wf2q: worst-case fair weighted fair queueing. In *Proceedings of INFOCOM*, 1996.
- [38] Pawan Goyal, Harrick M Vin, and Haichen Chen. Start-time fair queueing: A scheduling algorithm for integrated services packet switching networks. In *Proceedings of SIGCOMM*, 1996.
- [39] Madhavapeddi Shreedhar and George Varghese. Efficient fair queueing using deficit round robin. In *Proceedings of SIGCOMM*, 1995.
- [40] Ion Stoica, Hui Zhang, and TS Eugene Ng. A hierarchical fair service curve algorithm for link-sharing, real-time and priority services. 1997.
- [41] Carlee Joe-Wong, Soumya Sen, Tian Lan, and Mung Chiang. Multiresource allocation: Fairness–efficiency tradeoffs in a unifying framework. *IEEE/ACM Transactions on Networking*, 2013.
- [42] Changho Hwang, Taehyun Kim, Sunghyun Kim, Jinwoo Shin, and KyoungSoo Park. Elastic resource sharing for distributed deep learning. In *Proceedings of NSDI*, 2021.