

Checkpoint Merging via Bayesian Optimization in LLM Pretraining

Deyuan Liu¹, Zecheng Wang¹, Bingning Wang², Weipeng Chen²,
Chunshan Li¹, Zhiying Tu¹, Dianhui Chu¹, Bo Li³, Dianbo Sui^{1✉*}

¹ Harbin Institute of Technology

² Baichuan Inc

³ Peking University

suidianbo@hit.edu.cn

Abstract

The rapid proliferation of large language models (LLMs) such as GPT-4 and Gemini underscores the intense demand for resources during their training processes, posing significant challenges due to substantial computational and environmental costs. To alleviate this issue, we propose checkpoint merging in pretraining LLM. This method utilizes LLM checkpoints with shared training trajectories, and is rooted in an extensive search space exploration for the best merging weight via Bayesian optimization. Through various experiments, we demonstrate that: (1) Our proposed methodology exhibits the capacity to augment pretraining, presenting an opportunity akin to obtaining substantial benefits at minimal cost; (2) Our proposed methodology, despite requiring a given held-out dataset, still demonstrates robust generalization capabilities across diverse domains, a pivotal aspect in pretraining.

1 Introduction

With the rapid development of LLMs, such as GPT-3 (OpenAI, 2023), GPT-4 (OpenAI et al., 2023), PaLM (Chowdhery et al., 2023) and Gemini (Team et al., 2023), which boasts tens to hundreds of billions of parameters, the demand for new LLMs and the research aimed at enhancing their capabilities have significantly increased. But we should note that the training requirements for these LLMs are substantial, not only in terms of computational resources, human resources, and capital resources, but also regarding energy consumption and environmental impact. For instance, training the LLaMA2 70B model with 2T tokens necessitates 1,720,320 GPU hours (Touvron et al., 2023), and the development of a transformer with 213 million parameters through neural architecture search can lead to environmental burdens equivalent to the lifetime

CO₂ emissions of five cars over their entire lifespans (Strubell et al., 2019; Faiz et al., 2023). Consequently, reducing consumption and costs during the pretraining phase has emerged as a key challenge in this field.

In response to this challenge, researchers have adopted various strategies in LLM pretraining, including mixed-precision training (Shoeybi et al., 2019), zero-redundancy optimizer (Rajbhandari et al., 2020), continuous retraining (Qin et al., 2022), pipeline parallelism (Liu et al., 2023) and depth up-scaling methods (Kim et al., 2023). Although these approaches contribute to efficient pretraining and cost reduction, they primarily focus on model architecture or optimization processes, rather than directly reducing resource consumption in the pretraining phase (Hou et al., 2022).

Unlike these studies, we focus on the model merging strategy, a classic topic in machine learning (Granger, 1989; Utans, 1996; Chen et al., 2017; Wortsman et al., 2022; Sanyal et al., 2023; Singh and Jaggi, 2023), to enhance LLM pretraining in this paper. In particular, we employ checkpoints saved during pretraining and average these checkpoint parameters to improve pretraining without requiring substantial resources, since merged checkpoints can reduce the variance of the combined output relative to the output of the individual checkpoint while not increasing the bias (Utans, 1996).

However, conducting checkpoint merging is not trivial in pretraining, because different local minima may be found in averaging parameters (Utans, 1996; Chen et al., 2017). Therefore it is important to investigate the basic characters of checkpoint merging and wisely determine the merging weight.

To this end, we make the following effort: (1) we conduct some pilot experiments to explore the characters of checkpoint merging; (2) Based on the findings in the pilot experiments, we propose a method rooted in Bayesian optimization to find the optimal or near-optimal merging weight. In detail,

*Dianbo Sui is the corresponding author.

we first explore three research questions: “Which checkpoints in the pretraining trajectory should be merged?”, “How many checkpoints should be merged?” and “How to merge checkpoint?” via various pilot experiments. Then, based on findings in pilot experiments, we leverage Bayesian optimization to optimize the expensive, black-box, and derivative-free objective function of checkpoint merging, and determine the checkpoint merging weight.

Through various experiments, we mainly find that: (1) Our proposed approach has the potential to enhance pretraining, offering nearly a free lunch; (2) Besides superior performance, the merged soup¹, determined by a specific held-out dataset same as Wortsman et al. (2022); Matena and Raffel (2022), still exhibit a strong generalization capability across various domains, a crucial aspect in pretraining.

In summary, the contribution of this paper is threefold: (1) We propose merging checkpoints in the pretraining trajectory to reduce pretraining costs, offering nearly a free lunch. (2) To find the optimal merging weight, we leverage Bayesian optimization, which excels at optimizing expensive black-box derivative-free objective functions. (3) Through various experiments, we denote our method exhibits superior performance and the newly merged checkpoint maintains strong generalization across different domains.

2 Pilot Experiments

This section presents phenomena observed during our pilot experiments on checkpoint merging. Specifically, we mainly explore the following three research questions: **RQ1:** Which checkpoints in the pretraining trajectory should be merged? **RQ2:** How many checkpoints should be merged? **RQ3:** How to merge checkpoints?

2.1 Experiment Setup

In the pilot experiments, we use 11 checkpoints of Baichuan2 (Yang et al., 2023) at various stages of pretraining from 200 billion tokens up to the full 2.6 trillion tokens. Meanwhile, we select two representative benchmark datasets as the tested: C-Eval (Huang et al., 2023), a comprehensive evaluation benchmark comprising over 10k multiple-choice questions spanning 52 diverse disciplines

¹According to Wortsman et al. (2022), the merged result is called “soup”.




Figure 1: The performance of conducting pairwise checkpoint merging via greedy soup in C-Eval.

and four difficulty levels; CMMLU (Li et al., 2023), a general Chinese evaluation benchmark designed to assess the knowledge and reasoning abilities of law masters.

2.2 Which Checkpoints in the Pretraining Trajectory Should be Merged?

To answer the RQ1, we examine all possible pairwise merging scenarios, totaling 55 combinations (C_{11}^2), and evaluated their performance on the C-Eval and CMMLU test sets using the greedy soup strategy (Wortsman et al., 2022), where checkpoints are sequentially added to the soup if they improve accuracy on the development data.

The results on C-Eval are presented in the Figure 1. From the figure, we can find that: (1) In the C-Eval dataset, except for the merging of Baichuan2-220B with Baichuan2-440B and Baichuan2-440B with Baichuan2-660B, **merging two checkpoints from adjacent training stages generally yields better performance compared with individual checkpoint**, e.g., merging Baichuan2-1980B with Baichuan2-2200B can achieve a 56.65% accuracy, but the Baichuan2-2200B can only achieve a 54.98% accuracy. Moreover, merging Baichuan2-1980B with Baichuan2-2200B (achieving a 56.65% accuracy) can exceed the final checkpoint (Baichuan2-2420B, achieving a 54.82%) a lot, improving 1.83% in test accuracy. Meanwhile, the same trend is also evident in the CMMLU dataset, presented in the Appendix. (2) **Merging distant checkpoints can result in great performance decline**, e.g., in the C-Eval dataset,




Figure 2: (a) The result on merging Baichuan2-1540B with Baichuan2-1760B via the merging weight uniformly sampled from [0, 1]. (b) The result of merging Baichuan2-2200B with Baichuan2-2420B via the merging weight uniformly sampled from [0, 1].




Figure 3: Assessing the accuracy disparities in C-Eval from merging two adjacent checkpoints, three adjacent checkpoints and four adjacent checkpoints by using greedy soup.

merging Baichuan2-220B with Baichuan2-2200B can only achieve a 25.26% accuracy, which is near to the performance of the undertrained Baichuan2-220B (23.89%).

2.3 How Many Checkpoints Should be Merged?

Based on the first pilot experiment, we further conducted some experiments to investigate the effect on performance while combining varying numbers of checkpoints in the pre-trained phase. Specifically, using the C-Eval dataset as the testbed, we leverage the greedy soup strategy (Wortsman et al., 2022) to merge adjacent three or four checkpoints across different pretraining stages.

The experimental results are present in the Fig-

ure 3. From the figure, we can find that: **Compared with pairwise merging, merging three or four checkpoints does not show a significant advantage in performance.** For example, when merging two models, such as merging Baichuan2-1320B with Baichuan2-1540B, performance notably increases to 53.06% (+2.14), however, merging three checkpoints (Baichuan2-1100B, Baichuan2-1320B, and Baichuan2-1540B) leads to a performance increase to 51.76% (+0.84), and merging four checkpoints (Baichuan2-880B, Baichuan2-1100B, Baichuan2-1320B, and Baichuan2-1540B) resulted in a further reduced performance of 51.01% (+0.09).

2.4 How to Merge Checkpoints?

In checkpoint merging, the most critical question lies in determining the proportion (merging weight) to combine checkpoints in the LLM parameter space. To probe this question, we select merging representative Baichuan2-1540B with Baichuan2-1760B and Baichuan2-2200B with Baichuan2-2420B in the C-Eval dataset, meanwhile, uniformly sample 100 points in the entire merging weight distribution space ([0, 1]) for in-depth testing.

The experimental results are present in the Figure 2. From the figure, we can find that: (1) As shown in Figure 2(a), there is a huge performance gap between Baichuan2-1540B and Baichuan2-1760B. In this case, we observe a certain monotonic trend between the performance of merged

soup and merging weight. **as higher merging weight is assigned to the checkpoint with better performance, the performance of the merged soup gradually improves.** Besides, there are 13% of weights showing improvement beyond the superior base model (Baichuan2-1760B, which can achieve higher accuracy compared to Baichuan2-1540B).(2) In the Figure 2(b), due to reaching the late stage of pretraining, Baichuan2-2200B and Baichuan2-2420B show the similar performance. The monotonic trend shown in merging Baichuan2-1540B and Baichuan2-1760B disappears. Meanwhile, **76% merging weights have the potential to elevate the merged soup beyond the superior checkpoint.** To further verify this finding, we also conduct the same experiment on merging DeepSeek-1800B and DeepSeek-2000B, a 7B LLM trained by DeepSeek (DeepSeek-AI et al., 2024). We find that the experimental results are consistent with that on Baichuan 2, shown in the Appendix.

3 Method

In this section, we first illustrate the formulation of checkpoint merging in subsection §3.1. Then, we introduce the implementation of our method in subsection §3.2, which can effectively and efficiently determine the merging weight

3.1 Preliminary: Checkpoint Merging

When conducting LLM pretraining, we have already saved multiple checkpoints at the time t , denoted as $\{\Theta_1, \Theta_2, \dots, \Theta_t\}$. The linear combination of these multiple checkpoints in parameter space is referred to as ‘‘Checkpoint Soup’’ and can be represented as:

$$\tilde{\Theta}_t = \sum_{i=1}^t \lambda_i \Theta_i \quad \text{s.t.} \quad \sum_{i=1}^t \lambda_i = 1 \quad (1)$$

where $\lambda_i \in \mathbb{R}$ represents merging weight. According to the key findings in pilot experiments, in this paper, we only focus on pairwise merging, therefore, the Equation 1 can be reformulated as:

$$\tilde{\Theta}_t = \lambda_t \Theta_t + (1 - \lambda_t) \Theta_{t-1} \quad (2)$$

As shown in pilot experiments, the performance of $\tilde{\Theta}_t$ can surpass that of Θ_t when an appropriate λ_t is assigned. Therefore, for each checkpoint merging iteration, the primary challenge is to find the optimal or near-optimal merging weight λ_t .

3.2 Checkpoint Merging via BayesOpt

To find the optimal or near-optimal merging weight, we resort to Bayesian optimization (short for ‘‘BayesOpt’’). BayesOpt is an effective global optimization strategy widely used to find optimal solutions for functions that are costly or difficult to evaluate directly. BayesOpt consists of three main components: an objective function to be optimized, a Bayesian statistical model for modeling the objective function, and an acquisition function for deciding where to sample next (Frazier, 2018).

Objective Function in Checkpoint Merging. The objective function to be optimized in checkpoint merging during the pretraining phase can be formulated as

$$\max_{\lambda_t \in [\alpha, 1]} f(\lambda_t | \Theta_t, \Theta_{t-1}, \text{LLM}, D) \quad (3)$$

where given the LLM equipped with the parameter $\tilde{\Theta}_t$ (defined in the Equation 2) and a certain held out labeled dataset D , the objective function $f(\cdot)$ can project the merging weight λ_t to the overall performance of the LLM in D , e.g., F1 score in the named entity recognition task and BLEU score in the translation task. Besides, to reduce the search space, the range of the merging weight is controlled by a hyperparameter $\alpha \in [0, 1)$.

Gaussian Process: A Bayesian statistical model.

To model the object function in Equation 3, Gaussian process (GP) regression (Seeger, 2004) is utilized. In detail, given a finite collection of merging weight $\lambda_t^{1:k} = \lambda_t^1, \dots, \lambda_t^k$, it is able to collect the object function’s values at these points together into a vector $f(\lambda_t^{1:k}) = [f(\lambda_t^1), \dots, f(\lambda_t^k)] \in \mathbb{R}^k$. Note that, we omit the condition in $f(\cdot)$ for convenience. In GP, this prior distribution is supposed to be multivariate normal, with a particular mean vector and covariance matrix, which is denoted as

$$f(\lambda_t^{1:k}) \sim \text{Normal} \left(\mu_0 \left(\lambda_t^{1:k} \right), \Sigma_0 \left(\lambda_t^{1:k}, \lambda_t^{1:k} \right) \right) \quad (4)$$

where μ_0 and Σ_0 are mean function and covariance function with learnable parameters, which can be estimated by maximum likelihood estimation. $\mu_0 \left(\lambda_t^{1:k} \right) = [\mu_0 \left(\lambda_t^1 \right), \dots, \mu_0 \left(\lambda_t^k \right)] \in \mathbb{R}^k$ and $\Sigma_0 \left(\lambda_t^{1:k}, \lambda_t^{1:k} \right) = [\Sigma_0 \left(\lambda_t^1, \lambda_t^1 \right), \dots, \Sigma_0 \left(\lambda_t^1, \lambda_t^k \right); \dots; \Sigma_0 \left(\lambda_t^k, \lambda_t^1 \right), \dots, \Sigma_0 \left(\lambda_t^k, \lambda_t^k \right)] \in \mathbb{R}^{k \times k}$.

Using Bayes’ rule, we have a posterior probability distribution:

$$f(\lambda_t) | f \left(\lambda_t^{1:k} \right) \sim \text{Normal} \left(\mu_k \left(\lambda_t \right), \sigma_k^2 \left(\lambda_t \right) \right) \quad (5)$$

Algorithm 1 Checkpoint Merging Via BayesOpt

- 1: **for** $k = 1$ to N **do**
 - 2: Fit the parameters of the Gaussian process given observation history $(\lambda_t^{1:k}, f(\lambda_t^{1:k}))$
 - 3: Compute the acquisition function based on the posterior distribution (Equation 5).
 - 4: Evaluate the maximizer λ_t^{k+1} of the acquisition function.
 - 5: Conducting checkpoint merging $\tilde{\Theta}_t^{k+1} = \lambda_t^{k+1}\Theta_t + (1 - \lambda_t^{k+1})\Theta_{t-1}$
 - 6: Using $\tilde{\Theta}_t^{k+1}$ to obtain $f(\lambda_t^{k+1})$ on the held out dataset D
 - 7: Append the new observation pair $(\lambda_t^{k+1}, f(\lambda_t^{k+1}))$ to the observation history.
-

$$\begin{aligned} \mu_k(\lambda_t) = & \Sigma_0 \left(\lambda_t, \lambda_t^{1:k} \right) \Sigma_0^{-1} \left(\lambda_t^{1:k}, \lambda_t^{1:k} \right) \\ & \cdot \left(f \left(\lambda_t^{1:k} \right) - \mu_0 \left(\lambda_t^{1:k} \right) \right) + \mu_0(\lambda_t) \end{aligned} \quad (6)$$

$$\begin{aligned} \sigma_k^2(\lambda_t) = & \Sigma_0(\lambda_t, \lambda_t) - \Sigma_0 \left(\lambda_t, \lambda_t^{1:k} \right) \\ & \cdot \Sigma_0^{-1} \left(\lambda_t^{1:k}, \lambda_t^{1:k} \right) \Sigma_0 \left(\lambda_t^{1:k}, \lambda_t \right) \end{aligned} \quad (7)$$

From the above equations, we find that: (1) The posterior mean $\mu_n(\lambda_t)$ is a weighted average between the prior $\mu_0(\lambda_t)$ and an estimate based on the data $f(\lambda_t^{1:k})$. (2) The posterior variance $\sigma_n^2(\lambda_t)$ is equal to the prior covariance $\Sigma_0(\lambda_t, \lambda_t)$ less a term that corresponds to the variance removed by observing $f(\lambda_t^{1:k})$.

Acquisition Functions. Suppose we have $\lambda_t^{1:k}$ and $f(\lambda_t^{1:k})$, and currently we find the best solution is f_*^k , we need to use the acquisition function to determine where to sample new merging weight (next evaluation point). The acquisition function serves as a cheap-to-evaluate utility function to guide the sampling decisions.

One acquisition function used in this paper is Expected Improvement (EI) (Moćkus, 1975; Jones et al., 1998). In detail, we want to choose λ_t^{k+1} so that the performance of the LLM($\cdot|\tilde{\Theta}_t$) can be improved enhanced. Since $f(\lambda_t|\Theta_t, \Theta_{t-1}, \text{LLM}, D)$ is unknown until after the pass all data in D through the LLM, what we can do is to take the expected value of the improvement and choose λ_t^{k+1} to maximize it. We define the expected improvement as:

$$\text{EI}_k(\lambda_t) := E_k[\max(f(\lambda_t) - f_*^k, 0)] \quad (8)$$

Here, $E_k[\cdot]$ indicates the expectation taken under the posterior distribution (present in the Equation 5) given observations of $f(\cdot)$ at $\lambda_t^1, \dots, \lambda_t^k$. Then we evaluate the merging weight at the point with the largest expected improvement,

$$\lambda_t^{k+1} = \operatorname{argmax} \text{EI}_k(\lambda_t) \quad (9)$$

Another acquisition function used in this paper is Upper Confidence Bound (UCB) (Srinivas et al., 2009). Compared with the EI, the UCB tries to guide the search from an optimistic perspective, which is defined as:

$$\text{UCB} := \mu_k(\lambda_t) + \beta \cdot \sigma_k(\lambda_t) \quad (10)$$

where $\beta > 0$ is a learnable parameter to navigate the exploitation-exploration trade-off. Considering the objective function $f(\cdot)$ can be complex and non-convex, it may be the case that no single acquisition function will perform the best over the entire optimization. Therefore, a mixed strategy in which the acquisition function samples from a pool at each iteration might work better than any single acquisition (Hoffman et al., 2011).

Note that, the proposed checkpoint merging via BayesOpt is not limited to pairwise checkpoint merging, but can also handle merging multiple checkpoints in the same way as pairwise merging. The overall procedure of checkpoint merging via BayesOpt is illustrated in Algorithm 1.

4 Experiments

4.1 Experimental Setups

Datasets: Besides C-Eval (Huang et al., 2023) and CMMLU (Li et al., 2023) used in the pilot experiments, we further select three benchmark datasets as the testbed: MMLU (Hendrycks et al., 2021), a large-scale multi-task language understanding benchmark consisting of multiple-choice questions on academic subjects; and GSM8K (Cobbe et al., 2021), a well-known mathematics-focused evaluation benchmark.

Baseline Methods: We compared our merging method with the following strong baselines: (1) **Checkpoints before Merging** To better showcase the performance changes after model merging, we report the performance of checkpoints before merging. (2) **Uniform Soup** (Wortsman et al., 2022)

Dataset	Baichuan2-1980B	Baichuan2-2200B	Uniform Soup	Greedy Soup	Fisher	RegMean	Ours
C-Eval	55.63	54.98	53.00	55.63	55.73	55.21	56.17(+0.44)
CMMLU	55.68	56.29	54.20	56.29	56.13	55.21	56.88(+0.59)
MMLU	54.00	51.27	54.30	55.39	54.25	54.77	55.44(+0.05)
GSM8K	23.28	21.99	23.96	23.28	20.92	23.73	24.02(+0.29)
Average	47.15	46.13	46.37	47.65	46.76	47.23	48.13(+0.48)

Dataset	Baichuan2-2200B	Baichuan2-2420B	Uniform Soup	Greedy Soup	Fisher	RegMean	Ours
C-Eval	54.98	54.82	54.93	55.64	54.44	54.55	56.23(+0.59)
CMMLU	56.29	56.78	56.71	56.78	56.62	56.46	56.97(+0.19)
MMLU	51.27	53.97	54.62	54.82	54.16	54.77	54.56(-0.26)
GSM8K	19.64	21.00	20.92	21.92	22.44	23.88	24.32(+0.44)
Average	45.55	46.64	46.80	47.29	46.92	47.42	48.02(+0.50)

Table 1: The results of merging Baichuan2-1980B with Baichuan2-2200B and merging Baichuan2-2200B with Baichuan2-2420B across various benchmark datasets.

Dataset	DeepSeek-1400B	DeepSeek-1600B	Uniform Soup	Greedy Soup	Fisher	RegMean	Ours
C-Eval	38.80	39.40	41.26	40.70	40.24	39.55	41.79(+0.55)
CMMLU	40.27	40.94	42.18	42.25	41.76	41.80	42.55(+0.30)
MMLU	41.94	42.60	43.87	43.88	43.95	43.27	43.85(-0.03)
GSM8K	11.30	13.27	14.18	14.03	15.39	15.04	15.70(+0.41)
Average	33.08	34.05	35.37	35.22	35.34	34.92	35.97(+0.53)

Dataset	DeepSeek-1800B	DeepSeek-2000B	Uniform Soup	Greedy Soup	Fisher	RegMean	Ours
C-Eval	43.05	44.36	44.61	44.70	44.81	43.95	45.82(+1.01)
CMMLU	45.31	46.82	46.84	46.82	46.49	47.12	47.15(+0.03)
MMLU	47.68	49.29	49.02	49.29	48.73	49.07	49.43(+0.14)
GSM8K	16.60	18.88	17.82	18.88	18.73	18.56	19.04(+0.22)
Average	38.16	39.84	39.57	39.92	39.69	39.68	40.36(+0.44)

Table 2: The results of merging DeepSeek-1400B with DeepSeek-1600B and merging DeepSeek-1800B with DeepSeek-2000B across various benchmark datasets.

implements an equitable averaging of models, disregarding individual performance metrics to ensure uniform contribution. Note that LAWA (Sanyal et al., 2023) is also a particular case of uniform soup. (3) **Greedy Soup** (Wortsman et al., 2022), conversely, selectively incorporates checkpoints based on their demonstrated ability to augment model accuracy, adopting only those that yield tangible performance improvements in the held-out dataset. (4) **Fisher Weighted Averaging** (Matena and Raffel, 2022) (short for “Fisher”) strategically utilizes Fisher information to allocate weights to model parameters, thereby maximizing the ensemble’s joint posterior likelihood for superior efficiency. (5) **RegMean** (Jin et al., 2022) applies regression techniques to reduce prediction variance across models, thereby bolstering the ensemble’s overall robustness and performance.

LLM Checkpoints Besides checkpoints of pre-




Figure 4: This result of comparing our method with the checkpoint with superior performance before merging.

training Baichuan2-7B (Yang et al., 2023), we also leverage intermediate checkpoints of training Deepseek 7B (DeepSeek-AI et al., 2024).

4.2 Main Results

Figure 4 illustrates the performance improvement of our method over the best base checkpoint performance (short for “BestCKPT”) value on the C-Eval dataset during the mid to late stages of pretraining. Meanwhile, in Table 1, we present two merging combinations that are characterized by notable score improvements. For example, the merging of the Baichuan2-1980B and Baichuan2-2200B achieves a 0.59% improvement on the CMMLU dataset compared with the Baichuan2-2200B. Similarly, the merging of the Baichuan-2200B and Baichuan2-2420B demonstrates significant gains, achieving a 0.57% improvement on the C-Eval dataset compared to the Baichuan2-2420B.

In addition to surpassing baseline checkpoints, our approach also significantly outperforms other merging baselines across various datasets. On the CMMLU dataset, applying our proposed method to merge the Baichuan2-1980B with the Baichuan2-2200B can surpass Uniform Soup, Greedy Soup, Fisher Weighted Averaging, and RegMean by 2.68%, 0.59%, 0.75%, and 1.67%, respectively. A similar trend is also observed on the C-Eval dataset, with our method outperforming others by substantial margins.

To further validate our proposed method, we apply it to the DeepSeek 7B. Results are shown in Table 2, testing the merging of the DeepSeek-1800B with DeepSeek-2000B on the C-Eval dataset, achieving a score of 45.82, thereby outperforming Uniform Soup, Greedy Soup, Fisher Weighted Averaging, and RegMean by 1.34%, 1.24%, 0.57%, and 1.87%, respectively. These results not only underscore the robustness and applicability of our proposed method but also its effectiveness in enhancing model performance across different pre-training stages and models.

4.3 Can the Merged Soup Generalize to Unseen Domains?

Since the merging weight is determined in a certain held-out labeled dataset D (Equation 3), therefore, it is a very important question needs to be answered: “Can the merged soup perform well in unseen datasets?” To answer this question, we investigate the out-of-domain generalization capability of various merged soups. In our experiment, we use the C-Eval to determine the merging weight, and test merged soups on CMMLU, MMLU and GSM8K.

Dataset	Greedy Soup (IND/OOD)	Fisher (IND/OOD)	Ours (IND/OOD)
CMMLU	56.78/56.78	56.62/56.72	56.97/56.91
MMLU	54.82/54.54	54.16/54.54	54.56/55.29
GSM8K	21.92/23.65	22.44/24.34	24.32/24.40
$\Delta(\downarrow)$	2.01	2.38	1.05

Table 3: The results of testing the merged soups on the out-of-domain dataset. We use the C-Eval dataset to determine the merging weight and test the merged soups on the out-of-domain dataset, CMMLU, MMLU and GSM8K. “IND” and “OOD” denote “In-domain” and “Out-Of-Doamin”, respectively. Δ denotes the total difference in performance between IND and OOD on this three out-of-domain datasets.




Figure 5: The results of varying merging weight searching space size on merging Baichuan2-1760B and Baichuan2-1980B, were tested on the C-Eval dataset.

The results are displayed in the Table 3. From the table, we can find that: (1) Although determining the merging weight in a Chinese dataset, merged soups obtained by various merging methods consistently perform well in English datasets, like MMLU and GSM8K, which means merging pretraining checkpoints in the parameter space does not compromise the generalization of checkpoints. (2) Compared with Greedy Soup and Fisher Weighted Averaging, our proposed method presents a better result, since the difference in performance between the in-domain setting (determining weight and testing the merged soup using the data from the same domain) and out-of-domain setting is the smallest, indicating a high probability that the merging weight found on IND setting and OOD setting may be the same.

C-Eval	1/4	1/2	3/4	1
Ours	56.61	56.08	55.80	56.23

Table 4: "This is the result of studying the variation in the size of the held-out dataset after merging on the 2200B and 2420B checkpoints.

5 Discussion

5.1 The Impact of Varying the Held-out Dataset Size on Checkpoint Merging

Same as Wortsman et al. (2022); Matena and Raffel (2022), our proposed need a training set to determine the merging weight. Therefore, it is worth investigating the impact of variations in the held-out dataset size on the result. To this end, we extract some fractions of the C-Eval validation data as the held-out dataset, and test merging Baichuan2-2200B and Baichuan2-2420B.

The result is presented in Table 4. From the result, we find that the size of the held-out dataset appears to exert minimal influence on the efficacy of our method, which maintains commendable performance even when the available dataset is limited. We conjecture the reason is that the impact of dataset size on our proposed method pertains primarily to the assessment phase, therefore, a small dataset can still provide sufficient information to discern the quality of the weight allocation. With the C-Eval dataset, for instance, extracting a fraction of the data can still serve to evaluate the model’s capabilities effectively.

5.2 The Impact of Varying Merging Weight Searching Space Size

As shown in Equation 3, the hyperparameter α controls the merging weight searching space. To investigate the impact of this hyperparameter, we conduct some experiments. The experiment results are shown in the Figure 7. It can be observed that setting α to 0.5 or to 0.7 can achieve relatively good results, whereas setting α to 0.9 can result in a noticeable decline in accuracy. Digging deeper, we find that setting α to 0.5 or to 0.7 can both converge on the optimal merging weight within the range of (0.87, 0.89). Besides, in our experience, we also find that when the performance gap between checkpoints is apparent, a narrower searching space is beneficial, predominantly favoring the stronger checkpoint. In contrast, when checkpoints before merging can achieve balanced performance,

a broader searching space is preferable.

6 Related Work

Model Merging in LLM: Model merging focuses on the unification of several models into one coherent entity, aiming to harness the collective strengths and mitigate the individual weaknesses of each model (Jolicoeur-Martineau et al., 2023), and has recently emerged as a significant trend in the research of Large Language Models. In detail, Wortsman et al. (2022) proposes model soup to improve accuracy without increasing inference time by averaging weights of multiple fine-tuned models. Jin et al. (2022); Yu et al. (2024); Wan et al. (2024) investigate the problem of merging individual LM fine-tuned on different datasets to obtain a single model that performs well both across all dataset domains or obtain new capabilities. Ramé et al. (2024) proposes using model merging to obtain a reliable and robust reward model in RLHF. However, we find that conducting model merging during pretraining receives little attention.

Bayesian Optimization in NLP: Bayesian Optimization (BayesOpt) can efficiently optimize objective functions that take a long time to evaluate and are widely applied in NLP. In detail, Yogatama et al. (2015) leverage BayesOpt for Text Representations. Ruder and Plank (2017) learn data selection measures using BayesOpt in transfer learning for sentiment analysis and parsing. Simpson et al. (2020) proposes using BayesOpt for community QA and summarization, demonstrating its superiority in tasks requiring nuanced feedback interpretation. Besides, Brochu et al. (2010); Liaw et al. (2018) find that Gaussian process preference learning enables rapid, efficient inference, making it suitable for interactive applications requiring quick user feedback processing. In this paper, unlike previous work, we use BayesOpt to obtain the merging weight for checkpoint merging in LLM pretraining.

7 Conclusion

In this paper, to alleviate the huge computational cost of pretraining LLM, we propose merging checkpoints in the pretraining trajectory. Specifically, we first conduct some pilot experiments to explore the characters of checkpoint merging. Then, based on the findings in the pilot experiments, we propose a method rooted in Bayesian optimization to find the optimal or near-optimal merging weight. Through various experiments, we find that: our

proposed approach has the potential to enhance pretraining, offering nearly a free lunch. Besides superior performance, the merged result still exhibits a strong generalization capability across various domains, which means our proposed method does not compromise the generalization of pretraining checkpoints.

Limitations

The limitations of our work are presented as follows: First, the underlying mechanisms of checkpoint merging remain opaque. We cannot precisely delineate the knowledge encapsulated within two checkpoints or determine which specific weight components are pivotal. The lack of clarity extends to the decision of which parts of the weights should be merged. Second, the Bayesian Optimization approach, employing the Gaussian process, necessitates evaluating performance in each iteration on a held-out set to adjust the optimal merging weight. Consequently, using Gaussian processes for optimal merging weight search is more resource-intensive compared to merging methods like uniform soup. Third, in our experiments, we only use checkpoints from Baichuan2 7B and DeepSeek 7B, and we also notice that some researchers or projects, like [Groeneveld et al. \(2024\)](#) (OLMo) and [Biderman et al. \(2023\)](#) (Pythia), also release intermediate checkpoints when pretraining their LLMs.

These considerations highlight that while our method shows promising direction, it does so with a recognition of its inherent limitations and the need for further refinement. Our ultimate goal is to illuminate the “black box” of checkpoint merging, providing a clearer understanding of the intricate dynamics at play and paving the way for more resource-efficient optimization strategies in LLM pretraining.

References

- Stella Biderman, Hailey Schoelkopf, Quentin Anthony, Herbie Bradley, Kyle O’Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, USVSN Sai Prashanth, Edward Raff, Aviya Skowron, Lintang Sutawika, and Oskar van der Wal. 2023. [Pythia: A suite for analyzing large language models across training and scaling](#).
- Eric Brochu, Vlad M Cora, and Nando De Freitas. 2010. A tutorial on bayesian optimization of expensive cost functions, with application to active user modeling and hierarchical reinforcement learning. *arXiv preprint arXiv:1012.2599*.
- Hugh Chen, Scott Lundberg, and Su-In Lee. 2017. Checkpoint ensembles: Ensemble methods from a single training process. *arXiv preprint arXiv:1710.03282*.
- Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. 2023. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1–113.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. [Training verifiers to solve math word problems](#).
- DeepSeek-AI, :, Xiao Bi, Deli Chen, Guanting Chen, Shanhuang Chen, Damai Dai, Chengqi Deng, Honghui Ding, Kai Dong, Qiusi Du, Zhe Fu, Huazuo Gao, Kaige Gao, Wenjun Gao, Ruiqi Ge, Kang Guan, Daya Guo, Jianzhong Guo, Guangbo Hao, Zhewen Hao, Ying He, Wenjie Hu, Panpan Huang, Erhang Li, Guowei Li, Jiashi Li, Yao Li, Y. K. Li, Wenfeng Liang, Fangyun Lin, A. X. Liu, Bo Liu, Wen Liu, Xiaodong Liu, Xin Liu, Yiyuan Liu, Haoyu Lu, Shanghao Lu, Fuli Luo, Shirong Ma, Xiaotao Nie, Tian Pei, Yishi Piao, Junjie Qiu, Hui Qu, Tongzheng Ren, Zehui Ren, Chong Ruan, Zhangli Sha, Zhihong Shao, Junxiao Song, Xuecheng Su, Jingxiang Sun, Yaofeng Sun, Minghui Tang, Bingxuan Wang, Peiyi Wang, Shiyu Wang, Yaohui Wang, Yongji Wang, Tong Wu, Y. Wu, Xin Xie, Zhenda Xie, Ziwei Xie, Yiliang Xiong, Hanwei Xu, R. X. Xu, Yanhong Xu, Dejian Yang, Yuxiang You, Shuiping Yu, Xingkai Yu, B. Zhang, Haowei Zhang, Lecong Zhang, Liyue Zhang, Mingchuan Zhang, Minghua Zhang, Wentao Zhang, Yichao Zhang, Chenggang Zhao, Yao Zhao, Shangyan Zhou, Shunfeng Zhou, Qihao Zhu, and Yuheng Zou. 2024. [Deepseek llm: Scaling open-source language models with longtermism](#).
- Ahmad Faiz, Sotaro Kaneda, Ruhan Wang, Rita Osi, Parteek Sharma, Fan Chen, and Lei Jiang. 2023. Llmcarbon: Modeling the end-to-end carbon footprint of large language models. *arXiv preprint arXiv:2309.14393*.
- Peter I. Frazier. 2018. [A tutorial on bayesian optimization](#).
- Clive WJ Granger. 1989. Invited review combining forecasts—twenty years later. *Journal of forecasting*, 8(3):167–173.
- Dirk Groeneveld, Iz Beltagy, Pete Walsh, Akshita Bhagia, Rodney Kinney, Oyvind Tafjord, Ananya Harsh Jha, Hamish Ivison, Ian Magnusson, Yizhong Wang, Shane Arora, David Atkinson, Russell Authur, Khyathi Raghavi Chandu, Arman Cohan, Jennifer Dumas, Yanai Elazar, Yuling Gu, Jack Hessel, Tushar Khot, William Merrill, Jacob Morrison, Niklas Muenighoff, Aakanksha Naik, Crystal Nam, Matthew E.

- Peters, Valentina Pyatkin, Abhilasha Ravichander, Dustin Schwenk, Saurabh Shah, Will Smith, Emma Strubell, Nishant Subramani, Mitchell Wortsman, Pradeep Dasigi, Nathan Lambert, Kyle Richardson, Luke Zettlemoyer, Jesse Dodge, Kyle Lo, Luca Soldaini, Noah A. Smith, and Hannaneh Hajishirzi. 2024. [Olmo: Accelerating the science of language models](#).
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. [Measuring massive multitask language understanding](#).
- Matthew Hoffman, Eric Brochu, Nando De Freitas, et al. 2011. Portfolio allocation for bayesian optimization. In *UAI*, pages 327–336.
- Le Hou, Richard Yuanzhe Pang, Tianyi Zhou, Yuexin Wu, Xinying Song, Xiaodan Song, and Denny Zhou. 2022. [Token dropping for efficient BERT pretraining](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3774–3784, Dublin, Ireland. Association for Computational Linguistics.
- Yuzhen Huang, Yuzhuo Bai, Zhihao Zhu, Junlei Zhang, Jinghan Zhang, Tangjun Su, Junteng Liu, Chuancheng Lv, Yikai Zhang, Jiayi Lei, Yao Fu, Maosong Sun, and Junxian He. 2023. C-eval: A multi-level multi-discipline chinese evaluation suite for foundation models. In *Advances in Neural Information Processing Systems*.
- Xisen Jin, Xiang Ren, Daniel Preotiuc-Pietro, and Pengxiang Cheng. 2022. Dataless knowledge fusion by merging weights of language models. *arXiv preprint arXiv:2212.09849*.
- Alexia Jolicoeur-Martineau, Emy Gervais, Kilian Fatras, Yan Zhang, and Simon Lacoste-Julien. 2023. Population parameter averaging (papa). *arXiv preprint arXiv:2304.03094*.
- Donald R Jones, Matthias Schonlau, and William J Welch. 1998. Efficient global optimization of expensive black-box functions. *Journal of Global optimization*, 13:455–492.
- Dahyun Kim, Chanjun Park, Sanghoon Kim, Wonsung Lee, Wonho Song, Yunsu Kim, Hyeonwoo Kim, Yungi Kim, Hyeonju Lee, Jihoo Kim, et al. 2023. Solar 10.7 b: Scaling large language models with simple yet effective depth up-scaling. *arXiv preprint arXiv:2312.15166*.
- Haonan Li, Yixuan Zhang, Fajri Koto, Yifei Yang, Hai Zhao, Yeyun Gong, Nan Duan, and Timothy Baldwin. 2023. [Cmmlu: Measuring massive multitask language understanding in chinese](#).
- Richard Liaw, Eric Liang, Robert Nishihara, Philipp Moritz, Joseph E Gonzalez, and Ion Stoica. 2018. Tune: A research platform for distributed model selection and training. *arXiv preprint arXiv:1807.05118*.
- Ziming Liu, Shenggan Cheng, Haotian Zhou, and Yang You. 2023. Hanayo: Harnessing wave-like pipeline parallelism for enhanced large model training efficiency. In *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis*, pages 1–13.
- Michael S Matena and Colin A Raffel. 2022. Merging models with fisher-weighted averaging. *Advances in Neural Information Processing Systems*, 35:17703–17716.
- Jonas Moćkus. 1975. On bayesian methods for seeking the extremum. In *Optimization Techniques IFIP Technical Conference: Novosibirsk, July 1–7, 1974*, pages 400–404. Springer.
- OpenAI. :, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, Red Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Mo Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher Berner, Lenny Bogdonoff, Oleg Boiko, Madeleine Boyd, Anna-Luisa Brakman, Greg Brockman, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann, Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis, Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Ben Chess, Chester Cho, Casey Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux, Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix, Simón Posada Fishman, Juston Forte, Isabella Fulford, Leo Gao, Elie Georges, Christian Gibson, Vik Goel, Tarun Gogineni, Gabriel Goh, Rapha Gontijo-Lopes, Jonathan Gordon, Morgan Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hallacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu, Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Łukasz Kaiser, Ali Kamali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook Kim, Christina Kim, Yongjik Kim, Hendrik Kirchner, Jamie Kiros, Matt Knight, Daniel Kokotajlo, Łukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kosic, Gretchen Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez, Ryan Lowe, Patricia Lue, Anna Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney, Christine McLeavey, Paul McMillan,

- Jake McNeil, David Medina, Aalok Mehta, Jacob Menick, Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel Mossing, Tong Mu, Mira Murati, Oleg Murk, David Mély, Ashvin Nair, Reiichiro Nakano, Rajeesh Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Long Ouyang, Cullen O’Keefe, Jakub Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel Parish, Emy Parparita, Alex Passos, Mikhail Pavlov, Andrew Peng, Adam Perelman, Filipe de Avila Belbute Peres, Michael Petrov, Henrique Ponde de Oliveira Pinto, Michael, Pokorny, Michelle Pokrass, Vitchyr Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl, Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario Saltarelli, Ted Sanders, Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Selsam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor, Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin Sokolowsky, Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang, Nikolas Tezak, Madeleine Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Preston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cerón Uribe, Andrea Vallone, Arun Vijayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiayi Weng, Lilian Weng, Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Workman, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. 2023. [Gpt-4 technical report](#).
- R OpenAI. 2023. Gpt-4 technical report. arxiv 2303.08774. *View in Article*, 2:13.
- Yujia Qin, Jiajie Zhang, Yankai Lin, Zhiyuan Liu, Peng Li, Maosong Sun, and Jie Zhou. 2022. Elle: Efficient lifelong pre-training for emerging data. *arXiv preprint arXiv:2203.06311*.
- Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. 2020. Zero: Memory optimizations toward training trillion parameter models. In *SC20: International Conference for High Performance Computing, Networking, Storage and Analysis*, pages 1–16. IEEE.
- Alexandre Ramé, Nino Vieillard, Léonard Hussenot, Robert Dadashi, Geoffrey Cideron, Olivier Bachem, and Johan Ferret. 2024. [Warm: On the benefits of weight averaged reward models](#).
- Sebastian Ruder and Barbara Plank. 2017. Learning to select data for transfer learning with bayesian optimization. *arXiv preprint arXiv:1707.05246*.
- Sunny Sanyal, Atula Neerkaje, Jean Kaddour, Abhishek Kumar, and Sujay Sanghavi. 2023. [Early weight averaging meets high learning rates for llm pre-training](#).
- Matthias Seeger. 2004. Gaussian processes for machine learning. *International journal of neural systems*, 14(02):69–106.
- Mohammad Shoeybi, Mostofa Patwary, Raul Puri, Patrick LeGresley, Jared Casper, and Bryan Catanzaro. 2019. Megatron-lm: Training multi-billion parameter language models using model parallelism. *arXiv preprint arXiv:1909.08053*.
- Edwin Simpson, Yang Gao, and Iryna Gurevych. 2020. Interactive text ranking with bayesian optimization: A case study on community qa and summarization. *Transactions of the Association for Computational Linguistics*, 8:759–775.
- Sidak Pal Singh and Martin Jaggi. 2023. [Model fusion via optimal transport](#).
- Niranjan Srinivas, Andreas Krause, Sham M Kakade, and Matthias Seeger. 2009. Gaussian process optimization in the bandit setting: No regret and experimental design. *arXiv preprint arXiv:0912.3995*.
- Emma Strubell, Ananya Ganesh, and Andrew McCallum. 2019. Energy and policy considerations for deep learning in nlp. *arXiv preprint arXiv:1906.02243*.
- Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M. Dai, Anja Hauth, Katie Millican, David Silver, Slav Petrov, Melvin Johnson, Ioannis Antonoglou, Julian Schrittwieser, Amelia Glaese, Jilin Chen, Emily Pitler, Timothy Lillicrap, Angeliki Lazaridou, Orhan Firat, James Molloy, Michael Isard, Paul R. Barham, Tom Hennigan, Benjamin Lee, Fabio Viola, Malcolm Reynolds, Yuanzhong Xu, Ryan Doherty, Eli Collins, Clemens Meyer, Eliza Rutherford, Erica Moreira, Kareem Ayoub, Megha Goel, George Tucker, Enrique Piqueras, Maxim Krikun, Iain Barr, Nikolay Savinov, Ivo Danihelka, Becca Roelofs, Anaïs White, Anders Andreassen, Tamara von Glehn, Lakshman Yagati, Mehran Kazemi, Lucas Gonzalez, Misha Khalman, Jakub Sygnowski, Alexandre Frechette, Charlotte Smith, Laura Culp, Lev Proleev, Yi Luan, Xi Chen, James Lottes, Nathan Schucher, Federico Lebron, Alban Rustemi, Natalie Clay, Phil Crone, Tomas Kocisky, Jeffrey Zhao, Bartek Perz, Dian Yu, Heidi Howard, Adam Bloniarz, Jack W. Rae, Han Lu, Laurent Sifre, Marcello Maggioni, Fred Alcober, Dan Garette, Megan Barnes, Shantanu Thakoor, Jacob Austin, Gabriel Barth-Maron, William Wong, Rishabh Joshi, Rahma Chaabouni, Deeni Fatiha, Arun Ahuja, Ruibo Liu, Yunxuan Li, Sarah Cogan, Jeremy Chen, Chao Jia, Chenjie Gu, Qiao Zhang, Jordan Grimstad, Ale Jakse Hartman, Martin Chadwick, Gaurav Singh Tomar, Xavier Garcia, Evan Senter, Emanuel Taropa, Thanumalayan Sankaranarayanan Pillai, Jacob Devlin, Michael Laskin, Diego de Las Casas, Dasha Valter, Connie Tao, Lorenzo

Blanco, Adrià Puigdomènech Badia, David Reitter, Mianna Chen, Jenny Brennan, Clara Rivera, Sergey Brin, Shariq Iqbal, Gabriela Surita, Jane Labanowski, Abhi Rao, Stephanie Winkler, Emilio Parisotto, Yiming Gu, Kate Olszewska, Yujing Zhang, Ravi Ad-danki, Antoine Miech, Annie Louis, Laurent El Shafey, Denis Teplyashin, Geoff Brown, Elliot Catt, Nithya Attaluri, Jan Balaguer, Jackie Xiang, Pi-dong Wang, Zoe Ashwood, Anton Briukhov, Al-bert Webson, Sanjay Ganapathy, Smit Sanghavi, Ajay Kannan, Ming-Wei Chang, Axel Stjerngren, Josip Djolonga, Yuting Sun, Ankur Bapna, Matthew Aitchison, Pedram Pejman, Henryk Michalewski, Tianhe Yu, Cindy Wang, Juliette Love, Junwhan Ahn, Dawn Bloxwich, Kehang Han, Peter Humphreys, Thibault Sellam, James Bradbury, Varun Godbole, Sina Samangooei, Bogdan Damoc, Alex Kaskasoli, Sébastien M. R. Arnold, Vijay Vasudevan, Shubham Agrawal, Jason Riesa, Dmitry Lepikhin, Richard Tan-burn, Srivatsan Srinivasan, Hyeontaek Lim, Sarah Hodgkinson, Pranav Shyam, Johan Ferret, Steven Hand, Ankush Garg, Tom Le Paine, Jian Li, Yu-jia Li, Minh Giang, Alexander Neitz, Zaheer Abbas, Sarah York, Machel Reid, Elizabeth Cole, Aakanksha Chowdhery, Dipanjan Das, Dominika Rogozińska, Vitaly Nikolaev, Pablo Sprechmann, Zachary Nado, Lukas Zilka, Flavien Prost, Luheng He, Marianne Monteiro, Gaurav Mishra, Chris Welty, Josh Newlan, Dawei Jia, Miltiadis Allamanis, Clara Huiyi Hu, Raoul de Liedekerke, Justin Gilmer, Carl Saroufim, Shruti Rijhwani, Shaobo Hou, Disha Shrivastava, Anirudh Baddepudi, Alex Goldin, Adnan Ozturk, Albin Cassirer, Yunhan Xu, Daniel Sohn, Deven-dra Sachan, Reinald Kim Amplayo, Craig Swanson, Dessie Petrova, Shashi Narayan, Arthur Guez, Siddhartha Brahma, Jessica Landon, Miteyan Patel, Ruizhe Zhao, Kevin Vellela, Luyu Wang, Wenhao Jia, Matthew Rahtz, Mai Giménez, Legg Yeung, Hanzhao Lin, James Keeling, Petko Georgiev, Di-ana Mincu, Boxi Wu, Salem Haykal, Rachel Sapu-tro, Kiran Vodrahalli, James Qin, Zeynep Cankara, Abhanshu Sharma, Nick Fernando, Will Hawkins, Behnam Neyshabur, Solomon Kim, Adrian Hut-ter, Priyanka Agrawal, Alex Castro-Ros, George van den Driessche, Tao Wang, Fan Yang, Shuo yiin Chang, Paul Komarek, Ross McIlroy, Mario Lučić, Guodong Zhang, Wael Farhan, Michael Sharman, Paul Natsev, Paul Michel, Yong Cheng, Yamini Bansal, Siyuan Qiao, Kris Cao, Siamak Shakeri, Christina Butterfield, Justin Chung, Paul Kishan Rubenstein, Shivani Agrawal, Arthur Mensch, Kedar Soparkar, Karel Lenc, Timothy Chung, Aedan Pope, Loren Maggiore, Jackie Kay, Priya Jhakra, Shibo Wang, Joshua Maynez, Mary Phuong, Taylor Tobin, Andrea Tacchetti, Maja Trebacz, Kevin Robinson, Yash Katariya, Sebastian Riedel, Paige Bailey, Ke-fan Xiao, Nimesh Ghelani, Lora Aroyo, Ambrose Slone, Neil Houlsby, Xuehan Xiong, Zhen Yang, Elena Gribovskaya, Jonas Adler, Mateo Wirth, Lisa Lee, Music Li, Thais Kagohara, Jay Pavagadhi, So-phie Bridgers, Anna Bortsova, Sanjay Ghemawat, Zafarali Ahmed, Tianqi Liu, Richard Powell, Vijay Bolina, Mariko Iinuma, Polina Zablotskaia, James Besley, Da-Woon Chung, Timothy Dozat, Ramona

Comanescu, Xiance Si, Jeremy Greer, Guolong Su, Martin Polacek, Raphaël Lopez Kaufman, Simon Tokumine, Hexiang Hu, Elena Buchatskaya, Yingjie Miao, Mohamed Elhawaty, Aditya Siddhant, Nenad Tomasev, Jinwei Xing, Christina Greer, Helen Miller, Shereen Ashraf, Aurko Roy, Zizhao Zhang, Ada Ma, Angelos Filos, Milos Besta, Rory Blevins, Ted Kli-menko, Chih-Kuan Yeh, Soravit Changpinyo, Jiaqi Mu, Oscar Chang, Mantas Pajarskas, Carrie Muir, Vered Cohen, Charline Le Lan, Krishna Haridasan, Amit Marathe, Steven Hansen, Sholto Douglas, Ra-jkumar Samuel, Mingqiu Wang, Sophia Austin, Chang Lan, Jiepu Jiang, Justin Chiu, Jaime Alonso Lorenzo, Lars Lowe Sjösund, Sébastien Cevey, Zach Gleicher, Thi Avrahami, Anudhyan Boral, Hansa Srinivasan, Vittorio Selo, Rhys May, Kon-stantinos Aisopos, Léonard Hussenot, Livio Baldini Soares, Kate Baumli, Michael B. Chang, Adrià Re-casens, Ben Caine, Alexander Pritzel, Filip Pavetic, Fabio Pardo, Anita Gergely, Justin Frye, Vinay Ramasesh, Dan Horgan, Kartikeya Badola, Nora Kassner, Subhrajit Roy, Ethan Dyer, Víctor Cam-pos, Alex Tomala, Yunhao Tang, Dalia El Badawy, Elspeth White, Basil Mustafa, Oran Lang, Ab-hishek Jindal, Sharad Vikram, Zhitao Gong, Sergi Caelles, Ross Hemsley, Gregory Thornton, Fangxi-aoyu Feng, Wojciech Stokowiec, Ce Zheng, Phoebe Thacker, Çağlar Ünlü, Zhishuai Zhang, Moham-mad Saleh, James Svensson, Max Bileschi, Piyush Patil, Ankesh Anand, Roman Ring, Katerina Tsihlias, Arpi Vezer, Marco Selvi, Toby Shevlane, Mikel Rod-riguez, Tom Kwiatkowski, Samira Daruki, Keran Rong, Allan Dafoe, Nicholas FitzGerald, Keren Gu-Lemberg, Mina Khan, Lisa Anne Hendricks, Marie Pellat, Vladimir Feinberg, James Cobon-Kerr, Tara Sainath, Maribeth Rauh, Sayed Hadi Hashemi, Richard Ives, Yana Hasson, YaGuang Li, Eric Noland, Yuan Cao, Nathan Byrd, Le Hou, Qingze Wang, Thibault Sottiaux, Michela Paganini, Jean-Baptiste Lespiau, Alexandre Moufarek, Samer Hassan, Kaushik Shivakumar, Joost van Amers-foort, Amol Mandhane, Pratik Joshi, Anirudh Goyal, Matthew Tung, Andrew Brock, Hannah She-han, Vedant Misra, Cheng Li, Nemanja Rakićević, Mostafa Dehghani, Fangyu Liu, Sid Mittal, Junhyuk Oh, Seb Noury, Eren Sezener, Fantine Huot, Matthew Lamm, Nicola De Cao, Charlie Chen, Gamaleldin Elsayed, Ed Chi, Mahdis Mahdieh, Ian Tenney, Nan Hua, Ivan Petrychenko, Patrick Kane, Dylan Scand-inaro, Rishub Jain, Jonathan Uesato, Romina Datta, Adam Sadovsky, Oskar Bunyan, Dominik Rabiej, Shimu Wu, John Zhang, Gautam Vasudevan, Edouard Leurent, Mahmoud Alnahlawi, Ionut Georgescu, Nan Wei, Ivy Zheng, Betty Chan, Pam G Rabinovitch, Piotr Stanczyk, Ye Zhang, David Steiner, Subhajt Naskar, Michael Azzam, Matthew Johnson, Adam Paszke, Chung-Cheng Chiu, Jaume Sanchez Elias, Afroz Mohiuddin, Faizan Muhammad, Jin Miao, Andrew Lee, Nino Vieillard, Sahitya Potluri, Jane Park, Elnaz Davoodi, Jiageng Zhang, Jeff Stanway, Drew Garmon, Abhijit Karmarkar, Zhe Dong, Jong Lee, Aviral Kumar, Luowei Zhou, Jonathan Evens, William Isaac, Zhe Chen, Johnson Jia, Anselm Levskaya, Zhenkai Zhu, Chris Gorgolewski, Peter

Grabowski, Yu Mao, Alberto Magni, Kaisheng Yao, Javier Snaider, Norman Casagrande, Paul Suganthan, Evan Palmer, Geoffrey Irving, Edward Loper, Manaal Faruqui, Isha Arkatkar, Nanxin Chen, Izhak Shafran, Michael Fink, Alfonso Castaño, Irene Gianoumis, Wooyeol Kim, Mikołaj Rybiński, Ashwin Sreevatsa, Jennifer Prendki, David Soergel, Adrian Goedeckemeyer, Willi Gierke, Mohsen Jafari, Meenu Gaba, Jeremy Wiesner, Diana Gage Wright, Yawen Wei, Harsha Vashisht, Yana Kulizhskaya, Jay Hoover, Maigo Le, Lu Li, Chimezie Iwuanyanwu, Lu Liu, Kevin Ramirez, Andrey Khorlin, Albert Cui, Tian LIN, Marin Georgiev, Marcus Wu, Ricardo Aguilar, Keith Pallo, Abhishek Chakladar, Alena Repina, Xihui Wu, Tom van der Weide, Priya Ponnappalli, Caroline Kaplan, Jiri Simsa, Shuangfeng Li, Olivier Dousse, Fan Yang, Jeff Piper, Nathan Ie, Minnie Lui, Rama Pasumarthi, Nathan Lintz, Anitha Vijayakumar, Lam Nguyen Thiet, Daniel Andor, Pedro Valenzuela, Cosmin Paduraru, Daiyi Peng, Katherine Lee, Shuyuan Zhang, Somer Greene, Duc Dung Nguyen, Paula Kurylowicz, Sarmishta Velury, Sebastian Krause, Cassidy Hardin, Lucas Dixon, Lili Janzer, Kiam Choo, Ziqiang Feng, Biao Zhang, Achintya Singhal, Tejasi Latkar, Mingyang Zhang, Quoc Le, Elena Allica Abellan, Dayou Du, Dan McKinnon, Natasha Antropova, Tolga Bolukbasi, Orgad Keller, David Reid, Daniel Finchelstein, Maria Abi Raad, Remi Crocker, Peter Hawkins, Robert Dadashi, Colin Gaffney, Sid Lall, Ken Franko, Egor Filonov, Anna Bulanova, Rémi Leblond, Vikas Yadav, Shirley Chung, Harry Ashkam, Luis C. Cobo, Kelvin Xu, Felix Fischer, Jun Xu, Christina Sorokin, Chris Alberti, Chu-Cheng Lin, Colin Evans, Hao Zhou, Alek Dimitriev, Hannah Forbes, Dylan Banarse, Zora Tung, Jeremiah Liu, Mark Omernick, Colton Bishop, Chintu Kumar, Rachel Sterneck, Ryan Foley, Rohan Jain, Swaroop Mishra, Jiawei Xia, Taylor Bos, Geoffrey Cideron, Ehsan Amid, Francesco Piccinno, Xingyu Wang, Praseem Banzal, Petru Gurita, Hila Noga, Premal Shah, Daniel J. Mankowitz, Alex Polozov, Nate Kushman, Victoria Krakovna, Sasha Brown, MohammadHossein Bateni, Dennis Duan, Vlad Firoiu, Meghana Thotakuri, Tom Natan, Anhad Mohananey, Matthieu Geist, Sidharth Mudgal, Sertan Girgin, Hui Li, Jiayu Ye, Ofir Roval, Reiko Tojo, Michael Kwong, James Lee-Thorp, Christopher Yew, Quan Yuan, Sumit Bagri, Danila Sinopalnikov, Sabela Ramos, John Mellor, Abhishek Sharma, Aliaksei Severyn, Jonathan Lai, Kathy Wu, Heng-Tze Cheng, David Miller, Nicolas Sonnerat, Denis Vnukov, Rory Greig, Jennifer Beattie, Emily Caveness, Libin Bai, Julian Eisenschlos, Alex Korchemniy, Tomy Tsai, Mimi Jasarevic, Weize Kong, Phuung Dao, Zeyu Zheng, Frederick Liu, Fan Yang, Rui Zhu, Mark Geller, Tian Huey Teh, Jason Sanmiya, Evgeny Gladchenko, Nejc Trdin, Andrei Sozanschi, Daniel Toyama, Evan Rosen, Sasan Tavakkol, Linting Xue, Chen Elkind, Oliver Woodman, John Carpenter, George Papamakarios, Rupert Kemp, Sushant Kafle, Tanya Grunina, Rishika Sinha, Alice Talbert, Abhimanyu Goyal, Diane Wu, Denese Owusu-Afriyie, Cosmo Du, Chloe Thornton, Jordi Pont-Tuset, Pradyumna Narayana, Jing Li, Sabaer Fatehi,

John Wieting, Omar Ajmeri, Benigno Uria, Tao Zhu, Yeongil Ko, Laura Knight, Amélie Héliou, Ning Niu, Shane Gu, Chenxi Pang, Dustin Tran, Yeqing Li, Nir Levine, Ariel Stolovich, Norbert Kalb, Rebeca Santamaria-Fernandez, Sonam Goenka, Wenny Yustalim, Robin Strudel, Ali Elqursh, Balaji Lakshminarayanan, Charlie Deck, Shyam Upadhyay, Hyo Lee, Mike Dusenberry, Zonglin Li, Xuezhi Wang, Kyle Levin, Raphael Hoffmann, Dan Holtmann-Rice, Olivier Bachem, Summer Yue, Sho Arora, Eric Malmi, Daniil Mirylenka, Qijun Tan, Christy Koh, Soheil Hassas Yeganeh, Siim Pöder, Steven Zheng, Francesco Pongetti, Mukarram Tariq, Yanhua Sun, Lucian Ionita, Mojtaba Seyedhosseini, Pouya Tafti, Ragha Kotikalapudi, Zhiyu Liu, Anmol Gulati, Jasmine Liu, Xinyu Ye, Bart Chrzaszcz, Lily Wang, Nikhil Sethi, Tianrun Li, Ben Brown, Shreya Singh, Wei Fan, Aaron Parisi, Joe Stanton, Chenkai Kuang, Vinod Koverkathu, Christopher A. Choquette-Choo, Yunjie Li, TJ Lu, Abe Ittycheriah, Prakash Shroff, Pei Sun, Mani Varadarajan, Sanaz Bahargam, Rob Willoughby, David Gaddy, Ishita Dasgupta, Guillaume Desjardins, Marco Cornero, Brona Robenek, Bhavishya Mittal, Ben Albrecht, Ashish Shenoy, Fedor Moiseev, Henrik Jacobsson, Alireza Ghaffarkhah, Morgane Rivière, Alanna Walton, Clément Crepy, Alicia Parrish, Yuan Liu, Zongwei Zhou, Clement Farabet, Carey Radebaugh, Praveen Srinivasan, Claudia van der Salm, Andreas Fidleland, Salvatore Scellato, Eri Latorre-Chimoto, Hanna Klimczak-Plucińska, David Bridson, Dario de Cesare, Tom Hudson, Piermaria Mendolicchio, Lexi Walker, Alex Morris, Ivo Penchev, Matthew Mauger, Alexey Guseynov, Alison Reid, Seth Odoom, Lucia Loher, Victor Cotruta, Madhavi Yenugula, Dominik Grewe, Anastasia Petrushkina, Tom Duerig, Antonio Sanchez, Steve Yadlowsky, Amy Shen, Amir Globerson, Adam Kurzrok, Lynette Webb, Sahil Dua, Dong Li, Preethi Lahoti, Surya Bhupatiraju, Dan Hurt, Haroon Qureshi, Ananth Agarwal, Tomer Shani, Matan Eyal, Anuj Khare, Shreyas Rammohan Belle, Lei Wang, Chetan Tekur, Mihir Sanjay Kale, Jinliang Wei, Ruoxin Sang, Brennan Saeta, Tyler Liechty, Yi Sun, Yao Zhao, Stephan Lee, Pandu Nayak, Doug Fritz, Manish Reddy Vuyyuru, John Aslanides, Nidhi Vyas, Martin Wicke, Xiao Ma, Taylan Bilal, Evgenii Eltyshev, Daniel Balle, Nina Martin, Hardie Cate, James Manyika, Keyvan Amiri, Yelin Kim, Xi Xiong, Kai Kang, Florian Luisier, Nilesh Tripuraneni, David Madras, Mandy Guo, Austin Waters, Oliver Wang, Joshua Ainslie, Jason Baldridge, Han Zhang, Garima Pruthi, Jakob Bauer, Feng Yang, Riham Mansour, Jason Gelman, Yang Xu, George Polovets, Ji Liu, Honglong Cai, Warren Chen, XiangHai Sheng, Emily Xue, Sherjil Ozair, Adams Yu, Christof Angermueller, Xiaowei Li, Weiren Wang, Julia Wiesinger, Emmanouil Koukoumidis, Yuan Tian, Anand Iyer, Madhu Gurumurthy, Mark Goldenson, Parashar Shah, MK Blake, Hongkun Yu, Anthony Urbanowicz, Jennimaria Palomaki, Chrisantha Fernando, Kevin Brooks, Ken Durden, Harsh Mehta, Nikola Momchev, Elahe Rahimtoroghi, Maria Georgaki, Amit Raul, Sebastian Ruder, Morgan Redshaw, Jinhyuk Lee, Komal Jalan, Dinghua Li, Ginger

Perng, Blake Hechtman, Parker Schuh, Milad Nasr, Mia Chen, Kieran Milan, Vladimir Mikulik, Trevor Strohman, Juliana Franco, Tim Green, Demis Hassabis, Koray Kavukcuoglu, Jeffrey Dean, and Oriol Vinyals. 2023. [Gemini: A family of highly capable multimodal models](#).

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023. [Llama: Open and efficient foundation language models](#).

Joachim Utans. 1996. Weight averaging for neural networks and local resampling schemes. In *Proc. AAAI-96 Workshop on Integrating Multiple Learned Models*. AAAI Press, pages 133–138. Citeseer.

Fanqi Wan, Xinting Huang, Deng Cai, Xiaojun Quan, Wei Bi, and Shuming Shi. 2024. [Knowledge fusion of large language models](#).

Mitchell Wortsman, Gabriel Ilharco, Samir Ya Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, et al. 2022. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International Conference on Machine Learning*, pages 23965–23998. PMLR.

Aiyuan Yang, Bin Xiao, Bingning Wang, Borong Zhang, Ce Bian, Chao Yin, Chenxu Lv, Da Pan, Dian Wang, Dong Yan, Fan Yang, Fei Deng, Feng Wang, Feng Liu, Guangwei Ai, Guosheng Dong, Haizhou Zhao, Hang Xu, Haoze Sun, Hongda Zhang, Hui Liu, Jiaming Ji, Jian Xie, JunTao Dai, Kun Fang, Lei Su, Liang Song, Lifeng Liu, Liyun Ru, Luyao Ma, Mang Wang, Mickel Liu, MingAn Lin, Nuolan Nie, Peidong Guo, Ruiyang Sun, Tao Zhang, Tianpeng Li, Tianyu Li, Wei Cheng, Weipeng Chen, Xiangrong Zeng, Xiaochuan Wang, Xiaoxi Chen, Xin Men, Xin Yu, Xuehai Pan, Yanjun Shen, Yiding Wang, Yiyu Li, Youxin Jiang, Yuchen Gao, Yupeng Zhang, Zenan Zhou, and Zhiying Wu. 2023. [Baichuan 2: Open large-scale language models](#).

Dani Yogatama, Lingpeng Kong, and Noah A. Smith. 2015. Bayesian optimization of text representations. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 2100–2105, Lisbon, Portugal. Association for Computational Linguistics.

Le Yu, Bowen Yu, Haiyang Yu, Fei Huang, and Yongbin Li. 2024. [Language models are super mario: Absorb-ing abilities from homologous models as a free lunch](#).

A Appendix for Pilot Experiments

A.1 Performance on CMMLU Dataset

In this section, we describe the performance of merging checkpoints on the CMMLU dataset.




Figure 6: The performance of conducting pairwise checkpoint merging via greedy soup in CMMLU.

In accordance with the research question outlined in pilot experiments, we extended our analysis to the CMMLU dataset to corroborate the findings from the C-Eval dataset. Utilizing the same methodology, we evaluated all possible pairwise merging, totaling 55 combinations (C_{11}^2). Employing the greedy soup strategy as outlined by Wortsman et al. (2022), checkpoints are sequentially incorporated into the soup if they demonstrate an improvement in accuracy on the development data.

The analysis yields observations that are consistent with those obtained from the C-Eval dataset, reinforcing the generality of our findings. Specifically, we observe that:

(1) Adjacent checkpoint merging yields superior performance: Echoing the C-Eval dataset’s findings, merging two checkpoints from consecutive training phases in the CMMLU dataset generally led to performance enhancements over individual checkpoints. Notably, merging Baichuan2-1980B with Baichuan2-2200B achieved an accuracy of 56.57% on the CMMLU dataset, surpassing the 56.29% accuracy of Baichuan2-2200B when assessed independently. This not only highlights the effectiveness of adjacent checkpoint merging but also indicates a significant improvement over the final checkpoint, Baichuan-2420B (with an accuracy of 56.78%), by elevating the test accuracy by 0.10%. (2) Merging distant checkpoints leads

Dataset	Baichuan2-220B	Baichuan2-440B	Uniform Soup	Greedy Soup	Fisher	RegMean
C-Eval	23.89	34.12	24.10	34.12	26.68	26.37
CMMLU	25.54	37.11	25.78	37.11	27.46	25.23
MMLU	23.85	33.29	23.1	33.29	23.15	23.33
GSM8K	6.82	9.10	8.04	9.10	8.16	5.46

Table 5: The results of merging Baichuan2-220B with Baichuan2-440B across various benchmark datasets.




Figure 7: Merging DeepSeek checkpoints 1800B and 2000B reveals equal performance, with 69% of weights improving beyond the superior base model.

to performance deterioration: In line with the C-Eval dataset observations, merging significantly disparate checkpoints, such as Baichuan2-220B with Baichuan2-2200B, resulted in a notable performance decline, with accuracy dropping to 25.26% on the CMMLU dataset. This outcome closely mirrors the performance of the lesser-trained checkpoint, Baichuan2-220B, which has an accuracy of 25.54%, underscoring the negative impact of merging widely separated checkpoints.

The CMMLU dataset findings reinforce the C-Eval dataset’s results, highlighting the critical importance of strategic checkpoint merging for enhanced model performance across diverse datasets.

A.2 Performance on DeepSeek

In our initial experiments, we delve into the possibility of boosting performance through strategic checkpoint merging within the Baichuan pre-trained model, focusing on the checkpoint pairs 1540B and 1760B, along with 2200B and 2420B, in the advanced stages of pretraining. This exploration aims to uncover patterns of improvement that could be applied across different models. How-

ever, our analysis has not extended to other models like DeepSeek. To bridge this gap, we undertake a detailed examination of DeepSeek by evaluating the merging of checkpoints 1800B and 2000B, assessing 100 merging weight points distributed evenly within the $[0, 1]$ interval. Our objective is to ascertain if the trend of performance enhancement through merging observed in Baichuan is also evident in other pre-trained models, specifically through the lens of weight combination efficacy.

The pivotal question guiding our research is: Do similar patterns of performance improvement emerge in other pre-trained models, such as DeepSeek, when applying strategic checkpoint merging, as observed in the Baichuan model?

Our research confirms this hypothesis, revealing that: Specifically, an impressive 70% of the tested merging weight combinations for DeepSeek’s checkpoints 1800B and 2000B result in performance enhancements.

This finding indicates that the strategy of merging checkpoints to enhance performance is not unique to the Baichuan model but is also applicable to other pre-trained models like DeepSeek. The consistency of this pattern across different models highlights the potential of checkpoint merging as a universally effective method for optimizing pre-trained model performance during their later training phases.

B Additional Tables

B.1 All the results of Baichuan2-220B with Baichuan2-440B across various benchmark datasets.

As outlined in our pilot experiments, performing weight merging on checkpoints of LLMs during the early stages of pre-training leads to a degradation in performance. In the Table 5, we present our experimental results on weight merging between Baichuan2-220B and Baichuan2-440B models. We use Uniform Soup, Greedy Soup, Fisher, and RegMean to conduct merging and measure

the post merging performance. Without exception, none of the outcomes show performance surpassing that of the superior base model (Baichuan2-440B). This evidence suggests that conducting checkpoint merging in the early pre-training phase is not a viable strategy.