#### Preprint of the paper:

Satpute, A. & Giessing, N. & Greiner-Petter, A. & Schubotz, M. & Teschke, O. & Aizawa, A. & Gipp, B., "Can LLMs Master Math? Investigating Large Language Models on Math Stack Exchange", in 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '24), Washington D.C., USA.

Click to download: BibTeX

# Can LLMs Master Math? Investigating Large Language Models on Math Stack Exchange

Ankit Satpute<sup>†§</sup>, Noah Gießing<sup>†</sup>, André Greiner-Petter<sup>§</sup>, Moritz Schubotz<sup>†</sup>, Olaf Teschke<sup>†</sup>, Akiko

Aizawa<sup>\$</sup>, Bela Gipp<sup>§</sup>

Ankit.Satpute@fiz-karlsruhe.de

<sup>†</sup>FIZ Karlsruhe Berlin, <sup>§</sup>University of Göttingen Germany, <sup>§</sup>NII Japan

# ABSTRACT

Large Language Models (LLMs) have demonstrated exceptional capabilities in various natural language tasks, often achieving performances that surpass those of humans. Despite these advancements, the domain of mathematics presents a distinctive challenge, primarily due to its specialized structure and the precision it demands. In this study, we adopted a two-step approach for investigating the proficiency of LLMs in answering mathematical questions. First, we employ the most effective LLMs, as identified by their performance on math question-answer benchmarks, to generate answers to 78 questions from the Math Stack Exchange (MSE). Second, a case analysis is conducted on the LLM that showed the highest performance, focusing on the quality and accuracy of its answers through manual evaluation. We found that GPT-4 performs best (nDCG of 0.48 and P@10 of 0.37) amongst existing LLMs finetuned for answering mathematics questions and outperforms the current best approach on ArqMATH3 Task1, considering P@10. Our Case analysis indicates that while the GPT-4 can generate relevant responses in certain instances, it does not consistently answer all questions accurately. This paper explores the current limitations of LLMs in navigating complex mathematical problemsolving. Through case analysis, we shed light on the gaps in LLM capabilities within mathematics, thereby setting the stage for future research and advancements in AI-driven mathematical reasoning. We make our code and findings publicly available for research: https://github.com/gipplab/LLM-Investig-MathStackExchange

## CCS CONCEPTS

• **Computing methodologies** → *Discourse, dialogue and pragmatics*; • **Mathematics of computing** → *Mathematical software performance.* 

#### **KEYWORDS**

Math Language Models, Math Stack Exchange. Math Question Answer

SIGIR 2024, July 14-18, 2024, Washington D.C., USA

https://doi.org/XXXXXXXXXXXXXXX

#### **ACM Reference Format:**

Ankit Satpute<sup>†§</sup>, Noah Gießing<sup>†</sup>, André Greiner-Petter<sup>§</sup>, Moritz Schubotz<sup>†</sup>, Olaf Teschke<sup>†</sup>, Akiko Aizawa<sup>§</sup>, Bela Gipp<sup>§</sup>. 2024. Can LLMs Master Math? Investigating Large Language Models on Math Stack Exchange. In Proceedings of The 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR 2024). ACM, New York, NY, USA, 5 pages. https://doi.org/XXXXXXXXXXXXX

#### **1** INTRODUCTION

Large Language Models (LLMs) have been very popular because of their ability to solve natural language tasks, sometimes with humanlike accuracy [1, 2, 15]. Pre-training and fine-tuning the models have led to a performance-winning approach in tasks such as translation, writing code, passing professional exams, etc [19]. The LLMs are used in academia and scientific research for knowledge extraction, ideas, processing, comparison, and across multiple disciplines [18]. LLms have also been successful in Question-Answering tasks (QA) in which they provide human-like answers to questions in natural language [20]. Evaluation of LLMs on QA has been especially useful in detecting how accurate LLMs are in generating answers and finding cases in which it could halllucinate [12, 14].

Given that mathematical content is prevalent in science, technology, engineering, and mathematics (STEM), it is imperative to evaluate the capacity of LLMs to engage with mathematical language. The challenges of LLMs with mathematics are manifold; mathematics, with its rigorous logic and abstract concepts, is communicated through a specialized language that mixes symbols and syntax in complex arrangements [24]. Unlike natural language, mathematical expressions rely on unmentioned rules and assumptions, demanding explicit knowledge and a level of precision. Mathematical reasoning still poses a sizable challenge to even the most significant language models [10, 30]. There exists an evaluation of LLMs in answering math questions in which the expected answer is straightforward numerical value [9], and an LLM-based solution [8] is the leading method on the performance scoreboard. In contrast, answers for proof or conceptual questions, which form a large part of the MSE, are not verifiable without human aid yet. However, the evaluation of models in generating answers for unorganized open questions has not been performed.

In this paper, we investigate using LLMs to answer open-ended questions (questions that cannot be answered with a yes or no response) from mathematics. We utilized questions from Math Stack Exchange (MSE), a platform dedicated to solving a wide array of mathematical questions posed by users, offering an ideal testing ground. We evaluate LLMs to find the most relevant answer. MSE encompasses questions that range from elementary level to advanced mathematics MSE questions require correctly applying

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

<sup>© 2024</sup> Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 978-1-4503-XXXX-X/18/06...\$15.00

mathematical principles and articulating complex reasoning clearly and understandably. By focusing on open-ended questions from MSE, we not only underscore the importance of these questions in fostering a deeper understanding of mathematical concepts but also provide a benchmark against which the progress of LLMs in mathematical reasoning can be measured. In this work, we set a base to explore the path forward for LLMs by evaluating them on generated answers and highlighting the challenges using a case study, thus bridging the gap between natural and mathematical language comprehension for LLMs. We make our code and findings publicly available for **research**<sup>1</sup>.

### 2 RELATED WORK

Research on Large Language Models (LLMs) has extended into mathematical problem solving, albeit primarily focused on preuniversity mathematics. Several datasets featuring high-schoollevel math questions and answers exist, such as those introduced by Mao et al. [17], Urrutia et al. [29], and Deb et al. [7]. Hendrycks et al. [9] introduced the MATH dataset with 12,500 challenging competition mathematics problems. Cobbe et al. [6] developed the GSM8K dataset containing a linguistically diverse collection of high school math problems. MathQA dataset by Amini et al. [3] contains 37k English multiple-choice math word problems covering multiple math domain categories by modeling operation programs corresponding to word problems in the AQuA dataset [13]. The availability of datasets is hindered as primarily physical records are used for writing question answers instead of machine-processable and computer-aided resources [5, 25].

Specialized LLMs have been developed for particular mathematical fields. For instance, Trinh et al. [28] released AlphaGeometry, a theorem prover for Euclidean plane geometry, which solved 25 out of 30 latest Olympiad-level problems within the time limit. To mitigate the issue of LLMs generating inaccurate information, Romera-Paredes[22] developed FunSearch, which combines a pretrained LLM with a systematic evaluator to outline verified problemsolving approaches. Moreover, LLMs equipped with integrated verification codes have demonstrated remarkable success on the MATH and GSM8K datasets, achieving accuracies near 100% in some cases [34]. The ToRA series [8], based on LLaMA-2 [27] and CodeLLaMA [23], represents the forefront of open-source models on the MATH dataset. ToRA models are based on LLaMA-2 [27] and CodeLLaMA [23] and were finetuned on a dataset of reasoning paths produced by GPT-4 [21] for the MATH and GSM-8 datasets. These models are fine-tuned on reasoning paths generated by GPT-4 for the MATH and GSM-8 datasets and self-verify their solutions by generating and executing code. However, leveraging executable code for Multiple-Selection Questions (MSE) potentially poses challenges due to the complexity of verifying reasoning steps and has not been evaluated so far. The MAmmoTH [31] family of models is trained on a dataset of chain-of-thought and program-of-thought rationales produced by GPT-4, but draws from a more diverse distribution of questions that were asked. The Llemma [4] family of models have instead been finetuned on a general corpus of mathrelated documents and is intended to be a generalist model, leaving open the option of finetuning to specific tasks.

## **3 DATASET**

Manual verification of answers to questions from the Mathematics Stack Exchange (MSE) is impractical due to the interdisciplinary nature of the questions and the expertise required to assess answer correctness. The ArqMATH competition dataset [16] offers a collection of MSE question-answer pairs. Task 1 from the competition's third edition focused on retrieving relevant answers from MSE for 78 undergraduate-level mathematics questions. The relevancy of the top-ranked answers, as determined by competing systems, was assessed by student evaluators, averaging 450 evaluated answers per topic. While automated evaluation is feasible by excluding answers without evaluation scores, student assessments have shown some inaccuracies [26].

## 4 METHODOLOGY

For our evaluation, we select 6 LLMs. ToRA [8], LLeMa [4], GPT-4 [21], and MAmmoTH [31] give their performance of existing MathQA datasets. We also consider MABOWDOR [33], the best-performing approach for ArqMATH Task-1. Last, we consider Mistral 7B [11], general purpose LLM that has shown sub-level performance with LLaMa, GPT-4 in prompt-based tasks.

We explore two scenarios for our experiments by employing LLMs to answer MSE questions. We perform a two-step procedure in the first scenario (Answer generation). First, we gave 78 questions and generated answers using selected LLMs except MABOWDOR. MABOWDOR uses BERT-based Desne Passage Retrieval, which can only generate embeddings. Second, we indexed the answer as embedding and all the other answers from ArqMATH and found the answer most similar to the generated answer from ArqMATH. In the second scenario (Question-Answer comparison), we use selected LLMs to generate embeddings of all potential answers from ArqMATH and generate embeddings of 78 questions as well. Ultimately, we find out which answer is most similar to the question.

## **5 EVALUATION**

This section presents the evaluation of two scenarios using metrics such as Mean Average Precision (mAP'), Precision@10 (P@10), normalized Discounted Cumulative Gain (nDCG'), and Binary Preference (BPref), with scores derived exclusively from evaluated Arq-MATH dataset answers.

#### 5.1 Answer generation

In this phase, answers were generated using the six selected models. These models' outputs served as queries for retrieval within the ArqMATH answer pool. For retrieval, we used DPR vector embeddings [33] and cosine similarity. Table 1 displays the comparative performance across all models. Additionally, we executed a DPR run for comparison, akin to the method utilized by MABOWDOR. The outcome reveals that models fine-tuned on mathematical tasks underperformed relative to the DPR benchmark. Among the three 7b models (Tora, LLeMa, and MAmmoTH), variations in their performance align with their results on the MATH dataset. Notably, increasing the model size of the top performer did not yield better results. The Mistral [11] model, despite being the lowest scorer on the MATH dataset among the models considered, delivered performance comparable to that of Tora-7b. This suggests that models

<sup>&</sup>lt;sup>1</sup>https://github.com/gipplab/LLM-Investig-MathStackExchange

Can LLMs Master Math? Investigating Large Language Models on Math Stack Exchange

Model	nDCG'	mAP'	p@10	BPref
DPR (Cocomae)	0.464	0.191	0.324	0.192
Tora-7b-Code	0.400	0.159	0.279	0.170
Tora-13b-Code	0.355	0.140	0.266	0.154
LLema-7b	0.194	0.069	0.157	0.092
MAmmoTH-7b-Coder	0.369	0.145	0.253	0.166
Mistral-7b-Instruct	0.396	0.155	0.267	0.166
GPT-4* (right trunc.)	0.486	0.219	0.374	0.225
GPT-4§ (left trunc.)	0.473	0.210	0.367	0.215

Table 1: Performance of Large Language Models in generating accurate answers.(\*: Answer truncated to initial 512 tokens, §:answer truncated to last 512 tokens)

	nDCG'	mAP'	p@10	BPref
MABOWDOR	0.132	0.063	0.330	0.088
Tora-7b-Code	0.095	0.037	0.149	0.064
Ada-002	0.121	0.049	0.248	0.069
GPT-4	0.153	0.079	0.321	0.092

 Table 2: Performance Answer retrieval given question as query embedding.

excelling on the MATH dataset might be overfitted to that particular task. Conversely, GPT-4 generated answers exhibited increased effectiveness over the DPR baseline, outperforming the current best approach on ArqMATH3 Task1, i.e., MABOWDOR [33] considering P@10.

#### 5.2 Question-Answer comparison

This evaluation segment focused on matching questions with the most relevant answers using embeddings. Given the models' original design for prompt-based answering, adjustments were necessary to facilitate embedding generation. To this end, we prefixed the prompt "This passage text means in one word: " and used the embedding of the last token's last hidden state. To guide the LLMs, we introduced three math-related example answers: First, "This passage:' $E[X] = \int_{-\infty}^{\infty} xf(x)dx$ ' means in one word:'Expectation'". Second, "This passage:' $(x - a)^2 + (y - b)^2 = r^2$ ' means in one word: 'Circle'". Third, "This passage:'The distance between the center of an ellipse and either of its two foci. ' means in one word:'Eccentricity'."" For reranking, we limited our focus to the top 10 results per query as determined by MABOWDOR [33].

Following the discussions from Zhong et al. [32], not all systems were assessed for answer reranking due to the underperformance of Tora-7b compared to the average ArqMATH approach. Given that LLeMa and MAmmoTH lagged behind Tora in the MATH and GSM benchmarks, their reranking efficacy was anticipated to be inferior. The analysis revealed Tora-7b's Precision@10 to be inferior to all runs depicted in Table 1. This indicates that comparison question and answer embeddings might not solve the problem of retrieving relevant answers.

## 6 CASE STUDY

This case study examines the performance of answer generation by GPT-4 for a selected question, conducted by two annotators with expertise in Mathematics and Computer Science. Both annotators



Figure 1: Frequency of differences in P@10 values of DPR and GPT-4 (P@ $10^{GPT-4}$  - P@ $10^{DPR}$ ).

I am currently taking MIT6.006, and I came across this problem on the problem set. Despite the fact I have learned Discrete Mathematics before, I have never seen such notation before, and I would like to know what it means and how it works, Thank you:

 $f_3(n) = \binom{n}{2}$ 

## Figure 2: Question which is correctly answered by GPT-4.

consulted at zbMATH Open<sup>2</sup>, a comprehensive multilingual abstracting and reviewing service in pure and applied mathematics. The focus was on comparing the retrieval performance of GPT-4 and Dense Passage Retrieval (DPR), particularly on questions where GPT-4 enhanced retrieval and where DPR outperformed GPT-4. The analysis, depicted in Figure 1, indicates that GPT-4 improved precision in 38 of the 78 evaluated Mathematics Stack Exchange (MSE) questions, suggesting its efficacy in generating relevant answers for open-ended math questions on MSE compared to models fine-tuned on various MATHQA datasets. The study also explores the reasons behind ToRA's underperformance on MSE questions despite its training on the MATH dataset.

## 6.1 GPT-4

We delve into two specific cases: one where GPT-4's answers improved retrieval performance in Precision@10 (P@10) and another where it had the opposite effect. These cases are outliers, with most topics showing P@10 variations between -0.1 and 0.2. We do not mention answers due to space limitations, but all the recorded answers for GPT-4<sup>3</sup> and all the other LLMs are available in the repository.

6.1.1 A.384: Retrieval Boost. The question shown in Figure 2, GPT-4's answer strongly shows increases P@10 (from 0.0 of DPR to 0.6 of GPT-4). The reason is that the first retrieved results by the DPR do not feature a binomial coefficient at all, but the first results of the GPT-4 retrieved result include at least an expansion of  $\binom{n}{2}$ . We

```
<sup>2</sup>https://zbmath.org/
```

#### SIGIR 2024, July 14-18, 2024, Washington D.C., USA

 $<sup>\</sup>label{eq:stars} ^3 https://github.com/gipplab/LLM-Investig-MathStackExchange/blob/main/topics-and-qrels/topics.arqmath-2022-gpt4-generated-answers.csv$ 

**Question.** Suppose that all the tangent lines of a regular plane curve pass through some fixed point. Prove that the curve is part of a straight line. Prove the same result if all the normal lines are parallel. I am working on differential geometry from the book by Pressley and I have a doubt in the solution of the above question whose (brief) solution is given by: **Solution:** We can assume that the curve  $\gamma$  is unit-speed and that the tangent lines all pass through the origin (by applying a translation to  $\gamma$ ). Then, there is a scalar $\lambda(t)$  such that  $\gamma'(t) = \lambda(t)\gamma(t)$  for all *t*. Then,  $\gamma'' = \lambda'\gamma + \lambda\gamma' = (\lambda' + \lambda^2)\gamma$ . Can anyone please explain me how does this line follow : " Then, there is a scalar  $\lambda(t)$  such that  $\gamma'(t) = \lambda(t)\gamma(t)$  for all *t*." Thanks in advance.

**Reason for worsened retrieval.** Imagine a car driving along the curve, and at the point of interest, the car hits an oil slick and shoots off in the straight line of its travel as it hits the point. The line of the car gives the tangent line at the point (provided the curve is differentiable at the point). You can look at cars sliding off coming from both directions to see the tangent line.

Figure 3: Question which is incorrectly answered by GPT-4. The reason for worsened retrieval shows generated answers irrelevant to the question.

observe that, without context, DPR cannot infer any meaning from the formula. Hence, GPT-4 shows a good contextual understanding of the ground truth formula.

6.1.2 A.337: Retrival Worsened Figure 3. P@10 decreases from 0.5 for the DPR run to 0.1 for GPT-4 for the following question (only the title is shown due to length): The answer given by GPT-4 misses the point since it does not explain how the specific line the poster asks about follows from the assumptions. we observe a pattern representing how GPT-4-generated answers can guide the retrieval system in the wrong direction. The retrieved answer only gives a general explanation of the concept of a tangent line to a curve. This corresponds to a portion of GPT-4's answer, which, tending to be verbose, also explains what a tangent line means. This shows that GPT-4 cannot answer the questions about complex interactions between mathematical concepts.

#### 6.2 Tora-7b-Code

The answers obtained by all the smaller models (basically every model except GPT-4) are of quite low quality. The mathematical models exhibit the typical behavior of smaller models in that the prompt format is misunderstood, and the answers lack coherence. Additionally, all models generate no output other than an end-ofsequence token for multiple questions. (6 in the case of Tora-7b-Code). In contrast, Mistral is much better at keeping a conversational tone than Tora. Additionally, the reasoning appears to be more structured. However, formulas are not written in latex format and are of lower quality, as apparent in the faulty input variables. For both systems, there are individual cases where retrieval is significantly boosted.

*6.2.1 A.309 - Tora-7b-Code boosts retrieval.* Compared to the following question, using the answer by Tora-7b-Code improves Precision@10 from 0.5 to 0.8. Instead of an actual answer, ToRA simulates

**Question:** I have a question regarding the number of solutions of a equation over a finite field  $\mathbb{F}_p$ . First of all, consider the equation  $x^3 = a$  over  $\mathbb{F}_p$ , where p is a prime such that  $p \equiv 2 \pmod{3}$ . The book that I'm currently reading says that this equation has exactly one solution in  $\mathbb{F}_p$  for every  $a \in \mathbb{F}_p$ , because gcd(3, p - 1) = 1, but the book does not prove this. Unfortunately, this doesn't convince me enough. Is there is a convincing elementary straightforward proof justifying why is this true?

Answe by ToRA Proof: Suppose to the contrary that there are more than one solution in  $\mathbb{F}_p$ . By Fermat's little theorem,  $a^{p-1} =$ 1, then *a* is congruent to 1 modulo p - 1. Since gcd(3, p - 1) = 1, there is a  $k \in \mathbb{F}_p$  such that  $3k \equiv 1 \mod p - 1$ , then  $a = (3k)^2 \equiv 1$ mod p - 1, which contradicts *a* being in  $\mathbb{F}_p$ . Thus, the equation  $x^3 = a$  has exactly one solution in  $\mathbb{F}_p$ .  $\blacksquare$  I don't really get the last part: "Since gcd(3, p - 1) = 1, there is a  $k \in \mathbb{F}_p$  such that  $3k \equiv 1$ mod p - 1". Could you please elaborate on this part? Comment: I suggest you look into [this] ([...]) and [this]([...]). The way to show that an equation has exactly one solution in a finite field is usually by using the Chinese remainder theorem and the fact that if *a* is a cube modulo *p*, then  $a^{p-1}$  is congruent to 1 modulo p-1. Comment: This actually is a question that came up in my intro to computation class and we couldn't find a simple proof for it. I am looking for a basic level proof. Comment: If  $p \equiv 2$ (mod 3), then gcd(p - 1, 3) = 1. By the Euclidean Algorithm, there is some  $k \in \mathbb{F}_p$  such that  $3k \equiv 1 \pmod{p-1}$ . Therefore,  $a \equiv k^2 \pmod{p-1}$ . This contradicts [...]

#### Figure 4: Answer generated by ToRA where it boosts precision.

a thread that is typically present at the MSE as seen in Figure 4. As an answer, it is quite incoherent and logically false.

## 7 CONCLUSION

In this study, we explored the capabilities of Large Language Models (LLMs) in addressing questions from the Mathematics Stack Exchange (MSE) through a two-fold approach. Initially, we assessed the performance of state-of-the-art language models, known for their proficiency on established Math Question Answer (MathQA) datasets, against the diverse and open-ended questions found on MSE. Our findings indicate that GPT-4, with an nDCG score of 0.48 and a Precision@10 (P@10) of 0.37, surpassed its peers and showed good results despite domain-specific training. GPT-4 outperformed the current best approach on ArqMATH3 Task1, considering P@10. At the same time, the rest exhibited relatively inferior results. Subsequently, we conducted a detailed case analysis to evaluate GPT-4's effectiveness in generating accurate answers, thereby shedding light on its potential and limitations. It was observed that LLMs previously performing well on MathQA datasets frequently produced inaccurate responses. Conversely, GPT-4 demonstrated a potential in formulating appropriate answers for straightforward mathematical inquiries. Nonetheless, its accuracy degraded with more intricate questions demanding specialized knowledge. For the benefit of the research community, we have publicly shared the answers generated by the LLMs and the code utilized in our experiments, enabling further investigation and analysis.

Can LLMs Master Math? Investigating Large Language Models on Math Stack Exchange

SIGIR 2024, July 14-18, 2024, Washington D.C., USA

## ACKNOWLEDGEMENTS

This work was funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) - 437179652, the Deutscher Akademischer Austauschdienst (DAAD, German Academic Exchange Service - 57515245), and the Lower Saxony Ministry of Science and Culture and the VW Foundation.

## REFERENCES

- [1] Marwah Alaofi, Luke Gallagher, Mark Sanderson, Falk Scholer, and Paul Thomas. 2023. Can Generative LLMs Create Query Variants for Test Collections? An Exploratory Study. In Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval (Taipei,Taiwan) (SIGIR '23). Association for Computing Machinery, New York, NY, USA, 1869–1873. https://doi.org/10.1145/3539618.3591960
- [2] Marwah Alaofi, Luke Gallagher, Mark Sanderson, Falk Scholer, and Paul Thomas. 2023. Can Generative LLMs Create Query Variants for Test Collections? An Exploratory Study. In Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval (Taipei,Taiwan) (SIGIR '23). Association for Computing Machinery, New York, NY, USA, 1869–1873. https://doi.org/10.1145/3539618.3591960
- [3] Aida Amini, Saadia Gabriel, Peter Lin, Rik Koncel-Kedziorski, Yejin Choi, and Hannaneh Hajishirzi. 2019. MathQA: Towards Interpretable Math Word Problem Solving with Operation-Based Formalisms. arXiv:1905.13319 [cs.CL]
- [4] Zhangir Azerbayev, Hailey Schoelkopf, Keiran Paster, Marco Dos Santos, Stephen McAleer, Albert Q. Jiang, Jia Deng, Stella Biderman, and Sean Welleck. 2023. Llemma: An Open Language Model For Mathematics. arXiv:2310.10631 [cs.CL]
- [5] Marco Beck, Isabel Beckenbach, Thomas Hartmann, Moritz Schubotz, and Olaf Teschke. 2020. Transforming Scanned zbMATH Volumes to LaTeX: Planning the Next Level Digitisation. *European Mathematical Society Magazine* 117 (2020), 49–52.
- [6] Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training Verifiers to Solve Math Word Problems. arXiv:2110.14168 [cs.LG]
- [7] Aniruddha Deb, Neeva Oza, Sarthak Singla, Dinesh Khandelwal, Dinesh Garg, and Parag Singla. 2023. Fill in the Blank: Exploring and Enhancing LLM Capabilities for Backward Reasoning in Math Word Problems. arXiv:2310.01991 [cs.CL]
- [8] Zhibin Gou, Zhihong Shao, Yeyun Gong, yelong shen, Yujiu Yang, Minlie Huang, Nan Duan, and Weizhu Chen. 2023. ToRA: A Tool-Integrated Reasoning Agent for Mathematical Problem Solving. arXiv:2309.17452 [cs.CL]
- [9] Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring Mathematical Problem Solving With the MATH Dataset. arXiv:2103.03874 [cs.LG]
- [10] Pengfei Hong, Deepanway Ghosal, Navonil Majumder, Somak Aditya, Rada Mihalcea, and Soujanya Poria. 2024. Stuck in the Quicksand of Numeracy, Far from AGI Summit: Evaluating LLMs' Mathematical Competency through Ontologyguided Perturbations. arXiv:2401.09395 [cs.CL]
- [11] Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7B. arXiv:2310.06825 [cs.CL]
- [12] Ehsan Kamalloo, Nouha Dziri, Charles Clarke, and Davood Rafiei. 2023. Evaluating Open-Domain Question Answering in the Era of Large Language Models. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (Eds.). Association for Computational Linguistics, Toronto, Canada, 5591–5606. https://doi.org/10.18653/v1/2023.acl-long.307
- [13] Wang Ling, Dani Yogatama, Chris Dyer, and Phil Blunsom. 2017. Program Induction by Rationale Generation : Learning to Solve and Explain Algebraic Word Problems. arXiv e-prints, Article arXiv:1705.04146 (May 2017), arXiv:1705.04146 pages. https://doi.org/10.48550/arXiv.1705.04146 arXiv:1705.04146 [cs.AI]
- [14] Yiheng Liu, Hao He, Tianle Han, Xu Zhang, Mengyuan Liu, Jiaming Tian, Yutong Zhang, Jiaqi Wang, Xiaohui Gao, Tianyang Zhong, Yi Pan, Shaochen Xu, Zihao Wu, Zhengliang Liu, Xin Zhang, Shu Zhang, Xintao Hu, Tuo Zhang, Ning Qiang, Tianming Liu, and Bao Ge. 2024. Understanding LLMs: A Comprehensive Overview from Training to Inference. arXiv:2401.02038 [cs.CL]
- [15] Spyros Makridakis, Fotios Petropoulos, and Yanfei Kang. 2023. Large Language Models: Their Success and Impact. *Forecasting* 5, 3 (2023), 536–549. https: //doi.org/10.3390/forecast5030030
- [16] Behrooz Mansouri, Anurag Agarwal, Douglas W. Oard, and Richard Zanibbi. 2022. Advancing Math-Aware Search: The ARQMath-3 Lab at CLEF 2022. In Advances in Information Retrieval, Matthias Hagen, Suzan Verberne, Craig Macdonald, Christin Seifert, Krisztian Balog, Kjetil Nørvåg, and Vinay Setty (Eds.). Springer

International Publishing, Cham, 408-415.

- [17] Yujun Mao, Yoon Kim, and Yilun Zhou. 2024. CHAMP: A Competition-level Dataset for Fine-Grained Analyses of LLMs' Mathematical Reasoning Capabilities. arXiv:2401.06961 [cs.CL]
- [18] Jesse G Meyer, Ryan J Urbanowicz, Patrick C N Martin, Karen O'Connor, Ruowang Li, Pei-Chen Peng, Tiffani J Bright, Nicholas Tatonetti, Kyoung Jae Won, Graciela Gonzalez-Hernandez, and Jason H Moore. 2023. ChatGPT and large language models in academia: opportunities and challenges. *BioData mining* 16, 1 (July 2023), 20. https://doi.org/10.1186/s13040-023-00339-9
- [19] Bonan Min, Hayley Ross, Elior Sulem, Amir Pouran Ben Veyseh, Thien Huu Nguyen, Oscar Sainz, Eneko Agirre, Ilana Heintz, and Dan Roth. 2023. Recent Advances in Natural Language Processing via Large Pre-trained Language Models: A Survey. ACM Comput. Surv. 56, 2, Article 30 (sep 2023), 40 pages. https: //doi.org/10.1145/3605943
- [20] Mahdi Namazifar, Alexandros Papangelis, Gokhan Tur, and Dilek Hakkani-Tür. 2021. Language Model is all You Need: Natural Language Understanding as Question Answering. In ICASSP 2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). 7803-7807. https://doi.org/10. 1109/ICASSP39728.2021.9413810
- [21] OpenAI. 2023. GPT-4 Technical Report. arXiv:2303.08774 [cs.CL]
- [22] Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M. Pawan Kumar, Emilien Dupont, Francisco J. R. Ruiz, Jordan S. Ellenberg, Pengming Wang, Omar Fawzi, and Push. 2024. Mathematical discoveries from program search with large language models. *Nature* 625, 7995 (January 2024), 468–475. https://doi.org/10.1038/s41586-023-06924-
- [23] Baptiste Rozière, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Romain Sauvestre, Tal Remez, Jérémy Rapin, Artyom Kozhevnikov, Ivan Evtimov, Joanna Bitton, Manish Bhatt, Cristian Canton Ferrer, Aaron Grattafiori, Wenhan Xiong, Alexandre Défossez, Jade Copet, Faisal Azhar, Hugo Touvron, Louis Martin, Nicolas Usunier, Thomas Scialom, and Gabriel Synnaeve. 2024. Code Llama: Open Foundation Models for Code. arXiv:2308.12950 [cs.CL]
- [24] Ankit Satpute, Andre Greiner-Petter, Noah Giessing, Isabel Beckenbach, Moritz Schubotz, Olaf Teschke, Akiko Aizawa, and Bela Gipp. 2024. Taxonomy of Mathematical Plagiarism. In 46th European Conference on Information Retrieval (ECIR). Springer, Glasgow, Scotland. https://doi.org/10.1007/978-3-031-56066-8\_2
- [25] Ankit Satpute, Andre Greiner-Petter, Moritz Schubotz, Norman Meuschke, Akiko Aizawa, Olaf Teschke, and Bela Gipp. 2023. TEIMMA: The First Content Reuse Annotator for Text, Images, and Math. In 2023 ACM/IEEE Joint Conference on Digital Libraries (JCDL). 271–273. https://doi.org/10.1109/JCDL57899.2023.00056
- [26] Philipp Scharpf, Moritz Schubotz, Andre Greiner-Petter, Malte Ostendorff, Olaf Teschke, and Bela Gipp. 2020. ARQMath Lab: An Incubator for Semantic Formula Search in zbMATH Open? arXiv:2012.02413 [cs.DL]
- [27] LLaMa-2 Team. 2023. Llama 2: Open Foundation and Fine-Tuned Chat Models. arXiv:2307.09288 [cs.CL]
- [28] Trieu H Trinh, Yuhuai Wu, Quoc V Le, He He, and Thang Luong. 2024. Solving olympiad geometry without human demonstrations. *Nature* 625, 7995 (January 2024), 476–482. https://doi.org/10.1038/s41586-023-06747-5
- [29] Felipe Urrutia and Roberto Araya. 2023. Who's the Best Detective? LLMs vs. MLs in Detecting Incoherent Fourth Grade Math Answers. arXiv:2304.11257 [cs.CL]
- [30] Felipe Urrutia and Roberto Araya. 2024. Who's the Best Detective? Large Language Models vs. Traditional Machine Learning in Detecting Incoherent Fourth Grade Math Answers. *Journal of Educational Computing Research* 61, 8 (2024), 187-218. https://doi.org/10.1177/07356331231191174 arXiv:https://doi.org/10.1177/07356331231191174
- [31] Xiang Yue, Xingwei Qu, Ge Zhang, Yao Fu, Wenhao Huang, Huan Sun, Yu Su, and Wenhu Chen. 2023. MAmmoTH: Building Math Generalist Models through Hybrid Instruction Tuning. arXiv:2309.05653 [cs.CL]
- [32] Wei Zhong. 2023. Effective Math-Aware Ad-Hoc Retrieval based on Structure Search and Semantic Similarities. Ph. D. Dissertation. http://hdl.handle.net/10012/19865
- [33] Wei Zhong, Sheng-Chieh Lin, Jheng-Hong Yang, and Jimmy Lin. 2023. One Blade for One Purpose: Advancing Math Information Retrieval Using Hybrid Search. In Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval (<conf-loc>, <city>Taipei</city>, <country>Taiwan</country>, </conf-loc>) (SIGIR '23). Association for Computing Machinery, New York, NY, USA, 141–151. https://doi.org/10.1145/3539618.3591746
- [34] Aojun Zhou, Ke Wang, Zimu Lu, Weikang Shi, Sichun Luo, Zipeng Qin, Shaoqing Lu, Anya Jia, Linqi Song, Mingjie Zhan, and Hongsheng Li. 2023. Solving Challenging Math Word Problems Using GPT-4 Code Interpreter with Code-based Self-Verification. arXiv:2308.07921 [cs.CL]