# Forecasting with Neuro-Dynamic Programming

Pedro Afonso Fernandes<sup>∗</sup>

Universidade Católica Portuguesa Católica Lisbon School of Business & Economics Católica Lisbon Research Unit in Business  $&$  Economics (CUBE) Católica Lisbon Forecasting Lab (NECEP)

Portugal

April 8, 2024

#### Abstract

Economic forecasting is concerned with the estimation of some variable like gross domestic product (GDP) in the next period given a set of variables that describes the current situation or state of the economy, including industrial production, retail trade turnover or economic confidence. Neuro-dynamic programming (NDP) provides tools to deal with forecasting and other sequential problems with such high-dimensional states spaces. Whereas conventional forecasting methods penalises the difference (or loss) between predicted and actual outcomes, NDP favours the difference between temporally successive predictions, following an interactive and trial-and-error approach. Past data provides a guidance to train the models, but in a different way from ordinary least squares (OLS) and other supervised learning methods, signalling the adjustment costs between sequential states. We found that it is possible to train a GDP forecasting model with data concerned with other countries that performs better than models trained with past data from the tested country (Portugal). In addition, we found that non-linear architectures to approximate the value function of a sequential problem, namely, neural networks can perform better than a simple linear architecture, lowering the out-of-sample mean absolute forecast error (MAE) by 32% from an OLS model.

Keywords: time series; forecasting; neuro-dynamic programming; reinforcement learning; temporal differences. JEL codes: C22; C45; C52; C53.

<sup>\*</sup>ORCID: <https://orcid.org/0000-0001-5762-5157>. Correspondence: Universidade Católica Portuguesa, Católica Lisbon School of Business & Economics, Palma de Cima, Building 5, 4th floor, Room 5430, 1649-023 Lisboa, Portugal. Email: paf@ucp.pt. URL: <https://paf.com.pt>.

## 1 Introduction

Economic forecasting is concerned with the estimation of some variable of interest like gross domestic product (GDP) in the next period given a set of variables that describes the current situation or state of the economy. This set can include known values of the variable of interest or other covariates that describe the environment faced by economic agents. Forecasting is then finding the optimal value of the parameters of some (typically) linear model by minimising a loss function that measures the difference between the observed and the predicted values of the variable of interest.

Thus, forecasting is concerned with sequential problems where some cost is minimised given the current and future states of the economy. Dynamic programming (DP) is concerned with this kind of multistage decision processes that follow the principle of optimality, that is, whatever the initial state and initial decision are, the remaining decisions must constitute an optimal policy with regard to the state resulting form the first decision [\(Bellman and Dreyfus, 1962](#page-9-0)). Here, the state is a finite-dimensional object that, from the point of view of current and future costs, completely summarises the current situation faced by economic agents or decision makers [\(Ljungqvist and Sargent, 2018](#page-9-1), section 1.4).

States must be kept in low dimension in order to solve optimally the functional (Bellman) equation of a dynamic problem. Nevertheless, DP has a wide range of applications, namely, in economics following the dynamic recursive theories formulated by [Stockey and Lucas \(1989](#page-10-0)) and [Ljungqvist and Sargent \(2018](#page-9-1)). A good example is the savings problem where a representative household maximises the expected utility of the current and future consumption subject to a sequence of budget constraints that relates labour income, financial wealth and consumption. The state space of this model could be kept in a low discrete dimension, but complex models may require an approximation to the return function that expresses the optimal long run value of some state using, namely, quadratic forms, resulting in the so-called optimal linear regulator problem. Even these models require point estimates of their parameters [\(Mannor et al.](#page-9-2), [2007](#page-9-2)), which constitute a practical limitation of DP, namely, in the field of economics.

Originally formulated by [Bertsekas and Tsitsiklis \(1996](#page-9-3)), neuro-dynamic programming (NDP), also known as approximate DP or reinforcement learning (in machine learning literature), provides a set of methods and tools to deal with high-dimensional state spaces and challenging DP problems. It can deal also with problems where a mathematical model is unavailable or hard to construct using model-free methods. Thus, NDP is primarily concerned with approximating the return function of a dynamic problem using linear or nonlinear functional forms. Within this framework, optimality is relaxed in order to solve complex and computationally intensive DP problems, where regular approaches are not applicable or are too costly [\(Bertsekas](#page-9-4), [2011](#page-9-4)).

Simultaneously, NDP makes use of ideas from artificial intelligence involving simulationbased algorithms and neural networks [\(van Roy et al., 1997](#page-10-1)). Reinforcement learning (RL) algorithms learn what to do so as to maximise some reward (or minimise some cost), having in mind a long-term objective (Szepesvári, [2010](#page-10-2)). The learner is not told which actions to take, but instead must discover which actions yield the most reward (or least cost) by trying them in an interactive and trial-and-error process [\(Sutton and Barto, 2018](#page-10-3)).

The objective of this paper is to test the viability of using NDP/RL methods and tools to approximate the GDP level with the state of the economy described by several variables, possibly using big data. These variables include readily available data that can be used to forecast GDP in the current quarter like industrial production, retail sales, exports or economic confidence. Past data concerned with GDP provides a guidance to train the models, but in a different way from ordinary least squares and other supervised learning methods, signalling the adjustment costs between sequential states. Our models were trained using quarterly data from European countries and tested in Portugal. We found that a neural network architecture with tensor product can perform quite well, namely, during COVID-19 times.

The paper is organised as follow: firstly, we provide a review of selected, relevant literature

in section [2;](#page-2-0) then, in section [3,](#page-3-0) we describe succinctly two approaches to train NDP models using linear and nonlinear architectures, as well as the dynamic model here adopted to forecast GDP; a brief description of the data set and its treatment is made in section [4;](#page-5-0) section [5](#page-6-0) presents the main findings, followed by a final conclusion in section [6.](#page-7-0)

### <span id="page-2-0"></span>2 Literature

This paper covers a topic with contributions from the fields of forecasting, economics, dynamic programming and reinforcement learning. Here we track only the most important references.

Dynamic programming has a wide range of applications in economics including the savings problem, economic growth, job search, business cycles, olipoly equilibrium or recursive contracts [\(Ljungqvist and Sargent, 2018](#page-9-1)). Particularly important for the present research is the problem of a competitive firm that maximises the inter-temporal value of its production with an adjustment cost of the rate of output: in order to obtain a greater return (or value) in the future, the firm must invest (or set aside) a part of its current production incurring a quadratic cost, following a scheme like the one originally proposed by [Lucas and Prescott \(1971](#page-9-5)). The trade-off between immediate costs and future returns gives the firm the incentive to forecast the output market price as far as the investment (or change of output) decision is concerned.

This problem can be solved optimally by assuming that the firm's return function is quadratic on the state variables, namely, the current level of output. However, we have to know in advance the values of the model's parameters to get that kind of solution. Here, our goal is to estimate those parameters directly from data following the temporal difference (TD) method proposed by [Sutton \(1988](#page-10-4)). Whereas conventional forecasting methods penalises the difference (or loss) between predicted and actual outcomes, that method is guided by the difference between temporally successive predictions.

Our goal is also concerned with using other architectures than linear-quadratic ones for the return function, namely, neural networks. The approximation of Bellman's value and policy functions with neural networks was originally proposed by [Bertsekas and Tsitsiklis \(1996](#page-9-3)) with lately developments described by [Bertsekas \(2011](#page-9-4), [2020](#page-9-6)). Two broad approaches are available in neuro-dynamic programming (NDP): the direct estimation of the parameters using temporal differences or its indirect estimation using a least squares scheme on a projected Bellman equation.

NDP applications include parking, maintenance and repair [\(Bertsekas and Tsitsiklis, 1996](#page-9-3)), retailer inventory management [\(van Roy et al.](#page-10-1), [1997](#page-10-1)) and dynamic catalog mailing policies [\(Mannor et al.](#page-9-2), [2007](#page-9-2)). In addition, NDP is being applied with great success in machines that play masterly complex games like backgammon [\(Tesauro](#page-10-5), [1995](#page-10-5)), Go [\(Silver et al.](#page-10-6), [2016](#page-10-6)) or chess [\(Thrun, 1995](#page-10-7); [McIlroy-Young et al.](#page-10-8), [2020](#page-10-8)). Most advanced algorithms attained a superhuman performance by tabula rasa learning from games of self-play [\(Silver et al.](#page-10-9), [2017\)](#page-10-9). Economic interpretations of algorithms that play board games can be found in [Igami \(2020](#page-9-7)).

The approximation of functions with neural networks is a recent research topic in economics with a seminal contribution in [Duffy and McNelis \(2001](#page-9-8)) who approximated the conditional expectation function in the Euler equation of a stochastic growth model. In fact, heterogeneousagents models and other high-dimensional problems cannot be solved using classic dynamic programming due to the "curse of dimensionality" [\(Bellman and Dreyfus](#page-9-0), [1962](#page-9-0)). In this scope, [Maliar et al. \(2021](#page-9-9)) introduce a unified deep learning method that solves complex dynamic economic models by casting them into nonlinear regression equations. They use neural networks to perform model reduction and to handle multicollinearity. [Kahou et al. \(2021](#page-9-10)) propose a new method for solving high-dimensional dynamic programming problems and recursive competitive equilibria with a large number of heterogeneous agents using deep learning and exploring symmetry. [Kase et al. \(2022\)](#page-9-11) take advantage of the scalability of neural networks to estimate nonlinear heterogeneous-agents models with likelihood methods. [Azinovic et al. \(2022\)](#page-8-0) uses neural net-

works to compute approximate functional rational expectations equilibria of economic models featuring a significant amount of heterogeneity, uncertainty and binding restrictions, namely, a large-scale overlapping generations (OLG) model.

In a broad sense, this paper is about the application of reinforcement learning (RL) methods to economic forecasting. RL is founded on learning from interaction with the environment [\(Sutton and Barto](#page-10-3), [2018\)](#page-10-3). Guided by an immediate reward (or cost), an agent may find an optimal long-run policy by exploit the most advantageous actions and explore new, potentially better actions. RL develops the optimal control (or DP) framework by introducing computer science techniques like deep neural networks. Complete surveys of RL applications in economics and finance can be found in [Charpentier et al. \(2021\)](#page-9-12) and [Meng and Khushi \(2019](#page-10-10)).

The use of NDP/RL to forecast GDP is a relatively new topic in literature, we few applications such the ensembling approach of [Li et al. \(2022](#page-9-13)) that combine three deep neural networks to forecast the regional GDP of China.

### <span id="page-3-0"></span>3 Framework

#### 3.1 Dynamic programming

Dynamic programming is concerned with sequential problems where the state of a discrete-time dynamic system evolves according to given transition probabilities that depend on some control variable  $u$  [\(Bertsekas and Tsitsiklis](#page-9-3), [1996,](#page-9-3) chapter 1). Given an initial state  $i$ , we choose the control u to minimise either the immediate cost  $g(i, u, j)$  associated with the transition from i to the next state j or the optimal cost-to-go of j, denoted by  $J^*(j)$ , which is the expected cost of all subsequent periods starting from  $j$ . The objective of DP is to calculate the *optimal*  $cost-to-go function J^*$  by iterating on the following Bellman equation:

<span id="page-3-1"></span>
$$
J^*(i) = \min_{u} E\left[g(i, u, j) + \alpha J^*(j)|i, u\right],
$$
\n(1)

for all i, where  $\alpha \in (0,1)$  is a discount factor. The time-invariant rule  $\mu(i)$  that maps each state i to the optimal control u that attains the minimum in equation [\(1\)](#page-3-1) is called a policy or feedback control policy. It can be computed either simultaneously with the optimal cost-to-go  $J^*$  or in real time by minimising the right-and-side of the Bellman equation.

#### 3.2 Approximate dynamic programming

In many application, the number of states and controls becomes prohibitively large in terms of computing time. Neuro-dynamic or approximate dynamic programming deals with this "curse of dimensionality" [\(Bellman and Dreyfus](#page-9-0), [1962](#page-9-0)) by approximating the optimal cost-to-go function  $J^*$  through a neural network or linear architecture  $\tilde{\tilde{J}}(i,r)$ , where r is a parameter/weight vector [\(Bertsekas and Tsitsiklis](#page-9-3), [1996](#page-9-3); [Bertsekas](#page-9-4), [2011](#page-9-4)). Once  $r$  is determined, it yields a sub-optimal control at any state i through the one-step look-ahead minimisation:

$$
\tilde{\mu}(i) = \arg\min_{u} E\left[g(i, u, j) + \alpha \tilde{J}(j, r)|i, u\right].
$$
\n(2)

The function  $\tilde{J}$  is called the *scoring function* or *approximate cost-to-go function*, and the value  $J(j, r)$  is called the *score* or *approximate cost-to-go* of state j [\(Bertsekas and Tsitsiklis](#page-9-3), [1996\)](#page-9-3). It is a *compact representation* in the sense that it reduces the description of  $j$  to a few relevant features whose weights are the parameters r. For example, in computer chess, the state is the current board position described by features like the midgame/endgame material point values, material imbalances, mobility and trapped pieces, pawn structure, king safety, outposts, bishop pair, and other evaluation patterns [\(Bertsekas](#page-9-4), [2011](#page-9-4); [Silver et al.](#page-10-9), [2017\)](#page-10-9).

#### <span id="page-4-3"></span>3.3 Neural network

The scoring function  $\tilde{J}$  can be approximated by a nonlinear architecture, namely, a *feedforward* neural network (FFNN). Also know as deep neural network, artificial neural network or multilayer perceptron, it is a simple model where several linear combinations of inputs are passed through nonlinear activation functions called nodes [\(Taddy, 2019](#page-10-11), chapter 10). A set of nodes is called a layer, and the output of ones layer's node becomes the input of the next layer in multilayer architectures. Finally, the output of the last layer is combined linearly to produce a cost-to-go.

For a state i represented by a *feature vector*  $x(i) = (x_1(i), \ldots, x_q(i))'$ , the first layer of a FFNN is composed by s nodes  $h_k(i)$  such that [\(Bertsekas and Tsitsiklis](#page-9-3), [1996,](#page-9-3) chapter 3):

<span id="page-4-0"></span>
$$
h_k(i) = \sigma\left(\sum_{l=1}^q r_{kl} x_l(i)\right), k = 1, \dots, s,
$$
\n(3)

where  $\sigma(\cdot)$  is a nonlinear *activation function* specified in advance. Early implementations of FFNN typically favoured the logistic function:

$$
\sigma(\xi) = \frac{1}{1 + e^{-\xi}} = \frac{e^{\xi}}{e^{\xi} + 1}.
$$
\n(4)

Nowadays, the most common activation function is the ReLU (rectified linear unit):

<span id="page-4-2"></span>
$$
\sigma(\xi) = \max(0, \xi),\tag{5}
$$

because it can be computed and stored more efficiently than the logistic function and other options. The nonlinear nature of the activation function is fundamental to capture complex nonlinearities and interaction effects [\(James et al., 2021](#page-9-14), chapter 10).

The nodes given by equation [\(3\)](#page-4-0) can be used as input of a second layer whose output can be passed to a third layer, and so on. Following [Bertsekas and](#page-9-3) Tsitsiklis [\(1996,](#page-9-3) chapter 3), we adopt a FFNN with a single layer whose final output is given by

$$
\tilde{J}(i,r) = \sum_{k=1}^{s} r_k h_k(i) = \sum_{k=1}^{s} r_k \sigma \left( \sum_{l=1}^{q} r_{kl} x_l(i) \right),\tag{6}
$$

where the parameter vector r is composed by the weights  $r_k$  and  $r_{kl}$  for  $k = 1, \ldots, s$  and  $l = 1, \ldots, q$ . These coefficients can be estimated from training data using temporal difference learning (TD). Introduced by [Sutton \(1988](#page-10-4)), TD deals with multi-step prediction problems where a future outcome is predicted by updating the *weights* of the model from the changes or errors in successive predictions rather than from the overall error between predictions and the final outcome. Thus, our simple  $FFNN$  can be trained using the algorithm [1](#page-4-1) (Szepesvári, 2010, section 2.2) [\(Bertsekas](#page-9-4), [2011](#page-9-4), section 6.2):

#### <span id="page-4-1"></span>Algorithm 1 TD(0) with nonlinear cost-to-go approximation (neural network)

1:  $\delta \leftarrow \tilde{J}(i,r) - \alpha \tilde{J}(j,r) - g(i,u,j)$ 2:  $r_k \leftarrow r_k - \gamma \delta h_k(i)$ 3:  $r_{kl} \leftarrow r_{kl} - \gamma \delta r_k \nabla_{r_{kl}} h_k(i)$ 4: return r

where  $\gamma$  is a small non-negative number, called *step-size*, that decreases with time, and the gradient  $\nabla_{rkl}h_k(i)$  is the partial derivative of the node k with respect to the weight  $r_{kl}$ . Using the ReLU function [\(5\)](#page-4-2), this derivative is simply  $x_l(i)$  if the weighted sum of features  $\sum_{l=1}^q r_{kl}x_l(i)$ is positive and zero otherwise. The features  $x<sub>l</sub>(i)$  can be constructed from states individual components or attributes using the tensor product (Szepesvári, 2010, section 2.2).

#### <span id="page-5-3"></span>3.4 Linear architecture

Alternatively, the approximate cost-to-go function  $\tilde{J}$  may adopt the linear form

$$
\tilde{J}(i,r) = \sum_{l=1}^{q} r_l x_l(i),\tag{7}
$$

where  $r = (r_1, \ldots, r_q)'$  and the features  $x_l(i)$  are *basis functions* because they form a linear basis of the set of approximate functions [\(Sutton and Barto, 2018,](#page-10-3) section 9.4). The weights  $r_l$  can be estimated with temporal differences using the algorithm [2.](#page-5-1)

<span id="page-5-1"></span>Algorithm 2 TD(0) with linear cost-to-go approximation

1:  $\delta \leftarrow \tilde{J}(i,r) - \alpha \tilde{J}(j,r) - g(i,u,j)$ 2:  $r_l \leftarrow r_l - \gamma \delta x_l(i)$ 3: return r

#### 3.5 Dynamic model

In our simple model, output (GDP) is adjusted with a quadratic cost. The objective of a social planner is to minimise this immediate cost, as well as the future costs of adjustment. Thus, the cost-to-go function J reflects the adjustment path of the economy as a function of several state variables that describe the economic environment. The Bellman equation of the model is

<span id="page-5-2"></span>
$$
J(i) = \min_{u} E\left[u^2 + \alpha J(j)\right],\tag{8}
$$

where  $i$  is the state of the economy in the current quarter,  $u$  is the quarter-over-quarter change of output and  $j$  is the state in the next quarter. This model is basically a simplified version of the competitive firm model of [Ljungqvist and Sargent \(2018](#page-9-1), section 7.2) adapted from [Lucas and Prescott \(1971](#page-9-5)).

### <span id="page-5-0"></span>4 Data

The cost-to-go function  $J$  in equation  $(8)$  was approximated using the two architectures and algorithms described in sections [3.3](#page-4-3) and [3.4.](#page-5-3) NDP/RL algorithms can converge slowly, thus requiring long batches with several observations to produce accurate approximations. Economic time series are typically too short for that purpose. Anyway, it is possible to consider multiple series concerned with several countries. Thus, we trained our models with a panel of 26 countries from the European Union, reserving for testing the data concerned with Portugal. Data covered the period from the first quarter of 2000 to the fourth quarter of 2023 with 95 transitions between adjacent quarters for each country, and a total of 2470 records in the training data set.

Besides GDP, data covered the state variables indicated in table [1](#page-6-1) that describe the economic environment in each country, covering production and turnover (industry, construction and services), international trade (exports and imports) and the confidence of economic agents measured by the Economic Sentiment Indicator (ESI). These variables are readily available and can be used to assess the current situation of the economy right before the dissemination of official macroeconomic aggregates from the national quarterly accounts (NQA), supporting a nowcasting exercise [\(Baffigi et al.](#page-8-1), [2004;](#page-8-1) [Giannone et al., 2008](#page-9-15)).

Each observation was regularised by subtracting the minimum value and dividing by the range, that is, the difference between the maximum and minimum values. This operation was performed for each indicator individually and for each country separately in order to assure the comparability between records. Regularisation is a critical procedure to estimate, namely, the neural network weights using the temporal difference algorithm [1.](#page-4-1)

<span id="page-6-1"></span>

Data concerned with Portugal covers also the period  $2000Q1-2023Q4$ . The observations up to 2014 (first 15 years) were used to train a benchmark model, that is, an ordinary least squares (OLS) regression of GDP on the variables listed in table [1.](#page-6-1) Then, the predictive performance of the models was tested using the data for Portugal from the first quarter of 2015 to the fourth quarter of 2023.

## <span id="page-6-0"></span>5 Findings

Table [2](#page-6-2) presents the out-of-sample (OOS) mean absolute error (MAE) and root mean squared error (RMSE) for the models previously described, that is, a linear regression (benchmark), a neural network and a linear architecture, both estimated with temporal differences. The response was the regularised Portuguese GDP and the OOS errors were calculated for the testing period between the first quarter of 2015 and the fourth quarter of 2023.

<span id="page-6-2"></span>

Model		MAE RMSE
Linear regression (OLS)		0.0661 0.0832
$TD(0)$ with neural network		$0.0453$ $0.0597$
$TD(0)$ with linear architecture $0.1070$ 0.1281		

Table 2: OOS errors by model (regularised GDP level, Portugal, 2015Q1-2023Q4)

Firstly, we found that an OLS model of GDP level on industrial production, construction output, retail trade, international trade and economic sentiment can perform quite well. In fact, this model provides a MAE of only 6.6% of the range between the maximum and minimum levels of GDP for the testing period. The RMSE is about 8.3% of that range.

Secondly, a neural network trained with data for the European Union countries (excluding Portugal) can perform even better, lowering that MAE by 32% to 4.5% and the RMSE by 28% to 5.9%. In fact, the non-linear nature of this architecture might capture well the dramatic drop in GDP occurred during the "Great Lockdown" of the spring of 2020, as suggested by figure [1,](#page-7-1) lowering the OOS errors for the testing period. In addition, figure [2](#page-7-2) reveals that TD with neural network was quite effective during the COVID-19 times (since 2020) in mitigating the cumulative absolute OOS error.

Besides, the neural network performs better than a linear architecture estimated with temporal differences too. The last model is the worst with a MAE of 10.7% of the range between the maximum and minimum levels of GDP, and a RMSE of 12.8% of that range. Thus, a simple least squares model estimated with a restricted dataset (for Portugal) can perform better than a linear model estimated with TD over a full dataset (for the EU countries except Portugal), but so well than a neural network trained with the last dataset.



Figure 1: Forecasts of the regularised GDP level by different models and testing data (Portugal, 2015Q1-2023Q4)

<span id="page-7-1"></span>

<span id="page-7-2"></span><span id="page-7-0"></span>Figure 2: Cumulative absolute OOS error of the regularised GDP level by model (Portugal, 2015Q1-2023Q4)

## 6 Conclusion

NDP/RL algorithms proved to achieve remarkable results using generic or even simulated data, not directly connected with the predicted object, namely in the field of board games. Here, we found that it is possible to train a model with data concerned with other countries that performs quite well, even better than models trained with past data from the tested country. In fact, time series could be too short to train effectively forecasting models, and some advantage may be obtained by using panel data from other countries with algorithms that learn by trial-and-error, guided by the change of output as an adjustment cost.

In addition, we found that non-linear architectures to approximate the value function of a sequential problem, namely, neural networks with tensor product can perform better than a simple linear architecture as far as the prediction of GDP is concerned, despite the good achievement obtained by a linear model estimated with ordinary least squares using past data for the region of interest.

## Acknowledgments

This work was supported by Fundação para a Ciência e Tecnologia (FCT), Lisbon, Portugal under a doctorate auxiliary researcher grant with the reference CUBE-PhD-CEEC/1 from Católica Lisbon Research Unit in Business & Economics (UID/GES/00407/2020).

# Abbreviations

The following abbreviations are used in this paper:

- DP Dynamic Programming
- EC European Commission
- ESI Economic Sentiment Indicator
- FCT Portuguese Foundation for Science and Technology
- FFNN Feedforward Neural Network
- GDP Gross Domestic Product
- MAE Mean Absolute Error
- NDP Neuro-Dynamic Programming
- NQA National Quarterly Accounts
- OLG Overlapping Generations
- OLS Ordinary Least Squares
- OOS Out-Of-Sample
- ReLU Rectified Linear Unit
- RL Reinforcement Learning
- RMSE Root Mean Squared Error
- TD Temporal Difference

# References

- <span id="page-8-0"></span>M. Azinovic, L. Gaegauf, and S. Scheidegger. Deep Equilibrium Nets. International Economic Review, 63(4):1471–1525, 11 2022. ISSN 0020-6598. doi: 10.1111/iere.12575.
- <span id="page-8-1"></span>A. Baffigi, R. Golinelli, and G. Parigi. Bridge models to forecast the euro area GDP. International Journal of Forecasting, 20(3):447–460, 7 2004. ISSN 01692070. doi: 10.1016/ S0169-2070(03)00067-0.
- <span id="page-9-0"></span>R. E. Bellman and S. E. Dreyfus. Applied Dynamic Programming. Princeton University Press, Princeton, N.J., 1962. URL <https://www.rand.org/pubs/reports/R352.html>.
- <span id="page-9-4"></span>D. P. Bertsekas. Approximate Dynamic Programming (online chapter). In Dynamic Programming and Optimal Control, Volume II, chapter 6. Athena Scientific, Belmont, Massachusetts, 3rd edition, 2011. URL <https://www.mit.edu/~dimitrib/dpbook.html>.
- <span id="page-9-6"></span>D. P. Bertsekas. Rollout, Policy Iteration, and Distributed Reinforcement Learning. Athena Scientific, Belmont, Massachusetts, 2020.
- <span id="page-9-3"></span>D. P. Bertsekas and J. N. Tsitsiklis. Neuro-Dynamic Programming. Athena Scientific, Belmont, Massachusetts, 1996.
- <span id="page-9-12"></span>A. Charpentier, R. Élie, and C. Remlinger. Reinforcement Learning in Economics and Finance. Computational Economics, 2021. ISSN 15729974. doi: 10.1007/s10614-021-10119-4.
- <span id="page-9-8"></span>J. Duffy and P. D. McNelis. Approximating and simulating the stochastic growth model: Parameterized expectations, neural networks, and the genetic algorithm. Journal of Economic Dynamics and Control, 25(9):1273–1303, 9 2001. ISSN 01651889. doi: 10.1016/S0165-1889(99) 00077-9.
- <span id="page-9-15"></span>D. Giannone, L. Reichlin, and D. Small. Nowcasting: The real-time informational content of macroeconomic data. Journal of Monetary Economics, 55:665–676, 2008.
- <span id="page-9-7"></span>M. Igami. Artificial Intelligence as Structural Estimation: Economic Interpretations of Deep Blue, Bonanza, and AlphaGo. The Econometrics Journal, 23(3):1–24, 2020. doi: 10.1093/ ectj/utaa005.
- <span id="page-9-14"></span>G. James, D. Witten, T. Hastie, and R. Tibshirani. An Introduction to Statistical Learning with Applications in R. Springer, 2nd edition, 2021. URL <https://www.statlearning.com/>.
- <span id="page-9-10"></span>M. E. Kahou, J. Fern´andez-Villaverde, J. Perla, and A. Sood. Exploiting Symmetry in High-Dimensional Dynamic Programming. NBER Working Paper, 28981:1–52, 7 2021. doi: 10. 3386/w28981.
- <span id="page-9-11"></span>H. Kase, L. Melosi, and M. Rottner. Estimating Nonlinear Heterogeneous Agents Models with Neural Networks. Federal Reserve Bank of Chicago Working Paper, 26:1–55, 2022. doi: 10.21033/wp-2022-26.
- <span id="page-9-13"></span>Q. Li, C. Yu, and G. Yan. A New Multipredictor Ensemble Decision Framework Based on Deep Reinforcement Learning for Regional GDP Prediction. IEEE Access, 10:45266–45279, 2022. ISSN 2169-3536. doi: 10.1109/ACCESS.2022.3170905.
- <span id="page-9-1"></span>L. Ljungqvist and T. J. Sargent. Recursive Macroeconomic Theory. The MIT Press, Cambridge, MA, 4th edition, 2018.
- <span id="page-9-5"></span>R. E. Lucas and E. C. Prescott. Investment under Uncertainty. Econometrica, 39(5):659–681, 1971.
- <span id="page-9-9"></span>L. Maliar, S. Maliar, and P. Winant. Deep learning for solving dynamic economic models. Journal of Monetary Economics, 122:76–101, 9 2021. ISSN 03043932. doi: 10.1016/j.jmoneco.2021. 07.004.
- <span id="page-9-2"></span>S. Mannor, D. Simester, P. Sun, and J. N. Tsitsiklis. Bias and Variance Approximation in Value Function Estimates. Management Science, 53(2):308–322, 2 2007. ISSN 0025-1909. doi: 10.1287/mnsc.1060.0614.
- <span id="page-10-8"></span>R. McIlroy-Young, S. Sen, J. Kleinberg, and A. Anderson. Aligning Superhuman AI with Human Behavior: Chess as a Model System. arXiv preprint, 6 2020. doi: 10.1145/3394486.3403219.
- <span id="page-10-10"></span>T. L. Meng and M. Khushi. Reinforcement Learning in Financial Markets. Data, 4(3):110, 7 2019. ISSN 2306-5729. doi: 10.3390/data4030110.
- <span id="page-10-6"></span>D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. van den Driessche, J. Schrittwieser, I. Antonoglou, V. Panneershelvam, M. Lanctot, S. Dieleman, D. Grewe, J. Nham, N. Kalchbrenner, I. Sutskever, T. Lillicrap, M. Leach, K. Kavukcuoglu, T. Graepel, and D. Hassabis. Mastering the game of Go with deep neural networks and tree search. Nature, 529(7587): 484–489, 1 2016. ISSN 0028-0836. doi: 10.1038/nature16961.
- <span id="page-10-9"></span>D. Silver, T. Hubert, J. Schrittwieser, I. Antonoglou, M. Lai, A. Guez, M. Lanctot, L. Sifre, D. Kumaran, T. Graepel, T. Lillicrap, K. Simonyan, and D. Hassabis. Mastering Chess and Shogi by Self-Play with a General Reinforcement Learning Algorithm.  $arXiv$  preprint, 12 2017. doi: 10.48550/arXiv.1712.01815.
- <span id="page-10-0"></span>N. L. Stockey and R. E. Lucas. Recursive Methods in Economic Dynamics. Harvard University Press, 1989.
- <span id="page-10-4"></span>R. S. Sutton. Learning to predict by the methods of temporal differences. Machine Learning, 3 (1):9–44, 8 1988. ISSN 0885-6125. doi: 10.1007/BF00115009.
- <span id="page-10-3"></span>R. S. Sutton and A. G. Barto. Reinforcement Learning: An Introduction. The MIT Press, Cambridge, Massachusetts and London, England, 2nd edition, 2018. URL <http://incompleteideas.net/book/the-book-2nd.html>.
- <span id="page-10-2"></span>C. Szepesvári. Algorithms for Reinforcement Learning. Morgan and Claypool Publishers, San Francisco, California, 2010. URL <https://sites.ualberta.ca/~szepesva/rlbook.html>.
- <span id="page-10-11"></span>M. Taddy. Business Data Science: Combining Machine Learning and Economics to Optimize, Automate and Accelerate Business Decisions. McGraw-Hill, New York, USA, 2019.
- <span id="page-10-5"></span>G. Tesauro. Temporal difference learning and TD-Gammon. Communications of the ACM, 38 (3):58–68, 3 1995. ISSN 0001-0782. doi: 10.1145/203330.203343.
- <span id="page-10-7"></span>S. Thrun. Learning to Play the Game of Chess. In G. Tesauro, D. Touretzky, and T. Leen, editors, Advances in Neural Information Processing Systems (NIPS) 7, Cambridge, MA, 1995. The MIT Press. URL <http://robots.stanford.edu/papers/thrun.nips7.neuro-chess.html>.
- <span id="page-10-1"></span>B. van Roy, D. P. Bertsekas, Y. Lee, and J. N. Tsitsiklis. A Neuro-Dynamic Programming Approach to Retail Inventory Management. In Proceedings of the 36th Conference on Decision and Control, San Diego, California USA, 12 1997.