

Predefined Software Environment Runtimes As A Measure For Reproducibility*

Aaruni Kaushik^[0009–0006–3061–6553]

University of Kaiserslautern-Landau, DE aaruni.kaushik@math.rptu.de

Abstract. As part of Mathematical Research Data Initiative (MaRDI), we have developed a way to preserve a software package into an easy to deploy and use sandbox environment we call a “runtime”, via a program we developed called **MaPS : MaRDI Packaging System** [10]. The program relies on Linux user namespaces to isolate a library environment from the host system, making the sandboxed software reproducible on other systems, with minimal effort. Moreover an overlay filesystem makes local edits persistent. This project will aid reproducibility efforts of research papers: both mathematical and from other disciplines. As a proof of concept, we provide runtimes for the OSCAR Computer Algebra System [13], polymake software for research in polyhedral geometry [9], and VIBRANT Virus Identification By iterative ANnotation [11]. The software is in a prerelease state: the interface for creating, deploying, and executing runtimes is final, and an interface for easily publishing runtimes is under active development. We thus propose publishing predefined, distributable software environment runtimes along with research papers in an effort to make research with software based results reproducible.

Keywords: FAIR · MaRDI · Sandbox · Runtime · Reproducibility

1 Introduction

As the capabilities of computer devices have grown, so have their use as tools in scientific research. It is now possible to do wild and wonderful things by relying on computers to generate useful results in the support of research goals and arguments. However, this also means that a computer program plays a more central role in the defence of a thesis. As good science requires a peer review of the results, the computer programs so central to new computational results must also be readily available to the reviewers. However, this is not straightforward with software.

A naive approach to making computer software available is to simply make the source code available to reviewers. But this poses problems with regards to ease of use, and also with regards to reproducibility. It may not be the easiest thing to get running in the first place. This may just be due to the convoluted way

* supported by MaRDI, funded by the Deutsche Forschungsgemeinschaft (DFG), project number 460135501, NFDI 29/1 “MaRDI – Mathematische Forschungsdateninitiative”.

the pre requisites are meant to be installed. Or it may require obscure versions of libraries which may conflict with existing libraries on a reviewer’s host system. It might just require a fixed version of a language which was the state of the art when the paper was written, but has been deprecated and become unsupported on modern computers. Thus, for a FAIR ¹ approach to distributing research software, a system tailor made for the job must be created. We expect MaPS to be able to effectively preserve software in runtimes. Our work is heavily inspired by the work done in this direction by Flatpak [2] for generic Linux software, and Valve [7] for PC video games.

In the following section, we describe a method we have developed for packaging research software in an easy to distribute and easy to use way.

2 MaRDI Packaging System: An Overview

MaPS has only a very basic minimal set of requirements to work. It requires a reasonably recent Linux kernel (5.11+ , released February 2021), and Python (3.8+, released October 2019) pre-installed. Both of these are available in Ubuntu 22.04 LTS. The rest is grabbed automatically during installation. Root access is only required at installation time for a system wide installation, and resolving dependencies. MaPS can be installed with no root access when not installing system wide. In this case, MaPS and any missing pre requisites must be installed manually from source.

Instead of re-inventing the wheel, we make use of other Free and Open Source ² projects like bubblewrap [3] and libostree [4] as mature, stable building blocks. This has a two fold advantage: one, that we are saved from the workload of reimplementing parts of the upstream work that we require, and two, that we inherit any improvements from these upstream projects for free. While we trust that these projects will stick around, we have architected the solution in a way that in the unlikely scenario that these upstream projects are shut down, it is possible to reimplement the functionality required from scratch. The building blocks are only a time saving convenience.

In broad strokes, MaPS manages fetching and storing full runtimes from a network source onto the local disk. It deploys these runtimes in a usable format from the storage provided by libostree, and sets up the foundation of an overlay file system. When launching a runtime with MaPS, it dynamically sets up an overlay layer on top of the published runtime, so that any local changes persist on disk, without actually modifying the runtime. This allows end users to persist edits, while also leaving open the option to easily reset back to the published state for perfect reproducibility.

¹ FAIR Principles <https://www.go-fair.org/fair-principles/>

² The open source definition - Open Source Initiative <https://opensource.org/osd>

3 Technical Details

3.1 Bubblewrap

Bubblewrap is a low level tool to create containers using user namespaces on Linux. It is also used by other big projects like Flatpak and rpm-ostree. Using bubblewrap, it is possible to create secure isolated containers relatively easily, and with good granularity of the exact setup. Bubblewrap prevents privilege escalation (see [3, section System Security]), and also adds a reaper process into the container to avoid the docker PID 1 problem [12].

3.2 libostree

libostree (previously, just ostree) is a library for content addressed storage of arbitrary filesystem trees. One can think of it as git, but for large directories instead of source code. An ostree repository is initialized on the local disk, and a remote source is added, as a sort of “app store”. Data is then fetched from this remote using standard web protocols.

Along with managing the repository, and implementing the network activity, ostree also makes efficient use of disk space. All files inside the repository are addressed by a hash of their contents. Thus, files with identical data are stored only once on disk. Checking out trees from the repository creates hardlinks on the local filesystem. Thus, file level deduplication is achieved. However, note that any changes, even just a single bitflip, will defeat this deduplication.

3.3 fuse-overlayfs

fuse-overlayfs [6] is the userspace implementation of the overlayfs [1] filesystem. Overlayfs is a special Linux filesystem, which can present a directory overlaid on top of another directory as a single merged filesystem, with any modifications being written only to the “upper” layer. We need the userspace variant of this filesystem to maintain the rootless nature of our application. It requires at minimum four directories: a “lower directory”, an “upper directory”, a “working directory”, and finally, a “merged directory”. With terminology borrowed from the physical analogy, an upper directory is overlaid on top of one or more lower directories. The resulting tree is mounted onto the merged directory. A working directory is required for temporary storage while the overlay is active.

Mounting a filesystem, even inside a container, presents a potential security risk, as the contents of its superblock are executed in kernelmode. Thus, as of version 0.8.0, bubblewrap does not support mounting any filesystems in the container, not even overlayfs. In principle, an overlay operation is risk free as no superblocks are involved, and can safely be done as root inside a user namespace in Linux 5.11+. However, this is not currently implemented in bubblewrap. This point serves as a first example of inheriting improvements for free: as native overlayfs without root access is a soon to be implemented feature on the roadmap for bubblewrap, at which point, we can stop depending on fuse-overlayfs, while still keeping all our functionality.

3.4 MaPS

At its core, MaPS is very simple and elegant. Its main task is to carefully orchestrate its building blocks to achieve desired results. It tells ostree to setup a repository for all the data in `$XDG_DATA_HOME/org.mardi.maps/ostree/repo`, then checks out the files in `$HOME/.var/org.mardi.maps/<runtime_name>`. Under this location, four subdirectories are created: `rofs`, `rwfs`, `tmpfs`, and `live`. At the time of execution, `fuse-overlayfs` is used to layer `rwfs` over `rofs`, and the result is exposed as a merged writeable tree at `live`. Finally, `bubblewrap` is used to create a user namespace using `live` as the target filesystem tree. `$HOME/Public` is passed through into the namespace as `/home/runtime/Public`, and can be used to provide input, as well as extract output from the runtime. When the runtime is exited, i.e., when the last process in the namespace has exited, `bubblewrap` will shut down the created namespace, and MaPS unmounts the filesystem created by `fuse-overlayfs`.

Manifest File. Optionally, a runtime is allowed to contain a manifest file located at `/manifest.toml` in the namespace. (Note that this is in runtime, which corresponds to `<runtime>/live/manifest.toml` on the host.) This is a TOML³ file that can contain arbitrary metadata relating to the runtime, and, more importantly, a custom command for MaPS invoke. This command is specified in the `[Core]` section of the TOML file, as a string assigned to the variable `command`. In the absence of this variable in the manifest file (or in the absence of a manifest file), a shell is launched by default. This behaviour can be overridden by using the command line argument `--command`. The Manifest file from the runtime `org.oscar.system.oscar/x86_64/1.0.0` is included as an example:

```

1 [Core]
2 command = "julia -J /tmp/jl_UuXQwY/Oscar.so --banner=no"
3
4 [Meta]
5 Project = "OSCAR -- Open Source Computer Algebra Research
6           system, Version 1.0.0, The OSCAR Team, 2024. (https://www
           .oscar-system.org)"
7 URL = "https://www.oscar-system.org/"

```

Extended Attributes. `libostree` requires a file system with extended attributes available and enabled to be able to manage a repository, and also to check out files from the repository. This means that both required directories (`$XDG_DATA_HOME` and `$HOME`) must be on a filesystem with extended attributes. In particular, this means that NTFS disks or NFS shares will not work. If `$HOME` is on such an unsupported filesystem (as is common in large organizations), but access to another, supported, filesystem is available, one may override these environment variables before invoking MaPS to point to locations on the supported filesystem.

³ TOML: A config file format for humans. <https://toml.io/en/>

Fakeroot. In a user namespace, even though it appears that we have root access (the command `whoami` returns `root`), we don't really have root access on the host computer. This can lead to some conflicting operations like trying to `chown` a file. As you are root in the userspace, you expect to be able to do whatever you want in the userspace without an error. But some commands like `chown` would need to actually change the owner of a file on the host filesystem, which could be utilised to craft an attack to break out of the sandbox. While MaPS does not try to be a security layer, such an operation is not allowed on a kernel level, and results in an error. `fakeroot` is a linux utility which only simulates the result of such a command, and returns success to the calling program. However, the kernel does not allow even this inside a namespace, as a security measure. To get around this problem, `fakeroot` can be used with the environment variable `FAKEROOTDONTTRYCHOWN` set to 1. This makes `fakeroot` only pretend to execute such commands, and return a success code to the calling program. This workaround may be required in a MaPS runtime to successfully install new packages, or use `tar`.

Creating Runtimes. To create a runtime, start from a "minimal viable ch-root" environment. Debian rootfs is an excellent choice for reasons of compatibility and size. Initialise the tree in a convenient location using `maps package --initialise /path/to/tree`. Once initialised, open a live sandbox into the tree by running `maps package --sandbox /path/to/repository`. Even though this is really a sandbox inside the tree, it can be treated it as if one has SSH⁴'d into a freshly installed debian box, and set up programs as normal. When done, exit the sandbox, then package the runtime using `maps package --commit name_of_repository/arch/version path/to/tree`. This will create a MaPS runtime out of the tree.

Publishing Runtimes. A workflow for publishing runtimes created as in the previous step is under active development. This will allow scientists to request their runtimes to be published on the "Official" repository right from the MaPS command line.

3.5 Comparison with Competing Methods

There are several methods for sharing a program for running on another machine ranging from sharing just the source code, to docker containers (via a `dockerfile`), or a full fat Virtual Machine (VM) disk image. We think MaPS is a superior option to these alternate methods. a MaPS runtime is more complete than just sharing source code, more light weight than sharing a VM, and more streamlined than running docker. A more in depth comparison is discussed in the full paper of this extended abstract.

⁴ Secure Shell https://en.wikipedia.org/wiki/Secure_Shell

4 Examples

4.1 AccurateArithmetic.jl

The Julia package `AccurateArithmetic.jl` [5] implements the algorithms described in [8] in Julia. It also contains everything needed to reproduce the results shown in the paper. Below is a full list of the actions to be taken by anyone wanting to try and reproduce the results on their own Linux system (adapted for MaPS from [8, Appendix])

Commands prefixed with a `sh>` prompt are to be entered in a shell; commands prefixed with a `julia>` prompt are to be entered in a Julia interactive session. MaPS should have been downloaded and installed beforehand by following the instructions at <https://github.com/MaRDI4NFDI/maps/wiki/Installation>.

Be aware that step (3) in this procedure might take a few hours to complete. Afterwards, all measurements should be available as JSON files in the `AccurateArithmetic.jl/test` directory. After step (4), all figures showed in this paper should be available as PDF files in the same directory.

1. Get and launch the runtime:

```
1 sh> maps -d org.juliamath.accuratearithmetic/x86_64/
   papercorrectnessv3
2 sh> maps -r org.juliamath.accuratearithmetic/x86_64/
   papercorrectnessv3
```

2. Start Julia and run the test suite:

```
1 sh> cd /AccurateArithmetic.jl/test && julia --project
2 julia> using Pkg
3 julia> pkg"test"
```

3. Run the performance tests:

```
1 # Additional dependencies for performance tests.
2 # Package testing fails if these are already included.
3 julia> pkg"add BenchmarkTools Plots Printf Statistics Test
   "
4 julia> exit()
5 sh> julia --project -O3 -L perftests.jl -e 'run_tests()'
```

4. Plot the graphs:

```
1 sh> julia --project -L perfplots.jl -e 'plot_results()'
```

4.2 OSCAR

OSCAR is a comprehensive open source computer algebra system for computations in algebra, geometry, and number theory written in Julia ⁵. As a Julia

⁵ The Julia Programming Language <https://julialang.org/>

program, it benefits from just in time compilation, with a speedup step of pre-compilation. However, this precompilation step can be lengthy, and must be done by each user **after** installation, upon first use. This can leave end users with the false first impression of OSCAR being slow. As a way to mitigate this, OSCAR can be distributed as a MaPS runtime, already pre-compiled, with a custom system image.

1. Get the runtime:

```
1 maps -d org.oscar_system.oscar/x86_64/latest
```

2. Start the runtime:

```
1 maps -r org.oscar_system.oscar/x86_64/latest
```

Starting the runtime will automatically also start a Julia REPL⁶ environment and load a precompiled copy of OSCAR. To update the runtime, for the latest version of OSCAR, execute

```
1 maps --update org.oscar_system.oscar/x86_64/latest
```

5 Beyond Mathematical Software

We present an example which showcases non mathematical software which can benefit from MaPS.

5.1 VIBRANT

VIBRANT is a tool for automated recovery and annotation of bacterial and archaeal viruses, determination of genome completeness, and characterization of viral community function from metagenomic assemblies. VIBRANT uses neural networks of protein annotation signatures and genomic features to maximize identification of highly diverse partial or complete viral genomes as well as excise integrated proviruses. VIBRANT is a novel and useful tool which, unfortunately, requires versions of software which are not easy to install in modern operating systems. This presents a perfect opportunity for research software to be ported into a MaPS runtime, such that it can be run on current systems without having to install outdated versions of software, which might cause conflicts with, and threaten the stability of an up to date system.

As before, installing it is as simple as calling the MaPS deploy function with the runtime name :

```
1 maps --deploy github.anantharaman.vibrant/x86_64/1.2.1
```

⁶ Read-evaluate-print loop

6 Concluding Remarks

Packaging software for distribution always means an overhead in terms of work for a researcher. However, correctly doing so leads to great progress in the reproducibility and thus the credibility of the scientific work at hand. It also makes the research more FAIR. We have developed a software tool to simplify this packaging process, keeping in mind the long term reproducibility of the work. The runtimes we create are lighter than a VM, more straightforward than docker, and more complete than just a source distribution.

References

1. Overlay filesystem - the linux kernel documentation (2014), <https://www.kernel.org/doc/html/latest/filesystems/overlayfs.html?highlight=overlayfs>
2. Flatpak: The future of apps on linux (2015), <https://flatpak.org/>
3. Bubblewrap - low-level unprivileged sandboxing tool used by flatpak and similar projects (2016), <https://github.com/containers/bubblewrap>
4. libostree - operating system and container binary deployment and upgrades (2016), <https://github.com/ostreedev/ostree>
5. AccurateArithmetic.jl - calculate with error-free, faithful, and compensated transforms and extended significands (2019), <https://github.com/JuliaMath/AccurateArithmetic.jl/tree/paper-correctness-2019>
6. fuse-overlayfs - fuse implementation for overlayfs (2020), <https://github.com/containers/fuse-overlayfs>
7. ValveSoftware/steam-runtime - a runtime environment for steam applications (2020), <https://github.com/ValveSoftware/steam-runtime>
8. Elrod, C., Févotte, F.: Accurate and Efficiently Vectorized Sums and Dot Products in Julia (Aug 2019), <https://hal.science/hal-02265534>, version submitted to the Correctness2019 workshop
9. Gawrilow, E., Joswig, M.: polymake: a framework for analyzing convex polytopes. In: Polytopes—combinatorics and computation (Oberwolfach, 1997), DMV Sem., vol. 29, pp. 43–73. Birkhäuser, Basel (2000)
10. Kaushik, A.: Mardi packaging system (2023), <https://github.com/MaRDI4NFDI/maps>
11. Kieft, K., Zhou, Z., Anantharaman, K.: Vibrant: Virus identification by iterative annotation copyright (2020), <https://github.com/AnantharamanLab/VIBRANT>
12. Lai, H.: Docker and the pid 1 zombie reaping problem (2015), <https://web.archive.org/web/20240228145942/https://blog.phusion.nl/2015/01/20/docker-and-the-pid-1-zombie-r>
13. Oscar - open source computer algebra research system (2024), <https://www.oscar-system.org>