# Overlap Gap Property limits limit swapping in QAOA

## Mark Goh<sup>1</sup>

<sup>1</sup>Institute of Material Physics in Space, German Aerospace Center

May 8, 2024

#### Abstract

The Quantum Approximate Optimization Algorithm (QAOA) is a quantum algorithm designed for Combinatorial Optimization Problem (COP). We show that if a COP with an underlying Erdös–Rényi hypergraph exhibits the Overlap Gap Property (OGP), then a random regular hypergraph exhibits it as well. Given that Max-q-XORSAT on an Erdös–Rényi hypergraph is known to exhibit the OGP, and since the performance of QAOA for the pure q-spin model matches asymptotically for Max-q-XORSAT on large-girth regular hypergraph, we show that the average-case value obtained by QAOA for the pure q-spin model for even  $q \geq 4$  is bounded away from optimality even when the algorithm runs indefinitely. This suggests that a necessary condition for the validity of limit swapping in QAOA is the absence of OGP in a given combinatorial optimization problem. Furthermore, the results suggests that even when sub-optimised, the performance of QAOA on spin glass is equal in performance to classical algorithms in solving the mean field spin glass problem providing further evidence that the conjecture of getting the exact solution under limit swapping for the Sherrington–Kirkpatrick model to be true.

# Contents

1	Introduction		2
	1.1	Statement of result	3
2	Background		
	2.1	Random Graphs	4
	2.2	Spin glass	5
	2.3	Overlap Gap Property	6
	2.4	Local algorithms	7
3	Summary of known theorems		
	3.1	QAOA and COPs	8
	3.2	Equivalence of performance	10
4	Main Results		11
	4.1	Proof of theorem 4.1	12
	4.2	Numerical evidence	14
5	5 Discussion and further work		15
A	A lt.	ernate proof	17

# 1 Introduction

Combinatorial Optimization Problems (COPs) are notoriously difficult even as a decision problem [22] — well known examples include the travelling salesman problem [30] and finding the ground state of a spin glass Hamiltonian [17]. Rather than attempting to find an exact solution, one is rather often interested in approximate solutions. One such algorithm is the Quantum Approximate Optimization Algorithm (QAOA) introduced by Farhi [13].

Attempting to evaluate the expectation value of QAOA is incredibly difficult. Naively, for each layer p in QAOA, one would need to sum over  $2^N$  terms. In a series of works starting with [14], algorithms to evaluate the expectation value of QAOA on q-spin glass models for any arbitrary parameters  $(\gamma, \beta)$  with time complexity independent of N have been found with increasing performance in terms of time complexity. The best known one for evaluating q-spin glass is found in [3] with a time complexity of  $\mathcal{O}(p^24^p)$  using algebraic techniques.

Another line of research is to prove the limitation of QAOA via the Overlap Gap Property (OGP). One of the first applications to show the limitation of QAOA is when QAOA does not see the whole graph that a COP is based on [12]. The limitation of QAOA as a result of OGP has been predominately used on sparse graphs but a breakthrough came in [4] using a dense-from-sparse relation between complete graphs and sparse graphs to show that QAOA is also limited in performance even if it sees the whole graph.

In this paper, we note that the current research seems to suggest that for the q-spin glass model, QAOA is unlikely to find the optimal value even if p goes to infinity for even  $q \geq 4$  if we swap the order of limits, the thermodynamic limit and the run time of the algorithm. We will present the argument here. The paper is organised as follows: In section 2 we give a brief background to random graphs, Spin glass problems, the OGP, and local algorithms; in section 3, we summarise what is known in literature about the results of QAOA on spin glasses and their equivalence between the mean-field and dilluted spin model; in section 4 we formalise a point about OGP in random regular hypergraphs that was mentioned in [3] and show that if their observation is true, QAOA cannot find the optimal value in a dense graph even if the algorithm runs indefinitely under limit swapping. Following which, we outline a proof to affirm the theorem while providing some numerical evidence that the proof should extend to odd q-spin glass as well.

## 1.1 Statement of result

The main result of this work is to show that the OGP exists for Max-q-XORSAT on a random regular hypergraph with sufficiently large degree. This is done via the following theorem

#### Theorem 1.1

If the Overlap Gap Property limits the performance of a local algorithm on the Erdös-Rényi hypergraph, it also limits the performance on a random regular hypergraph.

The proof is done via contradiction. First, we show that we can trim the Erdös–Rényi hypergraph of average degree  $\lambda$  to a regular hypertree removing at most  $\mathcal{O}(1/\lambda^{\log \lambda})$  fraction of edges. Then, one can form a D-regular hypergraph from the hypertree. Assuming an algorithm, that is limited by the OGP, is able to find a near optimal solution on the regular hypergraph leads to a contradiction since such an algorithm is unable to find near optimal solution on Erdös–Rényi hypergraph. Thus, the OGP also acts as a barrier to optimization for random

regular graph.

The presence of the OGP in random regular hypergraph thus leads us to the following:

## Theorem 1.2 (Informal)

When  $q \geq 4$  and is even, the OGP is present for Max-q-XORSAT D-regular q-uniform hypergraphs and the performance of QAOA is limited at logarithmic depth.

There are several immediate corollaries of this result for QAOA. The first of which was noted in [3] as a side-note.

#### Corollary 1.2.1

Optimising QAOA using the algorithm in [3, 4] only allows it to perform equal in performance to local classical algorithms thus providing no quantum advantage.

The above corollary is a result of optimising QAOA under limit swapping of the algorithm run time and the problem size n. This therefore results in the following 2 corollaries:

#### Corollary 1.2.2

If a COP exhibit the OGP, then optimising QAOA via limit swapping results in sub-optimal performance

### Corollary 1.2.3

The failure of QAOA under limit swapping implies that a reduction to the quantum adiabatic algorithm is not possible (i.e. the spectral gap closes).

# 2 Background

# 2.1 Random Graphs

Here we standardize the notation we use to denote a hypergraph. A hypergraph G = (V, E) has |V| = n vertices, and |E| = m edges. Conventionally, an instance of the Erdös–Rényi–(Gilbert) q-uniform hypergraph  $G = \mathbb{G}_{ER}^q(n, p)$  is a random graph with n vertices where each hyperedge is added with probability p. The original Erdös–Rényi q-uniform hypergraph  $G = \mathbb{G}_{ER}^q(n, m)$  is chosen randomly from the set of hypergraph with n vertices and m hyperedges. The former is now more frequently used. The two types of Erdös–Rényi graphs are similar to each other when np = m. In fact, it has been shown that the two types of random graphs are asymptotically equivalent under certain conditions [23].

2 BACKGROUND 2.2 Spin glass

Another type of random hypergraph of interest is the d-regular q-uniform hypergraph  $G = \mathbb{R}^q(n,d)$  where we implicitly assume that nd = qm for some integer m. Unlike Erdös–Rényi graphs that can be generated randomly, there is no easy unbiased way to generate such graphs, though one such method is known as the configuration model introduced by Bollobás [5].

## 2.2 Spin glass

In this paper, we focus on the mean field spin glass model and the related dilluted spin glass model. For the mean field model, the main goal, roughly speaking, is to find the ground state energy of a spin glass Hamiltonian. A widely studied model is the Sherrington-Kirkpatrick (SK) model [29]

$$H_{SK}(\boldsymbol{z}) = \frac{1}{\sqrt{N}} \sum_{j < k} J_{jk} z_j z_k. \tag{1}$$

More generally, an Ising q-spin model is given by the following

$$H_q(\mathbf{z}) = \sqrt{\frac{q!}{2N^{(q-1)}}} \sum_{j < k < \dots < q} J_{jk\dots q} z_j z_k \dots z_q, \tag{2}$$

with the couplings randomly chosen over a normal distribution.

The exact solution, now known as the Parisi ansatz [26], was proven by Talagrand to give the correct solution for the even q case [31] and later generalized to all q by Panchenko [25]. Denote by  $\mathcal{M}$  the collection of all cumulative distribution functions  $\alpha$  on [0, 1], the Parisi formula [31] states that

$$F(\beta) = \lim_{N \to \infty} F(\beta, N) = \inf_{\alpha \in \mathcal{M}} \mathcal{P}(\beta, \alpha) \quad a.s.$$
 (3)

where  $\mathcal{P}$  is the so-called Parisi measure.

Thus, letting  $\Sigma_N = \{-1, +1\}^N$ , the ground state energy can be found via the following equation

$$\lim_{N \to \infty} \max_{\mathbf{z} \in \Sigma_N} \frac{H(\mathbf{z})}{N} = \lim_{\beta \to \infty} F(\beta) = \lim_{\beta \to \infty} \inf_{\alpha \in \mathcal{M}} \mathcal{P}(\beta, \alpha). \tag{4}$$

For the q-spin model, the limit can be computed explicitly which we denote as the Parisi constant

$$\Pi_q = \lim_{N \to \infty} \max_{\mathbf{z} \in \Sigma_N} \frac{H_q(\mathbf{z})}{N}.$$
 (5)

The diluted spin glass model is also known as the XOR-satisfiability (XOR-SAT) problem. Specifically, given a q-uniform hypergraph G = (V, E) where  $E \subset V^q$ , and a given signed weight  $J_{i_1,...,i_q} \in \{-1,+1\}$ , Max-q-XORSAT is the problem of maximising the following cost function

$$H_{XOR}^{q}(\mathbf{z}) = \sum_{(i_1, \dots, i_q) \in E} \frac{1}{2} (1 + J_{i_1 i_2 \dots i_q} z_{i_1} z_{i_2} \dots z_{i_q}).$$
 (6)

The cost function is essentially counting the number of satisfied clauses where a clause is satisfied if  $z_{i_1}z_{i_2}...z_{i_q} = J_{i_1i_2,...i_q}$  for a given hyperedge. MaxCUT is thus a special case of this problem with q = 2 and  $J_{i_1i_2} = -1$ .

We say that an instance of the problem is satisfied if there is an assignment of values to the bitstring z which satisfies all the clauses (i.e.  $H^q_{XOR}(z) = |E|$ ), otherwise, we say it is unsatisfiable. It is known that for an instance  $\xi$  of a random q-XORSAT problem, given |E| hyperedges and problem size n, the following theorem holds

#### **Theorem 2.1** (Theorem 1 of [9])

Let q > 2 be fixed. Let  $|E|/n = \delta$ . In the limit  $n \to \infty$ ,

- 1. if  $\delta > 1$ , then a random formula from  $\xi$  is unsatisfiable with high probability
- 2. if  $\delta < 1$ , then a random formula from  $\xi$  is satisfiable with high probability.

For a random q-uniform hypergraph, this condition implies that if the average degree d is greater than q, then a random formula is unsatisfiable with high probability. Suppose we fix d > q sufficiently large so that we are in the unsatisfiability regime. The maximum number of satisfiable equations in an instance of random XORSAT for both  $\mathbb{G}^q_{ER}(n,p)$ , and  $\mathbb{R}^q(n,d)$  has been found [28] to be

$$\frac{1}{|E|} \max_{\boldsymbol{z}} H_{XOR}^q(\boldsymbol{z}) = \frac{1}{2} + \Pi_q \sqrt{\frac{q}{2d}} + \mathcal{O}(1/\sqrt{d})$$
 (7)

## 2.3 Overlap Gap Property

One major obstacle to finding optimal solutions for COPs is known as the Overlap Gap Property (OGP). The term was introduced in [16], though the concept was already used by various authors [1, 24].

For the definition of the OGP, one can informally think that for certain choices of disorder J, there is a gap in the set of possible pairwise overlaps of near-optimal solution. For every two  $\epsilon$  optimal solution  $z^1, z^2$ , it is the case that the distance

between them is either extremely small, or extremely large. Formally, we define OGP for a single instance as the following:

#### **Definition 2.1** (Overlap Gap Property [15])

For a general maximization problem with random input J, the OGP holds if there exists some  $\epsilon > 0$ , with  $0 \le \mu_1 < \mu_2$  such that for every  $\mathbf{z}^1, \mathbf{z}^2$  that is an  $\epsilon$ -optimal solution

$$H_J(z^i) \ge \max_{z \in 2^n} H_J(z) - \epsilon,$$
 (8)

it holds that the overlap between them is either less than  $\mu_1$  or greater than  $\mu_2$ 

$$R_{1,2} \in [0, \mu_1] \cup [\mu_2, 1).$$
 (9)

The first interval is trivial as we can simply choose the overlap  $z^1$  with itself. It is the existence of the second overlap, or rather the non-existence of overlap in the interval  $(\mu_1, \mu_2)$ , that is difficult to prove.

A general version of it is known as the ensemble-OGP introduced in [7] or coupled-OGP as used in [8]. This version is required to prove limitations of local algorithm for technical reasons and requires an interpolation scheme between two different instances of Erdös–Réyni graphs. For spin glass, a branching OGP has been developed that makes use of the (lack of) ultrametric structure in the Parisi solution [21].

# 2.4 Local algorithms

Here, we recall the definition of local algorithms and how QAOA fits into it.

**Definition 2.2** (p-neighborhood and hypergraphs with radius p)

Let G = (V, E) be a hypergraph. For a vertex  $v \in V$ , the p-neighbourhood of v is defined as

$$B_G(v, p) = \{ w \in V | w \text{ is } p \text{ hyperedges away from } v \}.$$
 (10)

**Definition 2.3** (*p*-local hypertree)

A hypergraph G = (V, E) is  $(p, \epsilon)$ -locally treelike is isomorphic to a tree for at least  $(1 - \epsilon)n$  vertices.

**Definition 2.4** (Definition 3.1 of [8])

Consider an algorithm A that inputs a hypergraph G and outputs a label  $A(G) \in \Sigma$ , where  $\Sigma = \{-1,1\}^n$ . A is a p-local algorithm if, for any subset  $L \subset V$ , the following conditions hold:

- 1. (Local distribution determination) The joint marginal distribution  $(\mathcal{A}(G)_v)_{v \in L}$  is identical to  $(\mathcal{A}(G')_v)_{v \in L}$  where  $G' = \bigcup_{v \in L} B_G(v, p)$ .
- 2. (Local independence) The distribution  $\mathcal{A}(G)_v$  is statistically independent of the joint distribution of  $\mathcal{A}(G')_{v'}$  over all vertices  $v' \notin B_G(v, 2p)$

The QAOA is one such local algorithm designed to find approximate solutions to combinatorial optimization problems [13]. The goal is to find a bit string  $z \in \{-1, +1\}^N$  that maximizes the cost function C(z). Given a classical cost function C, we can define a corresponding quantum operator C that is diagonal in the computational basis,  $C|z\rangle = C(z)|z\rangle$ . In addition, define the operator  $B = \sum_{j=1}^{N} X_{j}$  where  $X_{j}$  is the Pauli X operator acting on qubit j. Given a set of parameters  $\gamma = (\gamma_{1}, \ldots, \gamma_{p}) \in \mathbb{R}^{p}$  and  $\beta = (\beta_{1}, \ldots, \beta_{p}) \in \mathbb{R}^{p}$ , the QAOA prepares the initial state as  $|s\rangle = |+\rangle^{N} = 2^{-N/2} \sum_{z} |z\rangle$  and applies p layers of alternating unitary operators  $e^{-i\gamma_{k}C}$  and  $e^{-i\beta_{k}B}$  to prepare the state

$$|\gamma,\beta\rangle = e^{-i\beta_p B} e^{-i\gamma_p C} \dots e^{-i\beta_1 B} e^{-i\gamma_1 C} |s\rangle.$$
 (11)

For a given cost function C, the corresponding QAOA objective function is the expectation value  $\langle \gamma, \beta | C | \gamma, \beta \rangle$ . Preparing the state  $| \gamma, \beta \rangle$  and measuring in the computational basis will yield a bit string z near the quantum expectation value. Heuristics strategies to optimize  $\langle \gamma, \beta | C | \gamma, \beta \rangle$  with respect to  $(\gamma, \beta)$  using a good initial guess have been proposed in [32].

# 3 Summary of known theorems

# 3.1 QAOA and COPs

The first result of QAOA on spin glass can be found in [14] where the authors applied the QAOA on the Sherrington–Kirkpatrick (SK) model and found an algorithm to evaluate the expectation value in the infinite limit after averaging over the disorder  $\mathbb{E}_J$ . More generally, for a q-spin glass with cost function

$$H_q(\mathbf{z}) = \sum_{j < k < \dots < q} J_{jk\dots q} z_j z_k \dots z_q, \tag{12}$$

it was shown in [4] that the following theorem holds

**Theorem 3.1** (Theorem 1 of [4])

For any p and any parameters  $(\gamma, \beta)$ , we have

$$\lim_{n \to \infty} \mathbb{E}_J \left[ \langle \boldsymbol{\gamma}, \boldsymbol{\beta} | H_q / N | \boldsymbol{\gamma}, \boldsymbol{\beta} \rangle \right] = V_p^{(q)}(\boldsymbol{\gamma}, \boldsymbol{\beta}), \tag{13}$$

In [3], the authors evaluated the performance of QAOA for Max-q-XORSAT on large-girth (D+1)-regular graphs. By restricting to graphs that are regular and girth (also known as the shortest Berge-cycle) greater than 2p+1, the subgraph explored by QAOA at depth p will appear as regular trees. Since the optimal cut fraction is of the form  $1/2 + \mathcal{O}(1/\sqrt{D})$  in a typical random graph as in eq. (7), we have

$$\frac{1}{|E|} \langle \boldsymbol{\gamma}, \boldsymbol{\beta} | H_{XOR}^q | \boldsymbol{\gamma}, \boldsymbol{\beta} \rangle = \frac{1}{2} + \nu_p^{[q]}(D, \boldsymbol{\gamma}, \boldsymbol{\beta}) \sqrt{\frac{q}{2D}} + \mathcal{O}(1/\sqrt{D}). \tag{14}$$

Let

$$\nu_p^{[q]}(\boldsymbol{\gamma}, \boldsymbol{\beta}) = \lim_{D \to \infty} \nu_p^{[q]}(D, \boldsymbol{\gamma}, \boldsymbol{\beta}), \tag{15}$$

then, we have the following theorem

## **Theorem 3.2** (Theorem 2 of [3])

For  $H^q_{XOR}$  on any (D+1)-regular q-uniform hypergraphs with girth > 2p+1, for any choice of J, eq. (14) can be evaluated using  $\mathcal{O}(p4^{pq})$  time and  $\mathcal{O}(4^p)$  space. In addition, the infinite D limit can be evaluated with an iteration using  $\mathcal{O}(p^24^p)$  time and  $\mathcal{O}(p^2)$  space.

One point to note is that in [12], it has been shown that at low depth p, if a problem exhibits OGP, then the locality of QAOA makes it such that it is prevented from getting close to the optimal value if it does not see the whole graph. Specifically, the following theorem is proven

## **Theorem 3.3** (modified version of Corollary 4.4 in [8])

For Max-q-XORSAT on a random Erdös-Réyi directed multi-hypergraph, for every even  $q \geq 4$ , there exists a value  $\eta_{OGP} < \eta_{OPT}$ , where  $\eta_{OPT}$  is the energy of the optimal solution, and a sequence  $\{\delta(d)\}_{d\geq 1}$  with the following property. For every  $\epsilon > 0$  there exists sufficiently large  $d_0$  such that for every  $d > d_0$ , every  $p \leq \delta(d) \log N$  and an arbitrary choice of parameters  $\gamma, \beta$  with probability converging to 1 as  $N \to \infty$ , the performance of QAOA with depth p satisfies  $\langle \gamma, \beta | C_{XOR}^q / N | \gamma, \beta \rangle \leq \eta_{OGP} + \epsilon$ .

The authors of [3] noted that assuming OGP also holds for regular hypergraphs, then a similar argument can be used to show that QAOA's performance as measured by the algorithm in theorem 3.2 does not converge to the Parisi value  $\Pi_q$  for even  $q \geq 4$ . This is because the large girth assumption implies that the graph has at least  $D^p$  vertices so p is always less than  $\epsilon \log n$  in this limit. For the Max-q-XORSAT, the subgraph explored at constant p has  $q[(q-1)^pD^p+\cdots+(q-1)D+1]$  vertices. This lays the foundation of theorem 4.2 later.

## 3.2 Equivalence of performance

The first equivalence between spin glass and MaxCut for QAOA was shown in [3], where the performance of QAOA at depth p on the SK model as  $N \to \infty$  is equal to the performance of QAOA at depth p on MaxCut problems on large-girth D-regular graphs when  $D \to \infty$ .

In the follow up work of [4], they generalize this result to show that QAOA's performance for the q-spin model is equivalent to that for Max-q-XORSAT on any large girth D-regular hypergraphs in the limit  $D \to \infty$ .

## **Theorem 3.4** (Theorem 3 of [4])

Let  $\nu_p^{[q]}(\boldsymbol{\gamma}, \boldsymbol{\beta})$  be the performance of QAOA on any instance of Max-q-XORSAT on any d-regular q-uniform hypergraphs with girth > 2p+1 as given in [3]. Then for any p and any parameters  $(\boldsymbol{\gamma}, \boldsymbol{\beta})$ , we have

$$V_p^{(q)}(\boldsymbol{\gamma}, \boldsymbol{\beta}) = \sqrt{2}\nu_p^{[q]}(\sqrt{q}\boldsymbol{\gamma}, \boldsymbol{\beta})$$
(16)

Remark. The additional factor of  $\sqrt{q}$  and  $\sqrt{2}$  compared to the equivalence in [3] is due to the different notation of the two papers and was acknowledge in [4] that  $\nu_p^{[q]}(\boldsymbol{\gamma},\boldsymbol{\beta})$  produced by the algorithm of theorem 3.2 matches (up to a rescalling) the formula  $V_p^{(q)}(\boldsymbol{\gamma},\boldsymbol{\beta})$  for the pure q-spin model.

The equivalence of performance of QAOA on dense and sparse graph is also shown to hold in the case of Erdös–Rényi graph.

**Theorem 3.5** (modified version of theorem 2 in [4]) Let

$$V_p(\mathbb{G}, \gamma, \beta) = \lim_{n \to \infty} \mathbb{E}_{J \sim \mathbb{G}(n)} \langle \gamma, \beta | H_q / N | \gamma, \beta \rangle, \qquad (17)$$

where  $\mathbb{G}$  denotes the underlying graph. Then, for the q spin model  $\mathbb{G}_q$  and the  $Erd\ddot{o}s$ -Rényi graph with connectivity  $\lambda$ , the asymptotic performance of QAOA on  $\mathbb{G}_q$  is the same as  $\mathbb{G}_{ER}^q$  for any  $(\gamma, \beta)$ 

$$V_p^{(q)}(\gamma,\beta) = \lim_{\lambda \to \infty} V_p(\mathbb{G}_{ER}^q, \gamma, \beta)$$
 (18)

Remark. In the original formulation, the Erdös–Rényi graph uses the convention  $\mathbb{G}_{d,q}$  where d denotes the average connectivity/degree of the graph since the number of edges is chosen via  $m \sim \operatorname{Poisson}(dn)$ . The order of limits taken in this case is first, the large n limit followed by the large d limit.

# 4 Main Results

We now have the pieces in place to state our main theorem

#### Theorem 4.1

Given a local algorithm A that is limited in performance by the OGP on an  $Erd\ddot{o}s$ - $R\acute{e}nyi$  hypergraph with sufficiently large connectivity  $\lambda$ , A is also limited in performance on a random D-regular hypergraph for sufficiently large D.

We delay the proof for section 4.1 and note an immediate consequence for the performance of QAOA.

#### Theorem 4.2

For Max-q-XORSAT on a D-regular q-uniform hypergraph, for every even  $q \geq 4$ , there exists a value  $\eta_{OGP}$  such that it is smaller than the optimal value  $\eta_{OPT}$  with the following property. For every  $\epsilon > 0$  there exists sufficiently large  $d_0$  such that for every  $d > d_0$ , every  $p \leq d \log N$  and an arbitrary choice of parameters  $\gamma, \beta$  with probability converging to 1 as  $N \to \infty$ , the performance of QAOA with depth p satisfies  $\langle \gamma, \beta | C_{XOR}^q/N | \gamma, \beta \rangle \leq \eta_{OGP} + \epsilon$ .

*Proof.* The proof follows from theorem 3.3 and theorem 4.1.

As a result of this theorem, then we have the following corollary:

#### Corollary 4.2.1

From theorem 4.2 the performance of QAOA on the pure q-spin glass for even  $q \geq 4$  converges to  $\eta_{OGP}$  as  $p \rightarrow \infty$  and is strictly less than the optimal value, i.e. the Parisi value  $\Pi_q$ , under the swapping of limits.

*Proof.* From theorem 3.4, we have that the performance of QAOA at constant p for q-spin glass in the large n limit is equal to any instance of Max-q-XORSAT on any d-regular q-uniform hypergraphs with girth > 2p+1 in the large D limit. This holds for any q. Thus, taking the limit  $p \to \infty$  gives

$$\lim_{p \to \infty} V_p^{(q)}(\boldsymbol{\gamma}, \boldsymbol{\beta}) = \lim_{p \to \infty} \sqrt{2} \nu_p^{[q]}(\sqrt{q} \boldsymbol{\gamma}, \boldsymbol{\beta})$$
 (19)

By theorem 4.2, the right hand side of eq. (19) will achieve a value  $\eta_{OGP}$  that is strictly less than  $\Pi_q$  for even  $q \geq 4$  so

$$\lim_{p \to \infty} \sqrt{2} \nu_p^{[q]}(\sqrt{q} \boldsymbol{\gamma}, \boldsymbol{\beta}) = \eta_{OGP} < \Pi_q$$
 (20)

This implies that QAOA on the q-spin glass for even  $q \geq 4$  will be strictly less than  $\Pi_q$  and this completes the proof.

We note that corollary 4.2.1 shows that QAOA will not be able to find the optimal value even when it sees the whole graph and the algorithm runs indefinitely if one optimises the parameters of QAOA via limit swapping.

Formally, the Parisi value is attainable via QAOA with the following limits:

$$\lim_{N \to \infty} \lim_{p \to \infty} V_p^{(q)}(N, \gamma, \beta) = \Pi_q. \tag{21}$$

The iteration provided in theorem 3.2 swaps the limits which results in failure of QAOA to find the optimal value. This leads us to the following corollaries

#### Corollary 4.2.2

If OGP exists in a problem, then the swapping of limits results in a sub-optimal solution for both random regular graphs and Erdös-Rényi graphs. In other words, a necessary condition for the validity of limit swapping is that the problem does not exhibit OGP.

Remark. For q-spin glass, it is expected that OGP holds for all  $q \geq 3$  which suggests that limit swapping is not allowed for all mean-field spin glasses with the possible exception for the 2-spin glass model (i.e. the SK model).

#### Corollary 4.2.3

If OGP exists for a problem, the spectral gap closes in the thermodynamic limit during the quantum adiabatic algorithm.

#### 4.1 Proof of theorem 4.1

The proof is as follows: first, we need to show that a  $\lambda$ -regular q-uniform hypertree can be embedded into an Erdös–Rényi hypergraph of sufficiently high average connectivity. Then, we show that a  $\lambda$ -regular q-uniform hypergraph can be generated from said hypertree. Finally, we show that algorithm  $\mathcal{A}$  must also fail to find solutions arbitrarily close to the optimal solution in a  $\lambda$ -regular q-uniform hypergraph as doing so would result in a contradiction.

We note that in [6], the authors have already shown that an Erdös–Rényi hypergraph can be converted into a hypertree by changing only  $\mathcal{O}(1/\sqrt{\lambda})$  edges. Given  $\mathbb{G}^q_{ER}(n,m)$  with average degree  $\lambda$ , define  $\lambda' = \lceil \lambda + \sqrt{\lambda} \log \lambda \rceil$ . Let  $\deg(v_i)$  be the degree of vertex  $v_i$ . Modify the graph as follows:

- 1. Remove edges until  $\deg(v_i) \leq \lambda'$  for all vertices.
- 2. Add edges to all vertices until  $\deg(v_i) = \lambda'$  where each verex is chosen with probability proportional to  $\lambda' \deg(v_i)$ .

Using this technique, the authors have proved the following

#### **Theorem 4.3** (Proposititions A.1-A.3 of [6])

With high probability, as  $n \to \infty$ , the number of removed edges is  $n \cdot \mathcal{O}(1/\lambda^{c \log \lambda})$  for some constant c > 0. Furthermore, for any fixed degree  $\lambda$  and positive integer p, with high probability, as  $n \to \infty$ ,  $1 - \mathcal{O}(1)$  fraction of p-local neighbourhood are tree like and adding clauses preserves is in  $1 - \mathcal{O}(1)$  fraction of p-local neighbourhood.

We generate a  $\lambda$ -regular, q-uniform hypergraph from the hypertree. At level p, there are  $q(q-1)^p\lambda^p$  leaves. A d-regular q-uniform hypergraph with n vertices is possible iff nd=qm for some integer m. Thus, it is possible to generate a random regular hypergraph from the p-local hypertree. Simply follow the configuration model of Bollobás [5] and repeat until we obtain a simple graph (i.e. no self-edges or repeated edges).

Now we can show that the OGP is also an obstruction in random regular hypergraph via contradiction. Assuming that an algorithm  $\mathcal{A}$  is able to find solutions arbitrarily close to the optimal solution for the Max-q-XORSAT on a regular hypergraph. Then this would imply that  $\mathcal{A}$  is also able to find such solutions when performed on an Erdös–Rényi hypergraph) since both graphs are p-locally the same. However, this contradicts theorem 3.3 and thus, the OGP must also be present in the regular hypergraph.

It is of note that proving that the OGP exists in a problem is much easier when the underlying graph is an Erdös–Rényi hypergraph as compared to a regular hypergraph since only the former can be described by a probability distribution. This is why there is no proof that the OGP exists for the Max-q-XORSAT on regular graph as it requires the Poisson distribution found in an Erdös–Rényi hypergraph. Given theorem 4.1 and that it is possible to show that the OGP exists in both Erdös–Rényi hypergraph and regular hypergraph in some problems [18], it is reasonable to think that if the OGP exists in the former, it also exists in the latter. Motivated by this, we make the following conjectures

#### Conjecture 4.4

If the overlap gap property exists in a COP with an underlying Erdös-Rényi hypergraph of sufficiently high connectivity, then it also exists when the underlying hypergraph is a regular hypergraph of sufficiently high degree.

#### Conjecture 4.5 (Monotonicity of the OGP)

For the Max-q-XORSAT problem, the overlap gap property is a monotonically increasing graph property.

We note that the proof of theorem 4.1 is much simpler if conjectures are true as can be seen in appendix A.

## 4.2 Numerical evidence

Here, we provide some numerical evidence that instances of OGP can occur in random regular hypergraph of odd degre. The code can be found here [20]. Our numerical simulation proceeds in the following manner. First, we define the problem size n, uniformity q, and degree d, where we implicitly assume that nd is a multiple of q. Then, randomly generate a d-regular q-uniform hypergraph so that the total number of hyperdeges |E| = (nd/q). Next, we randomly generate the list  $\mathbf{J} = \{-1, +1\}^{|E|}$  for the coupling strength of the hyperedges. Finally, we perform a branch and bound algorithm and record those whose cut-fraction exceeds a certain threshold. Since the maximum fraction of satisfied clauses is asymptotically equal to eq. (7), we define a cut-off point that a bit-string should return a cut-fraction > 0.8.

Once we have the list of bit-strings and their corresponding cut-fraction, we have to choose some  $\epsilon > 0$  such that the list of bit-strings that are  $\epsilon$ -optimal solutions is small. By default, we limit the bit-strings that are at least 95% to the optimal solution. Finally, compute the overlap between all such  $\epsilon$ -optimal bit-string and obtain the overlap spectrum.



Figure 1: n = 30 with constant degree 5.

Figure 2: Typical spectrum of Overlap obtained in 3-uniform random regular graphs. The overlaps include the optimal and first sub-optimal solution with a gap in the middle.

We find that on average, when d < q, OGP is not present. It is only when d is greater than q that instances of problems exhibiting OGP first appears. The numerical simulations was run on q = 3 and varying n up till 30.

We also ran simulations on the SK model as is it highly believed, though not yet proven, that the SK model does not exhibit the OGP [17, 2]. Modulo the

 $\mathbb{Z}_2$  symmetry, we find that indeed the SK model does not exhibit the OGP at n=45.




Figure 3: The overlap spectrum of an instance of the SK model with = 45. No gap was observed.

## 5 Discussion and further work

Being a heuristic algorithm, the limitations and potential of QAOA have not yet been fully explored. While swapping the order of limits allows us to evaluate the expectation value with a classical computer faster, it also seems to lead to sub-optimal results. This of course is expected and one can instead use the algorithm developed in [3] as a heuristic starting ansatz for  $(\gamma, \beta)$  to be further optimized for a specific problem.

This result come from a "dense-from-sparse" reduction first performed in [4]. It remains an open problem to show that OGP is a limitation on dense model without the need to rely on this reduction.

We note that under limit swapping, the performance of QAOA equals that of AMS's algorithm for the mean field spin glass [2]. This suggests that if QAOA is optimized correctly, it should outperform such classical algorithms. It is still an open question to determine at what depth p will QAOA outperform the AMP algorithm. Furthermore, given the similarity in performance to the AMP algorithm, this also suggests that the conjecture in [3] that the Parisi value for the Sherrington–Kirkpatrick model is obtained under limit swapping might be true as the AMP algorithm acheives the optimal value under the assumption that the OGP does not exists.

# Acknowledgement

We are thankful to Leo Zhou for answering questions on their work that this paper is a follow up on, and David Gamarnik for valuable discussions about the

## 5 DISCUSSION AND FURTHER WORK

overlap gap property. We thank David Gross, Matthias Sperl, and Michael Klatt for feedback on a draft of this article. We also thank an anonymous referee for suggesting the main proof could be done via modifying [6] replacing the original proof now in the appendix. This work was funded by DLR under the Quantum Computing Initiative.

# A Alternate proof

We provide here an alternate proof that relies and a conjecture that seems likely to be true as [19] notes that in the planted clique problem, the occurrence of OGP is related to the monotonicity of another graph property. For the Max-q-XORSAT, it is reasonable to think that the OGP is related to the density of edges in the graph which is clearly monotonically increasing.

#### Conjecture A.1

The OGP of Max-q-XORSAT on any graph is a monotonic increasing property in the sense that if the graph G exhibits the overlap gap property, then adding an additional edge does not destroy the graph exhibiting the OGP i.e. G + e exhibits the OGP.

Another result that we need comes from the fact that we can embed an Erdös–Rényi hypergraph into a random regular hypergraph.

#### **Theorem A.2** (Theorem 1 and Corollary 2 of [10])

For each  $q \ge 2$  there is a positive constant C such that if for some real  $\gamma = \gamma(n)$  and positive integer d = d(n),

$$C\left(\left(d/n^{q-1} + \log(n)/d\right)^{1/3} + 1/n\right) \le \gamma < 1,$$
 (22)

and  $m = (1 - \gamma)nd/q$  is an integer, then there is a joint distribution of  $\mathbb{G}^q_{ER}(n,m)$  and  $\mathbb{G}^q(n,d)$  with

$$\lim_{n \to \infty} \mathbb{P}(\mathbb{G}_{ER}^q(n, m) \subset \mathbb{R}^q(n, d)) = 1.$$
 (23)

Furthermore, let  $\mathcal{P}$  be a monotone increasing property. if  $\log n \ll d \ll n^{q-1}$ , for some  $m \leq (1-\gamma)nd/q$  where  $\gamma$  satisfies eq. (22), then if  $\mathbb{G}^q_{ER}(n,m) \in \mathcal{P}$  as  $n \to \infty$ , then  $\mathbb{R}^q(n,d) \in \mathcal{P}$  as  $n \to \infty$ .

For finite n and d, the proof trivially follows from the assumption of monotonicity. In the case for infinite n and d, we have to prove that our condition for large potentially infinite girth fit this condition for the embedding.

The girth g of a d-regular q-uniform hypergraph is known [11] to be bounded by

$$\frac{\log n - \log 4}{\log(q-1) + \log(d-1)} - 1 < g \le \frac{2\log n}{\log(q-1) + \log(d-1)} + 2. \tag{24}$$

For constant q, an infinite girth requires  $d \ll n$ 

Let  $d \sim \mathcal{O}(n^{\epsilon})$  for sufficiently small  $\epsilon > 0$  and  $n^{\epsilon} > q$ . Such a constraint satisfies the large girth requirement. Substituting d into eq. (22) gives us

$$C\left(\left(\frac{n^{\epsilon}}{n^{q-1}} + \frac{\log n}{n^{\epsilon}}\right)^{1/3} + 1/n\right) \le \gamma < 1,\tag{25}$$

where in the large n limit, we see that the lhs. approaches 0. Thus, for  $m = (1 - \gamma)nd/q \sim \mathcal{O}(n^{1+\epsilon})$ , an embedding can be performed.

From this, it follows that for some  $m^* \leq (1 - \gamma)nd/q$ , if  $\mathbb{G}_{ER}^q(n, m)$  has a monotone increasing property  $\mathcal{P}$ , then  $\mathbb{R}^q(n, d)$  also has it as well. For m to be drawn from a Poisson distribution where the graph has connectivity  $\lambda$ , we require  $m = n(\log n + (\lambda - 1)\log\log n + c)/d \sim \mathcal{O}(n^{1-\epsilon}\log n)$  for some finite constant c [27]. Thus, there exists a  $d_0$  such that, for  $d > d_0$ , the existence of OGP is present in the solution space of Max-q-XORSAT on Random Regular hypergraph  $\mathbb{R}^q(n, d)$  with high probability meaning that the result of [8] also applies to random regular hypergraphs.

## References

[1] Dimitris Achlioptas, Amin Coja-Oghlan, and Federico Ricci-Tersenghi. On the solution-space geometry of random constraint satisfaction problems. Random Structures & Algorithms, 38(3):251–268, 2011. URL: https://onlinelibrary.wiley.com/doi/abs/10.1002/rsa.20323, arXiv:https://onlinelibrary.wiley.com/doi/pdf/10.1002/rsa.20323, doi:10.1002/rsa.20323.

- [2] Ahmed El Alaoui and Andrea Montanari. Algorithmic thresholds in mean field spin glasses, 2020. arXiv:2009.11481.
- [3] Joao Basso, Edward Farhi, Kunal Marwaha, Benjamin Villalonga, and Leo Zhou. The quantum approximate optimization algorithm at high depth for maxcut on large-girth regular graphs and the Sherrington-Kirkpatrick model. Schloss Dagstuhl Leibniz-Zentrum für Informatik, 2022. URL: https://drops.dagstuhl.de/opus/volltexte/2022/16514/, doi:10.4230/LIPICS.TQC.2022.7.
- [4] Joao Basso, David Gamarnik, Song Mei, and Leo Zhou. Performance and limitations of the QAOA at constant levels on large sparse hypergraphs and spin glass models. In 2022 IEEE 63rd Annual Symposium on Foundations of Computer Science (FOCS). IEEE, oct 2022. URL: https://doi.org/10.1109%2Ffocs54457.2022.00039, doi:10.1109/focs54457.2022.00039.
- [5] Béla Bollobás. A probabilistic proof of an asymptotic formula for the number of labelled regular graphs. European Journal of Combinatorics, 1(4):311–316, 1980. URL: https://www.sciencedirect.com/science/article/pii/S0195669880800308, doi:10.1016/S0195-6698(80)80030-8.
- [6] Antares Chen, Neng Huang, and Kunal Marwaha. Local algorithms and the failure of log-depth quantum advantage on sparse random csps, 2023. arXiv:2310.01563.
- [7] Wei-Kuo Chen, David Gamarnik, Dmitry Panchenko, and Mustazee Rahman. Suboptimality of local algorithms for a class of max-cut problems. *The Annals of Probability*, 47(3), may 2019. URL: https://doi.org/10.1214% 2F18-aop1291, doi:10.1214/18-aop1291.

[8] Chi-Ning Chou, Peter J. Love, Juspreet Singh Sandhu, and Jonathan Shi. Limitations of Local Quantum Algorithms on Random MAX-k-XOR and Beyond. In Mikołaj Bojańczyk, Emanuela Merelli, and David P. Woodruff, editors, 49th International Colloquium on Automata, Languages, and Programming (ICALP 2022), volume 229 of Leibniz International Proceedings in Informatics (LIPIcs), pages 41:1–41:20, Dagstuhl, Germany, 2022. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. URL: https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.ICALP.2022.41, doi:10.4230/LIPIcs.ICALP.2022.41.

- [9] Martin Dietzfelbinger, Andreas Goerdt, Michael Mitzenmacher, Andrea Montanari, Rasmus Pagh, and Michael Rink. Tight thresholds for cuckoo hashing via xorsat. In Samson Abramsky, Cyril Gavoille, Claude Kirchner, Friedhelm Meyer auf der Heide, and Paul G. Spirakis, editors, Automata, Languages and Programming, pages 213–225, Berlin, Heidelberg, 2010. Springer Berlin Heidelberg.
- [10] Andrzej Dudek, Alan Frieze, Andrzej Ruciński, and Matas Šileikis. Embedding the erdős-rényi hypergraph into the random regular hypergraph and hamiltonicity. *Journal of Combinatorial Theory, Series B*, 122:719–740, January 2017. URL: http://dx.doi.org/10.1016/j.jctb.2016.09.003, doi:10.1016/j.jctb.2016.09.003.
- [11] David Ellis and Nathan Linial. On regular hypergraphs of high girth. *Electron. J. Comb.*, 21:1, 2013. URL: https://api.semanticscholar.org/CorpusID:961773.
- [12] Edward Farhi, David Gamarnik, and Sam Gutmann. The Quantum Approximate Optimization Algorithm Needs to See the Whole Graph: A Typical Case. 4 2020. arXiv:2004.09002.
- [13] Edward Farhi, Jeffrey Goldstone, and Sam Gutmann. A quantum approximate optimization algorithm, 2014. arXiv:1411.4028.
- [14] Edward Farhi, Jeffrey Goldstone, Sam Gutmann, and Leo Zhou. The Quantum Approximate Optimization Algorithm and the Sherrington-Kirkpatrick Model at Infinite Size. Quantum, 6:759, July 2022. doi:10.22331/q-2022-07-07-759.
- [15] David Gamarnik. The overlap gap property: A topological barrier to optimizing over random structures. *Proceedings of the National Academy of Sciences*, 118(41), oct 2021. URL: https://doi.org/10.1073%2Fpnas.2108492118, doi:10.1073/pnas.2108492118.

[16] David Gamarnik and Quan li. Finding a large submatrix of a Gaussian random matrix. *Annals of Statistics*, 46, 02 2016. doi:10.1214/17-AOS1628.

- [17] David Gamarnik, Cristopher Moore, and Lenka Zdeborová. Disordered systems insights on computational hardness. *Journal of Statistical Mechanics: Theory and Experiment*, 2022(11):114015, nov 2022. URL: https://doi.org/10.1088%2F1742-5468%2Fac9cc8, doi:10.1088/1742-5468/ac9cc8.
- [18] David Gamarnik and Madhu Sudan. Limits of local algorithms over sparse random graphs. *The Annals of Probability*, 45(4):2353 2376, 2017. doi: 10.1214/16-A0P1114.
- [19] David Gamarnik and Ilias Zadik. The landscape of the planted clique problem: Dense subgraphs and the overlap gap property, 2019. arXiv: 1904.07174.
- [20] Mark Goh. The overlap gap property limits limit swapping, 2024. URL: https://github.com/capselo/The-Overlap-Gap-Property-limits-limit-swapping.
- [21] Brice Huang and Mark Sellke. Algorithmic threshold for multi-species spherical spin glasses, 2023. arXiv:2303.12172.
- [22] Richard M. Karp. Reducibility among Combinatorial Problems, pages 85–103. Springer US, Boston, MA, 1972. doi:10.1007/978-1-4684-2001-2\_9.
- [23] Tomasz Luczak. On the equivalence of two basic models of random graph. In *Proceedings of Random graphs*, volume 87, pages 151–159, 1990.
- [24] M. Mézard, T. Mora, and R. Zecchina. Clustering of solutions in the random satisfiability problem. *Physical Review Letters*, 94(19), May 2005. URL: http://dx.doi.org/10.1103/PhysRevLett.94.197205, doi: 10.1103/physrevlett.94.197205.
- [25] Dmitry Panchenko. The Parisi formula for mixed p-spin models. The Annals of Probability, 42(3), May 2014. URL: http://dx.doi.org/10.1214/12-AOP800, doi:10.1214/12-aop800.
- [26] G. Parisi. A Sequence of Approximated Solutions to the S-K Model for Spin Glasses. J. Phys. A, 13:L115, 1980. doi:10.1088/0305-4470/13/4/009.
- [27] Daniel J. Poole. On the strength of connectedness of a random hypergraph. *Electron. J. Comb.*, 22(1):1, 2015. doi:10.37236/4666.

[28] Subhabrata Sen. Optimization on sparse random hypergraphs and spin glasses. Random Structures & Algorithms, 53(3):504-536, 2018. URL: https://onlinelibrary.wiley.com/doi/abs/10.1002/rsa.20774, arXiv:https://onlinelibrary.wiley.com/doi/pdf/10.1002/rsa.20774, doi:10.1002/rsa.20774.

- [29] David Sherrington and Scott Kirkpatrick. Solvable model of a spin-glass. *Phys. Rev. Lett.*, 35:1792–1796, Dec 1975. URL: https://link.aps.org/doi/10.1103/PhysRevLett.35.1792, doi: 10.1103/PhysRevLett.35.1792.
- [30] J.M. Steele. Probability Theory and Combinatorial Optimization. CBMS-NSF Regional Conference Series in Applied Mathematics. Society for Industrial and Applied Mathematics, 1997. URL: https://books.google.de/books?id=inyEeSEqqtwC.
- [31] Michel Talagrand. The Parisi formula. *Annals of Mathematics*, 163(1):221–263, 2006. URL: http://www.jstor.org/stable/20159953.
- [32] Leo Zhou, Sheng-Tao Wang, Soonwon Choi, Hannes Pichler, and Mikhail D. Lukin. Quantum approximate optimization algorithm: Performance, mechanism, and implementation on near-term devices. *Physical Review X*, 10(2), June 2020. URL: http://dx.doi.org/10.1103/PhysRevX.10.021067, doi:10.1103/physrevx.10.021067.