

A multi-phase thermo-mechanical model for rock-ice avalanche

Shiva P. Pudasaini^{1,2}

¹Technical University of Munich, School of Engineering and Design
Chair of Landslide Research, Arcisstrasse 21, D-80333, Munich, Germany.

²Kathmandu Institute of Complex Flows, Kageshwori Manohara-3, Bhadrabas, Kathmandu, Nepal.

E-mail: shiva.pudasaini@tum.de

Abstract: We propose a novel physically-based multi-phase thermo-mechanical model for rock-ice avalanche. The model is built on a multi-phase mass flow model and extends a two-phase rock-ice avalanche model. It considers rock, ice and fluid; includes the mechanism of ice-melting and a rigorously derived dynamically changing general temperature equation for avalanching bulk mass, the first of its kind. It explains advection-diffusion of heat including the heat exchange across the rock-ice avalanche body, basal heat conduction, production and loss of heat due to frictional shearing and changing temperature, a general formulation of the ice melting rate and enhancement of temperature due to basal entrainment. The temperature equation includes a composite term containing coupled dynamics: rate of change of thermal conductivity and temperature. Ice melt intensity determines these rates as mixture conductivity evolves, characterizing distinctive thermo-mechanical processes. The model highlights essential aspects of rock-ice avalanches. Lateral heat productions play an important role in temperature evolution. Fast moving avalanches produce higher amount of heat. Fast ice melting results in substantial change in temperature. We formally derive the melting efficiency dependent general fluid production rate. The model includes internal mass and momentum exchanges between the phases and mass and momentum productions due to entrainment. The latter significantly changes the state of temperature; yet, the former exclusively characterizes rock-ice avalanche. Temperature changes are rapid when heat entrainment across the avalanche boundary is substantial. It also applies to basal heat conduction. A strong coupling exists between phase mass and momentum balances and the temperature equation. The new model offers the first-ever complete dynamical solution for simulating rock-ice avalanche with changing temperature.

1 Introduction

Glaciarized or permafrost-affected high mountain slopes often witness high-magnitude, low-frequency rock-ice avalanches. As rock-ice avalanche volumes can exceed hundreds of millions of cubic meter and can rush down the slope at speeds as high as 100s of ms^{-1} , sometimes traveling 10s of kilometers, these events usually pose serious risks and cause catastrophic damages when they reach populated regions (Evans et al., 2009; Huggel et al., 2009). People and infrastructure in these regions are increasingly threatened by rock-ice avalanches as their frequencies are increasing in recent decades (Schneider et al., 2011a, 2011b; Sosio et al., 2012).

Permafrost degradation, thermal perturbations, heat conduction and advection caused by climatic and hydrological causes result in the initiation of the rock detachment and rockfalls in high-Alpine steep rockwalls (Gruber and Haeberli, 2007; Huggel, 2009; Raveland and Deline, 2011). One example is the huge rock-ice masses that detached in Huascarán, Peru in 1962 and 1970 that caused thousands of casualties (Evans et al., 2009; Schneider et al., 2011a, 2011b; Mergili et al., 2018). The extremely mobile 2002 rock-ice avalanche in Kolka glacier, Russian Caucasus, is another recent example of such catastrophic event (Haeberli et al., 2004; Huggel et al., 2005; Evans et al., 2009; Schneider et al., 2011a). Particularly, these two events highlight a mechanical and a flow dynamical complexity of rock-ice avalanches. The main point is that, these events consisted of rock, ice, snow and water. Crucially, high ice content and melting of ice can quickly transform the initially solid-type rock-ice avalanches into highly viscous debris flows, which, however, depends on the fragmented fine particles and the colloids (Pudasaini and Krautblatter, 2014; Mergili et al., 2018; Pudasaini and Mergili, 2019). Consequently, such flows can propagate exceptionally long travel distances with very high velocities. The rock-ice avalanches are characterized by these effects as they are coupled with the relatively smooth sliding path consisting of the

rock beds, glacial deposits, glaciers and vegetation (Schneider et al., 2011a). So, due to the two main reasons, rock-ice avalanche events are more challenging than the other types of mass flows (Schneider et al., 2011a; Pudasaini and Krautblatter, 2014): (i) They consist of rock, ice, snow and fluid with different physical and rheological properties. (ii) During propagation, they show changing flow behavior as the ice fragments and ice and snow melt by frictional heating and changing temperature producing substantial amount of fluid that transforms the initial solid-type rock-ice avalanche into a multi-phase rock-ice-fluid debris flow.

Considerable attention has been paid in the past to investigate the physical modeling of flows and their numerical simulations, related to rock-ice avalanches (Schneider et al., 2010; Sosio et al., 2012; Pudasaini and Krautblatter, 2014; Sansone et al., 2021). Pudasaini and Krautblatter (2014) presented the first-ever two-phase model for rock-ice avalanches capable of performing dynamic strength weakening due to internal fluidization and basal lubrication, and internal mass and momentum exchanges between the phases. In this model, effective basal and internal friction angles are variable and correspond to evolving effective solid volume fraction, friction factors, volume fraction of the ice, true friction coefficients, and lubrication and fluidization factors. Their benchmark numerical simulations demonstrate that the two-phase model can explain some basic, dynamically changing frictional properties of rock-ice avalanches that occur internally and along the flow path. Internal mass and momentum exchanges between the phases, and the associated internal and basal strength weakening provide a more realistic simulation and explain the exceptionally long runout distances and dynamically changing high mobilities of rock-ice avalanches.

However, field and laboratory observations on rock-ice mass movements clearly reveal changing flow properties from solid-like to fluid-like and thus largely showing the multi-phase nature of the flow as a mixture of rock, ice and fluid as the rock-ice mass propagates downslope (Schneider et al., 2011b; Mergili et al., 2018; Shugar et al., 2021). Thus, the more realistic simulations can be performed with a real multi-phase (or, three-phase) mass flow simulation model. Moreover, it often entrains a large amount of basal material. Due to the shear heating and changing state of temperature of the rock-ice avalanche, the ice melts. So, changing temperature, melting ice and entrainments of the basal material are some fundamental characteristic features of naturally multi-phase rock-ice avalanche motion. However, the existing rock-ice avalanche model by Pudasaini and Krautblatter (2014) is only for two-phase flows, it does not include the basal entrainment, and the temperature evolution utilizing the ice melting is not considered. But, these aspects play important role in rock-ice avalanche. For these reasons, here, by including all these important features, we aim at fundamentally advancing our knowledge by proposing a physically-based, multi-phase mechanical model for rock-ice avalanches.

There are five major aspects of the proposed multi-phase mechanical model for rock-ice avalanches. (i) It is based on the multi-phase mass flow model (Pudasaini and Mergili, 2019), considering the rock, ice and fluid as three constituents in the avalanching mixture of the rock-ice mass. (ii) Extending the two-phase mechanical rock-ice avalanche model (Pudasaini and Krautblatter, 2014), it utilizes the principle of ice melting, internal mass and momentum exchanges between the solid (rock and ice) and fluid, basal lubrication and internal fluidization, and the resulting mechanical strength weakening of the avalanching mass. (iii) The unified multi-phase entrainment model (Pudasaini, 2022) is incorporated. (iv) A novel and general temperature evolution equation for rock-ice avalanche is developed here, that includes dynamically evolving mixture properties: density, heat capacity, thermal conductivity, heat exchange across the boundary of the avalanche, heat conduction at the sliding base, frictional shear heat production, internal heat loss due to the ice melting for which a general model is formally derived, and enhancement of the temperature due to the entrainment of the basal material. (v) Whereas (i)-(iii) are already existing separately, (iv) is fundamentally new for the motion of rock-ice avalanches. Yet, there are two main tasks here. First, developing a general temperature equation for the rock-ice avalanche and a unified ice melt rate. And, second, a description on how to combine all components (i)-(iv), creating a general, operational multi-phase thermo-mechanical model for rock-ice avalanche. The resulting model is truly governed by the dynamics of the phases with different physical properties and mechanical responses, interfacial momentum exchanges between the phases, material strength weakening, phase change with the melting of ice and the internal mass and momentum exchanges, entrainment of the basal material by the rock-ice avalanche, and the complex evolution of its temperature. Consequently, this constitutes a comprehensive rock-ice avalanche dynamical simulation model, the first of this kind in the mass flow simulation.

2 The model construction

In order to understand the material response to thermal changes of the rock-ice mass, we need the knowledge of its thermal properties. To our purpose, these properties include the thermal conductivity, heat capacity, thermal diffusivity and the latent heat (Andersland and Ladanyi, 2003; Heinze, 2024). Often, these parameters (properties) change with the type of material under consideration, its density, temperature, ice and water content and the saturation degree. These thermal parameters are defined as follows. Thermal conductivity refers to the heat conduction in the rock-ice mass that involves a transfer of kinetic energy from a warmer part to a cooler part. The amount of heat required to raise the temperature of a unit of the rock-ice mass by one degree Celsius is called its heat capacity. Then, the specific heat of the rock-ice mass is defined as the heat capacity per unit mass. The thermal conductivity characterizes the rate at which the heat is transferred in the rock-ice mass. The produced heat causes the rise in temperature that varies inversely with the heat capacity and the bulk density of the rock-ice mass. The ratio of the thermal conductivity and the product of these quantities is called the thermal diffusivity of the rock-ice mass. The amount of heat energy absorbed when a unit of ice mass is converted into a liquid at the melting point is defined as its latent heat of fusion. The same amount of heat is released when the water is converted into ice with no change in temperature. For more on it, we refer to Robertson (1988), Andersland and Ladanyi (2003) and Heinze (2024). With these descriptions of the thermal quantities, we now proceed to the model development.

2.1 The basic temperature equation

First, we define some basic and induced (or composite) variables and parameters involved in the derivation of the temperature equation for rock-ice avalanches. Let, t be time, x, y, z be the coordinates along and across the slope and perpendicular to the sliding surface, and g^x, g^y, g^z be the components of gravitational acceleration along the coordinate directions, respectively. Let, $k = r, i, f$ indicate the rock, ice and fluid phases in the mixture. Then, $\alpha_k, \mathbf{u}_k = (u_k, v_k, w_k), \rho_k, c_k$ and κ_k are the volume fractions, velocities, densities, specific heat capacities and thermal conductivities of the phases. Next, we introduce the bulk properties of the mixture of rock, ice and fluid. The following bulk properties are involved (Clauser, 2009; Heinze, 2024): temperature T , density $\rho = \sum \alpha_k \rho_k$, velocity $\mathbf{u} = \sum \alpha_k \mathbf{u}_k$ ($\mathbf{u} = u, v, w$), specific heat capacity $c = \sum \alpha_k c_k$, thermal conductivity $\kappa = \sum \alpha_k \kappa_k$, and heat source and sink Q^+, Q^- , respectively.

As the first major task, here, we develop a dynamically evolving general temperature equation for the rock-ice avalanche. For this, we begin with the basic temperature equation. The temperature evolution plays a crucial role in the thermo-mechanical response and the dynamics of the rock-ice avalanche. This is so, because, the ice-melting and the temperature evolution are tightly related.

Considering the low internal shear rate, as often considered in mass flow simulation (Pudasaini and Hutter, 2007), we assume that the internal viscous heating can be ignored. Then, the temperature equation takes the form (Clauser, 2009; Dall’Amico et al., 2011; Heinze, 2021):

$$\frac{\partial}{\partial t} (\rho c T) + \frac{\partial}{\partial x} (\rho c u T) + \frac{\partial}{\partial y} (\rho c v T) + \frac{\partial}{\partial z} (\rho c w T) - \frac{\partial}{\partial x} \left(\kappa \frac{\partial T}{\partial x} \right) - \frac{\partial}{\partial y} \left(\kappa \frac{\partial T}{\partial y} \right) - \frac{\partial}{\partial z} \left(\kappa \frac{\partial T}{\partial z} \right) = Q^+ - Q^-. \quad (1)$$

This is an advection-diffusion equation for the evolution of the temperature of a body with source terms for the heat production and loss. This is the basic temperature equation for the bulk mixture of rock, ice and fluid.

2.2 The depth-averaging and thermo-mechanical closures

Functional landslide, avalanche and debris flow models are depth-averaged (Hungr and McDougall, 2004; Pitman and Le, 2005; Pudasaini and Hutter, 2007; Christen et al., 2010; Pudasaini, 2012; Pudasaini and Mergili, 2019). Yet, none of them include the important physical properties and dynamical evolution of the temperature of the sliding mass. We need to depth-average the temperature equation (1) in order to combine it with the existing balance equations for mass and momentum such that the resulting set of equations describe the overall picture of the rock-ice mass in motion. For this, we integrate (1) through the depth h ($h = s - b$) from the basal surface

b to the free-surface s of the avalanche (Pudasaini and Hutter, 2007; Pudasaini, 2012). Depth-averaging of a quantity $*$ is denoted by $\bar{*}$, and is defined as:

$$\bar{*} = \frac{1}{h} \int_b^s * dz. \quad (2)$$

Depth-averaging requires the implementation of the kinematic boundary conditions at the free- and the basal-surfaces, which, respectively, are:

$$\frac{\partial s}{\partial t} + u^s \frac{\partial s}{\partial x} + v^s \frac{\partial s}{\partial y} - w^s = 0, \quad (3)$$

$$\frac{\partial b}{\partial t} + u^b \frac{\partial b}{\partial x} + v^b \frac{\partial b}{\partial y} - w^b = -E_t, \quad (4)$$

where E_t is the flow-induced total erosion rate at the basal surface (Pudasaini, 2022), and the basal material is entrained into the rock-ice avalanche with this rate. The quantities with superscripts s and b indicate that these quantities are evaluated at the free-surface of the flow and the basal surface, respectively. Here, we assume that the mean of the product is the product of the mean (Pudasaini, 2012), which is equivalent to assume that the variations of the bulk properties (e.g., ρ and c) through the avalanche depth is negligible.

2.2.1 Advection

Now, depth-averaging the terms associated with the time variation and advection of temperature on the left hand side of (1), following the Leibniz rule of integrating the differentiation (Pudasaini and Hutter, 2007), and applying the kinematic boundary conditions (3)-(4), we obtain:

$$\int_b^s \left[\frac{\partial}{\partial t} (\rho c T) + \frac{\partial}{\partial x} (\rho c u T) + \frac{\partial}{\partial y} (\rho c v T) + \frac{\partial}{\partial z} (\rho c w T) \right] dz = \frac{\partial}{\partial t} (h \overline{\rho c T}) + \frac{\partial}{\partial x} (h \overline{\rho c u T}) + \frac{\partial}{\partial y} (h \overline{\rho c v T}) - \rho^b c^b T^b E_t, \quad (5)$$

where $\rho^b c^b$ is the thermal capacity (Clauser, 2009) and T^b is the temperature of the entrainable bed material.

2.2.2 Diffusion, heat transfer across the boundary

Depth-averaging diffusion terms is mathematically and thermo-mechanically much more demanding and challenging than the time rate of change and advection terms. Repeatedly depth-averaging the first diffusion term on the left hand side of (1) yields:

$$\int_b^s \frac{\partial}{\partial x} \left(\kappa \frac{\partial T}{\partial x} \right) dz = \frac{\partial}{\partial x} \left[\int_b^s \left(\kappa \frac{\partial T}{\partial x} \right) dz \right] - \left[\kappa \frac{\partial T}{\partial x} \frac{\partial z}{\partial x} \right]_b^s = \frac{\partial}{\partial x} \left[\bar{\kappa} \left\{ \frac{\partial}{\partial x} \left(\int_b^s T dz \right) - \left(T \frac{\partial z}{\partial x} \right)_b^s \right\} \right] - \left[\kappa \frac{\partial T}{\partial x} \frac{\partial z}{\partial x} \right]_b^s. \quad (6)$$

We assume that the depth variation of κ , T and the lateral gradients of T are negligible. Within the framework of the depth-averaged modeling, these approximations can be perceived for the quantities attached to the landslide body (Pudasaini, 2012). Then, (6) reduces to

$$\int_b^s \frac{\partial}{\partial x} \left(\kappa \frac{\partial T}{\partial x} \right) dz = \frac{\partial}{\partial x} \left[\bar{\kappa} \frac{\partial}{\partial x} (h \bar{T}) \right] - \frac{\partial}{\partial x} \left[\bar{\kappa} \bar{T} \frac{\partial h}{\partial x} \right] - \bar{\kappa} \frac{\partial \bar{T}}{\partial x} \frac{\partial h}{\partial x}. \quad (7)$$

Repeatedly applying the product rule of differentiation to (7), and simplifying the outcome results in:

$$\int_b^s \frac{\partial}{\partial x} \left(\kappa \frac{\partial T}{\partial x} \right) dz = h \left[\bar{\kappa} \frac{\partial^2 \bar{T}}{\partial x^2} + \frac{\partial \bar{\kappa}}{\partial x} \frac{\partial \bar{T}}{\partial x} \right]. \quad (8)$$

Analogously, repeatedly depth-averaging the second diffusion term on the left hand side of (1) and applying the product rule of differentiation to it yields:

$$\int_b^s \frac{\partial}{\partial y} \left(\kappa \frac{\partial T}{\partial y} \right) dz = h \left[\bar{\kappa} \frac{\partial^2 \bar{T}}{\partial y^2} + \frac{\partial \bar{\kappa}}{\partial y} \frac{\partial \bar{T}}{\partial y} \right]. \quad (9)$$

Moreover, depth-averaging the third diffusion term on the left hand side of (1) turns it into:

$$\int_b^s \frac{\partial}{\partial z} \left(\kappa \frac{\partial T}{\partial z} \right) dz = \left[\kappa \frac{\partial T}{\partial z} \right]_b^s = \kappa^s \left(\frac{\partial T}{\partial z} \right)^s - \kappa^b \left(\frac{\partial T}{\partial z} \right)^b \approx -\frac{\kappa^s}{h_s} (T - T^s) + \frac{\kappa^b}{h_b} (T^b - T), \quad (10)$$

where, h_s and h_b are some fractions of the flow depths ($1/h_s$ and $1/h_b$ are called the specific heat exchange areas, area per unit volume; Heinze, 2021, 2024) that are significantly influenced by the heat exchange across the free-surface and the basal substrate. And, T^s , T^b are the ambient atmospheric and ground temperatures, respectively. The structure (10) is the formal description of heat fluxes across the avalanche boundary. Nevertheless, for rapid motion of the rock-ice avalanche, conductive heat transfer may not be the primary process of heat transfer between the body and its surrounding.

In practice, however, the heat fluxes across the boundary are empirically expressed differently. For simplicity, we can apply the Newton's law of heat exchange (transfer) across the free-surface of the avalanche and the basal sliding surface. Then, (10) can be written in alternative form as:

$$\int_b^s \frac{\partial}{\partial z} \left(\kappa \frac{\partial T}{\partial z} \right) dz \approx -\Lambda^s (1 + \lambda_v) A^s (T - T^s) + \Lambda^b (1 + \lambda_v) A^b (T^b - T), \quad (11)$$

where, Λ^s, Λ^b [$\text{Wm}^{-2}\text{K}^{-1}$] are the free-surface and basal heat exchange coefficients; A^s [-], A^b [-] are some fractions of the area exposed to the heat exchange at the free-surface and at the base; and λ_v is a non-dimensional number with the magnitude resembling that of the landslide velocity, $|\mathbf{u}|$. As introduced here, λ_v emerges legitimately, because, the convective heat exchange can also depend on the landslide velocity when it moves sufficiently fast, similar to the fluid flow in porous media (Heinze, 2021).

Equations (10) and (11) represent two fundamentally different processes and two different ways of modelling heat exchanges between the solid surface and the ambient fluid (at the free-surface), and between two solid surfaces (along the bed). As the derivation shows, (10) is the formal description of heat fluxes across the avalanche boundary, in principle, it is perceived physically and mathematically better than (11). As κ^s and κ^b are known from the phase fractions and the thermal conductivities of the phases at the free-surface and at the basal surface, with (10), the heat fluxes (heat transfers) across the avalanche boundary is fully explained. This is an advantage over the model (11) as the heat transfer coefficient in (11) are difficult to measure and determine (Heinze, 2021).

A crucial point in fast moving rock-ice avalanche is that, at the free-surface the heat exchange can be predominantly due to convective heat transfer. However, at the bottom, both the conductive and convective processes may contribute significantly and jointly. So, a better way to include both of these processes at the bed is by considering their linear combination with $\mathcal{P}_b \in [0, 1]$. Yet, in slow moving rock-ice avalanche, at the free-surface the heat exchange can be primarily due to conductive heat transfer. This demands for the inclusion of both of the conductive and convective heat transfer at the free-surface by considering their linear combination, say, with $\mathcal{P}_s \in [0, 1]$. These considerations allow us combining (10) and (11) to develop a general model for the heat transfer across the boundary as:

$$\int_b^s \frac{\partial}{\partial z} \left(\kappa \frac{\partial T}{\partial z} \right) dz = - \left[\mathcal{P}_s \Lambda^s (1 + \lambda_v) A^s + (1 - \mathcal{P}_s) \frac{\kappa^s}{h_s} \right] (T - T^s) + \left[\mathcal{P}_b \Lambda^b (1 + \lambda_v) A^b + (1 - \mathcal{P}_b) \frac{\kappa^b}{h_b} \right] (T^b - T). \quad (12)$$

Depending on the situation, the basal heat transfer may be dominated either by the conductive ($\mathcal{P}_b \rightarrow 0$) or, by the convective ($\mathcal{P}_b \rightarrow 1$) process. However, for simplicity, one may consider the mean value with $\mathcal{P}_b = 0.5$. In principle, this also applies for the heat transfer at the free-surface of the avalanche.

The specific surface area can be calculated as $\frac{1}{h_b} = 6(1 - \alpha_f) \frac{1}{\lambda_n d_{ri}}$, where d_{ri} is a typical grain diameter of the rock-ice mixture, which also applies to the cubic element of size d_{ri} , and λ_n indicates that the effective heat exchange depth is a multiple of the grain size, typically, say 5 to 10. In general, for larger particle size λ_n can be small, and for smaller particle size λ_n can take larger values. More complex expressions for the specific area for flows in porous media are provided in Heinze (2024). For more on these and other parameters appearing in the above expressions, we refer to Robertson (1988), Crisp and Baloga (1990), Andersland and Ladanyi (2003), Costa and Macedonio (2005) and Clauser (2009).

2.2.3 Frictional shear heating

In avalanching motion, frictional shearing produces heat (Sosio et al., 2012; Pudasaini and Krautblatter, 2014). We assume that, dominant shearing takes place in the xz and yz planes (in the flow depth direction) perpendicular to the sliding surface xy . Then, the heat produced by shear (Q^+) per unit volume, per unit time, is given by (Leloup et al., 1999; Young et al., 2022):

$$Q^+ = \tau_{xz} \frac{\partial u}{\partial z} + \tau_{yz} \frac{\partial v}{\partial z}, \quad (13)$$

where τ_{xz} and τ_{yz} are the shear stresses in the xz and yz planes, respectively. In (13), $\tau_{xz} = \rho_{ri} g^z (s - z) \mu_{ri} \alpha_{ri} \frac{u}{|\mathbf{u}|}$ and $\tau_{yz} = \rho_{ri} g^z (s - z) \mu_{ri} \alpha_{ri} \frac{v}{|\mathbf{u}|}$ are the shear stresses with the slope normal load $\rho_{ri} g^z (s - z) \alpha_{ri}$ of the avalanche, $\alpha_{ri} = (\alpha_r + \alpha_i)$ is the fraction, $\rho_{ri} = (\rho_r \alpha_r + \rho_i \alpha_i) / (\alpha_r + \alpha_i)$ is the density, and $\mu_{ri} = (\alpha_r \mu_r + \alpha_i \mu_i) / (\alpha_r + \alpha_i)$ is the basal friction coefficient for the rock and ice combined. Now, depth-averaging the heat source term Q^+ in (13), we obtain:

$$\overline{Q^+} = l_s \frac{1}{2} \overline{\rho_{ri} g^z h \alpha_{ri} \mu_{ri}} \left[\frac{\overline{u}}{|\overline{\mathbf{u}}|} (u^s - u^b) + \frac{\overline{v}}{|\overline{\mathbf{u}}|} (v^s - v^b) \right], \quad (14)$$

where, l_s is a number indicating that only a fraction of the shear heat is transferred to the avalanche causing the ice melt, typically $l_s \in (0.3, 0.7)$ (Sosio et al., 2012), and $|\overline{\mathbf{u}}| = \sqrt{\overline{u}^2 + \overline{v}^2}$. The velocity differences through the depth ($u^s - u^b$) and ($v^s - v^b$) can be approximated by the basal slip velocities u^b and v^b as $(u^s - u^b) = \chi_u u^b$ and $(v^s - v^b) = \chi_v v^b$, where $\chi_u > 0$ and $\chi_v > 0$ are some quantities. Note that $\chi_u \rightarrow 0$ and $\chi_v \rightarrow 0$ correspond to the situation closer to the basal slip, because, for this, $u^s \rightarrow u^b$ and $v^s \rightarrow v^b$, while $\chi_u \rightarrow 1$ and $\chi_v \rightarrow 1$ represent strong shearing through the depth, because, for this, $u^s \rightarrow 2u^b$ and $v^s \rightarrow 2v^b$. Other admissible values of χ_u and χ_v can model different scenarios. With this, (14) can be simplified to yield:

$$\overline{Q^+} = \frac{1}{2} l_s \overline{\rho_{ri} g^z h \alpha_{ri} \mu_{ri}} \left(\chi_u \frac{\overline{u}}{|\overline{\mathbf{u}}|} u^b + \chi_v \frac{\overline{v}}{|\overline{\mathbf{u}}|} v^b \right). \quad (15)$$

Because of the presence of the mixture properties $\overline{\rho_{ri}}$, $\overline{\alpha_{ri}}$ and $\overline{\mu_{ri}}$, the formally derived heat source in (15) is an extension to the previously considered frictional energy dissipation in Sosio et al. (2012), and its application to the two-phase rock-ice avalanche model and simulation by Pudasaini and Krautblatter (2014). But, the new heat source involves a factor $\chi/2$, where $1/2$ appears from the formal depth-averaging of the shear stress, and χ originates due to the in-depth shearing of the velocity. In this respect, even for a single-phase flow, the heat source in the previous models (Leloup et al., 1999; Sosio et al., 2012) are twice as much as what we formally derived here showing the substantial difference between the present model and the previous models which appear to overestimate the heat production. However, such a formal and general derivation and use of the frictional heat generation in the rock-ice avalanche, and its application to the temperature evolution (see later) of the truly multi-phase rock-ice-fluid debris avalanche is novel.

2.2.4 Frictional heat dissipation in ice melting

The frictional heat is dissipated as the ice melts. We assume that such a heat dissipation is proportional to the rate of ice melt (per unit density) due to friction (Pudasaini and Krautblatter, 2014). Then, from (13)

$$M_i = \frac{l_s}{L_i \rho_i} \left[\tau_{xz} \frac{\partial u}{\partial z} + \tau_{yz} \frac{\partial v}{\partial z} \right], \quad (16)$$

which is a function of the latent heat L_i (Andersland and Ladanyi, 2003) and involves the ice density ρ_i . So, the heat dissipation in melting is given by:

$$Q^- = \frac{l_s C_i \rho_{ri}}{L_i \rho_i} g^z (s - z) \mu_{ri} \alpha_{ri} \left(\frac{u}{|\mathbf{u}|} \frac{\partial u}{\partial z} + \frac{v}{|\mathbf{u}|} \frac{\partial v}{\partial z} \right). \quad (17)$$

where, the coefficient C_i emerges due to the dimensional consistency, and has the dimension of $L_i \rho_i$ (with plausibly minimal values probably closer to unity). For ease of notation, we combine l_s and C_i together, and simply write as $C_{l_s} = l_s C_i$. We call C_{l_s} the frictional ice melt coefficient due to shearing. Depth-averaging (17), and following the procedure as in (14) and (15), leads to

$$\overline{Q^-} = \frac{1}{2} \frac{\overline{C_{l_s}}}{L_i} \frac{\overline{\rho_{ri}}}{\overline{\rho_i}} g^z h \overline{\alpha_{ri}} \overline{\mu_{ri}} \left(\chi_u \frac{\overline{u}}{|\overline{\mathbf{u}}|} u^b + \chi_v \frac{\overline{v}}{|\overline{\mathbf{u}}|} v^b \right). \quad (18)$$

The heat dissipation in ice melting given by (18) is an extension to the heat dissipation utilized in Sosio et al. (2012) and its use in the mechanical modeling and dynamic simulation of the two-phase rock-ice avalanche by Pudasaini and Krautblatter (2014). However, the formal, consistent and the general derivation (18) of the heat dissipation in relation to the temperature evolution (see later) in truly multi-phase rock-ice-fluid avalanche is new. This is so, because, (18) includes: (i) the heat dissipation in both the flow directions, (ii) the formal mean indicated by $\frac{1}{2} \left(\chi_u \frac{\overline{u}}{|\overline{\mathbf{u}}|} u^b + \chi_v \frac{\overline{v}}{|\overline{\mathbf{u}}|} v^b \right)$ of the slope normal load producing heat, and (iii) the mechanical consistency coefficient C_i , whereas (18) characteristically involves the latent heat L_i , and the density of ice ρ_i , and C_{l_s} probably also contains the physical properties of the mixture. Moreover, the heat dissipation in ice melting (18) is rigorously derived, and is based on the mechanics of the rock-ice avalanche.

2.2.5 Ice melt rates

I. Ice melt rate due to frictional shearing

From the derivations above, we obtain the depth-averaged ice melt rate, or the fluid mass production rate, due to frictional shearing (indicated by the superscript s in \mathcal{M}_p^s) as:

$$\mathcal{M}_p^s = \left[\rho_i \frac{1}{2} \frac{l_s}{L_i} \frac{\rho_{ri}}{\rho_i} g^z \mu_{ri} \alpha_{ri} h \left(\chi_u \frac{u}{|\mathbf{u}|} u^b + \chi_v \frac{v}{|\mathbf{u}|} v^b \right) \right] = M_{pf}^s \left[\alpha_{ri} h \left(\chi_u \frac{u}{|\mathbf{u}|} u^b + \chi_v \frac{v}{|\mathbf{u}|} v^b \right) \right], M_{pf}^s = \frac{1}{2} \frac{l_s}{L_i} \rho_{ri} g^z \mu_{ri}, \quad (19)$$

where, M_{pf}^s is the fluid mass production rate factor associated with the frictional shearing. These rate and factor are written in the structure that already appear in Pudasaini and Krautblatter (2014), but here, they are formally derived for the multi-phase mixture, and are in general form.

II. Ice melt rate due to changing temperature

The ice melt rate can also be related to the state of temperature. The amount of available energy for melting (denoted by the subscript m in Q_m) of frozen water is given by

$$Q_m = \rho_i c_i (T_i - T_{ph}), \quad (20)$$

where, T_{ph} is the temperature of the phase transition (Kelleners et al., 2016; Heinze, 2021), typically 0°C (freezing/melting point), and (20) is applied when $T_i > 0$. In general, one may also replace T_i in (20) by T_{si} , indicating the temperature of the material surrounding the ice. Then, the amount of frozen water per unit volume that can be melted with this energy turns out to be (Kelleners et al., 2016; Heinze, 2021):

$$-\frac{Q_m}{L_i} = -\frac{1}{L_i} \rho_i c_i (T_i - T_{ph}). \quad (21)$$

Depth-averaging (21) yields

$$-\overline{\frac{c_i}{L_i}} (\overline{T_i} - \overline{T_{ph}}) h. \quad (22)$$

So, the time rate of change of the frozen water becomes:

$$-\frac{\partial}{\partial t} \left[\overline{\frac{c_i}{L_i}} (\overline{T_i} - \overline{T_{ph}}) h \right]. \quad (23)$$

With this, the depth-averaged ice melt rate, or the fluid mass production rate, due to change in temperature (indicated by the superscript t in \mathcal{M}_p^t) is given by:

$$\mathcal{M}_p^t = \frac{\partial}{\partial t} \left[\frac{1}{L_i} \rho_i c_i (T_i h - T_{ph} h) \right], \quad (24)$$

where, as before, for simplicity, the over bars are removed. Heinze (2021) provides a numerical procedure on how to deal with T_{ph} for the time difference form of (24).

Although, at a first glance, (24) is very appealing, from a dynamical point of view, it bears its intricacy. There are two main reasons for that. First, it involves the temperature of the ice fraction T_i , rather than the bulk temperature T as in the temperature equation (see Section 2.3). We may tackle this problem by assuming that the ice temperature and the bulk temperature is connected by a relation of the type $T_i = \lambda_i T$, where λ_i needs to be parameterized, or given a proper value, probably closer to unity if the rock-ice mixture and the ice has similar temperature. This can be perceived as a reasonable undertaking because, as the ice melts, the surrounding temperature declines resulting in a decreased bulk temperature. Otherwise, its value may deviate away from unity. With this, (24) can be simplified to yield

$$\mathcal{M}_p^t = \frac{\partial}{\partial t} \left[\frac{1}{L_i} \rho_i c_i (\lambda_i h T - h T_{ph}) \right]. \quad (25)$$

Second, unlike (19), which does not involve any time or spatial rates of the field variables, (24), or (25) involves a time rate. So, whereas (19) is put (with proper sign, + for the fluid production rate, and - for the ice loss rate) on the right hand side of the balance equations for fluid and ice phases, due to its structure, (25) needs to be united (with proper sign) with the time rate of changes of the fluid and ice masses on the left hand side of the respective mass balance equations (Pudasaini and Krautblatter, 2014). This way, (25) can be well embedded into the standard phase mass balance equations considering the mass production and loss for the fluid and the ice phase in the rock-ice avalanche. The same applies to the momentum productions for the phases associated with the ice melting.

III. The effective ice melt rate

We now have two differently derived models to calculate the ice melt rate or the fluid production rate in the rock-ice avalanche: (i) as given by (19) due to shear heating and, (ii) given by (25) due to the changing temperature, respectively. However, structurally and thermo-mechanically, they are essentially distinct, and they influence the mass and momentum balances differently. This is important to perceive. In principle, the mechanism of (19) and its impact in the balance equations are known (Pudasaini and Krautblatter, 2014). However, as (25) is novel, its embedding into the mass and momentum balance equations needs to be analyzed carefully. Moreover, selection of (19) or (25), or probably even better their combination, is a technical question for practitioners. This also helps to scrutinize the practical appropriateness of these models and their combination.

For fast moving landslides, the frictional shear heating may dominate the ice melting process over the ice melting due to the changes in temperature (from within or external sources). However, for slow moving landslides, the frictional shear heating may be small, but the ice melting due to the changing temperature of the landslide body (resulting from within or external sources, e.g., the heat fluxes across the basal surface and the free-surface) may be crucial. So, it is preferred to combine both of the melting processes. Therefore, for general purpose, we suggest to take a linear combination between the ice melt rate due to the shear heating and the changing temperature. Let, the effective (total) ice melt rate be denoted by \mathcal{M}_p , and $\mathcal{P}_m \in [0, 1]$ provides a linear combination between \mathcal{M}_p^s and \mathcal{M}_p^t . Then, from (19) and (25), the effective and unified ice melt rate is given by

$$\mathcal{M}_p = \mathcal{P}_m \left[\frac{1}{2} \frac{l_s}{L_i} \rho_{ri} g^z \mu_{ri} \alpha_{ri} h \left(\chi_u \frac{u}{|\mathbf{u}|} u^b + \chi_v \frac{v}{|\mathbf{u}|} v^b \right) \right] + (1 - \mathcal{P}_m) \frac{\partial}{\partial t} \left[\frac{1}{L_i} \rho_i c_i (\lambda_i h T - h T_{ph}) \right], \quad (26)$$

where \mathcal{P}_m closer to 1 represents the dominantly frictional heat induced ice melting, whereas \mathcal{P}_m closer to 0 represents the ice melting rate principally dominated by the changes in the temperature. However, without

loss of generality, one may also choose $\mathcal{P}_m = 0.5$, the mean value between \mathcal{M}_p^s and \mathcal{M}_p^t , providing a simple possibility.

This completes the depth-averaging and developing the necessary closures associated with the thermo-mechanical processes associated with the energy conservation of the rock-ice avalanche.

2.2.6 Internal mass and momentum exchanges

As derived above, $-\mathcal{M}_p$ and \mathcal{M}_p are the effective mass loss and production rates for the ice (solid) and fluid phases in the mixture. Multiplying these with the respective ice (solid) and fluid velocities result in the internal momentum exchange between the ice and fluid.

However, unlike the basal erosion rate E_t , $-\mathcal{M}_p$ and \mathcal{M}_p are associated with the ice and fluid, internal to the rock-ice avalanche. This means, there are two mass and momentum productions: (i) Internal to the mixture, the internal mass and momentum exchanges between the ice and fluid in the rock-ice avalanche as modeled by the production and loss rates associated with \mathcal{M}_p . Nonetheless, this does not (substantially) change the mass (volume) of the rock-ice avalanche. And, (ii) the mass and momentum production rates due to the entrainment of the basal material through the basal erosion rate E_t (Pudasaini, 2022). This amplifies (changes) the mass of the rock-ice avalanche in proportion to the newly entrained basal mass into the avalanching material. So, these two mass and momentum productions are fundamentally different processes in the rock-ice avalanche. While the second process can occur in any erosive mass transport, the first process is a very special characteristic property of the rock-ice avalanche for which Pudasaini and Krautblatter (2014) proposed the first two-phase simulation model, that is extended here for the multi-phase rock-ice avalanche. However, as evident, depending on their inherent processes, either (i) or (ii) or both may play important role in the dynamics of the rock-ice avalanche.

2.3 The temperature equation for rock-ice avalanche

With the entities, and the closures developed in (5), (8), (9), (12), (15), (18) and (25), the temperature equation (1) takes the form:

$$\begin{aligned}
& \frac{\partial}{\partial t} (\rho c h T) + \frac{\partial}{\partial x} (\rho c h u T) + \frac{\partial}{\partial y} (\rho c h v T) \\
& = \kappa h \left\{ \frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} \right\} + h \left\{ \frac{\partial \kappa}{\partial x} \frac{\partial T}{\partial x} + \frac{\partial \kappa}{\partial y} \frac{\partial T}{\partial y} \right\} \\
& - \left[\mathcal{P}_s \Lambda^s (1 + \lambda_v) A^s + (1 - \mathcal{P}_s) \frac{\kappa^s}{h_s} \right] (T - T^s) + \left[\mathcal{P}_b \Lambda^b A^b (1 + \lambda_v) + (1 - \mathcal{P}_b) \frac{\kappa^b}{h_b} \right] (T^b - T) \\
& + \frac{1}{2} \rho_{ri} g^z \alpha_{ri} \mu_{ri} h \left[l_s \left(1 - \mathcal{P}_m \frac{C_i}{L_i \rho_i} \right) \right] \left(\chi_u \frac{u}{|\mathbf{u}|} u^b + \chi_v \frac{v}{|\mathbf{u}|} v^b \right) \\
& - (1 - \mathcal{P}_m) l_t \frac{\partial}{\partial t} [\rho_i c_i (\lambda_i h T - h T_{ph})] + \rho^b c^b T^b E_t,
\end{aligned} \tag{27}$$

where, for notational convenience, the over bars have been omitted, and $\mathcal{S}_i = \left[l_s \left(1 - \mathcal{P}_m \frac{C_i}{L_i \rho_i} \right) \right]$ is the net heat production factor due to frictional shear, and, $l_t \in (0, 1)$ is a number indicating that the fraction of heat loss due to ice melt associated with the changing temperature is proportional to the ice melt rate due to changing temperature. One may simplify the situation by assuming $l_t \rightarrow 1$, if not, it remains a parameter as stated. Moreover, even for $\chi_u \approx 1$ and $\chi_v \approx 1$ we should retain the structure $\left(\chi_v \frac{u}{|\mathbf{u}|} u^b + \chi_v \frac{v}{|\mathbf{u}|} v^b \right)$ in this form without further simplification, because this preserves the information that shear resistances act against the landslide motions in the xz and yz planes. Furthermore, in (27), the temperature (heat) flux across the boundary, and the entrainment terms are kept as they are to retain the information of the boundary fluxes. Otherwise, these terms would disappear, or, do not properly represent the complex processes at the boundary, losing the crucial

physics of rock-ice avalanches. We call (27) the general temperature equation for rock-ice avalanche, the first of this kind in the simulation of relevant mass transport.

The model (27) explains the advection-diffusion of the temperature T of a column of rock-ice mass per unit (basal) area including the heat exchange across the avalanche body, basal heat conduction, the production and loss of heat due to the frictional shear heating and ice melting, and the enhancement of the temperature associated with the entrainment of the basal material.

It is important to note that as the deformation intensifies and the rock-ice mass rapidly propagates along the slope (Pudasaini and Krautblatter, 2014; Mergili et al., 2018; Shugar et al., 2021), its thermodynamic properties (namely ρ, c, κ) can evolve quickly. In this situation, we must very carefully consider the temperature equation (27) with respect to the appearance of these bulk parameters in their proper places.

2.4 Parameter estimates

Most of the physical parameters involved in the general temperature equation for rock-ice avalanche (27) are known or can be obtained from the literature (Robertson, 1988; Crisp and Baloga, 1990; Andersland and Ladanyi, 2003; Costa and Macedonio, 2005; Schneider et al., 2011a, 2011b; Sosio et al., 2012; Pudasaini and Krautblatter, 2014; Young et al., 2022; Heinze, 2024). We list here some of the plausible parameter values: densities: $\rho_r = 2900$, $\rho_i = 907$, $\rho_f = 1100$ [kgm^{-3}]; thermal conductivities: $\kappa_r = 3.36$, $\kappa_i = 2.25$, $\kappa_f = 0.55$ [$\text{Wm}^{-1}\text{K}^{-1}$]; specific heat capacities: $c_r = 1000$, $c_i = 2000$, $c_f = 4000$ [$\text{Jkg}^{-1} \text{ }^\circ\text{C}^{-1}$]; friction coefficients: $\mu_r = 0.8$, $\mu_i = 0.4$ [-]; and the latent heat for ice: $L_i = 333.7$ [KJm^{-3}]. Based on Crisp and Baloga (1990) and Costa and Macedonio (2005): the heat exchange coefficient at the free-surface: $\Lambda^s = 70$ [$\text{Wm}^{-2}\text{K}^{-1}$], and at the bed Λ^b can be assumed reasonably lower than Λ^s ; and the fraction of areas exposed to the heat exchange at the free-surface and the sliding bed: $A^s, A^b \in (0.001, 0.1)$ [-]. Yet, the numerical values for Λ^s and A^s, A^b are derived from lava flows, and thus must be properly adjusted (may differ, or reduce, substantially) for the rock-ice avalanche motion. Moreover, due to the inclusion of the parameter λ_v incorporating the velocity of the sliding mass, in reality, the parameter values mentioned above for Λ^s and Λ^b may be substantially lower. Furthermore, the atmospheric and ground temperatures T^s, T^b should be properly prescribed, e.g., in the range [-10, 20]; ice melt coefficient: $C_i \approx 1.0$ (or, otherwise, see Section 2.5); and the erosion rate E_t (determined mechanically, Pudasaini, 2022), or selected empirically (Mergili et al., 2018). Andersland and Ladanyi (2003) provides a collective list of thermal parameters for different geo-materials. Thermal conductivities: for water at 0°C and 10°C , $\kappa_w = 0.56$ and 0.58 ; for ice at 0°C , $\kappa_i = 2.21$; for sand gravel mixture $\kappa_{sg} = 1.3 - 1.7$; and for quartz, $\kappa_q = 8.4$ [$\text{Wm}^{-1}\text{K}^{-1}$]. Similarly, the specific heat capacities are as follows: for water at 0°C , $c_w = 4217$; for ice $c_i = 2090$; for the sand gravel mixture, $c_{sg} = 890$; and for quartz, $c_q = 733$ [$\text{Jkg}^{-1} \text{ }^\circ\text{C}^{-1}$], respectively.

2.5 Mechanism and essence of the temperature equation

The temperature equation (27) for rock-ice avalanches is structurally interesting and possesses many important thermo-mechanical and dynamical properties of rock-ice avalanches.

(i) It is mathematically consistent and physically-explained.

(ii) For constant temperature, the equation vanishes identically as the heat production and heat loss balance each other. From this identity, we may obtain the upper bound of C_i : $C_i \approx L_i \rho_i$. So, $C_i \in (1, L_i \rho_i)$ provides a plausible range for C_i . However, C_i may also lie outside of this range as it may depend on the material and thermal properties of the rock-ice mass.

(iii) The term $\left[h \left\{ \frac{\partial \kappa}{\partial x} \frac{\partial T}{\partial x} + \frac{\partial \kappa}{\partial y} \frac{\partial T}{\partial y} \right\} \right]$ on the right hand side of (27) constitutes a very special structure and is probably one of the most important innovations here. It emerged due to the variation of the mixture (thermal) conductivity κ . As the constituent volume fractions evolve due to the fragmentation of the rock and ice, and melting of the ice, leading to the changes in the fractions of the rock, ice and the fluid in the mixture, κ evolves accordingly. The intensity of fragmentation and melting determines the rates of changes of κ , i.e., $\partial \kappa / \partial x$ and

$\partial\kappa/\partial y$. So, this special structure tells that it contains two coupled dynamics in it: the rate of changes of κ (i.e., $\partial\kappa/\partial x$ and $\partial\kappa/\partial y$), and the rate of changes of temperature T (i.e., $\partial T/\partial x$ and $\partial T/\partial y$). In contrast to the term associated with classical diffusion $\left[\kappa h \left\{ \frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} \right\}\right]$ and advection $\left[\frac{\partial}{\partial x}(\rho c h u T) + \frac{\partial}{\partial y}(\rho c h v T)\right]$ processes, $\left[h \left\{ \frac{\partial\kappa}{\partial x} \frac{\partial T}{\partial x} + \frac{\partial\kappa}{\partial y} \frac{\partial T}{\partial y} \right\}\right]$ is the only term that involves variations of both of κ and T . So, this term characterizes the special thermo-mechanical processes and their dynamical consequences in rock-ice avalanche propagation in a coupled way as it describes the changing state of the moisture content of the rock-ice mass connected to the latent heat.

(iv) It includes the heat production due to shearing in both the flow directions.

(v) The heat exchanges through the boundary of the rock-ice avalanche with its surrounding play crucial role in the temperature evolution. The model (27) includes the velocity dependent heat transfer uniquely combining both the convective and conductive heat transfer processes at the free-surface and the bed. If the heat entrainment (or detrainment) across the avalanche boundary is substantial, then, the temperature changes are rapid.

(vi) Heat production is proportional to the normal load of the avalanche. So, thicker (heavier) avalanches produce more heat than the thinner (lighter) avalanches.

(vii) Depending on the shearing in the longitudinal or the lateral direction, either one or both of the longitudinal or lateral heat productions can play important to dominant role in the temperature evolution. The factor $\left(\chi_u \frac{u}{|\mathbf{u}|} u^b + \chi_v \frac{v}{|\mathbf{u}|} v^b\right)$ in (27) explains this behavior. Examples include the locally expanding and/or compacting flows in the inception, in the transition to the run-out, or the deposition process.

(viii) Fast moving (or deforming) avalanches produce higher amount of heat than the slow moving (deforming) avalanches. This is explained by the shear rates $\partial u/\partial z$ and $\partial v/\partial z$ in (13), equivalently, $\left(\chi_u \frac{u}{|\mathbf{u}|} u^b\right)$ and $\left(\chi_v \frac{v}{|\mathbf{u}|} v^b\right)$ in (27).

(ix) The ice melting rate controls the change of temperature of the rock-ice avalanche. Conversely, the changing temperature controls the ice melt rate. Fast ice melting means substantial change in the temperature of the avalanching body. Fluid mass production or ice mass loss also depends on the melting efficiency as described by the unified ice melt rate (26) which is a remarkable development here. In principle, re-freezing of the fluid (water) to ice can take place (Heinze, 2024). However, during the rapid motion of the rock-ice mass (Pudasaini and Krautblatter, 2014; Shugar et al., 2021), this is less likely to happen.

(x) Entrainment of the basal material into the propagating body changes the state of temperature of the rock-ice avalanche. The rock-ice avalanche temperature is enhanced if the entrained mass has higher temperature than the avalanche, and the rock-ice avalanche temperature is reduced if the entrained mass has lower temperature than the avalanche itself.

All these intrinsic properties indicate that the rock-ice avalanches are more complex than the other types of avalanches. In principle, none of these (mostly new) aspects can be compromised for the propagation of the rock-ice mass.

2.6 The model structure, unification and coupling

The temperature equation (27) and the effective ice melt rate (26) are now ready to be combined with the existing multi-phase mass flow model, together with the two-phase rock-ice avalanche model and the multi-phase erosion model. The final stage of the model development involves: (i) considering the multi-phase mass flow model (Pudasaini and Mergili, 2019), considering the rock, ice and fluid as three constituents in the avalanching mixture, (ii) utilizing the principles of ice melting, internal mass and momentum exchanges between the solid

(rock and ice) and fluid, basal lubrication and internal fluidization described by the two-phase mechanical rock-ice avalanche model (Pudasaini and Krautblatter, 2014), (iii) incorporating the unified multi-phase entrainment model (Pudasaini, 2022), and (iv) embedding the novel temperature evolution equation and the proposed unified ice melt rate for rock-ice avalanche into the multi-phase equations.

There are nine conservative state variables in the multi-phase mass flow model (Pudasaini and Mergili, 2019). These are: the phase flow depths: $(h_r = h\alpha_r, h_i = h\alpha_i, h_f = h\alpha_f)$, where $\alpha_r + \alpha_i + \alpha_f = 1$ is the hold-up identity and $h_r + h_i + h_f = h$ (the total flow depth); and the phase fluxes in the down slope and cross slope directions: $(h_r u_r, h_i u_i, h_f u_f)$, $(h_r v_r, h_i v_i, h_f v_f)$, respectively. By definition, the bulk velocities are $u = \alpha_r u_r + \alpha_i u_i + \alpha_f u_f$, and $v = \alpha_r v_r + \alpha_i v_i + \alpha_f v_f$. The same applies to the bulk density, specific heat capacity and thermal conductivity: $\rho = \alpha_r \rho_r + \alpha_i \rho_i + \alpha_f \rho_f$, $c = \alpha_r c_r + \alpha_i c_i + \alpha_f c_f$ and $\kappa = \alpha_r \kappa_r + \alpha_i \kappa_i + \alpha_f \kappa_f$. The temperature equation (27) and the ice melting rate (26) contain these quantities. This, together with the other parameters involved in (26) and (27), indicates a strong coupling between the existing mass and the momentum balance equations for the phases and the new temperature equation for the bulk motion of the rock-ice avalanche and the unified ice melt rate. The model (27) introduces an additional conservative variable $\rho c h T$ (for the transport of the bulk temperature) to the set of existing conservative variables in Pudasaini and Mergili (2019). So, all together, there are ten conservative (state) variables in the newly proposed multi-phase rock-ice avalanche model.

The existing and the widely used mass flow simulation codes, e.g., Pudasaini and Krautblatter (2014), and `r.avaflow` (Pudasaini and Mergili, 2019; Mergili and Pudasaini, 2024) can be directly expanded to include the new ice melt rate (26) and the temperature model (27) into the computational framework, making it a comprehensive tool for the simulation of rock-ice avalanche. This is a structural advantage. This completes the construction of the novel, multi-phase, thermo-mechanical model for rock-ice avalanches.

3 Summary

Here, we fundamentally advanced our knowledge by proposing a physically-based, multi-phase thermo-mechanical model for rock-ice avalanches. The main focus is the development of the general temperature equation for the rock-ice avalanche, the first of this kind in the simulation of mass transport. This explains the comprehensive advection-diffusion of the temperature of the rock-ice mass including the complex heat exchange processes across the avalanche body, basal heat conduction, the uniquely combined production and loss of heat due to the frictional shear heating and the ice melting, and the enhancement of the temperature associated with the entrainment of the basal material. The new temperature equation is structurally interesting and possesses many important thermo-mechanical and dynamical properties of rock-ice avalanches. It is mathematically consistent and physically-explained. It includes an important composite term, constituting a very special form and is a crucial innovation here. The intensity of fragmentation and melting determines its rate of changes. This special form contains two coupled dynamics in it: the rate of change of the thermal conductivity and the rate of change of temperature of the bulk mixture. It emerged due to the variation of the mixture conductivity. As the constituent volume fractions evolve due to the melting of the ice, the conductivity evolves accordingly. In contrast to the classical diffusion and the advection processes, this composite structure is the only term that involves the variation of both of these quantities. This term uniquely characterizes the special thermo-mechanical processes and their dynamical consequences in rock-ice avalanche propagation in a tightly coupled way.

The model highlights many essential thermo-mechanical aspects of rock-ice avalanches. Thicker avalanches produce more heat than the thinner avalanches. Longitudinal or lateral heat productions, that are included in the new temperature equation, play important role in the temperature evolution. Fast moving avalanches produce higher amount of heat than the slow moving avalanches. The shear heating and the change of temperature of the rock-ice avalanche controls the ice melting rate. Conversely, the fast ice melting results in the substantial change in the temperature of the avalanching body. The intensity of the fluid mass production (or ice mass loss) depends on the melting efficiency as described by the newly developed unified effective ice melt rate. The fluid mass production rate is formally derived for multi-phase mixture, and is in general form. Entrainment of the basal material into the propagating body changes the state of temperature of the rock-ice avalanche. The model

includes the internal mass and momentum exchanges between the ice and fluid in the rock-ice avalanche, and the mass and momentum production rates due to the entrainment of the basal material through the basal erosion. These mass and momentum productions are fundamentally different processes in the rock-ice avalanche. Yet, the first is an exclusive characteristic property of the rock-ice avalanche. However, both may play important role in the evolution of the temperature in the rock-ice avalanche. If the heat entrainment across the avalanche boundary is substantial, then, the temperature changes are rapid. It also applies to the basal heat conduction. We revealed that there exists a strong coupling between the existing mass and momentum balance equations for the phases and the newly proposed general temperature equation for the bulk motion of the rock-ice avalanche, and the unified ice melting rate. The novel multi-phase thermo-mechanical model for rock-ice avalanches provides a useful method for practitioners and mountain engineers in better solving the problems associated with the hazard mitigation and planning.

Acknowledgments

Financial support from the German Research Foundation (DFG) through the research project: “Landslide mobility with erosion: Proof-of-concept and application - Part I: Modelling, Simulation & Validation; Project number 522097187” is acknowledged.

References

- [1] Andersland, O.B., Ladanyi, B. (2003): *Frozen Ground Engineering*, 2nd Edition. Wiley.
- [2] Christen, M., Kowalski, J., Bartelt, P. (2010): RAMMS: Numerical simulation of dense snow avalanches in three-dimensional terrain. *Cold Reg. Sci. Technol.* 63, 1-14.
- [3] Clauser, C. (2009): Heat Transport Processes in the Earth’s Crust. *Surveys in geophysics* 30, 163-191.
- [4] Costa, A., Macedonio, G. (2005): Numerical simulation of lava flows based on depth averaged equations. *Geophysical Research Letters*, 32(5).
- [5] Crisp, J., Baloga, S. (1990): A model for lava flows with two thermal components. *Journal of Geophysical Research: Solid Earth* 95(B2), 1255-1270.
- [6] Dall’Amico, M., Endrizzi, S., Gruber, S., Rigon, R. (2011): A robust and energy-conserving model of freezing variably-saturated soil. *The Cryosphere* 5, 469-484. <https://doi.org/10.5194/tc-5-469-2011>, 2011.
- [7] Evans, S.G., Bishop, N.F., Smoll, L.F., Valderrama Murillo, P., Delaney, K.B., Oliver-Smith, A. (2009): A re-examination of the mechanism and human impact of catastrophic mass flows originating on Nevado Huascaran, Cordillera Blanca, Peru in 1962 and 1970. *Eng. Geol.* 108(1-2), 96-118.
- [8] Gruber, S., Haeberli, W. (2007): Permafrost in steep bedrock slopes and its temperature-related destabilization following climate Change. *J. Geophys. Res.* 112, F02S18, doi:10.1029/2006JF000547.
- [9] Haeberli, W., Huggel, C., Kääh, A., Zraggen-Oswald, Z., Polkvoj, A., Galushkin, I., Zotikov, I., Osokin, N. (2004): The Kolka-Karmadon rock/ice slide of 20 September 2002: An extraordinary event of historical dimensions in North Ossetia, Russian Caucasus. *J. Glaciol.* 50(171), 533-546.
- [10] Heinze, T. (2024): Multi-phase heat transfer in porous and fractured rock. *Earth-Science Reviews*, 251, 104730. <https://doi.org/10.1016/j.earscirev.2024.104730>.
- [11] Heinze, T. (2021): A multi-phase heat transfer model for water infiltration into frozen soil. *Water Resour. Res.* 57(10), 10.1029/2021WR030067.
- [12] Huggel, C. (2009): Recent extreme slope failures in glacial environments: Effects of thermal perturbation. *Quat. Sci. Rev.* 28, 1119-1130.
- [13] Huggel, C., Zraggen-Oswald, S., Haeberli, W., Kaab, A., Polkvoj, A., Galushkin, I., Evans, S. (2005): The 2002 rock/ice avalanche at Kolka/Karmadon, Russian Caucasus: Assessment of extraordinary avalanche formation and mobility, and application of QuickBird satellite imagery. *Nat. Hazards Earth Sys. Sci.* 5(2), 173-187.

- [14] Hungr, O., McDougall, S. (2004): A Model for the Analysis of Rapid Landslide Motion across Three-Dimensional Terrain. *Can. Geotech. J.* 41, 1084-1097.
- [15] Kelleners, T., Koonce, J., Shillito, R., Dijkema, J., Berli, M., Young, M., Massman, W. (2016): Numerical modeling of coupled water flow and heat transport in soil and snow. *Soil Science Society of America Journal* 80(2), 247-263. <https://doi.org/10.2136/sssaj2015.07.0279>.
- [16] Leloup, P.H., Ricard, Y., Battaglia, J., Lacassin, R. (1999): Shear heating in continental strike-slip shear zones: model and field examples. *Geophys. J. Int.* 136, 19-40.
- [17] Mergili, M., Pudasaini, S.P. (2024): r.avaflow - The mass flow simulation tool. [Software] <https://www.avaflow.org>.
- [18] Mergili, M., Frank, B., Fischer, J.-T., Huggel, C., Pudasaini, S.P. (2018): Computational experiments on the 1962 and 1970 landslide events at Huascarán (Peru) with r.avaflow: Lessons learned for predictive mass flow simulations. *Geomorphology* 322, 15-28.
- [19] Nield, D.A., Bejan, A. (2017): Heat Transfer Through a Porous Medium. In: *Convection in Porous Media*. Springer, Cham. https://doi.org/10.1007/978-3-319-49562-0_2.
- [20] Pitman, E.B., Le, L. (2005): A two-fluid model for avalanche and debris flows. *Philosophical Transactions of the Royal Society*, A363, 1573-1602.
- [21] Pudasaini, S.P. (2022): Unified Mechanical Erosion Model for Multi-phase Mass Flows. arXiv:2209.10880v1.
- [22] Pudasaini, S.P., Mergili, M. (2019): A multi-phase mass flow model. *J. Geophys. Res.-Earth* 124, 2920-2942.
- [23] Pudasaini, S.P., Krautblatter, M. (2014): A two-phase mechanical model for rock ice avalanches. *Journal of Geophysical Research: Earth Surface* 119, 2272-2290. <https://doi.org/10.1002/2014jf003183>.
- [24] Pudasaini, S.P. (2012): A general two-phase debris flow model. *Journal of Geophysical Research* 117, F03010. <https://doi.org/10.1029/2011JF002186>.
- [25] Pudasaini, S.P., Hutter, K. (2007): *Avalanche Dynamics: Dynamics of Rapid Flows of Dense Granular Avalanches*. Springer, Berlin, New York, ISBN 978-3-540-32687-8.
- [26] Raveland, L., Deline, P. (2011): Climate influence on rockfalls in high-Alpine steep rockwalls: The north side of the Aiguilles de Chamonix (Mont Blanc massif) since the end of the 'Little Ice Age'. *Holocene* 21, 357-365.
- [27] Robertson, E.C. (1988): Thermal properties of rocks. Open-File Report 88-441, US Geological Survey, Reston, Virginia.
- [28] Sansone, S., Zugliani, D., Rosatti, G. (2021): A mathematical framework for modelling rock-ice avalanches. *J. Fluid Mech.* 919, A8, doi:10.1017/jfm.2021.348.
- [29] Schneider, D., Bartelt, P., Caplan-Auerbach, J., Christen, M., Huggel, C., McArdell, B.W. (2010): Insights into rock-ice avalanche dynamics by combined analysis of seismic recordings and a numerical avalanche model. *J. Geophys. Res.* 115, F04026, doi:10.1029/2010JF001734.
- [30] Schneider, D., Huggel, C., Haeberli, W., Kaitna, R. (2011a): Unraveling driving factors for large rock-ice avalanche mobility. *Earth Surf. Processes Landforms* 36(14), 1948-1966.
- [31] Schneider, D., Kaitna, R., Dietrich, W.E., Hsu, L., Huggel, C., McArdell, B. (2011b): Frictional behavior of granular gravel-ice mixtures in vertically rotating drum experiments and implications for rock-ice avalanches. *Cold Reg. Sci. Technol.* 69(1), 70-90.
- [32] Shugar, D.H., Jacquemart, M., Shean, D., et al. (2021): A massive rock and ice avalanche caused the 2021 disaster at Chamoli, Indian Himalaya. *Science* 373, 300-306.
- [33] Sosio, R., Crosta, G.B., Chen, J.H., Hungr, O. (2012): Modelling rock avalanche propagation onto glaciers. *Quat. Sci. Rev.* 47, 23-40.
- [34] Young, T.J. et al. (2022): Rapid basal melting of the Greenland Ice Sheet from surface meltwater drainage. *PNAS* 119 No. 10. <https://doi.org/10.1073/pnas.2116036119>.