Jessica Enright 🖂 🗈

School of Computing Science, University of Glasgow, UK

Laura Larios-Jones ⊠ [®] School of Computing Science, University of Glasgow, UK

Kitty Meeks ⊠ [©] School of Computing Science, University of Glasgow, UK

William Pettersson ⊠ [[]D] School of Computing Science, University of Glasgow, UK

— Abstract

Reachability and other path-based measures on temporal graphs can be used to understand spread of infection, information, and people in modelled systems. Due to delays and errors in reporting, temporal graphs derived from data are unlikely to perfectly reflect reality, especially with respect to the precise times at which edges appear. To reflect this uncertainty, we consider a model in which some number ζ of edge appearances may have their timestamps perturbed by $\pm \delta$ for some δ . Within this model, we investigate temporal reachability and consider the problem of determining the maximum number of vertices any vertex can reach under these perturbations. We show that this problem is intractable in general but is efficiently solvable when ζ is sufficiently large. We also give algorithms which solve this problem in several restricted settings. We complement this with some contrasting results concerning the complexity of related temporal eccentricity problems under perturbation.

2012 ACM Subject Classification Mathematics of computing \rightarrow Graph algorithms; Theory of computation \rightarrow Graph algorithms analysis; Theory of computation \rightarrow Fixed parameter tractability

Keywords and phrases Graph algorithms, Parameterized Algorithms, Temporal Graphs

Funding Jessica Enright: Supported by EPSRC grant EP/T004878/1.Kitty Meeks: Supported by EPSRC grants EP/T004878/1 and EP/V032305/1.William Pettersson: Supported by EPSRC grants EP/T004878/1 and EP/X013618/1.

1 Introduction

Temporal graphs are widely used to model movement and spread in time-sensitive networks [1, 6, 10, 24, 27]. However, the algorithmic tools used in solving problems on these graphs typically assume that the temporal graphs as given are correct and without uncertainty — unfortunately this may not be the case for real-world networks (e.g. [8, 31]), and thus this assumption significantly limits the applicability of temporal graph methods.

For example, reachability is used as a measure to assess risk of outbreaks in epidemiologicallyrelevant graphs such as livestock trading networks or human or animal contact networks [25, 22]. It is clear that a calculated reachability may be incorrect if the temporal graph itself is incorrect. From an application perspective, the robustness of the temporal graph's reachability to incorrect timings is important: if a small number of incorrectly-recorded edge times can result in a huge increase in reachability, then this temporal graph is more epidemiologically risky than one in which a small number of incorrect edge times do not significantly increase reachability.

In this work we address the question: what is the complexity, given a specification of the number and magnitude of errors in the temporal graph's edge timings, of determining if the reachability of the temporal graph could be above some given threshold? Put another way, we ask if there exists a perturbation of the times allocated to edges that increases the

reachability above a target threshold. This second formulation makes clear a link to temporal graph modification questions — an active area of research studying the minimum number of modifications required to a temporal graph that allow it to satisfy some specified property.

Following the definition given by Kempe, Kleinberg and Kumar [26], we say that temporal graphs (G, λ) consist of an underlying graph G = (V, E) and a temporal assignment $\lambda : E(G) \to 2^{\mathbb{N}}$ which describes when each edge is active. We introduce the concept of a (δ, ζ) -perturbation where up to ζ time-edges of a temporal graph are changed by at most $\pm \delta$. We ask, given a temporal graph (G, λ) , if there is a perturbation of (G, λ) such that there is temporal path from some vertex in the graph to at least h vertices. With the framing of a transport network, this asks if we can reach h places from some starting point by connections which occur chronologically. In an epidemiological framework, this asks how many nodes could, in the worst case, be infected by a single initially-infected node.

In previous work, Deligkas and Potapov [12] consider delaying and merging operations to optimise maximum, minimum and average reachability where merging of time-edges assigns all edges which are active in a set of consecutive times the latest time in that set. They show that it is NP-hard to find a set of merging operations that maximises the maximum reachability of a temporal graph, even when the underlying graph is a path. In contrast, they show that finding a set of delaying operations to minimize the maximum reachability is tractable if the number of delays made is unbounded. In a similar way, we find that allowing a large number of perturbations makes our problem easier.

In more recent work, Deligkas et al. [11] investigate the problem which asks how *long* it takes to reach every vertex in a temporal graph from a set of sources following some delays. They consider variations of this problem where the number of delayed edges and total sum of delays must be at most k for some integer k, and show that this problem is W[2]-hard with respect to the number of edges changed and prove tractability when the underlying graph is a tree or has bounded treewidth. Delaying appearances of edges to optimise reachability is also studied by Molter et al. [30], who show that the problem becomes fixed-parameter tractable with respect to the number of delayed edges. Other work on temporal graph modification to optimise reachability has considered deleting edges or edge appearances [30, 16] and assigning times to edges in a static graph [17].

Some related work exists on computing structures and properties which are robust to perturbation. Fuchsle et al. [23] ask if there is a path between two given vertices which is robust to delays. In network design, fault-tolerance describes a network's robustness to uncertainty [2, 3, 7, 13, 14, 28]. Other models containing uncertainty allow for queries to find true values and aim to optimise the number of queries needed to find a solution [18, 19, 21, 20].

1.1 Our Contributions

Motivated by the idea of uncertainty in temporal graphs, we work with perturbations of temporal graphs, and focus on the computational complexity of a problem that asks whether there exists a perturbation of an input temporal graph such that there exists a source vertex has at least a minimum specified reachability. We:

- show that this problem is NP-hard in general, and W[2]-hard with respect to the number of edges perturbed (Section 2),
- show that the problem is tractable when the number of the perturbations allowed is very large (Section 3), and

show that the problem is tractable using a knapsack-based dynamic program when the underlying graph is a tree, or using a more complex tree decomposition-based algorithm when the underlying graph has bounded treewidth (Section 4).

To provide contrast with our results on the reachability problem, we briefly investigate (in Section 5) related eccentricity-based problems on temporal graphs with perturbations — in these problems we require not only that vertices are reached from a source, but that they are reached within a given number of edges (shortest eccentricity) or within a given travel duration (fastest eccentricity). In contrast to our findings for our reachability question, for fastest and shortest eccentricity we show that the problem remains hard when we are allowed to perturb all of the edges.

1.2 Preliminaries

We give some notation and definitions, as well as including preliminary results relating to reachability in temporal graphs without perturbation.

A temporal graph is a pair (G, λ) , where G = (V, E) is an underlying (static) graph and $\lambda : E \to 2^{\mathbb{N}}$ is a time-labelling function which assigns to every edge of G a set of discrete-time labels. We call a pair (e, t) where $t \in \lambda(e)$ a time-edge and denote by $\mathcal{E}((G, \lambda))$ the set of all time-edges in (G, λ) . When the graph in question is clear from context, we denote the number of vertices in the graph |V(G)| by n and the number of edges in the underlying graph |E(G)| by m. We let $\tau(G, \lambda) := \max_{e \in E(G)} |\lambda(e)|$ denote the maximum number of time labels assigned to any one edge in (G, λ) , and call this quantity temporality following Mertzios et al. [29]. The maximum lifetime of a temporal graph, denoted $T(G, \lambda)$, is the largest $t \in \mathbb{N}$ such that there exists an edge $e \in E(G)$ with $t \in \lambda(e)$.

To discuss reachability, we first need a notion of a temporal path. Here we work with *strict* temporal paths, where a strict temporal path from v_0 to v_ℓ in (G, λ) is a sequence of time-edges $((v_0v_1, t_1), (v_1v_2, t_2) \dots, (v_{\ell-1}v_\ell, t_\ell))$ where, for each $i, t_i \in \lambda(v_{i-1}v_i)$ and $t_1 < t_2 < \dots < t_\ell$. In this paper, all temporal graphs discussed are strict, and so we will simply refer to them as temporal paths for brevity. We say that the length of a strict temporal path $((v_0v_1, t_1), \dots, (v_{\ell-1}v_\ell, t_\ell))$ is ℓ . Given a temporal path $P := ((v_0v_1, t_1), \dots, (v_{\ell-1}v_\ell, t_\ell))$, for each $1 \leq i < \ell$ the path $P' := ((v_0v_1, t_1), \dots, (v_{i-1}v_i, t_i))$ is a prefix of P.

If there exists a temporal path from v_s to v_t in (G, λ) , we say that v_t is reachable from v_s . For a given vertex v_s in a temporal graph (G, λ) , we define reach $((G, \lambda), v_s)$ to be the set of all vertices reachable from v_s in (G, λ) . The maximum temporal reachability of a graph $R_{\max}(G, \lambda) := \max_{v \in V(G)} |\operatorname{reach}((G, \lambda), v)|$ is the cardinality of the largest reachability set in (G, λ) .

We say that the arrival time of a path $P := ((v_0v_1, t_1), \ldots, (v_{\ell-1}v_\ell, t_\ell))$ is t_ℓ . A path P is foremost from a set of paths \mathcal{P} if there is no other path $P' \in \mathcal{P}$ with a strictly earlier arrival time. We will write $t_{Fo}((G, \lambda), v_s, v_t)$ to be the arrival time of a foremost temporal path from v_s to v_t , where $t_{Fo}((G, \lambda), v_s, v_s) := 0$ and, if there is no temporal path from v_s to v_t , we define $t_{Fo}((G, \lambda), v_s, v_t) := \infty$.

Bui-Xuan et al. [5] introduce a notion that we call a *ubiquitous foremost path* (they refer to this as a ubiquitous foremost journey). Let u and v be two vertices in a temporal graph (G, λ) . A foremost temporal path from u to v is a *ubiquitous foremost path* if all of its prefixes are themselves foremost temporal paths.

Given a source vertex v_s in a temporal graph (G, λ) , a *ubiquitous foremost temporal path* tree on v_s is defined to be a temporal tree (G_T, λ_T) with the following properties:

 \blacksquare G_T is a subtree of G,

for each $e \in E(G_T)$, $\lambda_T(e) \subseteq \lambda(e)$ with $|\lambda_T(e)| = 1$, and

■ for each $v_t \in \operatorname{reach}((G, \lambda), v_s)$, (G_T, λ_T) contains a ubiquitous foremost temporal path from v_t to v_s that arrives at the same time as a ubiquitous foremost temporal path from v_t to v_s in (G, λ) .

In particular, note that while there may be multiple ubiquitous foremost temporal paths from v_s to v_t in (G, λ) , (G_T, λ_T) will contain exactly one ubiquitous foremost temporal path from v_s to v_t , and the arrival time of a foremost temporal path from v_s to any v_t can be trivially inferred as the earliest active time over all temporal edges incident to v_t . We note that a ubiquitous foremost temporal path tree can be computed efficiently.

▶ **Theorem 1.1** (Theorem 2 in [5]). Given a temporal graph (G, λ) and a source vertex $v_s \in V(G)$, a ubiquitous foremost temporal path tree on v_s can be calculated in $O(m(\log n + \log \tau(G, \lambda)))$ time.

By applying Theorem 1.1 for each source vertex v_s in V(G), we get the following corollary.

▶ Corollary 1.2. Given a temporal graph (G, λ) we can calculate R_{\max} in $O(nm(\log n + \log \tau(G, \lambda)))$ time.

Note that we can reduce the complexity of this to O(n(n+m)) by using Algorithm 1 of Wu et al. [34] which calculates, for a given source v_s , foremost arrival times (but not actual temporal paths) for each vertex v_t in O(n+m) time. This, however, does need the input data to be in a specified streaming format which allows their algorithm to calculate foremost arrival times in one pass. For our purposes, knowing foremost arrival times is not as useful as knowing actual foremost temporal paths, so we omit further details and instead refer the reader to [34].

1.3 Problems considered and initial observations

Here we introduce the notion of perturbing the appearances of time-edges. To that end, we define δ -perturbations as follows.

▶ **Definition 1.3.** We say that a temporal assignment λ' is a δ -perturbation of λ if there is a bijection f from (G, λ) to (G, λ) such that, for all time-edges, f((e, t)) = (e, t') and $t' \in [\max(1, t - \delta), t + \delta]$. Here we say λ has been perturbed by δ .

We will at times want to consider all possible δ -perturbations of some temporal graph (G, λ) .

▶ **Definition 1.4.** A temporal assignment λ' is a (δ, ζ) -perturbation of λ if it is a δ -perturbation of λ and $|\{(e,t) \mid (e,t) \in \mathcal{E}((G,\lambda)) \land (e,t) \notin \mathcal{E}((G,\lambda'))\}| \leq \zeta$.

We can now define the main problem we consider in this paper.

Temporal Reachability with Limited Perturbation (TRLP) Input: A temporal graph (G, λ) and positive integers ζ , $h \leq |V(G)|$, and δ . Question: Is there a (δ, ζ) -perturbation λ' of λ such that $R_{\max}(G, \lambda') \geq h$?

We also consider a straightforward special case of this problem, in which the number of perturbations is unrestricted.

Temporal Reachability with Perturbation (TRP) Input: A temporal graph (G, λ) and positive integers $h \leq |V(G)|$ and δ . Question: Is there a δ -perturbation λ' of λ such that $R_{\max}(G, \lambda') \geq h$?

Let $N_G(v)$ denote the *neighbourhood* of a vertex, that is the set of all vertices which share an edge with v in G. We note a simple fact about neighbourhoods and reachability.

▶ **Observation 1.5** (Observation 3 in [17]). For any undirected temporal graph (G, λ) and $v \in V(G)$, we have reach $((G, \lambda), v) \supseteq N_G(v) \cup \{v\}$.

We note, as a result, that if $h \leq \Delta_G + 1$, then $((G, \lambda), \zeta, h, \delta)$ is a yes-instance of TRLP since there must be a vertex in (G, λ) with temporal reachability at least $\Delta_G + 1$ regardless of perturbation.

We now show that if we only add to the set of times at which edges are active, this cannot delay the arrival of a foremost temporal path, nor can it reduce temporal reachability.

▶ Lemma 1.6. Let (G, λ_1) and (G, λ_2) be two temporal graphs on the same underlying graph G. If $\mathcal{E}((G, \lambda_1)) \subseteq \mathcal{E}((G, \lambda_2))$, then for each $v_s, v_t \in V(G)$, $t_{Fo}((G, \lambda_1), v_s, v_t) \ge t_{Fo}((G, \lambda_2), v_s, v_t)$.

Proof. For any $v_s, v_t \in V(G)$, let P be a foremost temporal path in (G, λ_1) from v_s to v_t . But as $\lambda_1(e) \subseteq \lambda_2(e)$ for any $e \in E(G)$, this path P must also exist in (G, λ_2) .

This gives us the following corollary.

▶ Corollary 1.7. Let (G, λ_1) and (G, λ_2) be two temporal graphs on the same underlying graph G. If $\mathcal{E}((G, \lambda_1)) \subseteq \mathcal{E}((G, \lambda_2))$, then for each $v \in V(G)$, reach $((G, \lambda_1), v) \subseteq \operatorname{reach}((G, \lambda_2), v)$, and hence $R_{\max}(G, \lambda_1) \leq R_{\max}(G, \lambda_2)$.

We now show that we can take a temporal graph with an arbitrary number of time labels on each edge and remove all bar one of these time labels without affecting the temporal reachability of a given vertex v_s . We do this by only keeping, for each edge, the earliest time label at which any path from v_s might use the edge. Any earlier times by definition cannot be used by any path, and so are not necessary, and for any path that use the edge at a later time there is some path that reaches the same vertices, but uses the edge at the earlier time.

▶ Lemma 1.8. Given a temporal graph (G, λ) and vertex $v \in V(G)$ with reach_{G,\lambda}(v) = R, let \mathcal{P} be a set of ubiquitous foremost temporal paths such that for each $u \in R$, \mathcal{P} contains a ubiquitous foremost temporal path from v to u, and let λ' be a temporal labelling function such that for each $e \in E(G)$, if e appears in at least one path in \mathcal{P} then $\lambda'(e) = {\min\{t \mid (e,t) \in P \text{ for some } P \in \mathcal{P}\}}$. Then for any $u \in R$, $t_{Fo}((G,\lambda), u) = t_{Fo}((G,\lambda'), u)$, and reach $((G,\lambda), u) = \operatorname{reach}((G,\lambda'), u)$.

Proof. First, note that as $\mathcal{E}((G, \lambda')) \subseteq \mathcal{E}((G, \lambda))$ we get $\operatorname{reach}_{G,\lambda'}(u) \subseteq \operatorname{reach}_{G,\lambda'}(u)$ from Corollary 1.7, so it remains to show that $\operatorname{reach}_{G,\lambda}(u) \supseteq \operatorname{reach}_{G,\lambda'}(u)$. Towards this, assume there is some smallest time t_i such that there is some vertex $u \in R$, some path P = $((e_1, t_1), (e_2, t_2), \ldots, (e_\ell, t_\ell)) \in \mathcal{P}$ with $\ell \ge i$, e_1 incident with v, and e_ℓ incident with u, and such that at least one endpoint of e_i is not in $\operatorname{reach}_{G,\lambda'}(u)$. If no such t_i exists then each $P \in \mathcal{P}$ is a temporal path in (G, λ') and so $\operatorname{reach}_{G,\lambda}(u) \supseteq \operatorname{reach}_{G,\lambda'}(u)$; we will now show that assuming the existence of t_i leads to a contradiction. As we took t_i to be the smallest such integer, we know that $((e_1, t_1), \ldots, (e_{i-1}, t_{i-1}))$ is a temporal path in (G, λ') and so one

endpoint of e_i is reachable from v. Without loss of generality we can then label the endpoints of e_i as x and y such that $x \in R$ and $y \notin R$. We must have $t_i \notin \lambda'(e_i)$, and so by the criterion from the lemma there must be some other path $P' \in \mathcal{P}$ such that P' contains the temporal edge (e_i, t'_i) where $t'_i < t_i$. Let $P' = ((e'_1, t'_1), \dots, (e'_j, t'_j), \dots, (e'_s, t'_s))$ where $(e_i, t'_i) = (e'_j, t'_j)$ (i.e., the edge (e_i, t'_i) is the j-th edge in P'). Then $((e'_1, t'_1), (e'_2, t'_2), \dots, (e'_j, t'_j))$ is a temporal path that exists in (G, λ') as for $a \in [j], t'_a < t_i$. As $e'_j = e_i$, this means that $y \in \operatorname{reach}_{G,\lambda'}$ but this contradicts our assumption. The only other possibility is that no such t_i exists, so we can conclude that $\operatorname{reach}_{G,\lambda}(u) = \operatorname{reach}_{G,\lambda'}(u)$.

2 Intractability of TRLP

We begin by analysing the complexity of TRLP. We do this by giving a polynomial-time reduction from DOMINATING SET to TRLP, which lets us show that the problem

- \blacksquare is NP-complete,
- is W[2]-complete with respect to ζ ,
- is NP-hard to approximate to within a factor of $\alpha \log |V(G)|$ for some $\alpha > 0$, and
- has no $f(\zeta)n^{o(\zeta)}$ -time algorithm unless ETH fails.

Following this, we show that it is unlikely that the ETH lower bound can be significantly improved, as we give an algorithm running in time $n^{O(\zeta)} \log \tau(G, \lambda)$.

We begin by describing a particular construction of a temporal graph from a static graph.

▶ **Construction 2.1.** Given a graph G, let $\mathfrak{C}(G) = (G', \lambda)$ be the temporal graph constructed as follows. Create a vertex v_s in V(G'), and for each vertex $v_i \in V(G)$ create two vertices v_i^1 and v_i^2 in V(G'). For each $v_i \in V(G)$, add the edges $v_s v_i^1$ and $v_i^1 v_i^2$ to (G'). Then, for each edge $v_i v_j \in E(G)$, add the edges $v_i^1 v_j^2$ and $v_j^1 v_i^2$ to (G'). Let $\lambda(e) = 2$ for each $e \in E(G')$. A sample construction is given in Figure 1.

Note that G' is a bipartite graph where the sets $\{v_s\} \cup \{v_a^2 \mid v_a \in V(G)\}$ and $\{v_a^1 \mid v_a \in V(G)\}$ form the two partitions.

▶ Observation 2.2. Given a graph G, $\mathfrak{C}(G)$ can be constructed in time polynomial in the size of G.

We now demonstrate the relationship between the existence of a dominating set in G and the existence of a solution to TRLP in $\mathfrak{C}(G)$.

▶ Lemma 2.3. Given an instance (G, r) of dominating set with $r \ge 1$, G has a dominating set of size r if and only if $((G', \lambda), 1, r, |V(G')|)$ is a yes-instance of TRLP.

Proof. We begin by showing that if we have a dominating set $\mathcal{C} = \{v_1, \ldots, v_r\}$ of G, we can find a (1, r)-perturbation λ' of λ such that v_s has temporal reachability |V(G)|. We create λ' by perturbing the edges $v_s v_i^1$ for $v_i \in \mathcal{C}$ to be active at time 1. Clearly λ' is a (1, r)-perturbation of λ . We will show that v_s can reach every other vertex in V(G'). Let v be an arbitrary vertex in V(G'). If $v = v_s$ then clearly v_s reaches v. If $v = v_a^1$ for some a, then v_s can reach v along a temporal path of one edge. If $v = v_a^2$ for some a, then let v_b be the vertex in \mathcal{C} that dominates v_a in G. Then $\lambda'(v_s v_b^1) = 1$ and $\lambda'(v_b^1 v_a^2) = 2$, so v_s can reach v along a temporal path of two edges. As v was taken arbitrarily, there is a temporal path in (G', λ') from v_s to every other $v \in V(G')$, so $((G', \lambda), 1, r, |V(G')|)$ is a yes-instance of TRLP.




Figure 1 Diagram of the construction from Construction 2.1.

We now show that if $((G', \lambda), 1, r, |V(G')|)$ is a yes-instance of TRLP, there exists a dominating set of cardinality r. Assume that $((G', \lambda), 1, r, |V(G')|)$ is a yes-instance of TRLP. Let v be a vertex in V(G') and let λ' be a (1, r)-perturbation of λ such that v that has temporal reachability |V(G')| in (G', λ') . Note that for any (1, r)-perturbation λ' of λ and for any edge $e \in E(G')$, $\lambda'(e) \leq 3$. As a result, a temporal path in (G', λ') can have a length of at most three.

We now take cases based on whether the vertex $v \in V(G')$ is v_s , is of the form v_a^1 for some a, or is of the form v_a^2 for some a. If $v = v_s$, we show how to take the perturbation λ' and construct a dominating set. For the other cases we show either how to construct a dominating set, or how to construct a (1, r)-perturbation such that v_s can reach all other vertices, and then utilise the first case to complete the argument.

Case 1: $v = v_s$ Let $C = \{v_a \mid \lambda(v_s v_a^1) = 1 \lor \exists v_b^2 : \lambda(v_a^1 v_b^2) = 3\}$. That is, C contains the vertex v_a if and only if at least one edge incident to v_a^1 is perturbed to create λ' . It follows that $|C| \leq r$; we now show that C is a dominating set in G. Let v_b be an arbitrary vertex in G, and let $v_s v_a^1 v_b^2$ be a temporal path in (G', λ') . Such a path must exist as v can temporally reach all vertices in (G', λ') , and it must have a length of two as there is no path of length either one or three in G' from v_s to v_b^2 , and there are no temporal paths of length ≥ 4 in (G', λ') . It must also be that $\lambda'(v_s v_a^1) < \lambda'(v_a^1 v_b^2)$, and since $\lambda(v_s v_a^1) = \lambda(v_a^1 v_b^2) = 2$, it follows that at least one of $\lambda'(v_s v_a^1) = 1$ or $\lambda'(v_a^1 v_b^2) = 3$ must hold. However, then $v_a \in C$, and as $v_a^1 v_b^2 \in E(G')$, by construction we also have $v_a v_b \in E(G)$ and so v_a dominates v_b . As v_b was taken arbitrarily, C is a dominating set of size at most r in G.

Case 2: $v = v_a^1$ for some *a*: First, we will show that if there is no edge *e* incident to v_a^1 such that $\lambda'(e) = 1$, then $\{v_a\}$ forms a dominating set. If no such edge is perturbed, then all temporal paths from v_a^1 must have length at most two. As G' is bipartite, this means that

for v_a^1 to be able to temporally reach any vertex of the form v_b^2 , v_a^1 must be adjacent to it (and thus by construction v_a is adjacent to every other vertex v_b in G). As $r \ge 1$, $\{v_a\}$ is a dominating set in G with size at most r.

We next assume that there is some edge e incident to v_a^1 with $\lambda'(e) = 1$. We will construct a (1, r)-perturbation λ'' of λ such that v_s can temporally reach all vertices in (G', λ'') ; the result then follows by applying Case 1. We achieve this by ensuring that for each perturbed edge in λ' , we select at most one edge in λ'' to perturb. Recalling that at least one edge incident to v_a^1 is perturbed, let $\lambda''(v_s v_a^1) = 1$, and let $\lambda''(v_a^1 v_b^2) = 2$ for every edge of the form $v_a^1 v_b^2$ in E(G'). For any vertex v_b^1 such that there exists a vertex v_c^2 with $\lambda'(v_b^1 v_c^2) = 3$, let $\lambda''(v_s v_b^1) = 1$, and for every other edge e, let $\lambda''(e) = 2$. By this construction, λ'' is a (1,r)-perturbation of λ as λ' is a (1,r)-perturbation of λ . Note that v_s is adjacent to, and thus can temporally reach, every vertex of the form v_b^1 for any b. Consider next an arbitrary vertex of the form v_b^2 . If v_b^2 is adjacent to v_a^1 , then v_s can temporally reach v_b^2 along the temporal path $v_s v_a^1 v_b^2$ in (G, λ'') . Otherwise, v_b^2 is not adjacent to v_a^1 . As v_a^1 can temporally reach v_b^2 in (G', λ') , temporal paths in (G', λ') have length at most 3, and G' is bipartite, there is a vertex y and a temporal path $v_a^1 y v_c^1 v_b^2$ in (G', λ') , where either $y = v_s$ or y is of the form v_d^2 . This means that $\lambda'(v_c^1 v_b^2) = 3$, so $\lambda''(v_s v_c^1) = 1$ and $v_s v_c^1 v_b^2$ is a temporal path in (G', λ'') . Thus v_s can temporally reach every vertex in G' in (G', λ'') , and so by applying Case 1 there is a dominating set C of G of size at most r.

Case 3: $v = v_a^2$ for some *a*: We will construct a (1, r)-perturbation λ'' of λ such that v_s can temporally reach all vertices in (G', λ'') ; the result then follows by applying Case 1. We achieve this by ensuring that for each perturbed edge in λ' , we select at most one edge in λ'' to perturb. For every vertex v_b^1 incident to at least one edge e with $\lambda(e) \neq \lambda'(e)$, let $\lambda''(v_s v_b^1) = 1$, and for every vertex v_b^1 with $\lambda'(v_s v_b^1) = 3$, let $\lambda''(v_s v_b^1) = 1$. For any vertex of the form v_b^1 incident to one or more edges $v_b^1 v_c^2$ with $\lambda'(v_b^1 v_c^2) = 3$, let $\lambda''(v^s v_b^1) = 1$. For every other edge e, let $\lambda''(e) = 2$. By construction, λ'' is a (1, r)-perturbation of λ as λ' is a (1, r)-perturbation of λ . Note that v_s is adjacent to, and thus can temporally reach, every vertex of the form v_b^1 for any b. Consider an arbitrary vertex of the form v_b^2 . Recall that G' is bipartite, and that one of the partitions is given by $\{v_s\} \cup \{v_b^2 \mid v_b \in G\}$. As temporal paths in any (1, r)-perturbation of λ can have maximum length 3, we therefore know that any temporal path from v_a^2 to v_b^2 in (G', λ'') must have length either zero (if $v_a^2 = v_b^2$) or two, and that any temporal path from v^s to v_b^2 in (G', λ'') must have length two. If $v_b^2 = v_a^2$, then as v_a^2 can temporally reach v_s along some temporal path $v_a^2 v_c^1 v_s$ for some v_c^1 , where at least one of $\lambda'(v_a^2 v_c^1) \neq 2$ or $\lambda'(v_c^1 v_s) \neq 2$ must hold, we have $\lambda''(v_s v_c^1) = 1$ and so v_s can reach v_b^2 along the temporal path $v_s v_c^1 v_b^2$. Else $v_b^2 \neq v_a^2$, and so there is a temporal path $v_a^2 v_c^1 v_b^2$ in (G', λ') for some vertex v_c^1 . It must be that $\lambda'(v_a^2 v_c^1) < \lambda'(v_c^1 v_b^2)$, so either $\lambda'(v_a^2 v_c^1) \neq \lambda(v_a^2 v_c^1)$ or $\lambda'(v_c^1 v_b^2) \neq \lambda(v_c^1 v_b^2)$ holds. This means that $\lambda''(v_s v_c^1) = 1$ and $\lambda''(v_c^1 v_b^2) = 2$ so v_s can temporally reach v_b^2 . Thus v_s can temporally reach every vertex in G' in (G', λ'') , and so by applying Case 1 there is a dominating set C of G of size at most r.

We can now use this equivalence to give a number of hardness and lower-bound results. Together with the observation that the perturbation λ' serves as a certificate for the problem, Lemma 2.3 gives us NP-completeness of TRLP. We further observe that, given an instance of TRLP with all parameters except ζ specified, approximating the smallest value of ζ such that the resulting instance is a yes-instance to within a logarithmic factor is NP-hard; this follows as the size of a smallest dominating set cannot be approximated to a factor better than $\alpha \log |V(G)|$ for some $\alpha > 0$ (see [32]).

In addition, Dominating Set is W[2]-hard parameterised by the size of the dominating set (see e.g. [9, Proposition 13.20]). Therefore, TRLP must be W[2]-hard parameterised by ζ .

Finally, assuming ETH, there is no $f(k)n^{o(k)}$ -time algorithm for DOMINATING SET (see [9, Corollary 14.23]). This leads us to the following corollary.

- ► Corollary 2.4. *TRLP is* NP-complete.
- For some $\alpha > 0$ it is NP-hard to approximate to within a factor $\alpha \log |V(G)|$ the minimum number ζ of δ -perturbations required to transform the input temporal graph (G, λ) into a temporal graph with maximum reachability at least h.
- **TRLP** is W[2]-hard parameterised by ζ , the number of edges that may be perturbed.
- Assuming ETH, there is no $f(\zeta)n^{o(\zeta)}$ -time algorithm for TRLP for any computable function f.

We now give an algorithm which shows that our ETH lower bound is close to best possible. The algorithm considers every possible subset of edges of size ζ , and then for each such subset performs a Dijkstra-like exploration of a temporal graph using any edge in the selected subset as early as possible. We begin by giving Algorithm 1, which performs this exploration for a given source and given set of perturbed edges in $O(n^2)$ time. Repeatedly calling this algorithm for each possible set of perturbed edges and each possible source gives us the desired result.

For Algorithm 1, we need the concept of a priority queue. A priority queue is a data structure for storing data with an associated priority. For our purposes, priority queues allow for insertion of data as well as the removal of one entry with highest priority. Assuming the priority queue stores at most c elements, priority queues can be implemented to allow for either constant time insertion and O(c) removal, O(c) insertion and constant time removal, or $O(\log c)$ insertion and $O(\log c)$ removal. Any of these suffice for our result, and for further information on priority queues we point the reader to [33, Section 3.5].

▶ Theorem 2.5. TRLP is solvable in $O(n^{2\zeta+3}\log(\tau(G,\lambda)))$ time.

Proof. We solve TRLP by running Algorithm 1 for each set of perturbed edges and each possible source. This requires that we run Algorithm $1 n \cdot \binom{n^2}{c}$ times.

 \triangleright Claim 2.6. Algorithm 1 returns true if and only if there exists a perturbation of the edges in E' such that a source vertex reaches at least k vertices.

Proof. We show that a vertex is added to the set \mathcal{V} if and only if there is a δ -perturbation λ' where that vertex is reachable from v_s and a time-edge of λ is not a time-edge of λ' if and only if the edge is in E'. We can show this by induction on the time of arrival of a temporal path from the source vertex v_s . The base case is the source vertex itself, which is trivially temporally reachable from itself at time 0 and added to \mathcal{V} in line 3 of the algorithm.

Assume that, for all vertices temporally reachable from v_s by time t, they are added to \mathcal{V} if and only if they are reachable from v_s under some perturbation of the edges in E'. Then, for any vertex v_2 not in \mathcal{V} which is incident to a vertex v_1 in \mathcal{V} , v_2 is added to \mathcal{V} if and only if (v_1, v_2, t') is in Q for some t' > t and v_2 is not in \mathcal{V} . This occurs either in line 19 or line 23 (lines 8 or 10 if $v_1 = v_s$) of the algorithm. In the former, the edge v_1v_2 is in E' and there exists a $d \in [-\delta, \delta]$ and an occurrence of v_1v_2 at time t^* such that $t < t^* + \delta = t'$. Since v_1 is reached by time t, the time-edge (v_1v_2, t') can be appended to the walk from v_s to v_1 to give a temporal walk from v_s to v_2 arriving at time t'. Similarly, if the edge v_1v_2 is not in E', the time-edge (v_1, v_2, t') is in Q if and only if there is a path to v_2 by time t'' < t'by the inductive hypothesis. In this case, the edge v_1v_2 occurs at time t', therefore we can concatenate the path to v_1 from v_s with the time-edge (v_1v_2, t') . Thus, a time-edge appears in Q if and only if there is a walk from v_s to both endpoints. Therefore, a vertex is added to \mathcal{V} if and only if there exists a temporal path from v_s to it by time t for all $0 \le t \le T(G, \lambda)$. **Algorithm 1** An algorithm which determines if there exists a perturbation of the input temporal graph such that a source vertex reaches at least k vertices, given the exact edges which may be perturbed

Input: A temporal graph (G, λ) , a source vertex v_s , non-negative integers k and δ , and a set E' of edges of G.

Output: True if and only if there is a δ -perturbation λ' of λ where $\lambda'(e) \neq \lambda(e)$ implies $e \in E'$ for all $e \in E(G)$ and reach $((G, \lambda'), v_s) \geq k$.

- 1: Let Q be a time-based priority queue with priority for earlier times. We build Q such that if (v, t) is in Q then there exists a temporal path that reaches v at time t.
- 2: Let \mathcal{V} be a set such that if vertex v is in \mathcal{V} then a temporal path from v_s to v exists.

```
3: Add v_s to \mathcal{V}
```

4: for all edges (v_s, v_2) incident to v_s do

- 5: Add v_2 to \mathcal{V}
- 6: **if** $(v_s, v_2) \in E'$ then
- 7: Let $t' = \min(\{\lambda(v_s, v_2) + d \mid d \in [-\delta, \delta] \land \lambda(v_s, v_2) + d \ge 1\})$
- 8: Add (v_s, v_2, t') to Q
- 9: else

16:

17:

18:

19:

22:

23:

11: while Q is not empty do

12: Let (v_1, v_2, t) be a tuple of highest priority removed from Q

```
13: if v_2 \notin \mathcal{V} then
```

```
14: Add v_2 to \mathcal{V}
```

15: for all edges (v_2, v_3) incident to v_2 do

```
if v_2v_3 \in E' then
```

20: else 21: if max(

Add (v_2, v_3, t'') to Q

```
24: \overrightarrow{\mathbf{if}} \ |\mathcal{V}| \ge k \ \overrightarrow{\mathbf{then}}
```

```
25: L return True
```

26: return False

Once Q is empty, all vertices reachable from v_s under λ' must have been added to \mathcal{V} . Therefore, the algorithm returns true if and only if $|\mathcal{V}| \geq k$. This occurs if and only if there exists a perturbation of the edges in E' such that a source vertex reaches at least kvertices.

 \triangleright Claim 2.7. Algorithm 1 terminates in $O(n^2 \log(\tau(G, \lambda)))$ time.

Proof. Using the data structure given by Bui-Xuan et al. [5], we can look up the times at which an edge is active in $O(\log(\tau(G, \lambda)))$ time where τ is the temporality of the graph. Note that, in Algorithm 1, a vertex is added to \mathcal{V} at most once and any edge (u, v) is added to Q as part of a triple (u, v, t) at most twice (i.e. there are at most two times with which any edge appears in Q). Therefore, the algorithm runs in $O(n^2 \log(\tau(G, \lambda)))$ time.

This gives us the desired result.

◀

3 Tractability with many perturbations

In this section we show that allowing many perturbations makes our problem easier to solve. In particular, we prove that TRP is solvable in polynomial time, and also that TRLP is solvable in polynomial time if the number ζ of allowed perturbations is at least the target reachability.

As a warm-up, we begin by considering the case in which each perturbation may also be very large: suppose δ is at least the maximum of the lifetime of (G, λ) and the diameter of G. We claim that in this case, if h is the target reachability and $\zeta \geq h - 1$, we have a yes-instance. To see this, fix an arbitrary subtree H of G with exactly h vertices (noting that such a subtree contains $h - 1 \leq \zeta$ edges, and if no such tree exists we have a no-instance of TRP), and further pick an arbitrary vertex $r \in V(H)$ which we shall call the root. The permitted perturbations are large enough that we can perturb one appearance of each edge in H so that, for each leaf ℓ of H, the times of these edge appearances are strictly increasing along the path from r to ℓ . It follows that, in the perturbed graph, r has reachability at least h, as required.

The first step towards our tractability results is to show that, given a source vertex in a temporal graph, and an integer δ , we can identify a δ -perturbation that minimises the foremost arrival time from said source to any other target vertex over all δ -perturbations. Note that this is indeed one singular perturbation that minimises foremost arrival times to all target vertices: one perturbation achieves such a result exactly because a ubiquitous foremost temporal path tree is a tree with edges active at exactly one time step. Recall that we denote the arrival time of a foremost temporal path from v_s to v_t in (G, λ) by $t_{\rm Fo}((G, \lambda), v_s, v_t)$.

▶ Lemma 3.1. Given a temporal graph (G, λ) , vertex $v_s \in V(G)$, and integer δ , we can identify in $O(m(\log n + \log \delta \tau(G, \lambda)))$ time a δ -perturbation λ' such that for each $v_t \in V(G)$, $t_{Fo}((G, \lambda'), v_s, v_t) \leq t_{Fo}((G, \lambda''), v_s, v_t)$ for all δ -perturbations λ'' .

Proof. First we create the new time-labelling function λ'' as follows. For each $e \in E(G)$, let $\lambda''(e) = \{t + p \mid p \in [-\delta, \delta], t \in \lambda(e)\}$, noting that as a result $\tau(G, \lambda'') \leq (2\delta + 1)\tau(G, \lambda) = O(\delta\tau(G, \lambda))$. Then, by Theorem 1.1 we can calculate a ubiquitous foremost temporal path tree (G_T, λ_T) in (G, λ'') in $O(m(\log n + \log \tau(G, \lambda''))) = O(m(\log n + \log \tau(G, \lambda)\delta))$ time. Then we create λ' as follows. For each $e \in E(G_T)$, let $\lambda'(e) = \lambda_T(e)$, and for any $e \in E(G) \setminus E(G_T)$, let $\lambda'(e) = \lambda(e)$.

We now show that λ' satisfies the requirements of the theorem. By construction, $\mathcal{E}((G, \lambda_T)) \subseteq \mathcal{E}((G, \lambda''))$, and λ' is be a δ -perturbation of λ . Take an arbitrary $v_t \in V(G)$. By

definition of a ubiquitous foremost temporal path tree, there is some ubiquitous foremost temporal path P in (G_T, λ_T) , and by construction, this path P must also be a ubiquitous foremost temporal path in (G, λ'') . Thus the arrival time t of P must satisfy $t_{\text{Fo}}((G, \lambda''), v_s, v_t) = t$, and so as any δ -perturbation λ^{\dagger} of λ satisfies $\mathcal{E}((G, \lambda^{\dagger})) \subseteq \mathcal{E}((G, \lambda''))$, by Corollary 1.7 we get $t \leq t_{\text{Fo}}((G, \lambda^{\dagger}), v_s, v_t)$ for any δ -perturbation λ^{\dagger} of λ .

▶ Corollary 3.2. Given a temporal graph (G, λ) , vertex $v_s \in V(G)$, and integer δ , we can identify in $O(m(\log n + \log \delta \tau(G, \lambda)))$ time a δ -perturbation λ' of λ such that for each $v_t \in V(G)$, $t_{Fo}((G, \lambda'), v_s, v_t) \leq t_{Fo}((G, \lambda''), v_s, v_t)$ for all λ'' which are δ -perturbations of λ .

We are now ready to solve TRP using this result. Recall that $\tau(G, \lambda) = \max_{e \in E(G)} |\lambda(e)|$.

▶ **Theorem 3.3.** We can solve TRP in $O(nm(\log n + \log \delta \tau(G, \lambda)))$ time.

Proof. For each source vertex $v_s \in V(G)$, we use Lemma 3.1 to identify a δ -perturbation λ' that minimises the foremost arrival time to any target vertex $v_t \in V(G)$, and calculate reach $((G, \lambda'), v_s) = \{v \in V(G) \mid t_{Fo}((G, \lambda'), v_s, v_t) < \infty\}$. If, for any source vertex v_s we get $|\operatorname{reach}((G, \lambda'), v_s)| \geq h$ then the instance is a yes-instance to TRP, and additionally λ' can act as a certificate to this fact.

Now turning our attention to TRLP, we start with some further notation. To consider a perturbation of fewest time-edges such that the maximum reachability is at least h, we introduce the following notion of worthwhile perturbations.

▶ **Definition 3.4.** A perturbation λ' of λ is worthwhile if reverting any time-edge that exists under λ' but not λ back to the time assigned by λ decreases the maximum reachability of the temporal graph. We call any time-edge (e, t) of (G, λ') worthwhile if λ' is a worthwhile perturbation of λ , $t \in \lambda'(e)$ and $t \notin \lambda(e)$.

▶ Lemma 3.5. Let λ' be a perturbation of (G, λ) such that the maximum reachability of (G, λ') is h. Suppose there is no λ'' which perturbs fewer edges with maximum reachability (G, λ'') at least h. Then λ' is a worthwhile perturbation of λ .

Proof. We prove the lemma statement by contrapositive. Suppose that λ' is not a worthwhile perturbation of λ and the maximum reachability of (G, λ') is h. Then, there must be a time-edge in (G, λ') which we can revert to λ without decreasing the maximum reachability of the temporal graph. Therefore, λ' is not a perturbation which perturbs the minimum number of time-edges such that maximum reachability of the temporal graph is h.

▶ Lemma 3.6. Suppose that λ' is a worthwhile perturbation of (G, λ) . Then, for every vertex v with maximum reachability in (G, λ') , the subgraph induced by reach $((G, \lambda'), v)$ contains all edges perturbed by λ' .

Proof. Suppose, for a contradiction, that λ' is a worthwhile perturbation of (G, λ) and there is a vertex v in (G, λ') such that v has maximum reachability and the subgraph induced by reach $((G, \lambda'), v)$ does not contain all edges perturbed by λ' . By our assumption, there must be a perturbed edge e whose endpoints are not both reachable from v. This is because, under λ' there is no temporal path from v which uses the edge e. Therefore, reverting this edge to its original temporal assignment under λ cannot decrease the cardinality of the reachability set. This contradicts our definition of a worthwhile assignment.

▶ Lemma 3.7. The perturbed time-edges in a worthwhile perturbation λ' of (G, λ) form a forest.

Proof. Suppose, for a contradiction, that there is a cycle C of perturbed edges under a worthwhile perturbation λ' . Let v be a vertex with maximum reachability in (G, λ') . Then, by Lemma 3.6, the edges perturbed by λ' are in the subgraph induced by reach $((G, \lambda'), v)$. Hence the vertices in C are all temporally reachable from v.

We have two cases to consider. In the first, assume that for each perturbed time-edge, there is a temporal path from v using this time-edge. Then there is a vertex u in C that v can reach by two distinct temporal paths. This includes the trivial path if v = u. Reverting the final time-edge (e_u, t) to $\lambda(e_u)$ of a path that arrives latest cannot decrease the cardinality of the reachability set of v. Since v is a vertex with maximum reachability in (G, λ') , this means that reverting this time-edge does not decrease the maximum reachability of the temporal graph. Thus, λ' cannot be worthwhile. Second, we consider the case where there is a perturbed time-edge trivially cannot change the reachability set of (G, λ') . Hence, we cannot have a cycle of perturbed time-edges in a worthwhile perturbation.

We now show that, if the budget of perturbations is large enough, TRP and TRLP are equivalent problems.

▶ Lemma 3.8. If $\zeta \ge h - 1$, there is a solution for TRLP on (G, λ) and integers h, δ if and only if there is a solution for TRP on the same temporal graph with h and δ .

Proof. If $((G, \lambda), h, \delta, \zeta)$ is a yes-instance of TRLP, then this trivially implies $((G, \lambda), h, \delta)$ is a yes-instance of TRP. Let λ' be a solution for this instance of TRP which perturbs the fewest edges and v be a vertex in (G, λ') with reachability at least h. Let the number of perturbed edges under λ' be ζ' . By Lemma 3.5, λ' must be a worthwhile perturbation. Furthermore, Lemmas 3.6 and 3.7 state that the perturbed time-edges must form a forest and be in the subgraph induced by $\operatorname{reach}((G, \lambda'), v)$ where v is a vertex with maximum reachability in (G, λ') . Therefore v must reach both endpoints of every perturbed time-edge and the maximum reachability of (G, λ') must be at least $\zeta' + 1$.

At this point, if $\zeta \leq h - 1$ we are done. Now, suppose otherwise. We will find a subset of these perturbations which achieves maximum reachability at least h. Let $\zeta' > h - 1$, then v must have reachability strictly greater than h. To find a perturbation of at most h - 1 time-edges such that v has temporal reachability at least h, we let u_1 and u_2 be the two endpoints of a perturbed time-edge and calculate $\gamma = \max\{t_{Fo}((G, \lambda'), v, u_1), t_{Fo}((G, \lambda')v, u_2)\}$ and order the time-edges by these values. We then keep the h - 1 time-edges with smallest γ values and revert all other time-edges. Since we only revert time-edges whose endpoints are first reached after the time-edges must still be reachable from v. Recall that these time-edges cannot form any cycles. Therefore, since v reaches both endpoints of every perturbed edge, v must reach at least $\zeta + 1 \geq h$ vertices. Thus $((G, \lambda), \delta, h)$ is a yes-instance of TRP if and only if $((G, \lambda), \delta, h, \zeta)$ is a yes-instance of TRLP for $\zeta \geq h - 1$.

Combining Theorem 3.3 and Lemma 3.8 gives us the following.

▶ Theorem 3.9. We can solve TRLP in $O(nm(\log n + \log \delta \tau(G, \lambda)))$ time when $\zeta \ge h - 1$.

4 Structural Restrictions on the Underlying Graph

We now consider TRLP when the underlying graph G has restricted structure: in particular when G is a tree, or when has bounded treewidth. When the input underlying graph is a tree, we solve TRLP by a dynamic program which uses Multiple Choice Knapsack to choose

the perturbations which maximise the reachability from the vertex we are considering in time $O(n^2\zeta^3(T(G,\lambda)+\delta))$. When G has constant bounded treewidth and the lifetime and size of perturbations allowed are also bounded, we use a dynamic program over a tree decomposition to solve TRLP in polynomial time.

4.1 Knapsack-based dynamic program for trees

The formal definition of the knapsack problem that we use is as follows:

Multiple Choice Knapsack Problem (MCKP) Input: An integer c and q mutually disjoint classes N_1, \ldots, N_q of elements such that each element $j \in N_i$ has a profit p_{ij} and weight w_{ij} . Output: A function $\phi : \bigcup_i N_i \to \{0,1\}$ such that $\sum_{j \in N_i} \phi(j) = 1$ for all N_i , $\sum_{i=1}^q \sum_{j \in N_i} w_{ij} \phi(j) \leq c$, and $\sum_{i=1}^q \sum_{j \in N_i} p_{ij} \phi(j)$ is maximised.

Dudziński and Krzysztof [15] show that this can be solved by a dynamic program in time $O(c \sum_{i=1}^{q} n_i) = O(nc)$ where n_i is the size of the class N_i and n is the total number of elements. In our case, the size of each class is bounded by ζ .

We solve TRLP by a bottom-up dynamic programming argument. The algorithm checks whether there is a (δ, ζ) -perturbation λ' such that a given source vertex v_s has reachability at least h. We root the tree at the source, giving us an orientation so that we can refer to the parents and children of vertices. Since we are asking if there exists a (δ, ζ) -perturbation such that $R_{\max}(G, \lambda) \geq h$, we can repeatedly run the algorithm for different choices of source vertex. Once we reach the root, if there exists a state which corresponds to reachability at least h, we accept. Otherwise, we reject and try another source vertex.

For any vertex v in the rooted tree G, we define a state as the triple (ζ_v, r_v, t_v) where $0 \leq \zeta_v \leq \zeta$, $0 < r_v \leq h$ and $0 \leq t \leq T(G, \lambda) + \delta$. We say that a state (ζ_v, r_v, t_v) is valid if and only if there exists a (δ, ζ_v) -perturbation of the temporal subtree G_v rooted at v where v reaches r_v vertices after time t_v . By "after time t_v " we mean that the vertices are reachable by a temporal path which departs v at time t_v at the earliest. We say that the state is supported by this perturbation. We further say that a state (ζ_v, r_v, t_v) is maximally valid if, for every other valid state (ζ_v, r', t_v) of v, we have $r' < r_v$.

Given all maximally valid states of the children of a vertex v, for each time t we can calculate all maximally valid states (ζ_v, r_v, t) of v in $O(d_c \zeta^2)$ time where d_c is the number of children of v. To do this we use the algorithm of Dudziński and Krzysztof for MCKP [15].

We start by assigning every leaf the set of states $\{(0, 1, t): t \in [0, T(G, \lambda) + \delta]\}$. For any non-leaf vertex v and every time $t \in [0, T(G, \lambda) + \delta]$, we check if the state (ζ_v, r_v, t) is valid by the following method; we can then easily remove states that are not maximally valid. The intuition behind our method is that we use MCKP to find an allocation of perturbations to the subtrees rooted at each child of v which maximises the reachability of v.

- 1. For each child c, we make a list of pairs (ζ_c, r_c) . A pair (ζ_c, r_c) is present if
 - **a.** $\zeta_c = 0$ and $r_c = 1$; or
 - **b.** there is a time t' after t at which the edge vc is active and there exists a valid state $(\zeta_c, r_c 1, t_c)$ of c such that $t_c > t'$; or
 - c. there is a valid state $(\zeta_c 1, r_c 1, t')$ of c where t' is a time after t and vc is active in the interval $[t' \delta, t' + \delta]$.

- 2. If multiple pairs associated with a single child c have the same ζ_c value, we remove all but the one with the highest r_c value.
- 3. For each integer w with $0 \le w \le \zeta$, we can find a combination S of pairs in $O(n\zeta^2)$ time where: one pair is chosen per child; the sum of ζ_c is at most w; and the sum of r_c is maximised. Each set of the input of MCKP consists of the pairs belonging to a given child vertex. For a pair (ζ, r) , the profit is r and the weight is ζ . More formally, our input to an algorithm which solves MCKP is the integer c = w and the set of classes N_1, \ldots, N_{d_c} where a class N_i corresponds to the *i*th child. For each pair (ζ_c, r_c) of a child c, we add an element with weight ζ_c and profit r_c to the corresponding class. We can then solve MCKP for each w such that $1 \le w \le \zeta$. The state $(w, \max(r), t)$ where $\max(r)$ is the maximum value of profit as found by an algorithm solving MCKP with our inputs is then a valid state of v and records the maximum reachability in the subtree rooted at v given w perturbations.
- 4. Delete any states with $\zeta_v > \zeta$ or $t_c < 0$ and any states (ζ_v, r'_v, t_v) where there exists a state (ζ_v, r_v, t_v) such that $r_v > r'_v$.

▶ Lemma 4.1. For every vertex v, a state (ζ_v, r_v, t_v) is found by the algorithm above if and only if it is maximally valid for v.

Proof. We prove this statement by induction on the height of v. The height of a vertex v is defined as the maximum distance to a leaf in the subtree rooted at v. For the base case, it is clear that the set of states $\{(0, 1, t): t \in [0, T(G, \lambda) + \delta]\}$ contains precisely the maximally valid states for a leaf.

We now assume that the lemma statement is true for all descendants of v. In particular, we assume that for every child c of v, the algorithm finds a state (ζ_c, r_c, t_c) if and only if that state is maximally valid for c.

Suppose first that the algorithm returns the state (ζ_v, r_v, t_v) for v; we will show that this state is maximally valid for v. By our computation of states, there must be a set S of valid pairs (ζ_c, r_c) of the children consisting of one state per child such that the sum of r_c values is maximised and the sum of ζ_c values is at most ζ_v . These child pairs either correspond to a maximally valid child state with a t value later than t_v or account for a perturbation on the edge between v and the child.

By the inductive hypothesis, each of the child states (ζ_c, r_c, t_c) used to construct a state of v must be supported by a (δ, ζ_c) -perturbation. Let λ' be a perturbation of λ which, when restricted to each subtree, supports the state (ζ_c, r_c, t_c) . We also ensure that, if t_c is earlier than vc is active, the edge vc is perturbed under λ' so that it is active before t_c . This must be achievable by a δ -perturbation by our construction. Then, under λ' , v must reach each of the vertices reachable from its children after time t_c in the subtree rooted at v. This gives us a (δ, ζ_v) -perturbation such that v reaches r_v vertices after t_v .

Now assume the state (ζ_v, r_v, t_v) is maximally valid for v; we will show that the algorithm finds this state. Let λ^* be a (δ, ζ_v) -perturbation of the subtree induced at v which supports (ζ_v, r_v, t_v) . Denote by ζ_c the number of permutations made by λ^* in the subtree rooted at a child c of v. Let t_c be the earliest time after t_v at which the edge vc is active. Note that the number of vertices reached from c after time t_c under these perturbations must be maximal over the perturbations of $(G_c, \lambda|_{E(G_c)})$, otherwise λ^* would not maximise the vertices reached. By the inductive hypothesis, there must be maximally valid states (ζ_c, r_c, t_c) for each child cof v. These states correspond to pairs which maximise the profit in our instance of MCKP. Therefore, the state (ζ_v, r_v, t_v) is found by the algorithm in Step 3; moreover, by maximality, it will not be deleted in Step 4.

Hence the algorithm finds a state (ζ_v, r_v, t_v) if and only if it is maximally valid.

This proves correctness of the algorithm.

▶ **Theorem 4.2.** TRLP is solvable in $O(n^2\zeta^3(T(G,\lambda) + \delta))$ time on temporal graphs where the underlying graph G is a tree.

Proof. Lemma 4.1 shows correctness of our algorithm. This algorithm runs in $O(n^2\zeta^3(T(G,\lambda) + \delta))$ time. To see this, note that for any vertex there are at most $(\zeta + 1)(T(G,\lambda) + \delta)$ maximally valid states. That is, there are at most $\zeta + 1$ states per time $t \in T(G,\lambda) + \delta$. For the non-leaf vertices, we solve MCKP to find the maximally valid states. This is done in $O(n\zeta^2)$ time. All other computation done for each state of a given vertex is achievable in constant time. Thus, the algorithm takes at most $O(n\zeta^3(T(G,\lambda) + \delta))$ time per vertex. If we perform this on each vertex, then we solve TRLP in $O(n^2\zeta^3(T(G,\lambda) + \delta))$ time.

4.2 Tree Decomposition Algorithm

In this section, we prove the following result.

▶ **Theorem 4.3.** Given a temporal graph (G, λ) where the treewidth of G is at most ω , we can solve TRLP in time

$$O\left(n\omega^4\zeta^3(T(G,\lambda)+\delta)^{\omega})\cdot(2\delta hT(G,\lambda))^{4\omega^2(T(G,\lambda)+\delta)^{\omega}}\right).$$

In particular, we can solve TRLP in polynomial time when the treewidth of the underlying graph, the permitted perturbation size δ and the lifetime of (G, λ) are all bounded by constants.

Our algorithm proceeds by dynamic programming over a nice tree decomposition. Before giving the algorithm, we discuss some definitions and the construction of our states.

4.2.1 Algorithm preliminaries

We begin by defining tree decompositions. We note that we use *node* when referring to the tree decomposition and *vertex* when referring to the original graph for clarity.

▶ Definition (Cygan et al. [9]). A tree decomposition of a static graph G is a pair $\mathcal{T} = (T, \{\mathcal{D}(s)_{s \in V(T)}\})$ where T is a tree where every node is assigned a bag $\mathcal{D}(s) \subseteq V(G)$ such that the following conditions hold:

- 1. $\bigcup_{s \in V(T)} \mathcal{D}(s) = V(G);$
- **2.** for every $uv \in E(G)$, there exists a node s of T such that a bag $\mathcal{D}(s)$ contains both u and v;
- **3.** for every $u \in V(G)$, the set $\{s \in V(T) : u \in \mathcal{D}(s)\}$ induces a connected subtree of T.

The width of a tree decomposition is $\max_{s \in V(T)} |\mathcal{D}(s)| - 1$. The treewidth of a graph is the minimum width of a tree decomposition of that graph.

We use G_s to refer to the subgraph induced by vertices introduced in the subtree rooted at s. Let G'_s denote the subgraph induced by $V(G_s) \setminus \mathcal{D}(s)$.

For our algorithm we use a variation of a tree decomposition known as a nice tree decomposition. This allows us to reduce the number of cases we need to consider when computing the dynamic program over the decomposition.

▶ Definition (Cygan et al. [9]). A rooted tree decomposition $(T, \{\mathcal{D}(s)_{s \in V(T)}\})$ is nice if the following are true

- $\square \mathcal{D}(\ell) = \emptyset \text{ for all leaf nodes } \ell \text{ of } T;$
- every non-leaf node of T is one of the following three types:
 - (Introduce) a node s with exactly one child s' such that $\mathcal{D}(s) = \mathcal{D}(s') \cup \{v\}$ for some vertex $v \notin \mathcal{D}(s)$;
 - (Forget) a node s with exactly one child s' such that $\mathcal{D}(s) = \mathcal{D}(s') \setminus \{v\}$ for some vertex $v \in \mathcal{D}(s')$;
 - \square (Join) a node s with exactly two children s_1, s_2 such that $\mathcal{D}(s) = \mathcal{D}(s_1) = \mathcal{D}(s_2)$.

It is well known (see, for example, Cygan et al. [9, Lemma 7.4]) that if a graph G admits a tree decomposition of width at most w, then it must admit a nice tree decomposition of width at most w with at most O(w|V(G)|) nodes. Furthermore, they state that a nice tree decomposition can be computed in $O(\omega^2 \cdot \max(|V(G)|, |V(T)|))$ time, given a tree decomposition of the graph. We solve TRLP by dynamic program on a nice decomposition graph.

Without loss of generality, we assume that the root of the tree decomposition is a bag containing only a source vertex x. The algorithm finds the maximum reachability of the source vertex under any (δ, ζ) -perturbation. To find the maximum reachability of the graph under any (δ, ζ) -perturbation, we can run the algorithm with each possible source vertex. The dynamic program operates by computing a set of states for each bag. Calculation of states requires us to restrict departure and arrival times of temporal paths. Recall that the *arrival time* of a temporal path is the time of the last time-edge in the path. Similarly, the time at which a temporal path *departs* is the t time if first time-edge in the path occurs at $t' \geq t$. If there is no temporal path from a vertex v to a vertex u, we use the convention that the foremost arrival time of a path from v to u is ∞ . Our states record:

- the times at which edges in the bag are active following perturbation;
- for each vertex v and time t, the foremost arrival time of a path in G_s to each vertex in the bag from v which departs at time t;
- for each set of vertices where each vertex v has a specified (possibly different) departure time t, the total number of distinct vertices reached below the bag by vertices by a path departing each v at time t; and
- the number of edges perturbed below the bag.

To describe the times at which paths leave each vertex in a given set of vertices, we use the following notation. Let $\mathcal{U}_{\mathcal{D}(s)}$ be the set of functions which map the vertices in the bag $\mathcal{D}(s)$ to $[0, T(G, \lambda) + \delta] \cup \{\infty\}$. For notational convenience, we consider a function U in $\mathcal{U}_{\mathcal{D}(s)}$ to be the set $\{(v, U(v)) : v \in S \subseteq \mathcal{D}(s)\}$ of vertex-time pairs. Let (G, λ) be a temporal graph and $S \subseteq V(G)$, we use $\mathcal{E}((S, \lambda))$ to denote the set of time-edges in the subgraph induced by the vertices in the set S. The restriction of a function f to some domain H is denoted $f|_H$. A state is a tuple $(P_s, \mathcal{R}^{\text{below}}, \mathcal{R}^{\text{in}}, \zeta_{G'_s})$ where

- 1. P_s is a function $P_s : E(G[\mathcal{D}(s)]) \to \mathcal{P}([T(G,\lambda) + \delta])$ such that $|\lambda(e)| = |P_s(e)|$ for all $e \in E(G)$, where \mathcal{P} denotes the power set; this describes the time-edges in the bag following a perturbation;
- 2. $\mathcal{R}^{\text{in}} : \mathcal{D}(s) \times [0, T(G, \lambda) + \delta] \to \mathcal{U}_{\mathcal{D}(s)}$ is a function which maps a vertex-time pair (v, t) to a function which gives the foremost arrival time of a path in G_s from v departing at t to each vertex in the bag;
- **3.** for each $U \in \mathcal{U}_{\mathcal{D}(s)}, \mathcal{R}^{below} : \mathcal{U}_{\mathcal{D}(s)} \to [0, h]$ gives the number of distinct vertices below the bag to which there exists a temporal path from some vertex v departing at time U(v); and

4. $\zeta_{G'_s} \in [0, \zeta]$ gives the number of perturbations allowed on edges with at least one endpoint forgotten below this bag.

Since we only want to know whether the number of vertices reached is at least h, the set-function pair is mapped to h by R^{below} if there are at least h vertices reachable from vertices in the bag when the earliest permitted departure time for a vertex v is U(v). Note that, for $\mathcal{R}^{\text{in}}(u,t)$, we allow foremost arrival at vertices by paths traversing vertices in the bag and vertices which have been forgotten. That is, $\mathcal{R}^{\text{in}}(u,t)$ describes the set of vertices in $\mathcal{D}(s)$ reachable from u after time t by paths consisting of vertices in G_s .

We say that a state $(P_s, \mathcal{R}^{\text{below}}, \mathcal{R}^{\text{in}}, \zeta_{G'_s})$ is valid if there exists a perturbation λ' of $(G_s, \lambda|_{G_s})$ such that

- 1. under λ' , $\mathcal{R}^{in}(v, t)$ gives the foremost arrival times in (G_s, λ') at each vertex in $\mathcal{D}(s)$ from v departing at t;
- **2.** λ' is equal to P_s when restricted to $\mathcal{D}(s)$;
- **3.** λ' perturbs exactly $\zeta_{G'_s}$ edges in G'_s ;
- 4. for each assignment of times U ∈ U_{D(s)}, the cardinality of the union of vertices in G'_s reached from all vertices v ∈ D(s) by paths departing at time U(v) is min(h, R^{below}(U);
 5. the number of edges perturbed in G_s is at most ζ.

If this is the case we say that λ' supports $(P_s, \mathcal{R}^{below}, \mathcal{R}^{in}, \zeta_{G'_s})$. For ease, we refer to the set of time-edges perturbed by P_s as changed (P_s) . That is, changed $(P_s) = \{(e, t) : t \in P_s(e), t \notin \lambda(e)\}$.

We now describe how we determine the validity of states for each type of node.

Leaf nodes

We assume that a leaf node contains no vertices by the definition of a nice tree decomposition (Definition). In addition, there are no edges below a leaf which can be perturbed. Therefore, there is only one trivial possibility for a valid leaf state.

Introduce nodes

Suppose that an introduce node s has child s' and that $\mathcal{D}(s) \setminus \mathcal{D}(s') = \{u\}$. We determine whether a state of an introduce node is valid as follows.

▶ Lemma 4.4. Let s be an introduce node with child s' and introduced vertex u. A state $(P_s, \mathcal{R}_s^{below}, \mathcal{R}_s^{in}, \zeta_{G'_s})$ of an introduce node s is valid if and only if there is a valid state $(P_{s'}, \mathcal{R}_{s'}^{below}, \mathcal{R}_{s'}^{in}, \zeta_{G'_s})$ of its child s' such that

- 1. $P_s|_{E(G[\mathcal{D}(s')])} = P_{s'};$
- 2. for all vertices v in $\mathcal{D}(s)$ and times t, $\mathcal{R}_s^{in}(v,t)(u) = t''$ if and only if either v = u and t = t'', or t'' is the earliest time such that there exist t' < t'' and $w \in N(u) \cap \mathcal{D}(s)$ where $\mathcal{R}_{s'}^{in}(v,t)(w) = t'$ and $t'' \in P_s(wu)$;
- **3.** for all $v \in \mathcal{D}(s)$ such that $v \neq u$, each time t, and each neighbour w of u in $\mathcal{D}(s)$, if t_w is defined to be $\min\{t' \in P_s(uw) : t' \geq t\}$, then

$$\mathcal{R}_s^{in}(u,t)(v) = \begin{cases} \min\left(\min_{w \in N(u) \setminus \{v\}} \mathcal{R}_{s'}^{in}(w,t_w+1)(v),t_v\right) & \text{if } v \in N(u) \\ \min_{w \in N(u) \setminus \{v\}} \mathcal{R}_{s'}^{in}(w,t_w+1)(v) & \text{otherwise} \end{cases};$$

4. for each $v, x \neq u \in \mathcal{D}(s)$ and each time t, if we let t' be the earliest time such that there exists a neighbour w of u where $t' \in P_s(wu)$ and $\mathcal{R}_{s'}^{in}(v,t)(w) < t'$ or ∞ if no such neighbour exists, then $\mathcal{R}_s^{in}(v,t)(x) = \min(\mathcal{R}_{s'}^{in}(v,t)(x), \mathcal{R}_s^{in}(u,t'+1)(x));$

5. for all U in $\mathcal{U}_{\mathcal{D}(s)}$, $\mathcal{R}^{below}_{s}(U) = \mathcal{R}^{below}_{s'}(\min(U, \mathcal{R}^{in}_{s}(u, U(u))));$ 6. $\zeta_{G'_{s}} = \zeta_{G'_{s'}};$ 7. $|changed(P_{s})| + \zeta_{G'_{s}} \leq \zeta.$

Proof. We claim that a state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ is supported by a (δ, ζ) -perturbation of (G, λ) if and only if the restriction of that perturbation to $G_{s'}$ supports a state $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$ of s' such that the criteria in the lemma hold. We begin by showing that the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ is supported by a (δ, ζ) -perturbation λ' if the criteria hold. Let λ'' be the perturbation which supports the state $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$ and λ' be the extension of λ'' given by P_s .

If criteria (1), (6), and (7) hold, then λ' must be an extension of λ'' and it must be a (δ, ζ) -perturbation of $\lambda|_{G_s}$. We now show that if the remaining criteria hold ((2)-(5)), then λ' must support the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$. We begin by showing that the foremost arrival time of a path from $v \in \mathcal{D}(s)$ to $w \in \mathcal{D}(s)$ departing at time t under λ' is t' if and only if $\mathcal{R}_s^{in}(v,t)(y) = t'$ as given in criteria (2)-(4). We have 3 cases to consider, namely u = y, u = v, and $v \neq u \neq y$.

It is clear that if u = v = y, the foremost arrival time of a path departing at t under any temporal assignment from v to itself is t. To check the remainder of the first case, we see that if $v \neq u = y$, the foremost arrival time of a path from v to u departing at time t under λ' must be the earliest time t'' such that there exists a neighbour w of u with foremost arrival time t' < t'' of a path departing at t, and an appearance of $\lambda(uw)$ at t''. That is, we require a path to y to which we can prefix the edge uw. Since λ' coincides with P_s and supports $\mathcal{R}_{s'}^{in}$, this is precisely criterion (2).

Furthermore, suppose that for all vertices v in $\mathcal{D}(s)$ and times t, $\mathcal{R}_s^{\text{in}}(v,t)(u) = t'$ if and only if either v = u and t = t'', or t'' is the earliest time such that there exist t' < t'' and $w \in N(u) \cap \mathcal{D}(s)$ where $\mathcal{R}_{s'}^{\text{in}}(v,t)(w) = t'$ and $t'' \in P_s(wu)$. Then we either have the case where the foremost path to u in (G_s, λ') is trivial or the concatenation of a foremost path to a neighbour of u and an edge from that neighbour to u. Thus, the foremost path from a vertex $v \in \mathcal{D}(s)$ departing at time t to u arrives at time t'' if and only if $\mathcal{R}_s^{\text{in}}(v,t)(u) = t''$.

In the second case, we have that $u = v \neq y$. If there exists a foremost path from u to $y \in \mathcal{D}(s)$ under λ' which departs at some time t_1 and arrives at time t_2 , then, since u has no neighbours in $G_s \setminus \mathcal{D}(s)$, there must be a (possibly trivial) path from a neighbour w of u to y in $\mathcal{G}_{s'}$ which departs at some time $t'_1 > t_1$ and arrives at time t_2 . This must be the foremost path from a neighbour of u to y departing at t_1 such that the edge uw is active at a time t' such that $t_1 \leq t' < t'_1$. Therefore, criterion (3) describes the foremost arrival time at vertices in the bag of paths from u departing at time t under λ' .

Suppose that $\mathcal{R}_s^{\text{in}}(u,t)(y) = t''$. Then, if y is a neighbour of u, t'' is the minimum of the first appearance of the edge uy at or after t and the earliest arrival time of the foremost path from another neighbour w of u to y which does not traverse u and departs after the earliest appearance of uw at or after t. If y is not a neighbour of u, then earliest arrival time of the foremost path from any neighbour w of u to y which does not traverse u and departs after the earliest after the earliest appearance of uw at or after t. If y is not a neighbour of u, then earliest arrival time of the foremost path from any neighbour w of u to y which does not traverse u and departs after the earliest appearance of uw at or after t must be the foremost arrival time of a path from u to y. Hence, the foremost path from a vertex $u \in \mathcal{D}(s)$ departing at time t to y arrives at time t'' if and only if $\mathcal{R}_s^{\text{in}}(u,t)(y) = t''$.

For the final case, let $v \neq u \neq y$ and t'' be the earliest time of arrival of a path from v to y departing at time t under λ' . This path either traverses u or it does not. If it does, then the foremost arrival time of the path can be found by finding the foremost arrival time of a path from u to y departing after the arrival of the foremost path from v to u. If the path does not traverse u, t'' must be the same as the foremost arrival time in the graph $(G_{s'}, \lambda'')$.

Since we take the minimum of both values in (4), t'' must be equal to $\mathcal{R}_s^{\text{in}}(v,t)(y)$ for all v, $y \in \mathcal{D}(s)$ and times t. Therefore, if criteria (2)-(4) hold, there must be a (δ, ζ) -perturbation λ' consistent with P_s where the foremost arrival time under λ' at each vertex in $\mathcal{D}(s)$ by paths from vertices v in the bag departing at time t is given by $\mathcal{R}_s^{\text{in}}(v,t)$ for all $v \in \mathcal{D}(s)$ and times t.

We now show that, for each function $U \in \mathcal{U}_{\mathcal{D}(s)}$ the number of distinct vertices reached from vertices in the bag by paths departing $v \in \mathcal{D}(s)$ at time assigned by U(v) under λ' is $\mathcal{R}_{s'}^{\text{below}}(\min(U, \mathcal{R}_s^{\text{in}}(u, U(u))))$. This implies that if all criteria hold, the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ is supported by λ' and thus valid.

To do this, we argue that for all functions $U \in \mathcal{U}_{\mathcal{D}(s)}$, the number of vertices reached in G_s under λ' by the set A of vertices assigned finite times by U at the times assigned by U is $\mathcal{R}^{\text{below}}_{s}(U)$ if $\mathcal{R}^{\text{below}}_{s}(U) < h$ and at least h otherwise. Suppose, for contradiction, that under λ' the set A reaches h' vertices in G'_s at the times given by U and either $h > h' \neq \mathcal{R}_s^{\text{below}}(U)$, or $\mathcal{R}_s^{\text{below}}(U) < h \leq h'$. The vertices reachable below the bag must be reachable by a path terminating at a vertex in $\mathcal{D}(s')$ which prefixes a path which only traverses vertices in G'_{s} . The vertex u cannot be incident to any forgotten vertices by the construction of a nice tree decomposition, therefore the final vertex v in $\mathcal{D}(s)$ on this path must be in $\mathcal{D}(s')$. The path from v must depart at either U(v) or the time of arrival of the path from u to v (or both). In addition, no vertices are forgotten between s and s'. Hence, $G'_s = G'_{s'}$. This gives us that, under λ' , the number of vertices reached strictly below the bag by a set A at the times specified by the function U must be $\mathcal{R}_s^{\text{below}}(U) = \mathcal{R}_{s'}^{\text{below}}(\min(U, \mathcal{R}_s^{\text{in}}(u, U(u))))$. If the number of vertices reachable from A at the times given by U not equal to $\mathcal{R}_s^{\text{below}}(U)$ and $\mathcal{R}_s^{\text{below}}(U) < h$, then the number of vertices in $G'_{s'}$ reachable by the set of vertices assigned finite times by the function $\min(U, \mathcal{R}^{in}(u, U(u)))$ must not be equal to $\mathcal{R}^{below}_{s'}(\min(U, \mathcal{R}^{in}(u, U(u))))$. This contradicts validity of the state $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$ of s'. This shows that if (5) holds, then $\mathcal{R}_s^{\text{below}}(U)$ describes, under λ' , the number of distinct vertices reached below the bag by vertices in the bag departing at the times specified by U. Hence, if all criteria in the lemma statement hold, the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ must be supported by λ' .

We now show that if there exists a (δ, ζ) -perturbation λ^* of $(G_s, \lambda|_{G_s})$ that supports the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$, then the criteria must hold. Let $\lambda_{s'}^*$ be the restriction of λ^* to $G_{s'}$, and $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$ be the child state supported by λ^* . Then, if P_s is the extension of $P_{s'}$ which coincides with λ^* , (1) must be true. In addition, by the definitions of a nice tree decomposition and a (δ, ζ) -perturbation, (6) and (7) must also hold.

What remains is to show that (2)-(5) also hold. It is clear that (2) describes the foremost arrival time of paths to u under λ^* . That is, the foremost arrival time from some vertex $v \in \mathcal{D}(s)$ to u departing at t is t'' if and only if v = u and t = t'', or t'' is the earliest time such that there is a foremost path from v to a neighbour w of u arriving at time t' < t''and an appearance of the edge uw at time t''. Thus this criterion must match the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$.

The foremost arrival of paths from u departing at t to a vertex $v \neq u$ under λ^* must be the minimum arrival time of a foremost path to v from a neighbour w of u departing after the earliest occurrence of the edge uw at or after t. Therefore, criterion (3) also matches the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$. To see that criterion (4) also holds, let t_2 be the earliest time such that $\mathcal{R}_{s'}^{\text{in}}(v, t_1)(y) = t_2$ or $\mathcal{R}_s^{\text{in}}(u, t^*(u))(y) = t_2$ where $\mathcal{R}_s^{\text{in}}(v, t_1)(u) < t^*(u)$. Suppose that $\mathcal{R}_{s'}^{\text{in}}(v, t_1)(y) = t_2$. Then, since the restriction $\lambda_{s'}^*$ of λ^* supports $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$, there must be a foremost temporal path from v to y in $\mathcal{D}(s)$ under λ^* which departs at t_1 and arrives by t_2 . If $\mathcal{R}_s^{\text{in}}(u, t^*(u))(y) = t_2$ where $\mathcal{R}_s^{\text{in}}(v, t_1)(u) < t^*(u)$, then we have a path from v to u in $\mathcal{D}(s)$ which departs at t_1 and arrives before t^* and a path from u to y which

departs at t^* and arrives by t_2 . Concatenating these paths gives us a path under λ^* which departs v at t_1 and arrives at y by t_2 . We can see that t_2 must be the foremost arrival time of a path from v to w departing at t under λ^* , else we contradict that $(P_{s'}, \mathcal{R}^{\text{below}}_{s'}, \mathcal{R}^{\text{in}}_{s'}, \zeta_{G'_{s'}})$ is supported by $\lambda^*_{s'}$. Thus criteria (2)-(4) hold.

All that remains is to show that criterion (5) must hold. Since $G_s = G_{s'}$, the number of distinct vertices reached below by vertices in the bag $\mathcal{D}(s)$ given departure times U must be equal to the number of vertices reached by vertices in the bag $\mathcal{D}(s')$ given departure times which account for the possibility of a path which traverses u. Since u has no neighbours strictly below $\mathcal{D}(s')$, this is only possible if a path reaches a vertex in the bag by a time earlier than prescribed by U. By our assertions that criteria (2)-(4) hold, this departure time must be described by min $(U, \mathcal{R}_s^{in}(u, U(u)))$. For each function U the vertices in $\mathcal{D}(s)$ must reach exactly $\mathcal{R}_{s'}^{below}(U')$ distinct vertices below the bag where $U' = \min(U, \mathcal{R}_s^{in}(u, U(u)))$ by paths which depart at the times given by U if $\mathcal{R}_{s'}^{below}(U') < k$ and at least $\mathcal{R}_{s'}^{below}(U')$ vertices otherwise. This follows from the fact that the subtrees rooted at s and s' consist of the same vertex set. Thus, criterion (5) must hold. Therefore the state $(P_s, \mathcal{R}_s^{below}, \mathcal{R}_s^{in}, \zeta_{G'_s})$ is valid if and only if the criteria hold.

Forget nodes

Suppose that a forget node s has child s' and that $\mathcal{D}(s') \setminus \mathcal{D}(s) = \{u\}.$

▶ Lemma 4.5. Let s be a forget node with child s' and forgotten vertex u. A state $(P_s, \mathcal{R}_s^{below}, \mathcal{R}_s^{in}, \zeta_{G'_s})$ of a forget node s is valid if and only if there exists a valid state $(P_{s'}, \mathcal{R}_{s'}^{below}, \mathcal{R}_{s'}^{in}, \zeta_{G'_s})$ of s' such that

- **1.** $P_s = P_{s'}|_{E(G[\mathcal{D}(s')])};$
- 2. for each function $U \in \mathcal{U}_{\mathcal{D}(s)}$, if there is a vertex w and finite times t_1, t_2 such that $U(w) = t_1$ and $\mathcal{R}_{s'}^{in}(w, t_1)(u) = t_2 < \infty$, then $\mathcal{R}_s^{below}(U) = \min(\mathcal{R}_{s'}^{below}(U') + 1, h)$ where U' is the extension of U where $U'(u) = t_2 + 1$, otherwise $\mathcal{R}_s^{below}(U) = \mathcal{R}_{s'}^{below}(U'')$ where U'' is the extension of U such that $U''(u) = \infty$;
- **3.** $\mathcal{R}_{s}^{in}(v,t) = \mathcal{R}_{s'}^{in}(v,t)|_{\mathcal{D}(s)}$ for all $v \in \mathcal{D}(s)$;
- 4. $\zeta_{G'_s} = \zeta_{G'_{s'}} + |\{(e,t) : u \in e, (e,t) \in changed(P_{s'})\}|.$

Proof. We show that we have a valid state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ of s which fits the criteria given in the lemma statement if and only if there is a temporal assignment λ' which supports it.

We begin by showing that if the criteria hold, the perturbation λ' which supports the child state $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$ must also support $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$. Since we have a forget node, $G_s = G_{s'}$. Therefore, any (δ, ζ) -perturbation λ' of $(G_{s'}, \lambda)$ must be a (δ, ζ) -perturbation of (G_s, λ) . By description of the state, the restriction of $P_{s'}$ to P_s coincides with λ' and the number of edges perturbed below $\mathcal{D}(s)$ must be exactly the sum of $\zeta_{G'_{s'}}$ and the edges which are perturbed under $P_{s'}$ which have been forgotten in s. Therefore, $P_{s'}$ and $\zeta_{G'_{s'}}$ must coincide with λ' . Since we allow paths to vertices in the bag which traverse forgotten vertices in our calculation of $\mathcal{R}_s^{\text{in}}$ and, by criterion (3), $\mathcal{R}_s^{\text{in}} = \mathcal{R}_{s'}^{\text{in}}|_{\mathcal{D}(s)}$, if $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$ is supported by λ' , then our calculation of $\mathcal{R}_s^{\text{in}}$ must be supported by λ' .

Now suppose that $\mathcal{R}_s^{\text{below}}$ is as described in criterion (2). Then we show that the number of vertices below the bag $\mathcal{D}(s)$ temporally reachable under λ' from vertices in $\mathcal{D}(s)$ after the times assigned by U is exactly $\mathcal{R}_s^{\text{below}}(U)$ if $\mathcal{R}_s^{\text{below}}(U) < h$ and at least $\mathcal{R}_s^{\text{below}}(U)$ otherwise. We have two cases to consider: $\mathcal{R}_s^{\text{below}}(U) = \mathcal{R}_{s'}^{\text{below}}(U'')$ and $\mathcal{R}_s^{\text{below}}(U) = \min(\mathcal{R}_{s'}^{\text{below}}(U')+1, h)$. The latter occurs, by criterion (2), only if there is a vertex w and finite times t_1, t_2 such

that $U(w) = t_1$ and $\mathcal{R}_{s'}^{\text{in}}(w, t_1)(u) = t_2$. That is, it occurs if u is temporally reachable from any vertex w by a temporal path departing at U(w). If this is true, the vertices in $\mathcal{D}(s)$ must reach all of the vertices below the bag reached by vertices of the child bag and u by a path departing at either u or another vertex $v \in \mathcal{D}(s)$ the time given by U. We note in particular that any vertices below the bag reached from u must still be temporally reachable from vertices in the bag since the path from w to u arrives before the path from u to vertices below the bag departs under U'. Therefore, in this case, the number of vertices below the bag $\mathcal{D}(s)$ temporally reachable from vertices in $\mathcal{D}(s)$ after the times assigned by U is exactly $\mathcal{R}_s^{\text{below}}(U)$ under λ' if $\mathcal{R}_s^{\text{below}}(U) < k$ and at least $\mathcal{R}_s^{\text{below}}(U)$ otherwise.

In the other case, there are no temporal paths from any vertex $v \in \mathcal{D}(s)$ departing at time U(v) which traverse u under λ . Therefore, the number of vertices below the bag $\mathcal{D}(s)$ temporally reachable from vertices in $\mathcal{D}(s)$ after the times assigned by U is at least $\mathcal{R}^{\text{below}}_{s'}(U'')$ under λ' where U'' is the extension of U such that $U(u) = \infty$.

We now show the reverse direction, that if a state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ of s is supported by some (δ, ζ) -perturbation λ'' , then the criteria must hold. Since $G_s = G_{s'}$ and all (δ, ζ) -perturbations of $G_{s'}$ support valid states of s', λ'' must support a valid state $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$ of s' such that $P_s = P_{s'}|_{E(G[\mathcal{D}(s')])}$ and $\zeta_{G'_s} = \zeta_{G'_{s'}} + |\{(e,t) : u \in e, (e,t) \in \text{changed}(P_{s'})\}|$. What remains to show is that criteria (2) and (3) hold.

We begin with criterion (3). Since λ'' also supports $(P_{s'}, \mathcal{R}_{s'}^{\text{below}}, \mathcal{R}_{s'}^{\text{in}}, \zeta_{G'_{s'}})$, the foremost arrival time of any vertex v in $\mathcal{D}(s)$ under λ'' after some time t must be exactly $\mathcal{R}_{s'}^{\text{in}}(v, t)$. Finally, the total number of distinct vertices below the bag $\mathcal{D}(s)$ reached by vertices v in $\mathcal{D}(s)$ by paths departing at time U(v) must precisely be the total number of vertices reached by vertices in $\mathcal{D}(s)$ departing at the times assigned by U plus any vertices reached from udeparting after the foremost arrival of a path from a vertex in $\mathcal{D}(s)$. This is exactly the value of $\mathcal{R}_s^{\text{below}}$ as described by (2). Therefore, a state of a forget node is valid if and only if the criteria hold.

Join nodes

Suppose that a join node s has children s_1, s_2 and that $\mathcal{D}(s) = \mathcal{D}(s_1) = \mathcal{D}(s_2)$.

We begin with the following definition which will aid us in calculating states of a join node. We use the observation that any foremost path in G_s for a join node s must alternately traverse paths consisting of vertices in the bag $\mathcal{D}(s)$ and vertices strictly below either child. We find the foremost arrival time at a vertex in the bag by splitting a path using i "alternations" into two subpaths with some midpoint x and checking whether there is a faster path traversing xsuch that the paths to and from x are each allowed fewer than i alternations. The foremost arrival time using at most i alternations is calculated recursively using the following formula.

▶ Definition 4.6. Let $(P_s, \mathcal{R}_s^{below}, \mathcal{R}_s^{in}, \zeta_{G'_s})$ be a state of a join node s with children s_1 and s_2 . Let $(P_{s_1}, \mathcal{R}_{s_1}^{below}, \mathcal{R}_{s_1}^{in}, \zeta_{G'_{s_1}})$ be a valid state of s_1 and $(P_{s_2}, \mathcal{R}_{s_2}^{below}, \mathcal{R}_{s_2}^{in}, \zeta_{G'_{s_2}})$ be a valid state of s_2 such that $P_s = P_{s_1} = P_{s_2}$. For all pairs $(v, t) \in \mathcal{D}(s) \times [0, T(G, \lambda) + \delta]$, we define the function $\mathcal{R}^i : \mathcal{D}(s) \times [0, T(G, \lambda) + \delta] \rightarrow \mathcal{U}_{\mathcal{D}(s)}$ as follows: $\mathcal{R}^0(v, t) = \min(\mathcal{R}_{s_1}^{in}(v, t), \mathcal{R}_{s_2}^{in}(v, t));$ and for all i > 0

$$\mathcal{R}^{i}(v,t) = \min\left(\min_{x \in \mathcal{D}(s)} \left(\mathcal{R}^{i-1}(x,\mathcal{R}^{i-1}(v,t)(x)+1)\right), \mathcal{R}^{i-1}(v,t)\right).$$

We can now calculate the valid states of join nodes.

▶ Lemma 4.7. Let s be a join node with children s_1 and s_2 . A state $(P_s, \mathcal{R}_s^{below}, \mathcal{R}_s^{in}, \zeta_{G'_s})$ of a join node $\mathcal{D}(s)$ is valid if and only if there exist valid states $(P_{s_1}, \mathcal{R}_{s_1}^{below}, \mathcal{R}_{s_1}^{in}, \zeta_{G'_{s_1}})$ of s_1 and $(P_{s_2}, \mathcal{R}_{s_2}^{below}, \mathcal{R}_{s_2}^{in}, \zeta_{G'_{s_2}})$ of s_2 such that

- 1. $P_{s_1} = P_{s_2} = P_s;$ 2. $\mathcal{R}_s^{in} = \mathcal{R}^{\lceil \log |\mathcal{D}(s)| \rceil}$ (as defined in Definition 4.6);
- 3. for all functions $U \in \mathcal{U}_{\mathcal{D}(s)}, \mathcal{R}_s^{below}(U) = \min(\mathcal{R}_{s_1}^{below}(U') + \mathcal{R}_{s_2}^{below}(U'), h)$ where U'(v) = $\min(U(v), \min_{w \in \mathcal{D}(s)} \mathcal{R}_s^{in}(w, U(w))(v) + 1) \text{ for all } v \in \mathcal{D}(s);$
- 4. $\zeta_{G'_s} = \zeta_{G'_{s_1}} + \zeta_{G'_{s_2}}$ 5. $\zeta_{G_s} + |changed(P_s)| \le \zeta$.

Proof. We claim that a state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ is supported by a (δ, ζ) -perturbation λ' of (G,λ) if and only if restrictions of λ' support the states $(P_{s_1}, \mathcal{R}_{s_1}^{\text{below}}, \mathcal{R}_{s_1}^{\text{in}}, \zeta_{G'_{s_1}})$ and $(P_{s_2}, \mathcal{R}_{s_2}^{\text{below}}, \mathcal{R}_{s_2}^{\text{in}}, \zeta_{G'_{s_2}})$ of s_1 and s_2 respectively and the criteria in the lemma hold. We begin by showing that the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ is supported by some (δ, ζ) -perturbation λ' if the criteria hold. We refer to the (δ, ζ) -perturbations supporting s_1 and s_2 as λ_1 and λ_2 respectively. Let λ' be the (δ, ζ) -perturbation of G_s which is equal to λ_1 when restricted to G_{s_1} and equal to λ_2 when restricted to G_{s_2} . This is well-defined by criterion (1).

Since the set of vertices in the bags of nodes s, s_1 and s_2 is the same, and $P_s = P_{s_1} = P_{s_2}$, λ' must coincide with P_s when restricted to the edges in $G[\mathcal{D}(s)]$. In addition, since the edge sets of G'_{s_1} and G'_{s_2} are disjoint, λ' must perturb exactly ζ_{G_s} edges below the bag. By criterion (5), the number of edges perturbed by λ in total must be at most ζ . Thus λ' is a (δ, ζ) -perturbation of G_s . We now show that if criteria (2) and (3) hold, λ' supports the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s}).$

 \triangleright Claim 4.8. A foremost path in (G_s, λ') from v to u departing at t arrives at t' for all times t, t' and vertices u, v in $\mathcal{D}(s)$ if and only if $\mathcal{R}_s^{\text{in}}(v, t)(u) = t'$.

Proof. We begin with the observation that any foremost temporal path between two vertices in (G_s, λ') must be a concatenation of (possibly trivial) paths alternating between G_{s_1} and G_{s_2} which are separated by paths consisting of at least one vertex in $\mathcal{D}(s)$. This is because the only edges in G_s with an end point in each of G_{s_1} and G_{s_2} must be in $G[\mathcal{D}(s)]$. Since there are at most $|\mathcal{D}(s)|$ distinct vertices in $\mathcal{D}(s)$, there are at most $|\mathcal{D}(s)|$ subpaths of a foremost path contained entirely in $G[\mathcal{D}(s)]$. We will refer to a maximal subpath contained entirely in $G[\mathcal{D}(s)]$ as a separating subpath.

We will show by induction on i that $\mathcal{R}^{i}(v,t)(w) = t'$ if and only if t' is the earliest arrival time of a path from v to x departing at t which contains at most $2^{i} + 1$ separating subpaths. We begin with our base case, i = 0. Here we set the value of $\mathcal{R}^{0}(v, t)(w)$ to be $\min(\mathcal{R}_{s_1}^{in}(v,t)(w),\mathcal{R}_{s_2}^{in}(v,t)(w))$ for all $v,w \in \mathcal{D}(s)$ and $t \in [0,T(G,\lambda)+\delta]$. We first show that if a path containing at most two separating subpaths from v to w departing at time t arrives at time t', then $\mathcal{R}^0(v,t)(w) = t'$. Note that since we are looking for a path from $v \in \mathcal{D}(s)$ to $w \in \mathcal{D}(s)$ there must be at least one separating subpath if any temporal path exists. Therefore, we must show that $\min(\mathcal{R}_{s_1}^{in}(v,t)(w),\mathcal{R}_{s_2}^{in}(v,t)(w))$ for all $v,w \in \mathcal{D}(s)$ is the earliest arrival time of a temporal path containing either 1 or 2 separating subpaths. If a path contains at most 2 separating subpaths, then it must contain at most one subpath which traverses vertices in only one of G'_{s_1} or G'_{s_2} . Assume without loss of generality, that it traverses edges in the former subgraph. Then a path from v to w with at most 2 separating subpaths in G_s departing at time t must be of the form $p_v p_1 p_w$ where p_v and p_w are separating subpaths containing v and w respectively and p_1 is a path traversing only vertices in $V(G_{s_1}) \setminus \mathcal{D}(s)$. By validity of $(P_{s_1}, \mathcal{R}_{s_1}^{\text{below}}, \mathcal{R}_{s_1}^{\text{in}}, \zeta_{G'_{s_1}})$, the arrival time of this

path must be $\mathcal{R}_{s_1}^{\text{in}}(v,t)(w)$ which is at most $\mathcal{R}_{s_2}^{\text{in}}(v,t)(w)$. Thus $\mathcal{R}^0(v,t)(w)$ gives the earliest arrival time of a path with at most 2 separating subpaths from v to w departing at time t. Thus, $\mathcal{R}^0(v,t)(w) = t'$ if and only if the earliest arrival time of a path containing at most two separating subpaths from v to w departing at time t is t' under λ' .

We now assume that for all $j \leq i$, $\mathcal{R}^j(v,t)(w) = t'$ if and only if the earliest arrival time of a path with at most $2^j + 1$ separating subpaths from v to w departing at time t in (G_s, λ') arrives at t'. We begin by showing that if $\mathcal{R}^{i+1}(v,t)(w) = t'$, then a path containing at most $2^{i+1} + 1$ separating subpaths from v to w departing at time t which arrives earliest arrives at time at least t'. For all vertices $v, w \in \mathcal{D}(s)$ and times t, we calculate $\mathcal{R}^{i+1}(v,t)(w)$ by finding the minimum of $\mathcal{R}^i(v,t)(w)$ and $\min_{x\in\mathcal{D}(s)}\mathcal{R}^i(x,\mathcal{R}^i(v,t)(x)+1)(w)$ for all $x\in\mathcal{D}(s)$. Suppose, for a contradiction, that under λ' the earliest arrival time of a path P containing at most $2^{i+1} + 1$ separating subpaths from v to w departing at t is t'' < t'. We have two cases to consider. Namely, P contains at most $2^i + 1$ separating subpaths, or the number of separating subpaths in P is between $2^j + 1$ and $2^{i+1} + 1$. If the former is true, then $\mathcal{R}^i(v,t)(w) = t''$ by the inductive hypothesis; a contradiction.

Now suppose that the number of separating subpaths in P is between $2^i + 1$ and $2^{i+1} + 1$. Let x be the final vertex in the (2^i) th separating subpath, P_{vx} be the subpath of P from v to x, and P_{xw} be the subpath of P from x to w. Then, P_{vx} and P_{xw} must contain at most $2^i + 1$ and at least 2 separating subpaths each. In addition, P_{vx} must be a path containing at most $2^i + 1$ separating paths from v to x departing at time t with earliest arrival time, and P_{xw} must be a path containing at most $2^i + 1$ separating paths from x to x departing paths from x to w departing strictly after the arrival time of P_{vx} with earliest arrival time. Thus, $t'' \ge \mathcal{R}^i(x, \mathcal{R}^i(v, t)(x) + 1)(w)$, a contradiction of our assumption that t'' < t'.

We now show that if $\mathcal{R}^{i+1}(v,t)(w) = t'$, then a path containing at most $2^{i+1}+1$ separating subpaths from v to w departing at time t which arrives earliest arrives at time at most t'. If $\mathcal{R}^{i+1}(v,t)(w) = t'$, either $t' = \mathcal{R}^{i-1}(v,t)$ or there exists a vertex $x \in \mathcal{D}(s)$ such that $t' = \mathcal{R}^{i-1}(x, \mathcal{R}^{i-1}(v,t)(x) + 1)$. In both cases, this implies there exists a path containing at most $2^{i+1} + 1$ separating subpaths from v to w departing at time t which arrives at time t'. Thus the earliest such path must arrive at time $t'' \ge \mathcal{R}^{i+1}(v,t)(w)$. Therefore, if $\mathcal{R}^{i+1}(v,t)(w) = t'$, then a path containing at most $2^{i+1} + 1$ separating subpaths that arrives earliest from v to w departing at time t arrives at time t'.

We now show that if the path containing at most $2^{i+1} + 1$ separating subpaths from v to w departing at time t which arrives earliest arrives at time t', then $\mathcal{R}^{i+1}(v,t)(w) = t'$. We note that a path containing at most $2^{i+1} + 1$ separating subpaths must either contain at most $2^i + 1$ separating subpaths, or be the concatenation of 2 subpaths consisting of a path from v to a vertex $x \in \mathcal{D}(s)$ departing at time t containing at most $2^i + 1$ separating subpaths and a path from x to w departing at time t' + 1 containing at most $2^i + 1$ separating subpaths where t' is the time of arrival of the former subpath. Therefore, we can find the earliest arrival time of such a path by finding the vertex x in $\mathcal{D}(s)$ that minimises the earliest arrival time of a path comprised of a subpath containing at most $2^{i} + 1$ separating subpaths from v to x and a subpath containing at most $2^{i} + 1$ separating subpaths from x to w, and taking the minimum of this arrival time and the minimum time of arrival of a subpath containing at most $2^{i} + 1$ separating subpaths. This is precisely our calculation of \mathcal{R}^{i+1} . Thus, $\mathcal{R}^{i+1}(v,t)(w) = t'$ if and only if the earliest arrival time of a path with at most $2^{i+1} + 1$ separating subpaths from v to w departing at time t in (G_s, λ') arrives at t'. By induction, $\mathcal{R}^i(v, t)(w) = t'$ if and only if the earliest arrival time of a path with at most $2^{i} + 1$ separating subpaths from v to w departing at time t in (G_s, λ') arrives at t' for all $i \in \mathbb{N}$.

As stated earlier, there are at most $|\mathcal{D}(s)|$ subpaths of a foremost path contained entirely

in $G[\mathcal{D}(s)]$ since there are at most $|\mathcal{D}(s)|$ distinct vertices in $\mathcal{D}(s)$. Thus, there are at most $|\mathcal{D}(s)|$ separating paths in a foremost path in G_s . Therefore, the foremost arrival time under λ' of a path given a departing vertex and time must be given by $\mathcal{R}^{\lceil \log |\mathcal{D}(s)| \rceil}$. Therefore if (2) holds, $\mathcal{R}_s^{i_s}$ matches the state supported by λ' .

We now show that, if (3) holds, the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ must be supported by λ' . We do this by showing that, under λ' , the number of distinct vertices reached below the bag by vertices in the bag at the departure times given by any function U is precisely $\mathcal{R}_s^{\text{below}}$ as given by (3). The departure time of the paths reaching vertices below the bag must be after the foremost arrival time of a path from a vertex in the bag departing at the time specified by U. This includes the trivial path from v to itself departing at U(v). Note that, since each vertex is potentially assigned a different departure time by U, a path could arrive from a vertex w in $\mathcal{D}(s)$ at a vertex $v \in \mathcal{D}(s)$ before U(v) by a path departing at U(w). Since the sets of vertices in $G_{s_1} \setminus \mathcal{D}(s)$ and $G_{s_2} \setminus \mathcal{D}(s)$ are disjoint, the number of vertices below the bag which are temporally reachable from a vertex in the bag at the departure times given under λ' must be the sum of those reachable from that vertex in $G_{s_1} \setminus \mathcal{D}(s)$ and $G_{s_2} \setminus \mathcal{D}(s)$ under the restriction of λ to each subgraph. This is precisely the number described by (3) (upper bounded by h). Therefore, if all criteria hold, the (δ, ζ) -perturbation of G_s which is equal to λ_1 when restricted to G_{s_1} and equal to λ_2 when restricted to G_{s_2} must support the state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$.

Now suppose we have a (δ, ζ) -perturbation of G_s . Call this perturbation λ'' . We will show that the criteria must hold. We denote by λ''_1 and λ''_2 the restrictions of λ'' to G_{s_1} and G_{s_2} respectively. By construction, criteria (1), (4), and (5) must hold. Furthermore, given states supported by each of λ''_1 and λ''_2 , the foremost arrival time of paths between vertices in the bag under λ'' must be the foremost arrival time of a path containing at most $\mathcal{D}(s)$ separating subpaths. As shown in Claim 4.8, this is precisely $\mathcal{R}^{\lceil \log |\mathcal{D}(s)| \rceil} = \mathcal{R}_s^{\text{in}}$. Therefore, criterion (2) must hold. Finally, for any function $U \in \mathcal{U}_{\mathcal{D}(s)}$, the number of distinct vertices reachable from vertices $v \in \mathcal{D}(s)$ departing at U(v) under λ'' must be the sum of vertices reachable strictly below the bags $\mathcal{D}(s_1)$ and $\mathcal{D}(s_2)$ by paths departing after the earliest time of arrival at vertices in the bag by paths departing at the times given by U. Hence, criterion (3) gives $\mathcal{R}_s^{\text{below}}$ under λ'' . Thus all criteria hold and a state $(P_s, \mathcal{R}_s^{\text{below}}, \mathcal{R}_s^{\text{in}}, \zeta_{G'_s})$ is supported by a (δ, ζ) -perturbation λ' of (G, λ) if and only if restrictions of λ' support the states $(P_{s_1}, \mathcal{R}_{s_1}^{\text{below}}, \mathcal{R}_{s_1}^{\text{in}}, \zeta_{G'_{s_1}})$ and $(P_{s_2}, \mathcal{R}_{s_2}^{\text{below}}, \zeta_{s_2})$ of s_1 and s_2 respectively and the criteria in the lemma hold.

4.3 Proof of Theorem 4.3

▶ **Theorem (Theorem 4.3 restated).** Given a temporal graph (G, λ) where the treewidth of G is at most ω , we can solve TRLP in time

$$O\left(n\omega^4\zeta^3(T(G,\lambda)+\delta)^{\omega})\cdot(2\delta hT(G,\lambda))^{4\omega^2(T(G,\lambda)+\delta)^{\omega}}\right).$$

In particular, we can solve TRLP in polynomial time when the treewidth of the underlying graph, the permitted perturbation size δ and the lifetime of (G, λ) are all bounded by constants.

Proof. We can compute a tree decomposition $\operatorname{in} \omega^O(\omega^3)n$ time given a graph on n vertices with treewidth ω [4]. Furthermore, given a tree decomposition of a graph of width at most ω , we can find a nice tree decomposition of the graph of width at most ω in time bounded by $O(\omega^3 n)$ [9]. Given a nice tree decomposition of a temporal graph (G, λ) as described in Definition , we solve TRLP by finding all valid states of the root node for each choice of

source vertex x. For such a node, we check if there exists a valid state of the root node s containing a source vertex x such that $\mathcal{R}_s^{\text{below}}(U) \ge h - 1$ where U(x) = 0.

Our algorithm works up from the leaves to the root, computing all valid states for each node, so that when we consider any node we have access to the set of valid states for all its children. We use Lemmas 4.4, 4.5 and 4.7 to find the valid states of each type of node given the valid states of its children. To bound the running time of the algorithm, we bound the time needed to compute the valid states of a node given the valid states of its children (if there are any).

We can bound the number of possible states for each bag by considering the number of possibilities for each component of a state. There are at most ζ edges perturbed below a given bag. The number of time-edges per bag is bounded above by $O(w^2 \cdot T(G, \lambda))$ where w is the treewidth of the underlying graph G. For a given time-edge, there are 2δ times that it could be active under a perturbation of λ , therefore there are at most $(2\delta)^{w^2T(G,\lambda)}$ possible functions P_s . Recall that \mathcal{R}^{in} is a function from the set $\mathcal{D}(s) \times [0, T(G, \lambda) + \delta]$ to the set $\mathcal{U}_{\mathcal{D}(s)}$. There are at most $\omega(T(G, \lambda) + \delta)$ and $(T(G, \lambda) + \delta + 1)^{\omega}$ elements in the domain and codomain of \mathcal{R}^{in} respectively. Thus, there are at most $(T(G, \lambda) + \delta)^{\omega^2(T(G, \lambda) + \delta)}$ functions \mathcal{R}^{in} for each bag $\mathcal{D}(s)$.

As stated earlier, for a given bag $\mathcal{D}(s)$, there are at most $(T(G, \lambda) + \delta + 1)^{\omega}$ functions in $\mathcal{U}_{\mathcal{D}(s)}$. Since this is the domain of $\mathcal{R}^{\text{below}}$ and the codomain is of cardinality h + 1, there are at most

$$h^{(T(G,\lambda)+\delta+1)^{\omega}}$$

possible functions $\mathcal{R}^{\text{below}}$. There are therefore at most

$$O\left(\zeta \cdot (2\delta)^{w^2 T(G,\lambda)} \cdot (T(G,\lambda) + \delta + 1)^{\omega^2 (T(G,\lambda) + \delta)} \cdot h^{(T(G,\lambda) + \delta)^{\omega}}\right)$$
$$= O\left(\zeta \cdot (2\delta h T(G,\lambda))^{\omega^2 (T(G,\lambda) + \delta)^{\omega}}\right)$$

possible states for a node in the nice tree decomposition.

We can find the valid states for leaf nodes in constant time. Given a state of an introduce node, we check whether its valid by checking that each of the 7 criteria in Lemma 4.4 hold for a valid state of its child. Given a child state, the time needed to check each criterion is as follows:

- For Criterion 1, we can check in time $O(\omega^2 \tau)$ that P_s extends $P_{s'}$ of the child state by examining each time-edge in the bag.
- For each of Criteria 2-4, and for each pair (v, t), we need time $O(\omega \tau)$ to consider all time-edges incident with u and perform constant-time lookups for each; repeating for every pair (v, t) means the total time needed to check all three criteria is $O(\omega^2 \tau(T(G, \lambda) + \delta))$.
- For Criterion 5, for a fixed U we need time $O(\omega)$ to compute the updated departure times for all vertices, and then look up corresponding values in the child state; summing over all possible functions U means this criterion can be checked in time $O(\omega(T(G,\lambda) + \delta)^{\omega})$.
- For Criterion 6 we need only constant time to check that $\zeta_{G'_s} = \zeta_{G'_{s'}}$.
- For Criterion 7, we can compute the number of perturbed time-edges under P_s in time $O(\omega^2 \tau)$ by considering every time-edge in the bag, then perform a constant-time arithmetic operation.

Overall, this means the time needed to check consistency of a given combination of states for a parent and child is $O(\omega^2(T(G,\lambda) + \delta)^{\omega})$. This must be repeated for every pair of possible parent and child states, giving us a run-time of

$$O\left(\zeta^2\omega^2\cdot(2\delta hT(G,\lambda))^{3\omega^2(T(G,\lambda)+\delta)^{\omega}}\right).$$

To find valid states of forget nodes we check consistency of each combination of parent and child states using the criteria of Lemma 4.5 as follows:

- For Criterion 1, we can check in time $O(\omega^2 \tau)$ that P_s is a restriction of $P_{s'}$ of the child state by examining each time-edge in the bag.
- To check Criterion 2, for each function $U \in \mathcal{U}_{\mathcal{D}(s)}$ we must perform a constant number of constant-time operations for each vertex $w \in \mathcal{D}(s)$; repeating for every U and w therefore takes time $O(\omega(T(G,\lambda) + \delta)^{\omega})$.
- For Criterion 3, for each pair (v, t) with $v \in \mathcal{D}(s)$ we check that $\mathcal{R}_s^{\text{in}}(v, t) = \mathcal{R}_{s'}^{\text{in}}$ in time $O(\omega)$; repeating this for each pair (v, t) gives a total time of $O(\omega^2(T(G, \lambda) + \delta))$ to check the criterion.
- We require $O(\omega \tau)$ to check Criterion 4 by counting the perturbed edges incident to the forgotten vertex.

Overall, this means the time needed to check consistency of a given combination of states for a parent and child is $O(\omega^2(T(G,\lambda) + \delta)^{\omega})$. This must be repeated for every pair of possible parent and child states, giving us a run-time of

$$O\left(\zeta^2\omega^2\cdot(2\delta hT(G,\lambda))^{3\omega^2(T(G,\lambda)+\delta)^{\omega}}\right).$$

For join nodes we need to combinations of a parent state and a state for each child. The time needed to check whether the criteria of Lemma 4.7 hold for each combination is as follows:

- For Criterion 1, we can check in time $O(\omega^2 \tau)$ that $P_s = P_{s_1} = P_{s_2}$ by examining each time-edge in the bag.
- = To check Criterion 2 we must compute $R^{\lceil \log \omega \rceil}$ as in Definition 4.6. Initialising $R^0(v,t)(w)$ takes constant time for each pair (v,t) and vertex w, so time $O(\omega^2(T(G,\lambda) + \delta))$ overall. To compute $\mathcal{R}^i(v,t)$ for a fixed pair (v,t) and vertex w, given constant-time access to all values of \mathcal{R}^{i-1} , we require time $O(\omega)$; Calculating this for all pairs (v,t) and vertices w therefore takes time $O(\omega^3(T(G,\lambda) + \delta))$. Since we repeat this process $O(\log \omega)$ times, the total time needed to check Criterion 2 is $O(\omega^3 \log \omega(T(G,\lambda) + \delta))$ time.
- Criterion 3 requires us to compute an updated function for the departure times of the paths. For each vertex in the bag $\mathcal{D}(s)$, this takes time $O(\omega)$. Checking the criterion for all functions $U \in \mathcal{U}_{\mathcal{D}(s)}$, therefore requires $O(\omega^2(T(G,\lambda) + \delta)^{\omega})$ time.
- We can check Criterion 4 in constant time by checking that ζ_{G_s} is the sum of $\zeta_{G_{s_1}}$ and $\zeta_{G_{s_2}}$.
- Criterion 5, we can compute the number of perturbed time-edges under P_s in time $O(\omega^2 \tau)$ by considering every time-edge in the bag, then perform a constant-time arithmetic operation.

Overall, this means that the time needed to check consistency of a given combination of states for a parent and its two children is $O(\omega^3 \log \omega(T(G, \lambda) + \delta)^{\omega}))$. This must be repeated for every triple of possible parent and child states, giving us a run-time of

$$O\left(\omega^4 \zeta^3 (T(G,\lambda)+\delta)^{\omega}) \cdot (2\delta h T(G,\lambda))^{4\omega^2 (T(G,\lambda)+\delta)^{\omega}}\right)$$

To solve TRLP, we must find all valid states of every node in the nice tree decomposition. Note that we have O(n) nodes where n is the number of vertices in the input graph. Finding

valid states of join nodes is the most time-consuming part of the algorithm, therefore the worst-case running time is

$$O\left(n\omega^4\zeta^3(T(G,\lambda)+\delta)^{\omega})\cdot(2\delta hT(G,\lambda))^{4\omega^2(T(G,\lambda)+\delta)^{\omega}}\right).$$

5 **Eccentricity**

We now consider two closely related problems under the same model of perturbation. Instead of asking about the number of reachable vertices, we are interested in whether it is possible to reach all vertices in the graph by paths whose length or duration is at most some upper bound. It is unsurprising that the problem of determining whether there exists a set of perturbations achieving either goal is NP-complete; in contrast to TRLP, however, it turns out that these problems do not become easier when we allow an appearance of every edge to be perturbed. If all these perturbations can also be sufficiently large, however, we do still recover tractability.

Above, we discuss strict temporal paths, as well as their lengths. We will use the terms shortest and longest to be specifically in relation to the number of edges in the path. However, there are other measures of a temporal path that may be relevant under various real-world scenarios. Earlier, we defined foremost paths and the arrival time of a foremost path. In addition, we say that the duration of a path $P := ((v_0v_1, t_1), \dots, (v_{\ell-1}v_\ell, t_\ell))$ is $t_\ell - t_1$. A path P is fastest of a set of paths \mathcal{P} if there is no other path $P' \in \mathcal{P}$ of strictly smaller duration.

We begin with formal definitions of the problems we are considering. In all three definitions, we are given a temporal graph (G, λ) and a source vertex v_s . This vertex v_s has a temporal shortest eccentricity of at most k if, for every vertex $v_t \in V(G)$, a shortest temporal path from v_s to v_t contains at most k edges. The vertex v_s has a temporal fastest eccentricity of at most k if, for every vertex $v_t \in V(G)$, a fastest temporal path from v_s to v_t has a duration of at most k. We use the notation $ecc^{S}((G,\lambda),v)$ (respectively $ecc^{Fa}((G,\lambda),v)$) to mean the temporal shortest (respectively fastest) eccentricity of v in the temporal graph (G, λ) . We note that, given a temporal graph (G, λ) and a vertex $v \in V(G)$, both $ecc^{S}((G, \lambda), v)$ and $ecc^{Fa}((G,\lambda),v)$ can be computed in polynomial time [5].

We now define the problems of determining whether there is a perturbation achieving some specified eccentricity.

Temporal shortest eccentricity under perturbation (TSEP)

Input: A temporal graph (G, λ) , a source vertex $v_s \in V(G)$, and integers k, δ , and ζ . Question: Is there a (δ, ζ) -perturbation λ' of λ such that $\operatorname{ecc}^{\mathrm{S}}((G, \lambda'), v_s) < k$?

Temporal fastest eccentricity under perturbation (TFaEP)

Input: A temporal graph (G, λ) , a source vertex $v_s \in V(G)$, and integers k, δ , and ζ . Question: Is there a (δ, ζ) -perturbation λ' of λ such that $ecc^{Fa}((G, \lambda'), v_s) \leq k$?

Here we have considered two of the three standard notions of optimality for temporal paths. One could naturally define a third problem based on temporal *foremost* eccentricity (requiring the earliest arrival time of a path from v to every other vertex to be at most

k), but this problem has previously been studied by Deligkas et al. [11] under another name. The problem REACHFAST(k) is to minimise the foremost eccentricity of some set S of sources (i.e. minimise the maximum eccentricity over all $s \in S$) when at most k edges can be perturbed, while REACHFASTTOTAL(k) asks the same question when the sum of the sizes of all perturbations must be bounded by k. The behaviour of these problems is similar to what we see for TSEP and TFaEP: they are intractable in general, but can be solved in polynomial time if both the number and size of the perturbations are unrestricted.

We begin by observing that TSEP and TFaEP are both NP-complete. Inclusion in NP is trivial (the set of perturbations acts as a certificate), and to see NP-hardness we note that in the proof of Lemma 2.3 our constructed temporal graph contains a source vertex that reaches all vertices via a path of at most two edges and of duration at most two if and only if the original graph has a dominating set of size r. (We note that Construction 2.1 is similar to the construction used by Deligkas et al. [11, Theorem 2] to show hardness of REACHFAST(k) and REACHFASTTOTAL(k) by reduction from HITTING SET.) We can further conclude from this observation (as in Corollary 2.4) that both problems are W[2]-hard parameterised by ζ and are NP-hard to approximate (where the goal is to find the smallest number of perturbations required).

Recall that TRLP became polynomial-time solvable when we were allowed to perturb at least one appearance of every edge. In contrast with this result, we now show that both TFaEP and TSEP remain NP-hard even when an appearance of every edge can be perturbed, for any constant δ , and for constant values of k. Note that this is also a contrast to the behaviour for foremost eccentricity: Deligkas et al. [11, Algorithm 1] show that this problem is efficiently solvable when ζ is large.

We begin with TSEP, and give a hardness result via a reduction from SAT.

▶ **Theorem 5.1.** *TSEP remains* NP-*hard even for* $\zeta = m$ *, and for any constant integers* $\delta \geq 1$ and $k \geq 4$.

Proof. We show how, given integers δ and $k \geq 4$, an instance $((G,\lambda), k, 1, m)$ (where m = |E(G)|) of TSEP can be constructed from any instance $\bigwedge_j C_j$ of SAT such that $((G,\lambda), k, \delta, m)$ is a yes-instance of TSEP if and only if $C \bigwedge_j C_j$ is a yes-instance of SAT. To begin, we construct the temporal graph (G,λ) from an instance $\bigwedge_j C_j$ of SAT on variables $\{x_i\}$ as follows. First, create the vertex v_s . Then, for each clause C_j create the vertex v_j^c (collectively referred to as clause vertices), and for each variable x_i define $v_{i,0} = v_s$, create the vertices $v_{i,\ell}$ for $\ell \in [k]$, for $\ell \in [k-4]$ add the temporal edges $(v_{i,\ell}v_{i,\ell+1}, \ell+1)$, and add the temporal edges $(v_{i,k-4}v_{i,k-3}, k-3), (v_{i,k-4}v_{i,k-2}, 3\delta + k - 2), (v_{i,k-3}v_{i,k-2}, k-2), (v_{i,k-2}v_{i,k-1}, \delta + k - 1),$ and $(v_{i,k-1}v_{i,k}, 3\delta + k)$. Then, for each C_j that contains x_i as a literal we add the temporal edge $(v_{i,k}v_j^c, 3\delta + k + 1)$. A diagram of this appears in Figure 2.

We now note some properties of this construction. First, $v_{i,k-4}v_{i,k-2}v_{i,k-1}v_j^c$ can never form part of a temporal path in (G, λ') for any δ -perturbation λ' of λ as both $\lambda'(v_{i,k-4}v_{i,k-2}) \geq 2\delta + k - 2$ and $\lambda'(v_{i,k-1}v_j^c) \leq \delta + k$ hold for every δ -perturbation. Therefore any path of length k from v_s to an arbitrary clause vertex v_j^c in (G, λ') for some δ -perturbation λ' must be either of the form $v_s v_{i,1} v_{i,2} \dots v_{i,k-3} v_{i,k-2} v_{i,k-1} v_j^c$ for some i (we call this a \top -path for x_i), or of the form $v_s v_{i,1} v_{i,2} \dots v_{i,k-4} v_{i,k-2} v_{i,k-1} v_{i,k} v_j^c$ for some variable x_i (we will call this a \perp -path for x_i). If we have a \top -path for x_i in (G, λ') then $\lambda'(v_{i,k-2} v_{i,k-1}) \leq \delta + k - 1$, and if we have a \perp -path for x_i in (G, λ') then $\lambda'(v_{i,k-2} v_{i,k-1} \geq 2\delta + k - 1$.

Next we show that $((G, \lambda), v_s, k, 1, m)$ is a yes-instance for TSEP if and only if $\bigwedge_j C_j$ is satisfiable. First, assume that $\bigwedge_j C_j$ is satisfiable and that $\phi : \{x_i\} \mapsto \{\top, \bot\}$ is a truth

assignment that satisfies $\bigwedge_{i} C_{j}$, and construct λ' as follows.

$$\begin{array}{l} \forall i \quad \lambda'(v_s v_{i,1}) = 1 \\ \forall i \forall \ell \in [k-4] \quad \lambda'(v_{i,\ell} v_{i,\ell+1}) = \ell + 1 \\ \quad \forall i \quad \lambda'(v_{i,k-4} v_{i,k-2}) = 2\delta + k - 2 \\ \quad \forall i \quad \lambda'(v_{i,k-1} v_{i,k}) = 2\delta + k \\ \quad \forall i, j \quad \lambda'(v_{i,k-1} v_j^c) = \delta + k \\ \quad \forall i, j \quad \lambda'(v_{i,k-1} v_j^c) = 2\delta + k + 1 \\ \quad \forall i \text{ where } \phi(x_i) = \top \quad \lambda'(v_{i,k-2} v_{i,k-1}) = k - 1 \\ \quad \forall i \text{ where } \phi(x_i) = \bot \quad \lambda'(v_{i,k-2} v_{i,k-1}) = 2\delta + k - 1 \end{array}$$

This satisfies λ' is a (δ, ζ) -perturbation of λ , and note that in particular, if $\phi(x_i) = \top$ then we have a \top -path for x_i in (G, λ') , and if $\phi(x_i) = \bot$ then we have a \bot -path for x_i in (G, λ') .

We now consider shortest paths to various groups of vertices. First, for any variable x_i , if $\phi(x_i) = \top$ then $v_s v_{i,1} v_{i,2} \dots v_{i,k-3} v_{i,k-2} v_{i,k-1} v_{i,k}$ is a temporal path of length k, and if $\phi(x_i) = \bot$ then $v_s v_{i,1} v_{i,2} \dots v_{i,k-4} v_{i,k-2} v_{i,k-1} v_{i,k}$ is a temporal path of length k-1 and $v_s v_{i,1} v_{i,2} \dots v_{i,k-4} v_{i,k-2} v_{i,k-1} v_{i,k}$ is a temporal path of length k-1 and $v_s v_{i,1} v_{i,2} \dots v_{i,k-4} v_{i,k-2} v_{i,k-1} v_{i,k}$ is a temporal path of length k-1 and $v_s v_{i,1} v_{i,2} \dots v_{i,k-4} v_{i,k-3}$ is a temporal path of length k-3. It thus remains to see whether vertices of the form v_j^c are reachable in paths of length k. Take an arbitrary such vertex v_j^c ; as ϕ satisfies $\bigwedge_j C_j$, at least one literal in C_j must be true. If this literal is of the form x_i (i.e., x_i appears non-negated in C_j), then $\phi(x_i) = \top$ and so we have a \top -path for x_i in (G, λ') and thus the vertex v_j^c is reachable by a path of length k. Next, if this literal is of the form $\overline{x_i}$ (i.e., x_i appears negated in C_j), then $\phi(x_i) = \bot$ and so we have a \bot -path for x_i in (G, λ') and thus the vertex v_j^c is reachable by a path of length k. Thus as λ' is a (δ, m) -perturbation, $((G, \lambda), v_s, k, \delta, m)$ is a yes-instance for TSEP.

Next, assume that $((G, \lambda), v_s, k, 1, m)$ is a yes-instance for TSEP. Then there must be a (δ, m) -perturbation λ' of λ , such that for any clause vertex v_j^c , there is a path of length k from v_s to v_j^c . We now define $\phi : \{x_i\} \mapsto \{\top, \bot\}$. For each edge of the form $v_{i,k-2}v_{i,k-1}$, if $\lambda'(v_{i,k-2}v_{i,k-1}) \leq \delta + k - 1$ then let $\phi(x_i) = \top$, else let $\phi(x_i) = \bot$. Now consider an arbitrary clause C_j , and its associated clause vertex v_j^c . There must exist a temporal path of length k in (G, λ') from v_s to v_j^c , and by the construction of (G, λ) and the fact that λ' is a δ -perturbation, it must be that this path is either either a \top -path for some variable x_i , or a \bot -path for some variable x_i . If this path is a \top -path for some variable x_i then $\lambda'(v_{i,k-2}v_{i,k-1} \leq \delta + k - 1$ and so $\phi(x_i) = \top$, and by construction, the literal x_i appears non-negated in C_j , so C_j is satisfied. Alternatively, if this path is a \bot -path for some variable x_i then $\lambda'(v_{i,k-2}v_{i,k-1} \geq 2\delta + k - 1 > \delta + k - 1$ and so $\phi(x_i) = \bot$, and by construction, the literal x_i appears negated in C_j , so C_j is satisfied. Since we took an arbitrary clause vertex v_i^c , it follows that ϕ satisfies $\bigwedge_i C_j$.

We give an analogous result for TFaEP, which again involves a reduction from SAT.

▶ **Theorem 5.2.** For any integers $k \ge 2$ and any $\delta \ge 1$, TFaEP is NP-hard even if $\zeta = m$.

Proof. We show how, given integers $k \geq 2$ and δ , an instance $((G, \lambda), k, \delta, m)$ (where m = |E(G)|) of TFaEP can be constructed from an instance $\bigwedge C_j$ of SAT such that $((G, \lambda), k, \delta, m))$ is a yes-instance of TFaEP if and only if $\bigwedge C_j$ is a yes-instance of SAT. First, we take our instance $\bigwedge C_j$ of SAT and construct our temporal graph (G, λ) , beginning by creating the vertex v_s . Then for each variable x_i , define $v_i, 0 = v_s$, and create the vertices




Figure 2 Diagram of a partial construction for Theorem 5.1 showing the relevant vertices for variable x_1 and clauses C_1 and C_2 . In this construction, clause C_1 contains the literal x_1 and clause C_2 contains the literal $\overline{x_1}$. This diagram is labelled with time labels from λ , and the dashed line indicates a path on the vertices $v_{i,2} \dots v_{i,k-4}$, where $\lambda(v_{i,\ell}v_{i,\ell+1}) = \ell + 2$. Note that, as $\delta = 1$, if λ' is a 1-perturbation of λ and contains a path of either length or duration k from v_s to v_1^c through $v_{i,k-1}$ it must be that $\lambda'(v_{i,k-2}v_{i,k-1}) = k - 1$, while if (G, λ') is to contain a path of length or duration k from v_s to v_2^c through vertex $v_{i,k-1}$ it must that $\lambda'(v_{i,k-2}v_{i,k-1}) = k$. This dichotomy translates to setting the variable x_i to either true (if $\lambda'(v_{i,k-2}v_{i,k-1}) = k - 1$) or false (if $\lambda'(v_{i,k-2}v_{i,k-1}) = k$).

 $v_{i,\ell}$ for $\ell \in [k-1]$. Lastly, for each clause C_j in the SAT instance create the vertex v_j^c . We next create the temporal edges. First, for each variable x_i add the edge $(v_s v_{i,1}, 1)$. Then for each variable x_i , and for each $\ell \in [k-2]$, add the edge $(v_{i,\ell}v_{i,\ell+1}, \ell+1)$. Lastly, for each variable x_i , and each clause C_j , if x_i appears as a literal (i.e., non-negated) in C_j , add the edge $(v_{i,k-1}v_j^c, k+2\delta)$, and if $\overline{x_i}$ appears as a literal in C_j , add the edge $(v_{i,k-1}v_j^c, k-1)$. A diagram of this gadget is shown in Figure 3.

We now note some properties of this construction for an arbitrary δ -perturbation λ' of λ . First, consider some variable x_i , and some clause C_j . There can be no temporal path from v_s to v_j^c of length strictly less than k, and so for any temporal path from v_s to v_j^c in (G, λ') of duration at most k, if edge e' immediately follows edge e, then $\lambda'(e') = \lambda'(e) + 1$. Now consider some variable x_i , and some clause C_j such that x_i only appears non-negated in C_j . To have a valid temporal path of duration k in (G, λ') from v_s to v_j^c through $v_{i,k-1}$, we must have $\lambda'(v_{i,k-2}v_{i,k-1}) = k - 1 + \delta$ and $\lambda'(v_{i,k-1}v_j^c) = k + \delta$. On the other hand, if x_i only appears negated in C_j , then for a valid temporal path of duration k in (G, λ') from v_s to v_j^c through $v_{i,k-1}$ to exist, we must have $\lambda'(v_{i,k-1}v_j^c) \leq k - 1 + \delta$, and so we must have $\lambda'(v_{i,k-2}v_{i,k-1}) \leq k - 2 + \delta$. We later use this dichotomy to encode whether the variable x_i is true or false.

We now show that $((G, \lambda), v_s, k, \delta, m)$ is a yes-instance to TFaEP if and only if $\bigwedge_j C_j$ is a yes-instance to SAT. First, assume that $\bigwedge_j C_j$ is satisfiable, and let ϕ be a function mapping variables to $\{\top, \bot\}$ that satisfies $\bigwedge_j C_j$. We will use ϕ to construct a a δ -perturbation λ' of λ . For each variable x_i , if $\phi(x_i) = \top$ then let $\lambda'(v_s v_{i,1}, 1 + \delta)$, for each $\ell \in [k-2]$ let $\lambda'(v_{i,\ell}v_{i,\ell+1}) = \ell + 1 + \delta$, and for each clause C_j that contains x_i as a literal (i.e. non-negated) let $\lambda'(v_{i,k-1}v_j^c) = k + \delta$. For each variable x_i , if $\phi(x_i) = \bot$ then let $\lambda(v_s v_{i,1}, 1)$, for each $\ell \in [k-2]$ let $\lambda'(v_{i,\ell+1}) = \ell + 1$, and for each clause C_j that contains x_i as a literal (i.e. non-negated) let $\lambda'(v_{i,\ell+1}) = \ell + 1$, and for each clause C_j that contains x_i as a literal (i.e. non-negated) let $\lambda'(v_{i,k-1}v_j^c) = k$. We have not yet defined λ' for some edges e yet; for such edges, let $\lambda'(e) = \lambda(e)$. By this construction, λ' is a δ -perturbation of λ , so we now consider ecc^{Fa}($(G, \lambda'), v_s$). First, for any variable x_i , the path $v_s v_{i,1} \dots v_{i,k-2} v_{i,k-1}$ is a path of duration k - 1 in (G, λ') , so we need only consider vertices of the form v_j^c . Consider an arbitrary such vertex v_j^c , and let C_j be its associated clause. As ϕ satisfies C_j , there must be some variable x_i such that either $\phi(x_i) = \top$ and x_i appears as a literal in C_j , or $\phi(x_i) = \bot$




Figure 3 Diagram of a partial construction for Theorem 5.2 showing the relevant vertices for variable x_1 and clauses C_1 and C_2 . In this construction, clause C_1 contains the literal x_1 and clause C_2 contains the literal $\overline{x_1}$. This diagram is labelled with time labels from λ , and the dashed line indicates a path on the vertices $v_{1,2} \ldots v_{1,k-4}$, where $\lambda(v_{1,\ell}v_{i,\ell+1}) = \ell + 1$. Note that, as $\delta = 1$, if λ' is a δ -perturbation of λ and contains a path of duration at most k from v_s to v_1^c through $v_{1,k-1}$ it must be that $\lambda'(v_{1,k-2}v_{1,k-1}) = k + \delta - 1$, while if (G, λ') is to contain a path of duration at most k from v_s to v_2^c through vertex $v_{1,k-1}$ it must that $\lambda'(v_{1,k-2}v_{1,k-1}) < k + \delta - 1$. This dichotomy translates to setting the variable x_1 to either true (if $\lambda'(v_{1,k-2}v_{1,k-1}) = k - 1 + \delta$) or false (if $\lambda'(v_{1,k-2}v_{1,k-1}) \leq k - 2 + \delta$).

and $\overline{x_i}$ appears as a literal in C_j . In either case, the path $v_s v_{i,1} \dots v_{i,k-2} v_{i,k-1} v_j^c$ is a temporal path of duration k in (G, λ') , and so $\text{ecc}^{\text{Fa}}((G, \lambda'), v_s) = k$ and so $((G, \lambda), v_s, k, \delta, m)$ is a yes-instance to TFaEP.

Next, assume that $((G, \lambda), v_s, k, \delta, m)$ is a yes-instance to TFaEP, and let λ' be the associating perturbation that achieves $\operatorname{ecc}^{\operatorname{Fa}}((G, \lambda'), v_s) \leq k$. Construct a ϕ mapping variables to $\{\top, \bot\}$ as follows. If $\lambda'(v_{i,k-2}v_{i,k-1}) = k - 1 + \delta$ let $\phi(x_i) = \top$, else let $\phi(x_i) = \top$. Now take an arbitrary clause C_j , and associated vertex v_j^c . There is a temporal path of duration k in (G, λ') from v_s to v_j^c , as we have a yes-instance to TFaEP. By construction, such a path must use an edge of the form $v_{i,k-2}v_{i,k-1}$ for some i corresponding to a variable i. If $\lambda'(v_{i,k-2}v_{i,k-1}) = k - 1 + \delta$ then $\phi(x_i) = \top$ and the edge $v_{i,k-1}v_j^c$ must be used at time $k + \delta$, and so by construction (and as λ' is a δ -perturbation) it must be that x_i appears non-negated in C_j , and so C_j is satisfied. Alternatively, $\lambda'(v_{i,k-2}v_{i,k-1}) < k - 1 + \delta$ and $\phi(x_i) = \bot$, meaning we must have $\lambda'(v_{i,k-1}v_j^c) < k + \delta$, and so by construction (and as λ' is a δ -perturbation) it must be that x_i appears negated in C_j , and so C_j is satisfied. Alternatively, $\lambda'(v_{i,k-2}v_{i,k-1}) < k - 1 + \delta$ and $\phi(x_i) = \bot$, meaning we must have $\lambda'(v_{i,k-1}v_j^c) < k + \delta$, and so by construction (and as λ' is a δ -perturbation) it must be that x_i appears negated in C_j , and so C_j is satisfied. As we chose C_j arbitrarily, it follows that $\Lambda_j C_j$ is satisfied by ϕ , and so is a yes-instance to SAT.

We conclude this section with one positive result for TSEP and TFaEP. Recall that TRLP becomes trivial when both ζ and δ are sufficiently large (every instance is a yes-instance). While neither TSEP nor TFaEP becomes trivial under the same conditions, we now show that both problems can be solved in polynomial time when both ζ and δ are large.

Our algorithms make use of ubiquitous foremost temporal path trees. Recall that a ubiquitous foremost temporal path is a foremost temporal path P such that all prefixes of Pare themselves foremost temporal paths, and that a ubiquitous foremost temporal path tree from a source vertex v_s is a temporal graph (G_T, λ_T) such that G_T is a tree, $\tau(G_T, \lambda_T) = 1$ and for any $v_t \in V(G)$, a foremost temporal path in (G_T, λ_T) from v_s to v_t arrives at v_t no later than any temporal path. Our algorithms further rely on the following observation: for any edge e, the possible set of times it can be perturbed to includes the range $\{1, \ldots, r_e\}$ for some suitably large integer r_e , which means that along any sequence of (non-temporal) edges (e_1, e_2, \ldots) that can form a temporal path under some suitable perturbation, we can assume

that $\lambda(e_i) = i$. We write $d_G(v_1, v_2)$ for the number of edges in the shortest path between v_1 and v_2 in G.

▶ **Theorem 5.3.** Each of TSEP and TFaEP can be solved in time $O(m(\log n + \log \delta \tau(G, \lambda)))$ on instances $((G, \lambda), v_s, k, \delta, \zeta)$ if $\delta \ge T(G, \lambda)$ and $\zeta \ge n - 1$.

Proof. Define λ' by $\lambda'(e) = \{\lambda(e) + p \mid p \in [-\delta, \delta]\}$ for $e \in E(G)$, noting that as $\delta \geq T(G, \lambda)$, for each $e \in E(G)$ there is some positive integer r_e such that $\lambda'(e) = \{1, 2, \ldots, r_e\}$. Then use Theorem 1.1 to calculate a ubiquitous foremost temporal path tree (G_T, λ_T) on v_s in the temporal graph (G, λ') . in $O(m(\log n + \log \tau(G, \lambda'))) = O(m(\log n + \log \delta \tau(G, \lambda)))$ time. By setting $\lambda''(e) = \lambda_T(e)$ for $e \in E(G_T)$ and $\lambda''(e) = \lambda(e)$ for $e \notin E(G_T)$, we know that λ'' is a (δ, ζ) -perturbation of λ with the property that if a temporal path exists in (G_T, λ_T) , then the same path must also exist in (G, λ'') . Note that while $V(G_T) \subseteq V(G)$, it is possible that $V(G) \neq V(G_T)$: in this case the instance of either TSEP or TFaEP is a no-instance, so we assume from now on that $V(G_T) = V(G)$. We claim that for each goal vertex $v_g \in V(G)$, the unique temporal path from v_s to v_g in (G_T, λ_T) arrives at time $d_{G_T}(v_s, v_g)$, where $d_{G_T}(v_s, v_g)$ is the distance from v_s to v_g in the graph G_T .

We show this by induction on $d_{G_T}(v_s, v_g)$. If $d_{G_T}(v_s, v_g) = 1$, then $v_s v_g \in E(G_T)$, and as $1 \in \lambda'(v_s v_g)$, there is a foremost path from v_s to v_g that arrives at time 1. By definition of a ubiquitous foremost temporal path tree, the unique temporal path from v_s to v_g must therefore arrive at time 1, completing the base case for the induction.

We next proceed by induction. Let $d_{G_T}(v_s, v_g) = d > 1$, and let v_1 be a vertex such that $v_1v_g \in E(G_T)$ and $d_{G_T}(v_s, v_1) = d - 1$. Such a vertex v_1 must exist, else there can be no path of length d from v_s to v_g in G_T . By induction, the unique temporal path from v_s to v_1 in (G_T, λ_T) arrives at time d - 1. Additionally, there is a temporal path from v_s to v_g in (G_T, λ_T) (else we would have $v_g \notin V(G_T)$). Let d' be the arrival time of the unique foremost temporal path in (G_T, λ_T) from v_s to v_g . As $\lambda'(v_1v_g) = \{1, 2, \ldots, r_e\}$ for some positive integer r_e , if d' > d then $d' \in \{1, 2, \ldots, r_e\}$ and so we must have $d \in \{1, 2, \ldots, r_e\}$ as both are positive integers. But then the edge v_1v_g could be used at time d instead, breaking our assumption. Therefore the unique temporal path from v_s to v_g in (G_T, λ_T) arrives at time d.

Noting that, as (G_T, λ_T) is a ubiquitous foremost temporal path tree, no temporal path in any (δ, ζ) -perturbation of λ can arrive earlier than $d_{G_T}(v_s, v_g)$, we can also deduce that no temporal path in any (δ, ζ) -perturbation could be shorter than $d_{G_T}(v_s, v_g)$ (else it could arrive earlier than $d_{G_T}(v_s, v_g)$) and no temporal path in any (δ, ζ) -perturbation can have a lower duration (by the same argument). It therefore remains to check that either $\operatorname{ecc}^{\mathrm{S}}((G_T, \lambda_T), v_s) \leq k$ (if we are considering TSEP) or $\operatorname{ecc}^{\mathrm{Fa}}((G_T, \lambda_T), v_s) \leq k$ (if we are considering TFaEP). As (G_T, λ_T) is a ubiquitous foremost temporal path tree, each of those can be checked in O(n) time.

6 Conclusion and Open Questions

Motivated by the uncertainty and errors intrinsic in recording real-world temporal graphs, we have investigated temporal graph reachability problems under perturbation, in particular asking whether there exists a perturbation of time-edges of a temporal graph that results in a minimum required reachability. We find that when many perturbations are allowed, this can be resolved efficiently, but that the problem is, in general, NP-hard and W[2]-hard with respect to ζ . Furthermore, under the assumption of ETH, we show that there is no $f(\zeta)n^{o(\zeta)}$ -time algorithm for our problem. We have tractability results when the underlying

graph is a tree or when it has bounded treewidth and the lifetime and size of permitted perturbations are also bounded by constants. For contrast, we show that allowing many perturbations is not sufficient to give tractability of related eccentricity problems, where the question is not just whether there is some source vertex that reaches some specified number of vertices, but whether it reaches vertices within some travel duration (fastest) or in few steps (shortest).

An obvious avenue for further research is on other temporal graph problems with the same style of perturbations. However, inspired by the motivation to make temporal algorithms more suitable for real-world temporal contact data, we suggest exploring temporal graph modification problems that are robust to perturbations: for example, removing (by, e.g. vaccination) vertices from a temporal network to limit reachability in a way that has guarantees under possible bounds of perturbation.

— References -

- 1 Brenda Baker and Robert Shostak. Gossips and telephones. Discrete Mathematics, 2(3):191-193, June 1972. URL: https://www.sciencedirect.com/science/article/pii/ 0012365X72900015, doi:10.1016/0012-365X(72)90001-5.
- 2 Surender Baswana, Keerti Choudhary, and Liam Roditty. Fault tolerant subgraph for single source reachability: generic and optimal. In *Proceedings of the forty-eighth annual ACM symposium on Theory of Computing*, STOC '16, pages 509–518, New York, NY, USA, June 2016. Association for Computing Machinery. URL: https://dl.acm.org/doi/10.1145/2897518.2897648, doi:10.1145/2897518.2897648.
- 3 Davide Bilò, Gianlorenzo D'Angelo, Luciano Gualà, Stefano Leucci, and Mirko Rossi. Blackout-Tolerant Temporal Spanners. In Thomas Erlebach and Michael Segal, editors, *Algorithmics of Wireless Networks*, Lecture Notes in Computer Science, pages 31–44, Cham, 2022. Springer International Publishing. doi:10.1007/978-3-031-22050-0_3.
- 4 Hans L. Bodlaender. A Linear-Time Algorithm for Finding Tree-Decompositions of Small Treewidth. SIAM Journal on Computing, 25(6):1305–1317, December 1996. Publisher: Society for Industrial and Applied Mathematics. URL: https://epubs.siam.org/doi/10. 1137/S0097539793251219, doi:10.1137/S0097539793251219.
- 5 Binh-Minh Bui-Xuan, Afonso Ferreira, and Aubin Jarry. Computing shortest, fastest, and foremost journeys in dynamic networks. *International Journal of Foundations of Computer Science*, 14(02):267–285, April 2003. doi:10.1142/s0129054103001728.
- 6 Arnaud Casteigts. A Journey through Dynamic Networks (with Excursions). thesis, Université de Bordeaux, June 2018. URL: https://hal.science/tel-01883384.
- 7 Arnaud Casteigts, Swan Dubois, Franck Petit, and John M. Robson. Robustness: A new form of heredity motivated by dynamic networks. *Theoretical Computer Science*, 806:429–445, February 2020. URL: https://www.sciencedirect.com/science/article/pii/S0304397519304979, doi:10.1016/j.tcs.2019.08.008.
- 8 GL Chaters, PCD Johnson, Sarah Cleaveland, Joseph Crispell, WA De Glanville, Thomas Doherty, Louise Matthews, Sibylle Mohr, OM Nyasebwa, Gianluigi Rossi, et al. Analysing livestock network data for infectious disease control: an argument for routine data collection in emerging economies. *Philosophical Transactions of the Royal Society B*, 374(1776):20180264, 2019.
- 9 Marek Cygan, Fedor V. Fomin, Łukasz Kowalik, Daniel Lokshtanov, Dániel Marx, Marcin Pilipczuk, Michał Pilipczuk, and Saket Saurabh. *Parameterized Algorithms*. Springer International Publishing, Cham, 2015. URL: http://link.springer.com/10.1007/978-3-319-21275-3, doi:10.1007/978-3-319-21275-3.
- 10 Argyrios Deligkas, Michelle Döring, Eduard Eiben, Tiger-Lily Goldsmith, and George Skretas. Being an Influencer is Hard: The Complexity of Influence Maximization in Temporal Graphs

with a Fixed Source, March 2023. arXiv:2303.11703 [cs]. URL: http://arxiv.org/abs/2303. 11703.

- 11 Argyrios Deligkas, Eduard Eiben, and George Skretas. Minimizing reachability times on temporal graphs via shifting labels. In *Proceedings of the Thirty-Second International Joint Conference on Artificial Intelligence*, IJCAI '23, pages 5333–5340, August 2023. doi:10.24963/ ijcai.2023/592.
- 12 Argyrios Deligkas and Igor Potapov. Optimizing reachability sets in temporal graphs by delaying. Information and Computation, 285:104890, May 2022. URL: https://www.sciencedirect. com/science/article/pii/S0890540122000323, doi:10.1016/j.ic.2022.104890.
- 13 Michael Dinitz and Robert Krauthgamer. Fault-tolerant spanners: better and simpler. In Proceedings of the 30th annual ACM SIGACT-SIGOPS symposium on Principles of distributed computing, PODC '11, pages 169–178, New York, NY, USA, June 2011. Association for Computing Machinery. URL: https://dl.acm.org/doi/10.1145/1993806.1993830, doi:10. 1145/1993806.1993830.
- 14 Swan Dubois, Laurent Feuilloley, Franck Petit, and Mikaël Rabie. When Should You Wait Before Updating? - Toward a Robustness Refinement. In David Doty and Paul Spirakis, editors, 2nd Symposium on Algorithmic Foundations of Dynamic Networks (SAND 2023), volume 257 of Leibniz International Proceedings in Informatics (LIPIcs), pages 7:1-7:15, Dagstuhl, Germany, 2023. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. ISSN: 1868-8969. URL: https: //drops.dagstuhl.de/opus/volltexte/2023/17943, doi:10.4230/LIPIcs.SAND.2023.7.
- 15 Krzysztof Dudziński and Stanisław Walukiewicz. Exact methods for the knapsack problem and its generalizations. European Journal of Operational Research, 28(1):3-21, January 1987. URL: https://www.sciencedirect.com/science/article/pii/0377221787901652, doi:10. 1016/0377-2217(87)90165-2.
- 16 Jessica Enright, Kitty Meeks, George B. Mertzios, and Viktor Zamaraev. Deleting edges to restrict the size of an epidemic in temporal networks. *Journal of Computer and System Sciences*, 119:60-77, August 2021. URL: https://www.sciencedirect.com/science/article/pii/ S0022000021000155, doi:10.1016/j.jcss.2021.01.007.
- 17 Jessica Enright, Kitty Meeks, and Fiona Skerman. Assigning times to minimise reachability in temporal graphs. *Journal of Computer and System Sciences*, 115:169–186, February 2021. URL: https://www.sciencedirect.com/science/article/pii/S0022000020300799, doi:10.1016/j.jcss.2020.08.001.
- 18 Thomas Erlebach, Murilo Santos de Lima, Nicole Megow, and Jens Schlöter. Learning-Augmented Query Policies for Minimum Spanning Tree with Uncertainty. In Shiri Chechik, Gonzalo Navarro, Eva Rotenberg, and Grzegorz Herman, editors, 30th Annual European Symposium on Algorithms (ESA 2022), volume 244 of Leibniz International Proceedings in Informatics (LIPIcs), pages 49:1-49:18, Dagstuhl, Germany, 2022. Schloss Dagstuhl Leibniz-Zentrum für Informatik. ISSN: 1868-8969. URL: https://drops.dagstuhl.de/opus/volltexte/2022/16987, doi:10.4230/LIPIcs.ESA.2022.49.
- 19 Thomas Erlebach and Michael Hoffmann. Minimum Spanning Tree Verification Under Uncertainty. In Dieter Kratsch and Ioan Todinca, editors, Graph-Theoretic Concepts in Computer Science, Lecture Notes in Computer Science, pages 164–175, Cham, 2014. Springer International Publishing. doi:10.1007/978-3-319-12340-0_14.
- 20 Thomas Erlebach, Michael Hoffmann, and Murilo Santos de Lima. Round-Competitive Algorithms for Uncertainty Problems with Parallel Queries. *Algorithmica*, September 2022. doi:10.1007/s00453-022-01035-6.
- 21 Thomas Erlebach, Michael Hoffmann, Danny Krizanc, Matús Mihal'ák, and Rajeev Raman. Computing Minimum Spanning Trees with Uncertainty, February 2008. arXiv:0802.2855 [cs]. URL: http://arxiv.org/abs/0802.2855, doi:10.48550/arXiv.0802.2855.
- 22 Helen R Fielding, Trevelyan J McKinley, Matthew J Silk, Richard J Delahay, and Robbie A McDonald. Contact chains of cattle farms in great britain. *Royal Society Open Science*, 6(2):180719, 2019.

- 23 Eugen Füchsle, Hendrik Molter, Rolf Niedermeier, and Malte Renken. Delay-Robust Routes in Temporal Graphs, January 2022. arXiv:2201.05390 [cs]. URL: http://arxiv.org/abs/2201. 05390.
- 24 Samuel D. Hand, Jessica Enright, and Kitty Meeks. Making Life More Confusing for Firefighters, May 2022. Conference Name: 11th International Conference on Fun with Algorithms (FUN 2022) ISBN: 9783959772327 ISSN: 1868-8969 Meeting Name: 11th International Conference on Fun with Algorithms (FUN 2022) Place: Sicily, Italy. URL: https://eprints.gla.ac.uk/ 269008/.
- **25** Petter Holme. Network reachability of real-world contact sequences. *Physical Review E*, 71(4):046119, 2005.
- 26 David Kempe, Jon Kleinberg, and Amit Kumar. Connectivity and inference problems for temporal networks. *Journal of Computer and System Sciences*, 64(4):820–842, June 2002. doi:10.1006/jcss.2002.1829.
- 27 David C. Kutner and Laura Larios-Jones. Temporal Reachability Dominating Sets: Contagion in Temporal Graphs. In Konstantinos Georgiou and Evangelos Kranakis, editors, *Algorithmics* of Wireless Networks, Lecture Notes in Computer Science, pages 101–116, Cham, 2023. Springer Nature Switzerland. doi:10.1007/978-3-031-48882-5_8.
- 28 William Lochet, Daniel Lokshtanov, Pranabendu Misra, Saket Saurabh, Roohani Sharma, and Meirav Zehavi. Fault Tolerant Subgraphs with Applications in Kernelization. In Thomas Vidick, editor, 11th Innovations in Theoretical Computer Science Conference (ITCS 2020), volume 151 of Leibniz International Proceedings in Informatics (LIPIcs), pages 47:1–47:22, Dagstuhl, Germany, 2020. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik. ISSN: 1868-8969. URL: https://drops.dagstuhl.de/opus/volltexte/2020/11732, doi:10.4230/LIPIcs.ITCS.2020.47.
- George B. Mertzios, Othon Michail, and Paul G. Spirakis. Temporal Network Optimization Subject to Connectivity Constraints. *Algorithmica*, 81(4):1416–1449, April 2019. doi:10. 1007/s00453-018-0478-6.
- 30 Hendrik Molter, Malte Renken, and Philipp Zschoche. Temporal Reachability Minimization: Delaying vs. Deleting. In Filippo Bonchi and Simon J. Puglisi, editors, 46th International Symposium on Mathematical Foundations of Computer Science (MFCS 2021), volume 202 of Leibniz International Proceedings in Informatics (LIPIcs), pages 76:1–76:15, Dagstuhl, Germany, 2021. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. ISSN: 1868-8969. URL: https: //drops.dagstuhl.de/opus/volltexte/2021/14516, doi:10.4230/LIPIcs.MFCS.2021.76.
- 31 Ashleigh Myall, Robert L Peach, Yu Wan, Siddharth Mookerjee, Elita Jauneikaite, Frankie Bolt, James Price, Frances Davies, Andrea Y Weiße, Alison Holmes, et al. Characterising contact in disease outbreaks via a network model of spatial-temporal proximity. *medRxiv*, pages 2021–04, 2021.
- 32 Ran Raz and Shmuel Safra. A sub-constant error-probability low-degree test, and a subconstant error-probability pcp characterization of np. In *Proceedings of the Twenty-Ninth Annual ACM Symposium on Theory of Computing*, STOC '97, page 475–484, New York, NY, USA, 1997. Association for Computing Machinery. doi:10.1145/258533.258641.
- 33 Steven S. Skiena. The Algorithm Design Manual. Springer Publishing Company, Incorporated, 2nd edition, 2008.
- Huanhuan Wu, James Cheng, Silu Huang, Yiping Ke, Yi Lu, and Yanyan Xu. Path problems in temporal graphs. *Proc. VLDB Endow.*, 7(9):721–732, may 2014. doi:10.14778/2732939.
 2732945.