Can 3GPP New Radio Non-Terrestrial Networks Meet the IMT-2020 Requirements for Satellite Radio Interface Technology?

Mikko Majamaa*[†], Lauri Sormunen*, Verneri Rönty*, Henrik Martikainen*, Jani Puttonen*, and Timo Hämäläinen[†]

*Magister Solutions, Jyväskylä, Finland

email: {mikko.majamaa, lauri.sormunen, verneri.ronty, henrik.martikainen, jani.puttonen}@magister.fi

[†]Faculty of Information Technology, University of Jyväskylä, Finland

email: timo.t.hamalainen@jyu.fi

Abstract—The International Telecommunication Union defined the requirements for 5G in the International Mobile Telecommunications 2020 (IMT-2020) standard in 2017. Since then, advances in technology and standardization have made the ubiquitous deployment of 5G via satellite a practical possibility, for example, in locations where terrestrial networks (TNs) are not available. However, it may be difficult for satellite networks to achieve the same performance as TNs. To address this, the IMT-2020 requirements for satellite radio interface technology have recently been established. In this paper, these requirements are evaluated through system simulations for the 3rd Generation Partnership Project New Radio non-terrestrial networks with a low Earth orbit satellite. The focus is on the throughput, area traffic capacity, and spectral efficiency requirements. It is observed that the downlink (DL) requirements can be met for user equipment with 2 receive antenna elements. The results also reveal that frequency reuse factor 1 (FRF1) may outperform FRF3 in DL with a dual-antenna setup, which is a surprising finding since FRF3 is typically considered to outperform FRF1 due to better interference reduction. For uplink (UL), 1 transmit antenna is sufficient to meet the requirements by a relatively large margin - a promising result given that UL is generally more demanding. Keywords—5G, 6G, beyond 5G, low Earth orbit (LEO) satellite,

satellite network simulator

I. INTRODUCTION

The International Mobile Telecommunications 2020 (IMT-2020) standard [1], published by the International Telecommunication Union (ITU), defines the requirements for 5G networks, devices, and services. The standard covers ultrareliable low latency communications (URLLC), enhanced mobile broadband (eMBB), and massive machine-type communications (mMTC) usage scenarios.

Because terrestrial networks (TNs) are not available everywhere, satellite communications can be used to provide connectivity to areas where it would otherwise be impossible, costly, or hazardous. In addition, a satellite component can be used for load balancing or in the event of crises when TNs are out of service. However, as identified by ITU, the requirements set for 5G will need to be adapted for satellite radio interface technology, taking into account characteristics such as higher latency and possibly lower bandwidth. Therefore, ITU has defined requirements for satellite radio interfaces of IMT-2020 in ITU-R M.2514-0 [2]. These requirements include high reliability communications via satellite (HRC-s), enhanced mobile broadband via satellite (eMBB-s), and massive machine-type communications via satellite (mMTC-s) usage scenarios. Requirements for HRC-s, eMBB-s, and mMTC-s [2, Table 8.2.6.3] are less stringent than their terrestrial counterparts [3, Table II]. The 5G use cases for terrestrial/satellite components are illustrated in Fig. 1.



Fig. 1: 5G use cases. Adapted from [2].

The 3rd Generation Partnership Project (3GPP) [4] is an umbrella term for several standardization organizations that provide specifications for mobile communications. The work in 3GPP is organized in releases with cycles of about 18 months. Releases 15 through 17 focused on 5G, while the ongoing Release 18 (Rel-18) marks the beginning of 5G-Advanced (5G-A). Rel-17 was historic because it included satellite communications, or non-terrestrial networks (NTNs) in 3GPP nomenclature, in the 3GPP specifications for the

This work has been submitted to the IEEE for possible publication. Copyright may be transferred without notice, after which this version may no longer be accessible.

This work has been funded by the European Space Agency project HELENA (Highly skillEd sateLlite community mEmbers to drive 3GPP Non-Terrestrial Network stAndardization) - Support to Standardisation of Satellite 5G Component under program ARTES 4.0 Core Competitiveness Generic Programme Line – Future Preparation. The views expressed are those of the authors and can in no way be taken to reflect the official opinion of the European Space Agency.

first time, although, Rel-15 and Rel-16 included necessary preparatory work in the form of technical reports (TRs) and study items [5], [6]. The significance of the standardization efforts lies in cooperation – it is expected that TNs and NTNs will become a unified network [7]. From the user's point of view, this means an indistinguishable network, that is, the user could be connected to a network without noticing whether it is via a terrestrial or a satellite access point.

The NTN work in 3GPP covers low Earth orbit (LEO), medium Earth orbit (MEO), and geosynchronous orbit (GEO) satellite communications but also airborne vehicles such as high-altitude platform stations (HAPSs). Rel-17 included support for the basic functionality of New Radio (NR), the air interface of 5G, through satellites in S- and L-bands serving handheld terminals. Rel-18 extends NR capabilities through NTNs, for example, by considering higher frequencies, mobility enhancements, and support for very small aperture terminals (VSATs) [8].

In the past, several works have considered the performance of NTNs. In [9], the authors evaluate the capacity and throughput of NTN with LEO satellites. The throughput performance of NTN with GEO satellite is considered in [10]. The handover performance in LEO NTN is considered in [11]. In [12], the authors evaluate the performance of mMTC over a LEO satellite. Although evaluations of NTNs have been done in the past, to the best of the authors' knowledge no published work comprehensively evaluates 3GPP NR NTNs against the IMT-2020 requirements for satellite radio interface technology. It is therefore important to study whether the requirements can be met by 3GPP NR NTNs, which is critical to ensure the deliverability of anticipated services and to provide strategic adaptation in cases where these networks fail to meet the requirements.

This paper aims to fill the identified research gap by providing an evaluation of NR over NTN in relation to the ITU's requirements, focusing on the throughput, spectral efficiency, and area traffic capacity requirements in non-mobile eMBB-s scenarios. For the other requirements, the reader is referred to the results of the other partners in the research project, which indeed suggest that 3GPP NR NTNs can meet the ITU's requirements [13].

The remainder of the paper is organized as follows. In the next section, the IMT-2020 requirements for satellite radio interface technology are outlined. In Section III, the requirements are evaluated through system-level simulations. Section IV concludes the paper.

II. IMT-2020 REQUIREMENTS FOR SATELLITE RADIO INTERFACE TECHNOLOGY

Table I. outlines the minimum technical requirements for the 5G satellite radio interface set as defined by ITU. It also lists the evaluation methods, which include analysis, simulation, and inspection, depending on the requirement. Where applicable, the usage scenario, test environment, and link direction are listed. The last column shows which of the requirements are

considered in this paper. The focus is on non-mobile eMBBs throughput, spectral efficiency, and area traffic capacity statistics.

III. EVALUATION OF THE REQUIREMENTS

A. System Model

This section details the system model for evaluating the eMBB-s requirements in non-mobile cases through systemlevel simulations. The evaluation parameters are given in Table II. It should be noted that these parameters can be found in ITU-R M.2514-0 but also that these parameters are aligned with the calibration parameters found in TR 38.821.

The system considered consists of a single LEO satellite with 19 statistics beams, that is, beams from which statistics are collected. Two different frequency reuse factors (FRFs) are considered, namely, FRF1 and FRF3. With FRF1, the frequency is fully reused by the beams. With FRF3, each beam uses only one-third of the total frequency and adjacent beams use different portions of the frequency to minimize inter-cell interference. In addition to the statistics beams, wraparound beams are used to introduce a realistic level of background interference into the system. Two tiers of wraparound beams are used for FRF1 and four tiers for FRF3. FRF3 requires more tiers of wraparound beams because the interfering beams are further away due to the frequency reuse scheme. The different frequency reuse schemes are illustrated in Fig. 2.



Fig. 2: Different frequency reuse schemes illustrated [6].

Different antenna configurations are considered for users. In the (m,n,p) antenna configuration notation, m and n are the number of receive (Rx) antenna elements in the vertical and horizontal directions, respectively, and p is the number of polarizations used. As described in ITU-R M.2514-0, (1,1,2) and (1,2,2) configurations are considered. The two Rx antenna polarizations are assumed to revoke the depolarization loss of 3 dB caused by the mismatch between the satellite's transmit (Tx) antenna's single circular polarized elements. Additionally, given the different number of UE's horizontal Rx antenna components (1 or 2), the overall received signal-to-interference-plus-noise ratio (SINR) is the maximum ratio combining (MRC) version of the signal, that is, the average

Minimum technical	High-level assessment	Category			Required	Included
requirement item	method	Usage Test downlink (downlink (DL) or	DL) or value	
		scenario	environment	uplink (UL)		study
Peak data rate	Analytical	eMBB-s	N/A	UL	2 Mbit/s	
				DL	70 Mbit/s	
Peak spectral	Analytical	eMBB-s	N/A	UL	1.5 bit/s/Hz	
efficiency	7 mary trout	CIVIDD 5		DL	3 bit/s/Hz	
User experienced	Simulation and analytical	eMBB-s	Rural	UL	100 kbit/s	\checkmark
data rate	Simulation and analytical			DL	1 Mbit/s	\checkmark
5th percentile user	Simulation	eMBB-s	Rural	UL	0.003 bit/s/Hz	\checkmark
spectral efficiency	Sinuation			DL	0.03 bit/s/Hz	\checkmark
Average spectral	Simulation	eMBB-s	Rural	UL	0.1 bit/s/Hz	\checkmark
efficiency	Sinuation	ewibb-s		DL	0.5 bit/s/Hz	\checkmark
Area traffic capacity	Simulation and analytical	eMBB-s	Rural	UL	1.5 kbit/s/km ²	\checkmark
				DL	8 kbit/s/km ²	\checkmark
User Plane latency	Analytical and inspection	eMBB-s	N/A	N/A	10 ms	
Control Plane latency	Analytical and inspection	eMBB-s	N/A	N/A	40 ms	
Connection density	Simulation	mMTC-s	Rural	N/A	500 devices/km ²	
Energy officiency	Inspection	eMBB-s	N/A	N/A	High sleep ratio and	
Energy enrelency					long sleep duration	
Reliability	Simulation	HRC-s	Rural	N/A	0.999	
Mobility – UE speed	Simulation	eMBB-s	Rural	N/A	250 km/h	
Mobility – Traffic channel	Simulation	eMBB-s	Rural	N/A	0.005 hit/c/Uz	
link data rate	Simulation				0.005 DIVS/HZ	
Mobility interruption time	Analytical	eMBB-s	N/A	N/A	50 ms	
Dondwidth	Increation	N/A	N/A	NT/A	At least up to and	
Balluwiduli	Inspection			11/24	including 30 MHz	

TABLE I: Minimum technical requirements of the 5G satellite radio interface set by ITU.

SINR of the antenna elements multiplied by the number of them. The signal combination model for multiple Rx antennas is an idealized one, assuming that the neighboring beam interference is noise-like and does not combine at the receiver.

In the UL direction, the users have a single Tx antenna but two different configurations are considered. These are Configuration A and Configuration B, as described in Section 6.1.1.1 of TR 38.821. With Configuration A, similarly to the DL direction, a 3 dB depolarization loss is considered. Configuration A assumes polarization reuse on the satellite side, that is, each beam uses either right-hand circular polarization (RHCP) or left-hand circular polarization (LHCP). With Configuration B, the polarization mismatch loss is revoked by the use of two polarizations (RHCP and LHCP) per beam on the satellite side.

10 UEs are connected to each of the beams, each with full buffer traffic. The UEs considered are handheld devices and are served in S-band.

B. Simulations

The evaluations are performed using a 5G NTN simulator also known as the ALIX simulator [15]. The ALIX simulator is a packet-level system simulator. It is based on network simulator 3 (ns-3) [16] and its 5G LENA module [17], which can be used to simulate terrestrial 5G networks. As part of several research projects, multiple components have been developed on top of ns-3 and 5G LENA in the ALIX simulator to enable the simulation of NTNs. The TR 38.811 channel and beam modeling has been implemented in the simulator and the simulator has been calibrated using the TR 38.821 calibration scenarios. Each different simulation configuration is run five times with unique random number generator (RNG) seeds, resulting in variations such as differing UE positions. The results for the distribution statistics are combined, while the scalar statistics are averaged. For convenience, the simulation results are summarized in Table III where the cases that do not meet the requirements are marked with 'X'. The results capture the effect of using different UE antenna configurations and frequency reuse schemes. In DL, the (1,1,2) and (1,2,2) configurations correspond to 1 and 2 UE antennas, respectively.

Fig. 3. captures the throughput statistics per UE for a) DL and b) UL. According to the requirements of ITU-R M.2514-0, the required user-experienced throughput refers to the 5th percentile throughput. This means that the focus is on the lower end of the throughput measurements to ensure that even the users with the poorest performance receive an acceptable service. Meanwhile, the throughput distributions are constructed from the user spectral efficiency statistics by

$$R_{\text{user}} = W \cdot SE_{\text{user}}$$

where W is the bandwidth and SE_{user} is the UE spectral efficiency.

It is observed that with both frequency reuse schemes, the requirement (1 Mbit/s) cannot be met in DL with 1 Rx antenna. However, by increasing the number of UE antennas to 2, the requirements are met. In UL, the requirement (100 kbit/s) is met with both frequency reuse schemes and with both Configuration A and Configuration B.

The area traffic capacity is defined as

$$C = \rho \cdot W \cdot SE_{avg},$$

TABI	LE	II:	Eval	luation	parameters.
------	----	-----	------	---------	-------------

Technical configuration parameter	Reference value for NR NTN
Satellite orbit configuration	LEO, 600 km altitude
Beam deployment	Quasi-Earth-Fixed
Setellite results d	Transparent payload without
Satellite payload	inter-satellite links
Service link frequency	S-band (2 GHz)
Channel bandwidth	30 MHz
3 dB beam width	4.41°
Satellite EIRP density	34 dBW/MHz
Satellite antenna gain	30 dBi
Satellite G/T	1.1 dB/K
	Hexagonal pattern, 19 statistics
Spot beam pattern	beams + 2/4 tiers of interfering
	beams for FRF1/FRF3
Satellite beam diameter	50 km
Inter-cell distance	43.3 km
TRxP density (ρ)	1/1415 km ²
Terminal type	Handheld
UE Antenna type	Omni-directional
UE antenna polarisation	Linear: ±45°X-pol
UE Antenna gain	0 dB1
UE Antenna temperature	290 K
Noise figure	7 dB
UE Ix power	200 mW (23 dBm)
UE KX antenna configuration	(1,1,2) OF $(1,2,2)$
Device deployment	100% outdoor, randonny, and
LIE donaity	10 LIEs par spot beam
UE mobility model	Stationary
Traffic model	Full buffer
LIF antenna height	1.5 m
OE antenna height	Bessel function as in
Satellite antenna pattern	Section 6.4.1 in TR 38.811
Satellite antenna	
polarization configuration	Circular
Central beam elevation	90 degrees
FRF	1 or 3
Propagation conditions	Line-of-sight probability of 100%
	Large-scale model of
Large-scale channel model	Section 6.6 in TR 38.811
Small scale shannal model	Small-scale fading as in
Sman-scale channel model	Table 6.1.1.1-7 in TR 38.821
Handover margin	0 dB
UE attachment	Reference signal received
Satallita antanna configuration	1 Dy / 1 Ty per beem
Adaptive coding and modulation	Enabled
	Enabled
Scheduler	Proportional fair
Modulation and coding	
scheme index table	Table 3 [14]
RNG runs	5
	-
	1.0



Fig. 3: Throughput statistics per UE for a) DL and b) UL.

where ρ is the transmission point density, W is the system bandwidth, and SE_{avg} is the average spectral efficiency per cell. The area traffic capacity statistics are shown in Fig. 4. for a) DL and b) UL. The required capacity of 8 kbit/s/km² is only achieved with FRF3 in the DL direction when considering 1 UE Rx antenna. With 2 UE Rx antennas, both frequency reuse schemes meet the requirement. In UL, the requirement (1.5 kbit/s/km²) is met by a wide margin, with values more than twice the requirement for Configuration A and more than three times the requirement for Configuration B.

The average spectral efficiency statistics per cell are shown in Fig. 5. for a) DL and b) UL. Again, the UL requirement (0.1 b/s/Hz) is far exceeded. In DL, 2 UE Rx antennas are required to reach the requirement (0.5 b/s/Hz).



Fig. 4: Area traffic capacity statistics for a) DL and b) UL.



Fig. 5: Average spectral efficiency statistics per cell for a) DL and b) UL.

The spectral efficiency statistics per UE are shown in Fig. 6. for a) DL and b) UL. The requirement for DL is 0.03 b/s/Hz 5th percentile spectral efficiency, while the requirement for UL is 0.003 b/s/Hz 5th percentile spectral efficiency. For DL, 2 UE Rx antennas are required to meet the requirement regardless of the frequency reuse scheme while the UL requirements are met in all considered cases.

C. Effect of Scintillation

The results presented suggest that 1 Rx UE antenna is not capable of meeting the requirements. However, given the negligible impact of scintillation at mid-latitudes, simulation results with negligible scintillation paired with a single UE Rx antenna are presented below to determine if such a setup could meet the requirements.



Fig. 6: Spectral efficiency statistics per UE for a) DL and b) UL.

Scintillation, which causes rapid signal fluctuations, affects ionospheric propagation mainly below 6 GHz and occasionally up to 10 GHz, while it is most severe at frequencies below 3 GHz. Scintillation varies with location, time, season, and solar activity, being more pronounced post-sunset at low latitudes and at high latitudes. The following simulations consider regions such as the continental United States, Central Europe, and parts of East Asia, which typically fall within mid-latitude ranges where the effect of scintillation is negligible. The effect of scintillation is implemented in the simulator as described in Section 6.6.6 in TR 38.811.

Fig. 7 illustrates how scintillation affects throughput and spectral efficiency per UE. In the figure, the "Sc S" label corresponds to the significant scintillation case, and the "Sc N" label corresponds to the negligible scintillation case. The figure reveals that for FRF1, scintillation has little effect. For FRF3, there is a slight improvement in performance when scintillation is negligible. This is because, with FRF1, UEs experience interference as the primary limiting factor rather than noise. Scintillation, which acts as an additional fading component, affects both desired and interfering signals. Consequently, reducing scintillation does not significantly change the SINR because both signal and interference are affected proportionally by the scintillation loss, keeping the SINR at approximately the same level.

Conversely, for FRF3, where noise is more dominant than interference, the SINR is more sensitive to changes in scintillation. In these cases, the SINR is greater with negligible scintillation than the SINR with significant scintillation. Therefore, removing the fading effect of scintillation can result in a small performance improvement in such noise-sensitive scenarios. Fig. 8 supports this observation, showing that the area traffic capacity and the average spectral efficiency per cell follow the same pattern when scintillation effects are considered.

D. Result Summary

The results indicate that with a single Rx antenna, only the area traffic capacity requirement is achievable, both with significant and negligible scintillation and with FRF3. Even in scenarios with negligible scintillation, representative of midlatitude regions such as Central Europe, the requirements are not met with a single Rx antenna. This illustrates the



Fig. 7: a) Throughput and b) spectral efficiency statistics per UE for DL with 1 Rx antenna showing the effect of scintillation.



Fig. 8: a) Area traffic capacity and b) average spectral efficiency statistics per cell for DL with 1 Rx antenna showing the effect of scintillation.

potential challenge of meeting the requirements with a single Rx antenna.

When the number of Rx antennas is increased to two, all the considered requirements are met with both FRF1 and FRF3, with FRF1 showing higher overall performance than FRF3, which is a surprising finding, as FRF3 is typically considered to perform better than FRF1 due to better minimization of interference. This may be explained by the product of the improved spectral efficiency of the dual-antenna modulation and coding scheme and the full bandwidth for FRF1 being greater than the equivalent product for FRF3.

The implementation of additional Rx antennas may play a critical role in meeting the performance requirements. However, the combination gain in this study is an idealized version assuming interference from neighboring beams does not combine constructively at the receiver. The actual gain of the signal combination scheme is left for further study, although it is safe to assume that the use of antenna diversity improves the overall channel quality.

The UL requirements are consistently met even with Configuration A, which is a more challenging setup. This is particularly promising because it indicates that the requirements can be met even with polarization reuse. UL communications, which are generally more demanding, benefit from this observation. Due to the consistent compliance with UL requirements in all cases considered, results for UL with negligible scintillation are not detailed in the study. However, it is inferred

TABLE III: Simulation results. The cases that do not meet the requirements are marked with 'X'.

Link direction	Number of UE antennas	FRF	Scintillation		User experienced data rate [Mbit/s]	5th percentile spectral efficiency [bit/s/Hz]	Average spectral efficiency [bit/s/Hz]	Area traffic capacity [kbit/s/km ²]
DL	1	1	- Significant		0.62 🗶	0.021 X	0.36 X	7.6 X
		3			0.77 X	0.026 X	0.39 🗶	8.3
	2	1			1.20	0.040	0.64	13.6
		3			1.15	0.038	0.56	11.8
	1	1	Negligible		0.64 🗶	0.021 X	0.36 X	7.7 X
		3			0.81 🗶	0.027 X	0.41 X	8.6
				Required	1.0	0.03	0.5	8.0
UL, CFG A	1 -	1	- Significant		0.16	0.0052	0.16	3.4
		3			0.19	0.0064	0.18	3.8
UL, CFG B	1	1			0.23	0.0077	0.23	4.8
		3			0.32	0.011	0.26	5.4
UL				Required	0.1	0.003	0.1	1.5

that in such setups, UL could exceed the requirements by an even greater margin, further demonstrating the robustness of the system under varying conditions.

IV. CONCLUSION

In this paper, the IMT-2020 requirements for satellite radio interface technology were evaluated with a focus on the requirements for throughput, area traffic capacity, and spectral efficiency statistics in non-mobile eMBB-s scenarios. It was observed that the DL requirements can be met with 2 Rx antennas but not with 1 Rx antenna even when scintillation is negligible while the UL requirements can be met with a large margin with 1 Tx antenna with both Configuration A (beam polarization reuse) and B (no beam polarization reuse). Furthermore, the results indicate that FRF1 may outperform FRF3 in DL with a dual-antenna setup, which is a surprising finding since FRF3 is typically considered to outperform FRF1 due to better interference reduction.

A possible future work could be the analysis of the compliance of 3GPP NR NTNs with the other IMT-2020 requirements for satellite radio interface technology. In addition, it would be important to investigate whether the requirements could somehow be met with 1 Rx antenna, for example, by scheduling optimization, advanced antenna designs, new modulation schemes, or AI-driven network optimization. Furthermore, it was assumed that interference from neighboring beams does not constructively combine at the receiver, a topic that warrants further investigation in future work.

In conclusion, the research indicates that 3GPP NR NTNs comply with the ITU's requirements, supporting further standardization and deployment efforts. This development paves the way for seamless integration of terrestrial and nonterrestrial networks, aiding the transition to 6G and enabling global connectivity. It promises improved access in remote areas and supports multiple applications in broadband, emergency services, and IoT. However, it also highlights challenges in technology harmonization and equitable spectrum allocation, underscoring the need for collaborative solutions.

REFERENCES

- ITU-R, "IMT vision framework and overall objectives of the future development of IMT for 2020 and beyond," September 2015.
- [2] —, "Vision, requirements and evaluation guidelines for satellite radio interface(s) of IMT-2020," September 2022.
- [3] J. Navarro-Ortiz, P. Romero-Diaz, S. Sendra, P. Ameigeiras, J. J. Ramos-Munoz, and J. M. Lopez-Soler, "A survey on 5G usage scenarios and traffic models," *IEEE Communications Surveys & Tutorials*, vol. 22, no. 2, pp. 905–929, 2020.
- [4] "3GPP," Accessed on: Nov 14, 2023. [Online]. Available: https://www.3gpp.org/.
- [5] "TR 38.811: Study on new radio (NR) to support non-terrestrial networks," 3GPP, V15.4.0, Sept. 2020.
- [6] "TR 38.821: Solutions for NR to support non-terrestrial networks (NTN)," 3GPP, V16.0.0, Jan. 2020.
- [7] A. Guidotti *et al.*, "The path to 5G-Advanced and 6G non-terrestrial network systems," in 2022 11th Advanced Satellite Multimedia Systems Conference and the 17th Signal Processing for Space Communications Workshop (ASMS/SPSC), 2022, pp. 1–8.
- [8] X. Lin, "An overview of 5G advanced evolution in 3GPP Release 18," *IEEE Communications Standards Magazine*, vol. 6, no. 3, pp. 77–83, 2022.
- [9] J. Sedin, L. Feltrin, and X. Lin, "Throughput and capacity evaluation of 5G new radio non-terrestrial networks with LEO satellites," in *GLOBE-COM 2020 - 2020 IEEE Global Communications Conference*, 2020, pp. 1–6.
- [10] D. You, J. Kim, M. Y. Yun, M.-S. Lee, and J. Kang, "Performance evaluation of data transmission for non-terrestrial networks," in 2020 International Conference on Information and Communication Technology Convergence (ICTC), 2020, pp. 1073–1075.
- [11] J. Yu, W. Lee, and J.-H. Kim, "Performance evaluation of handover using A4 event in LEO satellites network," in 2022 IEEE VTS Asia Pacific Wireless Communications Symposium (APWCS), 2022, pp. 127–131.
- [12] J. Sedin et al., "5G massive machine type communication performance in non-terrestrial networks with LEO satellites," in 2021 IEEE Global Communications Conference (GLOBECOM), 2021, pp. 01–06.
- [13] 3GPP, "Self-evaluation results for NR NTN," 3GPP TSG RAN WG1 Meeting #115, Document R1-2310940, Chicago, USA, November 2023, agenda Item: 8.15.2. Source: Thales, Magister. Document for: Discussion and decision.
- [14] "TS 38.214: 5G; NR; physical layer procedures for data," 3GPP, V16.2.0, July 2020.
- [15] J. Puttonen, L. Sormunen, H. Martikainen, S. Rantanen, and J. Kurjenniemi, "A system simulator for 5G non-terrestrial network evaluations," 2021 IEEE 22nd International Symposium on a World of Wireless, Mobile and Multimedia Networks (WoWMoM), pp. 292–297, 2021.
- [16] G. F. Riley and T. R. Henderson, "The ns-3 network simulator," in Modeling and Tools for Network Simulation, K. Wehrle, M. Güneş, and J. Gross, Eds. Berlin, Heidelberg: Springer Berlin Heidelberg, 2010, pp. 15–34.
- [17] N. Patriciello, S. Lagén, B. Bojović, and L. Giupponi, "An E2E simulator for 5G NR networks," *Simulation Modelling Practice and Theory*, vol. 96, 2019.