

Local search for valued constraint satisfaction parameterized by treedepth

Artem Kaznatcheev

Department of Mathematics, and Department of Information and Computing Sciences, Utrecht University, Utrecht, The Netherlands

Abstract

Sometimes local search algorithms cannot efficiently find even local peaks. To understand why, I look at the structure of ascents in fitness landscapes from valued constraint satisfaction problems (VCSPs). Given a VCSP with a constraint graph of treedepth d , I prove that from any initial assignment there always exists an ascent of length $2^{d+1} \cdot n$ to a local peak. This means that short ascents always exist in fitness landscapes from constraint graphs of logarithmic treedepth, and thus also for all VCSPs of bounded treewidth. But this does not mean that local search algorithms will always find and follow such short ascents in sparse VCSPs. I show that with loglog treedepth, superpolynomial ascents exist; and for polylog treedepth, there are initial assignments from which all ascents are superpolynomial. Together, these results suggest that the study of sparse VCSPs can help us better understand the barriers to efficient local search.

2012 ACM Subject Classification Theory of computation → Constraint and logic programming

Keywords and phrases valued constraint satisfaction problem, local search, parameterized complexity, bounded treewidth, treedepth

1 Introduction

Kaznatcheev, Cohen and Jeavons [7] showed that no long adaptive paths exist in fitness landscapes corresponding to binary Boolean valued constraint satisfaction problems (VCSPs) with constraint graphs that are trees. However, they also showed that moving to three-valued VCSPs or increasing the constraint graph to treewidth 2, allows the existence of exponentially long adaptive paths. Cohen et al. [4] showed that not only do such long adaptive paths exist, but that for treewidth 7 constraint graphs, even reasonable local search dynamics like steepest ascent follow an exponential path to a local fitness peak. Kaznatcheev and van Marle [8] have recently reduced the parameter for long steepest ascents to just pathwidth 4.

The above results seem to stand in contrast to our knowledge of solving for the global optimum of VCSPs using non-local-search methods. In particular, the global optimum of a VCSPs with a bounded treewidth constraint graph can be found in polynomial time [1, 3]. In this paper, I want to address this discrepancy. In particular, I will show that in a fitness landscape corresponding to a bounded treewidth VCSP, there always exists a polynomial length ascent to some local optimum. I will do this by showing the stronger result that VCSPs with logarithmic treedepth always have a polynomial length ascent to a local optimum.

2 Background

A valued constraint satisfaction problem (VCSP) instance on n variables consists of n domains D_i and a finite set of valued constraints $\mathcal{C} = \{C_S\}$. If $|D_i| = 2$ for all $i \in [n]$ then we say that the VCSP is Boolean. Each valued constraint C_S with **scope** $S \subseteq [n]$ is a function $C_S : \prod_{i \in S} D_i \rightarrow \mathbb{Z}$. Each **assignment** $x \in D_1 \times \dots \times D_n$ has an associated **fitness** (or **value**) $f(x)$ given by $f(x) = \sum_{C_S \in \mathcal{C}} C_S(x[S])$ where $x[S]$ is the substring of assignment x with domain indexes in S . The **fitness landscape** from a VCSP instance is the above fitness function together with a notion of when two assignments are adjacent.

Two assignments x, y are **adjacent** if there exists a unique $k \in [n]$ such that $x_k \neq y_k$ and $x_i = y_i$ for all other $i \in [n] - \{k\}$. This unique k is the **step-index** between x and y . $N(x) \subseteq D_1 \times \dots \times D_n$ is the set of all assignments that are adjacent to x . A **step-sequence** $p = x^0, x^1, \dots, x^T$ is a sequence of $T + 1$ assignments such that $x^{t+1} \in N(x^t)$.

A **(local) solution** to a VCSP \mathcal{C} is an assignment x^* such that for all $y \in N(x^*)$ $f(x^*) \geq f(y)$. An **ascent** $p = x^0, x^1, \dots, x^T$ of length T in a VCSP \mathcal{C} is a step-sequence of $T + 1$ assignments such that $f(x^t) < f(x^{t+1})$ and x^T is a local solution to \mathcal{C} . An ascent p is **step-steepest** when for each t if k is the step-index between x^t and x^{t+1} and y is any string such that $y[[n] - \{k\}] = x[[n] - \{k\}]$ then $f(x^{t+1}) \geq f(y)$. In other words, if a step in p changes a variable x_k then it makes the most fitness-increasing change possible to that variable. Given a partial ordering \prec of $[n]$, a **\prec -ordered ascent** is an ascent $p = x^0, x^1, \dots, x^T$ with k^t as the step-index between x^t and x^{t+1} such that for all $j \prec k$ and $y \in N(x^t)$, if j is the step-index between x^t to y then $f(y) \leq f(x^t)$. In other words, each step in p flips a \prec -minimal index of those that are able to flip.

Given a VCSP \mathcal{C} , the corresponding **constraint graph** $G_{\mathcal{C}} = ([n], E)$ has $\{i, j\} \in E$ if and only if there exists some constraint $C_S \in \mathcal{C}$ such that $\{i, j\} \subseteq S$. Given a tree $T = ([n], P)$ rooted at r_0 , let \prec_T be the descendant relationship for T . In other words, $r \prec_T s$ if the path from r to r_0 in T passes through s and $r \neq s$. T is a **treedepth-decomposition** of $G_{\mathcal{C}}$ if for every $uv \in E$ either $u \prec_T v$ or $v \prec_T u$. The **treedepth** $\text{td}(G_{\mathcal{C}})$ is the minimal $\text{height}(T)$ over all treedepth-decompositions of $G_{\mathcal{C}}$. Treedepth is closely related to other sparsity metrics like treewidth [9]. In particular, graphs with bounded treewidth have at most logarithmic treedepth [2, 9].

3 Polynomial bound on ordered-ascent

With this terminology in place, I can state the main result:

► **Theorem 1.** *In a VCSP \mathcal{C} on n variables with domains of size $\leq v$ and constraint graph with treedepth-decomposition T , any \prec_T -ordered-ascent has length $v^{\text{height}(T)+1} \cdot n$ or less. If, in addition to the above, p is step-steepest then it has length $2^{\text{height}(T)+1} \cdot n$ or less.*

Define $\mathcal{C}(k) = \{c_S \mid i \in S \text{ and } c_S \in \mathcal{C}\}$ as the set of constraints that contain the variable k in their scope, and the scope-neighbourhood function $\text{NS}(k) = \cup_{c_S \in \mathcal{C}(k)} S$ as the union of these scopes. I will say that variable x_i is **smoothed-out** if we add a new constraint:

$$C_{\text{NS}(k) \setminus \{k\}}(y) = \max_{x_k} \sum_{c_S \in \mathcal{C}(k)} c_S(x_k, y[S]) \quad (1)$$

to the VCSP and remove variable x_k and all constraints in $\mathcal{C}(k)$ from the VCSP. I will use $\mathcal{C} \ominus k$ as the name of the new VCSP with x_k smoothed-out.

► **Lemma 2.** *Given a VCSP \mathcal{C} with treedepth-decomposition T , if k is a leaf in T then $T - \{k\}$ is a valid treedepth-decomposition for $\mathcal{C} \ominus k$.*

Proof. Consider a leaf in a treedepth-decomposition of depth $d + 1$. If we smooth that leaf, we will introduce a constraint of arity- d . This will not force us to redo the treedepth-decomposition because all d variables will be on the same path to the root. Since they are on the same path to the root, they are all already allowed to have edges in the treedepth decomposition. ◀

Given a step-sequence $p = x_0, x_1, \dots, x_T$ with assignment in $x_t \in \prod_{i=1}^n D_i$ define a step-sequence $p \ominus k$ by replacing each x_t by $x_t[[n] - \{k\}] \in \prod_{i \in [n] - \{k\}} D_i$ and for any x_t and x_{t+1} with step-index k , removing x_{t+1} from the sequence. In other words, $p \ominus k$ is the step-sequence that starts at $x_0[[n] - \{k\}]$ and follows all the same transitions as p but limited to variables with indexes in $[n] - \{k\}$. Note that $p \ominus k$ will be the same length or shorter than p because it will miss the transitions with step-index k . Specifically, $|p \ominus k| = |p| - |p|_k$ where $|p|_k$ is the number of transitions in p with step-index k .

► **Proposition 3.** *Given a VCSP \mathcal{C} with treedepth-decomposition T and a leaf k in T , if p is a \prec_T -ordered ascent in \mathcal{C} then:*

(1) $p \ominus k$ is a $\prec_{T - \{k\}}$ -ordered ascent in $\mathcal{C} \ominus k$,

(2) $|p|_k \leq (|D_k| - 1)(1 + \sum_{k \prec_T j} |p|_j)$.

If, in addition to the above, p is also step-steepest then:

(3) $p \ominus k$ is also step-steepest, and

(4) $|p|_k \leq 1 + \sum_{k \prec_T j} |p|_j$.

Proof. I show the consequences one at a time:

To show (1), I need to first show that $p \ominus k$ is an ascent. For this, let f be the fitness function for \mathcal{C} and f_{-k} be the fitness for $\mathcal{C} \ominus k$. Consider any two adjacent assignments x and y with step-index i .

1. If $i \notin \text{NS}(k)$ then $f(y) - f(x) = f_{-k}(y[[n] - \{k\}]) - f_{-k}(x[[n] - \{k\}])$ because on the left-hand side of the equation all occurrences of constraints from $\mathcal{C}(k)$ cancel since they have the same assignments to all variables in their scope, and similar for the right-hand side at the new smoothing constraint $C_{\text{NS}(k) \setminus \{k\}}$.
2. Now suppose that $i \in \text{NS}(k) - \{k\}$ and there is a t such that $x^t = x$ and $x^{t+1} = y$ in p and corresponding s such that $x^s = x[[n] - \{k\}]$ and $y^{s+1} = y[[n] - \{k\}]$ in $p \ominus k$ then $f_{-k}(x^s) = f(x^t) < f(x^{t+1}) \leq f_{-k}(x^{s+1})$ where:
 - a. the first equality follows from p being a \prec_T -ordered ascent and $k \prec_T i$. Thus, x_k must be set to its maximum value before x_i is flipped making the sum of constraints in $\mathcal{C}(k)$ equal to the value of $C_{\text{NS}(k) \setminus \{k\}}$ (following Equation (1));
 - b. the second strict inequality follows from p being an ascent; and,
 - c. the third inequality comes from the sum of constraints in $\mathcal{C}(k)$ with x_k being a particular value $x_k = x_k^{t+1}$ being less than or equal the maximum over all choices for x_k for the sum of constraints in $\mathcal{C}(k)$.
3. Last, if $i = k$ then i doesn't appear in $p \ominus k$. We don't have to check if it increases f_{-k} . That the ascent p is $\prec_{T - \{k\}}$ -ordered then follows from k being a leaf in T .

To see (2), consider any x^t in p and let $s \geq t$ be the lowest value such that the step-index between x^s and x^{s+1} is in $\text{NS}(k) - \{k\}$. In other words, during the time between t and s , no assignments changed in the scope neighbourhood of k . Thus, k itself was effectively subject to a unary constraint during this time and could have flipped at most $|D_k| - 1$ times. Consequence (2) then follows from looking at all the t - s gaps between flips in the scope neighbourhood of k (which is a subset of all $j \succ_T k$).

To see (3), we just need to note that \mathcal{C} and $\mathcal{C} \ominus k$ have the same conditions for being step-steepest.

Finally, (4) follows from a variable x_k being effectively under a unary constraint (see argument for (2)). With x_k subject to only a unary constraint, there cannot be two or more flips in x_k since the existence of a second flip would violate the max steepness property (i.e., the $f(x^{t+1}) \geq f(y)$ for all y that differ from x^t only at index k) of the first flip.

◀

The results of Proposition 3 can be applied recursively to give us an overall bound on the number of flips in a variable based on its depth in the treedepth-decomposition:

► **Proposition 4.** *Given a VCSP \mathcal{C} with domains of size $\leq v$, treedepth-decomposition T and a \prec_T -ordered ascent p in \mathcal{C} , if a node k is at depth d in T then x_k flips at most v^{d+1} times. If, in addition to the above, p is step-steepest then x_k flips at most 2^{d+1} times.*

Proof. Let $\text{mf}(d)$ be an upper bound on the maximum number of flips by a variable at depth d in the treedepth-decomposition then property (2) from Proposition 3 gives us:

$$\text{mf}(d) = (v - 1) \left(1 + \sum_{k=0}^{d-1} \text{mf}(k) \right) \quad (2)$$

$$= (v - 1) \text{mf}(d - 1) + \underbrace{(v - 1) \left(1 + \sum_{k=0}^{d-2} \text{mf}(k) \right)}_{\text{mf}(d-1)} \quad (3)$$

$$= v \text{mf}(d - 1) = v^d \text{mf}(0) = v^{d+1} \quad (4)$$

where the second equality comes from the recursive application of Proposition 3 and the last equality follows from an unconstrained variable flipping at most v times. If p is also step-steepest then property (4) from Proposition 3 improves the above to:

$$\text{mf}(d) = 1 + \sum_{k=0}^{d-1} \text{mf}(k) = \text{mf}(d - 1) + 1 + \underbrace{\sum_{k=0}^{d-2} \text{mf}(k)}_{\text{mf}(d-1)} = 2 \text{mf}(d - 1) = 2^d \text{mf}(0) = 2^{d+1} \quad (5)$$

◀

Theorem 1 then follows from the maximum depth of a node being the same as the height of the tree and there being n variables, all at the maximum depth or lower.

From Theorem 1 follows the important corollary:

► **Corollary 5.** *Polynomial ascents always exist in fitness landscapes from VCSPs with constraint graphs of logarithmic treedepth.*

4 All ascents are long with polylog treedepth

Corollary 5 is tight in the sense that relaxing from logarithmic treedepth to polylogarithmic treedepth allows for all ascents to be long. In fact, Theorem 1 is ‘tight’ in this stronger way:

► **Proposition 6.** *There exists a Boolean VCSP on n variables of treedepth d , such that – starting from 0^n – every ascent has length at least $\frac{9}{64(d+1)} 2^{d+1} \cdot n$.*

This follows directly from existing results on snake-in-the-box codes [10]. A **snake** is a connected path in the hypercube where each node on the path, with the exception of the head and tail, has exactly two neighbours that are also in the snake. The head and the tail each have only one neighbour in the snake. The snake can visit a candidate assignment in the hypercube if the candidate node is connected to the current node and it is not a neighbour of any previously visited node in the snake, other than the current node. Wojciechowski [10] showed there exists snakes on d -bits with length lower bounded by $\frac{9}{64} 2^d$.

Proof of Proposition 6. Consider a valued constraint on a set S of Boolean variables built in the following way. Set the fitness of all assignments corresponding to snake code words as their position on the snake path. Set the fitness of assignments to non-code words as zero. This single constraint creates a fitness landscape where every ascent from the assignment corresponding to the snake's head is long. Set 0^S as the snake's head, and call the above a *snake constraint* on S .

Now divide the n bits into $n/(d+1)$ blocks of $d+1$ bits each. On each block, put a snake constraint as above. Based on Wojciechowski [10]'s snake construction, each block will require at least $\frac{9}{64}2^{d+1}$ steps to reach its head. This will be repeated $n/(d+1)$ times, giving us the bound in Proposition 6. ◀

If we let S contain $d = \text{polylog}(n)$ bits then the above VCSP on n bits will implement a fitness landscape will all ascents of non-polynomial length. Thus, the VCSP will have no polynomial ascents from some initial assignment while having treedepth that is $\text{polylog}(n)$.

5 Long ascents with loglog treedepth

It is important to note that the existence of short ascents from Corollary 5 does not mean that local search algorithms will always find and follow short ascents in sparse VCSPs. In particular, alongside the short ascents that we saw in Section 3, there can also be long ascents in the same fitness landscapes. For instance, Kaznatcheev, Cohen and Jeavons [7]'s Example 7.2 is a binary Boolean VCSP on $4n+1$ variables with a constraint graph of pathwidth-2 that has ascents of length greater than 2^n . This example has logarithmic treedepth, and all other prior examples of long ascents that I know of also have at least logarithmic treedepth. To improve this state-of-the-art, I will to construct an binary Boolean VCSP on n variables with treedepth $O(\log \log n)$ that has long ascents.

At treedepth zero, the constraint graph has no edges and so can only produce a smooth additive landscape. This can have at most n flips for n bits.

For treedepth one, we have stars. Consider a star on $2n+1$ vertices. I will divide these vertices into 3 sets, a left set $L = \{1, \dots, n\}$ of n vertexes, one center vertex $c = n+1$, and a right set $R = \{n+2, \dots, 2n+1\}$ of n vertexes. For every edge cw with $w \in R$, add the constraint:

$$C_{\{c,w\}} = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \quad \text{where } x_c \text{ selects the row and } x_w \text{ selects the column.} \quad (6)$$

For the center variable, add the unary constraint:

$$C_{\{c\}} = \begin{pmatrix} 0 \\ n+1 \end{pmatrix} \quad \text{where } x_c \text{ selects the row.} \quad (7)$$

For every edge uc with $u \in L$, if $n-u$ is even then add the constraint:

$$C_{\{u,c\}} = \begin{pmatrix} 0 & 0 \\ 2n+2 & 0 \end{pmatrix} \quad \text{if } n-u \text{ is even, or} \quad (8)$$

$$C_{\{u,c\}} = \begin{pmatrix} 0 & 0 \\ 0 & 2n+2 \end{pmatrix} \quad \text{if } n-u \text{ is odd.} \quad (9)$$

Where for both constraints x_u selects the row and x_c selects the column. Finally, create a unary constraint for each $u \in L$ of $C_{\{u\}} = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$ where x_u selects the row.

Now consider a $>$ -ordered ascent on this VCSP starting from $x = 0^{2^{n+1}}$. This ascent will increase fitness by 1 at each step for a total length of $n^2 + 4n + 1$ flips.

Finally, for higher treedepth d , we will just repeat the pattern of the treedepth one construction. Specifically, we will have 2^d blocks of n variables with a $2^d - 1$ ‘center’ variables, with one center variable after each block of n variables. Name these center variables from *right to left* as c_1, \dots, c_m for $m = 2^d - 1$. We will connect each center variable to its preceding and following block of n variables in the same way as the treedepth 1 example above, except we will define the weights on c_k as follows. For c_1 , we will set the weights as in the star construction above. Specifically, the non-zero matrix entries of the binary constraints from left to center, unary constraint on center, and binary constraint from center to right will be $2n + 2, n + 1, 1$, respectively. Finally, for the first block, we will define $w_1 = 2n + 3$ (also $w_0 = 1$). For c_{k+1} , we will build the weights recursively from w_k by setting the non-zero matrix entries as $2nw_k + 2, nw_k + 1, w_k$ and define $w_{k+1} = 2nw_k + 3$. As with the star example, the leftmost block of n variables will have the additional unary constraints $\begin{pmatrix} 0 \\ 1 \end{pmatrix}$.

In the resulting VCSP, as with the star case, the $>$ -ordered ascent starting from $0^{2^d(n+1)-1}$ will increase the fitness by 1 at each step, with a maximum fitness greater than n^{2^d} . Thus, if we pick $d = \log \log n$, we will have a VCSP with $\log \log$ treedepth and an ascent that is quasipolynomially long.

6 Conclusion

I suspect that the construction from Section 5 cannot be significantly improved. Specifically, it would be interesting to show that all ascents have polynomial length in fitness landscapes from bounded treedepth VCSP. This is already known for treedepth 0 (smooth landscapes) and 1 (stars). Proving this general conjecture would require developing new techniques for proving short ascents, since prior techniques [7] like span arguments fail for stars and encouragement paths fail once we introduce cycles with treedepth ≥ 2 .

For log-bounded treedepth, the construction from Section 5 and prior results on long ascents [4, 7, 8] creates an interesting tension against Corollary 5. VCSPs of low treedepth always have short ascents to some local peak (Corollary 5), but can also hide long ascents. Thus, the question of tractability becomes a question of if specific local search algorithms that are used in practice – or forced on us by nature when we are modeling processes like biological evolution [5, 6, 7] – end up on one of the short ascents or one of the long ones. Overall, these results suggest that the study of sparse VCSPs can help us better understand the barriers to efficient local search and teach us something about the structure of locally optimal combinatorial objects.

Acknowledgements

I would like to thank Sukanya Pandey for introducing me to treedepth; and Dave Cohen, Peter Jeavons, and Melle van Marle for helpful discussions.

References

- [1] U. Bertelè and F. Brioschi. ‘On non-serial dynamic programming’. In: *Journal of Combinatorial Theory, Series A* 14.2 (1973), pp. 137–148. ISSN: 0097-3165. DOI: [https://doi.org/10.1016/0097-3165\(73\)90016-2](https://doi.org/10.1016/0097-3165(73)90016-2).

- [2] H. L. Bodlaender et al. ‘Approximating treewidth, pathwidth, frontsize, and shortest elimination tree’. In: *Journal of Algorithms* 18.2 (1995), pp. 238–255.
- [3] C. Carbonnel, M. Romero and S. Živný. ‘The Complexity of General-Valued Constraint Satisfaction Problems Seen from the Other Side’. In: *SIAM Journal on Computing* 51.1 (2022), pp. 19–69. DOI: 10.1137/19M1250121.
- [4] D. A. Cohen et al. ‘Steepest ascent can be exponential in bounded treewidth problems’. In: *Operations Research Letters* 48 (3 2020), pp. 217–224.
- [5] A. Kaznatcheev. ‘Algorithmic Biology of Evolution and Ecology’. PhD thesis. University of Oxford, 2020.
- [6] A. Kaznatcheev. ‘Computational complexity as an ultimate constraint on evolution’. In: *Genetics* 212.1 (2019), pp. 245–265.
- [7] A. Kaznatcheev, D. Cohen and P. Jeavons. ‘Representing fitness landscapes by valued constraints to understand the complexity of local search’. In: *Journal of Artificial Intelligence Research* 69 (2020), pp. 1077–1102.
- [8] A. Kaznatcheev and M. van Marle. ‘Exponential Steepest Ascent from Valued Constraint Graphs of Pathwidth Four’. In: *ArXiv* (2024).
- [9] J. Nešetřil and P. Ossona de Mendez. ‘Chapter 6: Bounded height trees and tree-depth’. In: *Sparsity: Graphs, Structures, and Algorithms*. Springer, 2012, pp. 115–144.
- [10] J. Wojciechowski. ‘A new lower bound for snake-in-the-box codes’. In: *Combinatorica* 9 (1989), pp. 91–99.