# A Privacy-Preserving DAO Model Using NFT Authentication for the Punishment not Reward Blockchain Architecture

Talgar Bayan<sup>a</sup>, Richard Banach<sup>a</sup>

<sup>a</sup>Department of Computer Science, The University of Manchester, , Manchester, M13 9PL, , UK

# Abstract

This paper presents a novel decentralized autonomous organization (DAO) model leveraging non-fungible tokens (NFTs) for advanced access control and privacy-preserving interactions within a Punishment not Reward (PnR) blockchain framework. The proposed model introduces a dual NFT architecture: Membership NFTs ( $NFT_{auth}$ ) for authentication and access control, and Interaction NFTs ( $NFT_{priv}$ ) for enabling private, encrypted interactions among participants. Governance is enforced through smart contracts that manage reputation and administer punitive measures, such as conditional identity disclosure. By prioritizing privacy, security, and deterrence over financial rewards, this model addresses key challenges in existing blockchain incentive structures, paving the way for more sustainable and decentralized governance frameworks.

*Keywords:* Blockchain, Decentralized Autonomous Organization (DAO), Non-Fungible Token (NFT), Privacy Preservation, Punishment not Reward (PnR), Smart Contracts

# 1. Introduction

As blockchain technology has evolved over the last 15 years, numerous innovations have emerged. From the initial 'killer app' Bitcoin [1], powered by the Proof of Work (PoW) consensus mechanism, we have seen the advent of decentralized autonomous organizations (DAOs), non-fungible tokens (NFTs), decentralized finance (DeFi), the Metaverse, Layer 2 solutions, modular chains, and even recent developments in Bitcoin scripting ecosystems like Ordinals [2] and the Lightning Network. Blockchain technology is increasingly being adopted by individuals, developers, and even nations, transforming various aspects of our lives. A DAO is one of the most significant branches of blockchain implementation, suitable for groups of people or organizations, allowing them to govern distributed activities on an immutable, transparent, and always ready network without the need for extensive platform preparation, implementation, and testing. This brings significant benefits by enabling participants to operate on established platforms such as Ethereum and its Layer 2 solutions.

DAOs have evolved significantly, particularly with the emergence of platforms like Ethereum that support on-chain self-executing code known as "smart contracts." A DAO is an online governance structure created by several smart contracts, which facilitate transparent operations and feature-rich management of participants on a tested blockchain platform. The concept of the DAO has gone through several stages. The first DAO was launched in April 2016 as a token sale [3]. At that time, "The DAO" referred to a specific organization, but as more chains were created to support DAOs and their applications diversified—such as DAOs for DeFi and governance (e.g., Arbitrum DAO)—the term DAO has since acquired a broader context.

DAOs have emerged as a transformative governance paradigm underpinned by blockchain technology. However, effectively balancing incentives and disincentives within DAOs remains an open challenge. Conventional reward-dominant designs risk encouraging misconduct, volatility, and wealth concentration.

Although DAOs help us achieve transparency and secure management practices, most are motivated and maintained by governance tokens. With increasing regulatory scrutiny, it is essential to explore alternative mechanisms to balance regulation. We propose that an NFT-based DAO is an ideal approach to avoid speculation and comply with regulatory requirements.

Similar to collectibles like baseball cards, NFTs are considered unique and transferable assets on-chain. The first popular NFT collection was CryptoKitties [4], which caused a significant slowdown on the Ethereum chain, ultimately driving the development of Layer 2 solutions for Ethereum. Many companies are now moving their intellectual property on-chain, with notable examples including NBA Top Shot [5] and the Bored Ape Yacht Club [6]. NFTs are well-suited for on-chain gaming, inspiring the Metaverse, and serving

<sup>\*</sup>Corresponding author

Preprint submitted to Elsevier

as digital collectibles. Crucially, they can also be used as proof of participation and tools for access control.

Integrating NFT-based access control introduces new possibilities for strengthening DAO architectures. Specifically, NFTs can serve as Sybil-resistant identity and permission certificates for authorized participants. Despite their promising capabilities, research into disincentive-focused, privacy-preserving DAO frameworks leveraging NFT authentication is still in its infancy.

We investigate the "Punishment not Reward" (PnR) paradigm [7] as an exemplar of a disincentive-centric architecture realized through a combination of NFT authentication, zero-knowledge proofs, and selective identity disclosure powered by Ethereum. The PnR model aims to discourage detrimental behavior by binding identities to the loss of reputation rather than relying on continuous remuneration. Our analysis assesses the viability of designing cryptographically enforced DAO rules that punish violations without compromising participant privacy. Although privacy risks associated with permissionless blockchains have become a major concern for individuals and institutions [8], by distributing NFTs fairly and preserving privacy, we can address membership issues for the PnR blockchain architecture.

We propose a purely on-chain solution for the PnR blockchain, utilizing the DAO management structure and NFTs as access control and membership tools to solve incentive issues. With the proven security features of Layer 2 blockchain technology, this solution can be implemented at a low cost without the need for extensive DevOps training, server establishment, or developer overhead. It operates on a permissionless blockchain supported by millions of participants worldwide, available 24/7.

The contributions of this work include:

- Identifying a low-cost implementation of a PnR DAO model for Layer2 blockchain, utilizing NFT authentication to provide a prototype for the PnR blockchain architecture.
- Proposing an on-chain commitment scheme to conceal and, when necessary, revoke the real ID associated with a participant's wallet address, enhancing privacy and accountability.
- Conducting a comprehensive analysis of Permissionless (PES) and Permissioned (PED) blockchain systems to identify the current lowest cost of implementation.

This paper explores the intersections between DAO design, incentive mechanisms, and privacy-preserving cryptography, presenting an instantiation of these concepts through an NFT-authenticated, disincentivefocused DAO model. We posit that the PnR archetype demonstrates the potential for sustainable DAO architectures founded on deterrence rather than rewards. To aid the understanding of the terms and abbreviations used throughout this paper, we provide a notation table below (Table 1).

Table 1: Notation Table				
Abbreviation	Description			
DE	Decentralized			
CE	Centralized			
NFT	Non-Fungible Token			
PnR	Punishment not Reward			
DAO	Decentralized Autonomous Organization			
L2	Layer 2			
zkEVM	Zero-Knowledge Ethereum Virtual Machine			
PoS	Proof of Stake			
PoW	Proof of Work			
PBFT	Practical Byzantine Fault Tolerance			
CBDC	Central Bank Digital Currency			
PES	Permissionless Blockchain			
PED	Permissioned Blockchain			
СМ	Consensus Mechanism			

# 2. Related Work

## 2.1. PnR (Punishment not Reward)

The main concept of PnR (Punishment not Reward) [7] is to use a completely different (dis)incentive mechanism, rather than issuing a coin, which can trigger speculation or regulation issues. PnR disincentives include denial of service and revocation of user anonymity. These cause the potential loss of reputation of individual participants rather than of the organization as a whole. The incentive structure within the PnR model is encapsulated by the following inequality (which presumes some method of quantifying the quantities mentioned):

$$Loss_{reputation} \gg Gain_{cheating}$$
 (1)

This mathematical representation ensures that the fear of reputational damage significantly outweighs any potential gains from system manipulation, thereby encouraging compliance.

## 2.2. Blockchain platforms

We can divide all Blockchains into two parts: Permissioned and Permissionless Blockchains. Hyperledger Fabric [9] and Ethereum are the top widely used chains by participants and also developers in each of those categories. Blockchain platforms are experiencing rapid growth, with various platforms focusing on different aspects such as privacy preservation (zkEVM), cost-efficiency (L2), modularity, and enterprise-level solutions like Hyperledger Fabric. The key characteristics of the two kinds are:

Chains	Ethereum	Polygon	Hyperledger	Private Chain	Arbitrum
Туре	PES, DE	PES, DE	PED, CE	PED, CE	PES, DE
Security Level	High	High	Moderate	Moderate	High
Transaction Fee	High	Low	Low	Low	Low
Operational Expenditure <sup>a</sup>	Low	Low	High	Substantial	Low
Ease of Implementation	Moderate	Moderate	High	Extensive	Moderate
Large Institutions Involvement	Yes	Yes	Yes	Yes <sup>b</sup>	Yes
Transaction Speed	Moderate	High	Rapid	Rapid	High
Regulatory Status	In Process	In Process	Regulated	Regulated	In Process
Scalability	Moderate	High	Moderate	Limited	High
CM <sup>c</sup>	Proof of Stake <sup>d</sup>	Proof of Stake	Pluggable <sup>e</sup>	Custom	Proof of Stake
Developer Community	Extensive	Growing	Moderate	Limited	Growing

Table 2: Comparative Analysis of Blockchains

<sup>a</sup> Server, Maintenance, Energy, Development etc.

<sup>b</sup> Primarily for CBDCs

<sup>c</sup> Consensus Mechanism

<sup>d</sup> Transitioned from PoW to PoS

- <sup>e</sup> e.g., PBFT
- Permissioned Blockchains: Need to set up nodes and servers, lack of decentralization, higher cost at the start, and no fee for transactions.
- Permissionless Blockchains: Proven by many devs and millions of nodes, decentralized and no additional fees except gas fees.

Selecting the most suitable blockchain platform for the PnR DAO is crucial to ensure optimal performance, security, and scalability. We have analyzed the most widely adopted blockchain platforms by both users and developers and present a comparative overview in Table 2. Based on our analysis, EVM-based L2 platforms emerge as the most favorable choice for our PnR DAO implementation, offering a combination of high transaction speed, reliability, developer-friendly tools, and cost-effectiveness.

After careful comparison, and as shown in Table 3, we notice that Layer 2 chains have low cost, balanced security due to the connection with the main Ethereum chain, and easier development. So for our DAO, we implement the Layer2 chain. The costs involved, such as they are, have become even lower due to the recent and continued updates of Ethereum like The Dencun Upgrade.

Table 3: Transaction Costs in USD					
Chain	Send	Execute	Total		
Ethereum	\$130.00	\$1,290.00	\$1,420.00		
Polygon	\$1.30	\$13.00	\$14.30		
Arbitrum	\$4.00	\$40.00	\$44.00		

## 2.3. Incentives and Disincentives of Blockchain

Effectively incentivizing participation while deterring misconduct is pivotal for decentralized ecosystems. However, poorly calibrated models risk enabling attack vectors or hampering adoption. A systemic perspective recognizing user motivations is essential when engineering robust tokenomic designs. Recent research highlights the importance of integrating incentive mechanisms within blockchain architectures to enhance user engagement and maintain network integrity.

A study of blockchain-based collaborative edge computing discusses the significance of incentives in optimizing resource allocation and enhancing system utility while minimizing task latency [10]. Similarly, blockchain and distributed ledger technology (DLT) have been recognized for their potential to revolutionize various sectors, including healthcare, by providing enhanced security, transparency, and reduced administrative overhead [11]. Additionally, a systematic review of blockchain research emphasizes the critical role of economic incentives in fostering sustainable adoption across different industries [12]. These insights underscore the necessity of wellstructured incentives and disincentives to foster sustainable blockchain ecosystems.

Table 4 presents an illustrative overview of various incentives and disincentives commonly used in blockchain systems. As highlighted in Table 4, tokenomic tactics leverage both intrinsic and extrinsic incentives across engagement, reputation, and governance dimensions. Loyalty rewards reflect sustained contributions while milestone privileges incentivize activities tied to roadmap objectives without fueling short-term speculation. Importantly, deterrence effects are structured to outweigh potential gains from malicious conduct.

# 2.4. DAO and NFT

Decentralization is based on a set of different roles and automated tasks adopted by the P2P community for validating, governance, and decision-making.

Type of Incentive/Disincentive	Description
Financial Rewards	Mining returns, staking rewards, and token appreciation.
Transaction Fee Incentives	Priority processing based on higher transaction fees paid by users.
Governance Participation	Voting rights are earned through holding native tokens.
Token Appreciation	Benefits from an increase in the value of the native token over time.
Network Utility	Use of native tokens for specific features within the blockchain network.
NFT Airdrop	Additional tokens distributed to NFT holders during airdrop campaigns.
Cosmos Staking Airdrop	Rewards for staking native tokens to secure the Cosmos network.
Developers Airdrop	Token rewards for developers contributing to the development of the blockchain ecosystem.
Referral Programs	Rewards for bringing new participants to the network.
Loyalty Programs	Rewards for consistent usage and engagement within the blockchain platform.
Milestone Events	Special rewards or incentives are given during significant achievements or mile- stones.
DeFi Participation	Rewards from participating in decentralized financial activities.
POAP (Proof of Attendance Protocol)	Tokens are given as proof of attendance at events or milestones.
Community Challenges	Incentives for participating in challenges or competitions within the community.

These automated tasks are based on DAO smart contracts and are encoded in the blockchain protocol [13]. DAOs also include other roles and tasks based on autonomous off-chain human interactions, mainly collective decision-making and voting [14]. To understand how these decentralized organizations perform, we focus on the main roles and tasks of DAOs.

Our proposed DAO prototype, based on the PnR architecture [7], aims to foster community alignment and sustainability through a recalibrated balance of incentives and disincentives. By foregoing direct financial rewards, speculative behavior is discouraged while still promoting contributions core to the ecosystem.

DAOs are expected to overturn the traditional hierarchical management model and significantly reduce organizations' costs related to communication, management, and collaboration [13]. For instance, platforms like Aragon, DigixDAO, and Steemit have showcased the potential of DAOs in various domains, highlighting the efficiency and transparency of smart contract-based governance [3].

Non-fungible tokens (NFTs) represent unique digital assets on blockchain platforms, enabling proof of ownership and authenticity for a wide range of items, from digital art to real estate. The ERC-721 and ERC-1155 standards are central to the utility and innovation of NFTs, facilitating the creation and trading of these digital assets on the Ethereum blockchain [15, 16]. ERC-721 pioneered the creation of NFTs, allowing each token to be unique and indivisible, making them suitable for use cases such as digital art and collectibles. ERC-1155, on the other hand, introduced a more versatile approach, enabling a single contract to manage multiple token types, including both fungible and non-fungible assets.

In our proposed DAO model, ERC-721 NFTs  $(NFT_{auth})$  are used for authentication and access con-

trol. Each  $NFT_{auth}$  is unique and linked to a participant's wallet address, serving as a proof of membership within the DAO. The structure of an ERC-721 NFT includes:

- A unique Token ID
- Metadata with the owner's public key and role
- · Ownership mapping to wallet addresses
- A URI linking to off-chain metadata stored on IPFS

Specifically, the metadata for  $NFT_{auth}$  includes attributes such as:

- The participant's role within the DAO (e.g., general user, service provider, arbitrator)
- Public key for verification
- Join date

For private transactions within the DAO, ERC-1155 NFTs ( $NFT_{priv}$ ) are utilized, allowing efficient handling of multiple token types. The structure of an ERC-1155 NFT includes:

- Token ID
- The balances mapping
- · Metadata about the private transaction
- A URI for off-chain metadata details
- The metadata for  $NFT_{priv}$  includes:
- Participants' wallet addresses
- Service amount
- · Deadline for service completion
- Payment type (typically a regulated stablecoin)
- Specific conditions or requirements for the transaction

Research shows that using NFTs as authentication tools in DAOs can significantly enhance security and privacy. For example, NFTs have been proposed for secure membership authentication and access control, ensuring that only authorized participants can engage in DAO activities [15]. These functionalities are pivotal in preventing Sybil attacks and maintaining a robust governance structure. However, several gaps remain. Existing NFT-DAO implementations often face challenges related to scalability, gas costs, and the integration of advanced privacy-preserving techniques. Our proposed system addresses these gaps by leveraging zero-knowledge proofs and selective identity disclosure, enhancing both privacy and scalability within the DAO framework [17].

In our model, NFTs serve a dual role: as a means of authentication and as a medium for securely carrying data. This approach enhances the security and privacy of DAO operations while leveraging blockchain technology's inherent benefits—immutability, transparency, and decentralization. By integrating NFTs with advanced access control mechanisms, we aim to address current challenges in incentive models and establish a more balanced, secure, and efficient framework for decentralized governance.

#### 2.5. Privacy preservation techniques

Due to the transparent nature of permissionless Blockchains, especially EVM, privacy concerns are a top priority. In [8], various techniques to improve blockchain privacy are discussed.

Public Key Encryption for Private Interactions To facilitate private trading interactions between participants  $(P_i)$  in the DAO system, public key cryptography mechanisms can be adopted. Specifically, the RSA algorithm allows two parties to securely exchange messages encrypted with public keys  $(pk_i)$  that can only be decrypted using the corresponding private keys  $(sk_i)$ .

Formally, each DAO member with a wallet address  $(w_i)$  and private key  $(sk_i)$  has an associated public key  $(pk_i)$  generated using a one-way function f:

$$pk_i = f(sk_i) \tag{2}$$

To trade an NFT, buyer *B* with public key  $pk_B$  encrypts a payment message *m* as:

$$c = E_{pk_S}(m) \tag{3}$$

where *E* represents asymmetric encryption and *S* is the seller. *c* is sent on-chain. Seller *S* can decrypt this using private key  $sk_S$ :

$$m = D_{sk_s}(c) \tag{4}$$

By embedding public keys into NFT metadata instead of transacting openly, privacy is enhanced. The RSA algorithm secures messages against brute-force attacks. This allows private order information to be shared selectively between parties while an NFT transfer occurs publicly as an anonymized transaction.

Commitment Schemes for Identity Management Commitment schemes also present a privacy-preserving technique for managing identities in the DAO. A cryptographic commitment  $C_i$  to an attribute  $x_i$  binds an entity to the attribute value without revealing it. Blockchain and commitment schemes can be an approach to protect critical data like healthcare records [18]. In our model, commitment schemes can be used to hide the real identity of the participants.

For member identities, the following property enables a private committment to a real-world identity  $I_i$ :

$$C_i = com(I_i; r_i) \tag{5}$$

where  $r_i$  introduces randomness to mask  $I_i$ . Later, the commitment  $C_i$  can be opened to prove identity ownership.

Commitments are useful before voting to punish members by revealing their identities. Once an adequate number of votes is reached, the committed value is unveiled. This preserves privacy while ensuring that misbehaving members can ultimately be deanonymized if required.

The integration of commitment schemes into the DAO design enables this flexible identity management mechanism.

## 3. Proposed DAO Model

## 3.1. User Onboarding

In the onboarding process, each participant  $U_i$  joins the DAO by generating a unique wallet address and authenticating their identity through a decentralized KYC (DKYC) procedure. This process ensures that only verified participants can mint their  $NFT_{auth}$  token and gain access to the DAO's functionalities. Let  $U = \{U_1, U_2, ..., U_n\}$  be the set of *n* participants seeking to join the DAO. Each participant  $U_i$  generates a wallet address represented by their public key  $PK_i$  and a corresponding private key  $SK_i$ . The public key serves as the participant's pseudonymous identifier within the DAO, while the private key is used to sign transactions and prove ownership of the wallet address.

The real identity of each participant  $U_i$  is denoted as  $ID_i$ , which is not directly linked to their wallet address  $PK_i$  onchain to maintain privacy. The mapping between the real identities and wallet addresses is represented as:

$$PK_i = genPK(ID_i) \tag{6}$$

where  $ID_i$  corresponds to the real identity of participant  $U_i$ .

To authenticate the real identities of participants, a decentralized KYC process is used. The DKYC procedure is a function that verifies the real identity  $ID_i$  of participant  $U_i$  and returns a boolean value indicating the success of the verification:

$$DKYC(ID_i) = \begin{cases} 1, & ID_i \text{ is verified} \\ 0, & ID_i \text{ is not verified} \end{cases}$$
(7)

The DKYC process can be implemented using various techniques, such as zero-knowledge proofs (ZKPs) or secure multi-party computation (MPC), to ensure the privacy and security of the participants' real identities during the verification process. Once a participant  $U_i$  successfully completes the DKYC process, they can interact with the DAO's smart contract to mint their  $NFT_{auth}$  token. The minting process is represented by the function:

$$NFT_{auth}^{U_i} = MintNFT_{auth}(PK_i, DKYC(ID_i))$$
 (8)

where  $NFT_{auth}^{U_i}$  is the  $NFT_{auth}$  token minted for participant  $U_i$ , and  $MintNFT_{auth}$  is the smart contract function that mints the token based on the participant's public key  $PK_i$  and the result of the DKYC verification.

The  $NFT_{auth}$  token serves as the participant's access pass to the DAO and is stored in their wallet. The smart contract maintains a mapping between the wallet addresses and the minted  $NFT_{auth}$  tokens:

$$NFT_{auth} = \{PK_1 \mapsto NFT_{auth}^{U_1}, \dots, PK_n \mapsto NFT_{auth}^{U_n}\}$$
(9)

where  $NFT_{auth}^{U_i}$  is the  $NFT_{auth}$  token minted for participant  $U_i$ . To remove a participant from the DAO, the smart contract includes a function *RemoveMember* that burns the participant's  $NFT_{auth}$  token and revokes their access rights. The removal process is triggered by a governance mechanism, such as a vote among the DAO members, to ensure decentralized decision-making.

#### 3.2. Governance

The governance mechanism in the PnR DAO plays a crucial role in balancing incentives and managing participants through the implementation of a Denial of Service (DoS) feature. The DAO can be viewed as a consortium of service providers, where participants holding  $NFT_{auth}$  tokens are entitled to receive services and actively engage within the community.

To achieve the DoS functionality in the PnR DAO, the *RemoveMember* function is utilized. When a participant  $U_i$  is identified as a Sybil account or violates the DAO's rules, any member of the DAO can initiate a proposal to remove the offending participant. The proposal includes setting a quorum threshold, typically 50% or 65%, which determines the minimum number of votes required for the proposal to pass.

Let  $P_{remove}^{U_i}$  denote the proposal to remove participant  $U_i$  from the DAO. The proposal is represented as:

$$P_{remove}^{U_i}(U_i, Q, T) \tag{10}$$

where Q is the quorum threshold and T is the deadline for the voting process.

All members holding  $NFT_{auth}$  tokens are eligible to vote on the proposal. The voting process is a function that takes the proposal  $P_{remove}^{U_i}$  and the votes cast by the members as input and returns the decision:

$$Vote(P_{remove}^{U_i}, V) = \begin{cases} 1, & \sum_{j=1}^n V_j \ge Q \cdot n \\ 0, & \sum_{j=1}^n V_j < Q \cdot n \end{cases}$$
(11)

where  $V = \{V_1, V_2, ..., V_n\}$  represents the votes cast by the *n* members, with  $V_j = 1$  indicating a vote in favor of the proposal and  $V_j = 0$  indicating a vote against the proposal.

If the number of votes in favor of the proposal reaches or exceeds the quorum threshold Q by the deadline T, the proposal is considered approved. The DAO smart contract then automatically executes the *RemoveMember* function to remove the offending participant  $U_i$  from the DAO:

$$RemoveMember(U_i) = \begin{cases} 1, & Vote(P_{remove}^{U_i}, V) = 1\\ 0, & Vote(P_{remove}^{U_i}, V) = 0 \end{cases}$$
(12)

Upon successful removal, the participant's  $NFT_{auth}$  token is burned, revoking their access rights and privileges within the DAO.

To further enhance the governance structure, each  $NFT_{auth}$  token includes role metadata that specifies the participant's role within the DAO. Roles can include general user, service provider, service buyer, arbitrator, and more. Participants can claim their roles based on predefined criteria set by the DAO.

To prevent removed participants from rejoining the DAO or transferring their  $NFT_{auth}$  tokens to other identities, the concept of soulbound tokens (SBTs) can be used. SBTs are

non-transferable tokens that are permanently bound to a specific identity. By making the  $NFT_{auth}$  tokens soulbound, the DAO ensures that removed participants cannot regain access to the DAO's services and privileges.

Compared to the traditional decision-making process, the DAO structure is fast, cost-efficient, and transparent.

## 3.3. Commitment Schemes to Revoke Anonymity

Commitment schemes provide a robust method to manage identity privacy within the DAO while allowing for identity revocation when necessary. A cryptographic commitment  $C_i$  to an attribute  $x_i$  binds an entity to the attribute value without revealing it. This approach can be leveraged to protect critical data and can be adapted for identity management within a DAO [18].

For member identities, this property allows privately committing to a real-world identity  $ID_i$ :

$$C_i = com(ID_i; r_i) \tag{13}$$

where  $r_i$  introduces randomness to mask  $ID_i$ . Later,  $C_i$  can be opened to prove identity ownership.

Commitments are useful before voting to punish members by revealing their identities. Once an adequate number of votes is reached, the committed value is forcibly unveiled. This preserves privacy while ensuring that misbehaving members can ultimately be deanonymized if required.

The integration of commitment schemes into the DAO model enables this flexible identity management mechanism.

## 3.4. Private Transactions

Within the PnR DAO, participants can engage in transactions, deals, or other on-chain activities. When privacy is required, they can utilize a smart contract associated with the DAO called *servicePrivateDeal*.

To initiate a private deal, two or more participants mint an  $NFT_{priv}$  token using the *servicePrivateDeal* smart contract. The minting process involves providing the following information:

- Participants involved in the deal  $(P_1, P_2, \ldots, P_n)$
- Service amount (S)
- Deadline for service completion (*D*)
- Payment type (T), typically a regulated stablecoin

The  $NFT_{priv}$  token represents the service deal, similar to liquidity NFTs in many DeFi applications. The buyer deposits the payment amount to the *servicePrivateDeal* smart contract, which holds the funds in escrow until the service is completed. The service provider performs the agreed-upon service and marks it as completed in the *servicePrivateDeal* before the specified deadline. If the service is completed satisfactorily and on time, the buyer confirms the completion, and the payment is released to the service provider. However, if the service is not completed or not satisfactory, the buyer can initiate a dispute resolution process within the DAO. The dispute resolution involves the following steps:

- The buyer initiates a dispute by providing the NFT<sub>priv</sub> token and their identity.
- The DAO members conduct a voting process to determine the outcome of the dispute.

- 3. If the voting result favors the buyer, the payment is refunded to the buyer, and the service provider may face penalties such as a reputation loss or temporary suspension from the DAO.
- 4. If the voting result favors the service provider, the payment is released to the service provider.

The servicePrivateDeal smart contract ensures that the funds are held securely in escrow during the deal process. The use of  $NFT_{priv}$  tokens provides a unique identifier for each private deal, enabling easy tracking and management of the deal lifecycle. The dispute resolution process leverages the decentralized governance mechanism of the PnR DAO, allowing the community to collectively decide on the outcome of disputes. This approach ensures fairness and transparency in the resolution of conflicts arising from private deals. By incorporating privacy-preserving mechanisms and a decentralized dispute-resolution process, the PnR DAO creates a trusted environment for participants to engage in private deals. The servicePrivateDeal smart contract and the NFT<sub>priv</sub> tokens work together to facilitate secure and confidential transactions while maintaining the integrity of the system.

The private deal mechanism in the PnR DAO demonstrates the potential of combining blockchain technology, smart contracts, and decentralized governance to enable secure and efficient transactions within a privacy-focused ecosystem. It showcases the flexibility and adaptability of the PnR DAO model in accommodating various use cases and requirements, including the need for confidentiality in specific deals or transactions.

#### 3.5. Dispute Resolution and Arbitration

A crucial aspect of the PnR DAO is its dispute resolution mechanism, which ensures fairness and transparency in resolving conflicts. When a dispute arises, it is essential to have a structured process to address grievances and ensure that all parties are treated equitably. The dispute resolution process involves the following steps:

- 1. Initiation: The aggrieved party initiates the dispute resolution process by submitting a formal complaint to the DAO, providing details of the dispute and any relevant evidence.
- Mediation: The DAO members attempt to mediate the dispute, encouraging the parties to reach a mutually acceptable resolution through discussion and negotiation.
- 3. Voting: If mediation fails, the dispute is put to a vote among the DAO members. Each member reviews the evidence and casts their vote on the resolution of the dispute.
- 4. Enforcement: The outcome of the vote is enforced by the DAO's smart contracts. If the vote favors the aggrieved party, appropriate actions are taken, such as refunding payments, penalizing the offending party, or revoking access rights.

This structured approach to dispute resolution ensures that conflicts are addressed promptly and fairly, maintaining the integrity of the PnR DAO ecosystem.

## 4. Evaluation and Future Work

In this section, as shown in Figure 1 we evaluate the proposed DAO model based on the Punishment not Reward (PnR) paradigm. The evaluation focuses on several key aspects, including the effectiveness of the governance mechanism, the robustness of the privacy preservation techniques, and the overall feasibility of the model in real-world applications.

## 4.1. Evaluation Methodology

We adopt a qualitative approach to evaluate the proposed model. Our methodology includes a literature review, theoretical analysis, comparative analysis, and outlining potential simulation studies. The literature review analyzes recent works in blockchain governance, privacy-preserving techniques, and DAO implementations to understand current trends and challenges. The theoretical analysis assesses the proposed mechanisms to ensure they align with the goals of the PnR model. The comparative analysis highlights the advantages of the proposed model over existing models and identifies potential gaps. Although this paper does not include actual code implementation, we propose simulation studies involving a blockchain testnet to create a DAO with a set number of participants, simulating various scenarios such as participant misconduct, and observing the outcomes.

#### 4.2. Governance and Privacy Mechanisms

The governance mechanism in the PnR DAO balances incentives and manages participants through the Denial of Service (DoS) feature and revocation of anonymity. The use of NFT-based authentication and DKYC (Decentralized Know Your Customer) ensures that participants are real entities with verifiable identities, significantly reducing the risk of Sybil attacks. The proposal to remove a participant is based on a quorum threshold and is decided through a decentralized voting process, ensuring fairness and transparency.

For privacy preservation, public key encryption and commitment schemes are used. The RSA algorithm allows secure exchange of messages between participants by embedding public keys into NFT metadata, enhancing privacy and ensuring that trading interactions remain confidential. Cryptographic commitment schemes enable participants to commit to their identities securely. The committed value can be revealed if necessary, ensuring that identities can be verified without being exposed prematurely. This balances privacy and accountability, fostering trust within the DAO.

#### 4.3. Airdrops and Sybil Detection

The PnR monitoring service plays a critical role in maintaining the integrity of the DAO by collecting open data, creating milestone events, and comparing interactions to build a dataset that helps in identifying and avoiding Sybil accounts. By continuously monitoring participant behavior and engagement, the PnR monitoring service ensures that only genuine participants benefit from the DAO's activities and resources.

Airdrops have evolved significantly since their inception. Initially, users needed only to submit an address or email to



Figure 1: Overview of the PnR DAO Model

receive rewards. As decentralized finance (DeFi) grew, airdrops began to require the provision of liquidity in DeFi protocols to earn rewards. With the emergence of Layer 2 solutions, airdrops have further evolved to necessitate interaction within the ecosystem of a blockchain, such as engaging in various activities across the chain.

This evolution of airdrops has seen participants shift from casual users to professional farmers and "baggers" who specialize in exploiting these opportunities. As a result, identifying and mitigating bad behaviors has become increasingly complex. Many projects, including Arbitrum, Hop, LayerZero, and zkSync, have begun collaborating with on-chain analytics companies like Nansen to detect Sybil attacks and fraudulent activities.

To address these evolving challenges, the PnR DAO uses data from the monitoring service to identify repeatable behaviors and minimize the impact of Sybil accounts. By analyzing patterns and interactions on-chain, the system can flag suspicious activities, providing a more robust solution to detect and deter malicious behavior.

#### 4.4. Comparative Analysis and Future Work

In comparison to existing DAO models, such as those based on Aragon or MolochDAO, our model focuses on punishment mechanisms instead of rewards, reducing speculative behavior and aligning the interests of participants towards the long-term sustainability of the DAO. Our approach provides a higher level of privacy through the use of advanced cryptographic techniques like ZKPs and commitment schemes.

Future work involves implementing the proposed model on a blockchain platform and conducting extensive testing to validate its effectiveness. Further research is needed to assess the scalability of the model, particularly in large-scale DAOs with thousands of participants. Exploring additional privacypreserving techniques, such as homomorphic encryption and secure multi-party computation, could further enhance the model.

The PnR DAO model offers a novel approach to decentralized governance that can be applied to various sectors, including education, healthcare, and professional services. By integrating advanced cryptographic techniques, the model enhances privacy and security, addressing major concerns in blockchain ecosystems. This work demonstrates the potential for sustainable DAO architectures founded on deterrence rather than rewards, paving the way for more secure and equitable decentralized ecosystems.

# 5. Conclusion

In this paper, we have proposed a novel privacy-preserving NFT-authenticated DAO model for Punishment not Reward (PnR) blockchain archetecture. The model leverages a dual NFT architecture, consisting of  $NFT_{auth}$  for access control and  $NFT_{priv}$  for private deals, to ensure secure and confidential transactions within the DAO ecosystem. The integration

of advanced cryptographic techniques, such as public key encryption and commitment schemes, enhances the privacy and security of participant identities and interactions.

The proposed governance mechanism, based on NFT stake-weighted voting and decentralized decision-making, enables efficient and transparent management of the DAO. The ability to remove malicious participants through the RemoveMember function and the use of soulbond tokens (SBTs) to prevent rejoining attacks demonstrate the robustness and resilience of the model. However, there are several open issues and challenges that require further investigation. One critical aspect is the conditions for triggering punitive actions, such as identity disclosure. Developing clear and fair criteria for initiating such actions is essential to maintain the balance between privacy and accountability within the DAO. Additionally, the potential for malicious participants to create new identities and rejoin the DAO after being removed (rejoin issues) needs to be addressed through more sophisticated identity management techniques.

Another important consideration is the reliance on trusted third parties for certain functions, such as decentralized KYC (DKYC) processes. While the use of zero-knowledge proofs (ZKPs) and secure multi-party computation (MPC) can mitigate some of the trust requirements, further research is needed to develop fully decentralized and trustless solutions. Despite these challenges, the proposed PnR DAO model represents a significant step toward building privacy-preserving and sustainable blockchain-based organizations. The combination of NFT-based authentication, privacy-enhancing techniques, and decentralized governance mechanisms offers a promising framework for future decentralized applications.

Future work could focus on implementing and evaluating the proposed model in real-world scenarios, exploring the scalability and performance aspects, and conducting more rigorous security and privacy analyses. Additionally, investigating the integration of advanced privacy technologies, such as zero-knowledge proofs and secure multi-party computation, could further enhance the privacy guarantees of the system.

In conclusion, the privacy-preserving NFT-authenticated DAO model presented in this paper contributes to the development of secure, transparent, and self-governing blockchain-based organizations. By prioritizing privacy, security, and deterrence over financial rewards, the proposed model paves the way for more sustainable and equitable decentralized ecosystems.

## References

- S. Nakamoto, Bitcoin: A peer-to-peer electronic cash system, https://bitcoin.org/bitcoin.pdf, accessed: 18 May 2024 (2008).
- [2] C. Casey, Ordinals: A new way to create and transfer nfts on bitcoin, https://example.com/ordinals-on-bitcoin, accessed: 18 May 2024 (2023).
- [3] A. J. Wright, The rise of decentralized autonomous organizations: Opportunities and challenges, Stanford Journal of Blockchain Law & PolicyAccessed: 18 May 2024 (2021).
- [4] Dapper Labs, Cryptokitties, https://www. cryptokitties.co/, accessed: 18 May 2024 (2017).
- [5] Dapper Labs, Nba top shot, https://www.nbatopshot. com/, accessed: 18 May 2024 (2021).

- [6] Yuga Labs, Bored ape yacht club, https:// boredapeyachtclub.com/, accessed: 18 May 2024 (2021).
- [7] R. Banach, Blockchain applications beyond the cryptocurrency casino: The punishment not reward blockchain architecture, Concurrency and Computation: Practice and Experience 33 (e5749) (2021).
- [8] T. Bayan, R. Banach, Exploring the privacy concerns in permissionless blockchain networks and potential solutions, in: 2023 IEEE International Conference on Smart Information Systems and Technologies (SIST), IEEE, 2023, pp. 567–572. doi:10.1109/SIST58284.2023.10223536.
- [9] E. Androulaki, A. Barger, V. Bortnikov, C. Cachin, K. Christidis, A. De Caro, D. Enyeart, C. Ferris, G. Laventman, Y. Manevich, et al., Hyperledger fabric: A distributed operating system for permissioned blockchains, in: Proceedings of the Thirteenth EuroSys Conference, 2018, pp. 1–15. doi:10.1145/3190508.3190538.
- [10] T.-T. Kuo, P. Zhang, Blockchain-based collaborative edge computing: efficiency, incentive and trust, Journal of Cloud Computing (2023). doi:10.1186/s13677-023-00357-8.
- [11] P. Zhang, T.-T. Kuo, Editorial: Blockchain and distributed ledger technology—enabled architectures for improving healthcare, Frontiers in Blockchain (2023). doi:10. 3389/fbloc.2023.00017.
- [12] D. Yermack, A systematic review of blockchain, Financial Innovation (2023). doi:10.1186/s40854-023-00479-9.
- [13] S. Wang, W. Ding, J. Li, Y. Yuan, L. Ouyang, F.-Y. Wang, Decentralized autonomous organizations: Concept, model, and applications, IEEE Transactions on Computational Social Systems 6 (5) (2019) 870–878. doi:10.1109/TCSS.2019. 2938190.
- [14] Y. Hsieh, J.-P. Vergne, P. Anderson, K. Lakhani, M. Reitzig, Bitcoin and the rise of decentralized autonomous organizations, Journal of Organization Design 7 (1) (2018) 1–16. doi:10.1186/s41469-018-0038-1.
- [15] J. Weng, H. Jin, S. Yan, Non-fungible tokens (nfts): Early thoughts and a research agenda, SSRN Electronic Journal (2023).
- [16] H. Taherdoost, A review of the key challenges of non-fungible tokens, ScienceDirect (2023).
- [17] U. Khalil, O. A. Malik, O. W. Hong, M. Uddin, Dscot: An nft-based blockchain architecture for the authentication of iotbased smart devices in smart cities, IEEE Access 11 (2023) 16114–16125.
- [18] S. Barman, S. Chattopadhyay, D. Samanta, S. Barman, A blockchain-based approach to secure electronic health records using fuzzy commitment scheme, Security and Privacy 5 (4) (2022) e231. doi:10.1002/spy2.231.