A dissimilarity measure for semidirected networks

Michael Maxfield¹, Jingcheng Xu¹, Cécile Ané^{1,2}

Abstract-Semidirected networks have received interest in evolutionary biology as the appropriate generalization of unrooted trees to networks, in which some but not all edges are directed. Yet these networks lack proper theoretical study. We define here a general class of semidirected phylogenetic networks, with a stable set of leaves, tree nodes and hybrid nodes. We prove that for these networks, if we locally choose the direction of one edge, then globally the set of paths starting by this edge is stable across all choices to root the network. We define an edge-based representation of semidirected phylogenetic networks and use it to define a dissimilarity between networks, which can be efficiently computed in near-quadratic time. Our dissimilarity extends the widely-used Robinson-Foulds distance on both rooted trees and unrooted trees. After generalizing the notion of treechild networks to semidirected networks, we prove that our edgebased dissimilarity is in fact a distance on the space of tree-child semidirected phylogenetic networks.

Index Terms—phylogenetic, admixture graph, Robinson-Foulds, tree-child, μ -representation, ancestral profile

I. INTRODUCTION

ISTORICAL relationships between species, virus strains or languages are represented by phylogenies, which are rooted graphs, in which the edge direction indicates the flow of time going forward. Semidirected phylogenetic networks are to rooted networks what undirected trees are to rooted trees. They appeared recently, following studies showing that the root and the direction of some edges in the network may not be identifiable, from various data types [25, 3]. Consequently, several methods to infer phylogenies from data aim to estimate semidirected networks, rather than fully directed networks, such as SNaQ [25], NANUQ [1], admixtools2 [21], poolfstat [10], NetRAX [20], and PhyNEST [16].

The theoretical identifiability of semidirected networks is receiving increased attention [11, 22, 30, 2] but graph theory is still at an early stage for this type of networks [but see 19]. In particular, adapted distance and dissimilarity measures are lacking, as are tools to test whether two phylogenetic semidirected networks are isomorphic. These tools are urgently needed for applications. For example, when an inference method is evaluated using simulations, its performance is quantified by how often the inferred network matches the true network used to simulate data, or how similar the inferred networks would also help summarize a posterior sample of networks output by Bayesian inference methods. Even for a basic summary such as the posterior probability of a given topology, we need to decide which semidirected networks are isomorphic, in a potentially very large posterior sample of networks.

Unless additional structure is assumed, current methods appeal to a naive strategy that considers all possible ways to root semidirected networks, and then use methods designed for directed networks, e.g. to check if the candidate rooted networks are isomorphic or to minimize a dissimilarity between the two rooted networks across all possible root positions.

In this work, we first generalize the notion of semidirected phylogenetic networks in which edges are either of tree type or hybrid type, such that any edge can be directed or undirected. We relax the constraint of a single root (of unknown position). Multi-rooted phylogenetic networks were recently introduced, although for directed networks, to represent the history of closely related and admixted populations [26] or distant groups of species that exchanged genes nonetheless [13]. Our general definition requires care to define a set of leaves consistent across all compatible directed phylogenetic networks.

For these semidirected networks, we define an edgebased " μ -representation" μ_E , extending the node-based μ representation, denoted here as μ_V , by Cardona et al. [7]. The "ancestral profile" of a rooted network is a data structure equivalent to its node-based representation μ_V [5], so that our edge-based representation μ_E also extends the notion of ancestral profile to semidirected networks, in which ancestral relationships are unknown between some nodes because the root is unknown. Briefly, μ_E 's information for an edge depends on whether the edge direction is known or implicitly constrained by the direction of other edges in the network. For example, if N is a semidirected tree and an edge is explicitly or implicitly directed, then μ_E associates the edge to the cluster of taxa below it. If instead the edge direction depends on the unknown placement of the root(s), then μ_E associates the edge to the bipartition of the taxa obtained by deleting the edge from the semidirected tree. If N has reticulations, μ_V uses μ -vectors to generalize the notion of clusters, storing the number of directed paths from a given node to each taxon. Our extension μ_E associates a directed edge to the μ -vector of its child node, and an undirected edge to two μ -vectors: one for each direction that the edge can take. To handle and distinguish semidirected networks with multiple roots, μ_E also associates each root to a μ -vector, well-defined even when the exact root position(s) are unknown. We then define a dissimilarity measure d_{μ_E} between semidirected networks.

Our network representation μ_E can be calculated in polynomial time, namely $\mathcal{O}(n|E|)$ where *n* is the number of leaves and |E| is the number of edges. The associated network dissimilarity d_{μ_E} can then be calculated in $\mathcal{O}(|E|(n+\log |E|))$ time. It provides the first dissimilarity measure adapted to

This work has been submitted to the IEEE for possible publication. Copyright may be transferred without notice, after which this version may no longer be accessible.

¹ Department of Statistics, University of Wisconsin - Madison, USA.

² Department of Botany, University of Wisconsin - Madison, USA.

semidirected networks (without iteratively network re-rooting) that can be calculated in polynomial time. Linz and Wicke [19] also recently considered semidirected networks (with a single root of unknown position). They showed that "cut edge transfer" rearrangements, which transform one network into another, define a finite distance on the space of level-1 networks with a fixed number of hybrid nodes. This distance is NP-hard to compute, however, because it extends the subtree prune and regraft (SPR) distance on unrooted trees [12].

Finally, we generalize the notion of tree-child networks to semidirected networks, and prove that d_{μ_E} is a true distance on the subspace of tree-child semidirected networks, extending the result of [7] to semidirected networks using an edge-based representation. On trees, this dissimilarity equals the widely used Robinson-Foulds distance between *unrooted* trees [24]. We provide concrete algorithms to construct μ_E from a given semidirected network, and to reconstruct the network from μ_E .

As a proper distance, d_{μ_E} can decide in polynomial time if two tree-child semidirected networks are isomorphic. For rooted phylogenetic networks, the isomorphism problem is polynomially equivalent to the general graph isomorphism problem, even if restricted to tree-sibling time-consistent rooted networks [8]. As semidirected networks include singlerooted networks, the graph isomorphism problem for semidirected networks is necessarily more complex. The general graph isomorphism problem was shown to be of subexponential complexity [4] but is not known to be solvable in polynomial time. Therefore, there is little hope of finding a dissimilarity that can be computed in polynomial time, and that is a distance for general semidirected phylogenetic networks. Hence, dissimilarities like d_{μ_E} offer a balance between computation time and the extent of network space in which it can discriminate between distinct networks.

II. BASIC DEFINITIONS FOR SEMIDIRECTED GRAPHS

For a graph G we denote its vertex set as V(G) and its edge set as E(G). The subgraph induced by a subset of vertices $V' \subseteq V(G)$ is denoted as G[V'], and the edge-induced subgraph is denoted as G[E'] for a subset $E' \subseteq E(G)$.

We use the following terminology for a directed graph G =(V, E). For a node v, its *in-degree* is denoted as deg_i(v, G)and out-degree as deg_o(v, G). Its total degree deg(v, G) is $\deg_i(v, G) + \deg_o(v, G)$. We may omit G when no confusion is likely. For $u, v \in V$, we write u > v if there exists a path $u \rightsquigarrow v$. A node v is a *leaf* if deg_o(v) = 0; v is an *internal* node otherwise. We denote the set of leaves as $V_L(G)$. A node v is a root if $\deg_i(v) = 0$; a tree node if $\deg_i(v) \le 1$; and a hybrid node otherwise. We denote the set of tree nodes as V_T and the set of hybrid nodes as V_H . An edge $(u, v) \in E$ is a tree edge if v is a tree node; a hybrid edge otherwise. We denote the set of tree edges as E_T and the set of hybrid edges as E_H . A descendant of v is any node u such that v > u. A tree path is a path consisting only of tree edges. A tree descendant of v is any node u such that there exists a tree path $v \rightsquigarrow u$. An *elementary path* is a path such that the first node has out-degree 1, and all intermediate nodes have in- and out-degree 1.



Fig. 1. N_1 is compatible with both N_2 and N_3 . N_1 is phylogenetically compatible with N_2 but not with N_3 , because N_3 contains one more hybrid node and 2 more hybrid edges: e and e' are tree edges in N_1 but hybrid edges in N_3 . Directed edges (E_D) are shown with arrows; hybrid edges (E_H) in blue.

We now extend these notions to semidirected graphs.

Definition 1 (semidirected graph). A semidirected graph N is a tuple N = (V, E), where V is the set of vertices, and $E = E_U \sqcup E_D$ is the set of edges, E_U being the set of undirected edges and E_D the set of directed edges.

Undirected edges in E_U are denoted as uv for some $u, v \in V$. Directed edges in E_D are denoted as (u, v) for some $u, v \in V$, implying the direction from u to v, with u referred to as the *parent* of the edge, and v as its *child*. A directed graph is a semidirected graph with no undirected edges: $E_U = \emptyset$.

For $v \in V(N)$, $\deg_i(v, N)$ denotes the number of directed edges with v as their child, $\deg_o(v, N)$ the number of directed edges with v as their parent, $\deg_u(v, N)$ the number of undirected edges in N incident to v, and $\deg = \deg_i + \deg_o + \deg_u$. We may omit N when no confusion is likely. Furthermore, $\operatorname{child}(v, N) = \{w \in V : (v, w) \in E_D\}.$

A semidirected graph N' = (V, E') is *compatible* with another semidirected graph N = (V, E) if N' can be obtained from N by directing some undirected edges in N.

The contraction of N, denoted as Cont(N), is the directed graph obtained by contracting every undirected edge in N. For $v \in V(N)$, Cont(v, N) is defined as the node in Cont(N) which v gets contracted into.

In a semidirected graph N, a node $v \in V(N)$ is a root if it only has outgoing edges. It is a *tree node* if $\deg_i(v, N) \leq 1$. Otherwise, v is called a *hybrid node*. The set of tree nodes is denoted as V_T or $V_T(N)$ and the set of hybrid nodes as V_H or $V_H(N)$. A *tree edge* is an undirected edge, or a directed edge whose child is a tree node. A *hybrid edge* is a directed edge whose child is a hybrid node. We denote the set of tree edges as E_T or $E_T(N)$ and the set of hybrid edges as E_H or $E_H(N)$.

A semidirected *cycle* is a semidirected graph that admits a compatible directed cycle. A semidirected graph is *acyclic* if it does not contain a semidirected cycle. We refer to directed acyclic graphs as DAGs and to semidirected acyclic graphs as SDAGs.

Next, we define a more stringent notion of compatibility to maintain the classification of nodes and edges as being of tree versus hybrid type, illustrated in Fig. 1.

Definition 2 (phylogenetically compatible, rooted partner, network). An SDAG N' is phylogenetically compatible with



Fig. 2. Example networks. Directed edges are shown with arrows, hybrid edges in blue, and edges in root components (E_R) in brown. Both networks have 2 root components. In N', one root component is trivial, composed of a single node (dot). In N, if d serves as root to obtain a rooted partner G, then G is not tree-child, therefore N is not tree-child. N' is tree-child. In N, only c and h are rooted leaves, and a, b, d, g are ambiguous leaves. N' satisfies $V_{UL}(N') = V_{RL}(N')$.

another SDAG N if N' is compatible with N and $E_H(N') = E_H(N)$. A rooted partner of N is a DAG that is phylogenetically compatible with N. A multi-root semidirected network, or network for short, is an SDAG that admits a rooted partner.

Note that if SDAG N' is phylogenetically compatible with SDAG N, then $V_T(N) = V_T(N')$ and $V_H(N) = V_H(N')$.

Not all SDAGs are networks. For example, the graph on $V = \{u, v, w\}$ with edges (u, v), (u, w) and vw is an SDAG but not a network. We are interested in networks because they represent evolutionary history up to "rerooting".

Traditionally, phylogenetic trees and networks are connected and with a single root [27]. We consider here a broader class of graphs, allowing for multiple connected components and multiple roots per connected component. We also allow for non-simple graphs, that is, for multiple parallel edges between the same two nodes u and v, directed and in the same direction for the graph to be acyclic. With a slight abuse of notation, we keep referring to each parallel edge as (u, v). Self-loops are not allowed as they would cause the graph to be cyclic. The term "rooted partner" was introduced by Linz and Wicke [19] in the context of traditional semidirected phylogenetic networks in which the set of directed edges is precisely the set of hybrid edges, and for which a rooted partner has a single root.

We will use the following results frequently. The first one is trivial.

Proposition 1. Let N be an SDAG phylogenetically compatible with SDAG N'. Then $E_D(N) \setminus E_D(N') \subseteq E_T(N)$.

Proposition 2. Let N be a network, and N' the semidirected graph obtained from N by undirecting some of the tree edges of N. Then N' is a network, and N is phylogenetically compatible with N'.

Proof. Let A be the set of tree edges in N that are undirected to obtain N'. By induction, we simply need to consider the case when A consists of a single edge (u, v). We shall establish the following claims:

- 1) N' is a network;
- the edges of N' in E(N)\A retains their type (undirected, tree, or hybrid);
- 3) N is phylogenetically compatible with N'.

3

For claim 1, suppose for contradiction that N' is not an SDAG. Then there exists in N' a semidirected cycle C which contains uv. Let G be a rooted partner of N, and C^+ the subgraph made of the corresponding edges in C. Since C^+ cannot be a directed cycle, there exist two hybrid edges (a, h) and (b, h) in C^+ . Both are also directed in N by phylogenetic compatibility. Because they are hybrid edges, they are distinct from (u, v), so they are directed in N' and C. This contradicts C being a semidirected cycle, showing that N' is an SDAG. Since it also admits G as a rooted partner, N' is a network.

Claim 2 follows from the observation that the types of nodes (tree vs hybrid) in N' stays the same. Claim 3 follows from claim 2.

The next definition is motivated by the fact that phylogenies are inferred from data collected at leaves, which are known entities with labels (individuals, populations, or species), whereas non-leaf nodes are inferred and unlabeled.

Definition 3 (unrooted and rooted leaves). A node $v \in V$ in a network N = (V, E) is a rooted leaf in N if v is a leaf in every rooted partner of N; and an unrooted leaf if it is a leaf in some rooted partner N. We denote the set of rooted leaves and unrooted leaves as $V_{RL}(N)$ and $V_{UL}(N)$ respectively. An ambiguous leaf is a node in $V_{UL}(N) \setminus V_{RL}(N)$.

Clearly, $V_{RL}(N) \subseteq V_{UL}(N)$. If N is directed, then $V_{RL}(N) = V_{UL}(N) = V_L(N)$. As we will see later in Lemma 12, an ambiguous leaf is of degree 1 in the undirected graph obtained by undirecting all edges in N, hence a leaf in the traditional sense. In Fig. 2 for example, a is an ambiguous leaf in N but not in N'.

In the next section we make no assumption regarding $V_{UL}(N)$ and $V_{RL}(N)$. We will later require $V_{UL}(N) = V_{RL}(N)$ in Definition 9, but we will see that this requirement is less stringent than it appears.

Our main result concerns the class of tree-child graphs. If G is a DAG, it is *tree-child* if every internal node v of G had at least one child that is a tree node [14]. We extend this notion to semidirected networks, illustrated in Fig. 2.

Definition 4 (**semidirected tree-child**). A network is *tree-child* if all its rooted partners are tree-child.

In Fig. 3, one but not all rooted partners of N_3 are tree child. Later in Proposition 11, we provide a characterization easy to check without enumerating rooted partners.

III. PROPERTIES OF SEMIDIRECTED ACYCLIC GRAPHS

Proposition 3. A semidirected graph N = (V, E) is acyclic if and only if the undirected graph induced by its undirected edges E_U is a forest, and Cont(N) is acyclic.

Proof. Let N be a semidirected graph. Suppose that $N[E_U]$ is not a forest. Then there exists a compatible directed graph of $N[E_U]$ which contains a cycle that exists in a compatible directed graph of N, therefore N is not acyclic. Next suppose that Cont(N) contains a cycle C'. Then there exists a compatible directed graph G of N which contains a cycle C such that C' is obtained from C after contracting edges in G that correspond to undirected edges in N, and so N is not acyclic.

Now suppose the graph induced by E_U is a forest and that $\operatorname{Cont}(N)$ is acyclic. If N is not acyclic, then by definition there exists a compatible directed graph G that contains a cycle C. Since $\operatorname{Cont}(N)$ is acyclic, C must contract into a single node in $\operatorname{Cont}(N)$. This implies that C contains undirected edges only, hence is contained in $N[E_U]$, a contradiction. Therefore N is acyclic.

In a network N, a semidirected path from u_0 to u_n is a sequence of nodes $u_0u_1 \ldots u_n$, such that for $i = 1, \ldots n$, either $u_{i-1}u_i$ or (u_{i-1}, u_i) is an edge in N. On V(N) we define $v \leq u$ if there is a semidirected path from u to v, and the associated equivalence relation: $u \sim v$ if $u \leq v$ and $v \leq u$. On equivalence classes, \leq becomes a partial order.

Definition 5 (root component, directed part). In a network N, an *undirected component* is the subgraph induced by an equivalence class under \sim . A *root component* of N is a maximal undirected component under \leq . The set of edges and nodes that are not in a root component is called the *directed part* of N. We denote the set of nodes in the directed part as $V_{DP}(N)$ and the set of edges $E_{DP}(N)$. We also denote the set of nodes in root components $V_R(N)$ and the set of edges $E_R(N)$.

The directed part of N is generally not a subgraph: it may contain an edge but not one of its incident nodes. The following result justifies the name given to the equivalence classes.

Proposition 4. For u, v nodes in a network N, $u \sim v$ if and only if there is an undirected path between u and v.

Proof. Consider u and v connected by an undirected path. Since this path does not contain any directed edge, clearly, $u \leq v$ and $v \leq u$, hence $u \sim v$.

Now suppose $u \sim v$. By definition, there exist a semidirected path $p_{uv} = u_0 u_1 \dots u_n$ from $u = u_0$ to $v = u_n$ and a semidirected path p_{vu} from v to u. If $p_{vu} = u_n u_{n-1} \dots u_0$ then all edges in these paths must be shared and undirected. (This is because N is acyclic, in case p_{uv} and p_{vu} have distinct edges incident to u_i and u_{i+1} .), Then, there is an undirected path between u and v as claimed. Otherwise, there exists $i_1 \geq 0$ and $i_2 > i_1 + 1$ such that p_{vu} is the concatenation of semidirected paths $u_n u_{n-1} \dots u_{i_2}$; $p_{u_{i_2} u_{i_1}}$ from u_{i_2} to u_{i_1} not containing any u_j for $i_1 < j < i_2$; and $u_{i_1} u_{i_1-1} \dots u_0$. Then, the concatenation of $p_{u_{i_2} u_{i_1}}$ with $u_{i_1} u_{i_1+1} \dots u_{i_2}$ forms a semidirected cycle. Since N is acyclic, this case cannot occur.

We now characterize undirected components as the undirected trees in the forest induced by N's undirected edges.

Proposition 5. Let N be a network and F the graph induced by the undirected edges of N. Then F is a forest where:

- 1) each tree corresponds to an undirected component of N, and has at most one node v with $\deg_i(v, N) \ge 1$;
- 2) the root components of N are exactly the trees without such nodes, and they contain tree nodes only.

Proof. By Proposition 3, F is a forest. By Proposition 4, each tree in F is an undirected component. If a tree T in F had more

4

than one node v with $\deg_i(v, N) \ge 1$, it would be impossible to direct the edges in T without making one of them hybrid, contradicting the existence of a rooted partner of N.

For the second claim, let T be a tree in F. Note that $(u, v) \in E_D$ implies that $u \not\sim v$ and v's equivalence class is not maximal. So if T is maximal, then all nodes v in T have $\deg_i(v, N) = 0$, which implies that v is a tree node. Conversely, if T is not maximal, then there exist nodes v in $T, u \gtrsim v$ in a different tree of F, and a semidirected path from u to v containing a directed edge. Taking the last directed edge on this path gives a node v' in T with $\deg_i(v', N) \ge 1$. \Box

Lemma 6. Let N be a network and G a rooted partner of N. Let $v \in V_R(N)$. If v < u in G, then $u \in V_R(N)$.

Proof. Let v < u in G. Then $v \leq u$ in N. By Definition 5, $u \leq v$ in N as well. Therefore, u belongs to the same root component as v, hence $u \in V_R(N)$.

Proposition 7. Let N be a network. Let G_1 and G_2 be rooted partners of N. Then edges in $E_{DP}(N)$ have the same direction in G_1 and G_2 .

Proof. Let T be an undirected component of N that is not a root component. We need to show that T's edges have the same direction in G_1 and G_2 . By Proposition 5, T is an undirected tree in N, and has exactly one node v_0 with an incoming edge in N. Then v_0 must be the root of T in both G_1 and G_2 , for G_1 and G_2 to be phylogenetically compatible with N, which completes the proof.

Definition 6. Let N be a network, and \mathcal{R} be the set of root components of N. A root choice function of N is a function $\rho : \mathcal{R} \to V(N)$ such that for a root component $T \in \mathcal{R}$, $\rho(T) \in V(T)$. In other words, ρ chooses a node for each root component.

Root choice functions are in one-to-one correspondence with rooted partners:

Proposition 8. Given a root choice function ρ of a network N, there exist a unique rooted partner N_{ρ}^+ of N such that the set of roots in N_{ρ}^+ is the image of ρ . Conversely, given any rooted partner G of N, there exists a unique root choice function ρ such that $G = N_{\rho}^+$.

Proof. Let G_0 be a rooted partner of N. For a root choice function ρ , let N_{ρ}^+ be the graph compatible with N obtained by directing edges in $E_{DP}(N)$ as they are in G_0 , and away from $\rho(T)$ in any root component T (which is possible by Proposition 5). N_{ρ}^+ is a DAG because N is acyclic. To prove that N_{ρ}^+ is phylogenetically compatible with N (and hence a rooted partner), we need to show that $E_H(N_{\rho}^+) = E_H(G_0)$. Since all edges in N incident to both $V_R = V_R(N)$ and $V_{DP} =$ $V_{DP}(N)$ are directed from V_R to V_{DP} , they have the same direction in N_{ρ}^+ and G_0 . Therefore nodes in V_{DP} and edges in $E_{DP}(N)$ are of the same type in N_{ρ}^+ and G_0 (and N). Furthermore, by construction and Proposition 5, all edges in $E_R(N)$ remain of tree type in both N_{ρ}^+ and G_0 . Hence N_{ρ}^+ is a rooted partner of N. Finally, the root set of N_{ρ}^+ is the image of ρ because a root component's root is a root of the full network (from $\deg_i(v, N) = 0$ for any $v \in V_R$) and because V_{DP} cannot contain any root of N_{ρ}^+ (by Proposition 5 again).

To prove that N_{ρ}^+ is unique, let G be a rooted partner of N whose set of roots is the image of ρ . By Proposition 7, edges in $E_{DP}(N)$ have the same direction in G and N^+ . For a root component T, $G[V(T)] = N_{\rho}^+[V(T)]$ because T is an undirected tree in N, rooted by the same $\rho(T)$ in both G and N_{ρ}^+ . Therefore $G = N_{\rho}^+$. Let G be a rooted partner of N. By Proposition 5 and

Let G be a rooted partner of N. By Proposition 5 and phylogenetic compatibility, G must have exactly one root in each root component T. Define ρ such that $\rho(T)$ is this root of G in T. By the arguments above, G cannot have any root in V_{DP} , and then $G = N_{\rho}^+$.

We can define the following thanks to Proposition 7:

Definition 7 (network completion). The completion $\mathcal{C}(N)$ of a network N is the semidirected graph obtained from N by directing every undirected edge in its directed part, as it is in any rooted partner of N. More precisely, let G by a rooted partner of N. We direct $uv \in E_{DP}(N)$ as (u, v) in $\mathcal{C}(N)$ if $(u, v) \in E(G)$. A network N is complete if $\mathcal{C}(N) = N$.

Proposition 9. For a network N, C(N) is a network and phylogenetically compatible with N.

Proof. From Proposition 8, any rooted partner of N is of the form N_{ρ}^+ . As seen in the proof of Proposition 8, $\mathcal{C}(N)$ and N_{ρ}^+ differ in root components only: if $e \in E_R(N)$ then e is undirected in N and in $\mathcal{C}(N)$, directed in N_{ρ}^+ , and is a tree edge in all. Therefore $\mathcal{C}(N)$ is phylogenetically compatible with N and is a network (admitting N_{ρ}^+ as rooted partner). \Box

Remark 1. Propositions 5 and 8 yield practical algorithms. Finding the root components requires only traversing the network N, tracking the forest F of undirected components, and which nodes have nonzero in-degree. Computing $\mathcal{C}(N)$ then consists in directing the edges away from such a node in each tree of F, if one exists. In particular, in a single traversal of N we can construct a rooted partner G, record the roots of G, record the edges of G that were in root components of N, and for each such edge record the corresponding root. To do this, for each tree T in F that is a root component, we arbitrarily choose and record a node u as root, direct the edges in T away from u, record these edges as belonging to a root component of N, and for all these edges record u as the corresponding root. We then direct the rest of the undirected edges the same way as when computing the completion. We shall use this in Algorithm 1 later.

With as many directed edges as can be possibly implied by the directed edges in N, C(N) is the network that we are generally interested in. We define phylogenetic isomorphism between networks based on their completion.

Definition 8 (network isomorphism). Let N and N' be networks. Then N and N' are phylogenetically isomorphic, denoted by $N \cong N'$, if there exists a renaming bijection between nodes such that C(N) = C(N').

For example, N_1 , N_2 and N_3 from Fig. 3 are phylogenetically isomorphic (N_2 is complete), but are not phylogenetically isomorphic to N_1 from Fig. 1.



Fig. 3. Example of network completion: $N_2 = C(N_1)$, and N_3 would be complete if the edge indident to *a* were directed towards *a*. Directed edges are shown with arrows, hybrid edges in blue. N_1 , N_2 and N_3 all have one root component (in brown). N_3 has two rooted partners: one that is tree-child (rooted at *u*) and one that is not (rooted at *v*, such that *u* has no tree child).

Lemma 10. Let N be a complete network. There exists a directed edge (u, v) in N if and only if $v \in V_{DP}(N)$.

Proof. If $v \in V_{DP}(N)$, its undirected component U has no undirected edges by Definition 7. Then by Proposition 5, $U = \{v\}$ and $\deg_i(v) \ge 1$, so v is the child of some directed edge. Conversely, if there exists $(u, v) \in E(N)$ then v's equivalence class is not maximal and $v \in V_{DP}(N)$.

Using C(N), we can now decide if a network is tree-child in a single network traversal, thanks to the following.

Proposition 11. Let N be a network, and W the set of nodes consisting of:

1) $u \in V_R(N)$ with $\deg_o(u) > 0$ and $\deg_u(u) \le 1$; and 2) $u \in V_{DP}(N)$ with $\deg_o(u) > 0$.

Then N is tree-child if and only if each node u in W has a tree child in C(N).

Recall that children are defined using directed edges only. If N is a DAG, then W consists of all internal nodes and we simply recover the tree-child definition.

Proof. Suppose N is tree-child and let $u \in W$. If $u \in V_R(N)$ and $\deg_u(u) = 1$, let G be a rooted partner of N where u is a not a root, otherwise let G be any rooted partner. Then u has a tree child v in G. We claim that (u, v) in G corresponds to an edge in $E_{DP}(N)$: if $u \in V_R(N)$ then $v \in V_{DP}(N)$; otherwise $u \in V_{DP}(N)$. Then u has v as a tree child in C(N).

Conversely, suppose each node W has a tree child in C(N). Let G be a rooted partner of N. Since G is phylogenetically compatible with C(N), any node in W already has a tree child in G. The other internal nodes in G can be of the form:

- 1) $u \in V_R(N)$ is an isolated leaf, or must be adjacent to some $v \in V_R(N)$ that is its tree child in G; or
- u ∈ V_{DP}(N) with deg_o(u) = 0: then any (u, v) in G corresponds to a tree edge in N, so u has a tree child in G.

Therefore G is tree-child; and then N is tree-child.

Finally, we characterize unambiguous leaves, which will be useful for guaranteeing that all leaves of any rooted partner are labeled.

Lemma 12. In a network N, v is an ambiguous leaf if and only if $v \in V_R(N)$, deg_u(v) = 1, and deg_o(v) = deg_i(v) = 0. *Proof.* Let v be an ambiguous leaf. Then $\deg_o(v) = 0$. By Proposition 7, v is in $V_R(N)$ so $\deg_i(v) = 0$. Finally, if $\deg_u(v) = 0$, then v is isolated, and a rooted leaf. If $\deg_u(v) \ge 2$, then in any rooted partner one of the incident edges is directed away from v, and v is never a leaf. Therefore $\deg_u(v) = 1$.

Conversely, let $v \in V_R(N)$ be incident to exactly one edge, uv. By Proposition 8, we can find a rooted partner where v is a non-leaf root as well as a rooted partner where u is a root and v is a leaf. Hence v is an ambiguous leaf.

IV. VECTORS AND REPRESENTATIONS

Formally a multiset is a tuple (A, m), where A is a set and $m: A \to \mathbb{Z}^+$ gives the multiplicity. We adopt the standard notion of sum and difference for multisets. We identify multisets (A, m_A) and (B, m_B) as long as $m_A|_{A \setminus B} = 0$, $m_B|_{B \setminus A} = 0$, and $m_A|_{A \cap B} = m_B|_{A \cap B}$. To simplify notations, we also use \bigcup to denote a multiset by enumerating each element as many times as its multiplicity. For example, $A = \lfloor a, a, b \rfloor$ contains a with multiplicity 2 and b with multiplicity 1. For brevity, we identify a multiset (A, m) with the set A if $m \equiv 1$, e.g. $\lfloor a, b, c \rfloor = \{a, b, c\}$.

In what follows, we consider a vector of distinct labels \mathcal{L} , whose order is arbitrary but fixed, as it will determine the order of coordinates in all μ vectors and representations. An \mathcal{L} -DAG is a DAG whose leaves are bijectively labeled by \mathcal{L} . For an \mathcal{L} -DAG G and for node $v \in V(G)$, the μ -vector of v is defined as the tuple $\mu(v, G) = (\mu_1(v), \dots, \mu_n(v))$ where n is the number of labels in \mathcal{L} and $\mu_i(v)$ is the number of paths in G from v to the leaf with the i^{th} label in \mathcal{L} . As in [7], the partial order \geq between μ -vectors is the coordinatewise order, i.e. $(m_1, \ldots, m_n) \ge (m'_1, \ldots, m'_n)$ if $m_i \ge m'_i$ for all $i = 1, \ldots, n$. The node-based μ -representation of G from [7], denoted as $\mu_V(G)$, is defined as the multiset $\mu(v,G); v \in$ V(G) Algorithm 1 in [7] computes $\mu_V(G)$ recursively in post-order thanks to the following property, which is a slight extension of Lemma 4 in [7] allowing for parallel edges by summing over child edges instead of child nodes.

Lemma 13. Let G be a DAG and u a node in G. Then

$$\mu(u,G) = \sum_{v \in \operatorname{child}(u,G)} \sum_{(u,v) \in E(G)} \mu(v,G)$$

We will make frequent use of the following result, whose original proof easily extends to DAGs with parallel edges thanks to Lemma 13.

Lemma 14 (Lemma 5 of [7]). Let G be a tree-child \mathcal{L} -DAG and u, v two nodes in G. We have the following:

- 1) If there exists a path $u \rightsquigarrow v$, then $\mu(u, G) \ge \mu(v, G)$.
- 2) If $\mu(u,G) > \mu(v,G)$, then there exist a path $u \rightsquigarrow v$.
- 3) If $\mu(u,G) = \mu(v,G)$, then u,v are connected by an elementary path.

Other results in [7] similarly hold when parallel edges are allowed, such as their Theorem 1 on tree-child networks (which must be non-binary if they have parallel edges).

To extend the μ -representation to semidirected graphs, we need to extend the definition of \mathcal{L} -DAGs.

Definition 9 (leaf-labeled network). A network N is labeled in \mathcal{L} and called an \mathcal{L} -network, if $V_{UL}(N) = V_{RL}(N)$ and $V_{UL}(N)$ is bijectively labeled by elements of \mathcal{L} . The leaf set of an \mathcal{L} -network N is defined as $V_L(N) = V_{UL}(N)$.

Two \mathcal{L} -networks N and N' are *phylogenetically isomorphic* if $N \cong N'$ with an isomorphism that preserves the leaf labels. For example, in Fig. 2 N' is an \mathcal{L} -network with $\mathcal{L} = \{a, b, c, d, g, h\}$, while N is not.

A rooted partner G of an \mathcal{L} -network N must be an \mathcal{L} -DAG: since $V_{RL}(N) \subseteq V_L(G) \subseteq V_{UL}(N)$ generally, we have that $V_L(G) = V_L(N)$ and $V_L(G)$ can inherit the labels in N.

We argue that requiring $V_{UL}(N) = V_{RL}(N)$ is reasonable in practice. By Lemma 12, an ambiguous leaf x is in a root component and incident to only one undirected edge. The ambiguity is whether x becomes a leaf or a root in a rooted partner. (By Proposition 8, at most one ambiguous leaf may root a root component in any given rooted partner.) In practice, one knows which nodes are supposed to be leaves, with a label and data. Then one can, for each root component, either direct all incident edges to ambiguous leaves towards them, making them rooted leaves (as in Fig. 2), or pick one ambiguous leaf to serve as root for that component and direct edges accordingly, turning the remaining ambiguous leaves into rooted leaves. This yields a network with $V_{UL} = V_{RL}$.

The rest of the section is organized as follows. In part IV-A we define the edge-based μ -representation for \mathcal{L} -networks, with Algorithm 1 to compute it. Part IV-B presents properties of this μ -representation for tree-child networks, and part IV-C describes how to reconstruct a complete tree-child \mathcal{L} -network from its edge-based μ -representation.

A. Edge-based μ -representation

Proposition 15. Let N be an \mathcal{L} -network, and $v \in V_{DP}(N)$. Then the set of paths starting at v, and consequently $\mu(v, G)$, are the same for any rooted partner G of N. We denote the latter by $\mu(v, N)$, extending the definition of μ -vector to nodes in the directed part of a network.

Proof. Let G be a rooted partner of N. Let $u_1 \ldots u_n$ $(n \ge 1)$, where $u_1 = v$, be a directed path starting at v in G. We claim $u_i, i = 1, \ldots, n$ are all in $V_{DP}(N)$: Otherwise, we can find i such that $u_i \in V_{DP}(N)$ and $u_{i+1} \in V_R(N)$. Since $(u_i, u_{i+1}) \in E(G)$, either $u_i u_{i+1}$ or (u_i, u_{i+1}) is in E(N). By Proposition 4, this implies either $u_i \in V_R(N)$ or $u_{i+1} \in$ $V_{DP}(N)$, a contradiction. Therefore any directed paths from v in G lies entirely in $G[V_{DP}(N)]$. The conclusion then follows from Proposition 7.

Proposition 16. Let N be an \mathcal{L} -network with $uv \in E_R(N)$. Then the set of paths starting at v, and consequently $\mu(v, G)$, are the same for any rooted partner G of N where uv is directed as (u, v), and there always exists such a rooted partner. We call $\mu(v, G)$ the directional μ -vector of (u, v), and write it as $\mu_d(u, v, N)$ or $\mu_d(u, v)$ if N is clear in the context.

Before the proof we establish a lemma.

Lemma 17. Let N be a network with uv an edge in some root component. Let N' be the semidirected graph obtained from N by directing uv as (u, v). Then N' is a network phylogenetically compatible with N.

Proof. Let G be a rooted partner of N where u is a root. Let $A = E(G) \setminus E(N)$ be the set of edges that are directed in G but not in N. By phylogenetic compatibility, A consists of tree edges only. A also contains (u, v).

Since from G we get back N' if we undirect all the edges in $A \setminus \{(u, v)\}$, by Proposition 2, G is phylogenetically compatible with N'. Then $E_H(N') = E_H(G) = E_H(N)$ and N' is phylogenetically compatible with N.

Proof of Proposition 16. The existence of a rooted partner where uv is directed as (u, v) follows from Proposition 8.

Let G_1 and G_2 be rooted partners of N such that uv is directed as (u, v) in both. Let N' be the semidirected graph obtained from N by directing uv as (u, v). By Lemma 17, N' is a network phylogenetically compatible with N. Thus, G_1 and G_2 are rooted partners of N'. Since $\deg_i(v, N') \ge 1$, $v \in V_{DP}(N')$ by Proposition 5. The conclusion then follows from Proposition 15.

Lemma 18. Let N be an \mathcal{L} -network, and T a root component of N. Then the μ -vector $\mu(\rho(T), N_{\rho}^{+})$ is independent of the root choice function ρ . We call this vector the root μ -vector of T and write it as $\mu_r(T, N)$ or $\mu_r(T)$ if N is clear from context. Furthermore, if uv is an edge in T, then $\mu_r(T) =$ $\mu_d(u, v) + \mu_d(v, u)$.

Proof. The claims obviously hold when T is trivial. Now consider T non-trivial and distinct nodes $u \neq v$ in T. Let G_u (resp. G_v) be a rooted partner of N where u (resp. v) is a root. To prove the first claim, we show that $\mu(u, G_u) = \mu(v, G_v)$ by constructing a bijection f_u between \mathcal{P}_u and \mathcal{P}_v , where \mathcal{P}_z (z = u, v) is the set of directed paths from z to x in G_z , for an arbitrary but fixed leaf x of N. Suppose $p_u = u \dots w \dots x \in \mathcal{P}_u$, where w is the last node such that $u \dots w$ lies in T. We can modify p_u to a new path p_v by changing the $u \dots w$ subpath to $v \dots w$, the unique tree path between v and w in T. By Lemma 6, the subpath $w \dots x$ only contain edges in $E_{DP}(N)$. Then by Proposition 7, $p_v \in \mathcal{P}_v$. Obviously, f_u is a bijection whose inverse is the map from \mathcal{P}_v to \mathcal{P}_u constructed by symmetry, proving the first claim.

For the second claim, let uv be an edge in T and x, G_u , G_v , \mathcal{P}_u and \mathcal{P}_v as before. Let \mathcal{P}_u^v be the set of directed paths from v to x in G_u , such that $|\mathcal{P}_u^v|$ is the coordinate for x in $\mu_d(u, v)$. Define \mathcal{P}_v^u similarly. We can partition $\mathcal{P}_u = A \sqcup B$ where paths in A contain v, and paths in B do not. It is easily verified that $B = \mathcal{P}_v^u$, and that prepending u to a path gives a bijection $\mathcal{P}_u^v \to A$. Since x is arbitrary, we get $\mu_r(T) = \mu_d(u, v) + \mu_d(v, u)$.

We are now ready to define the edge-based μ -representation of an \mathcal{L} -network, and an algorithm to compute it.

Definition 10 (edge-based μ -representation). Let N be a complete \mathcal{L} -network. To edge e of N we associate a set $\mu(e)$, called the *edge* μ -vector set of the edge e, as follows:



Fig. 4. Networks illustrating the need to include the μ -vector of trivial root components in Definition 10, to distinguish networks with multiple roots. N and N' are tree-child and non-isomorphic. They have the same multiset of edge μ -vector sets, but different root μ -vectors so $\mu_E(N) \neq \mu_E(N')$.

- For e = (u, v), by Lemma 10 we have v ∈ V_{DP}, and we define μ(e) = {(μ(v, N), t)} where μ(v, N) is defined in Proposition 15, and t is a tag taking value :t if e is a tree edge, and :h otherwise.
- For $e = uv \in E_R$, we define $\mu(e) = \{(\mu_d(u, v), :\mathbf{t}), (\mu_d(v, u), :\mathbf{t})\}$ with μ_d as defined in Proposition 16.

Let \mathcal{R} the set of root components of N, then the *edge-based* μ -representation of N, denoted by $\mu_E(N)$, is defined as the multiset

$$\{\mu(e): e \in E(N) \} + \{ \{(\mu_r(T), :\mathbf{r})\} : T \in \mathcal{R} \}$$

with μ_r from Lemma 18. For an \mathcal{L} -network N', $\mu_E(N')$ is defined as $\mu_E(\mathcal{C}(N'))$.

For example, for N' in Fig. 2 on (a, b, c, d, g, h), $\mu_E(N')$ is

$$\begin{array}{l} \left\{ \left((1,0,0,0,0,0), :\mathbf{t} \right) \right\}, \dots, \left\{ \left((0,0,0,0,0,1), :\mathbf{t} \right) \right\}, \\ \left\{ \left((0,0,0,0,0,1), :\mathbf{h} \right) \right\}, \ \left\{ \left((0,0,1,0,0,1), :\mathbf{h} \right) \right\}, \\ \left\{ \left((0,0,0,0,0,1), :\mathbf{h} \right) \right\}, \ \left\{ \left((0,0,1,0,0,1), :\mathbf{h} \right) \right\}, \\ \left\{ \left((1,1,0,0,0,0), :\mathbf{t} \right), \left((0,0,2,0,1,2), :\mathbf{t} \right) \right\}, \\ \left\{ \left((1,1,1,0,0,1), :\mathbf{t} \right), \left((0,0,1,0,1,1), :\mathbf{t} \right) \right\}, \\ \left\{ \left((1,1,2,0,1,2), :\mathbf{r} \right) \right\}, \ \left\{ \left((0,0,0,1,0,1), :\mathbf{r} \right) \right\}, \end{array} \right\}$$

Algorithm 1 Given \mathcal{L} -network N, compute its edge-based μ -representation $A = \mu_E(N)$

1: compute a rooted partner G of N, and store:

- R the set of roots in G
- ρ: V_R(N) → R the function that maps a node in a root component T of N to the root of T in G
- E_R⁺ the set of edges in G that corresponds to E_R(N)
 E_{DP}⁺ = E(G) \ E_R⁺
- compute the node-based μ-representation of G, let μ = μ_V(·, G)

3: $A_1 \leftarrow \{(\mu(v), :\mathbf{t})\} : (u, v) \in E_{DP}^+ \cap E_T(G)\}$ 4: $A_2 \leftarrow \{(\mu(v), :\mathbf{h})\} : (u, v) \in E_{DP}^+ \cap E_H(G)\}$ 5: $A_3 \leftarrow \{(\mu(r), :\mathbf{r})\} : r \in R\}$ 6: $A_4 \leftarrow \{(\mu(v), :\mathbf{t}), (\mu(\rho(v)) - \mu(v), :\mathbf{t})\} : (u, v) \in E_R^+\}$ 7: return $A = A_1 + A_2 + A_3 + A_4$

Compared to the node-based representation μ_V , μ_E has two features. Unsurprisingly, each undirected edge (whose direction is not resolved by completion) is represented as bidirectional using two μ vectors. This is similar to the representation of edges in unrooted trees, as bipartitions of \mathcal{L} . The second feature is the inclusion of a μ -vector for each root component, which may seem surprising. For a non-trivial root component T, $\mu_r(T)$ is redundant with information from $\mu(e)$ for any e in T, by Lemma 18. The purpose of including the root μ -vectors in $\mu_E(N)$ is to keep information from trivial root components, for networks with multiple roots. Without this information, μ_E cannot discriminate simple networks with multiple roots when one or more root component is trivial, as illustrated in Fig. 4.

Networks with a unique and non-trivial root component correspond to standard phylogenetic rooted networks, with uncertainty about the root location. For these networks, we could use edge μ -vectors only: $\mu_E(N) = \langle \mu(e) : e \in E(N) \rangle$, that is, omit A_3 in Algorithm 1. Indeed, the root μ -vector of the unique root component T is redundant with $\mu(e)$ of any edge e in T. For this class of standard networks, then, our results below also hold using the simplified definition of μ_E .

Lemma 18 together with Proposition 5 yields Algorithm 1 to compute the edge-based μ -representation of an \mathcal{L} -network N = (V, E) with n leaves. As discussed in Remark 1, line 1 in Algorithm 1 takes a single traversal of N and $\mathcal{O}(|E|)$ time. Computing the node-based μ -representation by Algorithm 1 in [7] takes $\mathcal{O}(n|E|)$ time. The remaining steps iterate over edges and take $\mathcal{O}(n|E|)$ time, giving an overall complexity of $\mathcal{O}(n|E|)$.

B. Properties for tree-child networks

We will use the following results to reconstruct a tree-child network from its edge-based μ -representation.

Proposition 19. Let T_1 and T_2 be distinct nontrivial root components of a tree-child \mathcal{L} -network N. Then directional μ -vectors from T_1 and from T_2 are incomparable to one another.

Proof. Let $uu' \in E(T_1)$ and $vv' \in E(T_2)$. Suppose for contradiction that $\mu_d(u, u') \ge \mu_d(v, v')$. Let G be a rooted partner of N in which u and v are roots. Then $\mu_d(u, u') = \mu(u', G)$ and $\mu_d(v, v') = \mu(v', G)$. Since G is tree-child, there exists a path $u' \rightsquigarrow v'$ in G by Lemma 5 in [7]. Since (v, v') is a tree edge in G, by Lemma 1 in [7], $u' \rightsquigarrow v'$ contains or is contained in (v, v'). Both cases imply that $u' \in \{v, v'\}$ (using that v is a root for the first case), a contradiction.

Proposition 20. In a tree-child \mathcal{L} -network, different root components have incomparable root μ -vectors.

Proof. Let $T_1 \neq T_2$ be root components of a tree-child \mathcal{L} -network N. In a rooted partner of N, there is no directed path between the roots of T_1 and T_2 . Therefore, by Lemmas 14 and 18, $\mu_r(T_1)$ and $\mu_r(T_2)$ are incomparable.

Lemma 21. Let N be a tree-child \mathcal{L} -network. Suppose uv, st are two (not necessarily distinct) edges in root component T of N such that the tree path from u to t in T contains v and s. Then:

1) $\mu_d(u, v) \ge \mu_d(s, t)$,

2) $\mu_d(v, u)$ is not comparable to $\mu_d(s, t)$,

3) $\mu_d(u, v)$ is not comparable to $\mu_d(t, s)$.

Proof. Let G_u (resp. G_v) be a rooted partner of N with u (resp. v) as a root. For part 1, by Lemma 14, we have $\mu_d(u, v) = \mu(v, G_u) \ge \mu(t, G_u) = \mu_d(s, t)$.

For part 2, by symmetry, it suffices to show that $\mu_d(v, u) \not\leq \mu_d(s, t)$. Let w_1, \ldots, w_k be the neighbors of u besides v. Then $\mu(w_i, G_u) = \mu(w_i, G_v)$ by Proposition 15 if $w_i \in V_{DP}(N)$, or Proposition 16 if $w_i \in V(T)$. Then by Lemma 13 we have $\mu_d(v, u) = \mu(u, G_v) = \sum_{i=1}^k \sum_{(u, w_i) \in E(G_v)} \mu(w_i, G_v) = \sum_{i=1}^k \sum_{(u, w_i) \in E(G_v)} \mu(w_i, G_u)$.

First, suppose for contradiction that $\mu_d(v, u) < \mu_d(s, t) = \mu(t, G_u)$. Then for each i, $\mu(t, G_u) > \mu(w_i, G_u)$, and since G_u is tree-child there exists a path $t \rightsquigarrow w_i$ in G_u by Lemma 14. As u is a root in G_u and not contained in these paths, w_1, \ldots, w_k are hybrid nodes. Then u does not have a tree child in G_v , a contradiction.

Now suppose instead $\mu_d(v, u) = \mu_d(s, t) = \mu(t, G_u)$, then $\mu(t, G_u) \ge \mu(w_i, G_u)$ for all *i*. If $\mu(t, G_u) = \mu(w_i, G_u)$ for some *i*, then $w_i = w_1$ is the only neighbor of *u* other than *v*. By Lemma 14, *t* and w_1 are connected by an elementary path in G_u , which is impossible as both have *u* as a parent. Therefore $\mu(t, G_u) > \mu(w_i, G_u)$ for all *i*, which leads to a contradiction by the argument above.

Part 3 follows from part 2 using that $\mu_d(a, b) + \mu_d(b, a) = \mu_r(T)$ for any $ab \in E(T)$ by Lemma 18.

Lemma 22. Let N be a tree-child \mathcal{L} -network, and x a fixed μ -vector. If we direct all edges $uv \in E_R(N)$ with $\mu_d(u, v) = x$ as (u, v), then these edges form a directed path. If the path is nonempty, we denote the first node as h(x, N).

Proof. Let $E_x = \{uv \in E_R(N) : \mu_d(u, v) = x\}$. Take uvand st in E_x . By Proposition 19, they are in the same root component T, so there is a path p in T connecting uv and st. By Lemma 21, and permuting labels if necessary, we may assume p is of the form $uv \dots st$ with $\mu_d(u, v) = \mu_d(s, t) = x$. For a rooted partner G of N with u a root, we have $\mu(v, G) =$ $\mu(t,G) = x$, which implies by Lemma 14 there is an elementary path in G from v to t. By Lemma 6, this path lies in $E_R(N)$. But since $E_R(N)$ induces a forest, this elementary path must be the $v \dots st$ part of the path p. Therefore all the intermediate nodes w in p have $\deg_{u}(w, N) = 2$ and $\deg_i(w, N) = \deg_o(w, N) = 0$. Furthermore, if w_1 and w_2 are consecutive nodes in p, then $w_1w_2 \in E_x$ because $x = \mu(v,G) \ge \mu(w_2,G) = \mu_d(w_1,w_2) \ge \mu(t,G) = x.$ Therefore all edges in p are in E_x , and form a directed path when directed as in the statement.

Now take a path p_0 of edges in E_x , of maximum length, and let e one of its edges. To show that p_0 contains all the edges in E_x , take $e' \in E_x$. By the previous argument, e and e' are connected by a tree path p_1 . Also by the previous argument, all intermediate nodes in p_0 and in p_1 have $\deg_u = 2$. Since p_1 cannot extend p_0 by definition of p_0 , p_1 must be contained in p_0 , therefore e' is in p_0 as claimed.

Finally, the next result was proved for orchard networks, which include tree-child networks, in Proposition 10 of Cardona et al. [9]. We restrict its statement to hybrid nodes here, because we allow networks to have in and out degree-1 nodes.

Lemma 23. Let G be a tree-child \mathcal{L} -DAG. Let u, v be distinct hybrid nodes in G. Then $\mu(u, G) \neq \mu(v, G)$.

C. Reconstructing a complete tree-child network

To reconstruct a complete tree-child network N from its edge-based μ -representation, Algorithm 2 will first construct $\mu_V(G)$ for a rooted partner G from $\mu_E(N)$. Then Algorithm 3 will use $\mu_E(N)$ to undirect some edges in G and recover N.

Algorithm 2 Given $A = \mu_E(N)$ from a tree-child \mathcal{L} -network N, compute $B = \mu_V(G)$ for some rooted partner G of N

Input: multiset A

Output: multiset B 1: $B_1 \leftarrow \{x: \{(x, :\mathbf{t})\} \in A\}$ 2: $B_2 \leftarrow \{x \colon \{(x, :\mathbf{h})\} \in A\}$ 3: $B_3 \leftarrow \{x \colon \{(x, \mathbf{r})\} \in A\}$ 4: $B_4 \leftarrow \Im$ 5: for z in B_3 do $M(z) \leftarrow \Im x : \{(x, :\mathbf{t}), (z - x, :\mathbf{t})\} \in A$ 6: if M(z) is empty then skip to next iteration 7: 8: $r(z) \leftarrow$ some arbitrary element of M(z)for $\{(x_1, :\mathbf{t}), (x_2, :\mathbf{t})\} \in A$ with $x_1 + x_2 = z$ do 9: $B_4 \leftarrow B_4 + \eta y$ where $y = x_i$ if $x_i \leq r(z)$ else 10: $y = z - x_i$ if $x_i > r(z)$ (i = 1 or 2) 11: $B \leftarrow B_1 + B_2 + B_3 + B_4$ 12: **return** *B*

Proof of correctness for Algorithm 2. As N and C(N) have the same rooted partners and $\mu_E(N) = \mu_E(C(N))$, we may assume N to be complete.

Let ρ be a root choice function such that $\rho(T) = h(r(\mu_r(T)), N)$, where r is the function on line 8 and h is defined in Lemma 22. By Lemma 18 and Proposition 20, $\rho(T) \in V(T)$ and ρ is well-defined. Let $G = N_{\rho}^+$. We shall show that Algorithm 2, with $A = \mu_E(N)$ as input, produces the output $B = \mu_V(G)$.

Consider partitioning V(N) = V(G) into the following sets:

 $V_1 = \{v \text{ is a tree node in the directed part of } N\},\$

 $V_2 = \{v \text{ is a hybrid node}\},\$

 $V_3 = \{v \text{ is a root in } G\},\$

 $V_4 = \{v \text{ in a root component of } N, \text{ but not a root in } G\}.$ We will establish $B_i = \langle \mu(v, G) : v \in V_i \rangle$ for the multisets B_i in the algorithm (i = 1, ..., 4), to conclude the proof.

By Lemma 10, $(u, v) \mapsto v$ is a bijection between the directed tree edges and V_1 . Then by Definition 10, $B_1 = \lfloor \mu(v, N) : (u, v) \in E_T(N) \rfloor = \lfloor \mu(v, G) : v \in V_1 \rfloor$, which concludes case i = 1.

For case 2, Lemma 23 implies that $\mu(u,G) \neq \mu(v,G)$ for distinct $u \neq v$ in V_2 . Therefore $\{\mu(v,G) : v \in V_2\} = \{\mu(v,G) : v \in V_2\}$. By the definition of hybrid edges, $B_2 = \{x : \{(x,:\mathbf{h})\} \in A\} = \{\mu(v,G) : (u,v) \in E_H(N)\}$ is equal to $\{\mu(v,G) : v \in V_2\}$, which implies $B_2 = \{\mu(v,G) : v \in V_2\}$.

For case 3, by Lemma 18 and Proposition 20, the μ -vectors of the roots in G are the same as the root μ -vectors, and are all distinct. Hence $B_3 = \{\mu(v, G) : v \in V_3\}$.

For case 4, let E_R^+ be the set of edges in G that corresponds to $E_R(N)$. Consider the map $V_4 \to E_R^+$ that associates vto its the parent edge (u, v) in G. It is well-defined because V_4 excludes the roots of G, root components only contain tree nodes (Proposition 5) and $uv \in E_R(N)$ by Lemma 10. Furthermore, the map is a bijection. Therefore we have $\lfloor \mu(v, G) : v \in V_4 \rfloor = \lfloor \mu_d(u, v) : (u, v) \in E_R^+ \rfloor$.

 B_4 is constructed in Algorithm 2 by taking a μ -vector from the pair $\mu_d(s,t)$ and $\mu_d(t,s)$, for each undirected edge stin each root component. Let T be the root component that contains st and let $z = \mu_r(T) \in B_3$. Then $\mu_d(s,t) + \mu_d(t,s)$ equals z but no other root μ -vector by Proposition 20, so $\mu(st)$ is considered at exactly one iteration of the loop on line 9. Next we need to show that on line 10, exactly one μ -vector gets chosen, and is $y = \mu_d(s,t)$ where $(s,t) \in E_R^+$.

From Lemma 22, let u = h(r(z), N) be the root of Tin G and v such that $r(z) = \mu_d(u, v)$. Since u is a root in G and $(s,t) \in E(G)$, the tree path p in T from u to t contains s. If p also contains v, then $\mu_d(s,t) \leq \mu_d(u,v)$ and $\mu_d(t,s) \not\leq \mu_d(u,v)$ by Lemma 21, so line 10 defines $y = \mu_d(s,t)$ as claimed. If p does not contain v, then the tree path from v to t contains u and s, so by Lemma 21 $\mu_d(s,t)$ is incomparable to $\mu_d(u,v)$ and $\mu_d(t,s) \geq \mu_d(u,v)$. Further, $\mu_d(t,s) > \mu_d(u,v)$ by the choice u = h(r(z), N)and Lemma 22. Therefore line 10 defines $y = z - \mu_d(t,s) =$ $\mu_d(s,t)$, which concludes the proof.

Algorithm 3 Given $A = \mu_E(N)$ from a tree-child \mathcal{L} -network N, and a rooted partner G of N, modify G to obtain $\mathcal{C}(N)$

1: $B \leftarrow \mu_E(G)$ 2: $M \leftarrow [x : \{(x, :t)\} \in B - A]$ 3: for $x \in \text{Unique}(M)$ do 4: $m(x) \leftarrow \text{multiplicity of } x \text{ in } M$ 5: $p(x) \leftarrow \text{the directed path in } G \text{ formed by } \{(u, v) \in E(G) : \mu_V(v, G) = x\}$ 6: undirect the first m(x) edges in p(x)7: return G

Proof of correctness of Algorithm 3. Note that line 5 uses Lemma 14 to claim that p(x) is a directed path, and so line 6 can be applied.

Let E_R^+ denote the set of edges in G that corresponds to edges in $E_R(N)$. It suffices to show that line 6 undirects all edges in E_R^+ and no other. Obviously, line 2 defines M = $(\mu(v, G) : (u, v) \in E_R^+)$. Suppose M consists of elements x_1, \ldots, x_k with multiplicities m_1, \ldots, m_k . We know that E_R^+ exactly consists of m_i edges whose children have μ -vector x_i , for $i = 1, \ldots, k$. Thus we only need to show that for each x_i , the first m_i edges in $p(x_i)$ are in E_R^+ . By Lemma 6, if an edge e is not in E_R^+ , then all edges below it are also not in E_R^+ . Therefore along the path $p(x_i)$, edges in E_R^+ must come first before any edge not in E_R^+ , which finishes the proof. \Box

The following theorem derives directly from Theorem 1 in [7] to reconstruct G from $\mu_V(G)$, and the application of Algorithms 2 and 3.

Theorem 1. Let N_1 and N_2 be tree-child \mathcal{L} -networks. Then $\mu_E(N_1) = \mu_E(N_2)$ if and only if $N_1 \cong N_2$.



Fig. 5. Example rooted networks for which the node-based and edge-based μ distances differ, on leaves (a, b, c, d): Left: N is tree-child, non-bicombining due to its hybrid node having 3 parent edges. Right: N' is not tree-child, but bicombining. Both have 3 nodes (including leaf c) with μ -vector (0,0,1,0), and $d_{\mu_V}(N,N') = 0$. N and N' both have 5 edges with μ -vector (0,0,1,0), of which 3 (resp. 4) are of hybrid type in N (resp. N'), and $d_{\mu_E}(N,N') = 2$.

V. The edge-based μ -distance

Definition 11 (edge-based μ -distance). Let N_1 and N_2 be \mathcal{L} -networks. The *edge-based* μ -dissimilarity between N_1 and N_2 is defined as

$$d_{\mu_E}(N_1, N_2) = |\mu_E(N_1) \triangle \mu_E(N_2)|$$
.

For example, $d_{\mu_E}(N, N') = 2$ in Fig. 5. In Fig. 1, we have $d_{\mu_E}(N_2, N_3) = 5$: N_2 and N_3 share (1, 1, 2, 2) as a root μ -vector, and N_3 has another root μ -vector; the edges in N_2 and N_3 have matching edge μ -vector sets except for e and e', which are also of different types in N_2 and N_3 regardless.

We are now ready to state our main theorem, which justifies why we may refer to d_{μ_E} as a distance.

Theorem 2. For a vector of leaf labels \mathcal{L} , d_{μ_E} is a distance on the class of (complete) tree-child \mathcal{L} -networks.

Proof. From the properties of the symmetric difference, d_{μ_E} is a dissimilarity in the sense that is it symmetric, non-negative, and satisfies the triangle inequality. It remains to show that d_{μ_E} satisfies the separation property. Let N_1 and N_2 be tree-child \mathcal{L} -networks. If $d_{\mu_E}(N_1, N_2) = 0$ then $\mu_E(N_1) = \mu_E(N_2)$ and by Theorem 1, $N_1 \cong N_2$.

For unrooted trees, the μ -vector of each undirected edge encodes the bipartition on \mathcal{L} associated with the edge, hence d_{μ_E} agrees with the Robinson-Foulds distance on unrooted trees.

On rooted trees, d_{μ_E} agrees with d_{μ_V} . Indeed, if T is a directed tree or forest on \mathcal{L} , then each non-root node v has a unique parent edge e with element $\{(\mu_V(v), :\mathbf{t})\}$ in $\mu_E(T)$; and each root u forms to a trivial root component with element $\mu_E(u) = \{(\mu_V(u), :\mathbf{r})\}$ in $\mu_E(T)$.

However, d_{μ_E} does not generally extend d_{μ_V} . For example, consider the rooted networks in Fig. 5. They have the same μ_V representation, hence $d_{\mu_V}(N, N') = 0$. However, their μ_E representations differ, due to edges with the same μ vector (1 path to c only) but different tags (tree edge in N versus hybrid edge in N'). Hence d_{μ_E} can distinguish these networks: $d_{\mu_E}(N, N') > 0$.

We can compute d_{μ_E} using a variant of Algorithm 3 in [7]. Specifically, we first group the elements of $\mu_E(N_i)$ (i = 1, 2) by their type: of the form $\{(x, :\mathbf{r})\}$, $\{(x, :\mathbf{t})\}$, $\{(x, :\mathbf{h})\}$, or $\{(x, :t), (y, :t)\}$. Then it suffices to equip a total order and apply Algorithm 3 in [7] to each group, then add the distances obtained from the 4 groups. For the first 3 types we can simply use the lexical order on the μ -vector x. For the last type, we may compare two elements by comparing the lexically smaller μ -vector first and then the larger one, to obtain a total order within the group.

As in [7], with $\mu_E(N_i)$ computed and sorted, the above takes $\mathcal{O}(n|E|)$ time where $|E| = \max(E_1, E_2)$. Taking into account computing and sorting $\mu_E(N_i)$, computing d_{μ_E} takes $O(|E|(n + \log |E|))$ time.

This complexity can also be expressed in terms of the number of leaves and root components, thanks to the following straightforward generalization of Proposition 1 in [7], allowing for multiple root components.

Proposition 24. Let N be a tree-child \mathcal{L} -network with n leaves and t root components. Then $|V_H| \leq n - t$.

A node v is called elementary if it is a tree node and either $\deg_o(v) = \deg(v) = 1$, or $\deg_o(v) < \deg(v) = 2$. If N has no elementary nodes then

$$|V| \le 2n - t + \sum_{v \in V_H} \deg_i(v) \le (m+2)(n-t) + t$$

where $m = \max_{v \in V_H} \{ \deg_i(v) \}$, and $|E| \le (2m+1)(n-t)$.

Proof. Since N has no ambiguous leaves, the elementary nodes in N are the tree nodes of out-degree 1 in any rooted partner. By considering a rooted partner, we may assume that N is a DAG with t roots, and follow the proof of Proposition 1 in [7]. Their arguments remain valid for the bounds on $|V_H|$ and |V| when N has $t \ge 1$ roots, and when the removal of all but 1 parent hybrid edges at each hybrid node gives a forest instead of a tree. To bound |E| we enumerate the parent edges of each node: $|E| \le (|V_T|-t)+m|V_H| = |V|-t+(m-1)|V_H|$ then use the previous bounds.

Therefore, as long as m and t are bounded and that there are no elementary nodes, for example in binary tree-child networks with a single root component, then |E| = O(n). Consequently, computing μ_E on one such network or computing d_{μ_E} on two such networks takes $O(n^2)$ time.

VI. CONCLUSION AND EXTENSIONS

For rooted networks, the node-based representation μ_V , or equivalently the ancestral profile, is known to provide a distance between networks beyond the class of tree-child networks, such as the class of semibinary tree-sibling timeconsistent networks [6] and stack-free orchard binary networks [5], a class that includes binary tree-child networks. Orchard networks can be characterized as rooted trees with additional "horizontal arcs" [29]. They were first defined as cherrypicking networks: networks that can be reduced to a single edge by iteratively reducing a cherry or a reticulated cherry [15]. A *cherry* is a pair of leaves (x, y) with a common parent. A *reticulated cherry* is a pair of leaves (x, y) such that the parent u of y is a tree node and the parent v of x is a hybrid node with e = (u, v) as a parent hybrid edge. Reducing the pair C = (x, y) means removing taxon x if C is a cherry or removing hybrid edge e if C is a reticulated cherry, and subsequently suppressing u and v if they are of degree 2. Cherries and reticulated cherries are both well-defined on the class of semidirected networks considered here, because leaves are well-defined (stable across rooted partners), each leaf is incident to a single tree edge, and hybrid nodes / edges are well-defined. A *stack* is a pair of hybrid nodes connected by a hybrid edge, and a rooted network is *stack-free* if it has no stack. As hybrid edges are well-defined on our general class of networks, the concepts of stacks and stack-free networks also generalize directly. Therefore, we conjecture that for semidirected networks, our edge-based representation μ_E and the associated dissimilarity d_{μ_E} also separate distinct networks well beyond the tree-child class, possibly to stack-free orchard semidirected networks.

To discriminate distinct orchard networks with possible stacks, Cardona et al. [9] introduced an "extended" node-based μ -representation of rooted phylogenetic networks. In this representation, the μ -vector for each node v is extended by one more coordinate, $\mu_0(v)$, counting the number of paths from v to a hybrid node (any hybrid node). On rooted networks, adding this extension allows μ_V to distinguish between any two orchard networks, even if they contain stacks (but assumed binary, without parallel edges and without outdegree-1 tree nodes in [9]). For semidirected networks, we conjecture that the edge-based representation μ_E can also be extended in the same way, and that this extension may provide a proper distance on the space of semidirected orchard networks.

Phylogenetic networks are most often used as metric networks with edge lengths and inheritance probabilities. Dissimilarities are needed to compare metric networks using both their topologies and edge parameters. For trees, extensions of the RF distance, which $d_{\mu E}$ extends, are widely used. They can be expressed using edge-based μ -vectors as

$$d(T_1, T_2) = \sum_{m \in \mu_E(T_1) \cup \mu_E(T_2)} |\ell(m, T_1) - \ell(m, T_2)|^p \quad (1)$$

where $\ell(m, T_i)$ is the length in tree T_i of the edge corresponding to the μ -vector m, considered to be 0 if m is absent from $\mu_E(T_i)$. The weighted RF distance uses p = 1 [23] and the branch score distance uses p = 2 [18]. If all weights $\ell(m, T)$ are 1 for $m \in \mu_E(T)$, then (1) boils down to the RF distance when restricted to trees (either rooted or unrooted), and to our d_{μ_E} dissimilarity on semidirected phylogenetic networks more generally. For networks with edge lengths, (1) could be used to extend d_{μ_E} , where $\ell(\mu_E(e), N)$ is defined as the length of edge e in N as it is for trees. A root μ -vector could be assigned weight $\ell(\mu_T(T), N) = 0$, because in standard cases, such as for networks with a single root component, the root μ -vector(s) carry redundant information.

Alternatively, using inheritance probabilities could be useful to capture the similarity between a network having a hybrid edge with inheritance very close to 0 and a network lacking this edge. To this end, we could modify μ -vectors. Recall that [7] defined $\mu(v, N) = (\mu_1, \ldots, \mu_n)$ with μ_i equal to the number m_i of paths from v to taxon i in a directed network N. We could generalize μ_i to be a function of these m_i paths, possibly reflecting inheritance probabilities. For example, we could use the weight of a path p, defined as $\gamma(p) = \prod_{e \in p} \gamma(e)$. These weights sum to 1 over up-down paths between v and i [30], although not over the m_i directed paths from v to i. The weights of the m_i paths could then be normalized before calculating their entropy $H_i = -\sum_{p:v \to i} \gamma(p) \log \gamma(p)$ and then define $\mu_i = e^{H_i}$. The original definition $\mu_i = m_i$ corresponds to giving all paths $v \rightsquigarrow i$ equal weight $1/m_i$. This extension carries over from directed to semidirected networks because we proved here that the set of directed paths from an edge e = (u, v) to i is independent of the root choice, given a fixed admissible direction assigned to e, as shown in Propositions 15 and 16. With this extension, μ -vectors are in the continuous space $\mathbb{R}_{\geq 0}^n$ instead of $\mathbb{Z}_{\geq 0}^n$. To use them in a dissimilarity between networks N and $\overline{N'}$, we could use nontrivial distance between μ -vectors (such as the L^1 or L^2 norm) then get the score of an optimal matching between μ -vectors in $\mu_E(N)$ and $\mu_E(N')$. Searching for an optimal matching would increase the computational complexity of the dissimilarity, but would remain polynomial using the Hungarian algorithm [17].

To reduce the dependence of d_{μ_E} on the number of taxa nin the two networks, d_{μ_E} should be normalized by a factor depending on n only. This is particularly useful to compare networks with different leaf labels, by taking the dissimilarity between the subnetworks on their shared leaves. Ideally, the normalization factor is the diameter of the network space, that is, the maximum distance $d_{\mu_E}(N, N')$ over all networks Nand N' in a subspace of interest. For the subspace of unrooted trees on n leaves, this is 2(n-3) [27]. Future work could study the diameter of other semidirected network spaces, such as level-1 or tree-child semidirected networks (which have n - tor fewer hybrid nodes, Proposition 24) or orchard semidirected networks (whose number of hybrids is unbounded).

To compare semidirected networks N_1 on leaf set \mathcal{L}_1 and N_2 on leaf set \mathcal{L}_2 with a non-zero dissimilarity if $\mathcal{L}_1 \neq \mathcal{L}_2$, one idea is to consider the subnetworks \tilde{N}_1 and \tilde{N}_2 on their common leaf set $\mathcal{L} = \mathcal{L}_1 \cap \mathcal{L}_2$ then use a penalized dissimilarity:

$$d_{\mu_E}(N_1, N_2) + \lambda d_{\text{Symm}}(\mathcal{L}_1, \mathcal{L}_2)$$

for some constant $\lambda \geq 0$. This dissimilarity may not satisfy the triangle inequality, which might be acceptable in some contexts. For example, consider as input a set of semidirected networks N_1, \ldots, N_n with N_i on leaf set \mathcal{L}_i , and consider the full leaf set $\mathcal{L} = \bigcup_i^n \mathcal{L}_i$. We may then seek an \mathcal{L} -network Nthat minimizes some criterion, such as

$$\sum_{i=1}^{n} d(N, N_i) . \tag{2}$$

When N is constrained to be an unrooted tree, input networks N_i are unrooted trees and when d is the RF distance using N pruned to \mathcal{L}_i , this is the well-studied RF supertree problem [28]. When the input trees N_i are further restricted to be on 4 taxa, (2) is the criterion used by ASTRAL [31]. The very wide use of ASTRAL and its high accuracy points to the impact of distances that are fast to calculate, such as our proposed d_{μ_E} .

ACKNOWLEDGEMENTS

This work was supported in part by the National Science Foundation (DMS 2023239) and by a H. I. Romnes faculty fellowship to C.A. provided by the University of Wisconsin-Madison Office of the Vice Chancellor for Research with funding from the Wisconsin Alumni Research Foundation.

REFERENCES

- Elizabeth S. Allman, Hector Baños, and John A. Rhodes. NANUQ: a method for inferring species networks from gene trees under the coalescent model. *Algorithms for Molecular Biology*, 14(1), 2019. doi: 10.1186/ s13015-019-0159-2.
- [2] Cécile Ané, John Fogg, Elizabeth S. Allman, Hector Baños, and John A. Rhodes. Anomalous networks under the multispecies coalescent: theory and prevalence. *Journal of Mathematical Biology*, 88:29, 2024. doi: 10.1007/s00285-024-02050-7.
- [3] Hector Baños. Identifying species network features from gene tree quartets under the coalescent model. *Bulletin* of Mathematical Biology, 81(2):494–534, 2019. doi: 10. 1007/s11538-018-0485-4.
- [4] László Babai. Graph isomorphism in quasipolynomial time. *arXiv*, 2016. doi: 10.48550/arXiv.1512.03547.
- [5] Allan Bai, Péter L. Erdős, Charles Semple, and Mike Steel. Defining phylogenetic networks using ancestral profiles. *Mathematical Biosciences*, 332:108537, 2021. doi: 10.1016/j.mbs.2021.108537.
- [6] Gabriel Cardona, Mercè Llabrés, Francesc Rosselló, and Gabriel Valiente. A distance metric for a class of treesibling phylogenetic networks. *Bioinformatics*, 24(13): 1481–1488, 2008. doi: 10.1093/bioinformatics/btn231.
- [7] Gabriel Cardona, Francesc Rosselló, and Gabriel Valiente. Comparison of tree-child phylogenetic networks. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 6(4):552–569, 2009. doi: 10.1109/tcbb. 2007.70270.
- [8] Gabriel Cardona, Mercè Llabrés, Francesc Rosselló, and Gabriel Valiente. The comparison of tree-sibling time consistent phylogenetic networks is graph isomorphismcomplete. *The Scientific World Journal*, 2014:254279, 2014. doi: 10.1155/2014/254279.
- [9] Gabriel Cardona, Joan Carles Pons, Gerard Ribas, and Tomás Martínez Coronado. Comparison of orchard networks using their extended μ-representation. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, in press:1–8, 2024. doi: 10.1109/TCBB.2024. 3361390.
- [10] Mathieu Gautier, Renaud Vitalis, Laurence Flori, and Arnaud Estoup. f-statistics estimation and admixture graph construction with pool-seq or allele count data using the R package poolfstat. *Molecular Ecology Resources*, 22 (4):1394–1416, 2022. doi: 10.1111/1755-0998.13557.
- [11] Elizabeth Gross, Leo van Iersel, Remie Janssen, Mark Jones, Colby Long, and Yukihiro Murakami. Distinguishing level-1 phylogenetic networks on the basis of data generated by Markov processes. *Journal of*

Mathematical Biology, 83(3):32, 2021. doi: 10.1007/s00285-021-01653-8.

- [12] Glenn Hickey, Frank Dehne, Andrew Rau-Chaplin, and Christian Blouin. SPR distance computation for unrooted trees. *Evolutionary Bioinformatics*, 4:EBO.S419, 2008. doi: 10.4137/EBO.S419.
- [13] Katharina T. Huber, Vincent Moulton, and Guillaume E. Scholz. Forest-based networks. *Bulletin of Mathematical Biology*, 84:119, 2022. doi: 10.1007/ s11538-022-01081-9.
- [14] Daniel H. Huson, Regula Rupp, and Celine Scornavacca. *Phylogenetic Networks: Concepts, Algorithms and Applications*. Cambridge University Press, Cambridge, 2010. doi: 10.1017/CBO9780511974076.
- [15] Remie Janssen and Yukihiro Murakami. On cherrypicking and network containment. *Theoretical Computer Science*, 856:121–150, 2021. doi: 10.1016/j.tcs.2020.12. 031.
- [16] Sungsik Kong, David L. Swofford, and Laura S. Kubatko. Inference of phylogenetic networks from sequence data using composite likelihood. *bioRxiv*, 2022. doi: 10.1101/ 2022.11.14.516468.
- [17] Harold W. Kuhn. The hungarian method for the assignment problem. *Naval Research Logistics Quarterly*, 2 (1-2):83–97, 1955. doi: 10.1002/nav.3800020109.
- [18] M K Kuhner and J Felsenstein. A simulation comparison of phylogeny algorithms under equal and unequal evolutionary rates. *Molecular Biology and Evolution*, 11 (3):459–468, 1994. doi: 10.1093/oxfordjournals.molbev. a040126.
- [19] Simone Linz and Kristina Wicke. Exploring spaces of semi-directed level-1 networks. *Journal of Mathematical Biology*, 87(70), 2023. doi: 10.1007/ s00285-023-02004-5.
- [20] Sarah Lutteropp, Celine Scornavacca, Alexey M Kozlov, Benoit Morel, and Alexandros Stamatakis. NetRAX: accurate and fast maximum likelihood phylogenetic network inference. *Bioinformatics*, 38(15):3725– 3733, 2022. doi: 10.1093/bioinformatics/btac396.
- [21] Robert Maier, Pavel Flegontov, Olga Flegontova, Ulaş Işıldak, Piya Changmai, and David Reich. On the limits of fitting complex models of population history to *f*statistics. *eLife*, 12:e85492, 2023. doi: 10.7554/eLife. 85492.
- [22] Samuel Martin, Vincent Moulton, and Richard M. Leggett. Algebraic invariants for inferring 4-leaf semidirected phylogenetic networks. *bioRxiv*, 2023. doi: 10.1101/2023.09.11.557152.
- [23] D. F. Robinson and L. R. Foulds. Comparison of weighted labelled trees. In A. F. Horadam and W. D. Wallis, editors, *Combinatorial Mathematics VI*, pages 119–126, Berlin, Heidelberg, 1979. Springer Berlin Heidelberg. ISBN 978-3-540-34857-3.
- [24] D.F. Robinson and L.R. Foulds. Comparison of phylogenetic trees. *Mathematical Biosciences*, 53(1):131–147, 1981. doi: doi.org/10.1016/0025-5564(81)90043-2.
- [25] Claudia Solís-Lemus and Cécile Ané. Inferring phylogenetic networks with maximum pseudolikelihood un-

der incomplete lineage sorting. *PLOS Genetics*, 12(3): e1005896, 2016. doi: 10.1371/journal.pgen.1005896.

- [26] Samuele Soraggi and Carsten Wiuf. General theory for stochastic admixture graphs and f-statistics. *Theoretical Population Biology*, 125:56–66, 2019. doi: 10.1016/j.tpb. 2018.12.002.
- [27] Mike Steel. Phylogeny: Discrete and Random Processes in Evolution. Society for Industrial and Applied Mathematics, Philadelphia, PA, 2016. doi: 10.1137/1. 9781611974485.
- [28] Pranjal Vachaspati and Tandy Warnow. Fastrfs: fast and accurate Robinson-Foulds supertrees using constrained exact optimization. *Bioinformatics*, 33(5):631–639, 2017. doi: 10.1093/bioinformatics/btw600.
- [29] Leo van Iersel, Remie Janssen, Mark Jones, and Yukihiro Murakami. Orchard networks are trees with additional horizontal arcs. *Bulletin of Mathematical Biology*, 84:76, 2022. doi: 10.1007/s11538-022-01037-z.
- [30] Jingcheng Xu and Cécile Ané. Identifiability of local and global features of phylogenetic networks from average distances. *Journal of Mathematical Biology*, 86(1):12, 2023. doi: 10.1007/s00285-022-01847-8.
- [31] Chao Zhang, Maryam Rabiee, Erfan Sayyari, and Siavash Mirarab. ASTRAL-III: polynomial time species tree reconstruction from partially resolved gene trees. *BMC Bioinformatics*, 19(Suppl 6):153, 2018. doi: 10.1186/ s12859-018-2129-y.