Privacy in LLM-based Recommendation: Recent Advances and Future Directions

Sichun Luo¹, Wei Shao¹, Yuxuan Yao¹, Jian Xu², Mingyang Liu¹, Qintong Li³, Bowei He¹, Maolin Wang¹, Guanzhi Deng¹, Hanxu Hou⁴, Xinyi Zhang⁵, Linqi Song¹ ¹CityUHK ²Tsinghua University ³HKU ⁴Dongguan University of Technology ⁵CUEB

sichun.luo@my.cityu.edu.hk, linqi.song@cityu.edu.hk

Abstract

Nowadays, large language models (LLMs) have been integrated with conventional recommendation models to improve recommendation performance. However, while most of the existing works have focused on improving the model performance, the privacy issue has only received comparatively less attention. In this paper, we review recent advancements in privacy within LLM-based recommendation, categorizing them into privacy attacks and protection mechanisms. Additionally, we highlight several challenges and propose future directions for the community to address these critical problems.

1 Introduction

Recommender systems have been proposed to address the information overload problem (Luo et al., 2022a,b, 2023b, 2024b). Recently, large language models (LLMs) have shown great ability in natural language understanding, generation, and reasoning (Zhao et al., 2023; Luo et al., 2024d; Wang et al., 2023; Yao et al., 2024b). They have also been integrated into recommendation systems, achieving significant progress and reshaping the paradigms of recommendation (Bao et al., 2023; Lin et al., 2023c; Zhao et al., 2024b).

Despite the extensive research on LLM-based recommendation systems, most studies have centered on model accuracy, with less attention dedicated to privacy issues. However, safeguarding privacy is paramount due to the critical nature of private information. Thus privacy issues are not peripheral; they are central to the ethical use of these technologies and warrant thorough investigation.

Several surveys have explored LLM-based recommendation systems (Lin et al., 2023c; Li et al., 2023a; Zhao et al., 2024b), privacy issues in recommendation systems (Huang et al., 2019; Fan et al., 2022; Ogunseyi et al., 2023), and privacy concerns specific to LLMs (Pan et al., 2020; Neel and Chang, 2023; Yao et al., 2024a; Yan et al., 2024). Nevertheless, there has been no comprehensive study that specifically focus on privacy in LLM-based recommendation systems, leaving a significant gap in the literature.

In this paper, we aim to bridge this gap. We first provide an overview of LLM-based recommendation systems and examine the privacy issues inherent to LLMs and their applications in recommendations. Thereafter, we discuss various privacy attacks and the corresponding privacy protection mechanisms. Subsequently, we point out some challenges and future directions. Our contributions are threefold:

- To the best of our knowledge, we are the first to conduct an extensive review of recent advances in privacy issues in LLM-based recommendation systems.
- We systematically introduce privacy in LLMbased recommendations, including privacy definition, attacks, and protection methods.
- We highlight current challenges and promising research directions for developing privacypreserving LLM-based recommender systems.

2 Preliminary

2.1 LLM-based Recommendation

LLM-based recommendation can be classified into several categories. Some works use LLMs as feature encoders (Harte et al., 2023; Rajput et al., 2024), feature engineering tools (Wei et al., 2024; Luo et al., 2024c), scoring/ranking functions (Luo et al., 2023a; Lin et al., 2023b), and for modeling user interaction (Liu et al., 2023c; Leszczynski et al., 2023). Noteworthy advancements have been made in utilizing LLMs as recommenders, either through in context learning (Luo et al., 2024a; Liu et al., 2023a) or supervised fine-tuning (Bao et al., 2023; Zhang et al., 2023). However, while a significant emphasis is placed on model accuracy, the aspect of privacy remains relatively under-explored, thereby presenting a substantial research gap.

2.2 Privacy Issues

2.2.1 Privacy Issues in LLMs

Privacy concerns pervade the life cycle of LLMs, including pre-training, fine-tuning, and inference stages. We briefly discuss them as follows.

Pre-training Stage LLMs are trained on massive datasets, often sourced from publicly available internet data, which can contain sensitive information such as addresses, emails, and Social Security numbers. As model parameters increase, the risk of memorizing and inadvertently outputting this private information also rises, leading to potential privacy breaches.

Fine-tuning Stage Fine-tuning (FT) adapts pretrained LLMs to specific tasks using smaller, domain-specific datasets from fields like healthcare, law, and finance. These datasets can include sensitive information, such as patient privacy data or corporate trade secrets. Despite regulations, LLMs may still memorize private content, and attacks like Membership Inference and Model Inversion can exploit this to reveal sensitive information.

Inference Stage During inference, LLMs generate content based on user inputs, which may contain sensitive or personally identifiable information, leading to privacy leaks. Even with assurances from LLM service providers, complete protection of user data is challenging. LLMs can infer user attributes and preferences from interaction history, even without explicit private information, posing significant privacy concerns.

2.2.2 Privacy in Recommendation

According to previous works (Huang et al., 2019; Ge et al., 2022), the definition of privacy shares similar ingredients. This includes sensitive user attributes such as identity, gender, age, and address, which necessitate stringent access restrictions. The concept of ownership dictates that only authorized entities—whether individual users or the platform itself—are permitted to access and control private information. However, these systems face significant threats from malicious entities, both internal and external, who seek to gain unauthorized access or manipulate this information. These adversaries often exploit auxiliary public information to facilitate their infiltration or attacks. Consequently, the primary goal of privacy protection within recommender systems is to uphold the ownership of private information and develop effective countermeasures against such threats. This ensures that users' sensitive data remains secure and their privacy intact, fostering trust in the technology.

2.2.3 Privacy Issues in LLM-based Recommendation

Privacy in LLM-based recommendation is the intersection of privacy in LLM and privacy in recommendation, since it may involve the incorporation of these two kinds of models. For example, when utilizing LLMs as recommenders, privacy concerns primarily center around the privacy of the LLM itself. Conversely, when employing LLMs as feature augmentors in conjunction with conventional recommender systems, privacy issues are more likely to arise within the recommendation process.

3 Privacy Attack in LLM-based Recommendation

Privacy attacks on recommendation include several categories, such as Membership Inference Attacks (Zhang et al., 2021a) (i.e., identify whether the target user is utilized to train the target recommendation model), Property Inference Attacks (Ganju et al., 2018) (i.e., infer global sensitive information in the training set), Reconstruction Attacks (Meng et al., 2019) (i.e., using the user's publicly available attributes and multiple queries to reconstruct their sensitive information), and Model Extraction Attacks (Yue et al., 2021) (i.e., extract useful information from model).

There are several kinds of privacy attacks on LLM, such as Prompt Hacking (Shen et al., 2023; Liu et al., 2023b) (i.e. strategically designing and manipulating input prompts so that they can influence LLMs's output), Adversarial Attack (Zhang et al., 2021b; Nguyen et al., 2024) (i.e. manipulating input data to cause the LLM to produce incorrect or unintended outputs), Gradient Leakage Attack (Deng et al., 2021; Balunovic et al., 2022) (i.e. access or infer the gradients or the gradient information, which may obtain access to the model or even compromise its privacy and safety).

Some pioneer works focus on privacy attacks in LLM-based recommendation (Zhang et al., 2024b,c). Zhang et al. (2024b) reveals that the LLM-based recommendation introduces security vulnerabilities, allowing attackers to subtly manipulate item recommendations without detection, and further propose a stealthy attack via prompt injection. Moreover, Zhang et al. (2024c) propose LoRec, a framework that effectively utilizes LLMs to detect and defend against poisoning attacks in sequential recommender systems, significantly improving their robustness.

4 Privacy Protection in LLM-based Recommendation

4.1 LLM-based Recommendation Unlearning

Machine unlearning (Bourtoule et al., 2021) is a privacy-preserving technique aiming at addressing the "right to be forgotten" challenge underscored by various privacy regulations (Mantelero, 2013; Illman and Temple, 2019). Its primary objective is to facilitate the effective and efficient erasure or exclusion of sensitive or unwanted information from the trained machine learning model while maintaining the model performance (Nguyen et al., 2022).

Recommendation unlearning, a subset of machine unlearning, is specifically tailored for recommendation scenarios (Chen et al., 2022; Li et al., 2023b, 2024). LLM-based recommendation unlearning focuses on the LLM-based recommendation siutation. E2URec (Wang et al., 2024) enhances unlearning efficiency by updating select LoRA parameters and employs a teacher-student framework to improve the unlearning process. Besides, APA (Hu et al., 2024) utilize unique adapters for segmented training data shards, retraining only those adapters impacted by unusable data, and employing parameter-level adapter aggregation with sample-adaptive attention for each test sample. These methods enable effective and efficient unlearning while preserving recommendation performance.

4.2 LLM-based Federated Recommendation

Recently, some pioneering studies have already equipped the LLM-based recommendation with the paradigm of federated learning to leverage the foundation models while preserving the users' data privacy (Zeng et al., 2024; Zhang et al., 2024a; Zhao et al., 2024a). For example, Zhao et al. (2024a) adopts a federated split learning manner to selectively retain certain sensitive LLM layers on the client side while offloading non-sensitive layers to the server to reduce the local training burden. Meanwhile, a dynamic balance strategy is also proposed to ensure relatively balanced performance across clients. Zeng et al. (2024) proposes a novel hybrid Retrieval Augmented Generation (RAG) mechanism for extracting the ID-based user patterns and text-based item features, which are then converted into text prompts and fed into the ChatGPT for re-ranking. In this way, generalized features could be extracted from the sparse and heterogeneous data, and the rich knowledge within the pre-trained LLM could be exploited. Zhang et al. (2024a) proposes a novel adapter-based foundation model customization for recommendation in a federated setting, where each client trains its local adapter using the private data and the local adapters are further clustered into multiple groups in the server. Finally, the personalized adapter is obtained by combining both the user-level and usergroup-level adapters. Then, the pre-trained foundation models equipped with personalized adapters can provide fine-grained recommendation service efficiently.

4.3 Other Privacy Preserving Techniques

There are other privacy-preserving techniques have been employed within the broader domain of recommender systems, including non-cryptographybased techniques (e.g., anonymization (Luo et al., 2013; Chang et al., 2010; Sakuma and Osame, 2017), randomization (Polat and Du, 2005; Li et al., 2006), and differential privacy (Berlioz et al., 2015; Shin et al., 2018; Saleem et al., 2021)) and a myriad of cryptography-based techniques (e.g., homomorphic encryption (Erkin et al., 2012; Kim et al., 2018; Jumonji et al., 2021), secure multiparty computation (Shmueli and Tassa, 2017; Kaur et al., 2019; Shmueli and Tassa, 2020), and secret sharing (Chen et al., 2020, 2021; Lin et al., 2022)). These methods have proven effective in their respective applications, providing robust privacy safeguards. Specifically, RAH (Shu et al., 2023) consists of LLM-based agents and emphasizes user alignment, to address challenges in recommender systems such as accuracy, biases, privacy, and coldstart problems. Carranza et al. (2023) addresses differential privacy in training deep retrieval systems by using DP language models to generate private synthetic queries, improving retrieval quality while maintaining privacy guarantees.

5 Challenges and Future Directions

We detail the existing works for privacy in LLMbased recommendation. However, there are also some other potential directions to be explored. In this section, we will illustrate some promising directions for further research on this topic.

• Challenge 1: Lack of Universally Applicability in Privacy-Preserving LLM-based Recommendations. The application of LLM-based recommender systems spans a wide array of scenarios, each with unique requirements and specificities. Current research often targets narrow, specific use cases, limiting the broader applicability and adaptability of these methods. This fragmentation hinders the development of universally and comprehensively applicable solutions that can seamlessly integrate across varying contexts and industries.

Future Directions: To address this challenge, there is a pressing need for a unified, general, and comprehensive framework that can accommodate the diverse requirements of different application scenarios while ensuring privacy preservation. This necessitates the development of multi-task, multi-domain solutions that are robust and versatile enough to handle the complexity and variability inherent in real-world applications.

• Challenge 2: Efficiency and Effectiveness in Privacy-Preserving LLM-based Recommendations. The substantial size of LLMs poses significant challenges in terms of computational efficiency. The sheer scale of these models can lead to resource-intensive operations, making them impractical for many applications where quick, reliable recommendations are crucial. Furthermore, privacy-preserving techniques, such as encryption, often incur additional computational costs. Besides, the trade-off between privacy and accuracy means that some privacy-preserving methods may compromise the model's effectiveness. Consequently, preserving user privacy effectively and efficiently remains a challenging task.

Future Directions: Innovative approaches are required to enhance the efficiency and effectiveness of LLM-based recommendation systems. Research should focus on optimizing model architectures, leveraging techniques

like model pruning (Ma et al., 2023), quantization (Lin et al., 2023a), and distillation (Hsieh et al., 2023) to reduce computational overhead without compromising performance. Additionally, exploring methods to improve inference speed and energy efficiency will be crucial for the practical deployment of LLMs in recommender systems.

• Challenge 3: Privacy-Preserving Cloud-Edge Collaboration for LLM-based Recommendation. Due to the large size of LLM, applying cloud-edge collaborative recommender systems could be a promising direction to relieve the computation and storage burden for edge devices. However, it may not be practical to fine-tune the cloud-side large models without the disclosure of local sensitive data, thus reducing the recommendation performance. Moreover, the tremendous volume of edge users also makes it infeasible to customize the cloud-side model for each individual user. Besides, latency caused by intermediate information transmission and extensive computation overhead highly impacts the user experience.

Future Directions: Model compression techniques for LLMs could be a promising direction for deploying recommendation models in the edge devices while parameter-efficient fine-tuning methods (Ding et al., 2023; Han et al., 2024), such as adapter (Hu et al., 2023) and LoRA (Hu et al., 2021), could also be applied for local model customization, thus avoiding uploading the local data. Considering heterogeneous device capabilities, novel model architectures with multiple exits could also offer a flexible trade-off between the performance and efficiency during the model inference.

6 Conclusion

In this paper, we provide a comprehensive overview of recent advancements for privacy in LLM-based recommendation. More specifically, we introduce the basic concepts and taxonomy to facilitate a better understanding of this topic. We also summarize the representative methods addressing privacy concerns in LLM-based recommendation systems, covering both privacy attacks and privacy protection. Finally, we analyze potential challenges and suggest possible future research directions in the realm of privacy for LLM-based recommendations.

References

- Mislav Balunovic, Dimitar Dimitrov, Nikola Jovanović, and Martin Vechev. 2022. Lamp: Extracting text from gradients with language model priors. *Advances in Neural Information Processing Systems*, 35:7641–7654.
- Keqin Bao, Jizhi Zhang, Yang Zhang, Wenjie Wang, Fuli Feng, and Xiangnan He. 2023. Tallrec: An effective and efficient tuning framework to align large language model with recommendation. In *Proceedings of the 17th ACM Conference on Recommender Systems*, pages 1007–1014.
- Arnaud Berlioz, Arik Friedman, Mohamed Ali Kaafar, Roksana Boreli, and Shlomo Berkovsky. 2015. Applying differential privacy to matrix factorization. In Proceedings of the 9th ACM Conference on Recommender Systems, pages 107–114.
- Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. 2021. Machine unlearning. In 2021 IEEE Symposium on Security and Privacy (SP), pages 141–159. IEEE.
- Aldo Gael Carranza, Rezsa Farahani, Natalia Ponomareva, Alex Kurakin, Matthew Jagielski, and Milad Nasr. 2023. Privacy-preserving recommender systems with synthetic query generation using differentially private large language models. *arXiv preprint arXiv:2305.05973*.
- Chih-Cheng Chang, Brian Thompson, Hui Wang, and Danfeng Yao. 2010. Towards publishing recommendation data with predictive anonymization. In *Proceedings of the 5th ACM Symposium on Information, Computer and Communications Security*, pages 24– 35.
- Chaochao Chen, Liang Li, Bingzhe Wu, Cheng Hong, Li Wang, and Jun Zhou. 2020. Secure social recommendation based on secret sharing. *arXiv preprint arXiv:2002.02088*.
- Chong Chen, Fei Sun, Min Zhang, and Bolin Ding. 2022. Recommendation unlearning. In *Proceedings* of the ACM Web Conference 2022, pages 2768–2777.
- Jinrong Chen, Lin Liu, Rongmao Chen, Wei Peng, and Xinyi Huang. 2021. Secrec: A privacy-preserving method for the context-aware recommendation system. *IEEE Transactions on Dependable and Secure Computing*, 19(5):3168–3182.
- Jieren Deng, Yijue Wang, Ji Li, Chao Shang, Hang Liu, Sanguthevar Rajasekaran, and Caiwen Ding. 2021. Tag: Gradient attack on transformer-based language models. arXiv preprint arXiv:2103.06819.
- Ning Ding, Yujia Qin, Guang Yang, Fuchao Wei, Zonghan Yang, Yusheng Su, Shengding Hu, Yulin Chen, Chi-Min Chan, Weize Chen, et al. 2023. Parameter-efficient fine-tuning of large-scale pretrained language models. *Nature Machine Intelligence*, 5(3):220–235.

- Zekeriya Erkin, Thijs Veugen, Tomas Toft, and Reginald L Lagendijk. 2012. Generating private recommendations efficiently using homomorphic encryption and data packing. *IEEE transactions on information forensics and security*, 7(3):1053–1066.
- Wenqi Fan, Xiangyu Zhao, Xiao Chen, Jingran Su, Jingtong Gao, Lin Wang, Qidong Liu, Yiqi Wang, Han Xu, Lei Chen, et al. 2022. A comprehensive survey on trustworthy recommender systems. *arXiv preprint arXiv:2209.10117*.
- Karan Ganju, Qi Wang, Wei Yang, Carl A Gunter, and Nikita Borisov. 2018. Property inference attacks on fully connected neural networks using permutation invariant representations. In *Proceedings of the 2018* ACM SIGSAC conference on computer and communications security, pages 619–633.
- Yingqiang Ge, Shuchang Liu, Zuohui Fu, Juntao Tan, Zelong Li, Shuyuan Xu, Yunqi Li, Yikun Xian, and Yongfeng Zhang. 2022. A survey on trustworthy recommender systems. ACM Transactions on Recommender Systems.
- Zeyu Han, Chao Gao, Jinyang Liu, Sai Qian Zhang, et al. 2024. Parameter-efficient fine-tuning for large models: A comprehensive survey. *arXiv preprint arXiv:2403.14608*.
- Jesse Harte, Wouter Zorgdrager, Panos Louridas, Asterios Katsifodimos, Dietmar Jannach, and Marios Fragkoulis. 2023. Leveraging large language models for sequential recommendation. In *Proceedings of the 17th ACM Conference on Recommender Systems*, pages 1096–1102.
- Cheng-Yu Hsieh, Chun-Liang Li, CHIH-KUAN YEH, Hootan Nakhost, Yasuhisa Fujii, Alex Jason Ratner, Ranjay Krishna, Chen-Yu Lee, and Tomas Pfister. 2023. Distilling step-by-step! outperforming larger language models with less training data and smaller model sizes. In *The 61st Annual Meeting Of The Association For Computational Linguistics*.
- Edward J Hu, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. 2021. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.
- Zhiqiang Hu, Lei Wang, Yihuai Lan, Wanyu Xu, Ee-Peng Lim, Lidong Bing, Xing Xu, Soujanya Poria, and Roy Ka-Wei Lee. 2023. Llm-adapters: An adapter family for parameter-efficient fine-tuning of large language models. In *The 2023 Conference on Empirical Methods in Natural Language Processing*.
- Zhiyu Hu, Yang Zhang, Minghao Xiao, Wenjie Wang, Fuli Feng, and Xiangnan He. 2024. Exact and efficient unlearning for large language model-based recommendation. arXiv preprint arXiv:2404.10327.
- Weiming Huang, Baisong Liu, and Hao Tang. 2019. Privacy protection for recommendation system: a survey. In *Journal of Physics: Conference Series*, volume 1325, page 012087. IOP Publishing.

- Erin Illman and Paul Temple. 2019. California consumer privacy act. *The Business Lawyer*, 75(1):1637– 1646.
- Seiya Jumonji, Kazuya Sakai, Min-Te Sun, and Wei-Shinn Ku. 2021. Privacy-preserving collaborative filtering using fully homomorphic encryption. *IEEE Transactions on Knowledge and Data Engineering*, 35(3):2961–2974.
- Harmanjeet Kaur, Neeraj Kumar, and Mohammad S Obaidat. 2019. Multi-party secure collaborative filtering for recommendation generation. In 2019 IEEE Global Communications Conference (GLOBECOM), pages 1–6. IEEE.
- Jinsu Kim, Dongyoung Koo, Yuna Kim, Hyunsoo Yoon, Junbum Shin, and Sungwook Kim. 2018. Efficient privacy-preserving matrix factorization for recommendation via fully homomorphic encryption. *ACM Transactions on Privacy and Security (TOPS)*, 21(4):1–30.
- Megan Leszczynski, Shu Zhang, Ravi Ganti, Krisztian Balog, Filip Radlinski, Fernando Pereira, and Arun Tejasvi Chaganty. 2023. Talk the walk: Synthetic data generation for conversational music recommendation. *arXiv preprint arXiv:2301.11489*.
- Lei Li, Yongfeng Zhang, Dugang Liu, and Li Chen. 2023a. Large language models for generative recommendation: A survey and visionary discussions. *arXiv preprint arXiv:2309.01157*.
- Ninghui Li, Tiancheng Li, and Suresh Venkatasubramanian. 2006. t-closeness: Privacy beyond k-anonymity and l-diversity. In 2007 IEEE 23rd international conference on data engineering, pages 106–115. IEEE.
- Yuyuan Li, Chaochao Chen, Xiaolin Zheng, Junlin Liu, and Jun Wang. 2024. Making recommender systems forget: Learning and unlearning for erasable recommendation. *Knowledge-Based Systems*, 283:111124.
- Yuyuan Li, Chaochao Chen, Xiaolin Zheng, Yizhao Zhang, Biao Gong, Jun Wang, and Linxun Chen. 2023b. Selective and collaborative influence function for efficient recommendation unlearning. *Expert Systems with Applications*, 234:121025.
- Ji Lin, Jiaming Tang, Haotian Tang, Shang Yang, Xingyu Dang, and Song Han. 2023a. Awq: Activation-aware weight quantization for llm compression and acceleration. *arXiv preprint arXiv:2306.00978*.
- Jianghao Lin, Bo Chen, Hangyu Wang, Yunjia Xi, Yanru Qu, Xinyi Dai, Kangning Zhang, Ruiming Tang, Yong Yu, and Weinan Zhang. 2023b. Clickprompt: Ctr models are strong prompt generators for adapting language models to ctr prediction. *arXiv preprint arXiv:2310.09234*.
- Jianghao Lin, Xinyi Dai, Yunjia Xi, Weiwen Liu, Bo Chen, Xiangyang Li, Chenxu Zhu, Huifeng Guo, Yong Yu, Ruiming Tang, et al. 2023c. How can

recommender systems benefit from large language models: A survey. arXiv preprint arXiv:2306.05817.

- Zhaohao Lin, Weike Pan, Qiang Yang, and Zhong Ming. 2022. A generic federated recommendation framework via fake marks and secret sharing. ACM Transactions on Information Systems, 41(2):1–37.
- Junling Liu, Chao Liu, Peilin Zhou, Renjie Lv, Kang Zhou, and Yan Zhang. 2023a. Is chatgpt a good recommender? a preliminary study. *arXiv preprint arXiv:2304.10149*.
- Yi Liu, Gelei Deng, Yuekang Li, Kailong Wang, Tianwei Zhang, Yepang Liu, Haoyu Wang, Yan Zheng, and Yang Liu. 2023b. Prompt injection attack against llm-integrated applications. *arXiv preprint arXiv:2306.05499*.
- Yuanxing Liu, Wei-Nan Zhang, Yifan Chen, Yuchi Zhang, Haopeng Bai, Fan Feng, Hengbin Cui, Yongbin Li, and Wanxiang Che. 2023c. Conversational recommender system and large language model are made for each other in e-commerce pre-sales dialogue. arXiv preprint arXiv:2310.14626.
- Sichun Luo, Bowei He, Haohan Zhao, Yinya Huang, Aojun Zhou, Zongpeng Li, Yuanzhang Xiao, Mingjie Zhan, and Linqi Song. 2023a. Recranker: Instruction tuning large language model as ranker for top-k recommendation. arXiv preprint arXiv:2312.16018.
- Sichun Luo, Chen Ma, Yuanzhang Xiao, and Linqi Song. 2023b. Improving long-tail item recommendation with graph augmentation. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*, pages 1707–1716.
- Sichun Luo, Jiansheng Wang, Aojun Zhou, Li Ma, and Linqi Song. 2024a. Large language models augmented rating prediction in recommender system. In ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 7960–7964. IEEE.
- Sichun Luo, Yuanzhang Xiao, and Linqi Song. 2022a. Personalized federated recommendation via joint representation learning, user clustering, and model adaptation. In Proceedings of the 31st ACM international conference on information & knowledge management, pages 4289–4293.
- Sichun Luo, Yuanzhang Xiao, Xinyi Zhang, Yang Liu, Wenbo Ding, and Linqi Song. 2024b. Perfedrec++: Enhancing personalized federated recommendation with self-supervised pre-training. *ACM Trans. Intell. Syst. Technol.* Just Accepted.
- Sichun Luo, Yuxuan Yao, Bowei He, Yinya Huang, Aojun Zhou, Xinyi Zhang, Yuanzhang Xiao, Mingjie Zhan, and Linqi Song. 2024c. Integrating large language models into recommendation via mutual augmentation and adaptive aggregation. *arXiv preprint arXiv:2401.13870*.

- Sichun Luo, Yuxuan Yao, Haohan Zhao, and Linqi Song. 2024d. A language model-based fine-grained address resolution framework in uav delivery system. *IEEE Journal of Selected Topics in Signal Processing*.
- Sichun Luo, Xinyi Zhang, Yuanzhang Xiao, and Linqi Song. 2022b. Hysage: A hybrid static and adaptive graph embedding network for context-drifting recommendations. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*, pages 1389–1398.
- Zhifeng Luo, Shuhong Chen, and Yutian Li. 2013. A distributed anonymization scheme for privacypreserving recommendation systems. In 2013 IEEE 4th International Conference on Software Engineering and Service Science, pages 491–494. IEEE.
- Xinyin Ma, Gongfan Fang, and Xinchao Wang. 2023. Llm-pruner: On the structural pruning of large language models. *Advances in neural information processing systems*, 36:21702–21720.
- Alessandro Mantelero. 2013. The eu proposal for a general data protection regulation and the roots of the 'right to be forgotten'. *Computer Law & Security Review*, 29(3):229–235.
- Xuying Meng, Suhang Wang, Kai Shu, Jundong Li, Bo Chen, Huan Liu, and Yujun Zhang. 2019. Towards privacy preserving social recommendation under personalized privacy settings. *World Wide Web*, 22:2853–2881.
- Seth Neel and Peter Chang. 2023. Privacy issues in large language models: A survey. *arXiv preprint arXiv:2312.06717*.
- Thanh Tam Nguyen, Thanh Trung Huynh, Phi Le Nguyen, Alan Wee-Chung Liew, Hongzhi Yin, and Quoc Viet Hung Nguyen. 2022. A survey of machine unlearning. *arXiv preprint arXiv:2209.02299*.
- Thuy Dung Nguyen, Tuan Nguyen, Phi Le Nguyen, Hieu H Pham, Khoa D Doan, and Kok-Seng Wong. 2024. Backdoor attacks and defenses in federated learning: Survey, challenges and future research directions. *Engineering Applications of Artificial Intelligence*, 127:107166.
- Taiwo Blessing Ogunseyi, Cossi Blaise Avoussoukpo, and Yiqiang Jiang. 2023. A systematic review of privacy techniques in recommendation systems. *International Journal of Information Security*, 22(6):1651– 1664.
- Xudong Pan, Mi Zhang, Shouling Ji, and Min Yang. 2020. Privacy risks of general-purpose language models. In 2020 IEEE Symposium on Security and Privacy (SP), pages 1314–1331. IEEE.
- Huseyin Polat and Wenliang Du. 2005. Svd-based collaborative filtering with privacy. In *Proceedings of the 2005 ACM symposium on Applied computing*, pages 791–795.

- Shashank Rajput, Nikhil Mehta, Anima Singh, Raghunandan Hulikal Keshavan, Trung Vu, Lukasz Heldt, Lichan Hong, Yi Tay, Vinh Tran, Jonah Samost, et al. 2024. Recommender systems with generative retrieval. *Advances in Neural Information Processing Systems*, 36.
- Jun Sakuma and Tatsuya Osame. 2017. Recommendation with k-anonymized ratings. *arXiv preprint arXiv:1707.03334*.
- Yasir Saleem, Mubashir Husain Rehmani, Noel Crespi, and Roberto Minerva. 2021. Parking recommender system privacy preservation through anonymization and differential privacy. *Engineering Reports*, 3(2):e12297.
- Xinyue Shen, Zeyuan Chen, Michael Backes, Yun Shen, and Yang Zhang. 2023. " do anything now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models. *arXiv preprint arXiv:2308.03825*.
- Hyejin Shin, Sungwook Kim, Junbum Shin, and Xiaokui Xiao. 2018. Privacy enhanced matrix factorization for recommendation with local differential privacy. *IEEE Transactions on Knowledge and Data Engineering*, 30(9):1770–1782.
- Erez Shmueli and Tamir Tassa. 2017. Secure multiparty protocols for item-based collaborative filtering. In *Proceedings of the eleventh ACM conference on recommender systems*, pages 89–97.
- Erez Shmueli and Tamir Tassa. 2020. Mediated secure multi-party protocols for collaborative filtering. ACM Transactions on Intelligent Systems and Technology (TIST), 11(2):1–25.
- Yubo Shu, Hansu Gu, Peng Zhang, Haonan Zhang, Tun Lu, Dongsheng Li, and Ning Gu. 2023. Rah! recsys-assistant-human: A human-central recommendation framework with large language models. *arXiv preprint arXiv:2308.09904*.
- Hangyu Wang, Jianghao Lin, Bo Chen, Yang Yang, Ruiming Tang, Weinan Zhang, and Yong Yu. 2024. Towards efficient and effective unlearning of large language models for recommendation. arXiv preprint arXiv:2403.03536.
- Ke Wang, Houxing Ren, Aojun Zhou, Zimu Lu, Sichun Luo, Weikang Shi, Renrui Zhang, Linqi Song, Mingjie Zhan, and Hongsheng Li. 2023. Mathcoder: Seamless code integration in Ilms for enhanced mathematical reasoning. In *The Twelfth International Conference on Learning Representations*.
- Wei Wei, Xubin Ren, Jiabin Tang, Qinyong Wang, Lixin Su, Suqi Cheng, Junfeng Wang, Dawei Yin, and Chao Huang. 2024. Llmrec: Large language models with graph augmentation for recommendation. In Proceedings of the 17th ACM International Conference on Web Search and Data Mining, pages 806–815.

- Biwei Yan, Kun Li, Minghui Xu, Yueyan Dong, Yue Zhang, Zhaochun Ren, and Xiuzheng Cheng. 2024. On protecting the data privacy of large language models (llms): A survey. *arXiv preprint arXiv:2403.05156*.
- Yifan Yao, Jinhao Duan, Kaidi Xu, Yuanfang Cai, Zhibo Sun, and Yue Zhang. 2024a. A survey on large language model (llm) security and privacy: The good, the bad, and the ugly. *High-Confidence Computing*, page 100211.
- Yuxuan Yao, Sichun Luo, Haohan Zhao, Guanzhi Deng, and Linqi Song. 2024b. Can llm substitute human labeling? a case study of fine-grained chinese address entity recognition dataset for uav delivery. In *Companion Proceedings of the ACM on Web Conference* 2024, pages 1099–1102.
- Zhenrui Yue, Zhankui He, Huimin Zeng, and Julian McAuley. 2021. Black-box attacks on sequential recommenders via data-free model extraction. In Proceedings of the 15th ACM Conference on Recommender Systems, pages 44–54.
- Huimin Zeng, Zhenrui Yue, Qian Jiang, and Dong Wang. 2024. Federated recommendation via hybrid retrieval augmented generation.
- Chunxu Zhang, Guodong Long, Hongkuan Guo, Xiao Fang, Yang Song, Zhaojie Liu, Guorui Zhou, Zijian Zhang, Yang Liu, and Bo Yang. 2024a. Federated adaptation for foundation model-based recommendations.
- Jinghao Zhang, Yuting Liu, Qiang Liu, Shu Wu, Guibing Guo, and Liang Wang. 2024b. Stealthy attack on large language model based recommendation. *arXiv preprint arXiv:2402.14836*.
- Junjie Zhang, Ruobing Xie, Yupeng Hou, Wayne Xin Zhao, Leyu Lin, and Ji-Rong Wen. 2023. Recommendation as instruction following: A large language model empowered recommendation approach. arXiv preprint arXiv:2305.07001.
- Kaike Zhang, Qi Cao, Yunfan Wu, Fei Sun, Huawei Shen, and Xueqi Cheng. 2024c. Lorec: Large language model for robust sequential recommendation against poisoning attacks. *arXiv preprint arXiv:2401.17723*.
- Minxing Zhang, Zhaochun Ren, Zihan Wang, Pengjie Ren, Zhunmin Chen, Pengfei Hu, and Yang Zhang. 2021a. Membership inference attacks against recommender systems. In Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security, pages 864–879.
- Xinyang Zhang, Zheng Zhang, Shouling Ji, and Ting Wang. 2021b. Trojaning language models for fun and profit. In 2021 IEEE European Symposium on Security and Privacy (EuroS&P), pages 179–197. IEEE.

- Jujia Zhao, Wenjie Wang, Chen Xu, Zhaochun Ren, See-Kiong Ng, and Tat-Seng Chua. 2024a. Llm-based federated recommendation.
- Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. 2023. A survey of large language models. *arXiv preprint arXiv:2303.18223*.
- Zihuai Zhao, Wenqi Fan, Jiatong Li, Yunqing Liu, Xiaowei Mei, Yiqi Wang, Zhen Wen, Fei Wang, Xiangyu Zhao, Jiliang Tang, et al. 2024b. Recommender systems in the era of large language models (llms). *IEEE Transactions on Knowledge and Data Engineering*.