Adaptive discretization algorithms for locally optimal experimental design

Jochen Schmid, Philipp Seufert, Michael Bortz

Fraunhofer Institute for Industrial Mathematics (ITWM), 67663 Kaiserslautern, Germany

jochen.schmid@itwm.fraunhofer.de

We develop adaptive discretization algorithms for locally optimal experimental design of nonlinear prediction models. With these algorithms, we refine and improve a pertinent state-of-the-art algorithm in various respects. We establish novel termination, convergence, and convergence rate results for the proposed algorithms. In particular, we prove a sublinear convergence rate result under very general assumptions on the design criterion and, most notably, a linear convergence result under the additional assumption that the design criterion is strongly convex and the design space is finite. Additionally, we prove the finite termination at approximately optimal designs, including upper bounds on the number of iterations until termination. And finally, we illustrate the practical use of the proposed algorithms by means of two application examples from chemical engineering: one with a stationary model and one with a dynamic model.

1 Introduction

In this paper, we are concerned with locally optimal experimental design for nonlinear prediction models. Such models are parametric models $f : \mathcal{X} \times \Theta \to \mathcal{Y}$ describing a functional input-output relationship of interest, that is, for every model parameter value θ , the model

$$\mathcal{X} \ni x \mapsto f(x,\theta) \in \mathcal{Y} \tag{1.1}$$

predicts the considered output quantities $y \in \mathcal{Y} = \mathbb{R}^{d_y}$ as a function of the considered input quantities $x \in \mathcal{X} \subset \mathbb{R}^{d_x}$.

In a nutshell, locally optimal experimental design [7, 10, 22] is about finding maximally informative experimental designs ξ for f locally around a given reference value $\overline{\theta}$ of the model parameters. As usual, an (approximate) experimental design ξ [10, 22] is a – discrete or nondiscrete – probability measure on a suitable subset of the input space, the so-called design space $X \subset \mathcal{X}$. In essence, an experimental design ξ indicates at which design points $x \in X$ experiments should be performed and how much weight each of these experiments x should be given (which, practically speaking, boils down to how often the individual experiments x should be repeated [9, 10, 24]). In practice, one is only interested in discrete designs, that is, designs of the form

$$\xi = \sum_{i=1}^{n} w_i \delta_{x_i} \tag{1.2}$$

with finitely many design points x_1, \ldots, x_n and corresponding importance weights w_1, \ldots, w_n ; but for theoretical investigations, non-discrete designs are important as well. In order to quantify the information content of a given design ξ for f around $\overline{\theta}$, one usually takes the so-called information matrix of ξ for f around $\overline{\theta}$, that is, the positive semidefinite matrix

$$M_f(\xi,\overline{\theta}) := \int_X D_\theta f(x,\overline{\theta})^\top \varsigma^{-1} D_\theta f(x,\overline{\theta}) \,\mathrm{d}\xi(x) \in \mathbb{R}^{d_\theta \times d_\theta}_{\mathrm{psd}}$$
(1.3)

with $\varsigma \in \mathbb{R}_{pd}^{d_y \times d_y}$ denoting the positive definite covariance matrix of the measurement errors for the considered output quantity.

With this notion of information content, the basic task of locally optimal experimental design can concisely be formulated as finding a design ξ^* that maximizes the information matrix map $\xi \mapsto M_f(\xi, \overline{\theta}) \in \mathbb{R}_{psd}^{d_{\theta} \times d_{\theta}}$ w.r.t. the standard (Löwner) ordering on the set of positive semidefinite matrices. Since this matrix-valued optimization problem, however, has no solution in general [10] (Example 2.1), one minimizes a suitable scalar-valued function $\xi \mapsto \Psi(M_f(\xi, \overline{\theta})) \in \mathbb{R} \cup \{\infty\}$ of the information matrix instead. Specifically, one considers convex antitonic functions $\Psi : \mathbb{R}_{psd}^{d_{\theta} \times d_{\theta}} \rightarrow \mathbb{R} \cup \{\infty\}$ which, in this context, are called design criteria. So, summarizing, the basic task of locally optimal experimental design can be formulated as follows: for a given design criterion Ψ , find a solution ξ^* to the locally optimal design problem

$$\min_{\xi \in \Xi(X)} \Psi(M_f(\xi, \overline{\theta})), \tag{1.4}$$

where $\Xi(X)$ denotes the convex set of all designs on X. Since the design criterion Ψ is convex by assumption and the information matrix map $\xi \mapsto M_f(\xi, \overline{\theta})$ is linear by (1.3), the locally optimal design problem (1.4) is a convex optimization problem. It is finite- or infinite-dimensional depending on whether the design space X is finite or infinite.

In the extensive literature on locally optimal experimental design, there exists a large variety of iterative algorithms that are specifically tailored to solving convex design problems of the kind (1.4). Important instances of such algorithms can be found in the works [9, 37, 3, 32, 6, 39, 40, 38], among others. See also [2, 10] and especially [22] for a good overview of these and many more iterative algorithms for (locally) optimal experimental design.

1.1 Contributions of this paper

In the present paper, we build upon the most recent and efficient of the aforementioned optimal design algorithms, namely the adaptive discretization algorithm from [38]. We refine and improve this algorithm in various respects and, most importantly, we establish novel termination, convergence, and convergence rate results for our adaptive discretization algorithms. In particular, we establish a sublinear convergence rate result under very general assumptions on the design criterion Ψ and, most notably, a linear convergence rate result under the additional assumption that the design criterion Ψ is strongly convex and the design space X is finite. So far, the convergence rate of optimal design algorithms like [9, 37, 3, 32, 6, 39, 40, 38] has not been investigated systematically yet, to the best of our knowledge. With the present paper, we close this gap in the literature. We also illustrate the practical use of the proposed algorithms by means of two application examples from chemical engineering, the first one being based on a stationary process model f and the second one being based a dynamic process model f.

In order to explain our contributions in more detail, we first have to briefly recap how the algorithm from [38] works. It is an iterative algorithm that in every iteration proceeds in two steps. In the first step, the algorithm computes a solution ξ^k to the discretized design problem

$$\min_{\xi \in \Xi(X^k)} \Psi(M_f(\xi, \overline{\theta})), \tag{1.5}$$

where $X^k \subset X$ is the current discretization (finite subset) of X. In the second step, the algorithm checks how far the solution ξ^k to (1.5) is from being already optimal for the original design problem (1.4). And for that purpose, it searches for a worst violator x^k of the (necessary and sufficient) optimality condition of ξ^k for (1.4), that is, it computes a solution x^k to the worstviolator problem

$$\min_{x \in X} \psi(M_f(\xi^k, \overline{\theta}), x) \tag{1.6}$$

where ψ is a suitable directional derivative of Ψ , the so-called sensitivity function of Ψ . In the case where x^k actually is not a violator of the optimality condition, ξ^k already is a solution to the original problem (1.4) and the iteration is terminated. In the opposite case, however, the worst violator x^k is added to the discretization according to

$$X^{k+1} := \operatorname{supp} \xi^k \cup \{x^k\}$$
(1.7)

and the iteration is continued with the updated discretization (1.7). In this relation, $\operatorname{supp} \xi^k \subset X^k$ denotes the support of the design ξ^k , of course.

We refine and improve this algorithm mainly in two respects. (i) Instead of the exact optimality condition for ξ^k , our algorithms work with the less restrictive (necessary and sufficient) condition for ε -approximate optimality of ξ^k , namely

$$\psi((M_f(\xi^k,\overline{\theta}), x) \ge -\varepsilon \quad (x \in X)$$
(1.8)

with some user-specified $\varepsilon \in [0, \infty)$. (ii) Instead of exact solutions of the subproblems (1.5) and (1.6), our algorithms only require approximate solutions ξ^k and x^k to these problems. In particular, the strict versions of our algorithms require only approximately worst violators x^k of (1.8) and the relaxed versions of our algorithms even require only arbitrary violators x^k of (1.8). It is clear that with these modifications, the computational effort per iteration is significantly reduced, in general.

We then establish novel termination, convergence, and convergence rate results for the proposed algorithms. A bit more specifically, we begin with basic termination and convergence results under minimal assumptions, namely essentially the lower semicontinuity, convexity, and continuous directional differentiability of the design criterion Ψ . We then establish a sublinear convergence rate result for our strict algorithms under the additional assumption that the design criterion Ψ is locally *L*-smooth. Specifically, we show that for the iterates $(\xi^k)_{k\in K}$ of our strict algorithms, the optimality errors can be bounded above as

$$\Psi(M_f(\xi^k,\overline{\theta})) - \Psi^* \le C/(k+1) \qquad (k \in K), \tag{1.9}$$

where C is a constant depending on the initial optimality error $\Psi(M_f(\xi^0, \overline{\theta})) - \Psi^*$, the local smoothness constant of Ψ , and the diameter of the matrix set $M_f(\Xi(X), \overline{\theta})$. And finally, we establish a linear convergence rate result for our strict algorithms under the additional assumption that the design criterion Ψ is locally L-smooth and μ -strongly convex and the design space X is finite. Specifically, we show that for the iterates $(\xi^k)_{k\in K}$ of our strict algorithms, the optimality errors can be bounded above as

$$\Psi(M_f(\xi^k,\overline{\theta})) - \Psi^* \le Cr^k \qquad (k \in K), \tag{1.10}$$

where $C := \Psi(M_f(\xi^0, \overline{\theta})) - \Psi^*$ is the initial optimality error and $r \in [1/2, 1)$ is a constant depending on the local smoothness constant L, the strong convexity constants μ of Ψ , and on the diameter and the pyramidal width [18] of the matrix set $M_f(\Xi(X), \overline{\theta})$ (which is a polytope by the assumed finiteness of X). As we will see, from a practical point of view, the assumptions of the sublinear and also of the linear convergence rate result pose no serious restrictions. In particular, they are satisfied for the arguably most commonly used design criteria, namely the A- and the D-criterion.

1.2 Conventions on notation

In the entire paper, we write $d := d_{\theta} \in \mathbb{N}$ for the number of model parameters and we use the symbols

$$\mathbb{R}_{\rm pd}^{d \times d} \subset \mathbb{R}_{\rm psd}^{d \times d} \subset \mathbb{R}_{\rm sym}^{d \times d} \tag{1.11}$$

to denote, respectively, the sets of positive definite, positive semidefinite, and symmetric $d \times d$ matrices over \mathbb{R} . Additionally, for a given matrix $M \in \mathbb{R}^{d \times d}$,

$$||M|| := \max_{|v| \le 1} |Mv|$$
 and $|M| := \operatorname{tr}(M^{\top}M)^{1/2}$ (1.12)

will always denote the operator norm (Schatten- ∞ norm) of M induced by the ℓ^2 -norm $|\cdot|$ on \mathbb{R}^d and, respectively, the Frobenius norm (Schatten-2 norm) of M. Also, for any metric space X, we denote by $\Xi(X)$ the set of probability measures on \mathcal{B}_X (Borel sigma-algebra of X) and by $\delta_x \in \Xi(X)$ we denote the point measure concentrated at x. And finally, monotonicity – especially antitonicity and monotonic increasing- and decreasingness – are always understood in the non-strict sense (with non-strict inequalities). In the case of strict monotonicity, we will always explicitly indicate this.

2 Setting and preliminaries

In this section, we introduce the formal setting of locally optimal experimental design and collect the necessary preliminaries for our termination, convergence, and convergence rate results.

2.1 Setting

In this section, we introduce the setting of locally optimal experimental design in formal terms. As indicated in the introduction, the starting point is a – linear or nonlinear – parametric model

$$f: \mathcal{X} \times \Theta \to \mathcal{Y} \tag{2.1}$$

for the prediction of the considered output quantities $y \in \mathcal{Y} = \mathbb{R}^{d_y}$ as a function of relevant input quantities $x \in \mathcal{X}$. As usual, such a model is called linear iff it is affine-linear w.r.t. to the model parameters $\theta \in \Theta$, that is, iff it is of the form $f(x,\theta) = c(x) + J(x)\theta$ for some arbitrary functions $c : \mathcal{X} \to \mathbb{R}^{d_y}$ and $J : \mathcal{X} \to \mathbb{R}^{d_y \times d_\theta}$. All one needs to assume about f to get locally optimal design going are a few mild regularity conditions (Condition 2.1) and a representativity condition (Condition 2.2), which is completely standard in experimental design and parameter estimation [10, 22, 31].

Condition 2.1. (i) X is a compact metric space (the design space) and X is contained in the set \mathcal{X} (the input space)

- (ii) Θ is a compact subset of $\mathbb{R}^{d_{\theta}}$ (the model parameter space) that is equal to the closure of its interior, in short, $\overline{\Theta^{\circ}} = \Theta$
- (iii) $\Theta \ni \theta \mapsto f(x,\theta)$ is differentiable for every $x \in X$ and $X \ni x \mapsto D_{\theta}f(x,\overline{\theta})$ is continuous for every $\overline{\theta} \in \Theta$.

Condition 2.2. A parameter value $\theta^* \in \Theta$ exists such that for every $n \in \mathbb{N}$ and every set of input values $x_1, \ldots, x_n \in X$, the corresponding measured values $y_1, \ldots, y_n \in \mathbb{R}^{d_y}$ of the output quantity are given by the predictions $f(x_1, \theta^*), \ldots, f(x_n, \theta^*)$ of the model $f(\cdot, \theta^*)$ up to independent normally distributed measurement errors $\epsilon_1, \ldots, \epsilon_n$, that is,

$$y_i = f(x_i, \theta^*) + \epsilon_i \qquad (i \in \{1, \dots, n\})$$

$$(2.2)$$

where $\epsilon_1, \ldots, \epsilon_n$ are realizations of independent and normally distributed measurement errors $\varepsilon_1, \ldots, \varepsilon_n$ having mean 0 and a known covariance matrix $\varsigma \in \mathbb{R}_{pd}^{d_y \times d_y}$.

Conventionally, every tuple $\tilde{x} = (x_1, \ldots, x_n) \in X^n$ of – not necessarily distinct – design points as above is called an exact design. Also, any value θ^* as above is called (the) true model parameter value. Since the true value θ^* is unknown, of course, one needs to come up with reliable estimates for it and a standard way of doing so is least-squares estimation, that is, for a given exact design $\tilde{x} = (x_1, \ldots, x_n) \in X^n$ one measures the values $\tilde{y} = (y_1, \ldots, y_n)$ of the output quantity and then computes a corresponding least-squares estimate

$$\widehat{\theta}_f(\tilde{x}, \tilde{y}) \in \operatorname*{argmin}_{\theta \in \Theta} \sum_{i=1}^n (f(x_i, \theta) - y_i)^\top \varsigma^{-1} (f(x_i, \theta) - y_i).$$
(2.3)

In view of Condition 2.1, it is clear that such a least-squares estimate exists and that it can be chosen to depend measurably on \tilde{y} (Lemma 2.9 of [22]). Since for every design \tilde{x} the corresponding measurement values \tilde{y} are subjected to random measurement errors by Condition 2.2, the same is true for the computed least-squares estimate $\hat{\theta}_f(\tilde{x}, \tilde{y})$. Specifically, $\hat{\theta}_f(\tilde{x}, \tilde{y})$ is a realization of the random variable $\hat{\theta}_f(\tilde{x}, \tilde{y}(\tilde{x}))$, where

$$\tilde{y}(\tilde{x}) := \tilde{f}(\tilde{x}, \theta^*) + \tilde{\varepsilon}(\tilde{x}) \tag{2.4}$$

is the random variable defined by the predictions $\tilde{f}(\tilde{x}, \theta^*) := (f(x_1, \theta^*), \dots, f(x_n, \theta^*))$ of the true model at \tilde{x} plus normally distributed measurement errors $\tilde{\varepsilon}(\tilde{x})$ with mean 0 and covariance matrix $\tilde{\varsigma} := \operatorname{diag}(\varsigma, \dots, \varsigma) \in \mathbb{R}_{\mathrm{pd}}^{nd_y \times nd_y}$.

In optimal experimental design [15, 9, 17, 33, 25, 2, 10, 22], the goal is to find a design \tilde{x} such that the uncertainty $\operatorname{Cov} \hat{\theta}_f(\tilde{x}, \tilde{y}(\tilde{x}))$ of the corresponding least-squares estimate becomes minimal. As is well-known, for nonlinear models f one usually has no closed-form expression of this covariance and one therefore has to resort to suitable approximations for it. In locally optimal experimental design, one uses the approximation

$$\operatorname{Cov}\widehat{\theta}_{f}(\tilde{x}, \tilde{y}(\tilde{x})) \approx \operatorname{Cov}\widehat{\theta}_{f_{\overline{a}}^{\lim}}(\tilde{x}, \tilde{y}(\tilde{x})).$$

$$(2.5)$$

In other words, one approximates the covariance of the least-squares estimate for f by the covariance of the least-squares estimate for the linearization $f_{\overline{\theta}}^{\text{lin}}$ of f around a suitable reference parameter value $\overline{\theta}$, that is,

$$f_{\overline{\theta}}^{\text{lin}}(x,\theta) := f(x,\overline{\theta}) + D_{\theta}f(x,\overline{\theta})(\theta - \overline{\theta}) \qquad ((x,\theta) \in \mathcal{X} \times \mathbb{R}^{d_{\theta}}).$$
(2.6)

And this linearized covariance, in turn, can be compactly expressed through the information matrix (1.3) of the (approximate) design

$$\xi_{\tilde{x}} := \frac{1}{n} \sum_{i=1}^{n} \delta_{x_i} \tag{2.7}$$

corresponding to the exact design $\tilde{x} = (x_1, \ldots, x_n)$.

Lemma 2.3. Suppose that Conditions 2.1 and 2.2 are satisfied. If $\tilde{x} \in X^n$ is an arbitrary exact design of size $n \in \mathbb{N}$ and $\overline{\theta} \in \Theta$ is an arbitrary reference parameter value, then

$$\operatorname{Cov}\widehat{\theta}_{f_{\overline{\theta}}^{\operatorname{lin}}}(\tilde{x}, \tilde{y}(\tilde{x})) = \frac{1}{n} M_f(\xi_{\tilde{x}}, \overline{\theta})^+, \qquad (2.8)$$

where $\widehat{\theta}_{f_{\overline{\theta}}^{\underline{\text{lin}}}}(\tilde{x}, \tilde{y})$ is the minimum-norm least-squares estimate of $f_{\overline{\theta}}^{\underline{\text{lin}}}$ for \tilde{x} and \tilde{y} and $M_f(\xi_{\tilde{x}}, \overline{\theta})^+$ is the (Moore-Penrose) pseudo-inverse of the information matrix of (2.7).

In view of (2.5) and (2.8), it becomes clear why the information matrix $M_f(\xi, \overline{\theta})$ is a valid measure of (local) information content of the design ξ about the true model $f(\cdot, \theta^*)$, thus justifying its central role in locally optimal experimental design.

2.2 Some technical preliminaries

In this section, we collect some basic definitions and facts that are important for the optimal design of experiments and, in particular, for our convergence results.

Lemma 2.4. $\mathbb{R}_{pd}^{d \times d}$ is convex and open in $\mathbb{R}^{d \times d}$. Additionally, $\mathbb{R}_{psd}^{d \times d}$ is convex and the closure of $\mathbb{R}_{pd}^{d \times d}$ in $\mathbb{R}^{d \times d}$.

Proof. Straightforward verification.

2.2.1 Convexity and differentiability

As usual, for a subset S of some real vector space V, the convex hull conv(S) of S is the smallest convex set in V that comprises S.

Lemma 2.5 (Carathéodory). If S is an arbitrary subset of some finite-dimensional real vector space V, then every element of $\operatorname{conv}(S)$ can be written as a convex combination of at most $\dim V + 1$ points from S. Additionally, every element of $\operatorname{conv}(S) \cap \partial \operatorname{conv}(S)$ can be written as a convex combination of at most dim V points from S.

Proof. See Theorem 17.1 of [26] for a proof of the first part of the lemma and Appendix 2 of [33] for a proof of the second part of the lemma.

We recall that for an extended real-valued function $\Psi : S \to \mathbb{R} \cup \{\infty\}$ on some subset S of a real vector space V, the domain dom Ψ is defined as

$$\operatorname{dom} \Psi := \{ x \in S : \Psi(x) < \infty \}, \tag{2.9}$$

that is, the set of points where Ψ takes finite values. We also recall that a function $\Psi : C \to \mathbb{R} \cup \{\infty\}$ on some convex subset C of V is convex iff

$$\Psi(\alpha x + (1 - \alpha)y) \le \alpha \Psi(x) + (1 - \alpha)\Psi(y)$$
(2.10)

for all $x, y \in C$ and all $\alpha \in [0, 1]$. It is trivial to verify that the extended real-valued function $\Psi: C \to \mathbb{R} \cup \{\infty\}$ is convex if and only if dom Ψ is convex and the real-valued function $\Psi|_{\text{dom }\Psi}$ is convex. Similarly, $\Psi: C \to \mathbb{R} \cup \{\infty\}$ on some convex subset C of V is called strictly convex iff

$$\Psi(\alpha x + (1 - \alpha)y) < \alpha \Psi(x) + (1 - \alpha)\Psi(y)$$
(2.11)

for all $x, y \in \text{dom } \Psi$ with $x \neq y$ and all $\alpha \in (0, 1)$ (Section 26 of [26]). In other words, $\Psi : C \to \mathbb{R} \cup \{\infty\}$ is strictly convex if and only if its real-valued restriction $\Psi|_{\text{dom } \Psi}$ is strictly convex. We call $\Psi : C \to \mathbb{R} \cup \{\infty\}$ strictly mid-point convex iff (2.11) holds true with $\alpha := 1/2$ for all $x, y \in \text{dom } \Psi$ with $x \neq y$.

Lemma 2.6. Suppose that $\Psi : C \to \mathbb{R} \cup \{\infty\}$ is convex, where C is a convex subset of some real vector space. Then Ψ is strictly convex if and only if it is strictly mid-point convex.

Proof. Simple verification – to get the idea, draw a picture using the geometric interpretation of (strict) convexity.

As usual, a real-valued function $\Psi: S \to \mathbb{R}$ on some subset S of a real vector space V is called directionally differentiable at $x \in S$ in the direction $e \in V$ iff $t \mapsto \Psi(x + te)$ is right-differentiable at t = 0. Spelled out, this means that there exists a $t^* \in (0, \infty)$ such that $x + te \in S$ for all $t \in [0, t^*]$ and the limit

$$\partial_e \Psi(x) := \frac{\mathrm{d}}{\mathrm{d}t} \Psi(x+te) \big|_{t=0+} := \lim_{t \searrow 0} \frac{\Psi(x+te) - \Psi(x)}{t}$$
(2.12)

exists in \mathbb{R} . In this case, the limit (2.12) is called the directional derivative of Ψ at x in the direction e (Section 3.1 of [14]). Apart from directional derivatives, we will also need derivatives of real-valued functions defined on arbitrary subsets, instead of just open subsets of a normed vector space. So, let $\Psi : S \to \mathbb{R}$ be a real-valued function on some arbitrary subset S of a real normed vector space V with norm $\|\cdot\|$. We then call Ψ (continuously) differentiable iff it can be extended to a real-valued function $\tilde{\Psi} : \tilde{S} \to \mathbb{R}$ on some open subset \tilde{S} of V that is (continuously) differentiable in the usual (Fréchet) sense (Section VII.2 of [1] or Section 3.2 of [14], for instance). In this case, we will write

$$D\Psi(x)e := D\tilde{\Psi}(x)e \tag{2.13}$$

for the derivative of Ψ at $x \in S$ in the direction $e \in V$. In general, this derivative (2.13) depends on the chosen extension $\tilde{\Psi}$, of course. If, however, for a given $x \in S$ and $e \in V$ there exists a $t^* \in (0, \infty)$ such that $x + te \in S$ for all $t \in [0, t^*]$, then the derivative (2.13) is independent of the chosen differentiable extension $\tilde{\Psi}$ (because then $D\tilde{\Psi}(x)e = \partial_e\Psi(x)$ for every differentiable extension).

Lemma 2.7. If $M \in \mathbb{R}^{d \times d}_{pd}$ and $p \in (0, \infty)$, then for every direction $E \in \mathbb{R}^{d \times d}$ one has the following directional derivatives:

$$\frac{\mathrm{d}}{\mathrm{d}t}\log\det(M+tE)^{-1}\big|_{t=0+} = -\operatorname{tr}(M^{-1}E)$$
(2.14)

$$\frac{\mathrm{d}}{\mathrm{d}t}\operatorname{tr}((M+tE)^{-p})\big|_{t=0+} = -p\operatorname{tr}(M^{-p-1}E).$$
(2.15)

Additionally, the map $\mathbb{R}^{d \times d}_{pd} \ni M \mapsto M^{-p}$ is locally Lipschitz continuous for every $p \in (0, \infty)$.

Proof. See [19] (Theorem 8.2), for instance, for a proof of (2.14). We now prove (2.15) because we could not find a proof for non-integer p in the literature. So, let $p \in (0, \infty)$ and $M \in \mathbb{R}_{pd}^{d \times d}$ and $E \in \mathbb{R}^{d \times d}$ be fixed and write $M_t := M + tE$ for brevity. Also, let $f : \mathbb{C} \setminus (-\infty, 0] \to \mathbb{C}$ be the holomorphic function defined by $f(z) := z^{-p} := e^{-p \log(z)}$, where $\log : \mathbb{C} \setminus (-\infty, 0] \to \mathbb{C}$ denotes the principal arc of the complex logarithm. In particular,

$$f'(z) = -pz^{-p-1}$$
 $(z \in \mathbb{C} \setminus (-\infty, 0]).$ (2.16)

Choose now $t_0 > 0$ and $\delta > 0$ so small that $M_t + \delta \in \mathbb{R}^{d \times d}_{pd}$ for every $t \in [0, t_0]$ (Lemma 2.4). It then follows that the spectrum $\sigma(M_t)$ of M_t is contained in $[\delta, \infty) \subset \mathbb{C} \setminus (-\infty, 0]$ for all $t \in [0, t_0]$ and that there exists a closed path γ in $\mathbb{C} \setminus (-\infty, 0]$ that has winding number 1 around $\sigma(M_t)$ and winding number 0 around the complement $\mathbb{C} \setminus \sigma(M_t)$. So, by the holomorphic functional calculus [8] (Section VII.3), [27] (Section 10.23) and (2.16) that

$$(M+tE)^{-p} = f(M_t) = \frac{1}{2\pi i} \int_{\gamma} f(z)(z-M_t)^{-1} dz$$
(2.17)

$$\frac{1}{2\pi i} \int_{\gamma} f(z)(z - M_t)^{-2} dz = \frac{1}{2\pi i} \int_{\gamma} f'(z)(z - M_t)^{-1} dz = f'(M_t)$$
$$= -p(M + tE)^{-p-1}$$
(2.18)

for all $t \in [0, t_0]$, where the first equality in (2.18) follows by Cauchy's theorem. It further follows from (2.17) by taking the derivative inside the path integral (dominated convergence theorem) that

$$\frac{\mathrm{d}}{\mathrm{d}t}(M+tE)^{-p}\big|_{t=0+} = \frac{1}{2\pi\mathrm{i}} \int_{\gamma} f(z) \frac{\mathrm{d}}{\mathrm{d}t} (z-M_t)^{-1} \big|_{t=0+} \mathrm{d}z,$$
$$= \frac{1}{2\pi\mathrm{i}} \int_{\gamma} f(z) (z-M)^{-1} E(z-M)^{-1} \mathrm{d}z$$
(2.19)

So, by taking the trace in (2.19) and using its invariance under cyclic permutations in conjunction with (2.18) at t = 0, we see that

$$\frac{\mathrm{d}}{\mathrm{d}t}\operatorname{tr}((M+tE)^{-p})\big|_{t=0+} = \frac{1}{2\pi\mathrm{i}} \int_{\gamma} f(z)\operatorname{tr}\left((z-M)^{-1}E(z-M)^{-1}\right)\mathrm{d}z$$
$$= -p\operatorname{tr}(M^{-p-1}E), \qquad (2.20)$$

as desired. It remains to establish the local Lipschitz continuity of $\mathbb{R}^{d \times d}_{pd} \ni M \mapsto M^{-p}$. So, let \mathcal{M} be a compact subset of $\mathbb{R}^{d \times d}_{pd}$. It then follows that

$$\mathcal{M} \subset \{ M \in \mathbb{R}_{pd}^{d \times d} : c \le M \le C \}$$
(2.21)

for some positive constants $c, C \in (0, \infty)$. It further follows by the holomorphic functional calculus that

$$M^{-p} - N^{-p} = \frac{1}{2\pi i} \int_{\gamma} z^{-p} \left((z - M)^{-1} - (z - N)^{-1} \right) dz \qquad (M, N \in \mathcal{M})$$
(2.22)

for the tank-shaped closed path γ in $\mathbb{C} \setminus (-\infty, 0]$ that connects the four points c+ic, C+ic, C-ic, c-ic by two horizontal straight lines and, respectively, by two vertically oriented semi-circles. Clearly, the length of that path is

$$l(\gamma) = 2(C-c) + 2\pi c/2 = 2(C-c) + \pi c$$
(2.23)

and, moreover, the operator norm of the inverse of the matrices z - A for z on the path γ and $A \in \mathcal{M}$ can be estimated as

$$\left\| (z-A)^{-1} \right\| = \frac{1}{\operatorname{dist}(z,\sigma(A))} \le \frac{1}{\operatorname{dist}(z,[c,C])} \le \frac{2}{c} \qquad (z \in \operatorname{ran}(\gamma) \text{ and } A \in \mathcal{M})$$
(2.24)

because the matrices $A \in \mathcal{M}$ are normal matrices with spectrum $\sigma(A) \subset [c, C]$ by (2.21). Since $(z-M)^{-1} - (z-N)^{-1} = (z-M)^{-1}(N-M)(z-N)^{-1}$ we see from (2.22) with the help of (2.23) and (2.24) that

$$\left\| M^{-p} - N^{-p} \right\| \le \frac{2(C-c) + \pi c}{2\pi} (2/c)^{p+2} \left\| N - M \right\| \qquad (M, N \in \mathcal{M}).$$
(2.25)

And therefore, $\mathcal{M} \ni \mathcal{M} \mapsto \mathcal{M}^{-p}$ is Lipschitz continuous, as desired.

We finally turn to the notions of L-smoothness and μ -strong convexity [36], which are essential for our convergence rate results. Suppose $\Psi : C \to \mathbb{R}$ is a real-valued function on some convex subset C of a normed real vector space V with norm $\|\cdot\|$. Also, let $L \in [0, \infty)$ and $\mu \in [0, \infty)$ be given numbers. Ψ is then called L-smooth w.r.t. $\|\cdot\|$ iff Ψ is differentiable in the sense defined above and

$$\Psi(y) - \Psi(x) - D\Psi(x)(y-x) \le \frac{L}{2} \|y-x\|^2 \qquad (x, y \in C).$$
(2.26)

Similarly, Ψ is called μ -strongly convex w.r.t. $\|\cdot\|$ iff Ψ is differentiable in the sense defined above and

$$\Psi(y) - \Psi(x) - D\Psi(x)(y-x) \ge \frac{\mu}{2} \|y-x\|^2 \qquad (x, y \in C).$$
(2.27)

It should be noted that by the assumed convexity of C, the derivatives $D\Psi(x)(y-x) = \partial_{y-x}\Psi(x)$ appearing in the defining relations (2.26) and (2.27) are actually independent of the chosen differentiable extension $\tilde{\Psi}$ of Ψ . See the remarks following (2.13). We close with a simple sufficient condition for *L*-smoothness. **Lemma 2.8.** Suppose that $\Psi : \mathbb{R}_{psd}^{d \times d} \to \mathbb{R} \cup \{\infty\}$ is a mapping such that $\Psi|_{\text{dom }\Psi}$ is differentiable. Suppose further that $\mathcal{M} \subset \text{dom }\Psi$ is a convex subset and the derivative mapping $\mathcal{M} \ni \mathcal{M} \mapsto D\Psi(\mathcal{M})$ restricted to \mathcal{M} is Lipschitz continuous, that is, there exists an $L \in [0, \infty)$ such that

$$\left| \left(D\Psi(M') - D\Psi(M) \right) E \right| \le L|M' - M||E| \qquad (M, M' \in \mathcal{M} \text{ and } E \in \mathbb{R}^{d \times d}).$$
(2.28)

Then $\Psi|_{\mathcal{M}}$ is L-smooth w.r.t. $|\cdot|$.

Proof. Since $\Psi|_{\operatorname{dom}\Psi}$ is differentiable and \mathcal{M} is a convex subset of dom Ψ by assumption, it follows by (2.28) that $[0,1] \ni t \mapsto \Psi(M + t(N - M))$ is continuously differentiable for all $M, N \in \mathcal{M}$. So, by the mean value theorem and (2.28), we conclude

$$\Psi(N) - \Psi(M) - D\Psi(M)(N - M) \le \int_0^1 \left| \left(D\Psi(M + t(N - M)) - D\Psi(M) \right) (N - M) \right| dt$$
$$\le L \int_0^1 t \, dt \cdot |N - M|^2 = \frac{L}{2} |N - M|^2$$
(2.29)

for all $M, N \in \mathcal{M}$. And therefore, $\Psi|_{\mathcal{M}}$ is L-smooth w.r.t. $|\cdot|$, as desired.

2.2.2 Support and convergence of probability measures

As usual, a point x of some metric space X is called a support point of the probability measure $\xi \in \Xi(X)$ iff $\xi(B_{\delta}(x)) > 0$ for every $\delta > 0$ (where $B_{\delta}(x)$ denotes the open δ -ball around x in X, of course). And accordingly, the set of all support points of a measure $\xi \in \Xi(X)$ is called its support, in short:

$$\operatorname{supp} \xi := \{ x \in X : x \text{ is a support point of } \xi \}.$$

$$(2.30)$$

Lemma 2.9. Suppose that X is a compact metric space and let $\xi \in \Xi(X)$. Then supp ξ is the largest closed subset C of X with $\xi(X \setminus C) = 0$. In particular,

$$\xi(A) = \xi(A \cap \operatorname{supp} \xi) \qquad (A \in \mathcal{B}_X).$$
(2.31)

Additionally, if supp ξ is finite, then $\xi(\{x\}) > 0$ for every $x \in \text{supp } \xi$ and

$$\xi = \sum_{x \in \operatorname{supp} \xi} \xi(\{x\}) \delta_x.$$
(2.32)

Proof. As a compact metric space, X is in particular separable. Consequently, the first part of the lemma (up until (2.31)) follows from Theorem II.2.1 of [20] (note that a measure in [20] is always meant to be a probability measure, see the footnote in Section II.1 of [20]). Suppose now that supp ξ is finite. Then, for every $x \in \text{supp } \xi$, there is a $\delta > 0$ such that $\{x\} = B_{\delta}(x) \cap \text{supp } \xi$ and therefore, by (2.31) and the definition of support points,

$$\xi(\{x\}) = \xi(B_{\delta}(x) \cap \operatorname{supp} \xi) = \xi(B_{\delta}(x)) > 0.$$

Additionally, it follows by (2.31) that

$$\xi(A) = \xi(A \cap \operatorname{supp} \xi) = \sum_{x \in \operatorname{supp} \xi} \xi(A \cap \{x\}) = \sum_{x \in \operatorname{supp} \xi} \xi(\{x\})\delta_x(A) \qquad (A \in \mathcal{B}_X)$$

and therefore (2.32) holds true.

We recall that a sequence (ξ_n) of probability measures in $\Xi(X)$ with some metric space X is said to converge weakly (or in distribution) to a probability measure $\xi \in \Xi(X)$ iff

$$\int_{X} m(x) \,\mathrm{d}\xi_n(x) \longrightarrow \int_{X} m(x) \,\mathrm{d}\xi(x) \qquad (n \to \infty) \tag{2.33}$$

for every $m \in C_{\rm b}(X,\mathbb{R}) := \{$ bounded continuous functions $X \to \mathbb{R} \}$ (Section II.6 of [20]).

Lemma 2.10 (Prohorov). If X is a compact metric space, then $\Xi(X)$ endowed with the weak topology is a metrizable compact space. In particular, $\Xi(X)$ is sequentially compact.

Proof. Invoke Theorem II.6.4 of [20] and recall that for metric spaces, compactness and sequential compactness are equivalent (Theorem III.3.4 of [1]).

2.3 Common design criteria

In this section, we recall the design criteria Ψ that are most commonly used in practice and record their monotonicity, convexity, continuity, and differentiability properties. In particular, we establish the strong convexity of a large class of practically relevant design criteria.

2.3.1 Simple design criteria

We begin by discussing a scale of design criteria Ψ_p that comprises the D- and the A-criterion as special cases. Specifically, Ψ_p is defined by

$$\Psi_0(M) := \log \det(M^{-1})$$
 and $\Psi_p(M) := (\operatorname{tr}(M^{-p}))^{1/p}$ $(p \in (0, \infty))$ (2.34)

for $M \in \mathbb{R}_{pd}^{d \times d}$ and by

$$\Psi_p(M) := \infty \qquad (p \in [0, \infty)) \tag{2.35}$$

for $M \in \mathbb{R}^{d \times d}_{psd} \setminus \mathbb{R}^{d \times d}_{pd}$. Commonly, Ψ_0 and Ψ_1 are called the (logarithmic) D-criterion and the A-criterion, respectively. With the help of a spectral decomposition of a given $M \in \mathbb{R}^{d \times d}_{pd}$, we immediately see that

$$\Psi_0(M) = -\sum_{i=1}^d \log(\lambda_i(M)) \quad \text{and} \quad \Psi_p(M) = \left(\sum_{i=1}^d \lambda_i(M)^{-p}\right)^{1/p}, \quad (2.36)$$

where $\lambda_1(M), \ldots, \lambda_d(M)$ are the eigenvalues of M counted according to their multiplicities and ordered increasingly. It is also easy to verify that $(1/d)\Psi_0(M) = \lim_{p \searrow 0} \log\left((1/d)^{1/p}\Psi_p(M)\right)$ (just calculate the derivative of $[0, \infty) \ni p \mapsto \log\left((1/d)\sum_{i=1}^d \lambda_i(M^{-1})^p \text{ at } p = 0\right)$.

Lemma 2.11. Suppose that $p \in [0, \infty)$ and $R \in (0, \infty)$. If $M \in \mathbb{R}^{d \times d}_{psd}$ with $\Psi_p(M) \leq R$, then

$$M \ge \mu_{p,R}(\|M\|),$$
 (2.37)

where $\mu_{0,R}(\|M\|) := e^{-R} \|M\|^{-(d-1)}$ and $\mu_{p,R}(\|M\|) := 1/R$ for $p \in (0,\infty)$.

Proof. Suppose first that p = 0 and that $M \in \mathbb{R}^{d \times d}_{psd}$ with $\Psi_0(M) \leq R < \infty$. It then follows by (2.34)-(2.36) that $M \in \mathbb{R}^{d \times d}_{pd}$ and

$$\log \lambda_i(M) \ge -R - \sum_{j \ne i} \log \lambda_j(M) \ge -R - (d-1) \log \|M\| \qquad (i \in \{1, \dots, d\}).$$
(2.38)

And therefore we obtain the claimed estimate in the case p = 0 as follows:

$$M \ge \min\{\lambda_i(M) : i \in \{1, \dots, d\}\} \ge e^{-R} \|M\|^{-(d-1)} = \mu_{0,R}(\|M\|),$$
(2.39)

Suppose now that $p \in (0,\infty)$ and that $M \in \mathbb{R}^{d \times d}_{psd}$ with $\Psi_p(M) \leq R < \infty$. It then follows by (2.34)-(2.36) that $M \in \mathbb{R}^{d \times d}_{pd}$ and

$$1/\lambda_i(M) \le \left(\sum_{i=1}^d \lambda_i(M)^{-p}\right)^{1/p} \le R \qquad (i \in \{1, \dots, d\}).$$
(2.40)

And therefore we obtain

$$M \ge \min\{\lambda_i(M) : i \in \{1, \dots, d\}\} \ge 1/R = \mu_{p,R}(\|M\|),$$
(2.41)

which is the claimed estimate in the case $p \in (0, \infty)$.

Proposition 2.12. Suppose that $p \in [0, \infty)$. Then Ψ_p is antitonic, strictly convex, and lower semicontinuous with dom $\Psi_p = \mathbb{R}^{d \times d}_{pd}$. Additionally, the restriction $\Psi_p|_{\mathbb{R}^{d \times d}_{pd}}$ is continuously differentiable with derivative given by

$$D\Psi_0(M)E = -\operatorname{tr}(M^{-1}E)$$
(2.42)

$$D\Psi_p(M)E = -\left(\operatorname{tr}(M^{-p})\right)^{1/p-1}\operatorname{tr}(M^{-p-1}E) \qquad (p \in (0,\infty))$$
(2.43)

for $M \in \mathbb{R}^{d \times d}_{pd}$ and $E \in \mathbb{R}^{d \times d}$. In particular, the derivative map $\mathbb{R}^{d \times d}_{pd} \ni M \mapsto D\Psi_p(M)$ is locally Lipschitz continuous.

Proof. It is clear by the definition (2.34)-(2.35) that dom $\Psi_p = \mathbb{R}_{pd}^{d \times d}$ and that $\Psi_p|_{dom \Psi_p}$ is continuous (Lemma 2.7) for $p \in [0, \infty)$. With this continuity property and Lemma 2.11, in turn, the lower semicontinuity of Ψ_p for $p \in [0, \infty)$ easily follows. Also, the antitonicity of Ψ_p for $p \in [0, \infty)$ immediately follows by (2.36) and the well-known isotonicity of the eigenvalue maps $M \mapsto \lambda_i(M)$ for $i \in \{1, \ldots, d\}$ (Theorem 11.9 of [19]). In order to see the directional differentiability of $\Psi_p|_{dom \Psi_p}$ and the formulas (2.42) and (2.43), we have only to apply Lemma 2.7. It is clear from (2.42) and (2.43) that

$$\mathbb{R}^{d \times d} \ni E \mapsto \partial_E \Psi_n(M) \in \mathbb{R}$$

is a bounded linear map $D\Psi_p(M)$ for every $M \in \mathbb{R}_{pd}^{d \times d}$ and that $\mathbb{R}_{pd}^{d \times d} \ni M \mapsto D\Psi_p(M)$, in turn, is continuous (Lemma 2.7). Consequently, $\Psi_p|_{\dim \Psi_p}$ is continuously (Fréchet) differentiable by a standard differentiability criterion (Proposition 4.8 of [41], for instance). Additionally, $\mathbb{R}_{pd}^{d \times d} \ni M \mapsto D\Psi_p(M)$ is locally Lipschitz continuous by the formulas (2.42) and (2.43) of Lemma 2.7 and the last part of Lemma 2.7. It remains to establish the strict convexity of Ψ_p for all $p \in [0, \infty)$. Strict convexity of Ψ_0 follows by Theorem 11.25 in [19]. Convexity of Ψ_p in the case $p \in [1, \infty)$ follows from (2.36) by noting first that

$$\lambda_i ((\alpha M + (1 - \alpha)N)^{-1}) \le \lambda_i (\alpha M^{-1} + (1 - \alpha)N^{-1}) \qquad (i \in \{1, \dots, d\})$$
(2.44)

for arbitrary $M, N \in \mathbb{R}_{pd}^{d \times d}$ and all $\alpha \in [0, 1]$ by virtue of the convexity of matrix inversion on $\mathbb{R}_{pd}^{d \times d}$ (Corollary V.2.6 of [4]) and by applying then the triangle inequality for the *p*-Schatten norms (Theorem 11.26 of [19] which is valid for $p \in [1, \infty)$) to the right-hand side of (2.44). Strict convexity of Ψ_p for $p \in [1, \infty)$ can be seen as follows: for $M \neq N$ and $\alpha = 1/2$ one has strict inequality in (2.44) for at least one $i \in \{1, \ldots, d\}$ (this follows by the explicit formula from Exercise V.1.15 of [4]) and thus the same arguments as for mere convexity above yield strict mid-point convexity which, in turn, proves strict convexity (Lemma 2.6). Strict convexity of Ψ_p in the case $p \in (0, 1)$ is stated in the first and second paragraph on page 864 of [17] – a proof of this is indicated on page 863 (Case 2) of [17].

In some cases, one is interested in further generalizations of the design criteria $\Psi_{p,Q}$, namely in the design criteria $\Psi_{p,Q}: \mathbb{R}_{psd}^{d \times d} \to \mathbb{R} \cup \{\infty\}$ defined by

$$\Psi_{0,Q}(M) := \log \det(Q^{\top} M^{-} Q) \quad \text{and} \quad \Psi_{p,Q}(M) := (\operatorname{tr}(Q^{\top} M^{-} Q)^{p})^{1/p} \quad (2.45)$$

for $p \in (0,\infty)$ and for all $M \in \mathbb{R}^{d \times d}_{psd}$ with $ran(Q) \subset ran(M)$ and defined by

$$\Psi_{p,Q}(M) := \infty \qquad (p \in [0,\infty)) \tag{2.46}$$

else. See [17] or [22] (Section 5.1.2). In the above definitions, $Q \in \mathbb{R}^{d \times s}$ with some $s \leq d$ and M^- denotes any generalized inverse of M (Section 9.1 of [12]), while ran(A) denotes the range of a matrix A. Such design criteria arise, for instance, if one only wants to estimate a linear function $Q^{\top}\theta$ of the model parameter (as opposed to the whole model parameter vector θ).

Corollary 2.13. Suppose that $p \in [0, \infty)$ and $Q \in \mathbb{R}^{d \times s}$ with full column rank $\operatorname{rk} Q = s \leq d$. Then $\Psi_{p,Q}$ is antitonic, convex, and lower semicontinuous. Additionally, the restriction $\Psi_{p,Q}|_{\mathbb{R}^{d \times d}_{pd}}$ is continuously differentiable and the derivative map

$$\mathbb{R}^{d \times d}_{\mathrm{pd}} \ni M \mapsto D\Psi_{p,Q}(M)$$

is locally Lipschitz continuous.

Proof. Since Q has full column rank s by assumption, it follows by Theorem 3.15 of [25] that $\Psi_{p,Q}$ can be expressed in terms of information matrices $C_Q(M)$ (Section 3.2 of [25]). Specifically,

$$\Psi_{p,Q}(M) = \Psi_p(C_Q(M)) \qquad (M \in \mathbb{R}^{d \times d}_{\text{psd}}).$$
(2.47)

And from this representation, in turn, the antitonicity, convexity and lower semicontinuity of $\Psi_{p,Q}$ can be concluded using the corresponding properties of Ψ_p (Proposition 2.12) and of the information matrix mapping C_Q (Theorem 3.13 of [25]). (In order to obtain the lower semicontinuity of $\Psi_{p,Q}$, assume $M_n, M \in \mathbb{R}^{d \times d}_{psd}$ with $M_n \longrightarrow M$. Setting $M'_n := M_n + ||M - M_n||$, we observe that $M'_n \longrightarrow M$ as $n \to \infty$ and that $M'_n \ge M$ and hence $C_Q(M'_n) \ge C_Q(M)$ for all $n \in \mathbb{N}$ by Theorem 3.13 of [25]. Applying Theorem 3.13.b of [25] to (M'_n) , we then arrive at the desired lower semicontinuity estimate, using the lower semicontinuity of Ψ_p in conjunction with the antitonicity of Ψ_p and the estimate $C_Q(M'_n) \ge C_Q(M_n)$.) Additionally, from (2.47), we easily obtain the continuous differentiability of $\Psi_{p,Q}|_{\mathbb{R}^{d \times d}_{pd}}$ and the local Lipschitz continuity of the derivative map. We have only to use that

$$C_Q(M) = \left(Q^\top M^{-1}Q\right)^{-1} \in \mathbb{R}^{d \times d}_{\mathrm{pd}} \qquad (M \in \mathbb{R}^{d \times d}_{\mathrm{pd}})$$
(2.48)

(Section 3.3 and Theorem 3.15 of [25]) and combine this with the continuous differentiability of $\Psi_p|_{\mathbb{R}^{d\times d}_{rd}}$ and the local Lipschitz continuity of the derivative map (Proposition 2.12).

Sometimes it is more convenient to work with the modified design criteria Ψ_p and $\Psi_{0,Q}$ defined by

$$\widetilde{\Psi}_0(M) := \Psi_0(M) \quad \text{and} \quad \widetilde{\Psi}_p(M) := (\Psi_p(M))^p \quad (p \in (0, \infty))$$
(2.49)

and, respectively, by $\tilde{\Psi}_{0,Q}(M) := \Psi_{0,Q}(M)$ and $\tilde{\Psi}_{p,Q}(M) := (\Psi_{p,Q}(M))^p$. See [38], for instance. Since $[0,\infty) \ni t \mapsto t^p$ is convex and monotonically increasing for $p \in [1,\infty)$, it follows by Proposition 2.12 and Corollary 2.13 that for $p \in [1,\infty)$ the modified criteria $\tilde{\Psi}_p$ and $\tilde{\Psi}_{p,Q}$ are antitonic, lower semicontinuous and convex as well. As we will show now, for $p \in \mathbb{N}_0$ the modified criteria $\tilde{\Psi}_p$ are even strongly convex.

Corollary 2.14. Suppose $C \in (0, \infty)$ and let $\mathcal{M} := \{A \in \mathbb{R}^{d \times d}_{pd} : A \leq C\}$. Then $\tilde{\Psi}_p|_{\mathcal{M}}$ for every $p \in \mathbb{N}_0$ is μ -strongly convex w.r.t. $|\cdot|$, where $\mu := \max\{1, p\}(p+1)/C^{p+2}$. In particular, $\Psi_0|_{\mathcal{M}}$ and $\Psi_1|_{\mathcal{M}}$ are strongly convex.

Proof. Suppose $p \in \mathbb{N}_0$ and write $\Psi := \tilde{\Psi}_p$ and $\varepsilon_p := \max\{1, p\}$ for brevity. Also, let $M, N \in \mathcal{M}$ and write E := N - M and $M_t := M + tE$ for $t \in [0, 1]$. Since $\Psi|_{\operatorname{dom}\Psi}$ is continuously differentiable (Proposition 2.12) and \mathcal{M} is a convex subset of dom $\Psi = \mathbb{R}^{d \times d}_{\operatorname{pd}}$, it follows by the mean value theorem that

$$\Psi(N) - \Psi(M) - D\Psi(M)(N - M) = \int_0^1 \left(D\Psi(M_t) - D\Psi(M) \right) E \, \mathrm{d}t$$
$$= \varepsilon_p \int_0^1 \operatorname{tr} \left((M^{-p-1} - M_t^{-p-1}) E \right) \, \mathrm{d}t = \varepsilon_p \sum_{q=1}^{p+1} \int_0^1 t \cdot \operatorname{tr} \left(M^{-q} E M_t^{-(p+2-q)} E \right) \, \mathrm{d}t, \quad (2.50)$$

where we used that $D\Psi(A)E = -\varepsilon_p \operatorname{tr}(A^{-p-1}E)$ for $A \in \mathbb{R}_{pd}^{d \times d}$ (Lemma 2.7) and that

$$M^{-p-1} - M_t^{-p-1} = t \sum_{q=1}^{p+1} M^{-q} E M_t^{-(p+2-q)}$$

for all $t \in [0,1]$ (induction over $p \in \mathbb{N}_0$). Since $M, M_t \in \mathcal{M}$, it further follows that

$$M_t^{-k} \ge C^{-k}$$
 and $M^{-k} \ge C^{-k}$ $(k \in \mathbb{N} \text{ and } t \in [0,1]).$ (2.51)

With the help of cyclic permutations under the trace and of (2.51) we conclude that

$$\operatorname{tr}\left(M^{-q}EM_{t}^{-(p+2-q)}E\right) = \operatorname{tr}\left((EM^{-q/2})^{\top}M_{t}^{-(p+2-q)}EM^{-q/2}\right)$$
$$\geq C^{-(p+2-q)}\cdot\operatorname{tr}\left((EM^{-q/2})^{\top}EM^{-q/2}\right) = C^{-(p+2-q)}\cdot\operatorname{tr}\left(EM^{-q}E\right)$$
$$\geq C^{-(p+2-q)}C^{-q}\cdot\operatorname{tr}(E^{2}) = C^{-(p+2)}|E|^{2}$$
(2.52)

for every $t \in [0, 1]$ and $q \in \{1, \ldots, p+1\}$. Inserting now (2.52) into (2.50), we immediately obtain the claimed $\varepsilon_p(p+1)/C^{p+2}$ -strong convexity of $\tilde{\Psi}_p|_{\mathcal{M}}$ w.r.t. $|\cdot|$.

2.3.2 Composite design criteria

We now discuss three common ways of constructing new design criteria from more basic ones, namely (i) incorporating information from a previous stage, (ii) taking averages, and (iii) taking suprema. In the case of (i), one speaks of two-stage design criteria. Important special cases of (ii) and (iii) are the weighted A-criterion (2.57) and the E-criterion (2.60).

Proposition 2.15. Suppose that $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is any mapping (design criterion) and let $M_0 \in \mathbb{R}^{d \times d}_{psd}$ and $\alpha \in [0, 1)$. Also, let $\Psi^{(\alpha)} : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ be the corresponding two-stage design criterion, that is,

$$\Psi^{(\alpha)}(M) := \Psi\left(\alpha M^0 + (1-\alpha)M\right) \qquad (M \in \mathbb{R}^{d \times d}_{\text{psd}}).$$
(2.53)

Convexity, lower semicontinuity and antitonicity then carry over from Ψ to $\Psi^{(\alpha)}$. Additionally, if $\Psi|_{\text{dom }\Psi}$ is differentiable, then $\Psi^{(\alpha)}|_{\text{dom }\Psi^{(\alpha)}}$ is differentiable as well with derivative given by

$$D\Psi^{(\alpha)}(M)E = (1-\alpha)D\Psi(\alpha M^0 + (1-\alpha)M)E \qquad (M \in \operatorname{dom}\Psi^{(\alpha)} \text{ and } E \in \mathbb{R}^{d \times d}).$$
 (2.54)

Proof. Straightforward verifications using our definition of differentiability and of derivatives of functions on arbitrary (not necessarily open) subsets of the vector space $\mathbb{R}^{d \times d}$. See the remarks around (2.13).

Proposition 2.16. Suppose that $\Psi_u : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is convex with dom $\Psi_u = \mathbb{R}^{d \times d}_{pd}$ for every $u \in U$, where U is a compact metric space. Suppose further that $\mathbb{R}^{d \times d}_{pd} \times U \ni (M, u) \mapsto \Psi_u(M) \in \mathbb{R}$ is continuous and that $\overline{\Psi} : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is an average of the Ψ_u , that is,

$$\overline{\Psi}(M) := \int_{U} \Psi_u(M) \,\mathrm{d}\zeta(u) \qquad (M \in \mathbb{R}^{d \times d}_{\mathrm{psd}})$$
(2.55)

with some finite measure ζ on \mathcal{B}_U . Then $\overline{\Psi}|_{\mathbb{R}^{d \times d}_{pd}}$ is convex and continuous and dom $\overline{\Psi} = \mathbb{R}^{d \times d}_{pd}$. Additionally, the following assertions hold true:

- (i) If Ψ_u is antitonic for every $u \in U$, then $\overline{\Psi}$ is antitonic as well.
- (ii) If Ψ_u is lower semicontinuous and antitonic for every $u \in U$, then $\overline{\Psi}$ is lower semicontinuous as well.

(iii) If $\Psi_u|_{\mathbb{R}^{d\times d}_{pd}}$ is directionally differentiable uniformly w.r.t. $u \in U$, then $\overline{\Psi}|_{\mathbb{R}^{d\times d}_{pd}}$ is directionally differentiable as well with

$$\partial_E \overline{\Psi}(M) = \int_U \partial_E \Psi_u(M) \,\mathrm{d}\zeta(u) \qquad (M \in \mathbb{R}^{d \times d}_{\mathrm{pd}} \text{ and } E \in \mathbb{R}^{d \times d}). \tag{2.56}$$

Proof. Simple verification using Fatou's lemma in the version for a sequence of measurable, not necessarily non-negative, functions with an integrable minorant. (At first glance, the antitonicity assumption in (ii) might seem superfluous. We impose it because then for every convergent sequence (M_n) in $\mathbb{R}^{d\times d}_{psd}$, we have

$$\Psi_u(M_n) \ge \Psi_u(C)$$
 $(n \in \mathbb{N} \text{ and } u \in U),$

where $C \in \mathbb{R}_{pd}^{d \times d}$ is an arbitrary positive definite upper bound of the M_n w.r.t. the standard partial order on $\mathbb{R}_{psd}^{d \times d}$. And therefore $u \mapsto \Psi_u(C)$ is a continuous, hence ζ -integrable, minorant of the functions $u \mapsto \Psi_u(M_n)$, whence Fatou's lemma in the mentioned version can be applied.)

As a simple application of the above result, one can derive standard properties of the weighted A-criterion defined by

$$\Psi_W(M) := \begin{cases} \operatorname{tr}(WM^{-1}), & M \in \mathbb{R}_{\mathrm{pd}}^{d \times d} \\ \infty, & M \in \mathbb{R}_{\mathrm{psd}}^{d \times d} \setminus \mathbb{R}_{\mathrm{pd}}^{d \times d} \end{cases},$$
(2.57)

where $W \in \mathbb{R}_{psd}^{d \times d}$ is some fixed positive semidefinite matrix.

Proposition 2.17. Suppose that $\Psi_u : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is convex with dom $\Psi_u = \mathbb{R}^{d \times d}_{pd}$ for every $u \in U$, where U is a compact metric space. Suppose further that $\mathbb{R}^{d \times d}_{pd} \times U \ni (M, u) \mapsto \Psi_u(M) \in \mathbb{R}$ is continuous and that $\overline{\Psi} : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is the supremum of the Ψ_u , that is,

$$\overline{\Psi}(M) := \sup_{u \in U} \Psi_u(M) \qquad (M \in \mathbb{R}^{d \times d}_{\text{psd}}).$$
(2.58)

Then $\overline{\Psi}|_{\mathbb{R}^{d \times d}_{pd}}$ is convex and continuous and dom $\overline{\Psi} = \mathbb{R}^{d \times d}_{pd}$. Additionally, the following assertions hold true:

- (i) If Ψ_u is antitonic for every $u \in U$, then $\overline{\Psi}$ is antitonic as well.
- (ii) If Ψ_u is lower semicontinuous for every $u \in U$, then $\overline{\Psi}$ is lower semicontinuous as well.
- (iii) If $\Psi_u|_{\mathbb{R}^{d\times d}_{pd}}$ is directionally differentiable uniformly w.r.t. $u \in U$, then $\overline{\Psi}|_{\mathbb{R}^{d\times d}_{pd}}$ is directionally differentiable as well with

$$\partial_E \overline{\Psi}(M) = \sup_{u \in U(M)} \partial_E \Psi_u(M) \qquad (M \in \mathbb{R}^{d \times d}_{\mathrm{pd}} \text{ and } E \in \mathbb{R}^{d \times d}), \tag{2.59}$$

where
$$U(M) := \operatorname{argmax}_{u \in U} \Psi_u(M) = \{ u \in U : \Psi_u(M) = \overline{\Psi}(M) \}.$$

Proof. Simple verification using Theorem 3.2 from [23] in the slightly generalized version where the normed space B is replaced by an open subset of a normed space. (It is easy to see that the proofs in [23] remain valid in this more general situation.)

As a simple application of the above result, one can derive standard properties of the E-criterion defined by

$$\Psi_{\infty}(M) := \begin{cases} \lambda_{\max}(M^{-1}), & M \in \mathbb{R}^{d \times d}_{\mathrm{pd}} \\ \infty, & M \in \mathbb{R}^{d \times d}_{\mathrm{psd}} \setminus \mathbb{R}^{d \times d}_{\mathrm{pd}} \end{cases},$$
(2.60)

where $\lambda_{\max}(M^{-1}) = 1/\lambda_{\min}(M)$ denotes the largest eigenvalue of M^{-1} . In view of (2.36) it is clear that $\Psi_{\infty}(M) = \lim_{p \to \infty} \Psi_p(M)$ for every $M \in \mathbb{R}^{d \times d}_{psd}$, explaining the notation Ψ_{∞} .

2.4 Solvability of optimal design problems

In this section, we address the solvability of optimal design problems or, more precisely, of optimal design problems of the form

$$\min_{\xi \in \Xi(X)} \Psi(M(\xi)), \tag{2.61}$$

where Ψ is an appropriate design criterion, X is the design space, $\Xi(X)$ is the set of probability measures on \mathcal{B}_X , and $M(\xi)$ is the information matrix of the design ξ . A design $\xi^* \in \Xi(X)$ is called an ε -optimal design for $\Psi \circ M$ iff it is an ε -approximate solution to (2.61), that is,

$$\Psi(M(\xi^*)) \le \inf_{\xi \in \Xi(X)} \Psi(M(\xi)) + \varepsilon.$$
(2.62)

In particular, a design ξ^* is called an *optimal design for* $\Psi \circ M$ iff it is a solution to (2.61) or, in other words, iff it is an ε -optimal design with $\varepsilon = 0$. In all results to come, we will need the following basic assumptions on the design space X and the information matrices $M(\xi)$.

Condition 2.18. X is a compact metric space, $m \in C(X, \mathbb{R}^{d \times d}_{psd})$, and $M : \Xi(X) \to \mathbb{R}^{d \times d}_{psd}$ is the corresponding information matrix map defined by

$$M(\xi) = \int_X m(x) \,\mathrm{d}\xi(x) \qquad (\xi \in \Xi(X)). \tag{2.63}$$

Lemma 2.19. Suppose that Condition 2.18 is satisfied. Then for every $M \in M(\Xi(X))$, there exists a design $\xi_0 \in \Xi(X)$ with at most d(d+1)/2 + 1 support points such that $M(\xi_0) = M$. Additionally, for every boundary point $M \in \partial M(\Xi(X))$, there even exists a design $\xi_0 \in \Xi(X)$ with at most d(d+1)/2 support points such that $M(\xi_0) = M$.

Proof. Consider the set $S := \{m(x) : x \in X\}$. Since X is compact and $m \in C(X, \mathbb{R}_{psd}^{d \times d})$, S is a compact subset of the vector space $V := \mathbb{R}_{sym}^{d \times d}$. Additionally, m is easily seen to be a uniform limit of \mathcal{B}_X -measurable functions m_k with finitely many values in S. (Indeed, the m_k can be constructed in a similar way as in Corollary X.1.13 of [1].) Consequently, for every $\xi \in \Xi(X)$, we have

$$M(\xi) = \int_X m(x) \,\mathrm{d}\xi(x) = \lim_{k \to \infty} \int_X m_k(x) \,\mathrm{d}\xi(x) \in \overline{\mathrm{conv}}(S) = \mathrm{conv}(S), \tag{2.64}$$

where the last equality follows by Theorem 17.2 of [26]. And conversely, for every convex combiniation $\sum_{i=1}^{n} w_i m(x_i) \in \text{conv}(S)$, we have

$$\sum_{i=1}^{n} w_i m(x_i) = M(\xi) \in M(\Xi(X)) \quad \text{for} \quad \xi := \sum_{i=1}^{n} w_i \delta_{x_i} \in \Xi(X).$$
(2.65)

So, combining (2.64) and (2.65), we see that

$$M(\Xi(X)) = \{M(\xi) : \xi \in \Xi(X)\} = \operatorname{conv}(S) \subset V.$$
(2.66)

And therefore the assertions follow by virtue of Lemma 2.5 from (2.65) and (2.66), taking into account that dim V = d(d+1)/2 and that $\operatorname{conv}(S) \cap \partial \operatorname{conv}(S) = \partial \operatorname{conv}(S)$ by the last equality in (2.64).

With the above preliminaries, one easily obtains the following existence result for optimal designs.

Theorem 2.20. Suppose that Condition 2.18 is satisfied and that $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is lower semicontinuous. Then there exists an optimal design for $\Psi \circ M$ with at most d(d+1)/2 + 1 support points. If, in addition, Ψ is antitonic, then there even exists an optimal design for $\Psi \circ M$ with at most d(d+1)/2 support points.

Proof. As a first step, we show that there exists an optimal design for $\Psi \circ M$ at all. Indeed, let (ξ^n) be a minimizing sequence for $\Psi \circ M$, that is, $\xi^n \in \Xi(X)$ and

$$\Psi(M(\xi^n)) \longrightarrow \inf_{\xi \in \Xi(X)} \Psi(M(\xi)) \qquad (n \to \infty).$$
(2.67)

Since $\Xi(X)$ is sequentially compact (Lemma 2.10), there exists a subsequence (ξ^{n_k}) and a ξ^* such that

$$\xi^* \in \Xi(X)$$
 and $\xi^{n_k} \longrightarrow \xi^*$ $(k \to \infty).$ (2.68)

Since $m \in C(X, \mathbb{R}^{d \times d}_{psd}) = C_{b}(X, \mathbb{R}^{d \times d}_{psd})$, the relation (2.68) also implies

$$M(\xi^{n_k}) = \int_X m(x) \,\mathrm{d}\xi^{n_k}(x) \longrightarrow \int_X m(x) \,\mathrm{d}\xi^*(x) = M(\xi^*) \qquad (k \to \infty).$$
(2.69)

Since, moreover, Ψ is lower semicontinuous, it follows from (2.69) that

$$\Psi(M(\xi^*)) \le \liminf_{k \to \infty} \Psi(M(\xi^{n_k})).$$
(2.70)

Inserting now (2.67) and (2.68.a) into (2.70), we finally obtain

$$\inf_{\xi \in \Xi(X)} \Psi(M(\xi)) \le \Psi(M(\xi^*)) \le \liminf_{k \to \infty} \Psi(M(\xi^{n_k})) = \inf_{\xi \in \Xi(X)} \Psi(M(\xi))$$
(2.71)

and therefore ξ^* is an optimal design for $\Psi \circ M$, as desired.

As a second step, we show that there also exists an optimal design ξ^* for $\Psi \circ M$ with at most d(d+1)/2+1 support points. Indeed, let ξ^* be an arbitrary an optimal design for $\Psi \circ M$ (which exists by the first step). Lemma 2.19 then yields a design ξ_0^* with at most d(d+1)/2+1 support points such that

$$M(\xi_0^*) = M(\xi^*) \tag{2.72}$$

In view of (2.72) and the optimality of ξ^* , the finitely supported design ξ_0^* is optimal for $\Psi \circ M$ as well, as desired.

As a third and last step, we show that under the additional antitonicity assumption there even exists an optimal design ξ^* with at most d(d+1)/2 support points. Indeed, let the additional antitonicity assumption be satisfied and let ξ^* be an arbitrary optimal design for $\Psi \circ M$ (which exists by the first step). Since $M(\xi^*) \in M(\Xi(X))$ and $M(\Xi(X))$ is compact, there exists an $\alpha^* \in [0, \infty)$

$$M(\xi^*) + \alpha^* I \in \partial M(\Xi(X)) \subset M(\Xi(X)), \tag{2.73}$$

where I denotes the identity matrix, and therefore there also exists a $\xi^{**} \in \Xi(X)$ such that

$$M(\xi^{**}) = M(\xi^*) + \alpha^* I \in \partial M(\Xi(X)).$$

$$(2.74)$$

In view of the antitonicity of Ψ and the optimality of ξ^* , we conclude from (2.74) that ξ^{**} is an optimal design for $\Psi \circ M$ with $M(\xi^{**}) \in \partial M(\Xi(X))$. Applying now Lemma 2.19 to $M(\xi^{**})$, we see that there also exists an optimal design ξ_0^* with at most d(d+1)/2 support points, as desired.

We point out that the lower semicontinuity assumption of the above theorem cannot be dropped. Indeed, as we will show in the next example, the optimal design problem for the weighted A-criterion (2.57) (with non-positive-definite weight matrix W) has no solution, in general. In particular, the existence statement of Theorem 2.2 from [10] is false as it stands.

Example 2.21. Consider a discrete metric space $X := \{x_1, x_2\}$ consisting of two elements and let $m : X \to \mathbb{R}^{2 \times 2}_{psd}$ be defined by

$$m(x_1) := \operatorname{diag}(1,0)$$
 and $m(x_2) := \operatorname{diag}(0,1).$ (2.75)

Also, let $\Psi:\mathbb{R}^{2\times 2}_{psd}\to\mathbb{R}\cup\{\infty\}$ be defined by

$$\Psi(M) := e_1^{\top} M^{-1} e_1 \quad (M \in \mathbb{R}_{pd}^{2 \times 2}) \quad \text{and} \quad \Psi(M) := \infty \quad (M \in \mathbb{R}_{psd}^{2 \times 2} \setminus \mathbb{R}_{pd}^{2 \times 2}), \tag{2.76}$$

where $e_1 := (1,0)^{\top} \in \mathbb{R}^2$. In other words, Ψ is the weighted A-criterion (2.57) with weight matrix W being the orthogonal projection on e_1 . With these definitions, it is easy to see that all assumptions of the existence theorem (Theorem 2.2) of [10] are satisfied, but there exists no optimal design for $\Psi \circ M$ (because Ψ fails to satisfy the lower semicontinuity assumption of our existence theorem above). Indeed, the assumptions from [10] are satisfied because X is a compact metric space, $m \in C(X, \mathbb{R}^{2\times 2}_{psd})$, and Ψ is antitonic, convex with dom $\Psi = \mathbb{R}^{2\times 2}_{pd}$ and because $\Psi|_{\mathbb{R}^{2\times 2}_{pd}}$ is continuous and directionally differentiable with

$$\lim_{t \searrow 0} \frac{\Psi\left(M + t(M(\eta) - M)\right) - \Psi(M)}{t} = \partial_{M(\eta) - M} \Psi(M) = \int_X \psi(M, x) \,\mathrm{d}\eta(x) \tag{2.77}$$

for every $M \in \mathbb{R}^{2 \times 2}_{pd}$ and $\eta \in \Xi(X)$, where $\psi(M, x) := e_1^\top M^{-1} e_1 - e_1^\top M^{-1} m(x) M^{-1} e_1$. Additionally,

$$M(\Xi(X)) = \{M(\xi) : \xi \in \Xi(X)\} = \{\operatorname{diag}(a, 1-a) : a \in [0, 1]\}$$
(2.78)

because $\Xi(X) = \{a\delta_{x_1} + (1-a)\delta_{x_2} : a \in [0,1]\}$ (Lemma 2.9). So, by (2.76) and (2.78),

$$\{\Psi(M(\xi)): \xi \in \Xi(X)\} = \{1/a: a \in (0,1)\} \cup \{\infty\}$$
(2.79)

and therefore

$$\inf_{\xi \in \Xi(X)} \Psi(M(\xi)) = 1 < \Psi(M(\xi^*)) \qquad (\xi^* \in \Xi(X)).$$
(2.80)

Consequently, there exists no optimal design for $\Psi \circ M$, as claimed.

2.5 Characterization of optimal designs

In this section, we record well-known characterizations of optimal and approximately optimal designs in terms of the so-called sensitivity function ψ of $\Psi|_{\text{dom }\Psi}$ [16, 10, 22]. In other words, we derive necessary and sufficient conditions for a design ξ^* to be ε -optimal for $\Psi \circ M$, in terms of the sensitivity function of $\Psi|_{\text{dom }\Psi}$. As before, we assume that X is a compact metric space, $m \in C(X, \mathbb{R}^{d \times d}_{psd})$,

$$M: \Xi(X) \to \mathbb{R}^{d \times d}_{\text{psd}}, \qquad M(\xi) := \int_X m(x) \,\mathrm{d}\xi(x)$$
 (2.81)

is the corresponding information matrix map (Condition 2.18) and that $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is the considered design criterion. A function $\psi : \operatorname{dom} \Psi \times X \to \mathbb{R}$ is then called a *sensitivity* function of $\Psi|_{\operatorname{dom} \Psi}$ w.r.t. $M(\Xi(X))$ iff for every $M \in \operatorname{dom} \Psi$ and every $\eta \in \Xi(X)$, the function $\psi(M, \cdot)$ is η -integrable and

$$\frac{\Psi(M + t(M(\eta) - M)) - \Psi(M)}{t} \longrightarrow \int_{X} \psi(M, x) \,\mathrm{d}\eta(x) \qquad (t \searrow 0).$$
(2.82)

Additionally, we call the restriction $\Psi|_{\operatorname{dom}\Psi}$ of the design criterion directionally differentiable w.r.t. $M(\Xi(X))$ iff there exists a sensitivity function ψ for $\Psi|_{\operatorname{dom}\Psi}$ w.r.t. $M(\Xi(X))$.

It is clear by the definition (2.82) that if for a given design criterion Ψ there exists any sensitivity function ψ w.r.t. $M(\Xi(X))$, then it is necessarily unique. (Simply consider (2.82) with all point measures $\eta := \delta_x$ for $x \in X$.) It is also clear by the definition (2.82) that if $\Psi|_{\text{dom }\Psi}$ is directionally differentiable w.r.t. $M(\Xi(X))$, then dom Ψ is *directionally open w.r.t.* $M(\Xi(X))$ in the following sense: for every $M \in \text{dom }\Psi$ and every $\eta \in \Xi(X)$, there exists a $t^* \in (0, 1]$ such that

$$M + t(M(\eta) - M) \in \operatorname{dom} \Psi$$
 $(t \in [0, t^*]).$ (2.83)

And finally, it is clear by the definition (2.82) that if $\Psi|_{\operatorname{dom}\Psi}$ is directionally differentiable w.r.t. $M(\Xi(X))$, then for every $\xi \in \operatorname{dom}\Psi \circ M$ and every $\eta \in \Xi(X)$ the function $(\Psi \circ M)|_{\operatorname{dom}\Psi \circ M}$ is directionally differentiable at ξ in the direction $\eta - \xi$ in the usual sense (2.12) and the directional derivative $\partial_{\eta-\xi}(\Psi \circ M)(\xi)$ takes the specific integral form

$$\partial_{\eta-\xi}(\Psi \circ M)(\xi) = \int_X \psi(M(\xi), x) \,\mathrm{d}\eta(x).$$
(2.84)

As the next lemma shows, directional differentiability w.r.t. $M(\Xi(X))$ follows from differentiability and thus is a mild condition.

Lemma 2.22. Suppose that Condition 2.18 is satisfied and that $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is a design criterion such that dom Ψ is directionally open w.r.t. $M(\Xi(X))$ and $\Psi|_{\text{dom }\Psi}$ is differentiable. Then $\Psi|_{\text{dom }\Psi}$ is directionally differentiable w.r.t. $M(\Xi(X))$ with sensitivity function ψ given by

$$\psi(M, x) = D\Psi(M)(m(x) - M) \qquad (M \in \operatorname{dom} \Psi \text{ and } x \in X).$$
(2.85)

Proof. Suppose $M \in \operatorname{dom} \Psi$ and $\eta \in \Xi(X)$. Since dom Ψ is directionally open w.r.t. $M(\Xi(X))$, there exists a $t^* \in (0, 1]$ such that $M + t(M(\eta) - M) \in \operatorname{dom} \Psi$ for every $t \in [0, t^*]$. And therefore, by the differentiability of $\Psi|_{\operatorname{dom} \Psi}$ and by (2.81),

$$\frac{\Psi(M+t(M(\eta)-M))-\Psi(M)}{t} \longrightarrow D\Psi(M)\big(M(\eta)-M\big)$$
$$= \int_X D\Psi(M)\big(m(x)-M\big)\,\mathrm{d}\eta(x) \qquad (t\searrow 0). \tag{2.86}$$

Consequently, dom $\Psi \times X \ni (M, x) \mapsto \psi(M, x) := D\Psi(M)(m(x) - M)$ is a sensitivity function for $\Psi|_{\text{dom }\Psi}$, as desired.

Example 2.23. Suppose that Condition 2.18 is satisfied. Also, let $M^0 \in \mathbb{R}^{d \times d}_{psd}$ and $\alpha \in [0, 1)$ and $p \in [0, \infty)$ and let $\Psi_p^{(\alpha)}$ be the two-stage design criterion defined by

$$\Psi_p^{(\alpha)}(M) := \Psi_p(\alpha M^0 + (1 - \alpha)M) \qquad (M \in \mathbb{R}_{psd}^{d \times d}).$$
(2.87)

Since dom $\Psi_p = \mathbb{R}_{pd}^{d \times d}$ is an open subset of $\mathbb{R}^{d \times d}$, it is straightforward to verify that dom $\Psi_p^{(\alpha)}$ is directionally open w.r.t. $M(\Xi(X))$. Since, moreover, $\Psi_p^{(\alpha)}$ restricted to its domain is differentiable (Proposition 2.12 and Proposition 2.15), it follows by Lemma 2.22 that the two-stage design criterion is directionally differentiable w.r.t. $M(\Xi(X))$ with sensitivity function $\psi_p^{(\alpha)} : \operatorname{dom} \Psi_p^{(\alpha)} \times X \to \mathbb{R}$ given by

$$\psi_p^{(\alpha)}(M,x) = (1-\alpha)D\Psi_p(M^{(\alpha)})(m(x)-M)$$
(2.88)

where $M^{(\alpha)} := \alpha M^0 + (1 - \alpha)M$. In view of (2.42) and (2.43), this implies that

$$\psi_0^{(\alpha)}(M,x) = (1-\alpha)\operatorname{tr}\left((M^{(\alpha)})^{-1}(M-m(x))\right) \qquad (p=0)$$
(2.89)

$$\psi_p^{(\alpha)}(M,x) = (1-\alpha) \left(\operatorname{tr}((M^{(\alpha)})^{-p}) \right)^{1/p-1} \operatorname{tr}((M^{(\alpha)})^{-p-1}(M-m(x))) \qquad (p \in (0,\infty)).$$
(2.90)

It follows from these formulas that the sensitivity function $\psi_p^{(\alpha)}$ is locally Lipschitz continuous w.r.t. $M \in \text{dom } \Psi_p^{(\alpha)}$ uniformly w.r.t. $x \in X$. Indeed, this follows from (2.89) and (2.90) by the local Lipschitz continuity of the maps $\mathbb{R}_{pd}^{d \times d} \ni M \mapsto M^{-q_1}$ (Lemma 2.7) and $(0, \infty) \ni t \mapsto t^{q_2}$ for $q_1 \in [0, \infty)$ and $q_2 \in \mathbb{R}$ and by the simple estimate

$$\operatorname{tr}(AB) = \operatorname{tr}(B^{1/2}AB^{1/2}) \le ||A|| \operatorname{tr}(B) \qquad (A, B \in \mathbb{R}^{d \times d}_{\mathrm{psd}}).$$
 (2.91)

Theorem 2.24. Suppose that Condition 2.18 is satisfied and that $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is convex. Suppose further that $\Psi|_{\text{dom }\Psi}$ is directionally differentiable w.r.t. $M(\Xi(X))$ and that

$$\Xi_{\text{fin}}(X) := \operatorname{dom} \Psi \circ M = \{\xi \in \Xi(X) : \Psi(M(\xi)) < \infty\}$$
(2.92)

is non-empty. Then for every $\varepsilon \in [0, \infty)$ the following two assertions are equivalent:

- (i) ξ^* is an ε -optimal design for $\Psi \circ M$
- (ii) $\xi^* \in \Xi_{\text{fin}}(X)$ and $\psi(M(\xi^*), x) \ge -\varepsilon$ for every $x \in X$.

Additionally, for every optimal design ξ^* for $\Psi \circ M$, one has $\psi(M(\xi^*), x) = 0$ for ξ^* -a.e. $x \in X$. In particular, for every optimal design ξ^* with finite support, one has $\psi(M(\xi^*), x) = 0$ for every $x \in \text{supp } \xi^*$.

Proof. Suppose first that assertion (i) is satisfied. Since $\Xi_{\text{fin}}(X) \neq \emptyset$, we immediately obtain $\Psi(M(\xi^*)) = \min_{\xi \in \Xi(X)} \Psi(M(\xi)) < \infty$ and thus

$$\xi^* \in \operatorname{dom} \Psi \circ M = \Xi_{\operatorname{fin}}(X). \tag{2.93}$$

Since ξ^* is an ε -optimal design for $\Psi \circ M$ and $(1-t)\xi^* + t\delta_x \in \Xi(X)$ for every $t \in [0,1]$ and $x \in X$, it follows that

$$\Psi\left(M((1-t)\xi^* + t\delta_x))\right) - \Psi(M(\xi^*)) \ge -\varepsilon \qquad (t \in [0,1] \text{ and } x \in X)$$
(2.94)

Since, moreover, ψ is a sensitivity function of $\Psi|_{\mathrm{dom}\,\Psi}$, it further follows by (2.94) that

$$\psi(M(\xi^*), x) = \int_X \psi(M(\xi^*), x') \, \mathrm{d}\delta_x(x')$$

= $\lim_{t \searrow 0} \frac{\Psi(M((1-t)\xi^* + t\delta_x))) - \Psi(M(\xi^*))}{t} \ge -\varepsilon \qquad (x \in X).$ (2.95)

In view of (2.93) and (2.95), assertion (ii) is now clear. Suppose now, conversely, that assertion (ii) is satisfied. Since Ψ is convex, it follows that

$$\frac{\Psi((1-t)M(\xi^*) + tM(\eta))) - \Psi(M(\xi^*))}{t} \le \Psi(M(\eta)) - \Psi(M(\xi^*))$$
(2.96)

for every $\eta \in \Xi(X)$ and every $t \in (0, 1]$. Since, moreover, ψ is a sensitivity function for $\Psi|_{\operatorname{dom}\Psi}$ and since $M(\xi^*) \in \operatorname{dom}\Psi$ and $\psi(M(\xi^*), x) \geq -\varepsilon$ for all $x \in X$ by the assumed assertion (ii), it further follows by (2.96) that

$$-\varepsilon \leq \int_{X} \psi(M(\xi^{*}), x) \, \mathrm{d}\eta(x) = \lim_{t \searrow 0} \frac{\Psi((1-t)M(\xi^{*}) + tM(\eta))) - \Psi(M(\xi^{*}))}{t} \\ \leq \Psi(M(\eta)) - \Psi(M(\xi^{*})) \qquad (\eta \in \Xi(X)).$$
(2.97)

Consequently, ξ^* is an ε -optimal design for $\Psi \circ M$, that is, assertion (i) is satisfied. We have thus established the equivalence of assertions (i) and (ii) and it remains to prove the additional statement of the theorem. So, let ξ^* be any optimal design for $\Psi \circ M$. It then follows by the equivalence just established that

$$M(\xi^*) \in \operatorname{dom} \Psi$$
 and $\psi(M(\xi^*), x) \ge 0$ $(x \in X).$ (2.98)

Consider now the sets $Z_n := \{x \in X : \psi(M(\xi^*), x) \ge 1/n\}$ for $n \in \mathbb{N}$. Since ψ is a sensitivity function for $\Psi|_{\dim \Psi}$, we see from (2.98) that $Z_n \in \mathcal{B}_X$ and that

$$0 \le (1/n) \cdot \xi^*(Z_n) \le \int_{Z_n} \psi(M(\xi^*), x) \,\mathrm{d}\xi^*(x) \le \int_X \psi(M(\xi^*), x) \,\mathrm{d}\xi^*(x) = 0 \qquad (n \in \mathbb{N}), \quad (2.99)$$

where for the last inequality we used (2.98.b) and for the last equality we used (2.82). Consequently, Z_n is a ξ^* -nullset for every $n \in \mathbb{N}$ and therefore

$$\{x \in X : \psi(M(\xi^*), x) \neq 0\} = \{x \in X : \psi(M(\xi^*), x) > 0\} = \bigcup_{n \in \mathbb{N}} Z_n$$
(2.100)

is a ξ^* -null set as well, which proves the first part of the additional statement. In order to prove also the second part of the additional statement, let ξ^* be a an optimal design for $\Psi \circ M$ with finite support. We then have, on the one hand, that

$$Z := \{x \in \operatorname{supp} \xi^* : \psi(M(\xi^*), x) \neq 0\} \subset \operatorname{supp} \xi^*$$
(2.101)

is a ξ^* -nullset by the statement just proven and, on the other hand, that $\xi^*(\{x\}) > 0$ for all $x \in \text{supp}\xi^*$ by Lemma 2.9. Consequently, Z must be the empty set, which proves the final statement.

3 Adaptive discretization algorithms to compute optimal designs

In this section, we introduce our adaptive discretization algorithms for the computation of optimal and approximately optimal designs, which refine and improve the algorithm from [38]. After introducing the algorithms, we establish our various termination, convergence and convergence rate results on them. In very rough terms, our algorithms work as follows. In each iteration of the algorithms, a discretized version

$$\min_{\xi \in \Xi(X^k)} \Psi(M(\xi)) \tag{3.1}$$

of (2.61) is solved up to some optimality tolerance $\overline{\delta}_k$. In this discretized optimal design problem (3.1), the discretization X^k is a finite subset of X that is adaptively updated in the following sense: the new discretization X^{k+1} depends on how much the solution ξ^k computed for (3.1) violates the necessary and sufficient ε -optimality condition

$$\min_{x \in Y} \psi(M(\xi^k), x) \ge -\varepsilon \tag{3.2}$$

for ξ^k (Theorem 2.24). In contrast to the results from the previous sections, we now also have to impose a continuity assumption on the sensitivity functions ψ . As was pointed out above (Example 2.23), this additional continuity assumption is satisfied for all standard design criteria Ψ_p with $p \in [0, \infty)$.

Condition 3.1. Condition 2.18 is satisfied and $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is convex and lower semicontinuous with

$$\Xi_{\text{fin}}(X) := \operatorname{dom} \Psi \circ M \neq \emptyset. \tag{3.3}$$

Condition 3.2. $\Psi|_{\operatorname{dom}\Psi}$ is directionally differentiable w.r.t. $M(\Xi(X))$ with a continuous sensitivity function ψ .

Condition 3.3. $\Psi|_{\operatorname{dom}\Psi}$ is continuously differentiable and $\operatorname{dom}\Psi$ is directionally open w.r.t. $M(\Xi(X))$.

Lemma 3.4. (i) If Condition 3.1 is satisfied, then there exists a finite subset X^0 of X with

$$\Xi_{\text{fin}}(X^0) := \{\xi \in \Xi(X^0) : \Psi(M(\xi)) < \infty\} \neq \emptyset$$
(3.4)

(ii) If Conditions 3.1 and 3.2 are satisfied, then the map $(\Psi \circ M)|_{\Xi_{\text{fin}}(X)}$ is continuous.

Proof. In order see assertion (i), choose an optimal design ξ^0 for $\Psi \circ M$ with finite support (Theorem 2.20). It is then clear by (3.3) that $X^0 := \operatorname{supp} \xi^0$ is a finite set satisfying (3.4). In order to see assertion (ii), let $\xi^n, \xi \in \Xi_{\operatorname{fin}}(X)$ with $\xi^n \longrightarrow \xi$ as $n \to \infty$. It then follows by the assumed convexity of Ψ , using the same arguments as for (2.96), that

$$\Psi(M(\xi^n)) - \Psi(M(\xi)) \le -\int_X \psi(M(\xi^n), x) \,\mathrm{d}\xi(x)$$

$$\Psi(M(\xi)) - \Psi(M(\xi^n)) \le -\int_X \psi(M(\xi), x) \,\mathrm{d}\xi^n(x)$$

for all $n \in \mathbb{N}$. Consequently,

$$|\Psi(M(\xi^{n})) - \Psi(M(\xi))| \le \max\left\{-\int_{X} \psi(M(\xi^{n}), x) \,\mathrm{d}\xi(x), -\int_{X} \psi(M(\xi), x) \,\mathrm{d}\xi^{n}(x)\right\}$$
(3.5)

for all $n \in \mathbb{N}$. Since by assumption $\psi(M(\cdot), x)$ is continuous for every $x \in X$ and $\psi(M(\xi), \cdot)$ is a bounded continuous function, we conclude with the dominated convergence theorem that the right-hand side of (3.5) converges to

$$\int_{X} \psi(M(\xi), x) \,\mathrm{d}\xi(x) = 0 \tag{3.6}$$

as $n \to \infty$. So, the same is true for the left-hand side of (3.5), whence $\Psi(M(\xi^n)) \longrightarrow \Psi(M(\xi))$ as $n \to \infty$, as desired.

3.1 Adaptive discretization algorithms without exchange

We begin with two algorithms without exchange, where the discretization sets X^k get larger and larger from iteration to iteration:

$$X^k \subset X^{k+1} \tag{3.7}$$

for all iteration indices k.

Algorithm 3.5. Input: a finite subset X^0 of X and optimality tolerances $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$. Initialize k = 0 and then proceed in the following steps.

1. Compute a $\overline{\delta}_k$ -approximate solution $\xi^k \in \Xi(X^k)$ of the discretized optimal design problem

$$\min_{\xi \in \Xi(X^k)} \Psi(M(\xi)) \tag{3.8}$$

2. Compute a $\underline{\delta}_k$ -approximate solution $x^k \in X$ of the strongest optimality violator problem

$$\min_{x \in X} \psi(M(\xi^k), x). \tag{3.9}$$

If $\psi(M(\xi^k), x^k) < -\varepsilon + \underline{\delta}_k$, then set $X^{k+1} := X^k \cup \{x^k\}$ and return to Step 1 with k replaced by k + 1. If $\psi(M(\xi^k), x^k) \ge -\varepsilon + \underline{\delta}_k$, then terminate.

Algorithm 3.6. Input: a finite subset X^0 of X and optimality tolerances $\varepsilon, \overline{\delta}_k \in [0, \infty)$. Initialize k = 0 and then proceed in the following steps.

1. Compute a $\overline{\delta}_k$ -approximate solution $\xi^k \in \Xi(X^k)$ of the discretized optimal design problem

$$\min_{\xi \in \Xi(X^k)} \Psi(M(\xi)) \tag{3.10}$$

2. Search for a violator of the ε -optimality condition for ξ^k , that is, for a point x^k in the set

$$\{x \in X : \psi(M(\xi^k), x) < -\varepsilon\}.$$
(3.11)

If such a point x^k is found, then set $X^{k+1} := X^k \cup \{x^k\}$ and return to Step 1 with k replaced by k+1. If no such point can possibly be found (that is, the set (3.11) is empty), then terminate.

We first convince ourselves that for a suitable initial discretization X^0 all the optimization problems encountered in the course of Algorithm 3.5 or 3.6 are solvable and that the sequence $(\Psi(M(\xi^k)))$ of optimal values is bounded above.

Lemma 3.7. Suppose that Conditions 3.1 and 3.2 are satisfied and that X^0 is a finite subset of X with (3.4) and $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ are arbitrary optimality tolerances. Then all optimization problems in Algorithm 3.5 and 3.6 are solvable and, for the (possibly finite) sequence $(\xi^k)_{k \in K}$ of iterates generated by Algorithm 3.5 or 3.6, one has

$$\Psi(M(\xi^l)) \le \Psi(M(\xi^k)) + \overline{\delta}_l \qquad (k, l \in K \text{ with } k < l).$$
(3.12)

In particular, $\xi^k \in \Xi_{\text{fin}}(X)$ and $\Psi(M(\xi^k)) \leq \Psi(M(\xi^0)) + \overline{\delta}_k$ for all $k \in K$.

Proof. It is straightforward to see by induction over K that for every iteration index $k \in K$ the following statements are true: (i) the discretized design problem (3.8) or (3.10), respectively, has a solution (so that ξ^k is well-defined also when $\overline{\delta}_k = 0$), (ii) if $k \neq 0$, then $\Psi(M(\xi^k)) \leq \Psi(M(\xi^{k-1})) + \overline{\delta}_k$, (iii) $\xi^k \in \Xi_{\text{fin}}(X)$, and (iv) the strongest violator problem (3.9) has a solution. Consequently, it only remains to prove (3.12), but this is straightforward as well. Indeed, by the algorithms' progressively refining updating rule, we have for every k < l that $X^k \subset X^l$ and therefore $\xi^k \in \Xi(X^l)$, which implies (3.12) by the $\overline{\delta}_l$ -approximate solution property of ξ^l .

Lemma 3.8. Suppose that Conditions 3.1 and 3.2 are satisfied. Suppose further that X^0 is a finite subset of X satisfying (3.4) and that $(\xi^k)_{k \in K}$ is generated by Algorithm 3.5 or 3.6 with such an X^0 and arbitrary optimality tolerances $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ such that $(\overline{\delta}_k)$ is bounded.

- (i) If (ξ^k) is terminating, then it terminates at an ε -optimal design for $\Psi \circ M$.
- (ii) If (ξ^k) is non-terminating, then every accumulation point ξ^* of (ξ^k) belongs to $\Xi_{fin}(X)$.

Proof. (i) Suppose that $(\xi^k)_{k \in K}$ is terminating, that is, $K = \{0, \ldots, k^*\}$ for some terminal index $k^* \in \mathbb{N}_0$. It then follows by Lemma 3.7 and by the termination rules of Algorithm 3.5 and 3.6, respectively, that

$$\xi^{k^*} \in \Xi_{\text{fin}}(X)$$
 and $\min_{x \in X} \psi(M(\xi^{k^*}), x) \ge -\varepsilon.$ (3.13)

And therefore, ξ^{k^*} is an ε -optimal design for $\Psi \circ M$ by virtue of Theorem 2.24, as desired.

(ii) Suppose now that $(\xi^k)_{k \in K}$ is non-terminating, that is, $K = \mathbb{N}_0$. Also, let ξ^* be any accumulation point of (ξ^k) and let (ξ^{k_l}) be any subsequence with $\xi^{k_l} \longrightarrow \xi^*$ as $l \to \infty$. Since Ψ is lower semicontinuous, it follows by the final boundedness statement of Lemma 3.7 and the assumed boundedness of $(\overline{\delta}_k)$ that $\Psi(M(\xi^*)) < \infty$ and therefore $\xi^* \in \Xi_{\text{fin}}(X)$, as desired.

With these preparations at hand, we can now show that Algorithm 3.5 or 3.6 applied with a tolerance $\varepsilon > 0$ is guaranteed to terminate, namely at an ε -optimal design for $\Psi \circ M$. Additionally, if instead of the mere continuity assumption, the sensitivity function is assumed to be locally Lipschitz continuous uniformly w.r.t. $x \in X$, then the number of iterations until termination can also be bounded above, namely in terms of packing numbers [35]. See Corollaries 3.17 and 3.17 for further estimates on the numbers of iterations until termination. As was shown above (Example 2.23), this additional uniform local Lipschitz continuity assumption is satisfied for the sensitivity function ψ_p of every standard design criterion Ψ_p with $p \in [0, \infty)$. Also, to obtain a concrete uniform Lipschitz constant L of $\psi_p(\cdot, x)|_{M(\Xi_{R_0}(X))}$ as specified after (3.17), one can combine the estimate (2.25) from the proof of Lemma 2.7 with Lemma 2.11. Specifically, one can use the following simple consequence of Lemma 2.11:

$$M(\Xi_{R_0}(X)) = \{M(\xi) : \xi \in \Xi(X) \text{ with } \Psi_p(M(\xi)) \le R_0\} \subset \{M \in \mathbb{R}^{d \times d}_{pd} : c \le M \le C\}$$
(3.14)

with $c := \mu_{p,R_0}(C) > 0$ and $C := \sup_{\xi \in \Xi_{R_0}(X)} \|M(\xi)\| \le \max_{x \in X} \|m(x)\| < \infty$.

Theorem 3.9. Suppose that Conditions 3.1 and 3.2 are satisfied. Suppose further that X^0 is a finite subset of X satisfying (3.4) and that $(\xi^k)_{k \in K}$ is generated by Algorithm 3.5 or 3.6 with optimality tolerances $\varepsilon > 0$ and $\overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ such that

$$\varepsilon > \overline{\delta} + \underline{\delta},$$
(3.15)

where $\overline{\delta} := \limsup_{k \to \infty} \overline{\delta}_k$ and $\underline{\delta} := \limsup_{k \to \infty} \underline{\delta}_k$. Then (ξ^k) terminates at an ε -optimal design for $\Psi \circ M$. If, in addition, the sensitivity function ψ is locally Lipschitz continuous w.r.t. $M \in$ dom Ψ uniformly w.r.t. $x \in X$ and if instead of (3.15) one even has $\varepsilon > \sup_{k \in \mathbb{N}_0} \overline{\delta}_k + \sup_{k \in \mathbb{N}_0} \underline{\delta}_k$, then the number of iterations until termination can be estimated above as follows:

$$|K| \le \operatorname{pac}_{\varepsilon^*/L, \|\cdot\|}(M(\Xi_{R_0}(X))).$$
 (3.16)

In this estimate, $\varepsilon^* := \varepsilon - \overline{\delta}^* - \underline{\delta}^*$ with $\overline{\delta}^* := \sup_{k \in \mathbb{N}_0} \overline{\delta}_k$ and $\underline{\delta}^* := \sup_{k \in \mathbb{N}_0} \underline{\delta}_k$, whereas

$$\Xi_{R_0}(X) := \{\xi \in \Xi(X) : \Psi(M(\xi)) \le R_0\} \quad with \quad R_0 := \Psi(M(\xi^0)) + \overline{\delta}^* \tag{3.17}$$

and L is a uniform Lipschitz constant of the restricted functions $\psi(\cdot, x)|_{M(\Xi_{R_0}(X))}$.

Proof. As a first step, we show that (ξ^k) terminates at an ε -optimal design for $\Psi \circ M$. Assume that $(\xi^k)_{k \in K}$ does not terminate, that is, $K = \mathbb{N}_0$. It then follows by the algorithms' termination conditions that

$$\psi(M(\xi^k), x^k) < -\varepsilon + \underline{\delta}_k \qquad (k \in \mathbb{N}_0). \tag{3.18}$$

(In fact, in the case where Algorithm 3.6 is used, this even holds with $\underline{\delta}_k = 0$.) Since ξ^l is a $\overline{\delta}_l$ -optimal design on X^l and since $X^l \supset X^{k+1} \ni x^k$ for all l > k by the algorithms' definitions, it further follows that

$$\psi(M(\xi^l), x^k) \ge -\overline{\delta}_l \qquad (k, l \in \mathbb{N}_0 \text{ with } k < l)$$
(3.19)

by virtue of Theorem 2.24 with X replaced by X^l . We now choose convergent subsequences (ξ^{k_j}) and (x^{k_j}) with limits denoted by ξ^* and x^* (Lemma 2.10). It then follows that $\xi^* \in \Xi_{\text{fin}}(X)$ (Lemma 3.8) and from (3.18) and (3.19) it further follows by the continuity of ψ that

$$\psi(M(\xi^*), x^*) = \lim_{j \to \infty} \psi(M(\xi^{k_j}), x^{k_j}) \le -\varepsilon + \underline{\delta}$$
(3.20)

$$\psi(M(\xi^*), x^*) = \lim_{j \to \infty} \psi(M(\xi^{k_{j+1}}), x^{k_j}) \ge -\limsup_{j \to \infty} \overline{\delta}_{k_{j+1}} \ge -\overline{\delta}.$$
(3.21)

Combining now the inequalities (3.20) and (3.21), we conclude that $-\varepsilon + \underline{\delta} \ge -\overline{\delta}$. Contradiction to (3.15)! So, our assumption that (ξ^k) does not terminate is false. And therefore (ξ^k) terminates at an ε -optimal design for $\Psi \circ M$ by Lemma 3.8 (i), as desired.

As a second step, we show that under the additional Lipschitz continuity assumption on the sensitivity function and under the sharpened optimality-tolerance assumption $\varepsilon > \overline{\delta}^* + \underline{\delta}^*$, the number of iterations until termination can be estimated above as in (3.16). So, let the sensitivity function ψ be locally Lipschitz continuous w.r.t. $M \in \text{dom } \Psi$ uniformly w.r.t. $x \in X$, that is, for every compact subset \mathcal{M} of dom Ψ the restricted functions $\psi(\cdot, x)|_{\mathcal{M}}$ are Lipschitz continuous uniformly w.r.t. $x \in X$. Since $M(\Xi_{R_0}(X))$ is a compact subset of dom Ψ by the lower semicontinuity of Ψ , it follows that there exists an x-independent Lipschitz constant $L \in (0, \infty)$ such that

$$|\psi(M(\eta), x) - \psi(M(\xi), x)| \le L ||M(\eta) - M(\xi)||$$
 $(\xi, \eta \in \Xi_{R_0}(X) \text{ and } x \in X).$ (3.22)

It further follows by the final boundedness statement of Lemma 3.7 that

$$\xi^k \in \Xi_{R_0}(X) \qquad (k \in K). \tag{3.23}$$

Combining now (3.18), (3.19), (3.22) and (3.23), we see that

$$0 < \varepsilon^* \le \varepsilon - \underline{\delta}_k - \overline{\delta}_l < \psi(M(\xi^l), x^k) - \psi(M(\xi^k), x^k) \le L \left\| M(\xi^l) - M(\xi^k) \right\| \qquad (k, l \in K \text{ with } k < l).$$
(3.24)

In other words, (3.23) and (3.24) say that $\{M(\xi^k) : k \in K\}$ is an (ε^*/L) -packing of the set $M(\Xi_{R_0}(X))$ w.r.t. $\|\cdot\|$. And therefore, we have

$$|K| = \left| \{ M(\xi^k) : k \in K \} \right| \le \operatorname{pac}_{\varepsilon^*/L, \|\cdot\|}(M(\Xi_{R_0}(X)))$$
(3.25)

by the definition of the packing number [35], as desired.

With essentially the same arguments, we can also prove that if Algorithm 3.5 is applied with tolerance $\varepsilon = 0$, then the sequence of iterates accumulates at an optimal design for $\Psi \circ M$. See Corollary 3.15 below.

3.2 Adaptive discretization algorithms with exchange

We now modify the above algorithms without exchange to algorithms with exchange in updating the discretizations. Instead of taking into account all points from the discretization X^k when passing to the next discretization X^{k+1} , we now take into account only the support points of ξ^k . In particular, the discretization sets are no longer guaranteed to increase from iteration to iteration as they did for the algorithms without exchange by (3.7).

Algorithm 3.10. Input: a finite subset X^0 of X and optimality tolerances $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$. Initialize k = 0 and then proceed in the following steps.

1. Compute a $\overline{\delta}_k$ -approximate solution $\xi^k \in \Xi(X^k)$ of the discretized optimal design problem

$$\min_{\xi \in \Xi(X^k)} \Psi(M(\xi)) \tag{3.26}$$

2. Compute a $\underline{\delta}_k$ -approximate solution $x^k \in X$ of the strongest optimality violator problem

$$\min_{x \in Y} \psi(M(\xi^k), x). \tag{3.27}$$

If $\psi(M(\xi^k), x^k) < -\varepsilon + \underline{\delta}_k$, then set $X^{k+1} := \operatorname{supp} \xi^k \cup \{x^k\}$ and return to Step 1 with k replaced by k + 1. If $\psi(M(\xi^k), x^k) \ge -\varepsilon + \underline{\delta}_k$, then terminate.

Algorithm 3.11. Input: a finite subset X^0 of X and optimality tolerances $\varepsilon, \overline{\delta}_k \in [0, \infty)$. Initialize k = 0 and then proceed in the following steps.

1. Compute a $\overline{\delta}_k$ -approximate solution $\xi^k \in \Xi(X^k)$ of the discretized optimal design problem

$$\min_{\xi \in \Xi(X^k)} \Psi(M(\xi)) \tag{3.28}$$

2. Search for a violator of the ε -optimality condition for ξ^k , that is, for a point x^k in the set

$$\{x \in X : \psi(M(\xi^k), x) < -\varepsilon\}.$$
(3.29)

If such a point x^k is found, then set $X^{k+1} := X^k \cup \{x^k\}$ and return to Step 1 with k replaced by k+1. If no such point can possibly be found (that is, the set (3.29) is empty), then terminate.

We first convince ourselves that for a suitable initial discretization X^0 all the optimization problems encountered in the course of Algorithm 3.10 or 3.11 are solvable and that the sequence $(\Psi(M(\xi^k)))$ of optimal values is essentially monotonically decreasing, provided that the sequence $(\overline{\delta}_k)$ of optimality tolerances for (3.26) is summable.

Lemma 3.12. Suppose that Conditions 3.1 and 3.2 are satisfied and that X^0 is a finite subset of X with (3.4) and $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ are arbitrary optimality tolerances. Then all optimization problems in Algorithm 3.10 or 3.11 are solvable and, for the (possibly finite) sequence $(\xi^k)_{k \in K}$ of iterates generated by Algorithm 3.10 or 3.11 with these inputs, one has

$$\Psi(M(\xi^{k+1})) \le \Psi\left(\alpha M(\xi^k) + (1-\alpha)M(\xi^{k+1})\right) + \overline{\delta}_{k+1} \qquad (k \in K-1 \text{ and } \alpha \in [0,1]).$$
(3.30)

In particular, $\xi^k \in \Xi_{\text{fin}}(X)$ for all $k \in K$ and, if $(\overline{\delta}_k)$ is summable, then there is a null sequence (ν_k) in \mathbb{R} such that $(\Psi(M(\xi^k)) + \nu_k)_{k \in K}$ is monotonically decreasing.

Proof. It is straightforward to see by induction over K that for every iteration index $k \in K$ the following statements are true: (i) the discretized design problem (3.26) or (3.28), respectively, has a solution (so that ξ^k is well-defined also when $\overline{\delta}_k = 0$), (ii) if $k \neq 0$, then $\Psi(M(\xi^k)) \leq \Psi(\alpha M(\xi^{k-1}) + (1-\alpha)M(\xi^k)) + \overline{\delta}_k$ for all $\alpha \in [0,1]$, (iii) $\xi^k \in \Xi_{\text{fin}}(X)$, and (iv) the strongest violator problem (3.9) has a solution. In order to see (ii), notice that by the algorithms' updating rule one has

$$\operatorname{supp}(\alpha\xi^{k-1} + (1-\alpha)\xi^k) \subset \operatorname{supp}\xi^{k-1} \cup \operatorname{supp}\xi^k \subset X^k \qquad (\alpha \in [0,1])$$
(3.31)

and therefore $\alpha\xi^{k-1} + (1-\alpha)\xi^k \in \Xi(X^k)$ for all $\alpha \in [0,1]$. Combining this with the $\overline{\delta}_k$ approximate solution property of ξ^k , one immediately obtains (ii). It only remains to prove the
monotonic decreasingness of $(\Psi(M(\xi^k)) + \nu_k)_{k \in K}$ for a suitable null sequence (ν_k) , but this is
straightforward as well. Indeed, define $\nu_k := \sum_{l=k}^{\infty} \overline{\delta}_{l+1}$. Since $(\overline{\delta}_k)$ is summable by assumption, (ν_k) is a null sequence in \mathbb{R} and, by (3.30) with $\alpha = 1$, it also follows that $(\Psi(M(\xi^k)) + \nu_k)_{k \in K}$ is monotonically decreasing, as desired.

In contrast to the termination lemma for Algorithm 3.5 and 3.6, we now have to additionally assume that the design criterion $\Psi|_{\text{dom }\Psi}$ be strictly convex. In view of Proposition 2.12, this additional assumption is satisfied for all standard design criteria Ψ_p with $p \in [0, \infty)$.

Lemma 3.13. Suppose that Conditions 3.1 and 3.2 are satisfied and that Ψ is even strictly convex. Suppose further that X^0 is a finite subset of X satisfying (3.4) and that $(\xi^k)_{k \in K}$ is generated by Algorithm 3.10 or 3.11 with optimality tolerances $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ such that $(\overline{\delta}_k)$ is summable.

(i) If (ξ^k) is terminating, then it terminates at an ε -optimal design for $\Psi \circ M$.

(ii) If (ξ^k) is non-terminating, then every accumulation point ξ^* of (ξ^k) belongs to $\Xi_{\text{fin}}(X)$ and for every subsequence (ξ^{k_l}) with $\xi^{k_l} \longrightarrow \xi^*$ there exists yet another subsequence (k_{l_j}) such that

$$M(\xi^{k_{l_j}+1}) \longrightarrow M(\xi^*) \qquad (j \to \infty).$$
 (3.32)

Proof. (i) Suppose that $(\xi^k)_{k \in K}$ is terminating, that is, $K = \{0, \ldots, k^*\}$ for some terminal index $k^* \in \mathbb{N}_0$. It then follows by Lemma 3.12 and by the termination rules of Algorithm 3.10 and 3.11, respectively, that

$$\xi^{k^*} \in \Xi_{\text{fin}}(X)$$
 and $\min_{x \in X} \psi(M(\xi^{k^*}), x) \ge -\varepsilon.$ (3.33)

And therefore, ξ^{k^*} is an ε -optimal design for $\Psi \circ M$ by virtue of Theorem 2.24, as desired.

(ii) Suppose now that $(\xi^k)_{k \in K}$ is non-terminating, that is, $K = \mathbb{N}_0$. Also, let ξ^* be any accumulation point of (ξ^k) and let (ξ^{k_l}) be any subsequence with $\xi^{k_l} \longrightarrow \xi^*$ as $l \to \infty$. Since $\Xi(X)$ is sequentially compact (Lemma 2.10), there exists yet another subsequence (k_{l_j}) and a $\xi^{**} \in \Xi(X)$ such that $\xi^{k_{l_j}+1} \longrightarrow \xi^{**}$ as $j \to \infty$. Consequently,

$$M(\xi^{k_l}) \longrightarrow M(\xi^*)$$
 $(l \to \infty)$ and $M(\xi^{k_l_j+1}) \longrightarrow M(\xi^{**})$ $(j \to \infty).$ (3.34)

Since $(\Psi(M(\xi^k) + \nu_k))$ is monotonically decreasing for a null sequence (ν_k) (Lemma 3.12), the subsequences are monotonically decreasing as well and

$$\lim_{l \to \infty} \Psi(M(\xi^{k_l})) = \lim_{l \to \infty} \left(\Psi(M(\xi^{k_l})) + \nu_{k_l} \right) = \inf_{k \in \mathbb{N}_0} \left(\Psi(M(\xi^k) + \nu_k) \right)$$
$$= \lim_{j \to \infty} \left(\Psi(M(\xi^{k_{l_j}+1})) + \nu_{k_{l_j}+1} \right) = \lim_{j \to \infty} \Psi(M(\xi^{k_{l_j}+1})).$$
(3.35)

Since, moreover, Ψ is lower semicontinuous by assumption, (3.34), (3.35) further imply

$$\Psi(M(\xi^*)), \Psi(M(\xi^{**})) \le \inf_{k \in \mathbb{N}_0} (\Psi(M(\xi^k) + \nu_k) \le \Psi(M(\xi^0)) + \nu_0 < \infty$$
(3.36)

and therefore

$$\xi^*, \xi^{**}, \xi^k \in \Xi_{\text{fin}}(X) \qquad (k \in \mathbb{N}_0).$$
 (3.37)

In view of the continuity of $(\Psi \circ M)|_{\Xi_{\text{fin}}(X)}$ (Lemma 3.4), it follows from (3.34) and (3.37) and by (3.30) with $\alpha := 1/2$ that, on the one hand,

$$\Psi(M(\xi^{**})) = \lim_{j \to \infty} \Psi(M(\xi^{k_{l_j}+1})) \le \lim_{j \to \infty} \left(\Psi\left(M(\xi^{k_{l_j}}/2 + \xi^{k_{l_j}+1}/2)\right) + \overline{\delta}_{k_{l_j}+1}\right)$$
$$= \Psi(M(\xi^{*}/2 + \xi^{**}/2)) = \Psi(M(\xi^{*})/2 + M(\xi^{**})/2).$$
(3.38)

In view of the continuity of $(\Psi \circ M)|_{\Xi_{\text{fin}}(X)}$ (Lemma 3.4), it further follows from (3.34) and (3.37) and by (3.35) that, on the other hand,

$$\Psi(M(\xi^*)) = \lim_{l \to \infty} \Psi(M(\xi^{k_l})) = \lim_{j \to \infty} \Psi(M(\xi^{k_{l_j}+1})) = \Psi(M(\xi^{**})).$$
(3.39)

Since Ψ is strictly convex by assumption, we conclude from (3.38) and (3.39) that

$$M(\xi^{**}) = M(\xi^{*}). \tag{3.40}$$

Combining now (3.34.b) and (3.40), we finally obtain the desired convergence (3.32) and thus the lemma is proved.

With these preparations at hand, we can now show that Algorithm 3.10 or 3.11 applied with a tolerance $\varepsilon > 0$ is guaranteed to terminate, namely at an ε -optimal design for $\Psi \circ M$. In contrast to Algorithm 3.5 and 3.6, a bound on the numbers of iterations until termination is not so easy to establish anymore. See Corollaries 3.17 and 3.23, however, which establish such bounds at least for Algorithm 3.10.

Theorem 3.14. Suppose that Conditions 3.1 and 3.2 are satisfied and that Ψ is even strictly convex. Suppose further that X^0 is a finite subset of X satisfying (3.4) and that $(\xi^k)_{k \in K}$ is generated by Algorithm 3.10 or 3.11 with optimality tolerances $\varepsilon > 0$ and $\overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ such that $(\overline{\delta}_k)$ is summable and

$$\varepsilon > \underline{\delta},$$
 (3.41)

where $\underline{\delta} := \limsup_{k \to \infty} \underline{\delta}_k$. Then (ξ^k) terminates at an ε -optimal design for $\Psi \circ M$.

Proof. Assume that $(\xi^k)_{k \in K}$ does not terminate, that is, $K = \mathbb{N}_0$. It then follows by the algorithms' termination conditions that

$$\psi(M(\xi^k), x^k) < -\varepsilon + \underline{\delta}_k \qquad (k \in \mathbb{N}_0). \tag{3.42}$$

(In fact, in the case where Algorithm 3.11 is used, this even holds with $\underline{\delta}_k = 0$.) Since ξ^{k+1} is a $\overline{\delta}_{k+1}$ -optimal design on X^{k+1} and since $X^{k+1} = \operatorname{supp} \xi^k \cup \{x^k\} \ni x^k$ by the algorithms' definitions, it further follows that

$$\psi(M(\xi^{k+1}), x^k) \ge -\overline{\delta}_{k+1} \qquad (k \in \mathbb{N}_0) \tag{3.43}$$

by virtue of Theorem 2.24 with X replaced by X^{k+1} . We now choose convergent subsequences (ξ^{k_l}) and (x^{k_l}) with limits denoted by ξ^* and x^* (Lemma 2.10) and another subsequence (k_{l_j}) such that (3.32) is satisfied (Lemma 3.13). It then follows that $\xi^* \in \Xi_{\text{fin}}(X)$ (Lemma 3.13) and from (3.42) and (3.43) it further follows by the continuity of ψ that

$$\psi(M(\xi^*), x^*) = \lim_{l \to \infty} \psi(M(\xi^{k_l}), x^{k_l}) \le -\varepsilon + \underline{\delta}$$
(3.44)

$$\psi(M(\xi^*), x^*) = \lim_{j \to \infty} \psi(M(\xi^{k_{l_j}+1}), x^{k_{l_j}}) \ge -\lim_{j \to \infty} \overline{\delta}_{k_{l_j}+1} = 0.$$
(3.45)

In the last equality of (3.45), we used the assumed summability of $(\overline{\delta}_k)$. Combining now the inequalities (3.44) and (3.45), we conclude that $-\varepsilon + \underline{\delta} \ge 0$. Contradiction to (3.41)! So, our assumption that (ξ^k) does not terminate is false. And therefore (ξ^k) terminates at an ε -optimal design for $\Psi \circ M$ by Lemma 3.13 (i), as desired.

With essentially the same arguments, we can also prove that if Algorithm 3.10 is applied with tolerance $\varepsilon = 0$, then the sequence of iterates accumulates at an optimal design for $\Psi \circ M$. See Corollary 3.15 below.

3.3 A basic convergence result

We move on to establish a basic convergence result on our strict algorithms (Algorithms 3.5 and 3.10). It says that when applied with optimality tolerance $\varepsilon = 0$, the strict algorithms might not terminate anymore but still converge to an optimal design as $k \to \infty$.

Corollary 3.15. Suppose that Conditions 3.1 and 3.2 are satisfied. Suppose further that X^0 is a finite subset of X satisfying (3.4) and that $(\xi^k)_{k\in K}$ is generated by Algorithm 3.5 or Algorithm 3.10 with optimality tolerances $\varepsilon = 0$ and $\overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ such that $\lim_{k\to\infty} \overline{\delta}_k = 0 = \lim_{k\to\infty} \underline{\delta}_k$. In case Algorithm 3.10 is used, additionally assume that Ψ is even strictly convex and that $(\overline{\delta}_k)$ is even summable.

- (i) If (ξ^k) is terminating, then it terminates at an optimal design for $\Psi \circ M$.
- (ii) If (ξ^k) is non-terminating, then each of its accumulation points is an optimal design for $\Psi \circ M$.

Additionally, for a strictly convex design criterion Ψ , the sequence of information matrices $(M(\xi^k))$ converges to the unique solution of

$$\min_{M \in \mathcal{M}(\Xi(X))} \Psi(M).$$
(3.46)

Proof. Assertion (i) is clear by Lemma 3.8 (i) or Lemma 3.13 (i), respectively, and we have only to prove assertion (ii) and the additional convergence assertion concerning the information matrices. Suppose therefore that (ξ^k) is non-terminating for the entire proof.

As a first step, we show that every accumulation point ξ^* of (ξ^k) is an optimal design for $\Psi \circ M$. So, let ξ^* be an accumulation point of (ξ^k) . With the same arguments as in the proof of the termination theorem for Algorithm 3.5 or Algorithm 3.10, respectively, it then follows that $\xi^* \in \Xi_{\text{fin}}(X)$ and that there are subsequences (ξ^{k_l}) and (x^{k_l}) and an $x^* \in X$ such that

$$\xi^{k_l} \longrightarrow \xi^*$$
 and $x^{k_l} \longrightarrow x^*$ $(l \to \infty)$ (3.47)

and such that the estimate (3.21) or (3.45) is satisfied, respectively (depending on whether Algorithm 3.5 or 3.10 is used). Since x^k is a $\underline{\delta}_k$ -approximate solution of (3.9) or (3.27), respectively, it further follows that

$$\psi(M(\xi^k), x) \ge \psi(M(\xi^k), x^k) - \underline{\delta}_k \qquad (k \in \mathbb{N}_0 \text{ and } x \in X).$$
(3.48)

Combining now (3.21) or (3.45) with (3.47) and (3.48), we conclude by the continuity of ψ and by the assumed convergences of $(\overline{\delta}_k)$ and $(\underline{\delta}_k)$ to 0 that

$$\psi(M(\xi^*), x) = \lim_{l \to \infty} \psi(M(\xi^{k_l}), x) \ge \lim_{l \to \infty} \left(\psi(M(\xi^{k_l}), x^{k_l}) - \underline{\delta}_{k_l} \right) = \psi(M(\xi^*), x^*) \ge 0$$
(3.49)

for all $x \in X$. And therefore, ξ^* is an optimal design for $\Psi \circ M$ by virtue of Theorem 2.24, as desired.

As a second step, we show that for strictly convex Ψ the sequence of information matrices $(M(\xi^k))$ converges to the unique solution M^* of (3.46). So, let Ψ be strictly convex. In particular, this implies that (3.46) indeed has a unique solution M^* . It then follows by the first step and Lemma 2.10 that every accumulation point of $(M(\xi^k))$ is a solution of (3.46) and thus is equal to M^* . Consequently, $(M(\xi^k))$ has only one accumulation point, namely M^* . And therefore $(M(\xi^k))$ converges to M^* , as desired.

3.4 A general sublinear convergence rate result

In this section, we improve the mere convergence result from the previous section to a convergence rate result with a sublinear convergence rate. In order to get this sublinear convergence rate, we have to strengthen the assumptions on the design criterion Ψ a bit, namely essentially add an *L*-smoothness assumption on Ψ . As we will see, the thus strenghtened assumptions cover a large variety of situations (including those considered in [38]) and therefore pose almost no restriction from practical point of view.

Theorem 3.16. Suppose that Conditions 3.1 and 3.3 are satisfied. Suppose further that X^0 is a finite subset of X satisfying (3.4) and that $(\xi^k)_{k\in K}$ is generated by Algorithm 3.5 or Algorithm 3.10 with optimality tolerances $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ such that

$$\overline{\delta}_k \le \overline{c}/(k+1)^2$$
 and $\underline{\delta}_k \le \underline{c}/(k+2)$ $(k \in \mathbb{N}_0)$ (3.50)

for some constants $\overline{c}, \underline{c} \in [0, \infty)$. Suppose finally that

$$\mathcal{M} := \operatorname{conv}\left(\left\{(1-\alpha)M(\xi^k) + \alpha m(x^k) : k \in K \text{ and } \alpha \in [0, 2/3]\right\}\right) \subset \operatorname{dom}\Psi$$
(3.51)

and that $\Psi|_{\mathcal{M}}$ is L-smooth w.r.t. $|\cdot|$ for some $L \in [0, \infty)$. We then have the following sublinear convergence rate estimate

$$\Psi(M(\xi^k)) - \Psi^* \le \frac{2}{k+2} \Big((\Psi(M(\xi^1)) - \Psi^*) + L\Big(\operatorname{diam}(M(\Xi(X)))\Big)^2 + \overline{c} + \underline{c} \Big)$$
(3.52)

for all $k \in K$ with $k \ge 2$, where $\Psi^* := \min_{\xi \in \Xi(X)} \Psi(M(\xi))$ and $\operatorname{diam}(M(\Xi(X))) := \sup\{|M-N| : M, N \in M(\Xi(X))\}$.

Proof. We proceed in three steps and in the entire proof we will use the following shorthand notation:

$$C := \frac{L}{2} \left(\operatorname{diam}(M(\Xi(X)))^2. \right)$$
(3.53)

As a first step, we show that

$$\Psi(M(\xi^{k+1})) \le \Psi(M(\xi^k)) + \alpha \psi(M(\xi^k), x^k) + C\alpha^2 + \overline{\delta}_{k+1}$$
(3.54)

for all $k \in K$ with $k + 1 \in K$ and for all $\alpha \in [0, 2/3]$. So, let $k, k + 1 \in K$ and let $\alpha \in [0, 2/3]$. It then follows by the updating rule both of Algorithm 3.5 and of Algorithm 3.10 that

$$\operatorname{supp}\left((1-\alpha)\xi^k + \alpha\delta_{x^k}\right) \subset \operatorname{supp}\xi^k \cup \{x^k\} \subset X^{k+1}$$
(3.55)

and therefore $(1 - \alpha)\xi^k + \alpha \delta_{x^k} \in \Xi(X^{k+1})$. Since ξ^{k+1} is a $\overline{\delta}_{k+1}$ -optimal design on X^{k+1} by the algorithms' definitions, it follows that

$$\Psi(M(\xi^{k+1})) \le \min_{\xi \in \Xi(X^{k+1})} \Psi(M(\xi)) + \overline{\delta}_{k+1} \le \Psi((1-\alpha)M(\xi^k) + \alpha m(x^k)) + \overline{\delta}_{k+1}.$$
(3.56)

Since, moreover, $(1 - \alpha)M(\xi^k) + \alpha m(x^k) \in \mathcal{M}$ by the choice of α , it further follows by the assumed *L*-smoothness of $\Psi|_{\mathcal{M}}$ and by Lemma 2.22 that

$$\Psi(M(\xi^{k+1})) \leq \Psi(M(\xi^{k})) + \alpha D \Psi(M(\xi^{k}))(m(x^{k}) - M(\xi^{k})) + \frac{L}{2} |m(x^{k}) - M(\xi^{k})|^{2} \alpha^{2} + \overline{\delta}_{k+1}$$

$$\leq \Psi(M(\xi^{k})) + \alpha \psi(M(\xi^{k}), x^{k}) + C \alpha^{2} + \overline{\delta}_{k+1}, \qquad (3.57)$$

which is precisely the desired estimate (3.54).

As a second step, we show that

$$\Psi(M(\xi^{k+1})) - \Psi^* \le (1-\alpha) \left(\Psi(M(\xi^k) - \Psi^*) + C\alpha^2 + \overline{\delta}_{k+1} + \underline{\delta}_k \alpha \right)$$
(3.58)

for all all $k \in K$ with $k + 1 \in K$ and for all $\alpha \in [0, 2/3]$. So, let $k, k + 1 \in K$ and let $\alpha \in [0, 2/3]$. Also, let $\xi^* \in \Xi(X)$ be an optimal design for $\Psi \circ M$ on X, that is, $\Psi(M(\xi^*)) = \Psi^*$. Since x^k is a $\underline{\delta}_k$ -approximate solution of the worst optimality violator problem for ξ^k by the algorithms' definitions and since Ψ is convex by assumption, it follows that

$$\psi(M(\xi^k), x^k) \le \min_{x \in X} \psi(M(\xi^k), x) + \underline{\delta}_k \le \int_X \psi(M(\xi^k), x) \,\mathrm{d}\xi^*(x) + \underline{\delta}_k \le -(\Psi(M(\xi^k)) - \Psi^*) + \underline{\delta}_k.$$
(3.59)

Inserting this inequality (3.59) into the estimate (3.54) established in the first step, we immediately obtain the desired estimate (3.58).

As a third step, we finally establish the claimed convergence rate estimate (3.52). In fact, we prove a slightly more general estimate, namely we prove that

$$\Psi(M(\xi^k)) - \Psi^* \le \frac{2}{k+2} \Big(\frac{k_0 + 1}{2} \big(\Psi(M(\xi^{k_0})) - \Psi^* \big) + 2C + \overline{c} + \underline{c} \Big)$$
(3.60)

for all $k \in K_{k_0+1} := \{l \in K : l \ge k_0 + 1\}$ and arbitrary $k_0 \in K$ with $k_0 \ge 1$. In the special case $k_0 = 1$, this reduces to the claimed convergence rate estimate (3.52). We prove (3.60) by induction over K_{k_0+1} and adopt the shorthand notations

$$h_k := \Psi(M(\xi^k)) - \Psi^*$$
 and $C' := C + \frac{\overline{c} + \underline{c}}{2}.$ (3.61)

In order to establish (3.60) for $k := k_0 + 1$, we set $\alpha := 2/(k_0 + 2) \in [0, 2/3]$ in (3.58). We thus obtain

$$h_{k_0+1} \leq (1-\alpha)h_{k_0} + C\alpha^2 + \overline{\delta}_{k_0+1} + \underline{\delta}_{k_0}\alpha \leq (1-\alpha)h_{k_0} + C'\alpha^2 \\ \leq \frac{2}{k_0+3} \Big(\frac{k_0+1}{2}h_{k_0} + 2C'\Big).$$
(3.62)

In the second inequality of (3.62) we used the assumptions (3.50), while in the last inequality of (3.62) we used that

$$1 - \alpha = \frac{k_0}{k_0 + 2} \le \frac{k_0 + 1}{k_0 + 3} = \frac{2}{k_0 + 3} \cdot \frac{k_0 + 1}{2}$$
(3.63)

$$\alpha^2 \le \frac{3}{k_0 + 3} \cdot \frac{2}{k_0 + 2} \le \frac{2}{k_0 + 3} \cdot 2. \tag{3.64}$$

Since (3.62) is precisely the claimed estimate (3.60) for $k := k_0 + 1$, the induction basis is finished. We now move on to the induction step, that is, we assume that the claimed estimate (3.60) is true for some given $k \in K_{k_0+1}$ with $k + 1 \in K_{k_0+1}$. Setting $\alpha := 2/(k+2) \in [0, 2/3]$, we then conclude from (3.58) and the induction assumption that

$$h_{k+1} \leq (1-\alpha)h_k + C\alpha^2 + \overline{\delta}_{k+1} + \underline{\delta}_k \alpha \leq (1-\alpha)h_k + C'\alpha^2$$

$$\leq (1-\alpha)\frac{2}{k+2}\left(\frac{k_0+1}{2}h_{k_0} + 2C'\right) + C'\alpha^2$$

$$= (1-\alpha)\frac{2}{k+2}\frac{k_0+1}{2}h_{k_0} + \left((1-\alpha)\frac{4}{k+2} + \alpha^2\right)C' \leq \frac{2}{k+3}\left(\frac{k_0+1}{2}h_{k_0} + 2C'\right). \quad (3.65)$$

In the second inequality of (3.65) we used the assumptions (3.50), while in the last inequality of (3.65) we used that

$$(1-\alpha)\frac{2}{k+2} = \frac{k}{k+2} \cdot \frac{2}{k+2} \le \frac{k+1}{k+3} \cdot \frac{2}{k+2} \le \frac{2}{k+3}$$
(3.66)

$$(1-\alpha)\frac{4}{k+2} + \alpha^2 = \frac{k}{k+2} \cdot \frac{4}{k+2} + \frac{1}{k+2} \cdot \frac{4}{k+2} = \frac{k+1}{k+2} \cdot \frac{4}{k+2} \le \frac{2}{k+3} \cdot 2.$$
(3.67)

Since (3.65) is precisely the claimed estimate (3.60) with k replaced by k + 1, the induction step – and thus the proof of (3.60) – is finished.

Corollary 3.17. Suppose the assumptions of the above theorem are satisfied with a tolerance $\varepsilon > \underline{\delta} := \sup_{k>2} \underline{\delta}_k$. Algorithms 3.5 and 3.10 then terminate at the very latest in iteration

$$k^* := \min\left\{k \ge 2 : \frac{2}{k+2} \left(\Psi(M(\xi^1)) - \underline{\Psi}^* + 2C'\right) \le \varepsilon - \underline{\delta}\right\},\tag{3.68}$$

where $\underline{\Psi}^*$ is an arbitrary lower bound for $\Psi^* := \min_{\xi \in \Xi(X)} \Psi(M(\xi))$ and C' is defined as in (3.61) above.

Proof. Assume, to the contrary, that Algorithm 3.5 or 3.10 runs at least until iteration $k^* + 1$. It then follows that $k^* \in K$ with $k^* \ge 2$ and thus, by the sublinear convergence rate estimate (3.52) and by the definition (3.68) of k^* , that

$$\Psi(M(\xi^{k^*})) - \Psi^* \le \frac{2}{k^* + 2} \left(\Psi(M(\xi^1)) - \underline{\Psi}^* + 2C' \right) \le \varepsilon - \underline{\delta}.$$
(3.69)

Consequently, ξ^{k^*} is an $(\varepsilon - \underline{\delta})$ -optimal design for $\Psi \circ M$. It follows (Theorem 2.24) that

$$\psi(M(\xi^{k^*}), x^{k^*}) \ge \min_{x \in X} \psi(M(\xi^{k^*}), x) \ge -\varepsilon + \underline{\delta} \ge -\varepsilon + \underline{\delta}_{k^*}.$$
(3.70)

And this in turn means, by the termination criteria of Algorithm 3.5 and 3.10, that the algorithm terminates at iteration k^* . Contradiction to our initial assumption!

Example 3.18. Suppose that X, m, M are as in Condition 2.18 and that the one-stage design criterion $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R} \cup \{\infty\}$ is defined by

$$\Psi(M) := \Psi_{p,Q}(M) \qquad (M \in \mathbb{R}^{d \times d}_{\text{psd}})$$
(3.71)

for some $p \in [0, \infty)$ and an invertible matrix $Q \in \mathbb{R}^{d \times d}$, see (2.45). Suppose further that (3.4) is satisfied for some finite subset X^0 of X. If the sequence $(\xi^k)_{k \in K}$ is then generated by Algorithm 3.5 or 3.10 with tolarences $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0, \infty)$ satisfying (3.50), then all assumptions of our sublinear convergence rate theorem are satisfied and therefore the error estimate (3.52) holds true. (Indeed, by the definition (2.45) and by the assumed invertibility of Q, it follows that

dom
$$\Psi = \{ M \in \mathbb{R}^{d \times d}_{psd} : ran(Q) \subset ran(M) \text{ and } Q^{\top} M^{-} Q \in \mathbb{R}^{d \times d}_{pd} \} = \mathbb{R}^{d \times d}_{pd}.$$
 (3.72)

And therefore, Conditions 3.1 and 3.3 are satisfied (Corollary 2.13). Additionally, it follows by the final statements of Lemmas 3.7 and 3.12 that $\Psi(M(\xi^k)) \leq \Psi(M(\xi^0)) + c_0 < \infty$ for all $k \in K$. And from this, in turn, it follows by (3.72) and (2.45), using analogous arguments as for Lemma 2.11, that

$$M(\xi^k) \ge \mu_0 \qquad (k \in K) \tag{3.73}$$

for some $\mu_0 > 0$. So, by (3.72) and (3.73), the assumption (3.51) is satisfied as well. And finally, the *L*-smoothness of $\Psi|_{\mathcal{M}}$ follows by Lemma 2.8 and Corollary 2.13, using that \mathcal{M} is a subset of the compact subset $\mathcal{C} := \{A \in \mathbb{R}^{d \times d}_{psd} : \mu_0/3 \le A \le \max_{x \in X} \|m(x)\|\}$ of $\mathbb{R}^{d \times d}_{pd}$.)

Example 3.19. Suppose that X, m, M are as in Condition 2.18 and that the two-stage design criterion $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R}$ is defined by

$$\Psi(M) := \Psi_{p,Q}(\alpha M^0 + (1 - \alpha)M) \qquad (M \in \mathbb{R}^{d \times d}_{psd})$$
(3.74)

for some $\alpha \in (0,1)$ and $M^0 \in \mathbb{R}_{pd}^{d \times d}$ and for some $p \in [0,\infty)$ and a matrix $Q \in \mathbb{R}^{d \times s}$ with $\operatorname{rk} Q = s \leq d$, see (2.45) and (2.53). If the sequence $(\xi^k)_{k \in K}$ is then generated by Algorithm 3.5 or 3.10 with tolarences $\varepsilon, \overline{\delta}_k, \underline{\delta}_k \in [0,\infty)$ satisfying (3.50), then all assumptions of our sublinear convergence rate theorem are satisfied and therefore the error estimate (3.52) holds true. (Indeed, by the definition (2.45) and the assumed positive definiteness of M^0 as well as the assumed injectivity of Q, it follows that

dom
$$\Psi = \{ M \in \mathbb{R}^{d \times d}_{\text{psd}} : Q^{\top} (\alpha M^0 + (1 - \alpha)M)^{-1}Q \in \mathbb{R}^{d \times d}_{\text{psd}} \} = \mathbb{R}^{d \times d}_{\text{psd}}.$$
 (3.75)

And therefore, Conditions 3.1 and 3.3 are satisfied (Corollary 2.13). In particular, the assumption (3.51) is satisfied trivially. And finally, the *L*-smoothness $\Psi|_{\mathcal{M}}$ follows by Lemma 2.8 and Corollary 2.13, using that $\mathcal{C} := \{\alpha M^0 + (1 - \alpha)M : M \in \mathcal{M}\}$ is a compact subset of $\mathbb{R}^{d \times d}_{pd}$.)

3.5 A linear convergence rate result

In this section, we further improve the sublinear convergence rate result from the previous section to a convergence rate result with an even linear convergence rate. In order to get this significantly better linear convergence rate, we have to strengthen the assumptions on the design criterion Ψ and the design space X a bit more, namely essentially add a μ -strong convexity assumption on Ψ and assume the finiteness of X. As we will see, the strong convexity assumptions is still satisfied for a large variety of practically relevant design criteria. Similarly, the finiteness assumption poses no serious restriction either because in practice set of possible experimental points is finite anyways.

We begin with a few preparations. Suppose that \mathcal{A} is a finite subset of $\mathbb{R}^{d \times d}_{psd}$ and that $M \in \mathbb{R}^{d \times d}_{psd}$. A subset \mathcal{S} of \mathcal{A} is then called an active set for M iff M is a proper convex combination of the elements of \mathcal{S} , that is,

$$M = \sum_{m \in \mathcal{S}} \lambda_m m \text{ for some } (\lambda_m)_{m \in \mathcal{S}} \in \Delta_{\mathcal{S}}^{\circ}, \qquad (3.76)$$

where $\Delta_{\mathcal{S}}^{\circ} := \{(\lambda_m)_{m \in \mathcal{S}} \in (0,1)^{|\mathcal{S}|} : \sum_{m \in \mathcal{S}} \lambda_m = 1\}$ is the interior of the $(|\mathcal{S}| - 1)$ -dimensional probability simplex $\Delta_{\mathcal{S}}$. We denote the set of subsets of \mathcal{A} that are active for a given M by

$$\mathcal{S}_{\mathcal{A}}(M) := \{ \mathcal{S} \subset \mathcal{A} : \mathcal{S} \text{ is an active set for } M \}.$$
(3.77)

Suppose in addition that $\Psi : \mathcal{M} \to \mathbb{R}$ is a differentiable map and that $M \in \mathcal{M}$ and $\mathcal{S} \subset \mathcal{A}$. We then need the sets

$$\mathcal{M}_M := \mathcal{M}_{M,\mathcal{A}} := \operatorname*{argmin}_{m \in \mathcal{A}} D\Psi(M)m \quad \text{and} \quad \mathcal{N}_{M,\mathcal{S}} := \operatorname*{argmax}_{n \in \mathcal{S}} D\Psi(M)n \quad (3.78)$$

of minimizers and maximizers of $a \mapsto D\Psi(M)a$ over \mathcal{A} or \mathcal{S} , respectively. Additionally, we also need the set

$$\mathcal{N}_M := \operatorname*{argmin}_{n \in \{n': n' \in \mathcal{N}_{M, \mathcal{S}} \text{ for some } \mathcal{S} \in \mathcal{S}_{\mathcal{A}}(M)\}} D\Psi(M)n \tag{3.79}$$

of those maximizers that yield the smallest maximum $\max_{n \in S} D\Psi(M)n$ among all active sets S for M. In other words, a matrix n_M belongs to \mathcal{N}_M if and only if there exists an active set $S^* \in \mathcal{S}_A(M)$ for M such that

$$n_M \in \mathcal{N}_{M,\mathcal{S}^*}$$
 and $D\Psi(M)n_M = \min_{\mathcal{S}\in\mathcal{S}_A(M)} \max_{n\in\mathcal{S}} D\Psi(M)n.$ (3.80)

Lemma 3.20. Suppose that \mathcal{A} is a finite subset of $\mathbb{R}^{d \times d}_{psd}$ and let $\mathcal{M} := conv(\mathcal{A})$. Suppose further that $\Psi : \mathcal{M} \to \mathbb{R}$ is convex and differentiable.

(i) If $M \in \mathcal{M}$ and $\mathcal{S} \in \mathcal{S}_{\mathcal{A}}(M)$, then

$$D\Psi(M)(n_{M,\mathcal{S}} - m_M) \ge D\Psi(M)(n_M - m_M) \ge \Psi(M) - \Psi^*$$
(3.81)

for arbitrary $m_M \in \mathcal{M}_M$, $n_M \in \mathcal{N}_M$ and $n_{M,S} \in \mathcal{N}_{M,S}$, where $\Psi^* := \min_{M \in \mathcal{M}} \Psi(M)$. Additionally, the quantity $D\Psi(M)(m_M - n_M)$ depends only on M but not on the particular choices of $m_M \in \mathcal{M}_M$ and $n_M \in \mathcal{N}_M$.

(ii) If $D\Psi(M)(M'-M) < 0$ for some $M, M' \in \mathcal{M}$, then also $D\Psi(M)(m_M - n_M) < 0$ for all $m_M \in \mathcal{M}_M$ and $n_M \in \mathcal{N}_M$.

Proof. (i) Suppose $M \in \mathcal{M}$ and $\mathcal{S} \in \mathcal{S}_{\mathcal{A}}(M)$ and let $m_M \in \mathcal{M}_M$, $n_M \in \mathcal{N}_M$ and $n_{M,\mathcal{S}} \in \mathcal{N}_{M,\mathcal{S}}$. Also, choose an $\mathcal{S}^* \in \mathcal{S}_{\mathcal{A}}(M)$ with (3.80) and an $M^* \in \mathcal{M}$ with $\Psi^* = \Psi(M^*)$ (which is possible, of course, by the continuity of Ψ and the compactness of \mathcal{M}). It follows by the definition (3.78.a) of \mathcal{M}_M and the convexity of Ψ that

$$D\Psi(M)(m_M - M) \le D\Psi(M)(M' - M) \le \Psi(M') - \Psi(M) \qquad (M' \in \mathcal{M}), \tag{3.82}$$

where for the first inequality we used that every $M' \in \mathcal{M} = \operatorname{conv}(\mathcal{A})$ can be represented as a convex combination $M' = \sum_{m \in \mathcal{A}} \lambda'_m m$ of elements of \mathcal{A} . In order to obtain the first inequality in (3.81), we have only to insert the definition (3.78.b) of $\mathcal{N}_{M,\mathcal{S}}$ into (3.80.b). In order to obtain the second inequality in (3.81), we have only to notice that $M = \sum_{n \in \mathcal{S}^*} \lambda_n n$ for some $(\lambda_n) \in \Delta_{\mathcal{S}^*}^\circ$, so that

$$D\Psi(M)n_M \ge \sum_{n\in\mathcal{S}^*} \lambda_n D\Psi(M)n = D\Psi(M)M$$
 (3.83)

by virtue of (3.80.a). Setting now $M' := M^*$ in (3.82) and combining the resulting inequality with (3.83), we obtain the second inequality in (3.81). And finally, the claimed independence of $D\Psi(M)(m_M - n_M)$ is obvious by (3.78.a) and (3.80.b).

(ii) Suppose now $D\Psi(M)(M'-M) < 0$ for some $M, M' \in \mathcal{M}$ and let $m_M \in \mathcal{M}_M$ and $n_M \in \mathcal{N}_M$. We then obtain the claimed inequality

$$D\Psi(M)(m_M - n_M) \le D\Psi(M)(m_M - M) \le D\Psi(M)(M' - M) < 0$$
(3.84)

by (3.83) and the first inequality in (3.82).

We recall from [18] the notion of the strong convexity constant $\mu_{\Psi,\mathcal{M}}$ and of the curvature constant $C_{\Psi,\mathcal{M}}$ of a differentiable map $\Psi: \mathcal{M} \to \mathbb{R}$ on a convex subset \mathcal{M} of $\mathbb{R}^{d \times d}_{psd}$. Specifically,

$$\mu_{\Psi,\mathcal{M}} := \inf_{\substack{M,M' \in \mathcal{M}, \\ D\Psi(M)(M'-M) < 0}} \frac{2}{\alpha(M,M')^2} \left(\Psi(M') - \Psi(M) - D\Psi(M)(M'-M) \right)$$
(3.85)

$$C_{\Psi,\mathcal{M}} := \sup_{\substack{M,M'\in\mathcal{M},\\\alpha\in\{0,1\}}} \frac{2}{\alpha^2} \left(\Psi(M + \alpha(M' - M) - \Psi(M) - \alpha D\Psi(M)(M' - M)) \right)$$
(3.86)

where $\alpha(M, M') := D\Psi(M)(M' - M)/D\Psi(M)(m_M - n_M)$ with arbitrary $m_M \in \mathcal{M}_M$ and $n_M \in \mathcal{N}_M$. In view of Lemma 3.20, the quantity $\alpha(M, M')$ is a well-defined positive real number as soon as $D\Psi(M)(M' - M) < 0$. We also recall from [18, 21] the notion of the pyramidal width pwidth(\mathcal{A}) of a finite subset \mathcal{A} of $\mathbb{R}^{d \times d}_{psd}$. Specifically,

$$pwidth(\mathcal{A}) := \min_{\substack{\mathcal{F} \in faces(conv(\mathcal{A})), \\ \emptyset \neq \mathcal{F} \neq conv(\mathcal{A})}} dist(\mathcal{F}, conv(\mathcal{F} \setminus \mathcal{A}))$$
$$= \min_{\substack{M,M' \in conv(\mathcal{A}), \\ M \neq M'}} pdirwidth(\mathcal{A}, M' - M, M)$$
(3.87)

(Theorems 1 and 2 of [21]), where faces(conv(\mathcal{A})) denotes the set of faces of the polytope conv(\mathcal{A}) (Section 2.1 of [42]) and where the pyramidal directional width of \mathcal{A} in the direction $J \neq 0$ with base point M is defined by

$$pdirwidth(\mathcal{A}, J, M) := \min_{\mathcal{S} \in \mathcal{S}_{\mathcal{A}}(M)} \max_{m \in \mathcal{A}, n \in \mathcal{S}} \langle J/|J|, m - n \rangle.$$
(3.88)

See the first formula after Example 2 and the last formula before Theorem 2 in [21]. In the above formula, the scalar product $\langle \cdot, \cdot \rangle$ is the one induced by the Frobenius norm $|\cdot|$.

Lemma 3.21. Suppose that \mathcal{A} is a finite subset of $\mathbb{R}^{d \times d}_{psd}$ with $|\mathcal{A}| \geq 2$ and let $\mathcal{M} := \operatorname{conv}(\mathcal{A})$. Suppose further that $\Psi : \mathcal{M} \to \mathbb{R}$ is differentiable and μ -strongly convex and L-smooth w.r.t. $|\cdot|$ for some $\mu, L \in (0, \infty)$. Then

$$0 < \mu \cdot (\operatorname{pwidth}(\mathcal{A}))^2 \le \mu_{\Psi,\mathcal{M}} \le C_{\Psi,\mathcal{M}} \le L \cdot (\operatorname{diam}(\mathcal{M}))^2, \tag{3.89}$$

where diam $(\mathcal{M}) := \sup\{|M - N| : M, N \in \mathcal{M}\}.$

Theorem 3.22. Suppose that Conditions 3.1 and 3.3 are satisfied. Suppose further that the set $\mathcal{A} := \{m(x) : x \in X\}$ of one-point information matrices is finite with $|\mathcal{A}| \ge 2$, that

$$\mathcal{M} := M(\Xi(X)) \subset \operatorname{dom} \Psi, \tag{3.90}$$

and that $\Psi|_{\mathcal{M}}$ is μ -strongly convex and L-smooth w.r.t. $|\cdot|$ for some $\mu, L \in (0, \infty)$. Suppose finally that X^0 is a finite subset of X satisfying (3.4) and that $(\xi^k)_{k \in K}$ is generated by Algorithm 3.5 or Algorithm 3.10 with optimality tolerances $\varepsilon \in [0, \infty)$ and $\overline{\delta}_k = 0 = \underline{\delta}_k$. We then have the following linear convergence rate estimate:

$$\Psi(M(\xi^k)) - \Psi^* \le r^k \cdot (\Psi(M(\xi^0)) - \Psi^*)$$
(3.91)

for all $k \in K$, where $\Psi^* := \min_{\xi \in \Xi(X)} \Psi(M(\xi))$ and $r := 1 - \min\{1/2, \mu_{\Psi,\mathcal{M}}/C_{\Psi,\mathcal{M}}\}$ and

$$1/2 \le r \le 1 - \min\{1/2, (\mu/L) \cdot (\operatorname{pwidth}(\mathcal{A})/\operatorname{diam}(\mathcal{M}))^2\} < 1.$$
 (3.92)

Proof. In the entire proof, we use the abbreviations

$$M_k := M(\xi^k)$$
 and $m_k := m(x^k)$ and $n_k := n_{M_k, \mathcal{S}_k} \in \mathcal{N}_{M_k, \mathcal{S}_k},$ (3.93)

where n_{M_k,S_k} is an arbitrary element of $\mathcal{N}_{M_k,S_k} = \operatorname{argmax}_{n \in S_k} D\Psi(M_k)n$ and

$$\mathcal{S}_k := \{ m(x) : x \in \operatorname{supp} \xi^k \}.$$
(3.94)

Additionally, we use the abbreviations

$$g_k := D\Psi(M_k)(n_k - m_k)$$
 and $h_k := \Psi(M_k) - \Psi(M^*),$ (3.95)

where $M^* := M(\xi^*)$ and ξ^* is an arbitrary optimal design for $\Psi \circ M$ (Theorem 2.20). It is clear by the definition of n_k and S_k that

$$n_k = m(y^k)$$
 for some $y^k \in \operatorname{supp} \xi^k$. (3.96)

Also, by the proof of Lemma 2.19,

$$\mathcal{M} = M(\Xi(X)) = \operatorname{conv}(\{m(x) : x \in X\}) = \operatorname{conv}(\mathcal{A}).$$
(3.97)

With these preliminaries at hand, we can now enter the core of the proof. We proceed in four steps, the third and fourth step following the lines of proof from [18] (Theorem 8).

As a first step, we show that

$$D\Psi(M_k)(m_k - M_k) = -g_k$$
 and $g_k \ge D\Psi(M_k)(n_{M_k} - m_{M_k}) \ge h_k$ (3.98)

for all $k \in K$ and arbitrary $m_{M_k} \in \mathcal{M}_{M_k}$ and $n_{M_k} \in \mathcal{N}_{M_k}$. In order to prove (3.98.a), choose and fix $k \in K$. Since ξ^k is an optimal design for $\Psi \circ M$ on X^k by the algorithms' definitions with $\overline{\delta}_k = 0$, it follows that

$$D\Psi(M_k)(n_k - M_k) = \psi(M(\xi^k), y^k) = 0, \qquad (3.99)$$

where for the first equality we used (3.96) together with Lemma 2.22 and for the second equality we used the last statement of Theorem 2.24 with X replaced by X^k . In view of (3.95.a) and (3.99), the asserted equality (3.98.a) is now clear. In order to prove also (3.98.b), choose and fix $k \in$ K and $m_{M_k} \in \mathcal{M}_{M_k}$ and $n_{M_k} \in \mathcal{N}_{M_k}$. Since x^k is a minimizer of $X \ni x \mapsto \psi(M_k, x) =$ $D\Psi(M_k)(m(x) - M_k)$ by the algorithms' definitions with $\underline{\delta}_k = 0$, it follows that

$$m_k = m(x^k) \in \operatorname*{argmin}_{m \in \mathcal{A}} D\Psi(M_k)m = \mathcal{M}_{M_k}.$$
(3.100)

Since $S_k \subset A$ and $M_k = M(\xi^k) = \int_X m(x) d\xi^k(x) = \sum_{x \in \text{supp } \xi^k} \xi^k(\{x\})m(x)$, it further follows that S_k is an active set for M_k , in short,

$$\mathcal{S}_k \in \mathcal{S}_\mathcal{A}(M_k). \tag{3.101}$$

In view of (3.93.c), (3.95.a), (3.100) and (3.101), the asserted inequality chain (3.98.b) is an immediate consequence of Lemma 3.20(i).

As a second step, we show that

$$h_k > 0$$
 and $D\Psi(M_k)(M^* - M_k) < 0$ (3.102)

for every non-terminal iteration index $k \in K$. So, let $k \in K$ be non-terminal. It then follows by the algorithms' termination rule that $\psi(M(\xi^k), x^k) < -\varepsilon \leq 0$. Consequently, ξ^k is not an optimal design for $\Psi \circ M$ by Theorem 2.24 and therefore

$$h_k = \Psi(M(\xi^k)) - \min_{\xi \in \Xi(X)} \Psi(M(\xi)) > 0, \qquad (3.103)$$

that is, (3.102.a) is proved. Additionally, by the convexity of Ψ and by (3.103),

$$D\Psi(M_k)(M^* - M_k) = \lim_{t \searrow 0} \frac{\Psi(M_k + t(M^* - M_k)) - \Psi(M_k)}{t}$$

$$\leq \Psi(M^*) - \Psi(M_k) = -h_k < 0, \qquad (3.104)$$

that is, (3.102.b) is proved as well.

As a third step, we show that for every non-terminal iteration index $k \in K$ the estimate

$$h_k \le \frac{g_k^2}{2\mu_{\Psi,\mathcal{M}}} \tag{3.105}$$

holds true. So, let $k \in K$ be non-terminal. It then follows by Lemma 3.20(ii) in conjunction with (3.102.b) that

$$\alpha_k := \alpha(M_k, M^*) = \frac{D\Psi(M_k)(M^* - M_k)}{D\Psi(M_k)(m_{M_k} - n_{M_k})} > 0.$$

So, by the definition (3.85) of the strong convexity constant $\mu_{\Psi,\mathcal{M}}$ combined with (3.102.b) and (3.98.b), it follows that

$$\frac{\alpha_k^2}{2}\mu_{\Psi,\mathcal{M}} \le \Psi(M^*) - \Psi(M_k) - D\Psi(M_k)(M^* - M_k) = -h_k + \alpha_k D\Psi(M_k)(n_{M_k} - m_{M_k}) \\ \le -h_k + \alpha_k g_k.$$

And therefore we obtain

$$h_k \le \alpha_k g_k - \alpha_k^2 \frac{\mu_{\Psi,\mathcal{M}}}{2} = \left(2\alpha_k \cdot \frac{g_k}{\mu_{\Psi,\mathcal{M}}}\right) \frac{\mu_{\Psi,\mathcal{M}}}{2} \le \frac{g_k^2}{\mu_{\Psi,\mathcal{M}}^2} \frac{\mu_{\Psi,\mathcal{M}}}{2} = \frac{g_k^2}{2\mu_{\Psi,\mathcal{M}}},\tag{3.106}$$

as desired.

As a fourth step, we show that for every non-terminal iteration index $k \in K$ the estimate

$$h_{k+1} \le r \cdot h_k \tag{3.107}$$

holds true with $r := 1 - \min\{1/2, \mu_{\Psi,\mathcal{M}}/C_{\Psi,\mathcal{M}}\}$, and then conclude the proof of the theorem. So, let $k \in K$ be non-terminal. It then follows by the updating rule both of Algorithm 3.5 and of Algorithm 3.10 that

$$\operatorname{supp}\left((1-\alpha)\xi^k + \alpha\delta_{x^k}\right) \subset \operatorname{supp}\xi^k \cup \{x^k\} \subset X^{k+1} \qquad (\alpha \in [0,1])$$
(3.108)

and therefore $(1 - \alpha)\xi^k + \alpha \delta_{x^k} \in \Xi(X^{k+1})$ for all $\alpha \in [0, 1]$. Since ξ^{k+1} is an optimal design for $\Psi \circ M$ on X^{k+1} by the algorithms' definitions with $\overline{\delta}_k = 0$, it follows that

$$\Psi(M_{k+1}) = \Psi(M(\xi^{k+1})) \le \Psi((1-\alpha)M(\xi^k) + \alpha m(x^k))$$

= $\Psi(M_k + \alpha(m_k - M_k)) \qquad (\alpha \in [0,1]).$

So, by the definition (3.86) of the curvature constant $C_{\Psi,\mathcal{M}}$ combined with (3.98.a), it follows that

$$\Psi(M_{k+1}) \leq \Psi(M_k) + \alpha D \Psi(M_k)(m_k - M_k) + \frac{\alpha^2}{2} C_{\Psi,\mathcal{M}}$$
$$= \Psi(M_k) - g_k \alpha + C_{\Psi,\mathcal{M}} \frac{\alpha^2}{2} \qquad (\alpha \in [0,1]).$$
(3.109)

And therefore we obtain

$$h_{k+1} \le \min_{\alpha \in [0,1]} \left(h_k - g_k \alpha + C_{\Psi,\mathcal{M}} \frac{\alpha^2}{2} \right) = h_k - g_k \alpha_k^* + C_{\Psi,\mathcal{M}} \frac{(\alpha_k^*)^2}{2}, \tag{3.110}$$

where α_k^* denotes a minimizer of the right-hand side of (3.109) as a function of $\alpha \in [0, 1]$. Since $g_k \geq h_k > 0$ by (3.98.b) and (3.102.a) and since $C_{\Psi,\mathcal{M}} \geq \mu_{\Psi,\mathcal{M}} > 0$ by Lemma 3.21, α_k^* is the only minimizer and it is given by

$$\alpha_k^* = \min\left\{\frac{g_k}{C_{\Psi,\mathcal{M}}}, 1\right\}.$$
(3.111)

We now consider the two cases in (3.111) separately. In case $g_k < C_{\Psi,\mathcal{M}}$, we conclude from (3.110) with (3.111) and (3.105) that

$$h_{k+1} \le h_k - \frac{g_k^2}{C_{\Psi,\mathcal{M}}} = h_k - \frac{\mu_{\Psi,\mathcal{M}}}{C_{\Psi,\mathcal{M}}} \frac{g_k^2}{2\mu_{\Psi,\mathcal{M}}} \le \left(1 - \mu_{\Psi,\mathcal{M}}/C_{\Psi,\mathcal{M}}\right)h_k.$$
(3.112)

In case $g_k \ge C_{\Psi,\mathcal{M}}$, we conclude from (3.110) with (3.111) and (3.98.b) that

$$h_{k+1} \le h_k - g_k + \frac{C_{\Psi,\mathcal{M}}}{2} \le h_k - \frac{g_k}{2} \le (1 - 1/2)h_k.$$
 (3.113)

So, combining (3.112) and (3.112), we immediately obtain the desired estimate (3.107). And from (3.107), in turn, the linear convergence rate estimate (3.91) immediately follows by induction over K, while the relations (3.92) immediately follow by Lemma 3.21.

Corollary 3.23. Suppose the assumptions of the above theorem are satisfied with a strictly positive tolerance $\varepsilon > 0$. Algorithms 3.5 and 3.10 then terminate at the very latest in iteration

$$k^* := \min\left\{k \in \mathbb{N}_0 : r^k \left(\Psi(M(\xi^0)) - \underline{\Psi}^*\right) \le \varepsilon\right\},\tag{3.114}$$

where $\underline{\Psi}^*$ is an arbitrary lower bound for $\Psi^* := \min_{\xi \in \Xi(X)} \Psi(M(\xi))$.

Proof. Completely analogous to the proof of Corollary 3.17.

Example 3.24. Suppose that X, m, M are as in Condition 2.18 and that, in addition, the design space X is finite but such that $\mathcal{A} := \{m(x) : x \in X\}$ is not a singleton. Suppose further that the two-stage design criterion $\Psi : \mathbb{R}^{d \times d}_{psd} \to \mathbb{R}$ is defined by

$$\Psi(M) := \tilde{\Psi}_p(\alpha M^0 + (1 - \alpha)M) \qquad (M \in \mathbb{R}^{d \times d}_{\text{psd}})$$
(3.115)

for some $\alpha \in (0,1)$ and $M^0 \in \mathbb{R}^{d \times d}_{pd}$ and for some $p \in \mathbb{N}_0$, see (2.49) and (2.53). In particular, we recall that this covers the D-criterion $\Psi_0 = \tilde{\Psi}_0$ and the A-criterion $\Psi_1 = \tilde{\Psi}_1$. If the sequence $(\xi^k)_{k \in K}$ is then generated by Algorithm 3.5 or 3.10 with tolarences $\varepsilon \in [0, \infty)$ and $\overline{\delta}_k = 0 = \underline{\delta}_k$, then all assumptions of our linear convergence rate theorem are satisfied and therefore the error estimate (3.91) holds true. (Indeed, the assumption (3.90) is trivially satisfied because dom $\Psi = \mathbb{R}^{d \times d}_{psd}$ by the assumed positive definiteness of M^0 . Additionally, Conditions 3.1 and 3.3 and the *L*-smoothness of $\Psi|_{\mathcal{M}}$ follow in a completely analogous way as in Example 3.19. And finally, the μ -strong convexity of $\Psi|_{\mathcal{M}}$ follows by Corollary 2.14, using that $\mathcal{C} := \{\alpha M^0 + (1-\alpha)M : M \in \mathcal{M}\}$ is a compact subset of $\mathbb{R}^{d \times d}_{pd}$.

4 Application examples

In this section, we apply the proposed adaptive discretization algorithms to two experimental design problems from chemical engineering. In both application examples, the underlying prediction model f is implicitly defined, namely by nonlinear algebraic equations in the first example and by nonlinear differential equations in the second example. We have implemented all our algorithms in Python and we apply them both with the A- and with the D-criterion Ψ . As in [38] and in all other practically feasible optimal experimental design implementations we are aware of, we choose the design space X to be a large but finite set. As a consequence, we can – and do – solve the occurring violator problems (1.6) by enumeration. In order to solve the convex discretized design problems (1.5), in turn, we use the sequential quadratic programming solver [28, 29].

4.1 An application with a stationary model

In our first application example, we consider the chlorination of benzene in a continuously fed and stirred tank reactor. As explained in [34], this process can be described by algebraic system equations of the form

$$g(s, x, \theta) = 0, \tag{4.1}$$

where the map $g: \mathcal{S} \times \mathcal{X} \times \Theta \to \mathbb{R}^4$ is defined as

$$g_1(s, x, \theta) := F_f - s_1 s_4 - \theta_1 \frac{s_1 V}{d(s)}$$
(4.2)

$$g_2(s, x, \theta) := -s_2 s_4 + \theta_1 \frac{s_1 V}{d(s)} - \theta_2 \frac{s_2 V}{d(s)}$$
(4.3)

$$g_3(s, x, \theta) := -s_3 s_4 + \theta_2 \frac{s_2 V}{d(s)}$$
(4.4)

$$g_4(s, x, \theta) := s_1 + s_2 + s_3 - 1 \tag{4.5}$$

and where $d(s) := v_A s_1 + v_B s_2 + v_C s_3$ with v_A, v_B, v_C being the molar volumes of A, B, Cfrom [34]. In these equations, $s = (s_1, \ldots, s_4) := (l_A, l_B, l_C, F_o) \in \mathcal{S} := [0, 1]^3 \times [60, 70]$ describes the state of the system through the molar fractions l_A, l_B, l_C of the components A, B, C in the tank and through the total molar outlet stream F_o from the tank. Additionally, the relevant input quantities

$$x := (F_f, V) \in \mathcal{X} := [60, 70] \times [10, 20] \tag{4.6}$$

of the system are given by the total molar feed stream F_f into the tank and by the mixture's volume V in the tank. And finally, the model parameters $\theta := (k_1, k_2) \in \Theta$ are the reaction rate constants for the two kinetic reactions taking place in the tank reactor.

What we are interested in here is to predict the molar composition in the tank reactor as a function of the aforementioned input quantities x and model parameters θ . So, the output quantity we are interested in here is $y = h(s) := (s_1, s_2, s_3) \in \mathcal{Y} := \mathbb{R}^3$ and the prediction model $f : \mathcal{X} \times \Theta \to \mathcal{Y}$ of interest is given by

$$f(x,\theta) := h(s(x,\theta)), \tag{4.7}$$

where $s(x,\theta)$ for every given $(x,\theta) \in \mathcal{X} \times \Theta$ is the solution to the system equation (4.1). As the design space X, we choose the finite subset

$$X := \{60, 60.1, 60.2, \dots, 70\} \times \{10, 10.1, 10.2, \dots, 20\}$$

$$(4.8)$$

of \mathcal{X} consisting of 10 201 design points (candidate experiments). And as the reference parameter value $\overline{\theta}$, we choose the value $\overline{\theta} := (0.4, 0.0555)$ from [34].

Table 1: Values of the A-criterion and the D-criterion at the different designs ξ^* , ξ^{fact} , ξ^{rand} from (4.10) and (4.11).

	A-criterion Ψ_1	D-criterion Ψ_0
$\Psi(\xi^*)$	2.2630	-0.6873
$\Psi(\xi^{ m fact})$	2.4974	-0.0381
$\Psi(\xi^{\mathrm{rand}})$	2.5178	-0.0085

Table 2: Comparison of our algorithms with exchange and without exchange with the vertexdirection algorithm for the stationary example with the D-criterion $\Psi = \Psi_0$.

	With exchange	Without exchange	Vertex-direction
Criterion value $\Psi(\xi^*)$	-0.6873	-0.6873	-0.6863
Iterations	1	1	450
Approximation error bound	0.0	0.0	0.0010
Support points	1	1	4
Computation time (in s)	0.5397	0.5070	36.39

After having specified the prediction model f along with the design space X and the reference parameter $\overline{\theta}$, we can now turn to solving the corresponding locally optimal design problem (1.4). In order to do so, we use our strict algorithms with and without exchange. Specifically, we apply Algorithm 3.5 and Algorithm 3.10 with the initial discretization

$$X^{0} := \{ (60, 10), (60, 20), (70, 10), (70, 10) \}$$

$$(4.9)$$

consisting of the 4 corner points of the design space X, and with optimality tolerances $\varepsilon := 10^{-4}$ and $\overline{\delta}_k = 0 = \underline{\delta}_k$.

With these settings, our Algorithms 3.5 and 3.10 terminate already after 1 iteration with an ε -optimal design ξ^* , namely the point measure

$$\xi^* := \delta_{x^*}$$
 with $x^* := (60, 20).$ (4.10)

As is to be expected, the objective value $\Psi(\xi^*)$ at the thus computed ε -optimal design is significantly better than the objective values $\Psi(\xi^{\text{fact}})$ and $\Psi(\xi^{\text{rand}})$ at the factorial design and the random design

$$\xi^{\text{fact}} = \frac{1}{4} \sum_{x \in X^{\text{fact}}} \delta_x \quad \text{and} \quad \xi^{\text{rand}} = \frac{1}{4} \sum_{x \in X^{\text{rand}}} \delta_x \quad (4.11)$$

with $X^{\text{fact}} := X^0$ and $X^{\text{rand}} := \{(62.5, 12.7), (66.2, 15.1), (68.9, 18.5), (63.2, 16.4)\}$, respectively. See Table 1. Additionally, our algorithms need substantially fewer iterations and computation time than the vertex-direction algorithm from [9, 37]. And moreover, they achieve a better objective function value at termination and terminate at a design with fewer support points. See Table 2.

4.2 An application with a dynamic model

In our second application example, we consider the Williams-Otto process which connects a continuously stirred tank reactor with a decanter and a distillation column. As explained in [30], this process can be described by differential system equations of the form

$$\dot{s}(t) = g(s(t), x, \theta)$$
 and $s(0) = s_0,$ (4.12)

where $g: \mathcal{S} \times X \times \Theta \to \mathbb{R}^6$ is defined as

$$g_1(s, x, \theta) := F_{fA} + \left((1 - \eta)\mu - \mu \right) \frac{s_1}{d(s)} - k_{10}(T, \theta) \frac{s_1 s_2}{d(s)}$$
(4.13)

$$g_2(s, x, \theta) := F_{fB} + \left((1 - \eta)\mu - \mu \right) \frac{s_2}{d(s)} - k_{10}(T, \theta) \frac{s_1 s_2}{d(s)} - k_{20}(T, \theta) \frac{s_2 s_3}{d(s)}$$
(4.14)

$$g_3(s,x,\theta) := \left((1-\eta)\mu - \mu \right) \frac{s_3}{d(s)} + 2k_{10}(T,\theta) \frac{s_1s_2}{d(s)} - 2k_{20}(T,\theta) \frac{s_2s_3}{d(s)} - k_{30}(T,\theta) \frac{s_3s_5}{d(s)}$$
(4.15)

$$g_4(s, x, \theta) := \left((1 - \eta)\mu - \mu \right) \frac{s_4}{d(s)} + 2k_{20}(T, \theta) \frac{s_2 s_3}{d(s)}$$
(4.16)

$$g_5(s, x, \theta) := 0.1(1 - \eta)\mu \frac{s_4}{d(s)} - \mu \frac{s_5}{d(s)} + k_{20}(T, \theta) \frac{s_2 s_3}{d(s)} - 0.5k_{30}(T, \theta) \frac{s_3 s_5}{d(s)}$$
(4.17)

$$g_6(s, x, \theta) := -\mu \frac{s_6}{d(s)} + 1.5k_{30}(T, \theta) \frac{s_3 s_5}{d(s)}$$
(4.18)

and where $d(s) := s_1 + \cdots + s_6$ and $k_{i0}(T, \theta) := a_i \exp(-b_i/T)$ for $i \in \{1, 2, 3\}$. In these equations, $s = (s_1, \ldots, s_6) := (m_A, m_B, m_C, m_P, m_E, m_G) \in \mathcal{S} := [0, \infty)^6$ describes the state of the system through the masses m_A, \ldots, m_G of the components A, \ldots, G in the tank. We set the initial masses to

$$s_0 = (m_A^0, \dots, m_G^0) = (10, 1, 0, 0, 0, 0).$$
 (4.19)

and the values $F_{fA} = 10$, $\mu = 129.5$ and $\eta = 0.2$. Additionally, the relevant input quantities

$$x := (F_{fB}, T, t_{meas}) \in \mathcal{X} := [20, 23] \times [650, 660] \times [1, 20]$$
(4.20)

of the system are given by the mass feed stream F_{fB} of component B into the tank, by the temperature T in the tank, and by the measurement time t_{meas} . And finally, the model parameters $\theta := (a_1, b_1, a_2, b_2, a_3, b_3) \in \Theta$ are the parameters of the reaction rate constants k_{10}, k_{20}, k_{30} for the three kinetic reactions taking place in the tank reactor.

What we are interested in here is to predict the masses m_P, m_E, m_G of the target, side, and waste products in the tank reactor at time t_{meas} as a function of the aforementioned input quantities x and model parameters θ . So, the output quantity we are interested in here is $y = h(s) := (s_4, s_5, s_6) \in \mathcal{Y} := \mathbb{R}^3$ and the prediction model $f : \mathcal{X} \times \Theta \to \mathcal{Y}$ of interest is given by

$$f(x,\theta) := h(s(t_{meas}, s_0, x, \theta)), \tag{4.21}$$

where $s(\cdot, s_0, x, \theta) : [0, 20] \to \mathbb{R}^6$ for every given initial state s_0 and every $(x, \theta) \in \mathcal{X} \times \Theta$ is the solution to the system equations (4.12). As the design space X, we choose the finite subset of \mathcal{X} consisting of 808 020 design points (candidate experiments) obtained by discretizing the ranges [20, 23] and [650, 660] with 201 equidistant points each, and the time range [1, 20] with 20 equidistant points. And as the reference parameter value $\overline{\theta}$, we choose the value $\theta :=$ $(a_1, b_1, a_2, b_2, a_3, b_3)$ from (20) in [30].

After having specified the prediction model f along with the design space X and the reference parameter $\overline{\theta}$, we can now turn to solving the corresponding locally optimal design problem (1.4). In order to do so, we use our strict algorithms with and without exchange. Specifically, we apply Algorithm 3.5 and Algorithm 3.10 with the initial discretization

$$X^{0} := \{20, 23\} \times \{550, 600\} \times \{1, 2, \dots, 20\}$$

$$(4.22)$$

consisting of 80 points, and with optimality tolerances $\varepsilon := 10^{-4}$ and $\overline{\delta}_k = 0 = \underline{\delta}_k$.

With these settings, our Algorithms 3.5 and 3.10 terminate already after 3 iterations with the ε -optimal designs ξ^* specified in Table 3. As is to be expected, the objective value $\Psi(\xi^*)$ at

	D-criterion	
Weights w_i	Support points x_i	Weights w_i
0.12	(22.925, 592.5, 16)	0.12
0.12	(22.925, 592.5, 16)	0.12
0.12	(22.925, 592.5, 16)	0.12
0.12	(22.925, 592.5, 16)	0.12
0.12	(22.925, 592.5, 16)	0.12
0.12	(22.925, 592.5, 16)	0.12
0.12	(22.925, 592.5, 16)	0.12
	Weights w_i 0.12 0.12 0.12 0.12 0.12 0.12 0.12 0.12 0.12 0.12 0.12 0.12 0.12	D-criterionWeights w_i Support points x_i 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$ 0.12 $(22.925, 592.5, 16)$

Table 3: Approximately optimal designs ξ^* for the A- and D-criterion computed by the algorithm with exchange.

Table 4: Values of the A-criterion and the D-criterion at the different designs ξ^* , ξ^{fact} , ξ^{rand} from Table 3 and (4.23).

	A-criterion Ψ_1	D-criterion Ψ_0
$\Psi(\xi^*)$	94.08	$0.4213 \cdot 10^{9}$
$\Psi(\xi^{ m fact})$	105.20	$4.9159\cdot 10^9$
$\Psi(\xi^{\mathrm{rand}})$	108.90	$123.7325 \cdot 10^9$

the thus computed ε -optimal design is significantly better than the objective values $\Psi(\xi^{\text{fact}})$ and $\Psi(\xi^{\text{rand}})$ at the factorial design and the random design

$$\xi^{\text{fact}} = \frac{1}{80} \sum_{x \in X^{\text{fact}}} \delta_x \quad \text{and} \quad \xi^{\text{rand}} = \frac{1}{8} \sum_{x \in X^{\text{rand}}} \delta_x$$
(4.23)

with $X^{\text{fact}} := X^0$ and with

$$X^{\text{rand}} := \{ (22.925, 592.5, 16), (20.36, 553.75, 16), (20.96, 550.75, 15), (22.22, 575.5, 6), \\ (22.625, 565.25, 12), (20.675, 563.5, 12), (20.705, 552.0, 8), (20.075, 582.0, 14) \}$$

respectively. See Table 4. Additionally, our algorithms need substantially fewer iterations and computation time than the vertex-direction algorithm from [9, 37]. And moreover, they achieve a better objective function value. See Table 5.

Acknowledgments

We gratefully acknowledge funding from the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) – project number 466397921 – within the Priority Programme "SPP 2331:

Table 5: Comparison of our algorithms with exchange and without exchange with the vertexdirection algorithm for the dynamic example with the A-criterion $\Psi = \Psi_1$.

	With exchange	Without exchange	Vertex-direction
Criterion value $\Psi(\xi^*)$	94.0759	94.0759	-0.6863
Iterations	3	3	450
Approximation error bound	0.0010	0.0010	0.0010
Support points	7	7	4
Computation time (in s)	14.8141	32.9620	36.39

Machine Learning in Chemical Engineering" and within the research unit "FOR 5359: Deep Learning on Sparse Chemical Process Data".

References

- [1] H. Amann, J. Escher: Analysis I, II, III. Birkhäuser (2005, 2008, 2009)
- [2] A.C. Atkinson, A.N. Donev, R.D. Tobias: Optimum experimental design, with SAS. Oxford University Press (2007)
- [3] C. Atwood: Sequences converging to D-optimal designs of experiments. Ann. Statist. 1 (1973), 342-352
- [4] R. Bhatia: Matrix analysis. Springer (1997)
- [5] J.W. Blankenship, J.E. Falk: Infinitely constrained optimization problems. J. Optim. Th. Appl. 19 (1976), 261-281
- [6] D. Böhning: A vertex-exchange method in D-optimal design theory. Metrika 33 (1986), 337-347
- [7] H. Chernoff: Locally optimal designs for estimating parameters. Ann. Math. Stat. 24 (1953), 586-602
- [8] N. Dunford, J.T. Schwartz: Linear operators I-III. Wiley (1958, 1963, 1971)
- [9] V.V. Fedorov: Theory of optimal experiments. Academic Press (1972)
- [10] V.V. Fedorov, S.L. Leonov: Optimal design for nonlinear response models. Chapman & Hall (2014)
- [11] D. Garber, E. Hazan: Faster rates for the Frank-Wolfe method over strongly-convex sets. Proceedings of the 32nd International Conference on Machine Learning 37 (2015), 541-549
- [12] D.A. Harville: Matrix algebra from a statistician's perspective. Springer (1997)
- [13] M. Jaggi: Revisiting Frank-Wolfe: projection-free sparse convex optimization. Proceedings of the 30th International Conference on Machine Learning 28 (2013), 427-435
- [14] J. Jahn: Introduction to the theory of nonlinear optimization. 3rd edition, Springer (2007)
- [15] J. Kiefer, J. Wolfowitz: Optimum designs in regression problems. Ann. Math. Stat. 30 (1959), 271-294
- [16] J. Kiefer, J. Wolfowitz: The equivalence of two extremum problems. Canad. J. Math. 12 (1960), 363-366
- [17] J. Kiefer: General equivalence theory for optimum designs (approximate theory). Ann. Stat. 2 (1974), 849-879
- [18] S. Lacoste-Julien, M. Jaggi: On the global linear convergence of Frank-Wolfe optimization variants. Advances in Neural Information Processing Systems 28 (2015), 496-504
- [19] J.R. Magnus, H. Neudecker: Matrix differential calculus with applications in statistics and econometrics. 3rd edition, Wiley (2007)
- [20] K.R. Parthasarathy: Probability measures on metric spaces. Academic Press (1967)
- [21] J. Peña, D. Rodríguez: Polytope conditioning and linear convergence of the Frank-Wolfe algorithm. Math. Oper. Res. 44 (2018), 1-18
- [22] L. Pronzato, A. Pázman: Design of experiments in nonlinear models. Asymptotic normality, optimality criteria and small-sample properties. Springer (2013)
- [23] B.N. Pshenichnyi: Necessary conditions for an extremum. Marcel Dekker (1971)
- [24] F. Pukelsheim, S. Rieder: Efficient rounding of approximate designs. Biometrika 79 (1992), 763-770
- [25] F. Pukelsheim: Optimal design of experiments. SIAM Classics of Applied Mathematics (2006)
- [26] R.T. Rockafellar: Convex analysis. Princeton University Press (1970)
- [27] W. Rudin: Functional analysis. 2nd edition, McGraw-Hill (1991)
- [28] K. Schittkowski: A robust implementation of a sequential quadratic programming algorithm with successive error restoration. Opt. Lett. 5 (2011), 283–296

- [29] K. Schittkowski: NLPQLP: A Fortran implementation of a sequential quadratic programming algorithm with distributed non-monotone line search. User's guide, Version 4.2 (2014)
- [30] J. Schmid, K. Teichert, M. Chioua, T. Schindler, M. Bortz: Industry-driven rapid prototyping for comparing nonlinear control schemes in Pyomo. Chem. Ing. Tech. 92 (2020), 2016-2027
- [31] G.A.F. Seber, C.J. Wild: Nonlinear regression. Wiley (1989)
- [32] S.D. Silvey, D.H. Titterington, B. Torsney: An algorithm for optimal designs on a design space. Comm. Statist. Theory Methods 14 (1978), 1379-1389
- [33] S.D. Silvey: Optimal design. An introduction to the theory for parameter estimation. Chapman & Hall (1980)
- [34] M.D. Stuber, P.I. Barton: Semi-infinite optimization with implicit functions. Ind. Eng. Chem. Res. 54 (2015), 307–317
- [35] V.M. Tikhomirov: ε -entropy and ε -capacity of sets in functional spaces. In: A.N. Shiryayev (editor): Selected Works of A.N. Kolmogorov. Volume III: Information theory and the theory of algorithms. Springer (1993), 86-170
- [36] J.-P. Vial: Strong and weak convexity of sets and functions. Mathematics of Operations Research 8 (1983), 231–259
- [37] H.P. Wynn: The sequential generation of D-Optimal experimental designs. Ann. Math. Statist. 41 (1970), 1655-1664
- [38] M. Yang, S. Biedermann, E. Tang: On optimal designs for nonlinear models: a general and efficient algorithm. J. Am. Stat. Assoc. 108 (2013), 1411-1420
- [39] Y. Yu: Monotonic convergence of a general algorithm for computing optimal designs. The Annals of Statistics 38 (2010), 1593
- [40] Y. Yu: D-optimal designs via a cocktail algorithm. Stat. Comp. 21 (2011), 475-481
- [41] E. Zeidler: Non-linear functional analysis and its applications I-IV. Springer (1985, 1990, 1985, 1988)
- [42] G.M. Ziegler: Lectures on polytopes. Corrected and updated printing, Springer (2007)