# Time-series-analysis-based detection of critical transitions in real-world non-autonomous systems

Klaus Lehnertz $1, 2, 3$ 

1)*Department of Epileptology, University of Bonn Medical Centre, Venusberg Campus 1, 53127 Bonn, Germany* 2)*Helmholtz Institute for Radiation and Nuclear Physics, University of Bonn, Nussallee 14–16, 53115 Bonn, Germany* 3)*Interdisciplinary Center for Complex Systems, University of Bonn, Brühler Straße 7, 53175 Bonn, Germany*

(\*Electronic mail: [klaus.lehnertz@ukbonn.de\)](mailto:klaus.lehnertz@ukbonn.de)

(Dated: 11 June 2024)

Real-world non-autonomous systems are open, out-of-equilibrium systems that evolve in and are driven by temporally varying environments. Such systems can show multiple timescale and transient dynamics together with transitions to very different and, at times, even disastrous dynamical regimes. Since such critical transitions disrupt the systems' intended or desired functionality, it is crucial to understand the underlying mechanisms, to identify precursors of such transitions and to reliably detect them in time series of suitable system observables to enable forecasts. This review critically assesses the various steps of investigation involved in time-series-analysis-based detection of critical transitions in real-world non-autonomous systems: from the data recording to evaluating the reliability of offline and online detections. It will highlight pros and cons to stimulate further developments, which would be necessary to advance understanding and forecasting nonlinear behavior such as critical transitions in complex systems.

Critical transitions are apparent sudden shifts in the states of complex dynamical systems and are often followed by extreme events that may entail loss of life and/or materials. Reliable detection and forecasting of critical transitions would allow for developing adaptation and/or mitigation strategies, which is thus of utmost importance in many scientific fields. Although we still lack a general understanding of the mechanisms underlying critical transitions, there is plenty of observational data which might qualify for a time-series-analysis-based detection of transitions in real-world non-autonomous systems. Successful detection and forecasting of critical transitions requires not only knowledge of the various concepts and methodologies involved, but also an assessment of possible sources of error. This is the subject of the present review.

## I. INTRODUCTION

Complex dynamical systems, ranging from the brain and the heart to ecosystems, financial markets and the earth and climate systems can show sudden transitions to very different and, at times, even disastrous dynamical regimes $1-\dot{2}0$  $1-\dot{2}0$ . Typical examples include epileptic seizures and cardiac arrest, population extinctions, market crashes, mass panics, wars, earthquakes, tsunamis, extreme weather events, rogue waves, or large-scale blackouts in power supply networks. Observations and model simulations indicate that such critical transitions often occur when changing conditions pass a critical or tipping  $point^{21-24}$  $point^{21-24}$  $point^{21-24}$ . Both reliable detection and forecasting of critical transitions are of utmost importance in many scientific fields. If critical catastrophic transitions occur in an unexpected way, they often do not allow for developing adaptation and/or mitigation strategies. It is thus crucial to understand the mechanisms underlying critical transitions, to identify early-warning indicators of such transitions, and to reliably detect them in time series of suitable system observables to enable forecasts.

The real-world systems referred to above can be consid-ered as non-autonomous dynamical systems<sup>[25,](#page-7-4)[26](#page-7-5)</sup>, for which the evolution of the state variable  $\mathbf{x} \in \mathbb{R}^d$  is governed by

$$
\frac{d\mathbf{x}(t)}{dt} = f(t, \mathbf{x}(t), \beta(t)), \qquad \frac{\partial f}{\partial t} \neq 0.
$$
 (1)

Such systems are usually subject to time-dependent forcing as well as to additive and/or multiplicative dynamical noise, which – together with the various possible transition mechanisms (bifurcation-, noise- , rate-, or shock-induced tip- $\text{ping}^{21-24,27}$  $\text{ping}^{21-24,27}$  $\text{ping}^{21-24,27}$  $\text{ping}^{21-24,27}$ ) – poses particular challenges for a time-seriesanalysis-based detection of critical transitions.

The last years have seen a rapid increase of data- and theory-driven approaches that aim at gaining deeper insights into non-autonomous dynamics<sup>[28](#page-7-7)</sup>, into the mechanisms underlying critical transitions and at their detection and forecasting. Among others, methods based on nonlinear time-series analysis<sup>[29](#page-7-8)</sup>, complex network theory<sup>[30,](#page-8-0)[31](#page-8-1)</sup>, or symbolic time-series representation<sup>[32](#page-8-2)</sup> have been demonstrated to be useful for specific systems, however, the general applicability of these methods remains an issue to be investigated. Importantly, and with an eye on field applications, it is crucial to estimate the reliability and significance of indicators for critical transitions.

In this review, we summarize recent conceptual and methodological developments that aim at a time-seriesanalysis-based investigation of critical transitions in realworld non-autonomous systems. We critically assess the various steps of investigation – from the experimental observation (Sect. [II\)](#page-1-0) via means to cope with non-stationarity (Sect. [III\)](#page-1-1) and time-series analyses (Sect. [IV\)](#page-2-0) to the offline detection of transitions (Sect. [V\)](#page-2-1) and (statistical) means to evaluate their reliability (Sect. [VI\)](#page-4-0) – and highlight areas that are under active investigation and that promise to provide new insights. Eventually, we briefly discuss possibilities for time-series-analysisbased online detections of critical transitions that could contribute to further increase reliability of forecasts.

# <span id="page-1-0"></span>II. EXPERIMENTAL OBSERVATION OF THE DYNAMICS OF REAL-WORLD NON-AUTONOMOUS SYSTEMS

For many real-world non-autonomous dynamical systems the governing equations of motion are unknown, and quite often one lacks detailed knowledge about the mechanisms that may underlie transitions. In such cases, one typically resorts to the analysis of time series of suitable observables  ${s(t) = s(\mathbf{x}(t))}$  with the measurement function  $s : \mathbb{R}^d \to \mathbb{R}$  and the discretized time  $t = N\Delta t$  (with the number of data points *N*, and  $\Delta t$  is the sampling interval). This approach is, however, associated with some difficulties that one should be aware of in order to avoid misinterpretations.

Frequently, one has access to a few (or even to only one) dynamical variables, and one should consider in advance whether these are "good" observables $33-35$  $33-35$ .

Lacking detailed knowledge about the system under investigation, one is faced with the problem of how to sufficiently sample the system dynamics in time and space. This requires choosing a priori various recording parameters such as number and placement of sensors, the sampling interval ∆*t*, filter and amplifier settings, and precision of analogue-to-digital conversion. The well-known Nyquist–Shannon sampling theorem[36–](#page-8-5)[38](#page-8-6) may have only limited significance, particularly if the full range of dynamical behaviors and their temporal and spatial scales are not known a priori. If the system contains nonlinearities, band-limiting possibly chaotic dynamics using inappropriate filters may lead to severe misinterpretations<sup>[29](#page-7-8)</sup>. Lacking detailed knowledge about the system's spatial scales and about how – if at all – to decompose it into subsystems, one typically resorts to a grid-like arrangement of sensors (Fig[.1\)](#page-1-2). In case of complex coupling topologies between subsystems, such a placement can lead to severe misinterpreta- $tions<sup>39,40</sup>$  $tions<sup>39,40</sup>$  $tions<sup>39,40</sup>$  $tions<sup>39,40</sup>$ .

A widely used approach to study a system's dynamics is probing, i.e., investigating the system's response (relaxation dynamics) to small perturbations. Such an approach, however, might not be feasible for any system and more importantly, it involves a high level of risk of inducing a transition to a new state with possibly undesirable properties – you may not know in advance how big a small perturbation actually is. From the point-of-view of time-series analysis, relaxation dynamics are typically reflected in noisy, short-lasting transient signals that require dedicated denoising techniques<sup>[41](#page-8-9)</sup> or multiple realizations[42](#page-8-10)[–50](#page-8-11) that may also be used to enhance time resolution by replacing the temporal average with an ensemble average. The latter, however, implicitly assumes stationarity of the system (at least on the considered timescale) and comparability of relaxation dynamics and of transitions.

An alternative to probing is observing a system over timescales long enough to capture all relevant aspects of



<span id="page-1-2"></span>FIG. 1. Sampling the dynamics of a spatially extended system – for which the actual division into subsystems (black dotted lines) is not known a priori – is often performed with a grid-like arrangement of sensors (blue circles). An associated problem is spatial oversampling whereby several sensors record the dynamics of a given subsystem. Such redundant and mostly noisy information might be hard to distinguish from synchronization or spreading phenomena. Another problem is related to sensors that were happened to be placed such that they capture the dynamics of neighboring subsystems. Disentangling superimposed dynamics is hard without having the necessary a priori information about the subsystems.

its dynamics (e.g. "normal" dynamics, critical and noncritical transitions). For real-world non-autonomous dynamical systems, however, this approach requires dedicated methods to cope with the inherently nonstationary dynamics (see Sect. [III\)](#page-1-1), with possible very long transients<sup>[12,](#page-7-9)[51–](#page-8-12)[53](#page-8-13)</sup>, or even with non-convergent (non-asymptotic) behaviors  $54,55$  $54,55$ . It should be determined in advance whether continuous data collection is required or whether collecting snippets of data suffices for an adequate characterization of the system's dynamics. Likewise, it is advisable to keep the aforementioned recording parameters constant throughout the observation time as these could easily represent time-dependent confounders.

## <span id="page-1-1"></span>III. COPING WITH NON-STATIONARITY

Non-autonomous dynamical systems are non-stationary, non-ergodic systems that do not obey Birkhoff's ergodic theorem equaling time and ensemble averages  $56,57$  $56,57$ . This property is usually regarded as an obstacle as it poses special challenges for time-series-analysis methods.

A (stochastic) process is called strictly (or strongly) stationary if the distribution of its states over an ensemble of realiza-tions of that process does not depend on time<sup>[58](#page-8-18)</sup>. This implies constancy of all statistical moments and all joint statistical moments. Within the scope of field applications, stationarity of a system can only be evaluated with respect to the observation time. The vast majority of time-series-analysis methods (see Sect. [IV\)](#page-2-0) require the system under investigation to be at least approximately stationary (constancy of first- and secondorder statistical moments) in order to allow for a robust and reliable characterization.

The most common way of dealing with a nonstationary system is to cut the time series into successive (non-)overlapping segments (or windows<sup>[59](#page-8-19)</sup>) during which the system's dynamics can be regarded as approximately stationary (sliding or rolling or moving-window analysis) $28,60-69$  $28,60-69$  $28,60-69$ . A characterizing metric is then calculated for each data window by employing some time-series-analysis method (see Fig. [2](#page-3-0) and Sect. [IV\)](#page-2-0).

Instead of identifying (approximately) stationary data segments, one might also consider non-stationarity as an interesting aspect of the dynamics. Methods that allow tracing non-stationarity are based e.g. on the concept of overembed- $\text{ding}^{70-72}$  $\text{ding}^{70-72}$  $\text{ding}^{70-72}$  that treats time-varying control parameters as independent dynamical variables. Other methods make use of recurrence quantification analysis $73-79$  $73-79$ , of state-space-based cross-predictions<sup>[80](#page-8-26)</sup>, or of symbolic data compression<sup>[81](#page-8-27)</sup>, to name just a few.

Regardless of the perspective taken, all approaches require some statistical test<sup>[58](#page-8-18)[,82](#page-8-28)[,83](#page-8-29)</sup> to assess the quality of differentiation/characterization.

## <span id="page-2-0"></span>IV. TIME-SERIES-ANALYSIS

Time-series analysis comprises methods for analyzing a single or multiple sequences of observations collected over a certain period of time in order to extract meaningful statistics and other characteristics of the data. A plethora of linear and nonlinear time-series-analysis methods is available that can be used to detect and characterize – in a data-driven way – differ-ent aspects and properties of a system's dynamics<sup>[29,](#page-7-8)[31](#page-8-1)[,84](#page-8-30)[–112](#page-9-0)</sup>. Some methods may also be used for forecasting (or anticipation) purposes.

Analysis methods can be classified into two main groups.

With univariate methods, the above-mentioned applications are limited to a single time series. Exemplary applications include estimating statistical moments (e.g., mean, standard deviation, skewness, kurtosis), characteristics of the autocorrelation function (e.g., decay time) or the power spectrum (e.g., spectral power in some frequency band), Kramers-Moyal coefficients (e.g., drift and diffusion), or state-spacebased quantities such as dimensions, entropies, stability indicators like Lyapunov exponents, or characteristics derived from recurrence quantification analysis. The latter quantities require an appropriate reconstruction of the dynamics in statespace from a single (or only a few) time series $113-122$  $113-122$ .

With bivariate (or, in general, multivariate) methods, investigations mostly concentrate on characterizing interdependences between pairs (or, in general, n-tuples) of time series. Exemplary applications include estimating characteristics of the cross-correlation function (e.g., interaction delay) or the cross-spectrum (e.g., coherence function), properties of interactions (strength, direction, functional form) and of synchronization phenomena, or characteristics derived from network theory.

Since there is no one-fits-all time-series-analysis method for all types of data, the choice of a specific method depends on the system under investigation and on the research question being asked. In addition, since one is interested in the physical mechanism(s) underlying the observed dynamics (or properties thereof), the choice of the method needs to be justified by a hypothesis about the appropriate data model. Given that almost all time-series analysis methods reduce the information content of some time series to some characteristic number or metric, interpretability of the latter is only possible if it has a specific meaning within the model framework. Only in that case does the reduced information increase our knowledge about the system under investigation. If the data to be analyzed does not pertain to the appropriate model class, the chosen metric may not make much sense, even if its numerical value can be calculated for the given time series using a numerical algorithm.

For the majority of time-series-analysis methods, a reduction of the information content of some time series involves time-, space-, or ensemble-averages or combinations thereof in order to achieve a sufficient accuracy and robustness against noise contaminations. It is often assumed that the more data enters some algorithm the higher is the method's accuracy and thus the reliability of the chosen metric. However, many timeseries-analysis methods, or rather the concepts/theories from which they originate, (implicitly) assume the system under investigation to be stationary. As already mentioned above, investigations of non-autonomous dynamical systems often rely on a moving-window analysis to account for non-stationarity. A shorter analysis window is usually associated with approximate stationarity, but one needs to take into account that the decreased amount of data entering some analysis method may decrease the reliability of a characterizing metric. Thus, the choice of a window length  $N_w \ll N$  is often a compromise between the required statistical accuracy for the estimation of a metric and approximate stationarity within a window length.

Calculating a metric using a time-series-analysis method is usually accompanied by the choice of algorithmic parameters. Depending on the research question, algorithmic parameters are often tuned to achieve an optimum characterization of the system's dynamics. For an investigation of long-term observations and using a moving-window analysis, however, tuning parameters for each window might not be advisable. The resulting (time-dependent) sequence of a metric's numerical values could then simply reflect this tuning-per-window which can lead to severe misinterpretations. It might thus be advisable to fix all necessary pre-processing steps and keep a priori best-chosen algorithmic parameters constant.

## <span id="page-2-1"></span>V. DETECTING TRANSITIONS

A number of metrics have been proposed in recent years to detect critical transitions based on bifurcations and the associated phenomenon of critical slowing down, i.e., an increas-ingly slow recovery from small perturbations<sup>[123](#page-9-3)[–127](#page-9-4)</sup>. With approaching the bifurcation (tipping point), the time needed to recover from perturbations becomes longer and hence the system dynamics becomes more correlated with its past, leading to an increase in the lag-1 autocorrelation and to spectral



<span id="page-3-0"></span>FIG. 2. A frequently used approach to investigate the dynamics of a non-stationary system is to estimate a characterizing metric *m* (cf. Sect. [IV\)](#page-2-0) using the data of successive segments (or windows; marked in gray) of time series of system observables. During each segment, the system is assumed to be (approximately) stationary (moving-window analysis). The resulting time-dependent sequence  $m(t_w)$ , where  $t_w$  denotes the sequence's temporal resolution, is then used to detect transitions as well as to identify indicators for the latter.

reddening<sup>[128](#page-9-5)</sup>. Since perturbations accumulate, one observes an increase in the size of the fluctuations<sup>[129](#page-9-6)</sup> as assessed with variance or other higher-order statistical moments. These classic statistical indicators have been used to investigate critical slowing in various contexts $130-142$  $130-142$  and were claimed to be generic. They continue, however, to be critically discussed from various perspectives  $143-169$  $143-169$ .

The quest for more robust and possibly more widely applicable indicators that may be sensitive to critical transitions other than those related to bifurcations – such as bound-ary crisis<sup>[170](#page-10-3)[,171](#page-10-4)</sup>, blowout bifurcations<sup>[172,](#page-10-5)[173](#page-10-6)</sup>, saddle escape<sup>[174](#page-10-7)</sup>, oscillation death<sup>[175](#page-10-8)[,176](#page-10-9)</sup>, or explosive synchronization<sup>[177](#page-10-10)[,178](#page-10-11)</sup> – has led to the development of metrics that are based on other time-series-analysis concepts. Among others, these include synchronization<sup>[179–](#page-10-12)[182](#page-10-13)</sup>, symbolic dynamics<sup>[183](#page-10-14)[–185](#page-10-15)</sup>, complex networks<sup>[18,](#page-7-10)[186–](#page-10-16)[190](#page-11-0)</sup>, algebraic topology<sup>[191–](#page-11-1)[193](#page-11-2)</sup>, au-toregressive modeling<sup>[194,](#page-11-3)[195](#page-11-4)</sup>, entropy concepts<sup>[196–](#page-11-5)[200](#page-11-6)</sup>, recon-struction of Jacobian matrices<sup>[201](#page-11-7)</sup>, (nonstationary) dynamical modeling<sup>[202](#page-11-8)[–206](#page-11-9)</sup>, or the Kramers-Moyal expansion<sup>[106,](#page-9-8)[207–](#page-11-10)[210](#page-11-11)</sup>.

All these time-series-analysis techniques have in common that, when investigating real-world non-autonomous dynamical systems, moving-window analyses of some system observable(s) yield time-dependent sequence(s) of a characterizing metric  $\{m(t_w), m(2t_w), m(3t_w), \ldots\}$ . These sequences have a temporal resolution  $t_w$  that is given by the window length  $N_w$ and can subsequently be used to detect transitions as well as to identify indicators for the latter.

There are two major techniques in use to detect transitions, namely threshold crossing and change point detection (see Fig[.3\)](#page-4-1). The latter is sometime also referred to as anomaly detection. Both techniques are often employed as offline methods that retrospectively detect changes when the data has already been gathered and using information on transitions that have taken place in the past. When employed as online methods, they aim to detect changes as soon as they occur in a real-time setting. This may be achieved with machine learn-ing techniques<sup>211-[216](#page-11-13)</sup> or Bayesian inference<sup>[209,](#page-11-14)[217](#page-11-15)</sup>.

## Threshold crossing

The onset of a transition is given by the first timepoint  $t_{\text{crit}}$ when the metric *m* exceeds or falls below some pre-defined threshold  $\Theta^{153,218-221}$  $\Theta^{153,218-221}$  $\Theta^{153,218-221}$  $\Theta^{153,218-221}$ . The latter may be defined as the mean plus or minus two standard deviations estimated from preced-ing data (two-sigma rule<sup>[222](#page-11-18)</sup>). Note, however, that in driven non-stationary systems statistical moments of a sequence of some metric may undergo fluctuations on timescales much longer than the one for which the system's dynamics has been regarded as approximately stationary<sup>[223](#page-11-19)</sup> (see Sect. [III\)](#page-1-1). In such a case it might be advisable to replace the fixed threshold by an adaptive one<sup>[224](#page-11-20)</sup>. Since the rather simple threshold-crossing-based criterion might be prone to isolated outliers, one can also consider the onset of a transition as the first timepoint for which multiple consecutive data points  ${m(t_{\text{crit}}), m(t_{\text{crit}} + t_w), m(t_{\text{crit}} + 2t_w), \ldots}$  fulfill the threshold criterion. Indeed, one can expect the number of consecutive data points fulfilling the threshold criterion to increase as the system approaches a critical transition. If assumptions can be made about how a metric changes during a critical transition (e.g. linear increase or decrease), one may eventually establish the presence of trends (e.g., using linear regression) in order



<span id="page-4-1"></span>FIG. 3. Illustration of techniques to detect transitions. With threshold crossing (top), the onset of a transition is related to the first time point *t*crit when a characterizing metric *m* crosses a pre-defined threshold Θ (either from above or from below). With change point detection (bottom), specific points in time (blue dots) are identified where the sequence of metric *m* exhibits a significant change either in its deterministic content or underlying stochastic distribution. The onset of a transition can be related, for example, to the first identified change point.

to further substantiate the evidence of a critical transition.

#### Change point detection

This technique aims to identify specific points in time where the sequence of metric *m* exhibits a significant change either in its deterministic content or underlying stochastic distribution<sup>[225](#page-11-21)[–233](#page-11-22)</sup>. In general, change point detection concerns both detecting whether or not a change has occurred, or whether several changes might have occurred, and identifying the times of any such changes. Depending on the application, this may involve measuring the statistical (dis-)similarity between two windows of data to either side of a purported change point or identifying changes in the mean, variance, au-tocorrelation, or spectral density of the sequence<sup>[230,](#page-11-23)[234](#page-11-24)</sup>. Note that the latter also requires the choice of a suitable and a priori defined window. In addition, the same restrictions apply in the case of driven non-stationary systems as with threshold crossing.

# <span id="page-4-0"></span>VI. TESTING THE RELIABILITY OF OFFLINE **DETECTIONS**

Consider an offline time-series-analysis-based detection of critical transitions in some real-world non-autonomous dynamical system for which we know the exact onset times of critical transitions. The applied analyses techniques are assumed to be sensitive enough to detect and characterize critical transitions, based on prior investigations (e.g., with toy models). We observe additional changes in the temporal sequence of the employed metric that would qualify as indicative of critical transitions, but we know a posteriori that the system has solely undergone transitions to some non-critical states – we refer to these as non-critical transitions. Such a situation can occur, for example, when analyzing brain dynamics and employing time-series-analysis techniques that can not (or only insufficiently) distinguish between a transition to a preseizure state (critical transition) and transitions to behavioral states like sleep or wakefulness. We consider all other changes as false detections.



<span id="page-4-2"></span>FIG. 4. Top: exemplary outcome of an offline detection of the onsets of critical transitions (CT, red). Onsets of non-critical transitions (nCT) are marked black. Detections are labeled with the letter "d". Bottom: the duration of a critical ( $\Delta_{CT}$ , red) and a non-critical ( $\Delta_{nCT}$ , black) transition can be defined as differences between the respective ending and onset times. Onset times are denoted by *t*o; for the critical transition, the ending of the transitory phase coincides with the occurrence of the extreme event at  $t_e$  (note that for  $\Delta_{CT} \rightarrow 0$ , the transition would be classified as abrupt and there are no early warning signs); for the non-critical transition, the ending of the transitory phase coincides with the return of the system to its *normal* dynamics at *t*<sup>r</sup> .

For the (quite typical) detection example shown in the upper part of Figure [4,](#page-4-2) the following interpretations can be made:

- since the method detected only half of the critical transitions, it appears to be not very sensitive;
- given that the method detected two out of three noncritical transitions, it might be more sensitive to the latter type of transitions;
- there are more false than true detections, so the method appears to be not very specific;
- there are two detections that precede the onsets of the critical transitions, however, since one detection coincides with the onset of a non-critical transition the method appears to have only a limited predictive significance;

• since there are three detections that follow the offsets of critical and non-critical transition, one might speculate about the method's capability to detect the offset of such transitions.

This example clearly points to the need to check reliability and quality of offline time-series-analysis-based methods for the detection of critical transitions<sup>[235](#page-12-0)</sup>. For this purpose, various statistical tests can (and should) be applied in order to avoid drawing false conclusions and to avoid wishful thinking.

Tests range from simple to advanced and require knowledge about the occurrence times of (non-)critical transitions (or events) as well as about characteristics of the respective transitory phases that may differ from event to event (in order to simplify things, one could treat false detections as noncritical transitions). Depending on the application, these characteristics include e.g. the durations of transitory phases ( $\Delta_{CT}$ and  $\Delta_{nCT}$ ; see lower part of Figure [4\)](#page-4-2), the maximum deflection from the threshold, or characteristics of a trend function<sup>[236](#page-12-1)</sup>.

#### Distinguishability of non-critical and critical transitory phases

A simple though not very reliable way to assess detection performance of offline methods is to use statistical ap-proaches<sup>[237](#page-12-2)</sup> to verify distinguishability of non-critical and critical transitory phases by comparing the distributions – or moments thereof – of their characteristics (durations, maximum deflections, etc.). The equality of distributions can be tested nonparametrically<sup>[238](#page-12-3)</sup> or rank-based<sup>[239](#page-12-4)</sup>. For Gaussiandistributed data, equality of means and standard deviations can be evaluated with the Student's t-test and the F-test, respectively. For non-Gaussian-distributed data, these are the median test or the Mann-Whitney U test and the Conover squared ranks test. It should be noted, however, that the tests assume that the data were taken independently (from some distribution). This implies no memory, no dynamics, time is not important, and stationarity of the investigated system.

#### Sensitivity analysis

Another simple way to assess detection performance of offline methods is to count the number of correct detections of critical transitions. This approach allows drawing some conclusions about a method's sensitivity but it does say anything about a method's specificity. Sensitivity refers to the probability of a positive test result ("is critical"), conditioned on each detection truly being positive. Specificity refers to the probability of a negative test result ("is non-critical"), conditioned on each detection truly being negative. Also, this approach does not take into account false detections (see below), and one quite often finds studies that report on sensitivity of a detection method only. Note that a detection method can easily be tuned through in-sample optimization to achieve 100 % sensitivity when ignoring its specificity. Lacking relevant information and, more importantly, considering the fact 6

that critical transitions are typically rare events, this simple way is not very robust and largely unsuited for analyses of empirical data.

## ROC analysis

A more robust way to assess detection performance is the Receiver Operating Characteristics (ROC) analysis<sup>[240,](#page-12-5)[241](#page-12-6)</sup>. In addition to counting the number of correct (true positive) and missing (true negative) detections of critical transitions as estimates for sensitivity and specificity, this approach also takes into account false detections. A false positive detection refers to a non-critical transition that was erroneously detected as critical transition (type I error). A false negative detection refers to a critical transition that was erroneously detected as non-critical transition (type II error). One then estimates the method's sensitivity (or the true positive rate; TPR) as well as 1−specificity (or the false positive rate; FPR) at each setting of the threshold value  $\Theta$  to obtain the so called ROC curve<sup>[242](#page-12-7)</sup> (see Fig. [5\)](#page-5-0). In this ROC space, the best possible detection method would yield a point in the upper left corner (or lower right depending on interpretation and change of metric *m*), representing 100 % sensitivity (no false negatives) and 100 % specificity (no false positives). In contrast, a detection method working at random would give a point along the diagonal from the bottom left to the top right corners (regardless of the positive and negative base rates; cf. random guessing).



<span id="page-5-0"></span>FIG. 5. Performance of a detection method can be evaluated on the basis of a receiver operating characteristic (ROC) curve that relates true positive rates to false positive rates. The area under the curve (AUC) can be used to quantify the detection method's performance (an ideal detection method has an AUC of 1).

An often used reduction of the ROC Curve to a single number is calculating the so called area under the ROC curve (AUC). Depending on application, AUC can be defined as the value of the area under the whole curve which yields 1.0 for the best possible detection method and 0.5 for a random de-tection<sup>[180](#page-10-18)</sup>. Alternatively, AUC can be defined as the (absolute) value of the area between the ROC curve and the diagonal which yields values between 0.0 (random detection) and 0.5 (best detection).

High AUC values for various detection methods continue to be reported from different disciplines<sup>[138,](#page-10-19)[153](#page-10-17)[,162,](#page-10-20)[232](#page-11-25)[,243](#page-12-8)[–251](#page-12-9)</sup>. Such values, however, can give a false impression about a method's genuine detection reliability, particularly for imbalanced probability distributions for true and false positive detections, which is the case for critical transitions that are typically rare events. This imbalance can lead to a bias towards a predominant number of detections of non-critical transitions and can render an interpretation of AUC values oversimplistic and even misleading<sup>[180,](#page-10-18)[252–](#page-12-10)[254](#page-12-11)</sup>. Such misinterpretations can be avoided with the help of surrogate-assisted ROC analyses that were introduced in the field of prediction of epileptic  $seizures<sup>255,256</sup>$  $seizures<sup>255,256</sup>$  $seizures<sup>255,256</sup>$  $seizures<sup>255,256</sup>$  in the context of detection of critical transitions (here: detection of a pre-seizure state).

#### Surrogate-guided ROC analysis

A simple and straightforward ansatz consists of comparing a method's detection performance against the one of a random detector $257-260$  $257-260$ . To do so, artificial detections are generated at random times (e.g., Poisson-distributed) but using the same rate as that of the method under investigation. This easy and computationally fast approach might require adjustments in case of (near-)periodic occurrences of transitions and it might not be generally applicable. A more advanced though more time-intensive ansatz makes use of null-hypothesis-based re-sampling or bootstrapping methods<sup>[261](#page-12-16)[,262](#page-12-17)</sup>, also known as surrogate techniques in time series $263-265$  $263-265$  and network analy- $sis^{266-272}$  $sis^{266-272}$  $sis^{266-272}$ . One such technique<sup>[273](#page-12-22)</sup> consists of a random shuffling of the time intervals between successive (true) detections of critical transitions to generate artificial detection time-points. A related technique<sup>[274](#page-12-23)</sup> leaves the (true) detection timepoints unchanged and instead performs a constrained randomization of the temporal sequence of a characterizing metric using e.g. simulated annealing $275$ . Both these techniques require formulating an appropriate null-hypothesis as well as a robust (non-parametric) test statistic to assess the statistical significance of the results obtained. The number of independent surrogates *N*surr determines the nominal size of the test statistic (i.e., the probability  $\alpha$  of making a type I error;  $1/N<sub>surr</sub> \le \alpha$ ). The performance (as assessed with AUC) of the detection method under investigation is then compared with the performances of a surrogate ensemble. If the method's performance exceeds to performances of the surrogates, then the method can be considered – with greater confidence – as performing better than chance. Reporting the "number of sigmas" can be misleading since it is accompanied by strict assumptions about the underlying distributions of performance values. Surrogate-based approaches can account for a possibly non-random occurrence of critical transitions which might be encountered with driven non-stationary systems.

#### Time series surrogates

Null-hypothesis-based surrogate techniques are also being used to generate ensembles of time series that share relevant statistical properties with the original time series of some suitable observable except for properties that are assumed to be indicative of a critical transition. As an example, we mention trends of indicators for critical slowing down such as variance and lag-1 autocorrelation. Techniques to generate such surrogate time series include random shuffling, autoregressive model-based methods, or iterative amplitude-adjusted Fourier transform[263](#page-12-18) and are often used to evaluate the significance of the aforementioned indicators<sup>[131,](#page-9-9)[137](#page-10-21)[,276](#page-12-25)[–280](#page-12-26)</sup>. Techniques require formulating an appropriate null-hypothesis as well as a robust (non-parametric) test statistic to assess the statistical significance of the results obtained. The number of independent surrogate time series determines the nominal size of the test statistic.

Before closing this section, it is important to recall the following caveats when interpreting an offline detection method's reliability evaluated with the aforementioned tests<sup>[281](#page-12-27)</sup>:

- statistical tests can neither prove the correctness of an offline detection method's reliability nor can they prove the existence of a critical transition;
- a rejection of a null hypothesis only provides a necessary but not a sufficient condition for a method to indicate reliable offline detection of a critical transition;
- an acceptance of a null hypothesis does not indicate its correctness;
- whenever a null hypothesis is rejected, it is always very important to keep in mind that the complementary hypothesis is typically very comprehensive and might include many different reasons that are possibly responsible for this rejection;
- consider including other (statistical) properties of your data and detection method into the null hypothesis.

# VII. PROSPECTS FOR TIME-SERIES-ANALYSIS-BASED ONLINE DETECTIONS OF CRITICAL TRANSITIONS

So far, only a few studies reported on above-chance-level online detections of critical transitions in real-world non-autonomous systems from empirical data<sup>[282](#page-12-28)[,283](#page-13-0)</sup>. Findings suggest that it is possible to forecast the occurrence of a recurrent extreme event in some cases, however, predicting exact timing and magnitude of an event is much more difficult. Forecasts should thus be probabilistic[284](#page-13-1) instead of aiming at fully deterministic predictions.

When judging the reliability of probabilistic forecasts (or forecast skill) of rare and recurrent extreme events, the statistical tests discussed in Sect. [VI](#page-4-0) can be oversimplistic or even misleading<sup>[253,](#page-12-29)[285](#page-13-2)</sup>. Proper scoring rules and strictly proper scores<sup>[286–](#page-13-3)[289](#page-13-4)</sup> and uncertainty quantification<sup>[290](#page-13-5)</sup> appear to be more suitable, however, their use for time-series-analysisbased online detections of critical transitions requires further conceptual and methodological developments.

## VIII. CONCLUSIONS

The time-series-analysis-based detection of critical transitions in real-world non-autonomous systems is a young area of research that carries the potential to advance understanding and reliable forecasting of such nonlinear behavior. In this paper, I provided an overview of and critically assessed the various involved steps of investigation: from the data recording via coping with non-stationarity when analyzing time series of system observables to evaluating the reliability of offline and online detections. I highlighted pros and cons to stimulate further developments that require a close interlinking of theory and experiment.

Time-series analysis methods in use appear to be suitable to allow detection and sufficient characterization of bifurcationinduced critical transitions in low-dimensional systems. Nevertheless, their suitability for these types of transition in highdimensional systems as well as for other transition mechanisms remains to be shown. Is is conceivable that the latter require novel developments also in terms of robustness, appropriateness for non-stationary systems, and – ideally – general interpretability. Likewise, the same applies to methods to test the reliability of detections.

Extreme events occur in a variety of natural, technical, and societal systems and their frequency appears to be increasing. Their catastrophic consequences and their low-probability, high-impact nature not only calls for improving our understanding of generating mechanisms but also to provide reliable early warnings to enable the development of adaptation and/or mitigation strategies.

# ACKNOWLEDGMENTS

The author acknowledges fruitful discussions with Manuel Adams, Timo Bröhl, Ulrike Feudel, and Thorsten Rings.

## AUTHOR DECLARATIONS

#### Conflict of Interest

The author has no conflicts to disclose.

# Data availability

Data sharing is not applicable to this article as no new data were created or analyzed in this study.

- <span id="page-7-0"></span><sup>1</sup>S. Albeverio, V. Jentsch, and H. Kantz, eds., *Extreme events in nature and society*, The Frontiers Collection (Springer, Berlin, 2006).
- <sup>2</sup>R. Basher, "Global early warning systems for natural hazards: systematic and people-centred," Phil. Trans. Roy. Soc. A: mathematical, physical and engineering sciences 364, 2167–2182 (2006).
- <sup>3</sup>H. E. Willoughby, E. Rappaport, and F. Marks, "Hurricane forecasting: The state of the art," Nat. Hazards Rev. 8, 45–49 (2007).
- <sup>4</sup>T. M. Lenton, "Early warning of climate tipping points," Nat. Clim. Change 1, 201 (2011).
- <sup>5</sup>G. Ansmann, R. Karnatak, K. Lehnertz, and U. Feudel, "Extreme events in excitable systems and mechanisms of their generation," [Phys. Rev. E](http://dx.doi.org/ 10.1103/PhysRevE.88.052911) 88, [052911 \(2013\).](http://dx.doi.org/ 10.1103/PhysRevE.88.052911)
- <sup>6</sup>E. Meron, *Nonlinear physics of ecosystems* (CRC Press, Boca Raton, FL, USA, 2015).
- <sup>7</sup>C. Trefois, P. M. Antony, J. Goncalves, A. Skupin, and R. Balling, "Critical transitions in chronic disease: transferring concepts from ecology to systems medicine," Curr. Opin. Biotechnol. 34, 48–55 (2015).
- <sup>8</sup>E. Intrieri and G. Gigli, "Landslide forecasting and factors influencing predictability," Nat. Hazards Earth Syst. Sci. 16, 2501–2510 (2016).
- <sup>9</sup>B. Bok, D. Caratelli, D. Giannone, A. M. Sbordone, and A. Tambalotti, "Macroeconomic nowcasting and forecasting with big data," Annu. Rev. Econ. 10, 615–643 (2018).
- $10$ T. P. Sapsis, "New perspectives for the prediction and statistical quantification of extreme events in high-dimensional dynamical systems," Phil. Trans. Roy. Soc. A: Mathematical, Physical and Engineering Sciences 376, 20170133 (2018).
- <sup>11</sup>S. Hanifi, X. Liu, Z. Lin, and S. Lotfian, "A critical review of wind power forecasting methods—past, present and future," Energies 13, 3764 (2020).
- <span id="page-7-9"></span><sup>12</sup>A. Morozov, K. Abbott, K. Cuddington, T. Francis, G. Gellner, A. Hastings, Y.-C. Lai, S. Petrovskii, K. Scranton, and M. L. Zeeman, "Long transients in ecology: Theory and applications," Phys. Life Rev. 32, 1–40  $(2020)$
- <sup>13</sup>M. Scheffer, *Critical transitions in nature and society*, Vol. 16 (Princeton University Press, Princeton, New Jersey, 2020).
- <sup>14</sup>J. B. Rundle, S. Stein, A. Donnellan, D. L. Turcotte, W. Klein, and C. Saylor, "The complex dynamics of earthquake fault systems: New approaches to forecasting and nowcasting of earthquakes," Rep. Prog. Phys.. 84, 076801 (2021).
- <sup>15</sup>Q. Bletery and J.-M. Nocquet, "The precursory phase of large earthquakes," Science 381, 297–301 (2023).
- <sup>16</sup>F. Cerini, D. Z. Childs, and C. F. Clements, "A predictive timeline of wildlife population collapse," Nat. Ecol. Evol. 7, 320–331 (2023).
- <sup>17</sup>D. I. Domeisen, E. A. Eltahir, E. M. Fischer, R. Knutti, S. E. Perkins-Kirkpatrick, C. Schär, S. I. Seneviratne, A. Weisheimer, and H. Wernli, "Prediction and projection of heatwaves," Nat. Rev. Earth Environ. 4, 36– 50 (2023).
- <span id="page-7-10"></span><sup>18</sup>K. Lehnertz, T. Bröhl, and R. von Wrede, "Epileptic-network-based prediction and control of seizures in humans," Neurobiol. Dis. 181, 106098 (2023).
- <sup>19</sup>B. M. Flores, E. Montoya, B. Sakschewski, N. Nascimento, A. Staal, R. A. Betts, C. Levis, D. M. Lapola, A. Esquível-Muelbert, C. Jakovac, *et al.*, "Critical transitions in the Amazon forest system," Nature 626, 555–564 (2024).
- <span id="page-7-1"></span> $^{20}$ J. L. Hardebeck, A. L. Llenos, A. J. Michael, M. T. Page, M. Schneider, and N. J. van der Elst, "Aftershock forecasting," [Annu. Rev. Earth Planet.](http://dx.doi.org/10.1146/annurev-earth-040522-102129) Sci. 52[, 2.1–2.24 \(2024\).](http://dx.doi.org/10.1146/annurev-earth-040522-102129)
- <span id="page-7-2"></span><sup>21</sup>W. Horsthemke and R. Lefever, *Noise-Induced Transitions. Theory and Applications in Physics, Chemistry and Biology* (Springer, Berlin, 1984).
- $22 \overline{C}$ . Kuehn, "A mathematical framework for critical transitions: Bifurcations, fast-slow systems and stochastic dynamics," [Physica D](http://dx.doi.org/10.1016/j.physd.2011.02.012) 240, 1020– [1035 \(2011\).](http://dx.doi.org/10.1016/j.physd.2011.02.012)
- <sup>23</sup>P. Ashwin, S. Wieczorek, R. Vitolo, and P. Cox, "Tipping points in open systems: bifurcation, noise-induced and rate-dependent examples in the climate system," Phil. Trans. Roy. Soc. A 370, 1166–1184 (2012).
- <span id="page-7-3"></span><sup>24</sup>U. Feudel, "Rate-induced tipping in ecosystems and climate: the role of unstable states, basin boundaries and transient dynamics," Nonlin. Processes Geophys. Discussions 2023, 1–29 (2023).
- <span id="page-7-4"></span><sup>25</sup>G. R. Sell, "Nonautonomous differential equations and topological dynamics. I. The basic theory," Trans. Amer. Math. Soc. 127, 241–262 (1967).
- <span id="page-7-5"></span><sup>26</sup>P. E. Kloeden and M. Rasmussen, *Nonautonomous dynamical systems* (American Mathematical Soc., Providence, RI, USA, 2011).
- <span id="page-7-6"></span> $27$ I. Pavithran, P. Midhun, and R. Sujith, "Tipping in complex systems under fast variations of parameters," Chaos: An Interdisciplinary Journal of Nonlinear Science 33, 081105 (2023).
- <span id="page-7-7"></span><sup>28</sup>P. T. Clemson and A. Stefanovska, "Discerning non-autonomous dynamics," Phys. Rep. 542[, 297–368 \(2014\).](http://dx.doi.org/10.1016/j.physrep.2014.04.001)
- <span id="page-7-8"></span><sup>29</sup>H. Kantz and T. Schreiber, *[Nonlinear Time Series Analysis](http://dx.doi.org/10.1017/CBO9780511755798)*, 2nd ed. (Cambridge University Press, Cambridge, UK, 2003).
- <span id="page-8-0"></span><sup>30</sup>S. Boccaletti, V. Latora, Y. Moreno, M. Chavez, and D.-U. Hwang, "Complex networks: Structure and dynamics," Phys. Rep. 424[, 175–308 \(2006\).](http://dx.doi.org/10.1016/j.physrep.2005.10.009)
- <span id="page-8-1"></span><sup>31</sup>Y. Zou, R. V. Donner, N. Marwan, J. F. Donges, and J. Kurths, "Complex network approaches to nonlinear time series analysis," Phys. Rep. 787, 1– 97 (2019).
- <span id="page-8-2"></span><sup>32</sup>J. Amigó, *Permutation complexity in dynamical systems: ordinal patterns, permutation entropy and all that* (Springer Science & Business Media, Berlin Heidelberg, 2010).
- <span id="page-8-3"></span><sup>33</sup>F. Kwasniok and L. A. Smith, "Real-time construction of optimized predictors from data streams," Phys. Rev. Lett. 92, 164101 (2004).
- <sup>34</sup>A. Mignan, "The debate on the prognostic value of earthquake foreshocks: A meta-analysis," Sci. Rep. 4, 4099 (2014).
- <span id="page-8-4"></span><sup>35</sup>A. Mignan, G. Ouillon, D. Sornette, and F. Freund, "Global earthquake forecasting system (GEFS): The challenges ahead," Eur. Phys. J. ST 230, 473–490 (2021).
- <span id="page-8-5"></span><sup>36</sup>H. Nyquist, "Certain topics in telegraph transmission theory," Trans. AIEE 47, 617–644 (1928).
- <sup>37</sup>C. E. Shannon, "Communication in the presence of noise," Proc. IRE 37, 10–21 (1949).
- <span id="page-8-6"></span><sup>38</sup>A. J. Jerri, "The Shannon sampling theorem—its various extensions and applications: A tutorial review," Proc. IEEE 65, 1565–1596 (1977).
- <span id="page-8-7"></span><sup>39</sup>S. Bialonski, M. Horstmann, and K. Lehnertz, "From brain to earth and climate systems: Small-world interaction networks or not?" [Chaos](http://dx.doi.org/10.1063/1.3360561) 20, [013134 \(2010\).](http://dx.doi.org/10.1063/1.3360561)
- <span id="page-8-8"></span><sup>40</sup>S. Porz, M. Kiel, and K. Lehnertz, "Can spurious indications for phase synchronization due to superimposed signals be avoided?" [Chaos](http://dx.doi.org/ 10.1063/1.4890568) 24, [033112 \(2014\).](http://dx.doi.org/ 10.1063/1.4890568)
- <span id="page-8-9"></span><sup>41</sup>A. Effern, K. Lehnertz, T. Schreiber, T. Grunwald, P. David, and C. E. Elger, "Nonlinear denoising of transient signals with application to eventrelated potentials," Physica D 140, 257–266 (2000).
- <span id="page-8-10"></span><sup>42</sup>I. M. Jánosi and T. Tél, "Time-series analysis of transient chaos," [Phys.](http://dx.doi.org/10.1103/PhysRevE.49.2756) Rev. E 49[, 2756–2763 \(1994\).](http://dx.doi.org/10.1103/PhysRevE.49.2756)
- <sup>43</sup>M. Dhamala, Y.-C. Lai, and E. J. Kostelich, "Analyses of transient chaotic time series," Phys. Rev. E 64[, 056207 \(2001\).](http://dx.doi.org/10.1103/PhysRevE.64.056207)
- <sup>44</sup>R. G. Andrzejak, A. Ledberg, and G. Deco, "Detecting event-related timedependent directional couplings," New J. Phys. 8, 6 (2006).
- <sup>45</sup>S. Łeski and D. K. Wójcik, "Inferring coupling strength from event-related dynamics," Phys. Rev. E 78, 41918–41927 (2008).
- <sup>46</sup>C. Komalapriya, M. Thiel, M. C. Romano, N. Marwan, U. Schwarz, and J. Kurths, "Reconstruction of a system's dynamics from short trajectories," Phys. Rev. E 78, 066217 (2008).
- <sup>47</sup>T. Wagner, J. Fell, and K. Lehnertz, "The detection of transient directional couplings based on phase synchronization," [New J. Phys.](http://dx.doi.org/ 10.1088/1367-2630/12/5/053031) 12, 053031 [\(2010\).](http://dx.doi.org/ 10.1088/1367-2630/12/5/053031)
- <sup>48</sup>M. Martini, T. A. Kranz, T. Wagner, and K. Lehnertz, "Inferring directional interactions from transient signals with symbolic transfer entropy," Phys. Rev. E 83[, 011919 \(2011\).](http://dx.doi.org/ 10.1103/PhysRevE.83.011919)
- <sup>49</sup>H. Ma, T. Zhou, K. Aihara, and L. Chen, "Predicting time series from short-term high-dimensional data," Int.. J. Bifurcation Chaos 24, 1430033 (2014).
- <span id="page-8-11"></span><sup>50</sup>W.-X. Wang, Y.-C. Lai, and C. Grebogi, "Data based identification and prediction of nonlinear and complex dynamical systems," Phys. Rep. 644, 1–76 (2016).
- <span id="page-8-12"></span><sup>51</sup>K. Kaneko, "Supertransients, spatiotemporal intermittency and stability of fully developed spatiotemporal chaos," Phys. Lett. A 149[, 105–112 \(1990\).](http://dx.doi.org/10.1016/0375-9601(90)90534-U)
- <sup>52</sup>T. Tél and Y.-C. Lai, "Chaotic transients in spatially extended systems," Phys. Rep. 460[, 245–275 \(2008\).](http://dx.doi.org/ 10.1016/j.physrep.2008.01.001)
- <span id="page-8-13"></span><sup>53</sup>H. Meyer-Ortmanns, "Heteroclinic networks for brain dynamics," Front. Netw. Physiol. 3, 1276401 (2023).
- <span id="page-8-14"></span><sup>54</sup>G. Ansmann, K. Lehnertz, and U. Feudel, "Self-induced switchings between multiple space-time patterns on complex networks of excitable units," Phys. Rev. X 6[, 011030 \(2016\).](http://dx.doi.org/10.1103/PhysRevX.6.011030)
- <span id="page-8-15"></span><sup>55</sup>A. Nandan and A. Koseska, "Non-asymptotic transients away from steady states determine cellular responsiveness to dynamic spatial-temporal signals," PLoS Comput. Biol. 19, e1011388 (2023).
- <span id="page-8-16"></span><sup>56</sup>L. Boltzmann, *Über die Beziehung zwischen dem zweiten Hauptsatze des mechanischen Wärmetheorie und der Wahrscheinlichkeitsrechnung, respective den Sätzen über das Wärmegleichgewicht* (K.k. Hof-und Staatsdruckerei, Vienna, Austria, 1877).
- <span id="page-8-17"></span><sup>57</sup>G. D. Birkhoff, "Proof of the ergodic theorem," Proc. Natl. Acad. Sci. 17, 656–660 (1931).
- <span id="page-8-18"></span><sup>58</sup>M. B. Priestley, *Nonlinear and Non-Stationary Time Series Analysis* (Academic Press, London, 1988).
- <span id="page-8-19"></span><sup>59</sup>K. M. M. Prabhu, *Window functions and their applications in signal processing* (Taylor & Francis, Boca Raton, USA, 2014).
- <span id="page-8-20"></span><sup>60</sup>G. Kitagawa, "Non-Gaussian state—space modeling of nonstationary time series," J. Am. Stat. Assoc. 82, 1032–1041 (1987).
- <sup>61</sup>R. Dahlhaus, "Fitting time series models to nonstationary processes," Ann. Stat. 25, 1–37 (1997).
- $62$ N. E. Huang, Z. Shen, S. R. Long, M. C. Wu, H. H. Shih, Q. Zheng, N.-C. Yen, C. C. Tung, and H. H. Liu, "The empirical mode decomposition and the Hilbert spectrum for nonlinear and non-stationary time series analysis," [Proc. Roy. Soc. London. Series A: Mathematical, Physical and Engineer](http://dx.doi.org/ 10.1098/rspa.1998.0193)ing Sciences 454[, 903–995 \(1998\).](http://dx.doi.org/ 10.1098/rspa.1998.0193)
- <sup>63</sup>P. Verdes, P. Granitto, H. Navone, and H. Ceccatto, "Nonstationary timeseries analysis: Accurate reconstruction of driving forces," Phys. Rev. Lett. 87, 124101 (2001).
- <sup>64</sup>J. W. Kantelhardt, S. A. Zschiegner, E. Koscielny-Bunde, S. Havlin, A. Bunde, and H. E. Stanley, "Multifractal detrended fluctuation analysis of nonstationary time series," Physica A: Statistical Mechanics and its Applications 316, 87–114 (2002).
- $^{65}$ K. Fukuda, H. E. Stanley, and L. A. N. Amaral, "Heuristic segmentation of a nonstationary time series," Phys. Rev. E 69, 021108 (2004).
- <sup>66</sup>Z. Wu, N. E. Huang, S. R. Long, and C.-K. Peng, "On the trend, detrending, and variability of nonlinear and nonstationary time series," Proc. Natl. Acad. Sci. 104, 14889–14894 (2007).
- <sup>67</sup>K. Lehnertz, C. Geier, T. Rings, and K. Stahn, "Capturing time-varying brain dynamics," EPJ Nonlin. Biomed. Phys. 5, 2 (2017).
- <sup>68</sup>B. Podobnik and H. E. Stanley, "Detrended cross-correlation analysis: a new method for analyzing two nonstationary time series," Phys. Eev. Lett. 100, 084102 (2008).
- <span id="page-8-21"></span><sup>69</sup>M. Rhif, A. Ben Abbes, I. R. Farah, B. Martínez, and Y. Sang, "Wavelet transform application for/in non-stationary time-series analysis: A review," Applied Sciences 9, 1345 (2019).
- <span id="page-8-22"></span> $70R$ . Hegger, H. Kantz, L. Matassini, and T. Schreiber, "Coping with nonstationarity by overembedding," Phys. Rev. Lett. 84, 4092–4095 (2000).
- <sup>71</sup>P. Verdes, P. Granitto, and H. Ceccatto, "Overembedding method for modeling nonstationary systems," Phys. Rev. Lett. 96, 118701 (2006).
- <span id="page-8-23"></span><sup>72</sup>M. De Domenico and V. Latora, "Fast detection of nonlinearity and nonstationarity in short and noisy time series," Europhys. Lett. 91, 30005 (2010).
- <span id="page-8-24"></span><sup>73</sup>R. Manuca and R. Savit, "Stationarity and nonstationarity in time series analysis," Physica D: Nonlinear Phenomena 99, 134–161 (1996).
- <sup>74</sup>M. B. Kennel, "Statistical test for dynamical nonstationarity in observed time-series data," Phys. Rev. E 56[, 316–321 \(1997\).](http://dx.doi.org/10.1103/PhysRevE.56.316)
- <sup>75</sup>J. Gao, "Detecting nonstationarity and state transitions in a time series," Phys. Rev. E 63, 066202 (2001).
- <sup>76</sup>C. Rieke, K. Sternickel, R. G. Andrzejak, C. E. Elger, P. David, and K. Lehnertz, "Measuring nonstationarity by analyzing the loss of recurrence in dynamical systems," Phys. Rev. Lett. 88, 244102 (2002).
- <sup>77</sup>C. Rieke, R. G. Andrzejak, F. Mormann, and K. Lehnertz, "Improved statistical test for nonstationarity using recurrence time statistics," Phys. Rev. E 69, 046111 (2004).
- <sup>78</sup>A. Facchini, H. Kantz, and E. Tiezzi, "Recurrence plot analysis of nonstationary data: the understanding of curved patterns," Phys. Rev. E 72, 021915 (2005).
- <span id="page-8-25"></span> $79$ Y. Chen and H. Yang, "Multiscale recurrence analysis of long-term nonlinear and nonstationary time series," Chaos, Solitons & Fractals 45, 978–987 (2012).
- <span id="page-8-26"></span>80T. Schreiber, "Detecting and analysing nonstationarity in a time series using nonlinear cross predictions," Phys. Rev. Lett. 78, 843 (1997).
- <span id="page-8-27"></span><sup>81</sup>M. B. Kennel and A. I. Mees, "Testing for general dynamical stationarity with a symbolic data compression technique," Phys. Rev. E 61, 2563 (2000).
- <span id="page-8-28"></span><sup>82</sup>P. M. Robinson, "Efficient tests of nonstationary hypotheses," J. Am. Stat. Assoc. 89, 1420–1437 (1994).
- <span id="page-8-29"></span><sup>83</sup>A. Witt, J. Kurths, and A. Pikovsky, "Testing stationarity in time series," Phys. Rev. E 58[, 1800–1810 \(1998\).](http://dx.doi.org/10.1103/PhysRevE.58.1800)
- <span id="page-8-30"></span><sup>84</sup>D. C. Champeney, *Fourier Transforms and their physical applications* (Academic Press, Cambridge, MA, USA, 1973).
- <sup>85</sup>T. A. Brody, J. Flores, J. B. French, P. A. Mello, A. Pandey, and S. S. M. Wong, "Random-matrix physics: Spectrum and strength fluctuations," Rev. Mod. Phys. 53, 385–479 (1981).
- <sup>86</sup>S. Haykin, ed., *[Nonlinear methods of spectral analysis](http://dx.doi.org/10.1007/3-540-12386-5)* (Springer, Berlin, Heidelberg, 1983).
- <sup>87</sup>P. Grassberger, T. Schreiber, and C. Schaffrath, "Nonlinear time sequence analysis," Int. J. Bifurcation Chaos Appl. Sci. Eng. 1, 521 (1991).
- <sup>88</sup>H. D. I. Abarbanel, R. Brown, J. J. Sidorowich, and L. S. Tsimring, "The analysis of observed chaotic data in physical systems," [Rev. Mod. Phys.](http://dx.doi.org/ 10.1103/RevModPhys.65.1331) 65[, 1331 \(1993\).](http://dx.doi.org/ 10.1103/RevModPhys.65.1331)
- <sup>89</sup>J. Honerkamp, *Stochastic Dynamical Systems: Concepts, Numerical Methods, Data Analysis* (Wiley-VCH, New York, 1993).
- <sup>90</sup>D. Kaplan and L. Glass, *Understanding Nonlinear Dynamics* (Springer, New York, 1995).
- <sup>91</sup>D. B. Percival and A. T. Walden, *Wavelet methods for time series analysis*, Vol. 4 (Cambridge University Press, Cambridge, UK, 2000).
- <sup>92</sup>A. S. Pikovsky, M. G. Rosenblum, and J. Kurths, *[Synchronization: A uni](http://dx.doi.org/10.1017/CBO9780511755743)[versal concept in nonlinear sciences](http://dx.doi.org/10.1017/CBO9780511755743)* (Cambridge University Press, Cambridge, UK, 2001).
- <sup>93</sup>C. Daw, C. Finney, and E. Tracy, "A review of symbolic analysis of experimental data." Rev. Sci. Instrum. 74, 915–930 (2003).
- <sup>94</sup>G. C. Reinsel, *Elements of multivariate time series analysis*, 2nd ed. (Springer, New York, 2003).
- 95 K. Keller and M. Sinn, "Ordinal analysis of time series," Physica A: Statistical Mechanics and its Applications 356, 114–120 (2005).
- <sup>96</sup>H. Lütkepohl, *New introduction to multiple time series analysis* (Springer Science & Business Media, Berlin, Heidelberg, Germany, 2005).
- $97$ K. Hlaváčková-Schindler, M. Paluš, M. Vejmelka, and J. Bhattacharya, "Causality detection based on information-theoretic approaches in time series analysis," Phys. Rep. 441[, 1–46 \(2007\).](http://dx.doi.org/10.1016/j.physrep.2006.12.004)
- 98<sub>N.</sub> Marwan, M. C. Romano, M. Thiel, and J. Kurths, "Recurrence plots for the analysis of complex systems," Phys. Rep. 438[, 237–329 \(2007\).](http://dx.doi.org/10.1016/j.physrep.2006.11.001)
- <sup>99</sup>L. Lacasa, B. Luque, F. Ballesteros, J. Luque, and J. C. Nuno, "From time series to complex networks: The visibility graph," [Proc. Natl. Acad. Sci.](http://dx.doi.org/10.1073/pnas.0709247105) U.S.A. 105[, 4972–4975 \(2008\).](http://dx.doi.org/10.1073/pnas.0709247105)
- <sup>100</sup>T. W. Anderson, *The statistical analysis of time series* (John Wiley & Sons, Hoboken, New Jersey, 2011).
- <sup>101</sup>R. Friedrich, J. Peinke, M. Sahimi, and M. R. R. Tabar, "Approaching complexity by stochastic methods: From biological systems to turbulence," Phys. Rep. 506[, 87–162 \(2011\).](http://dx.doi.org/ 10.1016/j.physrep.2011.05.003)
- <sup>102</sup>U. Von Toussaint, "Bayesian inference in physics," Rev. Mod. Phys. 83, 943 (2011).
- <sup>103</sup>E. Bradley and H. Kantz, "Nonlinear time-series analysis revisited," Chaos: An Interdisciplinary Journal of Nonlinear Science 25, 097610 (2015).
- <sup>104</sup>C. L. Webber, Jr. and N. Marwan, *[Recurrence Quantification Analysis –](http://dx.doi.org/10.1007/978-3-319-07155-8) [Theory and Best Practices](http://dx.doi.org/10.1007/978-3-319-07155-8)* (Springer, Cham, Switzerland, 2015).
- <sup>105</sup>T. Stankovski, T. Pereira, P. V. E. McClintock, and A. Stefanovska, "Coupling functions: Universal insights into dynamical interaction mechanisms," [Rev. Mod. Phys.](http://dx.doi.org/10.1103/RevModPhys.89.045001) 89, 045001 (2017).
- <span id="page-9-8"></span><sup>106</sup>M. R. R. Tabar, *[Analysis and Data-Based Reconstruction of Complex Non](http://dx.doi.org/10.1007/978-3-030-18472-8)[linear Dynamical Systems: Using the Methods of Stochastic Processes](http://dx.doi.org/10.1007/978-3-030-18472-8)* (Springer International Publishin, Cham, Switzerland, 2019).
- <sup>107</sup>J. D. Hamilton, *Time series analysis* (Princeton University Press, 2020).
- <sup>108</sup>T. Edinburgh, S. J. Eglen, and A. Ercole, "Causality indices for bivariate time series data: A comparative review of performance," Chaos: An Interdisciplinary Journal of Nonlinear Science 31, 083111 (2021).
- <sup>109</sup>G. Datseris and U. Parlitz, *Nonlinear dynamics: a concise introduction interlaced with code* (Springer International Publishing, Cham, Switzerland, 2022).
- <sup>110</sup>K. Fokianos, R. Fried, Y. Kharin, and V. Voloshko, "Statistical analysis of multivariate discrete-valued time series," J. Multivar. Anal. 188, 104805 (2022).
- <sup>111</sup>F. Nikakhtar, L. Parkavousi, M. Sahimi, M. R. R. Tabar, U. Feudel, and K. Lehnertz, "Data-driven reconstruction of stochastic dynamical equations based on statistical moments," New J. Phys. 25, 083025 (2023).
- <span id="page-9-0"></span><sup>112</sup>M. R. R. Tabar, F. Nikakhtar, L. Parkavousi, A. Akhshi, U. Feudel, and K. Lehnertz, "Revealing higher-order interactions in high-dimensional complex systems: A data-driven approach," Phys. Rev. X 14, 011050 (2024).
- <span id="page-9-1"></span><sup>113</sup>N. H. Packard, J. P. Crutchfield, J. D. Farmer, and R. S. Shaw, "Geometry from a time series," Phys. Rev. Lett. 45, 712–716 (1980).
- <sup>114</sup>F. Takens, "Detecting strange attractors in turbulence," in *[Dynamical Sys](http://dx.doi.org/10.1007/BFb0091924)[tems and Turbulence \(Warwick 1980\)](http://dx.doi.org/10.1007/BFb0091924)*, Lecture Notes in Mathematics, Vol. 898, edited by D. A. Rand and L.-S. Young (Springer, Berlin, 1981) pp. 366–381.
- <sup>115</sup>T. Sauer, J. Yorke, and M. Casdagli, "Embedology," J. Stat. Phys. 65, 579–616 (1991).
- <sup>116</sup>M. Casdagli, S. Eubank, J. D. Farmer, and J. Gibson, "State space reconstruction in the presence of noise," Physica D: Nonlinear Phenomena 51, 52–98 (1991).
- <sup>117</sup>M. B. Kennel, R. Brown, and H. D. I. Abarbanel, "Determining embedding dimension for phase-space reconstruction using a geometrical construction," Phys. Rev. A 45[, 3403–3411 \(1992\).](http://dx.doi.org/10.1103/PhysRevA.45.3403)
- <sup>118</sup>D. Kugiumtzis, "State space reconstruction parameters in the analysis of chaotic time series–the role of the time window length," Physica D: Nonlinear Phenomena 95, 13–28 (1996).
- <sup>119</sup>L. Cao, "Practical method for determining the minimum embedding dimension of a scalar time series," Physica D 110[, 43–50 \(1997\).](http://dx.doi.org/10.1016/S0167-2789(97)00118-8)
- <sup>120</sup>C. J. Cellucci, A. M. Albano, and P. E. Rapp, "Comparative study of embedding methods," Phys. Rev. E 67, 066210 (2003).
- <sup>121</sup>I. Vlachos and D. Kugiumtzis, "Nonuniform state-space reconstruction and coupling detection," Phys. Rev. E 82[, 016207 \(2010\).](http://dx.doi.org/ 10.1103/PhysRevE.82.016207)
- <span id="page-9-2"></span><sup>122</sup>K.-H. Krämer, G. Datseris, J. Kurths, I. Z. Kiss, J. L. Ocampo-Espindola, and N. Marwan, "A unified and automated approach to attractor reconstruction," New J. Physics 23, 033017 (2021).
- <span id="page-9-3"></span><sup>123</sup>V. Dakos, M. Scheffer, E. H. van Nes, V. Brovkin, V. Petoukhov, and H. Held, "Slowing down as an early warning signal for abrupt climate change," [Proc. Natl. Acad. Sci. U.S.A.](http://dx.doi.org/10.1073/pnas.0802430105) 105, 14308–14312 (2008).
- <sup>124</sup>M. Scheffer, J. Bascompte, W. A. Brock, V. Brovkin, S. R. Carpenter, V. Dakos, H. Held, E. H. van Nes, M. Rietkerk, and G. Sugihara, "Earlywarning signals for critical transitions," Nature 461, 53-59 (2009).
- <sup>125</sup>M. Scheffer, S. R. Carpenter, T. M. Lenton, J. Bascompte, W. Brock, V. Dakos, J. van de Koppel, I. A. van de Leemput, S. A. Levin, E. H. van Nes, M. Pascual, and J. Vandermeer, "Anticipating critical transitions," Science 338[, 344–348 \(2012\).](http://dx.doi.org/10.1126/science.1225244)
- <sup>126</sup>L. Dai, D. Vorselen, K. S. Korolev, and J. Gore, "Generic indicators for loss of resilience before a tipping point leading to population collapse," Science 336, 1175–1177 (2012).
- <span id="page-9-4"></span><sup>127</sup>T. Lenton, V. Livina, V. Dakos, E. Van Nes, and M. Scheffer, "Early warning of climate tipping points from critical slowing down: comparing methods to improve robustness," Phil. Trans. Roy. Soc. A: Mathematical, Physical and Engineering Sciences 370, 1185–1204 (2012).
- <span id="page-9-5"></span><sup>128</sup>T. M. Bury, C. T. Bauch, and M. Anand, "Detecting and distinguishing tipping points using spectral early warning signals," J. Roy. Soc. Interface 17, 20200482 (2020).
- <span id="page-9-6"></span><sup>129</sup>R. Kubo, "The fluctuation-dissipation theorem," Rep. Prog. Phys. 29, 255 (1966).
- <span id="page-9-7"></span><sup>130</sup>E. Cotilla-Sanchez, P. D. Hines, and C. M. Danforth, "Predicting critical transitions from time series synchrophasor data," IEEE Trans. Smart Grid 3, 1832–1840 (2012).
- <span id="page-9-9"></span><sup>131</sup>V. Dakos, S. R. Carpenter, W. A. Brock, A. M. Ellison, V. Guttal, A. R. Ives, S. Kéfi, V. Livina, D. A. Seekell, E. H. van Nes, and M. Scheffer, "Methods for detecting early warnings of critical transitions in time series illustrated using simulated ecological data," PLOS ONE 7[, 1–20 \(2012\).](http://dx.doi.org/ 10.1371/journal.pone.0041010)
- <sup>132</sup>I. A. van de Leemput, M. Wichers, A. O. Cramer, D. Borsboom, F. Tuerlinckx, P. Kuppens, E. H. van Nes, W. Viechtbauer, E. J. Giltay, S. H. Aggen, *et al.*, "Critical slowing down as early warning for the onset and termination of depression," Proc. Natl. Acad. Sci. U.S.A. 111, 87–92 (2014).
- <sup>133</sup>C. Meisel, A. Klaus, C. Kuehn, and D. Plenz, "Critical slowing down governs the transition to neuron spiking," PLoS Comput. Biol. 11, e1004097 (2015).
- <sup>134</sup>M. Perry, V. Livina, and P. Niewczas, "Tipping point analysis of cracking in reinforced concrete," Smart Mater. Struct. 25, 015027 (2015).
- <sup>135</sup>F. Nazarimehr, S. Jafari, M. Perc, and J. C. Sprott, "Critical slowing down indicators," Europhys. Lett. 132, 18001 (2020).
- <sup>136</sup>P. Brookes, G. Tancredi, A. D. Patterson, J. Rahamim, M. Esposito, T. K. Mavrogordatos, P. J. Leek, E. Ginossar, and M. H. Szymanska, "Critical slowing down in circuit quantum electrodynamics," Sci. Adv. 7, eabe9492

(2021).

- <span id="page-10-21"></span><sup>137</sup>S. V. George, S. Kachhara, and G. Ambika, "Early warning signals for critical transitions in complex systems," Phys. Scr. 98, 072002 (2021).
- <span id="page-10-19"></span><sup>138</sup>E. Southall, T. S. Brett, M. J. Tildesley, and L. Dyson, "Early warning signals of infectious disease transitions: a review," J. Roy. Soc. Interface 18, 20210555 (2021).
- <sup>139</sup>F. Dablander, A. Pichler, A. Cika, and A. Bacilieri, "Anticipating critical transitions in psychological systems using early warning signals: Theoretical and practical considerations." Psychol. Methods 28, 765–790 (2022).
- <sup>140</sup>S. Deb, S. Bhandary, S. K. Sinha, M. K. Jolly, and P. S. Dutta, "Identifying critical transitions in complex diseases," J. Biosci. 47, 25 (2022).
- <sup>141</sup>P. Ditlevsen and S. Ditlevsen, "Warning of a forthcoming collapse of the Atlantic meridional overturning circulation," Nat. Commun. 14, 1–12 (2023).
- <span id="page-10-0"></span><sup>142</sup>R. Mathevet, P. Marchou, C. Fabre, N. Lamrani, and N. Combe, "Coriolis acceleration and critical slowing-down: A quantitative laboratory experiment," Am. J. Physics 92, 100–107 (2024).
- <span id="page-10-1"></span><sup>143</sup>P. D. Ditlevsen and S. J. Johnsen, "Tipping points: early warning and wishful thinking," Geophys. Res. Lett. 37, L19703 (2010).
- <sup>144</sup>C. Boettiger and A. Hastings, "Early warning signals and the prosecutor's fallacy," Proc Roy Soc. B: Biol. Sci. 279, 4734–4739 (2012).
- <sup>145</sup>C. Boettiger and A. Hastings, "No early warning signals for stochastic transitions: insights from large deviation theory," Proc. Roy. Soc. B: Biol. Sci. 280, 20131372 (2013).
- <sup>146</sup>C. Boettiger, N. Ross, and A. Hastings, "Early warning signals: the charted and uncharted territories," Theor. Ecol. 6[, 255–264 \(2013\).](http://dx.doi.org/ 10.1007/s12080-013-0192-6)
- <sup>147</sup>S. Kéfi, V. Dakos, M. Scheffer, E. H. Van Nes, and M. Rietkerk, "Early warning signals also precede non-catastrophic transitions," Oikos 122, 641–648 (2013).
- <sup>148</sup>V. Guttal, C. Jayaprakash, and O. P. Tabbaa, "Robustness of early warning signals of regime shifts in time-delayed ecological models," [Theor. Ecol.](http://dx.doi.org/10.1007/s12080-013-0194-4) 6[, 271–283 \(2013\).](http://dx.doi.org/10.1007/s12080-013-0194-4)
- <sup>149</sup>V. Dakos, S. R. Carpenter, E. H. van Nes, and M. Scheffer, "Resilience indicators: prospects and limitations for early warnings of regime shifts," [Phil. Trans. R. Soc. B: Biol. Sci.](http://dx.doi.org/10.1098/rstb.2013.0263) 370, 20130263 (2015).
- <sup>150</sup>L. Dai, K. S. Korolev, and J. Gore, "Relation between stability and resilience determines the performance of early warning signals under different environmental drivers," Proc. Natl. Acad. Sci. U.S.A. 112, 10056– 10061 (2015).
- <sup>151</sup>C. Diks, C. Hommes, and J. Wang, "Critical slowing down as an early warning signal for financial crises?" [Empirical Economics , 1–28 \(2015\).](http://dx.doi.org/ https://doi.org/10.1007/s00181-018-1527-3)
- <sup>152</sup>T. J. Wagner and I. Eisenman, "False alarms: How early warning signals falsely predict abrupt sea ice loss," Geophys. Res. Lett. 42, 10–333 (2015).
- <span id="page-10-17"></span><sup>153</sup>X. Zhang, C. Kuehn, and S. Hallerberg, "Predictability of critical transitions," Phys. Rev. E 92[, 052905 \(2015\).](http://dx.doi.org/10.1103/PhysRevE.92.052905)
- <sup>154</sup>V. Guttal, S. Raghavendra, N. Goel, and Q. Hoarau, "Lack of critical slowing down suggests that financial meltdowns are not critical transitions, yet rising variability could signal systemic risk," PloS one 11, e0144198 (2016).
- <sup>155</sup>A. S. Gsell, U. Scharfenberger, D. Özkundakci, A. Walters, L.-A. Hansson, A. B. Janssen, P. Nõges, P. C. Reid, D. E. Schindler, E. Van Donk, *et al.*, "Evaluating early-warning indicators of critical transitions in natural aquatic ecosystems," Proc. Natl. Acad. Sci.. 113, E8089–E8095 (2016).
- <sup>156</sup>P. Milanowski and P. Suffczynski, "Seizures start without common signatures of critical transition," Int. J. Neural Syst. 26, 1650053 (2016).
- <sup>157</sup>P. S. Dutta, Y. Sharma, and K. C. Abbott, "Robustness of early warning signals for catastrophic and non-catastrophic transitions," Oikos 127, 1251–1263 (2018).
- <sup>158</sup>H. Wen, M. P. Ciamarra, and S. A. Cheong, "How one might miss early warning signals of critical transitions in time series data: A systematic study of two major currency pairs," PloS one 13, e0191439 (2018).
- <sup>159</sup>F. Romano and C. Kuehn, "Analysis and predictability of tipping points with leading-order nonlinear term," Int. J. Bifurcation Chaos 28, 1850103 (2018).
- <sup>160</sup>R. Arumugam, S. Sarkar, T. Banerjee, S. Sinha, and P. S. Dutta, "Dynamic environment-induced multistability and critical transition in a metacommunity ecosystem," Phys. Rev. E 99[, 032216 \(2019\).](http://dx.doi.org/ 10.1103/PhysRevE.99.032216)
- <sup>161</sup>C. F. Clements, M. A. McCarthy, and J. L. Blanchard, "Early warning signals of recovery in complex systems," Nat. Commun. 10, 1681 (2019).
- <span id="page-10-20"></span><sup>162</sup>H. Gatfaoui and P. De Peretti, "Flickering in information spreading precedes critical transitions in financial markets," Sci. Rep. 9, 5671 (2019).
- <sup>163</sup>G. Jäger and M. Füllsack, "Systematically false positives in early warning signal analysis," PloS one 14, e0211072 (2019).
- <sup>164</sup>T. Wilkat, T. Rings, and K. Lehnertz, "No evidence for critical slowing down prior to human epileptic seizures," Chaos 29, 091104 (2019).
- <sup>165</sup>M. Marconi, C. Métayer, A. Acquaviva, J. Boyer, A. Gomel, T. Quiniou, C. Masoller, M. Giudici, and J. Tredicce, "Testing critical slowing down as a bifurcation indicator in a low-dissipation dynamical system," Phys. Rev. Lett. 125, 134102 (2020).
- <sup>166</sup>B. van der Bolt, E. H. van Nes, and M. Scheffer, "No warning for slow transitions," J. Roy. Soc. Interface 18, 20200935 (2021).
- <sup>167</sup>M. Lapeyrolerie and C. Boettiger, "Limits to ecological forecasting: Estimating uncertainty for critical transitions with deep learning," Methods Ecol. Evol 14, 785–798 (2023).
- <sup>168</sup>D. A. O'Brien, S. Deb, G. Gal, S. J. Thackeray, P. S. Dutta, S.-i. S. Matsuzaki, L. May, and C. F. Clements, "Early warning signals have limited applicability to empirical lake data," Nat. Commun. 14, 7942 (2023).
- <span id="page-10-2"></span><sup>169</sup>D. Proverbio, A. Skupin, and J. Gonçalves, "Systematic analysis and optimization of early warning signals for critical transitions using distribution data," iScience 26, 107156 (2023).
- <span id="page-10-3"></span><sup>170</sup>C. Grebogi, E. Ott, and J. A. Yorke, "Crises, sudden changes in chaotic attractors, and transient chaos," Physica D 7, 181–200 (1983).
- <span id="page-10-4"></span>171H. M. Osinga and U. Feudel, "Boundary crisis in quasiperiodically forced systems," Physica D: Nonlinear Phenomena 141, 54–64 (2000).
- <span id="page-10-5"></span><sup>172</sup>E. Ott and J. C. Summerer, "Blowout bifurcations: the occurence of riddled basins and on-off intermittency," Phys. Lett. A 188, 39–47 (1994).
- <span id="page-10-6"></span><sup>173</sup>Y. Zhang, Z. G. Nicolaou, J. D. Hart, R. Roy, and A. E. Motter, "Critical switching in globally attractive chimeras," Phys. Rev. X 10, 011044 (2020).
- <span id="page-10-7"></span><sup>174</sup>C. Kuehn, G. Zschaler, and T. Gross, "Early warning signs for saddleescape transitions in complex networks," Sci. Rep. 5, 13190 (2015).
- <span id="page-10-8"></span><sup>175</sup>A. Koseska, E. Volkov, and J. Kurths, "Oscillation quenching mechanisms: Amplitude vs. oscillation death," Phys. Rep. 531[, 173 – 199 \(2013\).](http://dx.doi.org/ 10.1016/j.physrep.2013.06.001)
- <span id="page-10-9"></span><sup>176</sup>W. Zou, D. Senthilkumar, M. Zhan, and J. Kurths, "Quenching, aging, and reviving in coupled dynamical networks," Phys. Rep. 931, 1–72 (2021).
- <span id="page-10-10"></span><sup>177</sup>S. Boccaletti, J. Almendral, S. Guan, I. Leyva, Z. Liu, I. Sendiña-Nadal, Z. Wang, and Y. Zou, "Explosive transitions in complex networks' structure and dynamics: Percolation and synchronization," Phys. Rep. 660, 1– 94 (2016).
- <span id="page-10-11"></span><sup>178</sup>C. Kuehn and C. Bick, "A universal route to explosive phenomena," Sci. Adv. 7, eabe3824 (2021).
- <span id="page-10-12"></span><sup>179</sup>F. Mormann, R. Andrzejak, T. Kreuz, C. Rieke, P. David, C. E. Elger, and K. Lehnertz, "Automated detection of a preseizure state based on a decrease in synchronization in intracranial electroencephalogram recordings from epilepsy patients," Phys. Rev. E 67[, 021912 \(2003\).](http://dx.doi.org/10.1103/PhysRevE.67.021912)
- <span id="page-10-18"></span><sup>180</sup>F. Mormann, T. Kreuz, C. Rieke, R. G. Andrzejak, A. Kraskov, P. David, C. E. Elger, and K. Lehnertz, "On the predictability of epileptic seizures," [Clin. Neurophysiol.](http://dx.doi.org/ 10.1016/j.clinph.2004.08.025) 116, 569–587 (2005).
- <sup>181</sup>M. Winterhalder, B. Schelter, T. Maiwald, A. Brandt, A. Schad, A. Schulze-Bonhage, and J. Timmer, "Spatio-temporal patient-individual assessment of synchronization changes for epileptic seizure prediction," Clin. Neurophysiol. 117, 2399–2413 (2006).
- <span id="page-10-13"></span><sup>182</sup>L. Kuhlmann, D. Freestone, A. L. Lai, A. N. Burkitt, K. Fuller, D. Grayden, L. Seiderer, S. Vogrin, I. M. Y. Mareels, and M. J. Cook, "Patientspecific bivariate-synchrony-based seizure prediction for short prediction horizons," Epilepsy Res. 91[, 214–231 \(2010\).](http://dx.doi.org/10.1016/j.eplepsyres.2010.07.014)
- <span id="page-10-14"></span><sup>183</sup>A. Ray, "Symbolic dynamic analysis of complex systems for anomaly detection," Signal Process. 84, 1115–1130 (2004).
- <sup>184</sup>S. C. Chin, A. Ray, and V. Rajagopalan, "Symbolic time series analysis for anomaly detection: A comparative evaluation," Signal Process. 85, 1859– 1868 (2005).
- <span id="page-10-15"></span><sup>185</sup>K. Lehnertz and H. Dickten, "Assessing directionality and strength of coupling through symbolic analysis: an application to epilepsy patients," [Phil.](http://dx.doi.org/10.1098/rsta.2014.0094) Trans. R. Soc. A 373[, 20140094 \(2015\).](http://dx.doi.org/10.1098/rsta.2014.0094)
- <span id="page-10-16"></span><sup>186</sup>R. Liu, P. Chen, K. Aihara, and L. Chen, "Identifying early-warning signals of critical transitions with strong noise by dynamical network markers," Sci. Rep. 5, 17501 (2015).
- <sup>187</sup>X. Peng, M. Small, Y. Zhao, and J. M. Moore, "Detecting and predicting tipping points," Int. J. Bifurcation Chaos 29, 1930022 (2019).
- <sup>188</sup>T. Rings, M. Mazarei, A. Akhshi, C. Geier, M. R. R. Tabar, and K. Lehnertz, "Traceability and dynamical resistance of precursor of extreme events," Sci. Rep. 9, 1744 (2019).
- <sup>189</sup>T. Rings, R. von Wrede, and K. Lehnertz, "Precursors of seizures due to specific spatial-temporal modifications of evolving large-scale epileptic brain networks," Sci. Rep. 9, 10623 (2019).
- <span id="page-11-0"></span><sup>190</sup>J. Ludescher, M. Martin, N. Boers, A. Bunde, C. Ciemer, J. Fan, S. Havlin, M. Kretschmer, J. Kurths, J. Runge, *et al.*, "Network-based forecasting of climate phenomena," Proc. Natl. Acad. Sci. 118, e1922872118 (2021).
- <span id="page-11-1"></span><sup>191</sup>K. Mittal and S. Gupta, "Topological characterization and early detection of bifurcations and chaos in complex systems using persistent homology," Chaos: An Interdisciplinary Journal of Nonlinear Science 27, 051102 (2017).
- $192$ S. M. S. Syed Musa, M. S. Md Noorani, F. Abdul Razak, M. Ismail, M. A. Alias, and S. I. Hussain, "Using persistent homology as preprocessing of early warning signals for critical transition in flood," Sci. Rep. 11, 7234 (2021).
- <span id="page-11-2"></span><sup>193</sup>M. Ghil and D. Sciamarella, "Dynamical systems, algebraic topology and the climate sciences," Nonlin. Proc. Geophys. 30, 399–434 (2023).
- <span id="page-11-3"></span><sup>194</sup>R. Giacomini and B. Rossi, "Detecting and predicting forecast breakdowns," Rev. Econ. Stud. 76, 669–705 (2009).
- <span id="page-11-4"></span><sup>195</sup>P. F. Ghalati, S. S. Samal, J. S. Bhat, R. Deisz, G. Marx, and A. Schuppert, "Critical transitions in intensive care units: a sepsis case study," Sci. Rep. 9, 12888 (2019).
- <span id="page-11-5"></span><sup>196</sup>R. Liu, M. Li, Z.-P. Liu, J. Wu, L. Chen, and K. Aihara, "Identifying critical transitions and their leading biomolecular networks in complex diseases," Sci. Rep. 2, 813 (2012).
- <sup>197</sup>J. Meng, J. Fan, J. Ludescher, A. Agarwal, X. Chen, A. Bunde, J. Kurths, and H. J. Schellnhuber, "Complexity-based approach for El Niño magnitude forecasting before the spring predictability barrier," Proc. Nat. Acad. Sci. 117, 177–183 (2020).
- <sup>198</sup>I. Pavithran, V. R. Unni, and R. Sujith, "Critical transitions and their early warning signals in thermoacoustic systems," Eur. Phys. J. Spec. Top. 230, 3411–3432 (2021).
- <sup>199</sup>G. Tirabassi and C. Masoller, "Entropy-based early detection of critical transitions in spatial vegetation fields," Proc. Natl. Acad. Sci. 120, e2215667120 (2023).
- <span id="page-11-6"></span><sup>200</sup>S. Deb and P. S. Dutta, "Critical transitions in spatial systems induced by ornstein–uhlenbeck noise: spatial mutual information as a precursor," [Proc. R. Soc. A.: Mathematical, Physical and Engineering Sciences](http://dx.doi.org/ 10.1098/rspa.2023.0594) 480, [20230594 \(2024\).](http://dx.doi.org/ 10.1098/rspa.2023.0594)
- <span id="page-11-7"></span><sup>201</sup>E. Barter, A. Brechtel, B. Drossel, and T. Gross, "A closed form for jacobian reconstruction from time series and its application as an early warning signal in network dynamics," Proc. Roy. Soc. A 477, 20200742 (2021).
- <span id="page-11-8"></span> $202$ C. L. Franzke, "Predictions of critical transitions with non-stationary reduced order models," Physica D: Nonlinear Phenomena 262, 35–47 (2013).
- <sup>203</sup>F. Kwasniok, "Predicting critical transitions in dynamical systems from time series using nonstationary probability density modeling," Phys. Rev. E 88, 052917 (2013).
- <sup>204</sup>F. Kwasniok, "Forecasting critical transitions using data-driven nonstationary dynamical modeling," Phys. Rev. E 92, 062928 (2015).
- <sup>205</sup>F. Kwasniok, "Detecting, anticipating, and predicting critical transitions in spatially extended systems," Chaos: An Interdisciplinary Journal of Nonlinear Science 28, 033614 (2018).
- <span id="page-11-9"></span><sup>206</sup>A. Din, J. Liang, and T. Zhou, "Detecting critical transitions in the case of moderate or strong noise by binomial moments," Phys. Rev. E 98, 012114 (2018).
- <span id="page-11-10"></span><sup>207</sup>K. Lehnertz, L. Zabawa, and M. R. R. Tabar, "Characterizing abrupt transitions in stochastic dynamics," New J. Physics 20, 113043 (2018).
- <sup>208</sup>B. M. Arani, S. R. Carpenter, L. Lahti, E. H. Van Nes, and M. Scheffer, "Exit time as a measure of ecological resilience," Science 372, eaay4895 (2021).
- <span id="page-11-14"></span><sup>209</sup>M. Heßler and O. Kamps, "Bayesian on-line anticipation of critical transitions," New J. Phys. 24, 063021 (2022).
- <span id="page-11-11"></span><sup>210</sup>M. Heßler and O. Kamps, "Quantifying resilience and the risk of regime shifts under strong correlated noise," PNAS nexus 2, pgac296 (2023).
- <span id="page-11-12"></span><sup>211</sup>S. H. Lim, L. Theo Giorgini, W. Moon, and J. S. Wettlaufer, "Predicting critical transitions in multiscale dynamical systems using reservoir computing," Chaos: An Interdisciplinary Journal of Nonlinear Science 30,

123126 (2020).

- <sup>212</sup>L.-W. Kong, H.-W. Fan, C. Grebogi, and Y.-C. Lai, "Machine learning prediction of critical transition and system collapse," Phys. Rev. Res. 3, 013090 (2021).
- <sup>213</sup>A. Ray, T. Chakraborty, and D. Ghosh, "Optimized ensemble deep learning framework for scalable forecasting of dynamics containing extreme events," Chaos: An Interdisciplinary Journal of Nonlinear Science 31, 111105 (2021).
- <sup>214</sup>D. Patel, D. Canaday, M. Girvan, A. Pomerance, and E. Ott, "Using machine learning to predict statistical properties of non-stationary dynamical processes: System climate, regime transitions, and the effect of stochasticity," Chaos: An Interdisciplinary Journal of Nonlinear Science 31, 033149 (2021).
- <sup>215</sup>D. Patel and E. Ott, "Using machine learning to anticipate tipping points and extrapolate to post-tipping dynamics of non-stationary dynamical systems," Chaos: An Interdisciplinary Journal of Nonlinear Science 33, 023143 (2023).
- <span id="page-11-13"></span><sup>216</sup>D. Köglmayr and C. Räth, "Extrapolating tipping points and simulating non-stationary dynamics of complex systems using efficient machine learning," Sci. Rep. 14, 507 (2024).
- <span id="page-11-15"></span><sup>217</sup>R. Shcherbakov, J. Zhuang, G. Zöller, and Y. Ogata, "Forecasting the magnitude of the largest expected earthquake," Nat. Commun. 10, 4051 (2019).
- <span id="page-11-16"></span><sup>218</sup>K. Lehnertz and C. E. Elger, "Can epileptic seizures be predicted? Evidence from nonlinear time series analysis of brain electrical activity," Phys. Rev. Lett. 80, 5019–5023 (1998).
- <sup>219</sup>R. Streeter and A. J. Dugmore, "Anticipating land surface change," Proc. Natl. Acad. Sci.. 110, 5779–5784 (2013).
- <sup>220</sup>S. Bialonski, G. Ansmann, and H. Kantz, "Data-driven prediction and prevention of extreme events in a spatially extended excitable system," Phys. Rev. E 92[, 042910 \(2015\).](http://dx.doi.org/10.1103/PhysRevE.92.042910)
- <span id="page-11-17"></span><sup>221</sup>F. Grziwotz, C.-W. Chang, V. Dakos, E. H. van Nes, M. Schwarzländer, O. Kamps, M. Heßler, I. T. Tokuda, A. Telschow, and C.-h. Hsieh, "Anticipating the occurrence and type of critical transitions," Sci. Adv. 9, eabq4558 (2023).
- <span id="page-11-18"></span><sup>222</sup>D. J. Benjamin, J. O. Berger, M. Johannesson, B. A. Nosek, E.-J. Wagenmakers, R. Berk, K. A. Bollen, B. Brembs, L. Brown, C. Camerer, *et al.*, "Redefine statistical significance," Nat. Hum. Behav. 2, 6–10 (2018).
- <span id="page-11-19"></span><sup>223</sup>K. Lehnertz, T. Rings, and T. Bröhl, "Time in brain: How biological rhythms impact on EEG signals and on EEG-derived brain networks," Front. Netw. Physiol. 1, 755016 (2021).
- <span id="page-11-20"></span><sup>224</sup>R. Dahlhaus and M. H. Neumann, "Locally adaptive fitting of semiparametric models to nonstationary time series," Stoch. Process. Their Appl. 91, 277–308 (2001).
- <span id="page-11-21"></span><sup>225</sup>E. Carlstein, "Nonparametric change-point estimation," Ann. Stat. 16, 188–197 (1988).
- <sup>226</sup>M. Basseville, I. V. Nikiforov, *et al.*, *Detection of abrupt changes: theory and application*, Vol. 104 (Prentice Hall, Englewood Cliffs, NJ, USA, 1993).
- <sup>227</sup>S. Aminikhanghahi and D. J. Cook, "A survey of methods for time series change point detection," Knowl. Inf. Syst. 51, 339–367 (2017).
- <sup>228</sup>J. Cabrieto, F. Tuerlinckx, P. Kuppens, M. Grassmann, and E. Ceulemans, "Detecting correlation changes in multivariate time series: A comparison of four non-parametric change point detection methods," Behav. Res. Methods 49, 988–1005 (2017).
- <sup>229</sup>J. Cabrieto, F. Tuerlinckx, P. Kuppens, B. Hunyadi, and E. Ceulemans, "Testing for the presence of correlation changes in a multivariate time series: A permutation based approach," Sci. Rep. 8, 769 (2018).
- <span id="page-11-23"></span> $230$ C. Truong, L. Oudre, and N. Vayatis, "Selective review of offline change point detection methods," Signal Process. 167, 107299 (2020).
- <sup>231</sup>W. Bagniewski and M. Ghil, "Automatic detection of abrupt transitions in paleoclimate records," Chaos: An Interdisciplinary Journal of Nonlinear Science 31, 113129 (2021).
- <span id="page-11-25"></span><sup>232</sup>T. M. Bury, R. Sujith, I. Pavithran, M. Scheffer, T. M. Lenton, M. Anand, and C. T. Bauch, "Deep learning for early warning signals of tipping points," Proc. Natl. Acad. Sci. 118, e2106140118 (2021).
- <span id="page-11-22"></span><sup>233</sup>L. J. Gilarranz, A. Narwani, D. Odermatt, R. Siber, and V. Dakos, "Regime shifts, trends, and variability of lake productivity at a global scale," Proc. Natl. Acad. Sci. 119, e2116413119 (2022).
- <span id="page-11-24"></span><sup>234</sup>T. De Ryck, M. De Vos, and A. Bertrand, "Change point detection in time series data using autoencoders with a time-invariant representation," IEEE

Trans. Sig. Proc. 69, 3513–3524 (2021).

- <span id="page-12-0"></span><sup>235</sup>C. Boettiger and A. Hastings, "Quantifying limits to detection of early warning for critical transitions," J. Roy. Soc. Interface 9, 2527–2539 (2012).
- <span id="page-12-1"></span><sup>236</sup>A. Bunde, J. Ludescher, and H. J. Schellnhuber, "How to determine the statistical significance of trends in seasonal records: application to Antarctic temperatures," Clim. Dyn. 58, 1349–1361 (2022).
- <span id="page-12-2"></span><sup>237</sup>W. W. Daniel, *Applied nonparametric statistics (revised ed.)* (Duxbury, Pacific Grove, CA, USA, 2000).
- <span id="page-12-3"></span><sup>238</sup>A. Kolmogorov, "Sulla determinazione empirica di una legge didistribuzione," Giorn Dell'inst Ital Degli Att 4, 89–91 (1933).
- <span id="page-12-4"></span><sup>239</sup>H. B. Mann and D. R. Whitney, "On a test of whether one of two random variables is stochastically larger than the other," [Ann. Math. Stat.](http://dx.doi.org/10.0.4.190/aoms/1177730491) 18, 50– [60 \(1947\).](http://dx.doi.org/10.0.4.190/aoms/1177730491)
- <span id="page-12-5"></span><sup>240</sup>J. Yerushalmy, "Statistical problems in assessing methods of medical diagnosis, with special reference to x-ray techniques," Public Health Rep. (1896-1970) , 1432–1449 (1947).
- <span id="page-12-6"></span><sup>241</sup>T. Fawcett, "An introduction to ROC analysis," [Pattern Recogn. Lett.](http://dx.doi.org/ 10.1016/j.patrec.2005.10.010) 27, [861–874 \(2006\).](http://dx.doi.org/ 10.1016/j.patrec.2005.10.010)
- <span id="page-12-7"></span><sup>242</sup>J. P. Egan, *Signal detection theory and ROC-analysis* (Academic Press, Cambridge, MA, USA, 1975).
- <span id="page-12-8"></span><sup>243</sup>J. M. Drake, "Early warning signals of stochastic switching," Proc. Roy. Soc. B: Biological Sciences 280, 20130686 (2013).
- <sup>244</sup>B. H. Brinkmann, J. Wagenaar, D. Abbot, P. Adkins, S. C. Bosshard, M. Chen, Q. M. Tieng, J. He, F. J. Muñoz-Almaraz, P. Botella-Rocamora, J. Pardo, F. Zamora-Martinez, M. Hills, W. Wu, I. Korshunova, W. Cukierski, C. Vite, E. E. Patterson, B. Litt, and G. A. Worrell, "Crowdsourcing reproducible seizure forecasting in human and canine epilepsy," [Brain](http://dx.doi.org/10.1093/brain/aww045) 139, [1713–1722 \(2016\).](http://dx.doi.org/10.1093/brain/aww045)
- <sup>245</sup>M. Cavaliere, G. Yang, V. Danos, and V. Dakos, "Detecting the collapse of cooperation in evolving networks," Sci. Rep. 6, 30845 (2016).
- <sup>246</sup>L. Kuhlmann, P. Karoly, D. R. Freestone, B. H. Brinkmann, A. Temko, A. Barachant, F. Li, G. Titericz Jr, B. W. Lang, D. Lavery, *et al.*, "Epilepsyecosystem. org: crowd-sourcing reproducible seizure prediction with long-term human intracranial EEG," Brain 141, 2619–2630 (2018).
- <sup>247</sup>B. Yang, M. Li, W. Tang, W. Liu, S. Zhang, L. Chen, and J. Xia, "Dynamic network biomarker indicates pulmonary metastasis at the tipping point of hepatocellular carcinoma," Nat. Commun. 9, 678 (2018).
- <sup>248</sup>T. Brett, M. Ajelli, Q.-H. Liu, M. G. Krauland, J. J. Grefenstette, W. G. van Panhuis, A. Vespignani, J. M. Drake, and P. Rohani, "Detecting critical slowing down in high-dimensional epidemiological systems," PLoS Comput. Biol. 16, e1007679 (2020).
- <sup>249</sup>A. T. Tredennick, E. B. O'Dea, M. J. Ferrari, A. W. Park, P. Rohani, and J. M. Drake, "Anticipating infectious disease re-emergence and elimination: a test of early warning signals using empirically based models," J. Roy. Soc. Interface 19, 20220123 (2022).
- <sup>250</sup>D. Dylewsky, T. M. Lenton, M. Scheffer, T. M. Bury, C. G. Fletcher, M. Anand, and C. T. Bauch, "Universal early warning signals of phase transitions in climate systems," J. Roy. Soc. Interface 20, 20220562 (2023).
- <span id="page-12-9"></span><sup>251</sup>L. Gómez-Nava, R. T. Lange, P. P. Klamser, J. Lukas, L. Arias-Rodriguez, D. Bierbach, J. Krause, H. Sprekeler, and P. Romanczuk, "Fish shoals resemble a stochastic excitable system driven by environmental perturbations," Nat. Phys. 19, 663–669 (2023).
- <span id="page-12-10"></span><sup>252</sup>G. M. Weiss, "Mining with rarity: a unifying framework," ACM Sigkdd Explorations Newsletter 6, 7–19 (2004).
- <span id="page-12-29"></span><sup>253</sup>Z. Ben Bouallègue and D. S. Richardson, "On the ROC area of ensemble forecasts for rare events," Weather and Forecasting 37, 787–796 (2022).
- <span id="page-12-11"></span><sup>254</sup>J. West, Z. D. Bozorgi, J. Herron, H. J. Chizeck, J. D. Chambers, and L. Li, "Machine learning seizure prediction: one problematic but accepted practice," J. Neural Eng. 20, 016008 (2023).
- <span id="page-12-12"></span><sup>255</sup>F. Mormann, R. Andrzejak, C. E. Elger, and K. Lehnertz, "Seizure prediction: the long and winding road," Brain 130[, 314–333 \(2007\).](http://dx.doi.org/10.1093/brain/awl241)
- <span id="page-12-13"></span><sup>256</sup>L. Kuhlmann, K. Lehnertz, M. P. Richardson, B. Schelter, and H. P. Zaveri, "Seizure prediction – ready for a new era," Nat. Rev. Neurol. 14, 618–630 (2018).
- <span id="page-12-14"></span><sup>257</sup>M. Winterhalder, T. Maiwald, H. U. Voss, R. Aschenbrenner-Scheibe, J. Timmer, and A. Schulze-Bonhage, "The seizure prediction characteristic: A general framework to assess and compare seizure prediction methods," Epilepsy Behav. 3, 318–325 (2003).
- <sup>258</sup>B. Schelter, M. Winterhalder, T. Maiwald, A. Brandt, A. Schad, A. Schulze-Bonhage, and J. Timmer, "Testing statistical significance of multivariate time series analysis techniques for epileptic seizure prediction," Chaos 16, 013108 (2006).
- <sup>259</sup>H. Feldwisch-Drentrup, M. Staniek, A. Schulze-Bonhage, J. Timmer, H. Dickten, C. E. Elger, B. Schelter, and K. Lehnertz, "Identification of preseizure states in epilepsy: A data-driven approach for multichannel EEG recordings," [Front. Comput. Neurosci.](http://dx.doi.org/ 10.3389/fncom.2011.00032) 5, 32 (2011).
- <span id="page-12-15"></span><sup>260</sup>M. Mader, W. Mader, B. J. Gluckman, J. Timmer, and B. Schelter, "Statistical evaluation of forecasts," Phys. Rev. E 90, 022133 (2014).
- <span id="page-12-16"></span><sup>261</sup>B. Efron, *[The Jackknife, the Bootstrap and Other Resampling Plans](http://dx.doi.org/10.1137/1.9781611970319)* (Society for Industrial and Applied Mathematics, Philadelphia, PA, USA, 1982).
- <span id="page-12-17"></span><sup>262</sup>B. Efron and R. J. Tibshirani, *An Introduction to the Bootstrap* (Chapman & Hall/CRC, Boca Raton, London, New York, Washington DC, 1998) p. 436.
- <span id="page-12-18"></span><sup>263</sup>T. Schreiber and A. Schmitz, "Surrogate time series," [Physica D](http://dx.doi.org/10.1016/S0167-2789(00)00043-9) 142, 346– [382 \(2000\).](http://dx.doi.org/10.1016/S0167-2789(00)00043-9)
- <sup>264</sup>J. Lucio, R. Valdés, and L. Rodríguez, "Improvements to surrogate data methods for nonstationary time series," Phys. Rev. E 85, 056202 (2012).
- <span id="page-12-19"></span><sup>265</sup>G. Lancaster, D. Iatsenko, A. Pidde, V. Ticcinelli, and A. Stefanovska, "Surrogate data for hypothesis testing of physical systems," Phys. Rep. 748, 1–60 (2018).
- <span id="page-12-20"></span><sup>266</sup>G. Ansmann and K. Lehnertz, "Constrained randomization of weighted networks," Phys. Rev. E 84[, 026103 \(2011\).](http://dx.doi.org/ 10.1103/PhysRevE.84.026103)
- <sup>267</sup>G. Ansmann and K. Lehnertz, "Surrogate-assisted analysis of weighted functional brain networks," [J. Neurosci. Methods](http://dx.doi.org/10.1016/j.jneumeth.2012.05.008) 208, 165–172 (2012).
- <sup>268</sup>S. Bialonski, "Inferring complex networks from time series of dynamical systems: Pitfalls, misinterpretations, and possible solutions," [arXiv](http://arxiv.org/abs/1208.0800) [1208.0800](http://arxiv.org/abs/1208.0800) (2012).
- <sup>269</sup>I. Laut and C. Räth, "Surrogate-assisted network analysis of nonlinear time series," Chaos 26[, 103108 \(2016\).](http://dx.doi.org/10.1063/1.4964646)
- <sup>270</sup>M. Wiedermann, J. F. Donges, J. Kurths, and R. V. Donner, "Spatial network surrogates for disentangling complex system structure from spatial embedding of nodes," Phys. Rev. E 93[, 042308 \(2016\).](http://dx.doi.org/10.1103/PhysRevE.93.042308)
- <sup>271</sup>K. Stahn and K. Lehnertz, "Surrogate-assisted identification of influences of network construction on evolving weighted functional networks," Chaos 27, 123106 (2017).
- <span id="page-12-21"></span><sup>272</sup>D. Chorozoglou and D. Kugiumtzis, "Testing the randomness of correlation networks from multivariate time series," J. Complex Netw. 7, 190–209 (2019).
- <span id="page-12-22"></span><sup>273</sup>R. G. Andrzejak, F. Mormann, T. Kreuz, C. Rieke, A. Kraskov, C. E. Elger, and K. Lehnertz, "Testing the null hypothesis of the nonexistence of a preseizure state," Phys. Rev. E 67, 010901(R) (2003).
- <span id="page-12-23"></span><sup>274</sup>T. Kreuz, R. G. Andrzejak, F. Mormann, A. Kraskov, H. Stögbauer, C. E. Elger, K. Lehnertz, and P. Grassberger, "Measure profile surrogates: A method to validate the performance of epileptic seizure prediction algorithms," Phys. Rev. E 69, 061915 (2004).
- <span id="page-12-24"></span><sup>275</sup>D. Bertsimas and J. Tsitsiklis, "Simulated annealing," Stat. Sci. 8, 10–15 (1993).
- <span id="page-12-25"></span><sup>276</sup>M. A. Kramer, W. Truccolo, U. T. Eden, K. Q. Lepage, L. R. Hochberg, E. N. Eskandar, J. R. Madsen, J. W. Lee, A. Maheshwari, E. Halgren, C. J. Chu, and S. S. Cash, "Human seizures self-terminate across spatial scales via a critical transition," [Proc. Natl. Acad. Sci. U.S.A.](http://dx.doi.org/10.1073/pnas.1210047110) 109, 21116–21121 [\(2012\).](http://dx.doi.org/10.1073/pnas.1210047110)
- $277$ C. Boettner and N. Boers, "Critical slowing down in dynamical systems driven by nonstationary correlated noise," Phys. Rev. Res. 4, 013230 (2022).
- <sup>278</sup>S. Chen, A. Ghadami, and B. I. Epureanu, "Practical guide to using Kendall's  $\tau$  in the context of forecasting critical transitions," Roy. Soc. Open Sci. 9, 211346 (2022).
- $279$ K. Pal, S. Deb, and P. S. Dutta, "Tipping points in spatial ecosystems driven by short-range correlated noise," Phys. Rev. E 106, 054412 (2022).
- <span id="page-12-26"></span><sup>280</sup>N. Bochow and N. Boers, "The South American monsoon approaches a critical transition in response to deforestation," Sci. Adv. 9, eadd9973 (2023).
- <span id="page-12-27"></span><sup>281</sup>G. Shmueli, "To explain or to predict?" Stat. Sci. **25**, 289-310 (2010).
- <span id="page-12-28"></span><sup>282</sup>M. J. Cook, T. J. O'Brien, S. F. Berkovic, M. Murphy, A. Morokoff, G. Fabinyi, W. D'Souza, R. Yerra, J. Archer, L. Litewka, S. Hosking,
	- P. Lightfoot, V. Ruedebusch, W. D. Sheffield, D. Snyder, K. Leyde, and
	- D. Himes, "Prediction of seizure likelihood with a long-term, implanted

seizure advisory system in patients with drug-resistant epilepsy: a first-inman study," Lancet Neurol. 12[, 563–571 \(2013\).](http://dx.doi.org/ 10.1016/S1474-4422(13)70075-9)

- <span id="page-13-0"></span><sup>283</sup>J. Ludescher, A. Bunde, and H. J. Schellnhuber, "Forecasting the El Niño type well before the spring predictability barrier," npj Clim. Atmos. Sci. 6, 196 (2023).
- <span id="page-13-1"></span><sup>284</sup>T. Gneiting and M. Katzfuss, "Probabilistic forecasting," Annu. Rev. Stat. Appl. 1, 125–151 (2014).
- <span id="page-13-2"></span><sup>285</sup>L. J. Tashman, "Out-of-sample tests of forecasting accuracy: an analysis and review," Int. J. Forecast. 16, 437–450 (2000).
- <span id="page-13-3"></span><sup>286</sup>T. Gneiting, F. Balabdaoui, and A. E. Raftery, "Probabilistic forecasts, calibration and sharpness," J. R. Stat. Soc., B: Stat. Methodol. 69, 243– 268 (2007).
- <sup>287</sup>T. Gneiting, "Making and evaluating point forecasts," J. Am. Stat. Assoc. 106, 746–762 (2011).
- <sup>288</sup>S. Lerch, T. L. Thorarinsdottir, F. Ravazzolo, and T. Gneiting, "Forecaster's dilemma: extreme events and forecast evaluation," Statist. Sci. 32, 106–127 (2017).
- <span id="page-13-4"></span><sup>289</sup>T. Gneiting, D. Wolffram, J. Resin, K. Kraus, J. Bracher, T. Dimitriadis, V. Hagenmeyer, A. I. Jordan, S. Lerch, K. Phipps, *et al.*, "Model diagnostics and forecast evaluation for quantiles," Annu. Rev. Stat. Appl. 10, 597–621 (2023).
- <span id="page-13-5"></span><sup>290</sup>J. O. Berger and L. A. Smith, "On the statistical formalism of uncertainty quantification," Annu. Rev. Stat. Appl. 6, 433–460 (2019).