Flow of Reasoning: Efficient Training of LLM Policy with Divergent Thinking

Fangxu Yu¹

Lai Jiang¹ Haoqiang Kang¹ Shibo Hao¹ Lianhui Qin^{1 2} ¹University of California, San Diego ²Allen Institute for Artificial Intelligence

Abstract

Divergent thinking, the cognitive process of generating diverse solutions, is a hallmark of human creativity and problem-solving. For machines, sampling diverse solution trajectories in complex reasoning problems is crucial for robust outcomes, data augmentation, and enhanced model generalization. Large language models (LLMs) often struggle with generating high-quality, diverse reasoning. While supervised fine-tuning helps with quality, it requires extensive supervision data to capture the full diversity of solutions. Alternatively, reinforcement learning methods like PPO aim to find limited highest-reward solutions while neglecting the solution diversity, akin to convergent thinking. To address these limitations, we propose Flow of Reasoning (FOR)—an efficient LLM training approach enabling diverse reasoning with minimal data. FOR formulates multi-step LLM reasoning as a Markovian *flow* from an initial state to terminal states. The formulation allows to adapt principled GFlowNet approaches to train the LLM as a policy, which is able to sample multiple reasoning paths with probabilities proportional to the unnormalized reward. Empirical results show that, with limited training data (e.g., 15 examples), FOR can discover diverse high-quality solutions that excel greatly beyond current state-of-the-art methods across three tasks, including embodied reasoning (BlocksWorld), math puzzle solving (Game24), and logical reasoning (PrOntoQA). Code is available at https://github.com/Yu-Fangxu/FoR.

Introduction 1

Divergent thinking is the capability to generate diverse ideas with free-flowing thought. It is crucial for human creativity and for solving complex problems that require multiple steps of reasoning. As shown in Figure 1, such problems might involve planning a sequence of block manipulation actions in embodied reasoning, composing arithmetic operations in mathematical reasoning, or connecting various pieces of knowledge within an ontology to derive answers in logical reasoning. Branching out at each intermediate reasoning step naturally leads to diverse outcome trajectories. The ability of sampling this diversity of plausible trajectories is crucial in many contexts—it enhances the robustness of outcomes by aggregating multiple solutions, aids data augmentation, and exposes models to varied scenarios, thereby improving their generalization to unseen tasks. Therefore, efficient methods for generating a variety of high-quality reasonings are essential for tackling complex reasoning problems where a single solution path may not suffice.

Progress has been made with LLMs in handling tasks requiring complex reasoning. Techniques like Chain of Thought (CoT) [1] and Tree of Thoughts (ToT) [2] enhance LLM reasoning by encouraging intermediate and branching steps. However, the success of these inference methods highly relies on the capabilities of the underlying LLM and the sophisticated decoding algorithms [3-5] to obtain diverse outputs. While Supervised Fine-Tuning (SFT) [6, 7] helps improve reasoning performance, the training often demands extensive supervision data to capture the full diversity of solutions, which



Figure 1: Multi-step LLM reasoning as a Markovian flow in three tasks: embodied reasoning in BlocksWorld, math puzzle solving in Game24, and logical reasoning in PrOntoQA. The thickness of each edge represents the "water flow", which corresponds to the unnormalized likelihood of transitioning from one state to the next. FOR learns to generate diverse, high-quality reasoning trajectories for each problem.

can be costly to label in real-world tasks. Alternatively, widely used reinforcement learning methods, such as Proximal Policy Optimization (PPO) [8], refine decision-making policy to maximize rewards. Similarly, Reasoning-via-Planning (RAP) [9] converts reasoning into a planning process at inference time, using Monte Carlo Tree Search (MCTS) to find optimal solutions. As a result, both approaches tend to focus on a limited number of high-reward solutions and overlook the solution diversity.

To address this gap, we introduce Flow of Reasoning (**FOR**), an efficient approach for training LLM policy to enable diverse reasoning. *Generative Flow Networks* (GFlowNets) [10] have been studied in different machine learning settings (e.g., molecule synthesis) to learn a diversity-seeking policy that samples reasoning paths proportionally to the unnormalized reward [11–16]. Recent work [17] uses GFlowNets to improve LLMs in text generation tasks. However, this approach focuses on token-level reward and diversity training, which is infeasible for efficiently handling complex multi-step reasoning problems that demand higher-level modeling of reasoning steps [18, 9].

In this work, we formulate multi-step LLM reasoning from a generative flow perspective (Figure 1). Each reasoning step corresponds to an intermediate state (node), forming a Markovian flow that travels step-by-step from an initial state to terminal states. This new reasoning formulation enables us to seamlessly adapt successful GFlowNet approaches to train LLM-based policy efficiently, including the trajectory balance objective to match the policy with the desired unnormalized reward for diverse reasoning, and efficient explorations (e.g., on-/off-policy and local search strategies) for efficient policy training with minimal data.

To evaluate the performance and diversity of FOR, we conduct extensive experiments on three representative tasks: embodied reasoning in BlocksWorld, math puzzle solving in Game24, and logical reasoning in PrOntoQA. Empirical results show that FOR, with limited (e.g. about 15) training examples, generates diverse, high-quality solutions, greatly outperforming supervised training methods like SFT, reward-maximizing policy optimizations such as PPO and RAP, and the popular inference-time methods CoT and ToT, with 20% - 85% improvements. Ablation studies further validate the key designs in FOR that lead to the robustness and effectiveness.

2 Related Work

Reasoning with LLM. Recent LLMs [19–22] have demonstrated great potentials in tackling complex reasoning tasks [23–27]. (1) **Fine-tuning LLMs** is a primary way to enhance their reasoning abilities, including SFT and reinforcement learning (RL) approaches. SFT with large-scale and high-quality datasets of reasoning chains has proven very effective [7, 6]. Various methods for constructing training samples have been proposed when ground truth reasoning chains are not available. For example, STaR [28] uses online sampling with self-correction to find positive samples.



training object: trajectory balance

Figure 2: Left: The forward policy $P_F(s_t|s_{t-1}; \theta, g)$ in the flow-based formulation is parameterized as LLM (Eq.5) and finetuned with the trajectory balance objective (Eq.7) to achieve the desired flow $F(s_n) = R(s_n)$ on all terminal states s_n . **Right:** FOR incorporates local search with a destroy-and-reconstruction process to augment informative trajectories in training (Section 3.2.2). This facilitates efficient exploration and improves policy learning.

ReST^{EM} [29] and V-STaR[30] filter samples with external verifiers. On the other hand, rewardmaximizing policy optimization methods such as PPO, are widely used RL techniques in LLMs [31, 21, 32]. However, both the maximum likelihood training (i.e. SFT) and reward-maximizing policy optimization (e.g., PPO) do not encourage models to generate diverse solutions. (2) Inference-time reasoning algorithms aim to better elicit the knowledge inside LLMs without tuning their parameters. Techniques such as CoT [1] and its variants [33, 34] have improved LLM performance by enabling them to generate intermediate steps before arriving at a final answer. Additionally, combining LLM reasoning capabilities with planning and search algorithms, such as the ToT [18] and RAP [9], which integrates LLMs with Breadth-First Search and MCTS, respectively, has further enhanced their performance across broad reasoning tasks. These methods construct a search tree to solve each problem, which results in a significantly longer inference time.

GFlowNets. GFlowNets [10] were originally proposed to learn policies for sampling from unnormalized distributions, with a primary motivation from scientific discovery [35], which requires generating diverse high-reward samples [36–38]. Beyond the science domain, GFlowNets have also been applied in various downstream applications such as recommendation systems [39], domain adaptation [40], combinatorial optimization [41, 42] and explainability of deep neural networks [43]. Additionally, GFlowNets have proven to be suitable for sampling from posterior distributions [13, 44–46]. As a reinforcement learning method, prior works have incorporated intermediate feedback with GflowNets to address sparse reward issues [47–49] and multi-objective rewards [50–52]. There are also theoretical analyses treating GFlowNets as recurrent MCMC [53] and variational inference [54, 55] that are used to model the distribution over trajectories. Recently, GFlowNets have been extended to sample from posterior distributions in LLMs [17], focusing on token-level sequence generation. However, this makes it challenging to apply to structured reasoning tasks.. FOR is the first work to integrate GFlowNets to solve complex reasoning problems with LLMs.

3 FOR for Diverse Reasoning

3.1 Multi-step LLM Reasoning as Generative Flow

We start with formulating LLM step-by-step reasoning from the Markovian flow perspective. As we will show shortly, the new flow-based formulation allows us to connect LLM reasoning with the latest GFlowNet approaches for improved diverse reasoning. Meanwhile, the unique setting of LLM reasoning also inspires generalizations to the standard GFlowNets formalism (e.g., parameterization and exploration mechanisms) for enhanced efficiency. Figure 2 illustrates our approach.

The Reasoning Problem. Consider a reasoning problem that gives an initial state s_0 and a goal g. For example, in BlocksWorld (Figure 1 top and Figure 2), an initial state is the starting configuration of the block stack, and a goal describes the desired properties of terminal states. Reasoning aims to find complete trajectories that lead from the initial state to a terminal state fulfilling the goal. Each trajectory is a sequence of transitions $\tau = (s_0 \rightarrow s_1 \rightarrow \cdots \rightarrow s_n) \in \mathcal{T}$, where s_n is the terminal state and \mathcal{T} is the set of all complete trajectories. For example, in Figure 2, the transition from s_0 to s_1 corresponds to a reasoning step "pickup blue". Given a current state s_t , there could be multiple alternative next steps, resulting in different branches of the reasoning. As a result, similar to [9, 18], LLM reasoning could produce a tree structure.

The reasoning tree contains diverse trajectories landing in different terminal states (leaf nodes). A crucial component often given in the reasoning problem is a reward function $R(s_n) \in \mathbb{R}_{\geq 0}$ which measures a numerical reward on any terminal state s_n . For example, a terminal state that satisfies the goal q would receive a large reward.

As discussed earlier, it is desirable to sample diverse trajectories *proportional* to the unnormalized reward, for broad applications of Bayesian estimation [17], robust inference [56, 57], and data synthesis [7, 6, 58]. This differs crucially from the popular reinforcement learning methods (e.g., PPO) and the inference-time planning algorithms (e.g., RAP, ToT) that optimize for only the *maximum*-reward trajectories.

The Flow Perspective. Sampling complex multi-step trajectories from an unnormalized distribution (i.e., reward) is particularly challenging [10, 59, 57]. To overcome the challenge, we consider the above reasoning problem from a flow-based viewpoint which was initially developed in [10] and has been studied in other machine learning settings [49, 11, 60–64]. Specifically, we define a *trajectory flow* function $F : \mathcal{T} \to \mathbb{R}_{\geq 0}$. Analogous to the classical concept of flows in networks, the flow $F(\tau)$ can be thought of as the volume of water traveling along this path τ . Based on this, for any state *s*, we can further define the *state flow* $F(s) = \sum_{s \in \tau} F(\tau)$, and for any edge $s \to s'$, the *edge flow*:

$$F(s \to s') = \sum_{\tau = (\dots \to s \to s' \to \dots)} F(\tau).$$
⁽¹⁾

These concepts of (unnormalized) flow are connected to the (normalized) probability distributions. Specifically, the flow trajectory determines a distribution over trajectories:

$$P(\tau) = F(\tau)/Z, \quad Z = \sum_{\tau \in \mathcal{T}} F(\tau).$$
⁽²⁾

With a Markov assumption, it can be shown that the distribution factorizes into step-wise distributions:

$$P(\tau) = \prod_{t=1}^{n} P_F(s_t|s_{t-1}), \text{ where } P_F(s_t|s_{t-1}) = F(s_{t-1} \to s_t)/F(s_{t-1}).$$
(3)

That is, intuitively, $P_F(s_t|s_{t-1})$ characterizes the proportion of water at node s_{t-1} that travels toward node s_t . The distribution P_F is also called the *forward policy*, which can be used to generate a trajectory τ by sampling a sequence of transitions step-by-step starting from the initial state s_0 . Equivalently [12], there exists a *backward policy* that defines the distributions $P_B(\cdot|s_t)$ over the parents of each state s_t : $P_B(s_{t-1}|s_t) = F(s_{t-1} \rightarrow s_t)/F(s_t)$. Note that, in the LLM reasoning setting with a tree-structured flow, each state s_t has a unique parent and thus $P_B(s_{t-1}|s_t) = 1$ [11]. This simplifies the training formulation as shown later.

From this flow perspective, **our aim** in diverse LLM reasoning as described above now boils down to approximating a flow F such that $F(s_n)$ equals the reward:

$$F(s_n) = R(s_n), \quad \forall \text{ terminal state } s_n.$$
 (4)

Equivalently—let τ be the trajectory ending at the terminal s_n —according to Eqs.(2) and (3), we aim to obtain a forward policy $P_F(s_t|s_{t-1})$ such that the resulting trajectory distribution is proportional to the reward: $P(\tau) = R(s_n)/Z$. The above flow-based concepts provide a rich set of constraints that can be converted into training objectives for learning the desired forward policy. For example, the *detailed balance* constraint $F(s_{t-1})P_F(s_t|s_{t-1}) = F(s_t)P_B(s_{t-1}|s_t)$ yields the respective objective used in molecule generation tasks [12]. In this work (Section 3.2), we draw inspiration from the recent *trajectory balance* constraint which is shown to drive policy learning most efficiently [11].

LLM Parameterization. We parameterize the forward policy P_F with an LLM. The parameters are then finetuned with the flow-based objective to boost the performance as described in the next section. Specifically, for a reasoning problem, both its goal and the reasoning states s_t are expressed in natural language (Figure 1). For example, $s_t = (s_t^{(1)}, \ldots, s_t^{(j)})$ is a sequence of word tokens. We condition the forward policy (the LLM) on the goal so that the same model can be applied across different problems with different goals:

$$P_F(s_t|s_{t-1};\theta,g) = P_{\text{LLM}}(s_t|s_{t-1};\theta,g,c) = \prod_{k=1}^{j} P_{\text{LLM}}^{\theta}(s_t^{(k)}|s_{t-1},s_t^{((5)$$

where the LLM, with parameters θ , generates the next state s_t autoregressively. Here c is the prompt that steers the LLM generation as desired. The prompts used in the experiments are in Appendix B.

3.2 Efficient Policy Training

We now discuss the tuning of the forward policy inspired by the GFlowNet approaches previously studied in different contexts. Specifically, the new flow-based formulation of reasoning described above opens up the door for us to seamlessly import the existing successful GFlowNet training methods. These methods range from the *training objective*, such as flow matching [10], detailed balance [12], and trajectory balance [11], to the various *exploration strategies*, such as on-/off-policy sampling and local search [65, 46, 66], that substantially enhance the training efficiency. Algorithm 1 summarizes the overall FOR training procedure.

3.2.1 Trajectory Balance Objective

In this work, we derive our training objective based on the latest trajectory balance approach [11], which has shown improved efficiency than other alternatives [12, 10]. Specifically, for any complete forward trajectory $\tau = (s_0 \rightarrow s_1 \rightarrow \cdots \rightarrow s_n)$, the trajectory balance constraint says (Figure 2):

$$Z\prod_{t=1}^{n} P_F(s_t|s_{t-1}) = F(s_n)\prod_{t=1}^{n} P_B(s_{t-1}|s_t),$$
(6)

where we have used the fact that $P(s_n) = F(s_n)/Z$ for the terminal state s_n . Plugging in the reward R, as motivated by Eq.(4), to provide supervision signals, the constraint leads to a loss function w.r.t the parameterized forward policy P_F in Eq.(5):

$$l(\tau;\theta,g) = \left(\log\frac{Z\prod_{t=1}^{n} P_F(s_t|s_{t-1};\theta,g)}{R(s_n)\prod_{t=1}^{n} P_B(s_{t-1}|s_t;\theta,g)}\right)^2 = \left(\log\frac{Z\prod_{t=1}^{n} P_F(s_t|s_{t-1};\theta,g)}{R(s_n)}\right)^2.$$
 (7)

The second equation is because $P_B(s_{t-1}|s_t; \theta, g) = 1$ as mentioned earlier thanks to the treestructured flow in LLM reasoning. Note that Z is the total flow depending on each goal g and initial state s_0 . [11] learn an additional model to estimate $\log Z$, which could be difficult. To avoid performance hurt due to inaccurate estimation of $\log Z$, we instead follow [67] to implicitly estimate $\log Z$ based on a batch of trajectories. More details are provided in Appendix A.

The final training objective is then defined as:

$$\mathcal{L}(\theta) = \mathbb{E}_{\tau, g \sim \pi(\tau, g; \theta)}[l(\tau; \theta, g)], \tag{8}$$

where we draw samples from the distribution $\pi(\tau, g; \theta)$ for training. Different configurations of π result in on-policy, off-policy, and mixed explorations, which could impact the training efficiency as shown in the ablation studies (Section 4). We discuss our method of defining $\pi(\tau, g; \theta)$ below. It is shown in [11] that if $\mathcal{L}(\theta)$ is globally optimized, then the resulting flow satisfies Eq.(4) and $P_F(\cdot|\cdot; \theta, g)$ samples proportionally to the reward as desired.

3.2.2 Efficient Exploration

The trajectory space is combinatorially large. We want to set up a $\pi(\tau, g; \theta)$ distribution in Eq.(8) that enables efficient exploration of the trajectory space and produces effective samples for training the parameters θ of the policy P_F . Drawing inspirations from the recent GFlowNet literature [68, 60, 17], we combine both on-policy and off-policy strategies. Moreover, we adapt the local search strategy from [65, 46, 66] to further enhance the exploration and yield stronger performance (Section 4).

More specifically, for on-policy explorations, we use the online policy $P_F(s_t|s_{t-1}; \theta, g)$ itself and its tempered version to create training trajectories τ given the goal g and initial state s_0 in a reasoning problem. For off-policy explorations, we use standard options from previous work [68, 60, 17], including a replay buffer that prioritizes past trajectories, ϵ -greedy sampling, and offline trajectory data (for Game24 in Section 4.3). To further explore high-reward regions, we incorporate a local search method (Figure 2). Specifically, we select the trajectory with the highest reward in each batch, destroy the later portion of the trajectory, and reconstruct the portion with a random policy P_U . This produces augmented trajectories with a high probability of receiving large rewards. Further details on the exploration strategies and local search process are provided in Appendices C and D, respectively.

4 Experiments

We choose three challenging and popular reasoning tasks following previous works in LLM reasoning [18, 9, 69, 70], covering embodied reasoning (BlocksWorld [71]), math puzzle (Game24 [18]), and logical reasoning (PrOntoQA [72]). An illustration of these tasks is shown in Figure 1.

4.1 Experimental Settings

Baselines. We compare our approach with two finetuning-based methods, SFT and PPO. SFT adopts a traditional maximum likelihood training paradigm, while PPO is a reward maximization RL algorithm commonly used in RLHF [31]. Additionally, we evaluate three inference-time reasoning methods: CoT [1], ToT [2], and RAP [9], all of which have demonstrated state-of-the-art performance in various reasoning tasks. ToT structures reasoning into a tree format, and RAP additionally incorporates state information from a world model. Both methods employ search algorithms such as BFS or MCTS to explore the tree structure and identify optimal solutions. We implement all inference-time reasoning methods with LLM Reasoners [69]. Further details are in Appendix B.

Evaluation. As mentioned in Section 1, a desired reasoning method should not only produce correct solutions but also find as many correct solutions as possible. Unlike previous works that typically evaluate only one solution per reasoning problem, we introduce a new setting where the model can generate n solutions for each problem. We evaluate these methods based on three criteria: (1) **Accuracy**: A method is considered successful if at least one of the n solutions is correct. Accuracy measures the portion of test cases that are solved by the method, analogous to the Pass@k in previous works. (2) **Diversity**: For problems solved by the method, we count how many unique solutions in the n solutions are correct, and report the average number across these solved problems—the higher, the better. A more formal definition is provided in the Appendix B.1. (3) **Runtime**: The average time taken by a method to produce one solution, serving as an efficiency metric.

4.2 Embodied Reasoning: BlocksWorld

Task Description. As shown in figure 1, a model needs to give a sequence of actions to rearrange blocks into stacks in a particular order. A state is defined as the current orientation of the blocks, and an action is a textual instruction to move these blocks. An action involves one of four verbs (*STACK, UNSTACK, PUT, PICKUP*) and targeted objects. We generate valid actions based on domain restrictions and the current block orientation. To transit between states, the LLM is prompted to predict the next state s_t based on the last state s_{t-1} . The planning process is terminated once a state meets all goal conditions or reaches a maximum step limit.

Setup. We use the Llama3 8B¹ model as our policy model. We group the examples of Blocksworld [71, 9] by the minimum number of actions required. Following the setting from [9], we have 30 examples within 2 steps, 57 examples within 4 steps, and 114 examples within 6 steps. We select the first 15 of each group as the training examples for FOR and the rest as test examples. Since the examples with larger steps have larger trajectory space, we sample multiple times for FOR and keep the same number of samplings on other methods.

Baselines. We compare FOR to finetuning-based methods SFT and PPO, and inference-time methods including CoT, ToT (BFS), ToT (DFS), and RAP. For finetuning-based methods, we sample the same number of solutions at inference time as FOR. We also report the results of SFT with different decoding temperatures. More details of baselines are presented in Appendix B.

Reward Design. We have compositional rewards to help generate a sequence of actions on this task. Firstly, we give a relatively large positive reward when FOR reaches the goal g. To guide the model to explore the vast reasoning space, we make use of the action probabilities predicted by the base LLM $P_{\rm ref}$ (without finetuning) as the augmented reward. This leads to another term in the reward function. Formally, $R(s_n) = w \cdot \mathbb{I}(\operatorname{success}) + \lambda \sum_{t=1}^{n} \frac{-1}{\log P_{\rm ref}(s_t|s_{t-1},g)}$, where w is the success weight which we set to 100, and $P_{\rm ref}(s_t|s_{t-1},g)$ measures the confidence that state s_t should be taken to reach the goal g at last state s_{t-1} . When it gives a high possibility of s_t , we provide a large reward to encourage the policy P_F to follow this trajectory. We ablate the effect of λ below.

¹https://llama.meta.com/llama3/

Method	2-step Acc. (%)	4-ste	p Div	6-ste	p Div	Runtime (s)
Inference-time reasoning methods						
CoT (1-shot)	40.00	36.71	1.07	13.13	1.07	3.57
CoT (5-shot)	80.00	40.48	1.00	30.30	1.03	3.68
CoT (15-shot)	60.00	42.86	1.05	18.18	1.05	5.32
CoT (GPT-4)	53.33	38.10	-	45.45	-	6.83
ToT (BFS)	13.33	14.28	-	5.05	-	398.74
ToT (DFS)	13.33	16.67	-	8.08	-	48.91
RAP	100.00	92.86	-	69.70	-	466.09
Finetuning-based methods						
SFT (α=1.0)	46.66	40.48	1.04	35.35	1.05	4.05
SFT (α=0.5)	46.66	40.48	1.00	31.31	1.03	4.05
SFT (α =0.1)	33.33	30.95	1.00	19.19	1.00	4.05
SFT + PPO	46.66	47.62	1.11	25.25	1.10	4.95
FoR (Ours)	100.00	97.62	1.25	71.71	1.28	13.98
- w/o local search	100.00	90.48	1.17	54.54	1.33	13.98
- w/o augmented rewards	100.00	92.86	1.22	47.47	1.12	13.98

Table 1: Results of BlocksWorld. 2-step problems have only one correct plan, therefore we do not consider their diversity. ToT and RAP are search-based methods aiming to find the highest-reward plans. Thus they are not designed to generate diverse plans and compute the *Div* metric. For SFT, α is the temperature coefficient during LLM decoding. We report the inference time on 6-step problems.

4.2.1 Results

As shown in Table 1, FOR outperforms the leading baseline RAP in accuracy across various step scenarios. Inference-time methods like CoT and ToT rely on the model's intrinsic reasoning ability, which performs poorly with small models like Llama 8B. In terms of diversity, intrinsic knowledge makes LLM more inclined to choose fixed policies, leading to difficulty in generating diverse plans. Besides, methods like RAP and ToT require extensive searches for each test problem, which consumes significantly longer time and limits the ability to search for various plans. On the other hand, finetuning methods like SFT and PPO perform poorly on small training sets and learn less effectively in cases with more reasoning steps. This is due to their nature of maximum likelihood training and reward maximization, respectively. They tend to reinforce successful plans from positive examples, which weakens their generalization to unseen states and goals and reduces their ability to generate diverse trajectories. On the contrary, FOR fine-tunes the model to match the reward distribution, enabling it to learn multiple trajectories during exploration. This makes it a data-efficient training algorithm that achieves higher accuracy with small training sets. We also report the inference time when generating one plan for a 6-step instance, the reason why FOR is efficient is that it amortizes the computation for searching plans for each test problem independently to train a reasoner which infers new plans fast.

4.2.2 Ablation Study

We evaluate the efficacy of the following two components used in FoR separately.

Local search. We trained FOR without local search for the same number of iterations to assess its effectiveness. Table 1 shows a decline in performance for both 4-step and 6-step examples without local search, highlighting its importance in training. Additionally, the more substantial performance drop in the 6-step setting suggests that local search is particularly effective in scenarios with larger trajectory spaces. This effectiveness likely stems from local search starting with sub-trajectories that have higher rewards, increasing the likelihood of generating successful plans.

Augmented reward. We also run experiments using only the success reward to assess the impact of augmented rewards. In the last row of Table 1, without augmented rewards, the accuracy and *Div* on the 6-step examples decrease by 51% and 13%, respectively, which demonstrates the augmented reward helps the model better utilize the failed trajectory and explore more effectively. Additionally, as shown in Figure 3a, we observe that the accuracy increases as the weight of augmented rewards



(a) Performance with different reward weight λ on the training data.

(b) Test performance with different amounts of training data for SFT. Stars represent the performance of FOR.

Figure 3: Ablation study results: (a) A plot illustrating the most effective reward weight λ value during training. (b) A plot demonstrating that FOR is more data-efficient compared to SFT.

increases from 0 to 1. This improvement is likely because the differential in augmented rewards creates a more pronounced difference between failed trajectories, allowing the model better to distinguish and learn the helpful states in these trajectories. However, as the weight continues to increase, the accuracy decreases. In this case, larger augmented rewards weaken the effect of success reward $\mathbb{I}(success)$, thereby negatively affecting the performance.

Data Efficiency. To verify the data efficiency of FOR, we select the last 20 instances in the 6-step test set and compare the performance with different amounts of training samples for SFT. As shown in Figure 3b, the accuracy of SFT increases with more training data, and the diversity shows no obvious change. These two metrics are lower than FOR trained with 15 instances. We believe this improvement of FOR is due to training with diverse reasoning trajectories, which enhances the generalization ability to handle new instances.

4.3 Math Puzzle Solving: Game24

Task Description. We evaluate our proposed method on the task of the Game of 24, a mathematical reasoning task with possibly multiple solutions. The objective of this task is to use 4 integers and 4 basic arithmetic operations $(+, -, \times, \div)$ to reach 24, where each number can only be used once. As shown in Figure 1, a state s_t is the result after the calculations from previous t steps.

The Game of 24 presents a challenge to language models due to the extensive trajectory space. Additionally, the complexity of mathematical reasoning poses an obstacle for LLMs [73], hindering their performance to directly propose the optimal actions from such a large trajectory space.

Method	Acc. (%)	Div		
Inference-time reasoning methods				
СоТ	6.00	1.33		
ToT	21.00	-		
RAP	12.00	-		
Finetuning-based methods				
SFT	19.00	1.37		
FoR	41.00	1.51		
FoR @100	65.00	2.06		

Table 2: Results of the Game of 24. @100 means we sample 100 times during inference.

Setup. We use the Llama2 13B Chat [20] as our policy

model. Using the dataset from LLM-reasoner [69], we randomly select 20 examples for training and 100 examples for testing. Since prior works show that LLMs struggle to online sample a correct trajectory in this task [18, 74], we use the offline ground-truth data obtained from Python code to train the model for all finetuning-based methods. In addition, to avoid the pitfalls of arithmetic calculations with language models, we use Python code to calculate the results after "=" in a state s_t across all methods evaluated in our experiment.

Baselines. We compare FOR with SFT which uses the data in the CoT format. As for the stateof-the-art inference-time methods, we continue to use the CoT, ToT, and RAP. Unless otherwise specified, we sample 20 times for CoT, SFT, and FOR during inference.

Reward Design. Similar to the above, we have a success reward with an augmented reward. The success reward gives a positive reward w a trajectory τ is successful in reaching 24, and the

Mathad	In-distrib	ution	Out-of-distribution		
Method	Prediction Acc.(%)	Proof Acc.(%)	Prediction Acc.(%)	Proof Acc.(%)	
Inference-time reasoning methods					
ТоТ	49.80	32.20	-	-	
RAP	50.70	39.50	-	-	
Few-Shot CoT	52.20	35.40	43.50	18.50	
Finetuning-based methods					
STaR	88.90	54.00	50.10	24.60	
FoR	90.10	53.80	63.40	27.83	
FOR +STaR	91.50	54.70	63.00	26.67	

Table 3: Results of PrOntoQA.

augmented reward gives the product of the probability of correctness for each state s_t , given its last state s_{t-1} provided by the base LLM model: $R(s_n) = w \cdot \mathbb{I}(\operatorname{success}) + \prod_{t=1}^n P_{\text{ref}}(s_t|s_{t-1})$. We set w = 100 in our experiment.

4.3.1 Results

FOR achieves higher accuracy than other baselines. Under 20 times of sampling, the accuracy of FOR is 20.0% higher than the inference-time reasoning method ToT and 29.0% higher than RAP. Additionally, FOR outperforms the fine-tuning-based method SFT by 22.0%. As we increase the sampling to 100 times, FOR achieves 65.0% accuracy with a model on 13B size.

FOR is able to generate more diverse successful trajectories. The diversity of FOR outperforms other methods as well. With the same 20 samplings, FOR achieves an *Div* score of 1.51, outperforming the CoT baseline by 0.18 and the SFT baseline by 0.14. This enhancement in diversity is due to FOR' ability to explore and learn from diverse trajectories, a capability that the maximum likelihood training objective of methods like SFT does not support. When the sampling frequency is increased to 100, FOR further improves its *Div* score to 2.06.

4.4 Logical Reasoning: PrOntoQA

Task Description. We evaluate FOR using the logical reasoning task dataset from PrOntoQA [72] (Figure 1). For each test case in this dataset, there is a question, a set of facts A, an initial step of the reasoning chain as *initial state* s_0 , and a ground-truth final answer (True/False) with a detailed proof of reasoning chain. A *state* s_t is the conclusion derived from the reasoning process based on the previous state s_{t-1} . We compare the performance with both the *prediction accuracy* of the predicted final answer and the *proof accuracy* of the entire proof by using a rule-based string match. The metric of *Div* is not applicable to this task because each question has only one correct reasoning chain.

Setup. We randomly select 50 examples as the training set and 120 examples as the test set across different methods. We evaluate the methods on both in-distribution and out-of-distribution (OOD) examples. See Appendix **B.4** for more experimental details.

Baselines. We adopt STaR [28], which uses SFT on the correct examples through online sampling. We also evaluate FOR on top of the model fine-tuned by STaR. For inference-time baselines, similar as previous tasks, we use CoT, ToT, and RAP. We sample 32 times at inference for the CoT and finetuning-based methods.

Reward Design. In this task, we are evaluating the model's ability to generate correct proof steps, rather than only the prediction label. We find that a success reward leads the forward policy P_F to learn to obtain the correct answer through *shortcut*, so we only use a rule-based augmented reward to evaluate if a fact is feasible given the last state s_{t-1} by testing if they contain the same ontology. Formally, $R(s_n) = \frac{1}{n} \sum_{t=1}^{n} w \cdot \mathbb{I}(s_{t-1}, s_t)$, where w is a hyperparameter (e.g., 100), and $\mathbb{I}(s_{t-1}, s_t)$ is an indicator variable when there is no shortcut between s_{t-1} and s_t .

4.4.1 Results

Comparison to inference-time reasoning methods. As shown in Table 3, our proposed method outperforms RAP by 37% on prediction accuracy and ToT by 21% on proof accuracy on in-distribution

examples, which also exhibits prediction accuracies below 50% in a binary classification task. We observe that this can be attributed to the limitations of smaller models and their inability to consistently reach a final conclusion related to the query. Smaller models struggle with applying logical rules effectively, even conditioned on the query, leading to less improvement in inference-time methods.

Accuracy on in-distribution. In comparison to finetuning-based methods, the SFT-based method of STaR could only utilize the positive examples in training and FOR is able to make use of both positive and negative examples to learn more robustly. Our experiment shows that FOR performs slightly better performance on in-distribution examples and it is complimentary to the SFT-based method of STaR.

Generalization on OOD examples. Our method achieves over 4% higher proof accuracy on out-of-distribution examples compared to STaR and few-shot learning. STaR's maximum likelihood training objective focuses on maximizing positive in-distribution examples, which results in weaker generalization on unseen cases. In contrast, FOR exhibits more robust performance and better generalization on both prediction and proof accuracies due to the distribution-matching training objective. This underscores FOR' effectiveness in training smaller models on logical reasoning tasks.

5 Conclusion

We introduced FOR that efficiently trains LLM policy for diverse, high-quality reasoning proportional to unnormalized reward. The core of the approach is the flow-based formulation of multi-step reasoning that allows us to adapt principled GFlowNet training strategies. On three representative tasks across embodied, math, and logical reasoning, FOR show stronger performance and improved diversity than both finetuning-based and inference-time baselines. The present work still bears limitations which we are excited to investigate in the future, including its application on larger LLMs and more tasks, and extending the tree-structured flow into a more flexible graph flow. We discuss more limitations and broader impact in Appendix F and G.

References

- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.
- [2] Ziru Chen, Michael White, Raymond Mooney, Ali Payani, Yu Su, and Huan Sun. When is tree search useful for llm planning? it depends on the discriminator. *arXiv preprint arXiv:2402.10890*, 2024.
- [3] Angela Fan, Mike Lewis, and Yann Dauphin. Hierarchical neural story generation. *arXiv* preprint arXiv:1805.04833, 2018.
- [4] Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. The curious case of neural text degeneration. arXiv preprint arXiv:1904.09751, 2019.
- [5] Clara Meister, Tiago Pimentel, Gian Wiher, and Ryan Cotterell. Locally typical sampling. *Transactions of the Association for Computational Linguistics*, 11:102–121, 2023.
- [6] Xiang Yue, Xingwei Qu, Ge Zhang, Yao Fu, Wenhao Huang, Huan Sun, Yu Su, and Wenhu Chen. Mammoth: Building math generalist models through hybrid instruction tuning. *arXiv* preprint arXiv:2309.05653, 2023.
- [7] Longhui Yu, Weisen Jiang, Han Shi, Jincheng Yu, Zhengying Liu, Yu Zhang, James T Kwok, Zhenguo Li, Adrian Weller, and Weiyang Liu. Metamath: Bootstrap your own mathematical questions for large language models. *arXiv preprint arXiv:2309.12284*, 2023.
- [8] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.
- [9] Shibo Hao, Yi Gu, Haodi Ma, Joshua Jiahua Hong, Zhen Wang, Daisy Zhe Wang, and Zhiting Hu. Reasoning with language model is planning with world model. *arXiv preprint arXiv:2305.14992*, 2023.
- [10] Emmanuel Bengio, Moksh Jain, Maksym Korablyov, Doina Precup, and Yoshua Bengio. Flow network based generative models for non-iterative diverse candidate generation. Advances in Neural Information Processing Systems, 34:27381–27394, 2021.
- [11] Nikolay Malkin, Moksh Jain, Emmanuel Bengio, Chen Sun, and Yoshua Bengio. Trajectory balance: Improved credit assignment in gflownets. *Advances in Neural Information Processing Systems*, 35:5955–5967, 2022.
- [12] Yoshua Bengio, Salem Lahlou, Tristan Deleu, Edward J Hu, Mo Tiwari, and Emmanuel Bengio. Gflownet foundations. *Journal of Machine Learning Research*, 24(210):1–55, 2023.
- [13] Edward J Hu, Nikolay Malkin, Moksh Jain, Katie E Everett, Alexandros Graikos, and Yoshua Bengio. Gflownet-em for learning compositional latent variable models. In *International Conference on Machine Learning*, pages 13528–13549. PMLR, 2023.
- [14] Zarif Ikram, Ling Pan, and Dianbo Liu. Evolution guided generative flow networks. *arXiv* preprint arXiv:2402.02186, 2024.
- [15] Ling Pan, Moksh Jain, Kanika Madan, and Yoshua Bengio. Pre-training and fine-tuning generative flow networks. *arXiv preprint arXiv:2310.03419*, 2023.
- [16] Tristan Deleu, Padideh Nouri, Nikolay Malkin, Doina Precup, and Yoshua Bengio. Discrete probabilistic inference as control in multi-path environments. arXiv preprint arXiv:2402.10309, 2024.
- [17] Edward J Hu, Moksh Jain, Eric Elmoznino, Younesse Kaddar, Guillaume Lajoie, Yoshua Bengio, and Nikolay Malkin. Amortizing intractable inference in large language models. arXiv preprint arXiv:2310.04363, 2023.

- [18] Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. Advances in Neural Information Processing Systems, 36, 2024.
- [19] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. arXiv preprint arXiv:2303.08774, 2023.
- [20] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. arXiv preprint arXiv:2307.09288, 2023.
- [21] Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harmlessness from ai feedback. arXiv preprint arXiv:2212.08073, 2022.
- [22] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1– 113, 2023.
- [23] Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. arXiv preprint arXiv:2110.14168, 2021.
- [24] Swaroop Mishra, Matthew Finlayson, Pan Lu, Leonard Tang, Sean Welleck, Chitta Baral, Tanmay Rajpurohit, Oyvind Tafjord, Ashish Sabharwal, Peter Clark, et al. Lila: A unified benchmark for mathematical reasoning. arXiv preprint arXiv:2210.17517, 2022.
- [25] Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*, 2021.
- [26] David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. Gpqa: A graduate-level google-proof q&a benchmark. arXiv preprint arXiv:2311.12022, 2023.
- [27] Grégoire Mialon, Clémentine Fourrier, Craig Swift, Thomas Wolf, Yann LeCun, and Thomas Scialom. Gaia: a benchmark for general ai assistants. arXiv preprint arXiv:2311.12983, 2023.
- [28] Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah Goodman. Star: Bootstrapping reasoning with reasoning. *Advances in Neural Information Processing Systems*, 35:15476–15488, 2022.
- [29] Avi Singh, John D Co-Reyes, Rishabh Agarwal, Ankesh Anand, Piyush Patil, Peter J Liu, James Harrison, Jaehoon Lee, Kelvin Xu, Aaron Parisi, et al. Beyond human data: Scaling self-training for problem-solving with language models. *arXiv preprint arXiv:2312.06585*, 2023.
- [30] Arian Hosseini, Xingdi Yuan, Nikolay Malkin, Aaron Courville, Alessandro Sordoni, and Rishabh Agarwal. V-star: Training verifiers for self-taught reasoners. *arXiv preprint arXiv:2402.06457*, 2024.
- [31] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.
- [32] Alex Havrilla, Yuqing Du, Sharath Chandra Raparthy, Christoforos Nalmpantis, Jane Dwivedi-Yu, Maksym Zhuravinskyi, Eric Hambro, Sainbayar Sukhbaatar, and Roberta Raileanu. Teaching large language models to reason with reinforcement learning. *arXiv preprint arXiv:2403.04642*, 2024.
- [33] Wenhu Chen, Xueguang Ma, Xinyi Wang, and William W Cohen. Program of thoughts prompting: Disentangling computation from reasoning for numerical reasoning tasks. *arXiv* preprint arXiv:2211.12588, 2022.

- [34] Maciej Besta, Nils Blach, Ales Kubicek, Robert Gerstenberger, Michal Podstawski, Lukas Gianinazzi, Joanna Gajda, Tomasz Lehmann, Hubert Niewiadomski, Piotr Nyczyk, et al. Graph of thoughts: Solving elaborate problems with large language models. In *Proceedings of the* AAAI Conference on Artificial Intelligence, volume 38, pages 17682–17690, 2024.
- [35] Moksh Jain, Tristan Deleu, Jason Hartford, Cheng-Hao Liu, Alex Hernandez-Garcia, and Yoshua Bengio. Gflownets for ai-driven scientific discovery. *Digital Discovery*, 2(3):557–577, 2023.
- [36] Tony Shen, Mohit Pandey, and Martin Ester. Tacogfn: Target conditioned gflownet for structurebased drug design. arXiv preprint arXiv:2310.03223, 2023.
- [37] Moksh Jain, Emmanuel Bengio, Alex Hernandez-Garcia, Jarrid Rector-Brooks, Bonaventure FP Dossou, Chanakya Ajit Ekbote, Jie Fu, Tianyu Zhang, Michael Kilgour, Dinghuai Zhang, et al. Biological sequence design with gflownets. In *International Conference on Machine Learning*, pages 9786–9801. PMLR, 2022.
- [38] Julien Roy, Pierre-Luc Bacon, Christopher Pal, and Emmanuel Bengio. Goal-conditioned gflownets for controllable multi-objective molecular design. *arXiv preprint arXiv:2306.04620*, 2023.
- [39] Shuchang Liu, Qingpeng Cai, Zhankui He, Bowen Sun, Julian McAuley, Dong Zheng, Peng Jiang, and Kun Gai. Generative flow network for listwise recommendation. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 1524–1534, 2023.
- [40] Didi Zhu, Yinchuan Li, Yunfeng Shao, Jianye Hao, Fei Wu, Kun Kuang, Jun Xiao, and Chao Wu. Generalized universal domain adaptation with generative flow networks. In *Proceedings of the 31st ACM International Conference on Multimedia*, pages 8304–8315, 2023.
- [41] Dinghuai Zhang, Hanjun Dai, Nikolay Malkin, Aaron Courville, Yoshua Bengio, and Ling Pan. Let the flows tell: Solving graph combinatorial optimization problems with gflownets. arXiv preprint arXiv:2305.17010, 2023.
- [42] Minsu Kim, Sanghyeok Choi, Jiwoo Son, Hyeonah Kim, Jinkyoo Park, and Yoshua Bengio. Ant colony sampling with gflownets for combinatorial optimization. *arXiv preprint arXiv:2403.07041*, 2024.
- [43] Wenqian Li, Yinchuan Li, Zhigang Li, Jianye Hao, and Yan Pang. Dag matters! gflownets enhanced explainer for graph neural networks. *arXiv preprint arXiv:2303.02448*, 2023.
- [44] Tristan Deleu, António Góis, Chris Emezue, Mansi Rankawat, Simon Lacoste-Julien, Stefan Bauer, and Yoshua Bengio. Bayesian structure learning with generative flow networks. In Uncertainty in Artificial Intelligence, pages 518–528. PMLR, 2022.
- [45] Tristan Deleu, Mizu Nishikawa-Toomey, Jithendaraa Subramanian, Nikolay Malkin, Laurent Charlin, and Yoshua Bengio. Joint bayesian inference of graphical structure and parameters with a single generative flow network. *Advances in Neural Information Processing Systems*, 36, 2024.
- [46] Dinghuai Zhang, Nikolay Malkin, Zhen Liu, Alexandra Volokhova, Aaron Courville, and Yoshua Bengio. Generative flow networks for discrete probabilistic modeling. In *International Conference on Machine Learning*, pages 26412–26428. PMLR, 2022.
- [47] Ling Pan, Nikolay Malkin, Dinghuai Zhang, and Yoshua Bengio. Better training of gflownets with local credit and incomplete trajectories. In *International Conference on Machine Learning*, pages 26878–26890. PMLR, 2023.
- [48] Hyosoon Jang, Minsu Kim, and Sungsoo Ahn. Learning energy decompositions for partial inference of gflownets. *arXiv preprint arXiv:2310.03301*, 2023.
- [49] Ling Pan, Dinghuai Zhang, Aaron Courville, Longbo Huang, and Yoshua Bengio. Generative augmented flow networks. *arXiv preprint arXiv:2210.03308*, 2022.

- [50] Moksh Jain, Sharath Chandra Raparthy, Alex Hernández-Garcia, Jarrid Rector-Brooks, Yoshua Bengio, Santiago Miret, and Emmanuel Bengio. Multi-objective gflownets. In *International conference on machine learning*, pages 14631–14653. PMLR, 2023.
- [51] Alex Hernandez-Garcia, Nikita Saxena, Moksh Jain, Cheng-Hao Liu, and Yoshua Bengio. Multi-fidelity active learning with gflownets. arXiv preprint arXiv:2306.11715, 2023.
- [52] Yihang Chen and Lukas Mauch. Order-preserving gflownets. arXiv preprint arXiv:2310.00386, 2023.
- [53] Tristan Deleu and Yoshua Bengio. Generative flow networks: a markov chain perspective. *arXiv* preprint arXiv:2307.01422, 2023.
- [54] Nikolay Malkin, Salem Lahlou, Tristan Deleu, Xu Ji, Edward Hu, Katie Everett, Dinghuai Zhang, and Yoshua Bengio. Gflownets and variational inference. *arXiv preprint arXiv:2210.00580*, 2022.
- [55] Heiko Zimmermann, Fredrik Lindsten, Jan-Willem van de Meent, and Christian A Naesseth. A variational perspective on generative flow networks. arXiv preprint arXiv:2210.07992, 2022.
- [56] Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. arXiv preprint arXiv:2203.11171, 2022.
- [57] Lianhui Qin, Sean Welleck, Daniel Khashabi, and Yejin Choi. Cold decoding: Energy-based constrained text generation with langevin dynamics. *Advances in Neural Information Processing Systems*, 35:9538–9551, 2022.
- [58] Yuanzhi Li, Sébastien Bubeck, Ronen Eldan, Allie Del Giorno, Suriya Gunasekar, and Yin Tat Lee. Textbooks are all you need ii: phi-1.5 technical report. arXiv preprint arXiv:2309.05463, 2023.
- [59] Yann LeCun, Sumit Chopra, Raia Hadsell, M Ranzato, and Fujie Huang. A tutorial on energybased learning. *Predicting structured data*, 1(0), 2006.
- [60] Max W Shen, Emmanuel Bengio, Ehsan Hajiramezanali, Andreas Loukas, Kyunghyun Cho, and Tommaso Biancalani. Towards understanding and improving gflownet training. In *International Conference on Machine Learning*, pages 30956–30975. PMLR, 2023.
- [61] Yinchuan Li, Shuang Luo, Haozhi Wang, and Jianye Hao. Cflownets: Continuous control with generative flow networks. arXiv preprint arXiv:2303.02430, 2023.
- [62] Salem Lahlou, Tristan Deleu, Pablo Lemos, Dinghuai Zhang, Alexandra Volokhova, Alex Hernández-Garcia, Léna Néhale Ezzine, Yoshua Bengio, and Nikolay Malkin. A theory of continuous generative flow networks. In *International Conference on Machine Learning*, pages 18269–18300. PMLR, 2023.
- [63] Chunhui Li, Cheng-Hao Liu, Dianbo Liu, Qingpeng Cai, and Ling Pan. Bifurcated generative flow networks. arXiv preprint arXiv:2406.01901, 2024.
- [64] Haoran He, Can Chang, Huazhe Xu, and Ling Pan. Looking backward: Retrospective backward synthesis for goal-conditioned gflownets. *arXiv preprint arXiv:2406.01150*, 2024.
- [65] Minsu Kim, Taeyoung Yun, Emmanuel Bengio, Dinghuai Zhang, Yoshua Bengio, Sungsoo Ahn, and Jinkyoo Park. Local search gflownets. arXiv preprint arXiv:2310.02710, 2023.
- [66] Marcin Sendera, Minsu Kim, Sarthak Mittal, Pablo Lemos, Luca Scimeca, Jarrid Rector-Brooks, Alexandre Adam, Yoshua Bengio, and Nikolay Malkin. On diffusion models for amortized inference: Benchmarking and improving stochastic control and sampling. arXiv preprint arXiv:2402.05098, 2024.
- [67] David W Zhang, Corrado Rainone, Markus Peschl, and Roberto Bondesan. Robust scheduling with gflownets. *arXiv preprint arXiv:2302.05446*, 2023.

- [68] Nikhil Vemgal, Elaine Lau, and Doina Precup. An empirical study of the effectiveness of using a replay buffer on mode discovery in gflownets. *arXiv preprint arXiv:2307.07674*, 2023.
- [69] Shibo Hao, Yi Gu, Haotian Luo, Tianyang Liu, Xiyan Shao, Xinyuan Wang, Shuhua Xie, Haodi Ma, Adithya Samavedhi, Qiyue Gao, et al. Llm reasoners: New evaluation, library, and analysis of step-by-step reasoning with large language models. arXiv preprint arXiv:2404.05221, 2024.
- [70] Zhihan Liu, Hao Hu, Shenao Zhang, Hongyi Guo, Shuqi Ke, Boyi Liu, and Zhaoran Wang. Reason for future, act for now: A principled framework for autonomous llm agents with provable sample efficiency. arXiv preprint arXiv:2309.17382, 2023.
- [71] Karthik Valmeekam, Matthew Marquez, Sarath Sreedharan, and Subbarao Kambhampati. On the planning abilities of large language models-a critical investigation. *Advances in Neural Information Processing Systems*, 36, 2024.
- [72] Abulhair Saparov and He He. Language models are greedy reasoners: A systematic formal analysis of chain-of-thought. arXiv preprint arXiv:2210.01240, 2022.
- [73] Janice Ahn, Rishu Verma, Renze Lou, Di Liu, Rui Zhang, and Wenpeng Yin. Large language models for mathematical reasoning: Progresses and challenges. *ArXiv*, abs/2402.00157, 2024.
- [74] Fei Yu, Anningzhe Gao, and Benyou Wang. Outcome-supervised verifiers for planning in mathematical reasoning. arXiv preprint arXiv:2311.09724, 2023.
- [75] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv* preprint arXiv:2106.09685, 2021.
- [76] Peiyi Wang, Lei Li, Zhihong Shao, RX Xu, Damai Dai, Yifei Li, Deli Chen, Y Wu, and Zhifang Sui. Math-shepherd: A label-free step-by-step verifier for llms in mathematical reasoning. arXiv preprint arXiv:2312.08935, 2023.
- [77] Zhiheng Xi, Wenxiang Chen, Boyang Hong, Senjie Jin, Rui Zheng, Wei He, Yiwen Ding, Shichun Liu, Xin Guo, Junzhe Wang, et al. Training large language models for reasoning through reverse curriculum reinforcement learning. arXiv preprint arXiv:2402.05808, 2024.
- [78] Badr AlKhamissi, Siddharth Verma, Ping Yu, Zhijing Jin, Asli Celikyilmaz, and Mona Diab. Opt-r: Exploring the role of explanations in finetuning and prompting for reasoning skills of large language models. arXiv preprint arXiv:2305.12001, 2023.
- [79] Junxing Wang, Xinyi Li, Zhen Tan, Xiang Zhao, and Weidong Xiao. Relation-aware bidirectional path reasoning for commonsense question answering. In Arianna Bisazza and Omri Abend, editors, *Proceedings of the 25th Conference on Computational Natural Language Learning*, pages 445–453, Online, November 2021. Association for Computational Linguistics.
- [80] Ke Liang, Lingyuan Meng, Meng Liu, Yue Liu, Wenxuan Tu, Siwei Wang, Sihang Zhou, Xinwang Liu, and Fuchun Sun. A survey of knowledge graph reasoning on graph types: Static, dynamic, and multimodal. arXiv preprint arXiv:2212.05767, 2022.
- [81] Jiaxin Bai, Chen Luo, Zheng Li, Qingyu Yin, Bing Yin, and Yangqiu Song. Knowledge graph reasoning over entities and numerical values. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 57–68, 2023.

A Log Partition Variance Loss

In this section, we briefly introduce how to avoid parameterizing $\log Z$ with a neural network.

$$\Phi(\tau;\theta) = \log R(s_n) + \sum_{t=0}^{n-1} \log P_B(s_t|s_{t+1},g;\theta) - \sum_{t=0}^{n-1} \log P_F(s_{t+1}|s_t,g;\theta)$$
(9)

Ideally, when trajectory balance satisfies, $\Phi(\tau; \theta)$ equals the true $\log Z$ for all the trajectories with initial state s_0 and goal g. Therefore, the optimization objective can be turned into minimizing the variance of $\Phi(\tau; \theta)$ over different trajectories with the modified loss function:

$$\mathcal{L}_{V}(\tau;\theta) = (\Phi(\tau;\theta) - \mathbb{E}_{\tau}[\Phi(\tau;\theta)])^{2}$$
(10)

where $\mathbb{E}_{\tau}[\Phi(\tau; \theta)]$ is estimated with a mini-batch of sampled trajectories.

B Experimental details

B.1 Diversity Metric

we define the following metric to measure the diversity of reasoning paths found by different approaches. Under the same number of samplings at inference time, we count the number of different successful trajectories a policy finds for the successful example on average.

$$Div = \frac{\sum_{i=1}^{n} S_i \cdot \mathbb{I}(S_i \ge 1)_i}{\sum_{i=1}^{n} \mathbb{I}(S_i \ge 1)_i} \ge 1$$
(11)

where n is the total number of questions, S_i is the number of successful trajectories found for the *i*-th question, and $\mathbb{I}(S_i \ge 1)$ is an indicator function that is 1 if there is at least one successful trajectory found for the *i*-th question and 0 otherwise. Thus, the denominator is the number of examples in which a model finds at least one trajectory, and the nominator is the sum of all successful trajectories a model finds across all examples. The smallest Div is 1 when a method can only find at most one successful trajectory on average, and Div = 1.5 indicates a method is able to find 1.5 different successful trajectories on average.

B.2 BlocksWorld.

FoR Setup. During the training, we finetune the LLM with LoRA [75] with r = 32, $\alpha = 64$, and dropout=0.1. We set ϵ from 0.3 and decrease it to 0.01, β from 1 to 2, and the probability δ using replay buffer increases from 0.3 to 0.5 throughout the iterations linearly. The learning rate is set to 1e-4 with a cosine annealing schedule, and the number of training iterations is set to 20. Reward weight λ is set to 1.5. Table 4 shows the template we use for the forward policy in the 6-step setting, and its difference between 2-step and 4-step is only replacing the 6-step demonstration to 2-step and 4-step. During testing, we sample 8, 20, and 40 trajectories for 2, 4, and 6 steps respectively. As long as one trajectory reaches the goal, we label this instance as solved, all the baselines conform to the same rule.

Baselines. We compare FOR the following baselines:

(1) Chain-of-Thoughts prompting (CoT) [1]: It concatenates k problems with ground truth solutions and the test problem, and prompts the LLM to generate a solution. We test the setting where k = 1, 5, 15, and pass the test cases to LLMs at the same times as FOR, and the test case is regarded as solved if at least one plan is correct.

(2) *Tree-of-Thoughts prompting (ToT)* [18]: This approach constructs a tree of actions and searches for the solution with the highest reward. For each action, the reward includes (a) the likelihood of the LLM predicting the action and (b) self-evaluation, where the LLM is prompted with the question, "Is this action good?" and the answer is mapped to a reward value. We implement ToT with both breadth-first search (BFS) and depth-first search (DFS), terminating after generating 10 solutions.

(3) *Reasoning-via-Planning (RAP)* [9]: This method also conducts a tree search for the optimal solution. Different from ToT, it alternatively predicts the next action and predicts the resulting block arrangement. Besides the rewards used in ToT, if the predicted block arrangement matches the goal, a large reward will be assigned.

(4) *Supervised Fine-Tuning (SFT)*: We use problems in the training set and their corresponding ground truth solutions to finetune the LLM. Note that this is an easier setting than FOR which does not have access to ground truth solutions. We train LLM with the same iterations as FOR.

(5) *Proximal Policy Optimization (PPO)* [8]: This is a widely-used reinforcement learning method for LLM training. We design the objective to encourage the LLM to generate solutions that satisfy

I am playing with a set of blocks where I need to arrange the blocks into stacks. Here are the actions I can do

Pick up a block Unstack a block from on top of another block Put down a block Stack a block on top of another block

I have the following restrictions on my actions: I can only pick up or unstack one block at a time. I can only pick up or unstack a block if my hand is empty. I can only pick up a block if the block is on the table and the block is clear. A block is clear if the block has no other blocks on top of it and if the block is not picked up. I can only unstack a block from on top of another block if the block I am unstacking was really on top of the other block. I can only unstack a block from on top of another block if the block I am unstacking is clear. Once I pick up or unstack a block, I am holding the block. I can only put down a block that I am holding. I can only stack a block on top of another block if I am holding the block being stacked. I can only stack a block on top of another block if the block onto which I am stacking the block is clear. Once I put down or stack a block, my hand becomes empty. [STATEMENT] As initial conditions I have that, the orange block is clear, the hand is empty, the red block is on top of the blue block, the orange block is on top of the red block and the blue block is on the table. My goal is to have that the blue block is on top of the orange block. My plan is as follows: [PLAN] unstack the orange block from on top of the red block put down the orange block unstack the red block from on top of the blue block put down the red block pick up the blue block stack the blue block on top of the orange block [PLAN END] [STATEMENT] As initial conditions I have that, <current state> My goal is to My goal is to have that <goals> My plan is as follows: [PLAN]

Table 4: Prompt template for the embodied reasoning task (6-step).

the goal. Following the common practice of previous work [31, 76], we penalize the policy if it deviates too much from the reference policy. Formally, the objective is $\max_{\pi_{\theta}} \mathbb{E}_{\tau \sim \pi_{\theta}} [R(x, y)] - \beta \mathbb{D}_{\mathrm{KL}} [\pi_{\theta}(y \mid x) \| \pi_{\mathrm{ref}}(y \mid x)].$

B.3 Game of 24.

<action>

FOR Setup. See Table 5 for the prompt template used in the experiment of the Game of 24. We

Use numbers and basic arithmetic operations (+ - * /) to obtain 24. For each step, you are only allowed to choose two of the remaining numbers to obtain a new number. Input: 4 4 6 8 Steps: 4 + 8 = 12 (left: 4 6 12) 6 - 4 = 2 (left: 2 12) 2 * 12 = 24 (left: 24) Input: 291012 Steps: $12 \times 2 = 24$ (left: 9 10 24) 10 - 9 = 1 (left: 1 24) 24 * 1 = 24 (left: 24) Input: 4 9 10 13 Steps: 13 - 10 = 3 (left: 3 4 9) 9 - 3 = 6 (left: 4 6) 4 * 6 = 24 (left: 24) Input: 1 4 8 8 Steps: 8/4 = 2 (left: 1 2 8) 1 + 2 = 3 (left: 3 8) 3 * 8 = 24 (left: 24) Input: 5 5 5 9 Steps: 5 + 5 = 10 (left: 5 9 10) 10 + 5 = 15 (left: 9 15) 15 + 9 = 24 (left: 24) Input: <input> Steps:

Table 5: Prompt template for the mathematical puzzle task.

use LoRA to train the model with r = 8, $\alpha = 32$, dropout=0.1. We load the LLM in fp16, and set the hyperparameters as follows: batch size = 4, learning rate = 1e-5, number of epochs = 5, and the reward weight w = 100.

Baselines. Similar to BlocksWorld, we compare FOR with methods including CoT (5-shot), ToT, RAP, and SFT.

B.4 Logical Reasoning.

See Table 6 for the prompt template of the logical reasoning task.

OOD data creation We separate the in-distribution and OOD data by topics and ontology. We use the animal-related problems as in-distribution examples and the number-related problems as OOD examples.

Training details We use LoRA to train the model with r = 8, $\alpha = 32$, dropout=0.1. We load the LLM in fp16, and set the hyperparameters as follows: batch size = 4, learning rate = 5e-6, number of epochs = 40, and the reward weight w = 100.

Baselines. Apart from CoT, ToT, and RAP, we compare FOR with STaR [28], which uses online sampling to filter our positive examples consistent with ground truth trajectories to finetune the LLM. Note that this is an easier setting than FOR which doesn't have access to ground truth solutions. It

Given a list of facts, and a current claim, output one possible fact as the next step ONLY BASED ON THE LAST CLAIM without using your knowledge. Be sure to copy the EXACT sentence in the facts. Do NOT change any wording. Do NOT create your own words. Give me the next step ONLY.

Facts 1: Each lepidopteran is an insect. Each arthropod is a protostome. Every animal is multicellular. Protostomes are invertebrates. Each whale is bony. Each painted lady is a butterfly. Invertebrates are animals. Butterflies are lepidopterans. Each insect is six-legged. Every insect is an arthropod. Arthropods are not bony. Query 1: True or false: Sally is not bony. Claim 1.1: Sally is an insect. Next 1.1: Every insect is an arthropod.

Claim 1.2: Sally is an arthropod. Next 1.2: Arthropods are not bony.

Claim 1.3: Sally is not bony. Next 1.3: Finish.

Facts 2: Lepidopterans are insects. Every animal is multicellular. Each insect is an arthropod.
Each invertebrate is an animal. Insects are six-legged. Arthropods are small. Arthropods are invertebrates. Each butterfly is a lepidopteran. Whales are not small.
Query 2: True or false: Polly is not small.
Claim 2.1: Polly is a lepidopteran.
Next 2.1: Lepidopterans are insects.
Claim 2.2: Polly is an insect.
Next 2.2: Each insect is an arthropod.
Claim 2.3: Polly is an arthropod.
Next 2.3: Arthropods are small.
Claim 2.4: Polly is small.

Facts 3: <facts> Query 3: <query> Claim 3.1: <initial state> Next 3.1:

Table 6: Prompt template for logical reasoning task

also indicates an upper bound of SFT methods that do not rely on ground truth solutions, like. All baselines use Llama3 8B as the base model.

Computing. All experiments were conducted using a server with a single NVIDIA A100 GPU.

C Exploration and Training

FOR employs the following techniques to explore during the training phase:

- 1. Online training: (1) we employ the online policy $P_F(s_t|s_{t-1}, \alpha)$, and its tempered version (2) Similar to ϵ -greedy, we sample action at step t by P_F with probability ϵ , and sample with uniform distribution over action space $P_U(s_t|s_{t-1})$ with $(1 - \epsilon)$ probability. (3) To further explore the high-reward region, we modified the local search [65, 46]. More specifically, we select the trajectory with the highest reward in a batch and conduct a destroy and reconstruction process for augmenting the trajectories to enable a higher probability of sampling successful trajectories, referring to Appendix D for more details.
- 2. Offline training: (1) Experience replay represents a significant advancement in reinforcement learning, offering enhancements in both learning efficiency and stability, as evidenced by recent

empirical studies in GFlowNets [68, 60]. To optimize the utility of the trajectories collected, we set up a prioritized replay buffer (PRB). This buffer facilitates the sampling of trajectories in proportion to their reward value, $R(\tau)$, or its logarithmic value, thereby prioritizing potentially more informative experiences. (2) For tasks (e.g. Game of 24) that have a large space, online sampling diverse trajectories with LLMs is computationally expensive. Therefore, we integrate the offline trajectories to have a larger coverage of space and improve the efficiency, which means $\delta = 0$.

Algorithm 1 describes the training framework.

Algorithm 1 FOR Training

1:	Input: I: number of iterations, P_F : initial LLM policy, \mathcal{D} : Prioritized Replay Buffer. M
	Batch-size, δ : online-offline ratio, \mathcal{E} : Training Dataset, \mathcal{O} : offline Data
2:	Output: Trained policy P_F .
3:	for $i = 1$ to I do
4:	Sample from training dataset $\mathcal E$ with initial state s_0 and goal g
5:	Sample from $u \sim [0, 1]$
6:	if $u < \delta$ then
7:	// Exploration
8:	Sample M online trajectories $\{\tau_1,, \tau_M\}$ with forward policy P_F
9:	Select trajectory $\tau_m \in \{\tau_1,, \tau_M\}$ with the largest $R(\tau_m)$
10:	$\{\tau'_1,, \tau'_{N'}\} \leftarrow \text{Local Search}(\tau_m)$
11:	Update $\mathcal{D} \leftarrow \mathcal{D} \cup \{\tau_1,, \tau_M\} \cup \{\tau'_{1'} \tau'_{N'}\}$
12:	else
13:	// Exploitation
14:	if is Game24 then
15:	sample M offline trajectories from Offline Data \mathcal{O}
16:	else
17:	sample M offline trajectories from \mathcal{D}
18:	end if
19:	end if
20:	Exploit M (with N') trajectories to compute objective function in Eq 8.
21:	Update the parameter in P_F with respect to Eq 8
22:	end for
23:	return P _F

D Modified Local Search

Local search is a simple data augmentation technique for GFlowNets [65, 46, 66], which is designed to enhance training efficiency. Different from the original local search which is conducted on each sampled trajectory, we select the trajectory in a batch with the highest reward to conduct a local search. Here we denote the trajectory reward $R(\tau)$ as the reward of terminal state of the trajectory $R(\tau = (s_0 \rightarrow ... \rightarrow s_n)) = R(s_n)$. More specifically, we illustrate our modified local search for one instance as follows:

- Sampling: Sample a set of complete trajectories $\{\tau_1, ..., \tau_M\}$ using forward policy P_F and select the τ_m with the largest reward $R(\tau_m)$
- Searching: We destroy τ_m by backtracking K-step into a partial trajectory and reconstruct the complete trajectory from the partial trajectory:

$$\tau_{destroy} = (s_0 \to \ldots \to s'_{n-K}), \qquad \tau_{recon} = (s'_{n-K} \to \ldots \to s'_n) \tag{12}$$

We obtain the local searched trajectory τ' :

$$\tau' = (s_0 \to \ldots \to s'_{n-K} \to \ldots \to s'_n) \tag{13}$$

Where the τ_{recon} is completed by the random policy P_U which randomly selects a feasible action for efficiency. We can obtain a set of reconstructed trajectories $\{\tau'_1, ..., \tau'_N\}$

• Filtering: We now need to evaluate the collected reconstructed trajectories $\{\tau'_1, ..., \tau'_N\}$ and determine whether to accept or reject $\tau' \in \{\tau'_1, ..., \tau'_N\}$. Specifically, we accept τ' as follows:

$$A(\tau, \tau') = \mathbf{1}_{R(\tau') > R(\tau)} \tag{14}$$

This means we greedily filter out the candidates $\{\tau'_{1'}...\tau'_{N'}\} \subset \{\tau'_{1},...,\tau'_{N}\}$ that have a larger reward than τ_m , which has a higher possibility of reaching the goal. Then we return these trajectories and add them into the replay buffer \mathcal{D} .

E More Examples

Figure 4 shows generated samples for the BlocksWorld, Figure 5 for Game24, and Table 7 for PrOntoQA, respectively.



Figure 4: Example of BlocksWorld for 6-step planning.

Query: True or false	e: 31 is not imaginary. (OOD)		
State	Action		
31 is a natural number.31 is an integer.31 is a real number.31 is not imaginary.	Natural numbers are integers. Integers are real numbers. Real numbers are not imaginary. Finish.		
Query: True or false: V	Vren is not bony. (In-distribution)		
State	Action		
Wren is a painted lady.	Each painted lady is a butterfly.		
Wren is a butterfly.	Each butterfly is a lepidopteran.		
Wren is a lepidopteran.	Each lepidopteran is an insect.		
Wren is an insect.	Each insect is an arthropod.		
Wren is an arthropod.	Each arthropod is not bony.		
Wren is not bony.	Finish.		

Table 7: Examples for PrOntoQA.



Figure 5: Example of game of 24.

F Limitations

Due to resource constraints, our experiments use language models with up to 13B parameters. However, we expect FOR to hold for larger models as well, and may potentially benefit larger models even more. Recent works [77, 78] that finetune larger models to improve their reasoning ability with maximizing objectives usually need a large amount of data, and our data-efficient FOR may improve this process. Also, it would also be interesting to explore the real graph structure of reasoning. Currently, we only work on tree structures because this paper mainly focuses on forward reasoning, but real-world reasoning often involves more complex graph structures, such as (bidirectional) knowledge graph reasoning [79–81].

G Broader Impact

This study introduces FOR, a methodology that trains LLMs as policies to solve complex reasoning problems. We believe this work connects LLM reasoning with GFlowNets and contributes to the application of GFlowNets to LLMs.