A Survey on LLM-Based Agents: Common Workflows and Reusable LLM-Profiled Components

Xinzhe Li School of IT, Deakin University, Australia lixinzhe@deakin.edu.au

Abstract

Recent advancements in Large Language Models (LLMs) have catalyzed the development of sophisticated frameworks for developing LLM-based agents. However, the complexity of these frameworks r poses a hurdle for nuanced differentiation at a granular level, a critical aspect for enabling efficient implementations across different frameworks and fostering future research. Hence, the primary purpose of this survey is to facilitate a cohesive understanding of diverse recently proposed frameworks by identifying common workflows and reusable LLM-Profiled Components (LMPCs).

1 Introduction

Generative Large Language Models (GLMs or LLMs) have acquired extensive general knowledge and human-like reasoning capabilities (Santurkar et al., 2023; Wang et al., 2022; Zhong et al., 2022, 2023), positioning them as pivotal in constructing AI agents known as LLM-based agents. In the context of this survey, LLM-based agents are defined by their ability to interact actively with external tools (such as Wikipedia) or environments (such as householding environments) and are designed to function as integral components of agency, including acting, planning, and evaluating.

Purpose of the Survey The motivation behind this survey stems from the observation that many LLM-based agents incorporate similar workflows and components, despite the presence of a wide variety of technical and conceptual challenges, e.g., search algorithms (Yao et al., 2023a), tree structures (Hao et al., 2023), and Reinforcement Learning (RL) components (Shinn et al., 2023). (Wu et al., 2023) offer a modular approach but lack integration with prevalent agentic workflows. Wang et al. (2024) provide a comprehensive review of LLM agents, exploring their capabilities across profiling, memory, planning, and action. In contrast, our survey does not attempt to cover all components of LLM-based agents comprehensively. Instead, we concentrate on the involvement of LLMs


within agentic workflows and aim to clarify the roles of LLMs in agent implementations. We create common workflows incorporating reusable LLM-Profiled Components (LMPCs), as depicted in Figure 1.

Contributions This survey offers the following contributions. 1) Alleviating the understanding of complex frameworks: The complexity of existing frameworks can be simplified into implementable workflows, especially when they are extracted for specific tasks. This survey emphasizes reusable workflows and LM-PCs across popular frameworks, such as ReAct (Yao et al., 2023b), Reflexion (Shinn et al., 2023) and Treeof-Thoughts (Yao et al., 2023a). Specifically, based on the interaction environments (§2) and the use of common LMPCs (§3), we categorize and detail various workflows, e.g., tool-use workflows, search workflows, and feedback-learning workflows. Many existing frameworks are composed of these workflows and LMPCs, along with some specific non-LLM components. 2) Helping researchers/practitioners assess current frameworks at a more granular and cohesive level: Section 4 categorizes prominent frameworks and demonstrates how they are assembled by the common workflows and LMPCs, as summarized in Table 2¹. 3) Facilitating further extensions of existing frameworks: Existing frameworks could be modified by changing the implementations of LMPCs. To enable this, we not only summarize implementations of LMPCs but also their applicability across diverse workflows and tasks in Section 5.


2 Task Environments And Tool Environments

This section explores task environments and tool environments, which present different settings compared to traditional AI and reinforcement learning (RL) agent frameworks (Russell and Norvig, 2010; Sutton and Barto, 2018). After a brief overview of standard logicbased gaming and simulated embodied environments, we focus on two specific areas: Natural Language


¹A more detailed summarization is demonstrated in Appendix A



(a) Policy-Only Workflows.



(b) Search Workflows.



(c) Feedback-Learning Workflows.

Figure 1: Eight Common Workflows based on Three LLM-profiled Components (Policy, Evaluator and Dynamic Model) under Task or/and Tool-Use Environments.

Interaction Environments (NLIEs) and Tool Environments.

2.1 Typical Task Environments

Typically, there are two common types of task environments: 1) **Rule-Based Gaming Environments**: These environments, which are deterministic and fully ob-

Env Types	Entities Interacted With by Agent	Action Properties	Examples of Action Instances	Examples of Env Instances	
<i>Task Environments</i> Gaming	Virtual game	Discrete,	Move(Right)	BlocksWorld, CrossWords	
Environments	elements (objects, avatars, other characters), and possibly other players or game narratives	Executable, Deterministic	Move(Right)	Blocks world, Closs worlds	
Embodied	Physical world	Discrete,	Pick_Up[Object]	AlfWorld (Shridhar et al., 2021), VirtualHome, Mincorreft (Fore et al., 2022)	
Environments	(through sensors and actuators)	Executable, Deterministic			
	and actuators)	Deterministic		Minecraft (Fan et al., 2022)	
NLIEs	Humans (through	Free-form,	The answer is Answer	GSM8K,	
	conversation or text)	Discrete, Deterministic (Single-step QA) Stochastic (Multi-step)	Finish[Answer]	HotpotQA	
Tool Environments (N	ested with Task Enviro	nments)			
Retrieval	Retrieval	Discrete, Executable, Deterministic, Non-State- Altering	Wiki_Search[Entity]	A Wikipedia API (Goldsmith, 2023) (used by ReAct (Yao et al., 2023b))	
Calculator	Calculator	Executable, Deterministic, Non-State- Altering	2 x 62 = « Calculator »	Python's eval function (used by MultiTool-CoT (Inaba et al., 2023))	

Table 1: Common task environments and tool-use environments. We categorize all the benchmarks existing in the work of the 12 agentic workflows into four environment types. An action instance is commonly formalized by action predicates and action arguments. Tool use can be considered internal environments of an agent and commonly defined for QA tasks under NLIEs.

servable, include a variety of abstract strategy games like Chess and Go, and logic puzzles such as the Game of 24 (Yao et al., 2023a) and Blocksworld (Hao et al., 2023). They demand deep logical reasoning and strategic planning to navigate and solve. 2) **Simulated Embodied Environments**: These settings simulate real-world physical interactions and spatial relationships. They require agents to engage in navigation, object manipulation, and other complex physical tasks, reflecting changes in the physical environment.

2.2 Natural Language Interaction Environments

With the rise of LLM agents, there is a growing trend among NLP researchers to recontextualize typical NLP tasks as agentic environments (Yao et al., 2023b; Hao et al., 2023; Yao et al., 2023a). These settings are referred to as Natural Language Interaction Environments in our survey.

In NLIEs, the environment remains static until the agent acts. Unlike typical task environments where natural language serves as an intermediary, in NLIEs, both the states and actions are defined linguistically, making the states conceptual and the actions often ambiguous and broadly defined.

Single-Step NLIEs for Question Answering Many works (Yao et al., 2023b; Shinn et al., 2023) formulate the traditional QA setup as a single-step decision-making process, where the agent generates an answer in response to a question. The process starts with the question as the initial state and concludes when the answer is provided as an action.

Deliberate Multi-step NLIEs For tasks where "intermediate steps are not explicitly defined", several studies have transformed NLP tasks into a Markov Decision Process to facilitate agentic workflows. For example, Hao et al. (2023) reformulate subquestions in QA tasks as actions, enabling responses to user queries through a multi-step process. This approach allows the initial question to serve as the beginning of a series of state transitions. Actions may vary from providing direct, free-form answers in single-step QA to strategically formulating subquestions that navigate the agent through sequential updates toward a comprehensive solution. This method aligns more closely with a sequential decision-making process, making it apt for deployment in planning-based agent systems. Additionally, Wan et al. (2024) suggest that "splitting an output sequence into tokens might be a good choice" for defining multi-step NLIEs methodically. Furthermore, Yao et al. (2023a) formulate two-step NLIEs for creative writing by segmenting the problem-solving process into distinct planning and execution phases.

2.3 Tool Environments

Modern LLM agents are often enhanced with external tools that improve their problem-solving capabilities (Inaba et al., 2023; Yao et al., 2023b). The design and integration of these tools add complexity, requiring careful consideration of how LLMs interact not only with the task environments but also with these auxiliary tools. Typically, actions in tool environments involve interactions with resources that remain unaffected by these interactions. For instance, retrieving data from Wikipedia constitutes a "read-only" action, which does not modify the Wikipedia database. This feature distinguishes such tool-use actions from those in conventional task environments or typical reinforcement learning (RL) settings, where actions generally alter the environmental state. Nevertheless, it is important to recognize that tool environment can be dynamic that can undergo changes externally. This aspect reflects the nature that tools should be considered external environments rather than the agent's internal processes.

Nested NLIE-QA + Tool Environments Tool environments are frequently established along with NLIEs to aid in solving QA tasks. Shinn et al. (2023); Yao et al. (2023b) incorporate tools to enhance the factuality of responses. They define command-like actions such as "Search" and "LookUp" to interact with Wikipedia, with "Search" suggesting the top-5 similar entities from the relevant wiki page, and "LookUp" simulating the Ctrl+F functionality in a browser. Beyond simple retrieval, Thoppilan et al. (2022) include a language translator and a calculator for dialog tasks. Similarly, Inaba et al. (2023) employ a calculator, implemented using the Python eval function, to resolve numerical queries within the NumGLUE benchmark.

3 LLM-Profiled Components

This section explores common agentic roles for which LLMs are typically profiled. The components leverage the internal commonsense knowledge and reasoning abilities of LLMs to generate actions, plans, estimate values ², and infer subsequent states.

Universal LLM-Profiled Components Specifically, the following task-agnostic components are profiled and commonly used across various workflows. 1) LLM-Profiled Policy glmpolicy: Policy models are designed to generate decisions, which could be an action or a series of actions (plans) for execution in external environments or use in search and planning algorithms.³ In contrast to typical RL policy models, which learn to maximize cumulative rewards through trial and error, LLM-profiled policy models, denoted as glm_{policy}, utilize pre-trained knowledge and commonsense derived from extensive textual data. We distinguish between two types of glmpolicy: an actor glm_{actor} directly maps a state to an action, whereas a planner glm_{planner} generates a sequence of actions from a given state. 2) LLM-Profiled Evaluators glm_{eval}: glmeval provide feedback crucial for different workflows. They evaluate actions and states in search-based workflows (Hao et al., 2023; Yao et al., 2023a) and revise decisions in feedback-learning workflows (Shinn et al., 2023; Wang et al., 2023b) (refer to §4 for more details). These evaluators are integral to both direct action assessment and broader strategic adjustments. 3) LLM-Profiled Dynamic Models glm_{dynamic}: They predict or describe changes to the environment. Generally, dynamic models form part of a comprehensive world model by predicting the next state s' from the current state s and action a. While typical RL uses the probability distribution $p(s' \mid s, a)$ to model potential next states, LLM-based dynamic models directly predict the next state $s' = \text{glm}_{\text{dynamic}}(s, a)$.

Task-Dependent LLM-Profiled Components In addition to the universal components, certain LLMprofiled components are tailored to specific tasks. For instance, verbalizers are crucial in embodied environments but unnecessary in NLIEs. A verbalizer translates actions and observations into inputs for planners; for example, in the Planner-Actor-Reporter workflow (Wang et al., 2023a), a fine-tuned Visual Language Model (VLM) along with glm_{planner} translates pixel states into textual inputs. Similarly, if environmental feedback is perceivable along with states, a verbalizer may be needed to translate this feedback into verbal descriptions for glm_{policy}, akin to reward shaping in RL where numerical stimuli are generated for policy learning. LLMs profiled as verbalizers, glmverbalizer (Shinn et al., 2023), often guide descriptions according to specified criteria.

²Values refer to the estimated rewards (a quantitative measure of the success or desirability of the outcomes) associated with taking a certain action in a state, widely used in typical RL and MDP

settings to learn policy models that perform desirable behaviors.

³Note that planning algorithms may be utilized to structure a plan of plans; for example, Tree-of-Thought employs tree search, where each node potentially represents either a single action or an entire plan.

	Workflows	Related Frameworks	LMPCs	Applicable Environments
Policy-only	Base	LLM Planner (Huang et al., 2022), DEPS (Wang et al., 2023b), Planner-Actor-Reporter (Dasgupta et al., 2022), Plan- and-solve (Wang et al., 2023a), ReAct (Yao et al., 2023b)	glm _{planner} , glm _{action_selector} (Optional for Embodied Env), glm _{verbalizer} (Optional for Embodied Env)	Embodied Env, NLIEs- Writing, NLIE-QA
	Tool-Use	MultiTool-CoT (Inaba et al., 2023), ReAct (Yao et al., 2023b), Reflexion (Shinn et al., 2023)	glm _{actor}	NLIEs
Search	Traversal & Heuristic	Tree-of-Thoughts (ToT) (Yao et al., 2023a), Tree-BeamSearch (Xie et al., 2023), Boost-of- Thoughts (Chen et al., 2024)	glm _{actor} or glm _{planner} , glm _{eval}	Gaming, NLIEs-Writing, NLIE-QA
	MCTS	RAP (Hao et al., 2023), Wan et al. (2024)	$\mathrm{glm}_\mathrm{actor}, \mathrm{glm}_\mathrm{dynamic}, \mathrm{glm}_\mathrm{eval}$	Gaming, NLIEs-QA
Feedback Learning	from glm _{eval}	Reflexion (Shinn et al., 2023), Self-refine (Madaan et al., 2023)	glm _{actor} , glm _{eval}	NLIEs-QA
	from glm _{eval} & Task Env	Reflexion (Shinn et al., 2023)	$\begin{array}{ll} glm_{actor}, & glm_{eval}, \\ glm_{fb_verbalizer} \end{array}$	Embodied Env
	from Tools & Humans	Guan et al. (2023)	$glm_{planner}, glm_{pddl_{translator}}$	Embodied Env
	from Tools & glm _{eval}	CRITIC (Gou et al., 2024)	glm _{actor} , glm _{eval}	NLIEs

Table 2: Workflows of LLM-Based Agents and Related Frameworks. We summarize LLM-Profiled Components (LMPCs) and applicable environments based on the original papers of the listed frameworks, although other possibilities exist, e.g., using glm_{planner} within the tool-use workflow and applying the base workflow to gaming environments.

4 Workflows of LLM-Based Agents

This section explores different workflows and the utilization of various LLM-Profiled Components (LM-PCs), as illustrated in Figure 1. Specifically, we will aggregate proposed frameworks based on workflow types, as demonstrated in Table 2. This section delves into diverse workflows and the application of distinct LLM-Profiled Components (LMPCs), as visualized in Figure 1. We categorize and consolidate the related frameworks according to the workflows, exemplified in Table 2. It is noteworthy that one framework could employ distinct workflows according to tasks or environments. More details of the frameworks are summarized in Appendix A.

4.1 Policy-Only Workflows

Base and tool-use workflows only require LLMs to be profiled as policy models. In the realm of embodied tasks, many projects deploy base workflows with glm_{planner} to generate plans using LLM agents, such as the LLM Planner (Huang et al., 2022), Planner-Actor-Reporter (Dasgupta et al., 2022), and DEPS (Wang et al., 2023b). The Plan-and-solve approach (Wang et al., 2023a) applies a base workflow to NLIEs-QA. Such base workflow can also be applied to other NLIE tasks, e.g., creative writing (Yao et al., 2023a). In contrast, the tool-use workflow with glm_{actor} is always applied to NLIEs like ReAct (Yao et al., 2023b), Reflexion (Shinn et al., 2023), and MultiTool-CoT (Inaba et al., 2023).

4.2 Search Workflows

Unlike base agents with glm_{planner}, which generates a sequence of actions for a plan at one generation, actions in search workflows are organized into tree (Yao et al., 2023a; Hao et al., 2023) and graph (Liu et al., 2023) for exploration. Planning or search algorithms can explore sequential decisions in a non-linear manner. During the process, the tree (or solution) is constructed by adding nodes, each representing a partial solution with the input and the sequence of thoughts/actions so far. Data structures such as trees enable strategic searches over actions derived from multiple reasoning paths. This is accomplished using algorithms like beam search (Xie et al., 2023), depthfirst and breadth-first search (DFS and BFS) (Yao et al., 2023a), and Monte-Carlo Tree Search (MCTS) (Hao et al., 2023).

Generally, LMPCs are used to explore the path towards the goal. Instead of directly applying actions on external environments within policy-only workflows, glm_{policy} generates multiple action samples to facilitate action selection for a search process, while glm_{eval} is used to calculate values for action/state evaluation during exploration (Yao et al., 2023a; Chen et al., 2024) or as a reward model (Hao et al., 2023). Search via Traversal and Heuristic The Tree-of-Thoughts (ToT) workflow (Yao et al., 2023a) uses glm_{policy} to expand nodes over a tree, and glm_{eval} provides a fixed value estimate to select a node for further expansion. To expand a tree, the Tree-BeamSearch workflow (Xie et al., 2023) employs beam search, while ToT appies depth-/breadth-first search (DFS and BFS). However, the BFS is indeed beam search with Nbeams since the values generated by the utility model glm_{eval} to maintain the N most promising nodes. ⁴

Simulated-Based Search via MCTS The RAP workflow (Hao et al., 2023) also builds a tree through searching and includes glm_{policy} and glm_{eval} to expand nodes. However, through the employment of MCTS, a simulation-driven search strategy, the nodes chosen for expansion are determined not only by the static outputs from $\operatorname{glm}_{\operatorname{eval}}$ or other heuristics (whether they indicate goal attainment), but also by the cumulative statistics accrued over multiple simulations. Specifically, nodes that lead to better average rewards for subsequent nodes across all simulations (or trajectories) are indeed more likely to be expanded further. Following the selection phase, glm_{policy} participates in action sampling during the expansion phase. Then, it collaborates intimately with glm_{dynamic} and glm_{eval} in the simulation phase, functioning as the roll-out policy. Specifically, glm_{policy} samples an action a_t given the current state s_t , which in turn, is assessed by glm_{eval}. The top-scoring action is selected, with $glm_{dynamic}$ using it to derive s_{t+1} , iteratively simulating the trajectory.

4.3 Feedback-Learning Workflows

There are primarily four main sources of feedback: glm_{eval} (internal feedback), humans, task environments, and tools.

Reflexion (Shinn et al., 2023) and Self-Refine (Madaan et al., 2023) utilize glm_{eval} to reflect on the prior generations of glm_{policy} , enabling glm_{policy} to learn from such reflections. Unlike search workflows where the outputs of glm_{eval} are employed for action selection during tree expansion, here, the feedback is used to revise one complete decision, allowing glmpolicy to re-generate another. In tasks that involve physical interaction, glm_{eval} in Reflexion also integrates external information from the task environments (Shinn et al., 2023). Similarly, glm_{eval} can receive information from tools to generate feedback, as demonstrated in the CRITIC workflow (Gou et al., 2024). In this setup, the necessity of invoking tools for feedback

is autonomously determined by glm_{eval} (See Table 15 for an example), whereas in Reflexion, feedback transmission is hardcoded by the workflow design. Humans could provide direct feedback to glm_{policy} without the need of glm_{eval} , as noted by the workflow from Guan et al. (2023).

5 Implementations of LMPCs

In this section, we explore different implementation approaches for LMPCs, covering strategies that are independent of specific workflows and tasks, implementations specifically designed for certain tasks, and those tailored to particular workflows.

5.1 Universal Implementations

LLMs are normally profiled by leveraging Chain-of-Thought (CoT) prompting to transcend basic inputoutput inference, facilitating the creation of intermediate reasoning steps. This is achieved through two techniques: **Zero-shot CoT** integrates a CoT trigger, such as "Let's think step-by-step" (Kojima et al., 2022), within task instructions, while while **few-shot CoT** incorporates handcrafted reasoning steps within provided examples for in-context learning (Wei et al., 2022).

As shown in Table 3, some studies (Wang et al., 2023a) employ zero-shot CoT prompting, but most (Yao et al., 2023b; Shinn et al., 2023; Hao et al., 2023) implement LLM policy models via few-shot CoT. Zero-shot CoT implementation of $glm_{planner}$ often fails to produce long-horizon plans, unlike few-shot CoT prompting (Wang et al., 2023b). While effective, few-shot prompting requires manual compilation of demonstrations with reasoning sequences, leading to increased manual work and computational resource use. Methods like Auto CoTs (Zhang et al., 2023) that automatically generate few-shot demonstrations could mitigate this challenge.

5.2 Workflow-Specific Implementations

 glm_{policy} Implementations Two distinct implementations can be employed to enable glm_{policy} to trigger tool usage within tool-use and feedback learning workflows (receiving feedback from tools).

1. Using In-Generation Triggers: Tools could be invoked during the reasoning generation process, e.g., MultiTool-CoT (Inaba et al., 2023). The agent program monitors each token produced, pausing text generation when a tool trigger is detected. This pause allows for the invocation of tools, whose outputs are then inserted into the prompt to complete the reasoning. The triggers for these tools are defined either through

⁴Typically, BFS does not use a utility model to decide which nodes to expand because it systematically explores all possible nodes at each depth.

	Prompting	Example Works	Example Prompts (in Appendix)
glm _{actor}	Few-shot	ReAct (Yao et al., 2023b), Reflexion (Shinn et al., 2023), RAP (Hao et al., 2023), MultiTool-CoT (Inaba et al., 2023)	Table 8, 10
glm _{planner}	Zero-shot	Plan-and-Solve (Wang et al., 2023a), LLM Planner (Huang et al., 2022)	Table 6
	Few-shot	DEPS (Wang et al., 2023b), Planner-Actor-Reporter (Dasgupta et al., 2022)	
glm _{evaluator}	Few-shot	RAP (Hao et al., 2023), Tree-BeamSearch (Xie et al., 2023), Reflexion (Shinn et al., 2023), CRITIC (Gou et al., 2024)	Table 12, 13
glm _{dynamic}	Few-shot	RAP (Hao et al., 2023)	Table 16

Table 3: Prompting Methods of LLM-Profiled Components

Task Formulation	Feedback Types	Applicable Workflows	Example Works
Text Generation	Free-form reflection	Feedback-learning workflows	Self-Refine (Madaan et al., 2023), Reflexion (Shinn et al., 2023), CRITIC (Gou et al., 2024)
Binary/Multi-class Classification	Discrete values	Search workflows	RAP (Hao et al., 2023), Tree-BeamSearch (Xie et al., 2023) ToT (Yao et al., 2023a)
Binary Classifica- tion	Continuous values (log- its)	Search workflow via MCTS	RAP (Hao et al., 2023)
Multi-choice QA	Choices of top-N ac- tions	Search workflows via traversal and heuristic	ToT (Yao et al., 2023a)

Table 4: Workflow-Specific LLM-Profiled Evaluators According to Task Formulation and Feedback Types

tool descriptions, few-shot demonstrations 5 , or a combination of both 6 .

2. Reasoning-Acting (ReAct) Strategy for Tool Use: Introduced by Yao et al. (2023b), each reasoning or acting step is separately verbalized via a complete generation. Although the ReAct framework (Yao et al., 2023b) unifies tool actions within the tool-use workflow and task-specific actions within the base workflow, we argue that the strategies for tool actions and task-specific actions should be distinguished. Because tool actions and task-specific actions are triggered differently, an aspect that will be emphasized further in the subsequent section about task-specific implementations.

 glm_{eval} Implementations Commonly, different workflows require distinct feedback types and task formulations. There are four scenarios regarding the two perspectives, as summarized in Table 4: 1) Generating free-form reflection: This reflective output is frequently integrated into the prompt of glm_{policy} within feedback-learning workflows (Shinn et al., 2023; Gou et al., 2024). glm_{eval} is designed to reflect on previous states and actions within feedback-learning workflows. Depending on specific feedback-learning workflows, it could incorporate external inputs from task or tool environments to enrich the reflection process. 2) Binary/Multiclass Classification: Feedback is obtained from discrete output tokens, commonly "no" or "yes." These can be converted into 0/1 values for search workflows. This scalar values can be employed as reward signals within Monte Carlo Tree Search (MCTS) simulations (Hao et al., 2023), or they may be employed directly to guide decision-making at each step of tree traversal (Yao et al., 2023a). **3) Binary classification with scalar values**: This approach differs from the previous one by employing the logit values of tokens to calculate scalar feedback values. For instance, the probability of a "yes" response is computed using the formula:

$$v = \text{probs}_{"\text{yes"}} = \frac{e^{l_{"\text{yes"}}}}{e^{l_{"\text{yes"}}} + e^{l_{"\text{no"}}}},$$

where $l_{"yes"}$ and $l_{"no"}$ are the logits for the "yes" and "no" tokens, respectively. ⁷ These scalar values can then be utilized as rewards in search workflows for MCTS. **4) Multi-choice QA**: Employed in settings where a selection from multiple choices is required, supporting tasks that involve choosing from top-N possible actions, as utilized in search workflows for action selection (Yao et al., 2023a).

5.3 Task-Specific Implementations

glm_{policy} **Implementations** The noteworthy details include: 1) **Multi-Step Generation**: For tasks that inherently involve sequential decision-making (e.g., "put a cool tomato in the microwave"), post-processing steps are often required for glm_{policy} to work as a policy model. After a reasoning path is generated via

⁵In-generation triggers via few-shot demos: see an example prompt in Table 15)

⁶In-generation triggers via descriptions and few-shot demos: see an example prompt in Table 8)

 $^{^{7}}$ Note that such implementations of glm_{eval} are not accessible via black-box LLMs.

CoT implementations of glm_{policy}, a subsequent call is made to extract executable actions. Besides, the first generation of glm_{planner} often contains high-level actions (HLA) that must be further transformed into primitive actions, before executable actions are extracted. This is, normally, unnecessary for tasks from NLIEs since both plan generation and execution may occur within a single LLM generation⁸. 2) Implicit Planning: Another point to consider is that although glm_{actor} are not explicitly implemented to generate plans, it may autonomously formulate plans during the reasoning phase before deciding on the current action (Shinn et al., 2023; Yao et al., 2023b)⁹. These generated plans are maintained as internal states and do not serve as communication signals with other components.

ReAct Implementation of glm_{actor} The ReAct framework (Yao et al., 2023b) unifies tool actions within the tool-use workflow and task-specific actions within the base workflow. However, the sequence in which reasoning and action outputs alternate is task-dependent. For question answering (QA), the generations of reasoning steps and tool actions are fixed, with alternating prompts for thinking and acting. ¹⁰. In contrast, for embodied tasks, the decision whether to proceed with thinking or acting in the next step is autonomously determined by glm_{policy} ¹¹.

glm_{eval} **Implementations** glm_{eval} can be configured to assess different task-specific perspectives, with specific agentic prompts determining the evaluation criteria. Generally, usefulness could be used to evaluate any actions (Hao et al., 2023) ¹². In NLIE-QA scenarios, a common metric is the factuality (truthfulness) of responses (Gou et al., 2024) ¹³.

6 Future Work

As we delve deeper into LMPCs and agentic workflows, several key directions for future research are identified to advance the development of fully autonomous agents across various tasks.

Universal Tool Use One direction is to move beyond predefined tool use for specific tasks and develop

¹³Evaluation Criteria (Factuality/Truthfulness): See example prompts in Table 14 and 15

strategies that enable LLMs to autonomously determine tool usage based on the specific requirements of the task at hand. Another direction is to integrate tool use for both policy models and evaluators. In other words, LLMs could reason over the use of the tool across various tasks and flexibly jump between different roles. The insight of its potential is detailed in Appendix C.

Unified Frameworks Across Tasks As detailed in §5, despite many frameworks are presented with integrated conceptual workflows, many components are task-specific. For example, ReAct seeks to harmonize tool actions and task-specific actions. However, these workflows and specific implementations of LMPCs are different across tasks, such as hardcoded reasoning and acting steps in NLIE-QA versus autonomously determined reasoning and acting steps in embodied environments. Similarly, although the feedback-learning loop in Reflexion is theoretically unified, in practice, external feedback is generated only in embodied environments, not in NLIE-QA.

Reducing Bandwidth There are several potential strategies for reducing the bandwidth required for LLM inference ¹⁴, including using Stochastic glm_{actor} (Details in Appendix D).

7 Conclusion

This survey provides a summary of common workflows and LLM-Profiled Components to encourage the reuse of these components and the expansion of existing workflows through the integration of both task-specific LMPCs and non-LLM components. This approach aims to foster the development and reproducibility of agentic workflows.

Limitations

This survey omits discussions on memory design ¹⁵ and the integration of peripheral components into agentic workflows ¹⁶, as our focus is on the details of common LLM-profiled components within agentic workflows to facilitate the implementation of reusable components and extensible workflows. This distinctly sets our work apart from other surveys.

References

Sijia Chen, Baochun Li, and Di Niu. 2024. Boosting of thoughts: Trial-and-error problem solving with large lan-

 $^{^8 \}text{Simultaneous plan generation}$ and execution: See an example prompt in Table 6

⁹Implicit Planning: See an example prompt in Table 7

 $^{^{10}\}mbox{Reasoning-Acting Strategy (QA tasks): See an example prompt in Table 10$

¹¹Reasoning-Acting Strategy (embodied tasks): See an example prompt in Table 7

¹²Evaluation Criteria (Usefulness): See an example prompt in Table 12

¹⁴Here, bandwidth refers to the volume of information processed during a single LLM generation

¹⁵Appendix E provides a brief discussion on memory in LLMbased agents

¹⁶These are concisely summarized in Appendix A

guage models. In *The Twelfth International Conference* on Learning Representations.

- Ishita Dasgupta, Christine Kaeser-Chen, Kenneth Marino, Arun Ahuja, Sheila Babayan, Felix Hill, and Rob Fergus. 2022. Collaborating with language models for embodied reasoning. In *Second Workshop on Language and Reinforcement Learning*.
- Linxi Fan, Guanzhi Wang, Yunfan Jiang, Ajay Mandlekar, Yuncong Yang, Haoyi Zhu, Andrew Tang, De-An Huang, Yuke Zhu, and Anima Anandkumar. 2022. Minedojo: Building open-ended embodied agents with internetscale knowledge. In *Thirty-sixth Conference on Neural Information Processing Systems Datasets and Benchmarks Track.*
- Jonathan Goldsmith. 2023. Wikipedia: A python library that makes it easy to access and parse data from wikipedia. Python Package Index.
- Zhibin Gou, Zhihong Shao, Yeyun Gong, yelong shen, Yujiu Yang, Nan Duan, and Weizhu Chen. 2024. CRITIC: Large language models can self-correct with toolinteractive critiquing. In *The Twelfth International Conference on Learning Representations*.
- Lin Guan, Karthik Valmeekam, Sarath Sreedharan, and Subbarao Kambhampati. 2023. Leveraging pre-trained large language models to construct and utilize world models for model-based task planning. In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Shibo Hao, Yi Gu, Haodi Ma, Joshua Hong, Zhen Wang, Daisy Wang, and Zhiting Hu. 2023. Reasoning with language model is planning with world model. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, pages 8154–8173, Singapore. Association for Computational Linguistics.
- Wenlong Huang, Pieter Abbeel, Deepak Pathak, and Igor Mordatch. 2022. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. In *International Conference on Machine Learning*, pages 9118–9147. PMLR.
- Tatsuro Inaba, Hirokazu Kiyomaru, Fei Cheng, and Sadao Kurohashi. 2023. MultiTool-CoT: GPT-3 can use multiple external tools with chain of thought prompting. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 1522–1532, Toronto, Canada. Association for Computational Linguistics.
- Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. In Advances in Neural Information Processing Systems.
- Hanmeng Liu, Zhiyang Teng, Leyang Cui, Chaoli Zhang, Qiji Zhou, and Yue Zhang. 2023. Logicot: Logical chainof-thought instruction-tuning.
- Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, et al. 2023. Selfrefine: Iterative refinement with self-feedback. *arXiv preprint arXiv:2303.17651*.

- Potsawee Manakul, Adian Liusie, and Mark JF Gales. 2023. Selfcheckgpt: Zero-resource black-box hallucination detection for generative large language models. *arXiv preprint arXiv:2303.08896*.
- Stuart J Russell and Peter Norvig. 2010. Artificial intelligence a modern approach. London.
- Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. 2023. Whose opinions do language models reflect? *arXiv preprint arXiv:2303.17548*.
- Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning.
- Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Cote, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. 2021. {ALFW}orld: Aligning text and embodied environments for interactive learning. In *International Conference on Learning Representations*.
- Richard S Sutton and Andrew G Barto. 2018. *Reinforcement learning: An introduction*. MIT press.
- Romal Thoppilan, Daniel De Freitas, Jamie Hall, Noam Shazeer, Apoorv Kulshreshtha, Heng-Tze Cheng, Alicia Jin, Taylor Bos, Leslie Baker, Yu Du, et al. 2022. Lamda: Language models for dialog applications. *arXiv preprint arXiv:2201.08239*.
- Ziyu Wan, Xidong Feng, Muning Wen, Ying Wen, Weinan Zhang, and Jun Wang. 2024. Alphazero-like tree-search can guide large language model decoding and training.
- Lei Wang, Chen Ma, Xueyang Feng, Zeyu Zhang, Hao Yang, Jingsen Zhang, Zhiyuan Chen, Jiakai Tang, Xu Chen, Yankai Lin, et al. 2024. A survey on large language model based autonomous agents. *Frontiers of Computer Science*, 18(6):1–26.
- Lei Wang, Wanyu Xu, Yihuai Lan, Zhiqiang Hu, Yunshi Lan, Roy Ka-Wei Lee, and Ee-Peng Lim. 2023a. Plan-and-solve prompting: Improving zero-shot chainof-thought reasoning by large language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2609–2634, Toronto, Canada. Association for Computational Linguistics.
- Siyuan Wang, Zhongkun Liu, Wanjun Zhong, Ming Zhou, Zhongyu Wei, Zhumin Chen, and Nan Duan. 2022. From lsat: The progress and challenges of complex reasoning. *IEEE/ACM Trans. Audio, Speech and Lang. Proc.*, 30:2201–2216.
- Zihao Wang, Shaofei Cai, Guanzhou Chen, Anji Liu, Xiaojian Ma, and Yitao Liang. 2023b. Describe, explain, plan and select: Interactive planning with LLMs enables openworld multi-task agents. In *Thirty-seventh Conference* on Neural Information Processing Systems.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed H. Chi, Quoc V Le, and Denny Zhou. 2022. Chain of thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*.

- Brandon T Willard and Rémi Louf. 2023. Efficient guided generation for llms. *arXiv preprint arXiv:2307.09702*.
- Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Shaokun Zhang, Erkang Zhu, Beibin Li, Li Jiang, Xiaoyun Zhang, and Chi Wang. 2023. Autogen: Enabling next-gen llm applications via multi-agent conversation framework. *arXiv preprint arXiv:2308.08155*.
- Yuxi Xie, Kenji Kawaguchi, Yiran Zhao, Xu Zhao, Min-Yen Kan, Junxian He, and Qizhe Xie. 2023. Self-evaluation guided beam search for reasoning. In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik Narasimhan. 2023a. Tree of thoughts: Deliberate problem solving with large language models.
- Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. 2023b. React: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations*.
- Zhuosheng Zhang, Aston Zhang, Mu Li, and Alex Smola. 2023. Automatic chain of thought prompting in large language models. In *The Eleventh International Conference* on Learning Representations (ICLR 2023).
- Wanjun Zhong, Ruixiang Cui, Yiduo Guo, Yaobo Liang, Shuai Lu, Yanlin Wang, Amin Saied, Weizhu Chen, and Nan Duan. 2023. Agieval: A human-centric benchmark for evaluating foundation models. arXiv preprint arXiv:2304.06364.
- Wanjun Zhong, Siyuan Wang, Duyu Tang, Zenan Xu, Daya Guo, Yining Chen, Jiahai Wang, Jian Yin, Ming Zhou, and Nan Duan. 2022. Analytical reasoning of text. In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 2306–2319, Seattle, United States. Association for Computational Linguistics.

A Frameworks of LLM-Based Agents

Table 5 demonstrates the workflow(s), LMPCs, and non-LMPC components of each framework.

B Examples Prompts

B.1 LLM-Profiled Policy Models

Base Workflow: A planner for the NLIE-QA and an actor for the householding environment (ALFRED) are demonstrated in Table 6 and 7, respectively. 2) Tool-Use Workflow: Actors under NLIE-QA is demonstrated in Table 8, 9, and 10. The first two tables show the implementation of in-generation triggers, while the last one demonstrates the ReAct implementation.
 Search Workflow: An actor is required during the expansion stage of MCTS in the RAP workflow. The prompts and expected generations are shown in Table 11.

B.2 Prompts for LLM Evaluators

Table 12 and 13 show LLM evaluators that are profiled as classification tasks, while Table 15 demonstrates another to general free-form text.

B.3 Prompts as Dynamic Models

Table 16 is profiled as a dynamic model.

C Creation of a Task-Agnostic Tool Environment

Previous work always limits tools to specific applications like NLIE-QA, future work should aim to establish a comprehensive tool environment that encompasses a wide array of tools suitable for various tasks. A major challenge here is adapting a single actor to utilize such an environment effectively. While in-generation strategies are constrained as triggers are typically only straightforward for basic tools with simple arguments, a reasoning-acting strategy might offer more promise. Nonetheless, defining tools remains a challenge, especially in terms of efficient in-context learning or fine-tuning for tool utilization.

D Stochastic glm_{actor}

Typically, a single action is sampled from the output of glmactor. Exploring a stochastic glmactor, which provides a distribution over possible actions, can enhance the stochastic nature of the glmpolicy and improve efficiency. This approach could include investigating constrained generation techniques (Willard and Louf, 2023). Additionally, using such a distribution could efficiently serve as rewards for all possible actions, potentially eliminating the need for a separate glmeval to model rewards in certain workflows. This method allows for the simultaneous expansion of multiple potential nodes in one generation step, rather than expanding each node individually in search-based workflows (Hao et al., 2023).

E Memory

The implementations of memory in the reviewed works are typically straightforward and arbitrary. Commonly, static information (e.g., profiling messages) is manually constructed and stored, whereas dynamic information (e.g., feedback) is handled via runtime data structures during interactions within each workflow. While the management of hybrid memory systems—requiring the explicit processing and management of short-term and long-term memory—is extensively discussed in a previous survey by Wang et al. (2024), such memory management aspects are beyond the focus of this survey, which centers on LLM-based workflows.

	Involved Workflows	LMPCs	Non-LMPC Components	Applied Environments
Tree-of-Thoughts (ToT) (Yao et al., 2023a)	Search via Traversal & Heuristic	glm _{actor} , glm _{eval} , glm _{planner} (only for NLIEs-Writing)	Search Tree	Gaming; NLIEs-Writing
Tree-BeamSearch (Xie et al., 2023)	Search-based via Traversal & Heuristic	glm_{actor}, glm_{eval}	Search Tree	NLIE-QA
RAP (Hao et al., 2023)	Search via MCTS	glm _{actor} , glm _{dynamic} ,glm _{eval}	Search Tree	Gaming; NLIEs-QA
LLM Planner (Huang et al., 2022)	Base	glm _{planner}	MLM for action translation	Embodied Env
DEPS (Wang et al., 2023b)	Base	$glm_{planner},glm_{action_selector}, glm_{verbalizer}$	Immediate actor, VLM+GLM as verbalizer	Embodied Env
Planner-Actor- Reporter (Dasgupta et al., 2022)	Base	glm _{planner}	RL actor, Trained classi- fier+Hard code as verbalizer	Embodied Env
Plan-and-solve (Wang et al., 2023a)	Base	glm _{planner}	/	NLIEs-QA
MultiTool-CoT (In- aba et al., 2023)	Tool-Use	glm _{actor}	/	NLIEs
ReAct (Yao et al., 2023b)	Tool-Use	glm _{actor}	1	NLIEs
	Base	glm _{actor}	/	Embodied Env
Guan et al. (2023)	Feedback Learning (from Tools & Humans)	$\mathrm{glm}_{\mathrm{planner}},\mathrm{glm}_{\mathrm{pddl_translator}}$	Domain Ex- perts, Domain- independent Planner	Embodied Env
CRITIC (Gou et al., 2024)	Feedback Learning (from Tool & glm _{eval})	glm _{actor}	/	NLIEs
Self-refine (Madaan et al., 2023)	Feedback Learning (from glm _{eval})	glm _{actor} , glm _{eval} ,	/	NLIEs
Reflexion (Shinn et al., 2023)	Feedback Learning (from glm _{eval}), Tool-Use	$\operatorname{glm}_{\operatorname{actor}}, \operatorname{glm}_{\operatorname{eval}},$	/	NLIEs-QA
	Feedback Learning (from Task Env & glm _{eval}),	$\begin{array}{c} glm_{actor}, & glm_{eval}, \\ glm_{fb_verbalizer} \end{array}$	heuristic_func _{eval}	Embodied Env

Table 5: Frameworks for LLM-based Agents. MLM: Masked Language Model.

Q: In a dance class of 20 students, 20% enrolled in contemporary dance, 25% of the remaining enrolled in jazz dance, and the rest enrolled in hip-hop dance. What percentage of the entire students enrolled in hip-hop dance? A: Let's first understand the problem and devise a plan to solve the problem. Then, let's carry out the plan and solve the problem step by step. Plan:

Step 1: Calculate the total number of students who enrolled in contemporary and jazz dance.

Step 2: Calculate the total number of students who enrolled in hiphop dance.

Step 3: Calculate the percentage of students who enrolled in hiphop dance.

Solution:


Step 1: 20% of 20 students is 4 students. 25% of the remaining 16 students is 4 students. So, a total of 8 students enrolled in contemporary and jazz dance.

Step 2: The remaining 12 students enrolled in hip-hop dance.

Step 3: The percentage of students who enrolled in hip-hop dance is 12/20 = 60%.

Therefore, the answer (arabic numerals) is

60%



Interact with a household to solve a task. Here are two examples. You are in the middle of a room. Looking quickly around you, you see a cabinet 9, a cabinet 8, a cabinet 7, a cabinet 6, a cabinet 5, a cabinet 4, a cabinet 3, a cabinet 2, a cabinet 1, a coffeemachine 1, a countertop 3, a countertop 2, a countertop 1, a drawer 9, a drawer 8, a drawer 7, a drawer 6, a drawer 5, a drawer 4, a drawer 3, a drawer 2, a drawer 1, a fridge 1, a garbagecan 1, a microwave 1, a shelf 3, a shelf 2, a shelf 1, a sinkbasin 1, a stoveburner 4, a stoveburner 3, a stoveburner 2, a stoveburner 1, and a toaster 1.

Your task is to: put a cool mug in shelf.

> think: To solve the task, I need to find and take a mug, then cool it with fridge, then put it in shelf.

OK.

> think: First I need to find a mug. A mug is more likely to appear in countertop (1-3), coffeemachine (1), cabinet (1-9), shelf (1-3), drawer (1-9). I can check one by one, starting with countertop 1.

OK.

> go to countertop 1

On the countertop 1, you see a knife 1, a pan 2, a pan 1, and a plate 1.

•••

> think: Now I cool the mug. Next, I need to put it in/on shelf 1. OK.

> go to shelf 1

On the shelf 1, you see a cup 2, a cup 1, a peppershaker 1, and a saltshaker 1. > put mug 3 in/on shelf 1

You put the mug 3 in/on the shelf 1.

Here is the task: You are in the middle of a room. Looking quickly around you, you see a cabinet 6, a cabinet 5, a cabinet 4, a cabinet 3, a cabinet 2, a cabinet 1, a coffeemachine 1, a countertop 3, a countertop 2, a countertop 1, a drawer 3, a drawer 2, a drawer 1, a fridge 1, a garbagecan 1, a microwave 1, a shelf 3, a shelf 2, a shelf 1, a sinkbasin 1, a stoveburner 4, a stoveburner 3, a stoveburner 2, a stoveburner 1, and a toaster 1.

Your task is to: put a cool tomato in microwave.

>

think: To solve the task, I need to find a tomato, then cool it with the fridge, and finally put it in the microwave.

OK.

>

think: First, I need to find a tomato. A tomato is more likely to be found on the countertop (1-3), cabinet (1-6), drawer (1-3), shelf (1-3), or the sinkbasin. I can start by checking the countertop 1.

OK. >

go to countertop 1

On the countertop 1, you see a dishsponge 1, and a mug 2. ...

Table 7: An LLM Actor within Base Workflow under the Alfred World Benchmark, implemented by the few-shot CoT method. The content in the shadow box is generated by LLM. Source from (Yao et al., 2023b).

Use the following tools at your disposal and answer some questions:

- «Calculator»

- «Chemical reaction predictor»

- «Molar mass list»

Q: Find the amount of H2CO3 formed on combining 2 moles of CO2 and 2 moles of H2O. A: First, use the chemical reaction predictor to determine the chemical equation for the reaction. Reactants: 2CO2, 2H2O Products: 2CO2, 2H2OProducts: 2H2CO3«Chemical reaction predictor» $2CO2 + 2H2O \rightarrow 2H2CO3$ Second, use the molar mass list to determine the molar mass of H2CO3. H2CO3 «Molar mass list» 62 g/mol

Third, use the calculator to calculate the amount of 2 moles of H2CO3. $2 \times 62 =$ «Calculator» 124

Therefore, 124 g of H2CO3 is formed. Q: Find the amount of Calcium hydroxide that is required to react with 2 moles of Carbon dioxide to form 2 moles of Calcium carbonate along with 2 moles of Water.

A:

Table 8: An LLM actor with tool use implemented by MultiTool-CoT (Inaba et al., 2023).

Q: Julie is reading a 120-page book. Yesterday, she was able to read 12 pages and today, she read twice as many pages as yesterday. If she wants to read half of the remaining pages tomorrow, how many pages should she read?

A: Julie read twice as many pages as yesterday, so she read 12 * 2 = 24 pages today. Since yesterday, Julie read 12 + 24 = 36 pages. So, there are 120 - 36 = 84 pages left to be read. Since she wants to read half of the remaining pages, she should read 84 / 2 = 42 pages. The answer is 42.

Q: Ken created a care package to send to his brother, who was away at boarding school. Ken placed a box on a scale, and then he poured into the box enough jelly beans to bring the weight to 2 pounds. Then, he added enough brownies to cause the weight to triple. Next, he added another 2 pounds of jelly beans. And finally, he added enough gummy worms to double the weight once again. What was the final weight of the box of goodies, in pounds?

A: Ken poured jelly beans into the box until the weight was 2 pounds, so the weight of the box was 2 pounds at first. Then Ken added enough brownies to cause the weight to triple, so the weight of the box was 2 * 3 = 6 pounds. After Ken added another 2 pounds of jelly beans, the weight of the box was 6 + 2 = 8 pounds. Finally, he added enough gummy worms to double the weight once again, so the weight of the box was 8 * 2 = 16 pounds. The answer is 16.

Q: James writes a 3-page letter to 2 different friends twice a week. How many pages does he write a year?


A: James writes a 3-page letter to 2 different friends twice a week, so he writes 3 * 2 * 2 = 12 pages every week. There are 52 weeks in a year, so he writes 12 * 52 = 624 pages a year. The answer is 624.

Q: Natalia sold clips to 48 of her friends in April, and then she sold half as many clips in May. How many clips did Natalia sell altogether in April and May?

A: Natalia sold 48 clips in April and half as many clips in May, so she sold 48 / 2 = 24 clips in May. Altogether, she sold 48 + 24 = 72 clips. The answer is 72.

Q: Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with four. She sells the remainder at the farmers' market daily for \$2 per fresh duck egg. How much in dollars does she make every day at the farmers' market? A:"

Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with four, so she uses $3 + 4 = \ll 3 + 4 = 7 \gg 7$ eggs daily. Thus, she sells $16 - 7 = \ll 16 - 7 = 9 \gg 9$ eggs at the farmers' market daily. Therefore, she makes $9 * \$2 = \$ \ll 9 \ast 2 = 18 \gg 18$ every day at the farmers' market. Answer: 18.



Solve a question answering task by having a Thought, then Finish with your answer. Thought can reason about the current situation. Finish[answer] returns the answer and finishes the task. Here are some examples:

Question 1: What is the elevation range for the area that the eastern sector of the Colorado orogeny extends into?

Thought: Let's think step by step. The eastern sector of Colorado orogeny extends into the High Plains. High Plains rise in elevation from around 1,800 to 7,000 ft, so the answer is 1,800 to 7,000 ft.

Action: Finish[1,800 to 7,000 ft]

•••

Question 6: Were Pavel Urysohn and Leonid Levin known for the same type of work?

Thought: Let's think step by step. Pavel Urysohn is a mathematician. Leonid Levin is a mathematician and computer scientist. So Pavel Urysohn and Leonid Levin have the same type of work.

Action: Finish[Yes] END OF EXAMPLES)

Question: VIVA Media AG changed its name in 2004. What does their new acronym stand for?

Thought:

Let's think step by step. VIVA Media AG changed its name in 2004. The new acronym must stand for the new name they adopted. To find the answer, we need to research the new name of VIVA Media AG after 2004.Action: Finish[Further research is needed to determine the new acronym.]

Action:

Finish[Further research is needed to determine the new acronym.]

Table 10: An LLM Actor within tool-use workflow for the HotPot-QA Benchmark, implemented by few-Shot CoT. The content in the shadow box is generated by LLM. Source from Yao et al. (2023b).

Given a question, please decompose it into sub-questions. For each subquestion, please answer it in a complete sentence, ending with "The answer is". When the original question is answerable, please start the subquestion with "Now we can answer the question:"

Question 1: James writes a 3-page letter to 2 different friends twice a week. How many pages does he write a year?

Question 1.1: How many pages does he write every week?

Answer 1.1: James writes a 3-page letter to 2 different friends twice a week, so he writes 3 * 2 * 2 = 12 pages every week. The answer is 12.

Question 1.2: How many weeks are there in a year?

Answer 1.2: There are 52 weeks in a year. The answer is 52.

Question 1.3: Now we can answer the question: How many pages does he write a year?

Answer 1.3: James writes 12 pages every week, so he writes 12 * 52 = 624 pages a year. The answer is 624.

•••

Question 5: Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with four. She sells the remainder at the farmers' market daily for \$2 per fresh duck egg. How much in dollars does she make every day at the farmers' market?

Question 5.1:

How many eggs does Janet have left after eating three for breakfast and baking muffins with four?

Table 11: An LLM Actor under the GSM8K Benchmark. The content in the shadow box is generated by LLM. Source from Hao et al. (2023).

Given a question and some sub-questions, determine whether the last subquestion is useful to answer the question. Output 'Yes' or 'No', and a reason. **Question 1:** Four years ago, Kody was only half as old as Mohamed. If Mohamed is currently twice as 30 years old, how old is Kody? **Question 1.1:** How old is Mohamed? **Question 1.2:** How old was Mohamed four years ago? **New question 1.3:** How old was Kody four years ago? *Is the new question useful? Yes. We need the answer to calculate how old is Kody now.*

•••

Question 5: Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with four. She sells the remainder at the farmers' market daily for \$2 per fresh duck egg. How much in dollars does she make every day at the farmers' market?

New question 5.1: Now we can answer the question: How much in dollars does she make every day at the farmers' market? *Is the new question useful?*

Table 12: An LLM Evaluator within RAP Workflow under NLIE-QA, implemented by few-Shot CoT prompting. It assesses the usefulness of new sub-questions in solving the original question. Source from Hao et al. (2023)

Evaluate if given numbers can reach 24 (sure/likely/impossible) 10 14 10 + 14 = 24 sure ... 1 3 3 1 * 3 * 3 = 9 (1 + 3) * 3 = 12 1 3 3 are all too small impossible 11, 12

Table 13: An LLM Evaluator within Tree-of-Thought Workflow under Game 24, implemented by few-Shot CoT prompting. The LLM is profiled for multi-class classification. Source from Yao et al. (2023a).

Context: ... Sentence: ... Is the sentence supported by the context above? Answer Yes or No:

Table 14: An LLM Evaluator, implemented by zero-Shot CoT prompting. The LLM is profiled for multi-class classification. Source from Manakul et al. (2023).

Question: Serianna is a band of what genre that combines elements of heavy metal and hardcore punk?

Proposed Answer: Let's think step by step. Serianna is a band of metalcore genre. Metalcore is a subgenre of heavy metal and hardcore punk. So Serianna is a band of heavy metal and hardcore punk. So the answer is: heavy metal and hardcore punk.

1. Plausibility:

The question asks for the genre that combines elements of heavy metal and hardcore punk, and the answer is "heavy metal and hardcore punk", simply repeat the question. So it's not plausible.

2. Truthfulness: Let's search the question in google:

> Search Query: Serianna is a band of what genre that combines elements of heavy metal and hardcore punk? site: wikipedia.org
> Evidence:

[Metalcore - Wikipedia] Metalcore is a fusion music genre that combines elements of extreme metal and hardcore punk.

The evidence suggests that metalcore is a genre that combines elements of extreme metal and hardcore punk, as stated in the proposed answer.

Let's search the proposed answer in google:

> Search Query: Serianna is a band of metalcore genre. site: wikipedia.org > Evidence:

[Serianna - Wikipedia] Serianna was a metalcore band from Madison, Wisconsin. The band formed in 2006...

The evidence suggests Serianna is a metalcore band, the proposed answer is correct about this.

Above all, the proposed answer correctly identifies that Serianna is a band of the metalcore genre, which combines elements of heavy metal and hardcore punk. However, the final answer is not plausible since it just lists the genres that metalcore combines.

Table 15: An LLM Evaluator Within Feedback-Learning Workflow (Tools), implemented with few-shot demonstrations. The content in the shadow box is generated by LLM. We omit some demonstrations for brevity. Source from Gou et al. (2024).

Given a question, please decompose it into sub-questions. For each subquestion, please answer it in a complete sentence, ending with "The answer is". When the original question is answerable, please start the subquestion with "Now we can answer the question: ".

Question 1: Weng earns \$12 an hour for babysitting. Yesterday, she just did 50 minutes of babysitting. How much did she earn?

Question 1.1: How much does Weng earn per minute?

Answer 1.1: Since Weng earns \$12 an hour for babysitting, she earns \$12 / 60 = \$0.2 per minute. The answer is 0.2.

Question 1.2: Now we can answer the question: How much did she earn? **Answer 1.2:** Working 50 minutes, she earned $0.2 \times 50 = 10$. The answer is 10.

•••

Question 5: Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with four. She sells the remainder at the farmers' market daily for \$2 per fresh duck egg. How much in dollars does she make every day at the farmers' market?

Question 5.1: How many eggs does Janet have left after eating three for breakfast and using four for muffins?

Answer 5.1:

Table 16: An LLM-Profiled Dynamic Model.