James Bartusek UC Berkeley Berkeley, California, USA jamesbartusek@berkeley.edu Thiago Bergamaschi UC Berkeley Berkeley, California, USA thiagob@berkeley.edu

Saachi Mutreja Columbia University New York, New York, USA saachi@berkeley.edu Seri Khoury UC Berkeley Berkeley, California, USA seri khoury@berkeley.edu

Orr Paradise UC Berkeley Berkeley, California, USA orrp@eecs.berkeley.edu

1 INTRODUCTION

Secure multi-party computation (MPC) [2, 12, 25, 40] is a fundamental primitive in cryptography. In an MPC protocol, n parties desire to compute a joint function of their inputs, without letting any party learn about the input of another—other than what can already be learned from the output. Significant effort has been devoted to understanding how many bits must be communicated by parties during the execution of the protocol (hereafter *communication complexity*) [1, 16–18, 23].

MPC protocols are often constructed in a model where *broadcast* is available, which enables each party to send a message to all other parties, and guarantees that the same message will be heard by all receiving parties. The assumption that broadcast is available has played a crucial role in several classic MPC results. However, in practice, networks commonly consist only of *point-to-point* (also known as peer-to-peer) connections. In this point-to-point model, a malicious party may claim to have sent a message to all parties while only sending it to some. Achieving broadcast over point-to-point networks (without assuming a trusted preprocessing phase) is possible only when at most one third of the parties are malicious [22, 31].

Motivated by this infeasibility in the point-to-point model, Goldwasser and Lindell [26] introduced the notion of *MPC with selective abort* (hereafter *MPC with abort*). MPC with abort is a relaxation that allows each party to either correctly compute the function, or abort if malicious behavior is detected. As discussed in [26], it becomes possible to guarantee that all honest parties either correctly compute the function or abort, even when a majority of parties are malicious, and even when no broadcast channel is available. We are interested in the communication complexity of MPC in this setting (*i.e.*, no trusted preprocessing, no broadcast channel, and no bound on the number of adversaries). We ask:

How much must the parties communicate to correctly compute f, or detect malicious behavior?

Note that Goldwasser and Lindell [26] study the *round complexity* of MPC with abort—that is, the number of rounds until f is computed or the parties abort. However, not much is understood about MPC with abort in terms of *communication complexity*. Indeed, even a single round of communication in their protocol may require $\Omega(n^2)$ communicated bits.

ABSTRACT

A central goal of cryptography is Secure Multi-party Computation (MPC), where *n* parties desire to compute a function of their joint inputs without letting any party learn about the inputs of its peers. Unfortunately, it is well-known that MPC guaranteeing output de-livery to every party is infeasible when a majority of the parties are malicious. In fact, parties operating over a point-to-point network (*i.e.*, without access to a broadcast channel) cannot even reach an *agreement* on the output when more than one third of the parties are malicious (Lamport, Shostak, and Pease, JACM 1980).

Motivated by this infeasibility in the point-to-point model, Goldwasser and Lindell (J. Cryptol 2005) introduced a definition of MPC that *does not require agreement*, which today is generally referred to as MPC *with selective abort*. Under this definition, any party may abort the protocol if they detect malicious behavior. They showed that MPC with selective abort is feasible for any number of malicious parties by implementing a broadcast functionality with abort.

While the model of MPC with abort has attracted much attention over the years, little is known about its communication complexity over point-to-point networks. In this work, we study the communication complexity of MPC with abort and devise nearlyoptimal communication efficient protocols in this model. Namely, we prove trade-offs between the number of honest parties h, the communication complexity, and the *locality* of the protocols. Here, locality is a bound on the number of peers with which each party must communicate. Our results are as follows:

- (1) **Near-optimal communication:** A protocol with $\tilde{O}(n^2/h)$ communication complexity.
- (2) Near-optimal locality: A protocol with O
 (n³/h) communication complexity where each party communicates with only O
 (n/h) other parties.
- (3) Intermediate communication vs locality: A protocol with communication complexity Õ(n³/h^{3/2}) where each party communicates with only Õ(n/√h) parties.
- (4) Lower bound: An Ω(n²/h) lower bound on the communication complexity. In particular, we show that any party must communicate with Ω(n/h) other parties. Our lower bound is inspired by a recent lower bound for Broadcast by Blum et. al (DISC 2023).

James Bartusek, Thiago Bergamaschi, Seri Khoury, Saachi Mutreja, and Orr Paradise

Our focus is on the behavior of the MPC protocol as the number of parties *n* scales. In light of this, we try to optimize not just the communication complexity, but also the *locality* of the protocol [7], *i.e.*, the number of parties with which a single party communicates. Any protocol is trivially (n - 1)-local, but better locality of, say, polylog(*n*) is desirable as *n* grows, since each party then needs to secure and maintain far fewer channels.

1.1 Contributions

Following [26], our goal is to study how the communication complexity of MPC with abort over point-to-point networks scales as a function of both the total number of parties n, and (a lower bound on) the number of honest parties h in the network. While we allow for the very basic setup of a shared common random string (CRS), we do not assume strong trusted preprocessing such as public key infrastructure (PKI). For simplicity, in the ensuing discussion we focus on computing constant-depth functions f on n constant-sized inputs with a single constant-sized output and omit the dependence on the security parameter. The security of all of our protocols relies on computational assumptions, namely, the Learning with Errors assumption [38]¹. Finally, we stress again that, for us, "MPC with abort" refers to MPC with selective abort over point-topoint channels. We defer formal statements and generalizations to the body.²

Our first two contributions are two novel protocols achieving state-of-the-art communication complexity and locality (respectively):

THEOREM 1. There exists a protocol for MPC with abort against static malicious adversaries using $\tilde{O}(n^2/h)$ bits of communication, where n is the number of parties of which at least h are honest.

THEOREM 2. There exists a protocol for MPC with abort against static malicious adversaries using $\tilde{O}(n^3/h)$ bits of communication, with locality $\tilde{O}(n/h)$.

We complement these protocols with nearly-matching lower bounds, which imply that Theorems 1 and 2 are optimal for communication complexity and locality (respectively). Our proof is inspired by an "indistinguishability argument", similar to a recent lower bound for Broadcast by Blum et al. [4], which holds even in broader settings.

THEOREM 3. Any protocol for MPC with abort against malicious adversaries requires $\Omega(n^2/h)$ bits of communication. Furthermore, such protocols must have locality $\Omega(n/h)$.

Finally, although Theorem 2 achieves near-optimal locality, it comes at a cost in terms of communication complexity over Theorem 1. A natural question is whether this trade-off is inherent, or whether it is possible to sacrifice some locality to obtain better communication complexity. We answer this question in the positive, by combining ideas from Theorem 2 with our new communicationefficient protocol of Theorem 1 to obtain our final main result:

THEOREM 4. There exists a protocol for MPC with abort against static malicious adversaries using $\tilde{O}(n^3/h^{3/2})$ bits of communication, with locality $\tilde{O}(n/\sqrt{h})$.

1.2 **Prior work**

The focus of this work is on how the communication complexity of MPC scales with the number of parties and tolerated adversaries, which has a long and rich history of study in various models.

There has been significant effort towards optimizing the communication complexity of full-fledged Byzantine agreement (*i.e.*, without abort) [9, 19, 20, 29, 30]. These works study the problem with either no setup, or assuming a public-key infrastructure (PKI) where each party begins the protocol with knowledge of a public key associated with each other party.

There have also been many works that study the more general question of communication complexity of *MPC with guaranteed output delivery* (*i.e.*, without abort), either in the informationtheoretic setting (*e.g.* [17, 27]), or in the computational setting (*e.g.* [6, 7]).

In our work, we study the relaxed model of Goldwasser and Lindell [26] where the computation is considered secure even if some parties abort in the presence of adversaries. This notion of security with abort is now ubiquitous in the MPC literature, and is the de facto standard model for studying MPC in the dishonest majority setting [1, 3, 13, 24, 28, 35]. Some of these works (e.g. [1]) study the communication complexity of MPC with abort, however, to the best of our knowledge, no prior work has been dedicated to optimizing the communication complexity of MPC with abort over point-to-point networks. We also remark that, starting with [21], there has been a line of work devoted to studying the communication complexity of broadcast protocols over point-to-point networks in the dishonest majority setting, including recent progress on upper and lower bounds [14]. However, their setting is different from ours in that their end goal is broadcast (rather than general MPC), and they assume the existence of public-key infrastructure (PKI) between parties.

Lastly, we also study communication complexity in the setting of *locality* [7], where each party is may communicate with only a limited number of other parties. Prior work [7] has also considered this question, but *only* in the honest majority setting, and with strong setup assumptions (*e.g.* PKI).

1.3 Organization

We organize the remainder of this work as follows. In Section 2, we provide a technical overview of our new protocols. In Section 3, we provide preliminaries and basic definitions. In Section 4, we present our communication-optimal protocol for MPC with abort of Theorem 1. Subsequently, in Appendix A, we present our lower bounds. Finally, in Appendix B, we present our protocols with locality.

2 TECHNICAL OVERVIEW

The starting point for our work, and a key building block in our later constructions, is a simple protocol for MPC with abort with $\tilde{O}(n^2)$ communication complexity which works for all h < n. In Section 2.1 we describe how small modifications to the protocol of Goldwasser and Lindell [26] achieve this bound. In the ensuing Section 2.2, we describe how to "bootstrap" this result using subsampling techniques and stronger cryptographic primitives to

¹Refer to Section 3.3 for a description of parameters.

²We denote $g(n) = \tilde{O}(f(n))$ if there exists a constant c such that $g(n) \le cf(n) \operatorname{polylog} f(n)$.

achieve our result in Theorem 1. Finally, in Section 2.3, we describe our protocols with locality.

2.1 The case of h < n

We begin by outlining the protocol for MPC with abort introduced by Goldwasser and Lindell [26]. Their original protocol requires $O(n^3)$ bits of communication, and leverages the observation that MPC can be achieved by a constant number of invocations of Allto-All Broadcast (see also [15, 35] and references therein). In Allto-All Broadcast, every party wants to broadcast a message to all the other parties. Although Broadcast is impossible if the fraction of honest parties is smaller than 2/3 [32], Broadcast *with abort* is possible for any number of honest parties.

Single-source broadcast with abort [26]

- (1) **Broadcast step:** A party *P* that wants to broadcast a message *m*, sends *m* to all other parties.
- (2) **Verification step:** Each party sends to all other parties the message that it received from *P* in the first step.
- (3) Output step: If a party received two different messages in the second step, it aborts. Otherwise, if a party got the same message from all other parties in the second step, it outputs the value of that message.

Observe that the protocol uses all the links in the network, incurring $O(n^2)$ communication.

All-to-all broadcast with abort The All-to-All Broadcast with abort protocol of [26] simply runs *n* invocations of the above single-source Broadcast with abort protocol in parallel. Thus, it requires $O(n^3)$ communication, and implies the same communication complexity for MPC.

Succinct equality testing and efficient verification We begin with a simple observation which allows us to "shave-off" a factor of n on the communication complexity of All-to-All Broadcast (with aborts). Which, in turn, gives us a simple $\tilde{O}(n^2)$ protocol for MPC (with aborts) for any h < n. Informally, we optimize the verification step above by concatenating the messages from the n parallel runs of Broadcasts with abort, and use hash functions to pairwise test the equality between these strings using only $O(\log(n))$ bits of communication (see Section 3.2). While this protocol still communicates on all edges/links, it communicates only $O(\log n)$ bits on each edge, resulting in $O(n^2 \log n)$ bits total.

2.2 Protocols with optimal communication complexity

The $\Theta(n^2)$ **barrier** Goldwasser and Lindell [26] rely on All-to-All Broadcast to achieve MPC. Clearly, since there are $\Theta(n^2)$ edges in the network, any protocol for All-to-All Broadcast requires $\Omega(n^2)$ bits of communication. One may wonder whether it is actually possible to overcome this communication barrier. At first glance, to achieve MPC with abort on point-to-point networks, it may seem that each pair of parties needs to *verify* that they have consistent views of the rest of the network. Without such verification, the adversary could potentially mislead the parties causing them to arrive to different outputs *without aborting*.

Going below $\Theta(n^2)$ We overcome this issue by allowing honest parties to verify their views through other honest parties. At a high level, our protocol picks a random subset of the nodes which we refer to as *the committee*, and delegates the MPC task to this committee.³ Electing this subset in a communication-efficient manner, as well as delegating the computation itself, require overcoming several challenges. While the former is addressed via a combination of techniques from Section 2.1, overcoming the latter requires additional insight described next.

To delegate the computation we leverage an encrypted functionality akin to Threshold Fully Homomorphic Encryption (TFHE) [1, 5]. Informally, the committee members generate public key and secret key pairs, where the secret key is k-out-of-k secret shared among the parties. So long as there is at least one honest party in the committee, no information about the secret key—and consequently, about the honest parties inputs—is revealed to the adversary.

The relevant details on the encrypted functionality are provided in Section 3.3, and a formal description of our protocol is presented in Section 4. In what remains of this subsection, we provide an informal description of the main steps in our protocol. If at any step of our protocol a verification step fails, the parties immediately abort. We omit this detail from the high-level description below for conciseness, but include it in the formal description in Section 4.

Main steps of our protocol

- (1) A committee of size $k = O(nh^{-1}\log n)$ is selected uniformly at random via a "self-election" scheme. By a "Hitting-Set" argument, at least 1 honest party is elected.
- (2) The committee members notify the rest of the network of their election, and subsequently verify that they each have consistent views of the other committee members.
- (3) The committee creates a public/secret key pair (*pk*, *sk*), where the secret key is secret-shared into (*sk_j*)_{*i*∈[*k*]}.
- (4) Each party in the committee sends the public key *pk* to all other parties.
- (5) All *n* parties encrypt their inputs using *pk*, and send their ciphertexts to the committee members.
- (6) Using MPC, the committee members compute the output of the function from the encrypted inputs and the secret key shares.
- (7) Finally, the committee members forward the output to the other parties.

The full description of the protocol, as well as its formal details, are provided in Section 4.

Communication complexity In the protocol above, each party only communicates with the committee. As there are only $O(n \log n/h)$ parties in the committee, and since each other party only sends and receives $O(\log n)$ bits to and from the committee (as we show in

³This approach is inspired by committee-based consensus protocols used in largescale blockchains, albeit applied to a highly non-standard (strong) dishonest majority setting. The idea of leveraging a committee can be traced back to [8] (PODC 84) in an application to distributed deadlock detection; see [33, 39] for a modern review.

Section 4), it follows that the total communication complexity is $O(n^2 \text{polylog}n/h)$.

2.3 Protocols with locality

We build on our communication-efficient protocols for MPC with abort by designing protocols that achieve locality.

Establishing a sparse routing network The starting point for our local protocols is the observation that our protocol for All-to-All Broadcast with abort can be sparsified. Indeed, if the parties were given a sparse communication network on which to communicate, with the guarantee that all the honest parties are connected, then at least in principle they could ensure consistent views of each other's inputs.

To establish this sparse routing network, each party locally samples $d = \Theta(nh^{-1} \log n)$ nodes at random, and attempts to establish them as their "next hop" in the network. To ensure locality, parties must be wary not to accept too many incoming connections, which is why we set up a *bidirectional* network (*i.e.*, the "next hop" relation is symmetric). Indeed, if any party detects too many incoming connections, it notifies its next hops and aborts. The threshold for "too many" is chosen such that, with all but negligible probability, it is surpassed only if the party was maliciously targeted by the adversary (a distributed denial of service attack, if you will).

Responsible routing on the network It is tempting to declare victory (*i.e.*, a local protocol for simultaneous broadcast with abort): after all, all honest parties are connected, so they may simply broadcast their message over the routing network. Not quite, since the honest parties do not know each other's identities. Furthermore, without any public-key infrastructure, the adversary may forge messages as they please; that is, if party *P*'s next hop *X* is claiming to be forwarding a message originating in some source party *S* ($S \rightarrow X \rightarrow P$), party *P* has no way of ascertaining that the message indeed originated with *S*.

This is overcome using a similar strategy to that employed by Goldwasser and Lindell [26]: when party P hears (via one of its hops) that party S's input is x, it forwards this information to all of its other hops—unless it has *already heard* that S's input was some other $x' \neq x$ (an equivocation), in which case it warns all its hops, and aborts. Naturally, any party that receives such warning will then forward it and abort. We refer to this technique as *responsible gossip*, since parties spread rumors about other parties across the network, but only if the rumors are not contradictory.

Total communication is kept low by requiring each honest party P to forward a rumor ("*S* has input x") at most once. Thus, honest parties each send at most n + 1 different messages (accounting for the warning message) to each of their O(d) hops, for a total of $O(n^2 \cdot d) = O(n^3h^{-1}\log n)$ communication per simultaneous broadcast. Since All-to-All Broadcast (with aborts) is sufficient to achieve MPC (with aborts), this all but concludes our description of the proof of Theorem 2.

Local committee election While conceptually simple, Theorem 2 incurs a serious blowup in communication complexity. It is then natural to ask whether one can combine our network sparsification

techniques with our committee-based, communication-optimal protocols, in order to establish tradeoffs between locality and communication complexity.

To do so, the starting point is to leverage our "responsible gossip" protocol to perform the committee election *locally*. That is, the committee members $C \subset [n]$ announce their self-election by sending their ID via the routing network, using $O(|C| \cdot d \cdot n)$ bits total. While again it may seem tempting to claim victory, unfortunately simply electing the committee is not enough to decrease communication: for the parties' (encrypted) inputs to even reach the committee using the routing network, each of *n* different inputs would have to be sent over the $O(d \cdot n) = \tilde{O}(n^2h^{-1})$ edges of the graph, which regresses to our previous bound of $\tilde{O}(n^3h^{-1})$.

Sparsifying the committee–network communication, and a covering claim Instead, after the committee is elected, we entirely dispense with the routing network, and attempt to sparsify the committee–network interaction. To do so, the committee members partition the network by independently sampling (overlapping) subsets of the parties $S_u \subset [n]$ of size s, for each $u \in C$, which they are "responsible" for. So long as each party in the network is connected to–or "covered" by–at least one honest committee member, then its input will correctly reach the committee. To ensure every committee member contains the encrypted input of every party, the committee members forward to each other the inputs they received from their subsets S_u . Once the honest committee members have a consistent view of all the parties' (encrypted) inputs, the actual computation can be correctly delegated.

Unfortunately, to ensure the honest committee members $C \cap H$ "cover" the entire network, we need to increase the committee size. In particular, so long as $s \cdot |C \cap H| \approx n \cdot \log n$, a hitting set argument ensures the covering claim. The resulting locality of the protocol is then bounded by the sizes s, |C|, and the degree of the routing graph. In turn, the total communication complexity dominated by

$$\underbrace{O(|C| \cdot d \cdot n)}_{\text{Local Committee}} + \underbrace{\tilde{O}(|C|^2 \cdot s)}_{\text{Interaction}} + \underbrace{\tilde{O}(|C|^2)}_{\text{Computation}}$$
(1)
$$\leq \tilde{O}(|C|n^2h^{-1} + |C|^2 \cdot s).$$
(2)

Balancing the choice of |C| and *s* subject to the covering claim reveals the optimal choice of $|C| = s = \tilde{O}(nh^{-1/2})$, which gives us the advertised bounds of Theorem 4.

3 PRELIMINARIES

3.1 Model, basic definitions, and assumptions

The network. *n* parties want to compute a joint functionality \mathcal{F} on their private inputs in a synchronized point-to-point network. That is, any pair of parties may communicate directly via a communication channel. We assume parties have a lower bound on the number of honest parties *h* in the network; the tighter this bound, the more efficient the resulting protocol.

The adversary. We consider a *static* and *malicious* adversary. Of the *n* parties, the adversary may choose before the protocol begins to corrupt up to n - h parties, and we refer to the set of at least *h* honest parties as \mathcal{H} . The adversary may deviate from the protocol

in an attempt to trick the honest parties into computing a faulty result, or to learn something about their inputs.

Communication complexity. Our main measure of protocol efficiency is the number of bits communicated between parties during computation. However, as discussed in [7], an adversary may flood the network with messages which, intuitively, should not be counted towards the communication complexity of a protocol. To avoid this issue, we define the communication complexity of a protocol to be the total number of bits sent by all parties *if they were to honestly follow the protocol.* For a randomized protocol, we take the worst-case over all possible executions (in the all-honest case). Indeed, throughout this work, we will assume that each honest party aborts if it were to receive more bits than prescribed by the protocol.

The security parameter λ . Throughout the paper, we use λ to denote the security parameter, which is a variable that quantifies the level of security provided by a cryptographic algorithm, typically represented as the size (in bits) of the keys used.

3.2 Succinct equality testing

In this section we state the following folklore lemma, which says that two parties with strings of length *n* bits each, can detect whether their strings are equal with high probability while exchanging only $O(\log n)$ bits.

LEMMA 5. Fix $\lambda \in \mathbb{N}$. Two parties with inputs $m_1, m_2 \in \{0, 1\}^n$ can detect whether m_1 and m_2 are equal, using a randomized protocol which exchanges only $O(\lambda \log n)$ bits and such that:

- (1) If $m_1 = m_2$, then the protocol outputs 1.
- If m₁ ≠ m₂, then the protocol outputs 0 with probability at least 1 ¹/_{m³}.

Algorithm 1: Equality λ , Succinct Equality Test.

Input: Parties P_1, P_2 with inputs $m_1, m_2 \in \{0, 1\}^n$.

Output: A flag $f \in \{0, 1\}$.

1: P_1 samples a prime $p \in [n^{\lambda}]$ uniformly at random, and sends to P_2 the value of p and

 $v_1 \coloneqq m_1 \mod p$.

2: P_2 outputs and sends 1 to P_1 if and only if $v_1 = m_2 \mod p$. Else, it outputs and sends 0.

For a proof of Lemma 5, see e.g. [34, 37].

3.3 Secure multiparty computation

To formally define security, we follow the standard universal composability framework [10]. We consider a probabilistic polynomialtime (PPT) *environment* Z that is invoked on the security parameter 1^{λ} and auxiliary input *z*, and conducts the protocol execution in one of two worlds. In the *real world*, Z initializes parties P_1, \ldots, P_n with inputs x_1, \ldots, x_n and initializes an adversary Adv that corrupts up to n - h of the parties. The remaining honest parties execute a protocol Π with the corrupted parties controlled by Adv, who may interact arbitrarily with Z. At the end of the protocol, all honest parties and the adversary send output to Z. In the *ideal world*, Z initializes "dummy" parties $\tilde{P}_1, \ldots, \tilde{P}_n$ that are supposed to simply forward their inputs to a trusted third party and forward their outputs back to Z, and initializes an adversary Sim that corrupts up to n - h of the dummy parties. The remaining honest parties and Sim execute a protocol with the trusted third party who is implementing an "ideal functionality" for \mathcal{F} .

Clearly, in the ideal execution, the simulator does not learn anything besides their output of the function. Thus, if the environment cannot distinguish between the real world execution and the ideal world execution, then the real world adversary must have also learned nothing besides their output of the function.

Real execution. The environment $Z(1^{\lambda}, z)$ initializes parties P_1, \ldots, P_n with x_1, \ldots, x_n , and initializes a PPT Adv corrupting parties $[n] \setminus \mathcal{H}$. The protocol Π is executed in the presence of Adv. The honest parties follow the instructions of the protocol Π , and the adversary is allowed to deviate from it while communicating with Z. At the end of the protocol, Z receives outputs from the honest parties and output from Adv. Finally, it computes its own output. This output is denoted by the random variable $\text{Real}_{\Pi,\text{Adv}, Z}(1^{\lambda}, z)$.

Ideal execution. We describe the ideal execution for a non-interactive functionality $\mathcal{F}(x_1, \ldots, x_n) \rightarrow (y_1, \ldots, y_n)$. The environment $\mathcal{Z}(1^{\lambda}, z)$ initializes dummy parties $\tilde{P}_1, \ldots, \tilde{P}_n$ with x_1, \ldots, x_n , and initializes a PPT Sim corrupting parties $[n] \setminus \mathcal{H}$.

- The honest dummy parties send their inputs {x_i}_{i∈H} to the trusted third party. The simulator sends a set of inputs {x'_i}_{i∈[n]\H} on behalf of the corrupted dummy parties to the trusted third party.
- (2) The third party computes \mathcal{F} on this set of inputs to obtain (y_1, \ldots, y_n) , and returns the outputs to the dummy parties.
- (3) The honest dummy parties send their outputs to Z and Sim sends an output to Z.

Finally, \mathcal{Z} computes its own output, which is denoted by the random variable $\mathsf{Ideal}_{\mathcal{F},\mathsf{Sim},\mathcal{Z}}(1^{\lambda}, z)$.

Security with selective abort. Our default notion of security will allow for selective aborts: After the corrupted parties receive their output from the trusted third party, but *before* the honest parties have received their output, the adversary / simulator may decide to send a list \mathcal{L} of honest parties to the trusted third party. In this case, the third party will replace each of the honest party outputs y_i for $i \in \mathcal{L}$ with the abort symbol \perp .

Ideal execution for interactive functionalities. We will also consider generalizing the notion of a functionality \mathcal{F} to allow for some limited interaction. In particular, we consider functionalities $\mathcal{F} = (\mathcal{F}_1, \mathcal{F}_2)$ where $\mathcal{F}_1(x_1, \ldots, x_n) \rightarrow (y_{1,1}, \ldots, y_{1,n})$, and \mathcal{F}_2 takes an additional public input w and computes $\mathcal{F}_2(x_1, \ldots, x_n, w) \rightarrow (y_{2,1}, \ldots, y_{2,n})$. That is, the ideal execution for \mathcal{F} operates as follows. The environment $\mathcal{Z}(1^{\lambda}, z)$ initializes dummy parties $\widetilde{P}_1, \ldots, \widetilde{P}_n$ with x_1, \ldots, x_n , and initializes a PPT Sim corrupting parties $[n] \setminus \mathcal{H}$.

(1) The honest dummy parties send their inputs $\{x_i\}_{i \in \mathcal{H}}$ to the trusted third party. The simulator sends a set of inputs

 $\{x'_i\}_{i \in [n] \setminus \mathcal{H}}$ on behalf of the corrupted dummy parties to the trusted third party.

- (2) The third party computes *F*₁ on this set of inputs to obtain (*y*_{1,1},..., *y*_{1,n}), and returns the outputs to the dummy parties.
- (3) All outputs are forwarded to Z, who chooses w and sends it to all dummy parties, who then forward w to the trusted third party.
- (4) The third party computes \$\varF_2\$ on this set of inputs to obtain (\$y_{2,1}, \ldots, y_{2,n}\$), and returns the outputs to the dummy parties.
- (5) The honest dummy parties send their outputs to Z and the Sim sends an output to Z.

Finally, \mathcal{Z} computes its own output, which is denoted by the random variable $\mathsf{Ideal}_{\mathcal{F},\mathsf{Sim},\mathcal{Z}}(1^{\lambda}, z)$. Having defined both the real and ideal executions, we can now formally define a secure protocol.

DEFINITION 6 (SECURE PROTOCOLS). A protocol Π securely computes a (potentially interactive) functionality \mathcal{F} in the presence of static malicious adversaries if for any PPT adversary Adv, there exists a PPT simulator Sim such that for any PPT environment \mathcal{Z} with auxiliary input z,

$$\left|\mathbb{P}(\operatorname{Real}_{\Pi,\operatorname{Adv},\mathcal{Z}}(1^{\lambda},z)=1)-\mathbb{P}(\operatorname{Ideal}_{\mathcal{F},\operatorname{Sim},\mathcal{Z}}(1^{\lambda},z)=1)\right|<\operatorname{negl}(\lambda),$$

where negl(λ) is asymptotically smaller than any polynomial in λ .

That is, Definition 6 means that a protocol is secure if the environment cannot distinguish between the real and ideal world executions. This implies that the adversary does not learn anything besides the output.

Remark 7. This definition also captures correctness. For, if we consider an adversary/simulator that corrupts no parties, then the ideal execution is defined to honestly compute the functionality \mathcal{F} and output the result. Therefore, the real execution must also yield the correct result.

Next, we define our first very simple ideal functionality, which we refer to as *Simultaneous (All-to-All) Broadcast* \mathcal{F}_{SB} :

- Take input x_1, \ldots, x_n .
- Output $y_1 = (x_1, ..., x_n), ..., y_n = (x_1, ..., x_n).$

Remark 8. If $\ell_{in} = \max_{i \in [n]} \{|x_i|\}$, then from Section 2.1 and the equality test of Lemma 5 we can implement \mathcal{F}_{SB} on point-to-point networks using $\tilde{O}(n^2 \cdot (\ell_{in} + \lambda))$ total bits of communication, up to error negl (λ) .

Known communication complexity results. Given an interactive functionality $\mathcal{F} = (\mathcal{F}_1, \mathcal{F}_2)$, let $\ell_{in} = \max_{i \in [n]} \{|x_i|\}$, let D be the maximum circuit depth between \mathcal{F}_1 and \mathcal{F}_2 , and let ℓ_{out} be the *total* number of bits of output, that is $\ell_{out} = |y_{1,1}| + \dots + |y_{1,n}| + |y_{2,1}| + \dots + |y_{2,n}|$. Known results [35, 36] imply the following theorem; for convenience we will also provide a proof sketch.

THEOREM 9. Assuming the hardness of Learning with Errors (LWE), there exists a protocol for securely computing \mathcal{F} using one invocation of Simultaneous Broadcast \mathcal{F}_{SB} on inputs of size poly(λ , D, ℓ_{in}), plus an additional $\ell_{out} \cdot n \cdot poly(\lambda, D)$ bits of communication.

PROOF SKETCH. We will use the semi-malicious protocol of [35] based on (multi-key) fully-homomorphic encryption, combined with a universally composable non-interactive zero-knowledge (NIZK) protocol from LWE ([11, 36]), in order to obtain a fully-malicious protocol.

In some detail, the first round consists of a simultaneous broadcast, where each party broadcasts (i) their public key, (ii) one ciphertext for each of their input bits, and (iii) a NIZK proof that they sampled all of this information honestly. Each of these components grows with the size of the lattice dimension, which is polynomial in the security parameter λ and the depth *D* of (largest) circuit to be computed. Thus, each party broadcasts a message of size at most poly(λ , *D*, ℓ_{in}).

Next, for each bit of output across each of the two functionalities \mathcal{F}_1 and \mathcal{F}_2 , we describe the communication necessary to deliver that bit of output to the party *i* that is supposed to receive it. Each party $j \neq i$ must send to *i* (in a point-to-point message), (i) a partial decryption corresponding to the output bit, and (ii) a NIZK proof that they computed their partial decryption share honestly. Each partial decryption share is a field element that grows polynomially in the size of the lattice dimension $poly(\lambda, D)$. Moreover since the entire multi-key fully-homomorphic evaluation can be done publicly by each party, the only part of this computation that must be proven honest by the NIZK is the final (noisy) inner product between the *i*'th ciphertext component and party *i*'s secret key, which is also just the size of the lattice dimension $poly(\lambda, D)$. Thus, the NIZK proof itself is of size $poly(\lambda, D)$. So, we conclude that the communication necessary for each output bit is at most $n \cdot \text{poly}(\lambda, D).$

By combining the simultaneous broadcast step with the partial decryptions, we see that the entire protocol requires one simultaneous broadcast on inputs of size $poly(\lambda, D, \ell_{in})$, plus an additional $\ell_{out} \cdot n \cdot poly(\lambda, D)$ bits of communication.

Remark 10. By using [24] rather than [35], we could improve the assumption from LWE to the more general assumption of (maliciously-secure) two-round oblivious transfer, at the cost of replacing the depth parameter D with the size C of the largest circuit. That is, assuming maliciously-secure oblivious transfer, there exists a protocol that requires one invocation of simultaneous broadcast on inputs of size poly(λ , C, ℓ_{in}), plus an additional $\ell_{out} \cdot n \cdot poly(\lambda, C)$ bits of communication.

Encrypted functionality. We define an interactive ideal functionality that is parameterized by a public-key encryption scheme PKE = (Gen, Enc, Dec) and a function $f: (x_1, \ldots, x_m) \rightarrow \{0, 1\}$ with m inputs. This is, in fact, an input-less but *randomized* functionality. Such randomized functionalities can be implemented by taking a random string r_i as input from each party, and setting the random coins equal to $\bigoplus_{i \in [n]} r_i$. We make this explicit below. $\mathcal{F}[\mathsf{PKE}, f]$

• $\mathcal{F}_{\text{Gen}}[\text{PKE}, f](r_1, \dots, r_n)$: - Take input $r_1, \dots, r_n \in \{0, 1\}^{\lambda}$, define $r \coloneqq \bigoplus_{i \in [n]} r_i$, and compute

$$(\mathsf{pk},\mathsf{sk}) \coloneqq \mathsf{Gen}(1^{\lambda};r)$$

- Output pk to every party.

- $\mathcal{F}_{\text{Comp}}[\text{PKE}, f](r_1, \ldots, r_n, w = (\text{ct}_1, \ldots, \text{ct}_m)):$
 - Take input $r_1, \ldots, r_n \in \{0, 1\}^{\lambda}$, define $r := \bigoplus_{i \in [n]} r_i$, and compute

 $(\mathsf{pk},\mathsf{sk}) \coloneqq \operatorname{Gen}(1^{\lambda};r).$

- For each $i \in [m]$, compute $x_i := \text{Dec}(\text{sk}, \text{ct}_i)$.
- Compute $y = f(x_1, ..., x_m)$ and output y to every party.

According to Theorem 9 and the simultaneous broadcast protocol of Remark 8, we can securely implement the above functionality with communication complexity $n^2 \cdot \text{poly}(\lambda, D) + m \cdot n \cdot \text{poly}(\lambda, D)$, where *D* is the circuit depth of *f*.

4 COMMUNICATION-EFFICIENT PROTOCOLS

In this section we prove our main result on the communication complexity of MPC with abort.

THEOREM 11 (RESTATEMENT OF THEOREM 1). Assuming the hardness of LWE, there exists a protocol for MPC with abort against static malicious adversaries computing functions f of depth D using $O(n^2 \cdot h^{-1} \text{poly}(\lambda, D, \log n))$ bits of communication. The protocol has error negl (λ) .

We refer the reader to Section 2.2 for an overview. In this section, we begin with a committee election protocol in Section 4.1, and then proceed with our MPC protocol in Section 4.2.

4.1 Committee election protocol

The overarching principle behind the committee election protocol is that by its conclusion, the parties agree on a small subset of the network which contains at least an honest party. We refer the reader to Algorithm 2 for a description.

Algorithm 2: CommitteeElect, Committee Election Protocol.

Input: An integer $h \in [n]$, and integer security parameters α, λ .

Output: Each party $i \in [n]$ receives a subset $C_i \subset [n]$, or aborts \perp .

- 1: Each party $i \in [n]$ samples a bernoulli random variable with probability $p = \min(1, \alpha \cdot \frac{\log n}{h})$, resulting in a bit b_i .
- 2: If $b_i = 1$, then *i* sends b_i to all other $j \in [n]$.
- 3: Let $C_i \subset [n]$ denote the bits $b_j = 1$ received by $i \in [n]$ for $j \neq i$. If $|C_i| \ge 2 \cdot p \cdot n$, abort.
- 4: Each $i, j \in [n]$ s.t. $j \in C_i, i \in C_j$ engage in Equality $\lambda(C_i, C_j)$.
- 5: If no pair rejects, then party *i* "receives" C_i . Otherwise, abort.

Step 2 ("election notification") in Algorithm 2 ensures that only the committee members notify the rest of the network of their election. Naturally, some malicious parties may attempt to lie about their election results or equivocate during the execution. However, step 3 ensures the total number of liars is bounded, and step 4 ensures that the committee members at least have a consistent view of each other, even in the presence of equivocation.

Claim 12. The communication complexity of Algorithm 2 is $\tilde{O}(n^2 \cdot h^{-1} \text{poly}(\alpha, \lambda))$.

PROOF. In an honest execution of the protocol, one readily inspects the total amount of bits sent within the committee is $O(|C|^2 \lambda \log n)$ and $O(|C| \cdot n)$ from the committee to the network. The upper bound on the committee size $|C| \le nh^{-1}\alpha$ implies the claim.

Correctness is based on the following simple "Hitting Set" Lemma, which follows immediately from a Chernoff bound.

LEMMA 13. Fix $H \subset [n]$. Let $R \subset [n]$ be a random subset, defined by independently sampling each element of [n] with probability p. Then, $|H \cap R| \ge p \cdot |H|/2$ with probability $\ge 1 - 2^{-\Omega(p \cdot |H|)}$.

Claim 14. After Algorithm 2, with probability $\geq 1 - n^{-\Omega(\min(\alpha,\lambda))}$, either a party has aborted or

- (1) At least 1 honest party i was sampled in step 1, and
- (2) All the committee members agree on their view with $i, C_i \equiv C$.

In the absence of any malicious parties, the protocol aborts with probability $\leq n^{2-\alpha}$.

PROOF. Item 1 follows verbatim from Lemma 13. Item 2 follows from the security of the equality test Lemma 5 and a union bound over all $\leq |C|^2 \leq n^2$ tests.

4.2 MPC with abort

We can now describe our protocol for MPC, algorithm 3. As previously discussed, it is based on delegating the computation to a committee via the MPC functionality of Theorem 9. Succinct equality checks are run within the committee to ensure they all receive consistent views of the other parties inputs in the network.

Theorem 11 follows from the following Claims 15 to 17.

Claim 15. The communication complexity of Algorithm 3 is

$$O(n^2h^{-1}\operatorname{poly}(\lambda, D, \log n)).$$

PROOF. Suppose the bitlength of the public keys, secret key shares, and ciphertexts ct is bounded by *b*. Then, the total amount of communication between network and committee, and within the committee, during steps 1 and 3, 4, 5 is $O(b \cdot (n \cdot |C| + \lambda |C|^2 \log(n \cdot b))) \leq O(bn^2h^{-1}\text{poly}(\log n, \log b, \lambda))$ from the guarantees of CommitteeElect (Claim 12) and Equality_{λ} (Lemma 5).

In turn, from Theorem 9, the communication complexity of the encrypted functionality in steps 3 and 5 is $O(|C| \cdot n \cdot \text{poly}(\lambda, D))$, and $b \leq \text{poly}(\lambda, D)$. Under the bound $|C| \leq \tilde{O}(\alpha n h^{-1})$ for the committee size, and the choice $\alpha = \lambda$ we conclude the desired claim.

Claim 16. At the end of Algorithm 3, with probability all but $n^{-\Omega(\lambda)}$, the *n* parties have either all received the correct output or one of them has aborted. Moreover, if they are all honest, they abort with probability at most $n^{-\Omega(\lambda)}$.

Algorithm 3: Multi-party Computation with abort.

Input: Integer $h \in [n]$, a function $f: (\{0,1\}^{\ell})^n \to \{0,1\}^{\ell'}$ and an input $x_i \in \{0,1\}^{\ell} : \forall i \in [n]$.

- **Output:** Each party $i \in [n]$ outputs $f(x_1, \dots x_n)$, or a party aborts \perp .
- 1: Execute CommitteeElect, resulting in a committee $C \subset [n]$, and local views $C_i \subset [n]$ for $i \in [n]$.
- The committee generates (*pk*, *sk*_c)_{c∈C} pairs using the encrypted functionality *F*_{Gen}.
- 3: Each party $c \in C$ forwards the public key pk to all other $i \in [n]$. If any two messages differ, output \perp .
- 4: Parties $i \in [n]$ encode their input $ct_i = Enc_{pk}(x_i)$, and send them to all $c \in C_i$.
- 5: The committee members c ∈ C concatenate their received messages m_c = {ct_i}_{i∈[n]}, and pairwise run Equality_λ(m_{c'}, m_c). If the inputs are not all consistent, they abort ⊥.
- 6: The committee members engage in the encrypted functionality 𝓕_{Comp} with public inputs {ct_i}_{i∈[n]} and private inputs {sk_c}_{c∈C}, to compute the output Out = f(x₁, · · · , x_n).
- 7: Finally, each committee member forwards Out to all the members of the network.

PROOF. The second part of the claim above—non-triviality—follows from the fact that CommitteeElect and Equality individually fail with probability $n^{-\Omega(\lambda)}$, with honest or dishonest inputs. A union bound over the desired equality checks then gives us the claim.

In turn, conditioning on the success of CommitteeElect and Equality as above, the resulting protocol is correct if the encrypted functionality ($\mathcal{F}_{Enc}, \mathcal{F}_{Comp}$) is correct. Indeed, by Definition 6 we prove the claim.

Claim 17. Assuming the hardness of learning with errors, Algorithm 3 is secure.

PROOF. The proof of security is similarly inherited from the security of the encrypted functionality \mathcal{F} of Definition 6. Indeed, an adversary which breaks the security of Algorithm 3 can be turned into an adversary for \mathcal{F} by conditioning on the success of CommitteeElect and Equality—which as discussed occurs with probability 1–negl(λ).

4.3 Generalization to multi-output functionalities

Our protocol can be generalized to the setting where n parties desire to compute a function that maps n inputs to n constant sized outputs (one output for each party). The main modifications in the MPC with abort protocol are the following:

- Each party encrypts their input as well as a randomly sampled secret key which will be used to encrypt their output. This is because each party should only learn its output.
- (2) The output length is now of order *n* bits, so if every party in the committee forwards it to every other party in the network, the communication complexity in this setting would be $O(\frac{n^3}{h^2})$. In order to avoid this blow-up in communication, each party's output is *signed* using a digital signature after being encrypted. This is why we need 2 pairs of public and secret keys in our modified encrypted functionality (see below)—one pair is used to encrypt and decrypt the parties' inputs, the other pair is used to sign and verify signatures on the parties' outputs. From the security of digital signature on a modified output is negligible. Assuming this security, it is enough to have any one party (even adversarial) forward the output to all the members in the network.

Before we formally state the protocol, we will define a modified encrypt then authenticate functionality that is parameterized by a public-key encryption scheme PKE = (Gen_{enc}, Enc, Dec), a digital signature scheme DS = (Gen_{sig}, Sign, Vrfy), a secret key encryption scheme SKE = (Gen_{enc}', Enc', Dec') and a function $f: (x_1, \ldots, x_m) \rightarrow (\{0, 1\}^{l'})^m$ with *m* inputs and *m* constant sized outputs. This functionality is implemented by taking randomness and inputs from each party.

 $\mathcal{F}_{\mathsf{Enc}}[\mathsf{PKE},\mathsf{SKE},\mathsf{DS},f]$

•
$$\mathcal{F}_{\text{Gen},1}[\text{PKE}, \text{SKE}, \text{DS}, f](r_1, \ldots, r_n):$$

- Take input $r_1, \ldots, r_n \in \{0, 1\}^{\lambda}$, define $r := \bigoplus_{i \in [n]} r_i$, and compute

$$(pk, sk) \coloneqq Gen_{enc}(1^{\lambda}; r)$$

- Output pk to every party.
- $\mathcal{F}_{\text{Gen},2}[\text{PKE}, \text{SKE}, \text{DS}, f](r'_1, \dots, r'_n)$:
 - Take input $r'_1, \ldots, r'_n \in \{0, 1\}^{\lambda}$, define $r' \coloneqq \bigoplus_{i \in [n]} r'_i$, and compute

$$(\mathsf{pk}',\mathsf{sk}') \coloneqq \operatorname{Gen}_{\mathsf{sig}}(1^{\lambda};r')$$

- Output pk' to every party.

$$\mathcal{F}_{\text{Comp,Sign}}[\text{PKE}, \text{SKE}, \text{DS}, f](r_1, \dots, r_n, r'_1, \dots, r'_n)$$

- $w = (ct_1, \dots, ct_m), k' = (k'_1, \dots, k'_n)):$
 - Take input $r_1, \ldots, r_n \in \{0, 1\}^{\lambda}$, define $r \coloneqq \bigoplus_{i \in [n]} r_i$, and compute

$$(\mathsf{pk},\mathsf{sk}) \coloneqq \mathsf{Gen}_{\mathsf{enc}}(1^{\lambda};r).$$

- Take input $r'_1, \ldots, r'_n \in \{0, 1\}^{\lambda}$, define $r' \coloneqq \bigoplus_{i \in [n]} r'_i$, and compute

$$(\mathsf{pk'},\mathsf{sk'}) \coloneqq \operatorname{Gen}_{\mathsf{sig}}(1^{\lambda};r').$$

- For each $i \in [m]$, compute $x_i := \text{Dec}(\text{sk}, \text{ct}_i)$.
- For each $i \in [m]$, compute $k_i \coloneqq \text{Dec}(\text{sk}, k'_i)$.
- Compute $(y_1, ..., y_m) = f(x_1, ..., x_m)$.
- For each $i \in [m]$, compute $ct'_i \coloneqq \text{Enc}'(k_i, y_i)$.
- For each $i \in [m]$, compute $\sigma_i \leftarrow \text{Sign}(\text{sk}', \text{ct}'_i)$ and output $((\text{ct}'_1, \sigma_1), \dots, (\text{ct}'_m, \sigma_m))$ to a single designated party.

Finally, we formally describe the modified MPC protocol in Algorithm 4.

Algorithm 4: Multi-output Multi-party Computation with abort.

Input: Integer $h \in [n]$, a function $f: (\{0,1\}^{\ell})^n \to (\{0,1\}^{\ell'})^n$, and an input $x_i \in \{0,1\}^{\ell}$ for all $i \in [n]$.

Output: Each party $i \in [n]$ outputs $f(x_1, \dots x_n)_i$, or aborts and outputs \perp .

- 1: Execute CommitteeElect, resulting in a committee $C \subset [n]$, and local views $C_i \subset [n]$ for $i \in [n]$.
- The committee generates the encryption public key pk using the functionality \(\mathcal{F}_{Gen.1}\).
- 3: Each party c ∈ C forwards the public key pk to all other
 i ∈ [n]. If any two messages differ, output ⊥.
- 4: The committee generates the signature public key pk' using the functionality \$\mathcal{F}_{\text{Gen},2}\$.
- 5: Each party $c \in C$ forwards the public key pk' to all other $i \in [n]$. If any two messages differ, output \perp .
- 6: Parties $i \in [n]$ sample r_i^* , and compute $k_i \leftarrow \text{Gen}_{\text{enc}}'(1^{\lambda})$.
- 7: Parties i ∈ [n] encode their input ct_i ← Enc_{pk}(x_i), and their key k'_i ← Enc_{pk}(k_i) and send them to all c ∈ C_i.
- 8: The committee members c ∈ C concatenate their received messages m_c = {ct_i, k'_i}_{i∈[n]}, and pairwise run Equality_λ(m_{c'}, m_c). If the inputs are not all consistent, they abort ⊥.
- 9: The committee members engage in the encrypted functionality *F*_{Comp,Sign} with public inputs {ct_i, k_i'}_{i∈[n]} to compute the output Out = ((ct₁', σ₁),..., (ct_m', σ_m)).
- 10: Finally, one committee member forwards (ct'_i, σ_i) to party i, for each $i \in [n]$.
- 11: Each party $i \in [n]$ computes $Vrfy(pk', ct'_i, \sigma_i)$. Party *i* aborts if $Vrfy(pk', ct'_i, \sigma_i) \neq 1$. Otherwise, each party $i \in [n]$ computes $y_i = Dec'(k_i, ct'_i)$.

ACKNOWLEDGMENTS

We thank Shafi Goldwasser, Raluca Ada Popa, and Sukrit Kalra for discussions and several helpful comments. TB acknowledges support by the National Science Foundation Graduate Research Fellowship under Grant No. DGE 2146752. SK and OP acknowledge support by DARPA-ORACLEs under Grant No. 71654.

REFERENCES

- [1] Gilad Asharov, Abhishek Jain, Adriana López-Alt, Eran Tromer, Vinod Vaikuntanathan, and Daniel Wichs. 2012. Multiparty Computation with Low Communication, Computation and Interaction via Threshold FHE. In Advances in Cryptology - EUROCRYPT 2012 - 31st Annual International Conference on the Theory and Applications of Cryptographic Techniques, Cambridge, UK, April 15-19, 2012. Proceedings (Lecture Notes in Computer Science, Vol. 7237), David Pointcheval and Thomas Johansson (Eds.). Springer, 483-501. https://doi.org/10.1007/978-3-642-29011-4_29
- [2] Michael Ben-Or, Shafi Goldwasser, and Avi Wigderson. 2019. Completeness theorems for non-cryptographic fault-tolerant distributed computation. In Providing Sound Foundations for Cryptography: On the Work of Shafi Goldwasser and Silvio Micali, Oded Goldreich (Ed.). ACM, 351-371. https://doi.org/10.1145/3335741.3335756
- [3] Fabrice Benhamouda and Huijia Lin. 2018. k-Round Multiparty Computation from k-Round Oblivious Transfer via Garbled Interactive Circuits. In Advances in Cryptology - EUROCRYPT 2018 - 37th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Tel Aviv, Israel, April 29 - May 3, 2018 Proceedings, Part II (Lecture Notes in Computer Science, Vol. 10821), Jesper Buus Nielsen and Vincent Rijmen (Eds.). Springer, 500-532. https://doi.org/10.1007/978-3-319-78375-8_17
- [4] Erica Blum, Elette Boyle, Ran Cohen, and Chen-Da Liu-Zhang. 2023. Communication Lower Bounds for Cryptographic Broadcast Protocols. In 37th International Symposium on Distributed Computing, DISC 2023, October 10-12, 2023, L'Aquila, Italy (LIPIcs, Vol. 281), Rotem Oshman (Ed.). Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 10:1–10:19. https://doi.org/10.4230/LIPICS.DISC.2023.10
- [5] Dan Boneh, Rosario Gennaro, Steven Goldfeder, Aayush Jain, Sam Kim, Peter M. R. Rasmussen, and Amit Sahai. 2018. Threshold Cryptosystems from Threshold Fully Homomorphic Encryption. In Advances in Cryptology - CRYPTO 2018 - 38th Annual International Cryptology Conference, Santa Barbara, CA, USA, August 19-23, 2018, Proceedings, Part I (Lecture Notes in Computer Science, Vol. 10991), Hovav Shacham and Alexandra Boldyreva (Eds.). Springer, 565–596. https://doi.org/10.1007/978-3-319-96884-1_19
- [6] Elette Boyle, Ran Cohen, and Aarushi Goel. 2024. Breaking the \$O(\sqrt{n})\$-Bit Barrier: Byzantine Agreement with Polylog Bits Per Party. J. Cryptol. 37, 1 (2024), 2. https://doi.org/10.1007/S00145-023-09484-0
- [7] Elette Boyle, Shafi Goldwasser, and Stefano Tessaro. 2013. Communication Locality in Secure Multi-party Computation - How to Run Sublinear Algorithms in a Distributed Setting. In Theory of Cryptography - 10th Theory of Cryptography Conference, TCC 2013, Tokyo, Japan, March 3-6, 2013. Proceedings (Lecture Notes in Computer Science, Vol. 7785), Amit Sahai (Ed.). Springer, 356–376. https://doi.org/10.1007/978-3-642-36594-2_21
- [8] Gabriel Bracha and Sam Toueg. 1984. A Distributed Algorithm for Generalized Deadlock Detection. In Proceedings of the Third Annual ACM Symposium on Principles of Distributed Computing, Vancouver, B. C., Canada, August 27-29, 1984, Tiko Kameda, Jayadev Misra, Joseph G. Peters, and Nicola Santoro (Eds.). ACM, 285-301. https://doi.org/10.1145/800222.806756
- [9] Nicolas Braud-Santoni, Rachid Guerraoui, and Florian Huc. 2013. Fast byzantine agreement. In ACM Symposium on Principles of Distributed Computing, PODC '13, Montreal, QC, Canada, July 22-24, 2013, Panagiota Fatourou and Gadi Taubenfeld (Eds.). ACM, 57-64. https://doi.org/10.1145/2484239.2484243
- [10] Ran Canetti. 2001. Universally Composable Security: A New Paradigm for Cryptographic Protocols. In 42nd Annual Symposium on Foundations of Computer Science, FOCS 2001, 14-17 October 2001, Las Vegas, Nevada, USA. IEEE Computer Society, 136–145. https://doi.org/10.1109/SFCS.2001.959888
- [11] Ran Canetti, Pratik Sarkar, and Xiao Wang. 2022. Triply Adaptive UC NIZK. In Advances in Cryptology - ASIACRYPT 2022 - 28th International Conference on the Theory and Application of Cryptology and Information Security, Taipei, Taiwan, December 5-9, 2022, Proceedings, Part II (Lecture Notes in Computer Science, Vol. 13792), Shweta Agrawal and Dongdai Lin (Eds.). Springer, 466–495. https://doi.org/10.1007/978-3-031-22966-4_16
- [12] David Chaum, Claude Crépeau, and Ivan Damgård. 1988. Multiparty Unconditionally Secure Protocols (Extended Abstract). In Proceedings of the 20th Annual ACM Symposium on Theory of Computing, May 2-4, 1988, Chicago, Illinois, USA, Janos Simon (Ed.). ACM, 11–19. https://doi.org/10.1145/62212.62214
- [13] Arka Rai Choudhuri, Michele Ciampi, Vipul Goyal, Abhishek Jain, and Rafail Ostrovsky. 2020. Round Optimal Secure Multiparty Computation from Minimal Assumptions. In Theory of Cryptography - 18th International Conference, TCC 2020, Durham, NC, USA, November 16-19, 2020, Proceedings, Part II (Lecture Notes in Computer Science, Vol. 12551), Rafael Pass and Krzysztof Pietrzak (Eds.). Springer, 291–319. https://doi.org/10.1007/978-3-030-64378-2_11
- [14] Ran Cohen, Jack Doerner, Yashvanth Kondi, and Abhi Shelat. 2023. Secure Multiparty Computation with Identifiable Abort from Vindicating Release. *IACR Cryptol. ePrint Arch.* (2023), 1136. https://eprint.iacr.org/2023/1136
- [15] Claude Crépeau, Jeroen van de Graaf, and Alain Tapp. 1995. Committed Oblivious Transfer and Private Multi-Party Computation. In Advances

in Cryptology - CRYPTO '95, 15th Annual International Cryptology Conference, Santa Barbara, California, USA, August 27-31, 1995, Proceedings (Lecture Notes in Computer Science, Vol. 963), Don Coppersmith (Ed.). Springer, 110–123. https://doi.org/10.1007/3-540-44750-4_9

- [16] Ivan Damgård, Yuval Ishai, and Mikkel Krøigaard. 2010. Perfectly Secure Multiparty Computation and the Computational Overhead of Cryptography. In Advances in Cryptology - EUROCRYPT 2010, 29th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Monaco / French Riviera, May 30 - June 3, 2010. Proceedings (Lecture Notes in Computer Science, Vol. 6110), Henri Gilbert (Ed.). Springer, 445–465. https://doi.org/10.1007/978-3-642-13190-5_23
- [17] Ivan Damgård and Jesper Buus Nielsen. 2007. Scalable and Unconditionally Secure Multiparty Computation. In Advances in Cryptology -CRYPTO 2007, 27th Annual International Cryptology Conference, Santa Barbara, CA, USA, August 19-23, 2007, Proceedings (Lecture Notes in Computer Science, Vol. 4622), Alfred Menezes (Ed.). Springer, 572–590. https://doi.org/10.1007/978-3-540-74143-5_32
- [18] Ivan Damgård, Valerio Pastro, Nigel P. Smart, and Sarah Zakarias. 2012. Multiparty Computation from Somewhat Homomorphic Encryption. In Advances in Cryptology - CRYPTO 2012 - 32nd Annual Cryptology Conference, Santa Barbara, CA, USA, August 19-23, 2012. Proceedings (Lecture Notes in Computer Science, Vol. 7417), Reihaneh Safavi-Naini and Ran Canetti (Eds.). Springer, 643–662. https://doi.org/10.1007/978-3-642-32009-5_38
- [19] Danny Dolev. 1982. The Byzantine Generals Strike Again. J. Algorithms 3, 1 (1982), 14-30. https://doi.org/10.1016/0196-6774(82)90004-9
- [20] Danny Dolev and Rüdiger Reischuk. 1985. Bounds on Information Exchange for Byzantine Agreement. J. ACM 32, 1 (1985), 191–204. https://doi.org/10.1145/2455.214112
- [21] D. Dolev and H. R. Strong. 1983. Authenticated Algorithms for Byzantine Agreement. SIAM J. Comput. 12, 4 (1983), 656–666. https://doi.org/10.1137/0212045 arXiv:https://doi.org/10.1137/0212045
- [22] Michael J. Fischer, Nancy A. Lynch, and Michael Merritt. 1985. Easy Impossibility Proofs for Distributed Consensus Problems. In Proceedings of the Fourth Annual ACM Symposium on Principles of Distributed Computing (Minaki, Ontario, Canada) (PODC '85). Association for Computing Machinery, New York, NY, USA, 59–70. https://doi.org/10.1145/323596.323602
- [23] Matthew K. Franklin and Moti Yung. 1992. Communication Complexity of Secure Computation (Extended Abstract). In Proceedings of the 24th Annual ACM Symposium on Theory of Computing, May 4-6, 1992, Victoria, British Columbia, Canada, S. Rao Kosaraju, Mike Fellows, Avi Wigderson, and John A. Ellis (Eds.). ACM, 699–710. https://doi.org/10.1145/129712.129780
- [24] Sanjam Garg and Akshayaram Srinivasan. 2022. Two-round Multiparty Secure Computation from Minimal Assumptions. J. ACM 69, 5 (2022), 36:1–36:30. https://doi.org/10.1145/3566048
- [25] Oded Goldreich, Silvio Micali, and Avi Wigderson. 2019. How to play any mental game, or a completeness theorem for protocols with honest majority. In Providing Sound Foundations for Cryptography: On the Work of Shafi Goldwasser and Silvio Micali, Oded Goldreich (Ed.). ACM, 307–328. https://doi.org/10.1145/3335741.3335755
- [26] Shafi Goldwasser and Yehuda Lindell. 2005. Secure Multi-Party Computation without Agreement. J. Cryptol. 18, 3 (2005), 247-287. https://doi.org/10.1007/S00145-005-0319-Z
- [27] Martin Hirt, Ueli M. Maurer, and Bartosz Przydatek. 2000. Efficient Secure Multi-party Computation. In Advances in Cryptology - ASIACRYPT 2000, 6th International Conference on the Theory and Application of Cryptology and Information Security, Kyoto, Japan, December 3-7, 2000, Proceedings (Lecture Notes in Computer Science, Vol. 1976), Tatsuaki Okamoto (Ed.). Springer, 143–161. https://doi.org/10.1007/3-540-44448-3_12
- [28] Jonathan Katz, Rafail Ostrovsky, and Adam D. Smith. 2003. Round Efficiency of Multi-party Computation with a Dishonest Majority. In Advances in Cryptology - EUROCRYPT 2003, International Conference on the Theory and Applications of Cryptographic Techniques, Warsaw, Poland, May 4-8, 2003, Proceedings (Lecture Notes in Computer Science, Vol. 2656), Eli Biham (Ed.). Springer, 578–595. https://doi.org/10.1007/3-540-39200-9_36
- [29] Valerie King and Jared Saia. 2009. From Almost Everywhere to Everywhere: Byzantine Agreement with Õ(n^{3/2}) Bits. In Distributed Computing, 23rd International Symposium, DISC 2009, Elche, Spain, September 23-25, 2009. Proceedings (Lecture Notes in Computer Science, Vol. 5805), Idit Keidar (Ed.). Springer, 464–478. https://doi.org/10.1007/978-3-642-04355-0_47
- [30] Valerie King and Jared Saia. 2011. Breaking the O(n²) bit barrier: Scalable byzantine agreement with an adaptive adversary. J. ACM 58, 4 (2011), 18:1–18:24. https://doi.org/10.1145/1989727.1989732
- [31] Leslie Lamport, Robert Shostak, and Marshall Pease. 1982. The Byzantine Generals Problem. ACM Trans. Program. Lang. Syst. 4, 3 (July 1982), 382–401. https://doi.org/10.1145/357172.357176
- [32] Leslie Lamport, Robert E. Shostak, and Marshall C. Pease. 2019. The Byzantine generals problem. In Concurrency: the Works of Leslie Lamport, Dahlia Malkhi

(Ed.). ACM, 203-226. https://doi.org/10.1145/3335772.3335936

- [33] Yuzheng Li, Chuan Chen, Nan Liu, Huawei Huang, Zibin Zheng, and Qiang Yan. 2021. A Blockchain-Based Decentralized Federated Learning Framework with Committee Consensus. *IEEE Netw.* 35, 1 (2021), 234–241. https://doi.org/10.1109/MNET.011.2000263
- [34] Shachar Lovett. 2019. Lecture notes in Communication Complexity. https://cseweb.ucsd.edu/classes/wi19/cse291-b/3-randomized.pdf
- [35] Pratyay Mukherjee and Daniel Wichs. 2016. Two Round Multiparty Computation via Multi-key FHE. In Advances in Cryptology - EUROCRYPT 2016 - 35th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Vienna, Austria, May 8-12, 2016, Proceedings, Part II (Lecture Notes in Computer Science, Vol. 9666), Marc Fischlin and Jean-Sébastien Coron (Eds.). Springer, 735-763. https://doi.org/10.1007/978-3-662-49896-5_26
- [36] Chris Peikert and Sina Shiehian. 2019. Noninteractive Zero Knowledge for NP from (Plain) Learning with Errors. In Advances in Cryptology - CRYPTO 2019 - 39th Annual International Cryptology Conference, Santa Barbara, CA, USA, August 18-22, 2019, Proceedings, Part I (Lecture Notes in Computer Science, Vol. 11692), Alexandra Boldyreva and Daniele Micciancio (Eds.). Springer, 89– 114. https://doi.org/10.1007/978-3-030-26948-7_4
- [37] Toniann Pitassi. 2012. Lecture notes in Foundations of Communication Complexity. https://www.cs.toronto.edu/~toni/Courses/CommComplexity2/Lectures/lecture1.pdf
- [38] Oded Regev. 2009. On lattices, learning with errors, random linear codes, and cryptography. J. ACM 56, 6 (2009), 34:1-34:40. https://doi.org/10.1145/1568318.1568324
- [39] Jie Xu, Cong Wang, and Xiaohua Jia. 2023. A Survey of Blockchain Consensus Protocols. ACM Comput. Surv. 55, 13s (2023), 278:1–278:35. https://doi.org/10.1145/3579845
- [40] Andrew Chi-Chih Yao. 1986. How to Generate and Exchange Secrets (Extended Abstract). In 27th Annual Symposium on Foundations of Computer Science, Toronto, Canada, 27-29 October 1986. IEEE Computer Society, 162–167. https://doi.org/10.1109/SFCS.1986.25

A CONNECTIVITY-BASED LOWER BOUND

In this section we prove our lower bound result. At the heart of our lower bound result is a *connectivity* based argument, where we show that if the communication complexity is too small, then one honest party is doomed to be disconnected from all other honest parties, making it easy for the adversary to issue an attack. This idea is very similar to, and inspired by, a recent lower bound result for Broadcast by Blum et al. [4].

THEOREM 3. Any protocol for MPC with abort against malicious adversaries requires $\Omega(n^2/h)$ bits of communication. Furthermore, such protocols must have locality $\Omega(n/h)$.

PROOF. We show that the lower bound holds even for Broadcast with abort, a special case of MPC. Let \mathcal{A} be an arbitrary protocol solving Broadcast with abort, where the broadcasting party is P with input x. For any party Q, let $N(Q) \subset [n]$ be the random subset of parties that communicate with Q during an execution of \mathcal{A} . We claim that $\forall Q \in [n], \mathbb{E}[|N(Q)|] \geq \frac{n}{8(h-1)}$, which concludes our proof.

Assume towards a contradiction that $\exists Q : \mathbb{E}[|N(Q)|] < \frac{n}{8(h-1)}$. Then the adversary can execute the following simple attack: the adversary decides that Q is honest, picks h-1 other honest parties uniformly at random, and controls the rest of the parties. Let the set of honest parties be $H \subset [n]$. Since $\mathbb{E}[|N(Q)|] < \frac{n}{8(h-1)}$, by Markov's inequality, with probability at least 1/2 we have $|N(Q)| < \frac{n}{4(h-1)}$. Conditioned on this event, since the adversary picks the other h-1 honest parties uniformly at random, the expected number of honest parties in N(Q), $\mathbb{E}[|N(Q) \cap H||N(Q) < \frac{n}{8(h-1)}] \leq \frac{1}{4}$. Thereby, by another Markov's inequality, with probability at least 1/4 none of the parties in N(Q) are honest.

Thus, with non-negligible probability, the honest node Q is "isolated" and never communicates with any honest party. The adversary can now conclude the attack as follows:

- If Q = P. Since all the other honest parties never communicate with the sender P, it can be impersonated by the malicious adversaries, making the other honest parties output a value different from x, violating correctness.
- (2) If Q ≠ P. Then, N(Q) can impersonate the rest of the network to Q, forcing them to output a value different from that of the sender x' ≠ x, violating correctness.

B PROTOCOLS WITH LOCALITY

We dedicate this section to designing MPC protocols with locality. We present two protocols, which tradeoff communication complexity for locality. Both of which are based on replacing the communication on the complete graph for that on a sparse (random) routing network, and then engaging in either broadcast-with-aborts (as in Theorem 2), or our committee-based MPC protocol (in Theorem 4) on that network. We begin by stating a theorem which achieves near-optimal locality, albeit with a far-from-optimal communication complexity:

THEOREM 18 (NEAR-OPTIMAL LOCALITY, RESTATEMENT OF THE-OREM 2). Assuming the hardness of LWE, for any $n \in \mathbb{N}, h \in [n]$ there exists a protocol for MPC with abort against static malicious adversaries, computing depth D functions with constant-sized inputs using $O(n^3h^{-1}\text{poly}(\lambda, D, \log n))$ bits of communication and locality $O(\lambda nh^{-1}\log n)$. The protocol has error negl(λ).

We complement this result by combining its key ideas with our new communication-efficient protocols. In Theorem 19, we design a protocol which sacrifices some locality—yet still is polynomiallysparser than the clique—while improving on the communication complexity of Theorem 18.

THEOREM 19 (A COMMUNICATION–LOCALITY TRADEOFF, RESTATE-MENT OF THEOREM 4). Assuming the hardness of LWE, for any $n \in \mathbb{N}, h \in [n]$ there exists a protocol for MPC with abort against static malicious adversaries, computing depth D functions with constantsized inputs using $O(n^3h^{-3/2}\operatorname{poly}(\lambda, D, \log n))$ bits of communication and locality $O(\lambda nh^{-1/2} \log n)$. The protocol has error negl(λ).

B.1 Establishing and communicating on a sparse routing network

To begin, the parties in the network generate a routing network to communicate over a sparse graph—thereby achieving *locality*.

Claim 20. Fix a subset $H \subset [n]$ of h honest parties. After running SparseNetwork, with probability all but $n^{-\Omega(\alpha)}$ either the parties abort or

- The maximum degree of the resulting graph G is $O(\alpha nh^{-1}\log n)$,
- The subgraph of the resulting graph G induced by H is connected.

Moreover, in the absence of malicious parties, the parties abort with probability $\leq n^{-\Omega(\alpha)}$.

Algorithm	SparseNetwork,	Establishing a	a Sparse Rout-
ing Networl	κ.		

Input: An integer $\log n < h < n$.

Output: Each party $i \in [n]$ receives a subset $N_i \subset [n]$, or aborts \perp .

- 1: Each party $i \in [n]$ samples a uniformly random subset $N_i^{out} \subset [n]$ of $\alpha \cdot nh^{-1} \cdot \log n$ parties.
- Each party i ∈ [n] notifies j ∈ N_i. Let N_iⁱⁿ ⊂ [n] denote the notifications i received.
- 3: If $\frac{1}{2} \cdot \alpha \cdot nh^{-1} \cdot \log n \le |N_i^{in}| \le 2 \cdot \alpha \cdot nh^{-1} \cdot \log n$, *i* outputs \perp . Otherwise, $N_i = N_i^{in} \cup N_i^{out}$.

PROOF. The upper bound on the degree of the graph is implied by step 3 of Algorithm 5. Next, we turn to establish the non-triviality condition. In expectation, the number of incoming edges for a fixed node is $\mathbb{E}[|N_i^{in}|] \equiv d = \alpha n h^{-1} \log n$. By a Chernoff bound, the probability $|N_i^{in}|$ exceeds twice its expectation is $n^{-\Omega(\alpha)}$. By a union bound, in the absence of dishonest parties, the probability the parties abort is $\leq n \cdot n^{-\Omega(\alpha)}$.

Now, let us turn to the connectivity of honest parties in the network. It suffices to argue that each honest party is connected to at least h/2 + 1 other honest parties. The pigeonhole principle will then imply that any two parties are connected. Fix an honest party H_0 , and consider the following probabilistic process:

- Initialize *i* = 1. Initialize the set of permitted parties *S* to all honest parties but *H*₀, := *H* \ {*H*₀}.
- (2) Choose a set $R \subseteq [n]$ of size d uniformly at random. If $R \cap S = \emptyset$, halt. Else, let H_i be any party in $R \cap S$.
- (3) Update i := i + 1, and $S := S \setminus \{H_i\}$.

Note that this process is a different view on the very same process by which hops are formed in the protocol. We claim that the probability that this process halts before h/2 + 1 rounds is at most negl(n). Indeed, observe that for any $i \le h/2$, the probability that the process halts at round i (conditioned on not halting in prior rounds) is

$$\left(\frac{n-h+i}{n}\right)^d < \left(1-\frac{h}{2n}\right)^d \le 2^{-\Theta(h\cdot d/n)} \le n^{-\Omega(\alpha)}$$

Two more union bounds (one over the O(h) rounds, and another over at most h parties) conclude the claim.

The Gossip protocol below shows how to implement the simultaneous broadcast functionality over the graph G generated using SparseNetwork. In a nutshell, the parties repeatedly forward their received messages until each message has been forwarded by each node once. Although this protocol is local, it naturally comes at a communication cost.

Claim 21. Let k out of the n parties be given inputs of length ℓ . After running Gossip, with probability all but $n^{-\Omega(\alpha)}$

James Bartusek, Thiago Bergamaschi, Seri Khoury, Saachi Mutreja, and Orr Paradise

Al	gorithm	6: (Gossip, A	A Sparse	Broad	lcast l	Protocol.
----	---------	------	-----------	----------	-------	---------	-----------

Input: Private inputs $\{x_i\}_{i \in [n]}$, and a graph *G*.

Output: Each party $j \in [n]$ receives every other

 $x_i : i \in [n]$, or aborts \perp .

- Assuming x_i ≠ Null, each party i ∈ [n] sends their input,
 (x_i, i) together with their ID to their neighbors on G.
- Each party i ∈ [n] repeatedly forwards their received messages to their neighbors, without forwarding twice messages from the same ID.
- 3: If any two received messages with same ID *i* differ, then output \perp .
- Correctness: Either the parties reject, or the honest parties agree on their outputs.
- Non-triviality: In the absence of malicious parties, all parties agree on their outputs.
- Communication complexity: The total amount of bits of communication sent is O(αk · h⁻¹n² · poly(l, log n)).

PROOF. From Claim 20, we ensure that the graph *G* connects all the honest parties. Then, unless a party detects an equivocation and rejects, the honest parties successfully receive the inputs of the other honest parties. The communication length follows from a bound on the total number of edges in the graph. \Box

Our protocol for MPC with abort with optimal locality simply applies this local protocol for simultaneous broadcast to our encrypted functionality of Theorem 9. This concludes the proof of Theorem 18.

B.2 Local committee election

Using the local communication protocols developed in the previous subsection, we can now establish a local committee election protocol (in Algorithm 7).

Claim 22. After Algorithm 7, then with probability $1 - n^{-\Omega(\alpha)}$, either a party has aborted or

- (1) $\geq \frac{1}{2} \alpha h^{1/2} \log n$ honest parties were sampled in step 1, and
- (2) All the honest parties sampled in step 1 agree on their view $C_i \equiv C$.

Moreover, $|C| \le 2\alpha n h^{-1/2} \log n$, and the total amount of bits communicated is $\alpha^2 n^3 h^{-3/2} \log^3 n$.

PROOF. Item 1 follows from the hitting set Lemma 13. Item 2 follows from the receival guarantees of Claim 21 and its bit complexity, together with that of the equality test in Lemma 5. \Box

B.3 MPC with abort

To conclude this section, we build on our prior results on MPC to establish a protocol which tradeoffs communication complexity for locality. Its description is presented in Algorithm 8, and a formal statement of its guarantees in Theorem 19.

Algorithm 7: LocalCommitteeElect, Local Committee
Election.
Input: An integer $h \in [n]$.
Output: Each party $i \in [n]$ receives a subset $C_i \subset [n]$, or
aborts \perp .
1: Run SparseNetwork, resulting in a graph G .
2: Each party $i \in [n]$ flips a coin with bias $p = \min(1, \alpha \cdot \frac{\log n}{h^{1/2}})$,
resulting in a bit $b_i \in \{0, 1\}$.
3: Run Gossip, where parties with $b_i = 0$ have Null input.
4: Let $C_i \subset [n]$ denote the bits $b_j = 1$ received by $i \in [n]$ for
$j \neq i$. If $ C_i \geq 2 \cdot p \cdot n$, output \perp .

- 5: Each $i, j \in [n]$ s.t. $j \in C_i$ and $i \in C_j$ engage in Equality_{λ}(C_i, C_j).
- 6: If no pair rejects, then party *i* "receives" C_i. Otherwise, output ⊥.

At a high level, Algorithm 8 attempts to leverage the communicationefficiency of the committee-based MPC protocols we developed in Section 4, however, implemented in a local manner. To do so, we need to ensure that the committee members themselves communicate with few members of the rest of the network, and yet, each member of the network still communicates with at least an honest committee member. For this purpose, in step 3 of Algorithm 8, the Committee members randomly (and obliviously) partition the network into (overlapping) subsets.

To later prove security and correctness of our scheme, we begin with a "covering" claim, which both stipulates that each the parties in the network are connected to honest parties in the committee and that their

Claim 23. With probability all but $1 - n^{-\Omega(\alpha)}$, by the end of step 3 of Algorithm 8, either the parties have aborted or for every $i \in [n] \setminus C$ there exists an honest committee member $c \in C \cap H$ such that $i \in S_c$.

PROOF. From Claim 22, with probability all but $1-n^{-\Omega(\alpha)}$, there are $\geq \frac{1}{2}\alpha h^{1/2} \log n$ honest parties in the committee. Now, fix $i \in [n]$. The probability $i \in S_c$ is $|S_c|/n = h^{-1/2}$. Thereby,

$$\mathbb{P}[\nexists c \in C \cap H : i \in S_c] \le \left(1 - \frac{|S|}{n}\right)^{\frac{1}{2}\alpha h^{1/2} \log n}$$
(3)

$$\leq e^{-\Omega(\alpha \cdot \log n)} \tag{4}$$

A union bound over $i \in [n]$ concludes the argument. \Box

To prove Theorem 19, we proceed in a sequence of 3 claims, which analyze the locality, the communication complexity, the correctness, and finally the security of Algorithm 8.

Claim 24. The locality of Algorithm 8 is $O(\lambda \cdot nh^{-1/2} \cdot \log n)$.

PROOF. The locality of the protocol is the number of parties each node communicates with during the LocalCommitteeElect

Algorithm 8: A Local Protocol for Multi-party Computa-	
tion with abort.	

- **Input:** Integer $\log n < h < n$, a function $f : (\{0, 1\}^{\ell})^n \to \{0, 1\}^{\ell'}$ and an input $x_i \in \{0, 1\}^{\ell} :$ $\forall i \in [n].$
- **Output:** Each party $i \in [n]$ outputs $f(x_1, \dots x_n)$, or a party aborts \perp .
- 1: Execute LocalCommitteeElect, resulting in a committee $C \subset [n]$, and local views $C_i \subset [n]$ for $i \in [n]$.
- The committee generates (*pk*, *sk_c*)_{*c*∈*C*} pairs using the encrypted functionality *F*_{Gen}.
- Each committee member c ∈ C chooses a uniformly random subset S_c ⊂ [n] of size nh^{-1/2}.
- 4: Each c ∈ C forwards the public key pk to all i ∈ S_c. If any two messages differ, output ⊥.
- 5: Each $i \in [n]$ encodes their input $ct_i = Enc_{pk}(x_i)$, and send them to all c s.t. $i \in S_c$.
- 6: Each c ∈ C concatenates their received messages
 ct_{Sc} = {(i, ct_i)}_{i∈[Sc]} together with sender information, and forwards them to all other c' ∈ C. If any two received ciphers (i, ct_i) differ for a same i ∈ [n], output ⊥.
- 7: Each c ∈ C concatenates their received messages
 m_c = {ct_i}_{i∈[n]} and pairwise run Equality_λ(m_{c'}, m_c). If they don't all accept, output ⊥.
- 8: The committee members engage in the encrypted functionality *F*_{Comp} with public inputs {ct_i}_{i∈[n]} and private inputs {sk_c}_{c∈C}, to compute the output Out = f(x₁, ..., x_n).
- 9: Finally, each c ∈ C forwards Out to all the members of S_c. If any two received messages differ, they abort.

protocol, within the committee, and during the network partition. In this manner, it is bounded by

(Degree of *G*) + $|S_c|$ + $|C| \le O(\alpha \cdot n \cdot h^{-1/2} \log n)$

Where we extract the properties of *G* from Claim 20. The choice of $\alpha = \lambda$ concludes the claim.

Claim 25. The communication complexity of Algorithm 8 is

$$O(n^3h^{-3/2} \cdot \operatorname{poly}(\lambda, \log n, D))$$

PROOF. From Claim 22, the communication complexity of the local committee election protocol is $\alpha^2 n^3 h^{-3/2} \log^3 n$. If the size of the keys pk, sk_i, the ciphertexts ct_i, and the output Out are bounded by *b*, then steps 4, 5, and 9 require $O(\max(b, \log n) \cdot |C| \cdot n)$ bits of communication, due to the network-committee communication. In turn, steps 6 requires $O(\max(b, \log n) \cdot |C|^2 \cdot |S|_c)$, and, from

the properties of the equality check in Lemma 5, step 7 requires $O(\lambda \cdot \log n \cdot |C|^2)$ bits.

In turn, from Theorem 9, the communication complexity of the encrypted functionality in steps 2 and 8 is $O(|C| \cdot n \cdot \text{poly}(\lambda, D))$, and $b \leq \text{poly}(\lambda, D)$. Under the bound $|C| \leq \tilde{O}(\alpha n h^{-1/2})$ for the committee size, the bound $|S_c| \leq n h^{-1/2}$ on the network partitions, and the choice $\alpha = \lambda$ we conclude the desired claim.

Claim 26. Assuming the hardness of LWE, Algorithm 8 is correct, and secure with error $negl(\lambda)$.

PROOF. The event that either the parties abort, or the local committee election protocol succeeds (Claim 22), that every party $i \in [n]$ in the network is connected to at least one honest party in the committee (Claim 23), and all the equality tests are correct (Lemma 5), occurs with probability all but $n^{-\Omega(\alpha)}$ from Claim 23 and a union bound.

The proof of correctness and security of the protocol is now analogous to the proof of Claim 17. Indeed, an adversary which breaks the security of Algorithm 8 can be turned into an adversary for \mathcal{F} by conditioning on the events above. The choice of $\alpha = \lambda$ concludes the claim.

Put together, Claims 24 to 26 conclude the proof of Theorem 19.