

---

# Distributional MIPLIB: a Multi-Domain Library for Advancing ML-Guided MILP Methods

---

**Weimin Huang, Taoan Huang**  
University of Southern California

**Aaron Ferber**  
Cornell University

**Bistra Dilkina**  
University of Southern California

## Abstract

Mixed Integer Linear Programming (MILP) is a fundamental tool for modeling combinatorial optimization problems. Recently, a growing body of research has used machine learning to accelerate MILP solving. Despite the increasing popularity of this approach, there is a lack of a common repository that provides distributions of similar MILP instances across different domains, at different hardness levels, with standardized test sets. In this paper, we introduce *Distributional MIPLIB*, a multi-domain library of problem distributions for advancing ML-guided MILP methods. We curate MILP distributions from existing work in this area as well as real-world problems that have not been used, and classify them into different hardness levels. It will facilitate research in this area by enabling comprehensive evaluation on diverse and realistic domains. We empirically illustrate the benefits of using *Distributional MIPLIB* as a research vehicle in two ways. We evaluate the performance of ML-guided variable branching on previously unused distributions to identify potential areas for improvement. Moreover, we propose to learn branching policies from a mix of distributions, demonstrating that mixed distributions achieve better performance compared to homogeneous distributions when there is limited data and generalize well to larger instances.

## 1 Introduction

Mixed Integer Linear Programming (MILP) is an essential technique for modeling and solving Combinatorial Optimization (CO) problems, covering a wide range of applications such as production planning and scheduling [78]. Many CO problems are NP-complete or NP-hard [57, 29, 48, 40, 81] and are thus inherently challenging to solve. Exact algorithms [75] and heuristics [68, 8] have been studied for MILPs. However, solving MILPs remains challenging as problems scale in size and complexity, coupled with the increasing demand for real-time solutions.

Many algorithmic decisions in exact and heuristic algorithms for MILPs traditionally rely on intuition from problem structures and/or are manually made based on evaluation on specific instances [64, 55]. However, manual tuning requires domain-specific knowledge and may fail to realize the full performance potential of algorithms. In recent years, Machine Learning (ML) has been proposed to address this shortcoming. There has been an increasing interest in enhancing MILP-solving frameworks with adaptable learning components that exploit the correlation between algorithmic patterns and the performance of the algorithm [20, 23]. For example, [43, 24, 30, 80, 34, 49] improves Branch-and-Bound (B&B), a tree search algorithm used in MILP solvers [32, 12], with ML.

Despite the increasing popularity of ML-guided MILP solving, there is a lack of a common repository containing distributions of MILPs along with standardized test sets for ML approaches. Some researchers [59, 60] use MIPLIB, a library containing various MILP instances that differ in difficulties, structures, and sizes [27]. While MIPLIB has been traditionally used for benchmarking MILP solvers, its instances are heterogeneous, making it less suited for ML-based methods. As ML typically benefits from a large amount of data from a certain distribution, it remains a challenge for ML

methods to deliver state-of-the-art performance on MIPLIB instances [59, 60]. To leverage data in distributional settings, much of the existing work independently generates MILP distributions. This leads to two issues. First, the lack of standardized test sets makes it hard to benchmark and compare between different methods. Second, a small set of synthetic domains has been repeatedly used and there is a lack of evaluation on real-world domains, making the evaluation not comprehensive. In Table 1, we summarize problem domains used in representative papers for different learning tasks. Classical problems such as Set Covering (SC), Combinatorial Auction (CA), Maximum Independent Set (MIS), and Capacitated Facility Location Problem (CFLP) are commonly used. Although these problems are NP-hard, the instances are synthetic and less challenging compared to many real-world problems. A few papers [60, 71, 72] have used instances from real-world problems such as the production packing problem and electric grid optimization [60], but few of the real-world datasets are publicly accessible, making it hard to reproduce the results.

Table 1: MILP distributions used in previous work. <sup>†</sup> indicates those that are not publicly available. For each work, we mark whether the ML component is trained on distributions of Single Domain (SD), Mixed Domain (MD), or MIPLIB. We also mark whether it is tested in problem domains that are the same as training (ID), in the same domain but on larger distributions (ID(L)), or out of domains (OD). The names of domains corresponding to the abbreviations are in Sec 3.1 and Appendix A.

Track	Paper	Training	Testing	Problem Domains
<b>Learning for B&amp;B</b>				
Branching	Khalil et al. [43]	SD	ID	MIPLIB
	Gasse et al. [24]	SD	ID(L)	SC, CA, CFLP, MIS
	Nair et al. [60]	SD + MIPLIB	ID + MIPLIB	CORLAT, NNV, Google Production Packing <sup>†</sup> , Electric Grid Optimization <sup>†</sup> , MIPLIB
	Gupta et al. [30]	SD	ID(L)	SC, CA, CFLP, MIS
	Zarpellon et al. [80]	MIPLIB	MIPLIB	MIPLIB
	Gupta et al. [31]	SD	ID(L)	SC, CA, CFLP, MIS
	Scavuzzo et al. [70]	SD	ID(L)	SC, CA, CFLP, MIS, MK
	Lin et al. [52]	SD	ID(L)	SC, CA, CFLP, MIS
Backdoor prediction	Ferber et al. [22]	SD	ID	NNV, CFLP, GISP
	Cai et al. [13]	SD	ID(L)	SC, CA, CFLP, MIS, GISP, NNV
Node selection	He et al. [34]	SD	ID + OD	CA, CORLAT, MK
	Labassi et al. [49]	SD	ID(L)	GISP, Fixed Charge Network Flow, MAXSAT
Cut selection	Tang et al. [73]	SD	ID(L) + OD	Packing, Production Planning, Binary Packing, MC
	Huang et al. [41]	SD	ID	SC, MK, Production Planning <sup>†</sup>
	Li et al. [51]	SD + MIPLIB	ID + MIPLIB	CA, CFLP, MIS, Packing, Binary Packing, MC
Run heuristics	Khalil et al. [44]	SD + MIPLIB	ID + MIPLIB	GISP, MIPLIB
	Chmiela et al. [15]	SD	ID(L)	GISP, Fixed Charge Network Flow
<b>Learning for meta heuristics</b>				
LNS	Song et al. [71]	SD	ID	CA, MVC, MC, Risk-Aware Path Planning <sup>†</sup>
	Wu et al. [79]	SD + MIPLIB	ID(L) + MIPLIB	SC, CA, MIS, MC, MIPLIB
	Sonnerat et al. [72]	SD + MIPLIB	ID + MIPLIB	NNV, Google Production Packing <sup>†</sup> , Electric Grid Optimization <sup>†</sup> , MIPLIB, Google Production Planning <sup>†</sup>
	Liu et al. [53]	SD + MIPLIB + MD	MIPLIB + OD	SC, CA, MIS, GISP, MIPLIB
	Huang et al. [38]	SD	ID(L)	SC, CA, MIS, MVC
Solution prediction	Ding et al. [20]	SD	ID(L)	SC, CFLP, MIS, MK, Fixed Charge Network Flow, TSP, VRP, Generalized Assignment
	Nair et al. [60]	SD + MIPLIB	ID + MIPLIB	CORLAT, NNV, Google Production Packing <sup>†</sup> , Electric Grid Optimization <sup>†</sup> , MIPLIB
	Khalil et al. [45]	SD	ID	GISP, Fixed Charge Network Flow
	Han et al. [33]	SD	ID(L)	CA, MIS, IP, LB
	Huang et al. [39]	SD	ID(L)	CA, MIS, MVC, IP

This paper introduces *Distributional MIPLIB*, a comprehensive, multi-purpose MILP library encompassing various MILP problem distributions to support the development of ML-guided MILP-solving methods. We curate distributions from ten synthetic and real-world problems used in the existing literature on ML for MILPs and three real-world problems for which no ML methods have been attempted. For each problem, distributions are classified into multiple hardness levels. 100 test instances are pre-generated for each distribution, and 900 are used for training and validation <sup>1</sup>. Additionally, a generator is provided for most problems to generate additional instances for training.

*Distributional MIPLIB* will significantly accelerate research in MILP solving and data-driven algorithm design by providing distributional data for ML-based methods and enabling benchmarking.

<sup>1</sup>The number of test instances in 3 distributions is less than 100 due to limited available data.

The set of distributions covers various hardness levels and a diverse set of application domains, making it suitable for different types of MILP algorithms (e.g., smaller problems for exact solving and larger problems for heuristic design). Moreover, the standardized test set not only enables better comparison analysis of different methods but also enables evaluation across broader domains at different problem scales and on realistic problems, allowing researchers to identify gaps and open up new avenues of novel research.

To demonstrate the potential of *Distributional MIPLIB* in facilitating research, we evaluate the performance of ML-guided variable branching on previously unused distributions to identify potential areas for improvement. Moreover, we propose to learn branching policies in B&B from a mix of distributions, demonstrating that mixed distributions achieve better performance compared to homogeneous distributions when there is limited data and generalize well to larger instances. Furthermore, we propose several additional directions for utilizing the dataset, suggesting its potential for opening up new research avenues. To encourage further research and facilitate the curation of future distributions, we provide a website for *Distributional MIPLIB*. The URL to the website will be provided in the supplemental materials.

## 2 Background and Related Work

Formally, a MILP with  $n$  decision variables and  $m$  constraints is defined by a coefficient matrix  $A \in \mathbb{R}^{m \times n}$ , a vector  $b \in \mathbb{R}^m$ , a cost vector  $c \in \mathbb{R}^n$ , and a partition  $(B, I, C)$  of variables.  $B, I, C$  are the sets of indices of binary, general integer, and continuous variables, respectively. The goal is to find  $x$  such that  $c^T x$  is maximized, subject to linear constraints  $Ax \leq b$  and integrality constraints on binary decision variables  $x_j \in \{0, 1\}, \forall j \in B$  and integer decision variables  $x_j \in \mathbb{Z}, \forall j \in I$ .

MILP solvers such as Gurobi [32] and SCIP [12] use Branch-and-Bound (B&B), an exact tree search algorithm, as the core component. B&B starts with the root node representing the original input MILP. It then repeatedly chooses a leaf node and creates it two smaller subproblems by splitting the interval of a variable. This step is referred to as *branching*. Besides B&B, meta-heuristics, such as Large Neighborhood Search (LNS) and Predict-and-Search (PaS), are also popular MILP search algorithms that can find high-quality solutions to MILPs much faster without having to prove optimality.

### 2.1 Machine Learning for MILP Solving

ML has been proposed to accelerate MILP solving in different ways. A large body of research improves B&B by learning to select which variables to branch on [43, 24, 30, 80] or which nodes to expand in the search tree [34, 49]. There are also works on learning to schedule or execute primal heuristics [44, 15] and to select cutting planes [73, 62, 41] in B&B. ML has also been applied to improve meta-heuristics. [71, 72, 79, 38] apply learning techniques, such as imitation learning and reinforcement learning, to learn to select which subset of variables to reoptimize in LNS. [60, 33, 39] focus on PaS, where they learn to predict the optimal assignment for part of the variables to get a reduced-size MILP that is easier to solve. A comprehensive literature review is provided Appendix B.

### 2.2 Existing Libraries and Software Packages

MIPLIB [27] is a library that provides access to heterogeneous real-world MILP instances, containing 1065 instances from various domains that are diverse in size, structure, and hardness. It has become a standard test set used to compare the performance of MILP solvers, and several ML methods for MILP solving have been tested on MIPLIB instances [72, 79, 51]. Despite some early success, it remains a challenge for ML methods to deliver state-of-the-art performance on MIPLIB instances, due to the heterogeneous nature [59, 60].

There are also a few open-source software packages built to facilitate research in ML-guided CO. MIPLearn [69] is a software for ML-guided MILP solving that provides access to a complete ML pipeline including data collection, training, and testing. MIPLearn provides generators for one real-world problem, which is a simplified formulation for Unit Commitment (UC). However, domain knowledge is required to generate realistic UC instances that are more complex and more challenging to solve. Ecole [67] is a library designed to facilitate research on using ML to improve CO

solvers. It exposes the sequential decision-making processes in MILP-solving as control problems over Markov Decision Processes. Currently, Ecole provides instance generators for four classical problems. OR-Gym [42] is a framework for developing RL algorithms to produce high-quality solutions for CO, without using MILP solvers. Ecole and OR-Gym are designed for augmenting solvers and finding high-quality solutions without solvers, respectively. MIPLearn supports both tasks.

**Comparison with Existing Datasets and Contributions.** *Distributional MIPLIB* provides a counterpart for the MIPLIB that provides distributions of similar MILP instances of the same model, intended for the development and evaluation of ML-guided MILP methods. Similar to MIPLIB, it covers a broad range of application domains, allowing for a more comprehensive evaluation in problems with different structures, especially in real-world domains. All the instances are pre-compiled, and no domain knowledge is required to access complex real-world instances. It covers multiple hardness levels, making it suitable for a wide range of MILP methods (e.g., exact solving for easier instances and meta-heuristics for harder instances), compared to libraries designed for specific avenues.

### 3 Distributional MIPLIB

We pre-generate MILP distributions from both synthetic and real-world problem domains, classifying them into different hardness levels. Table 2 shows the sources where the distributions were initially used in existing work on ML for MILPs, along with instance statistics. While we precompile a fixed number of instances, an instance generator is available for generating additional training instances for all synthetic problems and one real-world problem (Optimal Transmission Switching).

#### 3.1 Data Sources

**Synthetic Problems.** We curate synthetic instances from domains commonly used in the literature on ML for MILPs. As shown in Table 1, the most frequently used NP-hard problem benchmarks are Combinatorial Auctions (CA) [50], Set Covering (SC) [5], Maximum Independent Set (MIS) [7], Capacitated Facility Location Problem (CFLP) [18], and Minimum Vertex Cover (MVC) [21]. Additionally, we compile distributions of the Generalized Independent Set Problem (GISP), a graph optimization problem proposed for forestry management [36, 16]. We used the instance generators provided in the existing work to compile MILP distributions as described in their work and generate additional distributions covering different hardness levels for frequently used domains such as Minimum Vertex Cover (MVC). Finally, we include Item Placement (IP), which involves spreading items across containers to utilize them evenly [58], and Load Balancing (LB) [77], which deals with apportioning workloads across workers, used in the NeurIPS 2021 Machine Learning for Combinatorial Optimization Competition (ML4CO) [23].

**Real-world Problems.** In addition to synthetic instances, we include MILP instances from five real-world domains. The Maritime Inventory Routing Problem (MIRP) [61] determines routes from production ports to consumption ports to minimize transportation costs and manages the inventory at these ports, covering both ship routing and inventory management. MIRP was used as a hidden test set in ML4CO [23]. Neural Network Verification (NNV) is an optimization problem in ML that verifies the robustness of a neural network on a given input example [14, 74]. The NNV instances we include were derived from verifying a convolutional network on MNIST examples, which was used in [60] for learning for branching and solution prediction.

Furthermore, we compile distributions from problems where no ML method has been applied, covering applications in energy, e-commerce, and sustainability. In energy planning, the Optimal Transmission Switching (OTS) problem under high wildfire ignition risk [66] is a subset of Network Topology Optimization problems. Transmission grids are represented as a series of buses (vertices) connected by power lines (edges). During high wildfire ignition risk, transmission lines can start wildfires; methods to mitigate this risk include de-energizing and undergrounding transmission lines. De-energizing lines prevent fires but interrupt power delivery to customers, whereas undergrounding lines can deliver power without the risk of igniting a fire but at a higher cost. OTS examines the optimal way to de-energize and underground transmission lines to reduce wildfire risk while minimizing power outages within a resource budget. In e-commerce, the Middle-Mile Consolidation Network (MMCN) [29] problem is a network design problem that creates load consolidation plans to transport shipments from stocking locations, including vendors and fulfillment centers, to last-mile delivery

locations. It determines a minimum-cost allocation of transportation capacity on network arcs that satisfies shipment lead-time constraints. For MMCN, we include distributions containing binary and integer variables (denoted as BI) and distributions containing binary and continuous variables (denoted as BC)<sup>2</sup>. The Seismic-Resilient Pipe Network (SRPN) Planning [37] is another network design problem that minimizes the cost of an SRPN in earthquake hazard zones and ensures water supply to critical facilities and households. The SRPN instances in this library are generated based on earthquake hazard zones in Los Angeles.

Table 2: Synthetic and Real-world problems in *Distributional* MIPLIB. † indicates domains for which generators are available. ‡ indicates distributions where # test instances is not 100. For the performance metrics, we use Gurobi (v10.0.3) [32] with 1 hour time limit, on a cluster with Intel Xeon Silver 4116 CPUs @ 2.10GHz, with a RAM allocation of 5G (For SRPN-Hard, MMCN-Very Hard, and OTS-Hard instances, we increased the RAM to 15G, due to memory errors at 5GB.)

Domain	Hardness Level	Dist. Source: ML4MILPs	Performance Metrics				Instance Statistics			
			# Opt	Opt Time(s)	NonOpt Gap	Integral	# Var B	# Var I	# Var C	# Constr
Synthetic										
CA†	Easy	Gasse et al. [24]	100	47.14	N/A	2.30	1000	0	0	385.04
	Medium	Gasse et al. [24]	100	358.14	N/A	7.29	1500	0	0	578.07
	Very hard	Huang et al. [38]	0	N/A	0.10	400.28	4000	0	0	2676.32
SC†	Easy	Gasse et al. [24]	100	18.05	N/A	0.99	1000	0	0	500
	Medium	Gasse et al. [24]	100	214.11	N/A	15.78	1000	0	0	1000
	Hard	Gasse et al. [24]	56	1603.66	0.04	180.25	1000	0	0	2000
	Very hard	Huang et al. [38]	0	N/A	0.20	847.11	4000	0	0	5000
MIS†	Easy	Gasse et al. [24]	100	50.52	N/A	0.86	1000	0	0	3946.25
	Medium	Gasse et al. [24]	88	470.44	0.01	11.28	1500	0	0	5941.14
	Very hard	Huang et al. [38]	0	N/A	0.30	1132.69	6000	0	0	23994.82
MVC†	Easy	New	100	27.26	N/A	0.27	1200	0	0	5975
	Medium	New	97	244.11	0.01	2.28	2000	0	0	9975
	Hard	New	55	1821.04	0.02	102.74	500	0	0	30100
	Very hard	Huang et al. [38]	0	N/A	0.12	454.02	1000	0	0	65100
GISP†	Easy	New	100	43.09	N/A	15.59	605.81	0	0	1967.05
	Medium	Ferber et al. [22]	100	671.89	N/A	204.83	988.81	0	0	3353.03
	Hard	Ferber et al. [22]	85	2623.16	0.08	866.16	1317.03	0	0	4567.83
	Very hard	Cai et al. [13]	0	N/A	0.44	2104.04	6017	0	0	7821.87
	Ext hard	Khalil et al. [44]	0	N/A	2.01	8139.33	12675.83	0	0	16515.44
CFLP†	Easy	Gasse et al. [24]	100	44.44	N/A	0.57	100	0	10000	10201
	Medium	Gasse et al. [24]	100	103.51	N/A	0.88	200	0	20000	20301
LB †	Hard	Gasse et al. [23]	9	2665.11	0.00	33.48	1000	0	60000	64307.17
IP †	Very hard	Gasse et al. [23]	0	N/A	0.44	1770.42	1050	0	33	195
Real-world										
MIRP	Medium	Gasse et al. [23]	10‡	697.24	0.23	728.75	0	15080.57	19576.15	44429.70
NNV	Easy	Nair et al. [60]	588‡	37.98	N/A	21.81	171.49	0	6972.60	6533.70
OTS†	Easy	New	100	45.86	N/A	3.72	4181	0	17137	48582
	Medium	New	100	419.55	N/A	25.80	7525	0	33202	92992
	Hard	New	52	2564.00	0.20	1926.19	6546	0	46423	111804
MMCN	Medium <sup>BI</sup>	New	100	114.93	N/A	3.01	1156.94	263.23	0	437.81
	Medium <sup>BC</sup>	New	100	468.17	N/A	37.30	4271.59	0	324.04	3171.23
	Hard <sup>BI</sup>	New	34	1998.57	0.01	79.79	2074.76	346.39	0	642.57
	Very hard <sup>BI</sup>	New	0	N/A	0.10	369.15	21596.72	1127.29	0.00	3944.01
	Very hard <sup>BC</sup>	New	0	N/A	0.61	2761.52	68345.21	0	2425.87	96272.60
SRPN	Easy	New	21‡	77.91	0.02	10.00	3016.42	0	3016.42	5917.27
	Hard	New	9‡	1321.43	0.03	134.12	11485.33	0	11485.33	22430.84

As shown in Table 2, most synthetic MILP instances contain only binary decision variables, except for CFLP, LB, and IP, which include continuous variables. The real-world problems, on the other hand, encompass diverse distributions with integer and continuous decision variables, enabling comprehensive benchmarking on more realistic and complex problems.

<sup>2</sup>BI and BC distributions correspond to 2 variants of MMCN. In the BI variant, all arcs in the network have the same transit mode. In the BC variant, multiple transit modes are allowed.

### 3.2 Evaluation

**Benchmark Data Generation.** For each synthetic distribution, we generate a total of 1000 instances, with 900 intended for training and validation in ML-guided methods and 100 for testing and evaluation. For the real-world problems OTS and MMCN, we follow the same practice as the synthetic problems, providing 100 test instances for each distribution. For NNV, since precompiled train, validation, and test splits are publicly available, we respect the established splits, including the same 588 instances in the test set. However, for MIRP and SRPN, the number of test instances is less than 100 as the total number of instances available is limited. MIRP contains 20 test instances. SRPN contains 22 and 20 test instances in the Easy and Hard group, respectively <sup>3</sup>.

**Performance Metrics and Problem Instance Statistics.** We design a set of evaluation metrics that characterize performance well from easy to hard settings. We report the number of instances in the test set that are solved to optimality in 1 hour (# Opt). For instances solved to optimality, we report the average solving time in seconds (Opt Time). For instances not solved to optimality, we report the average primal-dual gap after 1 hour (NonOpt Gap). The primal-dual gap represents the gap between the lower and upper objective bounds. Specifically, let  $z_P$  be the primal objective bound (i.e., the value of the best feasible solution found so far, serving as the upper bound for minimization problems), and  $z_D$  be the dual objective bound (i.e., linear relaxation of the MILP, serving as the lower bound for minimization problems). The primal-dual gap is defined as  $gap = |z_P - z_D|/|z_P|$  [32]. Additionally, we report the primal-dual integral (Integral), which is defined as the integral of the primal-dual gap over time [9], with lower values indicating faster (better) convergence. For instance statistics, we report the average number of binary (# Var B), integer (# Var I), and continuous (# Var C) variables, and the average number of constraints (# Constr).

**Hardness Levels.** We classify distributions into 5 hardness levels based on the runtime statistics. For distributions with instances solved to optimality within 1 hour, we classify them into three levels based on the average solving time. Distributions with average solving times under 100 seconds are categorized as *Easy*, 100-1000 seconds as *Medium*, and those exceeding 1000 seconds as *Hard*. For distributions with no instances solved to optimality within 1 hour, we further classify them into *Very hard* and *Extremely hard* based on the primal-dual gap. *Very hard* and *Extremely hard* (Ext hard) distributions are groups where the primal-dual gap is less than 1 and greater than 1, respectively.

## 4 Experiments on Learning to Branch

We illustrate the benefits of using *Distributional MIPLIB* as a research vehicle in the context of Learning to Branch (Learn2Branch) experiments [24]. Learn2Branch imitates Strong Branching, a branching rule that reduces the search tree size in B&B but is time-consuming. Learn2Branch encodes a MILP with a variable-constraint bipartite graph, employs a Graph Convolution Network (GCN) to learn variable representations, and trains a policy using imitation learning. In subsection 4.1, we evaluate the performance of Learn2Branch on previously unused domains and identify potential areas for improvement. In subsection 4.2, we propose training a branching policy from a mix of domains and demonstrate that this strategy offers advantages in the low-data regime.

Throughout the experiments, we use SCIP 6.0.1 [26] as the solver <sup>4</sup>. Following existing work [52, 24], we compare the ML methods against Reliability Pseudocost Branching (RPB), a state-of-the-art human-designed branching policy in B&B. We report the mean and standard deviation over 5 seeds for all metrics. We briefly introduce the setup; details are deferred to Appendix C.

### 4.1 Learning to Branch Evaluated on Unused Domains

We evaluate the performance of Learn2Branch on three novel domains. To our knowledge, GISP has not been used in learning variable branching (Table 1), and OST and SRPN have never been used in any ML-guided methods. We focus on Easy and Medium distributions as learning for branching is typically used on smaller instances in the literature.

<sup>3</sup>As MIRP has been used in ML4CO, we adhere to the train, validation, and test split established by ML4CO. For SRPN, we randomly selected 10% of the total instances as the test set for each distribution.

<sup>4</sup>We use SCIP in the Experiments as opposed to Gurobi, since Gurobi does not provide needed API for ML-guided branching

**Setup.** We use a train, validation, and test split of 80%, 10%, 10%, respectively. This results in 800 MILP instances used for collecting training data for GISP and OTS and 175 for SRPN-Easy, as SRPN instances are limited. We collect 10 Strong Branching expert samples from each instance. We report the performance metrics described in 3.2 with a time limit of 800s.

**Results and discussions.** As shown in Table 3, the trained policy did not outperform SCIP in any of the 3 distributions. We investigate the reason for failure by measuring the number of explored nodes in B&B (# Nodes), the integral of the primal-dual gap with respect to the nodes (Node Integral), and the % of time spent in ML inferences (Infer Pct (%)), which includes feature extraction, forward pass, and ranking. The reason why Learn2Branch did not work well on GISP and SRPN could be the overhead of the ML inference time, as they outperform SCIP on Node Integral. For OTS, the reasons why Learn2Branch fails to beat SCIP are less obvious and pose an open research question.

Table 3: Learn2Branch evaluated on previously unused domains. Note that the solving time differs from Table 2 because results in 2 were evaluated with Gurobi and under different RAM allocations.

Dist.	Method	Integral	# Opt	Opt Time(s)	NonOpt Gap	# Nodes	Infer Pct(%)	Node Integral
GISP (Medium)	SCIP	<b>118.0 ± 1.5</b>	<b>100</b>	<b>376.6 ± 4.7</b>	N/A	158866.1 ± 1693.4	N/A	38596.6 ± 508.0
	ML	139.0 ± 5.8	98.0 ± 1.5	472.8 ± 16.2	0.121 ± 0.007	<b>89354.6 ± 2622.5</b>	21.2 ± 0.4	<b>22636.5 ± 683.3</b>
OTS (Easy)	SCIP	<b>20.0 ± 4.7</b>	<b>94.4 ± 2.2</b>	179.4 ± 5.5	0.003 ± 0.002	<b>1798.7 ± 242.9</b>	N/A	<b>5.8 ± 2.2</b>
	ML	27.9 ± 10.4	80.4 ± 7.7	<b>129.7 ± 15.2</b>	0.003 ± 0.002	4073.2 ± 1416.0	4.9 ± 1.1	20.6 ± 8.2
SRPN (Easy)	SCIP	<b>47.0 ± 1.7</b>	<b>13.8 ± 0.4</b>	54.8 ± 15.1	<b>0.152 ± 0.006</b>	15420.2 ± 1937.0	N/A	1594.2 ± 160.9
	ML	52.3 ± 4.3	12.8 ± 0.7	<b>41.8 ± 8.4</b>	0.16 ± 0.011	<b>13003.5 ± 1739.8</b>	14.9 ± 1.9	<b>1371.6 ± 93.6</b>

## 4.2 Learning to Branch with Mixed Distributions

Collecting expert samples for imitation learning in Learn2Branch is computationally intensive [52]. While collecting a large number of expert samples can lead to stronger performance, it could be prohibitively costly. One strategy to make the best use of limited data is to pool data and train policies on mixed distributions, as opposed to existing work that trains models on a single distribution or completely heterogeneous distributions such as MIPLIB (Table 1). Empirically, we show that pooling data achieves better performance when limited training data is used.

**Setup.** We collect samples from training instances from 5 different domains: MIS-Easy, GISP-easy, CFLP-easy, CA-Medium, and SC-Medium. We use the collected data in two different ways. First, we train a separate model for each domain. Second, we pool expert samples collected for all domains and train a single model from the mixed distribution (denoted as ML-mix5). The number of training samples fed into ML-mix5 is five times the first strategy, but the data collection costs for the two

Table 4: Performance comparison under two training strategies, evaluated on five domains. Under the first strategy, a separate model is trained for each domain on expert samples collected from instances drawn from homogeneous distributions from the corresponding domain: ML-MIS, ML-GISP, ML-CFLP, ML-CA, and ML-SC. ML-mix5 is trained under the second strategy, where pooled data collected from instances in the 5 domains are used to train one single model. We present results when using different numbers  $n$  of training instances per domain:  $n = 80$  (left) and  $n = 320$  (right).

Dist.	Policy	Collected samples from 80 instances per domain				Collected samples from 320 instances per domain			
		Integral	# Opt	Opt Time(s)	NonOpt Gap	Integral	# Opt	Opt Time(s)	NonOpt Gap
MIS (Easy)	SCIP	4.412 ± 0.118	<b>99.0 ± 0.0</b>	145.4 ± 3.9	0.022 ± 0.004	4.412 ± 0.118	99.0 ± 0.0	145.4 ± 3.9	0.022 ± 0.004
	ML-MIS	5.408 ± 5.309	82.6 ± 31.3	140.5 ± 66.5	<b>0.016 ± 0.003</b>	<b>2.434 ± 0.074</b>	99.0 ± 0.6	<b>89.2 ± 5.1</b>	<b>0.015 ± 0.001</b>
	ML-mix5	<b>2.781 ± 0.197</b>	98.0 ± 1.1	<b>107.3 ± 13.0</b>	<b>0.016 ± 0.004</b>	2.545 ± 0.107	99.0 ± 0.6	97.4 ± 5.4	0.016 ± 0.003
GISP (Easy)	SCIP	12.509 ± 0.242	100	40.0 ± 0.7	N/A	12.509 ± 0.242	100	40.0 ± 0.7	N/A
	ML-GISP	11.299 ± 0.885	100	41.0 ± 3.4	N/A	10.700 ± 0.442	100	38.5 ± 1.6	N/A
	ML-mix5	<b>10.823 ± 0.383</b>	100	<b>39.1 ± 2.0</b>	N/A	<b>10.420 ± 0.279</b>	100	<b>37.3 ± 0.8</b>	N/A
CFLP (Easy)	SCIP	0.644 ± 0.021	100	48.5 ± 0.5	N/A	0.644 ± 0.021	100	48.5 ± 0.5	N/A
	ML-CFLP	0.642 ± 0.036	100	47.8 ± 3.4	N/A	<b>0.606 ± 0.028</b>	100	42.4 ± 1.9	N/A
	ML-mix5	<b>0.638 ± 0.020</b>	100	<b>46.7 ± 2.8</b>	N/A	0.610 ± 0.021	100	<b>42.1 ± 1.0</b>	N/A
CA (Med)	SCIP	2.347 ± 0.034	97.2 ± 0.4	157.4 ± 4.8	0.009 ± 0.001	2.347 ± 0.034	97.2 ± 0.4	157.4 ± 4.8	<b>0.009 ± 0.001</b>
	ML-CA	1.927 ± 0.063	97.0 ± 0.0	144.9 ± 6.2	<b>0.007 ± 0.001</b>	<b>1.775 ± 0.056</b>	98.2 ± 0.7	<b>136.8 ± 2.1</b>	<b>0.009 ± 0.003</b>
	ML-mix5	<b>1.815 ± 0.015</b>	<b>98.2 ± 0.7</b>	<b>141.0 ± 3.2</b>	0.009 ± 0.002	1.795 ± 0.199	<b>98.6 ± 0.8</b>	142.1 ± 12.5	0.011 ± 0.002
SC (Med)	SCIP	6.465 ± 0.023	100	90.3 ± 0.6	N/A	6.465 ± 0.023	100	90.3 ± 0.6	N/A
	ML-SC	5.602 ± 0.156	100	84.6 ± 2.2	N/A	4.965 ± 0.095	100	72.5 ± 1.7	N/A
	ML-mix5	<b>5.362 ± 0.131</b>	100	<b>79.8 ± 2.2</b>	N/A	<b>4.796 ± 0.104</b>	100	<b>68.4 ± 1.7</b>	N/A

strategies aggregated across the 5 domains are the same. We first start with  $n = 80$  training instances per domain, which is 10% what we used in 4.1. We then quadruple the number of training instances to  $n = 320$ . Following 4.1, we collect 10 expert samples per instance. We compare the performance of the two training strategies (single domain vs. mixed domains) on each domain separately.

**Results and Discussions.** As shown in Table 4, when the total number of instances used for data collection is small (80), ML-mix5 outperforms the models trained on homogeneous distributions and SCIP across multiple evaluation metrics for all domains. However, as the number of training instances increases (320), the models trained on a homogeneous distribution outperform ML-mix5 in some domains. This indicates that learning with mixed distributions can improve data collection efficiency in the case when we have a limited budget for data collection (e.g., under time or computational resource constraints), but does not surpass training on homogeneous distributions when training samples can be collected from a larger number of instances. Additionally, Table 4 suggests that when the number of training data points fed into the model is the same, using a training set where the data is drawn from mixed distributions is unlikely to surpass the performance of using a training set where the data is drawn from homogeneous distributions. The performance of ML-mix5 under 80 instances per domain, which was trained with samples collected from 400 training instances in total, did not outperform the separately trained models under 320 instances per domain. This underscores the benefits of having domain-specific distributional datasets as provided in our library.

Table 5: Performance comparison under two training strategies when transferred to different hardness. ML-MIS (trained on *Easy*), ML-SC (trained on *Medium*), and ML-mix5 are the ones presented in Table 4 (under  $n = 320$ ). The time cutoff is 800s, except for *Very hard* distributions where it is 3600s.

Policy	Integral	# Opt	Opt Time(s)	NonOpt Gap	Integral	# Opt	NonOpt Gap	Infer Pct(%)	Node Integral
<b>MIS (Medium)</b>					<b>MIS (Very hard)</b>				
SCIP	23.4 ± 0.1	11.4 ± 1.0	483.2 ± 10.5	0.024 ± 0.0	1479.3 ± 2.3	0	0.393 ± 0.002	N/A	223.6 ± 41.7
ML-MIS	21.9 ± 2.4	10.2 ± 10.4	377.2 ± 20.0	0.023 ± 0.003	1461.5 ± 4.8	0	<b>0.390 ± 0.002</b>	0.1 ± 0.0	179.0 ± 56.4
ML-mix5	<b>16.5 ± 0.2</b>	<b>24.2 ± 3.9</b>	<b>335.3 ± 19.6</b>	<b>0.017 ± 0.0</b>	<b>1459.0 ± 2.4</b>	0	<b>0.390 ± 0.001</b>	0.1 ± 0.0	<b>139.4 ± 42.9</b>
<b>SC (Hard)</b>					<b>SC (Very hard)</b>				
SCIP	53.3 ± 0.2	35.0 ± 3.5	378.5 ± 10.8	0.066 ± 0.000	<b>768.1 ± 1.0</b>	0	<b>0.238 ± 0.002</b>	N/A	3881.8 ± 69.8
ML-SC	49.6 ± 0.4	37.8 ± 1.0	367.1 ± 7.3	<b>0.062 ± 0.001</b>	870.3 ± 13.6	0	0.297 ± 0.009	9.2 ± 1.6	<b>2622.8 ± 579.1</b>
ML-mix5	<b>48.2 ± 0.3</b>	<b>40.2 ± 0.7</b>	<b>358.2 ± 3.3</b>	<b>0.062 ± 0.001</b>	830.3 ± 19.5	0	0.275 ± 0.010	13.3 ± 4.7	4051.3 ± 1734.7

**Transferring to Different Distributions.** We further evaluate the performance of trained models when applied to distributions of different hardness levels from the same domain, for MIS and SC. Table 5 shows that on MIS, ML-mix5 exhibits better generalization to harder instances compared to the model trained on homogeneous distributions, even though ML-mix5 did not outperform ML-MIS at the trained hardness level (Table 4). On SC, again ML-mix5 exhibits better performance than ML-SC on harder distributions of SC, however on the *Very hard* distribution neither is able to outperform SCIP, possibly due to the larger overhead of the GCN inference time on larger instances.

## 5 Potential Research Paths

Below we outline suggestions for potential research paths using *Distributional MIPLIB* to facilitate step-change in the ability to solve hard real-world MILP problems.

**Faster Inference.** Due to computational constraints, prior work has focused on training and testing on relatively small and/or easy MILP distributions. In addition to Learn2Branch, much of the existing work on ML for MILP focuses on replacing an expensive procedure with an ML oracle, such as ML for LNS. Our empirical results highlighted that often the advantage of the ML policy is outweighed by its cost of inference on large MILPs. This calls for investigations of ML model architectures or hardware solutions that specifically target this challenge.

**Synthetic Data Generation.** Synthetic Data Generation (SDG) captures the underlying distribution of a dataset and synthesizes targeted data through a generative process [3]. SDG has been applied to multiple domains including finance [4] and healthcare [35] to address the problem of limited available data or preserve the privacy of real data. SDG could also be used to improve ML-based methods for MILPs, as collecting algorithmic decision data from solving instances can be expensive,



as discussed in Section 4. Moreover, for some real-world domains, the number of instances is also limited, such as SRPN in this library. Synthetic data could be used to complement existing data in these cases. There has been existing work that uses data augmentation to generate MILP instances [54, 25] or algorithm decision data inside B&B [52]. *Distributional MIPLIB* could be used to develop theoretical and algorithmic frameworks that generate targeted data forming the same distributions.

**Foundation Model for Combinatorial Optimization.** Deep learning foundation models that leverage vast amounts of data to learn general-purpose representation can adapt to a wide range of downstream tasks, which has drastically transformed the domains of language, vision, and scientific discovery [11]. *Distributional MIPLIB* contains MILPs from a wide range of domains and hardness levels, which can be suited for a wide range of tracks (B&B, LNS, and finding primal solutions). Much of the existing works (e.g., learning for backdoors, LNS, and branching) use a common subset of features to learn a representation of MILP variables, which could be unified as a shared latent representation. *Distributional MIPLIB* could be used to develop and train foundation models for the discrete optimization world.

## 6 Conclusion and Discussion

We introduce *Distributional MIPLIB*, a curated dataset of more than 35 MILP distributions from 13 synthetic and real-world domains, making it a large-scale resource for developing ML-guided MILP solving and comprehensive evaluation. Compared to existing datasets and generators, it provides data in distributional settings which is better suited for ML-guided methods. It provides MILP distributions from a wide range of applications and requires no domain knowledge to access these instances. We intend for the library to continue to grow with domain contributions from the community.

We ran experiments on Learn2Branch focused on variable selection policies in B&B. We identified that in past research only a few distributions/domains were used to assess state of the art, and evaluated the performance of Learn2Branch on unused domains, identifying open challenges. Moreover, we propose to train a Learn2Branch model with mixed distributions and show that this offers advantages in the low-data regime. We also identified potential future directions that can benefit from this library.

We also would like to acknowledge some limitations of our work. Due to computational constraints, we did not experiment with other GNN architectures, with a larger number of samples, or on better GPUs. These could change our empirical conclusions, but do not affect the value of the library.

## Acknowledgments and Disclosure of Funding

The research was supported by the National Science Foundation (NSF) under grant number 2112533: "NSF Artificial Intelligence (AI) Research Institute for Advances in Optimization (AI4OPT)". We would like to thank Lacy Greening and Alan Erera for providing the Middle-Mile Consolidation Network (MMCN) problem instances. We would also like to thank Ryan Piansky and Daniel Molzahn for providing the data and generator for the Optimal Transmission Switching (OTS) problem instances.

## References

- [1] Abadi, M., Agarwal, A., Barham, P., Brevdo, E., Chen, Z., Citro, C., Corrado, G. S., Davis, A., Dean, J., Devin, M., Ghemawat, S., Goodfellow, I., Harp, A., Irving, G., Isard, M., Jia, Y., Jozefowicz, R., Kaiser, L., Kudlur, M., Levenberg, J., Mané, D., Monga, R., Moore, S., Murray, D., Olah, C., Schuster, M., Shlens, J., Steiner, B., Sutskever, I., Talwar, K., Tucker, P., Vanhoucke, V., Vasudevan, V., Viégas, F., Vinyals, O., Warden, P., Wattenberg, M., Wicke, M., Yu, Y., and Zheng, X. (2015). TensorFlow: Large-scale machine learning on heterogeneous systems. Software available from tensorflow.org.
- [2] Alvarez, A. M., Louveaux, Q., and Wehenkel, L. (2017). A machine learning-based approximation of strong branching. *INFORMS Journal on Computing*, 29(1):185–195.

- [3] An, S. and Jeon, J.-J. (2024). Distributional learning of variational autoencoder: Application to synthetic data generation. *Advances in Neural Information Processing Systems*, 36.
- [4] Assefa, S. A., Dervovic, D., Mahfouz, M., Tillman, R. E., Reddy, P., and Veloso, M. (2020). Generating synthetic data in finance: opportunities, challenges and pitfalls. In *Proceedings of the First ACM International Conference on AI in Finance*, pages 1–8.
- [5] Balas, E. and Ho, A. (1980). *Set covering algorithms using cutting planes, heuristics, and subgradient optimization: a computational study*. Springer.
- [6] Balcan, M.-F., Dick, T., Sandholm, T., and Vitercik, E. (2018). Learning to branch. In *International conference on machine learning*, pages 344–353. PMLR.
- [7] Bergman, D., Cire, A. A., Van Hoeve, W.-J., and Hooker, J. (2016). *Decision diagrams for optimization*, volume 1. Springer.
- [8] Berthold, T. (2006). *Primal heuristics for mixed integer programs*. PhD thesis, Zuse Institute Berlin (ZIB).
- [9] Berthold, T. (2013). Measuring the impact of primal heuristics. *Operations Research Letters*, 41(6):611–614.
- [10] Bixby, R. E. and Rothberg, E. E. (2007). Progress in computational mixed integer programming - A look back from the other side of the tipping point. 149:37–41.
- [11] Bodnar, C., Bruinsma, W. P., Lucic, A., Stanley, M., Brandstetter, J., Garvan, P., Riechert, M., Weyn, J., Dong, H., Vaughan, A., et al. (2024). Aurora: A foundation model of the atmosphere. *arXiv preprint arXiv:2405.13063*.
- [12] Bolusani, S., Besançon, M., Bestuzheva, K., Chmiela, A., Dionísio, J., Donkiewicz, T., van Doornmalen, J., Eifler, L., Ghannam, M., Gleixner, A., Graczyk, C., Halbig, K., Hedtke, I., Hoen, A., Hojny, C., van der Hulst, R., Kamp, D., Koch, T., Kofler, K., Lentz, J., Manns, J., Mexi, G., Mühmer, E., Pfetsch, M. E., Schlösser, F., Serrano, F., Shinano, Y., Turner, M., Vigerske, S., Weninger, D., and Xu, L. (2024). The SCIP Optimization Suite 9.0. Technical report, Optimization Online.
- [13] Cai, J., Huang, T., and Dilkina, B. (2024). Learning backdoors for mixed integer programs with contrastive learning. *arXiv preprint arXiv:2401.10467*.
- [14] Cheng, C.-H., Nührenberg, G., and Ruess, H. (2017). Maximum resilience of artificial neural networks. In *Automated Technology for Verification and Analysis: 15th International Symposium, ATVA 2017, Pune, India, October 3–6, 2017, Proceedings 15*, pages 251–268. Springer.
- [15] Chmiela, A., Khalil, E., Gleixner, A., Lodi, A., and Pokutta, S. (2021). Learning to schedule heuristics in branch and bound. *Advances in Neural Information Processing Systems*, 34:24235–24246.
- [16] Colombi, M., Mansini, R., and Savelsbergh, M. (2017). The generalized independent set problem: Polyhedral analysis and solution approaches. *European Journal of Operational Research*, 260(1):41–55.
- [17] Conrad, J., Gomes, C. P., Van Hoeve, W.-J., Sabharwal, A., and Suter, J. (2007). Connections in networks: Hardness of feasibility versus optimality. In *Integration of AI and OR Techniques in Constraint Programming for Combinatorial Optimization Problems: 4th International Conference, CPAIOR 2007, Brussels, Belgium, May 23–26, 2007. Proceedings 4*, pages 16–28. Springer.
- [18] Cornuéjols, G., Sridharan, R., and Thizy, J.-M. (1991). A comparison of heuristics and relaxations for the capacitated plant location problem. *European journal of operational research*, 50(3):280–297.
- [19] Dey, S. S. and Shah, P. (2022). Lower bound on size of branch-and-bound trees for solving lot-sizing problem. *Operations Research Letters*, 50(5):430–433.

- [20] Ding, J.-Y., Zhang, C., Shen, L., Li, S., Wang, B., Xu, Y., and Song, L. (2020). Accelerating primal solution findings for mixed integer programs based on solution prediction. In *Proceedings of the aaai conference on artificial intelligence*, volume 34, pages 1452–1459.
- [21] Dinur, I. and Safra, S. (2005). On the hardness of approximating minimum vertex cover. *Annals of mathematics*, pages 439–485.
- [22] Ferber, A., Song, J., Dilkina, B., and Yue, Y. (2022). Learning pseudo-backdoors for mixed integer programs. In *Integration of Constraint Programming, Artificial Intelligence, and Operations Research*, pages 91–102. Springer.
- [23] Gasse, M., Bowly, S., Cappart, Q., Charfreitag, J., Charlin, L., Chételat, D., Chmiela, A., Dumouchelle, J., Gleixner, A., Kazachkov, A. M., et al. (2022). The machine learning for combinatorial optimization competition (ml4co): Results and insights. In *NeurIPS 2021 competitions and demonstrations track*, pages 220–231. PMLR.
- [24] Gasse, M., Chételat, D., Ferroni, N., Charlin, L., and Lodi, A. (2019). Exact combinatorial optimization with graph convolutional neural networks. *Advances in neural information processing systems*, 32.
- [25] Geng, Z., Li, X., Wang, J., Li, X., Zhang, Y., and Wu, F. (2024). A deep instance generative framework for milp solvers under limited data availability. *Advances in Neural Information Processing Systems*, 36.
- [26] Gleixner, A., Bastubbe, M., Eifler, L., Gally, T., Gottwald, R. L., Hendel, G., Hojny, C., Koch, T., Lübbecke, M. E., Maher, S. J., et al. (2018). The scip optimization suite 6.0.
- [27] Gleixner, A., Hendel, G., Gamrath, G., Achterberg, T., Bastubbe, M., Berthold, T., Christophel, P. M., Jarck, K., Koch, T., Linderoth, J., Lübbecke, M., Mittelman, H. D., Ozyurt, D., Ralphs, T. K., Salvagnin, D., and Shinano, Y. (2021). MIPLIB 2017: Data-Driven Compilation of the 6th Mixed-Integer Programming Library. *Mathematical Programming Computation*.
- [28] Gomes, C. P., Van Hoes, W.-J., and Sabharwal, A. (2008). Connections in networks: A hybrid approach. In *Integration of AI and OR Techniques in Constraint Programming for Combinatorial Optimization Problems: 5th International Conference, CPAIOR 2008 Paris, France, May 20-23, 2008 Proceedings 5*, pages 303–307. Springer.
- [29] Greening, L. M., Dahan, M., and Erera, A. L. (2023). Lead-time-constrained middle-mile consolidation network design with fixed origins and destinations. *Transportation Research Part B: Methodological*, 174:102782.
- [30] Gupta, P., Gasse, M., Khalil, E., Mudigonda, P., Lodi, A., and Bengio, Y. (2020). Hybrid models for learning to branch. *Advances in neural information processing systems*, 33:18087–18097.
- [31] Gupta, P., Khalil, E. B., Chételat, D., Gasse, M., Bengio, Y., Lodi, A., and Kumar, M. P. (2022). Lookback for learning to branch. *arXiv preprint arXiv:2206.14987*.
- [32] Gurobi Optimization, LLC (2023). Gurobi Optimizer Reference Manual.
- [33] Han, Q., Yang, L., Chen, Q., Zhou, X., Zhang, D., Wang, A., Sun, R., and Luo, X. (2022). A gnn-guided predict-and-search framework for mixed-integer linear programming. In *The Eleventh International Conference on Learning Representations*.
- [34] He, H., Daume III, H., and Eisner, J. M. (2014). Learning to search in branch and bound algorithms. *Advances in neural information processing systems*, 27.
- [35] Hernandez, M., Epelde, G., Alberdi, A., Cilla, R., and Rankin, D. (2022). Synthetic data generation for tabular health records: A systematic review. *Neurocomputing*, 493:28–45.
- [36] Hochbaum, D. S. and Pathria, A. (1997). Forest harvesting and minimum cuts: a new approach to handling spatial constraints. *Forest Science*, 43(4):544–554.

- [37] Huang, T. and Dilkina, B. (2020). Enhancing seismic resilience of water pipe networks. In *Proceedings of the 3rd ACM SIGCAS Conference on Computing and Sustainable Societies*, pages 44–52.
- [38] Huang, T., Ferber, A. M., Tian, Y., Dilkina, B., and Steiner, B. (2023). Searching large neighborhoods for integer linear programs with contrastive learning. In *International Conference on Machine Learning*, pages 13869–13890. PMLR.
- [39] Huang, T., Ferber, A. M., Zharmagambetov, A., Tian, Y., and Dilkina, B. (2024). Contrastive predict-and-search for mixed integer linear programs. In *International Conference on Machine Learning*. PMLR.
- [40] Huang, W. and Khalil, E. B. (2023). Walkability optimization: formulations, algorithms, and a case study of toronto. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 14249–14258.
- [41] Huang, Z., Wang, K., Liu, F., Zhen, H.-L., Zhang, W., Yuan, M., Hao, J., Yu, Y., and Wang, J. (2022). Learning to select cuts for efficient mixed-integer programming. *Pattern Recognition*, 123:108353.
- [42] Hubbs, C. D., Perez, H. D., Sarwar, O., Sahinidis, N. V., Grossmann, I. E., and Wassick, J. M. (2020). Or-gym: A reinforcement learning library for operations research problems.
- [43] Khalil, E., Le Bodic, P., Song, L., Nemhauser, G., and Dilkina, B. (2016). Learning to branch in mixed integer programming. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30.
- [44] Khalil, E. B., Dilkina, B., Nemhauser, G. L., Ahmed, S., and Shao, Y. (2017). Learning to run heuristics in tree search. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence*, pages 659–666.
- [45] Khalil, E. B., Morris, C., and Lodi, A. (2022a). Mip-gnn: A data-driven framework for guiding combinatorial solvers. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 10219–10227.
- [46] Khalil, E. B., Vaezipoor, P., and Dilkina, B. (2022b). Finding backdoors to integer programs: A monte carlo tree search framework. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 3786–3795.
- [47] Kingma, D. P. and Ba, J. (2014). Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.
- [48] Kody, A., Piansky, R., Daniel, K., et al. (2022). Optimizing transmission infrastructure investments to support line de-energization for mitigating wildfire ignition risk. In *IREP Symposium on Bulk Power System Dynamics and Control-XI. A 100% Renewable Energy Source Bulk Power Grid: Opportunities and Challenges*.
- [49] Labassi, A. G., Chételat, D., and Lodi, A. (2022). Learning to compare nodes in branch and bound with graph neural networks. *Advances in neural information processing systems*.
- [50] Leyton-Brown, K., Pearson, M., and Shoham, Y. (2000). Towards a universal test suite for combinatorial auction algorithms. In *Proceedings of the 2nd ACM conference on Electronic commerce*, pages 66–76.
- [51] Li, S., Ouyang, W., Paulus, M., and Wu, C. (2024). Learning to configure separators in branch-and-cut. *Advances in Neural Information Processing Systems*, 36.
- [52] Lin, J., Xu, M., Xiong, Z., and Wang, H. (2024). Cambranch: Contrastive learning with augmented milps for branching. In *The Twelfth International Conference on Learning Representations*.
- [53] Liu, D., Fischetti, M., and Lodi, A. (2022). Learning to search in local branching. In *Proceedings of the aai conference on artificial intelligence*, volume 36, pages 3796–3803.

- [54] Liu, H., Kuang, Y., Wang, J., Li, X., Zhang, Y., and Wu, F. (2023). Promoting generalization for exact solvers via adversarial instance augmentation. *arXiv preprint arXiv:2310.14161*.
- [55] Lodi, A. (2013). The heuristic (dark) side of mip solvers. In *Hybrid metaheuristics*, pages 273–284. Springer.
- [56] Lodi, A. and Zarpellon, G. (2017). On learning and branching: a survey. *Top*, 25(2):207–236.
- [57] Magnanti, T. L. (1981). Combinatorial optimization and vehicle fleet planning: Perspectives and prospects. *Networks*, 11(2):179–213.
- [58] Martello, S. and Toth, P. (1990). *Knapsack problems: algorithms and computer implementations*. John Wiley & Sons, Inc.
- [59] Mattick, A. and Mutschler, C. (2023). Reinforcement learning for node selection in branch-and-bound. *arXiv preprint arXiv:2310.00112*.
- [60] Nair, V., Bartunov, S., Gimeno, F., Von Glehn, I., Lichocki, P., Lobov, I., O’Donoghue, B., Sonnerat, N., Tjandraatmadja, C., Wang, P., et al. (2020). Solving mixed integer programs using neural networks. *arXiv preprint arXiv:2012.13349*.
- [61] Papageorgiou, D. J., Nemhauser, G. L., Sokol, J., Cheon, M.-S., and Keha, A. B. (2014). Mirplib—a library of maritime inventory routing problem instances: Survey, core model, and benchmark results. *European Journal of Operational Research*, 235(2):350–366.
- [62] Paulus, M. B., Zarpellon, G., Krause, A., Charlin, L., and Maddison, C. (2022). Learning to cut by looking ahead: Cutting plane selection via imitation learning. In *International conference on machine learning*, pages 17584–17600. PMLR.
- [63] Pisinger, D. (1999). An exact algorithm for large multiple knapsack problems. *European Journal of Operational Research*, 114(3):528–541.
- [64] Pisinger, D. and Ropke, S. (2019). Large neighborhood search. *Handbook of metaheuristics*, pages 99–127.
- [65] Poljak, S. (1995). Integer linear programs and local search for max-cut. *SIAM Journal on Computing*, 24(4):822–839.
- [66] Pollack, M., Piansky, R., Gupta, S., Kody, A., and Molzahn, D. (2024). Equitably allocating wildfire resilience investments for power grids: The curse of aggregation and vulnerability indices. *arXiv preprint arXiv:2404.11520*.
- [67] Prouvost, A., Dumouchelle, J., Scavuzzo, L., Gasse, M., Chételat, D., and Lodi, A. (2020). Ecole: A gym-like library for machine learning in combinatorial optimization solvers. *arXiv preprint arXiv:2011.06069*.
- [68] Samà, M., Corman, F., Pacciarelli, D., et al. (2017). A variable neighbourhood search for fast train scheduling and routing during disturbed railway traffic situations. *Computers & Operations Research*, 78:480–499.
- [69] Santos Xavier, A., Qiu, F., Gu, X., Becu, B., and Dey, S. S. (2024). MIPLearn: An Extensible Framework for Learning- Enhanced Optimization.
- [70] Scavuzzo, L., Aardal, K., Lodi, A., and Yorke-Smith, N. (2024). Machine learning augmented branch and bound for mixed integer linear programming. *arXiv preprint arXiv:2402.05501*.
- [71] Song, J., Yue, Y., Dilkina, B., et al. (2020). A general large neighborhood search framework for solving integer linear programs. *Advances in Neural Information Processing Systems*, 33:20012–20023.
- [72] Sonnerat, N., Wang, P., Ktena, I., Bartunov, S., and Nair, V. (2021). Learning a large neighborhood search algorithm for mixed integer programs. *arXiv preprint arXiv:2107.10201*.
- [73] Tang, Y., Agrawal, S., and Faenza, Y. (2020). Reinforcement learning for integer programming: Learning to cut. In *International conference on machine learning*, pages 9367–9376. PMLR.

- [74] Tjeng, V., Xiao, K. Y., and Tedrake, R. (2018). Evaluating robustness of neural networks with mixed integer programming. In *International Conference on Learning Representations*.
- [75] Tomlin, J. A. (1971). An improved branch-and-bound method for integer programming. *Operations Research*, 19(4):1070–1075.
- [76] Williams, R., Gomes, C. P., and Selman, B. (2003). Backdoors to typical case complexity. In *IJCAI*, volume 3, pages 1173–1178.
- [77] Wilson, J. (1992). Approaches to machine load balancing in flexible manufacturing systems. *Journal of the Operational Research Society*, 43:415–423.
- [78] Wolsey, L. A. (1997). Mip modelling of changeovers in production planning and scheduling problems. *European Journal of Operational Research*, 99(1):154–165.
- [79] Wu, Y., Song, W., Cao, Z., and Zhang, J. (2021). Learning large neighborhood search policy for integer programming. *Advances in Neural Information Processing Systems*, 34:30075–30087.
- [80] Zarpellon, G., Jo, J., Lodi, A., and Bengio, Y. (2021). Parameterizing branch-and-bound search trees to learn branching policies. In *Proceedings of the aaai conference on artificial intelligence*, volume 35, pages 3931–3939.
- [81] Zhu, Y., Liu, J., Hu, Y., Xie, Y., Zeng, D., and Li, R. (2024). Distributionally robust optimization model considering deep peak shaving and uncertainty of renewable energy. *Energy*, 288:129935.

## Checklist

1. For all authors...
  - (a) Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope? [\[Yes\]](#)
  - (b) Did you describe the limitations of your work? [\[Yes\]](#) . Limitations are discussed in Section 6.
  - (c) Did you discuss any potential negative societal impacts of your work? [\[N/A\]](#)
  - (d) Have you read the ethics review guidelines and ensured that your paper conforms to them? [\[Yes\]](#)
2. If you are including theoretical results...
  - (a) Did you state the full set of assumptions of all theoretical results? [\[N/A\]](#)
  - (b) Did you include complete proofs of all theoretical results? [\[N/A\]](#)
3. If you ran experiments (e.g. for benchmarks)...
  - (a) Did you include the code, data, and instructions needed to reproduce the main experimental results (either in the supplemental material or as a URL)? [\[Yes\]](#) . We will include the code and data in the supplemental materials.
  - (b) Did you specify all the training details (e.g., data splits, hyperparameters, how they were chosen)? [\[Yes\]](#) Data splits were described in Section 4. More details are in Appendix C.
  - (c) Did you report error bars (e.g., with respect to the random seed after running experiments multiple times)? [\[Yes\]](#) . We report the mean and standard deviation over 5 random seeds.
  - (d) Did you include the total amount of compute and the type of resources used (e.g., type of GPUs, internal cluster, or cloud provider)? [\[Yes\]](#) . This is described in Appendix C.
4. If you are using existing assets (e.g., code, data, models) or curating/releasing new assets...
  - (a) If your work uses existing assets, did you cite the creators? [\[Yes\]](#)
  - (b) Did you mention the license of the assets? [\[Yes\]](#) . We mentioned them in Appendix D.

- (c) Did you include any new assets either in the supplemental material or as a URL? [Yes] . We will provide a URL to the website in the supplemental material.
  - (d) Did you discuss whether and how consent was obtained from people whose data you're using/curating? [N/A]
  - (e) Did you discuss whether the data you are using/curating contains personally identifiable information or offensive content? [N/A]
5. If you used crowdsourcing or conducted research with human subjects...
- (a) Did you include the full text of instructions given to participants and screenshots, if applicable? [N/A]
  - (b) Did you describe any potential participant risks, with links to Institutional Review Board (IRB) approvals, if applicable? [N/A]
  - (c) Did you include the estimated hourly wage paid to participants and the total amount spent on participant compensation? [N/A]

## A Domain Abbreviations

The abbreviations for the domains are listed in Table 6.

Abbreviation	Domain	Reference
CA	Combinatorial Auctions	[50]
SC	Set Covering	[5]
MIS	Maximum Independent Set	[7]
MVC	Minimum Vertex Cover	[21]
GISP	Generalized Independent Set Problem	[36, 16]
CFLP	Capacitated Facility Location Problem	[18]
MK	Multiple Knapsack	[63]
MC	Max Cut	[65]
CORLAT	Wildlife Management Problem	[17, 28]
LB	Load Balancing	[77]
IP	Item Placement	[58]
MIRP	Maritime Inventory Routing Problem	[61]
NNV	Neural Network Verification	[14, 74]
OTS	Optimal Transmission Switching	[66]
MMCN	Middle-Mile Consolidation Network	[29]
SRPN	Resilient Pipe Network Planning	[37]

Table 6: Abbreviation for domains.

## B Literature Review

**Learning to Branch** A series of papers have explored learning to branch by imitating the strong branching heuristic, a branching method that results in fewer search tree nodes but is expensive to compute [43, 56, 2, 6, 24, 30, 60, 52]. The strong branching heuristic computes a score for each branching candidate and these methods either learn to predict the variables' score or learn to rank them according to their scores. For the features and ML models, [43] develop the first ML-based framework for learning to branch using a Support Vector Machine (SVM) with hand-crafted features. [24] extend the framework by using a bipartite graph to encode the MILP and Graph Convolution Networks (GCN) to learn variable representations.

**Learning Backdoors** Backdoor for MILPs is a small subsets of variables such that a MILP can be solved optimally by branching *only* on the variables in the set [76]. Therefore, identifying backdoors efficiently and effectively can greatly improve the performance of B&B. [22] using ML to predict the most effective backdoor candidates generated by a LP relaxation-based sampling methods. More recently, [13] propose to use a Monte-Carlo tree search method [46] to improve the quality of training data and apply contrastive learning to directly construct backdoors.

**Learning Primal Heuristics** Primal heuristics refer to routines that find good feasible solutions in a short amount of time [12] and deciding which heuristics to run and when is an important task. These decisions are mostly made by hard-coded frequency rules in MILP solvers, which are static, instance-oblivious, and context-independent. To tackle this challenge, [44] propose a data-driven approach to decide when to execute primal heuristics. [15] derive a data-driven approach for scheduling primal heuristics.

Another line of research is to learn to predict solutions to MILPs. Both [60] and [33] learn to predict optimal solutions to MILPs and fix the values for a subset of variables based on the prediction to get reduced-size MILPs that are faster to solve.

**Large Neighbourhood Search (LNS)** LNS is a meta-heuristic that can find high quality solutions faster than B&B on large-scale MILP instances but provides no optimality guarantees. It starts with a feasible solution to the MILP and iteratively selects a subset of variables to reoptimize. Local Branching (LB) is a heuristic that finds the variables that lead to the largest improvement over the current solution in each iteration of LNS. But LB is often slow since it needs to solve a MILP of the same size as input. To mitigate this issues, [72] and [38] replace LB with imitation-learned policies. Other ML techniques, such as reinforcement learning (RL), have also been applied to learn destroy heuristics for LNS [71, 79].

**Learning to Cut** A cutting-plane is a constraint that is valid for feasible integer solutions but cuts into the feasible region of the linear programming (LP) relaxation, thus improving the bound on the optimal solution. Adding cutting planes has been shown to speed up B&B [10, 19]. Modern MILP solvers maintain a cut-pool that includes a large number of cutting planes of a diverse set of classes. The decisions regarding which classes of cutting planes to use, as well as the specific cutting planes to select from each class, significantly impact solver performance. In recent advancements, [73] introduce a Reinforcement Learning (RL) framework tailored for the Gomory cutting-plane algorithm. Additionally, [41] develop a method to approach cut selection as a learning-to-rank task, while [62] devise a strategy to imitate a lookahead strategy for cut selection.

## C Experiment Details

We used the Learn2Branch implementation from [24] in our experiments. Their code is publicly available at <https://github.com/ds4dm/learn2branch>.

**Setup.** All experiments in Section 4 were conducted on a cluster with Intel Xeon Gold 6130 CPUs @ 2.10GHz and Nvidia Tesla V100 GPUs. Each method was run with 5 different seeds. For ML-based methods, we trained the model using 5 different seeds and solved the instances using the trained policies that correspond to the 5 training seeds. For the non-ML methods, we used SCIP to solve the instances with 5 different seeds. The results report the mean and standard deviation across these 5 seeds.

**Data Collection.** In the original implementation [24], expert samples were collected by sampling from a set of training instances with replacement and solving it with SCIP. They iterated this process until the desired number of expert samples was collected. Therefore, in their implementation, the whole set of training and validation instances was not necessarily used to collect samples. In our implementation, we collected a fixed number of expert samples (10) from each instances, to ensure that all instances in the training set were used.

**Training.** We used the same GCN architecture as described in [24] and trained the models in TensorFlow [1]. We used the Adam Optimizer [47] with a batch size of 32 and an initial learning rate of 0.001. In case the when the validation loss does not decrease over a period of 10 epochs, the learning rate was reduced to 20% of its previous value.

## D License of existing assets

We curated new assets from the following existing assets. The NNV dataset was downloaded from [https://github.com/google-deepmind/deepmind-research/tree/master/neural\\_mip\\_solving](https://github.com/google-deepmind/deepmind-research/tree/master/neural_mip_solving), which is available under the terms of the Creative Commons Attribution 4.0 International (CC BY 4.0) license <https://creativecommons.org/licenses/by/4.0/legalcode>.



Datasets downloaded from ML4CO (LB, IP, MIRP) are under BSD-3-Clause license <https://github.com/ds4dm/ml4co-competition/blob/main/LICENSE>. CA, SC, MIS, CFLP instances were generated using code from [24], available at <https://github.com/ds4dm/learn2branch?tab=readme-ov-file> under the MIT license <https://github.com/ds4dm/learn2branch?tab=MIT-1-ov-file>.